

TC-400

GNSS | LTE | BLE

The TC-400 is a 4G GSM vehicle tracking solution built for reliable, real-time fleet and asset monitoring. Featuring Bluetooth connectivity and high-voltage support, it delivers accurate tracking and operational control. Ideal for fleet management, logistics, public transport, construction, mining, cold-chain, automotive, and industrial applications, the TC-400 enhances efficiency, security, and overall fleet performance.



Multiple IOs

9-90V DC Voltage

BLE 5.0 Powered

**Internal High Gain
LTE & GNSS Antenna**

IP54 Casing

**FOTA Web
Supported**



Municipal
Vehicles



Electric Vehicles
Fleet Management



Logistics and
Supply Chain



Theft Prevention

INTERFACE

Digital Input	2
Digital Output	1
Analog Input	1
GNSS Antenna	Internal High Gain GNSS
Cellular Antenna	Internal High Gain LTE
USB	2.0 Micro USB
Indicators	4 LEDs (Charging, Power, GSM, GPS)
SIM	Micro SIM
Memory	12,500 Log Packets (64 Mb Flash)

NAVIGATION

GNSS	GPS, GLONASS, BeiDou, QZSS, GALILEO
Receiver	47 Tracking Channels
Horizontal Position Autonomous	1.5m CEP
SBAS	Supported
Tracking Sensitivity	-166 dBm
Re-acquisition Sensitivity	-159 dBm
Velocity	0.1 m/s
Hot Start, Warm Start, Cold Start	1 sec, 2 sec, 15 sec

CELLULAR NETWORK

Technology	LTE
2G Band	EG915U-CN(B3,8), EG915U-EU(B2,3,5,8)
4G LTE Bands	EG915U-CN, LTE FDD: B1/B3/B5/B8, LTE TDD: B34/B38/B39/B40/B41
RF Power	EG915U-CN(EGSM900: Class 4 (33 dBm $\pm$ 2 dB), DCS1800: Class 1 (30 dBm $\pm$ 2 dB), LTE-FDD: Class 3 (23 dBm $\pm$ 2 dB), LTE-TDD: Class 3 (23 dBm $\pm$ 2 dB))
Coding Scheme	CS 1, 2, 3, 4
SMS	Point to point MO & MT, SMS cell broadcast

POWER

Input Voltage Range	9-90V DC
Internal Back-up battery	250mAh Li-Po 3.7V

BLUETOOTH

Specification	BLE 5.0
Supported Peripherals	TPMS, FLS, Beacons, Etc.

OPERATING ENVIRONMENT

Operating Temperature	-20 °C to +60 °C (With Battery), -30 °C to +75 °C (Without Battery)
Operating Humidity	5% to 95% non-condensing at +40 °C
Ingress Protection Rating	IP54

PHYSICAL SPECIFICATION

Dimensions & Weight	88x45x15 mm (LxBxH) & 71g
---------------------	---------------------------

FEATURES

Sensors	Accelerometer
Scenarios	Overspeeding, DOUT, Unplug detection
Configuration and firmware update	FOTA, Configuration over USB & BLE
SMS	Configuration, Events, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GPS
Fuel monitoring	LLS (BLE, Analog)

*represents optional