SYNAPSE EDGE DEFENSE

Synapse Client Integration

Install the CLI. Point it at a running Synapse. Inspect rules, evaluate requests, manage blocks — from the terminal or a TypeScript program. Four steps from npm install to first managed block.

4	20+	TS	Node 18+
ONBOARDING STEPS	CLI COMMANDS	TYPED CLIENT	RUNTIME

FOUR-STEP ONBOARDING

01 Install

Grab the CLI + typed TypeScript client from npm.

```
$ npm install -g \
  @atlascrew/synapse-client
```

02 Point

Set the server URL. Optional JSON output, debug, and timeout.

```
$ export SYNAPSE_URL=\
  https://synapse.example.com
```

03 Verify

First command: health check. Expect 200 & uptime.

```
$ synapse health
{"ok":true}
```

04 Operate

Manage rules, inspect blocks, evaluate live traffic shapes.

```
$ synapse status --json
$ synapse evaluate GET /api/
```

COMMAND SURFACE — WHAT YOU CAN DO

HEALTH & STATUS

```
synapse health
synapse status
synapse metrics # prom
```

ENTITY MANAGEMENT

```
synapse entities
synapse blocks
synapse release <ip>
synapse release-all
```

RULE MANAGEMENT

```
synapse rules
synapse rule-add <json> <ttl>
synapse rule-remove <id>
synapse reload
```

RULE EVALUATION

```
synapse evaluate GET \
  "/api/users?id=1"
# dry-run against loaded rules
```

CONFIGURATION

```
synapse config
synapse config-set \
  risk_decay=15
```

GLOBAL FLAGS

```
--json    # JSON output
--debug   # verbose
--timeout # ms
--url     # override
```

ENVIRONMENT CONFIGURATION

ENV VAR	FLAG	DESCRIPTION
SYNAPSE_URL	-u, --url	Synapse server base URL. Required. No default — fails fast if missing.
SYNAPSE_JSON	--json	Emit structured JSON instead of human-readable tables. Ideal for CI & scripts.
SYNAPSE_DEBUG	-d, --debug	Verbose HTTP & request-body logging. Shows every call the client makes.
SYNAPSE_TIMEOUT	-t, --timeout	Per-request timeout in milliseconds. Default 30000. Tune for slow networks.

PROGRAMMATIC — TYPESCRIPT CLIENT

Same capabilities, typed. Import directly from @atlascrew/synapse-api.

```typescript
// install:  npm install @atlascrew/synapse-api
import { SynapseClient } from '@atlascrew/synapse-api';

const client = new SynapseClient({
  baseUrl: process.env.SYNAPSE_URL!,
  timeout: 30_000,
});

// health & status
await client.health();
const status = await client.getStatus();
console.log(status.totalRequests, status.blockedRequests);

// manage rules at runtime
await client.addRule({ id: 9001, matches: [/* ... */] }, { ttlSec: 3600 });

// dry-run a request against the loaded rule set
const verdict = await client.evaluate('GET', '/api/users?id=1');
if (verdict.blocked) console.log('would block:', verdict.matched_rule);
```

From npm install to first managed block in under 60 seconds.

Single-binary CLI. Typed TypeScript client. JSON output for CI. Every command is scriptable.