

Tailwind CSS v4 Cheatsheet

Extended, grouped reference for Tailwind CSS v4 utility classes — compiled from the official docs so it actually reflects v4, not v3. Need something you can keep on your desk? [Try the condensed version.](#)

Changed since v3

The most common source of outdated cheatsheets: these utilities were renamed or changed behavior in v4.

v3	v4	Note
shadow-sm	shadow-xs	
shadow	shadow-sm	
drop-shadow-sm	drop-shadow-xs	
drop-shadow	drop-shadow-sm	
blur-sm	blur-xs	
blur	blur-sm	
backdrop-blur-sm	backdrop-blur-xs	
backdrop-blur	backdrop-blur-sm	
rounded-sm	rounded-xs	
rounded	rounded-sm	
outline-none	outline-hidden	
ring	ring-3	default ring width is now 1px, not 3px
flex-shrink-*	shrink-*	
flex-grow-*	grow-*	
overflow-ellipsis	text-ellipsis	
decoration-slice	box-decoration-slice	
decoration-clone	box-decoration-clone	
bg-opacity-*	bg-black/50	opacity modifiers replace all *-opacity-* utilities
text-opacity-*	text-black/50	
border-opacity-*	border-black/50	
ring-opacity-*	ring-black/50	
!flex	flex!	important modifier moved to the end of the class
bg-[--brand]	bg-(--brand)	arbitrary CSS variable syntax
grid-cols-[max-content,auto]	grid-cols-[max-content_auto]	commas in arbitrary values become underscores

Layout

`container`

Fixed max-width at each breakpoint

`flex` / `inline-flex`

`display: flex`

`hidden`

`display: none`

`columns-2 ... columns-12`

column-count

`box-border` / `box-content`

box-sizing

`clear-left` / `clear-right` / `clear-both`

`clear`

`object-cover` / `object-contain` / `object-fill` / `object-none`

`object-fit`

`overflow-auto` / `overflow-hidden` / `overflow-scroll` / `overflow-visible`

`overflow` (also `overflow-x-*`, `overflow-y-*`)

`static` / `fixed` / `absolute` / `relative` / `sticky`

position

`visible` / `invisible` / `collapse`

visibility

`block` / `inline-block` / `inline`

`display`

`grid` / `inline-grid`

`display: grid`

`aspect-square` / `aspect-video` / `aspect-[4/3]`

`aspect-ratio`

`break-after-column` / `break-before-page` / `break-inside-avoid`

CSS fragmentation breaks

`float-left` / `float-right` / `float-none`

`float`

`isolate` / `isolation-auto`

`isolation` (stacking context)

`object-center` / `object-top` / `object-left-bottom`

`object-position`

`overscroll-auto` / `overscroll-contain` / `overscroll-none`

`overscroll-behavior`

`inset-0` / `top-4` / `right-2` / `bottom-0` / `left-1/2`

`top` / `right` / `bottom` / `left`

`z-0 ... z-50` / `z-auto` / `-z-10`

`z-index`

Flexbox & Grid

`flex-row / flex-row-reverse / flex-col / flex-col-reverse`

flex-direction

`flex-1 / flex-auto / flex-initial / flex-none`

flex shorthand

`shrink / shrink-0`

flex-shrink (was flex-shrink-* in v3)

`order-1 ... order-12 / order-first / order-last / -order-1`

order

`col-span-2 / col-start-3 / col-end-5 / col-auto`

grid-column placement

`row-span-2 / row-start-1 / row-end-3`

grid-row placement

`auto-cols-auto / auto-cols-min / auto-cols-fr`

grid-auto-columns

`gap-4 / gap-x-2 / gap-y-6`

gap between flex/grid items

`justify-items-start / justify-items-center / justify-items-stretch`

justify-items

`content-center / content-between / content-stretch`

align-content

`self-auto / self-center / self-stretch`

align-self

`flex-wrap / flex-wrap-reverse / flex-nowrap`

flex-wrap

`grow / grow-0`

flex-grow (was flex-grow-* in v3)

`basis-0 / basis-1/2 / basis-full / basis-64`

flex-basis

`grid-cols-1 ... grid-cols-12 / grid-cols-none`

grid-template-columns

`grid-rows-1 ... grid-rows-6`

grid-template-rows

`grid-flow-row / grid-flow-col / grid-flow-dense`

grid-auto-flow

`auto-rows-auto / auto-rows-min / auto-rows-fr`

grid-auto-rows

`justify-start / justify-center / justify-between / justify-evenly`

justify-content

`justify-self-auto / justify-self-end`

justify-self

`items-start / items-center / items-baseline / items-stretch`

align-items

`place-content-center / place-items-center / place-self-center`

place-* shorthands

Spacing

`p-4` / `px-4` / `py-4` / `pt-4` / `pr-4` / `pb-4`
/ `pl-4`

padding (all sides / axis / single side)

`m-4` / `mx-auto` / `my-4` / `mt-4` / `-mt-4`

margin (negative values allowed with -)

`space-x-4` / `space-y-4`

gap between direct children (adds margin between siblings)

0, px, 0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 72, 80, 96

default spacing scale (1 unit = 0.25rem = 4px, so `p-4` = 1rem)

`ps-4` / `pe-4`

padding-inline-start / padding-inline-end (logical)

`ms-4` / `me-4`

margin-inline-start / margin-inline-end (logical)

`space-x-reverse`

reverses the direction spacing is applied

Sizing

`w-4` / `w-1/2` / `w-full` / `w-screen` / `w-fit`
/ `w-min` / `w-max`

width

`max-w-xs` ... `max-w-7xl` / `max-w-full` /
`max-w-prose` / `max-w-none`

max-width

`min-h-0` / `min-h-screen` / `min-h-full`

min-height

`size-4` / `size-full` / `size-1/2`

sets width and height together

`min-w-0` / `min-w-full` / `min-w-fit`

min-width

`h-4` / `h-1/2` / `h-full` / `h-screen` / `h-dvh`
/ `h-svh` / `h-lvh`

height (dvh/svh/lvh = dynamic/small/large viewport units)

`max-h-full` / `max-h-screen`

max-height

Typography

`font-sans / font-serif / font-mono`
font-family

`antialiased / subpixel-antialiased`
font-smoothing

`font-thin ... font-black`
font-weight (100-900)

`leading-none ... leading-loose /`
`leading-4 ... leading-10`
line-height

`list-none / list-disc / list-decimal`
list-style-type

`text-left / text-center / text-right /`
`text-justify`
text-align

`underline / overline / line-through /`
`no-underline`
text-decoration-line

`underline-offset-4`
text-underline-offset

`truncate / text-ellipsis / text-clip`
text-overflow

`indent-4 / -indent-4`
text-indent

`whitespace-normal / whitespace-nowrap /`
`whitespace-pre-wrap`
white-space

`hyphens-none / hyphens-manual /`
`hyphens-auto`
hyphens

`text-shadow-2xs ... text-shadow-lg /`
`text-shadow-none`
text-shadow (new utility in v4)

`text-xs ... text-9xl`
font-size (each step sets a matching line-height)

`italic / not-italic`
font-style

`tracking-tighter ... tracking-widest`
letter-spacing

`line-clamp-1 ... line-clamp-6 / line-`
`clamp-none`
truncate text to N lines

`list-inside / list-outside`
list-style-position

`text-red-500 / text-black/50`
text color (with opacity modifier)

`decoration-red-500 / decoration-2 /`
`decoration-wavy`
text-decoration color / thickness / style

`uppercase / lowercase / capitalize /`
`normal-case`
text-transform

`text-wrap / text-nowrap / text-balance`
`/ text-pretty`
text-wrap

`align-baseline / align-top / align-`
`middle / align-bottom`
vertical-align

`break-normal / break-words / break-all`
`/ break-keep`
word-break / overflow-wrap

`content-none / content-['*']`
content (for ::before / ::after)

Backgrounds

`bg-fixed` / `bg-local` / `bg-scroll`
background-attachment

`bg-red-500` / `bg-transparent` / `bg-black/25`
background-color (with opacity modifier)

`from-cyan-500 via-blue-500 to-indigo-500`
gradient color stops

`bg-center` / `bg-top` / `bg-[center_top_1rem]`
background-position

`bg-auto` / `bg-cover` / `bg-contain`
background-size

`bg-clip-border` / `bg-clip-padding` / `bg-clip-content` / `bg-clip-text`
background-clip

`bg-none` / `bg-linear-to-r` / `bg-radial` / `bg-conic`
background-image / gradients

`bg-origin-border` / `bg-origin-padding` / `bg-origin-content`
background-origin

`bg-repeat` / `bg-no-repeat` / `bg-repeat-x` / `bg-repeat-y`
background-repeat

Borders

`rounded-xs` ... `rounded-3xl` / `rounded-full`
border-radius (v4: `rounded-sm`→`rounded-xs`, `rounded`→`rounded-sm`)

`border` / `border-2` / `border-t` / `border-x-4`
border-width (default border color is `currentColor` in v4)

`border-solid` / `border-dashed` / `border-dotted` / `border-none`
border-style

`outline` / `outline-2` / `outline-offset-2`
outline-width / outline-offset

`outline-hidden` / `outline-none` / `outline-dashed`
outline-style (v4: `outline-none`→`outline-hidden` keeps focus ring for a11y)

`rounded-t-lg` / `rounded-tl-lg`
border-radius per side / corner

`border-red-500` / `border-black/50`
border-color

`divide-x` / `divide-y` / `divide-red-500`
border between children

`outline-red-500`
outline-color

Effects

`shadow-xs ... shadow-2xl / shadow-none`

box-shadow (v4: shadow-sm→shadow-xs, shadow→shadow-sm)

`opacity-0 ... opacity-100`

opacity

`bg-blend-multiply / bg-blend-overlay`

background-blend-mode

`mask-linear-to-r / mask-radial / mask-[<url>]`

mask-image utilities

`shadow-red-500/50`

colored box-shadow

`mix-blend-multiply / mix-blend-screen / mix-blend-overlay`

mix-blend-mode

`mask-clip-border / mask-origin-padding`

mask-clip / mask-origin

Filters

`blur-xs ... blur-3xl / blur-none`

filter: blur (v4: blur-sm→blur-xs, blur→blur-sm)

`contrast-50 ... contrast-200`

filter: contrast

`grayscale / grayscale-0`

filter: grayscale

`invert / invert-0`

filter: invert

`sepia / sepia-0`

filter: sepia

`backdrop-brightness-50 / backdrop-contrast-125 / backdrop-opacity-50`

other backdrop-filter utilities

`brightness-50 ... brightness-200`

filter: brightness

`drop-shadow-xs ... drop-shadow-2xl`

filter: drop-shadow (v4 renamed, see blur)

`hue-rotate-90 / -hue-rotate-90`

filter: hue-rotate

`saturate-50 ... saturate-200`

filter: saturate

`backdrop-blur-xs ... backdrop-blur-3xl`

backdrop-filter: blur (v4 renamed, see blur)

Tables

`border-collapse / border-separate`

border-collapse

`table-auto / table-fixed`

table-layout

`border-spacing-2 / border-spacing-x-2`

border-spacing

`caption-top / caption-bottom`

caption-side

Transitions & Animation

`transition` / `transition-all` /
`transition-colors` / `transition-none`
`transition-property`

`ease-linear` / `ease-in` / `ease-out` /
`ease-in-out`
`transition-timing-function`

`animate-spin` / `animate-ping` / `animate-pulse` / `animate-bounce` / `animate-none`
animation presets

`duration-75` ... `duration-1000`
`transition-duration`

`delay-75` ... `delay-1000`
`transition-delay`

Transforms

`scale-0` ... `scale-150` / `scale-x-50` /
`scale-y-50`
`scale`

`translate-x-4` / `-translate-y-1/2`
`translate`

`origin-center` / `origin-top-left`
`transform-origin`

`perspective-dramatic` / `perspective-none`
`perspective`

`rotate-0` ... `rotate-180` / `-rotate-45`
`rotate`

`skew-x-6` / `skew-y-3`
`skew`

`transform-none` / `transform-gpu`
force / disable hardware acceleration

`backface-visible` / `backface-hidden`
`backface-visibility`

Interactivity

[accent-red-500](#)

accent-color (checkboxes, radios, range inputs)

[caret-red-500](#)

caret-color

[field-sizing-content](#) / [field-sizing-fixed](#)

field-sizing (auto-growing textareas)

[resize](#) / [resize-none](#) / [resize-x](#) / [resize-y](#)

resize

[scroll-m-4](#) / [scroll-p-4](#)

scroll-margin / scroll-padding

[touch-auto](#) / [touch-none](#) / [touch-pan-x](#)

touch-action

[will-change-auto](#) / [will-change-scroll](#) / [will-change-transform](#)

will-change

[appearance-none](#) / [appearance-auto](#)

appearance

[cursor-pointer](#) / [cursor-not-allowed](#) / [cursor-wait](#) / [cursor-grab](#)

cursor

[pointer-events-none](#) / [pointer-events-auto](#)

pointer-events

[scroll-auto](#) / [scroll-smooth](#)

scroll-behavior

[snap-start](#) / [snap-center](#) / [snap-x](#) / [snap-mandatory](#)

scroll-snap utilities

[select-none](#) / [select-text](#) / [select-all](#) / [select-auto](#)

user-select

SVG

[fill-red-500](#) / [fill-current](#) / [fill-none](#)

fill

[stroke-0](#) / [stroke-1](#) / [stroke-2](#)

stroke-width

[stroke-red-500](#) / [stroke-current](#)

stroke

Accessibility

[sr-only](#) / [not-sr-only](#)

visually hide while keeping content for screen readers

[forced-color-adjust-auto](#) / [forced-color-adjust-none](#)

forced-color-adjust (Windows High Contrast Mode)

Responsive breakpoints

`sm: (≥40rem / 640px)`

small screens and up

`lg: (≥64rem / 1024px)`

large screens and up

`2xl: (≥96rem / 1536px)`

2x extra-large screens and up

`min-[475px]: / max-[600px]:`

arbitrary breakpoint values

`md: (≥48rem / 768px)`

medium screens and up

`xl: (≥80rem / 1280px)`

extra-large screens and up

`max-sm: / max-md: / max-lg: / max-xl: / max-2xl:`

applies below that breakpoint (stack with a lower prefix for a range, e.g. md:max-lg:)

Container queries

`@container / @container/name`

mark an element as a query container (optionally named)

`@max-sm: / @min-[475px]:`

max-width / arbitrary container query variants

`@xs ... @7xl:`

style based on container width instead of viewport (`@sm:flex-row`)

`@sm/name: / @max-md/name:`

target a specific named ancestor container

State variants

`hover:` / `focus:` / `active:` / `visited:`
interaction states

`disabled:` / `required:` / `invalid:` / `checked:`
form states

`group-hover:` / `group-focus:`
style based on a parent with the group class

`has-[:checked]:` / `has-checked:`
`:has()` — style based on a descendant's state

`dark:`
dark mode (based on `prefers-color-scheme` or a class strategy)

`starting:`
`@starting-style` — enter/exit transitions without JS

`focus-within:` / `focus-visible:`
focus states for parent / keyboard-only focus

`first:` / `last:` / `odd:` / `even:` / `only:`
structural pseudo-classes

`peer-checked:` / `peer-focus:`
style based on a sibling with the peer class

`not-hover:` / `not-disabled:`
`:not()` — style when a state does NOT apply

`before:` / `after:` / `placeholder:` / `selection:` / `file:`
pseudo-elements