

Tailwind CSS v4 Cheatsheet

Extended, grouped reference for Tailwind CSS v4 utility classes — compiled from the official docs so it actually reflects v4, not v3. Need something you can keep on your desk? [Try the condensed version.](#)

Changed since v3

The most common source of outdated cheatsheets: these utilities were renamed or changed behavior in v4.

v3	v4	Note
shadow-sm	shadow-xs	
shadow	shadow-sm	
drop-shadow-sm	drop-shadow-xs	
drop-shadow	drop-shadow-sm	
blur-sm	blur-xs	
blur	blur-sm	
backdrop-blur-sm	backdrop-blur-xs	
backdrop-blur	backdrop-blur-sm	
rounded-sm	rounded-xs	
rounded	rounded-sm	
outline-none	outline-hidden	
ring	ring-3	default ring width is now 1px, not 3px
flex-shrink-*	shrink-*	
flex-grow-*	grow-*	
overflow-ellipsis	text-ellipsis	
decoration-slice	box-decoration-slice	
decoration-clone	box-decoration-clone	
bg-opacity-*	bg-black/50	opacity modifiers replace all *-opacity-* utilities
text-opacity-*	text-black/50	
border-opacity-*	border-black/50	
ring-opacity-*	ring-black/50	
!flex	flex!	important modifier moved to the end of the class
bg-[--brand]	bg-(--brand)	arbitrary CSS variable syntax
grid-cols-[max-content,auto]	grid-cols-[max-content_auto]	commas in arbitrary values become underscores

Layout

`container`

Fixed max-width at each breakpoint

`block` / `inline-block` / `inline`

`display`

`flex` / `inline-flex`

`display: flex`

`grid` / `inline-grid`

`display: grid`

`hidden`

`display: none`

`aspect-square` / `aspect-video` / `aspect-[4/3]`

`aspect-ratio`

`columns-2 ... columns-12`

`column-count`

`break-after-column` / `break-before-page` / `break-inside-avoid`

CSS fragmentation breaks

`box-border` / `box-content`

`box-sizing`

`float-left` / `float-right` / `float-none`

`float`

`clear-left` / `clear-right` / `clear-both`

`clear`

`isolate` / `isolation-auto`

`isolation (stacking context)`

`object-cover` / `object-contain` / `object-fill` / `object-none`

`object-fit`

`object-center` / `object-top` / `object-left-bottom`

`object-position`

`overflow-auto` / `overflow-hidden` / `overflow-scroll` / `overflow-visible`

`overflow (also overflow-x-*, overflow-y-*)`

`overscroll-auto` / `overscroll-contain` / `overscroll-none`

`overscroll-behavior`

`static` / `fixed` / `absolute` / `relative` / `sticky`

`position`

`inset-0` / `top-4` / `right-2` / `bottom-0` / `left-1/2`

`top` / `right` / `bottom` / `left`

`visible` / `invisible` / `collapse`

`visibility`

Flexbox & Grid

`flex-row` / `flex-row-reverse` / `flex-col` / `flex-col-reverse`

`flex-direction`

`flex-wrap` / `flex-wrap-reverse` / `flex-nowrap`

`flex-wrap`

`flex-1` / `flex-auto` / `flex-initial` / `flex-none`

`flex shorthand`

`grow` / `grow-0`

`flex-grow (was flex-grow-* in v3)`

`shrink` / `shrink-0`

`flex-shrink (was flex-shrink-* in v3)`

`basis-0` / `basis-1/2` / `basis-full` / `basis-64`

`flex-basis`

`order-1 ... order-12` / `order-first` / `order-last` / `-order-1`

`order`

`grid-cols-1 ... grid-cols-12` / `grid-cols-none`

`grid-template-columns`

`col-span-2` / `col-start-3` / `col-end-5` / `col-auto`

`grid-column placement`

`grid-rows-1 ... grid-rows-6`

`grid-template-rows`

`row-span-2` / `row-start-1` / `row-end-3`

`grid-row placement`

`grid-flow-row` / `grid-flow-col` / `grid-flow-dense`

`grid-auto-flow`

`auto-cols-auto` / `auto-cols-min` / `auto-cols-fr`

`grid-auto-columns`

`auto-rows-auto` / `auto-rows-min` / `auto-rows-fr`

`grid-auto-rows`

`gap-4` / `gap-x-2` / `gap-y-6`

`gap between flex/grid items`

`justify-start` / `justify-center` / `justify-between` / `justify-evenly`

`justify-content`

`justify-items-start` / `justify-items-center` / `justify-items-stretch`

`justify-items`

`justify-self-auto` / `justify-self-end`

z-0 ... z-50 / z-auto / -z-10
z-index

justify-self

content-center / content-between /
content-stretch

align-content

items-start / items-center / items-
baseline / items-stretch

align-items

self-auto / self-center / self-stretch
align-self

place-content-center / place-items-
center / place-self-center

place-* shorthands

Spacing

p-4 / px-4 / py-4 / pt-4 / pr-4 / pb-4
/ pl-4

padding (all sides / axis / single side)

ps-4 / pe-4

padding-inline-start / padding-inline-end (logical)

m-4 / mx-auto / my-4 / mt-4 / -mt-4

margin (negative values allowed with -)

ms-4 / me-4

margin-inline-start / margin-inline-end (logical)

space-x-4 / space-y-4

gap between direct children (adds margin between
siblings)

space-x-reverse

reverses the direction spacing is applied

0, px, 0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4,
5, 6, 7, 8, 9, 10, 11, 12, 14, 16, 20,
24, 28, 32, 36, 40, 44, 48, 52, 56,
60, 64, 72, 80, 96

default spacing scale (1 unit = 0.25rem = 4px, so p-
4 = 1rem)

Sizing

w-4 / w-1/2 / w-full / w-screen / w-
fit / w-min / w-max

width

min-w-0 / min-w-full / min-w-fit

min-width

max-w-xs ... max-w-7xl / max-w-full /
max-w-prose / max-w-none

max-width

h-4 / h-1/2 / h-full / h-screen / h-
dvh / h-svh / h-lvh

height (dvh/svh/lvh = dynamic/small/large viewport
units)

min-h-0 / min-h-screen / min-h-full

min-height

max-h-full / max-h-screen

max-height

size-4 / size-full / size-1/2

sets width and height together

Typography

`font-sans / font-serif / font-mono`
font-family

`text-xs ... text-9xl`
font-size (each step sets a matching line-height)

`antialiased / subpixel-antialiased`
font-smoothing

`italic / not-italic`
font-style

`font-thin ... font-black`
font-weight (100-900)

`tracking-tighter ... tracking-widest`
letter-spacing

`leading-none ... leading-loose /`
`leading-4 ... leading-10`
line-height

`line-clamp-1 ... line-clamp-6 / line-clamp-none`
truncate text to N lines

`list-none / list-disc / list-decimal`
list-style-type

`list-inside / list-outside`
list-style-position

`text-left / text-center / text-right /`
`text-justify`
text-align

`text-red-500 / text-black/50`
text color (with opacity modifier)

`underline / overline / line-through /`
`no-underline`
text-decoration-line

`decoration-red-500 / decoration-2 /`
`decoration-wavy`
text-decoration color / thickness / style

`underline-offset-4`
text-underline-offset

`uppercase / lowercase / capitalize /`
`normal-case`
text-transform

`truncate / text-ellipsis / text-clip`
text-overflow

`text-wrap / text-nowrap / text-balance`
`/ text-pretty`
text-wrap

`indent-4 / -indent-4`
text-indent

Backgrounds

`bg-fixed / bg-local / bg-scroll`
background-attachment

`bg-clip-border / bg-clip-padding / bg-clip-content / bg-clip-text`
background-clip

`bg-red-500 / bg-transparent / bg-black/25`
background-color (with opacity modifier)

`bg-none / bg-linear-to-r / bg-radial /`
`bg-conic`
background-image / gradients

`from-cyan-500 via-blue-500 to-indigo-500`
gradient color stops

`bg-origin-border / bg-origin-padding /`
`bg-origin-content`
background-origin

`bg-center / bg-top / bg-`
`[center_top_1rem]`
background-position

`bg-repeat / bg-no-repeat / bg-repeat-x`
`/ bg-repeat-y`
background-repeat

`bg-auto / bg-cover / bg-contain`
background-size

`align-baseline` / `align-top` / `align-middle` / `align-bottom`
`vertical-align`

`whitespace-normal` / `whitespace-nowrap` / `whitespace-pre-wrap`
`white-space`

`break-normal` / `break-words` / `break-all` / `break-keep`
`word-break` / `overflow-wrap`

`hyphens-none` / `hyphens-manual` / `hyphens-auto`
`hyphens`

`content-none` / `content-['*']`
`content` (for `::before` / `::after`)

`text-shadow-2xs` ... `text-shadow-lg` / `text-shadow-none`
`text-shadow` (new utility in v4)

Borders

`rounded-xs` ... `rounded-3xl` / `rounded-full`
`border-radius` (v4: `rounded-sm`→`rounded-xs`, `rounded`→`rounded-sm`)

`rounded-t-lg` / `rounded-tl-lg`
`border-radius` per side / corner

`border` / `border-2` / `border-t` / `border-x-4`
`border-width` (default border color is `currentColor` in v4)

`border-red-500` / `border-black/50`
`border-color`

`border-solid` / `border-dashed` / `border-dotted` / `border-none`
`border-style`

`divide-x` / `divide-y` / `divide-red-500`
border between children

`outline` / `outline-2` / `outline-offset-2`
`outline-width` / `outline-offset`

`outline-red-500`
`outline-color`

`outline-hidden` / `outline-none` / `outline-dashed`
`outline-style` (v4: `outline-none`→`outline-hidden` keeps focus ring for a11y)

Effects

`shadow-xs` ... `shadow-2xl` / `shadow-none`
`box-shadow` (v4: `shadow-sm`→`shadow-xs`, `shadow`→`shadow-sm`)

`shadow-red-500/50`
colored box-shadow

`opacity-0` ... `opacity-100`
`opacity`

`mix-blend-multiply` / `mix-blend-screen` / `mix-blend-overlay`
`mix-blend-mode`

`bg-blend-multiply` / `bg-blend-overlay`
background-blend-mode

`mask-clip-border` / `mask-origin-padding`
`mask-clip` / `mask-origin`

`mask-linear-to-r` / `mask-radial` / `mask-[<url>]`
mask-image utilities

Filters

`blur-xs ... blur-3xl / blur-none`
filter: blur (v4: blur-sm→blur-xs, blur→blur-sm)

`brightness-50 ... brightness-200`
filter: brightness

`contrast-50 ... contrast-200`
filter: contrast

`drop-shadow-xs ... drop-shadow-2xl`
filter: drop-shadow (v4 renamed, see blur)

`grayscale / grayscale-0`
filter: grayscale

`hue-rotate-90 / -hue-rotate-90`
filter: hue-rotate

`invert / invert-0`
filter: invert

`saturate-50 ... saturate-200`
filter: saturate

`sepia / sepia-0`
filter: sepia

`backdrop-blur-xs ... backdrop-blur-3xl`
backdrop-filter: blur (v4 renamed, see blur)

`backdrop-brightness-50 / backdrop-contrast-125 / backdrop-opacity-50`
other backdrop-filter utilities

Tables

`border-collapse / border-separate`
border-collapse

`border-spacing-2 / border-spacing-x-2`
border-spacing

`table-auto / table-fixed`
table-layout

`caption-top / caption-bottom`
caption-side

Transitions & Animation

`transition` / `transition-all` /
`transition-colors` / `transition-none`
`transition-property`

`duration-75` ... `duration-1000`
`transition-duration`

`ease-linear` / `ease-in` / `ease-out` /
`ease-in-out`
`transition-timing-function`

`delay-75` ... `delay-1000`
`transition-delay`

`animate-spin` / `animate-ping` / `animate-pulse` / `animate-bounce` / `animate-none`
`animation` presets

Transforms

`scale-0` ... `scale-150` / `scale-x-50` /
`scale-y-50`
`scale`

`rotate-0` ... `rotate-180` / `-rotate-45`
`rotate`

`translate-x-4` / `-translate-y-1/2`
`translate`

`skew-x-6` / `skew-y-3`
`skew`

`origin-center` / `origin-top-left`
`transform-origin`

`transform-none` / `transform-gpu`
`force` / `disable hardware acceleration`

`perspective-dramatic` / `perspective-none`
`perspective`

`backface-visible` / `backface-hidden`
`backface-visibility`

Interactivity

`accent-red-500`

accent-color (checkboxes, radios, range inputs)

`appearance-none` / `appearance-auto`

appearance

`caret-red-500`

caret-color

`cursor-pointer` / `cursor-not-allowed` /
`cursor-wait` / `cursor-grab`

cursor

`field-sizing-content` / `field-sizing-fixed`

field-sizing (auto-growing textareas)

`pointer-events-none` / `pointer-events-auto`

pointer-events

`resize` / `resize-none` / `resize-x` /
`resize-y`

resize

`scroll-auto` / `scroll-smooth`

scroll-behavior

`scroll-m-4` / `scroll-p-4`

scroll-margin / scroll-padding

`snap-start` / `snap-center` / `snap-x` /
`snap-mandatory`

scroll-snap utilities

`touch-auto` / `touch-none` / `touch-pan-x`

touch-action

`select-none` / `select-text` / `select-all` /
`select-auto`

user-select

`will-change-auto` / `will-change-scroll` /
`will-change-transform`

will-change

SVG

`fill-red-500` / `fill-current` / `fill-none`

fill

`stroke-red-500` / `stroke-current`

stroke

`stroke-0` / `stroke-1` / `stroke-2`

stroke-width

Accessibility

`sr-only` / `not-sr-only`

visually hide while keeping content for screen readers

`forced-color-adjust-auto` / `forced-color-adjust-none`

forced-color-adjust (Windows High Contrast Mode)

Responsive breakpoints

`sm: (≥40rem / 640px)`

small screens and up

`md: (≥48rem / 768px)`

medium screens and up

`lg: (≥64rem / 1024px)`

large screens and up

`x1: (≥80rem / 1280px)`

extra-large screens and up

`2x1: (≥96rem / 1536px)`

2x extra-large screens and up

`max-sm: / max-md: / max-lg: / max-x1: / max-2x1:`

applies below that breakpoint (stack with a lower prefix for a range, e.g. md:max-lg:)

`min-[475px]: / max-[600px]:`

arbitrary breakpoint values

Container queries

`@container` / `@container/name`

mark an element as a query container (optionally named)

`@xs ... @7xl:`

style based on container width instead of viewport (`@sm:flex-row`)

`@max-sm:` / `@min-[475px]:`

max-width / arbitrary container query variants

`@sm/name:` / `@max-md/name:`

target a specific named ancestor container

State variants

`hover:` / `focus:` / `active:` / `visited:`
interaction states

`focus-within:` / `focus-visible:`
focus states for parent / keyboard-only focus

`disabled:` / `required:` / `invalid:` / `checked:`
form states

`first:` / `last:` / `odd:` / `even:` / `only:`
structural pseudo-classes

`group-hover:` / `group-focus:`
style based on a parent with the group class

`peer-checked:` / `peer-focus:`
style based on a sibling with the peer class

`has-[:checked]:` / `has-checked:`
`:has()` — style based on a descendant's state

`not-hover:` / `not-disabled:`
`:not()` — style when a state does NOT apply

`dark:`
dark mode (based on `prefers-color-scheme` or a class strategy)

`before:` / `after:` / `placeholder:` / `selection:` / `file:`
pseudo-elements

`starting:`
`@starting-style` — enter/exit transitions without JS