CLOUD4C



Linux Server Access Via CyberArk – UCP User Guide





Document control

Prepared By

Version	Author	Date
V 1.0	Sai Krishna	29-04-2022

Reviewed By

Version	Reviewer	Date
V 1.0	Priyadarshi Mishra	30-04-2022

Approved By

Version	Approver	Date
V 1.0	Harmandeep Singh	30-04-2022

Change Control

Version	Change Reason	Effective Date
V 1.0	Initial Release	

STATEMENT OF CONFIDENTIALITY

This document contains proprietary trade secret and confidential information to be used solely for evaluating CtrlS & Cloud4C Datacentres' Ltd. The information contained herein is to be considered confidential. Customer, by receiving this document, agrees that neither this document nor the information disclosed herein, nor any part thereof, shall be reproduced or transferred to other documents, or used or disclosed to others for any purpose except as specifically authorized in writing by Ctrl S Datacentres' Ltd.



Contents Document control______2 Prepared By _____ ___2 Reviewed By _____ 2 Approved By ______ Change Control ______2 STATEMENT OF CONFIDENTIALITY _____ 2 Contents _____ 1. Introduction to UCP_____ 4 2. Procedure _______ 4 3. Glossary_____ 15 3.1 Definition_______15



1. Introduction to UCP


Welcome to the UCP user guide

This document emphasizes on accessing a server via Cyberark


- 1. Ordering for server access via UCP
- 2. Steps in Cyberark to access VM

2. Procedure

Step 1 – Navigate to https://ucp.dhl.com




Step 1.a - Enter your DHL email id AD Credentials




The user will be landing on the dashboard as shown hereunder






Step 3 – Navigate to Manage -> Azure -> User VM Access Requests.



b. Click on New VM Access request





A Pop-up screen will appear.

Step 2 : Select the Subscription, Resource Group, OS Type: Linux, Account Type


BU Sysadmin – A Business user Admin who needs temporary access to all the virtual machines in the resource Group

BU Application Admin – A Business user Admin who needs temporary access to all the virtual machines of different application types such as Apache, Tomcat, JBOSS, Weblogic and Oracle Database, within the resource Group.

Select the email in the "Provide Access to" Dropdown list.

Note: If an email id is not visible in the dropdown list, then please refer to "AAD User Onboarding - UCP User guide v 1.0" to onboard the email id to UDLDHL-PVWA Group first. After 45-60 minutes the email id will appear in the dropdown list below.

Select the desired duration and click on "Submit"




The request then goes for an approval to the Resource Group Owner / Team Manager



Click on Approve -> Proceed

The requestor will receive an acknowledgement







The user who needs the access to the Virtual Machine will receive an acknowledgement email with the steps to login to the requested machine.

Below are the steps

Step1: Login into DHL network (VDI/VPN) and access the below PAM URL based on Region.

Region	URL
SEA	https://pvwa-sea.dhl.com
West EU	https://pvwa-weu.dhl.com
East U.S	https://pvwa-eus.dhl.com




Figure-1: SEA PAM URL

Figure-2: WEU PAM URL




Figure-3: EU.S PAM URL



Step2: Click on SAML authentication for login and then it will login directly to CyberArk Console using Azure AD credentials.




Figure-4: On Login End User Dashboard.

Step3: Navigate (On Left Pane) select Accounts → PSM for SSH MFA Caching.




Figure-5: Navigating to PSM for SSH MFA Caching Tab.



Step 4: Click on Generate and Download PPK private key from CyberArk portal (Which is valid for 60 minutes) from PSM for SSH MFA Caching window.




Figure-6: Generating Private Keys

Step4: Import the private key into putty (On Putty Application left pane select Connection \rightarrow SSH \rightarrow Auth \rightarrow Private key file for authentication)






Figure-7: Connection through Putty Private Key

Step5: Prepare the connection string and put it into the hostname. (Session → Hostname)

Connection String: <CyberArkUserID>%<TargetAccountName>%<TargetServerIP>@<RegionSpecificPSM-SSHServerLoadBalancerIP>

Example: keerthana.ch@dhl.com%sadminits%10.224.174.4@10.224.18.42

East US PSM-SSH Load Balancer IP: 10.224.18.42

West Europe PSM-SSH Load Balancer IP: 10.156.9.145

SEA PSM-SSH Load Balancer IP: 10.234.1.72






Figure-7: Connection to Target server using MFA Cache

Step 6: Specify the reason for accessing the target server and continue accessing the server.


```
🧬 10.224.18.42 - PuTTY
                                                                         \Box
                                                                               ×
         related to services provided by DPDHL. DPDHL reserves the
         right to monitor all usage of the computer system.
         Your use of this system shall be deemed to constitute
          (a) your irrevocable consent to DHL monitoring the
         system and all data contained in or accessed through
         it, and (b) your acknowledgement that unauthorized
         use may give rise to administrative, criminal, civil,
         or other action being taken against you.
  End of banner message from server
  Authenticating with public key "CyberArk Auto-generated Key"
  Further authentication required
  Keyboard-interactive authentication prompts from server:
 You are required to specify a reason for this operation:
End of keyboard-interactive prompts from server
Activate the web console with: systemctl enable --now cockpit.socket
This system is not registered to Red Hat Insights. See https://cloud.redhat.com/
To register this system, run: insights-client --register
This session is being recorded
```


Figure-8: Access to target server



Step 2: Extending the duration of the access.

Navigate to Manage -> Azure -> User VM Access List






The user can modify the duration of the by clicking on the edit button as shown below.








Click on "Update" for the duration to be updated.

The requestor will receive an acknowledgement email with the information about extended duration.

Step 3 – Revoke Access

The Resource group Owner can request to revoke the access of the virtual machines in the resource group at any time, so the business user is not allowed to access them at anytime.



Clicking on OK, will revoke the access of the servers to the business user.



3. Glossary

3.1 Definition

Terms	Abbreviation
VM	Virtual Machine
UCP	Universal Cloud Platform