



ADOBE® PHOTOSHOP® CS5



ADOBE PHOTOSHOP CS5

JAVASCRIPT SCRIPTING REFERENCE

Revision 1



© 2010 Adobe Systems Incorporated. All rights reserved.

Adobe® Creative Suite® 5 Photoshop® JavaScript Scripting Reference for Windows® and Macintosh®.

NOTICE: All information contained herein is the property of Adobe Systems Incorporated. No part of this publication (whether in hardcopy or electronic form) may be reproduced or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Adobe Systems Incorporated. The software described in this document is furnished under license and may only be used or copied in accordance with the terms of such license.

This publication and the information herein is furnished AS IS, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies, makes no warranty of any kind (express, implied, or statutory) with respect to this publication, and expressly disclaims any and all warranties of merchantability, fitness for particular purposes, and noninfringement of third party rights.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe®, the Adobe logo, Acrobat®, GoLive®, InDesign®, Illustrator®, Photoshop® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Apple®, Mac OS®, and Macintosh® are trademarks of Apple Computer, Inc., registered in the United States and other countries. Microsoft®, and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries. JavaScript™ and all Java-related marks are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries. UNIX® is a registered trademark of The Open Group.

All other trademarks are the property of their respective owners.

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe Systems Incorporated. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Adobe Systems Incorporated, 345 Park Avenue, San Jose, California 95110, USA.

Contents

1	Introduction	33
	JavaScript support in Adobe Photoshop CS5	33
	Executing scripts	34
	Installing scripts	34
	Executing other scripts	34
	Startup scripts	34
	Object model usage and naming	35
	Changes since earlier versions—CS5 changes	35
	36
2	JavaScript Object Reference	37
	Object descriptions.....	37
	Properties notation	37
	displayDialogs.....	37
	Methods notation	37
	crop.....	38
	ActionDescriptor	39
	Properties.....	39
	count	39
	typename	39
	Methods	39
	clear	39
	erase	39
	fromStream	39
	getBoolean.....	39
	getClass	39
	getData.....	39
	getDouble	39
	getEnumerationType	39
	getEnumerationValue.....	39
	getInteger.....	39
	getKey.....	39
	getList	40
	getObjectType.....	40
	getObjectValue.....	40
	getPath	40
	getReference	40
	getString	40
	getType	40
	getUnitDoubleType	40
	getUnitDoubleValue.....	40
	hasKey.....	40
	isEqual.....	40
	putBoolean	40
	putClass.....	40
	putData	40

putDouble	40
putEnumerated	40
putInteger	40
putList	41
putObject.....	41
putPath.....	41
putReference	41
putString.....	41
putUnitDouble.....	41
toStream	41
ActionList.....	42
Properties.....	42
count	42
typename	42
Methods	42
clear	42
getBoolean.....	42
getClass	42
getData.....	42
getDouble	42
getEnumerationType	42
getEnumerationValue.....	42
getInteger.....	42
getList	43
getObjectType.....	43
getObjectValue.....	43
getPath	43
getReference	43
getString	43
getType	43
getUnitDoubleType	43
getUnitDoubleValue.....	43
putBoolean	43
putClass.....	43
putData	43
putDouble	43
putEnumerated	43
putInteger	43
putList.....	43
putObject.....	43
putPath.....	43
putReference.....	43
putString.....	44
putUnitDouble.....	44
ActionReference	45
Properties.....	45
typename	45
Methods	45
getContainer	45
getDesiredClass.....	45
getEnumeratedType.....	45

getEnumeratedValue	45
getForm.....	45
getIdentifier.....	45
getIndex.....	45
getName	45
getOffset	45
getProperty	45
putClass.....	46
putEnumerated	46
putIdentifier.....	46
putIndex.....	46
putName	46
putOffset.....	46
putProperty.....	46
Application	47
Properties.....	47
activeDocument.....	47
backgroundColor.....	47
build.....	47
colorSettings	47
displayDialogs.....	47
documents	47
fonts.....	47
foregroundColor	47
freeMemory	47
locale	48
macintoshFileTypes	48
measurementLog	48
name.....	48
notifiers	48
notifiersEnabled	48
path.....	48
playbackDisplayDialogs	48
playbackParameters	48
preferences	48
preferencesFolder	48
recentFiles	48
scriptingBuildDate	48
scriptingVersion	48
systemInformation.....	48
typename	48
version	49
windowsFileTypes	49
Methods	49
batch	49
beep.....	49
bringToFront	49
charIDToTypeID.....	49
doAction	49
eraseCustomOptions.....	49
executeAction.....	49

executeActionGet.....	49
featureEnabled	49
getCustomOptions.....	50
isQuicktimeAvailable.....	50
load	50
makeContactSheet.....	50
makePDFPresentation	50
makePhotoGallery	50
makePhotomerge.....	50
makePicturePackage	50
open	51
openDialog	51
purge.....	51
putCustomOptions	51
refresh	51
refreshFonts.....	51
runMenuItem	51
showColorPicker	52
stringIDToTypeID.....	52
togglePalettes.....	52
TypeIDToCharID.....	52
TypeIDToStringID.....	52
ArtLayer.....	55
Properties.....	55
allLocked.....	55
blendMode.....	55
bounds.....	55
fillOpacity.....	55
filterMaskDensity.....	55
filterMaskFeather	55
grouped	55
isBackgroundLayer.....	55
kind	55
layerMaskDensity.....	55
layerMaskFeather	56
linkedLayers.....	56
name.....	56
opacity	56
parent.....	56
pixelsLocked	56
positionLocked	56
textItem.....	56
transparentPixelsLocked.....	56
typename	56
vectorMaskDensity.....	56
vectorMaskFeather	56
visible	56
xmpMetadata.....	56
Methods	57
adjustBrightnessContrast	57
adjustColorBalance	57

adjustCurves	57
adjustLevels	57
applyAddNoise	57
applyAverage	57
applyBlur	57
applyBlurMore	57
applyClouds	57
applyCustomFilter	57
applyDeInterlace	58
applyDespeckle	58
applyDifferenceClouds	58
applyDiffuseGlow	58
applyDisplace	58
applyDustAndScratches	58
applyGaussianBlur	58
applyGlassEffect	58
applyHighPass	58
applyLensBlur	59
applyLensFlare	59
applyMaximum	59
applyMedianNoise	59
applyMinimum	60
applyMotionBlur	60
applyNTSC	60
applyOceanRipple	60
applyOffset	60
applyPinch	60
applyPolarCoordinates	60
applyRadialBlur	60
applyRipple	60
applySharpen	60
applySharpenEdges	60
applySharpenMore	60
applyShear	60
applySmartBlur	61
applySpherize	61
applyStyle	61
applyTextureFill	61
applyTwirl	61
applyUnSharpMask	61
applyWave	61
applyZigZag	61
autoContrast	61
autoLevels	61
clear	61
copy	62
cut	62
desaturate	62
duplicate	62
equalize	62
invert	62

link.....	62
merge.....	62
mixChannels.....	63
move.....	63
photoFilter	63
posterize	63
rasterize.....	63
remove.....	63
resize	64
rotate.....	64
selectiveColor.....	64
shadowHighlight	64
threshold.....	64
translate	64
unlink	64
ArtLayers.....	67
Properties.....	67
length.....	67
parent.....	67
typename	67
Methods	67
add	67
getByName	67
removeAll	67
BatchOptions	68
Properties.....	68
destination	68
destinationFolder	68
errorFile	68
fileNameing.....	68
macintoshCompatible	68
overrideOpen.....	68
overrideSave.....	68
startingSerial	68
suppressOpen.....	68
suppressProfile	69
typename	69
unixCompatible.....	69
windowsCompatible	69
BitmapConversionOptions	70
Properties.....	70
angle.....	70
frequency.....	70
method.....	70
patternName	70
resolution.....	70
shape.....	70
typename	70
BMPSaveOptions	71
Properties.....	71
alphaChannels	71

depth.....	71
flipRowOrder	71
osType.....	71
rleCompression	71
typename	71
CameraRAWOpenOptions	72
Properties.....	72
bitsPerChannel	72
blueHue.....	72
blueSaturation	72
brightness.....	72
chromaticAberrationBY	72
chromaticAberrationRC.....	72
colorNoiseReduction	72
colorSpace.....	72
contrast	72
exposure	72
greenHue.....	72
greenSaturation	72
luminanceSmoothing	72
redHue.....	72
redSaturation	72
resolution.....	72
saturation	72
settings	72
shadows	72
shadowTint	72
sharpness.....	72
size	72
temperature.....	72
tint.....	73
typename	73
vignettingAmount	73
vignettingMidpoint	73
whiteBalance.....	73
Channel.....	74
Properties.....	74
color.....	74
histogram	74
kind	74
name.....	74
opacity	74
parent.....	74
typename	74
visible	74
Methods	74
duplicate	74
merge.....	75
remove.....	75
Channels.....	76
Properties.....	76

length.....	76
parent.....	76
typename	76
Methods	76
add	76
getByName	76
removeAll	76
CMYKColor	81
Properties.....	81
black	81
cyan.....	81
magenta	81
typename	81
yellow	81
ColorSampler	82
Properties.....	82
color.....	82
position	82
parent.....	82
typename	82
Methods	82
move.....	82
remove.....	82
ColorSamplers	83
Properties.....	83
length.....	83
parent.....	83
typename	83
Methods	83
add	83
removeAll	83
ContactSheetOptions	84
Properties.....	84
acrossFirst.....	84
bestFit	84
caption.....	84
columnCount	84
flatten.....	84
font.....	84
fontSize.....	84
height.....	84
horizontal	84
mode	84
resolution.....	84
rowCount.....	84
typename	84
useAutoSpacing	84
vertical	84
width	84
CountItem	85
Properties.....	85

position	85
parent.....	85
typename	85
Methods	85
remove.....	85
CountItems	86
Properties.....	86
length.....	86
parent.....	86
typename	86
Methods	86
add	86
getByName	86
removeAll	86
DCS1_SaveOptions	87
Properties.....	87
dCS	87
embedColorProfile	87
encoding.....	87
halftoneScreen	87
interpolation.....	87
preview	87
transferFunction.....	87
typename	87
vectorData.....	87
DCS2_SaveOptions	88
Properties.....	88
dCS	88
embedColorProfile	88
encoding.....	88
halftoneScreen	88
interpolation.....	88
multiFileDCS	88
preview	88
spotColors	88
transferFunction.....	88
typename	88
vectorData.....	88
DICOMOpenOptions	89
Properties.....	89
anonymize.....	89
columns.....	89
reverse	89
rows	89
showOverlays.....	89
typename	89
windowLevel	89
windowWidth	89
Document	90
Properties.....	90
activeChannels	90

activeHistoryBrushSource	90
activeHistoryState	90
activeLayer	90
artLayers.....	90
backgroundLayer.....	90
bitsPerChannel	90
channels	90
colorProfileName.....	90
colorProfileType.....	90
colorSamplers	90
componentChannels.....	90
countItems	91
fullName.....	91
guides	91
height.....	91
histogram	91
historyStates	91
info	91
layerComps	91
layers	91
layerSets.....	91
managed.....	91
measurementScale	91
mode	91
name.....	91
parent.....	91
path.....	91
pathItems	91
pixelAspectRatio	91
printSettings.....	91
quickMaskMode.....	92
resolution.....	92
saved	92
selection.....	92
typename	92
width	92
xmpMetadata.....	92
Methods	93
autoCount	93
changeMode	93
close.....	93
convertProfile.....	93
crop.....	93
duplicate	93
exportDocument	94
flatten.....	94
flipCanvas	94
importAnnotations	94
mergeVisibleLayers.....	94
paste	94
print	94

printOneCopy	94
rasterizeAllLayers	94
recordMeasurements	94
resizeCanvas	94
resizeImage	94
revealAll	95
rotateCanvas	95
save	95
saveAs	95
splitChannels	95
suspendHistory	95
trap	95
trim	95
DocumentPrintSettings	98
Properties	98
backgroundColor	98
bleedWidth	98
caption	98
centerCropMarks	98
colorBars	98
copies	98
cornerCropMarks	98
colorHandling	98
activePrinter	98
flip	98
hardProof	98
interpolate	98
labels	98
mapBlack	98
negative	98
renderIntent	98
posX	98
posY	98
printBorder	98
printerName	98
printSpace	98
registrationMarks	98
scale	99
vectorData	99
Methods	100
setPagePosition	100
DocumentInfo	101
Properties	101
author	101
authorPosition	101
caption	101
captionWriter	101
category	101
city	101
copyrighted	101
copyrightNotice	101

country	101
creationDate	101
credit	101
exif	101
headline	101
instructions	101
jobName	101
keywords	101
ownerUrl	101
parent	102
provinceState	102
source	102
supplementalCategories	102
title	102
transmissionReference	102
typename	102
urgency	102
Documents	104
Properties	104
length	104
parent	104
typename	104
Methods	104
add	104
getByName	104
EPSSaveOptions	105
Properties	105
antiAlias	105
constrainProportions	105
height	105
mode	105
resolution	105
typename	105
width	105
EPSSaveOptions	106
Properties	106
embedColorProfile	106
encoding	106
halftoneScreen	106
interpolation	106
preview	106
psColorManagement	106
transferFunction	106
transparentWhites	106
typename	106
vectorData	106
ExportOptionsIllustrator	107
Properties	107
path	107
pathName	107
typename	107

ExportOptionsSaveForWeb	108
Properties.....	108
blur.....	108
colorReduction	108
colors.....	108
dither.....	108
ditherAmount	108
format	108
includeProfile	108
interlaced.....	108
lossy	108
matteColor	108
optimized	108
PNG8.....	108
quality	109
transparency.....	109
transparencyAmount	109
transparencyDither	109
typename	109
webSnap	109
File.....	110
Folder	110
GalleryBannerOptions	111
Properties.....	111
contactInfo.....	111
date.....	111
font.....	111
fontSize.....	111
photographer.....	111
siteName	111
typename	111
GalleryCustomColorOptions	112
Properties.....	112
activeLinkColor.....	112
backgroundColor.....	112
bannerColor.....	112
linkColor	112
textColor	112
typename	112
visitedLinkColor.....	112
GalleryImagesOptions	113
Properties.....	113
border	113
caption.....	113
dimension.....	113
font.....	113
fontSize.....	113
imageQuality.....	113
includeCopyright.....	113
includeCredits.....	113
includeFilename.....	113

includeTitle	113
numericLinks	113
resizeConstraint	114
resizeImages	114
typename	114
GalleryOptions.....	115
Properties.....	115
addSizeAttributes	115
bannerOptions	115
customColorOptions	115
emailAddress.....	115
imagesOptions	115
includeSubFolders	115
layoutStyle	115
preserveAllMetadata	115
securityOptions	115
thumbnailOptions	115
typename	115
useShortExtension	115
useUTF8Encoding	115
GallerySecurityOptions	116
Properties.....	116
content	116
font.....	116
fontSize.....	116
opacity	116
text	116
textColor	116
textPosition.....	116
textRotate	116
typename	116
GalleryThumbnailOptions.....	117
Properties.....	117
border	117
caption.....	117
columnCount	117
dimension.....	117
font.....	117
fontSize.....	117
includeCopyright.....	117
includeCredits.....	117
includeFilename.....	117
includeTitle	117
rowCount.....	117
size	117
typename	117
GIFSaveOptions.....	118
Properties.....	118
colors.....	118
dither.....	118
ditherAmount	118

forced	118
interlaced	118
matte	118
palette	118
preserveExactColors	118
transparency	118
typename	118
GrayColor	119
Properties	119
gray	119
typename	119
Guide	120
Properties	120
direction	120
coordinate	120
Guides	121
Properties	121
length	121
parent	121
typename	121
Methods	121
add	121
getByName	121
HistoryState	122
Properties	122
name	122
parent	122
snapshot	122
typename	122
HistoryStates	123
Properties	123
length	123
parent	123
typename	123
Methods	123
getByName	123
HSBColor	124
Properties	124
brightness	124
hue	124
saturation	124
typename	124
IndexedConversionOptions	125
Properties	125
colors	125
dither	125
ditherAmount	125
forced	125
matte	125
palette	125
preserveExactColors	125

transparency.....	125
typename	125
JPEGSaveOptions	126
Properties.....	126
embedColorProfile.....	126
formatOptions	126
matte	126
quality	126
scans	126
typename	126
LabColor	127
Properties.....	127
a.....	127
b	127
l.....	127
typename	127
LayerComp.....	128
Properties.....	128
appearance	128
comment	128
name.....	128
parent.....	128
position	128
selected	128
typename	128
visibility	128
Methods	128
apply.....	128
recapture	128
remove.....	128
resetfromComp	128
LayerComps.....	129
Properties.....	129
length.....	129
parent.....	129
typename	129
Methods	129
add	129
getByName	129
removeAll	129
Layers.....	130
Properties.....	130
length.....	130
parent.....	130
typename	130
Methods	130
getByName	130
removeAll	130
LayerSet	131
Properties.....	131
allLocked.....	131

artLayers.....	131
blendMode.....	131
bounds.....	131
enabledChannels.....	131
layers.....	131
layerSets.....	131
linkedLayers.....	131
name.....	131
opacity.....	131
parent.....	131
typename.....	131
visible.....	131
Methods.....	132
duplicate.....	132
link.....	132
merge.....	132
move.....	132
remove.....	132
resize.....	132
rotate.....	132
translate.....	132
unlink.....	132
LayerSets.....	133
Properties.....	133
length.....	133
parent.....	133
typename.....	133
Methods.....	133
add.....	133
getByName.....	133
removeAll.....	133
MeasurementLog.....	135
Methods.....	135
exportMeasurements.....	135
deleteMeasurements.....	135
MeasurementScale.....	136
Properties.....	136
pixelLength.....	136
logicalLength.....	136
logicalUnits.....	136
NoColor.....	137
Properties.....	137
typename.....	137
Notifier.....	138
Properties.....	138
event.....	138
eventClass.....	138
eventFile.....	138
parent.....	138
typename.....	138
Methods.....	138

remove.....	138
Notifiers.....	139
Properties.....	139
length.....	139
parent.....	139
typename	139
Methods	139
add	139
removeAll	139
PathItem	140
Properties.....	140
kind	140
name.....	140
parent.....	140
subPathItems	140
typename	140
Methods	140
deselect	140
duplicate	140
fillPath	140
makeClippingPath.....	141
makeSelection	141
remove.....	141
select	141
strokePath	141
PathItems	144
Properties.....	144
length.....	144
parent.....	144
typename	144
Methods	144
add	144
getByName	144
removeAll	144
PathPoint.....	145
Properties.....	145
anchor	145
kind	145
leftDirection.....	145
parent.....	145
rightDirection.....	145
typename	145
PathPointInfo	146
Properties.....	146
anchor	146
kind	146
leftDirection.....	146
rightDirection.....	146
typename	146
PathPoints	148
Properties.....	148

length.....	148
parent.....	148
typename	148
PDFOpenOptions	149
Properties.....	149
antiAlias.....	149
bitsPerChannel	149
constrainProportions	149
cropPage.....	149
height.....	149
mode.....	149
name.....	149
page.....	149
resolution.....	149
suppressWarnings	149
typename	149
usePageNumber	149
width	149
PDFSaveOptions	150
Properties.....	150
alphaChannels	150
annotations.....	150
colorConversion.....	150
convertToEightBit.....	150
description	150
destinationProfile	150
downgradeColorProfile	150
downSample	150
downSampleSize	150
downSampleSizeLimit	150
embedColorProfile.....	150
embedFonts	150
embedThumbnail.....	150
encoding.....	150
interpolation.....	150
jpegQuality	151
layers	151
optimizeForWeb	151
outputCondition	151
outputConditionID.....	151
PDFCompatibility.....	151
PDFStandard	151
preserveEditing	151
presetFile	151
profileInclusionPolicy.....	151
registryName.....	151
spotColors	151
tileSize.....	151
transparency.....	151
typename	151
useOutlines	151

vectorData.....	152
view.....	152
PhotoCDOpenOptions	153
Properties.....	153
colorProfileName	153
colorSpace.....	153
orientation.....	153
pixelSize	153
resolution.....	153
typename	153
PhotoshopSaveOptions.....	154
Properties.....	154
alphaChannels	154
annotations.....	154
embedColorProfile.....	154
layers	154
spotColors	154
typename	154
PICTFileSaveOptions	155
Properties.....	155
alphaChannels	155
compression	155
embedColorProfile.....	155
resolution.....	155
typename	155
PICTResourceSaveOptions.....	156
Properties.....	156
alphaChannels	156
compression	156
embedColorProfile.....	156
name.....	156
resolution.....	156
resourceID	156
typename	156
PicturePackageOptions.....	157
Properties.....	157
content	157
flatten.....	157
font.....	157
fontSize.....	157
layout	157
mode	157
opacity	157
resolution.....	157
text	157
textColor	157
textPosition.....	157
textRotate	157
typename	157
PixarSaveOptions	158
Properties.....	158

alphaChannels	158
typename	158
PNGSaveOptions	159
Properties.....	159
interlaced.....	159
typename	159
Preferences	160
Properties.....	160
additionalPluginFolder.....	160
appendExtension.....	160
askBeforeSavingLayeredTIFF.....	160
autoUpdateOpenDocuments	160
beepWhenDone.....	160
colorChannelsInColor	160
colorPicker.....	160
columnGutter.....	160
columnWidth	160
createFirstSnapshot.....	160
dynamicColorSliders.....	160
editLogItems	160
exportClipboard.....	161
fontPreviewSize.....	161
fullSizePreview.....	161
gamutWarningOpacity.....	161
gridSize	161
gridStyle	161
gridSubDivisions	161
guideStyle.....	161
iconPreview	161
imageCacheLevels	161
imagePreviews	161
interpolation.....	161
keyboardZoomResizesWindows.....	161
macOSThumbnail	161
maximizeCompatibility	161
maxRAMuse.....	161
nonLinearHistory	161
numberOfHistoryStates	162
otherCursors.....	162
paintingCursors.....	162
parent.....	162
pixelDoubling	162
pointSize	162
recentFileListLength.....	162
rulerUnits	162
saveLogItems	162
saveLogItemsFile	162
savePaletteLocations	162
showAsianTextOptions	162
showEnglishFontNames	162
showSliceNumber	162

showToolTips	162
smartQuotes	162
textFontSize	162
typename	162
typeUnits	163
useAdditionalPluginFolder	163
useHistoryLog	163
useLowerCaseExtension	163
useShiftKeyForToolSwitch	163
useVideoAlpha	163
windowsThumbnail	163
PresentationOptions	164
Properties	164
autoAdvance	164
includeFilename	164
interval	164
loop	164
magnification	164
PDFFileOptions	164
presentation	164
transition	164
typename	164
RawFormatOpenOptions	165
Properties	165
bitsPerChannel	165
byteOrder	165
channelNumber	165
headerSize	165
height	165
interleaveChannels	165
retainHeader	165
typename	165
width	165
RawSaveOptions	166
Properties	166
alphaChannels	166
spotColors	166
typename	166
RGBColor	167
Properties	167
blue	167
green	167
hexValue	167
red	167
typename	167
Selection	168
Properties	168
bounds	168
parent	168
solid	168
typename	168

Methods	168
clear	168
contract	168
copy	168
cut	168
deselect	168
expand	168
feather	168
fill	169
grow	169
invert	169
load	169
makeWorkPath	169
resize	169
resizeBoundary	169
rotate	169
rotateBoundary	169
select	169
selectAll	169
selectBorder	170
similar	170
smooth	170
store	170
stroke	170
translate	170
translateBoundary	170
SGIRGBSaveOptions	173
Properties	173
alphaChannels	173
spotColors	173
typename	173
SolidColor	174
Properties	174
cmyk	174
gray	174
hsb	174
lab	174
model	174
nearestWebColor	174
rgb	174
typename	174
Methods	174
isEqual	174
SubPathInfo	175
Properties	175
closed	175
entireSubPath	175
operation	175
typename	175
SubPathItem	176
Properties	176

closed	176
operation	176
parent	176
pathPoints	176
typename	176
SubPathItems	177
Properties	177
length	177
parent	177
typename	177
TargaSaveOptions	178
Properties	178
alphaChannels	178
resolution	178
rleCompression	178
typename	178
TextFont	179
Properties	179
family	179
name	179
parent	179
postScriptName	179
style	179
typename	179
TextFonts	180
Properties	180
length	180
parent	180
typename	180
Methods	180
getByName	180
TextItem	181
Properties	181
alternateLigatures	181
antiAliasMethod	181
autoKerning	181
autoLeadingAmount	181
baselineShift	181
capitalization	181
color	181
contents	181
desiredGlyphScaling	181
desiredLetterScaling	182
desiredWordScaling	182
direction	182
fauxBold	182
fauxItalic	182
firstLineIndent	182
font	182
hangingPunctuation	182
height	182

horizontalScale	182
hyphenateAfterFirst.....	183
hyphenateBeforeLast.....	183
hyphenateCapitalWords	183
hyphenateWordsLongerThan.....	183
hyphenation	183
hyphenationZone.....	183
hyphenLimit	183
justification	183
kind	183
language	183
leading	183
leftIndent	183
ligatures	183
maximumGlyphScaling	183
maximumLetterScaling	184
maximumWordScaling	184
minimumGlyphScaling.....	184
minimumLetterScaling.....	185
minimumWordScaling.....	185
noBreak	185
oldStyle.....	185
parent.....	185
position	185
rightIndent	185
size	185
spaceAfter	185
spaceBefore	186
strikeThru.....	186
textComposer	186
tracking.....	186
typename	186
underline.....	186
useAutoLeading.....	186
verticalScale.....	186
warpBend	186
warpDirection	186
warpHorizontalDistortion.....	186
warpStyle.....	186
warpVerticalDistortion.....	186
width	186
Methods	187
convertToShape.....	187
createPath	187
TiffSaveOptions.....	188
Properties.....	188
alphaChannels	188
annotations.....	188
byteOrder	188
embedColorProfile.....	188
imageCompression.....	188

interleaveChannels	188
jpegQuality	188
layerCompression	188
layers	188
saveImagePyramid	188
spotColors	188
transparency	188
typename	188
UnitValue	189
xmpMetadata	190
Properties	190
parent	190
rawData	190
typename	190
3 JavaScript Resource	191
JavaScript resource syntax	191
Basic JavaScript resource example	192
Enable-info grammar	192
Undefined values in enable-info evaluation	194
Using the "in" function	195
Action Manager automation	195
Terminology dictionary	195
Value type definitions	196
Uniqueness rules for terminology entries	197
Terminology definition example	197
4 Scripting Constants	199
AdjustmentReference	199
AnchorPosition	199
AntiAlias	199
AutoKernType	199
BatchDestinationType	199
BitmapConversionType	200
BitmapHalfToneType	200
BitsPerChannelType	200
BlendMode	200
BMPDepthType	200
ByteOrder	201
CameraRAWSettingsType	201
CameraRAWSize	201
ChangeMode	201
ChannelType	201
ColorBlendMode	202
ColorModel	202
ColorPicker	202
ColorProfileType	202
ColorReductionType	202
ColorSpaceType	202
CopyrightedType	202
CreateFields	203
CropToType	203

DCSType.....	203
DepthMapSource	203
DescValueType	203
DialogModes	203
Direction	203
DisplacementMapType	203
Dither	204
DocPositionStyle.....	204
DocumentFill.....	204
DocumentMode.....	204
EditLogItemsType.....	204
ElementPlacement.....	204
EliminateFields	204
ExportType	204
Extension	204
FileNamingType.....	205
FontPreviewType.....	205
FontSize.....	205
ForcedColors	205
FormatOptions	205
GalleryConstrainType.....	205
GalleryFontType.....	206
GallerySecurityTextColorType	206
GallerySecurityTextPositionType	206
GallerySecurityTextRotateType	206
GallerySecurityType	206
GalleryThumbSizeType.....	206
Geometry.....	206
GridLineStyle	206
GridSize	206
GuideLineStyle.....	207
IllustratorPathType.....	207
Intent.....	207
Justification	207
Language.....	207
LayerCompression.....	207
LayerKind.....	208
LensType.....	208
MagnificationType	208
MatteType	208
MeasurementRange	208
MeasurementSource	208
NewDocumentMode.....	208
NoiseDistribution.....	209
OffsetUndefinedAreas	209
OpenDocumentMode.....	209
OpenDocumentType.....	209
OperatingSystem.....	209
Orientation.....	209
OtherPaintingCursors	210
PaintingCursors	210

PaletteType	210
PathKind	210
PDFCompatibility	210
PDFEncoding	210
PDFResample	211
PDFStandard	211
PhotoCDColorSpace	211
PhotoCDSIZE	211
PICTBitsPerPixels	211
PICTCompression	211
PicturePackageTextType	211
PointKind	212
PointType	212
PolarConversionType	212
Preview	212
PrintColorHandling	212
PurgeTarget	212
QueryStateType	212
RadialBlurMethod	212
RadialBlurQuality	212
RasterizeType	212
ReferenceFormType	212
ResampleMethod	213
RippleSize	213
SaveBehavior	213
SaveDocumentType	213
SaveEncoding	213
SaveLogItemsType	213
SaveOptions	213
SelectionType	214
ShapeOperation	214
SmartBlurMode	214
SmartBlurQuality	214
SourceSpaceType	214
SpherizeMode	214
StrikeThruType	214
StrokeLocation	214
TargaBitsPerPixels	214
TextCase	215
TextComposer	215
TextType	215
TextureType	215
TIFFEncoding	215
ToolType	215
TransitionType	215
TrimType	216
TypeUnits	216
UndefinedAreas	216
UnderlineType	216
Units	216
Urgency	216

WarpStyle	216
WaveType	217
WhiteBalanceType.....	217
ZigZagType	217
Appendix A: Event ID Codes	218
Index	226

This reference describes the objects and methods in the Adobe® Photoshop® CS5® JavaScript™ type library. A companion document, *Photoshop CS5 Scripting Guide*, describes basic scripting concepts and the Photoshop object model. This document provides reference details of the Photoshop object model, and additional information on JavaScript-specific features.

Adobe Photoshop CS5 uses ExtendScript, Adobe's extended implementation of JavaScript. See [JavaScript support in Adobe Photoshop CS5](#) for additional information.

This book contains the following sections:

- This introduction, which describes scripting support in Adobe Photoshop CS5, and lists changes to the JavaScript interface since the previous release.
- [JavaScript Object Reference](#), which provides a complete reference for all Photoshop DOM objects and commands.
- [Scripting Constants](#), which lists all enumerations used in the Photoshop type library.

JavaScript support in Adobe Photoshop CS5

For a JavaScript file to be recognized by Photoshop as a valid script file, it must use either a `.js` or a `.jsx` extension.

On the Mac OS, there is no difference in the way scripts with the two extensions function. On Windows, if the script files is opened from inside Photoshop, there is no difference between using the `.js` and `.jsx` extension. However, if the script is launched by double-clicking on it, a script with the `.js` extension is interpreted with the Microsoft JScript engine, and it cannot launch Adobe Photoshop CS5. For Windows, using the `.jsx` extension is preferable, since it interprets the script with the ExtendScript engine.

All of the Adobe Creative Suite 5 applications, including Adobe Photoshop CS5, use ExtendScript, Adobe's extended implementation of JavaScript. ExtendScript files are distinguished by the `.jsx` extension. ExtendScript offers all standard JavaScript features, plus additional features and utilities, such as:

- A debugging environment (the ExtendScript Toolkit)
- A localization utility
- Tools that allow you to combine scripts and direct them to particular applications
- Platform-independent file and folder representation

Many of the JavaScript objects and methods use objects defined in ExtendScript, such as the `File` object, the `Folder` object, and the `UnitValue` object. For that reason, using the `.jsx` extension for your script files is preferable.

For details of these and additional features, see the *JavaScript Tools Guide CS5*. This document is installed with Creative Suite 5 applications at these locations:

- In Windows:
C:\Program Files\Adobe\Adobe Utilities\ExtendScript Toolkit CS5\SDK

- In Mac OS:

Applications/Utilities/Adobe Utilities/ExtendScript Toolkit CS5/SDK

The latest versions of this document and of the ExtendScript Toolkit, can also be downloaded from Adobe Developer Center, <http://www.adobe.com/devnet/>.

Executing scripts

The Adobe Photoshop CS5 interface includes a Scripts menu (**File > Scripts**) which provides quick and easy access to your JavaScripts. Scripts can be listed directly as menu items that run when you select them, or you can navigate to and run any JavaScript in your file system.

If Adobe Photoshop CS5 encounters an error during script execution, it displays the error message.

Installing scripts

To install a JavaScript in the Scripts menu, place it in the Scripts folder (**Photoshop CS5/Presets/Scripts**). The names of the scripts in the Scripts folder, without the file name extension, will be displayed in the Scripts menu. Any number of scripts may be installed in the Scripts menu.

Scripts added to the Scripts folder while Adobe Photoshop CS5 is running will not appear in the Scripts menu until the next time you launch the application.

All scripts found in the Scripts folder and sub-folders are displayed at the top level of the **File > Scripts** menu. The addition of sub-folders does not add a hierarchical organization to the Scripts menu.

Executing other scripts

The **Browse** item at the end of the **Scripts** menu (**File > Scripts > Browse**) allows you to execute scripts which are not installed in the Scripts folder. You can also use Browse to select scripts installed in the Scripts folder after the application was last launched.

Selecting **Browse** displays a file browser dialog which allows you to select a script file for execution. Only `.js` or `.jsx` files are displayed in the browse dialog. When you select a script file, it is executed the same way as an installed script.

Startup scripts

On startup, Adobe Photoshop CS5 executes all `.jsx` files that it finds in the startup folders.

- On Windows, the startup folder for user-defined scripts is:

C:\Program Files\Common Files\Adobe\Startup Scripts CS5\Adobe Photoshop

- On Mac OS, the startup folder for user-defined scripts is:

~/Library/Application Support/Adobe/Startup Scripts CS5/Adobe Photoshop

If a script is meant to be executed only by Adobe Photoshop CS5, it must include code such as the following:

```
if ( BridgeTalk.appName == "photoshop" ) {  
    //continue executing script  
}
```

For additional details, see the *JavaScript Tools Guide CS5*.

Object model usage and naming

The JavaScript API follows JavaScript naming conventions in that all classes (object types) begin with uppercase letters and have mixed case. Typically, in JavaScript, you instantiate classes using the `new` operator:

```
new ClassName();
```

However, in the Photoshop Object Model, it is often not necessary to do this. Major object types are collected into collection classes; for example, a list of `Document` objects is contained in a `Documents` collection object. You then access the collection object through a corresponding collection property in its container in the object hierarchy.

For example, the collection of all open documents is contained in the top-level `Application` object. You can access this through the global variable `app`, or simply reference its properties directly at the top level:

```
app.documents[0] // get the first loaded document
documents[0] // this is the same
```

A collection property has the same name as the collection object, but begins with lowercase. For example, a `Document` contains a collection of `LayerSets`, and a `LayerSet` contains a collection of `ArtLayers`. To access one `ArtLayer` object in a set:

```
var myLayer = activeDocument.layerSets[0].artLayers[0];
```

The collections, as in this example, can be treated as arrays, which is useful for iteration. They also provide methods to create their contained objects, and to access them by name:

```
var newLayer = activeDocument.artLayers.add(); // Create a new ArtLayer object
newLayer.name = "My Layer"; // name it for later reference
...
var layerRef = activeDocument.artLayers.getByName("My Layer");
```

Some objects, such as the `Font` objects contained in the `app.fonts` collection, are created by the application, and never by your scripts.

Your scripts do use the JavaScript `new` operator to create helper objects, such as those that encapsulate a set of options for opening or saving a document in a particular format:

```
var opts = new PDFOpenOptions();
opts.page = 10;
app.open(myPDFFile, opts);
```

Changes since earlier versions—CS5 changes

The following changes have been made to the JavaScript object model and language support in Adobe Photoshop CS5:

We have made major changes around printing a document. After making such sweeping changes, your printing scripts may not work in CS5. The new printing interface makes maintaining backwards compatibility an issue and scripts will need to be updated for the new printing interface. See the [DocumentPrintSettings](#) object.

- New methods and properties:
 - `guides` collection of type `Guides` has been added to the `Document` object.
 - `refreshFonts` method has been added to the `Application` object.
 - `isQuicktimeAvailable` method has been added to the `Application` object.

- `showColorPicker` method has been added to the `Application` object.
- `fontSize` property has been added to the `Preferences` object.
- New enumerations:
 - `FontSize` has been added for the `Preferences` object.
- Modified enumerations:
 - `SUBTRACT` and `DIVIDE` has been added to the `BlendMode` enumeration.
 - `SUBTRACT` and `DIVIDE` has been added to the `ColorBlendMode` enumeration.

The Photoshop objects (the JavaScript type library for Adobe® Photoshop® CS5) are presented alphabetically and in tabular format in this chapter. Sample code for several object model classes is given to help illustrate the syntax as well as usage of the object class.

Object descriptions

Object properties and methods are described in separate tables for each object. The following sections describe the conventions used in these descriptions.

Properties notation

The Properties table for an object lists the following:

- The properties defined in each object.
- The value type for each property.

When the value type is a constant or another object, the value is a hypertext link to the listing for that constant or object.

- The property's input status: read-only or read-write.
- A description that explains what the property does.

Property	Value type	What it is
<code>displayDialogs</code>	DialogModes	Read-write. The dialog mode for the application, which controls what types of dialogs should be displayed when running scripts.

For constants, like [DialogModes](#) in the sample, click the link to go to the table that shows allowed values. Constants are represented by objects, and allowed values are properties of those objects. Specify a constant value in the form *ConstantName.VALUE*. For example:

```
app.displayDialogs = DialogModes.ERROR;
```

Methods notation

The Methods table for an object lists the following:

- The method name.
- The parameters list.
- The parameter value types, on lines corresponding to each parameter.
- Return value type
- A description of what the method does, and further descriptions of parameters, if needed.

Method	Parameter type	Returns	What it does
crop (bounds [, angle] [, width] [, height])	array of 4 UnitValue number UnitValue UnitValue		Crops the document. The <code>bounds</code> parameter is an array of four coordinates for the region remaining after cropping, [left, top, right, bottom].

When a parameter type or return value is a constant or another object, the value is a hypertext link to the listing for that constant or object.

Parameters can be required or optional. Optional parameters are indicated in the table by square brackets ([]). In the example, the first parameter, *bounds*, is required. The remaining parameters are all optional.

You must pass a value for each required parameter. You can leave out optional parameters if there are no remaining values to pass; however, if you wish to use the default value for any optional parameter that is not the last one specified, pass `undefined` as a placeholder. You must enter the values in the order they are listed, so that the JavaScript compiler knows which value you are entering.

For example, the following passes only the required parameter (using a previously-defined variable for the bounding region):

```
app.activeDocument.crop( myRegion );
```

The following skips the *angle* parameter, specifies the *width* value, and omits the final *height* value:

```
var myWidth = new UnitValue( "500 pixels" );  
app.executeAction( myRegion, undefined, myWidth );
```

ActionDescriptor

This object provides a dictionary-style mechanism for storing data as key-value pairs. It can be used for low-level access into Photoshop. See an example of this usage in [‘Selection sample script’ on page 170](#).

Many configuration files use serialized action descriptors to represent their data. It is used, for example, to encapsulate playback options in [Application.playbackParameters](#), and is returned by [Application.getCustomOptions\(\)](#).

Properties

Property	Value type	What it is
count	number	Read-only. The number of keys contained in the descriptor.
typename	string	Read-only. The class name of the referenced <code>actionDescriptor</code> object.

Methods

Method	Parameter type	Returns	What it does
clear ()			Clears the descriptor.
erase (key)	number		Erases a key from the descriptor.
fromStream (value)	string		Creates a descriptor from a stream of bytes; for reading from disk.
getBoolean (key)	number	boolean	Gets the value of a key of type boolean.
getClass (key)	number	number	Gets the value of a key of type class.
getData (key)	number	string	Gets raw byte data as a string value.
getDouble (key)	number	number	Gets the value of a key of type double.
getEnumerationType (key)	number	number	Gets the enumeration type of a key.
getEnumerationValue (key)	number	number	Gets the enumeration value of a key.
getInteger (key)	number	number	Gets the value of a key of type integer.
getKey (index)	number	number	Gets the ID of the <i>N</i> th key, provided by index.

Method	Parameter type	Returns	What it does (Continued)
getList (key)	number	ActionList	Gets the value of a key of type list.
getObjectType (key)	number	number	Gets the class ID of an object in a key of type object.
getObjectValue (key)	number	ActionDescriptor	Gets the value of a key of type object.
getPath (key)	number	File	Gets the value of a key of type File.
getReference (key)	number	ActionReference	Gets the value of a key of type ActionReference .
getString (key)	number	string	Gets the value of a key of type string.
getType (key)	number	DescValueType	Gets the type of a key.
getUnitDoubleType (key)	number	number	Gets the unit type of a key of type UnitDouble.
getUnitDoubleValue (key)	number	number	Gets the value of a key of type UnitDouble.
hasKey (key)	number	boolean	Checks whether the descriptor contains the provided key.
isEqual (otherDesc)	ActionDescriptor	boolean	Determines whether the descriptor is the same as another descriptor.
putBoolean (key, value)	number boolean		Sets the value for a key whose type is boolean.
putClass (key, value)	number number		Sets the value for a key whose type is class.
putData (key, value)	number string		Puts raw byte data as a string value.
putDouble (key, value)	number number		Sets the value for a key whose type is double.
putEnumerated (key, enumType, value)	number number number		Sets the enumeration type and value for a key.
putInteger (key, value)	number number		Sets the value for a key whose type is integer.

Method	Parameter type	Returns	What it does (Continued)
putList (key, value)	number ActionList		Sets the value for a key whose type is an <code>ActionList</code> object.
putObject (key, classID, value)	number number ActionDescriptor		Sets the value for a key whose type is an object, represented by an Action Descriptor.
putPath (key, value)	number File		Sets the value for a key whose type is path.
putReference (key, value)	number ActionReference		Sets the value for a key whose type is an object reference.
putString (key, value)	number string		Sets the value for a key whose type is string.
putUnitDouble (key, unitID, value)	number number number		Sets the value for a key whose type is a unit value formatted as a double.
toStream ()		string	Gets the entire descriptor as a stream of bytes, for writing to disk.

ActionList

This object provides an array-style mechanism for storing data. It can be used for low-level access into Photoshop.

This object is ideal when storing data of the same type. All items in the list must be of the same type.

You can use the "put" methods, such as [putBoolean\(\)](#), to append new elements, and can clear the entire list using [clear\(\)](#), but cannot otherwise modify the list.

Note: The `ActionList` object is part of the Action Manager functionality. For details on using the Action Manager, see the *Photoshop CS5 Scripting Guide*.

Properties

Property	Value type	What it is
count	number	Read-only. The number of commands that comprise the action.
typename	string	Read-only. The class name of the referenced <code>ActionList</code> object.

Methods

With the exception of the `clear()` method, you use the methods of this object to either get the value of a specific type of data in the list or set (put) the value type.

Method	Parameter type	Returns	What it does
clear ()			Clears the list.
getBoolean (index)	number	boolean	Gets the value of a list element of type boolean.
getClass (index)	number	number	Gets the value of a list element of type class.
getData (index)	number	string	Gets raw byte data as a string value.
getDouble (index)	number	number	Gets the value of a list element of type double.
getEnumerationType (index)	number	number	Gets the enumeration type of a list element.
getEnumerationValue (index)	number	number	Gets the enumeration value of a list element.
getInteger (index)	number	number	Gets the value of a list element of type integer.

Method	Parameter type	Returns	What it does (Continued)
getList (index)	number	ActionList	Gets the value of a list element of type list.
getObjectType (index)	number	number	Gets the class ID of a list element of type object.
getObjectValue (index)	number	ActionDescriptor	Gets the value of a list element of type object.
getPath (index)	number	File	Gets the value of a list element of type File.
getReference (index)	number	ActionReference	Gets the value of a list element of type ActionReference .
getString (index)	number	string	Gets the value of a list element of type string.
getType (index)	number	DescValueType	Gets the type of a list element.
getUnitDoubleType (index)	number	number	Gets the unit value type of a list element of type Double.
getUnitDoubleValue (index)	number	number	Gets the unit value of a list element of type double.
putBoolean (value)	boolean		Appends a new value, true or false.
putClass (value)	number		Appends a new value, a class or data type.
putData (value)	string		Appends a new value, a string containing raw byte data.
putDouble (value)	number		Appends a new value, a double.
putEnumerated (enumType, value)	number number		Appends a new value, an enumerated (constant) value.
putInteger (value)	number		Appends a new value, an integer.
putList (value)	ActionList		Appends a new value, a nested action list.
putObject (classID, value)	number ActionDescriptor		Appends a new value, an object.
putPath (value)	File		Appends a new value, a path.
putReference (value)	ActionReference		Appends a new value, a reference to an object created in the script.

Method	Parameter type	Returns	What it does (Continued)
putString (value)	string		Appends a new value, a string.
putUnitDouble (classID, value)	number number		Appends a new value, a unit/value pair.

ActionReference

This object provides information about what the action is referring to. For example, when referring to the name of something you might use `keyName`. The reference would also need to know what name you are referring to. In this case you could use `classDocument` for the name of the document or `classLayer` for the name of the layer. It can be used for low-level access into `Photoshop`. Contains data associated with an [ActionDescriptor](#).

Properties

Property	Value type	What it does
typename	string	Read-only. The class name of the referenced Action object.

Methods

Method	Parameter type	Returns	What it does
getContainer ()		ActionReference	Gets a reference contained in this reference. Container references provide additional pieces to the reference. This looks like another reference, but it is actually part of the same reference.
getDesiredClass ()		number	Gets a number representing the class of the object.
getEnumeratedType ()		number	Gets the enumeration type.
getEnumeratedValue ()		number	Gets the enumeration value.
getForm ()		ReferenceFormType	Gets the form of this action reference.
getIdentifier ()		number	Gets the identifier value for a reference whose form is identifier.
getIndex ()		number	Gets the index value for a reference in a list or array.
getName ()		string	Gets the name of a reference.
getOffset ()		number	Gets the offset of the object's index value.
getProperty ()		number	Gets the property ID value.

Method	Parameter type	Returns	What it does (Continued)
putClass (desiredClass)	number		Puts a new class form and class type into the reference.
putEnumerated (desiredClass, enumType, value)	number number number		Puts an enumeration type and ID into a reference along with the desired class for the reference.
putIdentifier (desiredClass, value)	number number		Puts a new identifier and value into the reference.
putIndex (desiredClass, value)	number number		Puts a new index and value into the reference.
putName (desiredClass, value)	number string		Puts a new name and value into the reference.
putOffset (desiredClass, value)	number number		Puts a new offset and value into the reference.
putProperty (desiredClass, value)	number number		Puts a new property and value into the reference.

Application

The Adobe Adobe Photoshop CS5 application object, which is the root of the object model and provides access to all other objects. This object provides application-wide information, such as application defaults and available fonts. It provides many important methods, such as those for opening files and loading documents.

To access the properties and methods, you can use the pre-defined global variable `app`. For example:

```
var docRef = app.documents.add(800, 600, 72, "docRef", NewDocumentMode.RGB);
```

The properties and methods of the `Application` object are also available at the top level; you can omit references to the `Application` object altogether. For example:

```
var docRef = documents.add(800, 600, 72, "docRef", NewDocumentMode.RGB);
```

This usage can be somewhat ambiguous; for clarity, it is recommended that you use an explicit reference to `app`.

Properties

Property	Value type	What it is
activeDocument	Document	Read-write. The frontmost document. Setting this property is equivalent to clicking an open document in the Adobe Photoshop CS5 application to bring it to the front of the screen. Tip: If there is no open document, accessing this property throws an exception.
backgroundColor	SolidColor	Read-write. The default background color and color style for documents.
build	string	Read-only. Information about the application.
colorSettings	string	Read-write. The name of the current color settings, as selected with Edit > Color Settings.
displayDialogs	DialogModes	Read-write. The dialog mode for the application, which controls what types of dialogs should be displayed when running scripts.
documents	Documents	Read-only. The collection of open documents. This is the primary point of access for documents that are currently open in the application. The array allows you to access any open document, or to iterate through all open documents.
fonts	TextFonts	Read-only. The fonts installed on this system.
foregroundColor	SolidColor	Read-write. The default foreground color (used to paint, fill, and stroke selections).
freeMemory	number	Read-only. The amount of unused memory available to Adobe Photoshop CS5.

Property	Value type	What it is (Continued)
locale	string	Read-only. The language location of the application. An Adobe locale code consists of a 2-letter ISO-639 language code and an optional 2-letter ISO 3166 country code separated by an underscore. Case is significant. For example, en_US, en_UK, ja_JP, de_DE, fr_FR.
macintoshFileTypes	array of string	Read-only. A list of file image types Adobe Photoshop CS5 can open.
measurementLog	MeasurementLog	The log of measurements taken.
name	string	Read-only. The application's name.
notifiers	Notifiers	Read-only. The collection of notifiers currently configured (in the Scripts Events Manager menu in the Adobe Photoshop CS5 application).
notifiersEnabled	boolean	Read-write. True if all notifiers are enabled.
path	File	Read-only. The full path to the location of the Adobe Photoshop CS5 application.
playbackDisplayDialogs	DialogModes	Read-write. The dialog mode for playback mode, which controls what types of dialog to display when playing back a recorded action with the Actions palette.
playbackParameters	ActionDescriptor	Read-write. Stores and retrieves parameters used as part of a recorded action. Can be used, for example, to control playback speed.
preferences	Preferences	Read-only. The application preference settings (equivalent to selecting Edit > Preferences in the Adobe Photoshop CS5 application in Windows or Photoshop > Preferences in Mac OS).
preferencesFolder	File	Read-only. The full path to the Preferences folder.
recentFiles	array of File	Read-only. Files in the Recent Files list.
scriptingBuildDate	string	Read-only. The build date of the Scripting interface.
scriptingVersion	string	Read-only. The version of the Scripting interface.
systemInformation	string	Read-only. Runtime details of the application and system.
typename	string	Read-only. The class name of the referenced app object.

Property	Value type	What it is (Continued)
version	string	Read-only. The version of Adobe Photoshop application you are running.
windowsFileTypes	array of string	Read-only. A list of file image extensions Adobe Photoshop CS5 can open.

Methods

Method	Parameter type	Returns	What it does
batch (inputFiles, action, from [, options])	array of File string string BatchOptions	string	Runs the batch automation routine (similar to the File > Automate > Batch command). The <code>inputFiles</code> parameter specifies the sources for the files to be manipulated by the batch command.
beep ()			Causes a "beep" sound.
bringToFront ()			Makes Adobe Photoshop CS5 the active (front-most) application.
charIDToTypeID (charID)	string	number	Converts from a four character code (character ID) to a runtime ID.
doAction (action, from)	string string		Plays an action from the Actions palette. The <code>action</code> parameter is the name of the action, the <code>from</code> parameter is the name of the action set.
eraseCustomOptions (key)	string		Erases the user object with specified ID value from the Photoshop registry.
executeAction (eventID [, descriptor] [, displayDialogs])	number ActionDescriptor DialogModes	ActionDescriptor	Plays an Action Manager event.
executeActionGet (reference)	ActionReference	ActionDescriptor	Obtains information about a predefined or recorded action.
featureEnabled (name)	string	boolean	Determines whether the feature specified by <code>name</code> is enabled. The following features are supported as values for <code>name</code> : "photoshop/extended" "photoshop/standard" "photoshop/trial"

Method	Parameter type	Returns	What it does (Continued)
getCustomOptions (key)	string	ActionDescriptor	Retreives user objects in the Photoshop registry for the ID with value key.
isQuicktimeAvailable ()		boolean	Returns true if Quicktime is installed.
load (document)	File		Loads a support file (as opposed to a Photoshop image document) from the specified location.
makeContactSheet (inputFiles [, options])	array of File ContactSheetOptions	string	DEPRECATED for Adobe Photoshop CS4.
makePDFPresentation (inputFiles, outputFiles [, options])	array of File File PresentationOptions	string	DEPRECATED for Adobe Photoshop CS4.
makePhotoGallery (inputFolder, outputFolder [, options])	File File GalleryOptions	string	DEPRECATED for Adobe Photoshop CS4.
makePhotomerge (inputFiles)	array of File	string	DEPRECATED for Adobe Photoshop CS5. Use provided script: <pre>runphotomergeFromScript = true; \$.evalFile(app.path + "Presets/Scripts/Photomerge.jsx") photomerge.createPanorama(fileList, displayDialog);</pre> Merges multiple files into one, with user interaction required.
makePicturePackage (inputFiles [, options])	array of File PicturePackageOptions	string	DEPRECATED for Adobe Photoshop CS4.

Method	Parameter type	Returns	What it does (Continued)
open (document [, as] [, asSmartObject])	File object or OpenDocumentType boolean	Document	<p>Opens the specified document.</p> <p>Use the optional <code>as</code> parameter to specify the file format using the constants in OpenDocumentType; or, you can specify a file format together with its open options using these objects:</p> <p> CameraRAWOpenOptions DICOMOpenOptions EPSOpenOptions PDFOpenOptions PhotoCDOpenOptions RawFormatOpenOptions </p> <p>Use the optional parameter <code>asSmartObject</code> (default: <code>false</code>) to create a smart object around the opened document.</p> <p>See the Application sample scripts for an example of using the File object in the <code>open</code> method.</p>
openDialog ()		array of File	<p>Invokes the Photoshop Open dialog box for the user to select files.</p> <p>Returns an array of File objects for the files selected in the dialog.</p>
purge (target)	PurgeTarget		Purges one or more caches.
putCustomOptions (key, customObject [, persistent])	string ActionDescriptor boolean		<p>Saves a customized settings object in the Photoshop registry.</p> <p><code>key</code> is the unique identifier for your custom settings.</p> <p><code>customObject</code> is the object to save in the registry.</p> <p><code>persistent</code> indicates whether the object should persist once the script has finished.</p>
refresh ()			Pauses the script while the application refreshes. Use to slow down execution and show the results to the user as the script runs. Use carefully; your script runs much more slowly when using this method.
refreshFonts ()			Force the font list to get updated.
runMenuItem (menuID)	number		Run a menu item given the menu ID.

Method	Parameter type	Returns	What it does (Continued)
showColorPicker ()		boolean	Returns false if dialog is cancelled, true otherwise.
stringIDToTypeID (stringID)	string	number	Converts from a string ID to a runtime ID.
togglePalettes ()			Toggle palette visibility.
TypeIDToCharID (TypeID)	number	string	Converts from a runtime ID to a character ID.
TypeIDToStringID (TypeID)	number	string	Converts from a runtime ID to a string ID.

Application sample scripts

Application.jsx

This script invokes an alert box to display Properties important to an application such as version number, the path to the application, the amount of memory available, and the number of documents open.

When a user presses the OK button on the alert box, a second dialog opens, which asks users whether they would like the foreground and background colors set for the document presently open. If no document is open, the script opens a new document for the user.

The script (with no document open) produces a progression of three dialogs.

```
//Create a Welcome message
// Use the name and version properties of the application object to
// Append the application's name and version to the Welcome message
// use "\r" to insert a carriage return
// use the combination operator += to append info to the message
var message = "Welcome to " + app.name
message += " version " + app.version + "\r\r"

// find out where Adobe Photoshop CS5 is installed
// and add the path to the message
// add the optional parameter fsName to the path property
// to display the file system name in the most common format
message += "I'm installed in " + app.path.fsName + "\r\r"

// see how much memory Adobe Photoshop CS5 has to play with
message += "You have this much memory available for Adobe Photoshop CS5: " +
app.freeMemory + "\r\r"

// use the length property of the documents object to
// see how many documents are open
var documentsOpen = app.documents.length
message += "You currently have " + documentsOpen + " document(s) open.\r\r"

// display the message to the user
alert(message)

// answer will be true for a "Yes" answer and false for a "No" answer
var answer = confirm("Set the foreground and background to my favorite colors?")
```

```
// set the colors
if (answer) {
    // I don't have a favorite color. Why did I ask you may wonder?
    app.foregroundColor.rgb.red = Math.random() * 255
    app.foregroundColor.rgb.green = Math.random() * 255
    app.foregroundColor.rgb.blue = Math.random() * 255
    app.backgroundColor.rgb.red = Math.random() * 255
    app.backgroundColor.rgb.green = Math.random() * 255
    app.backgroundColor.rgb.blue = Math.random() * 255
}

// Open a document
if (app.documents.length == 0) {

    // use the application's path and the offset to the samples folder
    var sampleDocToOpen = File(app.path + "/Samples/Fish.psd")

    // compose a message with the name of the file
    message = "Would you like me to open a sample for you? ("
    message += sampleDocToOpen.fsName
    message += ")"

    // ask the user another question
    answer = confirm(message)

    // open the document accordingly
    if (answer) {
        open(sampleDocToOpen)
    }
}
```

PDFPresentation.jsx

This script presents a progression of images as an Adobe PDF slide show.

```
// use all the files in the Samples folder
var inputFolder = new Folder(app.path + "/Samples/")

// see if we have something interesting
if (inputFolder != null) {

    // get all the files found in this folder that are Adobe Photoshop CS5 (.psd
    format)
    var inputFiles = inputFolder.GetFiles("*.psd")

    // output to the desktop
    var outputFile = File("~/Desktop/JavaScriptPresentation.pdf")

    // there are defaults but I like to set the options myself
    var options = new PresentationOptions
    options.presentation = true
    options.view = true
    options.autoAdvance = true
    options.interval = 5
    options.loop = true
    options.transition = TransitionType.RANDOM

    // create the presentation
    makePDFPresentation(inputFiles, outputFile, options)
```

```
alert("Presentation file saved to: " + outputFile.fsName)
}
```

ArtLayer

An object within a document that contains the visual elements of the image (equivalent to a layer in the Adobe Photoshop CS5 application).

Access an art layer in a document through the [Document.artLayers](#) collection. You can access a layer by name; for example:

```
var layerRef = app.activeDocument.artLayers.getBy_name("my layer");
layerRef.allLocked = true;
```

Access the art layers in a layer set through the [LayerSet.artLayers](#) collection in the parent set.

Properties

Property	Value type	What it is
allLocked	boolean	Read-write. True to completely lock the contents and settings of this layer.
blendMode	BlendMode	Read-write. The blending mode.
bounds	array of UnitValue	Read-only. An array of coordinates that describes the bounding rectangle of the layer.
fillOpacity	number [0.0..100]	Read-write. The interior opacity of the layer, a percentage value.
filterMaskDensity	double	Read-write. The density of the filter mask (between 0.0 and 250.0)
filterMaskFeather	double	Read-write. The feather of the filter mask (between 0.0 and 250.0)
grouped	boolean	Read-write. True if this layer is grouped with the layer beneath it.
isBackgroundLayer	boolean	Read-write. True if this is the background layer of the document. A document can have only one background layer. If there is no background layer, setting this to true causes this to become the background layer.
kind	LayerKind	Read-write. Sets the type (such as 'text layer') for an empty layer. Valid only when the layer is empty and when <code>isBackgroundLayer</code> is false. See isBackgroundLayer . You can use the <code>kind</code> property to make a background layer a normal layer; however, to make a layer a background layer, you must set <code>isBackgroundLayer</code> to true.
layerMaskDensity	double	Read-write. The density of the layer mask (between 0.0 and 100.0)

Property	Value type	What it is (Continued)
layerMaskFeather	double	Read-write. The feather of the layer mask (between 0.0 and 250.0)
linkedLayers	array of ArtLayer or LayerSet	Read-only. The layers linked to this layer. See ArtLayer.link .
name	string	Read-write. The name.
opacity	number [0.0..100.0].	Read-write. The master opacity of the layer, a percentage value.
parent	Document	Read-only. The object's container.
pixelsLocked	boolean	Read-write. True if the pixels in the layer's image cannot be edited using the paintbrush tool.
positionLocked	boolean	Read-write. True if the pixels in the layer's image cannot be moved within the layer.
textItem	TextItem	Read-only. The text item that is associated with the layer. Valid only when kind = <code>LayerKind.TEXT</code> .
transparentPixelsLocked	boolean	Read-write. True if editing is confined to the opaque portions of the layer.
typename	string	Read-only. The class name of the referenced <code>artLayer</code> object.
vectorMaskDensity	double	Read-write. The density of the vector mask (between 0.0 and 250.0)
vectorMaskFeather	double	Read-write. The feather of the vector mask (between 0.0 and 250.0)
visible	boolean	Read-write. True if the layer is visible.
xmpMetadata	xmpMetadata	Read-write. Metadata for the layer.

Methods

Method	Parameter type	Returns	What it does
adjustBrightnessContrast (brightness, contrast)	number number		Adjusts the brightness in the range [-100..100] and contrast [-100..100].
adjustColorBalance ([shadows] [, midtones] [, highlights] [, preserveLuminosity])	array of number array of number array of number boolean		Adjusts the color balance of the layer's component channels. For shadows, midtones, and highlights, the array must include three values in the range [-100..100], which represent cyan or red, magenta or green, and yellow or blue, when the document mode is CMYK or RGB. See Document.mode .
adjustCurves (curveShape)	array of array of number		Adjusts the tonal range of the selected channel using up to fourteen points. Each value in the <code>curveShape</code> array is a point pair, an array of an x and y integer value.
adjustLevels (inputRangeStart, inputRangeEnd, inputRangeGamma, outputRangeStart, outputRangeEnd)	number [0..253] number [(start + 2)..255] number [0.10..9.99] number [0..253] number [(start + 2)..255]		Adjusts the levels of the selected channels
applyAddNoise (amount, distribution, monochromatic)	number [0.1..400] NoiseDistribution boolean		Applies the Add Noise filter amount is a percentage value.
applyAverage ()			Applies the Average filter.
applyBlur ()			Applies the Blur filter.
applyBlurMore ()			Applies the Blur More filter.
applyClouds ()			Applies the Clouds filter.
applyCustomFilter (characteristics, scale, offset)	array of number number number		Applies a custom filter. The <code>characteristics</code> array has 25 members. See Adobe Photoshop CS5 Help for specific instructions.

Method	Parameter type	Returns	What it does (Continued)
applyDeInterlace (eliminateFields, createFields)	EliminateFields CreateFields		Applies the De-Interlace filter.
applyDespeckle ()			Applies the Despeckle filter.
applyDifferenceClouds ()			Applies the Difference Clouds filter.
applyDiffuseGlow (graininess, glowAmount, clearAmount)	number [0..10] number [0..20] number [0..20]		Applies the Diffuse Glow filter.
applyDisplace (horizontalScale, verticalScale, displacement, undefinedareas, displacementMapFiles)	number [-999..999] number [-999..999] DisplacementMapType UndefinedAreas File		Applies the Displace filter using the specified horizontal and vertical scale, mapping type, treatment of undistorted areas, and path to the distortion image map.
applyDustAndScratches (radius, threshold)	number [1..100] number [0..255]		Applies the Dust & Scratches filter.
applyGaussianBlur (radius)	number [0.1..250.0]		Applies the Gaussian Blur filter within the specified radius (in pixels)
applyGlassEffect (distortion, smoothness, scaling [, invert] [, texture] [, textureFile])	number [0..20] number [1..15] number [50..200] boolean TextureType File		Applies the Glass filter. scaling is a percentage value.
applyHighPass (radius)	number [0.1..250.0]		Applies the High Pass filter within the specified radius.

Method	Parameter type	Returns	What it does (Continued)
applyLensBlur ([source] [, focalDistance] [, invertDepthMap] [, shape] [, radius] [, bladeCurvature] [, rotation] [, brightness] [, threshold] [, amount] [, distribution] [, monochromatic])	DepthMapSource number boolean Geometry number number number number NoiseDistribution boolean		<p>Applies the Lens Blur filter.</p> <p>source: The source for the depth map (default: <code>DepthMapSource.NONE</code>)</p> <p>focalDistance : The blur focal distance for the depth map (default: 0).</p> <p>invertDepthMask : True if the depth map is inverted (default: false).</p> <p>shape: The shape of the iris (default: <code>Geometry.HEXAGON</code>)</p> <p>radius: The radius of the iris (default: 15).</p> <p>bladeCurvature: The blade curvature of the iris (default: 0).</p> <p>rotation: The rotation of the iris (default: 0)</p> <p>brightness: The brightness for the specular highlights (default: 0).</p> <p>threshold: The threshold for the specular highlights (default: 0).</p> <p>amount: The amount of noise (default: 0)</p> <p>distribution: The distribution value for the noise (default: <code>NoiseDistribution.UNIFORM</code>).</p> <p>monochromatic: True if the noise is monochromatic (default: false).</p>
applyLensFlare (brightness, flareCenter, lensType)	number array (UnitValue) LensType		<p>Applies the Lens Flare filter with the specified brightness (0 - 300, as a percentage), the x and y coordinates (unit value) of the flare center, and the lens type.</p>
applyMaximum (radius)	number [1..100]		<p>Applies the Maximum filter within the specified radius (in pixels).</p>
applyMedianNoise (radius)	number [1..100]		<p>Applies the Median Noise filter within the specified radius (in pixels).</p>

Method	Parameter type	Returns	What it does (Continued)
applyMinimum (radius)	number [1..100]		Applies the Minimum filter within the specified radius (in pixels) (1 - 100).
applyMotionBlur (angle, radius)	number [-360..360] number [1..999]		Applies the Motion Blur filter.
applyNTSC ()			Applies the NTSC colors filter.
applyOceanRipple (size, magnitude)	number [1..15] number [0..20]		Applies the Ocean Ripple filter.
applyOffset (horizontal, vertical, undefinedAreas)	UnitValue UnitValue OffsetUndefinedAreas		Moves the layer the specified amount horizontally and vertically (min/max amounts depend on layer size), leaving an undefined area at the layer's original location.
applyPinch (amount)	number [-100..100]		Applies the Pinch filter. amount is a percentage value.
applyPolarCoordinates (conversion)	PolarConversionType		Applies the Polar Coordinates filter.
applyRadialBlur (amount, blurMethod, blurQuality)	number [1..100] RadialBlurMethod RadialBlurQuality		Applies the Radial Blur filter in the specified amount, using either a spin or zoom effect and the specified quality.
applyRipple (amount, size)	number [-999..999] RippleSize		Applies the Ripple filter in the specified amount, throughout the image and in the specified size.
applySharpen ()			Applies the Sharpen filter.
applySharpenEdges ()			Applies the Sharpen Edges filter.
applySharpenMore ()			Applies the Sharpen More filter.
applyShear (curve, undefinedAreas)	array of array of number UndefinedAreas		Applies the Shear filter. The curve defines a curve with [2..255] points. Each value in the curve array is a point pair, an array of an x and y integer value.

Method	Parameter type	Returns	What it does (Continued)
applySmartBlur (radius, threshold, blurQuality, mode)	number [0.1..100.0] number [0.1..100.0] SmartBlurQuality SmartBlurMode		Applies the Smart Blur filter.
applySpherize (amount, mode)	number [-100..100] SpherizeMode		Applies the Spherize filter. amount is a percentage value.
applyStyle (styleName)	string		Applies the specified style to the layer. You must use a style from the Styles list in the Layer Styles Palette.
applyTextureFill (textureFile)	File		Applies the Texture Fill filter.
applyTwirl (angle)	number [-999..999]		Applies the Twirl filter.
applyUnSharpMask (amount, radius, threshold)	number [1..500] number [0.1..250.0] number [0..255]		Applies the Unsharp Mask filter. (amount is a percentage value.
applyWave (generatorNumber, minimumWavelength, maximumWavelength, minimumAmplitude, maximumAmplitude, horizontalScale, verticalScale, waveType, undefinedAreas, randomSeed)	number [1..999] number [1..998] number [2..min+1] number [1..998] number [2..min+1] number [1..100] number [1..100] WaveType UndefinedAreas number		Applies the Wave filter. Scale factors are percentage values.
applyZigZag (amount, ridges, style)	number [-100..100] number [0..20] ZigZagType		Applies the Zigzag filter.
autoContrast ()			Adjusts the contrast of the selected channels automatically.
autoLevels ()			Adjusts the levels of the selected channels using the auto levels option.
clear ()			Cuts the layer without moving it to the clipboard.

Method	Parameter type	Returns	What it does (Continued)
copy ([merge])	boolean		Copies the layer to the clipboard. When the optional argument is set to <code>true</code> , a merged copy is performed (that is, all visible layers are copied to the clipboard).
cut ()			Cuts the layer to the clipboard.
desaturate ()			Converts a color image to a grayscale image in the current color mode by assigning equal values of each component color to each pixel.
duplicate ([relativeObject] [, insertionLocation])	ArtLayer or LayerSet ElementPlacement	ArtLayer or LayerSet	Creates a duplicate of the object on the screen.
equalize ()			Redistributes the brightness values of pixels in an image to more evenly represent the entire range of brightness levels within the image.
invert ()			Inverts the colors in the layer by converting the brightness value of each pixel in the channels to the inverse value on the 256-step color-values scale.
link (with)	ArtLayer or LayerSet		Links the layer with the specified layer.
merge ()		ArtLayer	Merges the layer down, removing the layer from the document; returns a reference to the art layer that this layer is merged into.

Method	Parameter type	Returns	What it does (Continued)
mixChannels (outputChannels [, monochrome])	array of array of number boolean		<p>Modifies a targeted (output) color channel using a mix of the existing color channels in the image.</p> <p>The <code>outputChannels</code> parameter is an array of channel specifications. For each component channel, specify a list of adjustment values in the range [-200..200] followed by a 'constant' value [-200..200].)</p> <p>When <code>monochrome = true</code>, the maximum number of channel value specifications is 1.</p> <p>Valid only when <code>docRef.mode = DocumentMode.RGB</code> or <code>DocumentMode.CMYK</code>.</p> <p>RGB arrays must include four values. CMYK arrays must include five values.</p>
move (relativeObject, insertionLocation)	ArtLayer or LayerSet ElementPlacement		<p>Moves the layer relative to the object specified in parameters.</p> <p>For art layers, only the constant values <code>ElementPlacement.PLACEBEFORE</code> and <code>ElementPlacement.PLACEAFTER</code> are valid.</p> <p>For layer sets, only the constant values <code>ElementPlacement.PLACEBEFORE</code> and <code>ElementPlacement.INSIDE</code> are valid.</p>
photoFilter ([fillColor] [, density] [, preserveLuminosity])	SolidColor number [1..100] boolean		<p>Adjust the layer's color balance and temperature as if a color filter had been applied.</p> <p><code>density</code> is a percentage value.</p>
posterize (levels)	number [2..225]		<p>Specifies the number of tonal levels for each channel and then maps pixels to the closest matching level.</p>
rasterize (target)	RasterizeType		<p>Converts the targeted contents in the layer into a flat, raster image.</p>
remove ()			<p>Deletes the object.</p>

Method	Parameter type	Returns	What it does (Continued)
resize ([horizontal] [, vertical] [, anchor])	number number AnchorPosition		Resizes the layer to the specified dimensions (as a percentage of its current size) and places it in the specified position.
rotate (angle [, anchor])	number AnchorPosition		Rotates rotates the layer around the specified anchor point (default: MIDDLECENTER).
selectiveColor (selectionMethod [, reds] [, yellows] [, greens] [, cyans] [, blues] [, magentas] [, whites] [, neutrals] [, blacks])	AdjustmentReference array of number array of number array of number array of number array of number array of number array of number array of number		Modifies the amount of a process color in a specified primary color without affecting the other primary colors. Each color array must have four values.
shadowHighlight ([shadowAmount] [, shadowWidth] [, shadowRadius] [, highlightAmount] [, highlightWidth] [, highlightRadius] [, colorCorrection] [, midtoneContrast] [, blackClip] [, whiteClip])	number [0..100] number [0..100] number [0..2500] number [0..100] number [0..100] number [0..2500] number [-100..100] number [-100..100] number [0.000..50.000] number [0.000..50.000]		Adjusts the range of tones in the image's shadows and highlights. Amounts and widths are percentage values. Radius values are in pixels.
threshold (level)	number [1..255]		Converts grayscale or color images to high-contrast, B/W images by converting pixels lighter than the specified threshold to white and pixels darker than the threshold to black.
translate ([deltaX] [, deltaY])	UnitValue UnitValue		Moves the layer the specified amount (in the given unit) relative to its current position.
unlink ()			Unlinks the layer.

ArtLayer sample Script

The following script opens all the files in the samples folder, creating one multi-layered document. Each layer is pasted into one of four quadrants and given 50% transparency. Finally the layers are sorted by name.

ArtLayer.jsx


```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

//Close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// Create a new document to merge all the samples into
var mergedDoc = app.documents.add(1000, 1000, 72, "Merged Samples",
NewDocumentMode.RGB, DocumentFill.TRANSPARENT, 1)

// Use the path to the application and append the samples folder
var samplesFolder = Folder(app.path + "/Samples/")

//Get all the files in the folder
var fileList = samplesFolder.GetFiles()

// open each file
for (var i = 0; i < fileList.length; i++) {
    // The fileList is folders and files so open only files
    if (fileList[i] instanceof File) {
        open(fileList[i])

        // use the document name for the layer name in the merged document
        var docName = app.activeDocument.name

        // flatten the document so we get everything and then copy
        app.activeDocument.flatten()
        app.activeDocument.selection.selectAll()
        app.activeDocument.selection.copy()

        // don't save anything we did
        app.activeDocument.close(SaveOptions.DONOTSAVECHANGES)

        // make a random selection on the document to paste into
        // by dividing the document up in 4 quadrants and pasting
        // into one of them by selecting that area
        var topLeftH = Math.floor(Math.random() * 2)
        var topLeftV = Math.floor(Math.random() * 2)
        var docH = app.activeDocument.width.value / 2
        var docV = app.activeDocument.height.value / 2
        var selRegion = Array(Array(topLeftH * docH, topLeftV * docV),
            Array(topLeftH * docH + docH, topLeftV * docV),
            Array(topLeftH * docH, topLeftV * docV + docV),
            Array(topLeftH * docH + docH, topLeftV * docV + docV))
        app.activeDocument.selection.select(selRegion)
        app.activeDocument.paste()

        // change the layer name and opacity
        app.activeDocument.activeLayer.name = docName
        app.activeDocument.activeLayer.fillOpacity = 50
    }
}
```

```
    }  
  }  
  
  // sort the layers by name  
  for (var x = 0; x < app.activeDocument.layers.length; x++) {  
    for (var y = 0; y < app.activeDocument.layers.length - 1 - x; y++) {  
      // Compare in a non-case sensitive way  
      var doc1 = app.activeDocument.layers[y].name  
      var doc2 = app.activeDocument.layers[y + 1].name  
      if (doc1.toUpperCase() > doc2.toUpperCase()) {  
        app.activeDocument.layers[y].move(app.activeDocument.layers[y+1],  
          ElementPlacement.PLACEAFTER)  
      }  
    }  
  }  
}  
  
// Reset the application preferences  
app.preferences.rulerUnits = startRulerUnits  
app.preferences.typeUnits = startTypeUnits  
app.displayDialogs = startDisplayDialogs
```

ArtLayers

The collection of [ArtLayer](#) objects in a document or layer set.

Access through the [Document.artLayers](#) or [LayerSet.artLayers](#) collection. For example:

```
var layerRef = docRef.artLayers.add()
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>artLayers</code> collection.
parent	Document	Read-only. The object's container.
typename	string	Read-only. The class name of the referenced <code>artLayers</code> object.

Methods

Method	Parameter type	Returns	What it does
add ()		ArtLayer	Creates a new art layer in the document and adds the new object to this collection.
getByName (name)	string	ArtLayer	Get the first element in the <code>artLayers</code> collection with the provided name.
removeAll ()			Removes all elements from the <code>artLayers</code> collection.

BatchOptions

Options for running a batch operation using the [Application.batch\(\)](#) method.

JavaScript only supports folders as sources for batch commands. Specify the batch source folder as the `inputFiles` parameter of the [Application.batch\(\)](#) method.

Properties

Property	Value type	What it is
destination	BatchDestinationType	Read-write. The type of destination for the processed files (default: <code>BatchDestinationType.NODESTINATION</code>).
destinationFolder	Folder	Read-write. The folder location for the processed files. Valid only when destination = <code>BatchDestinationType.FOLDER</code> .
errorFile	File	Read-write. The file in which to log errors encountered. To display errors on the screen (and stop batch processing when errors occur) leave blank.
fileNaming	array of FileNamingType	Read-write. A list of file naming options (maximum: 6). Valid only when destination = <code>BatchDestinationType.FOLDER</code> .
macintoshCompatible	boolean	Read-write. True to make the final file names Macintosh compatible (default: <code>true</code>). Valid only when destination = <code>BatchDestinationType.FOLDER</code> .
overrideOpen	boolean	Read-write. True to override action open commands (default: <code>false</code>).
overrideSave	boolean	Read-write. True to override save as action steps with the specified destination (default: <code>false</code>). Valid only when destination = <code>BatchDestinationType.FOLDER</code> or <code>SAVEANDCLOSE</code> .
startingSerial	number	Read-write. The starting serial number to use in naming files (default: 1). Valid only when destination = <code>BatchDestinationType.FOLDER</code> .
suppressOpen	boolean	Read-write. True to suppress the file open options dialogs (default: <code>false</code>).

Property	Value type	What it is (Continued)
suppressProfile	boolean	Read-write. True to suppress the color profile warnings (default: <code>false</code>).
typename	string	Read-only. The class name of the referenced <code>batchOptions</code> object.
unixCompatible	boolean	Read-write. True to make the final file name Unix compatible (default: <code>true</code>). Valid only when destination = <code>BatchDestinationType.FOLDER</code> .
windowsCompatible	boolean	Read-write. True to make the final file names Windows compatible (default: <code>true</code>). Valid only when destination = <code>BatchDestinationType.FOLDER</code> .

BitmapConversionOptions

Options for converting an image to bitmap mode, using [Document.changeMode\(\)](#) with [ChangeMode.Bitmap](#).

Convert color images to grayscale before converting the image to bitmap mode. See the [ArtLayer.desaturate\(\)](#) method.

Properties

Property	Value type	What it is
angle	number [-180..180]	Read-write. The angle (in degrees) at which to orient individual dots. See shape . Valid only when method = <code>BitmapConversionType.HALFTONESCREEN</code> .
frequency	number [1.0..999.99]	Read-write. The number of printer dots (per inch) to use. Valid only when method = <code>BitmapConversionType.HALFTONESCREEN</code> .
method	BitmapConversionType	Read-write. The conversion method to use (default: <code>BitmapConversionType.DIFFUSIONDITHER</code>).
patternName	string	Read-write. The name of the pattern to use. For information about pre-installed valid patterns, see Adobe Photoshop CS5 Help on the bitmap conversion command, or view the options available in the Custom Color drop down box after choosing the bitmap conversion command. Valid only when method = <code>BitmapConversionType.CUSTOMPATTERN</code> .
resolution	number	Read-write. The output resolution in pixels per inch (default: 72.0).
shape	BitmapHalfToneType	Read-write. The dot shape to use. Valid only when method = <code>BitmapConversionType.HALFTONESCREEN</code> .
typename	string	Read-only. The class name of the referenced <code>bitmapConversionOptions</code> object.

BMPSaveOptions

Options for saving a document in BMP format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
depth	BMPDepthType	Read-write. The number of bits per channel.
flipRowOrder	boolean	Read-write. True to write the image from top to bottom (default: <code>false</code>). Available only when osType = <code>OperatingSystem.WINDOWS</code> .
osType	OperatingSystem	Read-write. The target OS. (default: <code>OperatingSystem.WINDOWS</code>).
rleCompression	boolean	Read-write. True to use RLE compression. Available only when osType = <code>OperatingSystem.WINDOWS</code> .
typename	string	Read-only. The class name of the referenced <code>BMPSaveOptions</code> object.

CameraRAWOpenOptions

Options for opening a document in Camera RAW format using the [Application.open\(\)](#) method.

Properties

Property	Value type	What it is
bitsPerChannel	BitsPerChannelType	Read-write. The number of bits per channel.
blueHue	number [-100..100]	Read-write. The blue hue of the shot.
blueSaturation	number [-100..100]	Read-write. The blue saturation of the shot.
brightness	number [0..150]	Read-write. The brightness of the shot.
chromaticAberrationBY	number [-100..100]	Read-write. The chromatic aberration B/Y of the shot.
chromaticAberrationRC	number [-100..100]	Read-write. The chromatic aberration R/C of the shot
colorNoiseReduction	number [0..100]	Read-write. The color noise reduction of the shot.
colorSpace	ColorSpaceType	Read-write. The colorspace for the image.
contrast	number [-50..100]	Read-write. The contrast of the shot.
exposure	number [-4.0..4.0]	Read-write. The exposure of the shot.
greenHue	number [-100..100]	Read-write. The green hue of the shot.
greenSaturation	number [-100..100]	Read-write. The green saturation of the shot.
luminanceSmoothing	number [0..100]	Read-write. The luminance smoothing of the shot.
redHue	number [-100..100]	Read-write. The red hue of the shot.
redSaturation	number [-100..100]	Read-write. The red saturation of the shot.
resolution	number [1..999]	Read-write. The resolution of the document in pixels per inch.
saturation	number [-100..100]	Read-write. The saturation of the shot.
settings	CameraRAWSettingsType	Read-write. The global settings for all Camera RAW options. Default: <code>CameraRAWSettingsType.CAMERA</code> .
shadows	number [0..100]	Read-write. The shadows of the shot.
shadowTint	number [-100..100]	Read-write. The shadow tint of the shot.
sharpness	number [0..100]	Read-write. The sharpness of the shot.
size	CameraRAWSize	Read-write. The size of the new document.
temperature	number [2000..50000]	Read-write. The temperature of the shot.

Property	Value type	What it is (Continued)
tint	number [-150..150]	Read-write. The tint of the shot.
typename	string	Read-only. The class name of the referenced <code>cameraRAWOpenOptions</code> object.
vignettingAmount	number [-100..100]	Read-write. The vignetting amount of the shot.
vignettingMidpoint	number [-100..100]	Read-write. The vignetting mid point of the shot.
whiteBalance	WhiteBalanceType	Read-write. The white balance options for the image. These are lighting conditions that affect color balance.

Channel

Information about a color element in the image.

Access through the [Document.channels](#) collection. You can access an individual channel object in this list by index or by name. For example, this accesses a channel object in the active document by name and assigns an `opacity` value:

```
var channelRef = app.activeDocument.channels.getByNamed("my channel");
channelRef.opacity = 22;
```

A channel is analogous to a plate in the printing process that applies a single color. The document's color mode determines the number of default channels; for example, an RGB document has three channels, red, green, and blue. A color can also have an alpha channel, which stores selections as masks, or a spot channel, which stores spot colors.

Properties

Property	Value type	What it is
color	SolidColor	Read-write. The color of the channel. Not valid when <code>kind</code> = <code>ChannelType.COMPONENT</code> .
histogram	array of number	Read-only. A histogram of the color of the channel. The array contains 256 members. Not valid when <code>kind</code> = <code>ChannelType.COMPONENT</code> . For component channel histogram values, use the histogram property of the Document object instead.
kind	ChannelType	Read-write. The type of the channel.
name	string	Read-write. The name of the channel.
opacity	number [0..100]	Read-write. The opacity to use for alpha channels or the solidity to use for spot channels. Valid only when <code>kind</code> = <code>ChannelType.MASKEDAREA</code> or <code>SELECTEDAREA</code> .
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>channel</code> object.
visible	boolean	Read-write. True if the channel is visible.

Methods

Method	Parameter type	Returns	What it does
duplicate ([targetDocument])	Document	Channel	Duplicates the channel.

Method	Parameter type	Returns	What it does
merge ()			Merges a spot channel into the component channels.
remove ()			Deletes the channel.

Channels

The collection of [Channel](#) objects in a document.

Access through the [Document.channels](#) collection property. For example:

```
var channelRef = app.activeDocument.channels.add()
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>channels</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>channels</code> object.

Methods

Method	Parameter type	Returns	What it does
add ()		Channel	Creates a new channel object and adds it to this collection.
getByName (name)	string	Channel	Get the first element in the <code>channels</code> collection with the provided name.
removeAll ()			Removes all alpha channel objects from the <code>channels</code> collection.

Channels sample script

The following script opens a file if one is not already open, and then writes a histogram report (`histogram.log`) for the channels in the active document.

Note: This script contains a switch construction that uses a `break` statement. The `break` statement requires an ending semicolon (;), as in the following sample:

```
break;
```

Histogram.jsx

```
// Function to activate all the channels according to the documents mode
// Takes a document reference for input
function TurnOnDocumentHistogramChannels(inDocument) {

    // see how many channels we need to activate
    var visibleChannelCount = 0

    // based on the mode of the document
    switch (inDocument.mode) {

        case DocumentMode.BITMAP:
```

```
        case DocumentMode.GRAYSCALE:
        case DocumentMode.INDEXEDCOLOR:
            visibleChannelCount = 1
            break;

        case DocumentMode.DUOTONE:
            visibleChannelCount = 2
            break;

        case DocumentMode.RGB:
        case DocumentMode.LAB:
            visibleChannelCount = 3
            break;

        case DocumentMode.CMYK:
            visibleChannelCount = 4
            break;

        case DocumentMode.MULTICHANNEL:
        default:
            visibleChannelCount = inDocument.channels.length + 1
            break;
    }

    // now get the channels to activate into a local array
    var aChannelArray = new Array()

    // index for the active channels array
    var aChannelIndex = 0

    for(var channelIndex = 0; channelIndex < inDocument.channels.length;
        channelIndex++) {
        if (channelIndex < visibleChannelCount) {
            aChannelArray[aChannelIndex++] = inDocument.channels[channelIndex]
        }
    }

    // now activate them
    inDocument.activeChannels = aChannelArray
}

// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// if there are no documents open then try to open a sample file
if (app.documents.length == 0) {
    open(File(app.path + "/Samples/Fish.psd"))
}

// get a reference to the working document
var docRef = app.activeDocument
```

```
// create the output file
// first figure out which kind of line feeds we need
if ($.os.search(/windows/i) != -1) {
    fileLineFeed = "Windows"
} else {
    fileLineFeed = "Macintosh"
}

// create the output file accordingly
fileOut = new File("~/Desktop/Histogram.log")
fileOut.lineFeed = fileLineFeed
fileOut.open("w", "TEXT", "????")

// write out a header
fileOut.write("Histogram report for " + docRef.name)

// find out how many pixels I have
var totalCount = docRef.width.value * docRef.height.value

// more info to the out file
fileOut.write(" with a total pixel count of " + totalCount + "\n")

// channel indexer
var channelIndex = 0

// remember which channels are currently active
var myActiveChannels = app.activeDocument.activeChannels

// document histogram only works in these modes
if (docRef.mode == DocumentMode.RGB ||
    docRef.mode == DocumentMode.INDEXEDCOLOR ||
    docRef.mode == DocumentMode.CMYK) {

    // activate the main channels so we can get the documents histogram
    TurnOnDocumentHistogramChannels(docRef)

    // Output the documents histogram
    OutputHistogram(docRef.histogram, "Luminosity", fileOut)
}

// local reference to work from
var myChannels = docRef.channels

// loop through each channel and output the histogram
for (var channelIndex = 0; channelIndex < myChannels.length; channelIndex++) {

    // the channel has to be visible to get a histogram
    myChannels[channelIndex].visible = true

    // turn off all the other channels
    for (var secondaryIndex = 0; secondaryIndex < myChannels.length;
         secondaryIndex++) {
        if (channelIndex != secondaryIndex) {
            myChannels[secondaryIndex].visible = false
        }
    }

    // Use the function to dump the histogram
    OutputHistogram(myChannels[channelIndex].histogram,
        myChannels[channelIndex].name, fileOut)
```

```
}

// close down the output file
fileOut.close()
alert("Histogram file saved to: " + fileOut.fsName)

// reset the active channels
docRef.activeChannels = myActiveChannels

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs

// Utility function that takes a histogram and name
// and dumps to the output file
function OutputHistogram(inHistogram, inHistogramName, inOutFile) {

    // find out which count has the largest number
    // I scale everything to this number for the output
    var largestCount = 0

    // a simple indexer I can reuse
    var histogramIndex = 0

    // see how many samples we have total
    var histogramCount = 0

    // search through all and find the largest single item
    for (histogramIndex = 0; histogramIndex < inHistogram.length;
        histogramIndex++) {
        histogramCount += inHistogram[histogramIndex]
        if (inHistogram[histogramIndex] > largestCount)
            largestCount = inHistogram[histogramIndex]
    }

    // These should match
    if (histogramCount != totalCount) {
        alert("Something bad is happening!")
    }

    // see how much each "X" is going to count as
    var pixelsPerX = largestCount / 100

    // output this data to the file
    inOutFile.write("One X = " + pixelsPerX + " pixels.\n")

    // output the name of this histogram
    inOutFile.write(inHistogramName + "\n")

    // loop through all the items and output in the following format
    // 001
    // 002
    for (histogramIndex = 0; histogramIndex < inHistogram.length;
        histogramIndex++) {

        // I need an extra "0" for this line item to keep everything in line
        if (histogramIndex < 10)
            inOutFile.write("0")
```

```
// I need an extra "0" for this line item to keep everything in line
if (histogramIndex < 100)
    inOutFile.write("0")

// output the index to file
inOutFile.write(histogramIndex)

// some spacing to make it look nice
inOutFile.write(" ")

// figure out how many X's I need
var outputX = inHistogram[histogramIndex] / largestCount * 100

// output the X's
for (var a = 0; a < outputX; a++)
    inOutFile.write("X")

    inOutFile.write("\n")
}

inOutFile.write("\n")
}
```


CMYKColor

Defines a CMYK color, used in the [SolidColor](#) object.

See also [GrayColor](#), [HSBColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

Properties

Property	Value type	What it is
black	number [0.0..100.00]	Read-write. The black color value (as percent).
cyan	number [0.0..100.00]	Read-write. The cyan color value (as percent).
magenta	number [0.0..100.00]	Read-write. The magenta color value (as percent).
typename	string	Read-only. The class name of the referenced <code>CMYKColor</code> object.
yellow	number [0.0..100.00]	Read-write. The yellow color value (as percent).

ColorSampler

A color sampler for a document. Access through the [Document.colorSamplers](#) collection. For example:

```
var colorSamplerRef = app.activeDocument.colorSamplers[0];  
var currentColor = colorSamplerRef.color;
```

Note: For additional information about color samplers, see Adobe Photoshop CS5 help on the Color Sampler Tool.

Properties

Property	Value type	What it is
color	SolidColor	Read-only. The color of the color sampler.
position	array of UnitValue	Read-only. The position of the color sampler in the document. The array (x,y) represents the horizontal and vertical location of the count item.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>ColorSampler</code> object.

Methods

Method	Parameter type	Returns	What it does
move (position)	array of UnitValue		Moves the color sampler to a new location in the document. The <code>position</code> parameter (x,y) represents the new horizontal and vertical locations of the moved color sampler.
remove ()			Deletes the <code>ColorSampler</code> object.

ColorSamplers

The collection of [ColorSampler](#) objects in a document. Access through the [Document.colorSamplers](#) collection property. For example:

```
app.activeDocument.colorSamplers.removeAll()
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>ColorSamplers</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>ColorSamplers</code> object.

Methods

Method	Parameter type	Returns	What it does
add (position)	array of UnitValue	ColorSampler	Creates a new color sampler object and adds it to this collection. The <code>position</code> parameter (x,y) represents the new horizontal and vertical locations of the moved color sampler.
removeAll ()			Removes all <code>ColorSampler</code> objects from the <code>ColorSamplers</code> collection.

ContactSheetOptions

Options for creating a contact sheet with the [Application.makeContactSheet\(\)](#) method.

Properties

Property	Value type	What it is
acrossFirst	boolean	Read-write. True to place the images horizontally (left to right, then top to bottom) first (default: <code>true</code>).
bestFit	boolean	Read-write. True to rotate images for the best fit (default: <code>false</code>).
caption	boolean	Read-write. True to use the filename as a caption for the image (default: <code>true</code>).
columnCount	number [1..100]	Read-write. The number of columns to include (default: 5).
flatten	boolean	Read-write. True to flatten all layers in the final document (default: <code>true</code>).
font	GalleryFontType	Read-write. The font used for the caption (default: <code>GalleryFontType.ARIAL</code>).
fontSize	number	Read-write. The font size to use for the caption (default: 12).
height	number [0..29000]	Read-write. The height (in pixels) of the resulting document (default: 720).
horizontal	number	Read-write. The horizontal spacing (in pixels) between images (default: 1).
mode	NewDocumentMode	Read-write. The document color mode (default: <code>NewDocumentMode.RGB</code>).
resolution	number [35..1200]	Read-write. The resolution of the document in pixels per inch (default: 72.0).
rowCount	number [1..100]	Read-write. The number of rows to use (default: 6).
typename	string	Read-only. The class name of the referenced <code>contactSheetOptions</code> object.
useAutoSpacing	boolean	Read-write. True to auto space the images (default: <code>true</code>).
vertical	number [0..29000]	Read-write. The vertical spacing (in pixels) between images (default: 1). Valid only when useAutoSpacing = <code>false</code> .
width	number [100..29000]	Read-write. The width (in pixels) of the resulting document (default: 576).

CountItem

A counted item in a document. Access through the [Document.countItems](#) collection. See the [Document.autoCount\(\)](#) method.

Note: This feature is available in the Extended Version only.

For additional information about count items, see Adobe Photoshop CS5 help on the Count Tool.

Properties

Property	Value type	What it is
position	array of UnitValue	Read-only. The position of the count item in the document.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>CountItem</code> object.

Methods

Method	Parameter type	Returns	What it does
remove ()			Deletes the <code>CountItem</code> object.

CountItems

The collection of [CountItem](#) objects in the document.

Access through the [Document.countItems](#) collection property. For example:

```
app.activeDocument.countItems.removeAll()
```

Note: This feature is available in the Extended Version only.

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>CountItems</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>CountItems</code> object.

Methods

Method	Parameter type	Returns	What it does
add (position)	array of UnitValue	CountItem	Creates a new count item object and adds it to this collection. Parameter <code>position (x,y)</code> represents the horizontal and vertical positions, respectively, of the <code>CountItem</code> object.
getByName (name)	string	CountItem	Get the first element in the <code>CountItems</code> collection with the provided name.
removeAll ()			Removes all <code>CountItem</code> objects from the <code>CountItems</code> collection.

DCS1_SaveOptions

Options for saving a CMYK document in DCS1 format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
dcs	DCSType	Read-write. (default: <code>DCSType.COLORCOMPOSITE</code>).
embedColorProfile	boolean	Read-write. True to embed the color profile in the document
encoding	SaveEncoding	Read-write. The type of encoding to use for document (default: <code>SaveEncoding.BINARY</code>).
halftoneScreen	boolean	Read-write. True to include halftone screen (default: <code>false</code>).
interpolation	boolean	Read-write. True to use image interpolation (default: <code>false</code>)
preview	Preview	Read-write. The type of preview (default: <code>Preview.MACOSEIGHTBIT</code>).
transferFunction	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code>).
typename	string	Read-only. The class name of the referenced <code>DCS1_SaveOptions</code> object.
vectorData	boolean	Read-write. True to include vector data. Valid only if the document includes vector data (unrasterized text).

DCS2_SaveOptions

Options for saving a CMYK document in DCS2 format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
dcs	DCSType	Read-write. The type of composite file to create (default: <code>DCSType.NOCOMPOSITE</code>).
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
encoding	SaveEncoding	Read-write. The type of encoding to use (default: <code>SaveEncoding.BINARY</code>).
halftoneScreen	boolean	Read-write. True to include the halftone screen (default: <code>false</code>).
interpolation	boolean	Read-write. True to use image interpolation (default: <code>false</code>).
multiFileDCS	boolean	Read-write. True to save color channels as multiple files or a single file (default: <code>false</code>).
preview	Preview	Read-write. The preview type (default: <code>Preview.MACOSEIGHTBIT</code>).
spotColors	boolean	Read-write. True to save spot colors.
transferFunction	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code>).
typename	string	Read-only. The class name of the referenced <code>DCS2_SaveOptions</code> object.
vectorData	boolean	Read-write. True to include vector data. Valid only if the document includes vector data (unrasterized text).

DICOMOpenOptions

Options for opening a document in DICOM format using the [Application.open\(\)](#) method.

Note: This feature is available in the Extended Version only.

Properties

Property	Value type	What it is
anonymize	boolean	Read-write. True to make the patient information anonymous.
columns	number	Read-write. Number of columns in n-up configuration.
reverse	boolean	Read-write. True to reverse (invert) the image.
rows	number	Read-write. The number of rows in n-up configuration.
showOverlays	boolean	Read-write. True to show overlays.
typename	string	Read-only. The class name of the referenced <code>DICOMOpenOptions</code> object.
windowLevel	number	Read-write. The contrast of the image in Hounsfield units.
windowWidth	number	Read-write. The brightness of the image in Hounsfield units.

Document

The active containment object for layers and all other objects in the script; the basic canvas for the file.

- Access the object for the currently active document through [Application.activeDocument](#).
- You can access other documents, or iterate through all open documents using the list in the [Application.documents](#) collection. You can access individual documents in the list by index, or use [Documents.getByIndex\(\)](#) to retrieve them by name.
- Create documents programmatically using the [Documents.add\(\)](#) method.

See [Document sample script](#) and the [Documents](#) collection object for examples.

Note: In Adobe Photoshop CS5, a document can also be referred to as an image or a canvas.

- The term *image* refers to the entire document and its contents. You can trim or crop an image. You resize an image using the [resizeImage\(\)](#) method.
- The term *canvas* refers to the space in which the document sits on the screen. You can rotate or flip the canvas. You resize the canvas using the [resizeCanvas\(\)](#) method.

Properties

Property	Value type	What it is
activeChannels	array of Channel	Read-write. The selected channels.
activeHistoryBrushSource	Guide	Read-write. The history state to use with the history brush.
activeHistoryState	Guide	Read-write. The selected <code>HistoryState</code> object.
activeLayer	ArtLayer or LayerSet	Read-write. The selected layer.
artLayers	ArtLayers	Read-only. The art layers collection.
backgroundLayer	ArtLayer	Read-only. The background layer of the document.
bitsPerChannel	BitsPerChannelType	Read-write. The number of bits per channel.
channels	Channels	Read-only. The channels collection.
colorProfileName	string	Read-write. The name of the color profile. Valid only when colorProfileType = <code>ColorProfile.CUSTOM OR WORKING</code> .
colorProfileType	ColorProfileType	Read-write. Whether the document uses the working color profile, a custom profile, or no profile.
colorSamplers	ColorSamplers	Read-only. The current color samplers associated with this document.
componentChannels	array of Channel	Read-only. The color channels that make up the document; for instance, the Red, Green, and Blue channels for an RGB document.

Property	Value type	What it is (Continued)
<code>countItems</code>	CountItems	Read-only. The current count items. Note: For additional information about count items, see Adobe Photoshop CS5 help on the Count Tool.
<code>fullName</code>	File	Read-only. The full path name of the document.
<code>guides</code>	Guides	Read-only. The guides collection.
<code>height</code>	UnitValue	Read-only. The height of the document (unit value).
<code>histogram</code>	array of number	Read-only. A histogram showing the number of pixels at each color intensity level for the composite channel. The array contains 256 members. Valid only when <code>mode</code> = <code>DocumentMode.RGB</code> , <code>CMYK</code> ; or <code>INDEXEDCOLOR</code> .
<code>historyStates</code>	HistoryStates	Read-only. The history states collection.
<code>info</code>	DocumentInfo	Read-only. Metadata about the document.
<code>layerComps</code>	LayerComps	Read-only. The layer compositions collection.
<code>layers</code>	Layers	Read-only. The layers collection.
<code>layerSets</code>	LayerSets	Read-only. The layer set collection.
<code>managed</code>	boolean	Read-only. True if the document is a workgroup document.
<code>measurementScale</code>	MeasurementScale	Read-only. The measurement scale for the document. Note: The measurement scale feature is available in the Extended version only.
<code>mode</code>	DocumentMode	Read-only. The color profile.
<code>name</code>	string	Read-only. The document's name.
<code>parent</code>	Application	Read-only. The application object that contains this document.
<code>path</code>	File	Read-only. The path to the document.
<code>pathItems</code>	PathItems	Read-only. The path items collection.
<code>pixelAspectRatio</code>	number [0.100..10.000]	Read-write. The (custom) pixel aspect ratio to use.
<code>printSettings</code>	DocumentPrintSettings	Read-only. The print settings for the document.

Property	Value type	What it is (Continued)
quickMaskMode	boolean	Read-write. True if the document is in Quick Mask mode.
resolution	number	Read-only. The document's resolution (in pixels per inch).
saved	boolean	Read-only. True if the document has been saved since the last change.
selection	Selection	Read-only. The selected area of the document.
typename	string	Read-only. The class name of the Document object.
width	UnitValue	Read-only. The width of the document (unit value).
xmpMetadata	xmpMetadata	Read-only. XMP metadata for the document. Camera RAW settings for the image are stored here for example.

Methods

Method	Parameter type	Returns	What it does
autoCount (channel, threshold)	Channel number		Counts the number of objects in a document. Available in the Extended Version only. Creates a CountItem object for each object counted. For additional information about how to set up objects to count, see the Count Tool in the Adobe Photoshop CS5 Help
changeMode (destinationMode [, options])	ChangeMode BitmapConversionOptions or IndexedConversionOptions		Changes the color profile of the document.
close ([saving])	SaveOptions		Closes the document. If any changes have been made, the script presents an alert with three options: save, do not save, prompt to save. The optional parameter specifies a selection in the alert box (default: <code>SaveOptionsType.PROMPTTOSAVECHANGES</code>).
convertProfile (destinationProfile, intent [, blackPointCompensation] [, dither])	string Intent boolean boolean		Changes the color profile. The <code>destinationProfile</code> parameter must be either a string that names the color mode or <code>Working RGB</code> , <code>Working CMYK</code> , <code>Working Gray</code> , <code>Lab Color</code> (meaning one of the working color spaces or Lab color).
crop (bounds [, angle] [, width] [, height])	array of 4 UnitValue number UnitValue UnitValue		Crops the document. The <code>bounds</code> parameter is an array of four coordinates for the region remaining after cropping, [left, top, right, bottom].
duplicate ([name] [, mergeLayersOnly])	string boolean	Document	Creates a duplicate of the document object. The optional parameter <code>name</code> provides the name for the duplicated document. The optional parameter <code>mergeLayersOnly</code> indicates whether to only duplicate merged layers.

Method	Parameter type	Returns	What it does (Continued)
exportDocument (exportIn [, exportAs] [, options])	File ExportType ExportOptionsIllustrator —or— ExportOptionsSaveForWeb		Exports the paths in the document to an Illustrator file, or exports the document to a file with Web or device viewing optimizations. This is equivalent to choosing File > Export > Paths To Illustrator , or File > Save For Web and Devices .
flatten ()			Flattens all layers in the document.
flipCanvas (direction)	Direction		Flips the image within the canvas in the specified direction.
importAnnotations (file)	File		Imports annotations into the document.
mergeVisibleLayers ()			Flattens all visible layers in the document.
paste ([intoSelection])	boolean	ArtLayer	Pastes the contents of the clipboard into the document. If the optional argument is set to <code>true</code> and a selection is active, the contents are pasted into the selection.
print ([sourceSpace] [, printSpace] [, intent] [blackPointCompensation])	SourceSpaceType string Intent boolean		Prints the document. <code>printSpace</code> specifies the color space for the printer. Valid values are <code>nothing</code> (that is, the same as the source); or <code>Working RGB</code> , <code>Working CMYK</code> , <code>Working Gray</code> , <code>Lab Color</code> (meaning one of the working color spaces or Lab color); or a string specifying a specific colorspace (default is same as source).
printOneCopy ()			Print one copy of the document.
rasterizeAllLayers ()			Rasterizes all layers.
recordMeasurements ([source] [, dataPoints])	MeasurementSource array of string		Record measurements of document.
resizeCanvas ([width] [, height] [, anchor])	UnitValue UnitValue AnchorPosition		Changes the size of the canvas to display more or less of the image but does not change the image size. See resizeImage .
resizeImage ([width] [, height] [, resolution] [, resampleMethod])	UnitValue UnitValue number ResampleMethod		Changes the size of the image.

Method	Parameter type	Returns	What it does (Continued)
revealAll ()			Expands the document to show clipped sections.
rotateCanvas (angle)	number		Rotates the canvas (including the image) in clockwise direction.
save ()			Saves the document.
saveAs (saveIn [, options] [, asCopy] [, extensionType])	File object (see description) boolean Extension		Saves the document in a specific format. Specify the save options appropriate to the format by passing one of these objects: BMPSaveOptions DCS1_SaveOptions DCS2_SaveOptions EPSSaveOptions GIFSaveOptions JPEGSaveOptions PDFSaveOptions PhotoshopSaveOptions PCTFileSaveOptions PCTResourceSaveOptions PixarSaveOptions PNGSaveOptions RawSaveOptions SGIRGBSaveOptions TargaSaveOptions TiffSaveOptions
splitChannels ()		array of Document	Splits the document channels into separate images.
suspendHistory (historyString javaScriptString)	string string		Provides a single entry in history states for the entire script provided by javaScriptString. Allows a single undo for all actions taken in the script. The historyString parameter provides the string to use for the history state. The javaScriptString parameter provides a string of JavaScript code to execute while history is suspended.
trap (width)	number		Applies trapping to a CMYK document. Valid only when <code>docRef.mode = DocumentMode.CMYK</code> .
trim ([type] [, top] [, left] [, bottom] [, right])	TrimType boolean boolean boolean boolean		Trims the transparent area around the image on the specified sides of the canvas. Default is <code>true</code> for all Boolean parameters.

Document sample script

The following script creates a document that contains two images (a sunflower and a duck) obtained from the Adobe Photoshop CS5 Samples folder and employs the following steps:

- Determines which image is larger.
- Resizes the smaller image to match the larger image.
- Creates a merged document twice as high as either image in order to hold both images.
- Selects part of the document and pastes the sunflower into the selection.
- Inverts the selection and pastes the duck into the lower part of the document.
- Positions the sunflower over the duck.

Document.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// first close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// Open the sunflower and duck files from the samples folder
var flowerDoc = open(File(app.path + "/Samples/Sunflower.psd"))
var duckDoc = open(File(app.path + "/Samples/Ducky.tif"))

// Find out which document is larger
// Resize the smaller document to the larger document's size
// The resize requires the document be the active/front document
if ((flowerDoc.width.value * flowerDoc.height.value) >
    (duckDoc.width.value * duckDoc.height.value)) {
    app.activeDocument = duckDoc
    duckDoc.resize(flowerDoc.width, flowerDoc.height)
}
else {
    app.activeDocument = flowerDoc
    flowerDoc.resizeImage(duckDoc.width, duckDoc.height)
}

// Create a new document twice as high as two files
var mergedDoc = app.documents.add(duckDoc.width, duckDoc.height * 2,
    duckDoc.resolution, "FlowerOverDuck")

// Copy the flower to the top; make it the active document so we can manipulate it
app.activeDocument = flowerDoc
flowerDoc.activeLayer.copy()

// Paste the flower to the merged document, making the merged document active
app.activeDocument = mergedDoc

// Select a square area at the top of the new document
```



```
var selRegion = Array(Array(0, 0),
    Array(mergedDoc.width.value, 0),
    Array(mergedDoc.width.value, mergedDoc.height.value / 2),
    Array(0, mergedDoc.height.value / 2),
    Array(0, 0))
// Create the selection
mergedDoc.selection.select(selRegion)

//Paste in the flower
mergedDoc.paste(TRUE)

// do the same thing for the duck
app.activeDocument = duckDoc
duckDoc.activeLayer.copy()

app.activeDocument = mergedDoc
mergedDoc.selection.select(selRegion)

// Inverting the selection so the bottom of the document is now selected
mergedDoc.selection.invert()

// Paste the duck
mergedDoc.paste(TRUE)

// get rid of our originals without modifying them
duckDoc.close(SaveOptions.DONOTSAVECHANGES)
flowerDoc.close(SaveOptions.DONOTSAVECHANGES)

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs
```

DocumentPrintSettings

The print settings for a document.

Properties

Property	Value type	What it is
backgroundColor	SolidColor	Read-write. Background color of page.
bleedWidth	UnitValue	Read-write. Bleed width
caption	boolean	Read-write. Print the caption found in FileInfo.
centerCropMarks	boolean	Read-write. Print center crop marks.
colorBars	boolean	Read-write. Print color calibration bars.
copies	number	Read-write. Number of copies to print.
cornerCropMarks	boolean	Read-write. Print corner crop marks.
colorHandling	PrintColorHandling	Read-only. Color handling.
activePrinter	string	Read-write. The currently active printer.
flip	boolean	Read-write. Flip the image horizontally.
hardProof	boolean	Read-write. Print a hard proof.
interpolate	boolean	Read-write.
labels	boolean	Read-write. Prints the document title.
mapBlack	boolean	Read-write. Map blacks.
negative	boolean	Read-write. Invert the image colors.
renderIntent	Intent	Read-write. Color conversion intent when print space is different from the source space.
posX	UnitValue	Read-only. The x position of the image on page.
posY	UnitValue	Read-only. The y position of the image on page.
printBorder	UnitValue	Read-write. The width of the print border.
printerName	string	Read-write. Name of the printer.
printSpace	string	Read-write. color space for printer. Can be nothing (meaning same as source); 'Working RGB', 'Working CMYK', 'Working Gray', 'Lab Color' (meaning one of the working spaces or Lab color); or a string specifying a specific colorspace (default is same as source)
registrationMarks	boolean	Read-write. Print registration marks.

Property	Value type	What it is (Continued)
scale	number	Read-only. Scale of image on page.
vectorData	boolean	Read-write. Include vector data.

Methods

Method	Parameter type	Returns	What it does
setPagePosition (docPosition, posX, posY, scale)	DocPositionStyle UnitValue UnitValue number		Set the position of the image on the page.

DocumentInfo

Metadata about a document object.

Access through the [Document.info](#) property. For example, the following sets the author, caption, and copyrighted properties:

```
var docRef = open(fileList[i])
// set the file info
docRef.info.author = "Mr. Adobe programmer"
docRef.info.caption = "Adobe Photo shoot"
docRef.info.copyrighted = CopyrightedType.COPYRIGHTEDWORK
```

These values can be set interactively by choosing **File > File Info**.

Properties

Property	Value type	What it is
author	string	Read-write.
authorPosition	string	Read-write.
caption	string	Read-write.
captionWriter	string	Read-write.
category	string	Read-write.
city	string	Read-write.
copyrighted	CopyrightedType	Read-write. The copyrighted status.
copyrightNotice	string	Read-write.
country	string	Read-write.
creationDate	string	Read-write.
credit	string	Read-write.
exif	array of array [<i>tag data</i>]	Read-only. Camera data that includes camera settings used when the image was taken. Each array member is a tag pair, an array of [<i>tag</i> , <i>tag_data</i>]; for example, ["camera" "Cannon"].
headline	string	Read-write.
instructions	string	Read-write.
jobName	string	Read-write.
keywords	array of string	Read-write. A list of keywords that can identify the document or its contents.
ownerUrl	string	Read-write.

Property	Value type	What it is (Continued)
parent	Document	Read-only. The <code>info</code> object's container.
provinceState	string	Read-write.
source	string	Read-write.
supplementalCategories	array of string	Read-write.
title	string	Read-write.
transmissionReference	string	Read-write.
typename	string	Read-only. The class name of the referenced <code>info</code> object.
urgency	Urgency	Read-write.

DocumentInfo sample Script

The following script sets document info (metadata) for all of the files in a specified folder and then saves the modified files as low-quality JPEG images in a new folder without changing the originals.

- Ask the user to specify the folder that contains the original files and the output folder for the JPEG images, and then check that the folders exist.
- Open each file and use the `documentInfo` object properties to tag it with the following metadata:
 - author: Adobe programmer
 - caption: Adobe Photo shoot
 - captionWriter: Adobe programmer
 - city: San Jose
 - copyrightNotice: Copyright (c) Adobe programmer Photography
 - copyrighted status: Copyrighted Work
 - country: USA
 - state: CA
- Save the new documents in JPEG format with a low quality setting.

DocumentInfo.jsx

```
// Save the current preferences
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.displayDialogs = DialogModes.NO

// ask the user for the input and output folders
var inputFolder = Folder.selectDialog("Select a folder to tag")
var outputFolder = Folder.selectDialog("Select a folder for the output files")

// see if we got something interesting from the dialog
if (inputFolder != null && outputFolder != null) {
    // get all the files found in this folder
    var fileList = inputFolder.GetFiles()
```

```
// save the outputs in JPEG
var jpegOptions = new JPEGSaveOptions()
// set the jpeg quality really low so the files are small
jpegOptions.quality = 1
// open each one in turn
for (var i = 0; i < fileList.length; i++) {
    // The fileList includes both folders and files so open only files
    if (fileList[i] instanceof File && fileList[i].hidden == false) {
        // get a reference to the new document
        var docRef = open(fileList[i])

        // tag all of the documents with photo shoot information
        docRef.info.author = "Adobe programmer"
        docRef.info.caption = "Adobe Photo shoot"
        docRef.info.captionWriter = "Adobe programmer"
        docRef.info.city = "San Jose"
        docRef.info.copyrightNotice = "Copyright (c) Adobe programmer
            Photography"
        docRef.info.copyrighted = CopyrightedType.COPYRIGHTEDWORK
        docRef.info.country = "USA"
        docRef.info.provinceState = "CA"

        // change the date to a Adobe Photoshop CS5 date format
        // "YYYYMMDD"
        var theDate = new Date()
        // the year is from 1900 ???
        var theYear = (theDate.getYear() + 1900).toString()
        // convert the month from 0..12 to 00..12
        var theMonth = theDate.getMonth().toString()
        if (theDate.getMonth() < 10) {
            theMonth = "0" + theMonth
        }
        // convert the day from 0..31 to 00..31
        var theDay = theDate.getDate().toString()
        if (theDate.getDate() < 10) {
            theDay = "0" + theDay
        }
        // stick them all together
        docRef.info.creationDate = theYear + theMonth + theDay

        // flatten because we are saving to JPEG
        docRef.flatten()
        // go to 8 bit because we are saving to JPEG
        docRef.bitsPerChannel = BitsPerChannelType.EIGHT

        // save and close
        docRef.saveAs(new File(outputFolder + "/Output" + i + ".jpg"), jpegOptions)

        // don't modify the original
        docRef.close(SaveOptions.DONOTSAVECHANGES)
    }
}

// Reset the application preferences
app.displayDialogs = startDisplayDialogs
```

Documents

The collection of open [Document](#) objects.

Access this list through the [Application.documents](#) collection property, which is available through the `app` global variable, or directly at the top level. For example, the following adds a new document to the collection:

```
app.documents.add(800, 500, 72, "myDocument", NewDocumentMode.RGB)
```

—or—

```
documents.add(800, 500, 72, "myDocument", NewDocumentMode.RGB)
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>documents</code> collection.
parent	Application	Read-only. The containing application.
typename	string	Read-only. The class name of the referenced <code>documents</code> object.

Methods

Method	Parameter type	Returns	What it does
add ([width] [, height] [, resolution] [, name] [, mode] [, initialFill] [, pixelAspectRatio] [, bitsPerChannel] [, colorProfileName])	UnitValue UnitValue number string NewDocumentMode DocumentFill number [0.1..10.00] BitsPerChannelType string	Document	Creates a new document object and adds it to this collection. <code>pixelAspectRatio</code> : Default is 1.0, a square aspect ratio. <code>bitsPerChannelType</code> : Default is <code>BitsPerChannelType.EIGHT</code> .
getByName (name)	string	Document	Gets the first element in the <code>documents</code> collection with the provided name

EPSOpenOptions

Options for opening a document in EPS format using the [Application.open\(\)](#) method.

Properties

Property	Value type	What it is
antiAlias	boolean	Read-write. True to use antialias.
constrainProportions	boolean	Read-write. True to constrain the proportions of the image.
height	UnitValue	Read-write. The height of the image (unit value).
mode	OpenDocumentMode	Read-write. The color profile to use as the document mode.
resolution	number	Read-write. The resolution of the document in pixels per inch.
typename	string	Read-only. The class name of the referenced <code>EPSOpenOptions</code> object.
width	UnitValue	Read-write. The width of the image (unit value).

EPSSaveOptions

Options for saving a document in EPS format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
embedColorProfile	boolean	Read-write. True to embed the color profile in this document.
encoding	SaveEncoding	Read-write. The type of encoding to use (default: <code>SaveEncoding.BINARY</code>).
halftoneScreen	boolean	Read-write. True to include the halftone screen (default: <code>false</code>).
interpolation	boolean	Read-write. True to use image interpolation (default: <code>false</code>).
preview	Preview	Read-write. The preview type.
psColorManagement	boolean	Read-write. True to use Postscript color management (default: <code>false</code>).
transferFunction	boolean	Read-write. True to include the Transfer functions to compensate for dot gain between the image and film (default: <code>false</code>).
transparentWhites	boolean	Read-write. True to display white areas as transparent. Valid only when <code>document.mode</code> = <code>DocumentMode.BITMAP</code> . See also changeMode() .
typename	string	Read-only. The class name of the referenced <code>EPSSaveOptions</code> object.
vectorData	boolean	Read-write. True to include vector data. Valid only if the document includes vector data (text).

ExportOptionsIllustrator

Options for exporting [PathItem](#) objects to an Adobe Illustrator® file using using the [Document.exportDocument\(\)](#) method. These options are the options that you can provide when you choose **File > Export > Paths To Illustrator**.

Properties

Property	Value type	What it is
path	IllustratorPathType	Read-write. The type of path to export (default: <code>IllustratorPathType.DOCUMENTBOUNDS</code>).
pathName	string	Read-write. The name of the path to export. Valid only when path = <code>IllustratorPathType.NAMEDPATH</code> .
typename	string	Read-only. The class name of the referenced <code>exportOptionsIllustrator</code> object.

ExportOptionsSaveForWeb

Options for optimizing a document for the web or devices using the [Document.exportDocument\(\)](#) method. These are the options that you can provide when you choose **File > Save For Web and Devices**.

Properties

Property	Value type	What it is
blur	number	Read-write. Applies blur to the image to reduce artifacts (default: 0.0).
colorReduction	ColorReductionType	Read-write. The color reduction algorithm (default: <code>ColorReductionType.SELECTIVE</code>).
colors	number	Read-write. The number of colors in the palette (default: 256).
dither	Dither	Read-write. The type of dither (default: <code>Dither.DIFFUSION</code>).
ditherAmount	number	Read-write. The amount of dither (default: 100). Valid only when dither = <code>Dither.DIFFUSION</code> .
format	SaveDocumentType	Read-write. The file format to use (default: <code>SaveDocumentType.COMPUSEVEGIF</code>). Note: For this property, only <code>COMPUSEVEGIF</code> , <code>JPEG</code> , <code>PNG-8</code> , <code>PNG-24</code> , and <code>BMP</code> are supported.
includeProfile	boolean	Read-write. True to include the document's embedded color profile (default: <code>false</code>).
interlaced	boolean	Read-write. True to download in multiple passes; progressive (default: <code>false</code>).
lossy	number	Read-write. The amount of lossiness allowed (default: 0).
matteColor	RGBColor	Read-write. The colors to blend transparent pixels against.
optimized	boolean	Read-write. True to create smaller but less compatible files (default: <code>true</code>). Valid only when format = <code>SaveDocumentType.JPEG</code> .
PNG8	boolean	Read-write. Indicates the number of bits; <code>true</code> = 8, <code>false</code> = 24 (default: <code>true</code>). Valid only when format = <code>SaveDocumentType.PNG</code> .

Property	Value type	What it is (Continued)
quality	number [0..100]	Read-write. The quality of the produced image as a percentage; default: 60.
transparency	boolean	Read-write. Indication of transparent areas of the image should be included in the saved image(default: true).
transparencyAmount	number	Read-write. The amount of transparency dither (default: 100). Valid only if transparency = true.
transparencyDither	Dither	Read-write. The transparency dither algorithm (default: transparencyDither = Dither.NONE).
typename	string	Read-only. The class name of the referenced <code>ExportOptionsSaveForWeb</code> object.
webSnap	number	Read-write. The tolerance amount within which to snap close colors to web palette colors (default: 0).

File

Folder

ExtendScript defines the JavaScript classes `File` and `Folder` to encapsulate file-system references in a platform-independent manner; see ['JavaScript support in Adobe Photoshop CS5' on page 33](#). For references details of these classes, see the *JavaScript Tools Guide*.

GalleryBannerOptions

Options for the [bannerOptions](#) property of the [GalleryOptions](#) object.

Tip: You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
<code>contactInfo</code>	string	Read-write. The web photo gallery contact info.
<code>date</code>	string	Read-write. The web photo gallery date (default: current date).
<code>font</code>	GalleryFontType	Read-write. The font setting for the banner text (default: <code>GalleryFontType.ARIAL</code>).
<code>fontSize</code>	number [1..7]	Read-write. The font size for the banner text (default: 3).
<code>photographer</code>	string	Read-write. The web photo gallery photographer.
<code>siteName</code>	string	Read-write. The web photo gallery site name (default: <code>Adobe Web Photo Gallery</code>).
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryBannerOptions</code> object.

GalleryCustomColorOptions

Options for the [customColorOptions](#) property of the [GalleryOptions](#) object.

Tip: You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
<code>activeLinkColor</code>	RGBColor	Read-write. The color to use to indicate an active link.
<code>backgroundColor</code>	RGBColor	Read-write. The background color.
<code>bannerColor</code>	RGBColor	Read-write. The banner color.
<code>linkColor</code>	RGBColor	Read-write. The color to use to indicate a link.
<code>textColor</code>	RGBColor	Read-write. The text color.
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryCustomColorOptions</code> object.
<code>visitedLinkColor</code>	RGBColor	Read-write. The color to use to indicate a visited link.

GalleryImagesOptions

Options for the [imagesOptions](#) property of the [GalleryOptions](#) object.

Tip: You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
border	number [0..99]	Read-write. The size (in pixels) of the border that separates images (default: 0).
caption	boolean	Read-write. True to generate image captions (default: false).
dimension	number	Read-write. The resized image dimensions in pixels (default: 350). Valid only when resizeImages = true.
font	GalleryFontType	Read-write. The font to use for image captions (default: <code>GalleryFontType.ARIAL</code>).
fontSize	number [1..7]	Read-write. The font size for image captions (default: 3). Valid only when caption = true.
imageQuality	number [0..12]	Read-write. The quality setting for a JPEG image (default: 5).
includeCopyright	boolean	Read-write. True to include copyright information in captions (default: false). Valid only when caption = true.
includeCredits	boolean	Read-write. True to include the credits in image captions (default: false). Valid only when caption = true.
includeFilename	boolean	Read-write. True to include the file name in image captions (default: true). Valid only when caption = true.
includeTitle	boolean	Read-write. True to include the title in image captions (default: false). Valid only when caption = true.
numericLinks	boolean	Read-write. True to add numeric links (default: true).

Property	Value type	What it is (Continued)
resizeConstraint	GalleryConstrainType	Read-write. The image dimensions to constrain in the gallery image (default: <code>GalleryConstrainType.CONSTRAINBOTH</code>). Valid only when resizeImages = <code>true</code> .
resizeImages	boolean	Read-write. True to automatically resize images for placement on the gallery pages (default: <code>true</code>).
typename	string	Read-only. The class name of the referenced <code>galleryImagesOptions</code> object.

GalleryOptions

Options for a Web photo gallery, created with [Application.makePhotoGallery\(\)](#).

Tip: You can preserve default values for many of these properties by choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
<code>addSizeAttributes</code>	boolean	Read-write. True to add width and height attributes for images (default: <code>true</code>).
<code>bannerOptions</code>	GalleryBannerOptions	Read-write. The options related to banner settings.
<code>customColorOptions</code>	GalleryCustomColorOptions	Read-write. The options related to custom color settings.
<code>emailAddress</code>	string	Read-write. The email address to show on the web page.
<code>imagesOptions</code>	GalleryImagesOptions	Read-write. The options related to images settings.
<code>includeSubFolders</code>	boolean	Read-write. True to include all files found in sub folders of the input folder (default: <code>true</code>).
<code>layoutStyle</code>	string	Read-write. The style to use for laying out the web page (default: <code>Centered Frame 1 - Basic</code>).
<code>preserveAllMetadata</code>	boolean	Read-write. True to save metadata (default: <code>false</code>).
<code>securityOptions</code>	GallerySecurityOptions	Read-write. The options related to security settings.
<code>thumbnailOptions</code>	GalleryThumbnailOptions	Read-write. The options related to thumbnail image settings.
<code>typename</code>	string	Read-only. The class name of the referenced <code>galleryOptions</code> object.
<code>useShortExtension</code>	boolean	Read-write. True to use the short web page extension <code>.htm</code> . If false, use the web page extension <code>.html</code> (default: <code>true</code>).
<code>useUTF8Encoding</code>	boolean	Read-write. True to use UTF-8 encoding for the web page (default: <code>false</code>).

GallerySecurityOptions

Options for the [securityOptions](#) property of the [GalleryOptions](#) object.

Tip: You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
content	GallerySecurityType	Read-write. The web photo gallery security content (default: <code>GallerySecurityType.NONE</code>).
font	GalleryFontType	Read-write. The web photo gallery security font (default: <code>GalleryFontType.ARIAL</code>).
fontSize	number [1..72]	Read-write. The web photo gallery security font size (default: 3).
opacity	number	Read-write. The web page security opacity as a percent (default: 100).
text	string	Read-write. The web photo gallery security custom text.
textColor	GallerySecurityTextColorType	Read-write. The web page security text color.
textPosition	GallerySecurityTextPositionType	Read-write. The web photo gallery security text position (default: <code>GallerySecurityTextPositionType.CENTERED</code>).
textRotate	GallerySecurityTextRotateType	Read-write. The web photo gallery security text orientation to use (default: <code>GallerySecurityTextRotateType.ZERO</code>).
typename	string	Read-only. The class name of the referenced <code>gallerySecurityOptions</code> object.

GalleryThumbnailOptions

Options for the [thumbnailOptions](#) property of the [GalleryOptions](#) object.

Tip: You can preserve default values for many of these properties by setting the [GalleryOptions](#) property [preserveAllMetadata](#) to true; this is the same as choosing **File > Automate > Web Photo Gallery**, and then choosing **Preserve all metadata** in the Options area of the Web Photo Gallery dialog.

Properties

Property	Value type	What it is
border	number [0..99]	Read-write. The amount of border pixels you want around your thumbnail images (default: 0).
caption	boolean	Read-write. True if there is a caption (default: false).
columnCount	number	Read-write. The number of columns on the page (default: 5).
dimension	number	Read-write. The web photo gallery thumbnail dimension in pixels (default: 75).
font	GalleryFontType	Read-write. The web photo gallery font (default: <code>GalleryFontType.ARIAL</code>).
fontSize	number [1..7]	Read-write. The font size for thumbnail images text (default: 3).
includeCopyright	boolean	Read-write. True to include copyright information for thumbnails (default: false).
includeCredits	boolean	Read-write. True to include credits for thumbnails (default: false).
includeFilename	boolean	Read-write. True to include file names for thumbnails (default: false).
includeTitle	boolean	Read-write. True to include titles for thumbnails (default: false).
rowCount	number	Read-write. The number of rows on the page (default: 3).
size	GalleryThumbSizeType	Read-write. The thumbnail image size (default: <code>GalleryThumbSizeType.MEDIUM</code>).
typename	string	Read-only. The class name of the referenced <code>GalleryThumbnailOptions</code> object.

GIFSaveOptions

Options for saving a document in GIF format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
colors	number	Read-write. The number of palette colors. Valid only when palette = <code>Palette.LOCALADAPTIVE</code> , <code>LOCALPERCEPTUAL</code> , <code>LOCALSELECTIVE</code> , <code>MACOSPALETTE</code> , <code>UNIFORM</code> , <code>WEBPALETTE</code> ; or <code>WINDOWSPALETTE</code> .
dither	Dither	Read-write. The dither type.
ditherAmount	number [1..100]	Read-write. The amount of dither (default: 75). Valid only when dither = <code>Dither.DIFFUSION</code> .
forced	ForcedColors	Read-write. The type of colors to force into the color palette.
interlaced	boolean	Read-write. True if rows should be interlaced (default: <code>false</code>).
matte	MatteType	Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code>). When transparency = <code>false</code> , the matte color is applied to transparent areas.
palette	PaletteType	Read-write. The type of palette to use (default: <code>Palette.LOCALSELECTIVE</code>).
preserveExactColors	boolean	Read-write. True to protect colors in the image that contain entries in the color table from being dithered. Valid only when dither = <code>Dither.DIFFUSION</code> .
transparency	boolean	Read-write. True to preserve transparent areas of the image during conversion to GIF format.
typename	string	Read-only. The class name of the referenced <code>GIFSaveOptions</code> object.

GrayColor

Defines a gray color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [HSBColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

Properties

Property	Value type	What it is
gray	number [0.0..100.0]	Read-write. The gray value (default: 0.0).
typename	string	Read-only. The class name of the referenced <code>grayColor</code> object.

Guide

Properties

Property	Value type	What it is
direction	Direction	Read-write. Indicates whether the guide is vertical or horizontal.
coordinate	UnitValue	Read-write. Location of the guide from origin of image.

Guides

The collection of open [Guide](#) objects.

Access this list through the [Document.guides](#) collection property, which is available through the `activeDocument` object. For example, the following adds a new guide to the collection:

```
activeDocument.guides.add (Direction.HORIZONTAL,UnitValue(20,20))
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>guides</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>guides</code> object.

Methods

Method	Parameter type	Returns	What it does
add (direction , coordinate)	Direction UnitValue	Guide	Creates a new guide object and adds it to this collection.
getByName (name)	string	Guide	Gets the first element in the <code>guides</code> collection with the provided name

HistoryState

A version of the document stored automatically (and added to the [HistoryStates](#) collection), which preserves the document's state, each time the document is changed.

Access through [Document.historyStates](#) collection. You can access a state in the list by name. For example, this assigns a property value in the state object named "AddLayerMask":

```
var stateRef = app.activeDocument.historyState.getByName("AddLayerMask");  
stateRef.snapshot = true;
```

Properties

Property	Value type	What it is
name	string	Read-only. The HistoryState object's name.
parent	Document	Read-only. The containing document.
snapshot	boolean	Read-only. True if the history state is a snapshot.
typename	string	Read-only. The class name of the referenced HistoryState object.

HistoryStates

The collection of [Guide](#) objects in the document.

Access through [Document.historyStates](#) collection property. For example, this accesses one of the states in the collection by index:

```
myState = app.activeDocument.historyStates[7];
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>HistoryStates</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>HistoryStates</code> object.

Methods

Method	Parameter type	Returns	What it does
getByName (name)	string	Guide	Get the first element in the <code>HistoryStates</code> collection with the provided name.

HSBColor

Defines an HSB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [LabColor](#), [NoColor](#), [RGBColor](#)

Properties

Property	Value type	What it is
brightness	number [0.0..100.0]	Read-write. The brightness value.
hue	number [0.0..360.0]	Read-write. The hue value.
saturation	number [0.0..100.0]	Read-write. The saturation value.
typename	string	Read-only. The class name of the referenced <code>HSBColor</code> object.

IndexedConversionOptions

Options for converting an RGB image to an indexed color model using [Document.changeMode\(\)](#).

Properties

Property	Value type	What it is
colors	number	Read-write. The number of palette colors. Valid only when palette = <code>Palette.LOCALADAPTIVE</code> , <code>LOCALPERCEPTUAL</code> , <code>LOCALSELECTIVE</code> , <code>MACOSPALETTE</code> , <code>UNIFORM</code> , <code>WEBPALETTE</code> , or <code>WINDOWSPALETTE</code> .
dither	Dither	Read-write. The dither type.
ditherAmount	number [1..100]	Read-write. The amount of dither. Valid only when dither = <code>Dither.diffusion</code> .
forced	ForcedColors	Read-write. The type of colors to force into the color palette.
matte	MatteType	Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code>). When transparency = <code>false</code> , the matte color is applied to transparent areas.
palette	PaletteType	Read-write. The palette type (default: <code>Palette.EXACT</code>).
preserveExactColors	boolean	Read-write. True to protect colors in the image that contain entries in the color table from being dithered. Valid only when dither = <code>Dither.DIFFUSION</code> .
transparency	boolean	Read-write. True to preserve transparent areas of the image during conversion to GIF format.
typename	string	Read-only. The class name of the referenced <code>IndexedConversionOptions</code> object.

JPEGSaveOptions

Options for saving a document in JPEG format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
formatOptions	FormatOptions	Read-write. The download format to use (default: <code>FormatOptions.STANDARDBASELINE</code>).
matte	MatteType	<p>Read-write. The color to use to fill anti-aliased edges adjacent to transparent areas of the image (default: <code>MatteType.WHITE</code>).</p> <p>When transparency is turned off for an image, the matte color is applied to transparent areas.</p>
quality	number [0..12]	Read-write. The image quality setting to use; affects file size and compression (default: 3).
scans	number [3..5]	<p>Read-write. The number of scans to make to incrementally display the image on the page (default: 3).</p> <p>Valid only for when formatOptions = <code>FormatOptions.PROGRESSIVE</code>.</p>
typename	string	Read-only. The class name of the referenced <code>JPEGSaveOptions</code> object.

LabColor

Defines an LAB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [NoColor](#), [RGBColor](#)

Properties

Property	Value type	What it is
a	number [-128.0..127.0]	Read-write. The a-value.
b	number [-128.0..127.0]	Read-write. The b-value.
l	number [0.0..100.0]	Read-write. The L-value.
typename	string	Read-only. The class name of the referenced <code>LabColor</code> object.

LayerComp

A snapshot of a state of the layers in a document, which can be used to view different page layouts or compositions.

Access through [Document.layerComps](#) collection. You can access a layer comp by its name. For example, this sets the `comment` property value for a `LayerComp` object named `myLayerComp`:

```
var layercompRef = app.activeDocument.layerComps.getByName("myLayerComp");  
layercompRef.comment = "View from shoreline";
```

Properties

Property	Value type	What it is
appearance	boolean	Read-write. True to use layer appearance (layer styles) settings.
comment	string	Read-write. A description of the layer comp.
name	string	Read-write. The name of the layer comp.
parent	Document	Read-write. The containing document.
position	boolean	Read-write. True to use layer position.
selected	boolean	Read-only. True if the layer comp is currently selected.
typename	string	Read-only. The class name of the referenced <code>layerComp</code> object.
visibility	boolean	Read-write. True to use layer visibility settings .

Methods

Method	Parameter type	Returns	What it does
apply ()			Applies the layer comp to the document.
recapture ()			Recaptures the current layer state(s) for this layer comp.
remove ()			Deletes the <code>layerComp</code> object.
resetfromComp ()			Resets the layer comp state to the document state.

LayerComps

The collection of [LayerComp](#) objects in the document.

Access through the [Document.layerComps](#) collection property. For example:

```
app.activeDocument.layerComps.add("myLayerComp", "View from Shoreline",  
    true, true, true);
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>layerComps</code> collection.
parent	Document	Read-only. The containing document.
typename	string	Read-only. The class name of the referenced <code>layerComps</code> object.

Methods

Method	Parameter type	Returns	What it does
add (name, comment, appearance, position, visibility)	string string boolean boolean boolean	LayerComp	Creates a new layer composition object and adds it to this collection.
getByName (name)	string	LayerComp	Gets the first element in the collection with the provided name.
removeAll ()			Removes all member objects from the <code>layerComps</code> collection.

Layers

The collection of layer objects, including [ArtLayer](#) and [LayerSet](#) objects, in the document. Access through [Document.layers](#), or the [LayerSet.layers](#) collections properties.

For example, this uses the `length` property to count the number of `layer` objects in the active document, then displays the number on the screen:

```
var layerNum = app.activeDocument.layers.length
alert(layerNum)
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>layers</code> collection.
parent	Document or LayerSet	Read-only. The containing document or layer set.
typename	string	Read-only. The class name of the referenced <code>layers</code> object.

Methods

Method	Parameter type	Returns	What it does
getByName (name)	string	Layer	Gets the first element in the <code>layers</code> collection with the provided name.
removeAll ()			Removes all layers from the collection.

LayerSet

A group of layer objects, which can include [ArtLayer](#) objects and other (nested) `LayerSet` objects. A single command can manipulate all layers in the set.

Access top-level layers sets in a document through the [Document.layerSets](#) collection. You can access a layer set by name. For example, the following sets the `allLocked` value for "myLayerSet":

```
var layerSetRef = app.activeDocument.layerSets.getByName("myLayerSet");
layerSetRef.allLocked = true
```

Access nested layer sets through the [LayerSet.layerSets](#) collection in the parent set. For example:

```
app.activeDocument.layerSets[0].layerSets[0];
```

Properties

Property	Value type	What it is
<code>allLocked</code>	boolean	Read-write. True if the contents in the layers in this set are not editable.
<code>artLayers</code>	ArtLayers	Read-only. The art layers in this layer set.
<code>blendMode</code>	BlendMode	Read-write. The blend mode to use for the layer set.
<code>bounds</code>	array of UnitValue	Read-only. The bounding rectangle of the layer set.
<code>enabledChannels</code>	array of Channel	Read-write. The channels enabled for the layer set; must be a list of component channels. See Channel.kind .
<code>layers</code>	Layers	Read-only. The layers in this layer set.
<code>layerSets</code>	LayerSets	Read-only. Nested layer sets contained within this layer set.
<code>linkedLayers</code>	array of ArtLayer and/or LayerSet	Read-only. The layers linked to this <code>layerSet</code> object.
<code>name</code>	string	Read-write. The name of this layer set.
<code>opacity</code>	number [0.0..100.0]	Read-write. The master opacity of the set.
<code>parent</code>	Document or LayerSet	Read-only. The containing document or layer set.
<code>typename</code>	string	Read-only. The class name of the referenced <code>LayerSet</code> object.
<code>visible</code>	boolean	Read-write. True if the set is visible.

Methods

Method	Parameter type	Returns	What it does
duplicate ([relativeObject] [, insertionLocation])	ArtLayer or LayerSet ElementPlacement	LayerSet	Creates a duplicate of the object.
link (with)	ArtLayer or LayerSet		Links the layer set with another layer.
merge ()		ArtLayer	Merges the layerset; returns a reference to the art layer created by this method.
move (relativeObject, insertionLocation)	ArtLayer or LayerSet ElementPlacement		Moves the object.
remove ()			Deletes the object.
resize ([horizontal] [, vertical] [, anchor])	number number AnchorPosition		Resizes all layers in the layer set to the specified dimensions (as a percentage of its current size) and places the layer set in the specified position.
rotate (angle [, anchor])	number AnchorPosition		Rotates all layers in the layer set around the specified anchor point (default: <code>AnchorPosition.MIDDLECENTER</code>)
translate ([deltaX] [, deltaY])	UnitValue UnitValue		Moves the position relative to its current position.
unlink ()			Unlinks the layer set.

LayerSets

The collection of [LayerSet](#) objects in the document.

Access the top-level layer sets in a document through the [Document.layerSets](#) collection property. For example:

```
var layerSetRef = app.activeDocument.layerSets.add()
```

Access the nested layer sets through the [LayerSet.layerSets](#) collection property in the parent set. For example:

```
var layerSetRef = app.activeDocument.layerSets.getByName("myParentSet");  
var childSet = layerSetRef.layerSets.getByName("myChildSet");
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>LayerSets</code> collection.
parent	Document or LayerSet	Read-only. The containing document or layer set.
typename	string	Read-only. The class name of the referenced <code>layerSets</code> object.

Methods

Method	Parameter type	Returns	What it does
add ()		LayerSet	Creates a new layer set object and adds it to the collection.
getByName (name)	string	LayerSet	Gets the first element in the collection with the provided name.
removeAll ()			Removes all member layer sets, and any layers or layer sets they contain, from the document.

LayerSets sample script

The following script creates three layer sets, then nests a second layer set in each layer set, and then creates a text layer in each nested set that displays the text "Layer in *n* Set Inside *n* Set", where *n* represents the ordinal number of the set (first, second, or third).

Note: This script uses the ExtendScript `$` debugging object. For further details, see the *JavaScript Tools Guide*.

LayerSets.jsx

```
$.level = 1  
  
//close all open documents  
while (app.documents.length) {
```

```
    app.activeDocument.close()
}

// create a working document
var docRef = app.documents.add()

// create an array to hold the layer sets
var myLayerSets = new Array()

// Create an array to hold the text
var textArray = Array("First", "Second", "Third")

//Create an indexer variable
var i = 0

// Create three layer sets at the top level
for (i = 0; i < 3; i++) {
    myLayerSets[i] = new Array()
    myLayerSets[i][0] = docRef.layerSets.add()
}

// Rearrange the layer sets with the first one on top, second next, etc.
myLayerSets[1][0].moveAfter(myLayerSets[0][0])
myLayerSets[2][0].moveAfter(myLayerSets[1][0])

// Create a layer set inside each layer set
for (i = 0; i < 3; i++) {
    myLayerSets[i][0].name = textArray[i] + " Set"
    myLayerSets[i][1] = myLayerSets[i][0].layerSets.add()
    myLayerSets[i][1].name = "Inside " + textArray[i] + " Set"
}

// Create an array to hold the layers
var myLayers = new Array()

// Create a text layer with a description inside each layer set
for (i = 0; i < 3; i++) {
    myLayers[i] = myLayerSets[i][1].artLayers.add()
    myLayers[i].kind = LayerKind.TEXT
    myLayers[i].textItem.contents = "Layer in " + textArray[i] + " Set Inside "
        + textArray[i] + " Set"
    myLayers[i].textItem.position = Array(app.activeDocument.width * i * 0.33,
        app.activeDocument.height * (i + 1) * 0.25)
    myLayers[i].textItem.size = 12
}
```

MeasurementLog

The measurement log for the application. Access through the [Application.measurementLog](#) property.

Note: This feature is available in the Extended Version only.

Methods

Method	Parameter type	Returns	What it does
exportMeasurements ([file] [, range] [, dataPoints])	File MeasurementRange array of string		Export measurement to a file.
deleteMeasurements ([range])	MeasurementRange		Delete measurements from the log.

MeasurementScale

The measurement scale for the document. Access through the [Document.measurementScale](#) property. For example:

```
app.activeDocument.measurementScale.pixelLength = 25
```

Note: This feature is available in the Extended Version only.

Properties

Property	Value type	What it is
<code>pixelLength</code>	number	Read-write. The length in pixels this scale equates to.
<code>logicalLength</code>	number	Read-write. The logical length this scale equates to.
<code>logicalUnits</code>	string	Read-write. The logical units for this scale.

NoColor

Represents a missing color object, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [LabColor](#), [RGBColor](#)

Properties

Property	Value type	What it is
<code>typename</code>	string	Read-only. The class name of the referenced <code>noColor</code> object.

Notifier

An event-handler object that tells a script to execute specified code when a specified event occurs. Notifiers must be enabled using the [Application.notifiersEnabled](#) property.

Access through the [Application.notifiers](#) collection.

Note: Events that occur within scripts do not generally trigger notifiers, because they occur inside a "play script" event.

Properties

Property	Value type	What it is
event	string	Read-only. The event identifier, a four-character code or a unique string. For a list of four-character codes, see Appendix A: Event ID Codes .
eventClass	string	Read-only. The class identifier, a four-character code or a unique string. When an event applies to multiple types of objects, use this property to distinguish which object this notifier applies to. For example, the Make event ("Mk ") can apply to documents ("Dcmn"), channels ("Chnl") and other objects.
eventFile	File	Read-only. The path to the file to execute when the event occurs and activates the notifier.
parent	Application	Read-only. The containing application.
typename	string	Read-only. The class name of the referenced object.

Methods

Method	Parameter type	Returns	What it does
remove ()			Deletes this object. You can also remove a <code>Notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from the Photoshop preferences folder. See Adobe Photoshop CS5 help for more information.

Notifiers

The collection of [Notifier](#) objects in the document. Access through the [Application.notifiers](#) collection property. For example:

```
var notRef = app.notifiers.add("OnClickGoButton", eventFile)
```

Notifiers must be enabled using the [Application.notifiersEnabled](#) property.

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the <code>notifiers</code> collection.
parent	Application	Read-only. The <code>notifiers</code> object's container
typename	string	Read-only. The class name of the referenced <code>notifiers</code> object.

Methods

Method	Parameter type	Returns	What it does
add (event, eventFile [, eventClass])	string File string	Notifier	<p>Creates a notifier object and adds it to this collection.</p> <p><code>event</code> defines the class ID of the event: use a 4-characters code or a unique string. See Appendix A: Event ID Codes.</p> <p><code>eventFile</code> defines the script file that executes when the event occurs.</p> <p>When an event applies to multiple types of objects, use the <code>eventClass</code> (a 4-character ID or unique string) to distinguish which object this <code>Notifier</code> applies to. For example, the Make event ("Mk ") applies to documents ("Dcmn"), channels ("Chnl") and other objects.</p> <p>Tip: When specifying an event or event calss wtih a 4-character ID code, omit the single quotes in your code.</p>
removeAll ()			<p>Removes all member objects from the <code>notifiers</code> collection.</p> <p>You can also remove a <code>notifier</code> object from the Script Events Manager drop-down list by deleting the file named <code>Script Events Manager.xml</code> from the Photoshop preferences folder. See Adobe Photoshop CS5 help for more information.</p>

PathItem

A path or drawing object, such as the outline of a shape or a straight or curved line, which contains sub paths that define its geometry.

Access through the collection in the [Document.pathItems](#) property. For example, this selects a named path item:

```
var currentPathItem = app.activeDocument.pathItems.getByName("myPath");
currentPathItem.select();
```

Create these objects by passing a set of [SubPathInfo](#) objects to the [PathItems.add\(\)](#) method. This method creates a [SubPathItem](#) object for each [SubPathInfo](#) object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths.

Properties

Property	Value type	What it is
kind	PathKind	Read-write. The type.
name	string	Read-write. The name.
parent	Document	Read-only. The containing document.
subPathItems	SubPathItems	Read-only. The contained sub-path objects.
typename	string	Read-only. The class name of the referenced <code>pathItem</code> object.

Methods

Method	Parameter type	Returns	What it does
deselect ()			Deselects this <code>pathItem</code> object.
duplicate (name)	string		Duplicates this <code>pathItem</code> object with the new name.
fillPath ([fillColor] [, mode] [, opacity] [, preserveTransparency] [, feather] [, wholePath] [, antiAlias])	SolidColor ColorBlendMode number [0..100] boolean number [0.0..250.0] boolean boolean		Fills the area enclosed by this path. <code>opacity</code> is a percentage. <code>feather</code> is in pixels. If <code>wholePath</code> is true, all subpaths are used when doing the fill (default: true).

Method	Parameter type	Returns	What it does
makeClippingPath ([flatness])	number [0.2..100]		Makes this the clipping path for this document. <i>flatness</i> tells the PostScript printer how to approximate curves in the path.
makeSelection ([feather] [, antiAlias] [, operation])	number [0.0..250.0] boolean SelectionType		Makes a Selection object whose border is this path. <i>feather</i> is in pixels.
remove ()			Deletes this object.
select ()			Makes this the active or selected PathItem object.
strokePath ([tool] [, simulatePressure])	ToolType boolean		Strokes the path with the specified tool.

PathItem sample script

The following creates a path in three segments: two diagonal lines that form a V, and a curved line above the V that makes it look like a 2D ice cream cone.

Paths.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

// first close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

// create a document to work with
var docRef = app.documents.add(5000, 7000, 72, "Simple Line")

//line 1--it's a straight line so the coordinates for anchor, left, and right
//for each point have the same coordinates
var lineArray = new Array()
    lineArray[0] = new PathPointInfo
    lineArray[0].kind = PointKind.CORNERPOINT
    lineArray[0].anchor = Array(100, 100)
```

```
lineArray[0].leftDirection = lineArray[0].anchor
lineArray[0].rightDirection = lineArray[0].anchor

lineArray[1] = new PathPointInfo
lineArray[1].kind = PointKind.CORNERPOINT
lineArray[1].anchor = Array(150, 200)
lineArray[1].leftDirection = lineArray[1].anchor
lineArray[1].rightDirection = lineArray[1].anchor

var lineSubPathArray = new Array()
lineSubPathArray[0] = new SubPathInfo()
lineSubPathArray[0].operation = ShapeOperation.SHAPEXOR
lineSubPathArray[0].closed = false
lineSubPathArray[0].entireSubPath = lineArray

// line 2
var lineArray2 = new Array()
lineArray2[0] = new PathPointInfo
lineArray2[0].kind = PointKind.CORNERPOINT
lineArray2[0].anchor = Array(150, 200)
lineArray2[0].leftDirection = lineArray2[0].anchor
lineArray2[0].rightDirection = lineArray2[0].anchor

lineArray2[1] = new PathPointInfo
lineArray2[1].kind = PointKind.CORNERPOINT
lineArray2[1].anchor = Array(200, 100)
lineArray2[1].leftDirection = lineArray2[1].anchor
lineArray2[1].rightDirection = lineArray2[1].anchor

lineSubPathArray[1] = new SubPathInfo()
lineSubPathArray[1].operation = ShapeOperation.SHAPEXOR
lineSubPathArray[1].closed = false
lineSubPathArray[1].entireSubPath = lineArray2

//ice cream curve
//it's a curved line, so there are 3 points, not 2
//coordinates for the middle point (lineArray3[1]) are different.
//The left direction is positioned "above" the anchor on the screen.
//The right direction is positioned "below" the anchor
//You can change the coordinates for these points to see
//how the curve works...
var lineArray3 = new Array()
lineArray3[0] = new PathPointInfo
lineArray3[0].kind = PointKind.CORNERPOINT
lineArray3[0].anchor = Array(200, 100)
lineArray3[0].leftDirection = lineArray3[0].anchor
lineArray3[0].rightDirection = lineArray3[0].anchor

lineArray3[1] = new PathPointInfo
lineArray3[1].kind = PointKind.CORNERPOINT
lineArray3[1].anchor = Array(150, 50)
lineArray3[1].leftDirection = Array(100, 50)
lineArray3[1].rightDirection = Array(200, 50)

lineArray3[2] = new PathPointInfo
lineArray3[2].kind = PointKind.CORNERPOINT
lineArray3[2].anchor = Array(100, 100)
lineArray3[2].leftDirection = lineArray3[2].anchor
lineArray3[2].rightDirection = lineArray3[2].anchor
```

```
    lineSubPathArray[2] = new SubPathInfo()
    lineSubPathArray[2].operation = ShapeOperation.SHAPEXOR
    lineSubPathArray[2].closed = false
    lineSubPathArray[2].entireSubPath = lineArray3

//create the path item
var myPathItem = docRef.pathItems.add("A Line", lineSubPathArray)

// stroke it so we can see something
myPathItem.strokePath(ToolType.BRUSH)

// Reset the application preferences
preferences.rulerUnits = startRulerUnits
preferences.typeUnits = startTypeUnits
displayDialogs = startDisplayDialogs
```

PathItems

The collection of [PathItem](#) objects in a document.

Access through the [Document.pathItems](#) collection property. For example, this creates a new path item using a previously-defined set of subpaths:

```
app.activeDocument.pathItems.add("myPath", lineSubPathInfoArray);
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of <code>pathItem</code> objects in the <code>pathItems</code> collection.
parent	Document	Read-only. The <code>pathItems</code> object's container.
typename	string	Read-only. The class name of the referenced <code>pathItems</code> object.

Methods

Method	Parameter type	Returns	What it does
add (name, entirePath)	string array of SubPathInfo	PathItem	Creates a new path item object and adds it to this collection. A new SubPathItem object is created for each <code>SubPathInfo</code> object provided in <code>entirePath</code> , and those <code>SubPathItem</code> objects are added to the subPathItems collection of the returned PathItem .
getByName (name)	string	PathItem	Get the first element in the <code>pathItems</code> collection with the provided name.
removeAll ()			Removes all <code>pathItem</code> objects from the <code>pathItems</code> collection.

PathPoint

Represents the anchor and control-handle endpoints for a path segment. Each point (the anchor point, left-direction point, and right-direction point) is an array containing X and Y position coordinates.

- Use the `PathPoint` object to retrieve information about the points that describe existing path segments. The properties are read-only. Access [PathPoint](#) objects through the [SubPathItem.pathPoints](#) property.
- Use [PathPointInfo](#) with [PathItems.add\(\)](#) to create path points. The properties are writeable.

For paths that are straight segments (not curved), the coordinates of all three points are the same. For curved segments, the the coordinates are different. The difference between the anchor point and the left or right direction points determines the arc of the curve. You use the left direction point to bend the curve "outward" or make it convex; you use the right direction point to bend the curve "inward" or make it concave.

Properties

Property	Value type	What it is
anchor	array of number	Read-only. The X and Y coordinates of the anchor point of the curve.
kind	PointKind	Read-only. The role (corner or smooth) this point plays in the containing path segment.
leftDirection	array of number	Read-only. The location of the left-direction endpoint ('in' position).
parent	SubPathItem	Read-only. The containing subpath object.
rightDirection	array of number	Read-only. The location of the right-direction endpoint ('out' position).
typename	string	Read-only. The class name of the referenced <code>PathPoint</code> object.

PathPointInfo

Used to create a [PathPoint](#), which represents the anchor and control-handle endpoints for a path segment. Each point (the anchor point, left-direction point, and right-direction point) is an array containing X and Y position coordinates.

- Use the JavaScript `new` operator to create these objects, and store them in the [SubPathInfo.entireSubPath](#) property before using that object to create a path item with [PathItems.add\(\)](#).
See the [PathPointInfo sample script](#) below.
- The resulting [SubPathItem](#) objects contain the resulting [PathPoint](#) objects. Use the [PathPoint](#) object to retrieve information about the points that describe existing path segments. The properties are read-only.

For paths that are straight segments (not curved), the coordinates of all three points are the same. For curved segments, the the coordinates are different. The difference between the anchor point and the left or right direction points determines the arc of the curve. You use the left direction point to bend the curve "outward" or make it convex; you use the right direction point to bend the curve "inward" or make it concave.

Properties

Property	Value type	What it is
anchor	array of number	Read-write. The X and Y coordinates of the anchor point of the curve.
kind	PointKind	Read-write. The role (corner or smooth) this point plays in the containing path segment.
leftDirection	array of number	Read-write. The location of the left-direction endpoint ('in' position).
rightDirection	array of number	Read-write. The location of the right-direction endpoint ('out' position).
typename	string	Read-only. The class name of the referenced <code>PathPointInfo</code> object.

PathPointInfo sample script

```
function drawLine(doc, start, stop) {  
  
    var startPoint = new PathPointInfo();  
    startPoint.anchor = start;  
    startPoint.leftDirection = start;  
    startPoint.rightDirection = start;  
    startPoint.kind = PointKind.CORNERPOINT;  
  
    var stopPoint = new PathPointInfo();  
    stopPoint.anchor = stop;  
    stopPoint.leftDirection = stop;  
    stopPoint.rightDirection = stop;  
    stopPoint.kind = PointKind.CORNERPOINT;  
}
```

```
var spi = new SubPathInfo();
spi.closed = false;
spi.operation = ShapeOperation.SHAPEXOR;
spi.entireSubPath = [startPoint, stopPoint];

var line = doc.pathItems.add("Line", [spi]);
line.strokePath(ToolType.PENCIL);
line.remove();
};

drawLine(app.activeDocument, [100,100], [200,200]);
```

PathPoints

A collection of [PathPoint](#) objects that define a subpath, kept in the [SubPathItem.pathPoints](#) property.

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the collection.
parent	SubPathItem	Read-only. The containing subpath object.
typename	string	Read-only. The class name of the referenced <code>PathPoints</code> object.

PDFOpenOptions

Options for opening a document in generic Adobe PDF format using the [Application.open\(\)](#) method.

Properties

Property	Value type	What it is
antiAlias	boolean	Read-write. True to use antialias.
bitsPerChannel	BitsPerChannelType	Read-write. The number of bits per channel.
constrainProportions	boolean	DEPRECATED for Adobe Photoshop CS5.
cropPage	CropToType	Read-write. The method of cropping to use.
height	UnitValue	DEPRECATED for Adobe Photoshop CS5.
mode	OpenDocumentMode	Read-write. The color model to use.
name	string	Read-write. The name of the object.
page	number	Read-write. The page or image to which to open the document, depending on the value of usePageNumber .
resolution	number	Read-write. The resolution of the document (in pixels per inch).
suppressWarnings	boolean	Read-write. True to suppress warnings when opening the document.
typename	string	Read-only. The class name of the referenced <code>PDFOpenOptions</code> object.
usePageNumber	boolean	Read-write. When true, the page property refers to a page number; when false, it refers to an image number.
width	UnitValue	DEPRECATED for Adobe Photoshop CS5.

PDFSaveOptions

Options for saving a document in Adobe PDF format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels with the file.
annotations	boolean	Read-write. True to save comments with the file.
colorConversion	boolean	Read-write. True to convert the color profile to a destination profile.
convertToEightBit	boolean	Read-write. True to convert a 16-bit image to 8-bit for better compatibility with other applications.
description	string	Read-write. Description of the save options to use.
destinationProfile	string	Read-write. Description of the final RGB or CMYK output device, such as a monitor or a press standard.
downgradeColorProfile	boolean	DEPRECATED for Adobe Photoshop CS5.
downSample	PDFResample	Read-write. The down sample method to use.
downSampleSize	number	Read-write. The size to downsample images if they exceed the limit in pixels per inch.
downSampleSizeLimit	number	Read-write. Limits downsampling or subsampling to images that exceed this value in pixels per inch.
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
embedFonts	boolean	DEPRECATED for Adobe Photoshop CS5.
embedThumbnail	boolean	Read-write. True to include a small preview image in Adobe PDF files.
encoding	PDFEncoding	Read-write. The type of compression to use (default: <code>PDFEncoding.PDFZIP</code>).
interpolation	boolean	DEPRECATED for Adobe Photoshop CS5.

Property	Value type	What it is (Continued)
jpegQuality	number [0..12]	Read-write. The quality of the produced image, which is inversely proportionate to the compression amount. Valid only when encoding = <code>PDFEncoding.JPEG</code> .
layers	boolean	Read-write. True to save the document's layers.
optimizeForWeb	boolean	Read-write. True to improve performance of PDF files on Web servers.
outputCondition	string	Read-write. An optional comment field for inserting descriptions of the output condition. The text is stored in the PDF/X file.
outputConditionID	string	Read-write. Identifier for the output condition.
PDFCompatibility	PDFCompatibility	Read-write. The PDF version to make the document compatible with.
PDFStandard	PDFStandard	Read-write. The PDF standard to make the document compatible with.
preserveEditing	boolean	Read-write. True to reopen the PDF in Adobe Photoshop CS5 with native Photoshop data intact.
presetFile	string	Read-write. The preset file to use for settings. Note: This option overrides other settings.
profileInclusionPolicy	boolean	Read-write. True to show which profiles to include.
registryName	string	Read-write. URL where the output condition is registered.
spotColors	boolean	Read-write. True to save spot colors.
tileSize	number	Read-write. Compression option. Valid only when encoding = <code>PDFEncoding.JPEG2000</code> .
transparency	boolean	DEPRECATED for Adobe Photoshop CS5.
typename	string	Read-only. The class name of the referenced <code>PDFSaveOptions</code> object.
useOutlines	boolean	DEPRECATED for Adobe Photoshop CS5.

Property	Value type	What it is (Continued)
vectorData	boolean	DEPRECATED for Adobe Photoshop CS5.
view	boolean	Read-write. True to open the saved PDF in Adobe Acrobat.

PhotoCDOpenOptions

DEPRECATED in Adobe Photoshop CS5. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.

Options for opening a document in Kodak Photo CD (PCD) format (including high-resolution files from Pro Photo CD discs) using the [Application.open\(\)](#) method.

Properties

Property	Value type	What it is
colorProfileName	string	Read-write. The profile to use when reading the image.
colorSpace	PhotoCDColorSpace	Read-write. The colorspace for the image.
orientation	Orientation	Read-write. The image orientation.
pixelSize	PhotoCDSIZE	Read-write. The image dimensions.
resolution	number	Read-write. The image resolution (in pixels per inch).
typename	string	Read-only. The class name of the referenced <code>photoCDOpenOptions</code> object.

PhotoshopSaveOptions

Options for saving a document in PSD format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
annotations	boolean	Read-write. True to save the annotations.
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
layers	boolean	Read-write. True to preserve the layers.
spotColors	boolean	Read-write. True to save the spot colors.
typename	string	Read-only. The class name of the referenced <code>photoshopSaveOptions</code> object.

PICTFileSaveOptions

Options for saving a document in PICT format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
compression	PICTCompression	Read-write. The type of compression to use (default: <code>PICTCompression.NONE</code>).
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
resolution	PICTBitsPerPixels	Read-write. The number of bits per pixel.
typename	string	Read-only. The class name of the referenced <code>PICTFileSaveOptions</code> object.

PICTResourceSaveOptions

Options for saving a document as a PICT Resource file using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
compression	PICTCompression	Read-write. The type of compression to use (default: <code>PICTCompression.NONE</code>).
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
name	string	Read-write. The name of the PICT resource.
resolution	PICTBitsPerPixels	Read-write. The number of bits per pixel.
resourceID	number	Read-write. The ID of the PICT resource (default: 128).
typename	string	Read-only. The class name of the referenced <code>PICTResourceSaveOptions</code> object.

PicturePackageOptions

Options for a picture package created with [Application.makePicturePackage\(\)](#).

Properties

Property	Value type	What it is
content	PicturePackageTextType	Read-write. The content information (default: <code>PicturePackageTextType.NONE</code>).
flatten	boolean	Read-write. True if all layers in the final document are flattened (default: <code>true</code>).
font	GalleryFontType	Read-write. The font used for security text (default: <code>GalleryFontType.ARIAL</code>).
fontSize	number	Read-write. The font size used for security text (default: 12).
layout	string	Read-write. The layout to use to generate the picture package (default: "(2) 5x7").
mode	NewDocumentMode	Read-write. Read-write. The color profile to use as the document mode (default: <code>NewDocumentMode.RGB</code>).
opacity	number	Read-write. The web page security opacity as a percent (default: 100).
resolution	number	Read-write. The resolution of the document in pixels per inch (default: 72.0).
text	string	Read-write. The picture package custom text. Valid only when content = <code>PicturePackageType.USER</code> .
textColor	RGBColor	Read-write. The color to use for security text.
textPosition	GallerySecurityTextPositionType	Read-write. The security text position (default: <code>GallerySecurityTextPositionType.CENTERED</code>).
textRotate	GallerySecurityTextRotateType	Read-write. The orientation to use for security text (default: <code>GallerySecurityTextRotateType.ZERO</code>).
typename	string	Read-only. The class name of the referenced <code>PicturePackageOptions</code> object.

PixarSaveOptions

Options for saving a document in Pixar format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
typename	string	Read-only. The class name of the referenced <code>PixarSaveOptions</code> object.

PNGSaveOptions

Options for saving a document in PNG format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
interlaced	boolean	Read-write. True to interlace rows (default: <code>false</code>).
typename	string	Read-only. The class name of the referenced <code>PNGSaveOptions</code> object.

Preferences

Represents application preferences for Photoshop. Access this object through the [Application.preferences](#) property. For example:

```
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
```

Setting values in this object is equivalent to selecting **Edit > Preferences** (in Windows) or **Photoshop > Preferences** (in Mac OS) in the Adobe Photoshop CS5 application. For explanations of individual settings, see Adobe Photoshop CS5 Help.

Properties

Property	Value type	What it is
additionalPluginFolder	File	Read-write. The path to an additional plug-in folder. Valid only when useAdditionalPluginFolder = true.
appendExtension	SaveBehavior	Read-write. The preferred policy for writing file extensions in Windows.
askBeforeSavingLayeredTIFF	boolean	Read-write. True to ask the user to verify layer preservation options when saving a file in TIFF format.
autoUpdateOpenDocuments	boolean	Read-write. True to automatically update open documents.
beepWhenDone	boolean	Read-write. True to beep when a process finishes.
colorChannelsInColor	boolean	Read-write. True to display component channels in the Channels palette in color.
colorPicker	ColorPicker	Read-write. The preferred color selection tool.
columnGutter	number [0.1..600.0]	Read-write. The width of the column gutters (in points).
columnWidth	number [0.1..600.0]	Read-write. Column width (in points)
createFirstSnapshot	boolean	Read-write. True to automatically make the first snapshot when a new document is created.
dynamicColorSliders	boolean	Read-write. True if dynamic color sliders appear in the Color palette.
editLogItems	EditLogItemsType	Read-write. The preferred level of detail in the history log. Valid only when useHistoryLog = true.

Property	Value type	What it is (Continued)
exportClipboard	boolean	Read-write. True to retain Adobe Photoshop CS5 contents on the clipboard after you exit the application.
fontPreviewSize	FontPreviewType	Read-write. The preferred type size to use for font previews in the type tool font menus.
fullSizePreview	boolean	Read-write. True to show image preview as a full size image, false to show thumbnail (in Mac OS only).
gamutWarningOpacity	number [0..100]	Read-write. Opacity value as a percentage.
gridSize	GridSize	Read-write. The preferred size to use for squares in the grid.
gridStyle	GridLineStyle	Read-write. The preferred formatting style for non-printing grid lines.
gridSubDivisions	number [1..100]	Read-write. Number of grid subdivisions.
guideStyle	GuideLineStyle	Read-write. The preferred formatting style for non-printing guide lines.
iconPreview	boolean	Read-write. True to use icon previews (in Mac OS only).
imageCacheLevels	number [1..8]	Read-write. The number of images to hold in the cache.
imagePreviews	SaveBehavior	Read-write. The preferred policy for writing image previews in Windows.
interpolation	ResampleMethod	Read-write. The method to use to assign color values to any new pixels created when an image is resampled or resized.
keyboardZoomResizesWindows	boolean	Read-write. True to automatically resize the window when zooming in or out using keyboard shortcuts.
macOSThumbnail	boolean	Read-write. True to create a thumbnail when saving the image (in Mac OS only).
maximizeCompatibility	QueryStateType	Read-write. The preferred policy for checking whether to maximize compatibility when opening PSD files.
maxRAMuse	number [5..100]	Read-write. The maximum percentage of available RAM used by Adobe Photoshop CS5 (5 - 100).
nonLinearHistory	boolean	Read-write. True to allow non-linear history.

Property	Value type	What it is (Continued)
<code>numberOfHistoryStates</code>	number	Read-write. The number of history states to preserve.
<code>otherCursors</code>	OtherPaintingCursors	Read-write. The preferred type of pointer to use with certain tools.
<code>paintingCursors</code>	PaintingCursors	Read-write. The preferred type of pointer to use with certain tools.
<code>parent</code>	Application	Read-write. The containing application.
<code>pixelDoubling</code>	boolean	Read-write. True to halve the resolution (double the size of pixels) to make previews display more quickly.
<code>pointSize</code>	PointType	Read-write. The point/pica size.
<code>recentFileListLength</code>	number [0..30]	Read-write. The number of items in the recent file list.
<code>rulerUnits</code>	Units	Read-write. The unit the scripting system will use when receiving and returning values.
<code>saveLogItems</code>	SaveLogItemsType	Read-write. The preferred location of history log data when saving the history items.
<code>saveLogItemsFile</code>	File	Read-write. The path to the history log file, when the preferred location is a file.
<code>savePaletteLocations</code>	boolean	Read-write. True to make new palette locations the default location.
<code>showAsianTextOptions</code>	boolean	Read-write. True to display Asian text options in the Paragraph palette.
<code>showEnglishFontNames</code>	boolean	Read-write. True to list Asian font names in English.
<code>showSliceNumber</code>	boolean	Read-write. True to display slice numbers in the document window when using the Slice tool.
<code>showToolTips</code>	boolean	Read-write. True to show pop up definitions on mouse over.
<code>smartQuotes</code>	boolean	Read-write. True to use curly, false to use straight quote marks.
<code>textFontSize</code>	FontSize	Read-write. Size of the small font used in panels and dialogs.
<code>typename</code>	string	Read-only. The class name of the referenced <code>preferences</code> object.

Property	Value type	What it is (Continued)
typeUnits	TypeUnits	Read-write. The preferred unit for text character measurements.
useAdditionalPluginFolder	boolean	Read-write. True to use an additional folder for compatible plug-ins stored with a different application.
useHistoryLog	boolean	Read-write. True to create a log file for history states.
useLowerCaseExtension	boolean	Read-write. True to use lowercase for file extensions.
useShiftKeyForToolSwitch	boolean	Read-write. True to enable cycling through a set of hidden tools.
useVideoAlpha	boolean	Read-write. True to enable Adobe Photoshop CS5 to send transparency information to your computer's video board. (Requires hardware support.)
windowsThumbnail	boolean	Read-write. True to create a thumbnail when saving the image in Windows. (Requires hardware support.)

PresentationOptions

Options for Adobe PDF presentations created using [Application.makePDFPresentation\(\)](#).

Properties

Property	Value type	What it is
autoAdvance	boolean	Read-write. True to auto advance images when viewing the presentation (default: <code>true</code>). Valid only when presentation = <code>true</code> .
includeFilename	boolean	Read-write. True to include the file name for the image (default: <code>false</code>).
interval	number [1..60]	Read-write. The time in seconds before the view is auto advanced (default: 5). Valid only when autoAdvance = <code>true</code> .
loop	boolean	Read-write. True to begin the presentation again after the last page (default: <code>false</code>). Valid only when autoAdvance = <code>true</code> .
magnification	MagnificationType	Read-write. The magnification type to use when viewing the image.
PDFFileOptions	PDFSaveOptions	Read-write. Options to use when creating the PDF file.
presentation	boolean	Read-write. True if the output will be a presentation (default: <code>false</code>); when <code>false</code> , the output is a Multi-Page document.
transition	TransitionType	Read-write. The method for transition from one image to the next (default: <code>TransitionType.NONE</code>). Valid only when autoAdvance = <code>true</code> .
typename	string	Read-only. The class name of the referenced <code>PresentationOptions</code> object.

RawFormatOpenOptions

Options for opening a document in RAW format using the [Application.open\(\)](#) method.

Properties

Property	Value type	What it is
bitsPerChannel	number	Read-write. The number of bits for each channel. The only valid values are <code>BitsPerChannelType.EIGHT</code> or <code>BitsPerChannelType.SIXTEEN</code> .
byteOrder	ByteOrder	Read-write. The order in which multibyte values are read. Valid only when bitsPerChannel = <code>BitsPerChannelType.SIXTEEN</code> .
channelNumber	number [1..56]	Read-write. The number of channels in the image. The value of cannot exceed the number of channels in the image. When bitsPerChannel = <code>BitsPerChannelType.SIXTEEN</code> , the only valid values are 1, 3, or 4.
headerSize	number [0..1919999]	Read-write. The number of bytes of information that will appear in the file before actual image information begins; that is, the number of zeroes inserted at the beginning of the file as placeholders.
height	number	Read-write. The height of the image (in pixels).
interleaveChannels	boolean	Read-write. True to store color values sequentially.
retainHeader	boolean	Read-write. True to retain the header when saving. Valid only when headerSize is 1 or greater.
typename	string	Read-only. The class name of the referenced <code>RawFormatOpenOptions</code> object.
width	number	Read-write. The image width in pixels.

RawSaveOptions

Options for saving a document in RAW format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True if alpha channels should be saved.
spotColors	boolean	Read-write. True if the spot colors should be saved.
typename	string	Read-only. The class name of the referenced <code>RawSaveOptions</code> object.

RGBColor

Defines an RGB color, used in the [SolidColor](#) object.

See also [CMYKColor](#), [GrayColor](#), [HSBColor](#), [LabColor](#), [NoColor](#).

Properties

Property	Value type	What it is
blue	number [0..255]	Read-write. The blue color value (default: 255).
green	number [0..255]	Read-write. The green color value (default: 255)
hexValue	string	Read-write. The hexadecimal representation of the color.
red	number [0..255]	Read-write. The red color value (default: 255)
typename	string	Read-only. The class name of the referenced <code>RGBColor</code> object.

Selection

The selected area of a document or layer. Access through the [Document.selection](#) property. For example:

```
app.activeDocument.selection.fill(app.foregroundColor)
```

Many of the properties and methods use the [UnitValue](#) type, which combines measurement values with the measurement unit. For information about this type, see the *JavaScript Tools Guide*.

Properties

Property	Value type	What it is
bounds	array of UnitValue	Read-only. The bounding rectangle of the entire selection.
parent	Document	Read-only. The object's container.
solid	boolean	Read-only. True if the bounding rectangle is a solid.
typename	string	Read-only. The class name of the referenced <code>selection</code> object.

Methods

Method	Parameter type	Returns	What it does
clear ()			Clears the selection and does not copy it to the clipboard.
contract (by)	UnitValue		Contracts (reduces) the selection by the specified amount.
copy ([merge])	boolean		Copies the selection to the clipboard. When the optional argument is used and set to <code>true</code> , a merged copy is performed (all visible layers in the selection are copied).
cut ()			Clears the current selection and copies it to the clipboard.
deselect ()			Deselects the current selection.
expand (by)	UnitValue		Expands the selection by the specified amount.
feather (by)	UnitValue		Feathers the edges of the selection by the specified amount.

Method	Parameter type	Returns	What it does (Continued)
fill (filltype [, mode] [, opacity] [, preserveTransparency])	SolidColor ColorBlendMode number [1..100] boolean		Fills the selection. opacity is a percentage value.
grow (tolerance, antiAlias)	number boolean		Grows the selection to include all adjacent pixels falling within the specified tolerance range.
invert ()			Inverts the selection (deselects the selection and selects the rest of the layer or document). Tip: To flip the selection shape, see rotate .
load (from [, combination] [, inverting])	Channel SelectionType boolean		Loads the selection from the specified channel.
makeWorkPath ([tolerance])	number		Makes this selection item the work path for this document.
resize ([horizontal] [, vertical] [, anchor])	number number AnchorPosition		Resizes the selected area to the specified dimensions and anchor position.
resizeBoundary ([horizontal] [, vertical] [, anchor])	number number AnchorPosition		Changes the size of the selection to the specified dimensions around the specified anchor.
rotate (angle [, anchor])	number AnchorPosition		Rotates the selection by the specified amount around the specified anchor point.
rotateBoundary (angle [, anchor])	number AnchorPosition		Rotates the boundary of the selection around the specified anchor.
select (region [, type] [, feather] [, antiAlias])	array of number SelectionType number boolean		Selects the specified region. The region parameter is an array of four coordinates, [left, top, right, bottom].
selectAll ()			Selects the entire layer.

Method	Parameter type	Returns	What it does (Continued)
selectBorder (width)	UnitValue		Selects the selection border only (in the specified width); subsequent actions do not affect the selected area within the borders.
similar (tolerance, antiAlias)	number boolean		Grows the selection to include pixels throughout the image falling within the tolerance range.
smooth (radius)	number		Cleans up stray pixels left inside or outside a color-based selection (within the radius specified in pixels).
store (into [, combination])	Channel SelectionType		Saves the selection as a channel.
stroke (strokeColor, width [, location] [, mode] [, opacity] [, preserveTransparency])	SolidColor number StrokeLocation ColorBlendMode number [1..100] boolean		Strokes the selection border. <code>opacity</code> is a percentage value.
translate ([deltaX] [, deltaY])	UnitValue UnitValue		Moves the entire selection relative to its current position.
translateBoundary ([deltaX] [, deltaY])	UnitValue UnitValue		Moves the selection relative to its current position.

Selection sample script

The following script creates a checkerboard using the following steps:

- Create an 800 x 800 pixel document.
- Divide the entire document into 100 x 100 pixel squares.
- Select every other square in the first row, then shift the selection criteria to select the alternate squares in the following row. Repeat until every other square in the document is selected.
- Fill the selected squares with the foreground color from the palette.
- Invert the selection and fill the newly selected squares with the background color from the palette.
- Deselect the squares to remove the selection outlines (the "marching ants").

Selection.jsx

```
// Save the current preferences
var startRulerUnits = app.preferences.rulerUnits
```

```
var startTypeUnits = app.preferences.typeUnits
var startDisplayDialogs = app.displayDialogs

// Set Adobe Photoshop CS5 to use pixels and display no dialogs
app.preferences.rulerUnits = Units.PIXELS
app.preferences.typeUnits = TypeUnits.PIXELS
app.displayDialogs = DialogModes.NO

//Close all the open documents
while (app.documents.length) {
    app.activeDocument.close()
}

//Create variables for the 800 pixel board divided in even 100 x 100 squares
var docSize = 800
var cells = 8
var cellSize = docSize / cells

// create a new document
var checkersDoc = app.documents.add(docSize, docSize, 72, "Checkers")

// Create a variable to use for selecting the checker board
// That allows me to shift the selection one square to the right
//on every other row, and then shift back for the rows in between.
var shiftIt = true

// loop through vertically to create the first row
for (var v = 0; v < docSize; v += cellSize) {

    // Switch the shift for a new row
    shiftIt = !shiftIt

    // loop through horizontally
    for (var h = 0; h < docSize; h += (cellSize * 2)) {

        // push over the cellSize to start with only
        if (shiftIt && h == 0) {
            h += cellSize
        }

        // Select a square
        selRegion = Array(Array(h, v),
            Array(h + cellSize, v),
            Array(h + cellSize, v + cellSize),
            Array(h, v + cellSize),
            Array(h, v))

        // In the first iteration of the loop, start the selection
        //In subsequent iterations, use the EXTEND constant value
        //of the select() method to add to the selection (in the loop's else clause)
        if (h == 0 && v == 0) {
            checkersDoc.selection.select(selRegion)
        } else {
            checkersDoc.selection.select(selRegion, SelectionType.EXTEND)
        }

        // turn this off for faster execution
        // turn this on for debugging
        WaitForRedraw()
    }
}
```

```
}

// Fill the current selection with the foreground color
checkersDoc.selection.fill(app.foregroundColor)

//Invert the selection
checkersDoc.selection.invert()

// Fill the new selection with the background color
checkersDoc.selection.fill(app.backgroundColor)

// Clear the selection to get rid of the non-printing borders
checkersDoc.selection.deselect()

// Reset the application preferences
app.preferences.rulerUnits = startRulerUnits
app.preferences.typeUnits = startTypeUnits
app.displayDialogs = startDisplayDialogs

// A helper function for debugging
// It also helps the user see what is going on
// if you turn it off for this example you
// get a flashing cursor for a number time
function WaitForRedraw()
{
    var eventWait = charIDToTypeID("Wait")
    var enumRedrawComplete = charIDToTypeID("RdCm")
    var typeState = charIDToTypeID("Stte")
    var keyState = charIDToTypeID("Stte")

    var desc = new ActionDescriptor()

    desc.putEnumerated(keyState, typeState, enumRedrawComplete)

    executeAction(eventWait, desc, DialogModes.NO)
}
```

SGIRGBSaveOptions

Options for saving a document in SGIRGB format using the [Document.saveAs\(\)](#) method.

Note: The SGIRGB format is not installed automatically with Adobe Photoshop CS5.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
spotColors	boolean	Read-write. True to save the spot colors.
typename	string	Read-only. The class name of the referenced <code>SGIRGBSaveOptions</code> object.

SolidColor

A color definition used in the document. Maps a color to equivalents in all available color models.

- Used in [Application.backgroundColor](#) and [foregroundColor](#) properties, in [Channel.color](#), in [ColorSampler.color](#), and in [TextItem.color](#)
- Passed to [PathItem.fillPath\(\)](#), [Selection.fill\(\)](#), and [Selection.stroke\(\)](#).

Properties

Property	Value type	What it is
cmyk	CMYKColor	Read-write. The CMYK color mode.
gray	GrayColor	Read-write. The Grayscale color mode.
hsb	HSBColor	Read-write. The HSB color mode.
lab	LabColor	Read-write. The LAB color mode.
model	ColorModel	Read-write. The color model.
nearestWebColor	RGBColor	Read-only. The nearest web color to the current color.
rgb	RGBColor	Read-write. The RGB color mode.
typename	string	Read-only. The class name of the referenced <code>SolidColor</code> object.

Methods

Method	Parameter type	Returns	What it does
isEqual (color)	SolidColor	boolean	True if the <code>SolidColor</code> object is visually equal to the specified color.

SubPathInfo

An array of [PathPoint](#) objects that describes a straight or curved segment of a path, used to create a [SubPathItem](#).

Pass an array of these objects to the [PathItems.add\(\)](#) method. This method creates a [SubPathItem](#) object for each `SubPathInfo` object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths.

- Use `SubPathInfo` to create subpaths; the properties are writeable.
- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.

Properties

Property	Value type	What it is
closed	boolean	Read-write. True if the path describes an enclosed area.
entireSubPath	array of PathPoint	Read-write.
operation	ShapeOperation	Read-write. The subpath's operation on other subpaths. Specifies how to combine the shapes if the destination path already has a selection.
typename	string	Read-only. The class name of the referenced <code>SubPathInfo</code> object.

SubPathItem

Represents a subpath; a collection of subpaths make up a [PathItem](#).

Create these objects by passing [SubPathInfo](#) objects to the [PathItems.add\(\)](#) method. This method creates a `SubPathItem` object for each [SubPathInfo](#) object, and creates and returns a new [PathItem](#) object for the path represented by all of the subpaths. Access these objects in the [PathItem.subPathItems](#) collection.

- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.
- Use [SubPathInfo](#) to create subpaths; the properties are writeable.

Properties

Property	Value type	What it is
closed	boolean	Read-only. True if the path is closed.
operation	ShapeOperation	Read-only. How this object behaves when it intersects another SubPathItem object. Specifies how to combine the shapes if the destination path already has a selection.
parent	PathItem	Read-only. The object's container.
pathPoints	PathPoints	Read-only. The <code>PathPoints</code> collection.
typename	string	Read-only. The class name of the referenced <code>SubPathItem</code> object.

SubPathItems

A collection of [SubPathItem](#) objects that make up a [PathItem](#). Access this object in the [PathItem.subPathItems](#) collection property.

- Use [SubPathInfo](#) to create subpaths; the properties are writeable.
- Use the [SubPathItem](#) object to retrieve information about existing subpaths. The properties are read-only.

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the collection.
parent	PathItem	Read-only. The containing path item.
typename	string	Read-only. The class name of the referenced <code>SubPathItems</code> object.

TargaSaveOptions

Options for saving a document in TGA (Targa) format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
resolution	TargaBitsPerPixels	Read-write. The number of bits per pixel (default: <code>TargaBitsPerPixels.TWENTYFOUR</code>).
rleCompression	boolean	Read-write. True to use RLE compression (default: <code>true</code>).
typename	string	Read-only. The class name of the referenced <code>TargaSaveOptions</code> object.

TextFont

Describes a font that is available to the application. Access this object in the [Application.fonts](#) collection. For example:

```
var myFont = app.fonts.getByName("ArialMT");
```

Properties

Property	Value type	What it is
family	string	Read-only. The font family.
name	string	Read-only. The name of the font.
parent	Application	Read-only. The containing application.
postScriptName	string	Read-only. The PostScript name of the font.
style	string	Read-only. The font style.
typename	string	Read-only. The class name of the referenced <code>TextFont</code> object.

TextFonts

The collection of fonts available on your computer. Fonts are represented by [TextFont](#) objects. Access this object in the [Application.fonts](#) collection property. For example, this displays the number of available fonts:

```
alert (app.fonts.length) ;
```

Properties

Property	Value type	What it is
length	number	Read-only. The number of elements in the collection.
parent	Application	Read-only. The containing application.
typename	string	Read-only. The class name of the referenced <code>TextFonts</code> object.

Methods

Method	Parameter type	Returns	What it does
getByName (name)	string	TextFont	Gets the first element in the <code>TextFonts</code> collection with the provided name.

TextItem

The text in an [ArtLayer](#) object whose [kind](#) property is `LayerKind.TEXT`. Access this object in the [ArtLayer.textItem](#) property. For example:

```
myLayers[i].textItem.contents = "Layer in " + textArray[i] + " Set Inside "
```

Many of the properties use the [UnitValue](#) type, which combines a measurement value with a measurement unit. For information about this type, see the *JavaScript Tools Guide*.

Properties

Property	Value type	What it is
alternateLigatures	boolean	Read-write. True to use alternate ligatures. Note: Alternate ligatures are the same as Discretionary Ligatures. See Adobe Photoshop CS5 Help for more information.
antiAliasMethod	AntiAlias	Read-write. The method of anti aliasing to use.
autoKerning	AutoKernType	Read-write. The auto kerning option to use.
autoLeadingAmount	number [0.01..5000.00]	Read-write. The percentage to use for auto (default) leading (in points). Valid only when useAutoLeading = <code>true</code> .
baselineShift	UnitValue	Read-write. The unit value to use in the baseline offset of text.
capitalization	TextCase	Read-write. The text case.
color	SolidColor	Read-write. The text color.
contents	string	Read-write. The actual text in the layer.
desiredGlyphScaling	number [50..200]	Read-write. The desired amount by which to scale the horizontal size of the text letters. A percentage value; at 100, the width of characters is not scaled. Valid only when justification = <code>Justification.CENTERJUSTIFIED</code> , <code>FULLYJUSTIFIED</code> , <code>LEFTJUSTIFIED</code> , or <code>Justification.RIGHTJUSTIFIED</code> . When used, the minimumGlyphScaling and maximumGlyphScaling values are also required.

Property	Value type	What it is (Continued)
desiredLetterScaling	number [100..500]	<p>Read-write. The amount of space between letters (at 0, no space is added between letters).</p> <p>Equivalent to Letter Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the minimumLetterScaling and maximumLetterScaling values are also required.</p>
desiredWordScaling	number [0..1000]	<p>Read-write. The amount (percentage) of space between words (at 100, no additional space is added between words).</p> <p>Equivalent to Word Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the minimumWordScaling and maximumWordScaling values are also required.</p>
direction	Direction	Read-write. The text orientation.
fauxBold	boolean	<p>Read-write. True to use faux bold (default: <code>false</code>).</p> <p>Setting this to true is equivalent to selecting text and clicking Faux Bold in the Character palette.</p>
fauxItalic	boolean	<p>Read-write. True to use faux italic (default: <code>false</code>).</p> <p>Setting this to true is equivalent to selecting text and clicking Faux Italic in the Character palette.</p>
firstLineIndent	UnitValue [-1296..1296] points	Read-write. The amount (unit value) to indent the first line of paragraphs.
font	string	Read-write. The text face of the character. Use the PostScript Name of the font. See TextFont and use the <code>postScriptName</code> property.
hangingPunctuation	boolean	Read-write. True to use Roman hanging punctuation.
height	UnitValue ^x	<p>Read-write. The height of the bounding box (unit value) for paragraph text.</p> <p>Valid only when kind = <code>TextType.PARAGRAPHTEXT</code>.</p>
horizontalScale	number [0..1000]	Read-write. Character scaling (horizontal) in proportion to verticalScale (a percentage value).

Property	Value type	What it is (Continued)
hyphenateAfterFirst	number [1..15]	Read-write. The number of letters after which hyphenation in word wrap is allowed.
hyphenateBeforeLast	number [1..15]	Read-write. The number of letters before which hyphenation in word wrap is allowed.
hyphenateCapitalWords	boolean	Read-write. True to allow hyphenation in word wrap of capitalized words.
hyphenateWordsLongerThan	number [2..25]	Read-write. The minimum number of letters a word must have in order for hyphenation in word wrap to be allowed.
hyphenation	boolean	Read-write. True to use hyphenation in word wrap.
hyphenationZone	UnitValue [0..720] pica	Read-write. The distance at the end of a line that will cause a word to break in unjustified type.
hyphenLimit	number	Read-write. The maximum number of consecutive lines that can end with a hyphenated word.
justification	Justification	Read-write. The paragraph justification.
kind	TextType	Read-write. The text-wrap type.
language	Language	Read-write. The language to use.
leading	UnitValue	Read-write. The leading amount.
leftIndent	UnitValue [-1296..1296] points	Read-write. The amount of space to indent text from the left.
ligatures	boolean	Read-write. True to use ligatures.
maximumGlyphScaling	number [50..200]	<p>Read-write. The maximum amount to scale the horizontal size of the text letters (a percentage value; at 100, the width of characters is not scaled).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the minimumGlyphScaling and desiredGlyphScaling values are also required.</p>

Property	Value type	What it is (Continued)
maximumLetterScaling	number [100..500]	<p>Read-write. The maximum amount of space to allow between letters (at 0, no space is added between letters).</p> <p>Equivalent to Letter Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the minimumLetterScaling and desiredLetterScaling values are also required.</p>
maximumWordScaling	number [0..1000]	<p>Read-write. The maximum amount of space to allow between words (a percentage value; at 100, no additional space is added between words).</p> <p>Equivalent to Word Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the minimumWordScaling and desiredWordScaling values are also required.</p>
minimumGlyphScaling	number [50..200]	<p>Read-write. The minimum amount to scale the horizontal size of the text letters (a percentage value; at 100, the width of characters is not scaled).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the maximumGlyphScaling and desiredGlyphScaling values are also required.</p>

Property	Value type	What it is (Continued)
minimumLetterScaling	number [100..500]	<p>Read-write. The minimum amount of space to allow between letters (a percentage value; at 0, no space is removed between letters).</p> <p>Equivalent to Letter Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the maximumLetterScaling and desiredLetterScaling values are also required.</p>
minimumWordScaling	number [0..1000]	<p>Read-write. The minimum amount of space to allow between words (a percentage value; at 100, no additional space is removed between words).</p> <p>Equivalent to Word Spacing in the Justification dialog (Select Justification on the Paragraphs palette menu).</p> <p>Valid only when justification = <code>Justification.CENTERJUSTIFIED</code>, <code>FULLYJUSTIFIED</code>, <code>LEFTJUSTIFIED</code>, or <code>Justification.RIGHTJUSTIFIED</code>.</p> <p>When used, the maximumWordScaling and desiredWordScaling values are also required.</p>
noBreak	boolean	<p>Read-write. True to disallow line breaks in this text.</p> <p>Tip: When true for many consecutive characters, can prevent word wrap and thus may prevent some text from appearing on the screen.</p>
oldStyle	boolean	Read-write. True to use old style type.
parent	ArtLayer	Read-write. The containing layer.
position	array of UnitValue	<p>Read-write. The position of origin for the text. The array members specify the X and Y coordinates.</p> <p>Equivalent to clicking the text tool at a point in the document to create the point of origin for text.</p>
rightIndent	UnitValue [-1296..1296] points	Read-write. The amount of space to indent text from the right.
size	UnitValue	Read-write. The font size in <code>UnitValue</code> . NOTE: Type was <code>points</code> for CS3 and older..
spaceAfter	UnitValue [-1296..1296] points	Read-write. The amount of space to use after each paragraph.

Property	Value type	What it is (Continued)
spaceBefore	UnitValue [-1296..1296] points	Read-write. The amount of space to use before each paragraph.
strikeThru	StrikeThruType	Read-write. The text strike-through option to use.
textComposer	TextComposer	Read-write. The composition method to use to evaluate line breaks and optimize the specified hyphenation and justification options. Valid only when kind = <code>TextType.PARAGRAPHTEXT</code> .
tracking	number [-1000..10000]	Read-write. The amount of uniform spacing between multiple characters. Tracking units are 1/1000 of an em space. The width of an em space is relative to the current type size. In a 1-point font, 1 em equals 1 point; in a 10-point font, 1 em equals 10 points. So, for example, 100 units in a 10-point font are equivalent to 1 point.
typename	string	Read-only. The class name of the referenced <code>textItem</code> object.
underline	UnderlineType	Read-write. The text underlining options.
useAutoLeading	boolean	Read-write. True to use a font's built-in leading information.
verticalScale	number [0-1000]	Read-write. Vertical character scaling in proportion to horizontalScale (a percentage value).
warpBend	number [-100..100]	Read-write. The warp bend percentage.
warpDirection	Direction	Read-write. The warp direction.
warpHorizontalDistortion	number [-100..100]	Read-write. The horizontal distortion of the warp (a percentage value).
warpStyle	WarpStyle	Read-write. The style of warp to use.
warpVerticalDistortion	number [-100..100]	Read-write. The vertical distortion of the warp (a percentage value).
width	UnitValue	Read-write. The width of the bounding box for paragraph text. Valid only when kind = <code>TextType.PARAGRAPHTEXT</code> .

Methods

Method	Parameter type	Returns	What it does
convertToShape ()			Converts the text item and its containing layer to a fill layer with the text changed to a clipping path.
createPath ()			Creates a clipping path from the outlines of the actual text items (such as letters or words).

TiffSaveOptions

Options for saving a document in TIFF format using the [Document.saveAs\(\)](#) method.

Properties

Property	Value type	What it is
alphaChannels	boolean	Read-write. True to save the alpha channels.
annotations	boolean	Read-write. True to save the annotations.
byteOrder	ByteOrder	Read-write. The order in which the document's multibyte values are read (default: <code>ByteOrder.MACOS</code> in Mac OS, <code>ByteOrder.IBM</code> in Windows).
embedColorProfile	boolean	Read-write. True to embed the color profile in the document.
imageCompression	TIFFEncoding	Read-write. The compression type (default: <code>TIFFEncoding.NONE</code>).
interleaveChannels	boolean	Read-write. True if the channels in the image will be interleaved.
jpegQuality	number [0..12]	Read-write. The quality of the produced image, which is inversely proportionate to the amount of JPEG compression. Valid only when imageCompression = <code>TIFFEncoding.JPEG</code> .
layerCompression	LayerCompression	Read-write. The method of compression to use when saving layers (as opposed to saving composite data). Valid only when layers = <code>true</code> .
layers	boolean	Read-write. True to save the layers.
saveImagePyramid	boolean	Read-write. True to preserve multi-resolution information (default: <code>false</code>).
spotColors	boolean	Read-write. True to save the spot colors.
transparency	boolean	Read-write. True to save the transparency as an additional alpha channel when the file is opened in another application.
typename	string	Read-only. The class name of the referenced <code>TiffSaveOptions</code> object.

UnitValue

ExtendScript defines the JavaScript class `UnitValue` to represent measurement values together with their measurement units; see [‘JavaScript support in Adobe Photoshop CS5’ on page 33](#). For references details of these classes, see the *JavaScript Tools Guide*.

xmpMetadata

Camera RAW image XMP metadata.

For camera RAW image files, the XMP metadata is stored in a *sidecar* file, which is a file in the same folder as the RAW file with the same base name and an XMP extension.

Properties

Property	Value type	What it is
parent	Document	Read-only. The containing document.
rawData	string	Read-write. A string containing the XMP metadata in XML (RDF) format. See the <i>XMP Specification</i> for details of this format.
typename	string	Read-only. The class name of the referenced <code>xmpMetadata</code> object.

This section describes the JavaScript resource that enables your JavaScripts to behave like a plug-in. This includes:

- the ability to specify a menu the script appears in as a command,
- a terminology resource so the script can function with the Action Manager, which allows your script to record and be automated by scripting parameters,
- a category to enable ordering and grouping of commands within menus, and
- an enable string that indicates whether the command is enabled or disabled given a set of conditions.
- The strings must be valid XML syntax. The "&" character will not work for example. Use the `& &` for example to get logical '&&' in the enableinfo block.

JavaScript resource syntax

The JavaScript Resource has an HTML-style syntax, with each `<tag>` matched by a closing `</tag>`. This resource needs to appear within comments (`/* ... */`) and should be defined at the top of your script file (within the first 10,240 characters of the file.)

Tag	Description
<code><javascriptresource></code>	The resource definition tag.
<code><name></code>	The command name that appears in the Photoshop menu. If this tag is not provided in the resource, the name of the command in the menu defaults to the name of the script.
<code><menu></code>	The menu the command appears in. If this tag is not provided, the command appears in the File > Scripts menu. Note: Currently the only supported values for <code><menu></code> are <code>automate</code> , <code>filter</code> and <code>help</code> . <code>automate</code> puts the script in the File > Automate menu for example.
<code><about></code>	A string that appears in an About box, which the user can select from the Help > About Plug-in menu.
<code><enableinfo></code>	A boolean expression that indicates whether the command is enabled in the menu. See Enable-info grammar . Note: If you provide this tag, the menu item is enabled if and only if there is at least one document open, and the boolean expression evaluates to true. If you always want the menu item enabled, do not use this tag.
<code><eventid></code>	A unique string that identifies the event. Using a UUID will ensure that your script won't share this identifier with another script.

Tag	Description
<category>	The category the command appears within in the menu. Used to group and order commands in the menu. Commands are placed in the menu alphabetically based on the string in <category>. If two commands use the same category, they are grouped together.
<terminology>	The terminology dictionary for the script to function with the Action Manager. See the Terminology dictionary .

Basic JavaScript resource example

This example shows a very basic <javascriptresource>. With this resource, the script can be executed by selecting the command **Add a Document**, which appears in the **Automate** menu. This command is enabled in the menu, provided at least one document is already open. If the user requests information about the script from the **About Plug-in** menu, the string contained in the <about> tag is displayed in a dialog box.

```

/*
  <javascriptresource>
  <name>Add a Document</name>
  <type>automate</type>
  <about>A short string providing information about the script.</about>
  <enableinfo>true</enableinfo>
</javascriptresource>
*/

app.documents.add();

```

Enable-info grammar

The <enableinfo> tag provides a boolean expression that, when evaluated, indicates whether the command is enabled in the menu. You can use this expression to enable or disable the menu item based on various characteristics of the document. The Enable Info grammar is as follows:

```

<booleanExpression> :=    <conjunction> { "|" <conjunction> }
<conjunction> :=          <relation> {"&&" <relation> }
<relation> :=             <equality> {<relationOperator><equality>}
<equality> :=             <simpleExpression> {<equalityOperator><simpleExpression>}
<simpleExpression> :=      <term> {<addOperator><term>}
<term> :=                 <factor> {<mulOperator><factor>}
<factor> :=               <integer> | <intrinsic> | <ident> |
                          "(" <booleanExpression> ")" | "(" simpleExpression ")" |
                          "+" <factor> | "-" <factor> | "!" <factor>

<integer> :=              digit {digit}
<intrinsic> :=            <limitFunction> | <dimFunction> | <inFunction>
<limitFunction> :=        ( "min" | "max" ) "(" <simpleExpression> ","
                          <simpleExpression> { "," <simpleExpression> } ")"
<dimFunction> :=          "dim" "(" <simpleExpression> "," <simpleExpression> ")"

```



```

<ident> :=          (alpha | "_" ) {alpha | digit | "_" }
<mulOperator> :=    "*" | "/"
<addOperator> :=    "+" | "-"
<equalityOperator> :=  "==" | "!="
<relationOperator> := "<" | "<=" | ">=" | ">"
<inFunction> :=      "in" "(" <simpleExpression> {"," <simpleExpression> } ")"

```

Operator precedence is shown in the following table. Operators are listed with the highest order of precedence at the top of the table

Operator	Description
	Or
&&	And
+ -	Addition or subtraction
* /	Multiply or divide
< <= >= >	Less than, less than or equal, greater than or equal, greater than
== !=	Equals, or does not equal.
(..) in() max() min() unary + - !	Functions Unary operators: increment, decrement, not

The grammar provides variables and constants that you can use in the `<enableinfo>` expression. The following table provides a list of the constants that are available.

Constant Name	Description
true	Boolean true
false	Boolean false
BitmapMode	Bitmap mode.
GrayscaleMode	Grayscale mode, 8 bit depth.
IndexedMode	Indexed color mode.
RGBMode	RGB color mode.
CMYKMode	CMYK color mode.
HSLMode	HSL color mode.
HSBMode	HSB color mode
MultiChannelMode	Multichannel mode.
DuotoneMode	Duotone mode.
LabMode	Lab color mode.

Constant Name	Description
Gray16Mode	Grayscale mode, 16 bits per channel
RGB48Mode	RGB color mode, 16 bits per channel.
Lab48Mode	LAB mode, 16 bits per channel.
CMYK64Mode	CMYK mode, 16 bits per channel.
DeepMultichannelMode	Deep multichannel mode.
Duotone16Mode	Duotone mode, 16 bit depth.
RGB96Mode	RGB color mode, 32 bits per channel.
Gray32Mode	Grayscale mode, 32 bit depth.

The following table show the set of variables you can use in the <enableinfo> expression. The value of these variables is set based on the properties of the active document.

Variable Name	Description
PSHOP_ImageMode	Image mode of the active document.
PSHOP_ImageDepth	Depth of the active document.
PSHOP_HasLayerMask	Boolean indicating presence of layer mask.
PSHOP_HasSelectionMask	Boolean indicating presence of selection mask.
PSHOP_HasTransparencyMask	Boolean indicating presence of transparency mask.
PSHOP_NumTargetChannels	Number of target channels.
PSHOP_NumTrueChannels	Numer of image channels.
PSHOP_IsAdjustorSheet	Boolean
PSHOP_IsTargetComposite	Boolean indicating whether channels are flattened.
PSHOP_IsTargetSection	Boolean.
PSHOP_IsTargetVisible	Boolean.
PSHOP_ImageWidth	Width of the image.
PSHOP_ImageHeight	Height of the image.
PSHOP_TargetProtectFlags.	

Undefined values in enable-info evaluation

If any arithmetic or relation operation contains an operand whose value is undefined, or a variable that is undefined, the result of that evaluation is `false`.

Boolean values are treated as in C/C++, where non-zero values are `true`, and zero is `false`, with the exception that an undefined value is also `false`.

Using the "in" function

The `in` function (see `<inFunction>`) returns `true` if the first parameter is equal to at least one of the subsequent parameters. A typical use might be to see if the image mode of the active document is one of a set of image modes. For example:

```
in(PSHOP_ImageMode, RGBMode, CMYKMode, LabMode)
```

Action Manager automation

For your script to be able to record scripting parameters and be automated by them, it requires the addition of two basic mechanisms:

- A *terminology dictionary* that maps your script's user interface to human readable text, providing text and type information for each parameter the script uses.
- Code to read parameter information when it comes from the Action Manager, rather than from the user-interface, and code to write parameter information to the Action Manager. This code uses the Action Manager classes [ActionDescriptor](#), [ActionList](#), and [ActionReference](#).

See `Conditional Mode Change.jsx` for an example of a script that can record and be automated by scripting parameters. This file can be found in the Presets/Scripts folder.

Terminology dictionary

The JavaScript resource provides a `<terminology>` tag that allows you to provide the terminology dictionary for your script. The first step in creating a terminology dictionary is to review your script's user interface, and create human-readable strings for each element in your user interface.

For example, in the Conditional Mode Change command, the user interface requests a source mode and a target mode. Both source mode and target mode have several options. All of these elements of the user interface need to have entries in the terminology dictionary.

The terminology dictionary is created in a PDF dictionary format, with the following entries, and must have the following format in the `<javascriptresource>`:

```
<terminology><![CDATA[<<<
  /Version integer
  /Events <<event dictionary>>
  /Classes <<class dictionary>>
  /Enumerations <<enumeration dictionary>>
>>> ]]></terminology>
```

Note: The information in the terminology tag needs to be wrapped in a `CDATA` block so the xml parser will ignore "/" and other tags that appear in the terminology.

The definitions for events, classes and enumerations dictionaries are provided below.

The `/Events` dictionary contains an entry for each event:

```

/eventName [                                // Name used in string-based API
  (String event name)                       // required
  /direct parameter type                   // optional; if omitted, no parameter
  <<                                       // optional parameter dictionary
    /parameterName [                      // Name used in string-based API
      (String name)                       // required
      /parameter type                     // required
    ]
    ...                                    // other parameters
  >>
]

```

The `/Classes` dictionary contains an entry for each class:

```

/className [                                // Name used in string-based API
  (ZString class name)                     // required
  <<                                       // property dictionary
    /propertyName [                      // Name used in string-based API
      (String name)                       // required
      /property type                     // required
    ]
    ...                                    // other properties
  >>
]

```

The `/Enumerations` dictionary contains an entry for each enumerated type:

```

/enumTypeName                               // Name used in string-based API
<<
  /enumValue (String name)                 // required
  ...
>>

```

Value type definitions

For `/parameter type` and `/property type` definitions, you can use the Class and Enumeration type declarations you make in your own terminology dictionary, you can use declarations provided by Photoshop or you can use basic value types.

Basic Value Types

The basic value types are shown in the following table:

Name	Code	Description
<code>typeInteger</code>	<code>'long'</code>	int32
<code>typeFloat</code>	<code>'doub'</code>	IEEE 64 bit double
<code>typeBoolean</code>	<code>'bool'</code>	TRUE OR FALSE.
<code>typeText</code>	<code>'TEXT'</code>	Block of any number of readable characters.
<code>typeAlias</code>	<code>'alis'</code>	Macintosh file system path.

Name	Code	Description
typePaths	'Pth '	Windows file system path.
typePlatformFilePath	'alis' or 'Pth	typeAlias for Mac OS, typePath for Windows.

Predefined Class Types

Photoshop provides a number of predefined classes that are available for use in the terminology dictionary. A useful subset of those classes is shown in the table below. Use these classes when they are appropriate, but you can define new classes in the terminology resource, if necessary.

Name	Code	Description
classColor	'Clr '	Class for color classes.
classRGBColor	'RGBC'	keyRed, keyGreen, keyBlue
classCMYKColor	'CMYC'	keyCyan, keyMagenta, keyYellow, keyBlack.
classUnspecifiedColor	'UnsC'	Unspecified.
classGrayscale	'Grsc'	keyGray
classBookColor	'BkCl '	Book color
classLabColor	'LbCl '	keyLuminance, keyA, keyB.

Uniqueness rules for terminology entries

Generally, the names for terminology entries must be unique within a particular category and scope. It is best to not make names unique unnecessarily; generic terms are preferable, and if a name already exists for something, go ahead and use it. Case matters in considering uniqueness of terminology entries.

The uniqueness rules for terminology entries are:

- All event names must be different from all other event names.
- All class names must be different from all other names.
- All enumeration type names must be different from all other enumeration type names.
- All keys must be different from all other keys used in the same class or event.
- All enumeration values must be different from all other enumeration values in the same enumeration type.
- A class, event, enumeration type, key, and enumeration value can all have the same name.

Terminology definition example

This example demonstrates the terminology definition for a new event; the example uses ZStrings. The event is called `newAnnot`, and it takes three parameters:

- `annotType`, an enumeration (`annotType`)
- `at`, a class (`point`), and
- `size`, a class (`annotSizeClass`).

The `annotSizeClass` has two properties: `width`, and `height`, both of type `floatType`. The enumeration `annotType` has three values: `annotUnknown`, `annotText`, and `annotSound`.

```
<terminology><![CDATA[<<<
  /Version 1
  /Events
    /newAnnot [(New Annotation) <<
      /annotType [(Type) /annotType]
      /at [(At) /Point]
      /size [(Size) /annotSizeClass] >>]
  /Classes
    /annotSizeClass [(Size) <<
      /width [(Width) /floatType]
      /height [(Height) /floatType]
      >>]
  /Enumerations
    /annotType <<
      /annotUnknown (Unknown)
      /annotText (Text)
      /annotSound (Sound)
    >>> ]]></terminology>
```

4

Scripting Constants

This section lists and describes the enumerations defined for use with Adobe Photoshop CS5 JavaScript properties and methods.

Constant type	Values	What it means
AdjustmentReference	ABSOLUTE RELATIVE	Method to use for interpreting selective color adjustment specifications: ABSOLUTE = % of the whole. RELATIVE = % of the existing color amount. Pass to ArtLayer.selectiveColor() .
AnchorPosition	BOTTOMCENTER BOTTOMLEFT BOTTOMRIGHT MIDDLECENTER MIDDLELEFT MIDDLERIGHT TOPCENTER TOPLEFT TOPRIGHT	The point around which to transform an object. This is the point that does not move when an object is rotated or resized using methods in ArtLayer , LayerSet , and Selection , or when the entire canvas is resized with Document.resizeCanvas() .
AntiAlias	CRISP NONE SHARP SMOOTH STRONG	Method to use to smooth edges by softening the color transition between edge pixels and background pixels. Used in a TextItem.antiAliasMethod .
AutoKernType	MANUAL METRICS OPTICAL	The type of kerning to use for characters. Used in TextItem.autoKerning .
BatchDestinationType	FOLDER NODESTINATION SAVEANDCLOSE	The destination, if any, for batch-processed files, specified in the BatchOptions used with the Application.batch() method: FOLDER: Save modified versions of the files to a new location (leaving the originals unchanged). NODESTINATIONTYPE: Leave all files open. SAVEANDCLOSE: Save changes and close the files.

Constant type	Values	What it means
BitmapConversionType	CUSTOMPATTERN DIFFUSIONDITHER HALFTHRESHOLD HALFTONESCREEN PATTERNDITHER	Specifies the quality of an image you are converting to bitmap mode. Used in BitmapConversionOptions .
BitmapHalfToneType	CROSS DIAMOND ELLIPSE LINE ROUND SQUARE	Specifies the shape of the dots (ink deposits) in the halftone screen. Used in BitmapConversionOptions .
BitsPerChannelType	EIGHT ONE SIXTEEN THIRTYTWO	The number of bits per color channel. Value of Document.bitsPerChannel ; pass to Documents.add() . Also used in PDFOpenOptions and CameraRAWOpenOptions .
BlendMode	COLORBLEND COLORBURN COLORDODGE DARKEN DIFFERENCE DISSOLVE DIVIDE EXCLUSION HARDLIGHT HARDMIX HUE LIGHTEN LINEARBURN LINEARDODGE LINEARLIGHT LUMINOSITY MULTIPLY NORMAL OVERLAY PASSTHROUGH PINLIGHT SATURATION SCREEN SOFTLIGHT SUBTRACT VIVIDLIGHT	Controls how pixels in an image are blended when a filter is applied. The value of ArtLayer.blendMode and LayerSet.blendMode .
BMPDepthType	BMP_A1R5G5B5 BMP_A4R4G4B4 BMP_A8R8G8B8 BMP_R5G6B5 BMP_R8G8B8 BMP_X1R5G5B5 BMP_X4R4G4B4 BMP_X8R8G8B8 EIGHT FOUR ONE SIXTEEN THIRTYTWO TWENTYFOUR	The number of bits per channel (also called pixel depth or color depth). The number selected indicates the exponent of 2. For example, a pixel with a bit-depth of <code>EIGHT</code> has 2^8 , or 256, possible color values. Used in BMPSaveOptions .

Constant type	Values	What it means
ByteOrder	IBM MACOS	The platform-specific order in which multibyte values are read.
CameraRAWSettingsType	CAMERA CUSTOM SELECTEDIMAGE	The default CameraRaw settings to use: the camera settings, custom settings, or the settings of the selected image. Set in CameraRAWOpenOptions .
CameraRAWSize	EXTRALARGE LARGE MAXIMUM MEDIUM MINIMUM SMALL	The camera RAW size type options: EXTRALARGE=5120 x 4096 LARGE=4096 x 2731 MAXIMUM=6144 X 4096 MEDIUM=3072 x 2048 MINIMUM=1536 x 1024 SMALL=2048 x 1365 Set in CameraRAWOpenOptions .
ChangeMode	BITMAP CMYK GRAYSCALE INDEXEDCOLOR LAB MULTICHANNEL RGB	The new color profile or mode for a document, specified in Document.changeMode() . Note: Color images must be changed to GRAYSCALE mode before you can change them to BITMAP mode.
ChannelType	COMPONENT MASKEDAREA SELECTEDAREA SPOTCOLOR	The type of a color channel: COMPONENT: related to document color mode. MASKEDAREA: Alpha channel where color indicates masked area. SELECTEDAREA: Alpha channel where color indicates selected are. SPOTCOLOR: Alpha channel to store a spot color.

Constant type	Values	What it means
ColorBlendMode	BEHIND CLEAR COLOR COLORBURN COLORDODGE DARKEN DARKERCOLOR DIFFERENCE DISSOLVE EXCLUSION HARDLIGHT HARDMIXBLEND HUE LIGHTEN LIGHTERCOLOR LINEARBURN LINEARDODGE LINEARLIGHT LUMINOSITY MULTIPLY NORMAL OVERLAY PINLIGHT SATURATION SCREEN SOFTLIGHT VIVIDLIGHT	The way color should be blended in a fill or stroke operation. Pass to PathItem.fillPath() , Selection.fill() , Selection.stroke()
ColorModel	CMYK GRAYSCALE HSB LAB NONE RGB	The color model to use for a SolidColor .
ColorPicker	ADOBE APPLE PLUGIN WINDOWS	The preferred color-selection tool, set in Preferences .
ColorProfileType	CUSTOM NONE WORKING	The type of color profile used to manage this document, set in Document.colorProfileType .
ColorReductionType	ADAPTIVE BLACKWHITE CUSTOM GRAYSCALE MACINTOSH PERCEPTUAL RESTRICTIVE SELECTIVE WINDOWS	The color reduction algorithm option for ExportOptionsSaveForWeb .
ColorSpaceType	ADOBERGB COLORMATCHRGB PROPHOTORGB SRGB	The type of color space to use in CameraRAWOpenOptions .
CopyrightedType	COPYRIGHTEDWORK PUBLICDOMAIN UNMARKED	The copyright status of a document. Used in DocumentPrintSettings.copyrighted .

Constant type	Values	What it means
CreateFields	DUPLICATION INTERPOLATION	The method to use for creating fields. Pass to ArtLayer.applyDelInterlace() .
CropToType	ARTBOX BLEEDBOX BOUNDINGBOX CROPBOX MEDIABOX TRIMBOX	The style to use when cropping a page in a PDF document. Set in PDFOpenOptions.cropPage .
DCSType	COLORCOMPOSITE GRAYSCALECOMPOSITE NOCOMPOSITE	The type of composite DCS file to create with DCS1_SaveOptions or DCS2_SaveOptions : COLORCOMPOSITE: Creates a color composite file in addition to DCS files. GRAYSCALECOMPOSITE: Creates a grayscale composite file in addition to DCS files. NOCOMPOSITE: Does not create a composite file.
DepthMapSource	IMAGEHIGHLIGHT LAYERMASK NONE TRANSPARENCYCHANNEL	The source to use for the depth map. Pass to ArtLayer.applyLensBlur() .
DescValueType	ALIATYPE BOOLEAN CLASSTYPE DOUBLET ENUMERATEDTYPE INTEGERTYPE LISTTYPE OBJECTTYPE RAWTYPE REFERENCETYPE STRINGTYPE UNITDOUBLE	The value type of an action key, returned by ActionDescriptor.getType() and ActionList.getType() .
DialogModes	ALL ERROR NO	Controls the type of dialogs Photoshop displays when running scripts.
Direction	HORIZONTAL VERTICAL	<ul style="list-style-type: none"> • The direction in which to flip the document canvas, passed to Document.flipCanvas(). • The orientation of text in TextItem.direction. • The direction of text warping in TextItem.warpDirection.
DisplacementMapType	STRETCHTOFIT TILE	Describes how the displacement map fits the image if the image is not the same size as the map. Pass to ArtLayer.applyDisplace() .

Constant type	Values	What it means
Dither	DIFFUSION NOISE NONE PATTERN	The type of dithering to use in GIFSaveOptions , IndexedConversionOptions and ExportOptionsSaveForWeb .
DocPositionStyle	PRINTCENTERED USERDEFINED	The type of positioning to use in <code>DocPosition</code>
DocumentFill	BACKGROUNDCOLOR TRANSPARENT WHITE	The fill type of a new document, passed to Documents.add() .
DocumentMode	BITMAP CMYK DUOTONE GRAYSCALE INDEXEDCOLOR LAB MULTICHANNEL RGB	The color mode of a open document, Document.mode . See also Document.changeMode() .
EditLogItemsType	CONCISE DETAILED SESSIONONLY	The preferred level of detail in th history log, set in Preferences : CONCISE: Save a concise history log. DETAILED: Save a detailed history log. SESSIONONLY: Save history log only for the session.
ElementPlacement	INSIDE PLACEATBEGINNING PLACEATEND PLACEBEFORE PLACEAFTER	The object's position in the Layers palette. Note: Not all values are valid for all object types. See the specific object description to make sure you are using a valid value.
EliminateFields	EVENFIELDS ODDFIELDS	The type of fields to eliminate. Pass to ArtLayer.applyDelInterlace() .
ExportType	ILLUSTRATORPATHS SAVEFORWEB	The type of export for Document.exportDocument() . This is equivalent to choosing File > Export > Paths To Illustrator , or File > Save For Web and Devices .
Extension	LOWERCASE NONE UPPERCASE	The policy and format for appending an extension to the filename when saving with Document.saveAs() .

Constant type	Values	What it means
FileNamingType	DDMM DDMMYY DOCUMENTNAMELOWER DOCUMENTNAMEMIXED DOCUMENTNAMEUPPER EXTENSIONLOWER EXTENSIONUPPER MMDD MMDDYY SERIALLETTERLOWER SERIALLETTERUPPER SERIALNUMBER1 SERIALNUMBER2 SERIALNUMBER3 SERIALNUMBER4 YYDDMM YYMMDD YYYYMMDD	File naming options for the BatchOptions used with the Application.batch() method.
FontPreviewType	LARGE MEDIUM NONE SMALL	The preferred type size to use for font previews in the type tool font menus , set in Preferences .
FontSize	LARGE MEDIUM SMALL	The preferred type size to use for panels and dialogs, set in Preferences .
ForcedColors	BLACKWHITE NONE PRIMARIES WEB	<p>The type of colors to be included the color table regardless of their usage. Used in GIFSaveOptions and IndexedConversionOptions.</p> <p>BLACKWHITE: Pure black and pure white.</p> <p>NONE: None</p> <p>PRIMARIES: Red, green, blue, cyan, magenta, yellow, black, and white.</p> <p>WEB: the 216 web-safe colors.</p>
FormatOptions	OPTIMIZEDBASELINE PROGRESSIVE STANDARDBASELINE	<p>The option with which to save a JPEG file, in JPEGSaveOptions.</p> <p>OPTIMIZEDBASELINE: Optimized color and a slightly reduced file size.</p> <p>PROGRESSIVE: Displays a series of increasingly detailed scans as the image downloads.</p> <p>STANDARDBASELINE: Format recognized by most web browsers.</p>
GalleryConstrainType	CONSTRAINBOTH CONSTRAINHEIGHT CONSTRAINWIDTH	The type of proportions to constrain for images. Used in GalleryImagesOptions .

Constant type	Values	What it means
GalleryFontType	ARIAL COURIERNEW HELVETICA TIMESNEWROMAN	The fonts to use for the Web photo gallery captions and other text. Used in GalleryBannerOptions , GalleryImagesOptions , and GalleryThumbnailOptions . Also used in PicturePackageOptions .
GallerySecurityTextColorType	BLACK CUSTOM WHITE	The color to use for text displayed over gallery images as an antitheft deterrent. Used in GallerySecurityOptions .
GallerySecurityTextPositionType	CENTERED LOWERLEFT LOWERRIGHT UPPERLEFT UPPERRIGHT	The position of the text displayed over gallery images as an antitheft deterrent. Used in GallerySecurityOptions . Also used in PicturePackageOptions .
GallerySecurityTextRotateType	CLOCKWISE45 CLOCKWISE90 COUNTERCLOCKWISE45 COUNTERCLOCKWISE90 ZERO	The orientation of the text displayed over gallery images as an antitheft deterrent. Used in GallerySecurityOptions . Also used in PicturePackageOptions .
GallerySecurityType	CAPTION COPYRIGHT CREDIT CUSTOMTEXT FILENAME NONE TITLE	The content to use for text displayed over gallery images as an antitheft deterrent. Used in GallerySecurityOptions . Note: All types draw from the image's file information except CUSTOMTEXT.
GalleryThumbSizeType	CUSTOM LARGE MEDIUM SMALL	The size of thumbnail images in the web photo gallery. Used in GalleryThumbnailOptions .
Geometry	HEPTAGON HEXAGON OCTAGON PENTAGON SQUARE TRIANGLE	Geometric options for shapes, such as the iris shape in the Lens Blur Filter. Pass to ArtLayer.applyLensBlur() .
GridLineStyle	DASHED DOTTED SOLID	The preferred line style for the nonprinting grid displayed over images, set in Preferences .
GridSize	LARGE MEDIUM NONE SMALL	The preferred size of grid line spacing, set in Preferences .

Constant type	Values	What it means
GuideLineStyle	DASHED SOLID	The preferred line style for nonprinting guides displayed over images, set in Preferences .
IllustratorPathType	ALLPATHS DOCUMENTBOUNDS NAMEDPATH	The paths to export to an Illustrator file using Document.exportDocument() .
Intent	ABSOLUTECOLORIMETRIC PERCEPTUAL RELATIVECOLORIMETRIC SATURATION	The rendering intent to use when converting from one color space to another with Document.convertProfile() or Document.print()
Justification	CENTER CENTERJUSTIFIED FULLYJUSTIFIED LEFT LEFTJUSTIFIED RIGHT RIGHTJUSTIFIED	The placement of paragraph text within the bounding box. Used in TextItem.justification .
Language	BRAZILLIANPORTUGUESE CANADIANFRENCH DANISH DUTCH ENGLISHUK ENGLISHUSA FINNISH FRENCH GERMAN ITALIAN NORWEGIAN NYNORSKNORWEGIAN OLDGERMAN PORTUGUESE SPANISH SWEDISH SWISSGERMAN	The language to use for text. Used in TextItem.language .
LayerCompression	RLE ZIP	Compression methods for data for pixels in layers, when saving to TIFF format. Used in TiffSaveOptions .

Constant type	Values	What it means
LayerKind	BLACKANDWHITE BRIGHTNESSCONTRAST CHANNELMIXER COLORBALANCE CURVES EXPOSURE GRADIENTFILL GRADIENTMAP HUESATURATION INVERSION LEVELS NORMAL PATTERNFILL PHOTOFILTER POSTERIZE SELECTIVECOLOR SMARTOBJECT SOLIDFILL TEXT THRESHOLD LAYER3D VIBRANCE VIDEO	The type of a layer object, in ArtLayer.kind . Note: You can create a text layer only from an empty art layer.
LensType	MOVIEPRIME PRIME105 PRIME35 ZOOMLENS	The type of lens to use. Pass to ArtLayer.applyLensFlare() .
MagnificationType	ACTUALSIZE FITPAGE	The type of magnification to use when viewing an image. Used in PresentationOptions .
MatteType	BACKGROUND BLACK FOREGROUND NETSCAPE NONE SEMIGRAY WHITE	The color to use to fill anti-aliased edges adjacent to transparent areas of the image. When transparency is turned off for an image, the matte color is applied to transparent areas. Used in GIFSaveOptions , IndexedConversionOptions , and JPEGSaveOptions .
MeasurementRange	ALLMEASUREMENTS ACTIVEMEASUREMENTS	The measurement to act upon. Pass to MeasurementLog methods.
MeasurementSource	MEASURESELECTION MEASURECOUNTOOL MEASURERULERTOOL	The source for recording measurements. Pass to Document.recordMeasurements() .
NewDocumentMode	BITMAP CMYK GRAYSCALE LAB RGB	The color profile to use for a new document. Pass to Documents.add() . Also used in ContactSheetOptions and PicturePackageOptions .

Constant type	Values	What it means
NoiseDistribution	GAUSSIAN UNIFORM	Distribution method to use when applying an Add Noise filter. Pass to ArtLayer.applyAddNoise() .
OffsetUndefinedAreas	REPEATEDGEPIXELS SETTOBACKGROUND WRAPAROUND	Method to use to fill the empty space left by offsetting a an image or selection. Pass to ArtLayer.applyOffset() .
OpenDocumentMode	CMYK GRAYSCALE LAB RGB	The color profile to use when opening an EPS or PDF document. Pass to <code>app.open()</code> in EPSOpenOptions or PDFOpenOptions .
OpenDocumentType	ALIASPIX BMP CAMERARAW COMPUSERVEGIF DICOM ELECTRICIMAGE EPS EPSPICTPREVIEW EPSTIFFPREVIEW FILMSTRIP JPEG PCX PDF PHOTOCOD PHOTOSHOP PHOTOSHOPDCS_1 PHOTOSHOPDCS_2 PHOTOSHOPEPS PHOTOSHOPPDF PICTFILEFORMAT PICTRESOURCEFORMAT PIXAR PNG PORTABLEBITMAP RAW SCITEXCT SGIRGB SOFTIMAGE TARGA TIFF WAVEFRONTTLA WIRELESSBITMAP	<p>The format in which to open the document, using <code>app.open()</code>.</p> <p>Note: PHOTOCOD is deprecated. Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.</p> <p>Note: The DICOM option is for the Extended version only.</p>
OperatingSystem	OS2 WINDOWS	The target operating system in BMPSaveOptions .
Orientation	LANDSCAPE PORTRAIT	<p>Page orientation for PhotoCDOpenOptions, deprecated in Photoshop CS3.</p> <p>Note: Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.</p>

Constant type	Values	What it means
OtherPaintingCursors	PRECISEOTHER STANDARDOTHER	The preferred pointer for the following tools: Eraser, Pencil, Paintbrush, Healing Brush, Rubber Stamp, Pattern Stamp, Smudge, Blur, Sharpen, Dodge, Burn, Sponge. Set in Preferences .
PaintingCursors	BRUSHSIZE PRECISE STANDARD	The preferred pointer for the following tools: Marquee, Lasso, Polygonal Lasso, Magic Wand, Crop, Slice, Patch Eyedropper, Pen, Gradient, Line, Paint Bucket, Magnetic Lasso, Magnetic Pen, Freeform Pen, Measure, Color Sampler. Set in Preferences .
PaletteType	EXACT LOCALADAPTIVE LOCALPERCEPTUAL LOCALSELECTIVE MACOSPALETTE MASTERADAPTIVE MASTERPERCEPTUAL MASTERSELECTIVE PREVIOUSPALETTE UNIFORM WEBPALETTE WINDOWSPALETTE	The palette type to use in GIFSaveOptions and IndexedConversionOptions .
PathKind	CLIPPINGPATH NORMALPATH TEXTMASK VECTORMASK WORKPATH	The type of a PathItem .
PDFCompatibility	PDF13 PDF14 PDF15 PDF16 PDF17	The PDF version to make the document compatible with. Used in PDFSaveOptions .
PDFEncoding	JPEG JPEG2000HIGH JPEG2000LOSSLESS JPEG2000LOW JPEG2000MED JPEG2000MEDHIGH JPEG2000MEDLOW JPEGHIGH JPEGLow JPEGMED JPEGMEDHIGH JPEGMEDLOW NONE PDFZIP PDFZIP4BIT	The type of compression to use when saving a document in PDF format. Used in PDFSaveOptions .

Constant type	Values	What it means
PDFResample	NONE PDFAVERAGE PDFBICUBIC PDFSUBSAMPLE	The down sample method to use. Used in PDFSaveOptions .
PDFStandard	NONE PDFX1A2001 PDFX1A2003 PDFX32002 PDFX32003 PDFX42008	The PDF standard to make the document compatible with. Used in PDFSaveOptions .
PhotoCDColorSpace	LAB16 LAB8 RGB16 RGB8	The color space for PhotoCDOpenOptions , deprecated in Photoshop CS3. Note: Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.
PhotoCDSize	EXTRALARGE LARGE MAXIMUM MEDIUM MINIMUM SMALL	The pixel dimensions of the image in PhotoCDOpenOptions , deprecated in Photoshop CS3. EXTRALARGE = 1024x1536 LARGE = 512x768 MAXIMUM = 2048x3072 MEDIUM = 256x384 MINIMUM = 64x96 SMALL = 128x192 Note: Kodak PhotoCD is now found in the Goodies folder on the Adobe Photoshop CS5 Install DVD.
PICTBitsPerPixels	EIGHT FOUR SIXTEEN THIRTYTWO TWO	The number of bits per pixel to use when compression a PICT file. Used in PICTFileSaveOptions and PICTResourceSaveOptions . Note: Use 16 or 32 for RGB images; use 2, 4, or 8 for bitmap and grayscale images.
PICTCompression	JPEGHIGHPICT JPEGLOWPICT JPEGMAXIMUMPICT JPEGMEDIUMPICT NONE	The type of compression to use when saving an image as a PICT file. Used in PICTFileSaveOptions and PICTResourceSaveOptions .
PicturePackageTextType	CAPTION COPYRIGHT CREDIT FILENAME NONE ORIGIN USER	The function or meaning of text in a Picture Package. Used in PicturePackageOptions .

Constant type	Values	What it means
PointKind	CORNERPOINT SMOOTHPOINT	The role a PathPoint plays in a PathItem .
PointType	POSTSCRIPT TRADITIONAL	The preferred measurement to use for type points, set in Preferences.pointSize : POSTSCRIPT = 72 points/inch. TRADITIONAL = 72.27 points/inch.
PolarConversionType	POLARTORECTANGULAR RECTANGULARTOPOLAR	The method of polar distortion to use. Pass to ArtLayer.applyPolarCoordinates() .
Preview	EIGHTBITTIFF MACOSEIGHTBIT MACOSJPEG MACOSMONOCHROME MONOCHROMETIFF NONE	The type of image to use as a low-resolution preview in the destination application. Used in DCS1_SaveOptions , DCS2_SaveOptions , and EPSSaveOptions .
PrintColorHandling	PRINTERMANAGED PHOTOSHOPMANAGED SEPARATIONS	The type of color handling to use for ColorHandling
PurgeTarget	ALLCACHES CLIPBOARDCACHE HISTORYCACHES UNDOCACHES	Cache to be targeted in an Application.purge() operation.
QueryStateType	ALWAYS ASK NEVER	The preferred policy for checking whether to maximize compatibility when opening PSD files, set in Preferences.maximizeCompatibility .
RadialBlurMethod	SPIN ZOOM	The blur method to use. Pass to ArtLayer.applyRadialBlur() .
RadialBlurQuality	BEST DRAFT GOOD	The smoothness or graininess of the blurred image. Pass to ArtLayer.applyRadialBlur() .
RasterizeType	ENTIRELAYER FILLCONTENT LAYERCLIPPINGPATH LINKEDLAYERS SHAPE TEXTCONTENTS	The layer element to rasterize, using ArtLayer.rasterize() .
ReferenceFormType	CLASSTYPE ENUMERATED IDENTIFIER INDEX NAME OFFSET PROPERTY	The type of an ActionReference object, returned by getForm() .

Constant type	Values	What it means
ResampleMethod	BICUBIC BICUBICSHARPER BICUBICSMOOTHER BILINEAR NEARESTNEIGHBOR NONE	The method to use for image interpolation. Passed to Document.resizeImage() , and used as the value of Preferences.interpolation .
RippleSize	LARGE MEDIUM SMALL	The size of undulations to use. Pass to ArtLayer.applyRipple() .
SaveBehavior	ALWAYS SAVE ASKWHENSAVING NEVERSAVE	The application's preferred behavior when saving a document. See Preferences.appendExtension and imagePreviews
SaveDocumentType	ALIASPIX BMP COMPUSEVEGIF ELECTRICIMAGE JPEG PCX PHOTOSHOP PHOTOSHOPDCS_1 PHOTOSHOPDCS_2 PHOTOSHOPEPS PHOTOSHOPPDF PICTFileFORMAT PICTRESOURCEFORMAT PIXAR PNG PORTABLEBITMAP RAW SCITEXCT SGIRGB SOFTIMAGE TARGA TIFF WAVEFRONTLA WIRELESSBITMAP	The format in which to save a document when exporting with Document.exportDocument() . Pass in ExportOptionsSaveForWeb.format , to specify the type of file to write. Only the following are supported for export: COMPUSEVEGIF, JPEG, PNG-8, PNG-24, and BMP.
SaveEncoding	ASCII BINARY JPEGHIGH JPEGLOW JPEGMAXIMUM JPEGMEDIUM	The type of encoding to use when saving a file to DCS or EPS with Document.saveAs() .
SaveLogItemsType	LOGFILE LOGFILEANDMETADATA METADATA	The preferred location of history log data, set in Preferences.saveLogItems .
SaveOptions	DONOTSAVECHANGES PROMPTTOSAVECHANGES SAVECHANGES	The policy for closing a document with Document.close() .

Constant type	Values	What it means
SelectionType	DIMINISH EXTEND INTERSECT REPLACE	<p>The selection behavior when a selection already exists:</p> <p>DIMINISH: Remove the selection from the already selected area.</p> <p>EXTEND: Add the selection to an already selected area.</p> <p>INTERSECT: Make the selection only the area where the new selection intersects the already selected area.</p> <p>REPLACE: Replace the selected area.</p> <p>Used in PathItem.makeSelection(), Selection.load(), Selection.select(), and Selection.store().</p>
ShapeOperation	SHAPEADD SHAPEINTERSECT SHAPESUBTRACT SHAPEXOR	<p>How to combine the shapes if the destination path already has a selection.</p> <p>Set for SubPathInfo.operation, stored in the resulting SubPathItem.</p>
SmartBlurMode	EDGEONLY NORMAL OVERLAYEDGE	<p>The method to use for smart blurring:</p> <p>EDGEONLY, OVERLAYEDGES: Apply blur only to edges of color transitions.</p> <p>NORMAL: Apply blur to entire image.</p> <p>Pass to ArtLayer.applySmartBlur().</p>
SmartBlurQuality	HIGH LOW MEDIUM	The blur quality to use. Pass to ArtLayer.applySmartBlur() .
SourceSpaceType	DOCUMENT PROOF	The color space for source when printing with Document.print() .
SpherizeMode	HORIZONTAL NORMAL VERTICAL	The curve (or stretch shape) to use for the distortion. Pass to ArtLayer.applySpherize() .
StrikeThruType	STRIKEBOX STRIKEHEIGHT STRIKEOFF	The style of strikethrough to use in text. Used in TextItem.strikeThru .
StrokeLocation	CENTER INSIDE OUTSIDE	The placement of path or selection boundary strokes. Pass to Selection.stroke() .
TargaBitsPerPixels	SIXTEEN THIRTYTWO TWENTYFOUR	The resolution to use when saving an image in Targa format. Used in TargaSaveOptions .

Constant type	Values	What it means
TextCase	ALLCAPS NORMAL SMALLCAPS	The capitalization style to use in text. Used in TextItem.capitalization .
TextComposer	ADOBEEVERYLINE ADOBESINGLELINE	The composition method to use to optimize the specified hyphenation and justification options. Used in TextItem.textComposer .
TextType	PARAGRAPHTEXT POINTTEXT	The type of text, used in TextItem.kind . PARAGRAPHTEXT: Text that wraps within a bounding box. POINTTEXT: Text that does not wrap.
TextureType	BLOCKS CANVAS FILE FROSTED TINYLENS	The type of texture or glass surface image to load for a texturizer or glass filter. Pass to ArtLayer.applyGlassEffect() .
TIFFEncoding	JPEG NONE TIFFLZW TIFFZIP	The type of compression to use for TIFF files. Used in TiffSaveOptions .
ToolType	ARTHISTORYBRUSH BACKGROUNDeraser BLUR BRUSH BURN CLONESTAMP COLORREPLACEMENTTOOL DODGE ERASER HEALINGBRUSH HISTORYBRUSH PATTERNSTAMP PENCIL SHARPEN SMUDGE SPONGE	The tool to use with PathItem.strokePath() .
TransitionType	BLINDSHORIZONTAL BLINDSVERTICAL BOXIN BOXOUT DISSOLVE GLITTERDOWN GLITTERRIGHT GLITTERRIGHTDOWN NONE RANDOM SPLITHORIZONTALIN SPLITHORIZONTALOUT SPLITVERTICALIN SPLITVERTICALOUT WIPEDOWN WIPELEFT WIPERIGHT WIPEUP	The method to use for transition from one image to the next in a PDF presentation. Used in PresentationOptions .

Constant type	Values	What it means
TrimType	BOTTOMRIGHT TOPLEFT TRANSPARENT	Type of pixels to trim around an image, passed to Document.trim() .: BOTTOMRIGHT = bottom right pixel color. TOPLEFT = top left pixel color.
TypeUnits	MM PIXELS POINTS	The preferred unit for text character measurements, set in Preferences .
UndefinedAreas	REPEATEDGEPIXELS WRAPAROUND	The method to use to treat undistorted areas or areas left blank in an image to which the a filter in the Distort category has been applied. Pass to ArtLayer.applyDisplace() , applyShear() , applyWave() .
UnderlineType	UNDERLINELEFT UNDERLINEOFF UNDERLINERIGHT	The placement of text underlining. Used in TextItem.underline . Note: UNDERLINELEFT and UNDELINERIGHT are valid only when <code>direction = Direction.VERTICAL</code> .
Units	CM INCHES MM PERCENT PICAS PIXELS POINTS	The preferred measurement unit for type and ruler increments, set in Preferences.rulerUnits .
Urgency	FOUR HIGH LOW NONE NORMAL SEVEN SIX THREE TWO	The editorial urgency status of a document, set in DocumentPrintSettings.urgency .
WarpStyle	ARC ARCH ARCLOWER ARCUPPER BULGE FISH FISHEYE FLAG INFLATE NONE RISE SHELLLOWER SHELLUPPER SQUEEZE TWIST WAVE	The warp style to use for text. Used in TextItem.warpStyle .

Constant type	Values	What it means
WaveType	SINE SQUARE TRIANGULAR	The type of wave to use. Pass to ArtLayer.applyWave() .
WhiteBalanceType	ASSHOT AUTO CLOUDY CUSTOM DAYLIGHT FLASH FLUORESCENT SHADE TUNGSTEN	Lighting conditions that affect color balance. Set in CameraRAWOpenOptions .
ZigZagType	AROUNDCENTER OUTFROMCENTER PONDRIPPLES	The method of zigzagging to use. Pass to ArtLayer.applyZigZag() .

Appendix A: Event ID Codes

The following table lists events and their four-character ID codes or string identifiers for use with the `notifier` object.

Note: Do not include single quotes (') with four-character IDs in your code. The single quotes are used in this table to illustrate the placement of required spaces in codes that do not contain four letters. However, string identifiers, which are longer than four characters, require double quotes in the code.

Tip: If you can't find the event you want to use for notification in this table, you can use `ScriptListener` to determine the event ID code. See the `ScriptListener` documentation in the Action Manager chapter of the *Photoshop CS5 Scripting Guide*.

Event	4-char ID or String
3DTransform	'TdT '
Average	'Avrg'
ApplyStyle	'ASty'
Assert	'Asrt'
AccentedEdges	'AccE'
Add	'Add '
AddNoise	'AdNs'
AddTo	'AddT'
Align	'Algn'
All	'All '
AngledStrokes	'AngS'
ApplyImage	'AppI'
BasRelief	'BsRl'
Batch	'Btch'
BatchFromDroplet	'BtcF'
Blur	'Blr '
BlurMore	'BlrM'
Border	'Brdr'
Brightness	'BrgC'
CanvasSize	'CnvS'
ChalkCharcoal	'ChlC'
ChannelMixer	'ChnM'

Event	4-char ID or String
Charcoal	'Chrc'
Chrome	'Chrm'
Clear	'Cler'
Close	'Cls '
Clouds	'Clds'
ColorBalance	'ClrB'
ColorHalftone	'ClrH'
ColorRange	'ClrR'
ColoredPencil	'ClrP'
ContactSheet	"0B71D221-F8CE-11d2-B21B-0008C75B322C"
ConteCrayon	'CntC'
Contract	'Cntc'
ConvertMode	'CnvM'
Copy	'copy'
CopyEffects	'CpFX'
CopyMerged	'CpyM'
CopyToLayer	'CpTL'
Craquelure	'Crql'
CreateDroplet	'CrtD'
Crop	'Crop'
Crosshatch	'Crsh'
Crystallize	'Crst'
Curves	'Crvs'
Custom	'Cstm'
Cut	'cut '
CutToLayer	'CtTL'
Cutout	'Ct '
DarkStrokes	'DrkS'
DeInterlace	'Dntr'
DefinePattern	'DfnP'
Defringe	'Dfrg'
Delete	'Dlt '
Desaturate	'Dstt'

Event	4-char ID or String
Deselect	'Dslc'
Despeckle	'Dspc'
DifferenceClouds	'DrfC'
Diffuse	'Dfs '
DiffuseGlow	'DfsG'
DisableLayerFX	'dlfx'
Displace	'Dspl'
Distribute	'Dstr'
Draw	'Draw'
DryBrush	'DryB'
Duplicate	'Dplc'
DustAndScratches	'DstS'
Emboss	'Embs'
Equalize	'Eqlz'
Exchange	'Exch'
Expand	'Expn'
Export	'Expr'
JumpTo	'Jpto'
ExportTransparentImage	"02879e00-cb66-11d1-bc43-0060b0a13dc4"
Extrude	'Extr'
Facet	'Fct '
Fade	'Fade'
Feather	'Fthr'
Fibers	'Fbrs'
Fill	'Fl '
FilmGrain	'FlmG'
Filter	'Fltr'
FindEdges	'FndE'
FitImage	"3caa3434-cb67-11d1-bc43-0060b0a13dc4"
FlattenImage	'FltI'
Flip	'Flip'
Fragment	'Frgm'
Fresco	'Frsc'

Event	4-char ID or String
GaussianBlur	'GsnB'
Get	'getd'
Glass	'Gls '
GlowingEdges	'GlwE'
Gradient	'Grdn'
GradientMap	'GrMp'
Grain	'Grn '
GraphicPen	'GraP'
Group	'GrpL'
Grow	'Grow'
HalftoneScreen	'Hlfs'
Hide	'Hd '
HighPass	'HghP'
HSBHSL	'HsbP'
HueSaturation	'HStr'
ImageSize	'ImgS'
Import	'Impr'
InkOutlines	'InkO'
Intersect	'Intr'
IntersectWith	'IntW'
Inverse	'Invs'
Invert	'Invr'
LensFlare	'LnsF'
Levels	'Lvls'
LightingEffects	'LghE'
Link	'Lnk '
Make	'Mk '
Maximum	'Mxm '
Median	'Mdn '
MergeLayers	'Mrg2'
MergeLayersOld	'MrgL'
MergeSpotChannel	'MSpt'
MergeVisible	'MrgV'

Event	4-char ID or String
Mezzotint	'Mztn'
Minimum	'Mnm '
ModeChange	"8cba8cd6-cb66-11d1-bc43-0060b0a13dc4"
Mosaic	'Msc '
Mosaic_PLUGIN	'MscT'
MotionBlur	'MtnB'
Move	'move'
NTSCColors	'NTSC'
NeonGlow	'NGlw'
Next	'Nxt '
NotePaper	'NtPr'
Notify	'Ntfy'
Null	typeNull
OceanRipple	'OcnR'
Offset	'Ofst'
Open	'Opn '
Paint	'Pnt '
PaintDaubs	'PntD'
PaletteKnife	'PltK'
Paste	'past'
PasteEffects	'PaFX'
PasteInto	'PstI'
PasteOutside	'PstO'
Patchwork	'Ptch'
Photocopy	'Phtc'
PicturePackage	"4C1ABF40-DD82-11d2-B20F-0008C75B322C"
Pinch	'Pnch'
Place	'Plc '
Plaster	'Plst'
PlasticWrap	'PlsW'
Play	'Ply '
Pointillize	'Pntl'
Polar	'Plr '

Event	4-char ID or String
PosterEdges	'PstE'
Posterize	'Pstr'
Previous	'Prvs'
Print	'Prnt'
ProfileToProfile	'PrfT'
Purge	'Prge'
Quit	'quit'
RadialBlur	'RdlB'
Rasterize	'Rstr'
RasterizeTypeSheet	'RstT'
RemoveBlackMatte	'RmvB'
RemoveLayerMask	'RmvL'
RemoveWhiteMatte	'RmvW'
Rename	'Rnm '
ReplaceColor	'RplC'
Reset	'Rset'
ResizeImage	"1333cf0c-cb67-11d1-bc43-0060b0a13dc4"
Reticulation	'Rtcl'
Revert	'Rvrt'
Ripple	'Rple'
Rotate	'Rtte'
RoughPastels	'RghP'
Save	'save'
Select	'slct'
SelectiveColor	'SlcC'
Set	'setd'
SharpenEdges	'ShrE'
Sharpen	'Shrp'
SharpenMore	'ShrM'
Shear	'Shr '
Show	'Shw '
Similar	'Smlr'
SmartBlur	'SmrB'

Event	4-char ID or String
Smooth	'Smth'
SmudgeStick	'SmdS'
Solarize	'Slrz'
Spatter	'Spt '
Spherize	'Sphr'
SplitChannels	'SplC'
Sponge	'Spng'
SprayedStrokes	'SprS'
StainedGlass	'StnG'
Stamp	'Stmp'
Stop	'Stop'
Stroke	'Strk'
Subtract	'Sbtr'
SubtractFrom	'SbtF'
Sumie	'Smie'
TakeMergedSnapshot	'TkMr'
TakeSnapshot	'TkSn'
TextureFill	'TxtF'
Texturizer	'Txtz'
Threshold	'Thrs'
Tiles	'Tls '
TornEdges	'TrnE'
TraceContour	'TrcC'
Transform	'Trnf'
Trap	'Trap'
Twirl	'Twrl'
Underpainting	'Undr'
Undo	'undo'
Ungroup	'Ungr'
Unlink	'Unlk'
UnsharpMask	'UnsM'
Variations	'Vrtn'
Wait	'Wait'

Event	4-char ID or String
WaterPaper	'WtrP'
Watercolor	'Wtrc'
Wave	'Wave'
Wind	'Wnd '
ZigZag	'ZgZg'
BackLight	'BacL'
FillFlash	'File'
ColorCast	'ColE'

Index

A

- Action Manager 195
- actions
 - command lists 42
 - descriptions 45
 - descriptors 39
 - playing 49
- active document 47
- activePrinter 98
- Add Noise filter
- adjustments
 - brightness 57
 - color 199
 - color balance 57, 63
 - contrast 57, 61
 - curves 57
 - highlights 64
 - levels 57, 61
 - shadows 64
 - temperature 63
- Adobe Illustrator, exporting paths to 107
- alpha channels
 - defined 74
 - from transparency (TIFF documents) 188
 - opacity 74
 - saving
 - in BMP documents 71
 - in PDF documents 150
 - in PICT documents 155
 - in PICT resources 156
 - in Pixar documents 158
 - in PSD documents 154
 - in RAW documents 166
 - in SGIRGB documents 173
 - in Targa documents 178
 - in TIFF documents 188
- anchor points
 - adding 145
- annotations, importing 94
- anti aliasing
 - text 181
- application
 - activating 49
 - checking if feature enabled 49
 - defaults 160
 - location 48
 - preferences 160
- artLayers, *See* layers
- Asian text 162
- authors 101
- auto kerning 181, 199
- auto leading 186
- auto spacing, contact sheets 84

- available memory 47
- Average filter 57

B

- background color
 - application 47
 - galleries 112
- background layers 55
- backgroundColor 98
- baseline shift 181
- batch command 49
- batches
 - destination folder 68, 199
 - specifying options 68
- beeping 160
- bitmap documents
 - converting to 200
 - depth type 200
 - halftone type 200
 - opening 209
 - saving 71
- bitmap images
 - See* bitmap documents
- black and white images 64
- bleedWidth 98
- blending modes
 - layer sets 131
 - layers 55
- Blur filter 57
- blur filters
 - Average 57
 - Blur More 57
 - Gaussian Blur 58
 - Lens Blur 59
 - Motion Blur 60
 - Radial Blur 60
 - Smart Blur 61
- Blur More filter 57
- BMP documents
 - See* bitmap documents
- brightness 57
 - adjusting 57
 - equalizing 62
- build 47

C

- caches
 - images 161
 - purging 51
- camera raw documents
 - opening 72
 - settings 201
 - size options 201

- canvas
 - flipping 94
 - resizing 94
 - canvas, defined 90
 - caption 98
 - captions
 - contact sheets 84
 - documents 101
 - gallery images 113
 - gallery thumbnails 117
 - images 101
 - centerCropMarks 98
 - channels
 - activating 90
 - adding 76
 - adjusting 57
 - alpha *See* alpha channels
 - creating 76
 - deleting 74
 - displaying in color 160
 - duplicating 74
 - making visible 74
 - merging 74
 - mixing 63
 - splitting 95
 - spot *See* spot channels
 - types of 74
 - clipping paths
 - from paths 141
 - from text 187
 - Clouds filter 57
 - CMYKColor 81
 - color balance, adjusting 63
 - color picker 160
 - color profiles
 - changing 93
 - determining type of 91
 - naming 90
 - color profiles, *see* individual document formats
 - color samplers
 - adding 83
 - creating 83
 - moving 82
 - removing 82
 - colorBars 98
 - colorHandling 98
 - colors
 - active links 112
 - adjusting 199
 - balancing 57
 - channels 74
 - CMYK 81
 - custom settings 115
 - in galleries 112
 - inverting 62
 - modifying 64
 - none 137
 - preserving (GIF only) 118
 - reduction 108
 - settings 47
 - solid color objects 174
 - testing if equal 174
 - visited links 112
 - comments, layer comps 128
 - compatibility, maximizing 161
 - component channels
 - color balance 57
 - defined 74
 - listing 90
 - See* composite channels
 - composite channels 74
 - See* component channels
 - Compuserve GIF documents
 - opening 209
 - saving 118
 - contact sheets
 - captions 84
 - columns 84
 - dimensions 84
 - making 50
 - rows 84
 - contrast
 - adjusting 57
 - adjusting automatically 61
 - camera raw settings 72
 - midtones 64
 - copies 98
 - copyrights 101
 - cornerCropMarks 98
 - count items
 - adding 86
 - creating 86
 - removing 85
 - cropping 93
 - CS5 version changes 35
 - cursors 162
 - curves, adjusting 57
 - Custom filters 57
- D**
- DCS 1 documents, saving 87
 - De-Interlace filter 58
 - desaturate 62
 - Despeckle filter 58
 - dialogs
 - displaying 47
 - Difference Clouds filter 58
 - Diffuse Glow filter 58
 - Displace filter 58
 - distort filters
 - Diffuse Glow 58
 - Displace 58
 - Glass Effect 58
 - Ocean Ripple 60
 - Pinch 60
 - Polar Coordinates 60
 - Ripple 60
 - Shear 60
 - Spherize 61

- Twirl 61
- Wave 61
- Zigzag 61
- document formats, *see* individual document formats
- DocumentPrintSettings 98
- documents 90
 - activating 47
 - adding 104
 - closing 92
 - code sample 96
 - color profiles 90
 - color samplers 90
 - counting items 91
 - counting objects 93
 - cropping 38, 93
 - dimensions 90
 - duplicating 38, 93
 - exporting 94
 - info 101
 - loading 50
 - managed 91
 - measurement scale 91
 - metadata 91, 101
 - open with Photoshop dialog 51
 - opening 51
 - optimizing for web 108
 - printing 94
 - resizing 94
 - resolution 92
 - saving 94, 95
 - suspending history 95
 - trapping (CMYK) 95
 - trimming 95
- Dust and Scratches filter 58

E

- Enable Info
 - constants 193
 - grammar 192
 - operator precedence 193
 - variables 194
- EPSSaveOptions 106
- equalize 62
- event IDs
 - using ScriptListener to find 218
- Events Manager 48
- executing scripts 34
- exif 101
- exporting
 - documents 94
 - paths 107
 - to Illustrator 107
 - to Web 108
- ExportOptionsIllustrator 107
- ExportOptionsSaveForWeb 108

F

- file extensions
 - format 163

- including 160
 - script files 33
- file metadata 101
- files
 - merging 50
- filetypes
 - macOS 48
 - Windows 49
- filling
 - paths 140
 - selections 169
- filter, *see* individual filter names
- flip 98
- Folder object 33
- fonts
 - detecting 47
 - determining family of 179
 - determining style of 179
- formats, *see* individual document formats

G

- galleries 115
 - background color 112
 - banners 111
 - captions 113
 - color options 112
 - credits 113
 - dimensions 113
 - filenames 113
 - link colors 112
 - making 49, 50
 - metadata 115
 - photographer 111
 - security text 116
 - thumbnail images 117
- GalleryBannerOptions 111
- GalleryCustomColorOptions 112
- GalleryImagesOptions 113, 114
- GalleryOptions 115
- GallerySecurityOptions 116
- GalleryThumbnailOptions 117
- Gaussian Blur filter 58
- GIF documents
 - See* Compuserve GIF documents
- GIFSaveOptions 118
- Glass Effect filter 58
- glyph scaling 181–184
- GrayColor 119
- grids 161
- grouped layers 55
- guides 161

H

- halftone screen 70
- hanging punctuation 182
- hardProof 98
- High Pass filter 58
- highlights
 - adjusting 64

- color balance 57
- histograms
 - channels 74
- history log 163
- history states
 - activating 90
 - allowing nonlinear 161
 - default number of 162
 - snapshot 122
 - suspending 95
- HSBColor 124
- hyphenation 183

I

- IDs
 - getting 39
 - PICT Resource 156
 - property 45
 - runtime 49
 - runtime to string 52
 - string to runtime 52
 - string to type 52
 - type to char 52
- Illustrator
 - See Adobe Illustrator
- image
 - resizing 94
- image pyramids 188
- images
 - bitmap 70
 - black and white 64
 - caches 161
 - captions 113
 - definition of 90
 - desaturating 62
 - equalizing 62
 - filetypes 48
 - from split channels 95
 - inverting colors 62
 - previewing 161
 - pyramids 188
 - resizing 94
 - resizing in galleries 114
 - thumbnails 117
- indexed color model 125
- IndexedConversionOptions 125
- individual document formats, examples 95
- installing scripts 34
- Intent 98
- interpolate 98
- interpolation 161

J

- JavaScript
 - changes in Photoshop CS5 35
 - supported features 33
- JavaScript Resource
 - Enable Info grammar 192
 - javascriptresource syntax 191

- javascriptresource tag 191
- JPEG
 - quality 126
- JPEG documents
 - quality 126
 - saving 126
- JPEG options
 - scans 126
- JPEGSaveOptions 126
- justification 183

K

- Kerning 181
 - text
 - auto kerning 199
- keyboard behavior 161

L

- LabColor 127
- labels 98
- languages 183
- layer comps 128
 - adding 129
 - applying 128
 - in documents 91
- layer sets
 - adding 133
 - art layers in 131
 - duplicating 132
 - in documents 91
 - linked layers in 131
 - linking 132
 - locking contents 131
 - moving 132
 - nesting 131
 - opacity 131
 - unlinking 132
- layer styles, applying 61
- LayerComps 129
- layered TIFF documents, saving 160
- Layers 130
- layers
 - adding 67
 - applying styles 61
 - background 55
 - blending mode 55
 - bounds 55
 - clipboard commands 61
 - comps 128
 - copying 61
 - duplicating 62
 - flattening 94
 - grouping 55
 - in documents 91
 - inverting 62
 - kind 55
 - linking 62
 - locking contents 55–56
 - making visible 56

- merging 62
- merging visible 94
- moving 63
- rasterizing 94
- rasterizing contents 63
- removing 67
- resizing 64
- rotating 64
- saving in PDF documents 150
- unlinking 64
- LayerSet 131
- LayerSets 133
- layersets
 - merging 132
- leading 183, 186
- Lens Blur filter
 - applying 59
- Lens Flare filter 59
- letter spacing 182–185
- levels
 - adjusting 57
 - adjusting automatically 57
- ligatures 181–183
- linked layers 62
 - unlinking 64
- links
 - colors 112

M

- MacOS
 - filetypes 48
- managed documents 91
- mapBlack 98
- maximizing compatibility 161
- Maximum filter 59
- Median Noise filter 59
- memory 47
- merging
 - layers 62
 - visible layers 94
- metadata
 - document 91
 - document object 101
 - galleries 115
 - xmp 92, 190
- methods
 - batch 49
- midtones
 - color balance 57
- Minimum filter 60
- Motion Blur filter 60

N

- negative 98
- noise filters
 - Add Noise
 - Despeckle 58
 - Dust and Scratches 58
 - Median Noise 59

- nonlinear history 161
- notifications
 - events within scripts 138
- notifiers
 - adding 139
 - event IDs 218
 - removing 138
- NTSC filter 60

O

- object model
 - changes in Photoshop CS5 35
- Ocean Ripple filter 60
- Offset filter 60
- old style type 185
- opacity
 - channels 74
 - gallery security text 116
 - layer fill 55
 - layer sets 131
 - layers 56
 - picture packages 157
- open options
 - DICOM format 89
 - EPS format 105
 - PDF format 149
 - Photo CD format 153
 - RAW format 72, 165
- optimizing 108
- other filters
 - Custom 57
 - High Pass 58
 - Maximum 59
 - Minimum 60
 - Offset 60

P

- palettes 162
- pasting 94
- path 48
- path items
 - adding 144
 - deselecting 140
 - filling 140
 - from text 187
 - making selection 141
 - path points 176
 - selecting 141
 - specifying path kind 140
 - stroking 141
 - sub items 140
 - sub path info 175
 - sub path items 176
 - work path from selection 169
- path point info
 - anchor points 146
 - left direction 146
 - right direction 146
- path points

- anchor points 145
 - left direction 145
 - right direction 145
- PathItems 144
- paths
 - See *path items*
- PDF documents
 - opening 149
 - saving 150
- PDF presentations
 - auto advance 164
 - making 50
 - output format 164
 - transition type 164
- Photo CD discs, opening 153
- photo filtering 63
- photo galleries
 - See *galleries*
- photomerge 50
- Photoshop documents
 - opening 209
 - saving 154
- Photoshop files, maximizing compatibility 161
- PICT documents
 - opening 209
 - saving 155
- PICT resources
 - opening 209
 - saving 156
- picture packages
 - contents 157
 - flattening 157
 - making 50
 - opacity 157
 - options 157
 - text properties 157
- Pinch filter 60
- Pixar documents
 - opening 209
 - saving 158
- PixarSaveOptions 158
- pixels
 - aspect ratio 91
 - doubling 162
 - equalizing 62
 - interpolation 161
 - locking 56
 - unit measures 216
- playback options 48
- playbackDisplayDialogs 48
- plug-in folder
 - additional plug-in folder 163
- PNG 8 documents, saving 108
- PNG documents
 - saving 159
- PNGSaveOptions 159
- Polar Coordinates filter 60
- posterrize 63
- postscript encoding 94
- PostScript names 179

- posX 98
- posY 98
- Preferences 160
- PresentationOptions 164
- presentations
 - making 50
 - PDF presentations
- printBorder 98
- printing, documents 94
- printOneCopy 94
- printSelected 98
- printSettings 91
- printSpace 98
- property
 - measurementLog 48
- PSD documents
 - opening 209
 - saving 154
- purging 51

Q

- quickMaskMode 92
- quote style 162

R

- Radial Blur filter 60
- rasterize 63
- rasterizing
 - document layers 94
- RAW documents
 - opening 165
- RawSaveOptions 166
- recentFiles 48
- registrationMarks 98
- render filters
 - Clouds 57
 - Difference Clouds 58
 - Lens Flare 59
- renderIntent 98
- resolution
 - bitmap conversions 70
 - documents 92
- RGBColor 167
- Ripple filter 60
- rotation 64
- ruler units 162
- runMenuItem 51

S

- save as 95
- saved 92
- saving 94
- saving, see *individual document formats*.
- scale 99
- scripting interface
 - build date 48
 - version 48
- scriptingVersion 48

scripts

- automation 191, 195
 - enabling/disabling in menu 191
 - executing 34
 - grouping in menu 191
 - installing 34
 - startup 34
 - terminology dictionary 195
 - valid file extensions 33
- Scripts Events Manager 48
- selected areas 92
- selections 168
- boundaries 168
 - clearing 168
 - copying 168
 - cutting 168
 - deselecting 168
 - feathering 168
 - filling 169
 - from paths 141
 - making work path from 169
 - resizing 168, 169
 - rotating 169
 - smoothing 170
 - stroking 170
- selective color 64
- SGIRGB documents
- saving 173, 213
- SGIRGBSaveOptions 173, 199
- shadows
- adjusting 64
 - color balance 57
- Sharpen Edges filter 60
- Sharpen filter 60
- sharpen filters
- Sharpen 60
 - Sharpen Edges 60
 - Sharpen More 60
 - Unsharp Mask 61
- Sharpen More filter 60
- Shear filter 60
- Smart Blur filter 61
- smart quotes 162
- Spherize filter 61
- spot channels
- defined 74
 - merging into component channels 75
 - opacity 74
 - saving
 - in DCS 2 documents 88
 - in PDF documents 151
 - in PSD documents 154
 - in RAW documents 166
 - in SGIRGB documents 173
 - in TIFF documents 188
- spotColors 173
- startup scripts 34
- strike thru 186
- stroking
- default stroke color 47

path items 141

selections 170

styles, applying 61

sub path items 140

systemInformation 48

T

temperature 63

terminology dictionary

defined 195

syntax 195

text

Asian 162

auto kerning 181

auto leading 186

captions 113

color

composer 186

content 181

creating paths from 187

formatting 186

gallery security 116, 206

hyphenation 183

in picture packages 157

justification 183

languages 183

offset 181

orientation 182

spacing 182–185

tracking 186

wrapping 183

text composer 186

text fonts

See fonts

text items

See text

text layers

adding contents 181

creating 55

Texture Fill filter 61

texture filters, Texture Fill 61

threshold 64

thumbnails 117

Mac OS 161

Windows 163

TIFF documents

layered 160

saving 188

togglePalettes 52

tool tips 162

tracking, text 186

transmission info 101

trapping 95

Twirl filter 61

type units 163

U

underlining 186

units

- ruler 162
- type 163
- UnitValue object 33, 189
- Unsharp Mask filter 61
- URLs, document 101
- UTF8 Encoding 115

V

- vectorData 99
- version
 - application 49
 - scripting interface 48
- video alpha 163
- video filters
 - De-Interlace 58
 - NTSC 60
- visibility
 - channels 74
 - layer comps 128
 - layers 56

W

- warp 186
- Wave filter 61
- Web photo galleries
 - See galleries.
- webSnap 109
- width 92
- Windows
 - filetypes 49
- word spacing 182–185
- work paths
 - designating 210
 - from selected area 169
- wrapping, text 183

X

- XML 190
- xmp metadata 92, 190

Z

- Zigzag filter 61
- zoom 161