Response to the Editor and Reviewer

Manuscript: *A Latent Oscillator Measurement Model to Simulate Emotional-Expression Score Dynamics in Video*

Dear Dr. Epskamp, Editors, and Reviewer,

Thank you for the careful reading and for the guidance on scope, structure, and examples. We revised the paper as a methods contribution centered on the Latent Oscillator Measurement Model (LOMM). The revision presents LOMM as a generator for model-derived emotional-expression score panels, adds a selected realism check against MAFW-derived classifier-output panels, and evaluates known-truth recovery on pre-link linear block-measurement panels. The public observation pipeline now defaults to a compositional profile with empirical between-clip baselines and clip-specific scale (B+S); loading-aligned B+S and the exactly nested homogeneous profile remain explicit alternatives.

Two scope decisions guided the revision. First, we renamed the model *Latent Oscillator Measurement Model* because damping is one velocity-feedback regime in LOMM; the model also permits zero or positive velocity feedback. The model section states that negative velocity feedback produces damped return, zero velocity feedback removes damping, and positive velocity feedback can sustain or amplify change over the finite interval. This framing better fits short video time series, where brief expressive episodes in the empirical MAFW example may show bursts, switching, or low expressivity without clearly exhibiting damping. Second, we moved tutorial material out of the paper because the *transforEmotion* R package tutorial has already been published separately and is cited in the revised Introduction. The present manuscript focuses on the model, selected realism targets, and benchmark.

The manuscript defines MAFW at first substantive mention as a large-scale, multimodal, compound affective database for dynamic facial-expression recognition in the wild.

The appendices carry the technical support. Appendix A gives the perturbation-target argument for the recovery methods on the historical homogeneous revision-v2 linear benchmark, and Appendix B gives numeric empirical-realism checks. Appendix C reports trajectory-recovery diagnostics for method-readout rows with recovered score summaries, Appendix D gives runtime and feasibility accounting, and Appendix E reports scenario parameter values.

Because line numbers can change during production, we refer below to sections, figures, tables, and pages in the rendered revised manuscript.

Response to the Editor

1. **Editorial guidance on structure and pipeline.**

   > *In your revision, I urge you to especially note the reviewer's comments on restructuring the paper, and also consider including a pipeline figure describing how all components interact.*

   Location in revised manuscript: Abstract, p. 1; Introduction, pp. 1–3; Figure 2, p. 10; Method, pp. 9–19; Results, pp. 19–25; Discussion, pp. 26–28.

   Response: We reorganized the manuscript around one sequence: classifier-output score series, the measurement problem, LOMM, and the benchmark design. The Introduction introduces three research questions and distinguishes the held-out compositional realism checks, the historical

matched method comparison, and the broader DynEGA extension. Figure 2 shows how empirical classifier-output scoring, realism targets, scenario selection, the configurable LOMM observation layer, versioned recovery panels, and method recovery tests connect.

2. **Editorial guidance on politically sensitive examples.**

> *In addition, please carefully reconsider the use of politically sensitive examples in the manuscript. My concerns are that (1) the political content may distract readers from the methodological contribution, which should be the focus; (2) the interpretive framing of emotion results (e.g., anger and fear in Boris Johnson's Brexit address) involves editorial judgment that goes beyond what a methods paper typically requires; and (3) politically charged examples risk dating the paper and may be less accessible to an international readership unfamiliar with the specific political context. The methodological points could likely be illustrated equally well with less politically loaded material, which may also be more suitable for guiding empirical researchers aiming to use your method in a lab setting.*

Location in revised manuscript: Empirical Calibration and Realism Targets, pp. 10–13; Figure 3, p. 12; Discussion, pp. 26–28.

Response: We replaced the political example with a non-political MAFW clip. Figure 3 shows four selected frames from that clip, the corresponding classifier-output score profiles, smoothed classifier-output trajectories, and a DynEGA network from non-neutral classifier-output trajectories. The frames serve only to identify the dataset-derived scoring example. The repository and archive do not include raw MAFW videos, and access to the original video materials remains governed by the dataset providers. The limitation language states that classifier-output scores are model-derived observations of visible expression, not validated emotion labels or exact empirical trajectories.

Action Editor Comments

3. **Notation for N_g and P_s.**

> *I find the notation N_g and P_s confusing, especially as N is already used for neutrality, making g and s read as subscripts rather than parts of compound variable names. Please consider clearer notation.*

Location in revised manuscript: The Latent Oscillator Measurement Model, pp. 3–8; Dimensional-Recovery Simulation Study, pp. 15–19.

Response: We removed the confusing notation and rewrote the model with explicit indices for videos, time, latent dimensions, and observed indicators. The notation uses i for videos, t for time, f for latent expressive dimensions, m for the number of dimensions, p for observed indicators, and B_f for the indicator block associated with dimension f.

4. **Matrix multiplication notation.**

> *Equation (2): The $\times$ symbol is used for matrix multiplication; the $\cdot$ symbol or simple juxtaposition would be more conventional in this context.*

Location in revised manuscript: Equations (1) and (2), pp. 3–6.

Response: We rewrote the equations with standard matrix notation. The current observation layer is $\mathbf{u}_{it} = \boldsymbol{\mu} + \mathbf{b}_i + \kappa s_i(\boldsymbol{\Lambda}\tilde{\mathbf{x}}_{it} + \boldsymbol{\varepsilon}_{it})$, with bounded outputs $\mathbf{p}_{it} = \text{softmax}(\mathbf{V}\mathbf{u}_{it}/\tau)$. The completed revision-v2 recovery panel retains the historical linear form $\mathbf{z}_{it} = \boldsymbol{\Lambda}_i\tilde{\mathbf{x}}_{it} + \boldsymbol{\varepsilon}_{it}$.

5. **Boldfacing of covariance matrices.**

   Line 277: The covariance matrix Q is not boldfaced, inconsistent with the boldfacing convention used for other matrices.

   Location in revised manuscript: Model equations and measurement model, pp. 3–7.

   Response: We revised the notation throughout the model section. The current observation layer uses the fixed loading matrix $\mathbf{\Lambda}$, activity-scaled latent vector $\tilde{\mathbf{x}}_{it}$, measurement-error vector $\boldsymbol{\varepsilon}_{it}$, and covariance matrix $\mathbf{\Sigma}_i$. The historical revision-v2 benchmark uses the item-jittered matrix $\mathbf{\Lambda}_i$. Scalar process shocks are written as $q_{if,t}$.

6. **Missing word.**

   Line 304: A word appears to be missing: "We will illustrate this approach [using?] OpenAI's CLIP..."

   Location in revised manuscript: Empirical Calibration and Realism Targets, pp. 10–13.

   Response: We removed the old tutorial-style sentence and replaced it with a direct description of the empirical scoring target, the prompt-defined score channels, complete-row retention, whole-ILR-vector interpolation for the bounded-gap sensitivity, simplex-closure checks, and normalization of small closure drift. Values are not clipped. The empirical scoring section identifies *transforEmotion* as the source of the frame-level classifier-output scores, using model key `oai-large`, mapped in the local registry to OpenAI CLIP ViT-Large/14 (`openai/clip-vit-large-patch14`).

7. **Interpretive claim in the previous political example.**

   Figure 3 implies that Boris Johnson expressed fear throughout the duration of his address on Brexit. This is a substantial interpretive claim that I do not think is suitable for a methods journal, and it relies on the validity of CLIP, which is not discussed. Furthermore, if this paper is to guide empirical research, it would be more suitable to demonstrate the method using neutral or controlled videos that researchers might encounter in a lab setting.

   Location in revised manuscript: Empirical Calibration and Realism Targets, pp. 10–13; Figure 3, p. 12; Discussion, pp. 26–28.

   Response: We removed the Boris Johnson and Brexit example. Figure 3 uses a non-political MAFW clip and shows selected dataset frames, score profiles, score trajectories, and recovered network communities. The still frames identify the scored clip while the raw MAFW videos remain outside the repository and archive; access to the original materials remains under the dataset providers' terms. The text avoids substantive political interpretation of a public speech.

8. **CLIP and FER validity.**

   The method relies heavily on CLIP being able to accurately classify emotions for any given set of emotion labels. However, the manuscript does not cite or discuss evidence for CLIP's validity in facial expression recognition specifically. At minimum, the authors should review existing work on CLIP's FER accuracy and acknowledge limitations.

   Location in revised manuscript: Introduction, pp. 1–3; Empirical Calibration and Realism Targets, pp. 10–13; Discussion, pp. 26–28.

   Response: We revised the framing so that the score series are treated as model-derived classifier outputs rather than validated emotion labels. The Introduction cites work on CLIP-like and

zero-shot FER models as scoring context, and the empirical section identifies the *transforEmotion* backend, model key `oai-large`, and OpenAI CLIP ViT-Large/14 model identifier. We address validity by limiting the claim: the panels are prompt-specific classifier outputs, and the selected empirical-realism construction check does not validate scoring-model labels, prompt labels, subjective emotional states, or exact empirical trajectories.

9. **Realism of LOMM simulations.**

> *How do we know that DLO-MM produces realistic FER-like data? It would strengthen the paper considerably to compare statistical properties of simulated datasets to those of real CLIP-derived FER data, to demonstrate that the simulation model produces data resembling real-world observations.*

Location in revised manuscript: Empirical Calibration and Realism Targets, pp. 10–13; Empirical Realism Results, pp. 20–21; Figure 4, p. 20; Appendix B, p. 44; Discussion, pp. 26–28.

Response: We added a historical revision-v2 empirical-realism construction check comparing simulated panels with MAFW-derived classifier-output score panels. That check evaluates six targets—channel IQR, derivative IQR, lag-1 autocorrelation, run-length entropy, spectral entropy, and effective rank—at observed-channel and recovered community-score-summary readouts. The later paired B/S/G adoption analysis is a separate five-fold analysis of eight probability-scale and the corresponding eight log-ratio metrics on the retained 100-clip score surface. Its fold-stratified clip-cluster percentile intervals are descriptive; the B and S point estimates fall below their respective intervals because the nonlinear discrepancy estimands show bootstrap bias. B gave the clearest descriptive discrepancy reduction, scale gave a smaller uncertain marginal reduction, and those results motivated the pipeline decision to use configurable B+S as the public compositional default. The completed dimensional-recovery grid uses its historical homogeneous pre-link linear generator, and the loading-aligned bridge uses `linear_z`. Neither recovery analysis validates recovery from bounded probabilities or CLR panels.

10. **Alternative dimensionality recovery benchmarks.**

> *I appreciate the effort in developing a simulation framework, which is not common in image classification work as far as I am aware. However, since the authors develop both the DLO-MM simulation method and the DynEGA analysis method, strong performance of DynEGA on DLO-MM data is not entirely surprising. It would considerably strengthen the contribution to include alternative dimensionality recovery methods as benchmarks, to determine whether DynEGA specifically excels or whether recovering latent dimensions from this type of data is straightforward more generally.*

Location in revised manuscript: Dimensional-Recovery Simulation Study, pp. 15–19; Simulation Results, pp. 21–25; Table 2, p. 22; Figure 5, p. 22; Figure 6, p. 24; Computational Feasibility, p. 25; Figure 7, p. 25; Appendix A, pp. 35–43; Appendix D, p. 46.

Response: We added GraphicalVAR and GIMME to a matched three-method grid. GraphicalVAR is the dynamic-network comparator. GIMME is an indirect feasibility-stress comparator whose clip-level contemporaneous structures are aggregated and partitioned.

The main Results summarize status-inclusive dimensional hit rate, assignment accuracy, successful-fit runtime, and valid, timeout, and error status counts. The Results and Appendix C report trajectory-recovery r and NRMSE among method-readout rows with recovered score summaries, excluding failed or timed-out fits.

Appendix A formalizes the historical homogeneous revision-v2 linear-panel recovery target as a graph-perturbation problem. DynEGA and GraphicalVAR read the block signal through partial-correlation graphs of derivative or VAR innovation readouts. GIMME is treated as an indirect graph-conversion pipeline with completion included in status-inclusive recovery. Figure A1 plots both readout maps against the filtered signal-to-noise ratio with the matched measurement grid marked. The shared perturbation margin also predicts the scenario-family ordering through the activity gains for the population readout pipelines, and Appendix A reports conditional hit rates among usable readouts alongside the status-inclusive rates. The derivation does not cover empirical-baseline compositions, CLR panels, or the loading-aligned bridge's between-clip mean structure.

Response to Reviewer 1

1. **General assessment and scope.**

> *The paper has the potential to be very timely and interesting to psychologists, as it uses both advanced zero-shot classification (AI-based) and theoretically motivated dynamic modeling (ODE-based). In principle, this is an exciting and valuable direction and I see a lot of applications. I would have been considerably more enthusiastic about the contribution if the manuscript did not suffer from notable lack of coherence, structure, conceptual clarity, and mathematical precision.*

Location in revised manuscript: Whole manuscript, especially Abstract, p. 1; Introduction, pp. 1–3; model section, pp. 3–8; Method, pp. 9–19; Results, pp. 19–25.

Response: We narrowed and reorganized the manuscript. LOMM has a single methods-paper role: it is a controlled generator for model-derived emotional-expression score panels and a benchmark framework for dynamic dimensional recovery.

2. **Introduction and conceptual clarity.**

> *I think the Introduction can be tightened in favor of conceptual clarity, such that the paper quickly comes to the point. Currently, it oscillates between aims, brief snippets of related work, and a restatement of a singular aim (P6L46). I suggest a more brain-friendly structure that briefly introduces emotion recognition, existing difficulties with theory-driven modeling (DLO-MM) and data-driven detection (DL, supervised and zero-shot classification), and how the proposed framework addressed these difficulties. Upon a naive reading, it may currently not become clear whether the authors propose new methods, apply existing methods in a new context, validate their own software, or a hodgepodge of different things revolving around the quantitative analysis of emotion dynamics. Some methodological aspects currently appear out of the blue (e.g., dynEGA) and it is not at all clear which method is being validated for what purpose. For example, only much later does it become clear that DLO-MM will be used as a simulator to validate the accuracy of dynEGA in in silico.*

Location in revised manuscript: Abstract, p. 1; Introduction, pp. 1–3; Figure 2, p. 10.

Response: We rewrote the Introduction to move from classifier-output score series, to the measurement problem, to LOMM, to the benchmark sequence. The Introduction states three research questions, and the final Present Research subsection introduces Figure 2 after the model details. DynEGA, GraphicalVAR, GIMME, static EGA, and the true-block oracle are presented as recovery pipelines evaluated under a prespecified simulation design.

3. **Connections among CLIP, simulation, and DynEGA.**

Related: It is unclear how the goals of the different methods connect to each other. For instance, even 15 pages deep in the paper, it remains unclear how the goal of generic synthetic emotion scores connects to the goal of applying zero-shot classification to the frames. How exactly do CLIPs outputs feed into DLO-MM or vice versa (or not at all?). Some figures appear at random places (e.g., Figure 3 presages the entire methodology of the paper, even though only DLO-MM has been formally introduced). It would be helpful it the paper included a "pull figure" describing all components of the pipeline and their interrelations (and priming for the tutorial part), instead of relying on readers to piece together the puzzle and fill in the blanks. Additionally, it would be helpful if sections include paragraphs (see AI papers) that group together and delineate core ideas. For instance, CLIP and details about its pretraining appear under "Emotion Dynamics as a Damper Oscillator Model", implying an apparent (but missing) connection.

Location in revised manuscript: Figure 2, p. 10; Method overview, pp. 9–10; Empirical Calibration and Realism Targets, pp. 10–13; Dimensional-Recovery Simulation Study, pp. 15–19.

Response: Figure 2 shows the full workflow. Empirical zero-shot classifier-output scores define realism targets and scenario constraints. The current public observation pipeline generates bounded compositional B+S panels by default. The completed known-truth recovery benchmark retains its versioned homogeneous linear panels, and the bridge evaluates loading-aligned B+S on selected pre-link linear panels with prespecified indicator blocks. The Method begins by restating this workflow so readers do not have to infer how the parts fit together.

4. **Uneven detail and tutorial framing.**

Furthermore, the granularity of description of the components of the pipeline differs widely, from more precise and theoretically argued for (DLO-MM), to less detailed with a patchwork of mathematical details and lots of submethods and moving parts (dynEGA), to merely explained on a high level (CLIP, zero-shot classification). Together with the fact that the descriptions of these methods are interleaved throughout the text, but their connections are often left implicit or informal, it becomes incredibly hard to follow the paper, especially as a "tutorial". The formal level of description also experiences an uninterrupted drop from DLO-MM onwards.

Location in revised manuscript: Introduction, pp. 1–3; Method, pp. 9–19; Dimensional-Recovery Simulation Study, pp. 15–19.

Response: We moved tutorial framing out of the manuscript because the *transforEmotion* R package tutorial has already been published separately and is cited in the Introduction. The Methods give the LOMM formal model and trace the *transforEmotion*/CLIP scoring provenance. They also define selected empirical-realism targets, add scenario-family settings, specify a common graph-partitioning target, and report the computational environment.

5. **Notation and mathematical precision.**

There are some unfortunate choices of notation and mathematical sloppiness. For example, in a dynamic modeling context, Nt (Eq.1) can easily be interpreted as N times t (continuous time). Why do the parameters eta and xi need an Nt subscript? I understand that Eq.1 applies to all three sentiment variables, but positive and negative sentiment are only briefly discussed. Matrices are not consistently bolded (e.g., P13L270). It is unclear where the 2D vector X_t comes from (which is bolded and capitalized as if it were a matrix). It is later redefined as a delay embedding matrix (P20L398). Where does the i index come from (P14L281)? The dynamic errors's symbol is redefined from sigma to q. The time index is redefined from t to i (I assume t was meant to be reserved for continuous time and i for discrete). These are just a few examples of sloppy mathematics, prompting a thorough revision for consistency and precision.

Location in revised manuscript: Model equations, pp. 3–7; measurement model, pp. 6–7; benchmark metrics, pp. 17–18.

Response: We rewrote the mathematical exposition and defined each index and object where it first appears. The model defines video index i, discrete time index t, and latent dimension f. It then defines latent level $x_{if,t}$, velocity $v_{if,t}$, and process shock $q_{if,t}$. The current observation layer uses loading matrix $\mathbf{\Lambda}$, measurement error $\boldsymbol{\varepsilon}_{it}$, and covariance matrix $\mathbf{\Sigma}_i$; the historical revision-v2 linear generator uses its item-jittered $\mathbf{\Lambda}_i$.

We also removed the continuous- versus discrete-time ambiguity the reviewer noted. The latent layer is written as the exact one-step recursion implemented in the simulation, $\mathbf{s}_{if,t+dt} = \mathbf{\Phi}_f(dt)\mathbf{s}_{if,t} + \mathbf{\Gamma}_f(dt)q_{if,t}$. The transition matrix $\mathbf{\Phi}_f(dt)$ and shock-loading vector $\mathbf{\Gamma}_f(dt)$ are given explicitly, so the printed equations match the generating code. The revised notation omits the old N_t, N_g, and P_s terms.

6. **Data-generation pipeline and relation to CLIP outputs.**

> *I am left puzzled by some aspects of the data generation pipeline. For example, it is called simulate_video (which would imply that video frames are simulated), but as far as I understood, it simply used DLO-MM to generate score time series. Also a new parameter eta (with no subscript) appears out of nowhere. Further, at a conceptual level, FER scores are said to apply to both sentiments (neutral, positive) and concrete emotions (excitement, fear,...), so in what sense are the outputs of CLIP compatible, conflicting with, or orthogonal to the outputs of DLO-MM? Can DLO-MM be fitted to CLIP outputs? In the latter case, DLO-MM will be rather a model of AI emotion detection performance than a model of emotion dynamics per se.*

Location in revised manuscript: Introduction, pp. 1–3; Empirical Calibration and Realism Targets, pp. 10–13; Scenario Selection, pp. 13–15; Appendix E, pp. 47–49; Discussion, pp. 26–28.

Response: We revised the terminology so the pipeline no longer implies that video frames are simulated. LOMM generates simulated score panels. The empirical classifier-output scores from MAFW are used as selected realism targets for the default compositional B+S observation layer. The completed known-truth recovery benchmark analyzes its versioned homogeneous pre-link linear panels, while the bridge uses loading-aligned B+S to preserve the declared indicator blocks. The affect-taxonomy paragraph is explicitly illustrative: approach-affiliation, threat-defense, and orienting-novelty are simulation-design dimensions, and the prompt labels are examples rather than validated affect categories in MAFW.

Appendix E lists the family codes, gains, dwell fractions, feedback sources, and numeric η, ζ, and base σ_q vectors used in the final runs. The Discussion states that the score series are model-derived observations of visible expression, so the current benchmark does not validate emotion labels or claim direct equivalence between empirical trajectories and latent affective states.

7. **Recovery metrics beyond correlation.**

> *Using correlation for validation the recovery of true scores only tells part of the story. Please, complement the results with a metric that reflects potential biases (e.g., NRMSE, predictive coefficient of determination, ...).*

Location in revised manuscript: Dimensional-Recovery Simulation Study, pp. 15–19; Simulation Results, pp. 21–25; Table 2, p. 22; Figure 5, p. 22; Appendix C, p. 45; Appendix D, p. 46.

Response: We added metrics beyond correlation. The benchmark reports status-inclusive dimensional hit rate, assignment accuracy, successful-fit runtime, and valid, timeout, and error status counts at method-readout and unique structure-fit levels where applicable. It also reports matched trajectory-recovery r and NRMSE among method-readout rows with recovered score summaries. Failed or timed-out fits are excluded from the trajectory diagnostics because they do not produce recovered score summaries. Appendix C reports the full marginal trajectory diagnostics, and Appendix D reports runtime and feasibility accounting. We interpret trajectory correlations as diagnostics for recovered score summaries rather than as the primary method-ranking criterion.

8. **Calibration and limitations of zero-shot classifiers.**

   The calibration of zero-shot classifiers is generally hard to measure or unknown (comapred to the calibration of supervised classifier). That means that CLIP-induced FER scores (which can be interpreted or converted into probabilities) for more exotic emotions (e.g., excitement, pride) have an unknown reliability. The same goes for its accuracy in detecting rare emotions. I believe these points warrant at least a small discussion, as users should know what to expect for their own applications and where to find numbers on accuracy and calibration for common emotion sets.

   Location in revised manuscript: Introduction, pp. 1–3; Empirical Calibration and Realism Targets, pp. 10–13; Discussion, pp. 26–28.

   Response: We describe these outputs as classifier-output score channels and prompt-specific classifier outputs rather than calibrated emotion probabilities. The Introduction cites recent zero-shot and CLIP-like FER work as scoring context. The empirical Methods identify the *transforEmotion* scoring backend. The Limitations section states that the selected realism check evaluates statistical signatures of score panels rather than the validity of emotion labels.

9. **Acronyms and model name.**

   Some acronyms are not introduced, redundantly introduced multiple times, or introduced following a different term (e.g., DLO is hidden among references on P7L52, but the term is Damped Oscillator Model, which would abbreviate to DOM).

   Location in revised manuscript: Title and Abstract, p. 1; Introduction, pp. 1–3; model section, pp. 3–8.

   Response: We changed the model name to Latent Oscillator Measurement Model (LOMM) and introduce it directly in the main title, abstract, and Introduction. Damping is one optional velocity-feedback regime in the model. The model section now explains damped, undamped, and amplifying velocity-feedback cases.

10. **Neutral factor.**

    Why is there no neutral factor in the measurement model? The latent neutral trajectory is plotted in Figure 2 but its relationship to the observable scores is unclear.

    Location in revised manuscript: Measurement model, pp. 6–7; Figure 2, p. 10; empirical illustration, pp. 10–12.

    Response: The final benchmark uses m latent expressive dimensions with observed indicator blocks. Neutral may appear as an empirical classifier-output channel, but it is not assigned a source-truth latent factor in the final benchmark unless a neutral block is specified by design.

11. **Equation 1.**

> *Eq. 1 needs attention. The first term literally evaluates to $dN_t/dt = dN_t/dt$ and is completely redundant. I suspect the zero and the one in the "parameter matrix" have to be swapped.*

Location in revised manuscript: Equation (1), pp. 3–5.

Response: We replaced the old equation with a standard second-order state representation. The first row now maps velocity to the derivative of position, and the second row maps position feedback, velocity feedback, and process shock to acceleration.

12. **Dynamic error.**

> *It is not clear where the "dynamic error" enters the model and what makes it dynamic (it is not introduced as a function of time). Since this is a tutorial, I would have expected a more precise and focused mathematical exposition.*

Location in revised manuscript: Equation (1), pp. 3–5; Figure 2 and accompanying text, pp. 9–10.

Response: We now define the shock process as $q_{if,t} \sim \mathcal{N}(0, \sigma^2_{qf})$, entering the acceleration equation at each time point. The Figure 2 text explains that σ_q perturbs each latent process locally, producing peaks, reversals, and irregular fluctuations around the underlying trajectory.

13. **Idiosyncratic expressions.**

> *Nit: Some expressions are rather idiosyncratic, e.g., "Emotion Dynamics as a Damped Oscillator Model" -> the notion of "X as a model" seems strange, a more natural expressions would be "Modeling emotion dynamics via ...", "quantitative methods approach" is redundant -> perhaps "a quantitative framework / method / approach", there are lots of synonyms.*

Location in revised manuscript: Title, p. 1; The Latent Oscillator Measurement Model, pp. 3–8; manuscript-wide prose revisions.

Response: We revised the title and section titles to better match the paper's methodological contribution. We also reduced tutorial-style and redundant phrasing throughout the revised manuscript.

14. **Figure captions.**

> *Figure captions are sloppy, use inconsistent capitalization, and rarely helpful or self-explanatory.*

Location in revised manuscript: Figure 1, p. 8; Figure 2, p. 10; Figure 3, p. 12; Figure 4, p. 20; Figure 5, p. 22; Figure 6, p. 24; Figure 7, p. 25.

Response: We rewrote the figure captions to be self-contained and consistent. The revised captions identify the panels, state what is being shown, and clarify the role of each figure in the model, empirical realism, benchmark recovery, measurement-quality, or feasibility analysis.

Closing

We appreciate the editor's and reviewer's guidance. The revision specifies LOMM as a benchmark generator with an explicit measurement layer, checks selected score-series realism targets against

MAFW-derived classifier-output score panels, and compares dimensional-recovery methods under known truth with feasibility accounting. We hope the revised manuscript makes the paper's scope, evidence, and limits easier to evaluate.

Sincerely,

The Authors