A Latent Oscillator Measurement Model to Simulate Emotional-Expression Score Dynamics in Video

Aleksandar Tomašević Hudson Golino Alexander P. Christensen

Abstract

Automated vision models turn video into dense time series of classifier-output scores for visible expression. Dynamic analyses of those scores need a measurement check: a recovery method should find the latent organization that generated the score channels after accounting for the observation process. We introduce the Latent Oscillator Measurement Model (LOMM), a simulation framework that generates latent oscillator trajectories, gates their activity over time, and maps them through an explicit observation model into noisy score channels. The default observation profile works in identified log-ratio contrast coordinates, includes clip-specific baselines and positive clip scale, and maps the contrasts to the probability simplex. Empirical, loading-aligned, and zero-baseline geometries are explicit options, and the homogeneous profile is exactly nested. We calibrated selected temporal and dimensional score-series targets against MAFW-derived classifier-output panels. The completed broad recovery benchmark used a separately versioned historical homogeneous linear generator. In a broad DynEGA grid and a matched comparison with GraphicalVAR and GIMME, DynEGA gave the most consistent dimensional and block recovery in these LOMM simulation designs and completed the broad grid. GraphicalVAR often recovered dimensionality but was slower and more sensitive to weak measurement conditions. GIMME had substantial runtime and completion limits in this design. LOMM gives method researchers a controlled setting for testing whether dynamic recovery methods can recover latent score organization before classifier-output score dynamics are interpreted substantively.

Introduction

Video is increasingly used as a source of intensive behavioral data because it preserves the temporal ordering of visible action and can be analyzed at a resolution that manual frame-by-frame coding cannot sustain. Deep-learning systems can now convert frames or short video segments into dense time series of model-derived

emotional-expression scores (S. Li & Deng, 2022; Meng et al., 2017). In a facial-expression recognition task, a model maps each image or segment to category probabilities or continuous scores for labels such as happiness, anger, sadness, fear, surprise, disgust, or neutral expression.

These score streams are valuable because many behavioral questions concern how visible affect unfolds over time. Researchers may ask whether expressive states persist or switch, whether they return after perturbation, and whether many model-output channels reflect a smaller number of expressive dimensions. Such questions arise in psychotherapy, autism assessment, collaborative work, public communication, and social-media video (Halamová et al., 2023; Holiday et al., 2023; Q. Li et al., 2024; Manelis-Baram et al., 2025).

Automated facial-analysis systems now make this kind of work feasible at scale. Datasets such as FER2013 supported deep learning approaches to facial-expression recognition, especially Convolutional Neural Networks (Arriaga et al., 2017; Ezerceli & Eskil, 2022; CNNs; Goodfellow et al., 2013). Most early systems inherited their emotion categories from the training data and focused on fixed classification tasks, commonly returning probabilities for seven categories: anger, disgust, fear, happiness, sadness, surprise, and neutral facial expression (Wang et al., 2022). More recently, CLIP-based and related vision-language models have enabled zero-shot classification with user-specified emotion labels (Foteinopoulou & Patras, 2023; H. Li et al., 2023; Radford et al., 2021; Tomašević et al., 2026), making it possible to represent each video frame as a vector of prompt-defined classifier scores.

The main obstacle is measurement. Emotional-expression scores are trained-model outputs that index visible expressive behavior through a scoring procedure. Facial-expression technologies can be interpreted as tools for emotion recognition or social-interaction analysis, and those interpretations answer different questions (Allison & McKeown, 2023). A separate psychometric question is whether multiple score channels should be treated as variables in their own right or as fallible indicators of lower-dimensional expressive processes (Mehu & Scherer, 2015; Nesselroade et al., 2013; Russell, 2003). Measurement error can alter the structure recovered by dynamic methods, so method validation must separate latent temporal organization from the observation process used to measure it (Kankaanpää et al., 2026).

The remaining methodological gap is practical. Researchers need a generator in which latent expressive dynamics and the multichannel observation process are known before any recovery method is applied. Oscillator models describe level, rate of change, damping, and perturbation in intraindividual dynamics (Boker, 2015; Boker & Nesselroade, 2002; Ollero et al., 2025). A useful validation design must vary dimensionality, indicator blocks, measurement quality, and dynamic regime while keeping the recovery target known.

This paper introduces the Latent Oscillator Measurement Model (LOMM), a generative simulation model for

model-derived emotional-expression score channels. LOMM first generates latent expressive trajectories from second-order oscillator dynamics and then maps those latent processes into classifier-output score channels through an explicit measurement layer. The model lets researchers control latent dimensionality, feedback regime, loading strength, measurement error, and activity pattern before testing whether dynamic methods recover the generating structure.

LOMM integrates several established modeling ideas in one inspectable generator. Latent differential-equation models represent level and velocity, continuous-time state-space models motivate the exact transition between observation times, dynamic factor models motivate a multivariate process representation, and the measurement layer separates latent trajectories from fallible observed indicators (Boker, 2015; Boker & Nesselroade, 2002; Nesselroade et al., 2002; Zhang et al., 2008). The network-recovery task then supplies a known indicator partition against which fitted structures can be evaluated. The contribution is this explicit bridge from latent dynamics through classifier-output measurement to structural recovery; the individual oscillator, state-space, factor-model, and graph-estimation components retain their established interpretations.

The Latent Oscillator Measurement Model

LOMM starts from a measurement object: a video produces frame-level classifier-output score channels for visible expression. The simulation treats those channels as fallible indicators of lower-dimensional expressive processes. A short clip can contain low expressivity, brief expressive episodes, gradual recovery, persistent activation, or alternation between expressive regimes. The latent representation therefore needs to describe level, rate of change, return toward equilibrium, overshoot, damping, and perturbation, concepts that are central to affective-dynamics research (Hollenstein, 2007; Houben et al., 2015; Kuppens & Verduyn, 2017).

Oscillator models provide a compact language for those features. Prior work has used second-order oscillator representations to describe intraindividual dynamics in which a current level and its rate of change jointly determine subsequent movement (Boker, 2015; Boker & Nesselroade, 2002; Ollero et al., 2025). LOMM uses the same state representation for multivariate simulation and measurement evaluation. It combines three layers: a latent oscillator layer that generates expressive trajectories, an activity layer that controls which latent dimension is expressed over time, and an observation layer that supports compositional classifier-output panels and explicitly versioned block-recovery surfaces (H. Golino et al., 2022; Nesselroade et al., 2013).

The latent layer treats each expressive dimension as a second-order state process advanced in discrete simulation steps. For state $\mathbf{s}_{if,t} = [x_{if,t}, v_{if,t}]^\top$, the implemented exact linear step is

$$\mathbf{s}_{if,t+dt} = \Phi_f(dt)\mathbf{s}_{if,t} + \Gamma_f(dt)q_{if,t}, \qquad q_{if,t} \sim \mathcal{N}(0, \sigma_{qf}^2), \tag{1}$$

where

$$\Phi_f(dt) = \exp(\mathbf{A}_f dt), \qquad \mathbf{A}_f = \begin{bmatrix} 0 & 1 \\ \eta_f & \zeta_f \end{bmatrix} \qquad \text{and} \qquad \Gamma_f(dt) = \int_0^{dt} \exp(\mathbf{A}_f u)\mathbf{b}\, du, \quad \mathbf{b} = \begin{bmatrix} 0 \\ 1 \end{bmatrix}.$$

For the nonzero position-feedback values used in the simulation grids, the input map has the equivalent exact form

$$\Gamma_f(dt) = \mathbf{A}_f^{-1}\{\Phi_f(dt) - \mathbf{I}_2\}\mathbf{b}.$$

The integral definition remains valid at singular parameter values and supplies the continuous limit used by the implementation near repeated roots.

In Equation 1, i indexes videos, f indexes latent expressive dimensions, and t indexes discrete simulation time points spaced dt apart. The state variable $x_{if,t}$ is the latent level of dimension f for video i, and $v_{if,t}$ is its rate of change. The parameter η_f is position feedback, ζ_f is velocity feedback, $q_{if,t}$ is the stepwise Gaussian acceleration input used at each transition, and σ_{qf} is the standard deviation of that input. Within a step, the recursion is the exact transition of the linear second-order oscillator $\ddot{x}_{if} = \eta_f x_{if} + \zeta_f \dot{x}_{if} + q_{if,t}$ with the shock held constant, so $\Phi_f(dt)$ propagates the deterministic state and $\Gamma_f(dt)$ is the zero-order-hold loading through which $q_{if,t}$ enters as a per-step acceleration input.

The dynamic parameters set the latent regime. The characteristic roots for factor f are

$$r_{f,\pm} = \frac{\zeta_f \pm \sqrt{\zeta_f^2 + 4\eta_f}}{2}.$$

Continuous-time asymptotic stability requires $\eta_f < 0$ and $\zeta_f < 0$, and the roots are oscillatory when $\zeta_f^2 + 4\eta_f < 0$. The exact discrete transition is asymptotically stable when

$$\rho\{\Phi_f(dt)\} = \exp\left[dt \max\{\mathrm{Re}(r_{f,+}), \mathrm{Re}(r_{f,-})\}\right] < 1.$$

Negative η_f supplies restoring acceleration, negative ζ_f attenuates velocity, and positive ζ_f produces anti-

damped amplification over a finite interval. For a sequence with T observations, the observed horizon is $H = (T-1)dt$, and the corresponding deterministic growth diagnostic is $g_f(H) = \exp\{H \max \mathrm{Re}(r_{f,+}, r_{f,-})\}$. Reporting T, dt, H, the roots, and $g_f(H)$ distinguishes stable oscillation, gated nonstationarity, and finite-horizon amplification.

The model uses an uncoupled multivariate system: η_f, ζ_f, and σ_{qf} may vary by factor, and off-diagonal dynamic effects are omitted. The checked-in simulations initialized every factor at $x_{if,1} = 0.25$ and $v_{if,1} = 2$. The revised robustness protocol uses independent starting states. For a stable factor, it solves

$$\mathbf{P}_f = \Phi_f \mathbf{P}_f \Phi_f^\top + \Gamma_f \sigma_{qf}^2 \Gamma_f^\top$$

and draws $\mathbf{s}_{if,1} \sim \mathcal{N}(\mathbf{0}, \mathbf{P}_f)$. For an anti-damped factor, it draws $x_{if,1} \sim \mathrm{Unif}(-0.25, 0.25)$ and $v_{if,1} \sim \mathrm{Unif}(-2, 2)$. These independent starts remove the common deterministic transient from the revised sensitivity design while leaving the observed horizon unchanged.

The activity layer turns raw oscillator states into scenario-specific expression episodes. The trajectory passed to the measurement model is $\tilde{x}_{if,t} = a_{if,t} x_{if,t}$, where $a_{if,t} \geq 0$ is a scenario-defined activity envelope generated from active gains, background gains, and dwell schedules. Its derivative contains both oscillator motion and gate motion,

$$\frac{d}{dt}\{a_{if}(t) x_{if}(t)\} = a'_{if}(t) x_{if}(t) + a_{if}(t) x'_{if}(t).$$

For the piecewise-constant schedules used in the checked-in simulations, the corresponding finite-difference identity is

$$\frac{\tilde{x}_{if,t+dt} - \tilde{x}_{if,t}}{dt} = a_{if,t+dt} \frac{x_{if,t+dt} - x_{if,t}}{dt} + \frac{a_{if,t+dt} - a_{if,t}}{dt} x_{if,t}.$$

In single-regime scenarios, one dimension has higher activity across the full sequence; in switching scenarios, the active dimension changes after sampled dwell intervals; and in low-expression scenarios, all dimensions remain close to background activity. Abrupt gates can introduce a derivative signal at a switch even when oscillator acceleration is unchanged. The revised challenge design therefore compares the checked-in step gates with five-observation half-cosine transitions while preserving the generating dimensions and indicator memberships.

The observation layer maps the activity-scaled latent trajectories into an identified contrast space before placing them on their reported scale. Let J denote the number of positive classifier-output channels, let $d = J - 1$, and let $\mathbf{V} \in \mathbb{R}^{J \times d}$ be a fixed orthonormal ILR basis satisfying $\mathbf{V}^\top \mathbf{V} = \mathbf{I}_d$ and $\mathbf{V}^\top \mathbf{1}_J = \mathbf{0}$. For video i and frame t, the pre-temperature contrast vector is

$$\mathbf{u}_{it} = \mu + \mathbf{b}_i + \kappa s_i \left(\Lambda \tilde{\mathbf{x}}_{it} + \varepsilon_{it}\right), \qquad \varepsilon_{it} \sim \mathcal{N}(\mathbf{0}, \Sigma_i). \tag{2}$$

In Equation 2, $\mu \in \mathbb{R}^d$ is a fixed contrast-space center, $\mathbf{b}_i \in \mathbb{R}^d$ is a clip baseline, $s_i > 0$ is a clip-specific profile scale, $\kappa > 0$ is a global observation scale, $\Lambda \in \mathbb{R}^{d \times m}$ maps the m activity-scaled latent positions into contrast coordinates, and ε_{it} is contrast-space measurement error. The placement of s_i is part of the model: it multiplies both the dynamic signal and the measurement residual, while $\mathbf{b}_i$ remains additive.

The public LOMM pipeline uses the `compositional_bs` profile by default. Its empirical baseline mode draws $\mathbf{b}_i$ from a zero-mean Gaussian distribution with a training-derived between-clip covariance in the locked contrast coordinates. Its clip scale follows $s_i \sim \mathrm{Unif}(0.5, 1.5)$, which is positive and has population mean one. The calibrated preset fixes a 12-frame oscillator period, damping ratio 0.5, $\kappa = 1$, $\tau = 1$, and contrast-residual standard deviation 0.25. The additional smooth-gate component evaluated in the observation-profile ablation is disabled in this preset.

The baseline geometry is an explicit simulation choice. The `empirical` mode uses the training-derived covariance in the full active contrast space. The `loading_aligned` mode uses

$$\mathbf{b}_i = \Lambda \beta_i, \qquad E(\beta_i) = \mathbf{0},$$

so between-clip variation remains in the declared loading space for known-truth recovery experiments. The `none` mode fixes $\mathbf{b}_i = \mathbf{0}$. Clip scale is controlled separately; the homogeneous profile combines `none` with $s_i = 1$ and is therefore an exact nested case:

$$\mathbf{u}_{it} = \mu + \kappa \left(\Lambda \tilde{\mathbf{x}}_{it} + \varepsilon_{it}\right).$$

For compositional output, LOMM maps the identified contrasts to the open probability simplex:

$$\mathbf{p}_{it} = \mathrm{softmax}\left(\frac{\mathbf{V}\mathbf{u}_{it}}{\tau}\right), \qquad \mathrm{ilr}_{\mathbf{V}}(\mathbf{p}_{it}) = \frac{\mathbf{u}_{it}}{\tau}. \tag{3}$$

The fixed ILR basis excludes the unidentified common-logit direction, and the softmax produces strictly positive rows that sum to one. A caller can retain $\mathbf{u}_{it}$ directly as a linear contrast surface when the estimand requires an unbounded known-truth panel. The completed revision-v2 method comparison used the historical homogeneous linear form $\mathbf{z}_{it} = \Lambda_i \tilde{\mathbf{x}}_{it} + \varepsilon_{it}$. In that benchmark, each of the $p = mk$ observed indicators belongs to one block B_f, has one primary loading with item-level jitter, and has diagonal measurement error with item-level variance jitter. The loading-aligned B+S bridge also used the pre-link `linear_z` representation. It screens the effect of B+S on selected known-block recovery conditions and does not validate recovery from bounded probabilities or CLR panels.

These observed channels are classifier-output measurements of visible expression. The model tests whether recovery methods recover a prespecified observation process under controlled loading strength, measurement error, dynamic regime, activity regime, and baseline geometry. Semantic label validity and subjective emotional experience remain outside the evidential scope of the simulation. Neutral can appear as an empirical classifier-output channel, but it is not assigned a source-truth latent factor unless a neutral block is specified by design.

As an illustrative substantive mapping, a three-factor LOMM could represent approach-affiliation, threat-defense, and orienting-novelty dimensions. Prompt-defined classifier-output channels related to happiness, amusement, trust, or smiling could form an approach-affiliation block. Channels related to anger, fear, disgust, contempt, or anxiety could form a threat-defense block. Channels related to surprise, anticipation, confusion, or attention could form an orienting-novelty block. These labels are examples for simulation design, not validated affect categories in the empirical MAFW panels. The example draws on affect taxonomies that distinguish broad dimensions, discrete expression families, and opponent tendencies (Plutchik, 2001; Russell, 1980, 2003; Russell & Mehrabian, 1977), and it is consistent with facial-expression benchmarks that combine categorical expression labels with dimensional ratings (Kollias et al., 2023; Mehu & Scherer, 2015; Mollahosseini et al., 2019). Alternative affective taxonomies can be encoded by changing the latent block map while keeping the LOMM architecture fixed.

Model Scope and Identifiability

The known simulation settings do not imply that every LOMM component can be identified from an empirical score panel. Block labels are recoverable only up to permutation, and latent trajectory signs and scales depend on the chosen constraints. For any nonsingular diagonal matrix $\mathbf{D}$,

$$\Lambda \tilde{\mathbf{x}}_{it} = (\Lambda \mathbf{D}^{-1})(\mathbf{D} \tilde{\mathbf{x}}_{it}),$$

so loading magnitude and latent-trajectory scale are not jointly identified without scale constraints. Activity gain and innovation scale also contribute to latent amplitude. The softmax layer adds common-location invariance and a temperature–scale tradeoff. LOMM is used here as a controlled generator with known settings and a prespecified partition target. Empirical use of the framework would require additional scale, loading, and observation-model constraints before its dynamic parameters could be interpreted as estimates.

The same three-factor example is shown in Figure 1 to make the role of the latent shock term visible.




Figure 1: Three-factor LOMM example for theory-guided visible expressive dimensions. The left panel shows smooth reference trajectories without dynamic shocks; the right panel shows trajectories generated by the implemented linear oscillator process with factor-specific position feedback, velocity feedback, and innovation variance.

Figure 1 shows the role of the innovation variance, σ_q^2, in LOMM. The reference panel shows the conceptual latent ordering without dynamic shocks: affiliative expression rises quickly and settles above the threat and orienting trajectories. The simulated oscillator panel retains this ordering while nonzero factor-specific σ_q perturbs each latent process at each time point, producing local peaks, reversals, and irregular fluctuations around the underlying trajectory. After approximately time point 100, affiliative expression (blue) remains the dominant latent tendency, while threat (orange) fluctuates at a moderate level and orienting (green) stays lower with shorter local excursions. In this example, σ_q turns a smooth conceptual model into latent score series that better resemble uneven temporal structure in model-derived visible-expression panels.

Present Research

Dynamic Exploratory Graph Analysis [DynEGA; H. Golino et al. (2022)] is the focal dynamic-dimensionality estimator because it was developed to recover groups of variables whose estimated changes are coordinated

over time. This role supplies a substantive reason to include DynEGA in the design before its performance is known. GraphicalVAR and GIMME provide adjacent intensive-longitudinal pipelines with different estimands and graph-conversion steps, while static EGA evaluates whether temporal preprocessing adds recovery information beyond contemporaneous score levels. A true-block oracle checks the simulation and partition code against the known measurement structure.

The revised study addresses three questions. First, can LOMM reproduce held-out observable properties of empirical video-derived classifier-output scores without allowing clip boundaries or training-derived summaries to enter the evaluation fold? Second, how do DynEGA, GraphicalVAR, GIMME, and static EGA recover the same known block structure on matched panels, and where does the oracle place the implementation ceiling? Third, how does recovery change under short records, alternative initialization and stability regimes, smooth activity transitions, cross-loadings, correlated errors and shocks, bounded score representations, and estimator feasibility limits?

The evaluation begins with five-fold clip-level empirical calibration and a matched method comparison on identical generated panels. The matched design provides the primary evidence because panel keys, simulation seeds, structural targets, and the downstream partition rule are shared across pipelines. A broad DynEGA grid then describes the focal method's wider operating envelope. A separate $T = 25$ same-cadence study and a bounded challenge suite evaluate departures that are especially relevant to short classifier-output streams and nonideal measurement. These revision-v2 analyses retain their original profile identifiers, generator hashes, panel keys, and output namespaces. The later B/S/G ablation and recovery bridge are separate, versioned evidence for the current public observation default.

Appendix A gives the population argument that motivates the recovery predictions. Under ideal block measurement, common within-block signal and independent cross-block processes produce separated population components. Weaker loadings, larger measurement error, lower activity, and cross-block dependence reduce the weakest within-block recovery margin. The simulations test these predictions as panel-paired changes while separating usable-output probability from recovery conditional on a usable output.

Method

The analyses follow the workflow in Figure 2. We first use empirical video-score panels to define selected realism targets for model-derived expression-score series (Panels A–C). We then translate those targets into LOMM scenario conditions (Panel D). The public observation pipeline applies the empirical B+S compositional profile by default, with loading-aligned B+S and homogeneous linear profiles as explicit alternatives




Figure 2: Visual overview of the LOMM pipeline. Panels A–C show clip-level empirical calibration and held-out realism targets. Panel D shows scenario construction through dynamics and activity parameters. Panels E–G show two versioned output paths: the empirical B+S public default maps to bounded compositions for realism checks; the completed revision-v2 benchmark uses homogeneous linear panels, and the bridge uses loading-aligned B+S `linear_z` panels, for known-truth recovery. Panel H compares recovered dimensions and blocks with the declared simulation target. No bounded-probability or CLR recovery result is claimed.

(Panels E–G). The historical revision-v2 generator and the `linear_z` bridge occupy separately versioned recovery paths. Recovery methods are evaluated only on panel surfaces whose dimensionality, indicator blocks, baseline geometry, and reported scale are declared by the simulation design (Panel H).

Empirical Calibration and Realism Targets

Figure 3 illustrates the empirical score-series surface used to motivate the simulation study. MAFW, introduced as *MAFW: A Large-scale, Multi-modal, Compound Affective Database for Dynamic Facial Expression Recognition in the Wild*, supplies naturalistic video clips for calibrating selected score-series statistics (Liu et al., 2022). The dataset does not validate the classifier-output labels, the scoring model, or the subjective emotional states of the people in the clips. The four frames identify the dataset-derived scoring example. The repository and archive do not include raw MAFW videos, and access to the original video materials remains governed by the dataset providers. The realism check uses a 100-clip calibration sample scored with the same zero-shot procedure as the illustrated clip.

We used the transforEmotion R package to generate frame-level classifier-output scores from the calibration videos (Tomašević et al., 2026). The scoring call used model key `oai-large`, which maps in the local model registry to `openai/clip-vit-large-patch14`, corresponding to OpenAI CLIP ViT-Large/14. Each sampled

video was decoded into frames and scored against the prompt-defined classifier-output channels labeled anger, disgust, fear, happiness, neutral, sadness, surprise, contempt, anxiety, helplessness, and disappointment. These 11 prompt channels follow the MAFW single-label schema and are model outputs rather than frame-level human annotations. Score vectors were closed to the simplex in the locked component order. The primary calibration view retained complete rows; a sensitivity view filled bounded internal gaps of at most two frames by interpolating the whole ILR vector within a clip segment. These prompt-defined classifier-output panels define empirical targets for the LOMM observation layer through their temporal persistence, variability, and co-fluctuation.

The selected frames from the same MAFW clip anchor the empirical example (Panel A). Their classifier-output score profiles show that different frames receive different values across channels labeled helplessness, fear, disgust, sadness, anxiety, and disappointment (Panel B). The frame-level trajectories show that the highest mean channels change in bursts with irregular local movement (Panel C). The single-video DynEGA network partitions the same clip's non-neutral classifier-output trajectories (Panel D). This panel is an illustrative readout of model-output channels in one clip; the simulation study later tests recovery under a prespecified generating structure.

The empirical calibration sample was assembled at the clip level from a label-diverse MAFW manifest, with MAFW category labels used for sample diversity rather than validation targets. The primary complete-case view contains 3,557 rows in 188 clip segments; usable clip lengths range from 16 to 50 frames, with a median of 35. The bounded-gap sensitivity view interpolates whole ILR vectors across internal gaps of at most two frames and contains 3,632 rows in 129 clip segments; usable clip lengths range from 17 to 50 frames, with a median of 36.5. Both views retain 100 clips spanning the 11 MAFW single-label categories. The primary complete-case view defines the adoption analysis, while the interpolated view is a sensitivity analysis. The short clip lengths bound the interpretation of autocorrelation and spectral summaries.

For the empirical realism check, empirical and simulated panels are summarized at two levels. Observable-channel metrics are computed directly from the classifier-output score series within each clip. Recovered community-score summaries are computed after applying pooled DynEGA to the score panel and extracting score summaries for the recovered communities. This second readout is method-dependent descriptive information, not independent evidence that the empirical videos contain the same latent dimensions as the simulation. The observable-channel readout evaluates channel-level amplitude and movement; the recovered community-score readout evaluates the lower-dimensional geometry induced by this DynEGA summarization step.




Figure 3: Single-video empirical score-series illustration from the MAFW dataset. Panel A shows four selected frames from one MAFW clip; Panel B shows the corresponding selected-frame classifier-output score profiles; Panel C shows smoothed frame-level classifier-output trajectories for the highest mean channels; Panel D shows a DynEGA network estimated from the same clip's non-neutral classifier-output trajectories. Scores were generated with transforEmotion using model key `oai-large`, which maps to OpenAI CLIP ViT-Large/14 (`openai/clip-vit-large-patch14`).

The primary realism targets summarize dispersion, local movement, temporal structure, and effective multivariate dimensionality. Channel IQR is the interquartile range of a score series, so higher values mean wider score dispersion. Derivative IQR is the interquartile range of first differences, so higher values mean larger frame-to-frame movement. Lag-1 autocorrelation indexes local persistence. Run-length entropy is the entropy of monotonic run lengths in the first-difference sign series, so higher values indicate more varied directional regimes. Spectral entropy is the normalized entropy of the fast-Fourier-transform power distribution, so higher values indicate broader spectral complexity. Effective rank is the entropy-based rank of the clip-level correlation matrix, so higher values indicate more effective multivariate dimensionality in the score panel.

For channel IQR, derivative IQR, lag-1 autocorrelation, run-length entropy, and spectral entropy, the empirical and simulated distributions contain one value for each clip-by-channel series or clip-by-community-summary series. For effective rank, the distributions contain one value for each clip panel. For each metric distribution, we compare empirical and simulated values using a scaled median difference and a scaled one-dimensional Wasserstein distance. Both discrepancies are divided by the empirical interquartile range for that metric distribution, with a standard-deviation fallback when the empirical interquartile range is near zero. We describe the larger discrepancy as small when it is at most 0.33 empirical interquartile ranges, intermediate when it is above 0.33 and at most 1.00 interquartile range, and large when it exceeds 1.00 interquartile range. The lower threshold approximates one-third of the empirical interquartile range and preserves the implemented value. These heuristic, scale-relative bands make the magnitude easier to read; the continuous discrepancy and its uncertainty remain the evidential quantities. The bands are neither inferential cutoffs nor validation thresholds for the scoring model or prompt labels.

The completed B/S/G realism ablation uses five clip-level folds assigned deterministically within MAFW label and usable-length order. Each fold holds out 20 clips. The contrast center, loading directions, between-clip covariance, and oscillator candidate are estimated on the remaining 80 clips and then held fixed. Candidate selection uses observable probability and log-ratio discrepancies. The selected calibration generates 100 evaluation panels for each held-out fold. Clip-level metric contributions are retained for 2,000-resample fold-stratified clip-cluster intervals; no held-out clip contributes to calibration. The earlier revision-v2 calibration and recovered-community summary remain a separate historical analysis.

Scenario Selection

Scenario selection links the empirical calibration targets to the simulation design. We group manipulated conditions into three parameter families (Panel D). The dynamics family varies the position feedback, velocity

feedback, and innovation variance parameters, η_f, ζ_f, and σ_{qf}. The activity family varies whether one latent expressive dimension dominates across the full sequence, whether dominance switches after sampled dwell intervals, or whether all dimensions remain close to low-expression background activity. In the historical revision-v2 generator, the measurement family varies the block loading matrix Λ_i and measurement-error covariance matrix Σ_i that generate the observed classifier-output score panels.

The scenario set contains six activity-and-dynamics families. Four families are generic score-panel regimes: low-expression single dominance, high-expression single dominance, high-expression switching, and high-expression rapid switching. Two families use the empirical calibration logic more directly: ranked-persistence and broad switching-geometry. Table 1 summarizes the activity envelope and dynamic rules used by each family. Across these families, LOMM varies the latent dimensionality and measurement layer so that the number of observed channels equals the number of latent dimensions times the number of indicators per dimension, $p = mk$. The matched three-method grid uses two- and three-dimensional generating structures, and the broad DynEGA extension includes two-, three-, and four-dimensional structures. The final crossed factors, replication counts, and method-specific grid sizes are specified in the dimensional-recovery simulation section below.

Table 1: Activity-and-dynamics scenario families used in the final simulations. Rows vary expression strength, switching, dwell length, feedback pattern, and innovation scale. Dwell values are fractions of the simulated sequence length.

Family	Source	Switching	Active/background gain	Dwell fraction	Dynamic rule
Low-expression single dominance	Generic score-panel regime	No	0.35 / 0.05	1.00 / 1.00	Template feedback; low innovation scale
High-expression single dominance	Generic score-panel regime	No	1.00 / 0.08	1.00 / 1.00	Template feedback; baseline innovation scale
High-expression switching	Generic score-panel regime	Yes	1.00 / 0.08	0.20 / 0.45	Template feedback; baseline innovation scale
High-expression rapid switching	Generic score-panel regime	Yes	1.25 / 0.08	0.03 / 0.10	Template feedback; high innovation scale
Ranked-persistence	Calibration-inspired regime	No	1.00 / 0.08	1.00 / 1.00	Ranked feedback; moderate innovation scale
Broad switching-geometry	Calibration-inspired regime	Yes	1.10 / 0.10	0.12 / 0.30	Ranked feedback; higher innovation scale

Numerical values for feedback and innovation-scale settings are reported in the supplementary scenario-parameter tables.

For each simulated video, LOMM first generates latent trajectories from the scenario-specific dynamic parameters. The activity schedule then scales those trajectories. Non-switching scenarios keep one active dimension

for the full sequence and rotate the dominant dimension across videos. Switching scenarios sample dwell intervals and change the active dimension over time. The observation layer is applied to the activity-scaled latent trajectories. New simulations default to empirical B+S on the compositional surface. The completed revision-v2 recovery grid retains its homogeneous linear surface, diagonal measurement-error covariance, and item-level variance jitter as a versioned historical design. The simulation design therefore records its profile, baseline geometry, scale setting, and observation surface before recovery is evaluated.

Dimensional-Recovery Simulation Study

The simulation begins with latent trajectories and the prespecified number of simulated expressive dimensions (Panel E). The LOMM observation layer adds the declared clip baseline, applies clip scale to the dynamic signal and residual, and returns either bounded compositions or the identified contrast surface (Panel F). This produces a panel with explicit profile and geometry metadata (Panel G). The final step compares the estimated number of dimensions and item memberships with the generating measurement structure (Panel H). The loading-aligned mode is used when between-clip baselines must remain inside a known loading space. The `none` mode with clip scale disabled is the exact homogeneous profile nested within the public layer; revision-v2 remains a separate historical generator.

The method comparison uses a common graph-partitioning target. Each pipeline receives the same simulated score panel, estimates a structure among observed score channels, converts that structure to communities, and compares the resulting partition with the generating indicator blocks. The target is recovery of LOMM-generated score blocks. Classifier-label validity and method superiority for substantive emotion inference are outside this test.

The matched three-pipeline design is the primary comparative analysis. We compare Dynamic Exploratory Graph Analysis [DynEGA; H. Golino et al. (2022)] with GraphicalVAR (Epskamp et al., 2018; Epskamp, 2024) and GIMME (Gates & Molenaar, 2012; Lane et al., 2019) because they represent adjacent approaches to intensive longitudinal structure. DynEGA is the focal dimensional-recovery method because it estimates groups of variables whose changes are coordinated over time. In the present simulation, DynEGA tests direct recovery of the generating score blocks. GraphicalVAR is a dynamic-network comparator that separates lagged temporal relations from contemporaneous partial associations, and its fitted contemporaneous structure is partitioned after estimation. GIMME is an indirect feasibility-stress comparator: it estimates time-series paths for each clip treated as a separate time series, and the resulting contemporaneous structures are aggregated and partitioned. This use of GIMME treats clips as analytic series and should not be read as participant-level idiographic affect modeling.

DynEGA combines time-delay embedding and derivative estimation from dynamical systems with exploratory graph analysis for dimensionality assessment (Boker et al., 2010; H. Golino et al., 2020; H. F. Golino & Epskamp, 2017). We apply DynEGA to the stacked video panel with video identity supplied as the grouping variable. The embedding dimension is selected by minimizing the Total Entropy Fit Index (TEFI) over candidate values (H. Golino et al., 2021), using $n_{\text{embed}} \in \{5, 10, 15, \lfloor T/4 \rfloor, \lfloor T/2 \rfloor\}$ where admissible. The LOMM generator retains the physical step $dt = 0.4$ and uses it to calculate the observed horizon. The EGAnet GLLA call records `delta = 1`, corresponding to one observation interval. Expressing the derivatives per unit of physical time would multiply every channel derivative by the common positive factor $1/dt$; this rescaling leaves the derivative correlation matrix and its downstream EBICglasso network unchanged. The run artifacts record physical `dt` and the DynEGA observation-unit `delta` separately. We explicitly set `model = "glasso"` so DynEGA estimates an EBICglasso regularized partial-correlation network from the pooled derivative panel. That network is partitioned into communities interpreted as recovered groups of score channels. The checked-in broad grid uses Louvain community detection (Blondel et al., 2008) with the expand rule for unidimensional solutions. The checked-in matched grid reports Louvain, Leiden (Traag et al., 2019), and Walktrap (Pons & Latapy, 2005) readouts.

GraphicalVAR estimates a graphical vector autoregressive model for intensive longitudinal data (Epskamp et al., 2018; Epskamp, 2024). In this framework, the temporal network contains directed lag-1 regression parameters, and the contemporaneous network contains partial correlations among residuals at the same time point after lagged effects have been taken into account. In multilevel applications, the model can also distinguish within-person temporal and contemporaneous structure from between-person associations among stationary means. We fit GraphicalVAR to the stacked simulated score panel and use the estimated contemporaneous partial-correlation matrix as the structural matrix for dimensional partitioning, because LOMM recovery targets an undirected grouping of score channels. The diagonal is ignored and the resulting weighted matrix is treated as an undirected graph. Positive edge weights define the graph, with absolute weights used only when no positive edges are available. Louvain, Leiden, and Walktrap are applied to the same fitted contemporaneous structure and are analyzed as the community-detection factor.

GIMME is an automated time-series modeling approach built around unified structural equation modeling and vector autoregressive representations (Gates & Molenaar, 2012; Lane et al., 2019). The algorithm searches for lagged and contemporaneous paths that improve fit across the sample, retains paths that are common to many series, and then allows subgroup-shared or series-specific paths. In this simulation, each video clip is treated as the time series supplied to GIMME. We fit the VAR specification to the video-level score panels, extract the contemporaneous block from the clip-specific Ψ matrices, and average those blocks

across clips to obtain a common structural matrix for dimensional partitioning. The diagonal is ignored, the matrix is symmetrized, and negative entries are set to zero. A matrix with no remaining positive edge yields singleton communities rather than an absolute-weight fallback. Louvain, Leiden, and Walktrap are applied to the same fitted GIMME structure and are analyzed as the community-detection factor.

The matched grid is the primary comparative design. All three fitted structures are converted to dimensional partitions and evaluated against the same prespecified generating structure. DynEGA is then evaluated on the broader grid to assess scalability across the larger LOMM design space. GraphicalVAR and GIMME are restricted to the matched grid because complete factorial estimation is computationally unstable in this setting. Community detection is a diagnostic factor in the matched design; method and simulation design remain the primary organizing variables. Appendix A derives the population structural signal supplied by each pipeline and collects implementation differences in a common perturbation framework.

The prospective revision specification locks the matched $T = 100$ design to 21,600 generated panels: six scenario families, two generating dimensionalities, two sample sizes, three measurement-error levels, three loading levels, and 100 paired replications. Every method receives a method-independent panel key, paired simulation seed, generator specification hash, observed horizon, and stability classification. DynEGA, GraphicalVAR, GIMME, and static EGA each supply one retained structure per panel; Louvain at resolution 1.0 is the primary common partition, and Leiden and Walktrap are paired sensitivity readouts of that same structure. The true-block oracle passes the generating block matrix through the identical partition helper. DynEGA additionally retains its native expand readout and a correlation-Louvain readout at resolution 0.95 as secondary paired analyses. GIMME's common structural matrix is the positive part of the symmetrized mean contemporaneous matrix, $[(\bar{\Psi} + \bar{\Psi}^{\top})/2]_{+}$.

The short-record study repeats the 21,600-panel design with $T = 25$, $dt = 0.4$, and observed horizon $H = 9.6$, using DynEGA embedding candidates $\{5, 6, 10, 12\}$ and seeds paired to the corresponding $T = 100$ conditions. It is interpreted as a same-cadence, shorter-horizon stress test. GIMME is designated as outside its preferred design range in this condition, and its 900-second per-panel budget is retained in the feasibility denominator. The separate challenge suite crosses the six scenario families, two dimensionalities, 50 paired replications, and seven one-factor-at-a-time variants. It fixes $N = 100$, $T = 100$, error standard deviation 0.25, loading 0.60, and four indicators per factor; the variants address initialization, smooth gates, cross-loadings, residual correlation, innovation correlation, and bounded softmax scores represented both raw and by centered log-ratios.

Performance is summarized using dimensional hit rate, assignment accuracy for observed score channels,

matched trajectory-recovery correlation, matched trajectory-recovery normalized root mean squared error (NRMSE), runtime, and failure or timeout accounting. Method-readout rows are the denominator for dimensional hit rate and the status counts in Table 2; they include one row per method, generated panel, and community-detection readout. For GraphicalVAR and GIMME, feasibility is also reported as unique structure-fit status counts before the repeated Louvain, Leiden, and Walktrap readouts. Dimensional hit rate is the proportion of method-readout rows in which the method returns the correct number of latent dimensions. Assignment accuracy is computed for readouts with available partitions and asks whether observed score channels are assigned to the correct generating blocks after optimal matching of estimated communities to those blocks. For trajectory-recovery metrics, observed variables are standardized within the full panel and recovered community-score summaries are computed from the first principal component of each estimated block, with row means used when a principal-component score cannot be estimated. Matched trajectory-recovery correlation and NRMSE compare these recovered score summaries with the generating latent trajectories after sign-invariant matching between estimated communities and generating dimensions. These trajectory-recovery diagnostics are computed only when score summaries are available; they are secondary diagnostics rather than status-inclusive method-performance measures. Runtime is recorded for each model fit.

The prospective result contract separates estimator feasibility from recovery after a usable output. It reports $P(\text{usable})$, $P(\widehat{m} = m \mid \text{usable})$, and $P(\text{usable and correct})$; signed and absolute dimension error; adjusted Rand index, variation of information, and assignment accuracy conditional on a usable partition; marginal score correlation and NRMSE; completion within 900 seconds; restricted compute time $\min(\text{runtime}, 900)$; and the median and interquartile range of runtime among successful fits. Method, horizon, oracle, and challenge contrasts are panel-paired. Uncertainty uses 2,000 panel-cluster resamples, accompanied by Monte Carlo standard errors. Error, timeout, and partial rows remain in every status-inclusive denominator.

The final simulation uses a split design. The matched three-method grid uses four indicators per latent dimension, two- and three-dimensional generating structures, two sample sizes, 100 time points, three loading strengths, three measurement-error standard deviations, and all six scenario families. The reported final runs fix the innovation quality scale at $Q = 0.75$, so the scenario base σ_q vectors listed in the supplementary scenario-parameter tables are the final-run innovation vectors. The latent systems were advanced with the exact linear transition of Equation 1 using step size $dt = 0.4$ for 100-point series and $dt = 0.25$ for 300-point series, so σ_{qf} is the per-step shock standard deviation at that resolution. This matched grid contains 216 structural cells with 100 replications. Louvain, Leiden, and Walktrap are included as community-detection levels, yielding 64,800 method-readout rows per method in the matched three-method grid. The

broad DynEGA extension varies the number of videos, series length, latent dimensionality, indicators per dimension, loading strength, and measurement-error standard deviation across 1,296 structural cells with 400 replications, yielding 518,400 DynEGA Louvain/expand method rows. Timeouts, failed fits, and post-estimation extraction errors are retained in the reporting denominator because they are part of method behavior in applied simulation workflows.

Computational Environment

Final run metadata records R 4.5.1 on Rocky Linux 8.8 (`x86_64-redhat-linux-gnu`), 48 available logical cores, OpenBLAS 0.3.15, and LAPACK 3.9.0. Local inspection of the execution host for this final-results workspace reports dual Intel Xeon Silver 4310 CPUs, 48 logical threads, and 125 GiB RAM. The run artifacts store the operating system, R session, and available-core count; they do not store RAM or a separate hostname. Key package versions were EGAnet 2.3.0, graphicalVAR 0.3.4, gimme 10.0, igraph 2.2.1, qgraph 1.9.8, psych 2.5.6, lavaan 0.6-20, dplyr 1.1.4, and ggplot2 4.0.1. Parallel jobs used one BLAS thread per worker. The broad DynEGA grid used 16 workers with one internal DynEGA core per fit, the matched DynEGA community-detection supplement used 32 workers, and the GraphicalVAR and GIMME matched-grid runs each used 24 workers with a 900-second elapsed-time limit per structure fit.

Runtime is elapsed wall-clock time, recorded with `proc.time()[["elapsed"]]` for successful fitted structures and summarized in seconds. For GraphicalVAR and GIMME, the recorded runtime includes the structure fit and post-fit extraction/community-detection readout. The same fitted structure is reused for Louvain, Leiden, and Walktrap, so feasibility accounting separates unique structure-fit status from repeated method-readout rows. Runtime summaries use successful fits. Timeout and error rows remain in feasibility and recovery denominators. The runtime results should therefore be read as within-machine feasibility estimates for this simulation workflow rather than hardware-independent speed benchmarks.

Results

Results are organized by the three research questions stated in the Introduction. Figure 4 gives the selected empirical-realism checks, Table 2 and Figure 5 summarize structural recovery, Figure 6 isolates simulated measurement-quality factors, and Figure 7 reports computational feasibility.

Empirical Realism Results

The first result checks the calibrated LOMM realism panel against selected distributional, temporal, spectral, and effective-dimensionality signatures of the MAFW-derived classifier-output score panels. Figure 4 summarizes the check at two levels: the observed score channels and the recovered community-score summaries extracted from the pooled DynEGA solution. The figure is generated from the empirical-realism file `metric_comparison_long.csv`, not from the final dimensional-recovery simulation outputs. The check is limited to selected score-series similarities used for simulation construction; scoring-model validity and emotion-label validity require separate evidence.




Figure 4: Selected empirical-realism checks for the calibrated LOMM realism panel. Panel A shows pass, partial, and fail classifications for six score-series targets at observed-channel and recovered community-summary readouts. Panel B shows the two discrepancy components separately; dashed reference lines mark the pass threshold of 0.33 and fail threshold of 1.00.

At the observed-channel level, the revision-v2 calibrated realism panel passed the derivative-IQR and run-length entropy checks. Lag-1 autocorrelation, spectral entropy, and effective rank were partial score-series matches because they did not meet the strictest threshold. Channel IQR failed, showing that the simulated

observed channels remained more dispersed than the empirical score channels. This result describes the historical softmax-linked realism panel. The later paired B/S/G ablation supplies the adoption evidence for the current public default, while the completed broad dimensional-recovery simulations retain the historical homogeneous linear panels described in the model section.

In the completed paired ablation, negative composite contrasts indicate lower held-out discrepancy. The complete-case marginal contrast for B was -0.0418, with a descriptive 95% fold-stratified clip-cluster percentile interval from 2,000 resamples of $[-0.0413, -0.0258]$. The S contrast was smaller at -0.0188, with a corresponding descriptive interval of $[-0.0143, 0.0009]$, and the tested additional smooth-gate component increased discrepancy. The B and S point estimates fall below their respective percentile intervals because these nonlinear discrepancy estimands show bootstrap bias; the intervals are reported descriptively and carry no stronger inferential claim. The selected B+S profile had a held-out mean composite discrepancy of 0.2567, compared with 0.3250 for the homogeneous profile, a descriptive reduction of 21.0%. The B+S comparison was not one of the prespecified factorial bootstrap contrasts, and the calibration uses one retained MAFW/CLIP score surface. These results motivated retaining B+S as a configurable calibrated default; the choice is a pipeline design decision rather than a universal observation law.

The recovered community-score summaries showed the same main boundary with a stronger amplitude mismatch. The community-score Channel IQR median was 0.832 in LOMM and 0.247 in the empirical panels, with a maximum scaled discrepancy of 1.481. This identifies amplitude dispersion as the main revision-v2 calibration boundary. The check does not establish empirical validity for the historical linear recovery panels or external validity for the current compositional default.

The next analyses use the historical homogeneous linear LOMM panels to evaluate known-truth recovery.

Simulation Results

The recovery analysis separates scalability, direct method comparison, simulated measurement-quality sensitivity, and computational feasibility. DynEGA was evaluated on the broad Louvain/expand grid and on the matched four-indicator design shared with GraphicalVAR and GIMME. The matched comparison aggregates across Louvain, Leiden, and Walktrap readouts and treats community detection as a diagnostic factor. Table 2 summarizes dimensional recovery, status counts, assignment accuracy, and successful-fit runtime by method.

Table 2: Overall method behavior in the final matched four-indicator grid, aggregated across Louvain, Leiden, and Walktrap readouts. Rows are method-community-detection readout rows. Hit rate is recovery of the generating number of latent dimensions using all readout rows as the denominator; Assignment is optimal block-assignment accuracy for readouts with available partitions. Median runtime is computed over successful fitted structures.

Method	Total rows	Valid rows	Timeouts	Errors	Hit (%)	Assignment (%)	Median runtime (s)
DynEGA	64800	64800	0	0	95.3	96.0	2.61
GraphicalVAR	64800	62616	2184	0	80.3	90.4	86.10
GIMME	64800	45882	12342	6576	25.9	67.2	280.50




Figure 5: Dimensional hit rate across the final matched four-indicator method-comparison conditions. Lines show methods and vertical intervals show cluster-bootstrap 95% confidence intervals, resampling generated panels while retaining their community-detection readouts. Condition codes A–F refer to the simulated score-panel regimes in Table 1. Hit rates are status-inclusive and aggregated across Louvain, Leiden, and Walktrap readouts.

DynEGA was the only method evaluated on the broad grid and completed all 518,400 Louvain/expand rows. On that grid, it recovered the generating number of dimensions in 93.7% of rows and assigned observed classifier-output channels to the generating blocks with 95.2% accuracy. Table 2 reports status-inclusive method-readout rows after community-detection readouts. Unique structure-fit feasibility counts are reported in the Computational Feasibility section and Appendix D. Aggregating across Louvain, Leiden,

and Walktrap, DynEGA recovered the generating number of dimensions in 95.3% of matched-grid rows, GraphicalVAR in 80.3%, and GIMME in 25.9%. Assignment accuracy followed the same ordering among readouts with available partitions: 96.0% for DynEGA, 90.4% for GraphicalVAR, and 67.2% for GIMME.

Figure 5 shows the matched-grid scenario pattern. DynEGA retained the strongest recovery profile across the simulated score-panel regimes. GraphicalVAR recovered the generating dimensionality in many ranked-persistence and broad-switching-geometry conditions when the structure fit completed, while recovery dropped in the low-expression single-dominance condition. GIMME showed the lowest status-inclusive recovery because many fits timed out or produced no usable contemporaneous structure for partitioning.

Because method and generated scenario family dominated dimensional hit rate, Figure 6 isolates the simulated measurement-quality factors that directly alter the observed score panels. The descriptive row-level factor screen showed the same ordering: method and scenario family had the largest associations with dimensional hit rate, measurement-error standard deviation also mattered, loading strength had a smaller association, and community detection contributed essentially no variation. These effect-size summaries are descriptive because community-detection readouts from the same fitted structure are repeated in the row-level data.




Figure 6: Dimensional hit rate stratified by measurement-error standard deviation and loading strength in the final matched four-indicator grid. Columns show loading strength; lines and symbols show methods. Hit rates are status-inclusive. Error bars are descriptive Wilson intervals computed from method-readout rows in each stratum, aggregated across community-detection readouts.

Figure 6 shows how method differences changed across measurement quality. DynEGA was most stable across the loading-by-error grid, although low-signal scenarios still reduced recovery. GraphicalVAR was more sensitive to the measurement layer: its hit rate was weakest when loadings were low and measurement error was high, and improved when observed channels carried a stronger signal from their generating dimensions. GIMME remained lower on status-inclusive hit rate across most strata because errors and timeouts occurred before dimensional recovery could be evaluated. This loading-by-error gradient tracks the population signal-to-noise ratio $\lambda^2 V/\psi$ that drives both graph readouts in Appendix A.

Conditional on obtaining a usable structural readout, trajectory-recovery diagnostics followed the same measurement pattern. Recovery was strongest in the ranked-persistence and broad switching-geometry generated regimes and deteriorated as measurement-error standard deviation increased. These diagnostics are conditional summaries, not status-inclusive method-performance measures; full marginal means are reported in

Appendix C.

Computational Feasibility

Computational feasibility was evaluated separately from recovery accuracy because the methods differed in both recovery behavior and scalability across the simulation design. Figure 7 summarizes successful-fit runtime in the matched four-indicator grid, and the text below accounts for broad-grid completion, timeouts, and post-estimation errors. This distinction is important for interpreting the comparator results: GraphicalVAR and GIMME are informative matched-grid comparisons with more limited scalability across the full LOMM grid.



Figure 7: Runtime of the compared methods in the final matched four-indicator grid. The y-axis is shown on a log10 time scale. Points show median runtime for successful fitted structures and intervals show the interquartile range. For GraphicalVAR and GIMME, the same fitted structure is reused across Louvain, Leiden, and Walktrap readouts.

DynEGA was substantially faster than the two model-based comparators in the matched design. Median successful-fit runtime was 2.61 s for DynEGA, compared with 86.1 s for GraphicalVAR and 280.5 s for GIMME. The broad DynEGA Louvain/expand grid also completed all 518,400 method rows without errors or timeouts. GraphicalVAR completed 20,872 of 21,600 matched-grid structure fits and timed out on 728 fits. GIMME completed 15,294 of 21,600 matched-grid structure fits, timed out on 4,114 fits, and returned post-estimation errors for 2,192 fits. Because GraphicalVAR and GIMME apply three community-detection algorithms to each fitted structure, these feasibility counts refer to unique structure fits before repeated CD readouts; Appendix D reports the fit-level and readout-row accounting side by side. In these LOMM simulation designs, DynEGA combined the strongest structural recovery with broad-grid scalability, GraphicalVAR

was informative but slower and more condition-sensitive, and GIMME was feasibility-limited.

Discussion

LOMM gave a controlled score-generation problem for evaluating dynamic dimensional recovery. The empirical-realism checks reproduced local movement and directional-change texture, partially matched persistence, spectral complexity, and effective multivariate dimensionality, and retained a clear amplitude-dispersion mismatch. In the recovery grids, DynEGA recovered the generating dimensionality and indicator blocks most consistently in these LOMM simulation designs and completed the broad focal-method grid. Recovery weakened when simulated measurement signal was lower. GraphicalVAR was informative but condition-sensitive, and GIMME was feasibility-limited in the matched design. The trajectory-recovery diagnostics add a conditional result among method-readout rows with recovered score summaries; they are not a status-inclusive method ranking.

Appendix A frames recovery in the historical homogeneous revision-v2 linear benchmark panels as a method-specific graph perturbation problem. Under that linear benchmark model, indicators assigned to the same latent oscillator share a common change signal. Indicators assigned to different oscillators are independent. The measurement signal within each dimension is rank-one, and per-channel filtered population graphs form disconnected weighted cliques under the symmetric block target. DynEGA reads this structure through smoothed derivative estimates. GraphicalVAR reaches the same block algebra through a multivariate VAR innovation projection under the simplified population target. GIMME adds an indirect graph-conversion and completion layer rather than a closed-form population block edge. The population edge sets how much common block signal reaches community detection, and recovery becomes more difficult when the method-specific perturbation approaches the weakest within-block edge.

DynEGA is closely aligned with this target in these LOMM simulation designs. DynEGA groups variables whose estimated changes are coordinated over time, so the common derivative signal within each LOMM block is the relevant recovery signal. The high dimensional hit rate, high block-assignment accuracy, and complete broad-grid coverage indicate that this signal usually remained identifiable across the simulated score-panel regimes. The reductions under weak loadings, high measurement error, and low-expression generated regimes identify conditions in which the observed channels no longer carry enough common dynamic variation for reliable partitioning.

The generator separates three parts of the measurement problem. The oscillator layer controls restoring forces, momentum, and stochastic perturbation. The activity layer controls dominance and switching. The

observation layer controls loading geometry, measurement error, between-clip baselines, clip scale, and the reported score surface. The public default activates empirical B+S on the compositional surface; loading-aligned and zero baselines remain explicit alternatives, and the homogeneous model is nested at zero baseline and unit scale. This separation lets method researchers test whether an analysis recovers latent organization or responds mainly to features of the observation system.

GraphicalVAR represents the generating measurement blocks less directly. In this comparison, community detection is applied to the contemporaneous partial-correlation matrix, which conditions each pairwise association on the remaining channels. Appendix A shows that, in the symmetric block model, the population VAR innovation graph preserves block support but compresses the within-block edge toward a ceiling set by block size. The VAR projection also removes the predictable part of the common block signal before the contemporaneous graph is read. The observed sensitivity of GraphicalVAR is consistent with this mechanism, especially when loadings are weak or measurement error is high. The simulation does not isolate this population attenuation from lag estimation, regularization, finite-sample variation, or timeout behavior. In the matched grid, GraphicalVAR completed most structure fits and had 728 unique structure-fit timeouts, so its main limitation in this comparison was condition sensitivity with some timeout loss.

GIMME has broader native aims than dimensional partitioning. It searches for group, subgroup, and individual lagged and contemporaneous paths. In the present evaluation, video clips are analytic time series; clip-specific contemporaneous structures are averaged and then partitioned with a separate community-detection step. Its lower status-inclusive hit rate therefore reflects both the indirect GIMME-to-community graph and substantial feasibility costs, including long successful-fit runtimes, timeouts, and post-estimation errors. The result evaluates the implemented clip-level GIMME-to-community procedure under this design. Person-level idiographic applications of GIMME require separate evidence.

With a valid structural graph, trajectory-recovery diagnostics showed the largest marginal differences by generated scenario family and measurement-error standard deviation. Ranked-persistence and broad switching-geometry panels produced the closest trajectory summaries. Low-expression single-dominance panels were the most difficult. These diagnostics evaluate recovery of simulated latent trajectories after a usable structure has been estimated. They do not evaluate classifier-output validity, emotion-label validity, or status-inclusive method performance. Full marginal summaries are reported in Appendix C.

The empirical realism evidence limits the interpretation to selected statistical resemblance between simulated panels and classifier-output score panels from the retained MAFW calibration sample. It cannot validate the scoring model, the prompt labels, or subjective emotional states in the videos. The calibration used one

dataset label schema and one scoring implementation, and the empirical clips were short relative to some simulation regimes. The short empirical clips support calibration of selected local score-series properties. The longer simulation conditions test method behavior under controlled series lengths. B was the clearest descriptive improvement over the homogeneous observation profile in the paired ablation; S produced a smaller and less certain marginal improvement, and B+S was retained as the practical calibrated default. The fold-stratified clip-cluster percentile intervals are descriptive, including the bootstrap-bias boundaries for the nonlinear B and S estimands. This default remains configurable and requires evaluation on other scoring systems and datasets.

The comparison is narrow by design. The broad method-comparison results apply to the historical homogeneous linear block-measurement panels. The paired bridge screens loading-aligned B+S on pre-link linear panels in selected stable $T = 100$ conditions; it does not evaluate recovery from bounded probabilities or establish equivalence across the full benchmark grid. For the primary Louvain status-inclusive usable-and-correct outcome, DynEGA was 0.750 under loading-aligned B+S and 0.775 under homogeneous, a paired effect of -0.025 with a 95% percentile interval of $[-0.100, 0.050]$. GIMME was 0.400 under both profiles, GraphicalVAR was 0.0375 under both, and the oracle was 1.000 under both; static EGA increased from 0.275 to 1.000. This was a compatibility screen rather than an equivalence test: the DynEGA interval remains compatible with a 0.10 loss, every three-dimensional GIMME fit timed out under both profiles, and the conditional GIMME partition metrics contain 40 paired usable two-dimensional fits. GraphicalVAR's zero primary dimensional contrast co-occurred with declines in Louvain adjusted Rand index (-0.0226, 95% interval $[-0.0484, -0.0013]$) and assignment accuracy (-0.0198, 95% interval $[-0.0391, -0.0026]$). These contrasts do not establish adequate absolute recovery. The present LOMM implementation uses independent oscillator dimensions, activity-gated latent trajectories, and configurable observation geometry. These choices keep the recovery target interpretable while leaving richer dependence structures for separate tests. The method comparison covers network-based or network-convertible recovery pipelines. Other dynamic latent-variable approaches remain outside the present evaluation. Future work should test richer oscillator coupling, cross-loadings, correlated measurement error, additional compositional scoring systems, and empirical applications where simulation results guide method validation before substantive interpretation of classifier-output score dynamics. The present results support LOMM as a controlled validation environment for selected temporal and dimensional properties. Full generative theories of affect and validation of scoring-model emotion labels require separate evidence.

Declarations

Funding

The authors received no specific funding for this work.

Competing interests

The authors declare that they have no competing interests.

Ethics approval

This study used simulations and secondary, publicly described reference materials. It did not involve new recruitment, intervention, or direct collection of human-participant data by the authors.

Consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The manuscript analyses use simulation outputs and derived classifier-output score summaries generated for this study. The OSF archive ([anonymized OSF link provided for masked review]) contains the version-controlled manuscript repository, final simulation runners, figure-generation scripts, manuscript-facing derived outputs, provenance manifests, and from-scratch rerun instructions for the final simulation grids. Raw MAFW video materials are third-party dataset materials; access to the original videos is governed by the MAFW dataset providers. Derived empirical score summaries needed for the realism check are included in the archive.

Code availability

All code needed to rerun the final LOMM simulations, rebuild the method-comparison summaries, regenerate the manuscript figures and tables, and render the manuscript is available in the archived project repository ([anonymized OSF link provided for masked review]). The repository includes the R simulation

runners, empirical realism and method-comparison scripts, manuscript rendering source, claim ledger, and run manifests.

Authors' contributions

Aleksandar Tomasevic contributed conceptualization, formal analysis, methodology, resources, software, validation, visualization, writing the original draft, and reviewing and editing the manuscript. Hudson Golino contributed formal analysis, methodology, resources, software, validation, visualization, writing the original draft, and reviewing and editing the manuscript. Alexander P. Christensen contributed methodology, software, writing the original draft, and reviewing and editing the manuscript.

Open Practices Statement

The study was not preregistered. The OSF archive ([anonymized OSF link provided for masked review]) contains analysis code, simulation code, manuscript source files, generated figure and table inputs, and derived empirical score summaries needed for the realism check. It also includes provenance materials for rerunning the final simulations from scratch. Raw MAFW video data are third-party materials governed by the dataset providers.

References

Allison, B., & McKeown, G. (2023). Are facial expression technologies tools for emotion recognition or social interaction analysis, or both? *2023 11th International Conference on Affective Computing and Intelligent Interaction Workshops and Demos (ACIIW)*, 1–8. https://doi.org/10.1109/ACIIW59127.2023.10388163

Arriaga, O., Valdenegro-Toro, M., & Plöger, P. (2017). *Real-time Convolutional Neural Networks for Emotion and Gender Classification* (arXiv:1710.07557). arXiv. https://doi.org/10.48550/arXiv.1710.07557

Blondel, V. D., Guillaume, J.-L., Lambiotte, R., & Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, *2008*(10), P10008. https://doi.org/10.1088/1742-5468/2008/10/P10008

Boker, S. M. (2015). Adaptive equilibrium regulation: A balancing act in two timescales. *Journal for Person-Oriented Research*, *1*(1-2), 99–109. https://doi.org/10.17505/jpor.2015.10

Boker, S. M., Deboek, P. R., Edler, C., & Keel, P. (2010). Generalized local linear approximation of derivatives from time series. In S. M. Chow, E. Ferrer, & F. Hsieh (Eds.), *The notre dame series on quantitative methodology. Statistical methods for modeling human dynamics: An interdisciplinary dialogue*

(pp. 161–178). Routledge/Taylor & Francis Group.

Boker, S. M., & Nesselroade, J. R. (2002). A Method for Modeling the Intrinsic Dynamics of Intraindividual Variability: Recovering the Parameters of Simulated Oscillators in Multi-Wave Panel Data. *Multivariate Behavioral Research*, *37*(1), 127–160. https://doi.org/10.1207/S15327906MBR3701_06

Epskamp, S. (2024). *graphicalVAR: Graphical VAR for experience sampling data*. https://CRAN.R-project.org/package=graphicalVAR

Epskamp, S., Waldorp, L. J., Mõttus, R., & Borsboom, D. (2018). The gaussian graphical model in cross-sectional and time-series data. *Multivariate Behavioral Research*, *53*(4), 453–480. https://doi.org/10.1080/00273171.2018.1454823

Ezerceli, Ö., & Eskil, M. T. (2022). Convolutional Neural Network (CNN) Algorithm Based Facial Emotion Recognition (FER) System for FER-2013 Dataset. *2022 International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME)*, 1–6. https://doi.org/10.1109/ICECCME55909.2022.9988371

Foteinopoulou, N. M., & Patras, I. (2023). *EmoCLIP: A Vision-Language Method for Zero-Shot Video Facial Expression Recognition* (arXiv:2310.16640). arXiv. https://doi.org/10.48550/arXiv.2310.16640

Gates, K. M., & Molenaar, P. C. M. (2012). Group search algorithm recovers effective connectivity maps for individuals in homogeneous and heterogeneous samples. *NeuroImage*, *63*(1), 310–319. https://doi.org/10.1016/j.neuroimage.2012.06.026

Golino, H. F., & Epskamp, S. (2017). Exploratory graph analysis: A new approach for estimating the number of dimensions in psychological research. *PloS One*, *12*(6), e0174035. https://doi.org/10.1371/journal.pone.0174035

Golino, H., Christensen, A. P., Moulder, R., Kim, S., & Boker, S. M. (2022). Modeling latent topics in social media using dynamic exploratory graph analysis: The case of the right-wing and left-wing trolls in the 2016 US elections. *Psychometrika*, *87*(1), 156–187.

Golino, H., Moulder, R., Shi, D., Christensen, A. P., Garrido, L. E., Nieto, M. D., Nesselroade, J., Sadana, R., Thiyagarajan, J. A., & Boker, S. M. (2021). Entropy fit indices: New fit measures for assessing the structure and dimensionality of multiple latent variables. *Multivariate Behavioral Research*, *56*(6), 874–902. https://doi.org/10.1080/00273171.2020.1779642

Golino, H., Shi, D., Garrido, L. E., Christensen, A. P., Nieto, M. D., Sadana, R., Thiyagarajan, J. A., & Martinez-Molina, A. (2020). Investigating the performance of exploratory graph analysis and traditional techniques to identify the number of latent factors: A simulation and tutorial. *Psychological Methods*, *25*(3), 292–320. https://doi.org/10.1037/met0000255

Goodfellow, I. J., Erhan, D., Carrier, P. L., Courville, A., Mirza, M., Hamner, B., Cukierski, W., Tang, Y.,

Thaler, D., Lee, D.-H., Zhou, Y., Ramaiah, C., Feng, F., Li, R., Wang, X., Athanasakis, D., Shawe-Taylor, J., Milakov, M., Park, J., … Bengio, Y. (2013). *Challenges in Representation Learning: A report on three machine learning contests* (arXiv:1307.0414). arXiv. https://doi.org/10.48550/arXiv.1307.0414

Halamová, J., Kanovský, M., Brockington, G., & Strnádelová, B. (2023). Automated facial expression analysis of participants self-criticising via the two-chair technique: Exploring facial behavioral markers of self-criticism. *Frontiers in Psychology*, *14*. https://doi.org/10.3389/fpsyg.2023.1138916

Holiday, S., Hayes, J. L., Park, H., Lyu, Y., & Zhou, Y. (2023). A multimodal emotion perspective on social media influencer marketing: The effectiveness of influencer emotions, network size, and branding on consumer brand engagement using facial expression and linguistic analysis. *Journal of Interactive Marketing*, *58*(4), 414–439. https://doi.org/10.1177/10949968231171104

Hollenstein, T. (2007). State space grids: Analyzing dynamics across development. *International Journal of Behavioral Development*, *31*(4), 384–396. https://doi.org/10.1177/0165025407077765

Houben, M., Van Den Noortgate, W., & Kuppens, P. (2015). The relation between short-term emotion dynamics and psychological well-being: A meta-analysis. *Psychological Bulletin*, *141*(4), 901–930. https://doi.org/10.1037/a0038822

Kankaanpää, R., Ron, J. de, Hoekstra, R. H. A., & Bork, R. van. (2026). Comparing multiple-indicator approaches to account for measurement error in dynamic networks. *Cognitive Therapy and Research*. https://doi.org/10.1007/s10608-026-10719-0

Kollias, D., Tzirakis, P., Baird, A., Cowen, A., & Zafeiriou, S. (2023). ABAW: Valence-arousal estimation, expression recognition, action unit detection, and emotional reaction intensity estimation challenges. *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 5889–5898. https://doi.org/10.1109/CVPRW59228.2023.00626

Kuppens, P., & Verduyn, P. (2017). Emotion dynamics. *Current Opinion in Psychology*, *17*, 22–26. https://doi.org/10.1016/j.copsyc.2017.06.004

Lane, S. T., Gates, K. M., Pike, H. K., Beltz, A. M., & Wright, A. G. C. (2019). Uncovering general, shared, and unique temporal patterns in ambulatory assessment data. *Psychological Methods*, *24*(1), 54–69. https://doi.org/10.1037/met0000192

Li, H., Niu, H., Zhu, Z., & Zhao, F. (2023). *CLIPER: A Unified Vision-Language Framework for In-the-Wild Facial Expression Recognition* (arXiv:2303.00193). arXiv. https://doi.org/10.48550/arXiv.2303.00193

Li, Q., Liu, Z., Zhang, Z., Wang, Q., & Ma, M. (2024). Decoding group emotional dynamics in a web-based collaborative environment: A novel framework utilizing multi-person facial expression recognition. *International Journal of Human-Computer Interaction*, 1–19. https://doi.org/10.1080/10447318.2024.2338614

Li, S., & Deng, W. (2022). Deep Facial Expression Recognition: A Survey. *IEEE Transactions on Affective Computing*, *13*(3), 1195–1215. https://doi.org/10.1109/TAFFC.2020.2981446

Liu, Y., Dai, W., Feng, C., Wang, W., Yin, G., Zeng, J., & Shan, S. (2022). MAFW: A large-scale, multi-modal, compound affective database for dynamic facial expression recognition in the wild. *Proceedings of the 30th ACM International Conference on Multimedia*, 24–32. https://doi.org/10.1145/3503161.3548190

Manelis-Baram, L., Barami, T., Ilan, M., Meiri, G., Menashe, I., Soskin, E., Sofer, C., & Dinstein, I. (2025). Comparing three algorithms of automated facial expression analysis in autistic children: Different sensitivities but consistent proportions. *Molecular Autism*, *16*(1). https://doi.org/10.1186/s13229-025-00685-x

Mehu, M., & Scherer, K. R. (2015). Emotion categories and dimensions in the facial communication of affect: An integrated approach. *Emotion*, *15*(6), 798–811. https://doi.org/10.1037/a0039416

Meng, Z., Liu, P., Cai, J., Han, S., & Tong, Y. (2017). Identity-Aware Convolutional Neural Network for Facial Expression Recognition. *2017 12th IEEE International Conference on Automatic Face & Gesture Recognition (FG 2017)*, 558–565. https://doi.org/10.1109/FG.2017.140

Mollahosseini, A., Hasani, B., & Mahoor, M. H. (2019). AffectNet: A database for facial expression, valence, and arousal computing in the wild. *IEEE Transactions on Affective Computing*, *10*(1), 18–31. https://doi.org/10.1109/TAFFC.2017.2740923

Nesselroade, J. R., McArdle, J. J., Aggen, S. H., & Meyers, J. M. (2002). Dynamic factor analysis models for representing process in multivariate time-series. In D. S. Moskowitz & S. L. Hershberger (Eds.), *Multivariate applications book series. Modeling intraindividual variability with repeated measures data: Methods and applications* (pp. 235--265). Lawrence Erlbaum Associates Publishers.

Nesselroade, J. R., McArdle, J. J., Aggen, S. H., & Meyers, J. M. (2013). Dynamic factor analysis models for representing process in multivariate time-series. In *Modeling intraindividual variability with repeated measures data* (pp. 235–265). Psychology Press.

Ollero, M. J. F., Estrada, E., Hunter, M. D., & Cáncer, P. F. (2025). Characterizing affect dynamics with a damped linear oscillator model: Theoretical considerations and recommendations for individual-level applications. *Psychological Methods*, *30*(5), 1095–1112. https://doi.org/10.1037/met0000615

Plutchik, R. (2001). The nature of emotions. *American Scientist*, *89*(4), 344–350. https://doi.org/10.1511/2001.4.344

Pons, P., & Latapy, M. (2005). Computing communities in large networks using random walks. In Pi. Yolum, T. Güngör, F. Gürgen, & C. Özturan (Eds.), *Computer and information sciences - ISCIS 2005* (pp. 284–293). Springer Berlin Heidelberg. https://doi.org/10.1007/11569596_31

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P.,

Clark, J., Krueger, G., & Sutskever, I. (2021). Learning transferable visual models from natural language supervision. *Proceedings of the 38th International Conference on Machine Learning*, 8748–8763.

Russell, J. A. (1980). A circumplex model of affect. *Journal of Personality and Social Psychology*, *39*(6), 1161–1178. https://doi.org/10.1037/h0077714

Russell, J. A. (2003). Core affect and the psychological construction of emotion. *Psychological Review*, *110*(1), 145–172. https://doi.org/10.1037/0033-295X.110.1.145

Russell, J. A., & Mehrabian, A. (1977). Evidence for a three-factor theory of emotions. *Journal of Research in Personality*, *11*(3), 273–294. https://doi.org/10.1016/0092-6566(77)90037-X

Tomašević, A., Golino, H., & Christensen, A. (2026). transforEmotion: An open-source R package for emotion analysis using transformer-based generative AI models. *Computational Communication Research*, *8*(2), 1. https://doi.org/10.5117/CCR2026.2.2.TOMA

Traag, V. A., Waltman, L., & Eck, N. J. van. (2019). From louvain to leiden: Guaranteeing well-connected communities. *Scientific Reports*, *9*(1), 5233. https://doi.org/10.1038/s41598-019-41695-z

Wang, W., Sebe, N., & Lepri, B. (2022). *Rethinking the Learning Paradigm for Facial Expression Recognition* (arXiv:2209.15402). arXiv. https://arxiv.org/abs/2209.15402

Zhang, Z., Hamaker, E. L., & Nesselroade, J. R. (2008). Comparisons of four methods for estimating a dynamic factor model. *Structural Equation Modeling: A Multidisciplinary Journal*, *15*(3), 377–402. https://doi.org/doi.org/10.1080/10705510802154281

Appendix A: Perturbation Targets for Historical Revision-v2 Linear Recovery

Appendix A explains why the historical homogeneous revision-v2 block-measured linear panel gives different recovery margins for DynEGA, GraphicalVAR, and GIMME. This linear panel can be written as a graph perturbation problem: each method supplies a population structural signal for the same score panel, and implementation adds finite-sample, estimation, convergence, extraction, and community-detection perturbations.

The argument has three claims. First, idealized DynEGA and GraphicalVAR population graphs preserve the generating block support exactly under the symmetric linear block target. Second, their within-block partial-correlation edges share one ceiling; their difference comes from the signal-to-noise ratio delivered by derivative or VAR innovation filtering. Third, GIMME has a different mathematical status because recovery depends on path search, convergence, extraction, averaging, graph conversion, and completion. The sections below define the target, derive the two population graph maps, state the perturbation margin, and summarize the method comparison. This appendix does not derive recovery for empirical-baseline compositions or CLR panels. The loading-aligned bridge adds between-clip mean structure outside the zero-mean population target derived here.

Table A1: Assumptions behind the Appendix A population results and the prespecified revision challenges.

Result or layer	Main assumptions	Planned departures and interpretation
Exact block support	Mutually independent latent factors, one primary loading per indicator, and independent measurement errors	Cross-loadings, correlated residuals, and correlated shocks test how cross-block edges erode separation
Per-channel filter invariance	The same linear temporal filter is applied to every indicator, with boundary handling fixed	Short records, embedding selection, and gate transitions can change finite-sample filter behavior
Within-block edge formula	Exchangeable loadings and error variances within a block, with positive filtered signal variance	Loading and variance jitter perturb edge equality while preserving the ideal support target

Result or layer	Main assumptions	Planned departures and interpretation
Connected-component recovery	The weakest population within-block edge exceeds the total graph perturbation	Regularization, sampling error, estimation failure, and community detection contribute to the perturbation
GIMME recovery decomposition	A usable contemporaneous graph can be extracted and partitioned	Convergence, timeout, extraction, symmetrization, and completion are separate parts of the pipeline estimand

A.1 Linear Block Target

Consider the population target for the historical homogeneous revision-v2 linear benchmark, with m latent dimensions, k observed indicators per dimension, and $p = mk$ observed score channels. Let $B_1, \dots, B_m$ denote the true indicator blocks. For indicator $j \in B_f$, use the equal-loading, equal-error measurement model

$$Y_j(t) = \lambda Z_f(t) + \varepsilon_j(t), \qquad Z_f(t) = a_f(t) X_f(t),$$

where $Z_f(t)$ is the activity-scaled latent oscillator for dimension f, $\lambda > 0$, and $\varepsilon_j(t)$ is measurement error with variance $\psi = s_\varepsilon^2$. Measurement errors are independent across indicators and time in this target, so $\mathrm{Cov}(\varepsilon_j(t), \varepsilon_\ell(s)) = 0$ whenever $j \neq \ell$ or $t \neq s$. The latent processes Z_f are zero-mean and mutually independent in this simplified population object. Activity gating makes Z_f nonstationary by design, so the variances used in this appendix are time-averaged second moments over the analyzed window. Loading jitter, item-level variance jitter, switching schedules, initialization transients, finite-sample activity imbalance, and estimator behavior are treated as perturbations around this symmetric target.

For a method readout r, write the fitted graph as

$$\widehat{\mathbf{W}}^{(r)} = \mathbf{W}_*^{(r)} + \mathbf{E}^{(r)}.$$

Here $\mathbf{W}_*^{(r)}$ is the population structural matrix induced by the method readout, and $\mathbf{E}^{(r)}$ collects finite-sample variation, derivative estimation, model estimation, regularization, convergence behavior, extraction

errors, and community-detection effects. This notation keeps the comparison focused on two quantities: the population signal available to the method and the perturbation added by the implemented pipeline.

A.2 Filtered Panels and Two Graph Readouts

The derivation uses two population graph maps for a per-channel filtered block panel. DynEGA estimates local derivatives of every channel, and a lag difference is a simple analytic example of the same channelwise operation. GraphicalVAR is handled separately in A.3 because its contemporaneous innovations come from a multivariate VAR projection rather than from an identical filter applied to each channel.

Let L denote a linear filter applied to each channel separately. Applying L to the measurement model for $j \in B_f$ gives

$$(LY_j)(t) = \lambda\,(LZ_f)(t) + (L\varepsilon_j)(t),$$

so the filtered panel keeps the one-factor block structure. Write $V_{L,f} = \mathrm{Var}(LZ_f)$ for the filtered common-signal variance and $\psi_L = \mathrm{Var}(L\varepsilon_j)$ for the filtered noise variance. Because L acts on each channel separately, filtered errors stay independent across channels, and the within-block covariance matrix of the filtered channels is

$$\Sigma_{L,f} = \lambda^2 V_{L,f}\,\mathbf{1}_k\mathbf{1}_k^\top + \psi_L I_k, \qquad \theta_{L,f} = \frac{\lambda^2 V_{L,f}}{\psi_L},$$

with zero cross-block covariance. The filtered signal-to-noise ratio $\theta_{L,f}$ is the only quantity through which the filter enters the population graph. Filtered errors can be serially correlated; the population readouts below use only the contemporaneous covariance across channels, and serial dependence is absorbed into the estimation perturbation in A.4.

The filtered panel admits two graph readouts. The marginal readout uses correlations directly. For two distinct indicators $j, \ell \in B_f$,

$$w_f^M(L) = \left|\mathrm{Cor}(LY_j, LY_\ell)\right| = \frac{\theta_{L,f}}{1+\theta_{L,f}}.$$

The partial readout conditions each pair on the remaining channels. Using the Sherman-Morrison identity,

$$\Sigma_{L,f}^{-1} = \psi_L^{-1}\left[I_k - \frac{\theta_{L,f}}{1+k\theta_{L,f}}\mathbf{1}_k\mathbf{1}_k^\top\right],$$

and the absolute partial correlation between two indicators in the same block is

$$w_f^P(L) = \frac{\theta_{L,f}}{1+(k-1)\theta_{L,f}}.$$

Because the filtered precision matrix is block-diagonal, cross-block partial correlations are exactly zero. These marginal and partial readouts therefore preserve the generating block support without error for the per-channel filtered population object, and the population graph has block-clique form for any per-channel filter,

$$\mathbf{W}_* = \text{blockdiag}\left(w_1(J_k - I_k), \ldots, w_m(J_k - I_k)\right), \qquad w_f \in \{w_f^M(L),\, w_f^P(L)\}.$$

The two readouts differ in how much within-block signal they keep. For the same signal-to-noise ratio θ,

$$\frac{w^P(\theta)}{w^M(\theta)} = \frac{1+\theta}{1+(k-1)\theta},$$

so $w^P(\theta) < w^M(\theta)$ whenever $k > 2$ and $\theta > 0$. As $\theta \to \infty$,

$$w^P(\theta) \to \frac{1}{k-1}, \qquad w^M(\theta) \to 1.$$

The partial readout compresses an arbitrarily strong common-source signal toward a ceiling set by block size alone: with four indicators per dimension, no within-block partial-correlation edge can exceed 1/3. Both readout maps are increasing in θ, so filter and readout separate cleanly. The filter sets $\theta_{L,f}$, and the readout maps $\theta_{L,f}$ to the edge weight supplied to community detection.

Figure A1 compares the marginal and partial maps for the matched grid's four indicators per dimension. The marginal map is a pre-conditioning benchmark; neither implemented pipeline uses it. The vertical gap between the curves shows how much compression the partial map applies to the common-source signal. The shaded band marks the $\lambda^2/s_\varepsilon^2$ span of the matched measurement grid, so the simulated loading and error conditions place $\theta_{L,f}$ inside the band up to the filtered common-signal variance $V_{L,f}$. Across that span, the marginal curve rises from mid-range values toward 1. The partial curve is already near its 1/3 ceiling: strong

measurement conditions widen the common-source signal margin but cannot widen the partial-correlation edge beyond the ceiling.




Figure A1: Population within-block edge weight as a function of the filtered signal-to-noise ratio for the marginal and partial readouts with four indicators per dimension. The dotted line marks the partial-readout ceiling $1/(k-1) = 1/3$. The shaded band spans the loading-to-error-variance ratios of the matched simulation grid; the filtered common-signal variance multiplies the signal-to-noise ratio within this band. Higher edge weight means more within-block signal margin before estimation perturbations.

A.3 Method-Specific Filters and Signal-to-Noise Ratios

The implemented pipelines are specific readout combinations. DynEGA estimates generalized local linear approximation (GLLA) derivatives of each score channel over a time-delay embedding window and then estimates a regularized partial-correlation network (EBICglasso) on the derivative panel. The implementation uses one observation interval as the GLLA `delta` and retains the generator's physical $dt = 0.4$ in separate horizon metadata. Conversion to physical-time derivatives applies the same positive scale factor to every channel and therefore leaves the derivative correlation readout unchanged. DynEGA's population object is the partial readout of a per-channel derivative filter, $w_f^P(L_{\mathrm{GLLA}})$. A lag-h difference, $\Delta_h Y_j(t) = Y_j(t+h) - Y_j(t)$, gives a transparent analytic stand-in for that filter, with

$$\theta_f^{\Delta} = \frac{\lambda^2 \operatorname{Var}(\Delta_h Z_f)}{2\psi},$$

because independent measurement errors contribute 2ψ to the variance of every differenced channel. Both

the lag difference and GLLA derivative estimation operate channel by channel. For the smooth oscillator trajectories generated here, the GLLA filter improves on this stand-in: it averages frame-level measurement noise over the embedding window while tracking the common latent change signal, which supports a high filtered signal-to-noise ratio.

GraphicalVAR reads partial correlations from the contemporaneous innovations of a lag-1 vector autoregression, so its population object is the partial readout of a multivariate VAR innovation projection, $w_f^P(L_{\mathrm{VAR}})$. For the population lag-1 fit of the symmetric block model, the implied coefficient matrix is proportional to $\mathbf{1}_k\mathbf{1}_k^\top$ within each block, and the innovation covariance retains the one-factor-plus-diagonal form. The compression map of A.2 therefore applies at the innovation scale under this symmetric target. The VAR projection also removes the predictable part of the common signal by construction: the simulated oscillator trajectories are strongly autocorrelated, so the lagged panel explains much of the common variance, while the serially independent measurement error passes into the innovations. The innovation readout therefore tends to enter the shared compression map with a smaller signal-to-noise ratio than a derivative filter applied to the same panel.

The population comparison between DynEGA and GraphicalVAR then has a precise form. Both population readouts supply partial-correlation edges to community detection, so both within-block edges are capped at $1/(k-1)$ and the generating block support is preserved in both population objects under the symmetric target. The population difference is where the derivative and innovation signal-to-noise ratios θ_{GLLA} and θ_{VAR} place each edge below that shared ceiling. The remaining differences are pipeline perturbations, which A.4 collects in a single margin.

A.4 Shared Perturbation Margin

Let a method's population graph have block-clique form

$$\mathbf{W}_*^{(r)} = \mathrm{blockdiag}\left(w_1^{(r)}(J_k - I_k), \ldots, w_m^{(r)}(J_k - I_k)\right),$$

where edge weights are on the nonnegative scale supplied to community detection and all m blocks share the same size k. For DynEGA and GraphicalVAR, $w_f^{(r)} = w_f^P(L_r)$ with the method-specific filter from A.3. Suppose every off-diagonal edge is estimated within δ_r of its readout-specific population value:

$$\max_{j\neq\ell}\left|\widehat{W}_{j\ell}^{(r)} - W_{*,j\ell}^{(r)}\right| \leq \delta_r.$$

For any node $j \in B_f$, the estimated total connection to its true block is at least

$$(k-1)(w_f^{(r)} - \delta_r),$$

whereas its estimated total connection to any wrong block is at most

$$k\delta_r.$$

Thus each node has stronger total connection to its true block than to any wrong block whenever

$$(k-1)(w_{\min}^{(r)} - \delta_r) > k\delta_r,$$

or equivalently

$$\delta_r < \frac{k-1}{2k-1} w_{\min}^{(r)}.$$

For the matched grid with $k = 4$, the sufficient node-level block-preference and threshold-separation condition is

$$\delta_r < \frac{3}{7} w_{\min}^{(r)}.$$

This margin is not a guarantee that Louvain, Leiden, or Walktrap recover the blocks, because exact recovery depends on the implemented community-detection algorithm. The bound has a narrower consequence. Because $\frac{k-1}{2k-1} < \frac{1}{2}$, the condition forces every estimated cross-block edge below every estimated within-block edge, so any threshold $\tau \in (\delta_r,\, w_{\min}^{(r)} - \delta_r)$ deletes all cross-block edges, keeps each block a connected clique, and reproduces the generating blocks exactly as the connected components of the thresholded graph.

The margin treats perturbation as symmetric noise on every edge, which makes δ_r a worst-case envelope. Regularized estimation acts asymmetrically: glasso shrinkage lowers within-block edges, which reduces $w_{\min}^{(r)}$, and sets weak cross-block edges to zero, which supports block separation.

The two population partial-readout pipelines share the same ceiling. DynEGA and GraphicalVAR supply partial-correlation edges to community detection, so $w_{\min}^{(r)} \leq 1/(k-1)$ for both pipelines, and with $k = 4$ the

sufficient perturbation margin approaches at most

$$\delta_r < \frac{3}{7} \cdot \frac{1}{3} = \frac{1}{7}$$

in the high-signal limit. The population comparison therefore reduces to the two quantities identified in A.3: how close each filtered signal-to-noise ratio keeps $w_{\min}^{(r)}$ to the shared ceiling, and how large each pipeline's realized perturbation δ_r is. The observed recovery ordering is consistent with the derivative filter preserving more within-block signal than the innovation filter. The full graphical vector-autoregression fit also adds larger estimation and timeout perturbations.

The margin also identifies which blocks are fragile in each scenario family. Activity gating enters the filtered signal directly: $V_{L,f}$ is the time-averaged variance of the filtered activity-scaled process, so a dimension held at background gain contributes a small $\theta_{L,f}$ and a weak within-block edge. In the single-dominance families, background dimensions run at gains of 0.05–0.08 against active gains of 0.35–1.25 (Appendix E), so $w_{\min}^{(r)}$ is set by the background blocks, and in the low-expression family every dimension sits near background activity. The margin therefore predicts the scenario-family ordering observed in Figure 5 for DynEGA and GraphicalVAR: recovery is hardest where the activity schedule holds the weakest block's signal lowest. For GIMME, the same activity envelope is an expected stressor, but its effect is mediated by path search, convergence, extraction, averaging, graph conversion, and completion.

A.5 GIMME as an Indirect Graph-Conversion Readout

The implemented GIMME comparator has a different mathematical status. Its readout can be summarized as

$$\widehat{\mathbf{W}}^{G} = \Pi\left(\frac{1}{V}\sum_{i=1}^{V}\widehat{\Psi}_i\right),$$

where $\widehat{\Psi}_i$ is the clip-specific contemporaneous structure extracted from GIMME for clip i, V is the number of clips, and $\Pi(\cdot)$ denotes conversion to the undirected graph supplied to community detection. This readout depends on path search, clip-level model selection, convergence, extraction, averaging, and graph conversion. We therefore summarize GIMME as an indirect graph-conversion pipeline without a closed-form block edge w_f^G.

Status-inclusive recovery also includes completion. For any pipeline,

$$\Pr(\text{hit}) = \Pr(\text{usable graph})\,\Pr(\text{hit} \mid \text{usable graph}).$$

The reported feasibility tables make this decomposition concrete. DynEGA returned usable graphs for every broad-grid and matched-grid row, so its status-inclusive and conditional hit rates coincide at 95.3%. GraphicalVAR completed 20,872 of 21,600 matched-grid structure fits (62,616 of 64,800 readout rows), so its 80.3% status-inclusive hit rate corresponds to a conditional hit rate of about 83% among usable readouts. GIMME completed 15,294 of 21,600 structure fits (45,882 of 64,800 readout rows), so its 25.9% status-inclusive hit rate corresponds to a conditional hit rate of about 37%. The decomposition separates GIMME's two losses: many fits return no usable graph, and partition quality after a usable graph remains well below the other pipelines.

A.6 Method-Comparison Summary

Table A2: Population signal and perturbation sources for the compared recovery pipelines under the simplified LOMM block target.

Pipeline	Population signal	Main perturbation	Expected implication
DynEGA	$w^P(\theta_{\text{GLLA}})$: partial readout of GLLA derivatives	Derivative estimation, embedding selection, glasso regularization, finite N, T, community detection	Derivative filter keeps the filtered signal near the shared ceiling
GraphicalVAR	$w^P(\theta_{\text{VAR}})$: partial readout of VAR innovations	VAR estimation, regularization, innovation-projection attenuation, timeouts	Population VAR innovation readout preserves block support under the symmetric block target
GIMME	No closed-form block signal for the implemented readout	Path search, clip-level fitting, extraction, averaging, timeouts	Indirect feasibility-stress comparator

Appendix B: Empirical Realism Numeric Summary

Table A3: Numeric summary for the historical revision-v2 empirical-realism checks. The selected candidate uses a row-wise softmax link with temperature 1.00 and no channel intercepts. Empirical IQR is the scaling denominator for the discrepancy components. Max discrepancy is the larger of the scaled median difference and scaled Wasserstein distance; lower values indicate closer empirical-simulated agreement. Status uses the pass, partial, and fail thresholds defined in the main text. The table predates the paired B/S/G adoption analysis and does not define the current public profile.

Readout	Metric	Empirical median	LOMM median	Empirical IQR	Scaled median diff.	Scaled Wasserstein	Max discrepancy	Status
Channels	Channel IQR	0.020	0.064	0.058	0.760	1.058	1.058	Fail
Channels	Derivative IQR	0.014	0.013	0.037	0.007	0.230	0.230	Pass
Channels	Lag-1 ACF	0.521	0.624	0.312	0.331	0.277	0.331	Partial
Channels	Run-length entropy	0.785	0.746	0.132	0.296	0.286	0.296	Pass
Channels	Spectral entropy	0.755	0.685	0.169	0.416	0.500	0.500	Partial
Channels	Effective rank	5.114	5.959	1.347	0.627	0.543	0.627	Partial
Recovered community-score summaries	Channel IQR	0.247	0.832	0.419	1.398	1.481	1.481	Fail
Recovered community-score summaries	Derivative IQR	0.159	0.294	0.258	0.523	0.505	0.523	Partial
Recovered community-score summaries	Lag-1 ACF	0.540	0.745	0.274	0.747	0.564	0.747	Partial
Recovered community-score summaries	Run-length entropy	0.785	0.756	0.132	0.217	0.216	0.217	Pass
Recovered community-score summaries	Spectral entropy	0.751	0.637	0.167	0.686	0.688	0.688	Partial
Recovered community-score summaries	Effective rank	2.371	2.803	0.569	0.758	0.766	0.766	Partial

Appendix C: Conditional Trajectory-Recovery Diagnostics

Table A4: Marginal matched trajectory-recovery diagnostics in the final matched four-indicator grid. Rows use method-readout rows with recovered score summaries and exclude failed or timed-out fits because trajectory summaries exist only after a usable recovered structure is available. Higher trajectory r and lower trajectory NRMSE indicate closer recovery of the generating latent trajectories. Scenario-family rows describe generated activity-and-dynamics regimes, not empirical affect-process categories.

Factor	Level	Usable score-summary rows	Mean trajectory r	Mean trajectory NRMSE
Method	DynEGA	64800	0.725	0.649
Method	GraphicalVAR	62616	0.717	0.659
Method	GIMME	45882	0.604	0.842
Scenario family	A: low-expression single-dominance	32400	0.396	1.167
Scenario family	B: high-expression single-dominance	31791	0.634	0.972
Scenario family	C: high-expression switching	31800	0.581	0.894
Scenario family	D: high-expression rapid switching	30909	0.716	0.686
Scenario family	E: ranked-persistence	23910	0.985	0.118
Scenario family	F: broad switching-geometry	22488	0.999	0.034
Measurement-error SD	0.125	54771	0.814	0.561
Measurement-error SD	0.25	59181	0.704	0.694
Measurement-error SD	0.5	59346	0.562	0.845
Loading strength	0.4	59466	0.631	0.767
Loading strength	0.6	58428	0.703	0.686
Loading strength	0.8	55404	0.740	0.654

Appendix D: Runtime and Feasibility Accounting

Table A5: Runtime and feasibility accounting for the broad DynEGA grid and the matched four-indicator grid. Structure fits count unique fitted structures. Readout rows count the community-detection readouts analyzed in the method-comparison denominator. For GraphicalVAR and GIMME, Louvain, Leiden, and Walktrap are applied to the same fitted structure.

Method	Scope	Structure fits	Readout rows	Valid fits	Timeout fits	Error fits	Valid rows	Timeout rows	Error rows
DynEGA	Matched four-indicator grid	21600	64800	21600	0	0	64800	0	0
DynEGA	Broad DynEGA grid	518400	518400	518400	0	0	518400	0	0
GIMME	Matched four-indicator grid	21600	64800	15294	4114	2192	45882	12342	6576
GraphicalVAR	Matched four-indicator grid	21600	64800	20872	728	0	62616	2184	0

Appendix E: Supplementary Scenario Parameter Values

The final scenario families use the numeric settings below. The reported final runs fix the quality scale at $Q = 0.75$. The base σ_q vectors in the numeric dynamic-vector table are therefore the final-run innovation vectors, applied as per-step shock standard deviations at the step size used for each series length ($dt = 0.4$ for 100-point series and $dt = 0.25$ for 300-point series). The simulation code also supports configurable reruns with $\sigma_q =$ scenario base $\sigma_q \times (Q/0.75)$.

Codes A–D use asymptotically stable template feedback. Codes E–F use ranked feedback with $\eta_f < 0$ and $\zeta_f > 0$, which produces finite-horizon anti-damped oscillations. Their interpretation is restricted to the reported observation horizons. The prospective empirical realism calibration compares unconstrained and stable negative-ζ grids; it does not alter these checked-in scenario parameters.

Table A6: Scenario schedule and feedback-source settings for the final simulation families.

Code	Family	Source	Switching	Gain	Dwell	Feedback source
A	Low-expression single dominance	Generic	No	0.35 / 0.05	1.00 / 1.00	Template
B	High-expression single dominance	Generic	No	1.00 / 0.08	1.00 / 1.00	Template
C	High-expression switching	Generic	Yes	1.00 / 0.08	0.20 / 0.45	Template
D	High-expression rapid switching	Generic	Yes	1.25 / 0.08	0.03 / 0.10	Template
E	Ranked-persistence	Calibration-inspired	No	1.00 / 0.08	1.00 / 1.00	Ranked
F	Broad switching-geometry	Calibration-inspired	Yes	1.10 / 0.10	0.12 / 0.30	Ranked

Table A7: Numeric dynamic vectors for the final simulation families. Base sigma-q values are the final-run values at Q = 0.75.

Code	Dimensions	eta	zeta	Base sigma-q
A	2D	-0.30; -0.55	-1.70; -1.00	0.06; 0.15
A	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.06; 0.15; 0.23
A	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.06; 0.15; 0.23; 0.33
B	2D	-0.30; -0.55	-1.70; -1.00	0.12; 0.30
B	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.12; 0.30; 0.45
B	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.12; 0.30; 0.45; 0.65
C	2D	-0.30; -0.55	-1.70; -1.00	0.12; 0.30
C	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.12; 0.30; 0.45
C	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.12; 0.30; 0.45; 0.65
D	2D	-0.30; -0.55	-1.70; -1.00	0.15; 0.38
D	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.15; 0.38; 0.56

D	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.15; 0.38; 0.56; 0.81
E	2D	-0.05; -0.10	0.08; 0.10	0.25; 0.25
E	3D	-0.05; -0.10; -0.15	0.08; 0.10; 0.12	0.25; 0.25; 0.25
E	4D	-0.05; -0.10; -0.15; -0.20	0.08; 0.10; 0.12; 0.14	0.25; 0.25; 0.25; 0.25
F	2D	-0.05; -0.10	0.08; 0.10	0.35; 0.35
F	3D	-0.05; -0.10; -0.15	0.08; 0.10; 0.12	0.35; 0.35; 0.35
F	4D	-0.05; -0.10; -0.15; -0.20	0.08; 0.10; 0.12; 0.14	0.35; 0.35; 0.35; 0.35

Table A8: Deterministic stability and finite-horizon growth diagnostics for every reported scenario factor. H[100] = 39.6 and H[300] = 74.75 under the retained time-step rules.

Code	Dimensions	Factor	eta	zeta	Discriminant	Max Re(root)	rho(Phi[.4])	rho(Phi[.25])	g(H[100])	g(H[300])	Regime
A	2D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
A	2D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
A	3D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
A	3D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
A	3D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
A	4D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
A	4D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
A	4D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
A	4D	4	-1.10	-0.30	-4.3100	-0.150	0.9418	0.9632	0.0026	0.0000	Stable oscillatory
B	2D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
B	2D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
B	3D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
B	3D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
B	3D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
B	4D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
B	4D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
B	4D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
B	4D	4	-1.10	-0.30	-4.3100	-0.150	0.9418	0.9632	0.0026	0.0000	Stable oscillatory
C	2D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
C	2D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
C	3D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
C	3D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
C	3D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
C	4D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
C	4D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
C	4D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
C	4D	4	-1.10	-0.30	-4.3100	-0.150	0.9418	0.9632	0.0026	0.0000	Stable oscillatory
D	2D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
D	2D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
D	3D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
D	3D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
D	3D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
D	4D	1	-0.30	-1.70	1.6900	-0.200	0.9231	0.9512	0.0004	0.0000	Stable nonoscillatory
D	4D	2	-0.55	-1.00	-1.2000	-0.500	0.8187	0.8825	0.0000	0.0000	Stable oscillatory
D	4D	3	-0.85	-0.65	-2.9775	-0.325	0.8781	0.9220	0.0000	0.0000	Stable oscillatory
D	4D	4	-1.10	-0.30	-4.3100	-0.150	0.9418	0.9632	0.0026	0.0000	Stable oscillatory
E	2D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
E	2D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory
E	3D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
E	3D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory
E	3D	3	-0.15	0.12	-0.5856	0.060	1.0243	1.0151	10.7618	88.6770	Anti-damped oscillatory
E	4D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
E	4D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory

E	4D	3	-0.15	0.12	-0.5856	0.060	1.0243	1.0151	10.7618	88.6770	Anti-damped oscillatory
E	4D	4	-0.20	0.14	-0.7804	0.070	1.0284	1.0177	15.9906	187.2604	Anti-damped oscillatory
F	2D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
F	2D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory
F	3D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
F	3D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory
F	3D	3	-0.15	0.12	-0.5856	0.060	1.0243	1.0151	10.7618	88.6770	Anti-damped oscillatory
F	4D	1	-0.05	0.08	-0.1936	0.040	1.0161	1.0101	4.8744	19.8857	Anti-damped oscillatory
F	4D	2	-0.10	0.10	-0.3900	0.050	1.0202	1.0126	7.2427	41.9929	Anti-damped oscillatory
F	4D	3	-0.15	0.12	-0.5856	0.060	1.0243	1.0151	10.7618	88.6770	Anti-damped oscillatory
F	4D	4	-0.20	0.14	-0.7804	0.070	1.0284	1.0177	15.9906	187.2604	Anti-damped oscillatory