A Latent Oscillator Measurement Model for Simulating Emotional-Expression Score Dynamics in Video

Aleksandar Tomašević Hudson Golino Alexander P. Christensen

Abstract

Automated vision models turn video into dense time series of model-derived emotional-expression scores. Before these scores are interpreted dynamically, researchers need to know whether analytic methods can separate latent expressive organization from the measurement process that produces the observed channels. We introduce the Latent Oscillator Measurement Model (LOMM), a controlled simulation framework that generates latent oscillator trajectories, gates their activity over time, and maps them through block loadings into noisy score channels. The generator varies latent dimensionality, feedback regime, activity pattern, loading strength, and measurement error. We calibrated LOMM against empirical video-score panels using targets for amplitude dispersion, local movement, temporal persistence, directional-change complexity, spectral complexity, and effective multivariate dimensionality. Empirical realism was evaluated with a softmax-linked bounded score panel, whereas the recovery simulations used pre-link linear block-measurement panels to isolate dimensional recovery under a known measurement structure. The calibrated generator reproduced several local temporal and dimensional features, while retaining an amplitude-dispersion mismatch. We then evaluated dimensional recovery in two designs: a broad DynEGA grid and a matched comparison of DynEGA, GraphicalVAR, and GIMME using common community-detection readouts. DynEGA showed the most consistent dimensional and block recovery and completed the broad grid. GraphicalVAR often recovered the generating dimensionality but was slower and more sensitive to weak measurement conditions. GIMME served as a flexible idiographic comparator with substantial runtime and completion limits in this design. LOMM provides a reusable framework for testing whether dynamic methods recover latent organization, tolerate measurement error, and scale to video-derived behavioral time series before substantive interpretation.

Introduction

Video is increasingly used as a source of intensive behavioral data because it preserves the temporal ordering of visible action and can be analyzed at a resolution that manual frame-by-frame coding cannot sustain. Deep-learning systems can now convert frames or short video segments into dense time series of model-derived emotional-expression scores (S. Li & Deng, 2022; Meng et al., 2017). In a facial-expression recognition task, a model maps each image or segment to category probabilities or continuous scores for labels such as happiness, anger, sadness, fear, surprise, disgust, or neutral expression.

These score streams are valuable because many behavioral questions concern how visible affect unfolds over time. Researchers may ask whether expressive states persist or switch, whether they return after perturbation, and whether many model-output channels reflect a smaller number of expressive dimensions. Such questions arise in psychotherapy, autism assessment, collaborative work, public communication, and social-media video (Halamová et al., 2023; Holiday et al., 2023; Q. Li et al., 2024; Manelis-Baram et al., 2025).

Automated facial-analysis systems now make this kind of work feasible at scale. Datasets such as FER2013 supported deep learning approaches to facial-expression recognition, especially Convolutional Neural Networks (Arriaga et al., 2017; Ezerceli & Eskil, 2022; CNNs; Goodfellow et al., 2013). Most early systems inherited their emotion categories from the training data and focused on fixed classification tasks, commonly returning probabilities for seven categories: anger, disgust, fear, happiness, sadness, surprise, and neutral facial expression (Wang et al., 2022). More recently, CLIP-based and related vision-language models have enabled zero-shot classification with user-specified emotion labels (Foteinopoulou & Patras, 2023; H. Li et al., 2023; Radford et al., 2021; Tomašević et al., 2026), making it possible to represent each video frame as a vector of prompt-defined classifier scores.

The main obstacle is measurement. Emotional-expression scores are trained-model outputs that index visible expressive behavior through a scoring procedure. Facial-expression technologies can be interpreted as tools for emotion recognition or social-interaction analysis, and those interpretations answer different questions (Allison & McKeown, 2023). A separate psychometric question is whether multiple score channels should be treated as variables in their own right or as fallible indicators of lower-dimensional expressive processes (Mehu & Scherer, 2015; Nesselroade et al., 2013; Russell, 2003). Measurement error can alter the structure recovered by dynamic-network methods, so method validation must separate latent temporal organization from the observation process used to measure it (Kankaanpää et al., 2026).

The remaining methodological gap is a controlled generator that jointly manipulates latent expressive dynamics and a multichannel observation process resembling video-derived scores. Oscillator models provide

a language for level, rate of change, damping, and perturbation in intraindividual dynamics (Boker, 2015; Boker & Nesselroade, 2002; Ollero et al., 2025). Network and dimensional-recovery methods can analyze observed intensive series. Researchers also need a simulation framework in which the generating dimensionality, indicator blocks, measurement quality, and dynamic regime are prespecified before recovery methods are interpreted.

This paper introduces the Latent Oscillator Measurement Model (LOMM), a generative simulation model for model-derived emotional-expression score channels. LOMM first generates latent expressive trajectories from second-order oscillator dynamics and then maps those latent processes into classifier-output score channels through an explicit measurement layer. The model lets researchers control latent dimensionality, feedback regime, loading strength, measurement error, and activity pattern before testing whether dynamic methods recover the generating structure.

This study addresses four questions. First, can a calibrated LOMM reproduce selected distributional, temporal, spectral, and multivariate features of empirical video-derived emotional-expression scores? Second, across a broad factorial grid, how accurately and efficiently does DynEGA recover the generating dimensionality and indicator blocks? Third, on the same reduced set of generated panels, how do DynEGA, GraphicalVAR, and GIMME compare when their fitted structures are partitioned with the same community-detection algorithms? Fourth, how do activity regime, loading strength, measurement error, and generating dimensionality alter structural recovery, trajectory-score recovery, and computational feasibility?

These questions require two complementary simulation designs. The empirical realism check uses a softmax-linked bounded score panel so simulated scores can be compared with probability-like empirical classifier outputs. The dimensional-recovery simulations use pre-link linear block-measurement panels so that the recovery target remains the known measurement structure generated by LOMM. A broad DynEGA grid evaluates the focal dimensional-recovery method across the full factorial space, including two-, three-, and four-dimensional generating structures. A matched three-method grid uses a reduced design, including four indicators per latent dimension and 100 time points, so that DynEGA, GraphicalVAR, and GIMME can be applied to the same generated panels with the same downstream community-detection procedures. This split preserves a broad scalability assessment for DynEGA while providing a panel-by-panel comparison of three network-based or network-convertible recovery pipelines. Figure 1 links the empirical calibration, scenario construction, and recovery analyses used to answer these questions.




Figure 1: Visual overview of the LOMM simulation pipeline. Panels A–C show the empirical calibration step and realism targets for model-derived emotional-expression score series. Panel D shows scenario selection through dynamics, activity, and measurement parameters. Panels E–H show the recovery simulation from latent trajectories, through the observation layer and simulated score panels, to the recovery test. The recovery test compares recovered dimensions and indicator blocks with the simulation design.

The Latent Oscillator Measurement Model

LOMM starts from a measurement object: a video produces frame-level classifier-output score channels for visible expression. The simulation treats those channels as fallible indicators of lower-dimensional expressive processes. A short clip can contain low expressivity, brief expressive episodes, gradual recovery, persistent activation, or alternation between expressive regimes. The latent representation therefore needs to describe level, rate of change, return toward equilibrium, overshoot, damping, and perturbation, concepts that are central to affective-dynamics research (Hollenstein, 2007; Houben et al., 2015; Kuppens & Verduyn, 2017).

Oscillator models provide a compact language for those features. Prior work has used second-order oscillator representations to describe intraindividual dynamics in which a current level and its rate of change jointly determine subsequent movement (Boker, 2015; Boker & Nesselroade, 2002; Ollero et al., 2025). LOMM uses the same state representation for multivariate simulation and measurement evaluation. It combines three layers: a latent oscillator layer that generates expressive trajectories, an activity layer that controls which latent dimension is expressed over time, and a block measurement layer adapted from direct autoregressive factor-score modeling (H. Golino et al., 2022; Nesselroade et al., 2013).

The latent layer treats each expressive dimension as a continuous-time second-order state process advanced in discrete simulation steps. The implemented process is

$$\frac{\mathrm{d}}{\mathrm{d}t}\begin{bmatrix} x_{if}(t) \\ v_{if}(t) \end{bmatrix} = \begin{bmatrix} 0 & 1 \\ \eta_f & \zeta_f \end{bmatrix}\begin{bmatrix} x_{if}(t) \\ v_{if}(t) \end{bmatrix} + \begin{bmatrix} 0 \\ q_{if,t} \end{bmatrix}, \qquad q_{if,t} \sim \mathcal{N}(0, \sigma_{qf}^2), \tag{1}$$

In Equation 1, i indexes videos, f indexes latent expressive dimensions, t indexes continuous time, and the simulation advances the process with step size dt. The state variable $x_{if}(t)$ is the latent level of dimension f for video i, and $v_{if}(t) = \dot{x}_{if}(t)$ is its instantaneous rate of change. The parameter η_f is position feedback, ζ_f is velocity feedback, $q_{if,t}$ is the stepwise Gaussian acceleration input used at each integration step, and σ_{qf} is the standard deviation of that input. Equivalently, within a simulation step, the acceleration has the form $\ddot{x}_{if}(t) = \eta_f x_{if}(t) + \zeta_f \dot{x}_{if}(t) + q_{if,t}$.

The dynamic parameters set the latent regime. Negative η_f pulls a displaced latent trajectory back toward its equilibrium level, with larger negative values producing stronger restoring acceleration. Negative ζ_f attenuates velocity over time, $\zeta_f = 0$ removes velocity feedback, and positive ζ_f can sustain or amplify ongoing change over the finite interval being simulated. The reported simulations use an uncoupled multivariate system: η_f, ζ_f, and σ_{qf} may vary by factor, and off-diagonal dynamic effects are omitted. The continuous-time linear system is advanced with the exact linear transition matrix and initialized with $x_{if}(1) = 0.25$ and $v_{if}(1) = 2$.

The activity layer turns raw oscillator states into scenario-specific expression episodes. The trajectory passed to the measurement model is $\tilde{x}_{if}(t) = a_{if}(t)x_{if}(t)$, where $a_{if}(t) \geq 0$ is a scenario-defined activity envelope generated from active gains, background gains, and dwell schedules. In single-regime scenarios, one dimension has higher activity across the full sequence; in switching scenarios, the active dimension changes after sampled dwell intervals; and in low-expression scenarios, all dimensions remain close to background activity. The activity envelope changes dominance, switching, and expression strength while preserving the prespecified generating dimensions and indicator memberships.

The measurement layer maps the activity-scaled latent trajectories into simulated score channels. For video i, if each latent dimension has k observed indicators, then the number of observed score channels is $p = mk$ and the linear score vector is

$$\mathbf{z}_{it} = \Lambda_i \, \tilde{\mathbf{x}}_{it} + \varepsilon_{it}, \qquad \varepsilon_{it} \sim \mathcal{N}(\mathbf{0}, \Sigma_i). \tag{2}$$

In Equation 2, $\mathbf{z}_{it}$ is the p-channel linear score vector, $\tilde{\mathbf{x}}_{it}$ is the m-dimensional activity-scaled latent vector, Λ_i is a $p \times m$ loading matrix, ε_{it} is measurement error, and Σ_i is the error covariance matrix. Each observed

score belongs to one indicator block B_f and loads on exactly one latent dimension: for indicator j in block B_f, $(\Lambda_i)_{jf} = \lambda + u_{ij}$ with baseline loading λ and loading jitter $u_{ij} \sim \text{Unif}(-0.15, 0.15)$; all off-block loadings are zero. The measurement-error covariance matrix is diagonal, $\Sigma_i = \text{diag}(\sigma^2_{\varepsilon,i1}, \ldots, \sigma^2_{\varepsilon,ip})$, with $\sigma^2_{\varepsilon,ij} = s^2_\varepsilon + r_{ij}$ and item-level variance jitter $r_{ij} \sim \text{Unif}(-0.01, 0.01)$. The simulation grid reports s_ε as the measurement-error standard deviation, and s^2_ε enters the covariance matrix before item-level jitter is added on the variance scale.

These observed channels are classifier-output measurements of visible expression. The block model tests whether recovery methods recover a prespecified observation process under controlled loading strength, measurement error, dynamic regime, and activity regime. It leaves semantic label validity and subjective emotional experience outside the evidential scope of the simulation.

For the empirical realism check, the linear score vector is transformed to a bounded observed scale with a row-wise softmax link. If $\mathbf{z}_{it}$ is the pre-link score vector from Equation 2, the retained realism layer uses

$$y_{itj} = \frac{\exp(z_{itj})}{\sum_{\ell=1}^{p} \exp(z_{it\ell})},$$

equivalent to a softmax temperature of 1.00. The empirical realism analysis uses the softmax-linked $\mathbf{y}_{it}$ panel to compare simulated scores with bounded probability-like empirical scores. The dimensional-recovery simulations use the linear $\mathbf{z}_{it}$ score panel. In both uses, generating block membership is defined by the nonzero entries of Λ_i. Neutral can appear as an empirical classifier-output channel, but it is not assigned a source-truth latent factor in the final benchmark unless a neutral block is specified by design.

As an illustrative substantive mapping, a three-factor LOMM could represent approach-affiliation, threat-defense, and orienting-novelty dimensions. Prompt-defined classifier-output channels related to happiness, amusement, trust, or smiling could form an approach-affiliation block. Channels related to anger, fear, disgust, contempt, or anxiety could form a threat-defense block. Channels related to surprise, anticipation, confusion, or attention could form an orienting-novelty block. These labels are examples for simulation design, not validated affect categories in the empirical MAFW panels. The example draws on affect taxonomies that distinguish broad dimensions, discrete expression families, and opponent tendencies (Plutchik, 2001; Russell, 1980, 2003; Russell & Mehrabian, 1977), and it is consistent with facial-expression benchmarks that combine categorical expression labels with dimensional ratings (Kollias et al., 2023; Mehu & Scherer, 2015; Mollahosseini et al., 2019). Alternative affective taxonomies can be encoded by changing the latent block map while keeping the LOMM architecture fixed.

The same three-factor example is shown in Figure 2 to make the role of the latent shock term visible.




Figure 2: Three-factor LOMM example for theory-guided visible expressive dimensions. The left panel shows smooth reference trajectories without dynamic shocks; the right panel shows trajectories generated by the implemented linear oscillator process with factor-specific position feedback, velocity feedback, and innovation variance.

Figure 2 highlights the role of the innovation variance, σ_q^2, in LOMM. The reference panel shows the conceptual latent ordering without dynamic shocks: affiliative expression rises quickly and settles above the threat and orienting trajectories. The simulated oscillator panel retains this ordering while nonzero factor-specific σ_q perturbs each latent process at each time point, producing local peaks, reversals, and irregular fluctuations around the underlying trajectory. After approximately time point 100, affiliative expression (blue) remains the dominant latent tendency, while threat (orange) fluctuates at a moderate level and orienting (green) stays lower with shorter local excursions. Thus, σ_q turns a smooth conceptual model into latent score series that better resemble uneven temporal structure in model-derived visible-expression panels.

Method

The analyses follow the workflow in Figure 1. We first use empirical video-score panels to define selected realism targets for model-derived expression-score series (Panels A–C). We then translate those targets into LOMM scenario conditions (Panel D) and evaluate dimensional-recovery methods on simulated panels whose dimensionality and indicator blocks are specified by the simulation design (Panels E–H).

Empirical Calibration and Realism Targets

Figure 3 illustrates the empirical score-series surface used to motivate the simulation study. MAFW is a large-scale, multimodal, compound affective database for dynamic facial-expression recognition in the wild (Liu et al., 2022). The dataset supplies naturalistic video clips for calibrating selected score-series statistics; it does not validate the classifier-output labels, the scoring model, or the subjective emotional states of the people in the clips. The realism check uses a 100-clip calibration sample scored with the same zero-shot procedure as the illustrated clip.

We used the transforEmotion R package to generate frame-level classifier-output scores from the calibration videos (Tomašević et al., 2026). The scoring call used model key `oai-large`, which maps in the local model registry to `openai/clip-vit-large-patch14`, corresponding to OpenAI CLIP ViT-Large/14. Each sampled video was decoded into frames and scored against the prompt-defined classifier-output channels labeled anger, disgust, fear, happiness, neutral, sadness, surprise, contempt, anxiety, helplessness, and disappointment. These 11 prompt channels follow the MAFW single-label schema and are model outputs rather than frame-level human annotations. Within each clip, short missing runs were interpolated, frames with complete usable scores were retained, and clipped score vectors were renormalized as probability-like outputs. These prompt-defined classifier-output panels provide empirical targets for the LOMM observation layer through their temporal persistence, variability, and co-fluctuation.

The selected-frame score profiles from the same MAFW clip anchor the empirical example (Panel A): different frames receive different values across channels labeled helplessness, fear, disgust, sadness, anxiety, and disappointment. The frame-level trajectories show that the highest mean channels change in bursts with irregular local movement (Panel B). The single-video DynEGA network partitions the same clip's non-neutral classifier-output trajectories (Panel C). This panel is an illustrative readout of model-output channels in one clip; the simulation study later tests recovery under a prespecified generating structure.

The empirical calibration sample was assembled at the clip level from a label-diverse MAFW manifest, with MAFW category labels used for sample diversity rather than validation targets. After interpolation of short missing runs and complete-row filtering, the retained panel contains 100 clips spanning the 11 MAFW single-label categories. Usable clip lengths ranged from 17 to 50 frames, with a median of 36.5 usable frames. These retained frame-score panels define the empirical distributions used for the realism targets, and the short clip lengths bound the interpretation of autocorrelation and spectral summaries.

For the empirical realism check, empirical and simulated panels are summarized at two levels. Observable-channel metrics are computed directly from the classifier-output score series within each clip. Recovered




Figure 3: Single-video empirical score-series illustration from the MAFW dataset. Panel A shows selected-frame classifier-output score profiles from one clip; Panel B shows smoothed frame-level classifier-output trajectories for the highest mean channels; Panel C shows a DynEGA network estimated from the same clip's non-neutral classifier-output trajectories. Scores were generated with transforEmotion using model key `oai-large`, which maps to OpenAI CLIP ViT-Large/14 (`openai/clip-vit-large-patch14`).

community-score summaries are computed after applying pooled DynEGA to the score panel and extracting score summaries for the recovered communities. This second readout is method-dependent descriptive information, not independent evidence that the empirical videos contain the same latent dimensions as the simulation. The observable-channel readout evaluates channel-level amplitude and movement; the recovered community-score readout evaluates the lower-dimensional geometry induced by this DynEGA summarization step.

The primary realism targets summarize dispersion, local movement, temporal structure, and effective multivariate dimensionality. Channel IQR is the interquartile range of a score series, so higher values mean wider score dispersion. Derivative IQR is the interquartile range of first differences, so higher values mean larger frame-to-frame movement. Lag-1 autocorrelation indexes local persistence. Run-length entropy is the entropy of monotonic run lengths in the first-difference sign series, so higher values indicate more varied directional regimes. Spectral entropy is the normalized entropy of the fast-Fourier-transform power distribution, so higher values indicate broader spectral complexity. Effective rank is the entropy-based rank of the clip-level correlation matrix, so higher values indicate more effective multivariate dimensionality in the score panel.

For channel IQR, derivative IQR, lag-1 autocorrelation, run-length entropy, and spectral entropy, the empirical and simulated distributions contain one value for each clip-by-channel series or clip-by-community-summary series. For effective rank, the distributions contain one value for each clip panel. For each metric distribution, we compare empirical and simulated values using a scaled median difference and a scaled one-dimensional Wasserstein distance. Both discrepancies are divided by the empirical interquartile range for that metric distribution, with a standard-deviation fallback when the empirical interquartile range is near zero. The larger discrepancy determines the classification: Pass for scaled discrepancy ≤ 0.33, Partial for scaled discrepancy ≤ 1.00, and Fail for scaled discrepancy > 1.00. Calls use the unrounded discrepancy values. These are construction thresholds, not validation thresholds; they do not validate the scoring model or the prompt labels.

Scenario Selection

Scenario selection links the empirical calibration targets to the simulation design. We group manipulated conditions into three parameter families (Panel D). The dynamics family varies the position feedback, velocity feedback, and innovation variance parameters, η_f, ζ_f, and σ_{qf}. The activity family varies whether one latent expressive dimension dominates across the full sequence, whether dominance switches after sampled dwell intervals, or whether all dimensions remain close to low-expression background activity. The measurement

family varies the block loading matrix Λ_i and measurement-error covariance matrix Σ_i that generate the observed classifier-output score panels.

The scenario set contains six activity-and-dynamics families. Four families are generic score-panel regimes: low-expression single dominance, high-expression single dominance, high-expression switching, and high-expression rapid switching. Two families use the empirical calibration logic more directly: ranked-persistence and broad switching-geometry. Table 1 summarizes the activity envelope and dynamic rules used by each family. Across these families, LOMM varies the latent dimensionality and measurement layer so that the number of observed channels equals the number of latent dimensions times the number of indicators per dimension, $p = mk$. The broad DynEGA grid includes two-, three-, and four-dimensional generating structures, and the matched three-method grid uses two- and three-dimensional generating structures. The final crossed factors, replication counts, and method-specific grid sizes are specified in the dimensional-recovery simulation section below.

Table 1: Activity-and-dynamics scenario families used in the final simulations. Rows vary expression strength, switching, dwell length, feedback pattern, and innovation scale. Dwell values are fractions of the simulated sequence length.

Family	Source	Switching	Active/background gain	Dwell fraction	Dynamic rule
Low-expression single dominance	Generic score-panel regime	No	0.35 / 0.05	1.00 / 1.00	Template feedback; low innovation scale
High-expression single dominance	Generic score-panel regime	No	1.00 / 0.08	1.00 / 1.00	Template feedback; baseline innovation scale
High-expression switching	Generic score-panel regime	Yes	1.00 / 0.08	0.20 / 0.45	Template feedback; baseline innovation scale
High-expression rapid switching	Generic score-panel regime	Yes	1.25 / 0.08	0.03 / 0.10	Template feedback; high innovation scale
Ranked-persistence	Calibration-inspired regime	No	1.00 / 0.08	1.00 / 1.00	Ranked feedback; moderate innovation scale
Broad switching-geometry	Calibration-inspired regime	Yes	1.10 / 0.10	0.12 / 0.30	Ranked feedback; higher innovation scale

Numerical values for feedback and innovation-scale settings are reported in the supplementary scenario-parameter tables.

For each simulated video, LOMM first generates latent trajectories from the scenario-specific dynamic parameters. The activity schedule then scales those trajectories: non-switching scenarios keep one active dimension for the full sequence, rotating the dominant dimension across videos, whereas switching scenarios sample dwell intervals and change the active dimension over time. The measurement layer is applied to the activity-scaled latent trajectories. Measurement error is reported as a standard deviation, with the corresponding

variance entering the diagonal measurement-error covariance before small item-level variance jitter is added. The simulation design evaluates dimensional recovery under controlled combinations of dynamics, activity regimes, and measurement quality.

Dimensional-Recovery Simulation Study

The simulation begins with latent trajectories and the prespecified number of simulated expressive dimensions (Panel E). The LOMM observation layer maps each observed score channel to one latent dimension through the block loading matrix and adds item-level measurement error (Panel F), producing a pre-link simulated score panel (Panel G). The final step is the dimensional-recovery test, where the estimated number of dimensions and item memberships are compared against the generating measurement structure (Panel H).

The method comparison uses a common graph-partitioning target. Each pipeline receives the same simulated score panel, estimates a structure among observed score channels, converts that structure to communities, and compares the resulting partition with the generating indicator blocks. This comparison evaluates recovery of LOMM-generated score blocks, not the validity of classifier labels or method superiority for substantive emotion inference.

We compare Dynamic Exploratory Graph Analysis [DynEGA; H. Golino et al. (2022)] with GraphicalVAR (Epskamp et al., 2018; Epskamp, 2024) and GIMME (Gates & Molenaar, 2012; Lane et al., 2019) because they represent adjacent but distinct approaches to intensive longitudinal structure. DynEGA is the focal dimensional-recovery method: it estimates groups of variables whose changes are coordinated over time. In the present simulation, DynEGA tests direct recovery of the generating score blocks. GraphicalVAR is a dynamic-network comparator that separates lagged temporal relations from contemporaneous partial associations, and its fitted contemporaneous structure is partitioned after estimation. GIMME is an indirect feasibility-stress comparator: it estimates time-series paths for each clip treated as a separate time series, and the resulting contemporaneous structures are aggregated and partitioned. This use of GIMME treats clips as analytic series and should not be read as participant-level idiographic affect modeling.

DynEGA combines time-delay embedding and derivative estimation from dynamical systems with exploratory graph analysis for dimensionality assessment (Boker et al., 2010; H. Golino et al., 2020; H. F. Golino & Epskamp, 2017). We apply DynEGA to the stacked video panel with video identity supplied as the grouping variable. The embedding dimension is selected by minimizing the Total Entropy Fit Index (TEFI) over candidate values (H. Golino et al., 2021), using $n_{\text{embed}} \in \{5, 10, 15, \lfloor T/4 \rfloor, \lfloor T/2 \rfloor\}$ where admissible. The estimated pooled simulated-panel network is then partitioned into communities, which are interpreted

as recovered groups of score channels. The broad DynEGA grid uses Louvain community detection (Blondel et al., 2008) with the expand rule for unidimensional solutions. In the matched three-method grid, community detection is analyzed as a factor with Louvain, Leiden (Traag et al., 2019), and Walktrap (Pons & Latapy, 2005), holding the unidimensional rule at expand.

GraphicalVAR estimates a graphical vector autoregressive model for intensive longitudinal data (Epskamp et al., 2018; Epskamp, 2024). In this framework, the temporal network contains directed lag-1 regression parameters, whereas the contemporaneous network contains partial correlations among residuals at the same time point after lagged effects have been taken into account. In multilevel applications, the model can also distinguish within-person temporal and contemporaneous structure from between-person associations among stationary means. We fit GraphicalVAR to the stacked simulated score panel and use the estimated contemporaneous partial-correlation matrix as the structural matrix for dimensional partitioning, because LOMM recovery targets an undirected grouping of score channels. The diagonal is ignored and the resulting weighted matrix is treated as an undirected graph. Positive edge weights define the graph, with absolute weights used only when no positive edges are available. Louvain, Leiden, and Walktrap are applied to the same fitted contemporaneous structure and are analyzed as the community-detection factor.

GIMME is an automated time-series modeling approach built around unified structural equation modeling and vector autoregressive representations (Gates & Molenaar, 2012; Lane et al., 2019). The algorithm searches for lagged and contemporaneous paths that improve fit across the sample, retains paths that are common to many series, and then allows subgroup-shared or series-specific paths. In this simulation, each video clip is treated as the time series supplied to GIMME. We fit the VAR specification to the video-level score panels, extract the contemporaneous block from the clip-specific Ψ matrices, and average those blocks across clips to obtain a common structural matrix for dimensional partitioning. The diagonal is ignored and the averaged matrix is treated as an undirected graph. As with GraphicalVAR, positive edge weights define the graph, with absolute weights used only when no positive edges are available. Louvain, Leiden, and Walktrap are applied to the same fitted GIMME structure and are analyzed as the community-detection factor.

All three fitted structures are converted to dimensional partitions and evaluated against the prespecified generating structure. DynEGA is evaluated on a broad grid for scalability and on the matched three-method grid; GraphicalVAR and GIMME are evaluated on the matched three-method grid because complete factorial estimation is computationally unstable in this setting. Community-detection algorithm is included as a diagnostic factor in the matched three-method grid; method and simulation design remain the primary organizing variables.

Performance is summarized using dimensional hit rate, assignment accuracy for observed score channels, matched trajectory-recovery correlation, matched trajectory-recovery normalized root mean squared error (NRMSE), runtime, and failure or timeout accounting. Method-readout rows are the denominator for dimensional hit rate and the status counts in Table 2; they include one row per method, generated panel, and community-detection readout. For GraphicalVAR and GIMME, feasibility is also reported as unique structure-fit status counts before the repeated Louvain, Leiden, and Walktrap readouts. Dimensional hit rate is the proportion of method-readout rows in which the method returns the correct number of latent dimensions. Assignment accuracy is computed for readouts with available partitions and asks whether observed score channels are assigned to the correct generating blocks after optimal matching of estimated communities to those blocks. For trajectory-recovery metrics, observed variables are standardized within the full panel and recovered community-score summaries are computed from the first principal component of each estimated block, with row means used when a principal-component score cannot be estimated. Matched trajectory-recovery correlation and NRMSE compare these recovered score summaries with the generating latent trajectories after sign-invariant matching between estimated communities and generating dimensions. These trajectory-recovery diagnostics are computed only when score summaries are available; they are secondary diagnostics rather than status-inclusive method-performance measures. Runtime is recorded for each model fit.

The final simulation uses a split design. The broad DynEGA grid varies the number of videos, series length, latent dimensionality, indicators per dimension, loading strength, and measurement-error standard deviation across 1,296 structural cells with 400 replications, yielding 518,400 DynEGA Louvain/expand method rows. The matched three-method grid uses four indicators per latent dimension, two- and three-dimensional generating structures, two sample sizes, 100 time points, three loading strengths, three measurement-error standard deviations, and all six scenario families. The reported final runs fix the innovation quality scale at $Q = 0.75$, so the scenario base σ_q vectors listed in the supplementary scenario-parameter tables are the final-run innovation vectors. This matched grid contains 216 structural cells with 100 replications. Louvain, Leiden, and Walktrap are included as community-detection levels, yielding 64,800 method-readout rows per method in the matched three-method grid. Timeouts, failed fits, and post-estimation extraction errors are retained in the reporting denominator because they are part of method behavior in applied simulation workflows.

Computational Environment

Final run metadata records R 4.5.1 on Rocky Linux 8.8 (`x86_64-redhat-linux-gnu`), 48 available logical cores, OpenBLAS 0.3.15, and LAPACK 3.9.0. Local inspection of the execution host for this final-results workspace reports dual Intel Xeon Silver 4310 CPUs, 48 logical threads, and 125 GiB RAM; the run artifacts store the operating system, R session, and available-core count but do not store RAM or a separate hostname. Key package versions were EGAnet 2.3.0, graphicalVAR 0.3.4, gimme 10.0, igraph 2.2.1, qgraph 1.9.8, psych 2.5.6, lavaan 0.6-20, dplyr 1.1.4, and ggplot2 4.0.1. Parallel jobs used one BLAS thread per worker. The broad DynEGA grid used 16 workers with one internal DynEGA core per fit, the matched DynEGA community-detection supplement used 32 workers, and the GraphicalVAR and GIMME matched-grid runs each used 24 workers with a 900-second elapsed-time limit per structure fit.

Runtime is elapsed wall-clock time, recorded with `proc.time()[["elapsed"]]` for successful fitted structures and summarized in seconds. For GraphicalVAR and GIMME, the recorded runtime includes the structure fit and post-fit extraction/community-detection readout; the same fitted structure is reused for Louvain, Leiden, and Walktrap, so feasibility accounting separates unique structure-fit status from repeated method-readout rows. Runtime summaries use successful fits, whereas timeout and error rows remain in feasibility and recovery denominators. The runtime results should therefore be read as within-machine feasibility estimates for this simulation workflow rather than hardware-independent speed benchmarks.

Results

Results are organized by the four research questions stated in the Introduction. Figure 4 gives the selected empirical-realism checks, Table 2 and Figure 5 summarize structural recovery, Figure 6 isolates simulated measurement-quality factors, and Figure 7 reports computational feasibility.

Empirical Realism Results

Before evaluating dimensional-recovery methods, we asked whether the calibrated LOMM realism panel reproduced selected distributional, temporal, spectral, and effective-dimensionality signatures of the MAFW-derived classifier-output score panels. Figure 4 summarizes this construction check at two readout levels: the observed score channels and the recovered community-score summaries extracted from the pooled DynEGA solution. The figure is generated from the empirical-realism file `metric_comparison_long.csv`, not from the final dimensional-recovery simulation outputs. This check evaluates selected score-series similarities for simulation construction; it does not assess general empirical realism, scoring-model validity, or emotion-label

validity.




Figure 4: Selected empirical-realism checks for the calibrated LOMM realism panel. Panel A shows pass, partial, and fail classifications for six score-series targets at observed-channel and recovered community-summary readouts. Panel B shows the two discrepancy components separately; dashed reference lines mark the pass threshold of 0.33 and fail threshold of 1.00.

At the observed-channel level, the calibrated realism panel passed the derivative-IQR and run-length entropy checks. Lag-1 autocorrelation, spectral entropy, and effective rank were partial score-series matches because they did not meet the strictest threshold. Channel IQR failed, showing that the simulated observed channels remained more dispersed than the empirical score channels. The softmax-linked panel is used for this realism check; the dimensional-recovery simulations use the linear block-measurement score panels described in the model section.

The recovered community-score-summary readout showed the same main boundary with a stronger amplitude mismatch. The community-score Channel IQR median was 0.832 in LOMM and 0.247 in the empirical panels, with a maximum scaled discrepancy of 1.481. This identifies amplitude dispersion as the main calibration boundary. Taken together, the selected realism checks support scenario construction for method testing;

they do not establish empirical validity for the linear recovery panels.

Simulation Results

The recovery analysis separates scalability, direct method comparison, simulated measurement-quality sensitivity, and computational feasibility. DynEGA was evaluated on the broad Louvain/expand grid and on the matched four-indicator design shared with GraphicalVAR and GIMME. The matched comparison aggregates across Louvain, Leiden, and Walktrap readouts and treats community detection as a diagnostic factor. Table 2 summarizes dimensional recovery, status counts, assignment accuracy, and successful-fit runtime by method.

Table 2: Overall method behavior in the final matched four-indicator grid, aggregated across Louvain, Leiden, and Walktrap readouts. Rows are method-community-detection readout rows. Hit rate is recovery of the generating number of latent dimensions using all readout rows as the denominator; Assignment is optimal block-assignment accuracy for readouts with available partitions. Median runtime is computed over successful fitted structures.

Method	Total rows	Valid rows	Timeouts	Errors	Hit (%)	Assignment (%)	Median runtime (s)
DynEGA	64800	64800	0	0	95.3	96.0	2.61
GraphicalVAR	64800	62616	2184	0	80.3	90.4	86.10
GIMME	64800	45882	12342	6576	25.9	67.2	280.50




Figure 5: Dimensional hit rate across the final matched four-indicator method-comparison conditions. Lines show methods and vertical intervals show cluster-bootstrap 95% confidence intervals, resampling generated panels while retaining their community-detection readouts. Condition codes A–F refer to the simulated score-panel regimes in Table 1. Hit rates are status-inclusive and aggregated across Louvain, Leiden, and Walktrap readouts.

DynEGA was the only method evaluated on the broad grid and completed all 518,400 Louvain/expand rows. On that grid, it recovered the generating number of dimensions in 93.7% of rows and assigned observed classifier-output channels to the generating blocks with 95.2% accuracy. Table 2 reports status-inclusive method-readout rows after community-detection readouts. Unique structure-fit feasibility counts are reported in the Computational Feasibility section and Appendix D. Aggregating across Louvain, Leiden, and Walktrap, DynEGA recovered the generating number of dimensions in 95.3% of matched-grid rows, GraphicalVAR in 80.3%, and GIMME in 25.9%. Assignment accuracy followed the same ordering among readouts with available partitions: 96.0% for DynEGA, 90.4% for GraphicalVAR, and 67.2% for GIMME.

Figure 5 shows the matched-grid scenario pattern. DynEGA retained the strongest recovery profile across the simulated score-panel regimes. GraphicalVAR recovered the generating dimensionality in many ranked-persistence and broad-switching-geometry conditions when the structure fit completed, while recovery dropped in the low-expression single-dominance condition. GIMME showed the lowest status-inclusive recovery because many fits timed out or produced no usable contemporaneous structure for partitioning.

Because method and generated scenario family dominated dimensional hit rate, Figure 6 isolates the simulated measurement-quality factors that directly alter the observed score panels. The descriptive row-level factor screen showed the same ordering: method and scenario family had the largest associations with dimensional hit rate, measurement-error standard deviation also mattered, loading strength had a smaller association, and community detection contributed essentially no variation. These effect-size summaries are descriptive because community-detection readouts from the same fitted structure are repeated in the row-level data.




Figure 6: Dimensional hit rate stratified by measurement-error standard deviation and loading strength in the final matched four-indicator grid. Columns show loading strength; lines and symbols show methods. Hit rates are status-inclusive. Error bars are descriptive Wilson intervals computed from method-readout rows in each stratum, aggregated across community-detection readouts.

Figure 6 shows how method differences changed across measurement quality. DynEGA was most stable across the loading-by-error grid, although low-signal scenarios still reduced recovery. GraphicalVAR was more sensitive to the measurement layer: its hit rate was weakest when loadings were low and measurement error was high, and improved when observed channels carried a stronger signal from their generating dimensions.

GIMME remained lower on status-inclusive hit rate across most strata because errors and timeouts occurred before dimensional recovery could be evaluated.

Conditional on obtaining a usable structural readout, trajectory-recovery diagnostics followed the same measurement pattern. Recovery was strongest in the ranked-persistence and broad switching-geometry generated regimes and deteriorated as measurement-error standard deviation increased. These diagnostics are conditional summaries, not status-inclusive method-performance measures; full marginal means are reported in Appendix C.

Computational Feasibility

Computational feasibility was evaluated separately from recovery accuracy because the methods differed in both recovery behavior and scalability across the simulation design. Figure 7 summarizes successful-fit runtime in the matched four-indicator grid, and the text below accounts for broad-grid completion, timeouts, and post-estimation errors. This distinction is important for interpreting the comparator results: GraphicalVAR and GIMME are informative matched-grid comparisons with more limited scalability across the full LOMM grid.




Figure 7: Runtime of the compared methods in the final matched four-indicator grid. The y-axis is shown on a log10 time scale. Points show median runtime for successful fitted structures and intervals show the interquartile range. For GraphicalVAR and GIMME, the same fitted structure is reused across Louvain, Leiden, and Walktrap readouts.

DynEGA was substantially faster than the two model-based comparators in the matched design. Median successful-fit runtime was 2.61 s for DynEGA, compared with 86.1 s for GraphicalVAR and 280.5 s for

GIMME. The broad DynEGA Louvain/expand grid also completed all 518,400 method rows without errors or timeouts. GraphicalVAR completed 20,872 of 21,600 matched-grid structure fits and timed out on 728 fits. GIMME completed 15,294 of 21,600 matched-grid structure fits, timed out on 4,114 fits, and returned post-estimation errors for 2,192 fits. Because GraphicalVAR and GIMME apply three community-detection algorithms to each fitted structure, these feasibility counts refer to unique structure fits before repeated CD readouts; Appendix D reports the fit-level and readout-row accounting side by side. The method-comparison result in this design is clear: DynEGA combined the strongest structural recovery with broad-grid scalability, GraphicalVAR was informative but slower and more condition-sensitive, and GIMME was feasibility-limited.

Discussion

This study introduced LOMM as a controlled generator of multivariate, video-derived emotional-expression score panels and used it to evaluate dynamic dimensional recovery. The findings are organized by the same four questions that guided the analysis. The selected empirical-realism checks reproduced local movement and directional-change texture, partially matched persistence, spectral complexity, and effective multivariate dimensionality, and retained a clear amplitude-dispersion mismatch. DynEGA recovered the generating dimensionality and indicator blocks most consistently across the broad focal-method grid and the matched three-method comparison. Recovery weakened when simulated measurement signal was lower, while GraphicalVAR was informative but condition-sensitive and GIMME was feasibility-limited in the matched design. The trajectory-recovery diagnostics add a conditional result among successful structural readouts rather than a status-inclusive method ranking.

Appendix A frames recovery in the linear panels as a method-specific graph perturbation problem. Under the linear LOMM measurement model, indicators assigned to the same latent oscillator share a common change signal, whereas indicators assigned to different oscillators are independent. The measurement signal within each dimension is rank-one, and the corresponding population dynamic-coordination graph is a disconnected weighted clique. DynEGA receives a direct dynamic-coordination signal, GraphicalVAR receives a partial-correlation signal with reduced within-block margin, and GIMME adds an indirect graph-conversion and completion layer. Recovery becomes more difficult when the method-specific perturbation approaches the weakest within-block signal.

This population structure is closely aligned with DynEGA's target. DynEGA groups variables whose estimated changes are coordinated over time, so the common derivative signal within each LOMM block provides direct evidence for community recovery. Its high dimensional hit rate, high block-assignment accuracy, and

complete broad-grid coverage indicate that this signal usually remained identifiable across the simulated score-panel regimes. The reductions under weak loadings, high measurement error, and low-expression generated regimes identify conditions in which the observed channels no longer carry enough common dynamic variation for reliable partitioning.

Beyond the method comparison, LOMM provides a reusable way to generate multivariate behavioral time series in which latent dynamics, activity regimes, and measurement quality can be manipulated separately. The oscillator layer controls restoring forces, momentum, and stochastic perturbation. The activity layer controls dominance and switching. The measurement layer controls indicator strength and error before scores are placed on their observed scale for empirical-realism checks. This separation supports targeted tests of whether an analysis recovers latent organization or responds primarily to features of the observation system.

GraphicalVAR provides a less direct representation of the generating measurement blocks. In this comparison, community detection is applied to the contemporaneous partial-correlation matrix, which conditions each pairwise association on the remaining channels. Appendix A shows that, in the symmetric block model, partial correlations preserve block support while reducing the within-block signal margin. The observed sensitivity of GraphicalVAR is consistent with this mechanism, especially when loadings are weak or measurement error is high, but the simulation does not isolate partial-correlation attenuation from lag estimation, regularization, finite-sample variation, or timeout behavior. In the matched grid, GraphicalVAR completed most structure fits and had 728 unique structure-fit timeouts, so its main limitation in this comparison was condition sensitivity with some timeout loss.

GIMME has broader native aims than dimensional partitioning. It searches for group, subgroup, and individual lagged and contemporaneous paths, whereas the present evaluation treats video clips as analytic time series, averages clip-specific contemporaneous structures, and applies a separate community-detection step. Its lower status-inclusive hit rate therefore reflects both this indirect GIMME-to-community readout and substantial feasibility costs, including long successful-fit runtimes, timeouts, and post-estimation errors. The result evaluates the implemented clip-level GIMME-to-community pipeline under this design. Person-level idiographic applications of GIMME require separate evidence.

Conditional on a valid structural readout, trajectory-recovery diagnostics showed the largest marginal differences by generated scenario family and measurement-error standard deviation. Ranked-persistence and broad switching-geometry panels produced the closest trajectory summaries, whereas low-expression single-dominance panels were the most difficult. These diagnostics evaluate recovery of simulated latent trajectories after a usable structure has been estimated. They do not evaluate classifier-output validity, emotion-label

validity, or status-inclusive method performance. Full marginal summaries are reported in Appendix C.

The empirical realism check sets the boundary on this interpretation. It evaluates selected statistical resemblance between simulated panels and classifier-output score panels from the MAFW calibration sample; it does not validate the scoring model, the prompt labels, or subjective emotional states in the videos. The calibration used one dataset label schema and one scoring implementation, and the empirical clips were short relative to some simulation regimes. The short empirical clips support calibration of selected local score-series properties, whereas the longer simulation conditions test method behavior under controlled series lengths. The current softmax-linked realism panel reproduces several local temporal and effective-dimensionality features, but the amplitude-dispersion failure shows that the observation layer still leaves marginal score dispersion too high.

Several limitations follow directly from this design. The method-comparison results apply to the linear block-measurement recovery panels, while the softmax-linked panels were used for empirical-realism calibration. The present LOMM implementation uses independent oscillator dimensions, activity-gated block loadings, and diagonal measurement error. These choices make the recovery target interpretable, but they simplify the geometry of visible expressive behavior and the dependence structure of classifier-output score channels. The method comparison covers network-based or network-convertible recovery pipelines, not all dynamic latent-variable approaches. Future work should test richer oscillator coupling, cross-loadings, correlated measurement error, alternative bounded or compositional observation layers, additional scoring systems, and empirical applications where simulation results guide method validation before substantive interpretation of classifier-output score dynamics. The present results support LOMM as a controlled validation environment for selected temporal and dimensional properties. Full generative theories of affect and validation of scoring-model emotion labels require separate evidence.

Declarations

Funding

The authors received no specific funding for this work.

Competing interests

The authors declare that they have no competing interests.

Ethics approval

This study used simulations and secondary, publicly described reference materials. It did not involve new recruitment, intervention, or direct collection of human-participant data by the authors.

Consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The manuscript analyses use simulation outputs and derived classifier-output score summaries generated for this study. The OSF archive will include the version-controlled manuscript repository, final simulation runners, figure-generation scripts, manuscript-facing derived outputs, provenance manifests, and from-scratch rerun instructions for the final simulation grids. Raw MAFW video materials are third-party dataset materials; access to the original videos is governed by the MAFW dataset providers. Derived empirical score summaries needed for the realism check will be included in the archive.

Code availability

All code needed to rerun the final LOMM simulations, rebuild the method-comparison summaries, regenerate the manuscript figures and tables, and render the manuscript will be available in the archived project repository. The repository includes the R simulation runners, empirical realism and method-comparison scripts, manuscript rendering source, claim ledger, and run manifests.

Authors' contributions

Aleksandar Tomasevic contributed conceptualization, formal analysis, methodology, resources, software, validation, visualization, writing the original draft, and reviewing and editing the manuscript. Hudson Golino contributed formal analysis, methodology, resources, software, validation, visualization, writing the original draft, and reviewing and editing the manuscript. Alexander P. Christensen contributed methodology, software, writing the original draft, and reviewing and editing the manuscript.

Open Practices Statement

The study was not preregistered. The OSF archive will include analysis code, simulation code, manuscript source files, generated figure and table inputs, derived empirical score summaries needed for the realism check, and provenance materials for rerunning the final simulations from scratch. Raw MAFW video data are third-party materials governed by the dataset providers.

References

Allison, B., & McKeown, G. (2023). Are facial expression technologies tools for emotion recognition or social interaction analysis, or both? *2023 11th International Conference on Affective Computing and Intelligent Interaction Workshops and Demos (ACIIW)*, 1–8. https://doi.org/10.1109/ACIIW59127.2023.10388163

Arriaga, O., Valdenegro-Toro, M., & Plöger, P. (2017). *Real-time Convolutional Neural Networks for Emotion and Gender Classification* (arXiv:1710.07557). arXiv. https://doi.org/10.48550/arXiv.1710.07557

Blondel, V. D., Guillaume, J.-L., Lambiotte, R., & Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, *2008*(10), P10008. https://doi.org/10.1088/1742-5468/2008/10/P10008

Boker, S. M. (2015). Adaptive equilibrium regulation: A balancing act in two timescales. *Journal for Person-Oriented Research*, *1*(1-2), 99–109. https://doi.org/10.17505/jpor.2015.10

Boker, S. M., Deboek, P. R., Edler, C., & Keel, P. (2010). Generalized local linear approximation of derivatives from time series. In S. M. Chow, E. Ferrer, & F. Hsieh (Eds.), *The notre dame series on quantitative methodology. Statistical methods for modeling human dynamics: An interdisciplinary dialogue* (pp. 161–178). Routledge/Taylor & Francis Group.

Boker, S. M., & Nesselroade, J. R. (2002). A Method for Modeling the Intrinsic Dynamics of Intraindividual Variability: Recovering the Parameters of Simulated Oscillators in Multi-Wave Panel Data. *Multivariate Behavioral Research*, *37*(1), 127–160. https://doi.org/10.1207/S15327906MBR3701_06

Epskamp, S. (2024). *graphicalVAR: Graphical VAR for experience sampling data*. https://CRAN.R-project.org/package=graphicalVAR

Epskamp, S., Waldorp, L. J., Mõttus, R., & Borsboom, D. (2018). The gaussian graphical model in cross-sectional and time-series data. *Multivariate Behavioral Research*, *53*(4), 453–480. https://doi.org/10.1080/00273171.2018.1454823

Ezerceli, Ö., & Eskil, M. T. (2022). Convolutional Neural Network (CNN) Algorithm Based Facial Emotion Recognition (FER) System for FER-2013 Dataset. *2022 International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME)*, 1–6. https://doi.org/10.1109/ICECCME55909.2022.9988371

Foteinopoulou, N. M., & Patras, I. (2023). *EmoCLIP: A Vision-Language Method for Zero-Shot Video Facial Expression Recognition* (arXiv:2310.16640). arXiv. https://doi.org/10.48550/arXiv.2310.16640

Gates, K. M., & Molenaar, P. C. M. (2012). Group search algorithm recovers effective connectivity maps for individuals in homogeneous and heterogeneous samples. *NeuroImage*, *63*(1), 310–319. https://doi.org/10.1016/j.neuroimage.2012.06.026

Golino, H. F., & Epskamp, S. (2017). Exploratory graph analysis: A new approach for estimating the number of dimensions in psychological research. *PloS One*, *12*(6), e0174035. https://doi.org/10.1371/journal.pone.0174035

Golino, H., Christensen, A. P., Moulder, R., Kim, S., & Boker, S. M. (2022). Modeling latent topics in social media using dynamic exploratory graph analysis: The case of the right-wing and left-wing trolls in the 2016 US elections. *Psychometrika*, *87*(1), 156–187.

Golino, H., Moulder, R., Shi, D., Christensen, A. P., Garrido, L. E., Nieto, M. D., Nesselroade, J., Sadana, R., Thiyagarajan, J. A., & Boker, S. M. (2021). Entropy fit indices: New fit measures for assessing the structure and dimensionality of multiple latent variables. *Multivariate Behavioral Research*, *56*(6), 874–902. https://doi.org/10.1080/00273171.2020.1779642

Golino, H., Shi, D., Garrido, L. E., Christensen, A. P., Nieto, M. D., Sadana, R., Thiyagarajan, J. A., & Martinez-Molina, A. (2020). Investigating the performance of exploratory graph analysis and traditional techniques to identify the number of latent factors: A simulation and tutorial. *Psychological Methods*, *25*(3), 292–320. https://doi.org/10.1037/met0000255

Goodfellow, I. J., Erhan, D., Carrier, P. L., Courville, A., Mirza, M., Hamner, B., Cukierski, W., Tang, Y., Thaler, D., Lee, D.-H., Zhou, Y., Ramaiah, C., Feng, F., Li, R., Wang, X., Athanasakis, D., Shawe-Taylor, J., Milakov, M., Park, J., … Bengio, Y. (2013). *Challenges in Representation Learning: A report on three machine learning contests* (arXiv:1307.0414). arXiv. https://doi.org/10.48550/arXiv.1307.0414

Halamová, J., Kanovský, M., Brockington, G., & Strnádelová, B. (2023). Automated facial expression

analysis of participants self-criticising via the two-chair technique: Exploring facial behavioral markers of self-criticism. *Frontiers in Psychology*, *14*. https://doi.org/10.3389/fpsyg.2023.1138916

Holiday, S., Hayes, J. L., Park, H., Lyu, Y., & Zhou, Y. (2023). A multimodal emotion perspective on social media influencer marketing: The effectiveness of influencer emotions, network size, and branding on consumer brand engagement using facial expression and linguistic analysis. *Journal of Interactive Marketing*, *58*(4), 414–439. https://doi.org/10.1177/10949968231171104

Hollenstein, T. (2007). State space grids: Analyzing dynamics across development. *International Journal of Behavioral Development*, *31*(4), 384–396. https://doi.org/10.1177/0165025407077765

Houben, M., Van Den Noortgate, W., & Kuppens, P. (2015). The relation between short-term emotion dynamics and psychological well-being: A meta-analysis. *Psychological Bulletin*, *141*(4), 901–930. https://doi.org/10.1037/a0038822

Kankaanpää, R., Ron, J. de, Hoekstra, R. H. A., & Bork, R. van. (2026). Comparing multiple-indicator approaches to account for measurement error in dynamic networks. *Cognitive Therapy and Research*. https://doi.org/10.1007/s10608-026-10719-0

Kollias, D., Tzirakis, P., Baird, A., Cowen, A., & Zafeiriou, S. (2023). ABAW: Valence-arousal estimation, expression recognition, action unit detection, and emotional reaction intensity estimation challenges. *2023 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, 5889–5898. https://doi.org/10.1109/CVPRW59228.2023.00626

Kuppens, P., & Verduyn, P. (2017). Emotion dynamics. *Current Opinion in Psychology*, *17*, 22–26. https://doi.org/10.1016/j.copsyc.2017.06.004

Lane, S. T., Gates, K. M., Pike, H. K., Beltz, A. M., & Wright, A. G. C. (2019). Uncovering general, shared, and unique temporal patterns in ambulatory assessment data. *Psychological Methods*, *24*(1), 54–69. https://doi.org/10.1037/met0000192

Li, H., Niu, H., Zhu, Z., & Zhao, F. (2023). *CLIPER: A Unified Vision-Language Framework for In-the-Wild Facial Expression Recognition* (arXiv:2303.00193). arXiv. https://doi.org/10.48550/arXiv.2303.00193

Li, Q., Liu, Z., Zhang, Z., Wang, Q., & Ma, M. (2024). Decoding group emotional dynamics in a web-based collaborative environment: A novel framework utilizing multi-person facial expression recognition. *International Journal of Human-Computer Interaction*, 1–19. https://doi.org/10.1080/10447318.2024.2338614

Li, S., & Deng, W. (2022). Deep Facial Expression Recognition: A Survey. *IEEE Transactions on Affective Computing*, *13*(3), 1195–1215. https://doi.org/10.1109/TAFFC.2020.2981446

Liu, Y., Dai, W., Feng, C., Wang, W., Yin, G., Zeng, J., & Shan, S. (2022). MAFW: A large-scale, multi-modal, compound affective database for dynamic facial expression recognition in the wild. *Proceedings of*

the 30th ACM International Conference on Multimedia, 24–32. https://doi.org/10.1145/3503161.3548190

Manelis-Baram, L., Barami, T., Ilan, M., Meiri, G., Menashe, I., Soskin, E., Sofer, C., & Dinstein, I. (2025). Comparing three algorithms of automated facial expression analysis in autistic children: Different sensitivities but consistent proportions. *Molecular Autism*, *16*(1). https://doi.org/10.1186/s13229-025-00685-x

Mehu, M., & Scherer, K. R. (2015). Emotion categories and dimensions in the facial communication of affect: An integrated approach. *Emotion*, *15*(6), 798–811. https://doi.org/10.1037/a0039416

Meng, Z., Liu, P., Cai, J., Han, S., & Tong, Y. (2017). Identity-Aware Convolutional Neural Network for Facial Expression Recognition. *2017 12th IEEE International Conference on Automatic Face & Gesture Recognition (FG 2017)*, 558–565. https://doi.org/10.1109/FG.2017.140

Mollahosseini, A., Hasani, B., & Mahoor, M. H. (2019). AffectNet: A database for facial expression, valence, and arousal computing in the wild. *IEEE Transactions on Affective Computing*, *10*(1), 18–31. https://doi.org/10.1109/TAFFC.2017.2740923

Nesselroade, J. R., McArdle, J. J., Aggen, S. H., & Meyers, J. M. (2013). Dynamic factor analysis models for representing process in multivariate time-series. In *Modeling intraindividual variability with repeated measures data* (pp. 235–265). Psychology Press.

Ollero, M. J. F., Estrada, E., Hunter, M. D., & Cáncer, P. F. (2025). Characterizing affect dynamics with a damped linear oscillator model: Theoretical considerations and recommendations for individual-level applications. *Psychological Methods*, *30*(5), 1095–1112. https://doi.org/10.1037/met0000615

Plutchik, R. (2001). The nature of emotions. *American Scientist*, *89*(4), 344–350. https://doi.org/10.1511/2001.4.344

Pons, P., & Latapy, M. (2005). Computing communities in large networks using random walks. In Pi. Yolum, T. Güngör, F. Gürgen, & C. Özturan (Eds.), *Computer and information sciences - ISCIS 2005* (pp. 284–293). Springer Berlin Heidelberg. https://doi.org/10.1007/11569596_31

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning transferable visual models from natural language supervision. *Proceedings of the 38th International Conference on Machine Learning*, 8748–8763.

Russell, J. A. (1980). A circumplex model of affect. *Journal of Personality and Social Psychology*, *39*(6), 1161–1178. https://doi.org/10.1037/h0077714

Russell, J. A. (2003). Core affect and the psychological construction of emotion. *Psychological Review*, *110*(1), 145–172. https://doi.org/10.1037/0033-295X.110.1.145

Russell, J. A., & Mehrabian, A. (1977). Evidence for a three-factor theory of emotions. *Journal of Research in Personality*, *11*(3), 273–294. https://doi.org/10.1016/0092-6566(77)90037-X

Tomašević, A., Golino, H., & Christensen, A. (2026). transforEmotion: An open-source R package for emotion analysis using transformer-based generative AI models. *Computational Communication Research*, *8*(2), 1. https://doi.org/10.5117/CCR2026.2.2.TOMA

Traag, V. A., Waltman, L., & Eck, N. J. van. (2019). From louvain to leiden: Guaranteeing well-connected communities. *Scientific Reports*, *9*(1), 5233. https://doi.org/10.1038/s41598-019-41695-z

Wang, W., Sebe, N., & Lepri, B. (2022). *Rethinking the Learning Paradigm for Facial Expression Recognition* (arXiv:2209.15402). arXiv. https://arxiv.org/abs/2209.15402

Appendix A: Perturbation Targets for LOMM Recovery

This appendix gives a population argument for the method-comparison results. LOMM recovery can be viewed as a graph perturbation problem. Each pipeline produces a population structural signal for the same block-measured linear score panel, and the fitted readout adds perturbations from finite samples, estimation choices, convergence behavior, extraction, and community detection.

A.1 Linear Block Target

Consider a population LOMM with m latent dimensions, k observed indicators per dimension, and $p = mk$ observed score channels. Let $B_1, \dots, B_m$ denote the true indicator blocks. For indicator $j \in B_f$, use the equal-loading, equal-error measurement model

$$Y_j(t) = \lambda Z_f(t) + \varepsilon_j(t), \qquad Z_f(t) = a_f(t) X_f(t),$$

where $Z_f(t)$ is the activity-scaled latent oscillator for dimension f, $\lambda > 0$, and $\varepsilon_j(t)$ is measurement error with variance $\psi = s_\varepsilon^2$. Measurement errors are independent across indicators and time in this target, so $\mathrm{Cov}(\varepsilon_j(t), \varepsilon_\ell(s)) = 0$ whenever $j \neq \ell$ or $t \neq s$. The centered latent processes Z_f are mutually independent in this simplified population object. Loading jitter, item-level variance jitter, switching schedules, finite-sample activity imbalance, and estimator behavior are treated as perturbations around this symmetric target.

For a method readout r, write the fitted graph as

$$\widehat{\mathbf{W}}^{(r)} = \mathbf{W}_*^{(r)} + \mathbf{E}^{(r)}.$$

Here $\mathbf{W}_*^{(r)}$ is the population structural matrix induced by the method readout, and $\mathbf{E}^{(r)}$ collects finite-sample variation, derivative estimation, model estimation, regularization, convergence behavior, extraction errors, and community-detection effects. This notation keeps the comparison focused on two quantities: the population signal available to the method and the perturbation added by the implemented pipeline.

A.2 DynEGA Dynamic-Coordination Target

DynEGA is aligned with the LOMM recovery target because it groups variables whose changes are coordinated over time. A stylized population target is the lag-h change graph

$$W^{\Delta}_{j\ell} = \left|\mathrm{Cor}(\Delta_h Y_j, \Delta_h Y_\ell)\right|, \qquad \Delta_h Y_j(t) = Y_j(t+h) - Y_j(t).$$

For two distinct indicators $j, \ell \in B_f$,

$$\Delta_h Y_j(t) = \lambda \Delta_h Z_f(t) + \Delta_h \varepsilon_j(t),$$

so

$$\mathrm{Cov}(\Delta_h Y_j, \Delta_h Y_\ell) = \lambda^2 \,\mathrm{Var}(\Delta_h Z_f)$$

and

$$\mathrm{Var}(\Delta_h Y_j) = \lambda^2 \,\mathrm{Var}(\Delta_h Z_f) + 2\psi.$$

The within-block dynamic edge is therefore

$$w^{\Delta}_f = \frac{\theta^{\Delta}_f}{1+\theta^{\Delta}_f}, \qquad \theta^{\Delta}_f = \frac{\lambda^2 \,\mathrm{Var}(\Delta_h Z_f)}{2\psi}.$$

For $j \in B_f$ and $\ell \in B_g$ with $f \neq g$, independence of the latent processes and measurement errors gives zero cross-block covariance. Thus the population dynamic-coordination graph has block-clique form,

$$\mathbf{W}^{\Delta}_{*} = \mathrm{blockdiag}\left(w^{\Delta}_1(J_k - I_k), \ldots, w^{\Delta}_m(J_k - I_k)\right).$$

In this population readout, the LOMM target is a disconnected block graph: indicators in the same latent block share a common change signal, and indicators in different latent blocks have zero population dynamic-coordination edges.

A.3 GraphicalVAR Partial-Correlation Compression

GraphicalVAR is converted into dimensional partitions by applying community detection to the contemporaneous partial-correlation matrix. Within block B_f, let

$$S_f = \mathrm{Var}(Z_f), \qquad \theta_f = \frac{\lambda^2 S_f}{\psi}.$$

The covariance matrix is

$$\Sigma_f = \lambda^2 S_f \mathbf{1}_k \mathbf{1}_k^\top + \psi I_k = \psi(I_k + \theta_f \mathbf{1}_k \mathbf{1}_k^\top).$$

Using the Sherman-Morrison identity,

$$\Sigma_f^{-1} = \psi^{-1}\left[I_k - \frac{\theta_f}{1 + k\theta_f}\mathbf{1}_k \mathbf{1}_k^\top\right].$$

The absolute partial correlation between two indicators in the same block is

$$w_f^P = \frac{\theta_f}{1 + (k-1)\theta_f}.$$

The corresponding marginal common-source edge is

$$w_f^M = \frac{\theta_f}{1 + \theta_f}.$$

For the same signal-to-noise ratio θ,

$$\frac{w^P(\theta)}{w^M(\theta)} = \frac{1 + \theta}{1 + (k-1)\theta}.$$

When $k > 2$ and $\theta > 0$, $w^P(\theta) < w^M(\theta)$. As $\theta \to \infty$,

$$w^P(\theta) \to \frac{1}{k-1}, \qquad w^M(\theta) \to 1.$$

This is the main population difference between a marginal common-source readout of the block signal and GraphicalVAR's partial-correlation readout under the reflective block target. DynEGA's dynamic-coordination target is a marginal common-source readout on changes. The matched grid uses four indicators per latent dimension, so GraphicalVAR's within-block partial-correlation signal approaches a ceiling of 1/3 even as the common-source signal becomes arbitrarily strong. A dynamic-coordination edge can approach

1 in the same signal-dominant limit. GraphicalVAR can preserve the ideal block support, while the partial-correlation representation compresses the common-source signal that defines a reflective measurement block. This gives GraphicalVAR less separation margin before finite-sample, regularization, and model-estimation perturbations are added.

A.4 Shared Perturbation Margin

Let a method's population graph have block-clique form

$$\mathbf{W}_*^{(r)} = \text{blockdiag}\left(w_1^{(r)}(J_k - I_k), \ldots, w_m^{(r)}(J_k - I_k)\right),$$

where edge weights are on the nonnegative scale supplied to community detection. Suppose every off-diagonal edge is estimated within δ_r of its readout-specific population value:

$$\max_{j \neq \ell} \left|\widehat{W}_{j\ell}^{(r)} - W_{*,j\ell}^{(r)}\right| \leq \delta_r.$$

For any node $j \in B_f$, the estimated total connection to its true block is at least

$$(k-1)(w_f^{(r)} - \delta_r),$$

whereas its estimated total connection to any wrong block is at most

$$k\delta_r.$$

Thus each node has stronger total connection to its true block than to any wrong block whenever

$$(k-1)(w_{\min}^{(r)} - \delta_r) > k\delta_r,$$

or equivalently

$$\delta_r < \frac{k-1}{2k-1} w_{\min}^{(r)}.$$

For the matched grid with $k = 4$, the sufficient node-level block-preference condition is

$$\delta_r < \frac{3}{7} w_{\min}^{(r)}.$$

This margin is a block-separation statement, and exact recovery by Louvain, Leiden, Walktrap, DynEGA, GraphicalVAR, or GIMME depends on the implemented estimator and community-detection algorithm. The margin still clarifies the method comparison. For DynEGA, $w_{\min}^{(r)} = w_{\min}^{\Delta}$, which can be large when the shared latent change signal is strong relative to measurement error. For GraphicalVAR, $w_{\min}^{(r)} = w_{\min}^{P}$. With $k = 4$, the high-signal partial-correlation limit is $w^P \to 1/3$, so the corresponding sufficient perturbation margin approaches at most

$$\delta_{\mathrm{GVAR}} < \frac{3}{7} \cdot \frac{1}{3} = \frac{1}{7}.$$

This explains why GraphicalVAR can be more fragile than DynEGA under the LOMM block-measurement target even when both readouts preserve the same ideal block support.

A.5 GIMME as an Indirect Graph-Conversion Readout

The implemented GIMME comparator has a different mathematical status. Its readout can be summarized as

$$\widehat{\mathbf{W}}^G = \Pi\left(\frac{1}{V}\sum_{i=1}^{V} \widehat{\Psi}_i\right),$$

where $\widehat{\Psi}_i$ is the clip-specific contemporaneous structure extracted from GIMME for clip i, V is the number of clips, and $\Pi(\cdot)$ denotes conversion to the undirected graph supplied to community detection. This readout depends on path search, clip-level model selection, convergence, extraction, averaging, and graph conversion. We therefore summarize GIMME as an indirect graph-conversion pipeline without a closed-form block edge w_f^G.

Status-inclusive recovery also includes completion. For any pipeline,

$$\Pr(\text{hit}) = \Pr(\text{usable graph})\,\Pr(\text{hit} \mid \text{usable graph}).$$

DynEGA returned usable graphs for the full broad grid and matched grid in this design. GraphicalVAR had some unique structure-fit timeouts. GIMME had many timeouts and post-estimation extraction errors.

This decomposition explains why GIMME's status-inclusive hit rate reflects both partition quality after a usable graph is returned and the probability that the pipeline returns a usable graph.

A.6 Method-Comparison Summary

Table 3: Population signal and perturbation sources for the compared recovery pipelines under the simplified LOMM block target.

Pipeline	Population signal	Main perturbation	Expected implication
DynEGA	$w^{\Delta} = \theta^{\Delta}/(1+\theta^{\Delta})$	Derivative estimation, embedding, finite N, T, community detection	Directly aligned with LOMM change blocks
GraphicalVAR	$w^{P} = \theta/[1+(k-1)\theta]$	VAR estimation, regularization, partial-correlation compression, timeouts	Preserves block support with reduced signal margin
GIMME	No closed-form block signal for the implemented readout	Path search, clip-level fitting, extraction, averaging, timeouts	Indirect feasibility-stress comparator

Appendix B: Empirical Realism Numeric Summary

Table 4: Numeric summary for the selected empirical-realism checks. The selected candidate uses a row-wise softmax link with temperature 1.00 and no channel intercepts. Empirical IQR is the scaling denominator for the discrepancy components. Max discrepancy is the larger of the scaled median difference and scaled Wasserstein distance; lower values indicate closer empirical-simulated agreement. Status uses the pass, partial, and fail thresholds defined in the main text.

Readout	Metric	Empirical median	LOMM median	Empirical IQR	Scaled median diff.	Scaled Wasserstein	Max discrepancy	Status
Channels	Channel IQR	0.020	0.064	0.058	0.760	1.058	1.058	Fail
Channels	Derivative IQR	0.014	0.013	0.037	0.007	0.230	0.230	Pass
Channels	Lag-1 ACF	0.521	0.624	0.312	0.331	0.277	0.331	Partial
Channels	Run-length entropy	0.785	0.746	0.132	0.296	0.286	0.296	Pass
Channels	Spectral entropy	0.755	0.685	0.169	0.416	0.500	0.500	Partial
Channels	Effective rank	5.114	5.959	1.347	0.627	0.543	0.627	Partial
Recovered community-score summaries	Channel IQR	0.247	0.832	0.419	1.398	1.481	1.481	Fail
Recovered community-score summaries	Derivative IQR	0.159	0.294	0.258	0.523	0.505	0.523	Partial
Recovered community-score summaries	Lag-1 ACF	0.540	0.745	0.274	0.747	0.564	0.747	Partial
Recovered community-score summaries	Run-length entropy	0.785	0.756	0.132	0.217	0.216	0.217	Pass
Recovered community-score summaries	Spectral entropy	0.751	0.637	0.167	0.686	0.688	0.688	Partial
Recovered community-score summaries	Effective rank	2.371	2.803	0.569	0.758	0.766	0.766	Partial

Appendix C: Conditional Trajectory-Recovery Diagnostics

Table 5: Marginal matched trajectory-recovery diagnostics in the final matched four-indicator grid. Rows use method-readout rows with recovered score summaries and exclude failed or timed-out fits because trajectory summaries exist only after a usable recovered structure is available. Higher trajectory r and lower trajectory NRMSE indicate closer recovery of the generating latent trajectories. Scenario-family rows describe generated activity-and-dynamics regimes, not empirical affect-process categories.

Factor	Level	Usable score-summary rows	Mean trajectory r	Mean trajectory NRMSE
Method	DynEGA	64800	0.725	0.649
Method	GraphicalVAR	62616	0.717	0.659
Method	GIMME	45882	0.604	0.842
Scenario family	A: low-expression single-dominance	32400	0.396	1.167
Scenario family	B: high-expression single-dominance	31791	0.634	0.972
Scenario family	C: high-expression switching	31800	0.581	0.894
Scenario family	D: high-expression rapid switching	30909	0.716	0.686
Scenario family	E: ranked-persistence	23910	0.985	0.118
Scenario family	F: broad switching-geometry	22488	0.999	0.034
Measurement-error SD	0.125	54771	0.814	0.561
Measurement-error SD	0.25	59181	0.704	0.694
Measurement-error SD	0.5	59346	0.562	0.845
Loading strength	0.4	59466	0.631	0.767
Loading strength	0.6	58428	0.703	0.686
Loading strength	0.8	55404	0.740	0.654

Appendix D: Runtime and Feasibility Accounting

Table 6: Runtime and feasibility accounting for the broad DynEGA grid and the matched four-indicator grid. Structure fits count unique fitted structures. Readout rows count the community-detection readouts analyzed in the method-comparison denominator. For GraphicalVAR and GIMME, Louvain, Leiden, and Walktrap are applied to the same fitted structure.

Method	Scope	Structure fits	Readout rows	Valid fits	Timeout fits	Error fits	Valid rows	Timeout rows	Error rows
DynEGA	Matched four-indicator grid	21600	64800	21600	0	0	64800	0	0
DynEGA	Broad DynEGA grid	518400	518400	518400	0	0	518400	0	0
GIMME	Matched four-indicator grid	21600	64800	15294	4114	2192	45882	12342	6576
GraphicalVAR	Matched four-indicator grid	21600	64800	20872	728	0	62616	2184	0

Appendix E: Supplementary Scenario Parameter Values

The final scenario families use the numeric settings below. The reported final runs fix the quality scale at $Q = 0.75$, so the base σ_q vectors in the numeric dynamic-vector table are the final-run innovation vectors. The simulation code also supports configurable reruns with σ_q = scenario base $\sigma_q \times (Q/0.75)$.

Table 7: Scenario schedule and feedback-source settings for the final simulation families.

Code	Family	Source	Switching	Gain	Dwell	Feedback source
A	Low-expression single dominance	Generic	No	0.35 / 0.05	1.00 / 1.00	Template
B	High-expression single dominance	Generic	No	1.00 / 0.08	1.00 / 1.00	Template
C	High-expression switching	Generic	Yes	1.00 / 0.08	0.20 / 0.45	Template
D	High-expression rapid switching	Generic	Yes	1.25 / 0.08	0.03 / 0.10	Template
E	Ranked-persistence	Calibration-inspired	No	1.00 / 0.08	1.00 / 1.00	Ranked
F	Broad switching-geometry	Calibration-inspired	Yes	1.10 / 0.10	0.12 / 0.30	Ranked

Table 8: Numeric dynamic vectors for the final simulation families. Base sigma-q values are the final-run values at Q = 0.75.

Code	Dimensions	eta	zeta	Base sigma-q
A	2D	-0.30; -0.55	-1.70; -1.00	0.06; 0.15
A	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.06; 0.15; 0.23
A	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.06; 0.15; 0.23; 0.33
B	2D	-0.30; -0.55	-1.70; -1.00	0.12; 0.30
B	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.12; 0.30; 0.45
B	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.12; 0.30; 0.45; 0.65
C	2D	-0.30; -0.55	-1.70; -1.00	0.12; 0.30
C	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.12; 0.30; 0.45
C	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.12; 0.30; 0.45; 0.65
D	2D	-0.30; -0.55	-1.70; -1.00	0.15; 0.38
D	3D	-0.30; -0.55; -0.85	-1.70; -1.00; -0.65	0.15; 0.38; 0.56
D	4D	-0.30; -0.55; -0.85; -1.10	-1.70; -1.00; -0.65; -0.30	0.15; 0.38; 0.56; 0.81
E	2D	-0.05; -0.10	0.08; 0.10	0.25; 0.25
E	3D	-0.05; -0.10; -0.15	0.08; 0.10; 0.12	0.25; 0.25; 0.25
E	4D	-0.05; -0.10; -0.15; -0.20	0.08; 0.10; 0.12; 0.14	0.25; 0.25; 0.25; 0.25
F	2D	-0.05; -0.10	0.08; 0.10	0.35; 0.35
F	3D	-0.05; -0.10; -0.15	0.08; 0.10; 0.12	0.35; 0.35; 0.35
F	4D	-0.05; -0.10; -0.15; -0.20	0.08; 0.10; 0.12; 0.14	0.35; 0.35; 0.35; 0.35