

New Billing Project

ICP Enquiry (Billing) API Specifications Part 6



Revision History

| Revision | Date | Description | Author |
|----------|--------------|--|--------------|
| 1.0 | Aug 21, 2025 | List of API for IS Billing API | Claudia Fung |
| | Aug 26, 2025 | Add company subsidy API | Claudia Fung |
| 1.1 | Sep 24, 2025 | Add WiFi Egg Travel Pack Info API | Claudia Fung |
| | Sep 26, 2025 | Add Adjustment History Transaction API | Claudia Fung |



CONTENTS

| OBJE | CTIVES | 4 |
|-------------|---|----|
| | NQUIRY (IS BILLING) API SPECIFICATIONS | |
| 1. | Postpaid - Check Local Data Top-up Flag by Account | 4 |
| 2. | Postpaid - Check Bnp Roaming Data Topup Flag Flag | 7 |
| 3. | Postpaid - Check CM Roaming Data Topup FlagFlag | 9 |
| 4. | Postpaid - Check Roaming Data Topup Flag By Account | 11 |
| 5. | Enquire Company Subsidy | 13 |
| 6. | WiFi Egg Travel Pack Information | 17 |
| 7. | Adjustment History | 19 |
| | | |



Objectives

This document is to provide the list of enquiry functions interfaced with IS Billing API (not vendor API) to postpaid services for New Billing Project. Parallel run logic is also included.

ICP Enquiry (IS Billing) API Specifications

1. Postpaid - Check Local Data Top-up Flag by Account

Purpose

To check local data top-up flag by account

Reference: GNV_DATA_ALERT_PKG.CheckSmsTopupFlagByAcct

Interface Details

Production Endpoints: https://tykapi-u.hksmartone.com/icp/custProf/

| System | Endpoint (UAT) | |
|--------|--|--|
| UAT | https://crm-uat.smartone.com/api/custProf | |
| TYK | https://tykapi-u.hksmartone.com/icp/custProf | |

API: /checkSmsTopupFlagByAcct

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOiI2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IjFiYzI4OGIzYzZjMTQxNjFiM2ZiMWUyNGJIMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |



Request Parameters

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| accountNum | String | Account number | | Mandatory |
| requestBy | String | Request By | ОМ | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |

Sample Request

Response Parameters

| Parameter | Data Type | Description | Possible | Remarks |
|---------------|-----------|--|-----------------|---------|
| | | | Value | |
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| status | String | Return valid result | | |
| | | 0 – success | | |
| | | 1 or 2 or 98 or 99 - fail | | |
| statusMessage | String | Status message | | |
| | | Status 0: Success | | |
| | | Status 1: Multiple replies | | |
| | | Status 2: No valid invitation records | | |
| | | Status 98 or 99: System error | | |
| | | | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |



Success response

```
{
    "resultCode": "0",
    "resultMsg": "",
    "status": "0",
    "statusMessage": "Success"
}
```

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```



2. Postpaid - Check Bnp Roaming Data Topup Flag

Purpose

To check postpaid Bnp roaming data topup flag

Reference: GNV_DATA_RG_ALERT_PKG.CheckBnpRoamSmsTopupFlag

Interface Details

Production Endpoints: https://tykapi-u.hksmartone.com/icp/custProf/

| System | Endpoint (UAT) | |
|--------|--|--|
| UAT | https://crm-uat.smartone.com/api/custProf | |
| TYK | https://tykapi-u.hksmartone.com/icp/custProf | |

API: /checkBnpRoamSmsTopupFlag

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOiI2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IJFiYzI4OGIzYzZJMTQxNjFiM2ZiMWUyNGJIMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| accountNum | String | Account number | | Mandatory |
| cat | String | Catalogue | e.g. DROAMCM:GBPT5:215 | Mandatory |
| requestBy | String | Request By | ОМ | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



Response Parameters

| Parameter | Data Type | Description | Possible Value | Remarks |
|---------------|-----------|--|-------------------|---------|
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| status | String | Return valid result | | |
| | | 0 – success | | |
| | | 1 or 2 or 98 or 99 - fail | | |
| statusMessage | String | Status message | | |
| | | Status 0: Success | | |
| | | Status 1: Multiple replies | | |
| | | Status 2: No valid invitation records | | |
| | | Status 98 or 99: System error | | |
| | | | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |

Success response

```
{
    "resultCode": "0",
    "resultMsg": "",
    "status": "0",
    "statusMessage": "Success"
}
```

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```



3. Postpaid - Check CM Roaming Data Topup Flag

Purpose

To check postpaid CM roaming data topup flag

 $Reference: GNV_DATA_RG_ALERT_PKG. CheckRoamSmsTopupFlag2$

Interface Details

Production Endpoints: https://tykapi-u.hksmartone.com/icp/custProf/

| System | Endpoint (UAT) | |
|--------|--|--|
| UAT | nttps://crm-uat.smartone.com/api/custProf | |
| TYK | https://tykapi-u.hksmartone.com/icp/custProf | |

API: /checkRoamSmsTopupFlag2

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOiI2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IjFiYzI4OGIzYzZjMTQxNjFiM2ZiMWUyNGJIMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| accountNum | String | Account number | | Mandatory |
| requestBy | String | Request By | ОМ | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



```
{
    "accountNum": "00008843.00028",
    "requestBy": "OM_Admin",
    "parallelRun": "11"
}
```

Response Parameters

| Parameter | Data Type | Description | Possible | Remarks |
|---------------|-----------|--|-----------------|---------|
| | | | Value | |
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| status | String | Return valid result | | |
| | | 0 – success | | |
| | | 1 or 2 or 98 or 99 - fail | | |
| statusMessage | String | Status message | | |
| | | Status 0: Success | | |
| | | Status 1: Multiple replies | | |
| | | Status 2: No valid invitation records | | |
| | | Status 98 or 99: System error | | |
| | | | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |

Success response

```
{
    "resultCode": "0",
    "resultMsg": "",
    "status": "0",
    "statusMessage": "Success"
}
```

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```



4. Postpaid - Check Roaming Data Topup Flag By Account

Purpose

To check postpaid roaming data topup flag by Account

 $Reference: GNV_DATA_RG_ALERT_PKG. CheckRoamSmsTopupFlagByAcct$

Interface Details

Production Endpoints: https://tykapi-u.hksmartone.com/icp/custProf/

| System | Endpoint (UAT) |
|--------|--|
| UAT | https://crm-uat.smartone.com/api/custProf |
| TYK | https://tykapi-u.hksmartone.com/icp/custProf |

API: /checkRoamSmsTopupFlagByAcct

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOiI2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IjFiYzI4OGIzYzZjMTQxNjFiM2ZiMWUyNGJIMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| accountNum | String | Account number | | Mandatory |
| requestBy | String | Request By | ОМ | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



Response Parameters

| Parameter | Data Type | Description | Possible | Remarks |
|---------------|-----------|--|-----------------|---------|
| | | | Value | |
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| status | String | Return valid result | | |
| | | 0 – success | | |
| | | 1 or 2 or 98 or 99 - fail | | |
| statusMessage | String | Status message | | |
| | | Status 0: Success | | |
| | | Status 1: Multiple replies | | |
| | | Status 2: No valid invitation records | | |
| | | Status 98 or 99: System error | | |
| | | | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |

Success response

```
{
    "resultCode": "0",
    "resultMsg": "",
    "status": "0",
    "statusMessage": "Success"
}
```

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```



5. Enquire Company Subsidy

Purpose

To enquire all company subsidy records under a particular dummy number for Corporate Account

 $Reference: Separate_Bill_Master.findActivateRecord, \ Separate_Bill_Master.findHistoryRecord, Separate_Bill_Master.findRecordByCust$

Interface Details

Production Endpoints: https://tykapi.hksmartone.com/icp/subscription/

| System | Endpoint (UAT) |
|--------|--|
| UAT | https://crm-uat.smartone.com/api/subscription |
| TYK | https://tykapi-u.hksmartone.com/icp/subscription |

API: /getEmployeeSubsidy

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|---|
| Value | eyJvcmciOiI2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IJFiYzI4OGIzYzZJMTQxNJFiM2ZiMWUyNGJIMDAyN2 FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| custNum | String | customer number | | Mandatory |
| subrNum | String | subscriber number | | Mandatory |
| isEmployer | String | The subscriber is employer or employee | Y – employer N - employee | Mandatory |
| recType | String | Subsidy record type – active or history | A – Active H - History | Mandatory |
| endDate | String | Mandatory input subsidy record end date for history | Format: YYYY-MM-DD | Optional |
| parallelRun | String | ParellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



Response Parameters

| Parameter | Data Type | Description | Possible Value | Remarks |
|----------------------------|------------|--|--------------------|---------|
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| subsidy | Json Array | Array for subsidy information | | |
| subsidy -> | String | Employer customer number | | |
| employerCustNum | | | | |
| subsidy -> | String | Employer account number | | |
| employerAccountNum | | | | |
| subsidy -> | String | Employer subscriber number | | |
| employerSubrNum | | | | |
| subsidy -> | String | Employee customer number | | |
| employeeCustNum | | | | |
| subsidy -> | String | Employee account number | | |
| employeeAccountNum | | | | |
| subsidy -> | String | Employee subscriber number | | |
| employeeSubrNum | | | | |
| subsidy -> | String | Start Date | | |
| startDate | | Format: YYYY-MM-DD HH24:MI:SS | | |
| subsidy -> | String | End Date | | |
| endDate | | Format: YYYY-MM-DD HH24:MI:SS | | |
| subsidy -> | String | Subsidy amount | | |
| subsidyAmount | | | | |
| subsidy -> subsidyType | String | Subsidy Type | | |
| subsidy ->remarks | String | Remarks | | |
| subsidy -> | String | Create Date | | |
| createDate | | Format: YYYY-MM-DD HH24:MI:SS | | |
| subsidy ->createBy | String | Create By | | |
| subsidy -> | String | Modified Date | | |
| modifiedDate | | Format: YYYY-MM-DD HH24:MI:SS | | |
| subsidy -> modifiedBy | String | Modified By | | |
| subsidy -> separatebillseq | String | Separate bill sequence only for GNV billing | | |



Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |

Success response

```
"resultCode": "0",
"resultMsg": "",
"subsidy ": [{
         "employerCustNum": "00008843",
         "employerAccountNum": "00008843.00002",
         "employerSubrNum": "60123456",
         "employeeCustNum": "00008843",
         "employeeAccountNum": "00008843.00001",
         "employeeSubrNum": "90123456",
         "startDate": "2024-01-01 13:00:00",
         "endDate": "2025-12-31 13:00:00",
         "subsidyAmount": "150",
         "subsidyType": "F",
         "remarks": "Modification",
         "separateBillSeq": "12345678",
         "createdDate": "2024-01-01 13:00:00",
         "createdBy": "John",
         "modifiedDate": "2024-12-01 13:00:00",
         "modifiedBy": "Nisha"
         "employerCustNum": "00008843",
         "employerAccountNum": "00008843.00002",
         "employerSubrNum": "60123456",
         "employeeCustNum": "00008843",
         "employeeAccountNum": "00008843.00002",
         "employeeSubrNum": "90123457",
         "startDate": "2024-02-01 13:00:00",
         "endDate": "2025-12-31 13:00:00",
         "subsidyAmount": "200",
         "subsidyType": "F",
         "remarks": "Modification",
         "separateBillSeq": "22345678",
         "createdDate": "2024-02-01 13:00:00",
         "createdBy": "John",
         "modifiedDate": "2024-12-01 13:00:00",
         "modifiedBy": "Nisha"
}]
```

```
{
  "resultCode": "-1",
  "resultMsg": "Missing input parameter"
}
```





6. WiFi Egg Travel Pack Information

Purpose

To get WiFi egg travel pack information for postpaid service in New Billing

 $Reference: OM_ROAMING_SIM.wifi_egg_travel_pack_info; gnv_travel_card.get_remaining_buckets$

Interface Details

Production Endpoints: https://tykapi.hksmartone.com/icp/subscription/

| System | Endpoint (UAT) |
|--------|--|
| UAT | https://crm-uat.smartone.com/api/subscription |
| TYK | https://tykapi-u.hksmartone.com/icp/subscription |

API: /wifiEggTravelPackInfo

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOil2NGY2Y2I1ZmFiYzRhYWI4MGNIZDE1NTUiLCJpZCI6IjFiYzI4OGIzYzZjMTQxNjFiM2ZiMWUyNGJIMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| custNum | String | Customer number | | Mandatory |
| acctNum | String | Account number | | Mandatory |
| subrNum | String | Subscriber number | | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



```
{
    "custNum": "00008843.00028",
    "accountNum": "00008843.00028",
    "subrNum": "91234567",
    "parallelRun": "11"
}
```

Response Parameters

| Parameter | Data Type | Description | Possible | Remarks |
|--------------------------|------------|--|-----------------|---------|
| | | | Value | |
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| cardExpiryDate | String | Card Expiry Date | | |
| | | Format: YYYY-MM-DD HH24:MI:SS | | |
| travelCard | Json Array | Travel Card Bucket Information | | |
| travelCard -> bucketName | String | Bucket name of Travel Birdie Zone A Z | TBIRDA | |
| | | | TBIRDZ | |
| travelCard -> remaining | String | Remaining bucket of the travel card | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |

Success response

```
{
    "resultCode": "0",
    "resultMsg": "",
    "cardExpiryDate": "2025-12-30 01:00:00",
    "travelCard": [{
        "bucketName": "TBIRDA",
        "remaining": "35461338"
    }]
}
```

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```



7. Adjustment History

Purpose

To get adjustment history for prepaid service in New Billing System

Reference: GNV table sa_subr_rbadjustment_view

Interface Details

Production Endpoints: https://tykapi.hksmartone.com/icp/NBill/brm/v1/subscription/

| System | Endpoint (UAT) |
|--------|---|
| UAT | https://crm-uat.smartone.com/api/subscription |
| TYK | https://tykapi-u.hksmartone.com/icp/NBill/brm/v1/subscription |

API: /adjustmentHistory

Type: REST

Method: POST

Add Key to HTTP Request Header for TYK API:

| Name | Auth_ID |
|-------|--|
| Value | eyJvcmciOil2NGY2Y2l1ZmFiYzRhYWl4MGNlZDE1NTUiLCJpZCl6ljFiYzl4OGlzYzZjMTQxNjFiM2ZiMWUyNGJlMDAyN2 |
| | FkliwiaCl6Im11cm11cjY0In0= |

| Parameter | Data Type | Description | Possible Value | Remarks |
|-------------|-----------|--|--|-----------|
| accountNum | String | Account number | | Mandatory |
| startDate | String | Start date for adjustment transaction | Format: YYYY-MM-DD | Mandatory |
| endDate | String | End date for adjustment transaction | Format: YYYY-MM-DD | Mandatory |
| parallelRun | String | parellelRun indicator to determine the state of the workflow | Postpaid parallel run - Value of 1st charatcer 0 - existing system 1 - new billing 2 - parallel run in GNV & new billing in OM Prepaid parallel run - Value of 2nd character 0 - existing system 1 - new billing | Mandatory |



Response Parameters

| Parameter | Data Type | Description | Possible Value | Remarks |
|---------------------------------|------------|--|-----------------|---------|
| resultCode | String | Response result | See below table | |
| resultMsg | String | Error description return from IS billing api | | |
| custNum | String | Customer number | | |
| acctNum | String | Account number | | |
| subrNum | String | Subscriber number | | |
| adjustInfo | Json Array | Adjustment transaction (exclude cancel case) | | |
| adjustInfo -> transactionDate | String | Transaction date Format: YYYY-MM-DD HH24:MI:SS | | |
| adjustInfo -> transactionType | String | Transaction type | ADJ | |
| adjustInfo -> transactionRef | String | Ledger reference | | |
| adjustInfo -> transactionText | String | Ledger text | | |
| adjustInfo -> amount | String | Adjusted amount | | |

Result Code

| Result Code | Severity | Description |
|-------------|----------|-------------------------|
| 0 | N/A | Success |
| -1 | N/A | Missing input parameter |



Success response

```
{
    "resultCode": "-1",
    "resultMsg": "Missing input parameter"
}
```