

Lecture 5: Tree

김수경

이화여자대학교 인공지능융합전공 소속

저작권 안내

(주)업스테이지가 제공하는 모든 교육 콘텐츠의 지식재산권은
운영 주체인 (주)업스테이지 또는 해당 저작물의 적법한 관리자에게 귀속되어 있습니다.

콘텐츠 일부 또는 전부를 복사, 복제, 판매, 재판매 공개, 공유 등을 할 수 없습니다.


유출될 경우 지식재산권 침해에 대한 책임을 부담할 수 있습니다.

유출에 해당하여 금지되는 행위의 예시는 다음과 같습니다.

- 콘텐츠를 재가공하여 온/오프라인으로 공개하는 행위
- 콘텐츠의 일부 또는 전부를 이용하여 인쇄물을 만드는 행위
- 콘텐츠의 전부 또는 일부를 녹취 또는 녹화하거나 녹취록을 작성하는 행위
- 콘텐츠의 전부 또는 일부를 스크린 캡처하거나 카메라로 촬영하는 행위
- 지인을 포함한 제3자에게 콘텐츠의 일부 또는 전부를 공유하는 행위
- 다른 정보와 결합하여 Upstage Education의 콘텐츠를 알 수 있는 저작물을 작성, 공개하는 행위
- 제공된 데이터의 일부 혹은 전부를 Upstage Education 프로젝트/실습 수행 이외의 목적으로 사용하는 행위

Definition of Tree

- A general tree T is partitioned into disjoint subsets:
 - A single node r , the **root**
 - Sets of general trees, called **subtrees** of r



- Terminology
 - node (vertex)
 - edge
 - parent
 - child
 - siblings
 - root
 - leaf
 - ancestor
 - descendant
 - subtree

Tree Examples




01

Binary Tree


Definition of Binary Tree

- T is **binary tree**, if
 - T is empty, or
 - T is partitioned into three disjoint subsets:
 - A single node r , the root
 - Up to two sets that are **binary trees**, called left and right subtrees of r



An Example of Binary Tree



- Algebraic expressions




[1]

Height of a Tree

- Def. **Height** of a Tree: the **number of nodes** on the longest path from the root to a leaf.




Height: 7



Full Binary Tree

- Def. A binary tree T of height h is called **Full binary tree**, if
 - it is empty ($h=0$), or
 - both its left and right subtrees are full (of height $h-1$).




So now, you may feel why this is called **full** binary tree:
it is **filled with nodes at all possible positions!**

Complete Binary Tree


- Def. A binary tree T is called **Complete binary tree**, if
 - T is full down to level $h-1$, and
 - with level h filled in from left to right.



Complete BT of
Height 2



Complete BT of
Height 3



Complete BT of Height 4



Must be filled (to be complete)





Optionally filled (to be complete)

Array-based Implementation

- Recall: Array is a fundamental data structure with **contiguous fixed-length chunk** of memory space.
 - When we implement **List** with an array, it was straightforward to map the indices.
 - How can we assign designated indices for a binary tree?


- Let's assume the tree is full, and assign the indices from root, left to right.



This implementation is efficient if the tree is (almost) full or complete.

Array-based Implementation


- One more thing to consider: How can we figure out **direct children** of a node?
 - With a tree, we usually access data from the root to the leaf.
 - Common rule connecting a node to its children?



- From parent, its **left child**:
 $[\text{parent index}] * 2 + 1$ 😊
- **Right child**:
 $[\text{parent index}] * 2 + 2$ 😊
- Similarly, from a child, its **parent**:
 $[\text{child index} - 1] // 2$

Array-based Implementation

- Now, think about more general case: the tree may not be close to complete.
 - If we don't have a node, we may set `None` (or some other indicator for emptiness).



[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]
5	2	1	8	No ne	3	No ne	No ne	7	...


- This implementation becomes **less efficient** if the tree gets **far from full or complete**.

Reference-based Implementation

- It is similar to the linked list; instead of having a single link to another node, Binary Tree Node has **two references** to other nodes!


```
class TreeNode():  
    def __init__(self, x):  
        self.item = x  
        self.left = None  
        self.right = None
```

```
class BinaryTree():  
    def __init__(self, node):  
        self.root = node
```




Tree Traversal

- Traversal: **visiting all nodes once**
 - It is not straightforward to visit all nodes in a given tree, unlike an array or a linked list.
- There can be many different ways of traversal. We cover a few widely-used ones:




Preorder

Root - Left - Right



Inorder

Left - Root - Right



Postorder

Left - Right - Root

- Inside each subtree, the same rule applies recursively.

Tree Traversal Example

● Preorder traversal?

60 {20 subtree} 70

60 20 10 {40 subtree} 70

60 20 10 40 30 50 70

● Inorder traversal?

{20 subtree} 60 70

10 20 {40 subtree} 60 70


10 20 30 40 50 60 70

● Postorder traversal?

{20 subtree} 70 60

10 {40 subtree} 20 70 60

10 30 50 40 20 70 60



Tree Traversal Implementation

- Use recursion!
 - Base case: empty tree. Do nothing!
 - General case: 2 recursive calls + visiting the root.
 - The order depends on {pre, in, post}-order.

```
def preorder(node):  
    if node is not None:  
        print(node.item)  
        preorder(node.left)  
        preorder(node.right)
```

```
preorder(root)
```


```
def inorder(node):  
    if node is not None:  
        inorder(node.left)  
        print(node.item)  
        inorder(node.right)
```

```
inorder(root)
```




Binary Search Tree

Definition of Binary Search Tree

- Each node has a **search key**.
 - There are **no duplicates** among the search keys in a binary search tree.
- For each node n , it satisfies:
 - n 's key is greater than all keys in its left subtree T_L .
 - n 's key is less than all keys in its right subtree T_R .
 - Both T_L and T_R are binary search trees.



Binary Search Tree Examples




Check! All these 3 BSTs contain the same data.

Binary Search Tree Operations

- **Insert** a new item into a binary search tree.
- **Retrieve (search)** the item with a given search key from a binary search tree.
- **Delete** the item with a given search key from a binary search tree.
- For all, according to the rule that $\{\text{left subtree}\} < \text{root} < \{\text{right subtree}\}$ at all levels!

Search (Retrieval)

- Task: Search if there is a node with the given key, and output the item if so.
 - If the given key is not in the tree, we should be able to figure it out as well.
- Main Idea: At each node, decide which subtree to search further. Only 3 cases:
 - [Case 1] If the **search key = item** at the node, we **found** it!
 - [Case 2] If the **search key < item** at the node, the target must be in its **left subtree** if exists.
 - [Case 3] If the **search key > item** at the node, the target must be in its **right subtree** if exists.
 - For Case 2 & 3, move to the corresponding subtree, then repeat the same testing.
 - Repeat until you reach at a leaf. If you still do not meet Case 1, we conclude the key is **not in the tree**.



Search (Retrieval): Implementation

- Implementation based on recursive calls:


```
def search(root, key):  
    if root is None:  
        return None # Not found  
    elif key == root.item:  
        return root # Found  
    elif key < root.item:  
        return search(root.left, key)  
    else: # key > root.item  
        return search(root.right, key)
```

} Base case (empty BST): Not found!

} General case: case 1, 2, 3


Search (Retrieval): Time Complexity

- Time complexity of search operation?
 - At each node, we compare two values once, and decide where to go. $\rightarrow O(1)$
 - How many times? **Length from the root to the leaf!**
- Thus, the worst time performance = tree height!
- In terms of N (the number of data points in the tree), what's the asymptotic (Big O) complexity of tree search?



If the tree is **balanced** (close to full), the height gets closer to **$O(\log M)$** .


If the tree is unbalanced (close to linked list), the height gets closer to **$O(M)$** .



Then, how the shape of a tree is determined? We will revisit this soon.

Insertion

- Task: Insert a new key into the BST, preserving BST conditions.
 - We need to find the right location to put the new node.
- Main Idea: Insertion is basically a **failed search**. When we conclude the item does not exist, insert the new node right there!
 - [Case 1] If the **search key = item** at the node, we **found** it!
 - [Case 2] If the **search key < item** at the node, the target must be in its **left subtree** if exists.
 - [Case 3] If the **search key > item** at the node, the target must be in its **right subtree** if exists.
 - For Case 2 & 3, move to the corresponding subtree, then do the same testing.
 - Repeat until you reach at a leaf. **Insert the new node there!**



Insertion: Implementation

- Implementation based on recursive calls:

```
def insert(root, item):  
    if root is None:  
        new_node = TreeNode(item)  
        return new_node  
    elif key == root.item:  
        # ERROR: already exists  
    elif key < root.item:  
        new_subtree = insert(root.left, item)  
        root.left = new_subtree  
        return root  
    else: # key > root.item  
        new_subtree = insert(root.right, item)  
        root.right = new_subtree  
        return root
```

Base case: Create new node


General case: 3 ways

Deletion

- Task: Delete a node with the given key, **preserving BST conditions** after deletion.
 - After deletion of an intermediate node, the tree will be broken 😬.
- Main Idea:
 - [Case 1] If the node to delete is a **leaf**, simply remove it.
 - [Case 2] If the node to delete has a **single child**, the subtree will take it over.
 - [Case 3] If the node to delete has **both children**, elect the leftmost item in the right subtree as the new root.


Deletion (Case 1)

- When the target node is a **leaf**, we can simply remove it.
- After deletion, the resulting tree
 - is still **connected**, and
 - still **satisfies the BST conditions**.



Deletion (Case 2)


- When the target node **has one child**, the existing child takes the position of the target node, taking its descendents (subtree).
- After the right subtree takes over, the resulting tree
 - is **no longer broken**,
 - still satisfies the BST conditions.
- After deletion, the resulting tree
 - is **broken**,
 - still satisfies the BST conditions.



This slide is best seen with animations.

Deletion (Case 3)

- When the target node **has both children**, we elect the target's immediate successor (=left-most node in the right subtree) as the new root.
- After deletion, the resulting tree is **broken**.
 - Cannot simply take one subtree as new root, since we have two.
- To make the resulting tree satisfy BST conditions, we elect the **immediate successor** of the deleted node. The resulting tree, however, is still **broken**!
 - Why immediate successor? With it, it's guaranteed to satisfy the BST conditions!
- The deleted immediate successor node may need to adopt its orphan right child (if any).
 - Here, it is guaranteed that no left child exists.



Similarly, we may nominate the **immediate predecessor** (=right-most item in the left subtree.)

Deletion: Implementation

```
def delete(root, key):  
    if root is None:  
        return root  
  
    if key < root.key:  
        root.left = delete(root.left, key)  
    elif key > root.key:  
        root.right = delete(root.right, key)  
    else:  
  
    ... (to be continued)
```

} Locating the target

delete function returns the subtree to replace the target node to be deleted.

Deletion: Implementation

Case 1: no child if `root.right` is also `None`

```
... (continuing)
```

```
else:
```

```
    if root.left is None:
```

```
        new_root = root.right
```

```
        root = None
```

```
        return new_root
```

```
    elif root.right is None:
```

```
        new_root = root.left
```

```
        root = None
```

```
        return new_root
```

```
    else:
```

```
        im_su = get_immediate_successor(root)
```

```
        root.key = im_su.key
```

```
        root.right = delete(root.right, im_su.key)
```

```
    return root
```

Case 2: single child

```
def get_immediate_successor(target):
```

```
    curr = target.right
```

```
    while curr.left is not None:
```

```
        curr = curr.left
```


```
    return curr
```

Case 3: both children

After this line, we now
delete the node `im_su`.


Revisiting the shape of BST

- For a given data, how is the shape of BST determined?
 - Let's try to insert "4, 7, 2, 3, 5, 1, 6":
 - Suppose the same data is given in a different order: "7, 6, 5, 4, 3, 2, 1":




Shape of the tree is determined by the **order of insertion!**

Unfortunately, we often cannot control the datastream itself. 🤔




Balanced Trees

- We desire to make the tree **more balanced** for faster operations.
- There are some special trees that **guarantee balance** up to some level, but details of them are beyond of this course.



Red-black tree

: guarantees that the height is lower than $2 \log(N+1)$.



AVL tree


: guarantees that heights of the two child subtrees of any node differ by at most 1.

[1] <https://kostja.github.io/misc/2017/02/23/tarantool-data-structures.html>

[2] <https://blog.naver.com/luexr/223479906039>

Tree Sort

- **Inorder traversal** on a binary search tree lists the data in sorted order.
 - Due to the BST conditions, all values in the left subtree < root value < all values in the right subtree, at all nodes.
 - Inorder traversal visits nodes in the order of left - root - right!
- Time complexity?
 - We first need to insert all data into a BST.
→ $O(\log M)$ per each element \times N of them = $O(N \log M)$
(This assumes use one of the balanced trees!)
 - Then, inorder traversal: $O(M)$
← we visit one node at a time.
 - Overall, $O(N \log M)$ if the tree is balanced.
Otherwise, worst performance will be $O(N^2)$.



Inorder

Left - Root - Right

Time Complexity

- Time complexity of Binary Search Tree operations?

Task	Average-case	Worst-case
Insertion	$O(\log M)$	$O(M)$
Retrieval	$O(\log M)$	$O(M)$
Deletion	$O(\log M)$	$O(M)$
Traversal	$O(M)$	$O(M)$



When?

= When the tree is significantly unbalanced.

Applications of Binary Search Trees



Problem 1

- Test if two binary trees are symmetric.



Problem 2

- Test if a binary tree is balanced.
 - A binary tree is balanced if the difference in the height of its left and right subtrees is at most 1 for all nodes in the tree.



Problem 3

100. Same Tree

Easy


Topics

Companies

Given the roots of two binary trees `p` and `q`, write a function to check if they are the same or not.

Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.

Example 1:




Input: `p = [1,2,3]`, `q = [1,2,3]`

Output: `true`

Problem 3


Example 2:



Input: $p = [1, 2]$, $q = [1, \text{null}, 2]$

Output: false

Example 3:





Building intelligence for the future of work