

# SoPa++: Leveraging explainability from hybridized RNN, CNN and weighted finite-state neural architectures

Atreya Shankar, shankar@uni-potsdam.de  
Cognitive Systems: Language, Learning, and Reasoning (M.Sc.)

Thesis Progress Update  
University of Potsdam, WiSe 20/21

March 7, 2021

# Recap

- 1 Source code refactored to work with latest PyTorch and CUDA versions
- 2 Facebook NLU multi-class intent detection data set from [Schuster et al. \(2018\)](#)
- 3 Performance is important for explainability, because it does not make sense to explain a poorly performing model
- 4 Focus would be to develop SoPa++ as a neural model which can be easily decomposed into a *globally* explainable model

# Semirings

## Kuich and Salomaa 1986:

A semiring is a set  $\mathbb{K}$  along with two binary associative operations  $\oplus$  (addition) and  $\otimes$  (multiplication) and two identity elements:  $\bar{0}$  for addition and  $\bar{1}$  for multiplication. Semirings require that addition is commutative, multiplication distributes over addition, and that multiplication by  $\bar{0}$  annihilates, i.e.,  $\bar{0} \otimes a = a \otimes \bar{0} = \bar{0}$

- Generic semiring notation:  $\langle \mathbb{K}, \oplus, \otimes, \bar{0}, \bar{1} \rangle$
- Max-sum semiring:  $\langle \mathbb{R} \cup \{-\infty\}, \max, +, -\infty, 0 \rangle$
- Max-product semiring:  $\langle \mathbb{R} \cup \{-\infty\}, \max, \times, -\infty, 1 \rangle$
- Many semirings are possible, but we stick to *max* based semirings


# Weighted Finite-State Automata

$$p(\mathbf{x}) = \boldsymbol{\pi} \otimes \left( \bigotimes_{i=1}^n \mathbf{T}(x_i) \right) \otimes \boldsymbol{\eta} \quad (1)$$

$$s(\mathbf{z}) = \bigoplus_{\mathbf{x} \in \Pi(\mathbf{z})} p(\mathbf{x}) \quad (2)$$

- Path  $\mathbf{x} = \langle x_1, x_2, \dots, x_n \rangle$  derives some string  $\mathbf{z} = \langle z_1, z_2, \dots, z_m \rangle$
- $\Pi(\mathbf{z})$  is the set of all possible paths that derive string  $\mathbf{z}$
- $\boldsymbol{\pi}, \boldsymbol{\eta}$  are start and end state vectors
- $\mathbf{T}$  is a transition matrix defining transition scores between states
- $p(\mathbf{x})$  refers to a score through a particular path
- $s(\mathbf{z})$  refers to an aggregate score through all possible paths
- Utilize Viterbi algorithm with *max* based semirings to compute  $s(\mathbf{z})$   
(Viterbi, 1967)


# Finite transition types



**Figure 1:** Schematic for finite-state transitions;  $\epsilon$  represents an epsilon-transition, “funny” and “magical” form self-loops and all other transitions are main transitions (Schwartz, Thomson, and Smith, 2018)

- Vanilla SoPa allowed 3 transitions types: main, epsilon and self-loops
- **SoPa++ uses only two transitions: namely main and wildcard transitions**
- Both consume one token and one state, which leads to pattern-string determinism and could make the *explainability* step easier

# SoPa++: Lower Model



**Figure 2:** SoPa++ lower model schematic where pattern 1 is activated by the substring "in years" and pattern 2 is activated by the substring "funniest and most likeable book" (Schwartz, Thomson, and Smith, 2018)

- Vanilla SoPa places a MLP on top of the max-pooled states to retrieve classification results
- This contributes to a lack of explainability since MLPs are generally not easily explainable

# SoPa++: Upper Model




Figure 3: SoPa++ upper model schematic (combined lower-upper schematic under-construction); STE refers to a straight-through-estimator (Yin et al., 2019)

# SoPa++: Explainable Model




Figure 4: SoPa++ explainable variant derived from antecedent neural model



# Training and Convergence



**Figure 5:** Excerpt from TensorBoard training logs for SoPa++ grid-search

- Model training procedure tends to converge fast
- Best model checkpoint(s) were reached within 1-6 epochs

# Evaluation

Patterns	Test Precision	Test Recall	Test $F_1$
6-10_5-10_4-10_3-10	0.982	0.981	0.982
6-50_5-50_4-50_3-50	0.988	0.987	<b>0.987</b>

**Table 1:** Performance summary of various SoPa++ models; evaluation metrics are based on weighted averages

- Performance is competitive with that from literature and online benchmarks, which show  $F_1$  scores ranging from 96-99% ([Schuster et al., 2018](#))
- In both the above cases, the max-sum semiring outperforms the max-product semiring
- Even though the SoPa++ model variant with higher number of patterns performs better, a **smaller model** might be more beneficial for explainability

# Explainability: Peek into the Regex Ensemble

Pattern length	Sample regular expressions
3	{* forecast}, {* activate}, {* weather}
4	{activate morning *}, {my alarm *}, {* minute snooze}
5	{add * reminder for}, {the boiled eggs *}
6	{to wish * * happy}, {* add * * to}

**Table 2:** Sample regular expressions that activate patterns of specified lengths; \* is used for aesthetic purposes to represent a wildcard instead of the appropriate `\w+` regular expression

- Patterns above were processed from a small subset of the training data; the full processing is still under development
- Patterns are indicative of important (generalized) n-grams in text
- Analyzing the weights of the linear layer can tell us how important each pattern is for the prediction of each class

# Next steps

- 1 Find a clever way for clustering/merging regular expressions to keep the size of explainable model small
- 2 Analyze the performance of both SoPa++ and its explainable variant on the test set to measure how different their performances are
- 3 For cases where the explainable model does not perform similar to the SoPa++ neural model, propose local sample explanations as alternative

# Bibliography I

- Kuich, Werner and Arto Salomaa (1986). “Linear Algebra”. In: *Semirings, automata, languages*. Springer, pp. 5–103.
- Schuster, Sebastian et al. (2018). “Cross-lingual transfer learning for multilingual task oriented dialog”. In: *arXiv preprint arXiv:1810.13327*.
- Schwartz, Roy, Sam Thomson, and Noah A. Smith (July 2018). “Bridging CNNs, RNNs, and Weighted Finite-State Machines”. In: *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Melbourne, Australia: Association for Computational Linguistics, pp. 295–305. DOI: 10.18653/v1/P18-1028. URL: <https://www.aclweb.org/anthology/P18-1028>.
- Viterbi, Andrew (1967). “Error bounds for convolutional codes and an asymptotically optimum decoding algorithm”. In: *IEEE transactions on Information Theory* 13.2, pp. 260–269.

# Bibliography II

Yin, Penghang et al. (2019). “Understanding straight-through estimator in training activation quantized neural nets”. In: *arXiv preprint arXiv:1903.05662*.