

SoPa++: Leveraging explainability from hybridized RNN, CNN and weighted finite-state neural architectures

M.Sc. Thesis Defense

Atreya Shankar (799227), shankar.atreya@gmail.com

Cognitive Systems: Language, Learning, and Reasoning (M.Sc.)

1st Supervisor: Dr. Sharid Loáiciga, University of Potsdam

2nd Supervisor: Mathias Müller, M.A., University of Zurich

Foundations of Computational Linguistics

Department of Linguistics

University of Potsdam, SoSe 2021

July 8, 2021

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Motivation

- Trend of increasingly complex deep learning models achieving SOTA performance on ML and NLP tasks (Figure 1)
- To address emerging concerns such as inductive biases, several studies make arguments for research into XAI; for example [Danilevsky et al. \(2020\)](#) and [Arrieta et al. \(2020\)](#)
- [Schwartz et al. \(2018\)](#) approach XAI in NLP by proposing an explainable hybridized neural architecture called **Soft Patterns** (SoPa; Figure 2)
- SoPa provides **localized** and **indirect** explainability despite being suited for globalized and direct **explanations by simplification**




Figure 1: Parameter counts of recently released pre-trained language models; figure taken from [Sanh et al. \(2019\)](#)

SoPa: Bridging CNNs, RNNs, and Weighted Finite-State Machines

Roy Schwartz* ♦♦ Sam Thomson* ♦ Noah A. Smith ♦

♦Paul G. Allen School of Computer Science & Engineering, University of Washington

♦Language Technologies Institute, Carnegie Mellon University

▽Allen Institute for Artificial Intelligence

{roysch,nasmith}@cs.washington.edu, sthompson@cs.cmu.edu

Figure 2: Excerpt from [Schwartz et al. \(2018\)](#)

Objective and research questions

Objective:

- Address limitations of SoPa by proposing **SoPa++**, which could allow for effective explanations by simplification.

Process:

- We study the performance and explanations by simplification of SoPa++ on the **FMTOD** data set from [Schuster et al. \(2019\)](#); focusing on the English-language intent classification task.

Research questions:

- 1 Does SoPa++ provide **competitive** performance?
- 2 To what extent does SoPa++ contribute to **effective** explanations by simplification?
- 3 What **interesting and relevant** explanations can SoPa++ provide?

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Explainability

- Transparency is a passive feature that a model exhibits
- Explainability is an active feature that involves target audiences (Figure 3)
- [Arrieta et al. \(2020\)](#) explore a taxonomy of post-hoc explainability techniques
- Prominent explainability techniques include local explanations, feature relevance and **explanations by simplification**
- Explainability techniques can provide meaningful insights into decision boundaries within black-box models (Figure 4)






Figure 3: Examples of various target audiences in XAI; figure taken from [Arrieta et al. \(2020\)](#)



(a) Husky classified as wolf



(b) Explanation

Figure 4: Local explanation for “Wolf” classification decision, figure taken from [Ribeiro et al. \(2016\)](#)

SoPa: Weighted Finite-State Automaton (WFA)

Definition 1 (Semiring; Kuich and Salomaa 1986)

A semiring is a set \mathbb{K} along with two binary associative operations \oplus (addition) and \otimes (multiplication) and two identity elements: $\bar{0}$ for addition and $\bar{1}$ for multiplication. Semirings require that addition is commutative, multiplication distributes over addition, and that multiplication by $\bar{0}$ annihilates, i.e., $\bar{0} \otimes a = a \otimes \bar{0} = \bar{0}$.

- Semirings follow the following generic notation: $\langle \mathbb{K}, \oplus, \otimes, \bar{0}, \bar{1} \rangle$.
- **Max-sum** semiring: $\langle \mathbb{R} \cup \{-\infty\}, \max, +, -\infty, 0 \rangle$
- **Max-product** semiring: $\langle \mathbb{R}_{>0} \cup \{-\infty\}, \max, \times, -\infty, 1 \rangle$

Definition 2 (Weighted finite-state automaton; Peng et al. 2018)

A weighted finite-state automaton over a semiring \mathbb{K} is a 5-tuple $\mathcal{A} = \langle \Sigma, \mathcal{Q}, \Gamma, \lambda, \rho \rangle$, with:

- a finite input alphabet Σ ;
- a finite state set \mathcal{Q} ;
- transition matrix $\Gamma : \mathcal{Q} \times \mathcal{Q} \times (\Sigma \cup \{\epsilon\}) \rightarrow \mathbb{K}$;
- initial vector $\lambda : \mathcal{Q} \rightarrow \mathbb{K}$;
- and final vector $\rho : \mathcal{Q} \rightarrow \mathbb{K}$.

SoPa: Computational graph




Figure 5: Linear-chain NFA with self-loop (blue), ϵ (red) and main-path (black) transitions; figure adapted from [Schwartz et al. \(2018\)](#)




Figure 6: SoPa's partial computational graph; figure taken from [Schwartz et al. \(2018\)](#)

SoPa: Post-hoc explainability techniques

- SoPa provides two post-hoc explainability techniques; namely **local explanations** and **feature relevance**
- Local explanations gather highest scoring phrases across the training data (Figure 7)
- Feature relevance perturbs inputs using an occlusion technique to determine the highest impact phrases for a classification decision (Figure 8)
- Overall, both techniques are **localized** and **indirect**
- WFAs have a rich theoretical background which can be exploited for more direct and globalized explanations

	Highest Scoring Phrases				
Patt. 1	thoughtful and entertaining gentle poignant	, astonishingly , , and	reverent articulate thought-provoking mesmerizing uplifting	portrait cast film portrait story	of of with of in
Patt. 2	's this this a is	€ € € € €	uninspired bad leaden half-assed clumsy ,SL	story on comedy film the	. purpose . . writing

Figure 7: Ranked local explanations from SoPa; table taken from [Schwartz et al. \(2018\)](#)

Analyzed Documents

it 's dumb , but more importantly , it 's just not scary

though moonlight mile is replete with **acclaimed actors and actresses** and tackles a subject that 's **potentially moving** , the movie is *too predictable* and *too self-conscious to reach* a level of **high drama**

While **its careful pace and** seemingly *opaque story* may not satisfy every moviegoer 's appetite, the film 's final scene is **soaringly , transparently moving**

Figure 8: Feature relevance outputs from SoPa; table taken from [Schwartz et al. \(2018\)](#)

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Overview

1 Introduction

2 Background concepts

3 Data and methodologies

4 Results

5 Discussion

6 Conclusions

7 Future work

Bibliography I

Arrieta, Alejandro Barredo, Natalia Díaz-Rodríguez, Javier Del Ser, Adrien Bennetot, Siham Tabik, Alberto Barbado, Salvador García, Sergio Gil-López, Daniel Molina, Richard Benjamins, et al. (2020). “Explainable Artificial Intelligence (XAI): Concepts, taxonomies, opportunities and challenges toward responsible AI”. In: *Information Fusion* 58, pp. 82–115.

Danilevsky, Marina, Kun Qian, Ranit Aharonov, Yannis Katsis, Ban Kawas, and Prithviraj Sen (Dec. 2020). “A Survey of the State of Explainable AI for Natural Language Processing”. In: *Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing*. Suzhou, China: Association for Computational Linguistics, pp. 447–459. URL: <https://www.aclweb.org/anthology/2020.aacl-main.46>.

Kuich, Werner and Arto Salomaa (1986). “Linear Algebra”. In: *Semirings, automata, languages*. Springer, pp. 5–103.

Peng, Hao, Roy Schwartz, Sam Thomson, and Noah A. Smith (2018). “Rational Recurrences”. In: *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. Brussels, Belgium: Association for Computational Linguistics, pp. 1203–1214. DOI: 10.18653/v1/D18-1152. URL: <https://www.aclweb.org/anthology/D18-1152>.

Bibliography II

Ribeiro, Marco Tulio, Sameer Singh, and Carlos Guestrin (2016). ““Why Should I Trust You?”: Explaining the Predictions of Any Classifier”. In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, CA, USA, August 13-17, 2016*, pp. 1135–1144.

Sanh, Victor, Lysandre Debut, Julien Chaumond, and Thomas Wolf (2019). “DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter”. In: *NeurIPS EMC² Workshop*.

Schuster, Sebastian, Sonal Gupta, Rushin Shah, and Mike Lewis (June 2019). “Cross-lingual Transfer Learning for Multilingual Task Oriented Dialog”. In: *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Minneapolis, Minnesota: Association for Computational Linguistics, pp. 3795–3805. DOI: 10.18653/v1/N19-1380. URL: <https://www.aclweb.org/anthology/N19-1380>.

Schwartz, Roy, Sam Thomson, and Noah A. Smith (July 2018). “Bridging CNNs, RNNs, and Weighted Finite-State Machines”. In: *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Melbourne, Australia: Association for Computational Linguistics, pp. 295–305. DOI: 10.18653/v1/P18-1028. URL: <https://www.aclweb.org/anthology/P18-1028>.