



How to install the integrated code

A. Fukuyama

Professor Emeritus, Kyoto University

1. Preparation for macOS
2. In case of macOS major version update
3. Preparation for Ubuntu
4. Introduction to git
5. Install task and related libraries
6. Introduction to the task code
7. Install PETSc

Preparation for macOS (1)

- **Install Xcode**

- Xcode: development environment on macOS
- Use App Store
- Category: Development
- Choose and install Xcode

- **Install Command Line Tools**

- Command_Line_Tools: various Unix commands
- Corresponding to the version of Xcode
- `xcode-select --install`
- or download from Apple Developer site

- **Install XQartz**

- Download and install XQartz from <https://www.xqartz.com/>

- **Install java** (when necessary)

- https://www.java.com/en/download/mac_download

Preparation for macOS (2)

- **Install Macports**

- Macports site: <https://www.macports.org>
- Select tab: Installing MacPorts
- Download the MacPorts installer for appropriate
- Run the MacPorts installer

- **Set environmental variables in \$HOME/.zprofile**

- **Add** export PATH=/opt/local/bin:\$PATH **in** .zprofile
- **Add** export MANPATH=/opt/local/man:\$MANPATH

- **Install compiler and related modules**

- `sudo port install gmake cmake imake gcc13 mpicc`
- `sudo port select gcc mp-gcc13`
- `sudo port select mpi mpich-mp-fortran`

Preparation for macOS (3)

- **To update Macports:** (If rsync is available)
 - `sudo port selfupdate`
 - `sudo port upgrade outdated`
- **If rsync is not available**, port selfupdate will hang
 - See <https://trac.macports.org/wiki/howto/Syncing>
 - **Create the source list**
 - Download the source list in MacPorts server b
 - Modify macports config to read the source list
 - **Find outdated ports and upgrade them**
 - Update the source list by git pull
 - Sync installed with the source list and select ou
 - `sudo port upgrade outdated`

In case of macOS major version

- **macOS major version-up**: e.g. 14.3 \implies 15.0
- **Update Xcode and Command_Line_Tools** for the
- **Install a new Macports binary** for the new version
- **Migrate Macports**: make ports list, uninstall ports
 - `port -qv installed > myports.txt`
 - `port echo requested | cut -d ' ' -f 1 | uniq >`
 - `sudo port -f uninstall installed`
 - `sudo port reclaim`
 - `curl -L -O https://github.com/macports/macports-contrib/raw/master/rest`
 - `chmod +x restore_ports.tcl`
 - `xattr -d com.apple.quarantine restore_ports.tc`
 - `sudo ./restore_ports.tcl myports.txt`
 - `sudo port unsetrequested installed`
 - `xargs sudo port setrequested < requested.txt`
- **See more detail in <https://trac.macports.org/wiki>**

Preparation for Ubuntu

1. Install required modules

```
sudo apt-get install gfortran-13
```

```
sudo apt-get install gcc-13
```

```
sudo apt-get install g++-13
```

```
sudo apt-get install git
```

```
sudo apt-get install xorg-dev
```

```
sudo apt-get install valgrind
```

```
sudo apt-get install cmake
```

```
sudo apt-get install python
```

```
sudo apt-get install mpich
```

How to use git (1)

- **git**: version and remote repository control facility
- **Repositories**
 - **local**: in your machine
 - **remotes**: in remote servers
 - **remotes/origin**: in default server: bpsi.nucleng.
- **Branches**
 - **There are several branches for code development**
 - **master**: default, stable version, often rather old
 - **develop**: latest version, where I am working
 - **others**: branches for working specific modules
 - **cd task**
 - **git branch** : list branch names, local only
 - **git branch -a** : list branch names, local and remote

How to use git (2)

- **To use task/develop branch** (cd task)
 - **Create local branch develop and associate develop**
 - `git checkout -t -b develop origin/develop`
 - `git branch`
- **Change working branch**
 - `git checkout master`
 - `git checkout develop`
- **Update working branch**: download from remote repository
 - `git pull`
 - Your modification is kept, if committed.
 - If uncommitted modification remains, no overwrite.
 - use `git stash` to keep away your modification.
 - If there are conflicts with your committed modification, conflicts are indicated in the file. Correct them and

How to use git (3)

- **To check your modification**
 - `git status`
- **To commit your modification with message:** on is updated. message is required.
 - `git commit -a -m'message'`
- **To list all modification**
 - `git log`
- **To show difference from committed repository**
 - `git diff [filename]`
- **For more detail, visit**
 - <https://git-scm.com/documentation>

Install TASK (1)

- **Check availability of git:** just command input “git”
- **Set your identity:** To record who changed the code
 - `git config --global user.name “[your-full-name]”`
 - `git config --global user.email [your-mail-address]`
 - For example,
 - `git config --global user.name “Atsushi Fukuyama”`
 - `git config --global user.email fukuyama@nuclei.ac.jp`
 - Data is saved in `$HOME/.gitconfig`
- **Create a working directory:** any directory name is fine
 - `mkdir git`
 - `cd git`

Install TASK (2)

- **Download TASK and necessary libraries** for download
 - `git clone https://bpsl.nucleng.kyoto-u.ac.jp/pub/g`
 - `git clone https://bpsl.nucleng.kyoto-u.ac.jp/pub/g`
 - `git clone https://bpsl.nucleng.kyoto-u.ac.jp/pub/g`
- **Download TASK and necessary libraries** for download
 - `git clone ssh://bpsl.nucleng.kyoto-u.ac.jp/pub/git`
 - `git clone ssh://bpsl.nucleng.kyoto-u.ac.jp/pub/git`
 - `git clone ssh://bpsl.nucleng.kyoto-u.ac.jp/pub/git`
 - `bpsl` should be replaced by `username@bpsl` if remote usernames are different.
- **Three directories will be created**
 - **gsaf**: graphic library
 - **bpsd**: data interface library
 - **task**: main TASK directory

Install TASK (3)

- **Install graphic library GSAF**

- `cd git/gsaf/src`
- Copy Makefile.arch appropriate for your environment
 - for macOS: `cp ../arch/macos-gfortran/Makefile`
 - for Ubuntu: `cp ../arch/ubuntu-gfortran64-static`
- **Edit Makefile.arch**: adjust BINPATH and LIBPATH
 - BINPATH: graphic commands are located, should be added to \$PATH in ~/.profile or ~/.zprofile
 - LIBPATH: graphic libraries are located, should be added to library path for compiling applications using the
- `make`
- `make install`
 - if BINPATH is protected, use “`sudo make install`”

Install TASK (4)

- **Check the availability of GSAF library**
 - `cd test`
 - `make`
 - Applications using GSAF library must be started such as xterm, not from Terminal on macOS.
 - `./bsctest`
 - `5` : Choose the size of window
 - `c` : Continue the run
 - `m`
 - New graphic window opens and marks and lines
 - To go back to the original window, enter CR.
 - If focus does not change, click the original window preferences.
 - `e` : Close the graphic window
 - `cd ../../..`

Install TASK (5)

- **Confirm the branch is develop and setup make**
 - `cd task`
 - `git branch` (indicated branch should be develop)
 - `cp make.header.org make.header`
 - **Edit make.header** to remove comments for target
- **Compile data exchange library BPSD**
 - `cd ../bpsd`
 - `make`
 - `cd ../task`

Install TASK (6)

- **Choice of matrix solver configuration**

- Single processing without MPI: `make.mtxp.nomp`
- Multi processing with single matrix solver:: `make`
- Multi processing with parallel real matrix solver:
- Multi processing with parallel real and complex s
`make.mtxp.petsc+mumps`

- **Modules using parallel matrix solver**

- **Real**: fp, ti, pic, t2
- **Complex**: wmx, wf2d, wf2dt, wf2dx, wq

- **Setup matrix solver library**

- `cd mtxp`
- `cp make.mtxp.XXX make.mtxp`
- `make`
- `cd ..`

Install TASK (7)

- **Compile modules:**
 - `cd lib`
 - `make`
 - `cd ..`
- **Compile and run TASK module:** eq for example
 - `cd eq`
 - `make`
 - `./eq`
 - `5`
 - `c`
 - `r`
 - `g`
 - `s, CR, CR, ...`
 - `x`
 - `q`

How to use GSAF

- **At the beginning of the program**
 - **Set graphic resolution** (0: metafile output only,
 - **commands**
 - **c**: continue
 - **f**: set metafile name and start saving
- **At the end of one page drawing**
 - **commands**
 - **c** or **CR**: change focus to original window and
 - **f**: set metafile name and start saving
 - **s**: start saving and save this page
 - **y**: save this page and continue
 - **n**: continue without saving
 - **d**: dump this page as a bitmap file “gsdumpn”
 - **b**: switch on/off bell sound
 - **q**: quit program after confirmation

Graphic Utilities

- **Utility program**

- **gsview**: View metafile
- **gsprint**: Print metafile on a postscript printer
- **gstoeps**: Convert metafile to eps files of each page
- **gstops**: Convert metafile to a postscript file of a page
- **gstotgif**: Convert metafile to a tgif file for graphical user interface
- **gstotsvg**: Convert metafile to a svg file for web browser

- **Options**

- **-a**: output all pages, otherwise interactive mode
- **-s ps**: output from page ps
- **-e pe**: output until page pe
- **-p np**: output contiguous *np* pages on a sheet
- **-b**: output without title
- **-r**: rotate page
- **-z**: gray output

Typical File Name of TASK

- **XXcomm.f90**: Definition of global variables, allocation
- **XXmain.f90**: Main program for standalone use, read
- **XXmenu.f90**: Command input
- **XXinit.f90**: Default values
- **XXparm.f90**: Read input parameters
- **XXview.f90**: Show input parameters
- **XXprep.f90**: Initialization of run, initial profile
- **XXexec.f90**: Execution of run
- **XXgout.f90**: Graphic output
- **XXfout.f90**: Text file output
- **XXsave.f90**: Binary file output
- **XXload.f90**: Binary file input

Typical input command

- When input line includes **=**, interpreted as a namelist
- When the first character is not an alphabet, interpreted as a comment
- **r**: Initialize profiles and execute
- **c**: Continue run
- **p**: Namelist input of input parameters
- **v**: Display of input parameters
- **s**: Save results into a file
- **l**: Load results from a file
- **q**: End of the program
- **Order of input parameter setting**
 - Setting at the subroutine **XX_init** in **XXinit.f90**
 - Read a namelist file **XXparm** at the beginning of the program
 - Setting by the input line

Install PETSc (1)

- **PETSc**: Parallel matrix solver library
 - blas,lapack: matrix solver tolls
 - scalapack, metis, parmetis, blacs, superlu: para
 - MUMPS: Direct matrix solver for real and compl
 - PETSc: Iterative matrix solver for real or comple
- **Make PETSc directory and change its owner**
 - `sudo mkdir /opt/PETSc`
 - `sudo chown /opt/PETSc $USERNAME`
 - `cd /opt/PETSc`
- **Download latest PETSc library package by git**
 - **First download of PETSc source**
 - `git clone -b release https://gitlab.com/pets`
 - **In order to update PETSc source**
 - `git pull`

Install PETSc (2)

- **Provide environment variables for PETSC in ~/.bashrc**
 - `export PETSC_DIR=/opt/PETSc/petsc`
 - `export PETSC_ARCH=default`
- **Configure script in python**
 - **Copy** `default.py` **to** `/opt/PETSc/petsc`
 - **Provide exec attribute to** `default.py`
 - `chmod 755 default.py`
 - **Execute configuration script** (It may take some time)
 - `./default.py`
 - **Additional libraries are created in default/external**
- **Make and check PETSc library**
 - `make` (It may take half an hour.)
 - `make check`