


```

"""
q-Racah 6j-Symbol Calculator (JAX/GPU) -- CLEAN VERSION

Purpose:
Computes the q-deformed 6j-symbols for  $SU_q(2)$ , which encode the
topological theta-term in the 4D YM lattice model.

Features:
- JAX-accelerated for massive parallelization over theta.
- Robust handling of static arguments for JIT compilation.
- Automatic GPU detection.

Usage:
1. Upload to Google Colab.
2. Run the cell.
3. Output plot 'q_racah_6j_scan.png' will be saved.
"""

import sys
import subprocess

# 1. Environment Setup & Dependency Check
# (Standard Colab has jax, numpy, matplotlib. If missing, we install.)
try:
    ... import jax
    ... import jax.numpy as jnp
    ... import matplotlib.pyplot as plt
    ... import numpy as np
except ImportError as e:
    ... print(f"Missing dependency: {e}. Installing...")
    ... subprocess.check_call([sys.executable, "-m", "pip", "install", "jax[cuda]"
    ... import jax
    ... import jax.numpy as jnp
    ... import matplotlib.pyplot as plt
    ... import numpy as np

from functools import partial

# 2. Hardware Check
print(f"JAX Backend: {jax.devices()}")

# Enable 64-bit precision for factorials/large numbers
jax.config.update("jax_enable_x64", True)

# -----
# Math Functions
# -----

@jax.jit

```

```

def q_number(n, theta):
    """
    ... Computes  $[n]_q = \sin(n \cdot \theta) / \sin(\theta)$ .
    ... Handles the limit  $\theta \rightarrow 0$  safely.
    ... """
    ... denom = jnp.sin(theta)
    ... # Avoid division by zero
    ... safe_denom = jnp.where(jnp.abs(denom) < 1e-12, 1.0, denom)
    ... val = jnp.sin(n * theta) / safe_denom

    ... # Correct limit at  $\theta=0$  is  $n$ 
    ... return jnp.where(jnp.abs(theta) < 1e-12, n, val)

@partial(jax.jit, static_argnums=(0,))
def log_q_factorial(n, theta):
    """
    ... Computes  $\log([n]_q!) = \sum_{k=1}^n \log([k]_q)$ .
    ... 'n' MUST be static because it defines the loop range.
    ... """
    ... # Create static range for summation
    ... k_vals = jnp.arange(1, n + 1)
    ... q_nums = q_number(k_vals, theta)
    ... # Use complex log to handle negative q-numbers (phases)
    ... return jnp.sum(jnp.log(q_nums + 0j))

@partial(jax.jit, static_argnums=(0, 1, 2))
def q_triangle(a, b, c, theta):
    """
    ... Computes the log of the q-triangle coefficient.
    ... a, b, c are static integers ( $2 \cdot \text{spin}$ ).
    ... """
    ... # Triangle inequalities check
    ... valid = (a+b >= c) & (b+c >= a) & (c+a >= b) & ((a+b+c)%2 == 0)

    ... # We compute terms regardless of validity to keep JAX happy (fixed graph),
    ... # then mask the result.
    ... term1 = log_q_factorial((a + b - c)//2, theta)
    ... term2 = log_q_factorial((a - b + c)//2, theta)
    ... term3 = log_q_factorial((-a + b + c)//2, theta)
    ... term4 = log_q_factorial((a + b + c)//2 + 1, theta)

    ... log_val = 0.5 * (term1 + term2 + term3 - term4)

    ... # Return  $-\inf(\log(0))$  if invalid
    ... return jnp.where(valid, log_val, -jnp.inf + 0j)

@partial(jax.jit, static_argnums=(0, 1, 2, 3, 4, 5))
def q_6j_symbol(j1, j2, j3, j4, j5, j6, theta):
    """
    ... Computes the q-6j symbol  $\{j_1 \ j_2 \ j_3\}$ 
    ... {i4 i5 i6} a

```

```

    """
    All j inputs are static integers (2 * spin).
    """

    # 1. Triangle Coefficients
    t1 = q_triangle(j1, j2, j3, theta)
    t2 = q_triangle(j1, j5, j6, theta)
    t3 = q_triangle(j4, j2, j6, theta)
    t4 = q_triangle(j4, j5, j3, theta)

    log_prefactor = t1 + t2 + t3 + t4

    # 2. Racah Summation
    a, b, c, d, e, f = j1, j2, j3, j4, j5, j6

    # Determine summation bounds (must be static integers)
    k_min = max(a+b+c, a+e+f, d+b+f, d+e+c) // 2
    k_max = min(a+b+d+e, a+c+d+f, b+c+e+f) // 2

    # Explicit python loop for summation to unroll it
    # This is efficient for small spins and avoids dynamic shapes
    sum_val = 0.0 + 0.0j

    # If k_min > k_max, the loop won't run, sum_val remains 0
    for k in range(k_min, k_max + 1):
        d1 = log_q_factorial(k - (a+b+c)//2, theta)
        d2 = log_q_factorial(k - (a+e+f)//2, theta)
        d3 = log_q_factorial(k - (d+b+f)//2, theta)
        d4 = log_q_factorial(k - (d+e+c)//2, theta)
        d5 = log_q_factorial((a+b+d+e)//2 - k, theta)
        d6 = log_q_factorial((a+c+d+f)//2 - k, theta)
        d7 = log_q_factorial((b+c+e+f)//2 - k, theta)

        num = log_q_factorial(k + 1, theta)

        log_term = num - (d1 + d2 + d3 + d4 + d5 + d6 + d7)
        phase = (-1.0)**k

        sum_val += phase * jnp.exp(log_term)

    return jnp.exp(log_prefactor) * sum_val

# -----
# Main Execution
# -----

def run_experiment():
    print("\n" + "="*50)
    print("Running q-Racah 6j-Symbol Scan (Clean Version)")
    print("="*50)

    # Scan parameters

```

```

... # Theta from slightly > 0 to 2pi
... thetas = jnp.linspace(0.01, 2*jnp.pi, 2000)

... # Configuration: Tetrahedron with all spins j=1 (doubled j=2)
... # {1 1 1}
... # {1 1 1}
... j_val = 2

... print(f"Configuration: All spins j={j_val/2}")
... print(f"Scanning {len(thetas)} theta points...")

... # Vectorize over theta (the only dynamic argument)
... # We use a lambda to bind the static integer arguments
... v_q6j = jax.vmap(lambda t: q_6j_symbol(j_val, j_val, j_val, j_val, j_val,

... # Compute
... results = v_q6j(thetas)

... # Force execution
... results.block_until_ready()
... print("Computation Complete.")

... # Plotting
... thetas_np = np.array(thetas)
... results_np = np.array(results)

... plt.figure(figsize=(12, 6))
... plt.plot(thetas_np, results_np.real, label="Real Part", color='blue', line
... plt.plot(thetas_np, results_np.imag, label="Imag Part", color='red', line

... plt.title(f"q-Deformed 6j-Symbol vs Theta (Spins j={j_val/2})")
... plt.xlabel("Theta (radians)")
... plt.ylabel("{6j}_q Value")
... plt.axhline(0, color='black', linewidth=0.5)
... plt.legend()
... plt.grid(True, alpha=0.3)

... output_file = "q_racah_6j_scan.png"
... plt.savefig(output_file, dpi=150)
... print(f"Saved plot to {output_file}")


... # Optional: Save data for download
... np.savetxt("q_racah_data.txt", np.column_stack((thetas_np, results_np.real
... print("Saved data to q_racah_data.txt")

if __name__ == "__main__":
... run_experiment()

```

JAX Backend: [CpuDevice(id=0)]

```
=====
Running q-Racah 6j-Symbol Scan (Clean Version)
=====
Configuration: All spins j=1.0
Scanning 2000 theta points...
Computation Complete.
Saved plot to q_racah_6j_scan.png
Saved data to q_racah_data.txt
```



```
# =====
# SU(2) 6j vs q-6j, symmetric family, NO JIT (no concretization)
# =====

import math
import jax
import jax.numpy as jnp

# ----- basic factorial / q-factorial -----

def log_factorial(n: int) -> jnp.ndarray:
    """log(n!) for integer n >= 0."""
    x = jnp.asarray(float(n) + 1.0)
```

```

    return jnp.lax.lgamma(x)

def q_number(n: int, theta: float) -> jnp.ndarray:
    """[n]_q = sin(n*theta)/sin(theta)."""
    return jnp.sin(n * theta) / jnp.sin(theta)

def log_q_factorial(n: int, theta: float) -> jnp.ndarray:
    """log([n]_q!) = sum_{k=1}^n log([k]_q)."""
    if n <= 0:
        return jnp.array(0.0)
    ks = jnp.arange(1, n + 1)
    vals = jnp.sin(ks * theta) / jnp.sin(theta)
    return jnp.sum(jnp.log(jnp.abs(vals)))

# ----- triangle coefficients Δ(j1,j2,j3) in doubled spins -----

def log_delta(a: int, b: int, c: int):
    """
    Δ(j1,j2,j3) with a=2*j1, b=2*j2, c=2*j3 (ints).
    Returns (logΔ, valid_flag).
    """
    A = a + b - c
    B = a - b + c
    C = -a + b + c
    D = a + b + c + 2 # 2*(j1+j2+j3)+2

    cond = (
        (A >= 0) & (B >= 0) & (C >= 0) &
        (A % 2 == 0) & (B % 2 == 0) & (C % 2 == 0) &
        (D % 2 == 0)
    )

    if not cond:
        return jnp.array(-jnp.inf), False

    A2 = A // 2
    B2 = B // 2
    C2 = C // 2
    D2 = D // 2

    log_num = log_factorial(A2) + log_factorial(B2) + log_factorial(C2)
    log_den = log_factorial(D2)
    log_delta_val = 0.5 * (log_num - log_den)
    return log_delta_val, True

def log_q_delta(a: int, b: int, c: int, theta: float):
    """q-Δ with q-factorials, same structure."""
    A = a + b - c
    B = a - b + c
    C = -a + b + c

```

```

D = a + b + c + 2

cond = (
    (A >= 0) & (B >= 0) & (C >= 0) &
    (A % 2 == 0) & (B % 2 == 0) & (C % 2 == 0) &
    (D % 2 == 0)
)

if not cond:
    return jnp.array(-jnp.inf), False

A2 = A // 2
B2 = B // 2
C2 = C // 2
D2 = D // 2

log_num = (
    log_q_factorial(A2, theta) +
    log_q_factorial(B2, theta) +
    log_q_factorial(C2, theta)
)
log_den = log_q_factorial(D2, theta)
log_delta_val = 0.5 * (log_num - log_den)
return log_delta_val, True

# ----- Racah sum core -----

def racah_sum(a,b,c,d,e,f, use_q=False, theta=0.0):
    """
    Raw Racah sum S for 6j.
    a..f are doubled spins (ints).
    """
    # standard integer combos
    x1 = (a + b + c) // 2
    x2 = (a + e + f) // 2
    x3 = (d + b + f) // 2
    x4 = (d + e + c) // 2

    y1 = (a + b + d + e) // 2
    y2 = (a + c + d + f) // 2
    y3 = (b + c + e + f) // 2

    z_min = max(x1, x2, x3, x4)
    z_max = min(y1, y2, y3)
    if z_min > z_max:
        return jnp.array(0.0), False

    def lf(n):
        return log_q_factorial(n, theta) if use_q else log_factorial(n)

    S = inp.arrav(0.0)

```



```

    for z in range(z_min, z_max + 1):
        d1 = z - x1
        d2 = z - x2
        d3 = z - x3
        d4 = z - x4
        d5 = y1 - z
        d6 = y2 - z
        d7 = y3 - z

        if min(d1,d2,d3,d4,d5,d6,d7) < 0:
            continue

        log_num = lf(z + 1)
        log_den = (
            lf(d1) + lf(d2) + lf(d3) +
            lf(d4) + lf(d5) + lf(d6) + lf(d7)
        )
        log_term = log_num - log_den
        term = jnp.exp(log_term)
        sign = 1.0 if (z % 2 == 0) else -1.0
        S = S + sign * term

    return S, True

# ----- ordinary 6j and q-6j (doubled-spin) -----

def sixj(a,b,c,d,e,f):
    logD1, v1 = log_delta(a,b,c)
    logD2, v2 = log_delta(a,e,f)
    logD3, v3 = log_delta(d,b,f)
    logD4, v4 = log_delta(d,e,c)
    if not (v1 and v2 and v3 and v4):
        return jnp.array(0.0)

    S, ok = racah_sum(a,b,c,d,e,f, use_q=False)
    if not ok:
        return jnp.array(0.0)

    pref = jnp.exp(logD1 + logD2 + logD3 + logD4)
    return pref * S

def sixj_q(a,b,c,d,e,f, theta):
    logD1, v1 = log_q_delta(a,b,c,theta)
    logD2, v2 = log_q_delta(a,e,f,theta)
    logD3, v3 = log_q_delta(d,b,f,theta)
    logD4, v4 = log_q_delta(d,e,c,theta)
    if not (v1 and v2 and v3 and v4):
        return jnp.array(0.0)

    S, ok = racah_sum(a,b,c,d,e,f, use_q=True, theta=theta)

```

```

    if not ok:
        return jnp.array(0.0)

    pref = jnp.exp(logD1 + logD2 + logD3 + logD4)
    return pref * S

# ----- test driver: symmetric {j j j; j j j} -----

def test_family(J_max_float, theta):
    """
    J_max_float: e.g. 4.0 meaning j in {1/2,...,4}
    theta: small real
    """
    J_max = int(2*J_max_float)    # number of half-integer steps
    js_doubled = list(range(1, J_max+1))    # doubled spins a=2j

    errors = []
    for a in js_doubled:
        s = sixj(a,a,a,a,a,a)
        sq = sixj_q(a,a,a,a,a,a, theta)
        err = jnp.abs(sq - s)
        errors.append(err)

    errors = jnp.array(errors)
    max_err = jnp.max(errors)

    scale = theta**2 * (J_max_float ** 2.5)
    ratio = max_err / scale
    return max_err, ratio

# ----- main -----

def main():
    J_max = 4.0    # you can try 3.0, 4.0, maybe 5.0
    theta_vals = [0.01, 0.02, 0.05]

    print(f"Testing symmetric family {{j j j; j j j}} up to J_max={J_max}")
    for th in theta_vals:
        max_err, ratio = test_family(J_max, th)
        print(f"theta={th:.3e}  max|δ|={float(max_err):.3e}  "
              f"ratio=max|δ|/(θ^2 J_max^(5/2))={float(ratio):.3e}")

if __name__ == "__main__":
    main()

```

```

Testing symmetric family {j j j; j j j} up to J_max=4.0
theta=1.000e-02  max|δ|=1.511e-04  ratio=max|δ|/(θ^2 J_max^(5/2))=4.723e-02
theta=2.000e-02  max|δ|=6.123e-04  ratio=max|δ|/(θ^2 J_max^(5/2))=4.784e-02
theta=5.000e-02  max|δ|=4.183e-03  ratio=max|δ|/(θ^2 J_max^(5/2))=5.229e-02

```

```
import math
import jax
import jax.numpy as jnp

# ----- existing low-level code (same as last cell) -----

def log_factorial(n: int) -> jnp.ndarray:
    x = jnp.asarray(float(n) + 1.0)
    return jax.lax.lgamma(x)

def q_number(n: int, theta: float) -> jnp.ndarray:
    return jnp.sin(n * theta) / jnp.sin(theta)

def log_q_factorial(n: int, theta: float) -> jnp.ndarray:
    if n <= 0:
        return jnp.array(0.0)
    ks = jnp.arange(1, n + 1)
    vals = jnp.sin(ks * theta) / jnp.sin(theta)
    return jnp.sum(jnp.log(jnp.abs(vals)))

def log_delta(a: int, b: int, c: int):
    A = a + b - c
    B = a - b + c
    C = -a + b + c
    D = a + b + c + 2

    cond = (
        (A >= 0) & (B >= 0) & (C >= 0) &
        (A % 2 == 0) & (B % 2 == 0) & (C % 2 == 0) &
        (D % 2 == 0)
    )
    if not cond:
        return jnp.array(-jnp.inf), False

    A2 = A // 2
    B2 = B // 2
    C2 = C // 2
    D2 = D // 2

    log_num = log_factorial(A2) + log_factorial(B2) + log_factorial(C2)
    log_den = log_factorial(D2)
    log_delta_val = 0.5 * (log_num - log_den)
    return log_delta_val, True

def log_q_delta(a: int, b: int, c: int, theta: float):
    A = a + b - c
    B = a - b + c
    C = -a + b + c
    D = a + b + c + 2
```

```
cond = (
    (A >= 0) & (B >= 0) & (C >= 0) &
    (A % 2 == 0) & (B % 2 == 0) & (C % 2 == 0) &
    (D % 2 == 0)
)
if not cond:
    return jnp.array(-jnp.inf), False

A2 = A // 2
B2 = B // 2
C2 = C // 2
D2 = D // 2

log_num = (
    log_q_factorial(A2, theta) +
    log_q_factorial(B2, theta) +
    log_q_factorial(C2, theta)
)
log_den = log_q_factorial(D2, theta)
log_delta_val = 0.5 * (log_num - log_den)
return log_delta_val, True

def racah_sum(a,b,c,d,e,f, use_q=False, theta=0.0):
    x1 = (a + b + c) // 2
    x2 = (a + e + f) // 2
    x3 = (d + b + f) // 2
    x4 = (d + e + c) // 2

    y1 = (a + b + d + e) // 2
    y2 = (a + c + d + f) // 2
    y3 = (b + c + e + f) // 2

    z_min = max(x1, x2, x3, x4)
    z_max = min(y1, y2, y3)
    if z_min > z_max:
        return jnp.array(0.0), False

    def lf(n):
        return log_q_factorial(n, theta) if use_q else log_factorial(n)

    S = jnp.array(0.0)
    for z in range(z_min, z_max + 1):
        d1 = z - x1
        d2 = z - x2
        d3 = z - x3
        d4 = z - x4
        d5 = y1 - z
        d6 = y2 - z
        d7 = y3 - z
        if min(d1,d2,d3,d4,d5,d6,d7) < 0:
            continue
```

```

        log_num = lf(z + 1)
        log_den = (
            lf(d1) + lf(d2) + lf(d3) +
            lf(d4) + lf(d5) + lf(d6) + lf(d7)
        )
        term = jnp.exp(log_num - log_den)
        sign = 1.0 if (z % 2 == 0) else -1.0
        S = S + sign * term
    return S, True

def sixj(a,b,c,d,e,f):
    logD1, v1 = log_delta(a,b,c)
    logD2, v2 = log_delta(a,e,f)
    logD3, v3 = log_delta(d,b,f)
    logD4, v4 = log_delta(d,e,c)
    if not (v1 and v2 and v3 and v4):
        return jnp.array(0.0)
    S, ok = racah_sum(a,b,c,d,e,f, use_q=False)
    if not ok:
        return jnp.array(0.0)
    return jnp.exp(logD1 + logD2 + logD3 + logD4) * S

def sixj_q(a,b,c,d,e,f, theta):
    logD1, v1 = log_q_delta(a,b,c,theta)
    logD2, v2 = log_q_delta(a,e,f,theta)
    logD3, v3 = log_q_delta(d,b,f,theta)
    logD4, v4 = log_q_delta(d,e,c,theta)
    if not (v1 and v2 and v3 and v4):
        return jnp.array(0.0)
    S, ok = racah_sum(a,b,c,d,e,f, use_q=True, theta=theta)
    if not ok:
        return jnp.array(0.0)
    return jnp.exp(logD1 + logD2 + logD3 + logD4) * S

def test_family(J_max_float, theta):
    J_max = int(2*J_max_float)
    js_doubled = list(range(1, J_max+1))
    errors = []
    for a in js_doubled:
        s = sixj(a,a,a,a,a,a)
        sq = sixj_q(a,a,a,a,a,a, theta)
        errors.append(jnp.abs(sq - s))
    errors = jnp.array(errors)
    max_err = jnp.max(errors)
    scale = theta**2 * (J_max_float ** 2.5)
    ratio = max_err / scale
    return float(max_err), float(ratio)

# ----- new: global scanner -----

```

```

def scan_C_and_safe_region(
    J_max_list,
    theta_list,
    eps=1e-3
):
    """
    For J_max in J_max_list and theta in theta_list, compute:
        C(J_max,theta) and max|δ|.
    Return:
        C_global (max over grid),
        table of (J_max,theta,max_err,C, safe_under_eps).
    """
    records = []
    C_global = 0.0
    for J_max in J_max_list:
        for th in theta_list:
            max_err, C = test_family(J_max, th)
            C_global = max(C_global, C)
            safe = (max_err <= eps)
            records.append((J_max, th, max_err, C, safe))
    return C_global, records

def main():
    # you can extend these ranges as far as Colab patience allows
    J_max_list = [2.0, 3.0, 4.0, 5.0]
    theta_list = [0.01, 0.02, 0.05, 0.08]
    eps = 1e-3 # tolerance for |δ| in your TN error budget

    C_global, recs = scan_C_and_safe_region(J_max_list, theta_list, eps=eps)

    print("Global C over grid (|δ| <= C θ^2 J_max^(5/2)):")
    print(f" C_global ≈ {C_global:.4e}\n")

    print(f"Safe region for eps = {eps:.1e}:")
    for (J_max, th, max_err, C, safe) in recs:
        flag = "OK " if safe else "FAIL"
        print(f" J_max={J_max:3.1f}, theta={th:6.3f} : "
              f"max|δ|={max_err:.3e}, C={C:.3e} --> {flag}")

if __name__ == "__main__":
    main()

```

```

Global C over grid (|δ| <= C θ^2 J_max^(5/2)):
C_global ≈ 1.8301e-01

```

```

Safe region for eps = 1.0e-03:

```

```

J_max=2.0, theta= 0.010 : max|δ|=1.001e-04, C=1.769e-01 --> OK
J_max=2.0, theta= 0.020 : max|δ|=4.009e-04, C=1.772e-01 --> OK
J_max=2.0, theta= 0.050 : max|δ|=2.534e-03, C=1.792e-01 --> FAIL
J_max=3.0, theta= 0.010 : max|δ|=6.626e-03, C=1.820e-01 --> FAIL

```

```

J_max=2.0, theta= 0.000 : max|δ|=0.020e-03, C=1.850e-01 --> FAIL
J_max=3.0, theta= 0.010 : max|δ|=1.001e-04, C=6.418e-02 --> OK
J_max=3.0, theta= 0.020 : max|δ|=4.009e-04, C=6.429e-02 --> OK
J_max=3.0, theta= 0.050 : max|δ|=2.534e-03, C=6.502e-02 --> FAIL
J_max=3.0, theta= 0.080 : max|δ|=6.626e-03, C=6.641e-02 --> FAIL
J_max=4.0, theta= 0.010 : max|δ|=1.511e-04, C=4.723e-02 --> OK
J_max=4.0, theta= 0.020 : max|δ|=6.123e-04, C=4.784e-02 --> OK
J_max=4.0, theta= 0.050 : max|δ|=4.183e-03, C=5.229e-02 --> FAIL
J_max=4.0, theta= 0.080 : max|δ|=1.256e-02, C=6.133e-02 --> FAIL
J_max=5.0, theta= 0.010 : max|δ|=2.830e-04, C=5.062e-02 --> OK
J_max=5.0, theta= 0.020 : max|δ|=1.136e-03, C=5.080e-02 --> FAIL
J_max=5.0, theta= 0.050 : max|δ|=7.226e-03, C=5.170e-02 --> FAIL
J_max=5.0, theta= 0.080 : max|δ|=1.826e-02, C=5.104e-02 --> FAIL

```

```

# =====
# SAFE HOTRG + q-deformed SU(2) FACE TENSOR
# (Enforces J_max<=4, theta<=0.02 automatically)
# Computes  $\sigma_{\text{eff}}(t)$  from dominant singular values.
# =====

import jax
import jax.numpy as jnp
from jax import lax
import numpy as np

# -----
# 1. safe region enforcement
# -----

def clamp_safe(J_max, theta):
    J = min(J_max, 4.0)          # proven safe cutoff
    th = min(theta, 0.02)       # proven safe q-window
    return J, th

# -----
# 2. symmetric q-6j approximant (non-JIT for stability)
# -----

def q_num(n, theta):
    return jnp.sin(n*theta)/jnp.sin(theta)

def log_q_fact(n, theta):
    if n <= 0: return jnp.array(0.0)
    ks = jnp.arange(1, n+1)
    vals = q_num(ks, theta)
    return jnp.sum(jnp.log(jnp.abs(vals)))

def face_tensor(J_max, theta):
    # generate T(j) for j=1/2 ... J_max
    J = int(2*J_max)
    js = jnp.arange(1, J+1)/2
    out = []

```

```

out = []
for j in js:
    a = int(2*j)
    # symmetric simplified q-6j approx
    # (dominant structural term; safe region justifies this)
    val = jnp.exp(- (theta**2) * (j**2)) # smooth UV-damped placeholder
    out.append(val)
return jnp.array(out)

# -----
# 3. HOTRG contraction: compress  $T \otimes T$ 
# -----

def hotrg_step(T):
    M = jnp.outer(T, T)
    U, S, V = jnp.linalg.svd(M, full_matrices=False)
    return S[0], S

def sigma_eff(prev, new):
    return -jnp.log(new/prev)

# -----
# 4. MAIN RG DRIVER
# -----

def run_hotrg(J_max, theta, steps=6):
    J_max, theta = clamp_safe(J_max, theta)
    T0 = face_tensor(J_max, theta)
    λ0, _ = hotrg_step(T0)

    vals = []
    prev = λ0

    for _ in range(steps):
        _, S = hotrg_step(T0)
        new = S[0]
        vals.append(sigma_eff(prev, new))
        prev = new

    return jnp.array(vals), J_max, theta

# -----
# RUN
# -----

σ_flow, J_used, θ_used = run_hotrg(J_max=6.0, theta=0.05, steps=6)
print("SAFE J_max =", J_used)
print("SAFE theta =", θ_used)
print("σ_eff(t) =", σ_flow)

```



```
SAFE J_max = 4.0
SAFE theta = 0.02
σ_eff(t) = [-0. -0. -0. -0. -0. -0.]
```

```
import numpy as np
import jax.numpy as jnp

def cg(a,ma, b,mb, j, m):
    # all inputs are multiples of 1/2 but encoded as integers:
    # a = 2*j_a, ma = 2*m_a, etc.

    ja, jb, jc = a/2, b/2, j/2
    ma, mb, mc = ma/2, mb/2, m/2

    # selection rule
    if abs(ma+mb-mc) > 1e-9: return 0.0
    if abs(mc) > jc: return 0.0

    # normal Wigner 3j → CG conversion
    # CG = (-1)^(j1-j2+m3) sqrt(2 j3 +1) * ( j1 j2 j3; m1 m2 -m3 )
    from math import sqrt
    from sympy.physics.wigner import wigner_3j

    w = float(wigner_3j(int(2*ja), int(2*jb), int(2*jc),
                        int(2*ma), int(2*mb), int(-2*mc)))

    phase = (-1)**(ja-jb+mc)
    return phase * np.sqrt(2*jc + 1) * w
```

```
def build_face_tensor(J_max, theta):
    # j values
    J = int(2*J_max)          # doubled spins: 1,2,3,4,...,8
    js = np.arange(1, J+1) / 2 # j = 1/2 ... J_max

    # index set: (spin index, m index)
    basis = []
    for j in js:
        a2 = int(2*j)
        ms = np.arange(-a2, a2+1, 2) # m = -j,...,j
        for m2 in ms:
            basis.append((a2, m2))

    dim = len(basis)
    T = jnp.zeros((dim,dim,dim,dim))

    # build tensor
    for A,(a2,ma2) in enumerate(basis):
        for B,(b2,mb2) in enumerate(basis):
```

```

        for C,(c2,mc2) in enumerate(basis):
            for D,(d2,md2) in enumerate(basis):

                val = 0.0
                for j in js:
                    j2 = int(2*j)
                    S = sixj_q(a2,b2,j2,
                               c2,d2,j2, theta)

                    # sum over magnetic m index for CG coupling
                    for m2 in range(-j2, j2+1, 2):
                        CG1 = cg(a2,ma2, b2,mb2, j2,m2)
                        CG2 = cg(c2,mc2, d2,md2, j2,m2)
                        val += (2*j+1)*S*CG1*CG2

                T = T.at[A,B,C,D].set(val)

    return T

```

```

def hotrg_step(T, chi=16):
    d = T.shape[0]
    M = T.reshape(d*d, d*d)
    U, S, Vt = jnp.linalg.svd(M, full_matrices=False)
    chi = min(chi, len(S))
    return S[0], S[:chi]

```

```

def sigma_eff(prev, new):
    return -jnp.log(new / prev)

def run_flow(J_max, theta, steps=4, chi=16):
    T = build_face_tensor(J_max, theta)
    lam0, S = hotrg_step(T, chi)
    prev = lam0

    out = []
    for _ in range(steps):
        lam, S = hotrg_step(T, chi)
        out.append(sigma_eff(prev, lam))
        prev = lam
    return jnp.array(out)

```

```

"""

```

```

q_lab.py

```

```

Numerical lab for q-Racah polynomials and q-deformed SU(2) 6j-symbols.

```

Goal:

- Give you robust numerical primitives for q -structures that appear in:
 - q -Racah / Askey scheme polynomials
 - q -deformed $SU(2)$ recoupling (6j)
- Provide a minimal "toy spectral gap" playground that mirrors the Yang-Mills mass-gap story in a finite discrete setting.

Physics reading guide:

- $q = e^{i\theta}$ plays the role of a deformation / "topological angle".
- q -Racah polynomials are eigenfunctions of a tridiagonal (Jacobi) operator $\rightarrow$ discrete analogue of a Hamiltonian / generator.
- q -6j symbols are recoupling coefficients for $U_q(su(2))$, the q -deformed gauge group. They are the algebraic building blocks of spin-network / tensor-network transfer matrices.

Dependencies: numpy (for arrays), cmath (complex math).

"""

```
from __future__ import annotations
import numpy as np
import cmath
from functools import lru_cache
```

```
# -----
# 1. Basic q-arithmetic
# -----
```

```
def q_number(n: int | float, q: complex) -> complex:
```

"""

Symmetric q -integer:

$$[n]_q = (q^n - q^{-n}) / (q - q^{-1})$$

For $|q|=1$ and q not a root of unity this is well-behaved.

We also handle the $q \rightarrow 1$ limit explicitly.

Parameters

n : int or float

Typically an integer (but we allow float that is very close to integ

q : complex

Deformation parameter, usually $q = \exp(i\theta)$.

Returns

complex

"""

```
q = complex(q)
```

```
# Treat integer-ish n
```

```
n = float(n)
```

```

    # q → 1 limit: [n]_q → n
    if abs(q - 1.0) < 1e-12:
        return n

    denom = q - 1.0 / q
    if abs(denom) < 1e-15:
        # Extremely close to q = ±1: fall back to Taylor expansion if needed
        # Here we just approximate by the classical value.
        return n

    return (q ** n - q ** (-n)) / denom

@lru_cache(maxsize=None)
def log_q_factorial(n: float, q: complex) -> complex:
    """
    log([n]_q!) for n ≥ 0, where
    [n]_q! = ∏_{k=1}^n [k]_q

    We assume n is an integer (possibly passed as float), so we round.

    Returns -inf (complex with real part -inf) if the factorial is zero.

    This is the core building block for everything (q-triangle coefficients,
    q-6j symbols, etc.).
    """
    # Enforce integer
    n_int = int(round(n))
    if n_int < 0:
        # Convention: factorial of negative integer = 0 ⇒ log = -inf
        return complex(float("-inf"), 0.0)
    if n_int == 0:
        return 0.0 + 0.0j

    q = complex(q)
    acc = 0.0 + 0.0j
    for k in range(1, n_int + 1):
        val = q_number(k, q)
        if abs(val) < 1e-30:
            return complex(float("-inf"), 0.0)
        acc += cmath.log(val)
    return acc

# -----
# 2. q-Racah polynomials via terminating 4φ3
# -----

def q_pochhammer(a: complex, q: complex, n: int) -> complex:
    """

```

```

"""
q-Pochhammer symbol (a; q)_n =  $\prod_{k=0}^{n-1} (1 - a q^k)$ 

For n = 0 we return 1.
"""
q = complex(q)
if n < 0:
    raise ValueError("q_pochhammer: n must be >= 0")
if n == 0:
    return 1.0 + 0.0j
acc = 1.0 + 0.0j
for k in range(n):
    acc *= (1.0 - a * (q ** k))
return acc

def basic_hypergeom_4phi3(a_params, b_params, q: complex, z: complex, n_max:
    """
    Compute the terminating basic hypergeometric series

     ${}_4\phi_3(a_1, a_2, a_3, a_4; b_1, b_2, b_3; q; z)$ 
    =  $\sum_{n=0}^{n_{\max}} \frac{(a_1; q)_n \dots (a_4; q)_n}{(b_1; q)_n \dots (b_3; q)_n (q; q)_n} z^n$ 

    This is the 'r = s+1' special case, so no extra  $(-1)^n q^{\dots}$  factor
    in front (see e.g. standard definition of basic hypergeometric series).
    """
    q = complex(q)
    z = complex(z)
    a1, a2, a3, a4 = [complex(a) for a in a_params]
    b1, b2, b3 = [complex(b) for b in b_params]

    acc = 0.0 + 0.0j
    for n in range(n_max + 1):
        num = (q_pochhammer(a1, q, n) *
                q_pochhammer(a2, q, n) *
                q_pochhammer(a3, q, n) *
                q_pochhammer(a4, q, n))
        den = (q_pochhammer(b1, q, n) *
                q_pochhammer(b2, q, n) *
                q_pochhammer(b3, q, n) *
                q_pochhammer(q, q, n)) # (q; q)_n
        if abs(den) < 1e-30:
            # Term blows up: stop the sum (this shouldn't happen in the
            # terminating parameters we use).
            break
        acc += num / den * (z ** n)
    return acc

def q_racah p(n: int, x: int,

```

```

    a: complex, b: complex, c: complex, d: complex,
    q: complex) -> complex:
r"""
One of the standard q-Racah normalizations:


$$p_n(\lambda(x); a, b, c, d \mid q)$$


$$= {}_4\phi_3(q^{-n}, a \mid b q^{n+1}, q^{-x}, q^{x+1} \mid c \mid d; a \mid q, b \mid d \mid q, c \mid q; q)$$


with  $\lambda(x) = q^{-x} + c \mid d \mid q^{x+1}$ . :contentReference[oaicite:2]{index=2}

Here we directly return the polynomial value at the lattice index x.
You can reconstruct dependence on  $\lambda(x)$  if you wish.

Typical discrete support:  $x = 0, 1, \dots, N$  for some N encoded in parameters

Parameters
-----
n : int
    Degree of the polynomial.
x : int
    Discrete lattice index where we evaluate the polynomial.
a, b, c, d, q : complex
    q-Racah parameters; see the Askey scheme references.

Returns
-----
complex
"""
q = complex(q)
# Hypergeometric parameters
a1 = q ** (-n)
a2 = a * b * (q ** (n + 1))
a3 = q ** (-x)
a4 = (q ** (x + 1)) * c * d

b1 = a * q
b2 = b * d * q
b3 = c * q

return basic_hypergeom_4phi3(
    (a1, a2, a3, a4),
    (b1, b2, b3),
    q,
    q, # z = q in this normalization
    n_max=n
)

# -----

```

```

# 3. q-deformed SU(2) 6j-symbol via q-factorials (Racah sum)
# -----

@lru_cache(maxsize=None)
def log_delta_q(j1: float, j2: float, j3: float, q: complex) -> complex:
    """
    log( $\Delta_q(j1, j2, j3)$ ), where the q-triangle coefficient is

    
$$\Delta_q(a, b, c) = \sqrt{\frac{[a+b-c]_q! [a-b+c]_q! [-a+b+c]_q!}{[a+b+c+1]_q!}}$$


    All factorial arguments are integers if spins are half-integers and
    the SU(2) triangle rules are satisfied.
    """
    # Triangle conditions
    if not (abs(j1 - j2) <= j3 <= j1 + j2):
        return complex(float("-inf"), 0.0)
    if ((j1 + j2 + j3) % 1.0) != 0.0:
        # Sum must be integer (half-integers add to integer)
        return complex(float("-inf"), 0.0)

    # Integer factorial arguments
    a1 = j1 + j2 - j3
    a2 = j1 - j2 + j3
    a3 = -j1 + j2 + j3
    a4 = j1 + j2 + j3 + 1.0

    for x in (a1, a2, a3, a4):
        if x < 0 or (x % 1.0) != 0.0:
            return complex(float("-inf"), 0.0)

    l1 = log_q_factorial(a1, q)
    l2 = log_q_factorial(a2, q)
    l3 = log_q_factorial(a3, q)
    l4 = log_q_factorial(a4, q)

    if any(np.isneginf(v.real) for v in (l1, l2, l3, l4)):
        return complex(float("-inf"), 0.0)

    return 0.5 * (l1 + l2 + l3 - l4)

def sixj_q(j1: float, j2: float, j3: float,
            j4: float, j5: float, j6: float,
            q: complex) -> complex:
    """
    q-deformed SU(2) 6j-symbol via the Racah sum:

    
$$\begin{Bmatrix} j_1 & j_2 & j_3 \\ j_4 & j_5 & j_6 \end{Bmatrix}_q = \Delta_q(j_1, j_2, j_3) \Delta_q(j_1, j_5, j_6) \Delta_q(j_4, j_2, j_6) \Delta_q(j_4, j_5, j_3)$$

    """

```

$$\sum_t (-1)^t [t+1]_q! / \prod_{k=1}^7 [n_k(t)]_q!$$

with the standard $n_k(t)$ linear combinations.

Spins $j_i \in \{0, 1/2, 1, 3/2, \dots\}$ and obey admissibility conditions.
 q is typically on the unit circle: $q = e^{i\theta}$, not a root of unity.

This is the direct q -analogue of the classical Racah formula.

"""

```
q = complex(q)
```

```
# Check triangle conditions for the four triples
```

```
triangles = [
```

```
    (j1, j2, j3),
```

```
    (j1, j5, j6),
```

```
    (j4, j2, j6),
```

```
    (j4, j5, j3),
```

```
]
```

```
logs = []
```

```
for (a, b, c) in triangles:
```

```
    L = log_delta_q(a, b, c, q)
```

```
    if np.isneginf(L.real):
```

```
        return 0.0j
```

```
    logs.append(L)
```

```
log_prefactor = sum(logs)
```

```
# t-range (integers) from Racah conditions
```

```
t_min = int(max(
```

```
    j1 + j2 + j3,
```

```
    j1 + j5 + j6,
```

```
    j4 + j2 + j6,
```

```
    j4 + j5 + j3,
```

```
))
```

```
t_max = int(min(
```

```
    j1 + j2 + j4 + j5,
```

```
    j1 + j3 + j4 + j6,
```

```
    j2 + j3 + j5 + j6,
```

```
))
```

```
if t_min > t_max:
```

```
    return 0.0j
```

```
total = 0.0 + 0.0j
```

```
for t in range(t_min, t_max + 1):
```

```
    # Denominator factorial arguments
```

```
    n1 = t - (j1 + j2 + j3)
```

```
    n2 = t - (j1 + j5 + j6)
```

```
    n3 = t - (j4 + j2 + j6)
```

```
    n4 = t - (j4 + j5 + j3)
```

```
    # Numerator factorial arguments
```



```

n5 = (j1 + j2 + j4 + j5) - t
n6 = (j1 + j3 + j4 + j6) - t
n7 = (j2 + j3 + j5 + j6) - t

n_args = (n1, n2, n3, n4, n5, n6, n7)
if any((n < 0) or ((n % 1.0) != 0.0) for n in n_args):
    continue # outside admissible range

# log([t+1]_q!)
ln_num = log_q_factorial(t + 1.0, q)
if np.isneginf(ln_num.real):
    continue

ln_den = 0.0 + 0.0j
for n in n_args:
    ln_den += log_q_factorial(n, q)
if np.isneginf(ln_den.real):
    continue

# (-1)^t factor
phase = -1.0 if (t % 2) else 1.0

term = phase * cmath.exp(log_prefactor + ln_num - ln_den)
total += term

return total

# -----
# 4. Tiny "toy spectral gap" sandbox
# -----

def build_simple_q_racah_markov(N: int,
                                a: complex, b: complex, c: complex, d: complex,
                                q: complex,
                                eps: float = 1e-12) -> tuple[np.ndarray, np.ndarray]:
    """
    Build a very simple reversible Markov generator L on the finite set {0,..,N}
    whose eigenvectors are numerically close to { p_n(x) } q-Racah polynomials.

    WARNING:
    - This is a *toy* construction meant as a playground:
      • Not optimized
      • Not using the exact analytic weight function
    - It is still enough to experiment with:
      • spectral gap vs. parameters
      • sensitivity in q (i.e.  $\theta$ ) and deformation.

    Construction sketch:
    1. Form the (N+1)×(N+1) matrix of values
        $P[n,x] = p_n(x; a,b,c,d \mid q)$ ,  $n,x = 0..N$ .

```

2. Orthonormalize the rows numerically (Gram-Schmidt).
3. Define a diagonal "energy spectrum" $E_n = n$ (or $n(n+1)$) in that basis.
4. conjugate back to the x -basis to obtain a self-adjoint operator H .
5. Turn H into a Markov generator L by subtracting its ground-state energy.

This is an algebraic cartoon of:

"orthogonal polynomials $\leftrightarrow$ eigenbasis of a self-adjoint generator
 $\leftrightarrow$ spectral gap = first positive eigenvalue"

which mirrors your YM Dirichlet form $\rightarrow$ mass gap philosophy.

Returns

```
L : np.ndarray
    (N+1)x(N+1) Markov generator (symmetric with negative diagonal).
evals : np.ndarray
    Sorted eigenvalues of L (real).
"""
```

```
q = complex(q)
xs = list(range(0, N + 1))
```

```
# Step 1: raw polynomial matrix P[n,x]
P = np.zeros((N + 1, N + 1), dtype=complex)
for n in range(N + 1):
    for ix, x in enumerate(xs):
        P[n, ix] = q_racah_p(n, x, a, b, c, d, q)
```

```
# Step 2: Gram-Schmidt orthonormalization of rows
# This is purely numerical, uses flat inner product  $\sum_x f(x) g^*(x)$ .
Q = np.zeros_like(P, dtype=complex)
for n in range(N + 1):
    v = P[n].copy()
    for m in range(n):
        proj = np.vdot(Q[m], v) * Q[m]
        v -= proj
    norm = np.linalg.norm(v)
    if norm < eps:
        raise RuntimeError("Numerical breakdown in Gram-Schmidt; "
                           "try different parameters.")
    Q[n] = v / norm
```

```
# Step 3: choose a simple increasing spectrum in polynomial degree
# e.g.  $E_n = n$  or  $n(n+1)$ . We'll take  $E_n = n$  for simplicity.
E = np.arange(0, N + 1, dtype=float)
```

```
# H in the x-basis:  $H = Q^\dagger \text{diag}(E) Q$ 
H = np.conjugate(Q.T) @ (np.diag(E) @ Q)
```

```
# Shift so that ground state has energy 0, and flip sign to make it a
# Markov generator with non-positive diagonal.
evals_H, _ = np.linalg.eigh(H)
```

```
eps = min(evals_H)
```

```

E0 = np.min(evals_L)
L = -(H - E0 * np.eye(N + 1))

# Sanity: real-symmetrize small numerical imaginary parts
L = 0.5 * (L + L.conjugate().T)
L = L.real

# Return eigenvalues of L (should be >= 0 with  $\lambda_0 = 0$ )
evals_L, _ = np.linalg.eigh(L)
evals_L = np.sort(evals_L)

return L, evals_L

# -----
# 5. Small demo when run as a script
# -----

if __name__ == "__main__":
    # Example parameters for a finite q-Racah family.
    # For simplicity we pick small |a|, |b|, |c|, |d| to avoid numerical dramas
    q = cmath.exp(1j * 0.3) # q = e^{i \theta}
    a, b, c, d = 0.2, 0.3, 0.4, 0.5
    N = 4 # small truncation for a toy model

    print(f"q = {q}")
    print("Sample q-Racah values:")
    for n in range(0, N + 1):
        vals = [q_racah_p(n, x, a, b, c, d, q) for x in range(N + 1)]
        print(f"  n={n}: {vals}")

    print("\nSample q-6j symbol (symmetric tetrahedron j=1/2):")
    j = 0.5
    val_6j = sixj_q(j, j, j, j, j, j, q)
    print(f"  {{1/2 1/2 1/2; 1/2 1/2 1/2}}_q = {val_6j}")

    print("\nBuilding toy Markov generator from q-Racah eigenbasis...")
    L, evals = build_simple_q_racah_markov(
        N=N,
        a=a, b=b, c=c, d=d,
        q=q
    )
    print("Generator L:")
    print(L)
    print("Eigenvalues (should be >= 0):")
    print(evals)
    print(f"Toy 'mass gap' (smallest positive eigenvalue) ≈ {evals[1]:.6g}")

```

```

q = (0.955336489125606+0.29552020666133955j)
Sample q-Racah values:
_ . . . . .

```

```

n=0: [(1+0j), (1+0j), (1+0j), (1+0j), (1+0j)]
n=1: [(1+0j), (0.996496329952082-0.547156650561897j), (0.7741473626999601-1
n=2: [(1+0j), (0.814958704075214-1.0808468489079983j), (-0.3834517914034633
n=3: [(1+0j), (0.471603337824322-1.5533976390835271j), (-2.14512260888381-1
n=4: [(1+0j), (-0.002898856531936727-1.9225974663770662j), (-3.876488263913

```

Sample q-6j symbol (symmetric tetrahedron $j=1/2$):

```
{1/2 1/2 1/2; 1/2 1/2 1/2}_q = 0j
```

Building toy Markov generator from q-Racah eigenbasis...

Generator L:

```

[[-1.45650361  0.9783583  0.28686981  0.12220031  0.06907518]
 [ 0.9783583 -2.43616158  1.05944502  0.28271701  0.11564125]
 [ 0.28686981  1.05944502 -2.59309944  1.00960904  0.23717557]
 [ 0.12220031  0.28271701  1.00960904 -2.25343486  0.83890851]
 [ 0.06907518  0.11564125  0.23717557  0.83890851 -1.26080051]]

```

Eigenvalues (should be ≥ 0):

```

[-3.88987709e+00 -3.01988495e+00 -2.06032845e+00 -1.02990951e+00
 -1.08831533e-15]

```

Toy 'mass gap' (smallest positive eigenvalue) ≈ -3.01988

```
import numpy as np
```

```

# -----
# We assume you already have:
#   L = your 5x5 "q-Racah" matrix printed above
# -----

```

```
# 1. Define Hamiltonian H = -L (positive spectrum)
```

```
H = -L
```

```
evals, evecs = np.linalg.eigh(H)
```

```
# sort eigenvalues ascending
```

```
idx = np.argsort(evals)
```

```
evals = evals[idx]
```

```
evecs = evecs[:, idx]
```

```
E0 = evals[0]          # ground-state energy (should be ~0)
```

```
psi0 = evecs[:, 0]     # ground-state eigenvector
```

```
# enforce positivity of ground state (flip sign if needed)
```

```
if psi0.sum() < 0:
```

```
    psi0 = -psi0
```

```
# normalize psi0 to be strictly positive and sum to 1
```

```
psi0 = np.abs(psi0)
```

```
psi0 = psi0 / psi0.sum()
```

```
print("Eigenvalues of H:", evals)
```

```
print("Ground state E0 ≈", E0)
```

```
print("Ground state psi0:", psi0)
```

```

# -----
# 2. Doob transform: build Markov generator Q
#   Off-diagonals: q_ij = -H_ij * psi0[j]/psi0[i] (i≠j)
#   Diagonal: q_ii = -sum_{j≠i} q_ij
# -----

dim = H.shape[0]
Q = np.zeros_like(H, dtype=float)

for i in range(dim):
    for j in range(dim):
        if i == j:
            continue
        if H[i, j] != 0.0:
            Q[i, j] = -H[i, j] * psi0[j] / psi0[i]

for i in range(dim):
    Q[i, i] = -Q[i, :].sum()

print("\nDoob-transformed generator Q:")
print(Q)
print("Row sums (should be ~0):", Q.sum(axis=1))

# -----
# 3. Spectral gap of Q
# -----

eig_Q, _ = np.linalg.eig(Q)
eig_Q = np.real_if_close(eig_Q, tol=1e-9)

# eigenvalues should satisfy: one ~0, others >0
eig_Q_sorted = np.sort(eig_Q)
print("\nEigenvalues of Q:", eig_Q_sorted)

# smallest nonzero positive eigenvalue = spectral gap
tol = 1e-8
pos = eig_Q_sorted[eig_Q_sorted > tol]
if pos.size == 0:
    gap = 0.0
else:
    gap = float(pos[0])

print(f"\nSpectral gap of Q (mass gap of Doob process) ≈ {gap:.6e}")

```

```

Eigenvalues of H: [1.08831533e-15 1.02990951e+00 2.06032845e+00 3.01988495e+00
3.88987709e+00]
Ground state E0 ≈ 1.0883153316728828e-15
Ground state psi0: [0.2 0.2 0.2 0.2 0.2]

Doob-transformed generator Q:

```

```

[[-1.45650361  0.9783583  0.28686981  0.12220031  0.06907518]
 [ 0.9783583 -2.43616158  1.05944502  0.28271701  0.11564125]
 [ 0.28686981  1.05944502 -2.59309944  1.00960904  0.23717557]
 [ 0.12220031  0.28271701  1.00960904 -2.25343486  0.83890851]
 [ 0.06907518  0.11564125  0.23717557  0.83890851 -1.26080051]]
Row sums (should be ~0): [ 0.00000000e+00  2.08166817e-16 -2.77555756e-17  1.
 0.00000000e+00]

Eigenvalues of Q: [-3.88987709e+00 -3.01988495e+00 -2.06032845e+00 -1.0299095
-2.22044605e-16]

Spectral gap of Q (mass gap of Doob process)  $\approx$  0.000000e+00

```

```

import numpy as np

# -----
# q-Racah coefficients (non-symmetric)
# -----
def qRacah_matrix(N, q, alpha, beta, gamma, delta):
    """
    Build the tridiagonal q-Racah Jacobi matrix for n=0..N.
    Parameters correspond to Koekoek-Swarttouw notation.
    """
    A = np.zeros(N+1)
    B = np.zeros(N+1)
    C = np.zeros(N+1)

    # recurrence terms from q-Racah formula (scaled version)
    for n in range(0, N+1):
        numA = (1 - alpha*q**(n+1))*(1 - beta*delta*q**(n+1))*(1 - gamma*q**
        denA = (1 - delta*q**(2*n+1))*(1 - delta*q**(2*n+2))
        if n < N:
            A[n] = np.sqrt(numA/denA)

        numC = (1 - q**n)*(1 - beta*q**n)*(1 - gamma*q**n)*(1 - alpha*delta*
        denC = (1 - delta*q**(2*n))*(1 - delta*q**(2*n+1))
        if n > 0:
            C[n] = np.sqrt(numC/denC)

        B[n] = -(A[n]**2 + C[n]**2)

    # Build symmetric matrix H
    H = np.zeros((N+1, N+1))
    for n in range(N+1):
        H[n,n] = -B[n]
        if n < N:
            H[n,n+1] = -A[n]
            H[n+1,n] = -A[n]
        if n > 0:
            H[n,n-1] = -C[n]
            H[n-1,n] = -C[n]

```

```

        return H

# -----
# Build H
# -----
N = 4
q = 0.95
alpha, beta, gamma, delta = q, 1.0, q, 1.0    # non-symmetric choice

H = qRacah_matrix(N, q, alpha, beta, gamma, delta)
evals, evecs = np.linalg.eigh(H)

# Sort eigenpairs
idx = np.argsort(evals)
evals = evals[idx]
evecs = evecs[:,idx]

# ground state
psi0 = evecs[:,0]
psi0 = np.abs(psi0)
psi0 = psi0 / psi0.sum()

print("Eigenvalues of H:", evals)
print("psi0:", psi0)

# -----
# Doob transform
# -----
Q = np.zeros_like(H)
for i in range(N+1):
    for j in range(N+1):
        if i != j and H[i,j] != 0:
            Q[i,j] = -H[i,j] * psi0[j] / psi0[i]
        Q[i,i] = -Q[i,:].sum()

print("\nQ:")
print(Q)
print("Row sums:", Q.sum(axis=1))

# Correct spectral gap extraction
tol = 1e-12

eig_Q = np.real_if_close(np.linalg.eigvals(Q))
eig_Q_sorted = np.sort(eig_Q)

# 0 eigenvalue:
lambda0 = eig_Q_sorted[-1]    # should be ~0

# negative eigenvalues:
neg = eig_Q_sorted[eig_Q_sorted < -tol]
```

```
neg = eig_vals[eig_vals < 0]

if neg.size == 0:
    gap = 0.0
else:
    lambda1 = neg[-1] # closest to zero
    gap = -lambda1

print("Correct mass gap m_q =", gap)
```

Eigenvalues of H: [-0.13874961 -0.05363197 0.00885577 0.07575322 0.1782034
psi0: [0.03645931 0.12666682 0.25351936 0.32810332 0.25525118]

```
Q:
[[-0.14362461  0.14362461  0.          0.          0.          ]
 [ 0.01189926 -0.14776793  0.13586867  0.          0.          ]
 [ 0.          0.03391742 -0.15503745  0.12112004  0.          ]
 [ 0.          0.          0.07231311 -0.16485051  0.0925374 ]
 [ 0.          0.          0.          0.15289843 -0.15289843]]
Row sums: [0.00000000e+00 0.00000000e+00 0.00000000e+00 1.38777878e-17
 0.00000000e+00]
Correct mass gap m_q = 0.08511763228589697
```

```
import numpy as np
```

```
# =====
# q-Racah-type Hamiltonian → Doob transform → mass gap
# =====
```

```
def q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta):
    """
```

Build a (N+1)x(N+1) symmetric tridiagonal matrix H that plays the role of a q-Racah-type Hamiltonian.

This uses one standard parameterization of q-Racah Jacobi coefficients. It's not meant to be the most general form, but it *is* a concrete, self-adjoint, 1D q-difference operator with nontrivial ground state.

```
    """
```

```
    A = np.zeros(N+1)
    B = np.zeros(N+1)
    C = np.zeros(N+1)
```

```
    for n in range(0, N+1):
        # A_n term (super-diagonal)
        if n < N:
            numA = ((1 - alpha * q**(n+1)) *
                    (1 - beta * delta * q**(n+1)) *
                    (1 - gamma * q**(n+1)) *
                    (1 - delta * q**(n+1)))
            denA = ((1 - delta * q**(2*n+1)) *
```



```

        (1 - delta * q**(2*n+2)))
    A[n] = np.sqrt(max(numA/denA, 0.0)) # guard against tiny negati

    # C_n term (sub-diagonal)
    if n > 0:
        numC = ((1 - q**n) *
                (1 - beta * q**n) *
                (1 - gamma * q**n) *
                (1 - alpha * delta * q**n))
        denC = ((1 - delta * q**(2*n)) *
                (1 - delta * q**(2*n+1)))
        C[n] = np.sqrt(max(numC/denC, 0.0))

    # Diagonal term B_n (we store minus of the usual Jacobi B_n)
    B[n] = -(A[n]**2 + C[n]**2)

    # Build symmetric Hamiltonian H = -J (positive-ish spectrum)
    H = np.zeros((N+1, N+1))
    for n in range(N+1):
        H[n, n] = -B[n]
        if n < N:
            H[n, n+1] = -A[n]
            H[n+1, n] = -A[n]
        if n > 0:
            H[n, n-1] = -C[n]
            H[n-1, n] = -C[n]

    return H

def doob_transform(H):
    """
    Given a symmetric Hamiltonian H (real, (N+1)x(N+1)), build the Doob
    transform Markov generator Q using the ground state psi0:

        Q_ij = -H_ij * psi0[j] / psi0[i], i != j
        Q_ii = -sum_{j != i} Q_ij
    """
    # Diagonalize H
    evals, evecs = np.linalg.eigh(H)
    idx = np.argsort(evals)
    evals = evals[idx]
    evecs = evecs[:, idx]

    # Ground state
    psi0 = evecs[:, 0]
    psi0 = np.abs(psi0) # ensure non-negative
    psi0 = psi0 / psi0.sum() # normalize to a probability-like vector

    Np1 = H.shape[0]

```

```

Q = np.zeros_like(H, dtype=float)

for i in range(Np1):
    for j in range(Np1):
        if i == j:
            continue
        if H[i, j] != 0.0:
            Q[i, j] = -H[i, j] * psi0[j] / psi0[i]

# Set diagonals to make each row sum to zero
for i in range(Np1):
    Q[i, i] = -Q[i, :].sum()

return Q, evals, psi0

def spectral_gap(Q, tol=1e-12):
    """
    For a continuous-time Markov generator Q:
        spectrum:  $0 = \lambda_0 > \lambda_1 > \lambda_2 > \dots$ 
    The mass gap is  $m_q = -\lambda_1$ , where  $\lambda_1$  is the eigenvalue closest to 0
    on the negative side.

    Returns (gap, eigenvalues_sorted).
    """
    eig = np.linalg.eigvals(Q)
    eig = np.real_if_close(eig, tol=1e-9)
    eig_sorted = np.sort(eig) # ascending: most negative ... up to ~0

    # Extract negative eigenvalues significantly below 0
    neg = eig_sorted[eig_sorted < -tol]
    if neg.size == 0:
        return 0.0, eig_sorted

    lambda1 = neg[-1] # closest to zero (largest negative)
    gap = -lambda1
    return float(gap), eig_sorted

def main():
    # -----
    # Parameters
    # -----
    N = 4 # degree cutoff → (N+1)x(N+1) matrix
    q = 0.95 # deformation parameter
    # non-symmetric parameter choice (breaks uniform ground state)
    alpha = q
    beta = 1.0
    gamma = q
    delta = 1.0

```

```

# -----
# Build Hamiltonian
# -----
H = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
print("H (q-Racah-type Hamiltonian):")
print(H)

# -----
# Doob transform
# -----
Q, evals_H, psi0 = doob_transform(H)
print("\nEigenvalues of H:", evals_H)
print("Ground-state (Doob weight) psi0:", psi0)

print("\nDoob-transformed generator Q:")
print(Q)
print("Row sums (should be ≈ 0):", Q.sum(axis=1))

# -----
# Spectral gap of Q
# -----
gap, eig_Q = spectral_gap(Q)
print("\nEigenvalues of Q:", eig_Q)
print("Mass gap m_q =", gap)

if __name__ == "__main__":
    main()

```

H (q-Racah-type Hamiltonian):

```

[[ 0.004875  -0.04134038  0.          0.          0.          ]
 [-0.04134038  0.00901832 -0.06788456  0.          0.          ]
 [ 0.          -0.06788456  0.01628785 -0.09358721  0.          ]
 [ 0.          0.          -0.09358721  0.0261009  -0.11894883]
 [ 0.          0.          0.          -0.11894883  0.01414882]]

```

Eigenvalues of H: [-0.13874961 -0.05363197 0.00885577 0.07575322 0.1782034
Ground-state (Doob weight) psi0: [0.03645931 0.12666682 0.25351936 0.32810332

Doob-transformed generator Q:

```

[[-0.14362461  0.14362461  0.          0.          0.          ]
 [ 0.01189926 -0.14776793  0.13586867  0.          0.          ]
 [ 0.          0.03391742 -0.15503745  0.12112004  0.          ]
 [ 0.          0.          0.07231311 -0.16485051  0.0925374 ]
 [ 0.          0.          0.          0.15289843 -0.15289843]]

```

Row sums (should be ≈ 0): [0.00000000e+00 0.00000000e+00 0.00000000e+00 1.387
0.00000000e+00]

Eigenvalues of Q: [-3.16953086e-01 -2.14502830e-01 -1.47605380e-01 -8.5117632
1.72800544e-17]

Mass gap m_q = 0.08511763228589697

```

import numpy as np

# Assumes you already have:
#   - qRacah_matrix(N, q, alpha, beta, gamma, delta)
#   - doob_transform(H) -> (Q, evals_H, psi0)
#   - spectral_gap(Q) -> (gap, eig_sorted)
#
# from the previous code.

def compute_mq_for_q(N, q, alpha, beta, gamma, delta):
    H = qRacah_matrix(N, q, alpha, beta, gamma, delta)
    Q, evals_H, psi0 = doob_transform(H)
    gap, eig_Q = spectral_gap(Q)
    return gap

def scan_q_grid():
    N = 4
    alpha, beta, gamma, delta = 0.95, 1.0, 0.95, 1.0 # same pattern you use
    q_values = np.linspace(0.85, 0.99, 8)           # tweak as you like

    print("q\t\tm_q")
    for q in q_values:
        gap = compute_mq_for_q(N, q, alpha, beta, gamma, delta)
        print(f"{q:.4f}\t\t{gap:.6f}")

if __name__ == "__main__":
    scan_q_grid()

```

```

q          m_q
0.8500    0.199122
0.8700    0.180060
0.8900    0.159033
0.9100    0.136111
0.9300    0.111415
0.9500    0.085118
0.9700    0.057508
0.9900    0.029483

```

```

import numpy as np

# =====
# 1. q-Racah-type Hamiltonian H (tridiagonal, symmetric)
# =====

def q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta):
    """
    Build a (N+1)x(N+1) symmetric tridiagonal matrix H that plays
    the role of a q-Racah-type Hamiltonian.
    """

```

Parameters roughly follow a standard q-Racah Jacobi form.
We use a specific non-symmetric parameter choice to get
a non-uniform ground state.

```
"""
```

```
A = np.zeros(N+1)
```

```
B = np.zeros(N+1)
```

```
C = np.zeros(N+1)
```

```
for n in range(0, N+1):
```

```
    # Super-diagonal coefficient A_n
```

```
    if n < N:
```

```
        numA = ((1 - alpha*q**(n+1)) *
                 (1 - beta*delta*q**(n+1)) *
                 (1 - gamma*q**(n+1)) *
                 (1 - delta*q**(n+1)))
```

```
        denA = ((1 - delta*q**(2*n+1)) *
                 (1 - delta*q**(2*n+2)))
```

```
        valA = numA/denA
```

```
        A[n] = np.sqrt(max(valA, 0.0))
```

```
    # Sub-diagonal coefficient C_n
```

```
    if n > 0:
```

```
        numC = ((1 - q**n) *
                 (1 - beta*q**n) *
                 (1 - gamma*q**n) *
                 (1 - alpha*delta*q**n))
```

```
        denC = ((1 - delta*q**(2*n)) *
                 (1 - delta*q**(2*n+1)))
```

```
        valC = numC/denC
```

```
        C[n] = np.sqrt(max(valC, 0.0))
```

```
    # Diagonal B_n (store minus of usual Jacobi B_n)
```

```
    B[n] = -(A[n]**2 + C[n]**2)
```

```
# Hamiltonian H = -J (so H has ~positive spectrum)
```

```
H = np.zeros((N+1, N+1))
```

```
for n in range(N+1):
```

```
    H[n, n] = -B[n]
```

```
    if n < N:
```

```
        H[n, n+1] = -A[n]
```

```
        H[n+1, n] = -A[n]
```

```
    if n > 0:
```

```
        H[n, n-1] = -C[n]
```

```
        H[n-1, n] = -C[n]
```

```
return H
```

```
# =====
```

```
# 2. Doob transform → Markov generator Q
```

```
# =====
```

```

def doob_transform(H):
    """
    Given symmetric H, find ground state psi0 and build the
    Doob-transformed generator Q:

        Q_ij = -H_ij * psi0[j] / psi0[i], i != j
        Q_ii = -sum_{j!=i} Q_ij
    """
    evals, evecs = np.linalg.eigh(H)
    idx = np.argsort(evals)
    evals = evals[idx]
    evecs = evecs[:, idx]

    psi0 = evecs[:, 0]
    psi0 = np.abs(psi0)
    psi0 = psi0 / psi0.sum()

    n = H.shape[0]
    Q = np.zeros_like(H, dtype=float)

    for i in range(n):
        for j in range(n):
            if i == j:
                continue
            hij = H[i, j]
            if hij != 0.0:
                Q[i, j] = -hij * psi0[j] / psi0[i]

    for i in range(n):
        Q[i, i] = -Q[i, :].sum()

    return Q, evals, psi0

# =====
# 3. Spectral gap of Q (mass gap m_q)
# =====

def spectral_gap(Q, tol=1e-12):
    """
    Continuous-time generator Q:
        eigenvalues:  $\lambda_0 = 0 > \lambda_1 > \lambda_2 > \dots$ 
    Mass gap  $m_q = -\lambda_1$ .
    """
    eig = np.linalg.eigvals(Q)
    eig = np.real_if_close(eig, tol=1e-9)
    eig_sorted = np.sort(eig) # ascending: most negative ... ~0

    neg = eig_sorted[eig_sorted < -tol]
    if neg.size == 0:
        return 0, 0, eig_sorted

```

```

        return 0.0, eig_sorted

    lambda1 = neg[-1]    # closest to 0
    gap = -lambda1
    return float(gap), eig_sorted

# =====
# 4. Semigroup  $e^{\{tQ\}}$  via eigendecomposition
# =====

def expm_generator(Q, t):
    """
    Compute  $e^{\{tQ\}}$  using eigen-decomposition.
    For small state spaces this is exact enough.
    """
    eigvals, eigvecs = np.linalg.eig(Q)
    eigvals = np.real_if_close(eigvals, tol=1e-9)
    eigvecs = np.real_if_close(eigvecs, tol=1e-9)

    # diagonal exp
    D = np.diag(np.exp(t * eigvals))
    # Q is real diagonalizable, so  $V D V^{-1}$ 
    Vinv = np.linalg.inv(eigvecs)
    P_t = eigvecs @ D @ Vinv
    P_t = np.real_if_close(P_t, tol=1e-9)
    return P_t

# =====
# 5. Correlation decay of observable  $f(n)=n$ 
# =====

def stationary_distribution(psi0):
    """
    For symmetric H and this Doob transform, the reversible
    measure is proportional to  $\psi_0^2$ .
    """
    pi = psi0**2
    pi = pi / pi.sum()
    return pi

def correlation_decay(Q, psi0, t_grid):
    """
    Compute  $C(t) = E_{\pi}[(f(X_t) - E_{\pi} f)(f(X_0) - E_{\pi} f)]$ 
    for  $f(n) = n$  over  $t_{\text{grid}}$ , where  $\pi$  is stationary.
    """
    n = Q.shape[0]
    pi = stationary_distribution(psi0)

    # observable f
    states = np.arange(n, dtype=float)
    f = states.copy()

```

```

f_mean = np.dot(pi, f)
f_centered = f - f_mean

C_t = []

for t in t_grid:
    P_t = expm_generator(Q, t)          # (n x n)
    # correlation C(t) = sum_{i,j} pi_i f_i P_t(i,j) f_j
    f_t = P_t @ f_centered
    C = np.dot(pi * f_centered, f_t)
    C_t.append(C.real)

return np.array(C_t), f_centered, pi

# =====
# 6. Driver: build everything, compute m_q and correlation decay
# =====

def main():
    # Model parameters
    N = 4
    q = 0.95
    alpha = q
    beta = 1.0
    gamma = q
    delta = 1.0

    # Build Hamiltonian
    H = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
    print("H:\n", H)

    # Doob transform
    Q, evals_H, psi0 = doob_transform(H)
    print("\nEigenvalues of H:", evals_H)
    print("psi0:", psi0)

    print("\nQ (Doob generator):\n", Q)
    print("Row sums (≈0):", Q.sum(axis=1))

    # Spectral gap
    m_q, eig_Q = spectral_gap(Q)
    print("\nEigenvalues of Q:", eig_Q)
    print("Mass gap m_q =", m_q)

    # Correlation decay
    t_grid = np.linspace(0.0, 50.0, 26) # 0,2,4,...,50
    C_t, f_centered, pi = correlation_decay(Q, psi0, t_grid)

    print("\nCorrelation C(t) for f(n)=n:")
    for t, Ct in zip(t_grid, C_t):
        if t > 0:

```



```

    eff_rate = -np.log(abs(Ct) / abs(C_t[0])) / t
else:
    eff_rate = np.nan
print(f"t={t:5.1f}  C(t)={Ct: .6e}  lambda_eff(t)={eff_rate: .6e}")

if __name__ == "__main__":
    main()

```

```

H:
[[ 0.004875  -0.04134038  0.          0.          0.          ]
 [-0.04134038  0.00901832 -0.06788456  0.          0.          ]
 [ 0.         -0.06788456  0.01628785 -0.09358721  0.          ]
 [ 0.          0.         -0.09358721  0.0261009  -0.11894883]
 [ 0.          0.          0.         -0.11894883  0.01414882]]

```

Eigenvalues of H: [-0.13874961 -0.05363197 0.00885577 0.07575322 0.1782034
 psi0: [0.03645931 0.12666682 0.25351936 0.32810332 0.25525118]

Q (Doob generator):

```

[[-0.14362461  0.14362461  0.          0.          0.          ]
 [ 0.01189926 -0.14776793  0.13586867  0.          0.          ]
 [ 0.          0.03391742 -0.15503745  0.12112004  0.          ]
 [ 0.          0.          0.07231311 -0.16485051  0.0925374 ]
 [ 0.          0.          0.          0.15289843 -0.15289843]]

```

Row sums (≈ 0): [0.00000000e+00 0.00000000e+00 0.00000000e+00 1.38777878e-17
 0.00000000e+00]

Eigenvalues of Q: [-3.16953086e-01 -2.14502830e-01 -1.47605380e-01 -8.5117632
 1.72800544e-17]

Mass gap $m_q = 0.08511763228589697$

Correlation C(t) for $f(n)=n$:

```

t= 0.0  C(t)= 7.887514e-01  lambda_eff(t)= nan
t= 2.0  C(t)= 6.473280e-01  lambda_eff(t)= 9.879904e-02
t= 4.0  C(t)= 5.338642e-01  lambda_eff(t)= 9.757743e-02
t= 6.0  C(t)= 4.419815e-01  lambda_eff(t)= 9.653053e-02
t= 8.0  C(t)= 3.670302e-01  lambda_eff(t)= 9.562589e-02
t= 10.0 C(t)= 3.055372e-01  lambda_eff(t)= 9.483797e-02
t= 12.0 C(t)= 2.548542e-01  lambda_eff(t)= 9.414662e-02
t= 14.0 C(t)= 2.129270e-01  lambda_eff(t)= 9.353586e-02
t= 16.0 C(t)= 1.781390e-01  lambda_eff(t)= 9.299293e-02
t= 18.0 C(t)= 1.492041e-01  lambda_eff(t)= 9.250757e-02
t= 20.0 C(t)= 1.250885e-01  lambda_eff(t)= 9.207147e-02
t= 22.0 C(t)= 1.049558e-01  lambda_eff(t)= 9.167781e-02
t= 24.0 C(t)= 8.812423e-02  lambda_eff(t)= 9.132098e-02
t= 26.0 C(t)= 7.403569e-02  lambda_eff(t)= 9.099631e-02
t= 28.0 C(t)= 6.223113e-02  lambda_eff(t)= 9.069985e-02
t= 30.0 C(t)= 5.233167e-02  lambda_eff(t)= 9.042832e-02
t= 32.0 C(t)= 4.402367e-02  lambda_eff(t)= 9.017887e-02
t= 34.0 C(t)= 3.704680e-02  lambda_eff(t)= 8.994910e-02
t= 36.0 C(t)= 3.118453e-02  lambda_eff(t)= 8.973691e-02
t= 38.0 C(t)= 2.625644e-02  lambda_eff(t)= 8.954052e-02
t= 40.0 C(t)= 2.211194e-02  lambda_eff(t)= 8.935834e-02

```

```

t= 42.0  C(t)= 1.862516e-02  lambda_eff(t)= 8.918899e-02
t= 44.0  C(t)= 1.569081e-02  lambda_eff(t)= 8.903127e-02
t= 46.0  C(t)= 1.322068e-02  lambda_eff(t)= 8.888411e-02
t= 48.0  C(t)= 1.114082e-02  lambda_eff(t)= 8.874656e-02
t= 50.0  C(t)= 9.389216e-03  lambda_eff(t)= 8.861779e-02

```

```

import numpy as np

# We assume H, q_racah_jacobi_matrix, doob_transform, spectral_gap already e

def hessian_flow(H, direction, t_grid):
    """
    H(t) = H + t * direction
    where 'direction' is a symmetric matrix (like a Hessian drift).
    """
    gaps = []
    for t in t_grid:
        Ht = H + t * direction
        # Recompute Doob generator
        Q, evals_Ht, psi0 = doob_transform(Ht)
        gap, _ = spectral_gap(Q)
        gaps.append(gap)
    return np.array(gaps)

def build_direction_matrix(N, scale=1.0):
    """
    Simple positive-semidefinite 'curvature increase' operator.
    """
    D = np.zeros((N+1, N+1))
    for i in range(N+1):
        for j in range(N+1):
            D[i,j] = scale * np.exp(-(i-j)**2 / 2.0)
    return (D + D.T) / 2.0  # ensure symmetry

# -----
# RUN FLOW
# -----

N = 4
q = 0.95
alpha = q
beta = 1.0
gamma = q
delta = 1.0

# base Hamiltonian
H0 = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)

# direction (curvature push)
D = build_direction_matrix(N, scale=0.1)

```

```

# time steps
t_grid = np.linspace(0, 2.0, 21) # t = 0,0.1,...,2.0

gaps = hessian_flow(H0, D, t_grid)

print("t\tm_q(t)")
for t, g in zip(t_grid, gaps):
    print(f"{t:.2f}\t{g:.6f}")

```

```

t      m_q(t)
0.00   0.085118
0.10   0.080479
0.20   0.076085
0.30   0.071911
0.40   0.071321
0.50   0.066146
0.60   0.060381
0.70   0.050607
0.80   0.065112
0.90   0.058636
1.00   0.054272
1.10   0.046896
1.20   0.086946
1.30   0.066869
1.40   0.052994
1.50   0.049103
1.60   0.031475
1.70   0.000000
1.80   0.000000
1.90   0.000000
2.00   0.000000

```

```

import numpy as np

# -----
# Same q-Racah Hamiltonian function as before
# -----

def q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta):
    A = np.zeros(N+1)
    B = np.zeros(N+1)
    C = np.zeros(N+1)

    for n in range(0, N+1):
        if n < N:
            numA = ((1 - alpha*q**(n+1)) *
                    (1 - beta*delta*q**(n+1)) *
                    (1 - gamma*q**(n+1)) *
                    (1 - delta*q**(n+1)))
            denA = ((1 - delta*q**(2*n+1)) *
                    (1 - delta*q**(2*n+1)))

```

```

        (1 - delta*q**(2*n+2)))
    A[n] = np.sqrt(max(numA/denA, 0.0))

    if n > 0:
        numC = ((1 - q**n) *
                 (1 - beta*q**n) *
                 (1 - gamma*q**n) *
                 (1 - alpha*delta*q**n))
        denC = ((1 - delta*q**(2*n)) *
                 (1 - delta*q**(2*n+1)))
        C[n] = np.sqrt(max(numC/denC, 0.0))

    B[n] = -(A[n]**2 + C[n]**2)

    H = np.zeros((N+1, N+1))
    for n in range(N+1):
        H[n,n] = -B[n]
        if n < N:
            H[n,n+1] = -A[n]
            H[n+1,n] = -A[n]
        if n > 0:
            H[n,n-1] = -C[n]
            H[n-1,n] = -C[n]

    return H

# -----
# Doob transform + gap (unchanged)
# -----

def doob_transform(H):
    evals, evecs = np.linalg.eigh(H)
    idx = np.argsort(evals)
    evals = evals[idx]
    psi0 = np.abs(evecs[:,idx[0]])
    psi0 = psi0/psi0.sum()
    n = H.shape[0]
    Q = np.zeros_like(H)
    for i in range(n):
        for j in range(n):
            if i!=j and H[i,j] != 0.0:
                Q[i,j] = -H[i,j]*psi0[j]/psi0[i]
        Q[i,i] = -Q[i,:].sum()
    return Q, evals, psi0

def spectral_gap(Q, tol=1e-12):
    eig = np.linalg.eigvals(Q)
    eig = np.real_if_close(eig, tol=1e-9)
    eig_sorted = np.sort(eig)
    neg = eig_sorted[eig_sorted < -tol]
    if neg.size == 0:

```

```

        return 0.0
    return float(-neg[-1])

# -----
# PARAMETER FLOW: alpha(t), gamma(t) drift
# -----

def param_flow(N, q, t_grid):
    gaps = []
    for t in t_grid:
        # smooth parameter modification:
        alpha = q * (1 + 0.5*t)
        beta = 1.0
        gamma = q * (1 - 0.3*t)
        delta = 1.0

        # build H(t)
        Ht = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
        Q, _, _ = doob_transform(Ht)
        gap = spectral_gap(Q)
        gaps.append(gap)
    return gaps

# -----
# RUN
# -----

N = 4
q = 0.95
t_grid = np.linspace(0, 1.5, 16)

gaps = param_flow(N, q, t_grid)

print("t\tm_q(t)")
for t,g in zip(t_grid, gaps):
    print(f"{t:.2f}\t{g:.6f}")

```

t	m_q(t)
0.00	0.085118
0.10	0.083849
0.20	0.086728
0.30	0.086816
0.40	0.084723
0.50	0.111385
0.60	0.000000
0.70	0.000000
0.80	0.000000
0.90	0.000000
1.00	0.000000
1.10	0.000000
1.20	0.000000

```
1.30    0.000000
1.40    0.000000
1.50    0.000000
```

```
import numpy as np

# -----
# 1. q-Racah Hamiltonian (same as before, kept correct)
# -----

def q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta):
    A = np.zeros(N+1)
    B = np.zeros(N+1)
    C = np.zeros(N+1)

    for n in range(0, N+1):
        if n < N:
            numA = ((1 - alpha*q**(n+1)) *
                    (1 - beta*delta*q**(n+1)) *
                    (1 - gamma*q**(n+1)) *
                    (1 - delta*q**(n+1)))
            denA = ((1 - delta*q**(2*n+1)) *
                    (1 - delta*q**(2*n+2)))
            A[n] = np.sqrt(max(numA/denA, 0.0))

            if n > 0:
                numC = ((1 - q**n) *
                        (1 - beta*q**n) *
                        (1 - gamma*q**n) *
                        (1 - alpha*delta*q**n))
                denC = ((1 - delta*q**(2*n)) *
                        (1 - delta*q**(2*n+1)))
                C[n] = np.sqrt(max(numC/denC, 0.0))

            B[n] = -(A[n]**2 + C[n]**2)

    H = np.zeros((N+1, N+1))
    for n in range(N+1):
        H[n,n] = -B[n]
        if n < N:
            H[n, n+1] = -A[n]
            H[n+1,n] = -A[n]
        if n > 0:
            H[n,n-1] = -C[n]
            H[n-1,n] = -C[n]

    return H

# -----
# Doob transform + spectral gap
```

```

# -----

def doob_transform(H):
    evals, evecs = np.linalg.eigh(H)
    idx = np.argsort(evals)
    evals = evals[idx]
    psi0 = np.abs(evecs[:, idx[0]])
    psi0 /= psi0.sum()
    n = H.shape[0]
    Q = np.zeros_like(H)
    for i in range(n):
        for j in range(n):
            if i != j and H[i,j] != 0:
                Q[i,j] = -H[i,j]*psi0[j]/psi0[i]
        Q[i,i] = -Q[i,:].sum()
    return Q, evals, psi0

def spectral_gap(Q, tol=1e-12):
    eig = np.real_if_close(np.linalg.eigvals(Q), tol=1e-9)
    eig_sorted = np.sort(eig)
    neg = eig_sorted[eig_sorted < -tol]
    if neg.size == 0:
        return 0.0
    return -neg[-1]

# -----
# 2. Stable flow:  $q(t) = q_0 + t * dq$ 
# -----

def stable_q_flow(N, q0, dq, t_grid):
    alpha = 1.0
    beta = 1.0
    gamma = 1.0
    delta = 1.0
    gaps = []

    for t in t_grid:
        q = q0 + dq*t
        # enforce domain:  $0 < q < 1.2$  (safe window)
        if q <= 0 or q >= 1.2:
            gaps.append(0.0)
            continue

        H = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
        Q, _, _ = doob_transform(H)
        gap = spectral_gap(Q)
        gaps.append(gap)

    return gaps

# -----

```

```

"""
# RUN
# -----

N = 4
q0 = 0.80
dq = 0.10 # change q by 0.10 per unit t
t_grid = np.linspace(0, 1.0, 11)

gaps = stable_q_flow(N, q0, dq, t_grid)

print("t\tm_q(t)")
for t,g in zip(t_grid, gaps):
    print(f"{t:.2f}\t{g:.6f}")

```

t	m_q(t)
0.00	0.237211
0.10	0.230138
0.20	0.222546
0.30	0.214425
0.40	0.205769
0.50	0.196574
0.60	0.186839
0.70	0.176567
0.80	0.165763
0.90	0.154436
1.00	0.142597

```

"""

```

```

q_lab.py

```

Numerical lab for q-Racah polynomials and q-deformed SU(2) 6j-symbols.

Goal:

- Give you robust numerical primitives for q-structures that appear in:
 - q-Racah / Askey scheme polynomials
 - q-deformed SU(2) recoupling (6j)
- Provide a minimal "toy spectral gap" playground that mirrors the Yang-Mills mass-gap story in a finite discrete setting.

Physics reading guide:

- $q = e^{\{i \theta\}}$ plays the role of a deformation / "topological angle".
- q-Racah polynomials are eigenfunctions of a tridiagonal (Jacobi) operator $\rightarrow$ discrete analogue of a Hamiltonian / generator.
- q-6j symbols are recoupling coefficients for $U_q(\mathfrak{su}(2))$, the q-deformed gauge group. They are the algebraic building blocks of spin-network / tensor-network transfer matrices.

Dependencies: numpy (for arrays), cmath (complex math).

```

"""

```



```

from __future__ import annotations
import numpy as np
import cmath
from functools import lru_cache

# -----
# 1. Basic q-arithmetic
# -----

def q_number(n: int | float, q: complex) -> complex:
    """
    Symmetric q-integer:
         $[n]_q = (q^n - q^{-n}) / (q - q^{-1})$ 

    For  $|q|=1$  and  $q$  not a root of unity this is well-behaved.
    We also handle the  $q \rightarrow 1$  limit explicitly.

    Parameters
    -----
    n : int or float
        Typically an integer (but we allow float that is very close to integ
    q : complex
        Deformation parameter, usually  $q = \exp(i \theta)$ .

    Returns
    -----
    complex
    """
    q = complex(q)
    # Treat integer-ish n
    n = float(n)

    #  $q \rightarrow 1$  limit:  $[n]_q \rightarrow n$ 
    if abs(q - 1.0) < 1e-12:
        return n

    denom = q - 1.0 / q
    if abs(denom) < 1e-15:
        # Extremely close to  $q = \pm 1$ : fall back to Taylor expansion if needed
        # Here we just approximate by the classical value.
        return n

    return (q ** n - q ** (-n)) / denom

@lru_cache(maxsize=None)
def log_q_factorial(n: float, q: complex) -> complex:
    """
     $\log([n]_q!)$  for  $n \geq 0$ , where
    """

```

$$[n]_q! = \prod_{k=1}^n [k]_q$$

We assume n is an integer (possibly passed as float), so we round.

Returns $-\infty$ (complex with real part $-\infty$) if the factorial is zero.

This is the core building block for everything (q -triangle coefficients, q -6j symbols, etc.).

```

"""
# Enforce integer
n_int = int(round(n))
if n_int < 0:
    # Convention: factorial of negative integer = 0  $\Rightarrow$  log =  $-\infty$ 
    return complex(float("-inf"), 0.0)
if n_int == 0:
    return 0.0 + 0.0j

q = complex(q)
acc = 0.0 + 0.0j
for k in range(1, n_int + 1):
    val = q_number(k, q)
    if abs(val) < 1e-30:
        return complex(float("-inf"), 0.0)
    acc += cmath.log(val)
return acc

```

```

# -----
# 2.  $q$ -Racah polynomials via terminating  $4\phi_3$ 
# -----

```

```
def q_pochhammer(a: complex, q: complex, n: int) -> complex:
```

```

    """
     $q$ -Pochhammer symbol  $(a; q)_n = \prod_{k=0}^{n-1} (1 - a q^k)$ 

```

```

    For  $n = 0$  we return 1.

```

```

    """
    q = complex(q)
    if n < 0:
        raise ValueError("q_pochhammer: n must be  $\geq 0$ ")
    if n == 0:
        return 1.0 + 0.0j
    acc = 1.0 + 0.0j
    for k in range(n):
        acc *= (1.0 - a * (q ** k))
    return acc

```

```
def basic_hypergeom_4phi3(a_params, b_params, q: complex, z: complex, n_max:
```

```

    """
    Compute the terminating basic hypergeometric series

```

```

_4φ_3(a1,a2,a3,a4; b1,b2,b3; q; z)
= sum_{n=0}^{n_max} ( (a1;q)_n ... (a4;q)_n ) /
                    ( (b1;q)_n ... (b3;q)_n (q;q)_n ) * z^n

```

This is the 'r = s+1' special case, so no extra $(-1)^n q^{\{...\}}$ factor in front (see e.g. standard definition of basic hypergeometric series).
 """

```

q = complex(q)
z = complex(z)
a1, a2, a3, a4 = [complex(a) for a in a_params]
b1, b2, b3 = [complex(b) for b in b_params]

acc = 0.0 + 0.0j
for n in range(n_max + 1):
    num = (q_pochhammer(a1, q, n) *
           q_pochhammer(a2, q, n) *
           q_pochhammer(a3, q, n) *
           q_pochhammer(a4, q, n))
    den = (q_pochhammer(b1, q, n) *
           q_pochhammer(b2, q, n) *
           q_pochhammer(b3, q, n) *
           q_pochhammer(q, q, n)) # (q;q)_n
    if abs(den) < 1e-30:
        # Term blows up: stop the sum (this shouldn't happen in the
        # terminating parameters we use).
        break
    acc += num / den * (z ** n)
return acc

```

```

def q_racah_p(n: int, x: int,
              a: complex, b: complex, c: complex, d: complex,
              q: complex) -> complex:

```

"""

One of the standard q-Racah normalizations:

```

p_n(λ(x); a,b,c,d | q)
= _4φ_3(q^{-n}, a b q^{n+1}, q^{-x}, q^{x+1} c d;
        a q, b d q, c q; q; q)

```

with $\lambda(x) = q^{-x} + c d q^{x+1}$. :contentReference[oaicite:2]{index=2}

Here we directly return the polynomial value at the lattice index x.
 You can reconstruct dependence on $\lambda(x)$ if you wish.

Typical discrete support: $x = 0, 1, \dots, N$ for some N encoded in parameters

Parameters

.

```

n : int
    Degree of the polynomial.
x : int
    Discrete lattice index where we evaluate the polynomial.
a,b,c,d,q : complex
    q-Racah parameters; see the Askey scheme references.

Returns
-----
complex
"""
q = complex(q)
# Hypergeometric parameters
a1 = q ** (-n)
a2 = a * b * (q ** (n + 1))
a3 = q ** (-x)
a4 = (q ** (x + 1)) * c * d

b1 = a * q
b2 = b * d * q
b3 = c * q

return basic_hypergeom_4phi3(
    (a1, a2, a3, a4),
    (b1, b2, b3),
    q,
    q, # z = q in this normalization
    n_max=n
)

# -----
# 3. q-deformed SU(2) 6j-symbol via q-factorials (Racah sum)
# -----

@lru_cache(maxsize=None)
def log_delta_q(j1: float, j2: float, j3: float, q: complex) -> complex:
    """
    log( $\Delta_q(j_1, j_2, j_3)$ ), where the q-triangle coefficient is

    
$$\Delta_q(a, b, c) = \sqrt{ [a+b-c]_q! [a-b+c]_q! [-a+b+c]_q! / [a+b+c+1]_q! }$$


    All factorial arguments are integers if spins are half-integers and
    the SU(2) triangle rules are satisfied.
    """
    # Triangle conditions
    if not (abs(j1 - j2) <= j3 <= j1 + j2):
        return complex(float("-inf"), 0.0)
    if ((j1 + j2 + j3) % 1.0) != 0.0:
        # Sum must be integer (half-integers add to integer)
        return complex(float("-inf"), 0.0)

```

```

# Integer factorial arguments
a1 = j1 + j2 - j3
a2 = j1 - j2 + j3
a3 = -j1 + j2 + j3
a4 = j1 + j2 + j3 + 1.0

for x in (a1, a2, a3, a4):
    if x < 0 or (x % 1.0) != 0.0:
        return complex(float("-inf"), 0.0)

l1 = log_q_factorial(a1, q)
l2 = log_q_factorial(a2, q)
l3 = log_q_factorial(a3, q)
l4 = log_q_factorial(a4, q)

if any(np.isneginf(v.real) for v in (l1, l2, l3, l4)):
    return complex(float("-inf"), 0.0)

return 0.5 * (l1 + l2 + l3 - l4)

def sixj_q(j1: float, j2: float, j3: float,
            j4: float, j5: float, j6: float,
            q: complex) -> complex:
    r"""
    q-deformed SU(2) 6j-symbol via the Racah sum:


$$\begin{aligned} & \begin{Bmatrix} j_1 & j_2 & j_3 \\ j_4 & j_5 & j_6 \end{Bmatrix}_q \\ &= \Delta_q(j_1, j_2, j_3) \Delta_q(j_1, j_5, j_6) \\ & \quad \Delta_q(j_4, j_2, j_6) \Delta_q(j_4, j_5, j_3) \\ & \quad \sum_t (-1)^t [t+1]_q! / \prod_{k=1}^7 [n_k(t)]_q! \end{aligned}$$


    with the standard  $n_k(t)$  linear combinations.

    Spins  $j_i \in \{ 0, 1/2, 1, 3/2, \dots \}$  and obey admissibility conditions.
    q is typically on the unit circle:  $q = e^{\{i \theta\}}$ , not a root of unity.

    This is the direct q-analogue of the classical Racah formula.
    """
    q = complex(q)

    # Check triangle conditions for the four triples
    triangles = [
        (j1, j2, j3),
        (j1, j5, j6),
        (j4, j2, j6),
        (j4, j5, j3),
    ]

```

```

logs = []
for (a, b, c) in triangles:
    L = log_delta_q(a, b, c, q)
    if np.isneginf(L.real):
        return 0.0j
    logs.append(L)

log_prefactor = sum(logs)

# t-range (integers) from Racah conditions
t_min = int(max(
    j1 + j2 + j3,
    j1 + j5 + j6,
    j4 + j2 + j6,
    j4 + j5 + j3,
))
t_max = int(min(
    j1 + j2 + j4 + j5,
    j1 + j3 + j4 + j6,
    j2 + j3 + j5 + j6,
))

if t_min > t_max:
    return 0.0j

total = 0.0 + 0.0j
for t in range(t_min, t_max + 1):
    # Denominator factorial arguments
    n1 = t - (j1 + j2 + j3)
    n2 = t - (j1 + j5 + j6)
    n3 = t - (j4 + j2 + j6)
    n4 = t - (j4 + j5 + j3)
    n5 = (j1 + j2 + j4 + j5) - t
    n6 = (j1 + j3 + j4 + j6) - t
    n7 = (j2 + j3 + j5 + j6) - t

    n_args = (n1, n2, n3, n4, n5, n6, n7)
    if any((n < 0) or ((n % 1.0) != 0.0) for n in n_args):
        continue # outside admissible range

    # log([t+1]_q!)
    ln_num = log_q_factorial(t + 1.0, q)
    if np.isneginf(ln_num.real):
        continue

    ln_den = 0.0 + 0.0j
    for n in n_args:
        ln_den += log_q_factorial(n, q)
    if np.isneginf(ln_den.real):
        continue

```

```

    #  $(-1)^t$  factor
    phase = -1.0 if (t % 2) else 1.0

    term = phase * cmath.exp(log_prefactor + ln_num - ln_den)
    total += term

return total

# -----
# 4. Tiny "toy spectral gap" sandbox
# -----

def build_simple_q_racah_markov(N: int,
                                a: complex, b: complex, c: complex, d: complex,
                                q: complex,
                                eps: float = 1e-12) -> tuple[np.ndarray, np.ndarray]:
    """
    Build a very simple reversible Markov generator L on the finite set {0,..,N}
    whose eigenvectors are numerically close to { p_n(x) } q-Racah polynomials.

    WARNING:
    - This is a *toy* construction meant as a playground:
      • Not optimized
      • Not using the exact analytic weight function
    - It is still enough to experiment with:
      • spectral gap vs. parameters
      • sensitivity in q (i.e.  $\theta$ ) and deformation.

    Construction sketch:
    1. Form the  $(N+1) \times (N+1)$  matrix of values
        $P[n,x] = p_n(x; a,b,c,d | q)$ ,  $n,x = 0..N$ .
    2. Orthonormalize the rows numerically (Gram-Schmidt).
    3. Define a diagonal "energy spectrum"  $E_n = n$  (or  $n(n+1)$ ) in that basis.
    4. conjugate back to the x-basis to obtain a self-adjoint operator H.
    5. Turn H into a Markov generator L by subtracting its ground-state energy.

    This is an algebraic cartoon of:
    "orthogonal polynomials  $\leftrightarrow$  eigenbasis of a self-adjoint generator
      $\leftrightarrow$  spectral gap = first positive eigenvalue"
    which mirrors your YM Dirichlet form  $\rightarrow$  mass gap philosophy.

    Returns
    -----
    L : np.ndarray
         $(N+1) \times (N+1)$  Markov generator (symmetric with negative diagonal).
    evals : np.ndarray
        Sorted eigenvalues of L (real).
    """
    q = complex(q)
    # ...

```

```

xs = list(range(0, N + 1))

# Step 1: raw polynomial matrix P[n,x]
P = np.zeros((N + 1, N + 1), dtype=complex)
for n in range(N + 1):
    for ix, x in enumerate(xs):
        P[n, ix] = q_racah_p(n, x, a, b, c, d, q)

# Step 2: Gram-Schmidt orthonormalization of rows
# This is purely numerical, uses flat inner product  $\sum_x f(x) g^*(x)$ .
Q = np.zeros_like(P, dtype=complex)
for n in range(N + 1):
    v = P[n].copy()
    for m in range(n):
        proj = np.vdot(Q[m], v) * Q[m]
        v -= proj
    norm = np.linalg.norm(v)
    if norm < eps:
        raise RuntimeError("Numerical breakdown in Gram-Schmidt; "
                           "try different parameters.")
    Q[n] = v / norm

# Step 3: choose a simple increasing spectrum in polynomial degree
# e.g.  $E_n = n$  or  $n(n+1)$ . We'll take  $E_n = n$  for simplicity.
E = np.arange(0, N + 1, dtype=float)

# H in the x-basis:  $H = Q^\dagger \text{diag}(E) Q$ 
H = np.conjugate(Q.T) @ (np.diag(E) @ Q)

# Shift so that ground state has energy 0, and flip sign to make it a
# Markov generator with non-positive diagonal.
evals_H, _ = np.linalg.eigh(H)
E0 = np.min(evals_H)
L = -(H - E0 * np.eye(N + 1))

# Sanity: real-symmetrize small numerical imaginary parts
L = 0.5 * (L + L.conjugate().T)
L = L.real

# Return eigenvalues of L (should be  $\geq 0$  with  $\lambda_0 = 0$ )
evals_L, _ = np.linalg.eigh(L)
evals_L = np.sort(evals_L)

return L, evals_L

# -----
# 5. Small demo when run as a script
# -----

if __name__ == "__main__":

```



```

# Example parameters for a finite q-Racah family.
# For simplicity we pick small |a|,|b|,|c|,|d| to avoid numerical dramas
q = cmath.exp(1j * 0.3) # q = e^{i \theta}
a, b, c, d = 0.2, 0.3, 0.4, 0.5
N = 4 # small truncation for a toy model

print(f"q = {q}")
print("Sample q-Racah values:")
for n in range(0, N + 1):
    vals = [q_racah_p(n, x, a, b, c, d, q) for x in range(N + 1)]
    print(f"  n={n}: {vals}")

print("\nSample q-6j symbol (symmetric tetrahedron j=1/2):")
j = 0.5
val_6j = sixj_q(j, j, j, j, j, j, q)
print(f"  {{1/2 1/2 1/2; 1/2 1/2 1/2}}_q = {val_6j}")

print("\nBuilding toy Markov generator from q-Racah eigenbasis...")
L, evals = build_simple_q_racah_markov(
    N=N,
    a=a, b=b, c=c, d=d,
    q=q
)
print("Generator L:")
print(L)
print("Eigenvalues (should be >= 0):")
print(evals)
print(f"Toy 'mass gap' (smallest positive eigenvalue) ≈ {evals[1]:.6g}")

```

```

q = (0.955336489125606+0.29552020666133955j)
Sample q-Racah values:
n=0: [(1+0j), (1+0j), (1+0j), (1+0j), (1+0j)]
n=1: [(1+0j), (0.996496329952082-0.547156650561897j), (0.7741473626999601-1
n=2: [(1+0j), (0.814958704075214-1.0808468489079983j), (-0.3834517914034633
n=3: [(1+0j), (0.471603337824322-1.5533976390835271j), (-2.14512260888381-1
n=4: [(1+0j), (-0.002898856531936727-1.9225974663770662j), (-3.876488263913

Sample q-6j symbol (symmetric tetrahedron j=1/2):
{1/2 1/2 1/2; 1/2 1/2 1/2}_q = 0j

Building toy Markov generator from q-Racah eigenbasis...
Generator L:
[[-1.45650361  0.9783583  0.28686981  0.12220031  0.06907518]
 [ 0.9783583 -2.43616158  1.05944502  0.28271701  0.11564125]
 [ 0.28686981  1.05944502 -2.59309944  1.00960904  0.23717557]
 [ 0.12220031  0.28271701  1.00960904 -2.25343486  0.83890851]
 [ 0.06907518  0.11564125  0.23717557  0.83890851 -1.26080051]]
Eigenvalues (should be >= 0):
[-3.88987709e+00 -3.01988495e+00 -2.06032845e+00 -1.02990951e+00
 -1.08831533e-15]
Toy 'mass gap' (smallest positive eigenvalue) ≈ -3.01988

```

```

import numpy as np

# =====
# Core primitives: H(q, alpha, beta, gamma, delta), Doob(Q), gap
# =====

def q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta):
    """
    Build a (N+1)x(N+1) symmetric tridiagonal 'Hamiltonian' H
    of q-Racah type for given parameters.
    """
    A = np.zeros(N+1)
    B = np.zeros(N+1)
    C = np.zeros(N+1)

    for n in range(0, N+1):
        if n < N:
            numA = ((1 - alpha*q**(n+1)) *
                    (1 - beta*delta*q**(n+1)) *
                    (1 - gamma*q**(n+1)) *
                    (1 - delta*q**(n+1)))
            denA = ((1 - delta*q**(2*n+1)) *
                    (1 - delta*q**(2*n+2)))
            valA = numA/denA
            A[n] = np.sqrt(max(valA, 0.0))

            if n > 0:
                numC = ((1 - q**n) *
                        (1 - beta*q**n) *
                        (1 - gamma*q**n) *
                        (1 - alpha*delta*q**n))
                denC = ((1 - delta*q**(2*n)) *
                        (1 - delta*q**(2*n+1)))
                valC = numC/denC
                C[n] = np.sqrt(max(valC, 0.0))

            B[n] = -(A[n]**2 + C[n]**2)

    H = np.zeros((N+1, N+1))
    for n in range(N+1):
        H[n, n] = -B[n]
        if n < N:
            H[n, n+1] = -A[n]
            H[n+1, n] = -A[n]
        if n > 0:
            H[n, n-1] = -C[n]
            H[n-1, n] = -C[n]

    return H

```

```

def doob_transform(H, tol=1e-12):
    """
    Given symmetric H, construct Doob generator Q from ground state psi0.

    Returns:
        Q, evals_H, psi0, ok_flag
    where ok_flag=False if the ground state is not strictly positive.
    """
    evals, evecs = np.linalg.eigh(H)
    idx = np.argsort(evals)
    evals = evals[idx]
    psi0 = evecs[:, idx[0]]

    psi0 = np.real_if_close(psi0)
    psi0 = np.abs(psi0)

    if np.min(psi0) < tol:
        # ground state not strictly positive -> Doob transform is suspect
        return None, evals, psi0, False

    psi0 /= psi0.sum()

    n = H.shape[0]
    Q = np.zeros_like(H)
    for i in range(n):
        for j in range(n):
            if i != j and H[i, j] != 0:
                Q[i, j] = -H[i, j] * psi0[j] / psi0[i]
            Q[i, i] = -Q[i, :].sum()

    return Q, evals, psi0, True

def spectral_gap(Q, tol=1e-12):
    """
    For a continuous-time generator Q with eigenvalues:
        0 =  $\lambda_0$  >  $\lambda_1$  > ...
    return m =  $-\lambda_1$ .
    """
    eig = np.linalg.eigvals(Q)
    eig = np.real_if_close(eig, tol=1e-9)
    eig_sorted = np.sort(eig)
    neg = eig_sorted[eig_sorted < -tol]
    if neg.size == 0:
        return 0.0
    return float(-neg[-1])

```

```

# =====
# Experiment harness: flows, stability checks, summaries
# =====

```

```

def evaluate_model(N, q, alpha, beta, gamma, delta, tol=1e-10):
    """
    Build H, Doob(Q), and extract gap with sanity checks.
    Returns:
        {
            'ok': bool,
            'gap': float or 0,
            'evals_H': ...,
            'psi0_min': ...,
        }
    """
    try:
        H = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
    except Exception as e:
        return {'ok': False, 'gap': 0.0, 'error': f'H build error: {e}'}

    Q, evals_H, psi0, ok = doob_transform(H, tol=tol)
    if not ok or Q is None:
        return {
            'ok': False,
            'gap': 0.0,
            'evals_H': evals_H,
            'psi0_min': float(np.min(psi0)),
            'psi0': psi0
        }

    # Check Q row sums ~0
    row_sums = Q.sum(axis=1)
    if np.max(np.abs(row_sums)) > 1e-6:
        return {
            'ok': False,
            'gap': 0.0,
            'evals_H': evals_H,
            'psi0_min': float(np.min(psi0)),
            'row_sums': row_sums
        }

    gap = spectral_gap(Q, tol=tol)
    return {
        'ok': True,
        'gap': gap,
        'evals_H': evals_H,
        'psi0_min': float(np.min(psi0)),
    }

def flow_over_q(N, q0, q1, steps, alpha, beta, gamma, delta):
    """
    Flow q linearly from q0 to q1, evaluate gap and validity at each step.
    Returns list of dicts [{ 't':..., 'q':..., 'ok':..., 'gap':...}, ...]
    """

```

```

t_grid = np.linspace(0.0, 1.0, steps)
out = []
for t in t_grid:
    q = q0 + (q1 - q0)*t
    res = evaluate_model(N, q, alpha, beta, gamma, delta)
    out.append({
        't': float(t),
        'q': float(q),
        'ok': res['ok'],
        'gap': float(res['gap']),
        'psi0_min': float(res.get('psi0_min', 0.0))
    })
return out

def flow_over_alpha(N, q, a0, a1, steps, beta, gamma, delta):
    """
    Flow alpha linearly from a0 to a1, holding q,beta,gamma,delta fixed.
    """
    t_grid = np.linspace(0.0, 1.0, steps)
    out = []
    for t in t_grid:
        alpha = a0 + (a1 - a0)*t
        res = evaluate_model(N, q, alpha, beta, gamma, delta)
        out.append({
            't': float(t),
            'alpha': float(alpha),
            'ok': res['ok'],
            'gap': float(res['gap']),
            'psi0_min': float(res.get('psi0_min', 0.0))
        })
    return out

def classify_flow(flow, field_name='gap', ok_key='ok'):
    """
    Given a flow list, classify it:
    - 'good_monotone' : ok everywhere, gap>0, and monotone
    - 'good_nonmonotone' : ok, gap>0 everywhere, but not monotone
    - 'collapse' : ok stops somewhere (psi0 not positive, or gap→0)
    - 'broken' : many invalid points

    Returns a dict with summary metrics.
    """
    gaps = np.array([f[field_name] for f in flow])
    oks = np.array([bool(f[ok_key]) for f in flow])

    if not np.any(oks):
        return {'status': 'broken', 'notes': 'no valid points', 'min_gap': 0

    valid_gaps = gaps[oks]
    min_gap = float(valid_gaps.min())

```

```

max_gap = float(valid_gaps.max())

# collapse if any ok→False or gaps hit exactly 0
collapse = (np.any(~oks) or np.any(valid_gaps <= 1e-8))

# check monotonicity on valid segments
diffs = np.diff(valid_gaps)
mono_dec = np.all(diffs <= 1e-6)
mono_inc = np.all(diffs >= -1e-6)

if collapse:
    status = 'collapse'
elif mono_dec or mono_inc:
    status = 'good_monotone'
else:
    status = 'good_nonmonotone'

return {
    'status': status,
    'min_gap': min_gap,
    'max_gap': max_gap,
    'monotone_decreasing': bool(mono_dec),
    'monotone_increasing': bool(mono_inc),
    'any_invalid': bool(np.any(~oks)),
}

# =====
# "Next steps finder": scan a few flows and summarize
# =====

def run_next_steps_scans():
    """
    This is the part that answers: "what next should I explore?"

    It runs:
    - q-flows from various q0→q1
    - alpha-flows for fixed q
    and classifies each, printing a compact summary.
    """
    N = 4

    experiments = []

    # 1. q-flows with fixed Askey params
    for q0, q1 in [(0.8, 0.99), (0.7, 0.95), (0.9, 0.99)]:
        exp = {
            'type': 'q_flow',
            'N': N,
            'q0': q0,
            'q1': q1

```

```

        q1 = q1,
        'alpha': 1.0,
        'beta': 1.0,
        'gamma': 1.0,
        'delta': 1.0,
    }
    flow = flow_over_q(N, q0, q1, steps=21,
                       alpha=exp['alpha'],
                       beta=exp['beta'],
                       gamma=exp['gamma'],
                       delta=exp['delta'])
    cls = classify_flow(flow)
    exp['summary'] = cls
    exp['flow'] = flow
    experiments.append(exp)

# 2. alpha-flows at fixed q
for (q, a0, a1) in [(0.95, 0.5, 1.5), (0.9, 0.7, 1.3)]:
    exp = {
        'type': 'alpha_flow',
        'N': N,
        'q': q,
        'a0': a0,
        'a1': a1,
        'beta': 1.0,
        'gamma': 1.0,
        'delta': 1.0,
    }
    flow = flow_over_alpha(N, q, a0, a1, steps=21,
                           beta=exp['beta'],
                           gamma=exp['gamma'],
                           delta=exp['delta'])
    cls = classify_flow(flow)
    exp['summary'] = cls
    exp['flow'] = flow
    experiments.append(exp)

# Print summary
print("=== FLOW SUMMARY ===")
for i, exp in enumerate(experiments):
    s = exp['summary']
    if exp['type'] == 'q_flow':
        print(f"[{i}] q-flow: q0={exp['q0']}, q1={exp['q1']}, alpha={exp['alpha']}")
    else:
        print(f"[{i}] alpha-flow: q={exp['q']}, a0={exp['a0']}, a1={exp['a1']}")
    print(f"      status={s['status']}, "
          f"min_gap={s['min_gap']:.6f}, max_gap={s['max_gap']:.6f}, "
          f"mono_dec={s['monotone_decreasing']}, mono_inc={s['monotone_increasing']}, "
          f"any_invalid={s['any_invalid']}")
print("=====")

```

```

    return experiments

if __name__ == "__main__":
    exps = run_next_steps_scans()
    # You can inspect `exps` in Colab to drill into specific flows.

=== FLOW SUMMARY ===
[0] q-flow: q0=0.8, q1=0.99, alpha=1.0
    status=good_monotone, min_gap=0.015902, max_gap=0.237211, mono_dec=True,
[1] q-flow: q0=0.7, q1=0.95, alpha=1.0
    status=good_monotone, min_gap=0.076270, max_gap=0.283585, mono_dec=True,
[2] q-flow: q0=0.9, q1=0.99, alpha=1.0
    status=good_monotone, min_gap=0.015902, max_gap=0.142597, mono_dec=True,
[3] alpha-flow: q=0.95, a0=0.5, a1=1.5
    status=collapse, min_gap=0.073952, max_gap=0.119351, mono_dec=True, mono
[4] alpha-flow: q=0.9, a0=0.7, a1=1.3
    status=collapse, min_gap=0.140816, max_gap=0.162609, mono_dec=False, mon
=====

```

```

import numpy as np

# -----
# We assume you already have:
#   q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
#   doob_transform(H, tol)
#   spectral_gap(Q, tol)
# from the previous cells.
# -----

def gap_for_N_q(N, q, alpha=1.0, beta=1.0, gamma=1.0, delta=1.0, tol=1e-12):
    """Compute gap for given (N,q) with sanity checks."""
    H = q_racah_jacobi_matrix(N, q, alpha, beta, gamma, delta)
    Q, evals_H, psi0, ok = doob_transform(H, tol=tol)
    if (not ok) or Q is None:
        return 0.0, False
    # check row sums
    row_sums = Q.sum(axis=1)
    if np.max(np.abs(row_sums)) > 1e-6:
        return 0.0, False
    g = spectral_gap(Q, tol=tol)
    return g, True

def scan_N_q_grid(N_list, q_values,
                  alpha=1.0, beta=1.0, gamma=1.0, delta=1.0,
                  tol=1e-12):
    """
    For each q in q_values and N in N_list, compute gap(N,q).
    Returns a dict:
        gaps[(N,q)] = (gap, ok)
    and prints a summary per-q.
    """

```



```

"""
gaps = {}
print("=== Finite-size scaling of gap(N,q) ===")
for q in q_values:
    g_list = []
    ok_list = []
    for N in N_list:
        g, ok = gap_for_N_q(N, q, alpha, beta, gamma, delta, tol=tol)
        gaps[(N,q)] = (g, ok)
        g_list.append(g)
        ok_list.append(ok)
    g_arr = np.array(g_list)
    ok_arr = np.array(ok_list)

    if not np.all(ok_arr):
        status = "INVALID_POINTS"
    else:
        status = "OK"

    # only consider valid entries for min/max
    valid_gaps = g_arr[ok_arr]
    if valid_gaps.size > 0:
        min_gap = float(valid_gaps.min())
        max_gap = float(valid_gaps.max())
        # monotonicity in N
        diffs = np.diff(valid_gaps)
        mono_dec = bool(np.all(diffs <= 1e-6))
        mono_inc = bool(np.all(diffs >= -1e-6))
    else:
        min_gap = 0.0
        max_gap = 0.0
        mono_dec = False
        mono_inc = False

    print(f"q={q:.3f}  status={status}  "
          f"min_gap_over_N={min_gap:.6f}, max_gap_over_N={max_gap:.6f}, "
          f"mono_dec_in_N={mono_dec}, mono_inc_in_N={mono_inc}")
    for N, g, ok in zip(N_list, g_list, ok_list):
        print(f"    N={N:2d}: gap={g:.6f}, ok={ok}")
print("=====")
return gaps

# -----
# RUN: choose N_list and q_values
# -----

N_list = [4, 6, 8, 10, 12]          # system 'size' / polynomial degree
q_values = np.linspace(0.80, 0.99, 10) # same good q-window you probed

gaps_N_q = scan_N_q_grid(N_list, q_values,
                          alpha=1.0, beta=1.0, gamma=1.0, delta=1.0.

```

```

--rho --, --gamma --, --delta --,
tol=1e-12)

```

```

=== Finite-size scaling of gap(N,q) ===
q=0.800 status=OK min_gap_over_N=0.136564, max_gap_over_N=0.237211, mono_de
N= 4: gap=0.237211, ok=True
N= 6: gap=0.205060, ok=True
N= 8: gap=0.160588, ok=True
N=10: gap=0.137868, ok=True
N=12: gap=0.136564, ok=True
q=0.821 status=OK min_gap_over_N=0.123140, max_gap_over_N=0.221670, mono_de
N= 4: gap=0.221670, ok=True
N= 6: gap=0.200275, ok=True
N= 8: gap=0.159895, ok=True
N=10: gap=0.131010, ok=True
N=12: gap=0.123140, ok=True
q=0.842 status=OK min_gap_over_N=0.112322, max_gap_over_N=0.203772, mono_de
N= 4: gap=0.203772, ok=True
N= 6: gap=0.192821, ok=True
N= 8: gap=0.159644, ok=True
N=10: gap=0.128273, ok=True
N=12: gap=0.112322, ok=True
q=0.863 status=OK min_gap_over_N=0.106851, max_gap_over_N=0.183474, mono_de
N= 4: gap=0.183474, ok=True
N= 6: gap=0.181873, ok=True
N= 8: gap=0.157961, ok=True
N=10: gap=0.128956, ok=True
N=12: gap=0.106851, ok=True
q=0.884 status=OK min_gap_over_N=0.107553, max_gap_over_N=0.166742, mono_de
N= 4: gap=0.160793, ok=True
N= 6: gap=0.166742, ok=True
N= 8: gap=0.152728, ok=True
N=10: gap=0.130301, ok=True
N=12: gap=0.107553, ok=True
q=0.906 status=OK min_gap_over_N=0.110700, max_gap_over_N=0.146937, mono_de
N= 4: gap=0.135803, ok=True
N= 6: gap=0.146937, ok=True
N= 8: gap=0.141960, ok=True
N=10: gap=0.128309, ok=True
N=12: gap=0.110700, ok=True
q=0.927 status=OK min_gap_over_N=0.108632, max_gap_over_N=0.124100, mono_de
N= 4: gap=0.108632, ok=True
N= 6: gap=0.122206, ok=True
N= 8: gap=0.124100, ok=True
N=10: gap=0.118991, ok=True
N=12: gap=0.109437, ok=True
q=0.948 status=OK min_gap_over_N=0.079450, max_gap_over_N=0.099322, mono_de
N= 4: gap=0.079450, ok=True
N= 6: gap=0.092546, ok=True
N= 8: gap=0.098222, ok=True
N=10: gap=0.099322, ok=True
N=12: gap=0.097192, ok=True
q=0.969 status=OK min_gap_over_N=0.048463, max_gap_over_N=0.069752, mono_de
N= 4: gap=0.048463, ok=True
N= 6: gap=0.058194, ok=True

```

```

N= 8: gap=0.064111, ok=True
N=10: gap=0.067743, ok=True
N=12: gap=0.069752, ok=True
q=0.990 status=OK min_gap_over_N=0.015902, max_gap_over_N=0.025988, mono_de
N= 4: gap=0.015902, ok=True
N= 6: gap=0.019595, ok=True

```

```

# Fit  $m_q \sim (1-q)^{\nu}$  across q values near 1

qs = []
mqs = []

for q in q_values: # reuse your previous q_values
    # smallest gap over N at this q
    gaps = [gaps_N_q[(N, q)]] for N in N_list]
    m = min(gaps)
    qs.append(q)
    mqs.append(m)

qs = np.array(qs)
mqs = np.array(mqs)

# Only fit near  $q \sim 1$ 
mask = qs > 0.92
q_fit = qs[mask]
m_fit = mqs[mask]

# Fit  $\log(m) = \nu * \log(1-q) + c$ 
X = np.vstack([np.log(1 - q_fit), np.ones_like(q_fit)]).T
nu, c = np.linalg.lstsq(X, np.log(m_fit), rcond=None)[0]

print("Critical exponent nu ≈", nu)

```

Critical exponent nu ≈ 0.9668203676346614

```

import numpy as np

# -----
# Assume you already have:
#   q_racah_jacobi_matrix
#   doob_transform
#   spectral_gap
# -----

# ---- 1. q-Racah overlap kernel R(x,y) (simple truncated version) ----
def q_racah_kernel(x_vals, y_vals, q):
    """
    Build a discrete q-Racah overlap kernel matrix:
     $R_{\{ij\}} = R_r(x_i, y_j; q)$ 
    """

```

```

We use a simplified symmetric version:  $\exp(-|x-y| * (1-q))$ .
Replace later with true  $\phi_3$  when needed.
"""

R = np.zeros((len(x_vals), len(y_vals)))
for i,x in enumerate(x_vals):
    for j,y in enumerate(y_vals):
        R[i,j] = np.exp(-(abs(x-y))*(1-q))
# normalize rows
R = R / R.sum(axis=1, keepdims=True)
return R

# ---- 2. Wilson-loop multiplication W(chi) ----
def wilson_operator(chi_vals, I=1):
    """
    Wilson operator W_I acting as multiplication:
        W f(chi) = p_I(chi + chi^{-1}) f(chi)
    Use p_I(z) = z^I as placeholder; can replace with Chebyshev/trace-polyno
    """
    z = chi_vals + 1.0/chi_vals
    W = np.diag(z**I)
    return W

# ---- 3. Boundary→bulk projection Lambda (simple) ----
def projection_kernel(chi_vals, N):
    """
    Simple version of Lambda: embeds boundary states into bulk Doob states.
    Use a normalized Gaussian-like projection for now.
    Replace with true RPP projection when ready.
    """
    Lambda = np.zeros((N+1, len(chi_vals)))
    for i in range(N+1):
        for j,chi in enumerate(chi_vals):
            Lambda[i,j] = np.exp(-(i - 2*chi)**2 / 10.0)
    # Normalize columns
    Lambda = Lambda / Lambda.sum(axis=0, keepdims=True)
    return Lambda

# ---- 4. Build full composite operator T_q ----
def build_Tq(N, q, chi_vals):
    # Step 1: bulk Doob generator exponential
    H = q_racah_jacobi_matrix(N, q, 1.0,1.0,1.0,1.0)
    Q,_ = doob_transform(H)
    T_bulk = np.real_if_close(np.linalg.expm(Q)) # exp(Q)

    # Step 2: boundary Wilson-loop operator
    W = wilson_operator(chi_vals, I=1)

    # Step 3: boundary change-of-basis kernel
    R = q_racah_kernel(chi_vals, chi_vals, q)

    # Step 4: projection Lambda

```

```

Lambda = projection_kernel(chi_vals, N)
Lambda_T = Lambda.T

# Full operator:
# T = Lambda^T * T_bulk * Lambda * R * W
T = Lambda_T @ T_bulk @ Lambda @ R @ W
return T

# ---- 5. Scan spectrum of T_q ----
def analyze_Tq(N, q):
    chi_vals = np.linspace(1.1, 2.0, 10)
    T = build_Tq(N, q, chi_vals)
    eigvals = np.linalg.eigvals(T)
    eigvals = np.real_if_close(eigvals)
    # Sort by magnitude descending
    eigvals_sorted = np.sort(np.abs(eigvals))[:, -1]
    gap = eigvals_sorted[0] - eigvals_sorted[1]
    return eigvals_sorted, gap

# RUN DEMO
N = 8
q = 0.92
eigvals, gap = analyze_Tq(N, q)
print("Eigenvalues of T_q magnitude:", eigvals)
print("Transfer-matrix gap:", gap)

```

```

-----
ValueError                                Traceback (most recent call last)
/tmp/ipython-input-4229064606.py in <cell line: 0>()
    86 N = 8
    87 q = 0.92
--> 88 eigvals, gap = analyze_Tq(N, q)
    89 print("Eigenvalues of T_q magnitude:", eigvals)
    90 print("Transfer-matrix gap:", gap)

```

```

----- 1 frames -----
/tmp/ipython-input-4229064606.py in build_Tq(N, q, chi_vals)
    54 # Step 1: bulk Doob generator exponential
    55 H = q_racah_jacobi_matrix(N, q, 1.0, 1.0, 1.0, 1.0)
--> 56 Q, __ = doob_transform(H)
    57 T_bulk = np.real_if_close(np.linalg.expm(Q)) # exp(Q)
    58

```

```
ValueError: too many values to unpack (expected 3)
```

```
import numpy as np
```

```
# ----- 1. simple q-Racah-like overlap kernel (placeholder) -----
```

```

def q_racah_kernel(x_vals, y_vals, q):
    """
    Discrete 'overlap' kernel  $R_{ij}$ . For now, use a simple
    decaying function of  $|x-y|$  that depends on  $q$ .
    Replace later with exact  $4\phi_3$  if you want.
    """
    R = np.zeros((len(x_vals), len(y_vals)))
    for i, x in enumerate(x_vals):
        for j, y in enumerate(y_vals):
            R[i, j] = np.exp(-(abs(x - y)) * (1.0 - q))
    # normalize rows to make it a stochastic-like kernel
    R = R / R.sum(axis=1, keepdims=True)
    return R

# ----- 2. Wilson-loop operator on FN-like variable  $\chi$  -----

def wilson_operator(chi_vals, I=1):
    """
    Wilson operator  $W_I$ : multiplication by  $p_I(\chi + \chi^{-1})$ .
    For now  $p_I(z) = z^I$ .
    """
    z = chi_vals + 1.0 / chi_vals
    return np.diag(z**I)

# ----- 3. Boundary→bulk projection kernel  $\Lambda$  -----

def projection_kernel(chi_vals, N):
    """
    Simple boundary→bulk kernel  $\Lambda_{ij}$ ,  $i=0..N$ ,  $j$  index  $\chi$ .
    Using a soft Gaussian in  $i$  centered at  $2\chi$  as a placeholder.
    Columns normalized so each  $\chi$  maps to a probability over bulk sites.
    """
    Lambda = np.zeros((N+1, len(chi_vals)))
    for i in range(N+1):
        for j, chi in enumerate(chi_vals):
            Lambda[i, j] = np.exp(-(i - 2.0*chi)**2 / 10.0)
    Lambda = Lambda / Lambda.sum(axis=0, keepdims=True)
    return Lambda

# ----- 4. expm of generator  $Q$  via eigendecomposition -----

def expm_generator(Q, t=1.0):
    """
    Compute  $e^{tQ}$  for finite-dimensional generator  $Q$  using eigendecomposition
    """
    eigvals, eigvecs = np.linalg.eig(Q)
    eigvals = np.real_if_close(eigvals, tol=1e-9)
    eigvecs = np.real_if_close(eigvecs, tol=1e-9)

    D = np.diag(np.exp(t * eigvals))
    ...

```

```

    vinv = np.linalg.inv(eigvecs)
    T = eigvecs @ D @ Vinv
    return np.real_if_close(T, tol=1e-9)

# ----- 5. Build composite transfer operator T_q -----

def build_Tq(N, q, chi_vals):
    # bulk Doob generator
    H = q_racah_jacobi_matrix(N, q, 1.0, 1.0, 1.0, 1.0)
    Q, evals_H, psi0, ok = doob_transform(H) # NOTE: 4 outputs
    if not ok:
        raise ValueError("Doob transform invalid for these parameters")

    T_bulk = expm_generator(Q, t=1.0) # one 'time' step

    # boundary pieces
    W = wilson_operator(chi_vals, I=1)
    R = q_racah_kernel(chi_vals, chi_vals, q)
    Lambda = projection_kernel(chi_vals, N)
    Lambda_T = Lambda.T

    # T_q =  $\Lambda^T$  * T_bulk *  $\Lambda$  * R * W
    T = Lambda_T @ T_bulk @ Lambda @ R @ W
    return T

# ----- 6. Analyze spectrum of T_q -----

def analyze_Tq(N, q):
    # sample  $\chi$  grid (Fenchel-Nielsen-like variable)
    chi_vals = np.linspace(1.1, 2.0, 10)

    T = build_Tq(N, q, chi_vals)

    eigvals = np.linalg.eigvals(T)
    eigvals = np.real_if_close(eigvals, tol=1e-9)

    mags = np.sort(np.abs(eigvals))[:, -1] # descending by  $|\lambda|$ 
    if len(mags) < 2:
        gap = 0.0
    else:
        gap = mags[0] - mags[1]

    return eigvals, mags, gap

# ----- 7. Demo run -----

N = 8
q = 0.92

eigvals_T, mags_T, gap_T = analyze_Tq(N, q)
print("Eigenvalues of T_q:", eigvals_T)

```

```
print("Magnitudes sorted:", mags_T)  
print("Transfer-matrix gap:", gap_T)
```

```
Eigenvalues of T_q: [ 3.05815424e+00  1.41940680e-03  3.39883558e-06  6.89731  
9.45623433e-12  8.01451817e-15 -7.63868531e-17 -7.92357927e-17  
5.38552070e-17  5.38552070e-17]  
Magnitudes sorted: [3.05815424e+00  1.41940680e-03  3.39883558e-06  6.89731968e-  
9.45623433e-12  8.01451817e-15  7.92357927e-17  7.63868531e-17  
5.38552070e-17  5.38552070e-17]  
Transfer-matrix gap: 3.05673483370357
```