

Exploring the housing crisis with ggplot2 and plyr

Hadley Wickham

1. Introduction to the data

2. Basic graphics
(histograms & scatterplots)

3. Adding extra variables
(aesthetics and facetting)

4. Time series
(using plyr to manipulate data)


5. Resources

About the data

521,495 house sales scraped from SF Chronicle, March 2003—November 2008.

Addresses geocoded using USC WebGIS.
(83% to interpolated city block or better)

Variables: longitude, latitude, date, price, bedrooms, area





433,157 points!

Basic graphics:

Scatterplots, bar charts and histograms

Where are the
houses?








```
sf <- subset(precise, city == "San Francisco")  
ggplot(sf, aes(x = long, y = lat)) +  
  geom_point(size = 0.5)
```




14,781 points!







```
# In principle:
```


```
ggplot(sf, aes(long, lat)) +  
  geom_point(stat = "sum")
```


```
# In practice: (takes 42 seconds)
```


```
sfsum <- ddpoly(sf, c("lat", "long"), summarise,  
  n = length(lat),  
  avg_year = mean(year, na.rm = TRUE),  
  .progress = "text"  
)
```


```
ggplot(sfsum, aes(long, lat, size = n)) +  
  geom_point(alpha = 1/2) +  
  scale_area(to = c(0.3, 6), breaks = c(1, 50, 100, 200, 252))
```


When were they build?












How does location
vary with age?


Additional variables

Can supplement any existing plot with additional variables in two ways: adding **aesthetics**, or creating **facets**.

Saw example of using size. Other aesthetics are: colour, fill, shape, linetype, alpha.

Facetting creates small multiples of subsets of the data.






```
ggplot(sfsum, aes(long, lat, colour = avg_year)) +  
  geom_point(alpha = 1/2, size = 2)
```


Interactive demo


(a taste of future directions)

Let's try facetting

First, need a categorical variable to facet by







```
# Recount number at each location
sfsumsect <- ddpoly(sf, c("lat", "long", "sect"),
  "nrow", .progress = "text")

# Display spatial distribution of each cut
ggplot(sfsumsect, aes(long, lat, size = nrow)) +
  geom_point(alpha = 1/2) +
  scale_area(to = c(0.5, 3)) +
  facet_wrap(~ sect)
```



Time series


using plyr to manipulate data

Zoom out to the Bay area.

What's going on in different cities?


Focus on average sale price,
summarising patterns, then
investigating possible explanatory
variables.






```
library(mgcv)
smooth <- function(y, x) {
  as.numeric(predict(gam(y ~ s(x)))
}


bigsum <- ddp1y(bigsum, "city", transform,
  price_s = smooth(price, as.numeric(date)))
```







```
index <- function(y, x) {  
  y / y[order(x)[1]]  
}
```


```
bigsum <- ddp1y(bigsum, "city", transform,  
  price_si = index(price_s, date))
```





Brentwood




Brentwood











```
ggplot(covar, aes(peak, plummet)) +
  geom_point() +
  geom_text(aes(label = city), size = 4, hjust = -0.05)
```




```
covar$delta <- with(covar, plummet - peak)  
  
census <- read.csv("census-city.csv")  
covar <- join(covar, census, by = "city")
```





Learn more



ggplot2

<http://had.co.nz/ggplot2>


<http://groups.google.com/group/ggplot2>



plyr

<http://had.co.nz/plyr>

<http://groups.google.com/group/manipulatr>



Chapter 18

All code and data
openly licensed:
[http://github.com/
hadley/sfhousing](http://github.com/hadley/sfhousing)

Beautiful data is
reproducible!

Thank you!