

Class 10: Halloween Mini-Project

Anh Tran

```
url <- "https://raw.githubusercontent.com/fivethirtyeight/data/master/candy-power-ranking/"
candy <- read.csv(url, row.names=1)
head(candy)
```

	chocolate	fruity	caramel	peanutyalmondy	nougat	crispedricewafer
100 Grand	1	0	1	0	0	1
3 Musketeers	1	0	0	0	1	0
One dime	0	0	0	0	0	0
One quarter	0	0	0	0	0	0
Air Heads	0	1	0	0	0	0
Almond Joy	1	0	0	1	0	0

	hard	bar	pluribus	sugarpercent	pricepercent	winpercent
100 Grand	0	1	0	0.732	0.860	66.97173
3 Musketeers	0	1	0	0.604	0.511	67.60294
One dime	0	0	0	0.011	0.116	32.26109
One quarter	0	0	0	0.011	0.511	46.11650
Air Heads	0	0	0	0.906	0.511	52.34146
Almond Joy	0	1	0	0.465	0.767	50.34755

Q1. How many different candy types are in this dataset?

```
nrow(candy)
```

```
[1] 85
```

Q2. How many fruity candy types are in the dataset?

```
sum(candy$fruity)
```

[1] 38

Q3. What is your favorite candy in the dataset and what is it's winpercent value?

My favorite candy is Milky Way

```
#rownames(candy)
candy["Milky Way",]$winpercent
```

[1] 73.09956

Q4. What is the winpercent value for “Kit Kat”?

```
candy["Kit Kat",]$winpercent
```

[1] 76.7686

Q5. What is the winpercent value for “Tootsie Roll Snack Bars”?

```
candy["Tootsie Roll Snack Bars",]$winpercent
```

[1] 49.6535

```
#install.packages("skimr")
```

```
#library("skimr")
```

```
#Instead of using library() to load the whole package, can use this function instead for j
```

```
skimr::skim(candy)
```

Table 1: Data summary

Name	candy
Number of rows	85
Number of columns	12
Column type frequency:	
numeric	12

Table 1: Data summary

Group variables	None
-----------------	------

Variable type: numeric

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
chocolate	0	1	0.44	0.50	0.00	0.00	0.00	1.00	1.00	
fruity	0	1	0.45	0.50	0.00	0.00	0.00	1.00	1.00	
caramel	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
peanutyalmondy	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
nougat	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
crispedricewafer	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
hard	0	1	0.18	0.38	0.00	0.00	0.00	0.00	1.00	
bar	0	1	0.25	0.43	0.00	0.00	0.00	0.00	1.00	
pluribus	0	1	0.52	0.50	0.00	0.00	1.00	1.00	1.00	
sugarpercent	0	1	0.48	0.28	0.01	0.22	0.47	0.73	0.99	
pricepercent	0	1	0.47	0.29	0.01	0.26	0.47	0.65	0.98	
winpercent	0	1	50.32	14.71	22.45	39.14	47.83	59.86	84.18	

Q6. Is there any variable/column that looks to be on a different scale to the majority of the other columns in the dataset?

Yes, winpercent is the only column that looks different from other other columns as its values are much higher than 0.


Q7. What do you think a zero and one represent for the candy\$chocolate column?

If contains chocolate or not (1=yes, 0=no)


Q8. Plot a histogram of winpercent values

```
hist(candy$winpercent)
```

Histogram of candy\$winpercent



```
#install.packages("ggplot2")  
  
library(ggplot2)  
ggplot(candy) +  
  aes(winpercent) +  
  geom_histogram(bins=10, fill="black", col="pink")
```



Q9. Is the distribution of winpercent values symmetrical?

No the distribution is not symmetrical. It is slightly skewed to the left.

Q10. Is the center of the distribution above or below 50%?

```
median(candy$winpercent)
```

```
[1] 47.82975
```

It is below 50%

Q11. On average is chocolate candy higher or lower ranked than fruit candy?

```
chocolate.inds <- as.logical(candy$chocolate)
chocolate.wins <- candy[chocolate.inds,]$winpercent
mean(chocolate.wins)
```

```
[1] 60.92153
```

```
fruity.inds <- as.logical(candy$fruity)
fruity.wins <- candy[fruity.inds,]$winpercent
mean(fruity.wins)
```

```
[1] 44.11974
```

```
t.test(chocolate.wins, fruity.wins)
```

Welch Two Sample t-test

```
data: chocolate.wins and fruity.wins
t = 6.2582, df = 68.882, p-value = 2.871e-08
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
 11.44563 22.15795
sample estimates:
mean of x mean of y
 60.92153 44.11974
```

Chocolate candy is higher ranked than fruit candy

Q12. Is this difference statistically significant?

Yes, this difference is statistically significant

3. Overall Candy Rankings

13. What are the five least liked candy types in this set?

```
head(candy[order(candy$winpercent),], n=5)
```

	chocolate	fruity	caramel	peanutyalmondy	nougat
Nik L Nip	0	1	0	0	0
Boston Baked Beans	0	0	0	1	0
Chiclets	0	1	0	0	0
Super Bubble	0	1	0	0	0
Jawbusters	0	1	0	0	0
	crispedricewafer	hard bar	pluribus	sugarpercent	pricepercent

Nik L Nip	0	0	0	1	0.197	0.976
Boston Baked Beans	0	0	0	1	0.313	0.511
Chiclets	0	0	0	1	0.046	0.325
Super Bubble	0	0	0	0	0.162	0.116
Jawbusters	0	1	0	1	0.093	0.511

	winpercent
Nik L Nip	22.44534
Boston Baked Beans	23.41782
Chiclets	24.52499
Super Bubble	27.30386
Jawbusters	28.12744

Q14. What are the top 5 all time favorite candy types out of this set?

```
head(candy[order(-candy$winpercent),], n=5)
```


	chocolate	fruity	caramel	peanut	almond	nougat
Reese's Peanut Butter cup	1	0	0		1	0
Reese's Miniatures	1	0	0		1	0
Twix	1	0	1		0	0
Kit Kat	1	0	0		0	0
Snickers	1	0	1		1	1

	crisped	rice	wafer	hard	bar	pluribus	sugar
Reese's Peanut Butter cup		0	0	0		0	0.720
Reese's Miniatures		0	0	0		0	0.034
Twix		1	0	1		0	0.546
Kit Kat		1	0	1		0	0.313
Snickers		0	0	1		0	0.546

	price	percent	winpercent
Reese's Peanut Butter cup	0.651		84.18029
Reese's Miniatures	0.279		81.86626
Twix	0.906		81.64291
Kit Kat	0.511		76.76860
Snickers	0.651		76.67378


Q15. Make a first barplot of candy ranking based on winpercent values.

```
library(ggplot2)
ggplot(candy) +
  aes(winpercent, rownames(candy)) +
  geom_col()
```




Q16. This is quite ugly, use the `reorder()` function to get the bars sorted by winpercent?

```
library(ggplot2)
ggplot(candy) +
  aes(winpercent, reorder(rownames(candy), winpercent)) +
  geom_col() +
  coord_fixed()
```

```
my_cols=rep("black", nrow(candy))
my_cols[as.logical(candy$chocolate)] ="chocolate"
my_cols[as.logical(candy$bar)]= "brown"
my_cols[as.logical(candy$fruity)]= "red"

ggplot(candy) +
  aes(winpercent, reorder(rownames(candy), winpercent)) +
  geom_col(fill=my_cols)
```



```
#Save the last ggplot as image
ggsave("tmp.png")
```

Saving 5.5 x 3.5 in image

Q17. What is the worst ranked chocolate candy?

Sixlets

Q18. What is the best ranked fruity candy?

Starburst

4. Taking a look at pricepercent

```
#install.packages("ggrepel")
library(ggrepel)

ggplot(candy) +
  aes(winpercent, pricepercent, label=rownames(candy)) +
  geom_point(col=my_cols) +
```

```
geom_text_repel(col=my_cols, size=2, max.overlaps=23)
```



Q19. Which candy type is the highest ranked in terms of winpercent for the least money - i.e. offers the most bang for your buck?

```
max <- which.max((candy[, "winpercent"] / candy[, "pricepercent"]))
candy[max,]
```

	chocolate	fruity	caramel	peanuty	almondy	nougat
Tootsie Roll Midgies	1	0	0	0	0	0
	crisped	ricewafer	hard bar	pluribus	sugar	percent
Tootsie Roll Midgies	0	0	0	1	0.174	
	pricepercent	winpercent				
Tootsie Roll Midgies	0.011	45.73675				

Q20. What are the top 5 most expensive candy types in the dataset and of these which is the least popular?

```
ord <- order(candy$pricepercent, decreasing = TRUE)
head(candy[ord, c(11,12)], n=5)
```

	pricepercent	winpercent
Nik L Nip	0.976	22.44534
Nestle Smarties	0.976	37.88719
Ring pop	0.965	35.29076
Hershey's Krackel	0.918	62.28448
Hershey's Milk Chocolate	0.918	56.49050


Among the top 5 most expensive candy types, the least popular is Nik L Nip

5. Exploring the correlation structure

```
#install.packages("corrplot")
library(corrplot)
```

corrplot 0.92 loaded

```
cij <- cor(candy)
corrplot(cij)
```



Q22. Examining this plot what two variables are anti-correlated (i.e. have minus values)?

chocolate and fruity

Q23. Similarly, what two variables are most positively correlated?

chocolate and winpercent

6. Principal Component Analysis

```
pca <- prcomp(candy, scale=TRUE)
summary(pca)
```


Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	2.0788	1.1378	1.1092	1.07533	0.9518	0.81923	0.81530
Proportion of Variance	0.3601	0.1079	0.1025	0.09636	0.0755	0.05593	0.05539
Cumulative Proportion	0.3601	0.4680	0.5705	0.66688	0.7424	0.79830	0.85369


	PC8	PC9	PC10	PC11	PC12
Standard deviation	0.74530	0.67824	0.62349	0.43974	0.39760
Proportion of Variance	0.04629	0.03833	0.03239	0.01611	0.01317
Cumulative Proportion	0.89998	0.93832	0.97071	0.98683	1.00000

```
#pca$rotation[]
```

```
plot(pca$x[,1], pca$x[,2])
```



```
plot(pca$x[,1], pca$x[,2], col=my_cols, xlab="PC1", ylab="PC2", pch=16)
```




```
my_data <- cbind(candy, pca$x[,1:3])
head(my_data)
```

	chocolate	fruity	caramel	peanut	almondy	nougat	crisped	rice	wafer
100 Grand	1	0	1		0	0			1
3 Musketeers	1	0	0		0	1			0
One dime	0	0	0		0	0			0
One quarter	0	0	0		0	0			0
Air Heads	0	1	0		0	0			0
Almond Joy	1	0	0		1	0			0

	hard	bar	pluribus	sugarpercent	pricepercent	winpercent	PC1
100 Grand	0	1	0	0.732	0.860	66.97173	-3.8198617
3 Musketeers	0	1	0	0.604	0.511	67.60294	-2.7960236
One dime	0	0	0	0.011	0.116	32.26109	1.2025836
One quarter	0	0	0	0.011	0.511	46.11650	0.4486538
Air Heads	0	0	0	0.906	0.511	52.34146	0.7028992
Almond Joy	0	1	0	0.465	0.767	50.34755	-2.4683383

	PC2	PC3
100 Grand	-0.5935788	2.1863087
3 Musketeers	-1.5196062	-1.4121986
One dime	0.1718121	-2.0607712
One quarter	0.4519736	-1.4764928
Air Heads	-0.5731343	0.9293893
Almond Joy	0.7035501	-0.8581089

```
p <- ggplot(my_data) +
  aes(x=PC1, y=PC2,
      size=winpercent/100,
      text=rownames(my_data),
      label=rownames(my_data)) +
  geom_point(col=my_cols)
p
```




```
library(ggrepel)

p + geom_text_repel(size=3.3, col=my_cols, max.overlaps = 10) +
  theme(legend.position = "none") +
  labs(title="Halloween Candy PCA Space",
        subtitle="Colored by type: chocolate bar (dark brown), chocolate other (light brown)",
        caption="Data from 538")
```

Warning: ggrepel: 54 unlabeled data points (too many overlaps). Consider increasing max.overlaps

Halloween Candy PCA Space


Colored by type: chocolate bar (dark brown), chocolate other (light brown),



Data from 538

```
#install.packages("plotly")
#library(plotly)
#ggplotly(p)

par(mar=c(8,4,2,2))
barplot(pca$rotation[,1], las=2, ylab="PC1 contribution")
```



Q24. What original variables are picked up strongly by PC1 in the positive direction? Do these make sense to you?

Fruity, hard, and pluribus. Yes, they make sense because these types of candy usually go together (fruity candies are hard and pluribus) so it makes sense that they are all positive values.