

Edeviser Complete Codebase Volume 04

Generated: 8/1/2026 | Author: Edeviser AI Reviewer

FILE: src/lib/schemas/coordinatorAcademic.ts

TYPE: .ts | LINES: 1-29 | SHA256: 6f5c83a985e2941e4bdc49f2cbc014efbe1966c40a0342aef484c5866f0cec64

```
1 | // =====
2 | // coordinatorAcademic – Zod schema for the coordinator "Me" academic edit form
3 | // =====
4 | // Validates the self-service academic profile fields (migration 20260823000001).
5 | // All fields are optional (blank allowed); years_experience must be blank or a
6 | // non-negative integer "d 80. Form values are strings (controlled inputs); the
7 | // submit handler maps blanks !' null and the experience string !' number.
8 | // =====
9 |
10 | import { z } from "zod";
11 |
12 | export const coordinatorAcademicSchema = z.object({
13 |   department: z.string().trim().max(120),
14 |   designation: z.string().trim().max(120),
15 |   academic_rank: z.string().trim().max(120),
16 |   highest_degree: z.string().trim().max(120),
17 |   years_experience: z
18 |     .string()
19 |     .trim()
20 |     .refine(
21 |       (v) => v === "" || (/^\d{1,2}$/.test(v) && Number(v) <= 80),
22 |       "Enter a whole number of years (0-80)"
23 |     ),
24 | });
25 |
26 | export type CoordinatorAcademicFormValues = z.infer<
27 |   typeof coordinatorAcademicSchema
28 | >;
29 |
```

FILE: src/lib/schemas/course.ts

TYPE: .ts | LINES: 1-29 | SHA256: 735f04a7ec8e6ac951490d6dd5e34fc4feb7267127f9da81a3e22f9783597f8d

```
1 | import { z } from "zod";
2 |
3 | export const createCourseSchema = z.object({
4 |   name: z.string().min(1, "Course name is required").max(255),
5 |   name_ar: z.string().max(255).optional(),
6 |   code: z.string().min(1, "Course code is required").max(50),
7 |   program_id: z.uuid(),
8 |   semester_id: z.uuid(),
9 |   teacher_id: z.uuid(),
10 |   academic_year: z
11 |     .string()
12 |     .min(1, "Academic year is required")
13 |     .default("2024-2025"),
14 |   semester: z.string().min(1, "Semester is required").default("Fall"),
15 |   is_active: z.boolean().default(true),
16 | });
17 |
18 | export const updateCourseSchema = z.object({
19 |   name: z.string().min(1).max(255).optional(),
20 |   name_ar: z.string().max(255).optional(),
21 |   code: z.string().min(1).max(50).optional(),
22 |   teacher_id: z.uuid().optional(),
23 |   semester_id: z.uuid().optional(),
24 |   is_active: z.boolean().optional(),
25 | });
26 |
27 | export type CreateCourseFormData = z.input<typeof createCourseSchema>;
28 | export type UpdateCourseFormData = z.infer<typeof updateCourseSchema>;
29 |
```

FILE: src/lib/schemas/courseFile.ts

TYPE: .ts | LINES: 1-9 | SHA256: 83145aa526d48d6d63c9708e6753d41ea9e4ca247941f550b03340b99f35a3a1

```
1 | import { z } from "zod";
2 |
3 | export const courseFileRequestSchema = z.object({
4 |   course_id: z.uuid(),
5 |   semester_id: z.uuid(),
6 | });
7 |
8 | export type CourseFileRequestData = z.infer<typeof courseFileRequestSchema>;
9 |
```

FILE: src/lib/schemas/courseModule.ts

TYPE: .ts | LINES: 1-25 | SHA256: 1a860c17398c4e9004544fda1599417bafb074b85a5b634e7f451d2e37d640e9

```
1 | import { z } from "zod";
2 |
3 | export const createModuleSchema = z.object({
4 |   course_id: z.uuid(),
5 |   title: z.string().min(1, "Module title is required").max(255),
6 |   description: z.string().optional(),
7 |   sort_order: z.number().int().min(0),
8 |   is_published: z.boolean().default(false),
9 | });
10 |
11 | export const createMaterialSchema = z.object({
12 |   module_id: z.uuid(),
13 |   title: z.string().min(1, "Material title is required").max(255),
14 |   type: z.enum(["file", "link", "video", "text"]),
15 | });
```

```

15 |   content_url: z.string().url().optional(),
16 |   file_path: z.string().optional(),
17 |   description: z.string().optional(),
18 |   sort_order: z.number().int().min(0),
19 |   is_published: z.boolean().default(false),
20 |   clo_ids: z.array(z.uuid()).optional(),
21 | });
22 |
23 | export type CreateModuleFormData = z.infer<typeof createModuleSchema>;
24 | export type CreateMaterialFormData = z.infer<typeof createMaterialSchema>;
25 |

```

FILE: src/lib/schemas/courseSection.ts

TYPE: .ts | LINES: 1-20 | SHA256: 75df1b12a27f926b4c72ad90a19e98b77515adcbe839a3b54ca30b755eaaaf448

```

1 | import { z } from "zod";
2 |
3 | export const createSectionSchema = z.object({
4 |   course_id: z.uuid(),
5 |   section_code: z.string().min(1, "Section code is required").max(10),
6 |   teacher_id: z.uuid(),
7 |   capacity: z.number().int().min(1).default(50),
8 |   is_active: z.boolean().default(true),
9 | });
10 |
11 | export const updateSectionSchema = z.object({
12 |   section_code: z.string().min(1).max(10).optional(),
13 |   teacher_id: z.uuid().optional(),
14 |   capacity: z.number().int().min(1).optional(),
15 |   is_active: z.boolean().optional(),
16 | });
17 |
18 | export type CreateSectionFormData = z.infer<typeof createSectionSchema>;
19 | export type UpdateSectionFormData = z.infer<typeof updateSectionSchema>;
20 |

```

FILE: src/lib/schemas/coverageHeatmap.ts

TYPE: .ts | LINES: 1-10 | SHA256: 6bd8ea1898ec5bb3d0cc17d1d76fff016e60fea75f870845c207261dd2c8e8b1

```

1 | import { z } from "zod";
2 |
3 | export const coverageHeatmapFilterSchema = z.object({
4 |   programId: z.string().uuid(),
5 |   semesterId: z.string().uuid().optional(),
6 |   attainmentThreshold: z.number().min(0).max(100).optional(),
7 | });
8 |
9 | export type CoverageHeatmapFilter = z.infer<typeof coverageHeatmapFilterSchema>;
10 |

```

FILE: src/lib/schemas/cqiPlan.ts

TYPE: .ts | LINES: 1-31 | SHA256: b965c3a30c875a5234447b121d919446791a3013ebb2e47ba73d16469ff56a10

```

1 | import { z } from "zod";
2 |
3 | const cqiStatusSchema = z.enum([
4 |   "planned",
5 |   "in_progress",
6 |   "completed",
7 |   "evaluated",
8 | ]);
9 |
10 | export const createCQIPlanSchema = z.object({
11 |   program_id: z.uuid(),
12 |   semester_id: z.uuid(),
13 |   outcome_id: z.uuid(),
14 |   outcome_type: z.enum(["PLO", "CLO"]),
15 |   baseline_attainment: z.number().min(0).max(100),
16 |   target_attainment: z.number().min(0).max(100),
17 |   action_description: z.string().min(1, "Action description is required"),
18 |   responsible_person: z.string().min(1, "Responsible person is required"),
19 |   status: cqiStatusSchema.default("planned"),
20 | });
21 |
22 | export const updateCQIPlanSchema = z.object({
23 |   action_description: z.string().min(1).optional(),
24 |   responsible_person: z.string().min(1).optional(),
25 |   status: cqiStatusSchema.optional(),
26 |   result_attainment: z.number().min(0).max(100).optional(),
27 | });
28 |
29 | export type CreateCQIPlanFormData = z.infer<typeof createCQIPlanSchema>;
30 | export type UpdateCQIPlanFormData = z.infer<typeof updateCQIPlanSchema>;
31 |

```

FILE: src/lib/schemas/department.ts

TYPE: .ts | LINES: 1-17 | SHA256: c6808bfc577a8a9ed20d35ffead5d9210841f4440a12839959179f1099144dc5

```

1 | import { z } from "zod";
2 |
3 | export const createDepartmentSchema = z.object({
4 |   name: z.string().min(1, "Department name is required").max(255),
5 |   code: z.string().min(1, "Department code is required").max(50),
6 |   head_of_department_id: z.uuid().optional(),
7 | });
8 |
9 | export const updateDepartmentSchema = z.object({
10 |   name: z.string().min(1).max(255).optional(),
11 |   code: z.string().min(1).max(50).optional(),
12 |   head_of_department_id: z.uuid().optional(),
13 | });
14 |
15 | export type CreateDepartmentFormData = z.infer<typeof createDepartmentSchema>;

```

```
16 | export type UpdateDepartmentFormData = z.infer<typeof updateDepartmentSchema>;
17 |
```

FILE: src/lib/schemas/discussion.ts

TYPE: .ts | LINES: 1-16 | SHA256: fd531a09fc4abb080d649da1189b1e0d15d13aeba9c546f035536f74046dca95

```
1 | import { z } from "zod";
2 |
3 | export const createThreadSchema = z.object({
4 |   course_id: z.uuid(),
5 |   title: z.string().min(1, "Thread title is required").max(255),
6 |   content: z.string().min(1, "Content is required"),
7 | });
8 |
9 | export const createReplySchema = z.object({
10 |   thread_id: z.uuid(),
11 |   content: z.string().min(1, "Reply content is required"),
12 | });
13 |
14 | export type CreateThreadFormData = z.infer<typeof createThreadSchema>;
15 | export type CreateReplyFormData = z.infer<typeof createReplySchema>;
16 |
```

FILE: src/lib/schemas/emailPrefs.ts

TYPE: .ts | LINES: 1-12 | SHA256: 551cd1a75ea6466dfb2ac0c0c0afef3c3d1709a050b96de89fb8e32d61ea41a1

```
1 | import { z } from "zod";
2 |
3 | export const emailPreferencesSchema = z.object({
4 |   streak_risk: z.boolean().default(true),
5 |   weekly_summary: z.boolean().default(true),
6 |   new_assignment: z.boolean().default(true),
7 |   grade_released: z.boolean().default(true),
8 |   notification_digest: z.boolean().default(false),
9 | });
10 |
11 | export type EmailPreferencesFormData = z.infer<typeof emailPreferencesSchema>;
12 |
```

FILE: src/lib/schemas/enrollmentImport.ts

TYPE: .ts | LINES: 1-10 | SHA256: 4a50d9b396b95379df08b631644fda7a00d47c3ac226466711385c0598207857

```
1 | import { z } from "zod";
2 |
3 | export const enrollmentImportRowSchema = z.object({
4 |   student_email: z.email("Invalid student email"),
5 |   course_code: z.string().min(1, "Course code is required"),
6 |   section_code: z.string().min(1, "Section code is required"),
7 | });
8 |
9 | export type EnrollmentImportRowData = z.infer<typeof enrollmentImportRowSchema>;
10 |
```

FILE: src/lib/schemas/exportData.ts

TYPE: .ts | LINES: 1-9 | SHA256: 4a8361bfa2ff2c260907dda5ded97c86f93f0acdc4e2fe726475ccaed662897c

```
1 | import { z } from "zod";
2 |
3 | export const exportRequestSchema = z.object({
4 |   student_id: z.uuid(),
5 |   format: z.enum(["json", "csv"]),
6 | });
7 |
8 | export type ExportRequestData = z.infer<typeof exportRequestSchema>;
9 |
```

FILE: src/lib/schemas/feeStructure.ts

TYPE: .ts | LINES: 1-24 | SHA256: 410bf6dbc354a3a481bbace3ce9661f0a87123c81c7ff6dca8d8ac6e43cddcda

```
1 | import { z } from "zod";
2 |
3 | export const feeStructureSchema = z.object({
4 |   program_id: z.uuid(),
5 |   semester_id: z.uuid(),
6 |   fee_type: z.enum(["tuition", "lab", "library", "exam"]),
7 |   amount: z.number().positive("Amount must be positive"),
8 |   currency: z.string().min(1).max(10).default("PKR"),
9 |   due_date: z.iso.date(),
10 | });
11 |
12 | export const feePaymentSchema = z.object({
13 |   student_id: z.uuid(),
14 |   fee_structure_id: z.uuid(),
15 |   amount_paid: z.number().min(0),
16 |   payment_date: z.iso.date(),
17 |   payment_method: z.string().min(1),
18 |   receipt_number: z.string().min(1),
19 |   status: z.enum(["pending", "paid", "overdue", "waived"]),
20 | });
21 |
22 | export type FeeStructureFormData = z.infer<typeof feeStructureSchema>;
23 | export type FeePaymentFormData = z.infer<typeof feePaymentSchema>;
24 |
```

FILE: src/lib/schemas/gapAnalysis.ts

TYPE: .ts | LINES: 1-9 | SHA256: 39eabe67955bb7d8c321f6a2636f84e71d3ce8f79c703247d5a8b5f63ce6722d

```
1 | import { z } from "zod";
2 |
3 | export const gapAnalysisFilterSchema = z.object({
4 |   programId: z.string().uuid(),
5 |   semesterId: z.string().uuid().optional(),
6 | });
```

```
7 |
8 | export type GapAnalysisFilter = z.infer<typeof gapAnalysisFilterSchema>;
9 |
```

FILE: src/lib/schemas/globalSearch.ts

TYPE: .ts | LINES: 1-28 | SHA256: f80cd728d17b67f88fe0724dfc5ef19ebe24b4606e3e8286a2c1a97342aceb86

```
1 | import { z } from "zod";
2 |
3 | export const searchQuerySchema = z.object({
4 |   query: z.string().min(1, "Search query is required").max(200),
5 |   category: z
6 |     .enum([
7 |       "all",
8 |       "courses",
9 |       "assignments",
10 |       "students",
11 |       "announcements",
12 |       "materials",
13 |     ])
14 |     .default("all"),
15 |   limit: z.number().int().min(1).max(50).default(10),
16 | });
17 |
18 | export const searchResultSchema = z.object({
19 |   id: z.string(),
20 |   title: z.string(),
21 |   category: z.string(),
22 |   description: z.string().optional(),
23 |   url: z.string(),
24 | });
25 |
26 | export type SearchQueryFormData = z.infer<typeof searchQuerySchema>;
27 | export type SearchResultData = z.infer<typeof searchResultSchema>;
28 |
```

FILE: src/lib/schemas/grade.ts

TYPE: .ts | LINES: 1-19 | SHA256: 2435ed26f5627be8f0063167304ab4d681019dc0188d3d7c379138f14fbf2c70

```
1 | import { z } from "zod";
2 |
3 | export const rubricSelectionSchema = z.object({
4 |   criterion_id: z.uuid(),
5 |   level_index: z.number().int().min(0),
6 |   points: z.number().min(0),
7 | });
8 |
9 | export const gradeSchema = z.object({
10 |   submission_id: z.uuid(),
11 |   rubric_selections: z.array(rubricSelectionSchema).min(1),
12 |   total_score: z.number().min(0),
13 |   score_percent: z.number().min(0).max(100),
14 |   overall_feedback: z.string().optional(),
15 | });
16 |
17 | export type RubricSelectionFormData = z.infer<typeof rubricSelectionSchema>;
18 | export type GradeFormData = z.infer<typeof gradeSchema>;
19 |
```

FILE: src/lib/schemas/gradeCategory.ts

TYPE: .ts | LINES: 1-11 | SHA256: f797d3c2227ab109b68c02607ac06668a85219a4606dc22477b2da6b5aacf929

```
1 | import { z } from "zod";
2 |
3 | export const gradeCategorySchema = z.object({
4 |   course_id: z.uuid(),
5 |   name: z.string().min(1, "Category name is required").max(100),
6 |   weight_percent: z.number().min(0).max(100),
7 |   sort_order: z.number().int().min(0),
8 | });
9 |
10 | export type GradeCategoryFormData = z.infer<typeof gradeCategorySchema>;
11 |
```

FILE: src/lib/schemas/graduateAttribute.ts

TYPE: .ts | LINES: 1-23 | SHA256: c7b9c549fb6ef940c48be338e6bc88e153211def51cc3b89e9213d307fddfb76

```
1 | // Task 112.2: Graduate Attribute Zod schemas
2 |
3 | import { z } from "zod";
4 |
5 | export const graduateAttributeSchema = z.object({
6 |   name: z.string().min(1, "Name is required").max(200),
7 |   description: z.string().max(1000).optional(),
8 |   sort_order: z.number().int().min(0).optional(),
9 | });
10 |
11 | export const graduateAttributeMappingSchema = z.object({
12 |   graduate_attribute_id: z.string().uuid(),
13 |   outcome_id: z.string().uuid(),
14 |   weight: z.number().min(0).max(1),
15 | });
16 |
17 | export type CreateGraduateAttributeInput = z.infer<
18 |   typeof graduateAttributeSchema
19 | >;
20 | export type GraduateAttributeMappingInput = z.infer<
21 |   typeof graduateAttributeMappingSchema
22 | >;
23 |
```

FILE: src/lib/schemas/habitDifficulty.ts

TYPE: .ts | LINES: 1-11 | SHA256: cd33d484f705ce75cefc434f1698192a80538d0dc8fde3129a6183b80fde2f9c

```
1 | // Task 145.2: Habit Difficulty Level Zod schema
2 |
3 | import { z } from "zod";
4 |
5 | export const habitDifficultyLevelSchema = z.object({
6 |   level: z.union([z.literal(1), z.literal(2), z.literal(3)]),
7 |   habit_level_streak: z.number().int().min(0),
8 | });
9 |
10 | export type HabitDifficultyLevel = z.infer<typeof habitDifficultyLevelSchema>;
11 |
```

FILE: src/lib/schemas/habitLog.ts

TYPE: .ts | LINES: 1-10 | SHA256: 595603a3d372d926fee998160b8f2ad5f6c392c071f97545ca1c499965d340c7

```
1 | import { z } from "zod";
2 |
3 | export const habitLogSchema = z.object({
4 |   student_id: z.uuid(),
5 |   date: z.iso.date(),
6 |   habit_type: z.enum(["login", "submit", "journal", "read"]),
7 | });
8 |
9 | export type HabitLogFormData = z.infer<typeof habitLogSchema>;
10 |
```

FILE: src/lib/schemas/historicalEvidence.ts

TYPE: .ts | LINES: 1-30 | SHA256: 3f59cef0e1b0f566875709b53ac797ffdd88924b4d23333d666218aff7c74653

```
1 | // Feature: qa-partner-review-remediation - Req 4 (B4)
2 | // Filter schema for the Admin Historical Evidence dashboard. Validates the
3 | // optional outcome-type / Bloom's-level / semester filters that drive both the
4 | // `useHistoricalEvidence` query and the dashboard's nuqs URL state.
5 | //
6 | // The enum members mirror the `outcome_type` and `blooms_level` Postgres enums
7 | // in `src/types/database.ts`, so a filter value is always a valid column value
8 | // for `mv_historical_evidence`.
9 |
10 | import { z } from "zod";
11 |
12 | export const historicalEvidenceFilterSchema = z.object({
13 |   outcomeType: z.enum(["ILO", "PLO", "CLO", "SUB_CLO"]).optional(),
14 |   bloomsLevel: z
15 |     .enum([
16 |       "remembering",
17 |       "understanding",
18 |       "applying",
19 |       "analyzing",
20 |       "evaluating",
21 |       "creating",
22 |     ])
23 |     .optional(),
24 |   semesterId: z.string().uuid().optional(),
25 | });
26 |
27 | export type HistoricalEvidenceFilter = z.infer<
28 |   typeof historicalEvidenceFilterSchema
29 | >;
30 |
```

FILE: src/lib/schemas/ilo.ts

TYPE: .ts | LINES: 1-29 | SHA256: 9e03f0e0cae875dc1a5b91d05871a3f81d7a5fcf6504fda5de74bcc387677a90

```
1 | import { z } from "zod";
2 |
3 | export const createILOSchema = z.object({
4 |   title: z.string().min(1, "Title is required").max(255),
5 |   title_ar: z.string().max(255).optional(),
6 |   description: z.string().optional(),
7 |   institution_id: z.uuid(),
8 |   sort_order: z.number().int().min(0).optional(),
9 | });
10 |
11 | export const reorderSchema = z.object({
12 |   items: z.array(
13 |     z.object({
14 |       id: z.uuid(),
15 |       sort_order: z.number().int().min(0),
16 |     })
17 |   ),
18 | });
19 |
20 | export const updateILOSchema = z.object({
21 |   title: z.string().min(1, "Title is required").max(255),
22 |   title_ar: z.string().max(255).optional(),
23 |   description: z.string().optional(),
24 | });
25 |
26 | export type CreateILOFormData = z.infer<typeof createILOSchema>;
27 | export type UpdateILOFormData = z.infer<typeof updateILOSchema>;
28 | export type ReorderFormData = z.infer<typeof reorderSchema>;
29 |
```

FILE: src/lib/schemas/impersonation.ts

TYPE: .ts | LINES: 1-9 | SHA256: bdf33e4b3b5b572ee38dddbc1645339860e19f284ca1f4826a0ac8e3d3696bab

```
1 | import { z } from "zod";
2 |
3 | export const impersonationSchema = z.object({
4 |   target_user_id: z.uuid(),
5 |   reason: z.string().min(1, "Reason is required").max(500),
6 | });
7 |
8 | export type ImpersonationFormData = z.infer<typeof impersonationSchema>;
9 |
```

FILE: src/lib/schemas/improvementBonus.ts

TYPE: .ts | LINES: 1-13 | SHA256: d48fe04ddb587bd7ca3ec956e6fdb9e38de326c50a84b00fdb7a8955d586671c

```
1 | // Task 139.2: Improvement Bonus Zod schema
2 |
3 | import { z } from "zod";
4 |
5 | export const improvementBonusSchema = z.object({
6 |   clo_id: z.string().uuid(),
7 |   previous_percent: z.number().min(0).max(100),
8 |   current_percent: z.number().min(0).max(100),
9 |   bonus_xp: z.number().int().positive(),
10 | });
11 |
12 | export type ImprovementBonus = z.infer<typeof improvementBonusSchema>;
13 |
```

FILE: src/lib/schemas/index.ts

TYPE: .ts | LINES: 1-53 | SHA256: 52019e88373d1dd98635bbd1e5bcb316b987fe1545da4c2e732aae31c9e5ba8

```
1 | export * from "./auth";
2 | export * from "./user";
3 | export * from "./program";
4 | export * from "./course";
5 | export * from "./ilo";
6 | export * from "./plo";
7 | export * from "./clo";
8 | export * from "./rubric";
9 | export * from "./assignment";
10 | export * from "./submission";
11 | export * from "./grade";
12 | export * from "./journal";
13 | export * from "./bulkImport";
14 | export * from "./habitLog";
15 | export * from "./bonusXPEvent";
16 | export * from "./emailPrefs";
17 | export * from "./aiSuggestion";
18 | export * from "./streakFreeze";
19 | export * from "./exportData";
20 | export * from "./themePrefs";
21 | export * from "./onboarding";
22 | export * from "./semester";
23 | export * from "./department";
24 | export * from "./courseSection";
25 | export * from "./survey";
26 | export * from "./cqiPlan";
27 | export * from "./institutionSettings";
28 | export * from "./programAccreditation";
29 | export * from "./announcement";
30 | export * from "./announcementAttachment";
31 | export * from "./courseModule";
32 | export * from "./discussion";
33 | export * from "./attendance";
34 | export * from "./quiz";
35 | export * from "./gradeCategory";
36 | export * from "./timetable";
37 | export * from "./academicCalendar";
38 | export * from "./parentLink";
39 | export * from "./feeStructure";
40 | export * from "./transcript";
41 | export * from "./courseFile";
42 | export * from "./languagePrefs";
43 | export * from "./cookieConsent";
44 | export * from "./impersonation";
45 | export * from "./bulkGradeExport";
46 | export * from "./enrollmentImport";
47 | export * from "./semesterTransition";
48 | export * from "./globalSearch";
49 | export * from "./notificationPrefs";
50 | export * from "./sessionManagement";
51 | export * from "./wellnessXpAmount";
52 | export * from "./historicalEvidence";
53 |
```

FILE: src/lib/schemas/institutionSettings.ts

TYPE: .ts | LINES: 1-45 | SHA256: 5a473232a18018adea5290e362fbb75fa7fe7fa778ccfed9d705e586eccc863

```
1 | import { z } from "zod";
2 |
3 | export const gradeScaleSchema = z.object({
4 |   letter: z.string().min(1).max(5),
5 |   min_percent: z.number().min(0).max(100),
6 |   max_percent: z.number().min(0).max(100),
7 |   gpa_points: z.number().min(0).max(4),
8 | });
9 |
10 | export const leagueThresholdsSchema = z.object({
11 |   bronze: z.number().min(0),
12 |   silver: z.number().min(0),
13 |   gold: z.number().min(0),
```

```

14 |     diamond: z.number().min(0),
15 |   });
16 |
17 | export const institutionSettingsSchema = z.object({
18 |   attainment_thresholds: z.object({
19 |     excellent: z.number().min(0).max(100),
20 |     satisfactory: z.number().min(0).max(100),
21 |     developing: z.number().min(0).max(100),
22 |   }),
23 |   success_threshold: z.number().min(0).max(100),
24 |   accreditation_body: z.enum([
25 |     "HEC",
26 |     "QQA",
27 |     "ABET",
28 |     "NCAAA",
29 |     "AACSB",
30 |     "Generic",
31 |   ]),
32 |   grade_scales: z
33 |     .array(gradeScaleSchema)
34 |     .min(1, "At least one grade scale is required"),
35 |   streak_sabbatical_enabled: z.boolean(),
36 |   league_thresholds: leagueThresholdsSchema.optional(),
37 |   default_language: z.enum(["en", "ar"]).optional(),
38 | });
39 |
40 | export type GradeScaleData = z.infer<typeof gradeScaleSchema>;
41 | export type LeagueThresholdsData = z.infer<typeof leagueThresholdsSchema>;
42 | export type InstitutionSettingsFormData = z.infer<
43 |   typeof institutionSettingsSchema
44 | >;
45 |

```

FILE: src/lib/schemas/invitation.ts

TYPE: .ts | LINES: 1-65 | SHA256: f6fd88b4aa45f450882b3a458ac0c262cd11fd4efef0cb4088f2245bd5c39815

```

1 | import { z } from "zod";
2 |
3 | /**
4 |  * Single invitation schema
5 |  */
6 | export const invitationSchema = z.object({
7 |   email: z.string().email("Invalid email address"),
8 |   role: z.enum([
9 |     "admin",
10 |     "coordinator",
11 |     "teacher",
12 |     "student",
13 |     "parent",
14 |   ] as const),
15 |   institution_id: z.string().uuid("Invalid institution ID"),
16 | });
17 |
18 | export type InvitationInput = z.infer<typeof invitationSchema>;
19 |
20 | /**
21 |  * Bulk invitation schema
22 |  */
23 | export const bulkInvitationSchema = z.object({
24 |   institution_id: z.string().uuid("Invalid institution ID"),
25 |   invites: z
26 |     .array(
27 |       z.object({
28 |         email: z.string().email("Invalid email address"),
29 |         role: z.enum([
30 |           "admin",
31 |           "coordinator",
32 |           "teacher",
33 |           "student",
34 |           "parent",
35 |         ] as const),
36 |       })
37 |     )
38 |     .min(1, "At least one invitation is required"),
39 | });
40 |
41 | export type BulkInvitationInput = z.infer<typeof bulkInvitationSchema>;
42 |
43 | /**
44 |  * Invitation response schema (from database)
45 |  */
46 | export const invitationResponseSchema = z.object({
47 |   id: z.string().uuid(),
48 |   institution_id: z.string().uuid(),
49 |   email: z.string().email(),
50 |   role: z.enum([
51 |     "admin",
52 |     "coordinator",
53 |     "teacher",
54 |     "student",
55 |     "parent",
56 |   ] as const),
57 |   token: z.string(),
58 |   expires_at: z.string().datetime(),
59 |   used_at: z.string().datetime().nullable(),
60 |   created_by: z.string().uuid(),
61 |   created_at: z.string().datetime(),
62 | });
63 |
64 | export type InvitationResponse = z.infer<typeof invitationResponseSchema>;
65 |

```

FILE: src/lib/schemas/journal.ts

TYPE: .ts | LINES: 1-13 | SHA256: ccc6ad9c61e3e823b0e4702c3105ce82a504ae2e44110e506daf1e265741a3a9

```
1 | import { z } from "zod";
2 |
3 | export const journalEntrySchema = z.object({
4 |   course_id: z.uuid(),
5 |   student_id: z.uuid(),
6 |   content: z.string().min(50, "Journal entry must be at least 50 characters"),
7 |   prompt_text: z.string().optional(),
8 |   is_shared: z.boolean().default(false),
9 |   word_count: z.number().int().min(0).optional(),
10 | });
11 |
12 | export type JournalEntryFormData = z.infer<typeof journalEntrySchema>;
13 |
```

FILE: src/lib/schemas/languagePrefs.ts

TYPE: .ts | LINES: 1-13 | SHA256: ba9d692c60308254646991c1176458fd823e9c1b45e8ed17ce61b6d417dbb18f

```
1 | import { z } from "zod";
2 |
3 | export const supportedLanguages = ["en", "ar"] as const;
4 | export type SupportedLanguage = (typeof supportedLanguages)[number];
5 |
6 | export const languagePreferenceSchema = z.object({
7 |   language: z.enum(supportedLanguages),
8 | });
9 |
10 | export type LanguagePreferenceFormData = z.infer<
11 |   typeof languagePreferenceSchema
12 | >;
13 |
```

FILE: src/lib/schemas/notificationPrefs.ts

TYPE: .ts | LINES: 1-32 | SHA256: fa727e159505aa7aa0a4936f4d819122085cd6452b4c2e94688ac92d78052117

```
1 | import { z } from "zod";
2 |
3 | export const notificationPreferencesSchema = z.object({
4 |   in_app: z.object({
5 |     grades: z.boolean().default(true),
6 |     assignments: z.boolean().default(true),
7 |     badges: z.boolean().default(true),
8 |     streaks: z.boolean().default(true),
9 |     peer_milestones: z.boolean().default(true),
10 |     announcements: z.boolean().default(true),
11 |     discussions: z.boolean().default(true),
12 |   }),
13 |   email_digest: z.boolean().default(false),
14 |   quiet_hours: z
15 |     .object({
16 |       enabled: z.boolean().default(false),
17 |       start: z
18 |         .string()
19 |         .regex(/^d{2}:d{2}$/)
20 |         .default("22:00"),
21 |       end: z
22 |         .string()
23 |         .regex(/^d{2}:d{2}$/)
24 |         .default("07:00"),
25 |     })
26 |     .optional(),
27 | });
28 |
29 | export type NotificationPreferencesFormData = z.infer<
30 |   typeof notificationPreferencesSchema
31 | >;
32 |
```

FILE: src/lib/schemas/onboarding.ts

TYPE: .ts | LINES: 1-20 | SHA256: cc2f16855659ebc2b93138e50a91c2791b5687f4a8f3099115b67baaf23fb891

```
1 | import { z } from "zod";
2 |
3 | export const onboardingStepSchema = z.object({
4 |   id: z.string().min(1),
5 |   title: z.string().min(1),
6 |   description: z.string(),
7 |   isCompleted: z.boolean(),
8 |   route: z.string().min(1),
9 | });
10 |
11 | export const checklistItemSchema = z.object({
12 |   id: z.string().min(1),
13 |   label: z.string().min(1),
14 |   isCompleted: z.boolean(),
15 |   route: z.string().min(1),
16 | });
17 |
18 | export type OnboardingStepData = z.infer<typeof onboardingStepSchema>;
19 | export type ChecklistItemData = z.infer<typeof checklistItemSchema>;
20 |
```

FILE: src/lib/schemas/parentLink.ts

TYPE: .ts | LINES: 1-10 | SHA256: 01e85bfea1814b6979e07b3ac7600da67a24ffa7252ef4512c48f7d8032e82d7

```
1 | import { z } from "zod";
2 |
3 | export const parentStudentLinkSchema = z.object({
4 |   parent_id: z.uuid(),
5 |   student_id: z.uuid(),
6 |   relationship: z.enum(["parent", "guardian"]),
7 | });
8 |
9 | export type ParentStudentLinkData = z.infer<typeof parentStudentLinkSchema>;
10 |
```



```

7 | });
8 |
9 | export type ParentStudentLinkFormData = z.infer<typeof parentStudentLinkSchema>;
10 |

```

FILE: src/lib/schemas/peerTeaching.ts

TYPE: .ts | LINES: 1-38 | SHA256: 06035674336e85b93e8d897a16660d4537884bb23e3870d1e7d1fb87a2361906

```

1 | // Peer Teaching Moment Zod schemas for the Team Challenges feature.
2 | // Validates teaching moment creation and rating inputs.
3 |
4 | import { z } from "zod";
5 |
6 | export const createTeachingMomentSchema = z.object({
7 |   team_id: z.string().uuid("Invalid team ID"),
8 |   clo_id: z.string().uuid("Invalid CLO ID"),
9 |   title: z
10 |     .string()
11 |     .min(3, "Title must be at least 3 characters")
12 |     .max(100, "Title must be at most 100 characters"),
13 |   explanation_text: z
14 |     .string()
15 |     .min(50, "Explanation must be at least 50 characters")
16 |     .max(500, "Explanation must be at most 500 characters"),
17 |   media_url: z.string().url("Invalid URL format").nullable().optional(),
18 | });
19 |
20 | export const rateTeachingMomentSchema = z.object({
21 |   teaching_moment_id: z.string().uuid("Invalid teaching moment ID"),
22 |   clarity_rating: z
23 |     .number()
24 |     .int("Clarity rating must be a whole number")
25 |     .min(1, "Clarity rating must be at least 1")
26 |     .max(5, "Clarity rating must be at most 5"),
27 |   helpfulness_rating: z
28 |     .number()
29 |     .int("Helpfulness rating must be a whole number")
30 |     .min(1, "Helpfulness rating must be at least 1")
31 |     .max(5, "Helpfulness rating must be at most 5"),
32 | });
33 |
34 | export type CreateTeachingMomentInput = z.infer<
35 |   typeof createTeachingMomentSchema
36 | >;
37 | export type RateTeachingMomentInput = z.infer<typeof rateTeachingMomentSchema>;
38 |

```

FILE: src/lib/schemas/planner.ts

TYPE: .ts | LINES: 1-150 | SHA256: 5a1fe7d6b8e7193e26967fb3ed8ce5492a01c08381fa91202034caec5a86aff4

```

1 | // =====
2 | // Weekly Planner & Today View - Zod Validation Schemas
3 | // =====
4 |
5 | import { z } from "zod";
6 |
7 | /** Schema for creating a new study session. */
8 | export const createStudySessionSchema = z.object({
9 |   title: z.string().min(1, "Title is required").max(255),
10 |   plannedDate: z.string().regex(/^\d{4}-\d{2}-\d{2}$/, "Invalid date format"),
11 |   plannedStartTime: z.string().regex(/^\d{2}:\d{2}$/, "Invalid time format"),
12 |   plannedDurationMinutes: z
13 |     .number()
14 |     .int()
15 |     .min(15, "Minimum duration is 15 minutes")
16 |     .max(240, "Maximum duration is 240 minutes")
17 |     .refine((v) => v % 15 === 0, "Duration must be in 15-minute increments"),
18 |   courseId: z.string().uuid("Invalid course"),
19 |   timerMode: z.enum(["pomodoro", "custom"]),
20 |   description: z.string().max(2000).nullable().optional(),
21 |   cloIds: z.array(z.string().uuid()).nullable().optional(),
22 | });
23 |
24 | export type CreateStudySessionInput = z.infer<typeof createStudySessionSchema>;
25 |
26 | /** Schema for creating a new planner task. */
27 | export const createPlannerTaskSchema = z.object({
28 |   title: z.string().min(1, "Title is required").max(255),
29 |   dueDate: z.string().regex(/^\d{4}-\d{2}-\d{2}$/, "Invalid date format"),
30 |   description: z.string().max(2000).nullable().optional(),
31 |   priority: z.enum(["low", "medium", "high"]).default("medium"),
32 |   courseId: z.string().uuid().nullable().optional(),
33 | });
34 |
35 | export type CreatePlannerTaskInput = z.infer<typeof createPlannerTaskSchema>;
36 |
37 | /** Schema for creating/updating weekly goals. */
38 | export const createWeeklyGoalSchema = z.object({
39 |   weekStartDate: z.string().regex(/^\d{4}-\d{2}-\d{2}$/, "Invalid date format"),
40 |   goalType: z.enum(["study_hours", "sessions_completed", "tasks_completed"]),
41 |   targetValue: z.number().positive("Target must be greater than 0"),
42 | });
43 |
44 | export type CreateWeeklyGoalInput = z.infer<typeof createWeeklyGoalSchema>;
45 |
46 | /** Schema for session completion data. */
47 | export const sessionCompletionSchema = z.object({
48 |   sessionId: z.string().uuid(),
49 |   notes: z.string().max(5000).nullable().optional(),
50 |   satisfactionRating: z.number().int().min(1).max(5).nullable().optional(),
51 | });
52 |
53 | export type SessionCompletionInput = z.infer<typeof sessionCompletionSchema>;
54 |

```

```

55 | /** Helper: word count validation. */
56 | const wordCountMin = (min: number) =>
57 |   z.string().refine(
58 |     (text) =>
59 |       text
60 |         .trim()
61 |         .split(/\s+/)
62 |         .filter((w) => w.length > 0).length >= min,
63 |     { message: `Reflection must be at least ${min} words` }
64 |   );
65 |
66 | /** Schema for session reflection (minimum 30 words). */
67 | export const sessionReflectionSchema = z.object({
68 |   sessionId: z.string().uuid(),
69 |   content: wordCountMin(30),
70 | });
71 |
72 | export type SessionReflectionInput = z.infer<typeof sessionReflectionSchema>;
73 |
74 | /** Schema for weekly reflection (minimum 50 words). */
75 | export const weeklyReflectionSchema = z.object({
76 |   weekStartDate: z.string().regex(/^d{4}-d{2}-d{2}$/, "Invalid date format"),
77 |   content: wordCountMin(50),
78 | });
79 |
80 | export type WeeklyReflectionInput = z.infer<typeof weeklyReflectionSchema>;
81 |
82 | // -----
83 | // Flow Check-In Schema
84 | // -----
85 |
86 | /** Schema for flow check-in responses during Pomodoro breaks. */
87 | export const flowCheckInSchema = z.object({
88 |   sessionId: z.string().uuid(),
89 |   intervalNumber: z.number().int().min(1),
90 |   response: z.enum(["in_the_zone", "stuck", "too_easy"]),
91 | });
92 |
93 | export type FlowCheckInInput = z.infer<typeof flowCheckInSchema>;
94 |
95 | // -----
96 | // Session Intent Schema
97 | // -----
98 |
99 | /** Schema for session intent (concept + success criterion). */
100 | export const sessionIntentSchema = z.object({
101 |   sessionId: z.string().uuid(),
102 |   concept: z.string().min(5).max(200),
103 |   successCriterion: z.string().min(5).max(200),
104 | });
105 |
106 | export type SessionIntentInput = z.infer<typeof sessionIntentSchema>;
107 |
108 | // -----
109 | // Quick Thought Schema
110 | // -----
111 |
112 | /** Schema for quick thought capture (1-280 chars). */
113 | export const quickThoughtSchema = z.object({
114 |   sessionId: z.string().uuid(),
115 |   text: z.string().min(1).max(280),
116 | });
117 |
118 | export type QuickThoughtInput = z.infer<typeof quickThoughtSchema>;
119 |
120 | // -----
121 | // Review Schedule Schema
122 | // -----
123 |
124 | /** Schema for creating a review schedule entry. */
125 | export const reviewScheduleCreateSchema = z.object({
126 |   cloId: z.string().uuid(),
127 |   courseId: z.string().uuid().nullable().optional(),
128 |   sourceSessionId: z.string().uuid().nullable().optional(),
129 |   reviewDate: z.string().regex(/^d{4}-d{2}-d{2}$/, "Invalid date format"),
130 |   intervalDays: z.union([z.literal(1), z.literal(3), z.literal(7)]),
131 | });
132 |
133 | export type ReviewScheduleCreateInput = z.infer<
134 |   typeof reviewScheduleCreateSchema
135 | >;
136 |
137 | // -----
138 | // Reflection Digest Share Schema
139 | // -----
140 |
141 | /** Schema for sharing a reflection digest with parent / advisor / teacher. */
142 | export const reflectionDigestShareSchema = z.object({
143 |   digestId: z.string().uuid(),
144 |   role: z.enum(["parent", "advisor", "teacher"]),
145 | });
146 |
147 | export type ReflectionDigestShareInput = z.infer<
148 |   typeof reflectionDigestShareSchema
149 | >;
150 |

```

FILE: src/lib/schemas/plo.ts

TYPE: .ts | LINES: 1-23 | SHA256: 4dcf0ed094e65885116302e01b32480909441ba987f8b24359f1f25b079d4c2c

```
1 | import { z } from "zod";
2 |
3 | export const createPLOSHEMA = z.object({
4 |   title: z.string().min(1, "Title is required").max(255),
5 |   title_ar: z.string().max(255).optional(),
6 |   description: z.string().optional(),
7 |   program_id: z.uuid(),
8 |   sort_order: z.number().int().min(0).optional(),
9 | });
10 |
11 | export const mappingSchema = z.object({
12 |   plo_id: z.uuid(),
13 |   ilo_mappings: z.array(
14 |     z.object({
15 |       ilo_id: z.uuid(),
16 |       weight: z.number().min(0).max(1),
17 |     })
18 |   ),
19 | });
20 |
21 | export type CreatePLOFormData = z.infer<typeof createPLOSHEMA>;
22 | export type MappingFormData = z.infer<typeof mappingSchema>;
23 |
```

FILE: src/lib/schemas/program.ts

TYPE: .ts | LINES: 1-24 | SHA256: babf2d69b09cd2da9b05b80278092ad2e4e6eeecd1795fe21516b5f8ed7b14c8

```
1 | import { z } from "zod";
2 |
3 | export const createProgramSchema = z.object({
4 |   name: z.string().min(1, "Program name is required").max(255),
5 |   name_ar: z.string().max(255).optional(),
6 |   code: z.string().min(1, "Program code is required").max(50),
7 |   description: z.string().optional(),
8 |   institution_id: z.uuid(),
9 |   coordinator_id: z.uuid().optional(),
10 |   department_id: z.uuid().optional(),
11 | });
12 |
13 | export const updateProgramSchema = z.object({
14 |   name: z.string().min(1).max(255).optional(),
15 |   name_ar: z.string().max(255).optional(),
16 |   code: z.string().min(1).max(50).optional(),
17 |   description: z.string().optional(),
18 |   coordinator_id: z.uuid().optional(),
19 |   department_id: z.uuid().optional(),
20 | });
21 |
22 | export type CreateProgramFormData = z.infer<typeof createProgramSchema>;
23 | export type UpdateProgramFormData = z.infer<typeof updateProgramSchema>;
24 |
```

FILE: src/lib/schemas/programAccreditation.ts

TYPE: .ts | LINES: 1-15 | SHA256: a67f358ddf65d3d9d3ee4dcfd223cbc9a23c7b1867850c3cb3181b5458ed48a8

```
1 | import { z } from "zod";
2 |
3 | export const programAccreditationSchema = z.object({
4 |   program_id: z.uuid(),
5 |   accreditation_body: z.string().min(1, "Accreditation body is required"),
6 |   framework_version: z.string().optional(),
7 |   accreditation_date: z.iso.date().optional(),
8 |   next_review_date: z.iso.date().optional(),
9 |   status: z.enum(["active", "expired", "pending"]).default("pending"),
10 | });
11 |
12 | export type ProgramAccreditationFormData = z.infer<
13 |   typeof programAccreditationSchema
14 | >;
15 |
```

FILE: src/lib/schemas/quiz.ts

TYPE: .ts | LINES: 1-49 | SHA256: 004cf69996d7b3d5857723436cf5fb7b7701fcdf51a0865e307a3d1d63cf7503

```
1 | import { z } from "zod";
2 |
3 | export const quizQuestionSchema = z.object({
4 |   question_text: z.string().min(1, "Question text is required"),
5 |   question_type: z.enum([
6 |     "mcq_single",
7 |     "mcq_multi",
8 |     "true_false",
9 |     "short_answer",
10 |     "fill_blank",
11 |   ]),
12 |   options: z.array(z.string()).nullable(),
13 |   correct_answer: z.union([z.string(), z.array(z.string())]),
14 |   points: z.number().min(0),
15 |   sort_order: z.number().int().min(0),
16 | });
17 |
18 | export const adaptationConfigSchema = z.object({
19 |   initial_difficulty: z.number().min(1.0).max(5.0).optional(),
20 |   difficulty_step_up: z.number().default(0.3),
21 |   difficulty_step_down: z.number().default(0.5),
22 |   difficulty_range: z.number().default(0.5),
23 | });
24 |
25 | export const createQuizSchema = z.object({
26 |   course_id: z.uuid(),
```

```

27 | title: z.string().min(1, "Quiz title is required").max(255),
28 | description: z.string().optional(),
29 | clo_ids: z.array(z.uuid()).min(1, "At least 1 CLO required"),
30 | time_limit_minutes: z.number().int().min(1).nullable(),
31 | max_attempts: z.number().int().min(1),
32 | is_published: z.boolean(),
33 | due_date: z.iso.datetime(),
34 | questions: z.array(quizQuestionSchema),
35 | is_adaptive: z.boolean(),
36 | adaptation_config: adaptationConfigSchema.optional(),
37 | practice_mode_enabled: z.boolean(),
38 | });
39 |
40 | export const quizAttemptSchema = z.object({
41 |   quiz_id: z.uuid(),
42 |   answers: z.record(z.string(), z.union([z.string(), z.array(z.string())])),
43 | });
44 |
45 | export type QuizQuestionFormData = z.infer<typeof quizQuestionSchema>;
46 | export type CreateQuizFormData = z.infer<typeof createQuizSchema>;
47 | export type AdaptationConfig = z.infer<typeof adaptationConfigSchema>;
48 | export type QuizAttemptFormData = z.infer<typeof quizAttemptSchema>;
49 |

```

FILE: src/lib/schemas/replacementVote.ts

TYPE: .ts | LINES: 1-14 | SHA256: 21422fd87007d1a22351c45c6ac2b4b1f3d67f1d9bd4b694240f750bfc7fee32

```

1 | // Replacement Vote Zod schema for the Team Challenges feature.
2 | // Validates vote initiation inputs.
3 |
4 | import { z } from "zod";
5 |
6 | export const initiateReplacementVoteSchema = z.object({
7 |   team_id: z.string().uuid("Invalid team ID"),
8 |   target_member_id: z.string().uuid("Invalid target member ID"),
9 | });
10 |
11 | export type InitiateReplacementVoteInput = z.infer<
12 |   typeof initiateReplacementVoteSchema
13 | >;
14 |

```

FILE: src/lib/schemas/rubric.ts

TYPE: .ts | LINES: 1-27 | SHA256: 933019295b5f3baa0f30ded552fa19ae82f86dfa51a190a284c11a87e72cde80

```

1 | import { z } from "zod";
2 |
3 | export const criterionSchema = z.object({
4 |   criterion_name: z.string().min(1, "Criterion name is required"),
5 |   sort_order: z.number().int().min(0),
6 |   levels: z
7 |     .array(
8 |       z.object({
9 |         label: z.string().min(1),
10 |         description: z.string(),
11 |         points: z.number().min(0),
12 |       })
13 |     )
14 |     .min(2, "At least 2 performance levels required"),
15 |   max_points: z.number().min(0),
16 | });
17 |
18 | export const rubricSchema = z.object({
19 |   title: z.string().min(1, "Rubric title is required").max(255),
20 |   clo_id: z.uuid(),
21 |   is_template: z.boolean().default(false),
22 |   criteria: z.array(criterionSchema).min(2, "At least 2 criteria required"),
23 | });
24 |
25 | export type CriterionFormData = z.infer<typeof criterionSchema>;
26 | export type RubricFormData = z.infer<typeof rubricSchema>;
27 |

```

FILE: src/lib/schemas/sankeyFilter.ts

TYPE: .ts | LINES: 1-10 | SHA256: a59401472c6898bdc1d8dcd6cf83e12af5e9cee89c4edd5086cd840605b01f79

```

1 | import { z } from "zod";
2 |
3 | export const sankeyFilterSchema = z.object({
4 |   programId: z.string().uuid().optional(),
5 |   courseId: z.string().uuid().optional(),
6 |   semesterId: z.string().uuid().optional(),
7 | });
8 |
9 | export type SankeyFilter = z.infer<typeof sankeyFilterSchema>;
10 |

```

FILE: src/lib/schemas/semester.ts

TYPE: .ts | LINES: 1-21 | SHA256: 3bb1247858b10588cc7ed08ac68ad36b78411345410add7fa57edb542b06a953

```

1 | import { z } from "zod";
2 |
3 | export const createSemesterSchema = z.object({
4 |   name: z.string().min(1, "Semester name is required").max(255),
5 |   code: z.string().min(1, "Semester code is required").max(50),
6 |   start_date: z.iso.date(),
7 |   end_date: z.iso.date(),
8 |   is_active: z.boolean().default(false),
9 | });
10 |
11 | export const updateSemesterSchema = z.object({
12 |   name: z.string().min(1).max(255).optional(),
13 |   code: z.string().min(1).max(50).optional(),

```

```

14 |   start_date: z.iso.date().optional(),
15 |   end_date: z.iso.date().optional(),
16 |   is_active: z.boolean().optional(),
17 | });
18 |
19 | export type CreateSemesterFormData = z.infer<typeof createSemesterSchema>;
20 | export type UpdateSemesterFormData = z.infer<typeof updateSemesterSchema>;
21 |

```

FILE: src/lib/schemas/semesterTransition.ts

TYPE: .ts | LINES: 1-14 | SHA256: 08835cf3a12c4da9af1bf014a570c96e90050d535afdd574efbcdea37ab893cf

```

1 | import { z } from "zod";
2 |
3 | export const semesterTransitionSchema = z.object({
4 |   from_semester_id: z.uuid(),
5 |   to_semester_id: z.uuid(),
6 |   archive_grades: z.boolean().default(true),
7 |   deactivate_courses: z.boolean().default(true),
8 |   carry_forward_enrollments: z.boolean().default(false),
9 | });
10 |
11 | export type SemesterTransitionFormData = z.infer<
12 |   typeof semesterTransitionSchema
13 | >;
14 |

```

FILE: src/lib/schemas/sessionManagement.ts

TYPE: .ts | LINES: 1-9 | SHA256: dab015c4e309534ba7e1e6cf307c1f538de984e75be571961efd232504e01d26

```

1 | import { z } from "zod";
2 |
3 | export const sessionActionSchema = z.object({
4 |   session_id: z.string().min(1),
5 |   action: z.enum(["revoke", "revoke_all_others"]),
6 | });
7 |
8 | export type SessionActionFormData = z.infer<typeof sessionActionSchema>;
9 |

```

FILE: src/lib/schemas/signUp.ts

TYPE: .ts | LINES: 1-58 | SHA256: c9eaac7f34e02f0fb40d2917cc414463f3fdcf11d4cae581244057c9ee27feaa

```

1 | import { z } from "zod";
2 |
3 | /**
4 |  * Self-registration schema for the public /signup flow.
5 |  *
6 |  * Scalability note (design.md ADR-12):
7 |  *   • default role on self-signup is always 'student' (the schema still
8 |  *     captures a requested role for display/analytics, but `handle_new_user()`
9 |  *     forces role='student' for self-signup without an invitation token)
10 |  *   • non-student onboarding flows through `accept-invite/:token` which uses
11 |  *     a separate schema in `src/lib/schemas/invitation.ts`
12 |  */
13 |
14 | const PASSWORD_MIN = 8;
15 | const USERNAME_RE = /^[a-zA-Z0-9_.-]{3,32}$/;
16 |
17 | export const signUpSchema = z
18 |   .object({
19 |     firstName: z
20 |       .string()
21 |       .trim()
22 |       .min(1, "First name is required")
23 |       .max(60, "First name is too long"),
24 |     lastName: z
25 |       .string()
26 |       .trim()
27 |       .min(1, "Last name is required")
28 |       .max(60, "Last name is too long"),
29 |     username: z
30 |       .string()
31 |       .trim()
32 |       .regex(
33 |         USERNAME_RE,
34 |         "Username must be 3-32 chars, letters/numbers/._- only"
35 |       ),
36 |     email: z.email("Invalid email address"),
37 |     password: z
38 |       .string()
39 |       .min(
40 |         PASSWORD_MIN,
41 |         `Password must be at least ${PASSWORD_MIN} characters`
42 |       ),
43 |     confirmPassword: z.string().min(1, "Please confirm your password"),
44 |     requestedRole: z.enum([
45 |       "student",
46 |       "teacher",
47 |       "coordinator",
48 |       "admin",
49 |       "parent",
50 |     ]),
51 |   })
52 |   .refine((data) => data.password === data.confirmPassword, {
53 |     message: "Passwords do not match",
54 |     path: ["confirmPassword"],
55 |   });
56 |
57 | export type SignUpFormData = z.infer<typeof signUpSchema>;
58 |

```

FILE: src/lib/schemas/signUpSchema.ts

TYPE: .ts | LINES: 1-34 | SHA256: 56912675004856f7ccee74b59390a712e7843f8caddab371ffe8cc6c2550aa2

```
1 | import { z } from "zod";
2 |
3 | /**
4 |  * Schema for the two-step signup wizard.
5 |  * Step 1: institution selection (handled by useInstitutionBrowse)
6 |  * Step 2: account form (email, password, full_name)
7 |  */
8 |
9 | export const signUpSchema = z
10 | .object({
11 |   email: z
12 |     .string()
13 |     .min(1, "Email is required")
14 |     .email("Invalid email address"),
15 |   password: z
16 |     .string()
17 |     .min(8, "Password must be at least 8 characters")
18 |     .regex(/[A-Z]/, "Password must contain at least one uppercase letter")
19 |     .regex(/[a-z]/, "Password must contain at least one lowercase letter")
20 |     .regex(/[0-9]/, "Password must contain at least one number"),
21 |   confirmPassword: z.string().min(1, "Please confirm your password"),
22 |   fullName: z
23 |     .string()
24 |     .min(2, "Full name must be at least 2 characters")
25 |     .max(100, "Full name must be less than 100 characters"),
26 |   institutionId: z.string().uuid("Invalid institution"),
27 | })
28 | .refine((data) => data.password === data.confirmPassword, {
29 |   message: "Passwords do not match",
30 |   path: ["confirmPassword"],
31 | });
32 |
33 | export type SignUpFormData = z.infer<typeof signUpSchema>;
34 |
```

FILE: src/lib/schemas/streakFreeze.ts

TYPE: .ts | LINES: 1-11 | SHA256: 8a8c964af88eec885a7608596eb61f16607365e2bb397c3cc597a788edcddc61

```
1 | import { z } from "zod";
2 |
3 | export const streakFreezePurchaseSchema = z.object({
4 |   student_id: z.uuid(),
5 |   xp_cost: z.literal(200),
6 | });
7 |
8 | export type StreakFreezePurchaseData = z.infer<
9 |   typeof streakFreezePurchaseSchema
10 | >;
11 |
```

FILE: src/lib/schemas/subCLO.ts

TYPE: .ts | LINES: 1-34 | SHA256: 4e8d6f1a57589b2494829d5123eb42f2fc451a46c6541232e944567619ba1584

```
1 | import { z } from "zod";
2 |
3 | export const subCLOSchema = z.object({
4 |   title: z.string().min(1, "Title is required").max(255),
5 |   description: z.string().optional(),
6 |   code: z.string().min(1, "Code is required").max(50),
7 |   weight: z.number().min(0, "Weight must be >= 0").max(1, "Weight must be <= 1"),
8 |   parent_outcome_id: z.string().uuid("Parent CLO ID is required"),
9 | });
10 |
11 | export type SubCLOFormData = z.infer<typeof subCLOSchema>;
12 |
13 | /**
14 |  * Validates that sibling Sub-CLO weights sum to 1.0 (±0.001 tolerance).
15 |  * Pass the full array of weights including the one being added/edited.
16 |  */
17 | export const subCLOWeightSumSchema = z.array(z.number().min(0).max(1)).refine(
18 |   (weights) => {
19 |     if (weights.length === 0) return true;
20 |     const sum = weights.reduce((a, b) => a + b, 0);
21 |     return Math.abs(sum - 1.0) <= 0.001;
22 |   },
23 |   { message: "Sub-CLO weights must sum to 1.0" }
24 | );
25 |
26 | /**
27 |  * Pure function to check weight sum validity – useful in UI indicators.
28 |  */
29 | export function isWeightSumValid(weights: number[]): boolean {
30 |   if (weights.length === 0) return true;
31 |   const sum = weights.reduce((a, b) => a + b, 0);
32 |   return Math.abs(sum - 1.0) <= 0.001;
33 | }
34 |
```

FILE: src/lib/schemas/submission.ts

TYPE: .ts | LINES: 1-11 | SHA256: 37b2df326a51d6df2dc7c3ba940cad01967c4287e8eff4f9d02ad8fd2df73e63

```
1 | import { z } from "zod";
2 |
3 | export const submissionSchema = z.object({
4 |   assignment_id: z.uuid(),
5 |   student_id: z.uuid(),
6 |   file_url: z.string().url("Invalid file URL"),
7 |   is_late: z.boolean().default(false),
8 | });
9 |
```

FILE: src/lib/schemas/survey.ts

```

1 import { z } from "zod";
2
3 export const surveyQuestionSchema = z.object({
4   question_text: z.string().min(1, "Question text is required"),
5   question_type: z.enum(["likert", "mcq", "text"]),
6   options: z.array(z.string()).nullable(),
7   sort_order: z.number().int().min(0),
8 });
9
10 export const createSurveySchema = z.object({
11   title: z.string().min(1, "Survey title is required").max(255),
12   type: z.enum(["course_exit", "graduate_exit", "employer"]),
13   target_outcomes: z.array(z.uuid()),
14   is_active: z.boolean().default(true),
15   questions: z
16     .array(surveyQuestionSchema)
17     .min(1, "At least 1 question required"),
18 });
19
20 export const surveyResponseSchema = z.object({
21   survey_id: z.uuid(),
22   responses: z.array(
23     z.object({
24       question_id: z.uuid(),
25       response_value: z.string().min(1),
26     })
27   ),
28 });
29
30 export type SurveyQuestionFormData = z.infer<typeof surveyQuestionSchema>;
31 export type CreateSurveyFormData = z.infer<typeof createSurveySchema>;
32 export type SurveyResponseFormData = z.infer<typeof surveyResponseSchema>;
33

```

[illegible]

```
1 | import { z } from "zod";
2 |
3 | export const themePreferenceSchema = z.object({
4 |   theme_preference: z.enum(["light", "dark", "system"]),
```

FILE: src/lib/schemas/timetable.ts

```

1 | import { z } from "zod";
2 |
3 | export const timetableSlotSchema = z.object({
4 |   section_id: z.uuid(),
5 |   day_of_week: z.number().int().min(0).max(6),
6 |   start_time: z.string().regex(/^\d{2}:\d{2}$/, "Use HH:MM format"),
7 |   end_time: z.string().regex(/^\d{2}:\d{2}$/, "Use HH:MM format"),
8 |   room: z.string().min(1, "Room is required").max(100),
9 |   slot_type: z.enum(["lecture", "lab", "tutorial"]),
10 | });
11 |
12 | export type TimetableSlotFormData = z.infer<typeof timetableSlotSchema>;
13 |

```

```

1 | import { z } from "zod";
2 |
3 | export const transcriptRequestSchema = z.object({
4 |   student_id: z.uuid(),
5 |   semester_id: z.uuid().optional(),
6 | });
7 |
8 | export type TranscriptRequestData = z.infer<typeof transcriptRequestSchema>;
9 |

```

```

1 | import { z } from "zod";
2 |
3 | const userRoleSchema = z.enum([
4 |   "admin",
5 |   "coordinator",
6 |   "teacher",
7 |   "student",
8 |   "parent",
9 | ]);
10 |
11 | export const createUserSchema = z.object({
12 |   email: z.email("Invalid email address"),
13 |   full_name: z.string().min(1, "Full name is required").max(255),
14 |   role: userRoleSchema,
15 |   institution_id: z.uuid(),
16 |   program_id: z.uuid().optional(),
17 | });
18 |
19 | export const updateUserSchema = z.object({
20 |   full_name: z.string().min(1, "Full name is required").max(255).optional(),
21 |   role: userRoleSchema.optional(),
22 |   is_active: z.boolean().optional(),
23 |   program_id: z.uuid().optional(),
24 | });
25 |
26 | export type CreateUserFormData = z.infer<typeof createUserSchema>;
27 | export type UpdateUserFormData = z.infer<typeof updateUserSchema>;
28 |

```

```
1 | import { z } from "zod";
2 |
3 | export const wellnessXpAmountSchema = z.number().int().min(0).max(25);
4 |
```

[illegible]

[illegible]

```

130 }
131
132 /**
133  * VARK Score Calculation
134  *
135  * 16 questions, each with 4 options mapped to a modality.
136  * VARK_Score = (count of selections for modality / totalQuestions) * 100, rounded
137  *
138  * Dominant style = highest score, or 'multimodal' if two or more within
139  * 10 points of the top score.
140  */
141 export function calculateVARKScores(
142   responses: VARKResponseInput[],
143   totalQuestions: number
144 ): VARKProfile {
145   let visual = 0;
146   let auditory = 0;
147   let readWrite = 0;
148   let kinesthetic = 0;
149
150   for (const r of responses) {
151     switch (r.selected_modality) {
152       case "visual":
153         visual++;
154         break;
155       case "auditory":
156         auditory++;
157         break;
158       case "read_write":
159         readWrite++;
160         break;
161       case "kinesthetic":
162         kinesthetic++;
163         break;
164     }
165   }
166
167   const visualScore = Math.round((visual / totalQuestions) * 100);
168   const auditoryScore = Math.round((auditory / totalQuestions) * 100);
169   const readWriteScore = Math.round((readWrite / totalQuestions) * 100);
170   const kinestheticScore = Math.round((kinesthetic / totalQuestions) * 100);
171
172   const scores = {
173     visual: visualScore,
174     auditory: auditoryScore,
175     read_write: readWriteScore,
176     kinesthetic: kinestheticScore,
177   } as const;
178
179   const maxScore = Math.max(
180     visualScore,
181     auditoryScore,
182     readWriteScore,
183     kinestheticScore
184   );
185
186   type Modality = "visual" | "auditory" | "read_write" | "kinesthetic";
187   const modalities: Modality[] = [
188     "visual",
189     "auditory",
190     "read_write",
191     "kinesthetic",
192   ];
193   const topModalities = modalities.filter(
194     (m) => maxScore - scores[m] <= MULTIMODAL_THRESHOLD
195   );
196
197   let dominant_style: VARKProfile["dominant_style"];
198   if (topModalities.length >= 2) {
199     dominant_style = "multimodal";
200   } else {
201     dominant_style = modalities.reduce((a, b) =>
202       scores[a] > scores[b] ? a : b
203     );
204   }
205
206   return {
207     ...scores,
208     dominant_style,
209   };
210 }
211
212 /**
213  * Baseline Score Calculation
214  *
215  * Per CLO: score = (correct_count / total_count) * 100, rounded
216  * Unanswered questions are treated as incorrect (score 0).
217  */
218 export function calculateBaselineScores(
219   responses: BaselineResponseInput[]
220 ): BaselineResult[] {
221   const cloMap = new Map<string, { total: number; correct: number }>();
222
223   for (const r of responses) {
224     const entry = cloMap.get(r.clo_id) ?? { total: 0, correct: 0 };
225     entry.total++;
226     if (r.selected_option === r.correct_option) {
227       entry.correct++;
228     }
229     cloMap.set(r.clo_id, entry);
230   }
231
232   return Array.from(cloMap.entries()).map(([clo_id, { total, correct }]) => ({
233     clo_id,

```

```

234 |     score: Math.round((correct / total) * 100),
235 |     question_count: total,
236 |     correct_count: correct,
237 |   }));
238 | }
239 |
240 | /**
241 |  * Self-Efficacy Score Calculation
242 |  *
243 |  * 6 items across 3 domains (2 per domain). Likert 1-5.
244 |  * Domain score = (sum of items in domain / (count * 5)) * 100, rounded
245 |  * Overall = (sum of all items / (total_count * 5)) * 100, rounded
246 |  * Supports partial scores (Day 1: 2 items).
247 |  */
248 | export function calculateSelfEfficacyScores(
249 |   responses: SelfEfficacyResponseInput[]
250 | ): SelfEfficacyProfile {
251 |   const byDomain = (domain: string) =>
252 |     computeDimensionScore(responses.filter((r) => r.domain === domain));
253 |
254 |   const allSum = responses.reduce((acc, r) => acc + r.selected_option, 0);
255 |   const allMax = responses.length * 5;
256 |   const overall = allMax > 0 ? Math.round((allSum / allMax) * 100) : 0;
257 |
258 |   return {
259 |     overall,
260 |     general_academic: byDomain("general_academic"),
261 |     course_specific: byDomain("course_specific"),
262 |     self_regulated_learning: byDomain("self_regulated_learning"),
263 |   };
264 | }
265 |
266 | /**
267 |  * Study Strategy Score Calculation
268 |  *
269 |  * 8 items across 4 dimensions (2 per dimension). Likert 1-5.
270 |  * Dimension score = (sum of items in dimension / (count * 5)) * 100, rounded
271 |  */
272 | export function calculateStudyStrategyScores(
273 |   responses: StudyStrategyResponseInput[]
274 | ): StudyStrategyProfile {
275 |   const byDim = (dim: string) =>
276 |     computeDimensionScore(responses.filter((r) => r.dimension === dim));
277 |
278 |   return {
279 |     time_management: byDim("time_management"),
280 |     elaboration: byDim("elaboration"),
281 |     self_testing: byDim("self_testing"),
282 |     help_seeking: byDim("help_seeking"),
283 |   };
284 | }
285 |
286 | /**
287 |  * Profile Completeness Calculation
288 |  *
289 |  * 5 dimensions, each weighted equally (20%):
290 |  * - personality: partial credit = items_answered / 25
291 |  * - self_efficacy: partial credit = items_answered / 6
292 |  * - study_strategies: partial credit = items_answered / 8
293 |  * - learning_style: partial credit = items_answered / 16
294 |  * - baseline: 1 if any course completed, 0 otherwise
295 |  *
296 |  * Total = (sum of dimension fractions / 5) * 100, rounded
297 |  */
298 | export function calculateProfileCompleteness(
299 |   input: ProfileCompletenessInput
300 | ): number {
301 |   const personality = Math.min(
302 |     input.personality_items / TOTAL_PERSONALITY_ITEMS,
303 |     1
304 |   );
305 |   const selfEfficacy = Math.min(
306 |     input.self_efficacy_items / TOTAL_SELF_EFFICACY_ITEMS,
307 |     1
308 |   );
309 |   const studyStrategies = Math.min(
310 |     input.study_strategy_items / TOTAL_STUDY_STRATEGY_ITEMS,
311 |     1
312 |   );
313 |   const learningStyle = Math.min(
314 |     input.learning_style_items / TOTAL_LEARNING_STYLE_ITEMS,
315 |     1
316 |   );
317 |   const baseline = input.baseline_courses > 0 ? 1 : 0;
318 |
319 |   const total =
320 |     personality + selfEfficacy + studyStrategies + learningStyle + baseline;
321 |   return Math.round((total / 5) * 100);
322 | }
323 |

```

FILE: src/lib/sentry.ts

TYPE: .ts | LINES: 1-87 | SHA256: f16bd07c4a3011df21f0c52cd24a88d71dffb53b154c0c5cbfcbbd5ac27224b8

```

1 | import * as Sentry from "@sentry/react";
2 |
3 | /** Regex patterns matching common PII tokens in strings. */
4 | const PII_PATTERNS: Array<{ pattern: RegExp; replacement: string }> = [
5 |   {
6 |     pattern: /[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}/g,
7 |     replacement: "[email]",
8 |   },
9 |   {
10 |     pattern:

```

```

11 |         /\b[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\b/gi,
12 |         replacement: "[uuid]",
13 |     },
14 | ];
15 |
16 | /** Scrub PII from a string value. */
17 | export function scrubPII(value: string): string {
18 |     let result = value;
19 |     for (const { pattern, replacement } of PII_PATTERNS) {
20 |         result = result.replace(pattern, replacement);
21 |     }
22 |     return result;
23 | }
24 |
25 | export function initSentry(): void {
26 |     const dsn = import.meta.env.VITE_SENTRY_DSN;
27 |     if (!dsn) return;
28 |
29 |     Sentry.init({
30 |         dsn,
31 |         integrations: [
32 |             Sentry.browserTracingIntegration(),
33 |             Sentry.replayIntegration({
34 |                 maskAllText: true,
35 |                 maskAllInputs: true,
36 |                 blockAllMedia: true,
37 |             }),
38 |         ],
39 |         tracesSampleRate: 0.1,
40 |         replaysSessionSampleRate: 0.1,
41 |         replaysOnErrorSampleRate: 1.0,
42 |
43 |         // FERPA/GDPR: strip PII from error events before they leave the browser
44 |         beforeSend(event) {
45 |             // Never attach user PII to Sentry events
46 |             if (event.user) {
47 |                 delete event.user.email;
48 |                 delete event.user.username;
49 |                 delete event.user.ip_address;
50 |             }
51 |
52 |             // Scrub PII from exception messages
53 |             if (event.exception?.values) {
54 |                 for (const ex of event.exception.values) {
55 |                     if (ex.value) ex.value = scrubPII(ex.value);
56 |                 }
57 |             }
58 |
59 |             return event;
60 |         },
61 |
62 |         // FERPA/GDPR: scrub PII from breadcrumbs (navigation, console, XHR)
63 |         beforeBreadcrumb(breadcrumb) {
64 |             if (breadcrumb.message) {
65 |                 breadcrumb.message = scrubPII(breadcrumb.message);
66 |             }
67 |             // Strip query params from navigation breadcrumbs (may contain search terms with names)
68 |             if (breadcrumb.category === "navigation" && breadcrumb.data?.to) {
69 |                 const url =
70 |                     typeof breadcrumb.data.to === "string" ? breadcrumb.data.to : "";
71 |                 const qIdx = url.indexOf("?");
72 |                 if (qIdx !== -1) breadcrumb.data.to = url.slice(0, qIdx);
73 |
74 |                 if (typeof breadcrumb.data?.from === "string") {
75 |                     const fIdx = breadcrumb.data.from.indexOf("?");
76 |                     if (fIdx !== -1)
77 |                         breadcrumb.data.from = breadcrumb.data.from.slice(0, fIdx);
78 |                 }
79 |             }
80 |             return breadcrumb;
81 |         },
82 |
83 |         // Never send default PII (cookies, IP, user-agent fingerprinting)
84 |         sendDefaultPii: false,
85 |     });
86 | }
87 |

```

FILE: src/lib/storageUrl.ts

TYPE: .ts | LINES: 1-73 | SHA256: 1725050eda9f5f033e0072536380c9eca6553254a1339f300c1d40ca1852bfc8d

```

1 | // =====
2 | // storageUrl – utilities for generating signed URLs for private storage buckets.
3 | //
4 | // IMPORTANT: `submissions`, `session-evidence`, `course-materials`, and
5 | // `accreditation-reports` are PRIVATE buckets. `getPublicUrl()` returns a URL
6 | // that won't actually work for them (it returns a 404). Use `getSignedUrl()`
7 | // at READ time instead (when about to display or download), and store only
8 | // the storage path in the database.
9 | //
10 | // Buckets:
11 | // - avatars           !' PUBLIC, use getPublicUrl()
12 | // - submissions       !' PRIVATE, use getSignedUrl()
13 | // - session-evidence  !' PRIVATE, use getSignedUrl()
14 | // - course-materials !' PRIVATE, use getSignedUrl()
15 | // - accreditation-reports !' PRIVATE, use getSignedUrl()
16 | // =====
17 |
18 | import { supabase } from "@lib/supabase";
19 |
20 | const SIGNED_URL_TTL_SECONDS = 60 * 60; // 1 hour
21 |
22 | /**
23 |  * Generate a signed URL for a file in a private bucket.

```

```

24 | * Pass the storage path (not the full URL) you stored in the database.
25 | *
26 | * Example:
27 | *   const url = await getSignedUrl("submissions", submission.file_url);
28 | *   if (url) window.open(url, "_blank");
29 | *
30 | * Returns null if the file doesn't exist or signing fails.
31 | */
32 | export async function getSignedUrl(
33 |   bucket: string,
34 |   path: string,
35 |   ttlSeconds: number = SIGNED_URL_TTL_SECONDS
36 | ): Promise<string | null> {
37 |   if (!path) return null;
38 |   const { data, error } = await supabase.storage
39 |     .from(bucket)
40 |     .createSignedUrl(path, ttlSeconds);
41 |   if (error) {
42 |     console.error(`getSignedUrl(${bucket}, ${path}) failed:`, error.message);
43 |     return null;
44 |   }
45 |   return data.signedUrl;
46 | }
47 |
48 | /**
49 | * Generate signed URLs for many paths in one round trip.
50 | * Falls back to per-path createSignedUrl if the batch API isn't available.
51 | */
52 | export async function getSignedUrls(
53 |   bucket: string,
54 |   paths: string[],
55 |   ttlSeconds: number = SIGNED_URL_TTL_SECONDS
56 | ): Promise<Record<string, string>> {
57 |   if (paths.length === 0) return {};
58 |   const { data, error } = await supabase.storage
59 |     .from(bucket)
60 |     .createSignedUrls(paths, ttlSeconds);
61 |   if (error || !data) {
62 |     console.error(`getSignedUrls(${bucket}) failed:`, error?.message);
63 |     return {};
64 |   }
65 |   const result: Record<string, string> = {};
66 |   for (const item of data) {
67 |     if (item.signedUrl && item.path) {
68 |       result[item.path] = item.signedUrl;
69 |     }
70 |   }
71 |   return result;
72 | }
73 |

```

FILE: src/lib/streakCalculator.ts

TYPE: .ts | LINES: 1-273 | SHA256: 12f88c3a150910e31a2a95d421a9d8f541894be8c5b61c5a59b86af2af344840

```

1 | // =====
2 | // Streak Calculator - Pure functions for streak update logic
3 | // =====
4 |
5 | export interface StreakState {
6 |   streak_count: number;
7 |   last_login_date: string | null;
8 |   streak_freezes_available: number;
9 | }
10 |
11 | export interface StreakResult {
12 |   new_streak_count: number;
13 |   streak_frozen: boolean;
14 |   freeze_consumed: boolean;
15 |   milestone_reached: number | null;
16 |   should_reset: boolean;
17 |   is_new_day: boolean;
18 | }
19 |
20 | export const STREAK_MILESTONES = [7, 14, 30, 60, 100] as const;
21 |
22 | export const MILESTONE_XP: Record<number, number> = {
23 |   7: 100,
24 |   14: 100,
25 |   30: 250,
26 |   60: 250,
27 |   100: 500,
28 | };
29 |
30 | /**
31 | * Calculate the number of calendar days between two YYYY-MM-DD date strings.
32 | * Returns the absolute difference in days.
33 | */
34 | export function daysBetween(dateA: string, dateB: string): number {
35 |   const a = new Date(dateA + "T00:00:00Z");
36 |   const b = new Date(dateB + "T00:00:00Z");
37 |   return Math.floor(Math.abs(a.getTime() - b.getTime()) / 86_400_000);
38 | }
39 |
40 | /**
41 | * Determine the streak milestone reached at a given streak count.
42 | * Returns the milestone number if the count exactly matches, otherwise null.
43 | */
44 | export function checkMilestone(streakCount: number): number | null {
45 |   return STREAK_MILESTONES.includes(
46 |     streakCount as (typeof STREAK_MILESTONES)[number]
47 |   )
48 |     ? streakCount
49 |     : null;
50 | }

```

[illegible]

```

155 | /**
156 |  * Check if a given date is a Streak Sabbatical rest day (Saturday or Sunday).
157 |  * Returns false when sabbatical is not enabled.
158 |  */
159 | export function isStreakSabbaticalDay(
160 |   sabbaticalEnabled: boolean,
161 |   dateStr: string
162 | ): boolean {
163 |   if (!sabbaticalEnabled) return false;
164 |   const d = new Date(dateStr + "T00:00:00Z");
165 |   const day = d.getUTCDay();
166 |   return day === 0 || day === 6; // Sunday = 0, Saturday = 6
167 | }
168 |
169 | /**
170 |  * Calculate the streak update given the current state and today's UTC date.
171 |  *
172 |  * Rules:
173 |  * - Same day login !' no-op (is_new_day = false)
174 |  * - Yesterday !' increment streak by 1
175 |  * - Missed exactly 1 day + freeze available !' consume freeze, keep streak
176 |  * - Missed >1 day or no freeze !' reset streak to 1
177 |  * - No existing record (null) !' new streak of 1
178 |  * - When streakSabbaticalEnabled, weekend days in the gap are excluded from the day count
179 |  */
180 | export function calculateStreakUpdate(
181 |   current: StreakState | null,
182 |   todayUTC: string,
183 |   streakSabbaticalEnabled = false
184 | ): StreakResult {
185 |   // No existing record - first login ever
186 |   if (!current || !current.last_login_date) {
187 |     return {
188 |       new_streak_count: 1,
189 |       streak_frozen: false,
190 |       freeze_consumed: false,
191 |       milestone_reached: null,
192 |       should_reset: false,
193 |       is_new_day: true,
194 |     };
195 |   }
196 |
197 |   const dayDiff = daysBetween(current.last_login_date, todayUTC);
198 |
199 |   // Same day - no-op
200 |   if (dayDiff === 0) {
201 |     return {
202 |       new_streak_count: current.streak_count,
203 |       streak_frozen: false,
204 |       freeze_consumed: false,
205 |       milestone_reached: null,
206 |       should_reset: false,
207 |       is_new_day: false,
208 |     };
209 |   }
210 |
211 |   // Consecutive day (yesterday)
212 |   if (dayDiff === 1) {
213 |     const newCount = current.streak_count + 1;
214 |     return {
215 |       new_streak_count: newCount,
216 |       streak_frozen: false,
217 |       freeze_consumed: false,
218 |       milestone_reached: checkMilestone(newCount),
219 |       should_reset: false,
220 |       is_new_day: true,
221 |     };
222 |   }
223 |
224 |   // Streak Sabbatical: count weekend days in the gap and subtract them
225 |   let effectiveDayDiff = dayDiff;
226 |   if (streakSabbaticalEnabled && dayDiff > 1) {
227 |     let weekendDaysInGap = 0;
228 |     const gapStart = new Date(current.last_login_date + "T00:00:00Z");
229 |     for (let i = 1; i < dayDiff; i++) {
230 |       const checkDate = new Date(gapStart.getTime() + i * 86_400_000);
231 |       const dow = checkDate.getUTCDay();
232 |       if (dow === 0 || dow === 6) weekendDaysInGap++;
233 |     }
234 |     effectiveDayDiff = dayDiff - weekendDaysInGap;
235 |   }
236 |
237 |   // After sabbatical adjustment, check if effectively consecutive
238 |   if (effectiveDayDiff <= 1) {
239 |     const newCount = current.streak_count + 1;
240 |     return {
241 |       new_streak_count: newCount,
242 |       streak_frozen: false,
243 |       freeze_consumed: false,
244 |       milestone_reached: checkMilestone(newCount),
245 |       should_reset: false,
246 |       is_new_day: true,
247 |     };
248 |   }
249 |
250 |   // Missed exactly 1 effective day (effectiveDayDiff === 2) with freeze available
251 |   if (effectiveDayDiff === 2 && current.streak_freezes_available > 0) {
252 |     const newCount = current.streak_count + 1;
253 |     return {
254 |       new_streak_count: newCount,
255 |       streak_frozen: true,
256 |       freeze_consumed: true,
257 |       milestone_reached: checkMilestone(newCount),
258 |       should_reset: false,

```

```

259 |         is_new_day: true,
260 |     };
261 | }
262 |
263 | // Missed more than 1 effective day or no freeze !' reset
264 | return {
265 |     new_streak_count: 1,
266 |     streak_frozen: false,
267 |     freeze_consumed: false,
268 |     milestone_reached: null,
269 |     should_reset: true,
270 |     is_new_day: true,
271 | };
272 | }
273 |

```

FILE: src/lib/streakMilestones.ts

TYPE: .ts | LINES: 1-61 | SHA256: 30d5254d56380a835a7b385aa2da05b6f93deaf493afef9e9eb68711dbb5fd31

```

1 | import type { HeatmapDay, StreakMilestone } from "@types/habits";
2 |
3 | const MILESTONES = [7, 14, 30, 60, 100] as const;
4 |
5 | /**
6 |  * Returns the next milestone threshold above the current streak count,
7 |  * or null if all milestones have been reached.
8 |  */
9 | export function getNextMilestone(streakCount: number): number | null {
10 |     for (const m of MILESTONES) {
11 |         if (streakCount < m) return m;
12 |     }
13 |     return null;
14 | }
15 |
16 | /**
17 |  * Returns the percentage progress (0-100) toward the next milestone.
18 |  * If all milestones are reached, returns 100.
19 |  */
20 | export function getMilestoneProgress(streakCount: number): number {
21 |     if (streakCount <= 0) return 0;
22 |
23 |     let prevMilestone = 0;
24 |     for (const m of MILESTONES) {
25 |         if (streakCount < m) {
26 |             const rangeSize = m - prevMilestone;
27 |             const progressInRange = streakCount - prevMilestone;
28 |             return Math.round((progressInRange / rangeSize) * 100);
29 |         }
30 |         prevMilestone = m;
31 |     }
32 |
33 |     return 100;
34 | }
35 |
36 | /**
37 |  * Detects streak milestones (30, 60, 100 consecutive active days) from
38 |  * a sorted array of HeatmapDay objects. A day is considered "active" when
39 |  * its academicCount > 0. Returns milestones in the order they were achieved.
40 |  */
41 | export function detectStreakMilestones(days: HeatmapDay[]): StreakMilestone[] {
42 |     const milestoneThresholds = [30, 60, 100] as const;
43 |     const milestones: StreakMilestone[] = [];
44 |     let consecutiveDays = 0;
45 |
46 |     for (const day of days) {
47 |         if (day.academicCount > 0) {
48 |             consecutiveDays++;
49 |             for (const threshold of milestoneThresholds) {
50 |                 if (consecutiveDays === threshold) {
51 |                     milestones.push({ days: threshold, achievedDate: day.date });
52 |                 }
53 |             }
54 |         } else {
55 |             consecutiveDays = 0;
56 |         }
57 |     }
58 |
59 |     return milestones;
60 | }
61 |

```

FILE: src/lib/studentCourseCards.ts

TYPE: .ts | LINES: 1-185 | SHA256: cf68b9bda93cb08db26dabbe65282bd01c7d661985814f545b7b8b5ae3b3a59e

```

1 | /**
2 |  * Pure aggregation logic for student course cards.
3 |  *
4 |  * Kept free of React and Supabase so it can be unit-tested directly and reused
5 |  * by `useStudentCourses`. The hook performs a fixed, small number of batched
6 |  * queries and hands the raw rows to {@link buildCourseCards}, which merges them
7 |  * in memory – there is no per-card (N+1) fetching.
8 |  *
9 |  * Satisfies Requirements 9.1, 9.2, 9.2a, 9.4, 9.5.
10 |  */
11 |
12 | export interface CourseCardCourse {
13 |     id: string;
14 |     name: string;
15 |     code: string;
16 |     color: string | null;
17 |     teacher_name: string | null;
18 | }
19 |
20 | export interface CourseCardEnrollment {

```



```

21 |   course_id: string;
22 |   course: CourseCardCourse;
23 | }
24 |
25 | export interface CourseCardAttainmentRow {
26 |   course_id: string | null;
27 |   attainment_percent: number;
28 | }
29 |
30 | export interface CourseCardAssignmentRow {
31 |   id: string;
32 |   course_id: string | null;
33 |   title: string;
34 |   /** `due_date` is non-null in the schema, but modelled nullable for R9.2a. */
35 |   due_date: string | null;
36 | }
37 |
38 | export interface NextAssignment {
39 |   title: string;
40 |   due_at: string | null;
41 | }
42 |
43 | export interface EnrolledCourseCard {
44 |   id: string;
45 |   name: string;
46 |   code: string;
47 |   teacher_name: string | null;
48 |   /** Average course-scoped attainment, or null when no evidence exists. */
49 |   attainment_percent: number | null;
50 |   /** Completed-vs-total assignment progress, 0-100. */
51 |   progress_percent: number;
52 |   /** Earliest upcoming assignment, or null when there is no upcoming work. */
53 |   next_assignment: NextAssignment | null;
54 |   /** Course color identifier, or null when unassigned. */
55 |   color: string | null;
56 |   /** Total assignments in the course. */
57 |   assignments_count: number;
58 | }
59 |
60 | export interface BuildCourseCardsInput {
61 |   enrollments: CourseCardEnrollment[];
62 |   attainmentRows: CourseCardAttainmentRow[];
63 |   assignmentRows: CourseCardAssignmentRow[];
64 |   /** Assignment ids for which the student has a completed (graded) submission. */
65 |   completedAssignmentIds: ReadonlySet<string>;
66 |   /** Reference "now" used to determine which assignments are upcoming. */
67 |   now: Date;
68 | }
69 |
70 | const roundPercent = (value: number): number => Math.round(value);
71 |
72 | /**
73 |  * Merge batched query rows into per-course card view models.
74 |  *
75 |  * - `attainment_percent` is the mean of all course-scoped attainment rows for
76 |  *   the course, or null when none exist.
77 |  * - `progress_percent` is completed (graded) assignments over total assignments.
78 |  * - `next_assignment` is the earliest assignment whose `due_date` is at or after
79 |  *   `now`; assignments without a due date are still surfaced (R9.2a) but ordered
80 |  *   after dated ones so a concrete deadline is preferred.
81 |  * - `assignments_count` is the total number of assignments for the course.
82 |  */
83 | export function buildCourseCards(
84 |   input: BuildCourseCardsInput
85 | ): EnrolledCourseCard[] {
86 |   const {
87 |     enrollments,
88 |     attainmentRows,
89 |     assignmentRows,
90 |     completedAssignmentIds,
91 |     now,
92 |   } = input;
93 |
94 |   const attainmentByCourse = new Map<string, number[]>();
95 |   for (const row of attainmentRows) {
96 |     if (!row.course_id) continue;
97 |     const arr = attainmentByCourse.get(row.course_id) ?? [];
98 |     arr.push(row.attainment_percent);
99 |     attainmentByCourse.set(row.course_id, arr);
100 |   }
101 |
102 |   const assignmentsByCourse = new Map<string, CourseCardAssignmentRow[]>();
103 |   for (const row of assignmentRows) {
104 |     if (!row.course_id) continue;
105 |     const arr = assignmentsByCourse.get(row.course_id) ?? [];
106 |     arr.push(row);
107 |     assignmentsByCourse.set(row.course_id, arr);
108 |   }
109 |
110 |   const nowMs = now.getTime();
111 |
112 |   return enrollments.map((enrollment) => {
113 |     const course = enrollment.course;
114 |
115 |     const attainmentVals = attainmentByCourse.get(course.id) ?? [];
116 |     const attainment_percent =
117 |       attainmentVals.length > 0
118 |         ? roundPercent(
119 |             attainmentVals.reduce((sum, v) => sum + v, 0) /
120 |             attainmentVals.length
121 |           )
122 |       : null;
123 |
124 |     const courseAssignments = assignmentsByCourse.get(course.id) ?? [];

```

```

125;
126
127 const completedCount = courseAssignments.reduce(
128   (count, a) => (completedAssignmentIds.has(a.id) ? count + 1 : count),
129   0
130 );
131 const progress_percent =
132   assignments_count > 0
133     ? roundPercent((completedCount / assignments_count) * 100)
134     : 0;
135
136 const next_assignment = selectNextAssignment(courseAssignments, nowMs);
137
138 return {
139   id: course.id,
140   name: course.name,
141   code: course.code,
142   teacher_name: course.teacher_name,
143   attainment_percent,
144   progress_percent,
145   next_assignment,
146   color: course.color,
147   assignments_count,
148 };
149 });
150 }
151
152 /**
153  * Pick the earliest upcoming assignment for a course. Assignments with a due
154  * date at or after 'nowMs' are preferred and ordered by due date ascending;
155  * those without a due date are returned only when no dated upcoming work exists.
156  */
157 function selectNextAssignment(
158   assignments: CourseCardAssignmentRow[],
159   nowMs: number
160 ): NextAssignment | null {
161   let earliestDated: CourseCardAssignmentRow | null = null;
162   let earliestDatedMs = Number.POSITIVE_INFINITY;
163   let undatedFallback: CourseCardAssignmentRow | null = null;
164
165   for (const assignment of assignments) {
166     if (assignment.due_date == null) {
167       undatedFallback ??= assignment;
168       continue;
169     }
170     const dueMs = new Date(assignment.due_date).getTime();
171     if (Number.isNaN(dueMs)) {
172       undatedFallback ??= assignment;
173       continue;
174     }
175     if (dueMs >= nowMs && dueMs < earliestDatedMs) {
176       earliestDated = assignment;
177       earliestDatedMs = dueMs;
178     }
179   }
180
181   const chosen = earliestDated ?? undatedFallback;
182   if (!chosen) return null;
183   return { title: chosen.title, due_at: chosen.due_date };
184 }
185

```

FILE: src/lib/submissionDeadline.ts

```
TYPE: .ts | LINES: 1-71 | SHA256: 362fbf0a7105041ee67b005d486c7790ba52cd2c067e3684918e1797126c40c2
```

[illegible]

```

40 |         isLate: false,
41 |         canSubmit: true,
42 |         dueDate: due,
43 |         lateDeadline,
44 |         timeRemaining: formatDistanceToNow(due, { addSuffix: true }),
45 |         isExtended,
46 |     };
47 | }
48 |
49 | if (!isPast(lateDeadline)) {
50 |     return {
51 |         window: "late_window",
52 |         isLate: true,
53 |         canSubmit: true,
54 |         dueDate: due,
55 |         lateDeadline,
56 |         timeRemaining: formatDistanceToNow(lateDeadline, { addSuffix: true }),
57 |         isExtended,
58 |     };
59 | }
60 |
61 | return {
62 |     window: "closed",
63 |     isLate: false,
64 |     canSubmit: false,
65 |     dueDate: due,
66 |     lateDeadline,
67 |     timeRemaining: "Closed",
68 |     isExtended,
69 | };
70 | }
71 |

```

FILE: src/lib/supabase.ts

TYPE: .ts | LINES: 1-20 | SHA256: 4d737c74426e6cb207f0ca59e63d75a9e65c5599ddab140b233d15e5399887f5

```

1 | import { createClient } from "@supabase/supabase-js";
2 | import type { Database } from "@types/database";
3 |
4 | const supabaseUrl = import.meta.env.VITE_SUPABASE_URL;
5 | const supabaseAnonKey = import.meta.env.VITE_SUPABASE_ANON_KEY;
6 |
7 | if (!supabaseUrl || !supabaseAnonKey) {
8 |     throw new Error(
9 |         "Missing Supabase environment variables. Set VITE_SUPABASE_URL and VITE_SUPABASE_ANON_KEY in .env.local"
10 |    );
11 | }
12 |
13 | export const supabase = createClient<Database>(supabaseUrl, supabaseAnonKey, {
14 |     auth: {
15 |         autoRefreshToken: true,
16 |         persistSession: true,
17 |         detectSessionInUrl: true,
18 |     },
19 | });
20 |

```

FILE: src/lib/surveyAggregators.ts

TYPE: .ts | LINES: 1-60 | SHA256: a12923bc2cc4f2a32679d59c83a926d93e11a6ae887259683d67479df58e156a

```

1 | // Shared survey aggregation helpers used by SurveyResultsPage and tests
2 | // Extracted to avoid logic duplication between production and test code.
3 |
4 | export const LIKERT_LABELS = [
5 |     "Strongly Disagree",
6 |     "Disagree",
7 |     "Neutral",
8 |     "Agree",
9 |     "Strongly Agree",
10 | ] as const;
11 |
12 | export interface LikertAggregation {
13 |     label: string;
14 |     count: number;
15 | }
16 |
17 | export interface MCQAggregation {
18 |     option: string;
19 |     count: number;
20 | }
21 |
22 | export interface AggregableResponse {
23 |     question_id: string;
24 |     response_value: string;
25 | }
26 |
27 | export function aggregateLikert(
28 |     responses: AggregableResponse[],
29 |     questionId: string
30 | ): LikertAggregation[] {
31 |     const counts = new Map<string, number>();
32 |     for (const label of LIKERT_LABELS) counts.set(label, 0);
33 |
34 |     for (const r of responses) {
35 |         if (r.question_id === questionId && counts.has(r.response_value)) {
36 |             counts.set(r.response_value, (counts.get(r.response_value) ?? 0) + 1);
37 |         }
38 |     }
39 |
40 |     return LIKERT_LABELS.map((label) => ({
41 |         label,
42 |         count: counts.get(label) ?? 0,
43 |     }));
44 | }

```

```

45 |
46 | export function aggregateMCQ(
47 |   responses: AggregableResponse[],
48 |   questionId: string
49 | ): MCQAggregation[] {
50 |   const counts: Record<string, number> = {};
51 |
52 |   for (const r of responses) {
53 |     if (r.question_id === questionId) {
54 |       counts[r.response_value] = (counts[r.response_value] ?? 0) + 1;
55 |     }
56 |   }
57 |
58 |   return Object.entries(counts).map(([option, count]) => ({ option, count }));
59 | }
60 |

```

FILE: [src/lib/teamBadgeChecker.ts](#)

TYPE: .ts | LINES: 1-69 | SHA256: 3aea2818bde9ce32b31f6651c2298e621b28eac8035b2ef6d869bf6af7ef1e39

```

1 | // =====
2 | // Team Badge Checker – Pure functions for team badge eligibility
3 | // =====
4 |
5 | export interface TeamBadgeState {
6 |   xp_total: number;
7 |   challenge_wins: number;
8 |   all_members_perfect_day: boolean;
9 |   team_streak_current: number;
10 | }
11 |
12 | export type TeamBadgeId =
13 |   | "team_spirit"
14 |   | "unstoppable"
15 |   | "dream_team"
16 |   | "study_squad";
17 |
18 | export interface TeamBadgeResult {
19 |   badge_id: TeamBadgeId;
20 |   eligible: boolean;
21 | }
22 |
23 | export const TEAM_BADGE_CONDITIONS: Record<
24 |   TeamBadgeId,
25 |   (state: TeamBadgeState) => boolean
26 | > = {
27 |   team_spirit: (state) => state.xp_total >= 500,
28 |   unstoppable: (state) => state.challenge_wins >= 3,
29 |   dream_team: (state) => state.all_members_perfect_day,
30 |   study_squad: (state) => state.team_streak_current >= 7,
31 | };
32 |
33 | /**
34 |  * Check which team badges a team is eligible for, excluding already-earned badges.
35 |  * Returns only NEW badges that should be awarded.
36 |  */
37 | export function checkTeamBadgeEligibility(
38 |   state: TeamBadgeState,
39 |   alreadyEarned: Set<string>
40 | ): TeamBadgeResult[] {
41 |   const results: TeamBadgeResult[] = [];
42 |
43 |   for (const [badgeId, condition] of Object.entries(TEAM_BADGE_CONDITIONS)) {
44 |     const id = badgeId as TeamBadgeId;
45 |     const eligible = condition(state) && !alreadyEarned.has(id);
46 |     results.push({ badge_id: id, eligible });
47 |   }
48 |
49 |   return results;
50 | }
51 |
52 | /**
53 |  * Simulate awarding badges idempotently.
54 |  * Given a set of already-earned badges and new eligible badges,
55 |  * returns the final set of earned badges (union, no duplicates).
56 |  */
57 | export function awardTeamBadgesIdempotent(
58 |   alreadyEarned: Set<string>,
59 |   newEligible: TeamBadgeResult[]
60 | ): Set<string> {
61 |   const result = new Set<string>(alreadyEarned);
62 |   for (const badge of newEligible) {
63 |     if (badge.eligible) {
64 |       result.add(badge.badge_id);
65 |     }
66 |   }
67 |   return result;
68 | }
69 |

```

FILE: [src/lib/teamBadgeDefinitions.ts](#)

TYPE: .ts | LINES: 1-90 | SHA256: 21928dd44aec062d4b8f84d2f5931565f259229cf0a42ea94d5be019a5afc636

```

1 | // Team badge definitions for the Edeviser gamification engine.
2 | // All team badge conditions are defined here as a single source of truth.
3 | // Follows the same pattern as badgeDefinitions.ts.
4 |
5 | import type { BadgeCategory, BadgeDef } from "@lib/badgeDefinitions";
6 |
7 | export const TEAM_BADGE_DEFINITIONS: BadgeDef[] = [
8 |   {
9 |     id: "team_spirit",
10 |    name: "Team Spirit",
11 |    description: "All members submitted an assignment on the same calendar day",

```

```

12 |     icon: "0>Ý ",
13 |     category: "team" as BadgeCategory,
14 |     isMystery: false,
15 |     condition: "All team members submit an assignment on the same calendar day",
16 |     xpReward: 100,
17 | },
18 | {
19 |     id: "streak_squad",
20 |     name: "Streak Squad",
21 |     description: "Team maintained a 7-day streak",
22 |     icon: "0=Y%",
23 |     category: "team" as BadgeCategory,
24 |     isMystery: false,
25 |     condition: "Team streak reaches 7 consecutive days",
26 |     xpReward: 75,
27 | },
28 | {
29 |     id: "streak_champions",
30 |     name: "Streak Champions",
31 |     description: "Team maintained a 14-day streak",
32 |     icon: "0<ßA",
33 |     category: "team" as BadgeCategory,
34 |     isMystery: false,
35 |     condition: "Team streak reaches 14 consecutive days",
36 |     xpReward: 100,
37 | },
38 | {
39 |     id: "streak_legends",
40 |     name: "Streak Legends",
41 |     description: "Team maintained a 30-day streak",
42 |     icon: "0<ßÆ",
43 |     category: "team" as BadgeCategory,
44 |     isMystery: false,
45 |     condition: "Team streak reaches 30 consecutive days",
46 |     xpReward: 150,
47 | },
48 | {
49 |     id: "full_house",
50 |     name: "Full House",
51 |     description: "Team reached maximum 6 members",
52 |     icon: "0<ßà",
53 |     category: "team" as BadgeCategory,
54 |     isMystery: false,
55 |     condition: "Team reaches the maximum of 6 active members",
56 |     xpReward: 50,
57 | },
58 | {
59 |     id: "quest_conquerors",
60 |     name: "Quest Conquerors",
61 |     description: "Team completed 3 social challenges",
62 |     icon: "&"p ",
63 |     category: "team" as BadgeCategory,
64 |     isMystery: false,
65 |     condition: "Team completes 3 social challenges",
66 |     xpReward: 150,
67 | },
68 | {
69 |     id: "team_player",
70 |     name: "Team Player",
71 |     description: "Maintained active contribution for 14+ consecutive days",
72 |     icon: "0=Ua",
73 |     category: "team" as BadgeCategory,
74 |     isMystery: false,
75 |     condition:
76 |       'Maintain contribution status "active" for 14 or more consecutive days',
77 |     xpReward: 100,
78 | },
79 | ];
80 |
81 | /** Get a team badge definition by ID */
82 | export function getTeamBadgeById(id: string): BadgeDef | undefined {
83 |   return TEAM_BADGE_DEFINITIONS.find((b) => b.id === id);
84 | }
85 |
86 | /** Get all team badge IDs */
87 | export function getAllTeamBadgeIds(): string[] {
88 |   return TEAM_BADGE_DEFINITIONS.map((b) => b.id);
89 | }
90 |

```

FILE: [src/lib/teamHealthCalculator.ts](#)

TYPE: .ts | LINES: 1-177 | SHA256: 0f6eb8e6afd8bff4afb18004094289015b9aaf399167c5bfa8d7b71042e53f22

```

1 | // Team Health Calculator – AI-powered team health monitoring.
2 | // Computes Gini coefficient, engagement trends, and composite health scores.
3 | // Used by the weekly health computation cron job (Monday 02:00 UTC).
4 |
5 | export type EngagementTrend = "rising" | "stable" | "declining";
6 | export type HealthStatus = "healthy" | "needs_attention" | "at_risk";
7 |
8 | export interface TeamHealthInput {
9 |   /** XP contributions per member for the current evaluation period */
10 |   memberXpContributions: number[];
11 |   /** Total team XP this week */
12 |   thisWeekXp: number;
13 |   /** Total team XP last week */
14 |   lastWeekXp: number;
15 |   /** Challenge participation rate (0-1): fraction of available challenges the team joined */
16 |   participationRate: number;
17 |   /** Activity overlap rate (0-1): fraction of days with 2+ active members out of 7 */
18 |   overlapRate: number;
19 | }
20 |
21 | export interface TeamHealthResult {

```

[illegible]

```

126 | export function classifyHealthStatus(healthScore: number): HealthStatus {
127 |   if (healthScore >= 70) {
128 |     return "healthy";
129 |   }
130 |   if (healthScore >= 40) {
131 |     return "needs_attention";
132 |   }
133 |   return "at_risk";
134 | }
135 |
136 | /**
137 |  * Compute the composite team health score and classification.
138 |  *
139 |  * Formula:
140 |  *   health = 0.30 × (1 - Gini) × 100
141 |  *           + 0.25 × trend_score
142 |  *           + 0.25 × participation × 100
143 |  *           + 0.20 × overlap × 100
144 |  *
145 |  * @param input - Team health input data
146 |  * @returns Health score (0-100), status, Gini coefficient, and engagement trend
147 |  */
148 | export function computeTeamHealth(input: TeamHealthInput): TeamHealthResult {
149 |   const giniCoefficient = computeGiniCoefficient(input.memberXpContributions);
150 |   const engagementTrend = detectEngagementTrend(
151 |     input.thisWeekXp,
152 |     input.lastWeekXp
153 |   );
154 |   const trendScore = trendToScore(engagementTrend);
155 |
156 |   // Clamp rates to [0, 1]
157 |   const participation = Math.max(0, Math.min(1, input.participationRate));
158 |   const overlap = Math.max(0, Math.min(1, input.overlapRate));
159 |
160 |   const rawScore =
161 |     WEIGHT_EQUALITY * (1 - giniCoefficient) * 100 +
162 |     WEIGHT_TREND * trendScore +
163 |     WEIGHT_PARTICIPATION * participation * 100 +
164 |     WEIGHT_OVERLAP * overlap * 100;
165 |
166 |   // Clamp to [0, 100] and round
167 |   const healthScore = Math.round(Math.max(0, Math.min(100, rawScore)));
168 |   const healthStatus = classifyHealthStatus(healthScore);
169 |
170 |   return {
171 |     healthScore,
172 |     healthStatus,
173 |     giniCoefficient,
174 |     engagementTrend,
175 |   };
176 | }
177 |

```

FILE: [src/lib/teamStreakCalculator.ts](#)

TYPE: .ts | LINES: 1-131 | SHA256: 42adbb74a4a1980aa1865d7c3fb58f40b256fe58591fef6e0a8788629e33f914

```

1 | // =====
2 | // Team Streak Calculator – Pure functions for team streak logic
3 | // =====
4 |
5 | import { daysBetween } from "@lib/streakCalculator";
6 |
7 | export interface TeamStreakState {
8 |   streak_current: number;
9 |   streak_longest: number;
10 |   last_streak_date: string | null;
11 | }
12 |
13 | export interface TeamStreakResult {
14 |   new_streak_current: number;
15 |   new_streak_longest: number;
16 |   is_new_day: boolean;
17 |   streak_reset: boolean;
18 | }
19 |
20 | /**
21 |  * Calculate team streak update.
22 |  *
23 |  * Rules:
24 |  * - ALL members must have logged in on the same calendar day for streak to increment
25 |  * - If any member misses a day, streak resets to 0
26 |  * - Same day != no-op
27 |  * - Consecutive day with all members logged in != increment
28 |  * - Gap > 1 day != reset to 1 (if all logged in today) or 0
29 |  */
30 | export function calculateTeamStreakUpdate(
31 |   current: TeamStreakState | null,
32 |   todayUTC: string,
33 |   allMembersLoggedIn: boolean
34 | ): TeamStreakResult {
35 |   // No existing record
36 |   if (!current || !current.last_streak_date) {
37 |     if (allMembersLoggedIn) {
38 |       return {
39 |         new_streak_current: 1,
40 |         new_streak_longest: Math.max(current?.streak_longest ?? 0, 1),
41 |         is_new_day: true,
42 |         streak_reset: false,
43 |       };
44 |     }
45 |     return {
46 |       new_streak_current: 0,
47 |       new_streak_longest: current?.streak_longest ?? 0,
48 |       is_new_day: true,

```



```

18 |   box_shadow?: string;
19 | }
20 |
21 | /**
22 |  * Resolve profile theme metadata into CSS custom properties.
23 |  *
24 |  * Maps theme accent colours to CSS variables that override the default
25 |  * design-system tokens on the student dashboard.
26 |  */
27 | export function resolveThemeCSS(theme: ThemeMetadata): Record<string, string> {
28 |   return {
29 |     "--theme-accent": theme.accent_primary,
30 |     "--theme-accent-dark": theme.accent_secondary,
31 |     "--theme-accent-bg": theme.accent_bg,
32 |     "--theme-gradient-start": theme.gradient_start,
33 |     "--theme-gradient-end": theme.gradient_end,
34 |   };
35 | }
36 |
37 | /**
38 |  * Resolve avatar frame metadata into CSS custom properties.
39 |  *
40 |  * Produces border and glow properties that wrap the student's profile picture.
41 |  */
42 | export function resolveFrameCSS(frame: FrameMetadata): Record<string, string> {
43 |   const css: Record<string, string> = {
44 |     "--frame-border-color": frame.border_color,
45 |     "--frame-border-width": frame.border_width,
46 |   };
47 |
48 |   if (frame.border_style) {
49 |     css["--frame-border-style"] = frame.border_style;
50 |   }
51 |
52 |   if (frame.border_radius) {
53 |     css["--frame-border-radius"] = frame.border_radius;
54 |   }
55 |
56 |   if (frame.box_shadow) {
57 |     css["--frame-glow"] = frame.box_shadow;
58 |   }
59 |
60 |   return css;
61 | }
62 |

```

FILE: src/lib/timerPersistence.ts

TYPE: .ts | LINES: 1-29 | SHA256: 50629c84db601d517a9ca634abfa2f46cfb641c34b6724a29e643b6ecc084552

```

1 | // =====
2 | // Focus Mode Timer – localStorage Persistence
3 | // =====
4 |
5 | import type { TimerPersistState } from "@types/planner";
6 |
7 | const TIMER_STATE_KEY = "edeviser_focus_timer";
8 |
9 | /** Persist timer state to localStorage. */
10 | export function persistTimerState(state: TimerPersistState): void {
11 |   localStorage.setItem(TIMER_STATE_KEY, JSON.stringify(state));
12 | }
13 |
14 | /** Restore timer state from localStorage. Returns null if not found or invalid. */
15 | export function restoreTimerState(): TimerPersistState | null {
16 |   const raw = localStorage.getItem(TIMER_STATE_KEY);
17 |   if (!raw) return null;
18 |   try {
19 |     return JSON.parse(raw) as TimerPersistState;
20 |   } catch {
21 |     return null;
22 |   }
23 | }
24 |
25 | /** Clear persisted timer state from localStorage. */
26 | export function clearTimerState(): void {
27 |   localStorage.removeItem(TIMER_STATE_KEY);
28 | }
29 |

```

FILE: src/lib/timetableNow.ts

TYPE: .ts | LINES: 1-180 | SHA256: d821c6dfec345f07dad97d6992c2df1da5f88d61127ac2858758492cca9ad500

```

1 | // Task 19.3: Current/next-class context for the student timetable (pure logic)
2 | // Requirements: 12.4, 13.2, 21.3
3 | //
4 | // Given the student's section timetable slots and the current moment, decide
5 | // whether a class is happening *now* or which class is *next*, and how much
6 | // time remains until the relevant transition. Kept as a pure, side-effect-free
7 | // module in `src/lib/` so it is unit-testable independently of the timetable
8 | // view, the data hook, and the wall clock.
9 |
10 | import type { TimetableSlot } from "@hooks/useTimetable";
11 |
12 | /** Minutes in a single day. */
13 | const MINUTES_PER_DAY = 24 * 60;
14 | /** Minutes in a full week – the modulus for week-wrapping arithmetic. */
15 | const MINUTES_PER_WEEK = 7 * MINUTES_PER_DAY;
16 |
17 | /**
18 |  * Discriminated status of the timetable "now" context.
19 |  * - `in_class` – a slot is currently in progress.
20 |  * - `upcoming` – no slot is in progress, but at least one starts later.
21 |  * - `none` – there are no (parseable) slots to anchor a context to.
22 |  */

```

```

23 | export type TimetableNowStatus = "in_class" | "upcoming" | "none";
24 |
25 | export interface TimetableNowContext {
26 |   /** Which case applies right now. */
27 |   status: TimetableNowStatus;
28 |   /** The relevant slot (current class or next class); `null` when `none`. */
29 |   slot: TimetableSlot | null;
30 |   /**
31 |    * Whole minutes until the relevant transition:
32 |    * - for `in_class`: minutes until the current class ends,
33 |    * - for `upcoming`: minutes until the next class starts (week-wrapping),
34 |    * - for `none`: `null`.
35 |    * Always a non-negative integer when present.
36 |    */
37 |   minutes: number | null;
38 | }
39 |
40 | export interface DurationParts {
41 |   days: number;
42 |   hours: number;
43 |   minutes: number;
44 | }
45 |
46 | /**
47 |  * Parse a `HH:MM` / `HH:MM:SS` time-of-day string into minutes since midnight.
48 |  * Returns `null` for anything that is not a valid 24-hour time so callers can
49 |  * skip malformed slots instead of producing nonsensical contexts.
50 |  */
51 | export function parseTimeToMinutes(
52 |   time: string | null | undefined
53 | ): number | null {
54 |   if (typeof time !== "string") return null;
55 |   const match = /^(\d{1,2}):(\d{2})(?::(\d{2}))?$/ .exec(time.trim());
56 |   if (!match) return null;
57 |   const hours = Number(match[1]);
58 |   const mins = Number(match[2]);
59 |   if (hours > 23 || mins > 59) return null;
60 |   return hours * 60 + mins;
61 | }
62 |
63 | /**
64 |  * Convert a `Date` to "minutes elapsed since the start of the week" using the
65 |  * same 0=Sunday ... 6=Saturday convention as `timetable_slots.day_of_week`.
66 |  * Uses the local clock because timetable times are stored as local wall-clock
67 |  * times for the section.
68 |  */
69 | function nowWeekMinute(now: Date): number {
70 |   return (
71 |     now.getDay() * MINUTES_PER_DAY + now.getHours() * 60 + now.getMinutes()
72 |   );
73 | }
74 |
75 | interface ResolvedSlot {
76 |   slot: TimetableSlot;
77 |   startWeekMin: number;
78 |   endWeekMin: number;
79 | }
80 |
81 | /**
82 |  * Resolve a slot into absolute week-minute start/end bounds, discarding slots
83 |  * with an unparseable day or time, or with a non-positive duration.
84 |  */
85 | function resolveSlot(slot: TimetableSlot): ResolvedSlot | null {
86 |   const day = slot.day_of_week;
87 |   if (!Number.isInteger(day) || day < 0 || day > 6) return null;
88 |   const start = parseTimeToMinutes(slot.start_time);
89 |   const end = parseTimeToMinutes(slot.end_time);
90 |   if (start === null || end === null || end <= start) return null;
91 |   const base = day * MINUTES_PER_DAY;
92 |   return { slot, startWeekMin: base + start, endWeekMin: base + end };
93 | }
94 |
95 | /**
96 |  * Compute the current-or-next class context for a set of timetable slots.
97 |  *
98 |  * Resolution rules:
99 |  * 1. If a slot is in progress (`start <= now < end`), report `in_class` with
100 |  * the minutes remaining until it ends. When several overlap, the one ending
101 |  * soonest is chosen so the countdown reflects the nearest transition.
102 |  * 2. Otherwise, report `upcoming` with the slot whose start is the smallest
103 |  * positive distance ahead of `now`, wrapping across the week boundary so a
104 |  * Friday-evening "now" can point at a Sunday-morning class.
105 |  * 3. With no parseable slots, report `none`.
106 |  *
107 |  * The function is total and pure: identical inputs always yield identical
108 |  * output, and `now` is injected for deterministic testing.
109 |  */
110 | export function computeTimetableNow(
111 |   slots: readonly TimetableSlot[],
112 |   now: Date
113 | ): TimetableNowContext {
114 |   const resolved = slots
115 |     .map(resolveSlot)
116 |     .filter((r): r is ResolvedSlot => r !== null);
117 |
118 |   if (resolved.length === 0) {
119 |     return { status: "none", slot: null, minutes: null };
120 |   }
121 |
122 |   const nowMin = nowWeekMinute(now);
123 |
124 |   // 1) In-progress slot, preferring the one that ends soonest.
125 |   let current: ResolvedSlot | null = null;
126 |   for (const r of resolved) {

```

```

127 |     if (r.startWeekMin <= nowMin && nowMin < r.endWeekMin) {
128 |         if (current === null || r.endWeekMin < current.endWeekMin) {
129 |             current = r;
130 |         }
131 |     }
132 | }
133 | if (current !== null) {
134 |     return {
135 |         status: "in_class",
136 |         slot: current.slot,
137 |         minutes: current.endWeekMin - nowMin,
138 |     };
139 | }
140 |
141 | // 2) Nearest upcoming slot, wrapping around the week.
142 | let next: ResolvedSlot | null = null;
143 | let bestDelta = Number.POSITIVE_INFINITY;
144 | for (const r of resolved) {
145 |     const rawDelta = r.startWeekMin - nowMin;
146 |     // Positive distance ahead; a slot starting "now" or earlier maps to its
147 |     // occurrence next week via the modulus.
148 |     const delta =
149 |         ((rawDelta % MINUTES_PER_WEEK) + MINUTES_PER_WEEK) % MINUTES_PER_WEEK;
150 |     const forwardDelta = delta === 0 ? MINUTES_PER_WEEK : delta;
151 |     if (forwardDelta < bestDelta) {
152 |         bestDelta = forwardDelta;
153 |         next = r;
154 |     }
155 | }
156 |
157 | if (next !== null) {
158 |     return { status: "upcoming", slot: next.slot, minutes: bestDelta };
159 | }
160 |
161 | // Unreachable given resolved.length > 0, but keeps the function total.
162 | return { status: "none", slot: null, minutes: null };
163 | }
164 |
165 | /**
166 |  * Break a non-negative minute count into `{ days, hours, minutes }`.
167 |  * Negative or non-finite inputs collapse to all-zero so presentation never
168 |  * shows a negative countdown.
169 |  */
170 | export function formatDurationParts(totalMinutes: number): DurationParts {
171 |     if (!Number.isFinite(totalMinutes) || totalMinutes <= 0) {
172 |         return { days: 0, hours: 0, minutes: 0 };
173 |     }
174 |     const whole = Math.floor(totalMinutes);
175 |     const days = Math.floor(whole / MINUTES_PER_DAY);
176 |     const hours = Math.floor((whole % MINUTES_PER_DAY) / 60);
177 |     const minutes = whole % 60;
178 |     return { days, hours, minutes };
179 | }
180 |

```

FILE: src/lib/tours/adminTour.ts

TYPE: .ts | LINES: 1-54 | SHA256: c9c2402467f5848d858aa3d1d889a7e0a86c0d55321d827b17318310bf8db605

```

1 | import type { Step } from "react-joyride";
2 |
3 | /**
4 |  * Admin role guided tour steps.
5 |  * Targets: top-bar !' sidebar nav !' KPI row !' primary action !' section cards !' language/theme switcher !' profi
6 |  * Design: ADR-02, §8.5
7 |  * Requirements: 2.15
8 |  */
9 |
10 | export const adminTourSteps: Step[] = [
11 |     {
12 |         target: '[data-tour="top-bar"]',
13 |         content: "tour.admin.step1.content",
14 |         title: "tour.admin.step1.title",
15 |         placement: "bottom",
16 |     },
17 |     {
18 |         target: '[data-tour="primary-nav"]',
19 |         content: "tour.admin.step2.content",
20 |         title: "tour.admin.step2.title",
21 |         placement: "bottom",
22 |     },
23 |     {
24 |         target: '[data-tour="kpi-row"]',
25 |         content: "tour.admin.step3.content",
26 |         title: "tour.admin.step3.title",
27 |         placement: "bottom",
28 |     },
29 |     {
30 |         target: '[data-tour="primary-action"]',
31 |         content: "tour.admin.step4.content",
32 |         title: "tour.admin.step4.title",
33 |         placement: "bottom",
34 |     },
35 |     {
36 |         target: '[data-tour="section-card"]',
37 |         content: "tour.admin.step5.content",
38 |         title: "tour.admin.step5.title",
39 |         placement: "top",
40 |     },
41 |     {
42 |         target: '[data-tour="language-switcher"]',
43 |         content: "tour.admin.step6.content",
44 |         title: "tour.admin.step6.title",
45 |         placement: "bottom",
46 |     },

```

```

47 | {
48 |   target: '[data-tour="profile"]',
49 |   content: "tour.admin.step7.content",
50 |   title: "tour.admin.step7.title",
51 |   placement: "bottom",
52 | },
53 | ];
54 |

```

FILE: src/lib/tours/coordinatorTour.ts

TYPE: .ts | LINES: 1-54 | SHA256: 372cc26bb830365b88684d358f02f0b948dc461675b4723f2a9c66b8fce170de

```

1 | import type { Step } from "react-joyride";
2 |
3 | /**
4 |  * Coordinator role guided tour steps.
5 |  * Targets: top-bar !' sidebar nav !' KPI row !' curriculum matrix !' PLO management !' language/theme switcher !' p
6 |  *
7 |  * Design: ADR-02, §8.5
8 |  * Requirements: 2.15
9 |  */
10 | export const coordinatorTourSteps: Step[] = [
11 |   {
12 |     target: '[data-tour="top-bar"]',
13 |     content: "tour.coordinator.step1.content",
14 |     title: "tour.coordinator.step1.title",
15 |     placement: "bottom",
16 |   },
17 |   {
18 |     target: '[data-tour="primary-nav"]',
19 |     content: "tour.coordinator.step2.content",
20 |     title: "tour.coordinator.step2.title",
21 |     placement: "bottom",
22 |   },
23 |   {
24 |     target: '[data-tour="kpi-row"]',
25 |     content: "tour.coordinator.step3.content",
26 |     title: "tour.coordinator.step3.title",
27 |     placement: "bottom",
28 |   },
29 |   {
30 |     target: '[data-tour="curriculum-matrix"]',
31 |     content: "tour.coordinator.step4.content",
32 |     title: "tour.coordinator.step4.title",
33 |     placement: "top",
34 |   },
35 |   {
36 |     target: '[data-tour="plo-management"]',
37 |     content: "tour.coordinator.step5.content",
38 |     title: "tour.coordinator.step5.title",
39 |     placement: "top",
40 |   },
41 |   {
42 |     target: '[data-tour="language-switcher"]',
43 |     content: "tour.coordinator.step6.content",
44 |     title: "tour.coordinator.step6.title",
45 |     placement: "bottom",
46 |   },
47 |   {
48 |     target: '[data-tour="profile"]',
49 |     content: "tour.coordinator.step7.content",
50 |     title: "tour.coordinator.step7.title",
51 |     placement: "bottom",
52 |   },
53 | ];
54 |

```

FILE: src/lib/tours/parentTour.ts

TYPE: .ts | LINES: 1-54 | SHA256: ade765c8f484046bf115911a8c9a01cfe8d056d40dc84d0636e08fb5f4e963a1

```

1 | import type { Step } from "react-joyride";
2 |
3 | /**
4 |  * Parent role guided tour steps.
5 |  * Targets: top-bar !' sidebar nav !' KPI row !' linked students !' fees/billing !' planner !' language/theme switch
6 |  *
7 |  * Design: ADR-02, §8.5
8 |  * Requirements: 2.15
9 |  */
10 | export const parentTourSteps: Step[] = [
11 |   {
12 |     target: '[data-tour="top-bar"]',
13 |     content: "tour.parent.step1.content",
14 |     title: "tour.parent.step1.title",
15 |     placement: "bottom",
16 |   },
17 |   {
18 |     target: '[data-tour="primary-nav"]',
19 |     content: "tour.parent.step2.content",
20 |     title: "tour.parent.step2.title",
21 |     placement: "bottom",
22 |   },
23 |   {
24 |     target: '[data-tour="kpi-row"]',
25 |     content: "tour.parent.step3.content",
26 |     title: "tour.parent.step3.title",
27 |     placement: "bottom",
28 |   },
29 |   {
30 |     target: '[data-tour="linked-students"]',
31 |     content: "tour.parent.step4.content",
32 |     title: "tour.parent.step4.title",
33 |     placement: "top",
34 |   },

```

```

35 | {
36 |   target: '[data-tour="fees-billing"]',
37 |   content: "tour.parent.step5.content",
38 |   title: "tour.parent.step5.title",
39 |   placement: "top",
40 | },
41 | {
42 |   target: '[data-tour="planner"]',
43 |   content: "tour.parent.step6.content",
44 |   title: "tour.parent.step6.title",
45 |   placement: "top",
46 | },
47 | {
48 |   target: '[data-tour="profile"]',
49 |   content: "tour.parent.step7.content",
50 |   title: "tour.parent.step7.title",
51 |   placement: "bottom",
52 | },
53 | ];
54 |

```

FILE: src/lib/tours/studentTour.ts

TYPE: .ts | LINES: 1-54 | SHA256: 351006c72429193b60c7692db76302c53264158037da08d829175787aa6acf62

```

1 | import type { Step } from "react-joyride";
2 |
3 | /**
4 |  * Student role guided tour steps.
5 |  * Targets: top-bar !' sidebar nav !' welcome hero !' KPI row !' habits tracker !' XP/streak display !' badges !' lan
6 |  *
7 |  * Design: ADR-02, $8.5
8 |  * Requirements: 2.15
9 |  */
10 | export const studentTourSteps: Step[] = [
11 |   {
12 |     target: '[data-tour="top-bar"]',
13 |     content: "tour.student.step1.content",
14 |     title: "tour.student.step1.title",
15 |     placement: "bottom",
16 |   },
17 |   {
18 |     target: '[data-tour="primary-nav"]',
19 |     content: "tour.student.step2.content",
20 |     title: "tour.student.step2.title",
21 |     placement: "bottom",
22 |   },
23 |   {
24 |     target: '[data-tour="welcome-hero"]',
25 |     content: "tour.student.step3.content",
26 |     title: "tour.student.step3.title",
27 |     placement: "bottom",
28 |   },
29 |   {
30 |     target: '[data-tour="kpi-row"]',
31 |     content: "tour.student.step4.content",
32 |     title: "tour.student.step4.title",
33 |     placement: "bottom",
34 |   },
35 |   {
36 |     target: '[data-tour="habits-tracker"]',
37 |     content: "tour.student.step5.content",
38 |     title: "tour.student.step5.title",
39 |     placement: "top",
40 |   },
41 |   {
42 |     target: '[data-tour="xp-streak"]',
43 |     content: "tour.student.step6.content",
44 |     title: "tour.student.step6.title",
45 |     placement: "top",
46 |   },
47 |   {
48 |     target: '[data-tour="profile"]',
49 |     content: "tour.student.step7.content",
50 |     title: "tour.student.step7.title",
51 |     placement: "bottom",
52 |   },
53 | ];
54 |

```

FILE: src/lib/tours/teacherTour.ts

TYPE: .ts | LINES: 1-54 | SHA256: 206735b673a6293e299df9118bf9cc740c54413199dab10a3bd5280880abc6f7

```

1 | import type { Step } from "react-joyride";
2 |
3 | /**
4 |  * Teacher role guided tour steps.
5 |  * Targets: top-bar !' sidebar nav !' KPI row !' CLO creation !' rubric builder !' grading queue !' language/theme s
6 |  *
7 |  * Design: ADR-02, $8.5
8 |  * Requirements: 2.15
9 |  */
10 | export const teacherTourSteps: Step[] = [
11 |   {
12 |     target: '[data-tour="top-bar"]',
13 |     content: "tour.teacher.step1.content",
14 |     title: "tour.teacher.step1.title",
15 |     placement: "bottom",
16 |   },
17 |   {
18 |     target: '[data-tour="primary-nav"]',
19 |     content: "tour.teacher.step2.content",
20 |     title: "tour.teacher.step2.title",
21 |     placement: "bottom",
22 |   },

```


[illegible]

[illegible]

[illegible]

FILE: src/lib/tutorAutonomy.ts

```
TYPE: .ts | LINES: 1-63 | SHA256: 0f9bf148a4b05548999153c499ecef07f45df8701602d603eba8d1f245b4d8b9
```

```

1  /**
2   * Tutor Autonomy Level Resolution
3   *
4   * Resolves the effective autonomy level for a tutor conversation based on:
5   * 1. Assignment-level setting (highest priority)
6   * 2. CLO-level setting (fallback)
7   * 3. Default L2 (if neither is set)
8   * 4. Student override: L1 ("Figure it out") always applies
9   * 5. Student override: L3 ("Just explain it") is capped by teacher ceiling
10  */
11
12  export type AutonomyLevel = "L1" | "L2" | "L3";
13
14  const AUTONOMY_LEVELS: readonly AutonomyLevel[] = ["L1", "L2", "L3"] as const;
15
16  export interface ResolveAutonomyInput {
17    /** Teacher-configured autonomy level on the assignment (null if not set) */
18    assignmentAutonomy: AutonomyLevel | null;
19    /** Teacher-configured autonomy level on the CLO (null if not set) */
20    cloAutonomy: AutonomyLevel | null;
21    /** Student toggle override – can only be L1 or L3 (null if no override) */
22    studentOverride: "L1" | "L3" | null;
23  }
24
25  /**
26   * Resolves the effective autonomy level for a tutor interaction.
27   *
28   * Resolution order:
29   * 1. If assignment has a tutor_autonomy_level set, use it as the base level
30   * 2. Else if CLO has a tutor_autonomy_level set, use it as the base level
31   * 3. Else default to L2
32   * 4. Student override L1 ("Figure it out"): always use L1 regardless of base
33   * 5. Student override L3 ("Just explain it"): use L3 but capped by teacher ceiling
34   *    (the base level acts as the ceiling – student can't exceed it)
35   */
36  export function resolveAutonomyLevel(
37    input: ResolveAutonomyInput
38  ): AutonomyLevel {
39    const { assignmentAutonomy, cloAutonomy, studentOverride } = input;
40
41    // Step 1-3: Determine the base (teacher-configured) level
42    const baseLevel: AutonomyLevel = assignmentAutonomy ?? cloAutonomy ?? "L2";
43
44    // No student override – use the base level directly
45    if (studentOverride === null) {
46      return baseLevel;
47    }
48
49    // Step 4: Student selects L1 ("Figure it out") – always honor it

```

FILE: src/lib/tutorChunker.ts

[illegible]

```

87 |
88 | const flushChunk = (): void => {
89 |   if (currentSentences.length === 0) return;
90 |
91 |   const chunkText = currentSentences.join(" ");
92 |   chunks.push({
93 |     text: chunkText,
94 |     tokenCount: estimateTokenCount(chunkText),
95 |     chunkIndex,
96 |   });
97 |   chunkIndex++;
98 |
99 |   // Calculate overlap: take sentences from the end of the current chunk
100 |   // that total approximately overlapTokens
101 |   const overlapSentences: string[] = [];
102 |   let overlapTokenCount = 0;
103 |
104 |   for (let i = currentSentences.length - 1; i >= 0; i--) {
105 |     const sentence = currentSentences[i];
106 |     if (sentence === undefined) continue;
107 |     const sentenceTokens = estimateTokenCount(sentence);
108 |     if (overlapTokenCount + sentenceTokens > opts.overlapTokens) break;
109 |     overlapSentences.unshift(sentence);
110 |     overlapTokenCount += sentenceTokens;
111 |   }
112 |
113 |   currentSentences = overlapSentences;
114 |   currentTokens = overlapTokenCount;
115 | };
116 |
117 | for (const sentence of sentences) {
118 |   const sentenceTokens = estimateTokenCount(sentence);
119 |
120 |   // If a single sentence exceeds maxTokens, force-split it by character count
121 |   if (sentenceTokens > opts.maxTokens) {
122 |     // Flush any accumulated sentences first
123 |     if (currentSentences.length > 0) {
124 |       flushChunk();
125 |     }
126 |
127 |     // Split the long sentence into sub-chunks
128 |     const charsPerChunk = opts.maxTokens * 4; // reverse of token estimation
129 |     for (
130 |       let i = 0;
131 |       i < sentence.length;
132 |       i += charsPerChunk - opts.overlapTokens * 4
133 |     ) {
134 |       const subText = sentence.slice(i, i + charsPerChunk).trim();
135 |       if (subText) {
136 |         chunks.push({
137 |           text: subText,
138 |           tokenCount: estimateTokenCount(subText),
139 |           chunkIndex,
140 |         });
141 |         chunkIndex++;
142 |       }
143 |     }
144 |     currentSentences = [];
145 |     currentTokens = 0;
146 |     continue;
147 |   }
148 |
149 |   // If adding this sentence would exceed maxTokens, flush the current chunk
150 |   if (
151 |     currentTokens + sentenceTokens > opts.maxTokens &&
152 |     currentSentences.length > 0
153 |   ) {
154 |     flushChunk();
155 |   }
156 |
157 |   currentSentences.push(sentence);
158 |   currentTokens += sentenceTokens;
159 | }
160 |
161 | // Flush any remaining sentences
162 | if (currentSentences.length > 0) {
163 |   const chunkTextStr = currentSentences.join(" ");
164 |   chunks.push({
165 |     text: chunkTextStr,
166 |     tokenCount: estimateTokenCount(chunkTextStr),
167 |     chunkIndex,
168 |   });
169 | }
170 |
171 | return chunks;
172 | };
173 |

```

FILE: [src/lib/tutorCitationParser.ts](#)

TYPE: .ts | LINES: 1-24 | SHA256: 987357fb7f2d4a18e04b26d6c8e100b3563b94b578823d7be562f40dca4bc8d6

```

1 | /**
2 |  * Extracts citation marker numbers from response text.
3 |  *
4 |  * Citation markers follow the pattern [1], [2], [3], etc.
5 |  * This is the same regex pattern used in ChatMessage.tsx for rendering.
6 |  *
7 |  * @param text - The assistant response text potentially containing citation markers
8 |  * @returns An array of unique citation numbers (1-indexed), sorted ascending
9 |  */
10 | export const extractCitationMarkers = (text: string): number[] => {
11 |   const matches = text.match(/\[(\d+)\]/g);
12 |   if (!matches) return [];
13 |

```

```
14 |     const numbers = new Set<number>();
15 |     for (const match of matches) {
16 |         const num = parseInt(match.slice(1, -1), 10);
17 |         if (!isNaN(num) && num > 0) {
18 |             numbers.add(num);
19 |         }
20 |     }
21 |
22 |     return Array.from(numbers).sort((a, b) => a - b);
23 | };
24 |
```

[illegible]

FILE: src/lib/tutorPersonaAutoSelect.ts

```
TYPE: .ts | LINES: 1-70 | SHA256: 230944b5b12da521452505ba262e1fc5f8f68d94bb2f2a3279b1a23b1fce50a7
```

```

1 // =====
2 // tutorPersonaAutoSelect – Big Five personality to tutor persona mapping
3 // =====
4
5 import type { TutorPersona } from "@lib/tutorSchemas";
6 import type { BigFiveTraits } from "@lib/scoreCalculator";
7
8 /**
9  * Percentile threshold for considering a trait "high".
10  * Scores are 0-100 (already percentile-based from onboarding scoring).
11  */
12 const HIGH_TRAIT_THRESHOLD = 70;
13
14 export interface PersonaAutoSelectResult {
15   persona: TutorPersona;
16   toneModifier?: string;
17 }
18
19 /**
20  * Auto-select a tutor persona based on the student's Big Five personality profile.
21  *
22  * Mapping rules (from Requirement 26):
23  * - High Openness ("e70th percentile") !' "socratic_guide"
24  * - High Conscientiousness ("e70th percentile") !' "step_by_step_coach"
25  * - Default fallback !' "quick_explainer"
26  * - When multiple traits score high, prioritize the highest percentile
27  * - High Neuroticism ("e70") adds a supportive tone modifier regardless of persona
28  *
29  * @param bigFiveProfile - The student's Big Five trait scores (0-100 scale)
30  * @returns The recommended persona and optional tone modifier, or null if profile is missing
31  */
32 export function autoSelectPersona(
33   bigFiveProfile: BigFiveTraits | null | undefined
34 ): PersonaAutoSelectResult | null {
35   if (!bigFiveProfile) return null;
36
37   // Consider only the traits that map to personas
38   const traits: Array<{ trait: string; score: number }> = [
39     { trait: "openness", score: bigFiveProfile.openness },
40     { trait: "conscientiousness", score: bigFiveProfile.conscientiousness },
41   ];
42
43   // Sort by score descending – highest percentile wins when multiple are high
44   traits.sort((a, b) => b.score - a.score);
45
46   const dominant = traits[0] as { trait: string; score: number };
47   let persona: TutorPersona;
48
49   if (dominant.trait === "openness" && dominant.score >= HIGH_TRAIT_THRESHOLD) {
50     persona = "socratic_guide";
51   } else if (
52     dominant.trait === "conscientiousness" &&
53     dominant.score >= HIGH_TRAIT_THRESHOLD
54   ) {
55     persona = "step_by_step_coach";
56   } else {
57     persona = "quick_explainer";
58   }
59
60   // High neuroticism adds a supportive tone modifier regardless of persona
61   let toneModifier: string | undefined;
62   if (bigFiveProfile.neuroticism >= HIGH_TRAIT_THRESHOLD) {
63     toneModifier =
64       "Use an especially warm, encouraging, and supportive tone. " +
65       "Validate the student's effort frequently. Avoid language that could feel critical or pressuring.";
66   }
67
68   return { persona, toneModifier };
69 }
70

```

FILE: src/lib/tutorPrompt.ts

TYPE: .ts | LINES: 1-172 | SHA256: 4e3f8a64173cd8aefc0314c69af0eb72c83b605f7f5e06af77dfa7c9fc435308

[illegible]

[illegible]

[illegible]

FILE: src/lib/tutorSchemas.ts

TYPE: .ts | LINES: 1-219 | SHA256: 70d3d256ab1a9f1122f224bc91fe1c5fb38d4c164e08ade4676c1de84d20fc1c

[illegible]

[illegible]


```

44 | /** Optional backend message threaded into the `error` fallback. */
45 | message?: string;
46 | }
47 |
48 | /** Default copy for the guaranteed fallback state. */
49 | const DEFAULT_ERROR_MESSAGE = "The AI Tutor is unavailable right now.";
50 |
51 | /**
52 |  * Structured error codes emitted by the `chat-with-tutor` edge function
53 |  * (HTTP body `code` and SSE `error` event `code`). Compared case-insensitively.
54 |  */
55 | const RATE_LIMITED_CODES = new Set([
56 |   "rate_limit_exceeded",
57 |   "token_budget_exceeded",
58 | ]);
59 | const UNAVAILABLE_CODES = new Set([
60 |   "embedding_error",
61 |   "llm_error",
62 |   "llm_unavailable",
63 |   "no_stream",
64 | ]);
65 | const NO_EMBEDDINGS_CODES = new Set(["no_embeddings"]);
66 |
67 | const errorState = (message?: string): TutorUiState => ({
68 |   kind: "error",
69 |   message:
70 |     message && message.trim().length > 0 ? message : DEFAULT_ERROR_MESSAGE,
71 | });
72 |
73 | /**
74 |  * Map a backend signal to a `TutorUiState`. Total over all inputs.
75 |  *
76 |  * Precedence:
77 |  * 1. A network failure is always `unavailable` regardless of any other field.
78 |  * 2. A recognized structured `code` (from the body or an SSE error event) is
79 |  *    authoritative, because SSE errors arrive on an otherwise-200 response.
80 |  * 3. Otherwise the HTTP status decides: 2xx != `ready`, 403 != `not_enrolled`,
81 |  *    429 != `rate_limited`, 500/502/503 != `unavailable`.
82 |  * 4. Anything unrecognized (other statuses, unknown codes, empty signal,
83 |  *    detection failure) falls back to the guaranteed `error` state.
84 |  */
85 | export function mapTutorError(signal: TutorSignal): TutorUiState {
86 |   // 1. Network failure dominates – the backend was never reached.
87 |   if (signal.networkError === true) {
88 |     return { kind: "unavailable" };
89 |   }
90 |
91 |   // 2. A recognized structured code is authoritative (covers SSE error events
92 |   //    that stream over a 200 response).
93 |   const code = signal.code?.toLowerCase();
94 |   if (code) {
95 |     if (RATE_LIMITED_CODES.has(code)) {
96 |       return { kind: "rate_limited", resetHint: signal.resetHint };
97 |     }
98 |     if (UNAVAILABLE_CODES.has(code)) {
99 |       return { kind: "unavailable" };
100 |     }
101 |     if (NO_EMBEDDINGS_CODES.has(code)) {
102 |       return { kind: "no_embeddings" };
103 |     }
104 |     // Unknown code: fall through to the HTTP status check below.
105 |   }
106 |
107 |   // 3. Map by HTTP status.
108 |   const status = signal.httpStatus;
109 |   if (typeof status === "number") {
110 |     if (status >= 200 && status < 300) {
111 |       return { kind: "ready" };
112 |     }
113 |     if (status === 403) {
114 |       return { kind: "not_enrolled" };
115 |     }
116 |     if (status === 429) {
117 |       return { kind: "rate_limited", resetHint: signal.resetHint };
118 |     }
119 |     if (status === 500 || status === 502 || status === 503) {
120 |       return { kind: "unavailable" };
121 |     }
122 |   }
123 |
124 |   // 4. Guaranteed fallback (R4.2a).
125 |   return errorState(signal.message);
126 | }
127 |

```

FILE: src/lib/useEquippedTheme.ts

TYPE: .ts | LINES: 1-66 | SHA256: dedb5f3caea9d050ea48f54e062a3f1f9735f7a0f990b530d122b5ecb013575a

```

1 | // =====
2 | // useEquippedTheme – Apply equipped theme CSS vars to student dashboard
3 | // =====
4 |
5 | import { useEffect, useMemo } from "react";
6 | import { useAuth } from "@hooks/useAuth";
7 | import { useEquippedItems } from "@hooks/useEquippedItems";
8 | import { resolveThemeCSS } from "@lib/themeResolver";
9 | import type { ThemeMetadata } from "@lib/themeResolver";
10 |
11 | /**
12 |  * Hook that applies the student's equipped profile theme as CSS custom
13 |  * properties on the document root. When the student unequips or has no
14 |  * theme, the variables are removed so the default design-system tokens
15 |  * take effect.
16 |  */

```

```

17 | * Usage: call `useEquippedTheme()` once in StudentLayout or StudentDashboard.
18 | */
19 | export const useEquippedTheme = () => {
20 |   const { user } = useAuth();
21 |   const { data: equippedItems } = useEquippedItems(user?.id ?? "");
22 |
23 |   const themeItem = useMemo(
24 |     () => equippedItems?.find((item) => item.slot === "profile_theme"),
25 |     [equippedItems]
26 |   );
27 |
28 |   useEffect(() => {
29 |     const root = document.documentElement;
30 |
31 |     if (!themeItem) {
32 |       // Remove theme CSS vars when no theme is equipped
33 |       root.style.removeProperty("--theme-accent");
34 |       root.style.removeProperty("--theme-accent-dark");
35 |       root.style.removeProperty("--theme-accent-bg");
36 |       root.style.removeProperty("--theme-gradient-start");
37 |       root.style.removeProperty("--theme-gradient-end");
38 |       return;
39 |     }
40 |
41 |     const metadata = themeItem.metadata as Partial<ThemeMetadata>;
42 |     const themeData: ThemeMetadata = {
43 |       accent_primary: metadata.accent_primary ?? "#3b82f6",
44 |       accent_secondary: metadata.accent_secondary ?? "#2563eb",
45 |       accent_bg: metadata.accent_bg ?? "#eff6ff",
46 |       gradient_start: metadata.gradient_start ?? "#14b8a6",
47 |       gradient_end: metadata.gradient_end ?? "#3b82f6",
48 |     };
49 |
50 |     const cssVars = resolveThemeCSS(themeData);
51 |
52 |     for (const [key, value] of Object.entries(cssVars)) {
53 |       root.style.setProperty(key, value);
54 |     }
55 |
56 |     // Cleanup on unmount or theme change
57 |     return () => {
58 |       for (const key of Object.keys(cssVars)) {
59 |         root.style.removeProperty(key);
60 |       }
61 |     };
62 |   }, [themeItem]);
63 |
64 |   return { hasTheme: !!themeItem };
65 | };
66 |

```

FILE: src/lib/utils.ts

TYPE: .ts | LINES: 1-7 | SHA256: d1f1e0d62cb8d8d1e04c26e14de842d8a151f75812d81b046c65b5d1fe8e4b27

```

1 | import { clsx, type ClassValue } from "clsx";
2 | import { twMerge } from "tailwind-merge";
3 |
4 | export function cn(...inputs: ClassValue[]) {
5 |   return twMerge(clsx(inputs));
6 | }
7 |

```

FILE: src/lib/viewTransition.ts

TYPE: .ts | LINES: 1-55 | SHA256: 67088e5d3c74f0c3cde8c4ff30894fb4d6da7aa85f3d115e6eee575348c74abb

```

1 | /**
2 |  * View Transitions wrapper (spec: dashboard-and-ux-performance, Req 11).
3 |  *
4 |  * Wraps an imperative state/section swap in `document.startViewTransition` when
5 |  * the browser supports it AND the user has not requested reduced motion. In any
6 |  * other case it runs the update synchronously, so the swap is always correct and
7 |  * the View Transition is pure progressive enhancement (Req 11.2 fallback).
8 |  *
9 |  * For route-level navigation the React Router `viewTransition` prop is used
10 |  * instead (declarative); this helper is for component-driven swaps (tabs, view
11 |  * toggles). Reduced motion is gated here in JS AND via the `::view-transition-*`
12 |  * `prefers-reduced-motion` rule in `index.css`, so both code paths are covered.
13 |  */
14 |
15 | type StartViewTransition = (callback: () => void) => {
16 |   finished?: Promise<void>;
17 | };
18 |
19 | /** True when the user asked the OS/browser to minimise motion. */
20 | export const prefersReducedMotion = (): boolean =>
21 |   typeof window !== "undefined" &&
22 |   typeof window.matchMedia === "function" &&
23 |   window.matchMedia("(prefers-reduced-motion: reduce)").matches;
24 |
25 | /**
26 |  * Runs `update` inside a View Transition when supported and motion is allowed;
27 |  * otherwise runs it synchronously. Never throws on account of the transition.
28 |  */
29 | export const withViewTransition = (update: () => void): void => {
30 |   const doc =
31 |     typeof document !== "undefined"
32 |     ? (document as Document & {
33 |       startViewTransition?: StartViewTransition;
34 |     })
35 |     : undefined;
36 |
37 |   if (
38 |     !doc ||
39 |     typeof doc.startViewTransition !== "function" ||

```

```

40 |     prefersReducedMotion()
41 |   ) {
42 |     update();
43 |     return;
44 |   }
45 |
46 |   try {
47 |     doc.startViewTransition(() => {
48 |       update();
49 |     });
50 |   } catch {
51 |     // If the transition API throws for any reason, the swap must still happen.
52 |     update();
53 |   }
54 | };
55 |

```

FILE: [src/lib/weeklyPlannerContent.ts](#)

TYPE: .ts | LINES: 1-211 | SHA256: e8a95e2ab39e32ab673d768f813ada36de40f716f18f36b498ba3f181a1fcdeb

```

1 | // =====
2 | // Weekly Planner – Derived & Suggested Content (pure, testable)
3 | // =====
4 | //
5 | // Builds the seven-day `WeekDay[]` model for the weekly planner, attaching
6 | // derived assignments/deadlines per day and – for days that have no real
7 | // student-created work – a suggested study session so an empty week still
8 | // helps a student plan instead of showing seven blank "No items" columns.
9 | //
10 | // Kept free of React and Supabase so it can be unit-tested directly and reused
11 | // by `WeeklyPlannerPage`. The seven-day model and example-goal builders are
12 | // pure data transforms; the surface-level localization gate delegates to the
13 | // shared `resolveLocalizationGate` policy helper in `@/lib/localization` so the
14 | // planner and timetable share one source of truth for i18n gating. All
15 | // user-facing labels are produced by the consumer; this module only emits
16 | // structured data.
17 | //
18 | // Satisfies Requirements 19.1, 19.2, 19.4, 19.6, 19.7.
19 | // =====
20 |
21 | import type {
22 |   GoalType,
23 |   PlannerTask,
24 |   StudySession,
25 |   SuggestedStudySession,
26 |   UpcomingDeadline,
27 |   WeekDay,
28 | } from "@types/planner";
29 | import {
30 |   resolveLocalizationGate,
31 |   type LocalizationGateState,
32 | } from "@lib/localization";
33 |
34 | /** Default focus-block length, in minutes, used for suggested sessions. */
35 | export const SUGGESTED_SESSION_MINUTES = 25;
36 |
37 | /** Minimal course shape needed to scope a suggested study session. */
38 | export interface SuggestionCourse {
39 |   id: string;
40 |   name: string;
41 | }
42 |
43 | export interface BuildPlannerWeekInput {
44 |   /** Monday of the week being rendered (YYYY-MM-DD). */
45 |   weekStartDate: string;
46 |   /** Today's date (YYYY-MM-DD) – suggestions are only offered today or later. */
47 |   todayStr: string;
48 |   sessions: StudySession[];
49 |   tasks: PlannerTask[];
50 |   deadlines: UpcomingDeadline[];
51 |   /** Enrolled courses used to scope suggestions; may be empty. */
52 |   courses: SuggestionCourse[];
53 |   /** Dates (YYYY-MM-DD) that already carry a scheduled review, if any. */
54 |   reviewDates?: readonly string[];
55 | }
56 |
57 | /**
58 |  * Add `days` whole days to a `YYYY-MM-DD` string using UTC arithmetic, so the
59 |  * result is stable regardless of the host timezone.
60 |  */
61 | function addDaysToISO(dateStr: string, days: number): string {
62 |   const [year, month, day] = dateStr.split("-").map(Number) as [
63 |     number,
64 |     number,
65 |     number
66 |   ];
67 |   const d = new Date(Date.UTC(year, month - 1, day + days));
68 |   return d.toISOString().split("T")[0] as string;
69 | }
70 |
71 | /** True when an ISO `dueDate` (date or datetime) falls on the given day. */
72 | function deadlineFallsOn(dueDate: string, date: string): boolean {
73 |   return typeof dueDate === "string" && dueDate.startsWith(date);
74 | }
75 |
76 | /**
77 |  * Produce a single suggested study session for an empty day, rotating through
78 |  * the student's courses so suggestions feel varied across the week. When the
79 |  * student has no courses, a generic (course-less) suggestion is returned.
80 |  */
81 | function buildSuggestion(
82 |   date: string,
83 |   courses: SuggestionCourse[],
84 |   index: number

```

```

85 | ): SuggestedStudySession {
86 |   const course =
87 |     courses.length > 0 ? courses[index % courses.length] ?? null : null;
88 |   return {
89 |     id: `suggestion-${date}`,
90 |     date,
91 |     courseId: course?.id ?? null,
92 |     courseName: course?.name ?? null,
93 |     durationMinutes: SUGGESTED_SESSION_MINUTES,
94 |   };
95 | }
96 |
97 | /**
98 |  * Build the seven-day planner model for a week.
99 |  *
100 |  * - Each day surfaces the sessions, tasks, and deadlines that fall on it
101 |  *   (deadlines are drawn from the student's enrolled courses – R19.1).
102 |  * - A day with no real items (no sessions, tasks, deadlines, or reviews) that
103 |  *   is today or in the future is given one suggested study session instead of
104 |  *   a bare empty state (R19.2). Past empty days carry no suggestion, since a
105 |  *   study session cannot be planned in the past.
106 |  */
107 | export function buildPlannerWeek(input: BuildPlannerWeekInput): WeekDay[] {
108 |   const {
109 |     weekStartDate,
110 |     todayStr,
111 |     sessions,
112 |     tasks,
113 |     deadlines,
114 |     courses,
115 |     reviewDates = [],
116 |   } = input;
117 |
118 |   const reviewDateSet = new Set(reviewDates);
119 |   const days: WeekDay[] = [];
120 |   let suggestionIndex = 0;
121 |
122 |   for (let i = 0; i < 7; i++) {
123 |     const date = addDaysToISO(weekStartDate, i);
124 |     const daySessions = sessions.filter((s) => s.plannedDate === date);
125 |     const dayTasks = tasks.filter((t) => t.dueDate === date);
126 |     const dayDeadlines = deadlines.filter((d) =>
127 |       deadlineFallsOn(d.dueDate, date)
128 |     );
129 |     const hasReview = reviewDateSet.has(date);
130 |
131 |     const hasRealItems =
132 |       daySessions.length > 0 ||
133 |       dayTasks.length > 0 ||
134 |       dayDeadlines.length > 0 ||
135 |       hasReview;
136 |
137 |     const day: WeekDay = {
138 |       date,
139 |       sessions: daySessions,
140 |       tasks: dayTasks,
141 |       deadlines: dayDeadlines,
142 |       isToday: date === todayStr,
143 |     };
144 |
145 |     if (!hasRealItems && date >= todayStr) {
146 |       day.suggestions = [buildSuggestion(date, courses, suggestionIndex)];
147 |       suggestionIndex += 1;
148 |     }
149 |
150 |     days.push(day);
151 |   }
152 |
153 |   return days;
154 | }
155 |
156 | // -----
157 | // Example goals (shown when a student has set no weekly goals – R19.4)
158 | // -----
159 |
160 | export interface ExampleGoal {
161 |   goalType: GoalType;
162 |   targetValue: number;
163 | }
164 |
165 | /**
166 |  * Example weekly goals used to guide goal-setting when the student has none.
167 |  * Returned as structured data; the consumer renders localized labels.
168 |  */
169 | export function getExampleGoals(): ExampleGoal[] {
170 |   return [
171 |     { goalType: "study_hours", targetValue: 5 },
172 |     { goalType: "sessions_completed", targetValue: 3 },
173 |     { goalType: "tasks_completed", targetValue: 5 },
174 |   ];
175 | }
176 |
177 | // -----
178 | // Bilingual-availability gate (R19.5, R19.6, R19.7)
179 | // -----
180 |
181 | /**
182 |  * Planner localization readiness:
183 |  * - `ready` – both English and Arabic packs are available.
184 |  * - `actions-withheld` – exactly one of the two packs is available; derived
185 |  *   content and planner actions are withheld until both
186 |  *   load (R19.6).
187 |  * - `hidden` – neither pack is available; planner content is hidden
188 |  *   entirely (R19.7).

```



```

8 |
9 | export interface XPPurchase {
10 |   xp_cost: number;
11 |   status: "active" | "consumed" | "expired" | "refunded";
12 | }
13 |
14 | /**
15 |  * Compute the spendable XP balance for a student.
16 |  *
17 |  * Balance = GREATEST(0, SUM(xp_amounts) - SUM(xp_costs where status != 'refunded'))
18 |  *
19 |  * Refunded purchases are excluded from the spent total because the XP
20 |  * was returned to the student.
21 |  */
22 | export function computeXPBalance(
23 |   transactions: readonly XPTransaction[],
24 |   purchases: readonly XPPurchase[]
25 | ): number {
26 |   const totalEarned = transactions.reduce((sum, tx) => sum + tx.xp_amount, 0);
27 |
28 |   const totalSpent = purchases.reduce(
29 |     (sum, p) => (p.status !== "refunded" ? sum + p.xp_cost : sum),
30 |     0
31 |   );
32 |
33 |   return Math.max(0, totalEarned - totalSpent);
34 | }
35 |

```

FILE: [src/lib/xpClient.ts](#)

TYPE: .ts | LINES: 1-66 | SHA256: 8b2e86a3c4325be3a92e88891ff70bd8de73b90a2c7611055b656702e3702af8

```

1 | // =====
2 | // XP Client - Fire-and-forget XP award via the award-xp Edge Function
3 | // =====
4 |
5 | import { supabase } from "@lib/supabase";
6 | import { emitXPFeedback } from "@lib/xpFeedback";
7 | import type { XPSource } from "@types/app";
8 |
9 | export interface AwardXPParams {
10 |   studentId: string;
11 |   xpAmount: number;
12 |   source: XPSource;
13 |   referenceId?: string;
14 |   note?: string;
15 | }
16 |
17 | export interface AwardXPResult {
18 |   success: boolean;
19 |   xp_awarded: number;
20 |   new_total: number;
21 |   level_up: boolean;
22 |   new_level: number;
23 |   mystery_reward_triggered?: boolean;
24 | }
25 |
26 | /**
27 |  * Fire-and-forget XP award via the award-xp Edge Function.
28 |  * Never blocks user-facing flows - errors are logged silently.
29 |  */
30 | export async function awardXP(
31 |   params: AwardXPParams
32 | ): Promise<AwardXPResult | null> {
33 |   try {
34 |     const { data, error } = await supabase.functions.invoke("award-xp", {
35 |       body: {
36 |         student_id: params.studentId,
37 |         xp_amount: params.xpAmount,
38 |         source: params.source,
39 |         reference_id: params.referenceId,
40 |         note: params.note,
41 |       },
42 |     });
43 |
44 |     if (error) {
45 |       console.error("[XP Client] Award failed:", error.message);
46 |       return null;
47 |     }
48 |
49 |     const result = data as AwardXPResult;
50 |     if (result.success) {
51 |       emitXPFeedback({
52 |         studentId: params.studentId,
53 |         amount: result.xp_awarded,
54 |         source: params.source,
55 |         levelUp: result.level_up,
56 |         newLevel: result.new_level,
57 |         mysteryRewardTriggered: result.mystery_reward_triggered ?? false,
58 |       });
59 |     }
60 |     return result;
61 |   } catch (err) {
62 |     console.error("[XP Client] Unexpected error:", err);
63 |     return null;
64 |   }
65 | }
66 |

```

FILE: src/lib/xpFeedback.ts

TYPE: .ts | LINES: 1-51 | SHA256: bbc97678a5c9e1397de541ba6608d853045b34fcb901a653388abdea22d6288e

```
1 | import type { XPSource } from "@types/app";
2 |
3 | export const XP_FEEDBACK_EVENT = "edeviser:xp-feedback";
4 |
5 | export interface XPFeedbackDetail {
6 |   id: string;
7 |   studentId: string;
8 |   amount: number;
9 |   source: XPSource;
10 |   levelUp: boolean;
11 |   newLevel: number;
12 |   mysteryRewardTriggered: boolean;
13 | }
14 |
15 | interface EmitXPFeedbackInput {
16 |   studentId: string;
17 |   amount: number;
18 |   source: XPSource;
19 |   levelUp: boolean;
20 |   newLevel: number;
21 |   mysteryRewardTriggered?: boolean;
22 | }
23 |
24 | /**
25 |  * Publishes visual feedback only after the backend confirms an XP award.
26 |  * Duplicate/idempotent responses return zero XP and intentionally stay quiet.
27 |  */
28 | export const emitXPFeedback = ({
29 |   studentId,
30 |   amount,
31 |   source,
32 |   levelUp,
33 |   newLevel,
34 |   mysteryRewardTriggered = false,
35 | }: EmitXPFeedbackInput): void => {
36 |   if (typeof window === "undefined" || amount <= 0) return;
37 |
38 |   const detail: XPFeedbackDetail = {
39 |     id: `${Date.now()}-${crypto.randomUUID()}`,
40 |     studentId,
41 |     amount,
42 |     source,
43 |     levelUp,
44 |     newLevel,
45 |     mysteryRewardTriggered,
46 |   };
47 |   window.dispatchEvent(
48 |     new CustomEvent<XPFeedbackDetail>(XP_FEEDBACK_EVENT, { detail })
49 |   );
50 | };
51 |
```

FILE: src/lib/xpLevelCalculator.ts

TYPE: .ts | LINES: 1-76 | SHA256: 07fe2b2a6aaf58ff8b9cbf8f664487d511b6e906dc2f5fe66aa45c6ffe54b272

```
1 | // =====
2 | // XP Level Calculator – Pure functions for level threshold generation and lookup
3 | // =====
4 |
5 | import type { LevelThreshold } from "@types/app";
6 |
7 | const MAX_LEVEL = 50;
8 |
9 | /**
10 |  * Generate level thresholds up to MAX_LEVEL.
11 |  * Level 1: 0 XP, Level 2: 100 XP, Level 3: 250 XP
12 |  * Level N (N >= 4): floor(50 * N^1.5)
13 |  */
14 | export function generateLevelThresholds(): LevelThreshold[] {
15 |   const thresholds: LevelThreshold[] = [
16 |     { level: 1, xpRequired: 0, title: "Newcomer" },
17 |     { level: 2, xpRequired: 100, title: "Beginner" },
18 |     { level: 3, xpRequired: 250, title: "Learner" },
19 |   ];
20 |
21 |   for (let n = 4; n <= MAX_LEVEL; n++) {
22 |     thresholds.push({
23 |       level: n,
24 |       xpRequired: Math.floor(50 * Math.pow(n, 1.5)),
25 |       title: getLevelTitle(n),
26 |     });
27 |   }
28 |
29 |   return thresholds;
30 | }
31 |
32 | function getLevelTitle(level: number): string {
33 |   if (level <= 5) return "Apprentice";
34 |   if (level <= 10) return "Scholar";
35 |   if (level <= 15) return "Adept";
36 |   if (level <= 20) return "Expert";
37 |   if (level <= 30) return "Master";
38 |   if (level <= 40) return "Grandmaster";
39 |   return "Legend";
40 | }
41 |
42 | /** Cached thresholds for repeated lookups */
43 | const LEVEL_THRESHOLDS = generateLevelThresholds();
44 |
45 | /**
```

```

46 | * Calculate the level for a given XP total.
47 | * Returns the highest level whose xpRequired <= xpTotal.
48 | */
49 | export function calculateLevel(xpTotal: number): number {
50 |   if (xpTotal < 0) return 1;
51 |
52 |   let level = 1;
53 |   for (const threshold of LEVEL_THRESHOLDS) {
54 |     if (xpTotal >= threshold.xpRequired) {
55 |       level = threshold.level;
56 |     } else {
57 |       break;
58 |     }
59 |   }
60 |   return level;
61 | }
62 |
63 | /**
64 | * Apply bonus multiplier to base XP amount.
65 | * Multiplier must be >= 1. Returns the multiplied amount (floored to integer).
66 | */
67 | export function applyBonusMultiplier(
68 |   baseXP: number,
69 |   multiplier: number
70 | ): number {
71 |   if (multiplier < 1) return baseXP;
72 |   return Math.floor(baseXP * multiplier);
73 | }
74 |
75 | export { LEVEL_THRESHOLDS };
76 |

```

FILE: src/lib/xpSchedule.ts

TYPE: .ts | LINES: 1-52 | SHA256: 48676a576fe13c7c19fde4a4e8724fb26af2e280ad84077138b7639dbe40ad99

```

1 | // =====
2 | // XP Schedule Constants – Base XP amounts per source
3 | // =====
4 |
5 | import type { XPSource } from "@types/app";
6 |
7 | /**
8 | * Base XP amounts awarded per trigger source.
9 | * The Edge Function applies bonus multipliers server-side.
10 | * Sources with 0 XP have variable amounts set at call time.
11 | */
12 | export const XP_SCHEDULE: Record<XPSource, number> = {
13 |   login: 10,
14 |   submission: 25,
15 |   grade: 15,
16 |   journal: 20,
17 |   streak_milestone: 50,
18 |   perfect_day: 50,
19 |   first_attempt_bonus: 10,
20 |   perfect_rubric: 75,
21 |   badge_earned: 0,
22 |   level_up: 0,
23 |   streak_freeze_purchase: 0,
24 |   discussion_question: 10,
25 |   discussion_answer: 15,
26 |   survey_completion: 15,
27 |   quiz_completion: 50,
28 |   onboarding_personality: 25,
29 |   onboarding_learning_style: 25,
30 |   onboarding_baseline: 20,
31 |   onboarding_complete: 50,
32 |   onboarding_self_efficacy: 25,
33 |   onboarding_study_strategy: 25,
34 |   micro_assessment: 10,
35 |   profile_complete: 30,
36 |   starter_session_complete: 15,
37 |   wellness_habit: 0, // Variable: looked up from institution_settings.wellness_xp_amount
38 |   practice_quiz: 10,
39 |   study_session: 0, // Variable: calculated client-side via calculateSessionXP
40 |   planner_task: 10,
41 |   session_reflection: 10,
42 |   weekly_goal: 25,
43 |   tutor_engagement: 15,
44 |   tutor_rating: 5,
45 | };
46 |
47 | /** XP awarded for late submissions (assignment or quiz) */
48 | export const LATE_SUBMISSION_XP = 15;
49 |
50 | /** XP awarded for late quiz completion */
51 | export const LATE_QUIZ_XP = 15;
52 |

```

FILE: src/locales/_translation-memory.json

TYPE: .json | LINES: 1-281 | SHA256: c73380cc58381b849e91f65ba0aa21eabb4f473c1b070ca67c8f61839716274a

```

1 | {
2 |   "en": {
3 |     "common": {
4 |       "nav.dashboard": "Dashboard",
5 |       "nav.users": "Users",
6 |       "nav.programs": "Programs",
7 |       "nav.courses": "Courses",
8 |       "nav.outcomes": "Outcomes",
9 |       "nav.assignments": "Assignments",
10 |      "nav.grading": "Grading",
11 |      "nav.reports": "Reports",
12 |      "nav.settings": "Settings",
13 |      "nav.profile": "Profile",

```

```

14 | "nav.notifications": "Notifications",
15 | "nav.leaderboard": "Leaderboard",
16 | "nav.journal": "Journal",
17 | "nav.progress": "Progress",
18 | "nav.calendar": "Calendar",
19 | "nav.timetable": "Timetable",
20 | "nav.discussions": "Discussions",
21 | "nav.attendance": "Attendance",
22 | "nav.quizzes": "Quizzes",
23 | "nav.gradebook": "Gradebook",
24 | "nav.auditLog": "Audit Log",
25 | "buttons.save": "Save",
26 | "buttons.cancel": "Cancel",
27 | "buttons.delete": "Delete",
28 | "buttons.edit": "Edit",
29 | "buttons.create": "Create",
30 | "buttons.submit": "Submit",
31 | "buttons.confirm": "Confirm",
32 | "buttons.back": "Back",
33 | "buttons.next": "Next",
34 | "buttons.close": "Close",
35 | "buttons.retry": "Try Again",
36 | "buttons.export": "Export",
37 | "buttons.import": "Import",
38 | "buttons.search": "Search",
39 | "buttons.filter": "Filter",
40 | "buttons.reset": "Reset",
41 | "buttons.download": "Download",
42 | "buttons.upload": "Upload",
43 | "status.active": "Active",
44 | "status.inactive": "Inactive",
45 | "status.pending": "Pending",
46 | "status.completed": "Completed",
47 | "status.dropped": "Dropped",
48 | "status.loading": "Loading...",
49 | "status.saving": "Saving...",
50 | "status.error": "Error",
51 | "status.success": "Success",
52 | "form.required": "This field is required",
53 | "form.email": "Email",
54 | "form.password": "Password",
55 | "form.name": "Name",
56 | "form.description": "Description",
57 | "form.title": "Title",
58 | "form.code": "Code",
59 | "form.selectOption": "Select an option",
60 | "form.noResults": "No results found",
61 | "errors.generic": "Something went wrong. Please try again.",
62 | "errors.notFound": "The requested resource was not found.",
63 | "errors.unauthorized": "You are not authorized to perform this action.",
64 | "errors.forbidden": "Access denied.",
65 | "errors.networkError": "Network error. Please check your connection.",
66 | "errors.timeout": "The request timed out. Please try again.",
67 | "errors.validation": "Please check the form for errors.",
68 | "pagination.previous": "Previous",
69 | "pagination.next": "Next",
70 | "pagination.showing": "Showing {{from}} to {{to}} of {{total}}",
71 | "pagination.rowsPerPage": "Rows per page",
72 | "confirmation.deleteTitle": "Are you sure?",
73 | "confirmation.deleteMessage": "This action cannot be undone.",
74 | "confirmation.unsavedChanges": "You have unsaved changes. Are you sure you want to leave?",
75 | "errorBoundary.title": "Something went wrong",
76 | "errorBoundary.defaultMessage": "An unexpected error occurred.",
77 | "errorBoundary.retry": "Try Again",
78 | "blooms.remembering": "Remembering",
79 | "blooms.understanding": "Understanding",
80 | "blooms.applying": "Applying",
81 | "blooms.analyzing": "Analyzing",
82 | "blooms.evaluating": "Evaluating",
83 | "blooms.creating": "Creating",
84 | "attainment.excellent": "Excellent",
85 | "attainment.satisfactory": "Satisfactory",
86 | "attainment.developing": "Developing",
87 | "attainment.notYet": "Not Yet",
88 | "parentDashboard.greeting.morning": "Good morning",
89 | "parentDashboard.greeting.afternoon": "Good afternoon",
90 | "parentDashboard.greeting.evening": "Good evening",
91 | "parentDashboard.subtitle": "Stay connected with your child's learning journey.",
92 | "parentDashboard.children": "Children",
93 | "parentDashboard.totalCourses": "Total Courses",
94 | "parentDashboard.avgAttainment": "Avg Attainment",
95 | "parentDashboard.deadlines": "Deadlines",
96 | "parentDashboard.yourChildren": "Your Children",
97 | "parentDashboard.levelLabel": "Level",
98 | "parentDashboard.coursesLabel": "courses",
99 | "parentDashboard.noChildren": "No linked children yet. Ask your institution's admin to set up the parent
100 | "parentDashboard.xp": "XP",
101 | "accessibility.title": "Accessibility Settings",
102 | "accessibility.fontSize": "Font Size",
103 | "accessibility.fontDefault": "Default",
104 | "accessibility.fontLarge": "Large",
105 | "accessibility.fontXLarge": "Extra Large",
106 | "accessibility.highContrast": "High Contrast",
107 | "accessibility.reducedAnimations": "Reduced Animations",
108 | "accessibility.dyslexiaFont": "Dyslexia-Friendly Font",
109 | "accessibility.simplifiedView": "Simplified View",
110 | "accessibility.cognitiveLoadMessage": "This page has a lot of information – would you like a simplified
111 | "user": "User",
112 | "search": "Search",
113 | "searchPlaceholder": "Search courses, assignments, announcements...",
114 | "searchLoading": "Searching...",
115 | "searchEmpty": "No results for \"{{q}}\"",
116 | "searchType.course": "Course",
117 | "searchType.assignment": "Assignment",

```

```

118 |         "searchType.announcement": "Announcement",
119 |         "notifications": "Notifications",
120 |         "settings": "Settings",
121 |         "profileMenu": "Profile menu",
122 |         "myProfile": "My Profile",
123 |         "profileSettings": "Profile Settings",
124 |         "institutionSettings": "Institution Settings",
125 |         "header.user": "User",
126 |         "header.search": "Search",
127 |         "header.searchPlaceholder": "Search courses, assignments, announcements...",
128 |         "header.searchLoading": "Searching...",
129 |         "header.searchEmpty": "No results for \"{q}\"",
130 |         "header.searchType.course": "Course",
131 |         "header.searchType.assignment": "Assignment",
132 |         "header.searchType.announcement": "Announcement",
133 |         "header.notifications": "Notifications",
134 |         "header.settings": "Settings",
135 |         "header.profileMenu": "Profile menu",
136 |         "header.myProfile": "My Profile",
137 |         "header.profileSettings": "Profile Settings",
138 |         "header.institutionSettings": "Institution Settings"
139 |     }
140 | },
141 | "ar": {
142 |     "common": {
143 |         "nav.dashboard": "dFHb0) bVDb!-d6E",
144 |         "nav.users": "bVdV3b! .b0EdtF",
145 |         "nav.programs": "bVDb!1bvEbA",
146 |         "nav.courses": "bVdDVbc 1bv*",
147 |         "nav.outcomes": "bVdDV.c ,bv*",
148 |         "nav.assignments": "bVDb!CdFjd 'b¢"A
149 |         "nav.grading": "bVDb!Bd!JdR"A
150 |         "nav.reports": "bVDb!Bbv1d!1",
151 |         "nav.settings": "bVDbV9b0'b0'b¢"A
152 |         "nav.profile": "bVdDVdD 'dF4bæ5d¢"A
153 |         "nav.notifications": "bVDbV4c-'c 'b¢"A
154 |         "nav.leaderboard": "dFHb0) bVdDV*cV/c Jdb"A
155 |         "nav.journal": "bVdD!HdvJb"A
156 |         "nav.progress": "bVDb!Bb0E",
157 |         "nav.calendar": "bVDb!Bd!JdR"A
158 |         "nav.timetable": "bVDbæ/dtD bVDb01bv3d¢"A
159 |         "nav.discussions": "bVdVFBvBcF'b¢"A
160 |         "nav.attendance": "bVDb006dt1",
161 |         "nav.quizzes": "bVDbv.b!(bv1bv*",
162 |         "nav.gradebook": "c6,dB 'dF/c ,bv*",
163 |         "nav.auditLog": "c6,dB 'dFEc 'bæ9b"A
164 |         "buttons.save": "b0Ac,"A
165 |         "buttons.cancel": "bVDC!'b "A
166 |         "buttons.delete": "b00d "A
167 |         "buttons.edit": "b!9b0JdB"A
168 |         "buttons.create": "bVFcF'b "A
169 |         "buttons.submit": "bV1c6'dB"A
170 |         "buttons.confirm": "b!#d6Jb0"A
171 |         "buttons.back": "c ,dt9",
172 |         "buttons.next": "bVDb!dFJ",
173 |         "buttons.close": "bV:dF'd""A
174 |         "buttons.retry": "bV9bv/b' 'dFEb0'dtDb'"A
175 |         "buttons.export": "b!5b0Jc "A
176 |         "buttons.import": "bV3b!Jc 'b0"A
177 |         "buttons.search": "b!-b²"A
178 |         "buttons.filter": "b!5d Jb'"A
179 |         "buttons.reset": "bV9bv/b' *c-Jd!F",
180 |         "buttons.download": "b!-dVJdB"A
181 |         "buttons.upload": "c Ac'"A
182 |         "status.active": "df4cr"A
183 |         "status.inactive": "c!Jc FcF7",
184 |         "status.pending": "d&Jb0 'dF'df*c†'c "A
185 |         "status.completed": "dVCb!EdB"A
186 |         "status.dropped": "dVFc6-b,"A
187 |         "status.loading": "bæ'c J bVDb!-dVJdBâââ"A
188 |         "status.saving": "bæ'c J bVDb0Ac,âââ"A
189 |         "status.error": "bæ7b2"A
190 |         "status.success": "df,bv-",
191 |         "form.required": "dv0br 'dF-d&D dV7dFhb,"A
192 |         "form.email": "bVDbt1d!;/ bVDbVDd6*c HdFJ",
193 |         "form.password": "d6DdV) bVdV1dt1",
194 |         "form.name": "bVDbv3dR"A
195 |         "form.description": "bVdDt5d "A
196 |         "form.title": "bVdc-Fdt!db"A
197 |         "form.code": "bVdc_Ec""A
198 |         "form.selectOption": "bv.b!1 bæJbv1bvK",
199 |         "form.noResults": "dFE d!*dR 'dF9b!Hc 9dFI df*bv&bA"A
200 |         "errors.generic": "b0/b² .cv# dv'. d!1bæI bVdDV-bvHdF) dV1b' #bæ1d'â"A
201 |         "errors.notFound": "dFE d!*dR 'dF9b!Hc 9dFI bVdDVHc / bVdDV7dFhb,â"A
202 |         "errors.unauthorized": "c!Jc EcV1b0 Dd2 (b!Fd Jc Gc ' bVDbV,c 'b â"A
203 |         "errors.forbidden": "b!E c Acb 'dFHcVHdBâ"A
204 |         "errors.networkError": "bæ7b2 Ad¢ 'dF4b†Cb'â Jc ,d' 'dF*b0Bd" Edb 'b!5bvDd2â"A
205 |         "errors.timeout": "bVfb!Gb¢ EdvDb' 'dF7dF(. d!1bæI bVdDV-bvHdF) dV1b' #bæ1d'â"A
206 |         "errors.validation": "d!1bæI bVDb!-d&B dVF bVdVdEd†0bA (b0+bvK c-F b6.cv'b â"A
207 |         "pagination.previous": "bVdC6!b†B",
208 |         "pagination.next": "bVDb!dFJ",
209 |         "pagination.showing": "c-1cb .!g&0×0 %dFI {{to}} dVF {{total}}",
210 |         "pagination.rowsPerPage": "cVAd†A dFCdB 5d -b'"A
211 |         "confirmation.deleteTitle": "dVd b6Fb¢ Eb!#d6/a0"A
212 |         "confirmation.deleteMessage": "dF' d!Ed6F bVDb!1bv,c' 9db Gc ' bVDbv,c 'b â"A
213 |         "confirmation.unsavedChanges": "dF/d!C b! :d!Jc 'b¢ :d!1 dv-d Hc†). dVd b6Fb¢ Eb!#d6/ b6Fd2 *c Jb0 'dFEc!b01b- ",
214 |         "errorBoundary.title": "b0/b² .cv# dv'",
215 |         "errorBoundary.defaultMessage": "b0/b² .cv# c!Jc Eb!Hd&9.",
216 |         "errorBoundary.retry": "bV9bv/b' 'dFEb0'dtDb'"A
217 |         "blooms.remembering": "bVDb!0d61",
218 |         "blooms.understanding": "bVdD GdR"A
219 |         "blooms.applying": "bVDb!7b†Jd"A
220 |         "blooms.analyzing": "bVDb!-dFJdB"A
221 |         "blooms.evaluating": "bVDb!Bd!JdR"A

```

```

222 |         "blooms.creating": "bvDbV(bö'c'"Ä
223 |         "attainment.excellent": "dVEb{'c'"Ä
224 |         "attainment.satisfactory": "dV0c 6d0"Ä
225 |         "attainment.developing": "d&Jbò 'dF*cvHd{1",
226 |         "attainment.notYet": "dFE d{'b0Bd" (c~/
227 |         "parentDashboard.greeting.morning": "cv(bv- bvDbæJc "Ä
228 |         "parentDashboard.greeting.afternoon": "dV3bv! bvDbæJc "Ä
229 |         "parentDashboard.greeting.evening": "dV3bv! bvDbæJc "Ä
230 |         "parentDashboard.subtitle": "bv(d&N c-Dd' *d†'cVD dV9 c -dF) cvAdFC bvDb{9dFJdVJb'â"Ä
231 |         "parentDashboard.children": "bvDb6(df'b "Ä
232 |         "parentDashboard.totalCourses": "bv,dV'dfJ bvDdVBC 1bv*",
233 |         "parentDashboard.avgAttainment": "dV*d†3cr 'dF*b05d;D",
234 |         "parentDashboard.deadlines": "bvDdVHbv9d{/ bvDdf6bv&d{)",
235 |         "parentDashboard.yourChildren": "b6(df'bFC",
236 |         "parentDashboard.levelLabel": "bvDdV3b{Hd'"Ä
237 |         "parentDashboard.coursesLabel": "dVBC 1bv*",
238 |         "parentDashboard.noChildren": "dF' d{HbÆ/ b6(df'b Ec *b†7d†F b†9b0â 'cvDb, Edb Ec6$†d bvDdV$c63b' %c~/bv/ c (cr HdFJ bvDb6Ec (
239 |         "parentDashboard.xp": "df8bv7 bvDbæ(c )",
240 |         "accessibility.title": "bv9b0'b0'bç %dVCbvFd{) bvDd†5d†D",
241 |         "accessibility.fontSize": "b0,dR 'dF.cr"Ä
242 |         "accessibility.fontDefault": "bvAb{1bv6dç"Ä
243 |         "accessibility.fontLarge": "d6(d{1",
244 |         "accessibility.fontXLarge": "d6(d{1 bÆ/bvK",
245 |         "accessibility.highContrast": "b{bvJdb 9bvDd0"Ä
246 |         "accessibility.reducedAnimations": "b{BdFJdB 'dF-c Cb'"Ä
247 |         "accessibility.dyslexiaFont": "bæ7 cv/d{B dF9c61 bvDd&1bv!b'"Ä
248 |         "accessibility.simplifiedView": "c-1cb Eb†3cr"Ä
249 |         "accessibility.cognitiveLoadMessage": "b{-b{Hdç Gc G bvDcVAb0) c-Dd' 'dFCb{Jc Edb 'dFEc-Dd†Ebv* - dvD b{1d{/ c-1cf'd² Eb†3cv'd¶
250 |         "user": "bvDdV3b{.b0E",
251 |         "search": "b†-b²"Ä
252 |         "searchPlaceholder": "bv(b0+ d J bvDdVBC 1bv* d†'dF*d6Dd{Abv* d†'dF%c-DbvFbv*...",
253 |         "searchLoading": "bÆ'c J bvDb†-b,R"Ä
254 |         "searchEmpty": "dF' b{HbÆ/ df*bv&bÄ Dd Ä'.. x0Ä""Ä
255 |         "searchType.course": "dVBC 1",
256 |         "searchType.assignment": "b{CdFJd "Ä
257 |         "searchType.announcement": "bv9dF'db"Ä
258 |         "notifications": "bvDbV4c-'c 'bç"Ä
259 |         "settings": "bvDbV9b0'b0'bç"Ä
260 |         "profileMenu": "d&'bfEb' 'dFEdFA bvDcF.cVJ",
261 |         "myProfile": "dVd J bvDcF.cVJ",
262 |         "profileSettings": "bv9b0'b0'bç 'dFEdFA bvDcF.cVJ",
263 |         "institutionSettings": "bv9b0'b0'bç 'dFEbF3c6)",
264 |         "header.user": "bvDdV3b{.b0E",
265 |         "header.search": "b†-b²"Ä
266 |         "header.searchPlaceholder": "bv(b0+ d J bvDdVBC 1bv* d†'dF*d6Dd{Abv* d†'dF%c-DbvFbv*...",
267 |         "header.searchLoading": "bÆ'c J bvDb†-b,R"Ä
268 |         "header.searchEmpty": "dF' b{HbÆ/ df*bv&bÄ Dd Ä'.. x0Ä""Ä
269 |         "header.searchType.course": "dVBC 1",
270 |         "header.searchType.assignment": "b{CdFJd "Ä
271 |         "header.searchType.announcement": "bv9dF'db"Ä
272 |         "header.notifications": "bvDbV4c-'c 'bç"Ä
273 |         "header.settings": "bvDbV9b0'b0'bç"Ä
274 |         "header.profileMenu": "d&'bfEb' 'dFEdFA bvDcF.cVJ",
275 |         "header.myProfile": "dVd J bvDcF.cVJ",
276 |         "header.profileSettings": "bv9b0'b0'bç 'dFEdFA bvDcF.cVJ",
277 |         "header.institutionSettings": "bv9b0'b0'bç 'dFEbF3c6)"
278 |     }
279 | }
280 | }
281 |

```

FILE: src/locales/ar/admin.json

TYPE: .json | LINES: 1-161 | SHA256: 73a0c034f6bcfb4293e624032cd2eb5d3b138f419f3e421997b9ba2e4a834067

```

1 | {
2 |   "dashboard": {
3 |     "title": "dFHb0) bvDb{-d6E",
4 |     "totalUsers": "bv,dV'dfJ bvDdV3b{.b0Ed{F",
5 |     "activeUsers": "bvDdV3b{.b0Ed†F bvDdf4cvHdb"Ä
6 |     "programs": "bvDb†1bvEbÄ"Ä
7 |     "courses": "bvDdVBC 1bv*",
8 |     "onboarding": "bvDb{Gd{&b'"Ä
9 |     "activeCourses": "bvDdVBC 1bv* bvDdf4cv)",
10 |     "avgAttainment": "dV*d†3cr 'dF*b05d;D",
11 |     "atRiskStudents": "bvDcVDbv( bvDdV9c 6d†F dFDbæ7c "Ä
12 |     "usersByRole": "bvDdV3b{.b0Ed†F b03b, 'dF/d†1",
13 |     "recentActivity": "bvDdf4bv7 bvDb6.d{1",
14 |     "noActiveUsers": "dF' d{HbÆ/ dV3b{.b0Ed†F df4cvHdb (c~/.",
15 |     "noRecentActivity": "dF' d{HbÆ/ df4bv7 b0/d{+.",
16 |     "ploHeatmap": "bæ1d{7b' -c 'c Jb' Db{-cVJdB Ebæ1bÆ'bç 'dF*c-DdR 'dF(c FbvEbÆJb'"Ä
17 |     "ploHeatmapEmpty": "c6*c†Gc .c Jcv) b{-cVJdB Ebæ1bÆ'bç 'dF*c-DdR 'dF(c FbvEbÆJb' Gdf' c-Fb0 *d†Ac (d{'df'bç 'dFEbæ1bÆ'bçÄ"Ä
18 |     "ploHeatmapError": "b{9c Qc *b0Ed;D b†JbvFbv* b{-cVJdB Ebæ1bÆ'bç 'dF*c-DdR 'dF(c FbvEbÆJb'Ä Jc ,d' 'dFEb0'd†Db' Ec ) b6.c I.",
19 |     "ploHeatmapUnmeasured": "dF' b{HbÆ/ b†JbvFbv*",
20 |     "ploHeatmapLegend": "dV3b{Hd' 'dF*b05d;D",
21 |     "totalContributors": "{count} dv.c ,bv* dv3bv6dv)",
22 |     "ploDrillDown": {
23 |       "title": "b{Abv5d;D b{-cVJdB Ebæ1bÄ 'dF*c-DdR 'dF(c FbvEbÆJ",
24 |       "subtitle": "bvDb{-cVJdB 'dF%bÆEbVdDç .f ÇVwX0 †.¶0Wf†0Gx0'Ä Ebæ1bÆ'bç 'dFEd&1c 'bç 'dFEc6'dvEb"ç"Ä
25 |       "column": "dv.c , b{9dFE bvDdVBC 1",
26 |       "courseColumn": "bvDdVBC 1",
27 |       "attainmentColumn": "bvDb{-cVJdBÄ
28 |       "emptyTitle": "dF' b{HbÆ/ dv.c ,bv* dv3bv6dv) b†9b0Ä
29 |       "emptyDescription": "dF' b{HbÆ/ dv.c ,bv* dVBC 1bv* dV1b{(cv) c6,e Dbç *b05d{DbvK dFGc ' bvDdV.c , bvDb†1df'dV,dçÄ"Ä
30 |       "method": {
31 |         "program": "dV*d†3cr 9dFI dv3b{Hd' 'dF(c FbvEbÄ"Ä
32 |         "clo_rollup": "dv,dVQc' Edb Ebæ1bÆ'bç 'dFEd&1c 'bç"Ä
33 |         "none": "dF' b{HbÆ/ b†JbvFbv* dv3bÆDb'"
34 |       },
35 |       "level": {
36 |         "Excellent": "dVEb{'c'"Ä
37 |         "Satisfactory": "dV0c 6d0"Ä
38 |         "Developing": "d&Jbò 'dF*cvHc "Ä
39 |         "Not_Yet": "dFE d{'b0Bd" (c~/
40 |     }

```

```
41 | },
42 | "aiCoPilot": "b6/bv! bvDdV3bv9b0 'dF0d6J",
43 | "suggestionAcceptance": "d&(d†D bvDbvBb!1bv-bv*",
44 | "totalSuggestions": "{count} bvBb!1bv- bv,dV'dFJ",
45 | "predictionAccuracy": "b0Bb' dF*df(bF'b¢"Ä
46 | "validatedPredictions": "{count} b!Fb†$ b!E bvDb!-d&B dVfDr"Ä
47 | "draftAcceptance": "d&(d†D bvDdV3d†/bv*",
48 | "feedbackDrafts": "{count} dV3d†/b' *c!0d!) c 'bæ9b'"Ä
49 | "aiNoFeedback": "dFE d!*"dR *c6,d!D b6J dVDbv-c†'b¢ dFEc6'c-/ bvDc Cd¢ (c-/",
50 | "onboardingPending": "{count} cv'dF( dFE d!CdVD bvDb!Gd!&b'"Ä
51 | "onboardingPendingAction": "c-1cb 'dFbBv&dV) d†%c 3bvD b!0d6Jc 'b¢"Ä
52 | "graduateAttributes": "bvDc6Ebv* bvDb!.c ,d!)",
53 | "attributeAttainment": "b!-cVJdB 'dF3dV'b¢"Ä
54 | "attributeAttainmentDesc": "c-1cb HbV/bv1b' 1b†7 bvDc6Ebv* bvDb!.c ,d!) d†Fc†1b' 9bvEb' 9dFI bvDb!-cVJdBâ"Ä
55 | "historicalEvidence": "bvDb6/dF) bvDb! 'c JbæJb'"Ä
56 | "evidenceDashboard": "dFhb0) bvDb6/dF)",
57 | "evidenceDashboardDesc": "b!5d - c6,dF'b¢ 'dF#b0Db' 'dF*bv1d! ,d!) c-(c 'dFACVHdB 'dF/c 'c6Jb' HbvDb†1bvEbâ"Ä
58 | "competencyFrameworks": "b67c 'dFCd 'b 'b¢"Ä
59 | "frameworkManagement": "bv/bv1b' 'dF#cv1",
60 | "frameworkManagementDesc": "b!-b0Jb0 'dF*c6Dc6Dbv* bvDdv1dVJb' dDFCd 'b 'b¢ Hc (cvGbr (c6Dbv3dB 'dFEbæ1bæ'b¢â"Ä
61 | "manage": "bv/bv1b'"Ä
62 | "view": "c-1cb"Ä
63 | "rail": {
64 |   "label": "bvDdV$c63b'"Ä
65 |   "institution": "0<ß0p bvDdV$c63b'"Ä
66 |   "users": "bvDdV3b!.b0Ed†F",
67 |   "active": "bvDb03bv(bv* bvDdf4cv)",
68 |   "programs": "bvDb†1bvEbâ"Ä
69 |   "courses": "bvDdVbC 1bv*",
70 |   "analytics": "c-1cb 'dF*b0Dd!Dbv* !*",
71 |   "governance": "0=PaP b0Hd6Eb' 'dF0d6'b 'dF'cV7df'c-J",
72 |   "autonomyCeiling": "b0/ bvDdv3b!BdF'dFJb'"Ä
73 |   "a2": "A2 . d!*cvDb, 'dFEd†'d Bb'"Ä
74 |   "governanceNote": "dF' d!*cV1d 'dF0d6'b 'dF'cV7df'c-J d J b†JbvFbv* bvDdV$c63b' /d†F dVHbvAd&) b†4c Jb'â"Ä
75 |   "departments": "bvDb6Bc6'dR"Ä
76 |   "allDepartments": "bæEd!9 bvDb6Bc6'dR "Ä
77 |   "departmentsEmpty": "dF' b!Hbæ/ b†JbvFbv* b!-cVJdB (c-/."
78 | }
79 | },
80 | "users": {
81 |   "title": "bv/bv1b' 'dFEc6*bæ/dVJdb"Ä
82 |   "addUser": "bV6bvAb' Ec6*bæ/dR"Ä
83 |   "editUser": "b!9b0JdB Ec6*bæ/dR"Ä
84 |   "bulkImport": "bv3b!Jc 'b0 ,dV'c-J",
85 |   "role": "bvDb0Hc "Ä
86 |   "fullName": "bvDbv3dB 'dFCbvEdB"Ä
87 |   "email": "bvDb†1d! / bvDbVd6*c HdFJ",
88 |   "status": "bvDb0'dF)",
89 |   "deleteConfirm": "c6Jb!E b!9cvJdB -c6'b, 'dFEc6*bæ/dRâ"Ä
90 |   "importSuccess": "b!E bv3b!Jc 'b0 .¶6+VçG×0 Ec6*bæ/dR (df,bv-.",
91 |   "importErrors": "{count} cVA d!-b!Hd¢ 9dFI b6.cv'b â"
92 | },
93 | "inviteUsers": {
94 |   "title": "b09d†) bvDdV3b!.b0Ed†F",
95 |   "subtitle": "bv1c6'dB /c-Hbv* bæBbv9d!) dF#c-6bv! dvJbf) bvDb!/c Jc2 Hb6HdFJbv! bvDb6Ed†1",
96 |   "defaultRole": "bvDb0Hc 'dF'd *c 'cfJ",
97 |   "roleHint": "c6Jb05dB ,dVJc' 'dFEb09d†Jdb 9dFI dv0br 'dF/d†1. d!Ed6Fd2 'dF*bæ5d!5 dFCdB Ec6*bæ/dR Ad¢ EdFA CSV.",
98 |   "csvContent": "dV-b!Hd! 55b"Ä
99 |   "csvFormat": "bvDcVJc!): bvDb†1d! / bvDbVd6*c HdFJ"Ä 'dF/d†1 (c67c Hbv-b0 Dd6D dV3b!.b0E`Ä Jb†/b2 (cVA bvDc #c2'"Ä
100 |   "uploadFile": "c Ac' EdFA CSV",
101 |   "chooseFile": "bv.b!1 dVd 'd2"Ä
102 |   "downloadTemplate": "b!Fc&JdB 'dFBbvDb,"Ä
103 |   "sendInvites": "bv1c6'dB 'dF/c-Hbv*",
104 |   "cancel": "bvDc!'b "Ä
105 |   "noValidEmails": "dFE d!*dR 'dF9b¶Hc 9dFI c-FbvHd!F b†1d! / bVd6*c HdFJ cv'dF-b' Ad¢ EdFA CSV",
106 |   "noInstitution": "bvDdV$c63b' :d!1 dVHbæHb0)",
107 |   "results": "dF*bv&bâ 'dF/c-Hb'"Ä
108 |   "sent": "b!E bvDbV1c6'dB"Ä
109 |   "failed": "d 4dB"Ä
110 |   "pending": "d&Jb0 'dF'df*c†'c "Ä
111 |   "email": "bvDb†1d! / bvDbVd6*c HdFJ",
112 |   "role": "bvDb0Hc "Ä
113 |   "status": "bvDb0'dF)",
114 |   "message": "bvDc 3bvDb'"Ä
115 |   "sendMore": "bv1c6'dB 'dFEc&Jb0 Edb 'dF/c-Hbv*",
116 |   "copyResults": "df3bâ 'dFFb!'bf,",
117 |   "copiedToClipboard": "b!E df3bâ 'dFFb!'bf, bVdD' 'dF-bvAct)",
118 |   "invitesSent": "b!E bv1c6'dB 'dF/c-Hbv* b†Fbæ'b0"Ä
119 |   "invitesFailed": "d 4dB %c 3bvD b†9cb 'dF/c-Hbv*"
120 | },
121 | "programs": {
122 |   "title": "bv/bv1b' 'dF(c 'dv,",
123 |   "addProgram": "bv6bvAb' (c FbvEbâ"Ä
124 |   "editProgram": "b!9b0JdB (c FbvEbâ"Ä
125 |   "coordinator": "bvDdVFc6B",
126 |   "department": "bvDd&3dR"Ä
127 |   "deleteBlocked": "dF' d!Ed6F b00d (c FbvEbâ Jb0*d†J c-Dd' Ed&1c 'b¢ FcF7b'â"
128 | },
129 | "outcomes": {
130 |   "title": "dV.c ,bv* bvDb!9dFE bvDdV$c63d!)",
131 |   "addILO": "bv6bvAb' Ebæ1bâ *c-DdR EbF3c6J",
132 |   "editILO": "b!9b0JdB Ebæ1bâ *c-DdR EbF3c6J",
133 |   "deleteBlocked": "dF' d!Ed6F b00d Ebæ1bâ *c-DdR EbF3c6J dV1b!(cr (dV.c ,bv* b†1df'dV,d!)",
134 |   "sortOrder": "b!1b!Jb, 'dFAC 2"
135 | },
136 | "audit": {
137 |   "title": "c6,dB 'dFEc 'bæ9b'"Ä
138 |   "action": "bvDbV,c 'b "Ä
139 |   "entity": "bvDd6JbvF",
140 |   "performedBy": "dFAC (d†'c67b'"Ä
141 |   "timestamp": "bvDd†Bb¢"Ä
142 |   "changes": "bvDb!;d!Jc 'b¢"
143 | },
144 | "settings": {
```

```
145 |     "title": "bv9bö'bö'b¢ 'dFEbF3c6)",
146 |     "kpiThresholds": "b0/d†/ dv$cf1bv* bvd6/bv!",
147 |     "gradeScale": "dVBd;'c2 'dF/c ,bv*",
148 |     "accreditationBody": "bÆGb' 'dF'c~dv'bö"Å
149 |     "defaultLanguage": "bvDdF:b' 'dF'd *c 'cfJb'"Å
150 |     "defaultLanguageDesc": "c6Jb†/b2 'dFEc6*bæ/dvHdb 'dF,bö/ b†*d 6d†D dvödr 'dFdc†).",
151 |     "english": "bvDbvFbÆDd†2d†)",
152 |     "arabic": "bvDc-1b†Jb'"
153 | },
154 | "bilingual": {
155 |     "arabicTitle": "bvDc-Fd†'db (bvDc-1b†Jb'"Å
156 |     "arabicName": "bvDbv3dR (bvDc-1b†Jb'"Å
157 |     "arabicTitlePlaceholder": "b6/bæD bvDc-Fd†'db (bvDc-1b†Jb' †'bæ*d†'c J)",
158 |     "arabicNamePlaceholder": "b6/bæD bvDbv3dR (bvDc-1b†Jb' †'bæ*d†'c J)"
159 | }
160 | }
161 | }
```

FILE: src/locales/ar/ai.json

TYPE: .json | LINES: 1-144 | SHA256: 24828946c0f0586fbab9ab439344f4103bf7bf524ca5a83790e729c50a59b694

```
1 | {
2 |   "suggestions": {
3 |     "title": "bvBb†1bv-bv* bvdC Cbv! bvDbv5cvFbv9d¢"Å
4 |     "moduleSuggestion": "dV,bvD bvDb†1d6Jc" 'dFEd&*c -",
5 |     "weakArea": "d†-b†'bÅ %dFI b†-c6Jdb Ad¢ .¶6Æ÷×0"Å
6 |     "socialProof": "bvDcVDbv( bvdC Jdb -c6QdfHb' Gc ' bvdDv,bvD b0Bd&Hbr /c ,bv* b69dFI b†Fc6(b' .. W&6VçG×0R"Å
7 |     "feedback": "dvD d6†'db Gc ' dVAd†/bvKaö"Å
8 |     "noSuggestions": "dF' b†HbÆ/ bvBb†1bv-bv* d J bvdD†Bb¢ 'dF-bvDd¢â"
9 |   },
10 |   "atRisk": {
11 |     "title": "b†Fb†$bv* bvdBæ7c "Å
12 |     "probability": "b01bÆ) bvdBæ7c ¢ ..66÷&W×0R"Å
13 |     "signals": "bvDbv4bv1bv* bvdDv3bv6dV)",
14 |     "loginFrequency": "b†Cc 'c *c6,d†D bvdBö.d†D",
15 |     "submissionPattern": "dFecr 'dF*c6Dd†E",
16 |     "attainmentTrend": "bv*bÆ'dr 'dF*b05d†D",
17 |     "sendNudge": "bv1c6†dB *df(d†G",
18 |     "nudgeSent": "b†E bv1c6†dB 'dF*df(d†G bvdD' .¶æ ÖW×0â"
19 |   },
20 |   "feedbackDraft": {
21 |     "title": "dV3d†/b' 'dF*c†0d†) bvdC 'bÆ9b' 'dF0d6Jb'"Å
22 |     "generating": "bÆ'c J bVFcF'b Ec6Hb0) bvDb†:c Jb' 'dF1bv,c-)..." ,
23 |     "accept": "d&(d†D"
24 |     "edit": "b†9b0JdB"Å
25 |     "reject": "c Ach"Å
26 |     "overallFeedback": "dV3d†/b' 'dF*c†0d†) bvdC 'bÆ9b' 'dF4bvEdF)"
27 |   },
28 |   "tutor": {
29 |     "page": {
30 |       "title": "bvDdV9dFE bvdC Cd¢"Å
31 |       "openConversations": "d *b0 'dFEb0'bö+bv*",
32 |       "newConversationTitle": "bv(b0# dv-bv/b¶) bÆ/d†/b'"Å
33 |       "newConversationSubtitle": "bv.b†1 b63dFhb, 'dF*b01d†3 bvdC J d†Fbv3b†C b6Cb¶1",
34 |       "startChatting": "bv(b0# bvdDv-bv/b¶)",
35 |       "personaHint": "d†Ed6Fd2 *c†Jd†1 bvdCf.cVJb' Ad¢ #d¢ Hd&* b6+d†'b 'dFEb0'bö+b'"
36 |     },
37 |     "states": {
38 |       "unavailable": {
39 |         "title": "bvDdV9dFE bvdC Cd¢ :d†1 dv*bv-",
40 |         "message": "b†9c Qc 'dFHcVhdB %dFI bvdDv9dFE bvdC Cd¢ -bvDd†'d²â Jc ,d' 'dFEb0'd†Db' Ec ) b6.c I b†9b0 (cf9 b0Bbv&d"â"
41 |       },
42 |       "notEnrolled": {
43 |         "title": "c†Jc Ec6,e D d J dvödr 'dFEbv/b'"Å
44 |         "message": "b6Fb¢ :d†1 dv3bÆQdB Ad¢ Gc G bvdDv(bö) b†9b0 dF0br Dbr JdVCdb DdFec-DdR 'dF0d6J dv3bv9b0*d2 Gdf'. b†Hbv5dB Ec' Ec-
45 |       },
46 |       "noEmbeddings": {
47 |         "title": "dv† c†'dB Jb†9dFQdR Gc G bvdDv(bö)",
48 |         "message": "dFE d†Fb†Ge 'dFec-DdR 'dF0d6J dVF b01bv3b' Eb0*d†I dvödr 'dFEbv/b' (c-/ d†1bÆI bvdC-Hb0) d&1d†(bvK."
49 |       },
50 |       "rateLimited": {
51 |         "title": "b†E b†Dd†: bvDb0/ bvdD†HdVJ",
52 |         "message": "dFBB0 HcVDb¢ %dFI b0/ c 3bv&dB 'dFec-DdR 'dF0d6J dFGc ' bvdD†HdRâ 3b†*dR %c-'b0) bvDb†9d†Jdb 9df/ dVFB†5d 'dFDD†D.",
53 |         "reset": "b†*dR %c-'b0) bvDb†9d†Jdb .¶†-çG×0â"
54 |       },
55 |       "error": {
56 |         "title": "b0/b² .cv# dv'",
57 |         "message": "d†'bÆG bvdDv9dFE bvdC Cd¢ EcFCdF). d†1bÆI bvdDv-bvHdF) dv1b' #bæ1d'â"
58 |       },
59 |       "retry": "b0'd†D dv1b' #bæ1d'"
60 |     },
61 |     "chat": {
62 |       "title": "bvDdV9dFE bvdC Cd¢"Å
63 |       "emptyTitle": "d6Jd JdVCdfFd¢ Ec6'c-/b†C bvdD†HdV ",
64 |       "emptyBody": "bv3b6DdfJ c-F dv-b†Hd' Ebv/b†C b6H b†CdFJd 'b†C b6H b6J dVAdvHdR *b0*bv, bVd†' Ec6'c-/b' Ad¢ AdvEdrâ"Å
65 |       "messagesLabel": "c 3bv&dB 'dFEb0'bö+b'"Å
66 |       "typingLabel": "bvDdV9dFE bvdC Cd¢ Jd6*b,"Å
67 |       "userMessageLabel": "c 3bvDb†C",
68 |       "tutorMessageLabel": "c 3bvDb†'dFec-DdR 'dF0d6J",
69 |       "messagesRemaining": "dF/d†C {{count}} c 3bvDb† Eb†(d&Jb' 'dFJd†E.",
70 |       "limitReached": "dFBB0 HcVDb¢ %dFI b0/ bvdC 3bv&dB 'dFJd†Ed¢â 3b†*dR %c-'b0) bvDb†9d†Jdb 9df/ dVFB†5d 'dFDD†D.",
71 |       "tokenBudgetExceeded": "b†E b†,bvHc' Ed†2bvFd†*d2 'dFJd†Ed†) dVF bvdC Ed†2. d†1bÆI bvdDv-bvHdF) dv1b' #bæ1d' :b0'd²â"Å
72 |       "attachImage": "bv1d 'd" 5d†1b'"Å
73 |       "attachImages": "bv1d 'd" 5d†1",
74 |       "attachDocument": "bv1d 'd" Ec6*df/",
75 |       "removeImage": "bv2bvDb† 'dF5d†1b' .¶-æFW†×0"Å
76 |       "removeDocument": "bv2bvDb† 'dFec6*df/",
77 |       "attachmentAlt": "dv1d B {{index}}",
78 |       "messageInput": "bv/bæ†dB 'dF1c6†dF)",
79 |       "sendMessage": "bv1c6†dB 'dF1c6†dF)",
80 |       "inputPlaceholder": "bv7c - c6$bvDbvK...",
81 |       "inputPlaceholderDisabled": "b†E b†Dd†: bvDb0/ bvdD†HdVJ",
82 |       "citationLabel": "dv1bÆ9 {{number}}",
83 |       "documentAttached": "b†E bv1d 'd" Ec6*df/",
```



```

84 |         "integrityGuidance": "bv1cF'bö'b¢ 'dFFc&'dv) bvDb6Cbv/d!Ed!)",
85 |         "errors": {
86 |             "imageType": "{name}}: d!0b09dR Ad&7 cVHc ¥ r HPNG",
87 |             "imageSize": "{name}}: d!,b, #db *d6Hdb 'dF5d†1b' #d&D dVF 5 dVJc!|b†|d!\"",
88 |             "maxImages": "d!0c6Eb0 (b0/ b6BcVI {{count}} cVHc "Ä
89 |             "docType": "d!0b09dR Ad&7 dV3b!Fb0'b¢ Db HD0CX",
90 |             "docSize": "d!,b, #db Jd6Hdb 'dFec6*dF/ b6BdB Edb Ed!:bv(bvJb¢"Ä
91 |             "uploadFailed": "b!9c Qc 1d 9 bvDdV1d B. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'â"
92 |         }
93 |     },
94 |     "sidebar": {
95 |         "newConversation": "dV-bv/b¶) bÆ/d!/b' "Ä
96 |         "pastConversations": "bvDdV-bv/b¶) b¢ 'dF3bv(d&)",
97 |         "noConversations": "dF' b!HbÆ/ dV-bv/b¶) b¢ (c-/",
98 |         "noConversationsHint": "bv(b0# dV-bv/b¶) bÆ/d!/b' DdF-cvHdB 9dFI bvDdV3bv9b0)",
99 |         "newConversationPreview": "dV-bv/b¶) bÆ/d!/b' "Ä
100 |         "conversationLabel": "dV-bv/b¶): {{title}}",
101 |         "messageCount_one": "{count}} c 3bvDb' "Ä
102 |         "messageCount_other": "{count}} c 3bv&dB"Ä
103 |         "deleteConversation": "b00d 'dFEb0'b0+b' "Ä
104 |         "deleteTitle": "b00d 'dFEb0'b0+b' "Ä
105 |         "deleteDescription": "c6JbF/d¢ Gc ' bVDd' -c A dv0dr 'dFEb0'b0+b' HbÆEd!9 c 3bv&dFGbr Fdv'bFJbvK. dF' d!Ed6F bvDb!1bv,c' 9db Gc '
106 |         "deleteConfirm": "b00d "Ä
107 |         "relativeTime": {
108 |             "justNow": "bvDb&F",
109 |             "minutesAgo": "dVFc .¶6÷V¢G×0 /d&Jd&)",
110 |             "hoursAgo": "dVFc .¶6÷V¢G×0 3bv9b' "Ä
111 |             "daysAgo": "dVFc .¶6÷V¢G×0 Jd†E"
112 |         }
113 |     },
114 |     "persona": {
115 |         "yourStyle": "b63dFHB, Ec-De Ed2"Ä
116 |         "chooseStyle": "bv.b!1 b63dFHB, Ec-De Ed2"Ä
117 |         "selectLabel": "bv.b!1 cF.cVJb' 'dFec-DdR 'dF0d6J",
118 |         "groupLabel": "cF.cVJb' 'dFec-DdR 'dF0d6J",
119 |         "recommendedGroupLabel": "cF.cVJb' 'dFec-DdR 'dF0d6J bvDdVHcVI b†Gbr"Ä
120 |         "recommended": "dVHcVI b†G",
121 |         "changeStyle": "b!;d!Jc #c6Dd†( bvDdV9dFQdR"Ä
122 |         "socratic_guide": {
123 |             "label": "bvDdV1cF/ bvDc6Bc 'cvJ",
124 |             "description": "d!7c - b63bFDb' 'c6*d&5bv&d!) dFJd&Hb0C bVDd' 'dF%bÆ'b†)"
125 |         },
126 |         "step_by_step_coach": {
127 |             "label": "bvDdV/c Qb, .cvHb' (bæ7d†)",
128 |             "description": "d!Bc6QdR 'dFec6'bF0 bVDd' .cvHbv* dV*c6Dc6Db'"
129 |         },
130 |         "quick_explainer": {
131 |             "label": "bvDcF'c - bvDc61d!9",
132 |             "description": "d!Bb0QdR 4c Hb0'b¢ Ed†,c&) d†Eb†'cF1b'"
133 |         }
134 |     },
135 |     "autonomy": {
136 |         "groupLabel": "dV3b!Hd' 'c6*d&DbvDd!) bvDdV9dFE bvDc Cd¢"Ä
137 |         "figureItOut": "b09dFJ b6Cb!4d (dFAc6J",
138 |         "figureItOutLabel": "b09dFJ b6Cb!4d (dFAc6J - b!DdVJb0'b¢ Ad&7",
139 |         "justExplain": "bv4c - dFJ dV(bv4c )",
140 |         "justExplainLabel": "bv4c - dFJ dV(bv4c ) - cF1b0 Eb†'cF1"
141 |     }
142 | }
143 | }
144 | }

```

FILE: src/locales/ar/auth.json

TYPE: .json | LINES: 1-168 | SHA256: d1377f70168afd8e455786a80ee559efe78398359a0aa27890797a98c844dd98

```

1 | {
2 |     "brand": {
3 |         "tagline": "bvDb!9dFJdR 'dFBbv&dR 9dFI bvDdV.c ,bv*",
4 |         "headline": "b!9dFJdVL d!*d6Je A dv9 d6D dV*c-De E",
5 |         "subtitle": "b!9dFJdVL d&bFE c-Dd' 'dFEbæ1bÆ'b! b†Ec-De E c Cbv! bv5cvFbv9d! d†Eb0Ae 2 b†'dFDC-( dF%b!BbvF b0Bd!Bd¢ r DdF7dF'b,
6 |         "bulletOutcomes": "bvDdV.c ,bv* b!-b0Qb0 .cvHb!C bvDb!|dFJb'"Ä
7 |         "bulletTutor": "dV9dFQdR 0d6'b 'cv7df'c-J d!9c A dFBbv7 cf9d C",
8 |         "bulletHabits": "c-'b0'b¢ HbV*d&'df dF' dV,c / b01bÆ'b¢"Ä
9 |         "chipFerpa": "dV*d†'d B dv9 FERPA",
10 |         "chipBilingual": "EN / bvDc-1b†Jb'"
11 |     },
12 |     "sso": {
13 |         "google": "bvDdV*bv(c-) c-(c vöövÆR"Ä
14 |         "microsoft": "bvDdV*bv(c-) c-(c 0-7&÷6ögB"Ä
15 |         "institution": "b!3bÆJdB 'dF/bæHdB 9b†1 dV$¢63b!C",
16 |         "orWithEmail": "b6H c-(c 'dF(c Jb0 'dF%dfCb!1d†Fd¢"Ä
17 |         "magicLink": "b61c6D dFJ c 'b†7 b0.d†D c-(c 'dF(c Jb0 (b0BbvK dVF c Dd2"Ä
18 |         "magicLinkSent": "b!E bv1c6'dB 1bv(cr 'dF/bæHdB r *b0Bd' Edb (c Jb0C dF%d6EbvD b!3bÆJdB 'dF/bæHdBâ"Ä
19 |         "magicLinkError": "b!9c Qc %c 3bvD c 'b†7 bvDb0.d†D. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'â"Ä
20 |         "error": "b!9c Qc (b0! b!3bÆJdB 'dF/bæHdB 'dFEd†-e /. bÆ1e ( b!3bÆJdB 'dF/bæHdB (bvDb†1d!/ bvDbvDd6*c HdfJ."
21 |     },
22 |     "password": {
23 |         "show": "bv8dv'c CdFEb' 'dFec Hc "Ä
24 |         "hide": "bv.d 'b CdFEb' 'dFec Hc "
25 |     },
26 |     "tabs": {
27 |         "login": "b!3bÆJdB 'dF/bæHdB"Ä
28 |         "register": "bvFcF'b -c6'b,"
29 |     },
30 |     "roles": {
31 |         "admin": "dV/d!1 bvDdF8bvE",
32 |         "coordinator": "dVFc6B",
33 |         "teacher": "dV9dFE",
34 |         "student": "cv'dF(",
35 |         "parent": "d†Dd¢ 'dF#dV1"
36 |     },
37 |     "login": {
38 |         "title": "b!3bÆJdB 'dF/bæHdB"Ä
39 |         "subtitle": "b6/bæD b†JbvFbv* bvDbv9b!Ebv/ bvDbæ'cV) b†C dFdD†5d†D bVDd' 'dFEdf5b'"Ä

```

```
40 | "emailLabel": "bvDbt1d! / bvDbVDD6*c HdfJ",
41 | "emailPlaceholder": "b6/bæD b†d! /d2 'dF%DFCb!1d†Fd¢"Å
42 | "passwordLabel": "d6DdV) bvDdV1d†1",
43 | "passwordPlaceholder": "b6/bæD d6DdV) bvDdV1d†1",
44 | "submitButton": "b!3bÆJdB 'dF/bæHdB"Å
45 | "forgotPassword": "df3d! * d6DdV) bvDdV1d†1aø"Å
46 | "signingIn": "bÆ'c J b!3bÆJdB 'dF/bæHdBåå"Å
47 | "welcomeTitle": "dv1b0(bvK b†9d†/b!C",
48 | "welcomeSubtitle": "c6,e D bvDb0.d†D bVdD' -c6'b†C dFdV*bv(c-)",
49 | "successMessage": "b!E b!3bÆJdB 'dF/bæHdB (df,bv-!",
50 | "genericError": "b0/b² .cv# dV'. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'å"Å
51 | "defaultError": "bvDbt1d! / bvDbVDD6*c HdfJ b6H d6DdV) bvDdV1d†1 c!Jc 5b0Jb0).",
52 | "demoLabel": "b0.d†D b!,c Jb†J c61d!9:",
53 | "rolePickerLabel": "bv3b!CcFA b6-b0 'dF#b0Hbv1",
54 | "demoSuccess": "b!E b!3bÆJdB 'dF/bæHdB 'dF*bæ1d!(d¢ (df,bv-! bÆ'c J bvDb!-d†JdB %dFI dFhb0) b!-d6E {{role}}...",
55 | "demoError": "d 4dB *c6,d!D bvDb0.d†D bvDb!,c Jb†J. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'å"Å
56 | "noAccount": "dFJc2 Db0Jd2 -c6'b†",
57 | "createAccount": "b6FcF& b03bv(bvK",
58 | "keepSignedIn": "b6(d&Fd¢ Ec6,e DbvK"
59 | },
60 | "signup": {
61 |   "title": "bvFcF'b -c6'b,"Å
62 |   "subtitle": "bvFcF bVdD' VFwf-6W" Db†/b 'dF*c-DdR"Å
63 |   "firstName": "bvDbv3dR 'dF#d†D",
64 |   "firstNamePlaceholder": "bvDb6HdB"Å
65 |   "lastName": "bv3dR 'dF9bv&dF)",
66 |   "lastNamePlaceholder": "bvDc-'b†Db'"Å
67 |   "username": "bv3dR 'dFEc6*bæ/dR"Å
68 |   "usernamePlaceholder": "bv3dR 'dFEc6*bæ/dR"Å
69 |   "email": "bvDbt1d! / bvDbVDD6*c HdfJ",
70 |   "emailPlaceholder": "bvDbt1d! / bvDbVDD6*c HdfJ",
71 |   "password": "d6DdV) bvDdV1d†1",
72 |   "passwordPlaceholder": "d6DdV) bvDdV1d†1",
73 |   "confirmPassword": "b!#d6Jb0"Å
74 |   "confirmPasswordPlaceholder": "b!#d6Jb0"Å
75 |   "role": "bvDb0Hc "Å
76 |   "roleStudent": "cv'dF( (dV*c-DdR'"Å
77 |   "roleTeacher": "dV9dFE",
78 |   "roleCoordinator": "dVFc6B (dV4c A)",
79 |   "roleAdmin": "dV/d!1 bvDdf8bvE",
80 |   "roleHint": "bvDb!3bÆJdB 'dF0bv*d¢ Jdf4bb -c6'b, 7bvDb,å 'dF#b0Hbv1 bvDb6.c I b! *cvDb, /c-Hb'å"Å
81 |   "submitButton": "bvFcF'b -c6'b,"Å
82 |   "successMessage": "b!E bvFcF'b 'dF-c6'b, (df,bv-!",
83 |   "verificationSent": "b!E bvFcF'b 'dF-c6'b, Jc ,d', Ab!- b†1d! /d2 'dF%DFCb!1d†Fd¢ DdF*b0Bd" Edb 9dfHbvFd2 Bb†D b!3bÆJdB 'dF/bæHdB"Å
84 |   "defaultError": "d 4dB *df4bv! bvDb03bv(. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'å"Å
85 |   "genericError": "b0/b² .cv# dV'. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'å"Å
86 |   "chooseInstitution": "bv.b!1 dV$c63b!C",
87 |   "institutionSubtitle": "bv.b!1 bvDdV$c63b' 'dF*d¢ *df6dR %dFJdv'",
88 |   "createAccount": "b6FcF& b03bv(d2"Å
89 |   "accountSubtitle": "b69b0Q b!Abv5d!D b03bv(d2"Å
90 |   "selectInstitution": "bv.b!1 dV$c63b'"Å
91 |   "searchInstitution": "bv(b0+ c-F bvDdV$c63bv*...",
92 |   "noInstitutions": "dFE d! *dR 'dF9b†Hc 9dFI dV$c63bv*",
93 |   "noInstitutionsAvailable": "dF' b!Hb& dV$c63bv* dV*bv-b' DdF*c6,d!D b0'dFJbvK",
94 |   "joinModeOpen": "b! *d!- dv0dR 'dFEbF3c6) bvDb!3bÆJdB 'dF0bv*d¢å 3b!-b! 'bÅ %dFI bvDb!-d&B dVF b†1d! /d2 'dF%DFCb!1d†Fd¢å"Å
95 |   "joinModeInviteOnly": "b! *cvDb, Gc G bvDdV$c63b' /c-Hb' DdF'df6dV'dRå"Å
96 |   "joinModeDomainRestricted": "b!Bb†D dv0dR 'dFEbF3c6) c 3bv&dB 'dF(c Jb0 'dF%DFCb!1d†Fd¢ Edc¢ .†F00 -ç7×0"Å
97 |   "inviteOnlyWarning": "b! *cvDb, Gc G bvDdV$c63b' /c-Hb'å Jc ,d' 'dF*d†cVD dV9 bvDdV3bFHdBå"Å
98 |   "invalidEmailDomain": "df7bvB b†1d! /d2 'dF%DFCb!1d†Fd¢ :d!1 dV5c - b†G dF6c G bvDdV$c63b'å 'dFFcv'd&b¢ 'dFEc6Ed†- b†Gbs¢ .†F00 -ç7",
99 |   "emailVerificationRequired": "c6*b0*bv, bVdD' 'dF*b0Bd" Edb (c Jb0c bvDbVDD6*c HdfJ d&(dB 'dFHcVHdB %dFI bvDdVFcV).",
100 |   "fullName": "bvDbv3dR 'dFCbvEdB"Å
101 |   "fullNamePlaceholder": "b6/bæD bv3dVC bvDd6'dVD",
102 |   "continue": "dV*bv(c-)",
103 |   "back": "c ,d†9",
104 |   "backToLogin": "bvDc-Hb0) bVdD' *c6,d!D bvDb0.d†D",
105 |   "haveAccount": "dvD dF/d!C b03bv( b†'dFAC-Da0"Å
106 |   "signIn": "c6,e D bvDb0.d†D dvFbr"Å
107 |   "strengthHint": "bv3b!.b0E 8 b6-c A c-Dd' 'dF#d&D dv9 dV2d!, dVF bvDb6-c A d†'dF#c BbvE d†'dF1dVHc"å"Å
108 |   "strengthWeak": "cf9d!Ab' r #cfA cvHdF'd²"Å
109 |   "strengthFair": "dVBb†HdF) - b66d #c BbvEbVcK d†1dVHc&'d²"Å
110 |   "strengthGood": "d6DdV) dV1d†1 bÆJb0)",
111 |   "strengthStrong": "d6DdV) dV1d†1 d&Hd!)",
112 |   "terms": "b†'dFEb!b†9b' Ab6Fb¢ *d†'d B c-Dd' 'dF4c Hcr HbvDbæ5d†5d!). dF' b!0b†'c' (d!'df'b¢ 'dF7dF'b, #b†/bvK."
113 | },
114 | "acceptInvite": {
115 |   "title": "d&(d†D bvDb09d†)",
116 |   "subtitle": "b6CdVD bv9b0'b0 -c6'b†C",
117 |   "invalidToken": "c Ec" 'dF/c-Hb' :d!1 cV'dF- b6H dVAd&Hb0"Å
118 |   "tokenExpiredOrInvalid": "bvFb!Gb¢ 5dF'b0Jb' Gc G bvDb09d†) b6H b6Fdv' c!Jc 5bvDb0)",
119 |   "fetchError": "d 4dB Ad¢ ,dF( b!Abv5d!D bvDb09d†)",
120 |   "noInvitation": "dFE d! *dR 'dF9b†Hc 9dFI b09d†)",
121 |   "signupError": "d 4dB Ad¢ %df4bv! bvDb03bv(",
122 |   "genericError": "b0/b² .cv# dV'. d!1bÆI bvDdV-bvHdF) dV1b' #bæ1d'å"Å
123 |   "successMessage": "b!E bvFcF'b 'dF-c6'b, (df,bv-!",
124 |   "email": "c-Fd†'db 'dF(c Jb0 'dF%DFCb!1d†Fd¢"Å
125 |   "institution": "bvDdV$c63b'"Å
126 |   "role": "bvDb0Hc "Å
127 |   "fullName": "bvDbv3dR 'dFCbvEdB"Å
128 |   "fullNamePlaceholder": "b6/bæD bv3dVC bvDd6'dVD",
129 |   "password": "d6DdV) bvDdV1d†1",
130 |   "passwordPlaceholder": "b6FcF& d6DdV) dV1d†1",
131 |   "confirmPassword": "b!#d6Jb0 CdFEb' 'dFEc Hc "Å
132 |   "confirmPasswordPlaceholder": "b6Ce / d6DdV) dV1d†1d2"Å
133 |   "acceptButton": "d&(d†D bvDb09d†) d†%df4bv! bvDb03bv(",
134 |   "haveAccount": "dvD dF/d!C b03bv( b†'dFAC-Da0"Å
135 |   "signIn": "c6,e D bvDb0.d†D dvFbr"
136 | },
137 | "logout": {
138 |   "button": "b!3bÆJdB 'dF.c HbÅ"Å
139 |   "confirmMessage": "dvD b6Fb¢ Eb!#d6/ b6Fd2 *c Jb0 *c6,d!D bvDbæ1d†,a0"
140 | },
141 | "resetPassword": {
142 |   "title": "bv9bv/b' *c-Jd!F d6DdV) bvDdV1d†1",
143 |   "subtitle": "b6/bæD b†1d! /d2 'dF%DFCb!1d†Fd¢ Db!Dd&J c 'b†7 bv9bv/b' 'dF*c-Jd!F",
```

```

144 |     "emailLabel": "bvDbt1d!/ bVDbvDd6*c HdfJ",
145 |     "submitButton": "bv1c6!dB 1bv(cr %-b0) bVDb!9d!Jdb"Å
146 |     "successMessage": "b!E bv1c6!dB 1bv(cr %-b0) b!9d!Jdb CdFEb' 'dFEC Hc %dFI bt1d!/d2 'dF%DFCb!1d!Fdca"Å
147 |     "backToLogin": "bvDc-Hb0) bVDd' *c6,d!D bVDb0.d!D"
148 | },
149 | "updatePassword": {
150 |     "title": "b!9d!Jdb CdFEb' Ec Hc ,b0Jb0)",
151 |     "subtitle": "b6/bæD d6DdV) bVDdV1d!1 bVDbÆ/d!/b' #b0FbvG",
152 |     "newPasswordLabel": "d6DdV) bVDdV1d!1 bVDbÆ/d!/b"Å
153 |     "confirmPasswordLabel": "b!#d6Jb0 CdFEb' 'dFEC Hc "Å
154 |     "submitButton": "b!-b0Jb2 CdFEb' 'dFEC Hc "Å
155 |     "successMessage": "b!E b!-b0Jb2 CdFEb' 'dFEC Hc (df,bv-.", 'dFEC Hc 'dF,b0Jb0).",
156 |     "loginPrompt": "d!Ed6Fd2 'dF"db *c6,d!D bVDb0.d!D btCdFEb' 'dFEC Hc 'dF,b0Jb0).",
157 |     "goToLogin": "bvDc Gbv( bVDd' *c6,d!D bVDb0.d!D",
158 |     "passwordPlaceholder": "8 b6-c A c-Dd' 'dF#d&D",
159 |     "confirmPlaceholder": "b69b0 %b0.bvD d6DdV) bVDdV1d!1"
160 | },
161 | "errors": {
162 |     "invalidCredentials": "bvDbt1d!/ bVDbvDd6*c HdfJ b6H d6DdV) bVDdV1d!1 c!Jc 5b0Jb0).",
163 |     "accountLocked": "b!E d&AdB 'dF-c6'b,â Jc ,d' 'dFEb0!d!Db' Ec ) b6.c I bt!9b0 R /d&Jd&).",
164 |     "sessionExpired": "bvFb!Gb0 5dF'b0Jb',dF3b!C. d!1b!EI b!3b!JdB 'dF/bæHdB Ec ) b6.c I.",
165 |     "resetLinkExpired": "bvFb!Gb0 5dF'b0Jb' 1bv(cr %-b0) bVDb!9d!Jdbâ Jc ,d' 7dF( c 'bt!7 bÆ/d!/. "
166 | }
167 | }
168 |

```

FILE: src/locales/ar/common.json

TYPE: .json | LINES: 1-1203 | SHA256: 4145aec45b64139be018dab484d3c55c31aeec3e32add5741fc404f4b9e5248d

```

1 | {
2 |   "carousel": {
3 |     "previous": "bvDcF1d!-b' 'dF3bv(d&)",
4 |     "next": "bvDcF1d!-b' 'dF*bvDd!)",
5 |     "slideOf": "{current} dVF {total}",
6 |     "goTo": "bvFb!BdB %dFI bvDcF1d!-b' .!çV0&W'x0"
7 |   },
8 |   "nav": {
9 |     "dashboard": "dFHb0) bVDb!-d6E",
10 |    "users": "bvDdV3b!b0Ed!F",
11 |    "departments": "bvDb6Bc6'dR"Å
12 |    "programs": "bvDbt1bvEb"Å
13 |    "courses": "bvDdVBc 1bv*",
14 |    "semesters": "bvDd 5d!D bVDb01bv3d!)",
15 |    "outcomes": "bvDdV.c ,bv*",
16 |    "ilos": "dV.c ,bv* bVDb!9dFE bVDdV$c63d!)",
17 |    "timetable": "bvDbÆ/d!D bVDb01bv3d0"Å
18 |    "calendar": "bvDb!Bd!JdR"Å
19 |    "fees": "bvDc 3d!E",
20 |    "reports": "bvDb!Bbv1d!1",
21 |    "accreditationReports": "b!Bbv1d!1 bVDbv9b!Ebv/",
22 |    "security": "bvDb6EbvF",
23 |    "auditLog": "c6,dB 'dFEC 'bÆ9b' "Å
24 |    "bonusXp": "dfBbv7 bV6bvAd!)",
25 |    "badgeSpotlight": "cF'c ) dVEd!2b' "Å
26 |    "badges": "bvDb6HcEb' "Å
27 |    "learningProfile": "dVDd 'dF*c-De E",
28 |    "marketplace": "bvDc6Hd"Å
29 |    "surveys": "bvDbv3b!7dF'c-'b0"Å
30 |    "settings": "bvDbV9b0'b0'b0"Å
31 |    "plos": "dV.c ,bv* bVDbt1df!dV, ",
32 |    "matrix": "bvDdV5d Hd )",
33 |    "sankeyDiagram": "dV.cv7 c6'dfCd0"Å
34 |    "gapAnalysis": "b!-dFJdB 'dFAbÆHbv*",
35 |    "coverageHeatmap": "bæ1d!7b' 'dF*c!7d!) bVDb01bv1d!)",
36 |    "semesterTrends": "bv*bÆ!dv'b0 'dFACVD bVDb01bv3d0"Å
37 |    "cohortComparison": "dVBbv1df) bVDdV,dVHC-'b0"Å
38 |    "cqIPlans": "bæ7cr *b03d!F bVDbÆHb0)",
39 |    "courseFile": "dVDd 'dFEd&1c "Å
40 |    "outcomeChain": "c6Dc6Db' 'dFEbæ1bÆ'b0"Å
41 |    "clos": "dV.c ,bv* b!9dFE bVDdVBc 1",
42 |    "rubrics": "dV9bvJd!1 bVDb!Bd!JdR"Å
43 |    "assignments": "bvDb!CdFJd 'b0"Å
44 |    "grading": "bvDb!Bd!JdR"Å
45 |    "gradebook": "c6,dB 'dF/c ,bv*",
46 |    "announcements": "bvDbV9dF'df'b0"Å
47 |    "modules": "bvDd!-b0'b0"Å
48 |    "students": "bvDcVDbv(",
49 |    "challenges": "bvDb!-b0Jbv*",
50 |    "teams": "bvDd 1d"Å
51 |    "teamHealth": "cV-b' 'dFAC Jd"Å
52 |    "tutorAnalytics": "b!-dFJdF'b0 'dFEC-DdR 'dF.bv5",
53 |    "tutorHandoffs": "b!3dFJdV'b0 'dFEC-DdR 'dF.bv5",
54 |    "baselineTests": "bvDbv.b!(bv1bv* bVDb!EdvJb0Jb' "Å
55 |    "planner": "bvDdV.cv7",
56 |    "today": "bvDd!HdR"Å
57 |    "progress": "bvDb!Bb0E",
58 |    "leaderboard": "dFHb0) bVDdV*cV/c Jdb"Å
59 |    "myTeam": "d 1d!Bd0"Å
60 |    "habits": "bvDc-'b0'b0"Å
61 |    "myContent": "dV-b!HbvJ",
62 |    "journal": "bvDd!HdVJb' "Å
63 |    "aiTutor": "bvDdV9dFE bVDC Cd0"Å
64 |    "portfolio": "dVd 'dF%df,bv2bv*",
65 |    "coursesTasks": "bvDdVBc 1bv* dt'dFEdv'dR"Å
66 |    "dailyReview": "bvDdV1bv,c-) bVDd!HdVJb' "Å
67 |    "wellness": "bvDc-'d Jb' "Å
68 |    "focus": "bvDb!1d6Jc"Å
69 |    "quests": "bvDdVGbvE",
70 |    "shop": "bvDdV*bÆ1",
71 |    "children": "bvDb6(df'b "Å
72 |    "attendance": "bvDb06d!1",
73 |    "studyPlan": "bæ7b' 'dF/c 'c6)",
74 |    "support": "bvDb09dR"Å
75 |    "profile": "bvDdVDd 'dF4bæ5d0"Å

```

```
76 | "me": "b6Fbr"Ã
77 | "notifications": "bvDbv4c-'c 'b¢"Ã
78 | "studentTriage": "d 1c" 'dF7dF'b,"Ã
79 | "curriculumStudio": "bv3b|HbðJd, 'dFedfGbÂ"Ã
80 | "rubricBuilder": "dVFCF& c6DbvDdR 'dF*d&Jd|E",
81 | "courseMaterials": "dVHbv/ bvDdVbC 1",
82 | "gradingQueue": "d&'bFb' 'dF*d&Jd|E",
83 | "growthWellbeing": "bvDdfEd, HbvDc-'d Jb'"Ã
84 | "supportMessages": "bvDbð9dR HbvDc 3bv&dB"Ã
85 | "feesPayments": "bvDc 3d†E d†'dFEbðAd†9bv*",
86 | "gradesReports": "bvDbð1bÆ'b¢ HbvDb|Bbv1d|1",
87 | "outcomeAttainment": "b|-'cVJdB 'dFEbæ1bÆ'b¢"Ã
88 | "curriculumMatrix": "dV5d Hd ) bvDdVfDv,",
89 | "courseFileGenerator": "dVHDf/ dVdD 'dFEd&1c "Ã
90 | "accreditation": "bvDbv9b|Ebv/",
91 | "aiGovernance": "b0Hd6Eb' 'dF0d6'b 'dF'cV7df'c-J",
92 | "institutionStructure": "dvJd6D bvDdV$c63b'"Ã
93 | "bulkImport": "bvDbv3b|Jc 'bò 'dFEbÆEc'"Ã
94 | "badgeDefinitions": "b|9c Jd 'b¢ 'dF4bv1bv*",
95 | "feesManagement": "bv/bv1b' 'dF1c6HdR"Ã
96 | "questionBank": "b†Fd2 'dF#c6&dF)",
97 | "discussions": "bvDdVfBvBcF'b¢"Ã
98 | "teamHealthReport": "b|Bc Jc 5b0) bvDd 1d|B",
99 | "competencyFrameworks": "b67c 'dFCd 'b 'b¢"Ã
100 | "mobile": {
101 |   "home": "bvDc &d|3d|)",
102 |   "learn": "bvDb|9dFQdR"Ã
103 |   "tutor": "bvDdV9dFE",
104 |   "progress": "bvDb|BbðE",
105 |   "students": "bvDcVDbv(",
106 |   "studio": "bvDbv3b|HbðJd,"Ã
107 |   "grade": "bvDb|Bd|JdR"Ã
108 |   "growth": "bvDdfEd,"Ã
109 |   "support": "bvDbð9dR"Ã
110 |   "outcomes": "bvDdV.c ,bv*",
111 |   "curriculum": "bvDdVfDv,",
112 |   "accredit": "bvDbv9b|Ebv/",
113 |   "analytics": "bvDb|-'dFJdF'b¢"Ã
114 |   "aiGov": "b0Hd6Eb' 'dF0d6'b 'dF'cV7df'c-J",
115 |   "people": "bvDb64bæ'cR"
116 | },
117 | "more": "bvDdV2d|/",
118 | "upgradeToPremium": "bvDb|1d&Jb' %dFI b†1d|Ed|HdR"Ã
119 | "upgradeDescription": "bv3b|.b0E dfBbv7 bvDbæ(c ) dFAb|- dVCbvAb&* b|9dFJdVJb' Ed Jbð).",
120 | "exploreRewards": "bv3b|CcFÅ bvDdVCbvAb&*",
121 | "level": "bvDdV3b|Hd' .¶ÆwFVÇ×0"Ã
122 | "xp": "dfBcv) bæ(c )",
123 | "levelProgress": "b|Bb0E bvDdV3b|Hd'"Ã
124 | "discussions": "bvDdVfBvBcF'b¢"Ã
125 | "quizzes": "bvDbv.b|(bv1bv*",
126 | "groups": {
127 |   "learn": "bvDb|9dFQdR"Ã
128 |   "growth": "bvDdfEd,"Ã
129 |   "community": "bvDdV,b|Ec'"Ã
130 |   "tools": "bvDb6/d†'b¢"
131 | }
132 | },
133 | "emailVerification": {
134 |   "banner": "d|1bÆI bvDb|-d&B dVF c-Fd†'db (c Jb0c bvDbvDd6*c HdFJ dFDd†5d†D bVdD' ,dVJc' 'dFed|2bv*.",
135 |   "resend": "bv9bv/b' %c 3bvD b†1d|/ bvDb|-d&B",
136 |   "resendSuccess": "b|E bV1c6'dB (c Jb0 'dF*b0Bd"Ã Edb 5df/d†B bvDd†'c /.",
137 |   "resendError": "d 4dB %c-'b0) bV1c6'dB (c Jb0 'dF*b0Bd"Ã Jc ,d' 'dFEb0'd†Bb' Ec ) b6.c I.",
138 |   "dismiss": "bV:dF'd""
139 | },
140 | "buttons": {
141 |   "save": "b0Ac,"Ã
142 |   "cancel": "bvDc|'b "Ã
143 |   "delete": "b00d "Ã
144 |   "edit": "b|9b0JdB"Ã
145 |   "create": "bVFcF'b "Ã
146 |   "submit": "bV1c6'dB"Ã
147 |   "confirm": "b|d6Jb0"Ã
148 |   "back": "c ,d†9",
149 |   "next": "bvDb|'dFJ",
150 |   "close": "bv:dF'd""Ã
151 |   "retry": "bv9bv/b' 'dFEb0'd†Db'"Ã
152 |   "export": "b|5b0Jc "Ã
153 |   "import": "bv3b|Jc 'b0"Ã
154 |   "search": "b†-b²"Ã
155 |   "filter": "b|5d Jb'"Ã
156 |   "reset": "bv9bv/b' *c-Jd|F",
157 |   "download": "b|-'dVJdB"Ã
158 |   "upload": "c Ac'"
159 | },
160 | "status": {
161 |   "active": "df4cr"Ã
162 |   "inactive": "c|Jc FcF7",
163 |   "pending": "d&Jb0 'dF'df*ct'c "Ã
164 |   "completed": "dVCb|EdB"Ã
165 |   "dropped": "dVFc6-b,"Ã
166 |   "loading": "bÆ'c J bvDb|-'dVJdBååå"Ã
167 |   "saving": "bÆ'c J bvDb0Ac,ååå"Ã
168 |   "error": "bæ7b2"Ã
169 |   "success": "df,bv-"
170 | },
171 | "form": {
172 |   "required": "dv0br 'dF-d&D dv7dFHb,"Ã
173 |   "email": "bvDb†1d|/ bvDbVdD6*c HdFJ",
174 |   "password": "d6DdV) bvDdV1d†1",
175 |   "name": "bvDbv3dR"Ã
176 |   "description": "bvDd†5d "Ã
177 |   "title": "bvDc-Fd†'db"Ã
178 |   "code": "bvDc Ec""Ã
179 |   "selectOption": "bv.b|1 bæJbv1bvK",
```

```
180 "noResults": "dFE d! *dR 'dF9b¶Hc 9dFI df*bv&bÂ"
181 },
182 "errors": {
183 "generic": "b0/b2 .cv# dV'. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
184 "notFound": "dFE d! *dR 'dF9b¶Hc 9dFI bVDdVHc / bVDdV7dFhb,â"Â
185 "unauthorized": "c!Jc EcV1b0 Dd2 (b!Fd Jc Gc ' bVDbv,c 'b â"Â
186 "forbidden": "b!E c Acb 'dHcVhdBâ"Â
187 "networkError": "bæ7b2 Ad¢ 'dF4b†Cb'â Jc ,d' 'dF*b0Bd" Edb 'b!5bvDd2â"Â
188 "timeout": "bvFb!Gb¢ EdvDb' 'dF7dF(. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
189 "validation": "d!1bÆI bVDb!-d&B dVF bVDdFEd†0bÂ (b0+bvK c-F b6.cv'b â"
190 },
191 "pagination": {
192 "previous": "bVDC6'b†B",
193 "next": "bVDb!dFJ",
194 "showing": "c-1cb .¶g&ö××0 %dFI {{to}} dVF {{total}}",
195 "rowsPerPage": "cVAd†A dFCdB 5d -b'"Â
196 "noResults": "dFE d! *dR 'dF9b¶Hc 9dFI df*bv&bÂâ"Â
197 "pageOf": "cVAb0) {{page}} dVF {{total}}"
198 },
199 "confirmation": {
200 "deleteTitle": "dvd b6Fb¢ Eb!#d6/a0"Â
201 "deleteMessage": "dF' d!Ed6F bVDb!1bv,c' 9db Gc ' bVDbv,c 'b â"Â
202 "unsavedChanges": "dF/d!C b! :d!Jc 'b¢ :d!1 dV-d Hc†). dVD b6Fb¢ Eb!#d6/ b6Fd2 *c Jb0 'dFec!'b01b- "
203 },
204 "errorBoundary": {
205 "title": "b0/b2 .cv# dV'",
206 "defaultMessage": "b0/b2 .cv# c!Jc Eb!Hd&9.",
207 "retry": "bv9bv/b' 'dFEb0'd†Db'"
208 },
209 "notFound": {
210 "code": "404",
211 "title": "bvDcVAb0) c!Jc Ed†,d†/b'"Â
212 "description": "bvDcVAb0) bVDb!J b!(b0+ c-Fdv' c!Jc Ed†,d†/b' #d, 1b†Ebr *dR Fd&Ddv'." ,
213 "backToLogin": "bvDc-Hb0) bVDD' *c6,d!D bVDb0.d†D",
214 "goBack": "c ,d†9"
215 },
216 "blooms": {
217 "remembering": "bVDb!0d61",
218 "understanding": "bvDd GdR"Â
219 "applying": "bVDb!7b†Jd""Â
220 "analyzing": "bVDb!-dFJdB"Â
221 "evaluating": "bVDb!Bd!JdR"Â
222 "creating": "bVDbV(b0'c'"
223 },
224 "attainment": {
225 "excellent": "dVEb!c""Â
226 "satisfactory": "dV0c 6d0"Â
227 "developing": "d&Jb0 'dF*cvHd!1",
228 "notYet": "dFE d! *b0Bd" (c-/"
229 },
230 "attainmentInfo": {
231 "triggerLabel": "dv'c ' b!9dfJ df3b†) bVDb!-cVJdB Gc Ga0"Â
232 "title": "d GdR 'dF*b05d!D"
233 "description": "d!HcfQb0 'dF*b05d!D dv/d' %b!BbvFd2 DdV.c ,bv* b!9dFE bVDdVBc 1.",
234 "bandsHeading": "bVDdV3b!Hd! 'b¢"Â
235 "ranges": {
236 "excellent": "{{min}}% d #d6+c "Â
237 "satisfactory": "{{min}}-{{max}}%",
238 "developing": "{{min}}-{{max}}%",
239 "notYet": "b6BdB Edb ..F&W6†0ÆG×0R"
240 }
241 },
242 "mascot": {
243 "regionLabel": "bVJb0J dV/c ( bVDb!9dFQdR"Â
244 "moments": {
245 "welcome": {
246 "title": "dV1b0(d¶!`Â #df' bVJb0J!",
247 "message": "c6#d6Hdb Eb01b†C cvHbvd bVDcv1d!B. dFFd09e /e 1b0Db!C bVDb!9dFJdVJb' Ec-Kbrâ"
248 },
249 "assessmentIntro": {
250 "title": "b!-d&Qd" 3c Jc'"Â
251 "message": "b6,b, (cV/d" r Dbr *d†,b0 %bÆ'b†'b¢ .bv7bf) dvFbrâ Gc ' d!3bv9b0Fd¢ 9dFI b!.cVJcR *bÆ1b†*d2â"
252 },
253 "emptyState": {
254 "title": "dF' d!HbÆ/ cFJb Gdf' b†9b0"Â
255 "message": "dvFbr 3b!8dv1 bVDb6Ed†1 b†EbÆ1b0 #db *b†/b2â 'b!.c 'dF.cvHb' 'dF#d†Dd' Hc6#cF,c-C."
256 },
257 "firstXp": {
258 "title": "b6HdB Fd&'cr .b†1b' Dd2 "Â
259 "message": "c-EdB 1bv&c' r Dd&/ b05dF* dFDb!H c-Dd' #d†D dfBbv7 bæ(c ). d†'cVD bVDb!Bb0QdR HcF'dv/ dv3b!HbvC d!1b!Ac'â"
260 },
261 "firstEnrollment": {
262 "title": "b!E b!3bÆJdFC!",
263 "message": "dV1b0(d¶! b†C d J dVbc 1d2 'dF#d†D. bv3b!CcFa bVDb01d†3 d†3b63bv9b0C c-Dd' Eb!'b†9b' Ec6'c C."
264 },
265 "password": {
266 "title": "df-bvAc, 9dFI b6EbvFd2"Â
267 "message": "bv.b!1 d6DdV) dV1d†1 d!3dvD b!0d6Qc Gbrâ 'cf:cr 9dFI b6Jd&Hdf) bVDC-Jdb Ad¢ #d¢ Hd&* dFDb!-d&B dVEbr Cb!(b!G."
268 }
269 },
270 },
271 "timetable": {
272 "title": "bVDbÆ/d†D bVDb01bv3d¢"Â
273 "weeklySchedule": "bVDbÆ/d†D bVDb63b†Hc-J",
274 "time": "bvDd†Bb¢"Â
275 "class": "b05b'"Â
276 "sectionLabel": "bvDcF9b†) {{code}}",
277 "days": {
278 "0": "bVDb6-b0"Â
279 "1": "bVDbV+dfJdb"Â
280 "2": "bVDb¶Dbv+bv!",
281 "3": "bVDb61b†9bv!",
282 "4": "bVDbæEd!3",
283 "5": "bVDbÆEc-)",
```

```
284 |         "6": "bvDc6(b¢"
285 |     },
286 |     "slotType": {
287 |         "lecture": "dv-bv6c )",
288 |         "lab": "dv.b!{c "Å
289 |         "tutorial": "b!Ebv1d!F"
290 |     },
291 |     "now": {
292 |         "happeningNow": "b!,c J bvDb&F",
293 |         "upNext": "bvDb! 'dFJb' "Å
294 |         "endsIn": "b!Fb!Gd¢ .dF'dB ..F-Öw×ð"Å
295 |         "startsIn": "b!(bð# bæDbvD {{time}}",
296 |         "room": "d&'c-) {{room}}",
297 |         "noUpcoming": "dF' b!HbÆ/ b05cR Bbv/dv)",
298 |         "noUpcomingHint": "b6Fb¢ 9dFI bv7dF'c' (d6D cFJb r Dbr *d†,bò -cV5 dV,b0HdF) bvDb&F."
299 |     },
300 |     "remaining": {
301 |         "days": "{{value}} d!HdR"Å
302 |         "hours": "{{value}} c2"Å
303 |         "minutes": "{{value}} b0"Å
304 |         "lessThanMinute": "b6BdB Edb /d&Jd&)"
305 |     }
306 | },
307 | "calendar": {
308 |     "title": "bvDb!Bd†JdR"Å
309 |     "subtitle": "c-1cb DdFBC 'b ) d Bcr DdVHbv9d!/d2 'dFFdv'bfJb' 'dFBbv/dv).",
310 |     "readOnlyNotice": "dv0br 'dF*d&Hd!E dFDd&1bv!b' Ad&7. dF%cf'd ) bvDdVGBvE d†,dF3bv* bvDb01bv3b' #d, *c-/d!Ddv'`Å 'c6*bæ/dR 'dFEbæ7e
311 |     "monthly": "cFGc J"
312 |     "weekly": "b63b†Hc-J",
313 |     "previous": "bvDc6!b†B",
314 |     "next": "bvDb! 'dFJ",
315 |     "noEvents": "dF' b!HbÆ/ b6-b0'b²"Å
316 |     "moreEvents": "+{{n}} b6.c I",
317 |     "daysShort": {
318 |         "0": "b6-b0"Å
319 |         "1": "bv+dFJdb"Å
320 |         "2": "b¶Dbv+bv!",
321 |         "3": "b61b†9bv!",
322 |         "4": "bæEd!3",
323 |         "5": "bÆEc-)",
324 |         "6": "c6(b¢"
325 |     }
326 | },
327 | "parentDashboard": {
328 |     "greeting": {
329 |         "morning": "cV(bv- bvDbæJc "Å
330 |         "afternoon": "dV3bv! bvDbæJc "Å
331 |         "evening": "dV3bv! bvDbæJc "
332 |     },
333 |     "subtitle": "bv(d&N c-Dd' *d†'cVD dV9 c -dF) cvAdFC bvDb!9dFJdVJb'â"Å
334 |     "children": "bvDb6(df'b "Å
335 |     "totalCourses": "bv,dV'dFJ bvDdVBC 1bv*",
336 |     "avgAttainment": "dV*d†3cr 'dF*b05d!D)",
337 |     "deadlines": "bvDdVHbv9d!/ bvDdfGbv&d!)",
338 |     "yourChildren": "b6(df'bFC"
339 |     "levelLabel": "bvDdV3b!Hd' "Å
340 |     "coursesLabel": "dVBC 1bv*",
341 |     "noChildren": "dF' d!HbÆ/ b6(df'b Ec *b†7d†F b†9b0â 'cvDb, Edb Ec6$d†D bvDdV$c63b' %c-/bv/ c (cr HdFJ bvDb6Ec (bvDcv'dF(.",
342 |     "xp": "dFbBv7 bvDbæ(c )"
343 | },
344 | "parentPlanner": {
345 |     "title": "bæ7b' 'dF/c 'c6)",
346 |     "today": "bvDd!HdR"Å
347 |     "previousWeek": "bvDb63b†Hc' 'dF3bv(d""Å
348 |     "nextWeek": "bvDb63b†Hc' 'dF*bvDd¢"Å
349 |     "studyHours": "c6'c-'b¢ 'dF/c 'c6)",
350 |     "sessions": "bvDbÆDc6'b¢"Å
351 |     "tasksDone": "bvDdVGBvE bvDdVFbÆ2b' "Å
352 |     "weeklySchedule": "bvDbÆ/d†D bvDb63b†Hc-J",
353 |     "noStudent": {
354 |         "title": "dFE d!dR 'bæ*d! 'c 7bvDb,"Å
355 |         "description": "bv.b!1 cv'dF(d¶' dVF cVAb0) bvDb6(df'b Dc-1cb .cv) b01bv3b!G.",
356 |         "cta": "bvDc Gbv( bvDd' 'dF#b†Fbv!"
357 |     }
358 | },
359 | "parentProfile": {
360 |     "title": "bvDdVDD 'dF4bæ5d¢"Å
361 |     "info": "dV9dFHDV'b¢ 'dFEdFA bvDcF.cVJ"
362 | },
363 | "accessibility": {
364 |     "title": "bv9b0'b0'b¢ %dVCbvFd!) bvDd†5d†D",
365 |     "fontSize": "b0,dR 'dF.cr"Å
366 |     "fontDefault": "bvAb!1bv6d¢"Å
367 |     "fontLarge": "d6(d!1",
368 |     "fontXLarge": "d6(d!1 bÆ/bvK",
369 |     "highContrast": "b!(bvJdb 9bvDd0"Å
370 |     "reducedAnimations": "b!BdFJdB 'dF-c Cb' "Å
371 |     "dyslexiaFont": "bæ7 cV/d!B dF9c61 bvDd&1bv!b' "Å
372 |     "simplifiedView": "c-1cb Eb†3cr"Å
373 |     "cognitiveLoadMessage": "b!-b!Hd¢ Gc G bvDcVAb0) c-Dd' 'dFCb¶Jc Edb 'dFEC-Dd†Ebv* - dvD b!1d!/ c-1cf'd² Eb†3cv'd¶ "
374 | },
375 | "user": "bvDdV3b!.b0E",
376 | "skipToMain": "bvDb! .cvJ bVDD' 'dFEb0*d†I bvDc &d!3d¢"Å
377 | "search": "b†-b²"Å
378 | "searchPlaceholder": "bv(b0+ d J bvDdVBC 1bv* d†'dF*d6Dd!Abv* d†'dF%-DbvFbv*...",
379 | "searchLoading": "bÆ'c J bvDb†-b,R"Å
380 | "searchEmpty": "dF' b!HbÆ/ df*bv&bÅ Dd 7·. ×ÜB"Å
381 | "searchType": {
382 |     "course": "dVBC 1",
383 |     "assignment": "b!CdFJd "Å
384 |     "announcement": "bv9dF'db"
385 | },
386 | "notifications": "bvDbV4c-'c 'b¢"Å
387 | "settings": "bvDbV9b0'b0'b¢"Å
```

```
388 "profileMenu": "d&'bF Eb' 'dFedFA bvDcF.cVJ",
389 "myProfile": "dVDD J bvDcF.cVJ",
390 "profileSettings": "bv9b0'b0'b0c 'dFedFA bvDcF.cVJ",
391 "institutionSettings": "bv9b0'b0'b0c 'dFEbF3c6)",
392 "header": {
393   "user": "bvDdV3b!.b0E",
394   "search": "b+-b2"Å
395   "searchPlaceholder": "bv(b0+ d J bvDdVBC 1bv* d+ 'dF*d6Dd!Abv* d+ 'dF%c-DbvFbv*...",
396   "searchLoading": "bÆ'c J bvDd+-b.R"Å
397   "searchEmpty": "dF' b;HbÆ/ df*bv&bÅ Dd 7.. xÜB"Å
398   "searchType": {
399     "course": "dVBC 1",
400     "assignment": "b;CdFJd "Å
401     "announcement": "bv9dF'db"
402   },
403   "notifications": "bvDbV4c-'c 'b0"Å
404   "settings": "bvDbV9b0'b0'b0c"Å
405   "profileMenu": "d&'bF Eb' 'dFedFA bvDcF.cVJ",
406   "myProfile": "dVDD J bvDcF.cVJ",
407   "profileSettings": "bv9b0'b0'b0c 'dFedFA bvDcF.cVJ",
408   "institutionSettings": "bv9b0'b0'b0c 'dFEbF3c6)",
409   "primaryNav": {
410     "label": "bvDb;Fd&D bvDc &d;3d0"
411   },
412   "unreadCount": "{count} bv4c-'c :d;1 dVBC Hb "Å
413   "notificationsLabel": "bvDbV4c-'c 'b0"Å
414   "markAllRead": "b;-.b0Jb0 'dFCdB CdVBC Hb "Å
415   "whyThis": "dFEbv0br #c I dv0bv ",
416   "whyThisDescription": "b;9b;Eb0 Gc G bvDbV1cF'b0'b0c 9dFI dV$cF1bv* bvDb;9dFE bvDb0'dfJb' 'dF*bvDd;).",
417   "whySignals": {
418     "teacher": "d;+cfEdb 9b+! c-EdFc bvDb0'dfJ {pending} b;3dFJdV'b0c *b0*bv, bVDd' *cV-d;- d;+E&-6-×0 7dF'b+!d'2 Jb0*bv,d+f bVDd'
419     "parent": "d;3b;!.b0E dv0br 'dFedF.cR 3bÆDbv* bvDb;9dFE d+ 'dFed+!c-Jb0 'dFFdv'bfJb' 'dFBbv/dv) dF#cvAbvDd2 'dFEc *b+7d;F d+9b0/dvE
420     "coordinator": "b;3b;!.b0E dv0dr 'dF4bv4b' .¶&VÆ÷uF &vW0×0 Edb Ebæ1bÆ'b0c 'dF(c FbvEbÅ 'dFHbvBC-) b0'dfJbvK b0Hdb 'dFGb0A d+9b0/b'2 (
421     "admin": "b;3b;!.b0E dv0dr 'dF4bv4b' 3bÆDbv* bvDdV$c63b' 'dFEb;!.b0) dF/d+1 bvDdV3bFHD B Db0Jd6 d+EdfGbr ..w6W'7×0 Ec6*bæ/dV'd'2 H{
422   },
423   "openGlobalSearch": "d *b0 'dF(b0+ bvDcF'dVD",
424   "search": "b+-b2"Å
425   "searchPrompt": "bvCb;( dFDb+-b2 #d, 'dF'df*d&'dB %dFI...",
426   "commandSection": { "goTo": "bvFb;BdB %dFI", "actions": "bv,c 'b 'b0" Å
427   "commands": {
428     "today": "bvDd;HdR"Å
429     "learningPath": "dv3bv1 bvDb;9dFE",
430     "tutor": "bvDdV9dFE bvDc Cd0"Å
431     "progress": "bvDb;Bb0E",
432     "fixWeakest": "c-'dF, b66c-A dV.c , b;9dFE",
433     "askTutor": "bv3b6D bvDdV9dFE bvDc Cd0"Å
434     "home": "bvDc &d;3d;)",
435     "studentTriage": "d 1c" 'dF7dF'b,"Å
436     "curriculumStudio": "bv3b;Hb0Jd, 'dFedfGbÅ"Å
437     "gradingQueue": "d&'bF Eb' 'dF*d&Jd;E",
438     "draftFeedback": "cVJbv:b' EdF'b08bv* b+ 'dF0d6'b 'dF'cv7df'c-J",
439     "uploadLessons": "c Ac' " /c Hc2"Å
440     "growth": "bvDdfEd, HbvDc AbvGd;)"Å
441     "support": "bvDb09dR HbvDc 3bv&dB"Å
442     "outcomes": "b;-d&B bvDdV.c ,bv*",
443     "curriculumMatrix": "dv5d Hd ) bvDdVfEdv,",
444     "accreditation": "bvDbv9b;Ebv/ bvDb6Cbv/d;Ed0"Å
445     "analytics": "bvDb;-dFJdF'b0"Å
446     "aiGovernance": "b0Hd6Eb' 'dF0d6'b 'dF'cv7df'c-J",
447     "people": "bvDb64bæ'cR"
448   },
449   "profileSubtitle": {
450     "admin": "dv3bFHD B 'dFEbF3c6)",
451     "coordinator": "dvFc6B bvDb+1df'dV,",
452     "teacher": "dv9dFE",
453     "student": "cv'dF(",
454     "parent": "d+Dd0 #dV1",
455     "studentLevel": "bvDdV3b;Hd' .¶ÆwFVÇ×0 r ..+ ×0 Fd&7b' .b+1b'"Å
456     "teacherDetail": "{department} . {count} dVBC 1bv*",
457     "guardianOf": "d+Dd0 #dV1 {name}"
458   },
459   "stats": {
460     "teacher": "dvDbæ5 bvDb;/c Jc2"Å
461     "coordinator": "dvDbæ5 bvDb+1df'dV,",
462     "admin": "dvDbæ5 bvDdV$c63b'"Å
463     "parent": "dvDbæ5 b;Bb0E bvDcvAdB"Å
464     "classes": "dVBC 1bv*",
465     "toGrade": "b+ 'df*c+!c 'dF*d&Jd;E",
466     "programs": "b+1bvEbÅ"Å
467     "belowTarget": "b0Hdb 'dFEc6*dv/d "Å
468     "learners": "dv*c-DdVJdb"Å
469     "activeAccounts": "df4cr"Å
470     "onTrack": "c-Dd' 'dFEc6'c "Å
471     "needsAttention": "d;-b;!'bÅ 'dv*dV'dV'd'2"Å
472     "childProgress": "b;Bb0E bvDcvAdB"
473   },
474   "emptyNotifications": {
475     "title": "dF' b;HbÆ/ bv4c-'c 'b0"Å
476     "description": "b6Fb0 9dFI bv7dF'c' (d6D cFJb "
477   },
478   "groupLabel": {
479     "today": "bvDd;HdR"Å
480     "earlierThisWeek": "d J d+Bb0 3bv(d" Edb Gc ' bvDb63b+Hc'"Å
481     "older": "b6Bb0E"
482   }
483 },
484 "notificationsCta": {
485   "viewGrade": "c-1cb 'dF/c ,b'"Å
486   "openAssignment": "d *b0 'dF*d6Dd!A",
487   "viewBadge": "c-1cb 'dF4bv1b'"Å
488   "viewStreak": "c-1cb 'dF3dF3dF)",
489   "viewProgress": "c-1cb 'dF*d&/dR"Å
490   "viewLeaderboard": "c-1cb Dd+-b' 'dFEb;5b01d;F",
491   "viewHabits": "c-1cb 'dF9bv/bv*",
```

```
492 "viewAssignment": "c-1cb 'dF*d6Dd!A",
493 "viewAll": "c-1cb 'dFCdB"
494 },
495 "studentRailFallback": {
496 "label": "c&.dR 'dF*c-DdR"Å
497 "title": "d†'cVD bvDb!BbøE",
498 "streak": "bvDc6Dc6Db' 'dF-bvDd!)",
499 "level": "bvDdV3b!Hd' 'dF-bvDd¢"Å
500 "cta": "bvAb!- cVAb0) bvDd!HdR"
501 },
502 "tour": {
503 "takeTour": "bv(b0# bvDbÆHdF) bvDb!9c Jd Jb'"Å
504 "back": "c ,d†9"
505 "close": "bv:dF'd""Å
506 "finish": "bvFdv'b "Å
507 "next": "bvDb!dFJ",
508 "open": "d *b0 'dF-d†'c "Å
509 "skip": "b!.cvJ bvDbÆHdF)",
510 "student": {
511 "step1": {
512 "title": "dV1b0(bvK b†C d J dFHB0*d2"Å
513 "content": "dvødr Fd&7b' 'df7dF'd&C. c6*bÆ/ bvDbV4c-'c 'b¢ HdFbBv7 bvDbæ(c ) d†3dF3dF) bvDb6JbvE bvDdV*b! 'dFJb' Gdf' d J bvDb69d
514 },
515 "step2": {
516 "title": "bvDb!Fd&D",
517 "content": "bvFb!BdB (d!F bvDdVBC 1bv* d†dFEbæ7cr HbvDd!HdVJbv* d†Dd†-b' 'dF5b0'c ) dVF bvDcF1d!7 bvDbÆ'df(d¢â"
518 },
519 "step3": {
520 "title": "b!-d!) bvDd!HdR"Å
521 "content": "b!1b0Jb, 4bæ5d¢ 3c Jc' Hb6GdR .cvHb!C bvDb! 'dFJb' Ad¢ (cv'd&) bvDb!1b0Jb, Gc G."
522 },
523 "step4": {
524 "title": "b6GdR %b05bv!bv*d2"Å
525 "content": "b! 'b†9 dfBbv7 bvDbæ(c ) d†dFEc6*d†I d†dF3dF3dF) d†dF9bv/bv* d J dFEb0) d†b0/b'â"
526 },
527 "step5": {
528 "title": "bvDc-'b0'b¢ 'dFJd†Ed!)",
529 "content": "b6CdVD b!3bÆJdB 'dF/bæHdB HbvDbV1c6'dB HbvDd!HdVJb' HbvDd&1bv!b' CdB Jd†E dF*b0Bd!B d!HdR Eb¶'dFJ."
530 },
531 "step6": {
532 "title": "dfBbv7 bvDbæ(c ) d†dF3dF'c6D",
533 "content": "cF!dv/ dfBbv7 bæ(c *d2 *c *d 9 dF-c†JbvK'Å Hb0'd 8 c-Dd' 3dF3dF*d2 Jd†EbvK b†9b0 Jd†E."
534 },
535 "step7": {
536 "title": "bvDdVDd 'dF4bæ5d¢ HbvDbV9b0'b0'b¢"Å
537 "content": "b†/e D bvDdF:b' #d, 'dFEc†Gc #d, 3bÆQdB 'dF.c HbÅ Edb Bbv&dV) bvDdVDd 'dF4bæ5d¢ Ad¢ 'dF#c-Dd'â"
538 }
539 },
540 "teacher": {
541 "step1": {
542 "title": "dV1b0(bvK b†C b6Jdv' bvDdV9dFE",
543 "content": "dvødr :c Ab' *b0CdVC. bvDbV4c-'c 'b¢ HbvDcvDbv( d†dFFcF'cr 'dFEb†'cF1 dvFbr Ad¢ 'dF#c-Dd'â"
544 },
545 "step2": {
546 "title": "b6/d†'b!C",
547 "content": "bvAb!- bvDdVBC 1bv* d†dFHbv,b†'b¢ HbvDb!5b0Jb0 HbvDdV.c ,bv* d†dF*b0Dd!Dbv* dVF bvDcF1d!7 bvDbÆ'df(d¢â"
548 },
549 "step3": {
550 "title": "df8c ) c61d!9b' 9dFI bvDd 5dR"Å
551 "content": "cF!dv/ bvDb!5b0Jb0'b¢ 'dFEc-Dd&) d†b!,bvGbv* bvDb!-cvJdB HbvDcvDbv( bvDdV9c 6d!F dFDbæ7c Ad¢ DdV-b'â"
552 },
553 "step4": {
554 "title": "b!9c Jd Ebæ1bÆ'b¢ 'dF*c-DdR"Å
555 "content": "b6FcF& dV.c ,bv* bvDdVBC 1 dV*dV'cFJb' Ec' Ec6*d†Jbv* b†Dd†E - b!/c-E d6D bvDdV9bvJd!1 d†dF*d&'c Jc â"
556 },
557 "step5": {
558 "title": "b†Fbv! dV9bvJd!1 bvDb!Bd!JdR"Å
559 "content": "bv3b0( dV9bvJd!1 bvDb!Bd!JdR Hc (cvGbr (dV.c ,bv* bvDdVBC 1`Å +dR #c-/ bv3b!.b0'dVGbr 9b†1 bvDd†'bÆ(bv*."
560 },
561 "step6": {
562 "title": "d&'bfEb' 'dF*cV-d!-",
563 "content": "b!5dB 'dF*c6Dd!Ebv* dvFbr -c6( bvDb6HdFHd!). dV3d†/bv* bvDb! :c Jb' 'dF1bv,c-) b†dF0d6'b 'dF'cV7df'c-J b!3c Qc' 9dV
564 },
565 "step7": {
566 "title": "bvDdF:b' HbvDdVDd 'dF4bæ5d¢"Å
567 "content": "b†/e D b†Jdb 'dF9c (d!) d†dF%df,dFJc&Jb' Hbv/bæD bVDd' EdFAd2 'dF4bæ5d¢ Edb 'dF#c-Dd'â"
568 }
569 },
570 "coordinator": {
571 "step1": {
572 "title": "dV1b0(bvK b†C b6Jdv' bvDdVFc6B",
573 "content": "b!(b0# dV1bvBb†) bvDb†1bvEbÅ Gdf'. bvDbV4c-'c 'b¢ HbvDbV,c 'b 'b¢ 'dF3c Jc-) d J bvDb69dFI."
574 },
575 "step2": {
576 "title": "b6/d†'b¢ 'dF(c 'dV,",
577 "content": "b6/c 'dF(c 'dV, d†Ebæ1bÆ'b¢ 'dF(c FbvEbÅ HbvDdVBC 1bv* d†.cv7 bvDb!-c6Jdb 'dFEc6*dV1 dVF bvDcF1d!7 bvDbÆ'df(d¢â"
578 },
579 "step3": {
580 "title": "cV-b' 'dF(c FbvEbÅ"Å
581 "content": "d ,d†'b¢ 'dF*c!7d!) d†'b!,bvGbv* bvDb!-cvJdB HdV$cF1bv* bvDbæ7c 9b†1 b†1bvEbÆC."
582 },
583 "step4": {
584 "title": "dV5d Hd ) bvDdVdV",
585 "content": "bv7e Dc' 9dFI b!:cvJb' Ebæ1bÆ'b¢ 'dF(c FbvEbÅ 9b†1 bvDdVBC 1bv* d†-b0/ bvDd ,d†'b¢ HbvDb!/bv.dF'b¢ (c61c-)."
586 },
587 "step5": {
588 "title": "bv/bv1b' Ebæ1bÆ'b¢ 'dF(c FbvEbÅ"Å
589 "content": "b6FcF& dV.c ,bv* bvDb†1df'dV, d†-c Qc Gbr Hbv1b†7dv' b†Ebæ1bÆ'b¢ 'dFEbF3c6)."
590 },
591 "step6": {
592 "title": "bvDdF:b' HbvDdV8dv1",
593 "content": "b†/e D b†Jdb 'dF9c (d!) d†dF%df,dFJc&Jb' #d, Ac-QdB 'dFHcf9 bvDb0'd6F d J b6J d†Bbæâ"
594 },
595 "step7": {
```



```
596         "title": "d&'bEb' 'dEdFA bVdCf.cVJ",
597         "content": "bvDdVdd 'dF4bæ5d¢ HbvDb|AcfJdF'b¢ Hb|3bÆJdB 'dF.c HbÂ Ad¢ 'dFBbv&dV) bvDc-Dd†Jb' 'dFJc61d'â"
598     }
599 },
600     "parent": {
601         "step1": {
602             "title": "dV1b0(bvK b†C b6Jdv' bVdD†'dF/",
603             "content": "b|'b†9 b|Bb0E cvAdFC c-F d&1b,â 'dF%cF9bv1bv* d†'dF*dF(d|Gbv* d J bVDb69dFI."
604         },
605         "step2": {
606             "title": "dV1d62 bVDb63c )",
607             "content": "bv7e Dc' 9dFI bVDb6(df'b HbvDb|Bb0E d†'dF-cfHc HbvDc 3d†E d†'dF1c6'bfd dVF bVdCf1d|7 bVDbÆ'df(d¢â"
608         },
609         "step3": {
610             "title": "df8c ) c61d|9b' 9db 'dF7d D",
611             "content": "dV$cf1bv' c61d|9b' 9b†1 bÆEd|9 b6(df'bfc bVdDv1b| (cvJdb r 'dF-cfHc HbvDb01bÆ'b¢ HbvDc6Dbv3dB HdV$cf1bv* bVDbæ7c â"
612         },
613         "step4": {
614             "title": "bvDb6(df'b 'dFEc *b†7d†F",
615             "content": "b†/e D b†Jdb 'dF#b†Fbv| dF1bFJb' Dd†-bv*dvE bVdD 1b0Jb' (bvDb|AcvJdBâ"
616         },
617         "step5": {
618             "title": "bvDc 3d†E d†'dFAd†'b|Jc "Â
619             "content": "bv7e Dc' 9dFI bVdD Hbv*d|1 d†-bVDb' 'dF/d 9 d†-dVQdB 'dF%d|5bvDbv* d J b6J d†Bb¢â"
620         },
621         "step6": {
622             "title": "bvDdV.cv7",
623             "content": "b|'b†9 bVdD†'bÆ(bv* d†'dF'dv*b0'df'b¢ 'dFBbv/dV) dF7d Dd2 dF*bæ7d|7 dV3b†BbvK."
624         },
625         "step7": {
626             "title": "d&'bEb' 'dEdFA bVdCf.cVJ",
627             "content": "bvDbV9b0'b0'b¢ HbvDdF:b' Hb|3bÆJdB 'dF.c HbÂ Ad¢ 'dFBbv&dV) bvDc-Dd†Jb' 'dFJc61d'â"
628         }
629     },
630     "admin": {
631         "step1": {
632             "title": "dV1b0(bvK b6Jdv' bVdDv3bFHdB"Â
633             "content": "b6/d†'b¢ 'dF*b0CdR 9dFI dV3b|Hd' 'dFEbF3c6) b|(b0# dvFbrâ 'dF%cF9bv1bv* d†'dF*dF(d|Gbv* bVDb0Jb' Ad¢ 'dF#c-Dd'â"
634         },
635         "step2": {
636             "title": "b6/d†'b¢ 'dFEc6$d†D",
637             "content": "bvDdV3b|.b0Ed†F d†'dF(c 'dV, d†'dF%-/bv/bv* d†3bÆDbv* bVDb|/d&Jd" HbvDb|-dFJdF'b¢ Ad¢ 'dF4c Jcr 'dF,bVb†J."
638         },
639         "step3": {
640             "title": "cv-b' 'dFEbF3c6)",
641             "content": "bv,dV'dfJ bVdDv3b|.b0Ed|F d†'dFEd&1c 'b¢ 'dFFcF7b' HdV*d†3cr 'dF*b05d|D d†9b0/ bVdDv9c 6d|F dFDbæ7c Ad¢ DdV-b'â"
642         },
643         "step4": {
644             "title": "bvDbV,c 'b 'dF1bfJc6J",
645             "content": "b66d Ec6*bæ/dVJdb #d, #df4bb (c 'dV, b6H cF:e D c-EdFJbv* bv3b|Jc 'b0 ,dV'c-Jb' Edb 1b63 bVdDFHb0)."
646         },
647         "step5": {
648             "title": "b†7bvBbv* bVDb6Bc6'dR"Â
649             "content": "d6D b†7bvBb' Gdf' b|Ab|- c-1cf'd2 #c-Ed" r 'dFEc6*bæ/dVHdb -c6( bVDb0Hc HbvDdf4bv7 bVDb0/d|+ d†Ec6'c 'dF*b0Bd|B."
650         },
651         "step6": {
652             "title": "bvDdF:b' HbvDdV8dv1",
653             "content": "b†/e D b†Jdb 'dF9c (d|) d†'dF%df,dFJc&Jb' Hd 9e D bVdD†6c' 'dF/bvCdb Ad¢ #d¢ Hd&.*"
654         },
655         "step7": {
656             "title": "d&'bEb' 'dEdFA bVdCf.cVJ",
657             "content": "bvDdVdd 'dF4bæ5d¢ HbvDb|AcfJdF'b¢ Hb|3bÆJdB 'dF.c HbÂ Ad¢ 'dFBbv&dV) bvDc-Dd†Jb' 'dFJc61d'â"
658         }
659     }
660 },
661     "theme": {
662         "label": "bvDdV8dv1",
663         "light": "d 'b|.-",
664         "dark": "b0'd6F",
665         "system": "b|Dd&'bfJ"
666     },
667     "auth": {
668         "signedOut": "b|E b|3bÆJdB 'dF.c HbÂ (df,bv-",
669         "signOut": "b|3bÆJdB 'dF.c HbÂ"
670     },
671     "common": {
672         "error": "b0/b2 .cv#. d|1bÆI bVdDv-bVHdF) dV1b' #bæ1d'â"Â
673         "uploading": "bÆ'c J bVdC Ac'âââ"Â
674         "cancel": "bVdC|'b "
675     },
676     "weekPicker": {
677         "weekOf": "b63b†Hc'"Â
678         "selectWeek": "bv.b|1 b63b†Hc-'d2"
679     },
680     "roleProfile": {
681         "me": "b6Fbr"Â
682         "subtitle": "dvHd|*d2 HdV3bv-b' 9dVdd2 Hb|AcfJdF'b|C d†-c6'b†C.",
683         "fallbackName": "dV3b|.b0E",
684         "noEmail": "dF' d|HbÆ/ b†1d|/ bVdD6*c HdfJ",
685         "editProfile": "b|9b0JdB 'dEdFA bVdCf.cVJ",
686         "contact": "b|Hbv5dB"Â
687         "workspace": "dV3bv-b' 'dF9dVD",
688         "workspaceDescription": "bvAb|- bVDb6/d†'b¢ 'dF#d6+c 'c *b†'cv'd2 (b0Hc C.",
689         "appearance": "bvDdV8dv1",
690         "appearanceDescription": "bv.b|1 dv8dv1 bV/d 'd|2c 'dFEdf'c6( dFC.",
691         "security": "bvDb6EbvF d†'dFhcVHdB"Â
692         "securityDescription": "b6/c -dV'd|) bVDb03bv( d†'dF%cF9bv1bv*.",
693         "changePassword": "b|:d|Jc CdFEb' 'dFEc Hc "Â
694         "open": "d *b0"Â
695         "notifications": "dV1d62 bVDbV4c-'c 'b¢"Â
696         "statusActive": "df4cr"Â
697         "statusInactive": "c|Jc FcF7",
698         "notSet": "c|Jc Eb0/b0"Â
699         "admin": {
```

```
700 | "role": "dv3bFHdB 'dFEbF3c6)",
701 | "scope": "dv3bv-b' 9dVD bvDdV$c63b'"Å
702 | "users": "bvDdV3b|.b0EdtF",
703 | "active": "bvDdf4cvHdb"Å
704 | "programs": "bvDbt1bvEbÅ"Å
705 | "courses": "bvDdVbc 1bv*",
706 | "overview": "bvDdV$c63b' HbvDdt5dtD",
707 | "overviewDescription": "df7bvB dv$c63b!C dt5dF'b0Jbv*d2 'dF%b0'c Jb'å"Å
708 | "accountStatus": "b0'df) bvDb03bv(",
709 | "institutionId": "dv9c Qd 'dFEbF3c6)",
710 | "accessLevel": "dv3b!Hd' 'dFHcVHdB"Å
711 | "fullAccess": "dv3bFHdB 'dFEbF3c6)",
712 | "institutionPage": "cVAb0) bvDdV$c63b'"Å
713 | "institutionConnected": "dv3bv-b' 9dVD bvDdV$c63b' Eb!5dF)",
714 | "learners": "bvDdV*c-DdVHdb"Å
715 | "teachers": "bvDdV9dFedtF",
716 | "institutionSettings": "bv9b0'b0'b0' 'dFEbF3c6)",
717 | "bilingual": "b!Fbv&dc 'dFdc!() (bvDc-1b!Jb' 0 'dF%df, dFJc&Jb'/'Å
718 | "bilingualDescription": "b!|.cvJcr Edb 'dFJdVJdb %dFI bvDd!3bv1 dtEb0*dtI bt'dFdc!*d!F",
719 | "enabled": "dVAc-QdB"Å
720 | "thresholds": "b0'df/ bvDb!-cVJdB"Å
721 | "thresholdDescription": "dVEb!'c" fR r Ed01cfM 70 . df'dVM 50",
722 | "configure": "b!Gd!&b'"Å
723 | "parentReports": "b!Bbv1d!1 dfEd, #dtDd!'b 'dF#dVHc "Å
724 | "parentReportsDescription": "dVDb05 b63b!Hc-J dFdc AbvGd!) dt'dF*d&/dR"Å
725 | "platformPreferences": "b!AcfJdF'b0' 'dFEdf5b'"Å
726 | "notificationPreferences": "b!AcfJdF'b0' 'dF%cf9bv1bv*",
727 | "notificationDescription": "bv.b!1 b6-b0'b2 'dFEbF3c6) bvDb!J b!5dB %dFI bt!d!/d2å"Å
728 | "newRegistrations": "b!3b0JdF'b0' 'dFEc6*b0/dVJdb 'dF, b0/",
729 | "newRegistrationsDescription": "b!FbtJdr 9df/ bvFcfEbvE b03bv( b0/d!/ bvDd' 'dFEbF3c6)",
730 | "securityAlerts": "b!FbtJdv'b0' 'dF#dV'db Hb!3b0JdB 'dF/b0HdB"Å
731 | "securityAlertsDescription": "b6-b0'b2 'dF-c6'b, HbvDdV5bv/d&) bvDdVgDv)",
732 | "weeklySummary": "dVDb05 bvDdV$c63b' 'dF#c6(d!9dc"Å
733 | "weeklySummaryDescription": "b!Bc Jc *cF:d!Ddc #c6(d!9dc Edt,c""Å
734 | "quotaWarnings": "b!-c Jc 'b0' 'dF*b02d!F dt'dF-cv)",
735 | "quotaWarningsDescription": "b!FbtJdv'b0' 'dF3c-) d&(dB *b6+c 'dF.b0Ebv*",
736 | "permissions": "bvDb0Hc HbvDcVDbv-d!b0"Å
737 | "manageUsers": "bv/bv1b' 'dFEc6*b0/dVJdb HbvDb6/dt'c "Å
738 | "configureInstitution": "b!Gd!&b' %c-/bv/bv* bvDdV$c63b'"Å
739 | "setAiPolicy": "cf(cr 'c6*d0bvdD!) bvDc Cbv! bvDbv5cvFbv9d0c Hc6Jbv3bv*dr"Å
740 | "viewAuditLogs": "c-1cb 'dF*b0Dd!Dbv* dt3b0Dbv* bvDb!;/d&Jd"Å
741 | "manageBilling": "bv/bv1b' 'dFAdt*c ) dt'dF*d6'dVDbv*",
742 | "governanceShortcuts": "bv.b!5bv1bv* bvDb0Hd6Eb'"Å
743 | "aiPolicy": "bv3b!BdF'dFJb' 'dF0d6'b 'dF'cv7df'c-J dt3d!'c6'b!G",
744 | "auditLog": "c6,dB %b01bv!bv* bvDc Cbv! bvDbv5cvFbv9d0c"Å
745 | "memoryPrivacy": "bvDc 'd61b' HbvDb05dt5d!)",
746 | "viewAsUser": "bvDc-1cb Cdv3b|.b0E",
747 | "audited": "b0'cf9 dFDb!;/d&Jd"
748 | },
749 | "teacher": {
750 | "role": "dv9dFE",
751 | "scope": "dv3bv-b' 9dVD bvDb!/c Jc2"Å
752 | "students": "bvDcVDbv(",
753 | "toGrade": "bt'df*ct'c 'dF*cv-d!-",
754 | "graded": "b!E b!5b0Jb0Gbr"Å
755 | "attainment": "bvDb!-cVJdB"Å
756 | "overview": "bvDdVdD 'dF#d6'b0JdVJ",
757 | "overviewDescription": "dvHd!*d2 'dF*b01d!3d!) dt(d!'df'b!C bvDb6Cbv/d!Ed!)." ,
758 | "department": "bvDd&3dR"Å
759 | "designation": "bvDdV3dVI bvDdt8d!Adc"Å
760 | "academicRank": "bvDc *bt) bvDb6Cbv/d!Ed!)",
761 | "highestDegree": "b69dFI dV$dvd",
762 | "viewPublicProfile": "c-1cb 'dFEdFA bvDc-'dR"Å
763 | "classes": "bvDd 5dtD",
764 | "courses": "bvDdVbc 1bv*",
765 | "clos": "dfHbv*b0 'dFEd&1c "Å
766 | "impact": "b6+c 'dF*b01d!3",
767 | "avgMastery": "dv*d!3cr 'dF%b!BbvF",
768 | "gradingCompletion": "bvCb!EbvD bvDb!Bd!JdR"Å
769 | "atRisk": "cvDbv( bt-bv,b' DdF/c-E",
770 | "aiAutonomy": "bv3b!BdF'dFJb' 'dF0d6'b 'dF'cv7df'c-J dFACvHdFC",
771 | "reviewControls": "dv1bv,c-) bvdCfHbv(cr"Å
772 | "autonomyDescription": "A2 . d!Ed6F dFdc Cbv! bvDbv5cvFbv9d0c %c-/bv/ bvDbv,c 'b 'b! 'dFCdcF b!HbvAd" 9dFI d6D b!:/d!Jc Bb!D b!7b.",
773 | "notificationPreferences": "b!AcfJdF'b0' 'dF%cf9bv1bv*",
774 | "notificationDescription": "bv.b!1 bv4bv1bv* bvDb!/c Jc2 'dF*d0c *cVD bvDd' (c Jb0c.",
775 | "atRiskAlerts": "b!FbtJdv'b0' 'dF7df'b, 'dFEc-1cfJdb DdF.cv1",
776 | "atRiskAlertsDescription": "bv4bv1bv* c-Fb0Ebr Jb0*bv, bvDdV*c-DdR %dFI bvDb09dR"Å
777 | "newSubmissions": "b!3dFJdV'b0, b0Jb0) dFDb!Bd!JdR"Å
778 | "newSubmissionsDescription": "b!FbtJdv'b0' 9df/ b0.d!D b69dV'dB ,b0Jb0) bvDd' Bbv&dV) bvDb!Bd!JdR"Å
779 | "handoffRequests": "cvDbt!b0 *b0Hd!D bvdDv9dFE bvDc Cdc"Å
780 | "handoffDescription": "b!FbtJdv'b0' 9df/ b!5c-Jb0 'dFEc-DdR 'dF0d6J bvDd!C",
781 | "weeklySummary": "dVDb05 bvDd 5dB 'dF#c6(d!9dc"Å
782 | "weeklySummaryDescription": "dVDb05 b63b!Hc-J c-(c AcvHdFC",
783 | "myClasses": "d 5dtDdc"
784 | },
785 | "parent": {
786 | "role": "dt'dF/ / dtDdc #dV1",
787 | "scope": "dtDdc #dV1 {{names}}",
788 | "noChildren": "dF' d!Hb0/ b6(df'b Ec *bt7dtF",
789 | "children": "bvDb6(df'b "Å
790 | "courses": "bvDdVbc 1bv*",
791 | "attainment": "bvDb!-cVJdB"Å
792 | "deadlines": "bvDdVHbv9d!/," ,
793 | "overview": "dt5dtD bvDb63c)",
794 | "overviewDescription": "c Hbv(cr 'dF#c61b' 'dFEdt+d&) dt5dF'b0Jbv* bvDb03bv(.",
795 | "linkedChildren": "bvDb6(df'b 'dFEc *bt7dtF",
796 | "accountStatus": "b0'df) bvDb03bv(",
797 | "access": "bvDdt5dtD",
798 | "verifiedAccess": "dtDdc #dV1 dVHb!B",
799 | "contactSchool": "bvDb!Hbv5dB Ec' 'dFEb01c6)",
800 | "alerts": "bvDb!FbtJdv'b0"Å
801 | "linkedLearners": "bvDdV*c-DdVHdb 'dFEc *bt7dtF",
802 | "linkedCount": "{{count}} dV1b!(cr"Å
803 | "learnerSummary": "{{courses}} dV8c 1bv* . b!-cVJdB .! GF -00VcGx0j . bv1b!(bv7 dVHb!Qd""Å
```

```
804 | "linkAnotherChild": "c (cr 7d D b&.c "Ã
805 | "feesPayments": "bvDc 3d†E d†dFEbðAd†9bv*",
806 | "announcements": "bvDbv9dF'df'b¢"Ã
807 | "privacy": "bvDbæ5d†5d†) d†Ebr JdVCdFc c $d†*dr"Ã
808 | "details": "bvDb†Abv5d†D",
809 | "growthShared": "dVDbæ5bv* bvDdfEd, HbvDc AbvGd†)",
810 | "shared": "dv4bv1d2"Ã
811 | "rawScores": "bð1bÆ'b¢ 'dF'bæ*b†'c 'b¢ 'dF.bvE",
812 | "notShared": "c†Jc EcF'c C",
813 | "privateJournal": "bvDd†HdVJbv* bvDbæ'cV)",
814 | "private": "bæ'cR (bvDdV*c-DdR"Ã
815 | "notificationPreferences": "bvDbv4c-'c 'b¢"Ã
816 | "notificationDescription": "bv.b†1 b†-bðJb¶'b¢ 'dF#c61b' 'dF*d¢ *cVD bVDd' (c JbðC.",
817 | "weeklyGrowth": "d&5b' 'dFFdVH bvDb63b†HC-Jb'"Ã
818 | "weeklyGrowthDescription": "dVDbæ5 b†BbðE d†1d62 c-Dd' Fd&'cr 'dFBd†)",
819 | "wellbeingAlerts": "b†Fb†Jdv'b¢ 'dF1d 'dvJb' Ad&7",
820 | "wellbeingAlertsDescription": "bv4bv1bv* bvDc AbvGd†) bVDdVgDv) d Bcr"Ã
821 | "celebrate": "bvDbv-b†Abv! b†'dF*bð3db"Ã
822 | "celebrateDescription": "b†-bðJb¶'b¢ 'dF*d&/dR 'dF%d†,bv(d¢ HbvDbvFbÆ'c&'b¢"
823 | }
824 | },
825 | "avatar": {
826 | "title": "bvDcVHC ) bvDcF.cVJb'"Ã
827 | "description": "bv1d 9 cVHC ) dF*bæ5d†5 dVDD C bvDcF.cVJ.",
828 | "current": "bvDcVHC ) bvDbð'dFJb'"Ã
829 | "preview": "dv9bvJdf)",
830 | "dragDrop": "bv3bð( d†#d Db¢ 5d†1b' Gdf'",
831 | "formats": "PNG b6H JPG b6H WebP - bvDbð/ bvDb6BcVI 2 dVJc†'b†'d†*",
832 | "selectFile": "bv.b†1 dVDD 'd2"Ã
833 | "upload": "c Ac' 'dF5d†1b'"Ã
834 | "uploadSuccess": "b†E b†-bðJb² 'dF5d†1b' 'dF4bæ5d†)",
835 | "invalidType": "d†1bÆI c Ac' 5d†1b' (cVJc†) PNG b6H JPG b6H WebP.",
836 | "fileTooLarge": "bvDdVDD Cb†Jc ,bð'd²â 'dF-bð 'dF#d&5d' " Ed†:bv(bvJb¢â"
837 | },
838 | "captcha": {
839 | "devMode": "d6'b†*cF' (d†6c' 'dF*cVhd†1 - dFE d†*dR *c-Jd†F VITE_CAPTCHA_SITE_KEY)",
840 | "bypass": "b†,bvHc""
841 | },
842 | "profile": {
843 | "myProfile": "dVDD J bvDcF.cVJ"
844 | },
845 | "greeting": {
846 | "morning": "cV(bv- bvDbæJc "Ã
847 | "afternoon": "dv3bv! bvDbæJc "Ã
848 | "evening": "dv3bv! bvDbæJc "Ã
849 | "there": "dvFbvC"
850 | },
851 | "tos": {
852 | "title": "cF1d†7 bvDbæ/dv)",
853 | "description": "d†1bÆI dv1bv,c-) cF1d†7 bvDbæ/dv) d†3d†'c6) bvDbæ5d†5d†) d†'dFEd†'d Bb' 9dFJdv' dFDdV*bv(c-) d J bv3b†.bð'dR 'dFEdf
854 | "checkboxLabel": "dFBbð Bc #b¢ Hb6HbvAd" 9dFI",
855 | "termsLink": "cF1d†7 bvDbæ/dv)",
856 | "and": "d,"Ã
857 | "privacyLink": "c6Jbv3b' 'dF.cVHCvJb'"Ã
858 | "acceptButton": "d&(d†D",
859 | "acceptSuccess": "b†E d&(d†D cF1d†7 bvDbæ/dv)",
860 | "acceptError": "d 4dB Bb†HdB 4c Hcr 'dF.bðEb'â Jc ,d' 'dFEbð'd†Db' Ec ) b6.c I."
861 | },
862 | "notificationsGroup": {
863 | "askTutor": "bv3b6D bvDdV9dFE bvDc Cd¢"
864 | },
865 | "admin": {
866 | "badges": {
867 | "title": "b†9c Jd 'b¢ 'dF#d†3dV)",
868 | "description": "d&HbvDb, #d†3dV) c-Dd' Ec6*d†I bvDdV$c63b' Ec' *bð1bÂ Eb†9bð/ bvDdV3b†Hd†'b¢â"Ã
869 | "spotlight": "bÆ/d†D bvDb6Hc6Eb' 'dFEdVJc&)",
870 | "new": "d†3bvE bÆ/d†/",
871 | "loadError": "b†9c 1 b†-dvJdB *c-1d†Abv* bvDb6Hc6Eb'â"Ã
872 | "empty": "dF' b†HbÆ/ b†9c Jd 'b¢ #d†3dV) b†9bðâ #df4bb #d†D d†3bvE dFDdV$c63b'â"Ã
873 | "uncategorized": "c†Jc EcVfd "Ã
874 | "archivedLabel": "dv$¢ 4d "Ã
875 | "noDescription": "dF' d†HbÆ/ d†5d "Ã
876 | "archive": "b61cFAb'"Ã
877 | "restore": "bv3b†9bv/b'"Ã
878 | "archived": "b†Eb¢ #c 4d ) bvDd†3bvE",
879 | "restored": "b†Eb¢ 'c6*c-'bð) bvDd†3bvE",
880 | "deleted": "b†E bð0d *c-1d†A bvDd†3bvE",
881 | "updated": "b†E b†-bðJb² *c-1d†A bvDd†3bvE",
882 | "created": "b†E bvFcF'b *c-1d†A bvDd†3bvE",
883 | "missingInstitution": "bð3bv(d2 :d†1 dv1b†(cr (dv$c63b'â"Ã
884 | "editTitle": "b†9bðJdB *c-1d†A bvDd†3bvE",
885 | "createTitle": "bvFcF'b *c-1d†A d†3bvE",
886 | "formDescription": "bð/bð 4d6D bvDd†3bvE d†4c Hcr 'dF*bð1bÂ 'dF(c HdF2d¢ HbvDd 6d¢ HbvDc Gb†J.",
887 | "emoji": "bvDc Ec" 'dF*c-(d†1d¢"Ã
888 | "name": "bvDbv3dR"Ã
889 | "key": "dvAb†'bð 'dFHc6'dR"Ã
890 | "category": "bvDd &b'"Ã
891 | "badgeDescription": "bvDd†5d "Ã
892 | "tierConditions": "cF1d†7 bvDdV3b†Hd†'b¢"Ã
893 | "bronze": "b†1d†Fc&J",
894 | "silver": "d 6d¢"Ã
895 | "gold": "c Gb†J",
896 | "conditionPlaceholder": "cVA bvDbð/ bvDd&'b†D dFDd&Jbv3",
897 | "singleTier": "dv3b†Hd' Hbv-bð r DdR Jb†E bv9bð'bð 'dF4c 7",
898 | "create": "bvFcF'b 'dFHc6'dR"Ã
899 | "deleteTitle": "bð0d *c-1d†A bvDd†3bvEað"Ã
900 | "deleteDescription": "c6JbF/d¢ Gc ' bVDd' -c A d&'dF( d†3bvE bvDdV$c63b' Fdv'b†FJbvK. dFF b†*dR %c&'dF) bvDb6Hc6Eb' 'dFEd6*c6(b' 3I
901 | },
902 | "governance": {
903 | "title": "bðHd6Eb' 'dFðd6'b 'dF'cv7df'c-J",
904 | "auditLog": "c6,dB 'dF'bðBd†B bvDd6'dVD",
905 | "description": "b†8dB 'dFEd†'d Bb' 'dF(cF1d†) dvJ bvDbð/ bvDb69dFI dFDbV,c 'b 'b¢ 'dF-c6'c6). b†3b†Fbð Ed&'d†Jc2 'dF'c6*bæ/bvE d†
906 | "autonomyCeiling": "bvDbð/ bvDb69dFI dFDbv3b†BdF'dFJb' Ad¢ 'dFEbF3c6)",
907 | "roadmap": "c6Jbv3b' DdFBC 'b ) d Bcr r 6dVF bæ'c 7b' 'dF7c Jd"Ã
```

```
908 | "roadmapNote": "b!.c&Jdb 3d!'c6'b¢ .bv5b' (bvDdV$c63b' :d!1 dV*bv- b†9bôâ Jc†Gc 6bv(cr 'dFEdf*bÂ 'dF-bvDd¢ (cFABvAd!) d†Dbr JdVc
909 | "currentPolicy": "cf'b†7 bvDdVfCv) bvDdô'dfJ: A2 - dF' d!°cv1d 'dF0d6'b 'dF'cv7df'c-J bVDbr (c-/ dVHbvAd&) b†4c Jb'â HdF' d!°dR
910 | "loadError": "b!9c 1 b!-dVJdE Ed&d!Jc2 -d†CdV) bvDc Cbv! bVDbv5cvFbv9d¢â"Â
911 | "usage": "bv3b! .bô'dR 'dFec-DdR 'dF0d6J dv0br 'dF4dv1",
912 | "requests": "bvDcvDb†'b¢"Â
913 | "loggedRequests": "bv3b!/c-'b 'b¢ FdVHc , bvDdV9dFE bvDc Cd¢ 'dFec6,dF)",
914 | "successRate": "dv9bôD bVDdf,bv-",
915 | "successful": "df'b£-",
916 | "tokens": "bvDc Ed†2",
917 | "monthToDate": "dVFc (bô'd!) bvDcFGc "Â
918 | "latency": "dv*d†3cr 2dVF bvDbv3b!,bv(b' "Â
919 | "responseTime": "c&Edb 'c6*b£b†) bVDbæ'bôE",
920 | "models": "bvDdfEbvdôÂ 'dFec6*bæ/dV)",
921 | "noUsage": "dFE d!°dR *c6,d!D b6J bv3b!/c-'b 'b¢ DdfEd†0bÂ 'dFec-DdR 'dF0d6J dv0br 'dF4dv1.",
922 | "modelUsage": "{(requests)} cvDb, r .-F0¶Vc7×0 1dv2",
923 | "quality": "dv$cF1bv* b£Hbô) bvDc Cbv! bVDbv5cvFbv9d¢"Â
924 | "suggestionAcceptance": "d&(d†D bVDvbBb!1bv-bv*",
925 | "suggestionsReviewed": "b!Eb¢ Ec 'b£9b' .¶6÷VcG×0 'd&*c 'bô"Â
926 | "predictionAccuracy": "bôBb' 'dF*d†f(bB"Â
927 | "validatedPredictions": "{count} b!Fb†S b!E bVDb!-d&B dVfDr"Â
928 | "draftAcceptance": "d&(d†D bVDdV3d†/bv*",
929 | "feedbackDrafts": "{count} dv3d†/b' EdF'bô8bv*",
930 | "liveData": "b†JbvFbv* bVDdV$c63b' 'dFAC-Dd!)",
931 | "noFabricatedMetrics": "dF' b!0c-1cb #c BbvE bæ'cv) b†'dFFdVHc , bVDd6HdFJ d Bcrâ"Â
932 | "perAction": "dv' d!Ed6F dFDC Cbv! bVDbv5cvFbv9d¢ Ac-Ddr (bô3b, 'dF%b£1bv!",
933 | "action": "bvDbv,c 'b "Â
934 | "level": "bvDdV3b!Hd' 'dF-bvDd¢"Â
935 | "hardCap": "bvDb0/ bVDd6BcVI",
936 | "memory": "c 'd61b' 'dF0d6'b , 'dF'cv7df'c-J d†'dF.cvHcVJb'"Â
937 | "review": "bvDdV1bv,c-) d†'dFec6'b Db'"Â
938 | "reviewNote": "b!0c6,dB 'dF%b£1bv!bv* bVDbv/bv1d!) d J c6,dB 'dF*bôBd!B. c6*c†Gc Ed†'d Bbv* bV,c 'b 'b¢ 'dF0d6'b 'dF'cv7df'c-J
939 | "openAudit": "d *bô 3b£D bVDb!/d&Jd""Â
940 | "levels": {
941 |   "a0": "bvDdV1bvBb†) d†'dF9c 6",
942 |   "a1": "bvDbvBb!1bv- d†°c-/bv/ bVDdV3d†/bv*",
943 |   "a2": "bvDb!Fd Jc (c-/ bVDdVHbvAd&)",
944 |   "a3": "bv,c 'b 'b¢ 'dVFb' Ec6*d&Db'"
945 | },
946 | "actions": {
947 |   "showInsights": "c-1cb 'dF1bFI d†'dFEBf4c 'b¢"Â
948 |   "suggestAction": "bvBb!1bv- bVDbv,c 'b 'dF*bvDd¢"Â
949 |   "scheduleReviews": "b£/d†Db' 'dFec 'b£9bv* bVDdV*b†'c-/b'"Â
950 |   "reorderPlan": "bv9bv/b' *c *d!( bVDbæ7b' 'dFJd†Ed!) dFDdV*c-DdR"Â
951 |   "sendStudentNudge": "bv1c6'dB *d†(d!G dFDCv'dF(",
952 |   "draftTeacherFeedback": "cVJbv:b' EdF'bô8bv* bVDdV9dFE",
953 |   "generateEvidencePack": "bvFcF'b *d&1d!1 b6H bô2dV) b6/dF)",
954 |   "sendParentCommunication": "bv1c6'dB 1c6'dF) dFHdFJ bVDd6Ec "Â
955 |   "assignGrade": "bv3df'bô /c ,b'"Â
956 |   "publishContent": "df4c Ebô*d†I b!9dFJdVJ"
957 | },
958 | "memoryItems": {
959 |   "tutorLabel": "dv-bv/b¶) bVDdV9dFE bvDc Cd£¢"Â
960 |   "tutorValue": "dv-bô/b' (df7bvB bVDd£Dc6)",
961 |   "learnerLabel": "dfEd†0bÂ 'dFEB!9dFE:",
962 |   "learnerValue": "bô'b£E d†Bbv(dB DdF*cV/d!1 d†Ad" 3d!'c6'b¢ #dV'db 'dF5d Hd "Â
963 |   "evidenceLabel": "b6/dF) bVDdV.c ,bv*",
964 |   "evidenceValue": "b6/dF) b!/d&Jd" :d!1 d&'b†Db' DdF*c!Jd!1",
965 |   "piiLabel": "d6DdV'b¢ 'dFec Hc HbvDb†JbvFbv* bVDcF.cvJb' 'dF.bvE:",
966 |   "piiValue": "dF' b!0bæ2db Ecvd&d² Ad¢ EcV'dF(bv* bVDdV9dFE bvDc Cd¢"
967 | }
968 | }
969 | },
970 | "legal": {
971 |   "eyebrow": "bvDcF$d†F bVDd&'dfHdfJb' Ad¢ VFwf-6W""Â
972 |   "lastUpdated": "b&c *bô/d!+: 1 d!FbvJc # #b"Â
973 |   "backToSignIn": "bvDc-Hbô) bVDd' *c6,d!D bVDbô.d†D",
974 |   "summary": {
975 |     "title": "dVDdæ5 b†Dc!) d†'cf-b'"
976 |   },
977 |   "terms": {
978 |     "title": "cF1d†7 bVDdæ/dV)",
979 |     "subtitle": "bvDd&Hbv9bô 'dF*d¢ *bô'd 8 c-Dd' #dV'db VFwf-6W" HdVHb¶Hd&Jb!G d†9bô'dF*dr Dd6D dV*c-DdR HdV$c63b'â"Â
980 |     "summary": "bv3b!.bôE bVDdVfCv) b†Ec6$d†Dd!)`Â Hbv-dvp bô3bv(d6 d†'bô*c E cVDbv-d!°b¢ 'dF'bæ1d!F d†Ebô*d†'dvE.",
981 |     "sections": {
982 |       "1": {
983 |         "title": "1. d&(d†D bVDcF1d†7",
984 |         "body": "b†/bæHdFc bVDd' Edf5b' VFwf-6W" #d, 'c6*bæ/bvEdv' d %dfc b!HbvAd" 9dFI bVDbvDb!2bvE b†4c Hcr 'dF.bôEb' Gc G. d†°c '
985 |       },
986 |       "2": {
987 |         "title": "2. d†5d 'dF.bôEb'"Â
988 |         "body": "Edeviser dVfCv) dF%bô'c ) bVDd!9dFJdR 'dFBbv&dR 9dFI bVDdV.c ,bv*`Â Hb!Hd 1 b6/d†'b¢ DbV/bv1b' 'dF*c-DdR HbvDb!Bd!JdF
989 |       },
990 |       "3": {
991 |         "title": "3. bô3bv(bv* bVDdV3b!.bôEd!F",
992 |         "body": "b6Fb¢ Ec6$d†D c-F bVDdôABv8 c-Dd' 3c Jb' (d!'df'b¢ /bæHdB -c6'b†C`Â Hd!,b, %b†Dbv:df' d Hc 'd² (b6J bv3b!.bô'dR :d!1
993 |       },
994 |       "4": {
995 |         "title": "4. bVDbv3b!.bô'dR 'dFEd&(d†D",
996 |         "body": "b!HbvAd" 9dFI c-/dR %c6'b ) bv3b!.bô'dR 'dFEdf5b- b†Ebr Ad¢ 0dFC dV-bvHdF) bVDd†5d†D c!Jc 'dFecV1bô (dr #d, %c-'d&
997 |       },
998 |       "5": {
999 |         "title": "5. bVDdVDd6Jb' 'dFAd61d!)",
1000 |         "body": "d!(d&I bVDdV-b!Hd' 'dF0d¢ *df4bfG c-Dd' 'dFEdf5b' EdFcBvK dFC`Â (d!Fdv' b!-b!Ac, VFwf-6W" (bôBd†B b†1dV,d!°b¢ 'dFEdf
1001 |       },
1002 |       "6": {
1003 |         "title": "6. bô/d†/ bVDdV3bFHdFJb'"Â
1004 |         "body": "b!Od&/dR VFwf-6W" CdV' dvJ bôHdb 6dV'df'b¢ Edb #d¢ Fd†9. d†Dbr Fb!-dVD dV3bFHdFJb' 'dF#cf1bv1 c!Jc 'dFEB†'cf1b' #d,
1005 |       },
1006 |       "7": {
1007 |         "title": "7. b!9bôJdB 'dF4c Hcr"Â
1008 |         "body": "d&/ df-bôQb² Gc G bVDcF1d†7 dVF d†Bb¢ %dFI b&c.â Hd!9bô 'c6*dV1bv1 bv3b!.bô'dR 'dFEdf5b' (c-/ bVDd!°d!Jc 'b¢ Bb†HdF
1009 |       },
1010 |       "8": {
1011 |         "title": "8. bVDd!Hbv5dB"Â
```

```
1012         "body": "dFDbv3b!Ac6'c 'b¢ 'dFEb!9dFBb' (dv0dr 'dF4c Hcv b!Hbv5dB Ec' Ac Jd&Fbr 'dFBBvFd†Fd¢â"
1013     }
1014 }
1015 },
1016 "privacy": {
1017     "title": "c6Jbv3b' 'dF.cVHCvJb'"Å
1018     "subtitle": "d6Jd Jb' ,dV9 Edeviser dFDdV9dFHdV'b¢ Hb0EbvJb!Gbr Hbv3b!.b0!dVGbr 9b†1 c -dF) bvDb!9dFE.",
1019     "summary": "df3b!.b0E bvDb†JbvFbv* dF*d&/d!E bæ/dV'b¢ 'dF*c-DdR Hb!-dFJdF'b¢ 'dFEbF3c6)`Å HdF' df(d!9 bvDb†JbvFbv* bvDcF.cvJb'â"Å
1020     "sections": {
1021         "1": {
1022             "title": "1. bvDdV9dFHdV'b¢ 'dF*d¢ FbÆEc-Gbr"Å
1023             "body": "df,dV9 bvDdV9dFHdV'b¢ 'dF*d¢ *d&/dVGbr Eb†cF1b- d†EdfGbr 'dF'c6E d†dF(c Jb0 'd%dfCb!1d†Fd¢ HbvDdV$c63b- bv6bvAb
1024         },
1025         "2": {
1026             "title": "2. d6Jd Jb' 'c6*bæ/bvE dV9dFHdV'b!C",
1027             "body": "b!0c6*bæ/dR (d! 'df' b!C dF*d&/d!E Edeviser d†b03d!Fdv d†*bæ5d!5 bvDb!9dFE`Å HbVFcF'b *b0Dd!Dbv* dFDdV9dFEd!F`Å Hb0
1028         },
1029         "3": {
1030             "title": "3. dVDd 'b¢ *c-1d!A bvdBv1b!(bv7",
1031             "body": "df3b!.b0E dVDd 'b¢ *c-1d!A bvdBv1b!(bv7 bvDb63bv3d!) dFDdV5bv/d&) d†b0'c ) bvDbÆDc6'b¢â HdF' b!0d 9e D dVDd 'b¢ 'dF
1032         },
1033         "4": {
1034             "title": "4. dV4bv1d6) bvDb†JbvFbv*",
1035             "body": "dF' df(d!9 bvDb†JbvFbv* bvDcF.cvJb'â Hd&/ b!0cF'c C bvDb†JbvFbv* dV9 dV3bFHdFJ dV$c63b!C d†Ec-DdVJdv' c-Fb0 'dF-bv,b
1036         },
1037         "5": {
1038             "title": "5. bvDbv-b!Abv8 b†dF(d! 'df'b¢"Å
1039             "body": "b!0b0Ac, 'dF(d! 'df'b¢ 7d†dB Eb0) b03bv(d2â Hb†9b0 -c A bvDb03bv( b!0c&'dB 'dF(d! 'df'b¢ 'dF4bæ5d!) bæDbvD 30 d!HdV'd
1040         },
1041         "6": {
1042             "title": "6. b0Bd†Bd2"Å
1043             "body": "d!Ed6Fd2 'dFHCvHdB %dFI b†JbvFbv*d2 'dF4bæ5d!) b6H b!5b0Jb0Gbr #d, -c Adv!`Å CdV' d!Ed6Fd2 *cV/d!1 b†JbvFbv*d2 Edb %
1044         },
1045         "7": {
1046             "title": "7. bvDb6EbVf",
1047             "body": "df3b!.b0E bV,c 'b 'b¢ -dV'd!) dV*d†d Bb' Ec' Ec-'d!Jc 'dFBcv'c- d†EdfGbr 'dF*cFAd!1 b6+df'b 'dFFd&D d†#dV'db Ec6
1048         },
1049         "8": {
1050             "title": "8. bvDb!Hbv5dB"Å
1051             "body": "dFDbv3b!Ac6'c 'b¢ 'dFEb!9dFBb' (bvDbæ5d†5d!)`Å *d†'cVD dV9 d 1d!B bvDbæ5d†5d!)."
1052         }
1053     }
1054 }
1055 },
1056 "empty": {
1057     "noCourses": {
1058         "title": "dF' b!HbÆ/ dVbC 1bv* b†9b0"Å
1059         "description": "c6*c†Gc 'dFEd&1c 'b¢ Gdf' b†EbÆ1b0 %df4bv&dv' d†*c-Jd!Fdv'."
1060     },
1061     "noProgress": {
1062         "title": "dF' b!HbÆ/ b†JbvFbv* b!Bb0E",
1063         "description": "bv(b0# b†%d6Ebvd bvDb6FcF7b' Db! *b†9 b!Bb0Ed2 Ad¢ 'dF*c-DdRâ"
1064     },
1065     "noUsers": {
1066         "title": "dF' d!HbÆ/ dV3b!.b0Ed†F",
1067         "description": "d&E b†c-Hb' 'dFEc6*bæ/dVJdb %dFI dV$c63b!C dFDb†/b â"
1068     },
1069     "noNotifications": {
1070         "title": "dF' b!HbÆ/ bv4c-'c 'b¢"Å
1071         "description": "b6Fb¢ 9dFI bv7dF'c' (d6D cFJb 3b!8dv1 bvDbV4c-'c 'b¢ 'dF,b0Jb0) dvFbrâ"
1072     },
1073     "noBadges": {
1074         "title": "dF' b!HbÆ/ cF'c 'b¢ Ed6*c6(b'"Å
1075         "description": "b6CdVD bvDb!-b0Jbv* d†dF%df,bv2bv* dFCc6( bvDcF'c 'b¢â"
1076     },
1077     "noEvidence": {
1078         "title": "dF' b!HbÆ/ b6/dF) b†9b0"Å
1079         "description": "c6*c†Gc *d&/d!Ebv* bvDcvDbv( d†#b0Db' 'dF*d&Jd!E dvFbrâ"
1080     },
1081     "noMarketplaceItems": {
1082         "title": "dF' b!HbÆ/ c-Fbv5c Eb!b0)",
1083         "description": "c6*c†Gc 9df'cV1 bvDc6Hd" Gdf' b†EbÆ1b0 %b01bv,dv'."
1084     },
1085     "noLinkedStudents": {
1086         "title": "dF' d!HbÆ/ cvDbv( dV1b!(cvHdb"Å
1087         "description": "bv7dF( dVF dV3bFHdB EbF3c6*d2 1b†7 b03bv(bv* bvDcvDbv(.
1088     },
1089     "noTeams": {
1090         "title": "dF' b!HbÆ/ d 1d" (c-/",
1091         "description": "b6FcF& d 1d&'d2 Db!Fc†JdR 'dF7dF'b, Ad¢ EbÆEd†9bv* b!9bvHdfJb'â"
1092     },
1093     "noChallenges": {
1094         "title": "dF' b!HbÆ/ b!-b0Jbv* b†9b0"Å
1095         "description": "b6FcF& b!-b0Jbv* dF%cF1bvC bvDcvDbv( d J b6FcF7b' ,dV'c-Jb'â"
1096     },
1097     "noOutcomes": {
1098         "title": "dF' b!HbÆ/ dV.c ,bv*",
1099         "description": "b66d Ebæ1bÆ'b¢ 'dF*c-DdR Db†/b 'dF*bæ7d!7 d†dF*b0Dd!D."
1100     },
1101     "noQuestions": {
1102         "title": "dF' b!HbÆ/ b63bfDb' (c-/",
1103         "description": "b66d #d, #df4bb #c6&dF) dF(df'b (dFc bvDb63bfDb'â"
1104     },
1105     "noResults": {
1106         "title": "dF' b!HbÆ/ dF*bv&bÅ (c-/",
1107         "description": "c6*c†Gc 'dFFb! 'bF, dvFbr (dV,c / bVCdV'dB 'dF7dF'b, Db!Bd!JdV'b!GdRâ"
1108     },
1109     "noData": {
1110         "title": "dF' b!HbÆ/ b†JbvFbv* dV*bv-b'"Å
1111         "description": "c6*c†Gc 'dF(d! 'df'b¢ Gdf' dV9 bVCdV'dB 'dF#df4cv)."
1112     },
1113     "noSessions": {
1114         "title": "dF' b!HbÆ/ bÆDc6'b¢ (c-/",
1115         "description": "b6FcF& bÆDc6'b¢ Db†/b *b!(c' 'dF-cfHc â"
```

```

1116 | },
1117 | "noSurveys": {
1118 |   "title": "dF' b|HbÆ/ bv3b|7dF'c~'b¢ (c~/",
1119 |   "description": "b6FcF& b6HdB 'c6*cvDbbv9 dF,dv9 bvDdVDbv-c†'b¢â"
1120 | },
1121 | "noSemesters": {
1122 |   "title": "dF' b|HbÆ/ d 5d†D bô1bv3d|) b†9bò"Â
1123 |   "description": "b6FcF& b6HdB AcVD bô1bv3d¢ DdF(bô!.."
1124 | },
1125 | "noTimetable": {
1126 |   "title": "dF' b|HbÆ/ bô5cR Ad¢ 'dF,bôHdB"Â
1127 |   "description": "b66d -cV5bvK dF*df8d|E bvdBÆ/d†D bvdBô1bv3d¢â"
1128 | },
1129 | "noResponses": {
1130 |   "title": "dF' b|HbÆ/ c /d†/ b†9bò"Â
1131 |   "description": "c6*c†Gc 'dF1bôHbô Gdf' b†EbÆ1bò *d&/d|E bvdDv4bv1d6Jdbâ"
1132 | },
1133 | "noAssignments": {
1134 |   "title": "dF' b|HbÆ/ d†'bÆ(bv* b†9bò"Â
1135 |   "description": "c6*c†Gc 'dFHbv,b†'b¢ Gdf' b†EbÆ1bò %df4bv&dv'.."
1136 | },
1137 | "noSubmissions": {
1138 |   "title": "b|E bVbÆ'c" ,dVJc' #c-EbvD bvdB|5bôJbô"Â
1139 |   "description": "c6*c†Gc *c6Dd|EbV* bvdCvDbb( bvdBÆ/d|/b' Gdf' c-FbôEbr *cV(bô ,bvGc&) dFDb|Bd|JdRâ"
1140 | },
1141 | "noCLOs": {
1142 |   "title": "dF' b|HbÆ/ dv.c ,bv* b|9dFE dFDdVbC 1",
1143 |   "description": "c6*c†Gc Ebæ1bÆ'b¢ *c-DdR 'dFEd&1c Gdf' b†EbÆ1bò %df4bv&dv'.."
1144 | },
1145 | "noPLOs": {
1146 |   "title": "dF' b|HbÆ/ dv.c ,bv* b†1df'dV," ,
1147 |   "description": "bv7dF( dVF bvdDVfC6B bVFcF'b Ebæ1bÆ'b¢ 'dF(c FbvEbÂ #d†DbvK."
1148 | },
1149 | "noILOs": {
1150 |   "title": "dF' b|HbÆ/ dv.c ,bv* dV$c63d|)",
1151 |   "description": "bv7dF( dVF bvdDV3bFHD b %df4bv! dv.c ,bv* bvdB|9dFE bvdDV$c63d|) b6HdF'd²â"
1152 | },
1153 | "noStudents": {
1154 |   "title": "dF' d|HbÆ/ cvDbb(",
1155 |   "description": "c6Jc†Gc 'dF7dF'b, 'dFEc6,dFHdb Gdf'.."
1156 | },
1157 | "noRubrics": {
1158 |   "title": "dF' b|HbÆ/ dv9bvJd|1 b|Bd|JdR (c~/",
1159 |   "description": "b6FcF& dv9bvJd|1 b|Bd|JdR Db|HbôJbô Ec-'d|Jc 'dF*cV-d|-'.."
1160 | },
1161 | "noActionPlans": {
1162 |   "title": "dF' b|HbÆ/ bæ7cr 9dVD b†9bò"Â
1163 |   "description": "b6FcF& bæ7b' *bô3d|F bÆHbô) dF(bô! bv:dF'd" 'dF-dFbB'â"
1164 | },
1165 | "noAttendance": {
1166 |   "title": "dF' b|HbÆ/ c6,dF'b¢ -cfHc "Â
1167 |   "description": "b6FcF& bÆDc6'b¢ Hc6,dB 'dF-cfHc Dc $d|) bvdC6,dF'b¢ Gdf'.."
1168 | },
1169 | "noXPData": {
1170 |   "title": "dF' b|HbÆ/ b†JbvFbv* XP b†9bò"Â
1171 |   "description": "bv(bô# b†Cc6( XP dF1bFJb' #d 6dB %df,bv2bv*d2 Gdf'.."
1172 | },
1173 | "noImprovementData": {
1174 |   "title": "dF' b|HbÆ/ b†JbvFbv* b|-'c6F",
1175 |   "description": "bv3b|Ec (d63b, ... DdV9c Ab' Edb Jb|-'c6F b6Cb¶1.."
1176 | },
1177 | "noLeaderboardData": {
1178 |   "title": "dF' b|HbÆ/ b†JbvFbv* dFHbô) bvdCv/bv1b'"Â
1179 |   "description": "c6*c†Gc %bô.bvDbv* dFHbô) bvdCv/bv1b' 9df/dv' d|Cc6( bvdCvDbb( XP."
1180 | },
1181 | "noCorrelationData": {
1182 |   "title": "dF' b|HbÆ/ b†JbvFbv* bv1b|(bv7",
1183 |   "description": "c6*c†Gc (d|'df'b¢ 'c *b†'cr Fd†'b|, bvdB|9dFE b†9bò %d6EbvD bvdBv.b|(bv1bv*.."
1184 | },
1185 | "noBloomsData": {
1186 |   "title": "dF' b|HbÆ/ b†JbvFbv* b†Dd†E",
1187 |   "description": "c6Jc†Gc *d†2d|9 dv3b|Hd|'b¢ (dFHdR Ec' ,dv9 b†JbvFbv* bvdBv.b|(bv1bv*.."
1188 | },
1189 | "noUsageData": {
1190 |   "title": "dF' b|HbÆ/ b†JbvFbv* bv3b|.bô'dR"Â
1191 |   "description": "c6*c†Gc 'b|,bvGbv* bvdBv3b|.bô'dR Ec' *d 'c-D bvdCvDbb( dv9 bvdDV9dFE bvdC Dc¢â"
1192 | },
1193 | "noCitationData": {
1194 |   "title": "dF' b|HbÆ/ b†JbvFbv* bvBb|(bv3bv*",
1195 |   "description": "c6*c†Gc 'd&*b†'c6'b¢ 'dFEd†'bô 9df/dv' d|4d|1 bvdDV9dFE bvdC Cdc %dFI bvdDV-b|Hd'â"
1196 | },
1197 | "noAttainmentData": {
1198 |   "title": "dF' b|HbÆ/ b†JbvFbv* b|-'cVJdB"Â
1199 |   "description": "c6Jc†Gc *bô5d|D dFhbv*bÂ 'dF*c-DdR 9df/ bvdCv'dB 'dF*d&Jd|Ebv*.."
1200 | }
1201 | }
1202 | }
1203 |

```

FILE: src/locales/ar/coordinator.json

TYPE: .json | LINES: 1-397 | SHA256: 2b5a5cf3959fa70f8364a0f99234236db40a7ad5a1c8b0a1d2d9a203cce5585f

```

1 | {
2 |   "dashboard": {
3 |     "title": "dFHbô) b|-'d6E bvdDVfC6B",
4 |     "welcome": {
5 |       "subtitle": "c 'd&( dv.c ,bv* bvdB†1df'dV, d†*b|(c' 'dF*bô5d|D d†'bôAc' 9bÆDb' 'dF*bô3d|F bvdDV3b|Ec DdF,d†/b'â"
6 |     },
7 |     "totalPLOs": "bv,dV'dFJ dv.c ,bv* bvdB|9dFE bvdB†1df'dV,d|)",
8 |     "activeCourses": "bvdDVbC 1bv* bvdDf4cv)",
9 |     "cloCoverage": "b|:cvJb' Ebæ1bÆ'b¢ 'dF*c-DdR"Â
10 |     "teacherCompliance": "bvEb|+bvD bvdDV9dFEd|F",
11 |     "curriculumMatrix": "dV5d Hd ) bvdDVfDv,",
12 |     "selectProgram": "bv.b|1 b†1df'dV,bvK",

```

```

13 | "viewFullMatrix": "c-1cb 'dFEcVAd†Ab' 'dFCbvEdF)",
14 | "noProgramsAvailable": "dF' b!HbÆ/ b†1bvEbÅ Eb!b0). b6FcF& b†1df'dV,bvK dF9c 6 dV5d Hd ) bvDdVfDv,.",
15 | "atRiskStudents": "bvDcvDbv( bvDdV9c 6d†F dFDbæ7c "Å
16 | "atRiskPending": "c6Jb!Hd 1 bvCb!4bvA bvDcvDbv( bvDdV9c 6d†F dFDbæ7c 9df/ bÆEc' (d!df'b¢ 'dF*b05d!D.",
17 | "atRiskBelowThreshold": "cvDbv( b0Hdb 9b!(b' 'dF*b05d!D bvDb†dF:b' S R"Å
18 | "noAtRiskStudents": "dF' d!HbÆ/ cvDbv( dv9c 6d†F dFDbæ7c å ,dvJc' 'dF7dF'b, 9df/ c-*b†) bvDb!-cVJdB #d, #c-Dd' Edf6brå"Å
19 | "avgAttainment": "dv*d†3cr 'dF*b05d!D",
20 | "recoveryPathways": "dv3bv1bv* bvDbv3b!9bv/b'"Å
21 | "totalActivations": "bv,dv'dfJ bvDb!Ac-JdF'b¢"Å
22 | "completionRate": "dv9b0D bvDbvCdV'dB"Å
23 | "avgCompletionTime": "dv*d†3cr Hd&* bvDbvCdV'dB"Å
24 | "retrySuccessRate": "dv9b0D df,bv- bv9bv/b' 'dFb0!d†Db'"Å
25 | "cqiActionPlans": "bæ7cr 9dVd bvDb!-c6Jdb 'dFEc6*dV1",
26 | "viewAll": "c-1cb 'dFCdB"Å
27 | "planned": "dv.cv7",
28 | "inProgress": "d&Jb0 'dF*dfAd!0",
29 | "completed": "dVCb!EdB"Å
30 | "evaluated": "b!E bvDb!Bd!JdR"Å
31 | "noCqiPlans": "dF' b!HbÆ/ bæ7cr 9dVd dFDb!-c6Jdb 'dFEc6*dV1 b†9b0å #df4bb Hbv-b0) dVF cVAb0) bæ7cr 'dF*b03d!F.",
32 | "sectionComparison": "dvBbv1df) bvDcF0c-(",
33 | "selectCourse": "bv.b!1 dVBc 1bvK",
34 | "selectCourseToCompare": "bv.b!1 dVBc 1bvK dFEd&'c Fb' Ed&'d!Jc2 *b05d!D bvDcF0c-(.",
35 | "noSectionsFound": "dFE d!dR 'dF9b!Hc 9dFI cF0c-( dFGc 'bvDdVbC 1.",
36 | "obeVisualizations": "b!5d†1bv* bvDb!9dFJdR 'dFBbv&dR 9dFI bvDdV.c ,bv*",
37 | "sankeyDiagram": "dv.cv7 c6'dfCd¢"Å
38 | "sankeyDesc": "b!d B bvDdV.c ,bv* bvDdV$c63d!) !* bvDb†1df'dV,d!) !* bvDdVbC 1d!)",
39 | "gapAnalysis": "b!-dFJdB 'dFAbÆHbv*",
40 | "gapAnalysisDesc": "bvDdV.c ,bv* c!Jc 'dFEc (d†7b'"Å
41 | "coverageHeatmap": "bæ1d!7b' 'dF*c!7d!) bvDb0!bv1d!)",
42 | "coverageHeatmapDesc": "d6+bvAb' *c!7d!) dV.c ,bv* bvDb!9dFE",
43 | "semesterTrends": "bv*bÆ'dv'b¢ 'dFACvd bvDb0!bv3d¢"Å
44 | "semesterTrendsDesc": "bvDb!-cVJdB 9b†1 bvDc&Edb"Å
45 | "cohortComparison": "dvBbv1df) bvDb6Ad†bÅ"Å
46 | "cohortComparisonDesc": "dvBbvJd!3 c-(c 'dF#d Hbv,",
47 | "hub": {
48 |   "title": "cV-b' 'dF(c FbvEbÆ bÆ'dv2b'"Å
49 |   "subtitle": "c Ce 2 c-Dd' 'dF9df'cV1 b6/df'dr 'dF*d¢ *b0*bv, bvFb!(bvGd2å"Å
50 |   "why": "dFEbv0br #c I dv0bv ",
51 |   "plotTitle": "b!-cVJdB Ebæ1bÆ'b¢ 'dF(c FbvEbÅ 9dFI bvDdV3bv1",
52 |   "plotBelow": "{count}} dVF dv.c ,bv* bvDb†1df'dV, b0Hdb 'dFGb0Å",
53 |   "review": "dv1bv,c-)",
54 |   "gapTitle": "b!cvJb' 'dFEdf6bÅ"Å
55 |   "openMatrix": "bvAb!- bvDdV5d Hd )",
56 |   "accredTitle": "bÆ'dv2d!) bvDbv9b!Ebv/",
57 |   "continueEvidence": "dv*bv(c-) bvDb6/dF)"
58 | },
59 | "kpi": {
60 |   "programs": "bvDb†1bvEbÅ"Å
61 |   "avgPlo": "dv*d†3cr *b05d!D PLO",
62 |   "belowTarget": "b0Hdb 'dFGb0Å",
63 |   "accredReady": "bÆ'dv2d!) bvDbv9b!Ebv/"
64 | },
65 | "alerts": {
66 |   "title": "b!Fb†Jdv'b¢ 'dF*b05d!D",
67 |   "allOutcomes": "bÆEd!9 bvDdV.c ,bv*",
68 |   "priorityHigh": "b6HdFHd!) c-'dFJb'"Å
69 |   "priorityMedium": "b6HdFHd!) dv*d†3cv)",
70 |   "draftCqi": "cVJbv:b' (cv) b!-c6Jdb"Å
71 |   "drillDown": "b!Abv5d!D b69dVB",
72 |   "gapBody": "bvDb!-cVJdB .. 7G×0R r ·¶v ×0 Fd&7b' /d†F dv/d ..F‡&W6†0ÆG×0Rå"Å
73 |   "weakest": "b66c-A dVBc 1: {{code}} ({{pct}}%)",
74 |   "affected": "{count}} cvDbv( dv*b6+c Hdb ‡.. W&6VcG×0R'"Å
75 |   "empty": "bÆEd!9 dv.c ,bv* bvDb†1df'dV, b!-d&B bvDdv/d "Å
76 |   "emptyDetail": "bÆEd!9 dv.c ,bv* bvDb†1df'dV, bvDb†dF:b' ·¶6÷VcG×0 9df/ c-*b†) bvDdf,bv- {{threshold}}% b6H b69dFI.",
77 |   "lowest": "bvDb6/dFI: {{title}} c-Fb0 .. 7G×0R"
78 | },
79 | "gap": {
80 |   "title": "b!E bvCb!4bvA d ,d†) dVFdv,d!)",
81 |   "body": "«bvDb!2bvEdk² Dd!3 dFG b!Bd!JdR Ec *b†7",
82 |   "detail": "d!9b!Eb0 9dFJdr Å0F dFCdb Dbr Jd&Je Edr #d¢ Ed&1c -bvDd!'d² r +c!1b' *c!7d!) dFDbv9b!Ebv/.",
83 |   "impact": "bvDb6+c 'dFEd&/e 1: dv*d†3cr"Å
84 |   "cta": "bvAb!- bvDdV5d Hd )"
85 | },
86 | "evidence": {
87 |   "title": "b6/dF) bvDbv9b!Ebv/",
88 |   "overall": "bvDbÆ'dv2d!) bvDbv,dv'dFJb'"Å
89 |   "cloMapping": "c (cr Ebæ1bÆ'b¢ 'dFEd&1c "Å
90 |   "samples": "c-Je Fbv* (b69dV'dB 'dF7dF'b,"Å
91 |   "analysis": "b!-dFJdB 'dF*d&Jd!E",
92 |   "reflection": "b!#dVD b69cf'b Gd!&b' 'dF*b01d!3",
93 |   "cqi": "bvDb!-c6Jdb 'dFEc6*dV1 (CQI)",
94 |   "completed": "dVCb!EdB"Å
95 |   "inProgress": "d&Jb0 'dF*dfAd!0",
96 |   "pending": "dv9dFQd"Å
97 |   "cta": "dv1bv,c-) bvDdV3d†/b'"
98 | },
99 | "cqi": {
100 |   "title": "bv:dF'd' 'dF-dFBb' „5 ' "Å
101 |   "statusCompleted": "dVCb!EdB"Å
102 |   "statusInProgress": "d&Jb0 'dF*dfAd!0",
103 |   "statusPlanned": "dv.cv7",
104 |   "statusEvaluated": "b!E bvDb!Bd!JdR"Å
105 |   "empty": "dF' b!HbÆ/ bæ7cr 9dVd dFDb!-c6Jdb 'dFEc6*dV1 b†9b0å"Å
106 |   "cta": "c-1cb 3bÆD bvDb!-c6Jdb"
107 | },
108 | "timeline": {
109 |   "title": "bvDbÆ/d†D bvDc&EdfJ dFDb†1df'dV,",
110 |   "statusCompleted": "dVCb!EdB"Å
111 |   "statusNow": "bvDb&F",
112 |   "statusNext": "bvDb!dFJ",
113 |   "statusUpcoming": "d&'b0E",
114 |   "empty": "dF' b!HbÆ/ b6-b0'b² Bbv/dV).",
115 |   "cta": "c-1cb 'dF,b0HdB 'dFCbvEdB"
116 | }

```

```
117 },
118 "rail": {
119   "attainmentAlerts": "b;FbJdv'b¢ 'dF*b05d;D",
120   "alertPlo": "PL02 -6% dv0br 'dFACVD",
121   "alertClo": "CL05 b0Hdb 'dFGb0A x2",
122   "viewAllAlerts": "c-1cb ,dVJc' 'dF*dF(d;Gbv*",
123   "curriculumGap": "d ,d†) dVFdv,d;)",
124   "gapBody": "«bvdB;2bvEdk² Dd;3 dFG b;Bd;JdR Ec *b†7.",
125   "openMatrix": "bvAb;- bvdV5d Hd )",
126   "accreditation": "bvDbv9b;Ebv/",
127   "evidenceReadiness": "bÆ;dv2d;) bvdB6/dF)",
128   "reviewDraft": "dV1bv,c-) bvdDv3d†/b'"
129 },
130 "attainment": {
131   "title": "b;-cVJdB 'dFEbæ1bÆ'b¢"Å
132   "subtitle": "bvDdV.c ,bv* bvdDv$C63d;) !• bvdB†1df'dV,d;) !• bvdDvBC 1d;). b; ,dVJc' -d¢ Edb #b0Db' 'dF7dF'b,â 'dfBc 9dFI dV.c , b†;
133   "howItWorks": "d6Jd Jc-EdB"Å
134   "iloSection": "dV.c ,bv* bvdB;9dFE bvdDv$C63d;) (ILO)",
135   "viewIloDetails": "c-1cb *d 'cVJdB "Å0"Å
136   "ploSection": "dV.c ,bv* bvdB;9dFE bvdB†1df'dV,d;) (PLO)",
137   "allTerms": "bÆEd;9 bvdD 5d†D",
138   "currentTerm": "bvDd 5dB 'dF-bvdD¢"Å
139   "downloadReport": "b;Fc&JdB 'dF*d&1d;1",
140   "target": "bvDdv/d "Å
141   "onTrack": "c-Dd' 'dFEc6'c "Å
142   "watch": "dV1bvBb†)",
143   "belowTarget": "b0Hdb 'dFGb0A",
144   "contributingClos": "{count}} dV.c ,bv* dV3bvGdV)",
145   "vsPrev": "dVBbv(dB -. 7G×0R"Å
146   "vsLastTerm": "dVBbv(dB 'dFACVD bvdC6'b†B",
147   "ofCohort": "{pct}}% dVF bvdD HbÅ"Å
148   "cloBreakdown": "b;AcVJdB 'dFEbæ1bÆ'b¢ 'dFEd&1c Jb'"Å
149   "aiInsight": "c $d;) bvdC Cbv! bvdBv5cvFbv9d¢"Å
150   "sourceAi": "dVF bvdC Cbv! bvdBv5cvFbv9d¢"Å
151   "sourceComputed": "dv-c6Hb†)",
152   "insight": "c $d;)",
153   "insightText": "{clo}} dvH b6/dfI dV.c , dV3bvGdR 9df/ {pct}}%",
154   "insightNone": "bÆEd;9 bvdDv.c ,bv* bvdDv3bvGdV) c-Fb0 'dFGb0A b6H b69dFI dVdFdrâ"Å
155   "empty": "dF' b;HbÆ/ b†JbvFbv* b;-cVJdB Ebæ1bÆ'b¢ (c-./.",
156   "recommendedAction": "bvDbv,c 'b 'dFEd†5d' (dr"Å
157   "draftCqiPlan": "cVJbv:b' .cv) b;-c6Jdb"Å
158   "evidenceLinks": "c Hbv(cr 'dF#b0Db'"Å
159   "evAssessment": "b;-dFJdB 'dF*d&Jd;E",
160   "evSamples": "c-Je Fbv* bvdB69dV'dB ±.¶6÷VçG×0'"Å
161   "evFeedback": "dVDbv-c†'b¢ 'dF7dF'b,"Å
162   "ilo1Title": "bvDb;Ad6Jc 'dFFbvBb0"Å
163   "ilo2Title": "bvDbV*d&'db 'dF*d&Fdc"Å
164   "ilo3Title": "bvDb;Hbv5dB"Å
165   "plo1Title": "b;-dFJdB 'dFEc6'bFd bvdB0'c6Hb†Jb'"Å
166   "plo1Desc": "b;-b0Jb0 HcVJbv:b' Hb;-dFJdB 'dFEc6'bFd b†'c6*bæ/bvE bvdB;Ad6Jc 'dF-bv3d†(d¢â"Å
167   "plo1Weakest": "CS301 dvJbvCdB 'dF(d;'df'b¢"Å
168   "plo1Clo1": "b;Ad6Jd2 'dFEc6#dF)",
169   "plo1Clo2": "b;-dFJdB 'dF.d†'c 2dVJbv*",
170   "plo1Insight": "d;Hbv,dr 'dF7dF'b, 5c-Hb†) d J b;Ad6Jd2 'dFEc6'bFd bvdDv9d&/b' %dFI b6,c&b #cv:c d†Jdf.d 6 bvdB6/bv! d J bvdDvG
171   "plo1Recommended": "b66d *b01d;(bvK c-Dd' *d Cd;C bvdDv3bv&dB Bb†D bvdBv.b;(bv1 bvdDf5d J 2 d†'dFEc&Jb0 Edb #c6&dF) bvdBv3b;1bÆ'c'
172   "plo2Title": "b;7b†Jd" Eb†'b0& bvdDvFb03b'"Å
173   "plo2Desc": "b;7b†Jd" 'dFEc-1d ) bvdDvFb03d;) dF*cVED;E d†(df'b 'dF-dFHdBâ"Å
174   "plo2Weakest": "CS205 d†'bÆgbv* REST",
175   "plo2Clo1": "b;5dVJdR Hbv,dv'b¢ $U5B"Å
176   "plo2Clo2": "dFec ,b' 'dF(d;'df'b¢"Å
177   "plo2Insight": "d;†*b6.c *cVED;E d†'bÆgbv* REST d J cF9b†*d;Fa² Hd;:d D bvdDcvDbv( bvFc-/bvE bvdB0'dF) d†'cv7dF'b0'b¢ Ec-'dF,b' 'dF#
178   "plo2Recommended": "d&/e E dV.b;(c $U5B Ed†,dv'd² HdFbCv) b;-d&B dF*cVED;E bvdD†'bÆgbv* dV*d†'d Bb' Ec' 3dFQdR 'dF*d&Jd;E.",
179   "plo3Title": "b;5dVJdR #df8dV) bvdB†1dV,d;'b¢"Å
180   "plo3Desc": "b;5dVJdR #df8dV) b†1dV,d;) d&'b†Db' DdF*d†3c' HdVHb¶Hd&) d†Ac-QbvDb'â"Å
181   "plo3Weakest": "CS310 b;5dVJdR 'dF(c EbÆJbv*",
182   "plo3Clo1": "b6FdV'cr 'dFEc-Ebv1d;)",
183   "plo3Clo2": "b;-dFJdB 'dFEd 'cfDbv*",
184   "plo3Insight": "b;-dFJdB 'dFEd 'cfDbv* dvH b66c-A dVgbv1b' Ac 9d;)a² Hb;Ed;D bvdB;5bvEd;E bvdD' 'dFEb6Dd†A c-Dd' -c6'b, Bbv(dFJb' '
185   "plo3Recommended": "b66d Fb0Hb' Ec 'bÆ9b' *cVED;E b;Bbv1db Ed 'cfDbv* bvdDv9dV'c Jb' 9dFI b01bv3b' -bvdB' EcF*c Ch'â"Å
186   "plo4Title": "b†Fbv! b6Fc†Eb' Ed†d†Bb'"Å
187   "plo4Desc": "b;Fd Jc Hbv.b;(bv1 d†FcF1 b6Fc†Eb' (c EbÆJb' Ed†d†Bb'â"Å
188   "plo4Weakest": "SE310 dvFb03b' 'dF(c EbÆJbv*",
189   "plo4Clo1": "bvDbv.b;(bv1 d†'dF*d6'dVD bvdDv3b;Ec "Å
190   "plo4Clo2": "bvDdf4c "Å
191   "plo4Insight": "bvDb;-cVJdB Ec6*d&1 c-Fb0 'dFGb0Aa² Hd;*d d†* c-Ed" 'dF'bæ*b†'c (d;F bvdCf9b,â"Å
192   "plo4Recommended": "dt-e / bæ7 b63bv3 dFDb;CbvEdB 'dFEc6*dV1 d†*c;7d;) bvdBv.b;(bv1bv* c-(c 'dF4c-( dFDb0Abv8 c-Dd' 'dFEc6*d†I."
193 },
194 "me": {
195   "roleTitle": "dVFc6B bvdB†1df'dV,",
196   "department": "c-Dd†E bvdB0'c6(",
197   "editProfile": "b;9b0JdB 'dFEdFA",
198   "viewPublicProfile": "c-1cb 'dFEdFA bvdC-'dR"Å
199   "statPrograms": "bvDb†1bvEbÅ"Å
200   "statCourses": "bvDdVBC 1bv*",
201   "statStudents": "bvDcvDbv(",
202   "statFaculty": "b69cf'b Gd; &b' 'dF*b01d;3",
203   "phone": "+92 300 1234567",
204   "office": "c;1d ) 305"Å Eb†Fd' 9dFHdR 'dF-bv3b,"Å
205   "officeHours": "c6'c-'b¢ 'dFEd6*bfc 'dF#b¶Fd;F-bvdBæEd;3 (10cR b &E)",
206   "aiTitle": "b;AcfJdF'b¢ Ec6'c-/b' 'dF0d6'b 'dF'cv7df'c-J",
207   "aiSubtitle": "bv6b†7 d6Jd Jb' Ec6'c-/b' 'dF0d6'b 'dF'cv7df'c-J d J dVgbvEd2 'dFJd†Ed;).",
208   "aiManage": "bv/bv1b' %c-/bv/bv* bvdC Cbv! bvdBv5cvFbv9d¢"Å
209   "aiAutonomyLabel": "dv3b;Hd' 'dF'c6*d&DbvDd;)",
210   "aiAutonomyValue": "A2 - cVJbv:b' Ec' 'dFEd†'d Bb'"Å
211   "aiAllow1": "cVJbv:b' .cv7 bvdB;-c6Jdb"Å
212   "aiAllow2": "cVJbv:b' 'dF#b0Db' HbvDb;-dFJdB"Å
213   "aiAllow3": "bvCb;4bvA bvdD ,d†'b¢ 'dFEdfGbÆJb'"Å
214   "aiAllow4": "bvBb;1bv- bv,c 'b 'b¢ 'dF'b03d;F",
215   "aiDeny1": "b;5b0Jc -c&Eb' 'dF'c-*dV'b0"Å
216   "aiDeny2": "df4c 'dF*c;Jd;1bv*",
217   "roleSectionTitle": "bvDb0Hc HbvDcvDbv-d;'b¢"Å
218   "roleSectionSubtitle": "b0Hc C d†Ebr JdVCdFc d 9dFG d J bvdDf8bvE.",
219   "roleName": "dVFc6B bvdB†1df'dV,",
220   "roleViewAll": "c-1cb ,dVJc' 'dF5dF'b0Jbv*",
```



```
221 | "perm1": "dv1bv,c-) d†*d†Bd!9 bvDb6/dF)",
222 | "perm2": "bv9b;Ebv/ bæ7cr 9dVd bvDb!-c6Jdb"Å
223 | "perm3": "c-1cb 'dF*d&'c Jc 'dF#d6'b0JdVJb'"Å
224 | "perm4": "b!5b0Jc -cEb' 'dF'c-*dV'b0"Å
225 | "perm5": "bv3df'b0 'dFEdv'dR Db69cf'b Gd!&b' 'dF*b01d!3",
226 | "programsTitle": "bvDb†1bvEbÅ 'dF*d¢ #b0Jc Gbr"Å
227 | "programsSubtitle": "bvDb†1bvEbÅ *b0* b!Fc6Jd&C.",
228 | "programsViewAll": "c-1cb ,dvJc' 'dF(c 'dV,",
229 | "programsEmpty": "dF' b!HbÆ/ b†1bvEbÅ Ec6Fb0) bvDd!C b†9b0a"Å
230 | "courses": "dVBc 1bv*",
231 | "students": "cvDbv(",
232 | "facultyTitle": "b69cf'b Gd!&b' 'dF*b01d!3 bvDdV1b!(cvHdb"Å
233 | "facultySubtitle": "b69cf'b Gd!&b' 'dF*b01d!3 bvDc-'dVd†F c-(c (c 'dV,d2a"Å
234 | "facultyManage": "bv/bv1b' HcVHD #c-6bv! dvJbf) bvDb!/c Jc2"Å
235 | "facultyMembers": "c-6d, Gd!&b' *b01d!3",
236 | "facultyActive": "df4cr"Å
237 | "facultyInactive": "c!Jc FcF7",
238 | "notifTitle": "b!AcfJdF'b¢ 'dF%cF9bv1bv*",
239 | "notifSubtitle": "b69dFEdfJ c-Fb0Ebs¢"Å
240 | "notifManage": "bv/bv1b' 'dF%cF9bv1bv*",
241 | "notif1": "bvFbæAbv6 PLO b0Hdb 'dFGb0A",
242 | "notif2": "d ,d†) dVfDv,d!) bÆ/d!/b'"Å
243 | "notif3": "b6/dF) bÆ'dv2b' DdFEC 'bÆ9b'"Å
244 | "notif4": "bæEd†D bvDdV9dFE",
245 | "notif5": "bvBb!1bv( dVHC-/ bvDb!-c6Jdb"Å
246 | "securityTitle": "bvDb6EbvF d†'dFHcVHDb"Å
247 | "securitySettings": "bv9b0'b0'b¢ 'dF#dV'db"Å
248 | "changePassword": "b!:d!Jc CdFEB' dFEC Hc "Å
249 | "twoFactor": "bvDdV5bv/d&) bvDb!Fbv&d!)",
250 | "on": "dVAc-QdB"Å
251 | "activeSessions": "bvDbÆDc6'b¢ 'dFFcF7b'"Å
252 | "authorizedDevices": "bvDb6,dv2b' 'dFECV1e - b†Gbr"Å
253 | "integrationsTitle": "bvDb!CbvEdF'b¢ 'dFEB!5dF)",
254 | "integrationsManage": "bv/bv1b' 'dF*d6'dVDbv*",
255 | "googleCalendar": "b!Bd†JdR ,d†,d8"Å
256 | "outlook": "dV'd!Cc Hc6Hd * b6Hb!Dd†C",
257 | "slack": "c6DbvC",
258 | "connected": "dv*cVD",
259 | "connect": "bv*cV'dB"Å
260 | "integrationComingSoon": "c (cr Gc ' bvDb!CbvEdB Bbv/dR Bc Jb†'d2 r Jb!7dF( bv9b0'b0 'dFEC&He /.",
261 | "academicTitle": "bvDdVDD HbvDdV9dFHDv'b¢ 'dF#d6'b0JdVJb'"Å
262 | "academicEdit": "b!9b0JdB 'dFEdFA bvDb6Cbv/d!Ed¢"Å
263 | "academicDepartment": "bvDd&3dR"Å
264 | "academicDesignation": "bvDdV3dVI",
265 | "academicRank": "bvDc *b†) bvDb6Cbv/d!Ed!)",
266 | "academicRankValue": "b63b! 'c Ec6'c-/",
267 | "academicDegree": "b69dFI cFGbv/b'"Å
268 | "academicDegreeValue": "b0Cb!Hc 'dr †9dFHD 'dF-bv3b,'"Å
269 | "academicExperience": "bvDbæ(c )",
270 | "academicExperienceValue": "11 c6Fb'"Å
271 | "notSet": "c!Jc Eb0/b0"Å
272 | "experienceYears": "{count} c6Fb'"Å
273 | "academicSaved": "b!E b!-b0Jb2 'dFEdFA bvDb6Cbv/d!Ed¢"Å
274 | "academicSaveError": "b!9c Qc -d 8 dVdD C bvDb6Cbv/d!Ed¢a -bvHdB EbÆ/b0'd2a"Å
275 | "notifSaveError": "b!9c Qc *b0/d!+ b!AcfJdF'b¢ 'dF%cF9bv1bv*.",
276 | "save": "b0Ac,"Å
277 | "cancel": "bvDc!'b "
278 | },
279 | "plos": {
280 | "title": "dv.c ,bv* bvDb!9dFE bvDb†1df'dV,d!)",
281 | "addPLO": "bv6bvAb' Ebæ1bÅ *c-DdR (c FbvEbÆJ",
282 | "editPLO": "b!9b0JdB Ebæ1bÅ *c-DdR (c FbvEbÆJ",
283 | "reorder": "bv9bv/b' 'dF*c *d!(",
284 | "saveOrder": "b0Ac, 'dF*c *d!(",
285 | "orderSaved": "b!E b0Ac, *c *d!( dv.c ,bv* bvDb!9dFE bvDb†1df'dV,d!)",
286 | "filterByProgram": "b!5d Jb' -c6( bvDb†1df'dV,",
287 | "allPrograms": "bÆEd!9 bvDb†1bvEbÅ"Å
288 | "dragHint": "bv3b0( bvDc-Fbv5c Dbv9bv/b' 'dF*c *d!(^ Å +dR 'dfBc -d 8 bvDb!1b!Jb,Å"Å
289 | "active": "df4cr"Å
290 | "deletePLO": "b00d Ebæ1bÅ *c-DdR (c FbvEbÆJ",
291 | "deleteConfirm": "dvD b6Fb¢ Eb!#d6/ b6Fd2 *c Jb0 -c A \\'{{title}}\''a0 Dbr JdVCdb 'dF*c 'bÆ9 c-F dv0br 'dF%bÆ1bv!. bv0br CbvF dv0br",
292 | "deleted": "b!E b00d Å!..F-FÆW×0Å""
293 | },
294 | "curriculumMatrix": {
295 | "title": "dv5d Hd ) bvDdVFdv,",
296 | "program": "bvDb†1df'dV,",
297 | "selectProgram": "bv.b!1 b†1df'dV,bvK",
298 | "exportCsv": "b!5b0Jc 55b"Å
299 | "selectPrompt": "bv.b!1 b†1df'dV,bvK dF9c 6 dv5d Hd ) bvDdVFdv,.",
300 | "allTerms": "bÆEd!9 bvDd 5d†D",
301 | "currentTerm": "bvDd 5dB 'dF-bvDd¢"Å
302 | "coverage": "bvDb!:cvJb'"Å
303 | "legendAssessed": "dV0d&JdæQdR"Å
304 | "legendIntroduced": "dV0d&/dæQdR"Å
305 | "legendNotCovered": "c!Jc Ec!7e I",
306 | "legendGap": "d ,d†) b!:cvJb'"Å
307 | "gapTitle": "b!E bvCb!4bvA d ,d†) b!:cvJb'"Å
308 | "gapBody": "b6-b0 Ebæ1bÆ'b¢ 'dF(c FbvEbÅ Ed0Bb0Ne E d Bcr r Dbr Jd&Je Edr #d¢ Ed&1c -bvDd! 'd2â Gc G b¶:c ) b!:cvJb' DdF'c-*dV'b0a"Å
309 | "aiRec": "b!HcVJb' 'dF0d6'b 'dF'cv7df'c-J",
310 | "aiBestCourseLabel": "b6AcfD dVBc 1 dF%b0.bvDdr"Å
311 | "aiBestCourseValue": "SE310 - dvFb03b' 'dF(c EbÆJbv*",
312 | "aiAssessmentLabel": "bvDb!Bd!JdR 'dFEd†5d' (dr"Å
313 | "aiAssessmentValue": "dv.b!(c *c&dVf dv9 c6De E b!Bd!JdR Ec *b†7",
314 | "aiActionLabel": "bæ7b' 'dF9dVd",
315 | "aiActionValue": "b66d 'dFEBæ*b†1 d J bvDb63b†Hc' f bv1b†7dr (bvDdV.c ,^ Å Hbv,dv9 c-Je Fb!J b6/dF) d&(dB Ec 'bÆ9b' 'dFACVD.",
316 | "draftAssessment": "cVJbv:b' *d&Jd!E",
317 | "notifyTeacher": "bv(dF'c¢ 'dFEC-DdR"
318 | },
319 | "accreditation": {
320 | "title": "b6/dF) bvDbv9b!Ebv/",
321 | "viewCqi": "c-1cb .cv7 c-EdB 'dF*b03d!F",
322 | "readiness": "bÆ'dv2d!) bvDbv9b!Ebv/",
323 | "overallReadiness": "bvDbæ'dv2d!) bvDbV, dv'dFJb'"Å
324 | "complete": "dVCb!EdB"Å
```

```

325 | "inProgress": "d&Jbò 'dF*dFAd!0",
326 | "blocked": "dV-c†Hc "Å
327 | "notStarted": "dFE d!(bø#",
328 | "courseEvidence": "b6/dF) bvDdVBC 1bv*",
329 | "statusSigned": "dVHd&Qc' "Å
330 | "statusDraft": "dV3d†/b' "Å
331 | "statusBlocked": "dV-c†Hc "Å
332 | "statusNotStarted": "dFE d!(bø#",
333 | "statusDocumented": "dVHb†Qd" "Å
334 | "statusPartial": "bÆ2b†fJ",
335 | "c1Name": "dvJbvCdB 'dF(d! 'df' b¢" Å
336 | "c2Name": "b!7d†Jc 'dFHd!( ",
337 | "c3Name": "dVBbøEb' Ad¢ 'dF0d6'b 'dF'cV7df'c-J",
338 | "c4Name": "dvFbø3b' 'dF(c EbÆJbv*",
339 | "c5Name": "dV4c Hc' 'dF* bæ1bÅ" Å
340 | "pack": "b02dV) bvDbv9b!Ebv/",
341 | "pack1": "bvDbæ7b' 'dF/c 'c6Jb' " Å
342 | "pack2": "c (cr 4Åue Å0" Å
343 | "pack3": "b6/d†'b¢ 'dF*d&Jd!E",
344 | "pack4": "c-Je Fbv* b69dV'dB 'dF7dF'b," Å
345 | "pack5": "b!-dFJdB 'dF*b05d!D",
346 | "pack6": "b!#dVD b69cf'b Gd!&b' 'dF*b01d!3",
347 | "pack7": "b!HcVJbv' bvDb!-c6Jdb 'dFEc6*dV1",
348 | "packComplete": "dVCb!EdB" Å
349 | "packInProgress": "d&Jbò 'dF*dFAd!0",
350 | "packOutstanding": "dV9dFQd" " Å
351 | "packCloMapping": "c (cr Ebæ1bÆ'b¢ 'dFEd&1c (bvDb†1df'dV,",
352 | "packSamples": "c-Je Fbv* b69dV'dB 'dF7dF'b," Å
353 | "packAnalysis": "b!-dFJdB 'dF*d&Jd!E",
354 | "packCqi": "bvDb!-c6Jdb 'dFEc6*dV1 (CQI)",
355 | "readinessPending": "c6*c†Gc ,bvGc&Jb' 'dF'c-*dV'bò (dV,c / dV9bvDbÆ) bvDb6/dF).",
356 | "evidenceEmpty": "dF' b!HbÆ/ b6/dF) dVBC 1bv* b†9b0â" Å
357 | "packEmpty": "c6*c†Gc 9df'cV1 b02dV) bvDbv9b!Ebv/ dvFbrâ" Å
358 | "workflow": "c6Jc 'dFEd†'d Bb' " Å
359 | "wf1": "bvDdVFc6B",
360 | "wf2": "c &d!3 bvDd&3dR" Å
361 | "wf3": "dVCb!( bvDbÆHb0)",
362 | "wf4": "dVCb!( bvDbv9b!Ebv/",
363 | "wfDone": "dV9b!Eb0" Å
364 | "wfCurrent": "d&Jbò 'dFEc 'bÆ9b' " Å
365 | "wfPending": "dV9dFQd" " Å
366 | "generateTitle": "bVFcF'b EdFA bvDdVBC 1",
367 | "course": "bvDdVBC 1",
368 | "semester": "bvDd 5dB' 'dF/c 'c6J",
369 | "selectCourse": "bv.b!1 dVBC 1bvK",
370 | "selectSemester": "bv.b!1 d 5dF'd² /c 'c6JbvK",
371 | "generate": "bVFcF'b EdFA bvDdVBC 1",
372 | "generating": "bÆ'c M bvDbVFcF'b ååå" Å
373 | "ready": "dVDd 'dFEd&1c ,bvGc" " Å
374 | "downloadPdf": "b!Fc&JdB Db" Å
375 | "generated": "b60df4bb" Å
376 | "noCourses": "dF' b!HbÆ/ dVBC 1bv* dV*bv-b' " Å
377 | "noSemesters": "dF' b!HbÆ/ d 5d†D b01bv3d!) dV*bv-b' " Å
378 | "selectCourseError": "bvDc ,bv! bv.b!Jbv1 dVBC 1",
379 | "selectSemesterError": "bvDc ,bv! bv.b!Jbv1 d 5dB /c 'c6J",
380 | "generateSuccess": "b!E bVFcF'b EdFA bvDdVBC 1 b†FbÆ'b0" Å
381 | "generateError": "d 4Db %df4bv! dVdD 'dFEd&1c "
382 | },
383 | "bilingual": {
384 | "arabicTitle": "bvDc-Fd†'db (bvDc-1b†Jb' " Å
385 | "arabicTitlePlaceholder": "b6/bæD bvDc-Fd†'db (bvDc-1b†Jb' †'bæ*d!'c J)"
386 | },
387 | "obe": {
388 | "ILO": "dV.c ,bv* bvDb!9dFE bvDdV$c63d!)",
389 | "PLO": "dV.c ,bv* bvDb!9dFE bvDb†1df'dV,d!)",
390 | "CLO": "dV.c ,bv* bvDb!9dFE dFdVBC 1",
391 | "attainment": "bvDb!-cVJdB" Å
392 | "outcomeMapping": "c (cr 'dFEbæ1bÆ'b¢" Å
393 | "CQI": "bvDb!-c6Jdb 'dFEc6*dV1 dFDbÆHb0)",
394 | "courseFile": "dVDd 'dFEd&1c "
395 | }
396 | }
397 |

```

FILE: src/locales/ar/gamification.json

TYPE: .json | LINES: 1-88 | SHA256: 91686a5494a5f01d1823d4e122abff411394ee5b7cbc385bf9bbcb7f2719995e

```

1 | {
2 |   "xp": {
3 |     "title": "dfBbv7 bvDbæ(c )",
4 |     "earned": "+{{amount}} dfBcv) bæ(c )"
5 |     "rewardEarned": "b!E d63b, Ed6'd #b' " Å
6 |     "total": "bv,dV'dFJ dfBbv7 bvDbæ(c )",
7 |     "history": "c6,dB Fd&'cr 'dF.b†1b' " Å
8 |     "sources": {
9 |       "login": "b!3bÆJdB 'dF/bæHdB 'dFJd†Ed¢" Å
10 |       "submission": "b!3dFJdR 'dF*d6Dd!A",
11 |       "grade": "bv5b0'c 'dF/c ,b' " Å
12 |       "journal": "bv/bæ'dB 'dFJd†Ed!)",
13 |       "streakMilestone": "bvFbÆ'c' 'dF3dF3dF)",
14 |       "perfectDay": "d!HdR Eb†'dFJ",
15 |       "firstAttempt": "dVCbvAb6) bvDdV-bvHdF) bvDb6HdFI",
16 |       "perfectRubric": "b01bÆ) d6'dVDdb' Ad¢ 'dFEc-'d!Jc " Å
17 |       "badgeEarned": "cF'c ) dVCb!3b†)"
18 |     }
19 |   },
20 |   "streaks": {
21 |     "title": "c6Dc6Db' *c6,d!D bvDb0.d†D",
22 |     "days": "c6Dc6Db' .†6÷VçG×0 Jd†E",
23 |     "atRisk": "c6Dc6Db!C d J bæ7c " Å
24 |     "lost": "bvFd&7c-* bvDc6Dc6Db'" Å
25 |     "freeze": "b!,dVJb0 'dF3dF3dF)",
26 |     "freezeAvailable": ">{{count}} b!,dVJb0 Eb!'b0" Å
27 |     "freezeCost": "bvDb!CdFAb"¢ # Fd&7b' .b†1b' " Å

```

```

28 |     "milestone": "0=Ý% bVfBÆ'c" 3dF3dF) {{count}} d!HdR "
29 | },
30 | "badges": {
31 |   "title": "bvDcF'c 'b¢"Ä
32 |   "earned": "b!E bVDb05d†D c-Dd' 4bv1b' "Ä
33 |   "collection": "dV,dVHC-) bVdCf'c 'b¢"Ä
34 |   "mystery": "cF'c ) c! 'dV6b'"Ä
35 |   "mysteryHint": "b6CdVD bVDb!-b0Jbv* bVdV.d Jb' Dd *b0Gbr"Ä
36 |   "locked": "dVbD Db'"
37 | },
38 | "mystery": {
39 |   "overlayLabel": "dVCbvAb6) c! 'dV6b'"
40 | },
41 | "leaderboard": {
42 |   "title": "dFHB0) bVdDv*cV/c Jdb"Ä
43 |   "rank": "bVDb!1b!Jb,"Ä
44 |   "player": "bVdCv'dF(",
45 |   "xpTotal": "bV,dV'dfJ dfBbv7 bVDbæ(c )",
46 |   "level": "bVdDv3b!Hd'"Ä
47 |   "gold": "c Gb†J",
48 |   "silver": "d 6d¢"Ä
49 |   "bronze": "b†1d†Fc&J"
50 | },
51 | "transactions": {
52 |   "title": "c6,dB 'dFEC-'dVDbv*",
53 |   "filters": {
54 |     "all": "bVdD6D",
55 |     "earnings": "bVdDVCb!3b†'b¢"Ä
56 |     "spending": "bVdDv5c Hd 'b¢"
57 |   },
58 |   "empty": "dF' b!HbÆ/ dV9bvEdF'b¢â"Ä
59 |   "showing": "c-1cb .¶g&0××Üg..F÷×0 Edb ..F÷F Ç×0"Ä
60 |   "previous": "bVdC6'b†B",
61 |   "next": "bVDb!'dFJ",
62 |   "unit": "dfBcv) bæ(c )",
63 |   "error": {
64 |     "title": "b!9c Qc *b0Ed!D dV9bvEdF'b!C",
65 |     "body": "b!9c Qc *b0Ed!D c6,dB Ec-'dVDbv*d2 Ad¢ 'dFHD&* bVDb0'dfJ. d!1bÆI bVdDv-bVdHd) dV1b' #bæ1d'â"Ä
66 |     "toast": "d 4dB *b0Ed!D c6,dB 'dFEC-'dVDbv*"
67 |   }
68 | },
69 | "habits": {
70 |   "title": "bVdC-'b0'b¢ 'dFJd†Ed!)",
71 |   "login": "b!3bÆJdB 'dF/bæHdB"Ä
72 |   "submit": "b!Bb0JdR"Ä
73 |   "journal": "bVdD!HdVJb'"Ä
74 |   "read": "bVdD&1bv!b'"Ä
75 |   "perfectDay": "d!HdR Eb¶!dfJ! b!E bVCdV'dB ,dVJc' 'dF9bv/bv* 0<ß%",
76 |   "almostThere": "b6HcFCb¢ #d6EdB .¶† &-G×0 Dd!HdR Eb¶!dfJ."
77 | },
78 | "level": {
79 |   "title": "bVdDv3b!Hd'"Ä
80 |   "current": "bVdDv3b!Hd' .¶ÆwFVÇ×0"Ä
81 |   "levelUp": "bv1b!Bbv! d J bVdDv3b!Hd' f!0'"Ä
82 |   "nextLevel": "{xp} dfBcv) bæ(c ) dFDDv3b!Hd' 'dF*bVdD¢"Ä
83 |   "levelUpLabel": "bv1b!Bbv! d J bVdDv3b!Hd'"Ä
84 |   "overlayLabel": "bVDbv1b!Bbv! bVdD' 'dFEC6*d†I {{level}}",
85 |   "dismiss": "bv6c!7 d J b6J dVCbvF dFDbv:dF'd""
86 | }
87 | }
88 |

```

FILE: src/locales/ar/glossary.md

TYPE: .md | LINES: 1-115 | SHA256: 5c0ac915e723e2975ed12e257887a45c247ea12d8c1879ed8146e166f37395dd

```

1 | # Qatar MOEHE MSA Glossary
2 |
3 | ## Outcome-Based Education (OBE) Terminology
4 |
5 | ### Core Concepts
6 |
7 | | English | Arabic (MSA) | Context |
8 | | ----- | ----- | ----- |
9 | | Outcome-Based Education | bVDb!9dFJdR 'dFBbv&dR 9dFI bVdDv.c ,bv* | Educational philosophy |
10 | | Learning Outcome | dV.c , bVDb!9dFE | Specific competency or skill |
11 | | Institutional Learning Outcome (ILO) | dV.c , bVDb!9dFE bVdDv$c63d¢ | Ä -ç7F-GWF-0â×v-FR 60× WfVæ7' | Ä
12 | | Program Learning Outcome (PLO) | dV.c , bVDb!9dFE bVDb†1df'dV,d¢ | Ä &0w& 00ÆwFVÄ 60× WfVæ7' | Ä
13 | | Course Learning Outcome (CLO) | dV.c , bVDb!9dFE bVdDvBC 1d¢ | Ä 6÷w'6R0ÆwFVÄ 60× WfVæ7' | Ä
14 | | Sub-CLO | dV.c , bVDb!9dFE bVdD 1c-J | | Sub-competency within a CLO |
15 |
16 | ### Assessment & Evidence
17 |
18 | | English | Arabic (MSA) | Context |
19 | | ----- | ----- | ----- |
20 | | Assessment | bVDb!Bd!JdR | Ä 0V 7w&V0VçB 0b ÄV &æ-ær | Ä
21 | | Evidence | bVDb0Dd!D / bVDb†Jdf) | | Proof of learning achievement |
22 | | Rubric | dV9bvJd!1 bVDb!Bd!JdR | Ä 66÷&-ær wV-FR v-F, 7&-FW&- | Ä
23 | | Criterion | dV9d!'c | Ä 6-ævÆR Wf ÇV F-0â 7F æF &B | Ä
24 | | Attainment | bVDb!-d&B / bVDbv*d&'db Ä 6†-wFV0VçB æwFVÄ 0b ä ÷wF600R | Ä
25 | | Attainment Level | dV3b!Hd' 'dF%b!BbvF | | Classification (Excellent, Satisfactory, Developing, Not Yet) |
26 |
27 | ### Bloom's Taxonomy
28 |
29 | | Level | Arabic (MSA) | Verbs (Sample) |
30 | | ----- | ----- | ----- |
31 | | Remembering | bVDb!0d61 | | d! *c Cc d!3b! /c-J Ä Jc-1e A |
32 | | Understanding | bVdD GdR | Ä JcF1b0 d!Hcf- Ä Jd 3c | Ä
33 | | Applying | bVDb!7b†Jd" | Ä Jcv(d& d!3b!.b0E Ä JdfAc | Ä
34 | | Analyzing | bVDb!-dFJdB | Ä Jb0DdF d!Bbv1df d!Ed!2 |
35 | | Evaluating | bVDb!Bd†JdR | Ä Jd&Je E Ä Jb0CdV d!c 1 |
36 | | Creating | bVDbV(b0'c' | Ä Jdf*bÆ d!(b!Cc d!5dVE |
37 |
38 | ### Accreditation & Quality
39 |

```

English	Arabic (MSA)	Context
Accreditation	bvDbv9b Ebv/ bvDb6Cbv/d Edc	Ä öff-6- Ä &V6övä-F-öä öb V Ä-G' Ä
Continuous Quality Improvement (CQI)	bvDb -c6Jdb 'dFEc6*dV1 dFDbÄHb0	Closing the loop cycle
Gap Analysis	b -dFJdB 'dFABÄHbv*	Identifying deficiencies
Curriculum	bvDdVFdv, bvDb01bv3dç	Ä 6÷W'6R 6öçFVçB æB 7G'V7GW&R Ä
Syllabus	bvDdVBC 1 bvDb01bv3dç	Ä 6÷W'6R ÷WFÄ-æR æB &W V-&VÖVçG2 Ä
Course File	dVDd 'dFEd&1c	Ä 6ö× &V†Vç6-fR 6÷W'6R Fö7VÖVçF F-öä Ä

Mapping & Alignment

English	Arabic (MSA)	Context
Mapping	bvDc (cr ö 'dF*d†'d B	Connecting outcomes across levels
Alignment	bvDdV-bv0bv)	Ensuring consistency
Weight	bvDd†2db ö 'dFFc6(b' Ä &VÆ F-fR -x ÷'F æ6R f ö R' Ä	
Coverage	bvDb :cvJb' Ä W†FVçB öb ÷WF6öÖR -æ6çW6-öä Ä	
Prerequisite	bvDdV*cvDb, 'dF3bv(d" Ä &W V-ÄVB &-÷" ¶æ÷vÆVFvR Ä	

Gamification & Engagement

English	Arabic (MSA)	Context
Experience Points (XP)	dfBbv7 bvDbæ(c)	Reward for learning activities
Level	bvDdV3b Hd' Ä &öw&W76-öä F-W" Ä	
Badge	bvDcF'c)	Achievement recognition
Streak	bvDc6Dc6Db' Ä 6öç6V7WF-fR F -ç' Væv vVÖVçB Ä	
Leaderboard	dFHb0) bvDb 1b Jb, Ä & æ¶-æR F-7 Ä' Ä	
Habit	bvDc-'bö)	Daily learning practice

Platform-Specific Terms

English	Arabic (MSA)	Context
Dashboard	dFHb0) bvDb -d6E	Main interface
Profile	bvDdVdD 'dF4bæ5dç Ä W6W" 66÷VçB -æf÷&ö F-öä Ä	
Notification	bvDbV4c-'c Ä æW'B ÖW76 vR Ä	
Preference	bvDb AcFJdB Ä W6W" 6WGF-æR Ä	
Theme	bvDdV8dv1	Light/Dark mode
Language	bvDdF:b' Ä T' Ä æwV vR 6VÆV7F-öä Ä	

Roles

English	Arabic (MSA)	Context
Admin	bvDdV3bFHDß Ä 7-7FV0 F0-æ-7G& F÷" Ä	
Coordinator	dVFc6B bvDb†1df'dV,	Program coordinator
Teacher	bvDdV9dFE	Instructor
Student	bvDcv'dF(	Learner
Parent	d†Ddç 'dF#dV1	Guardian

Status & States

English	Arabic (MSA)	Context
Active	df4cr Ä 7W'&VçFç' Væ &ÆVB Ä	
Pending	d&Jb0 'dF'df*c†'c Ä v -F-æR 7F-öä Ä	
Completed	dVCb EdB Ä f-æ-6†VB Ä	
In Progress	d&Jb0 'dF*dFAd 0	Ongoing
Suspended	dVHd&Hd Ä FV× ÷& &-ç' F-6 &ÆVB Ä	
Verified	dVHb¶B	Confirmed

Translation Notes

- **MSA (Modern Standard Arabic)**: Use formal Arabic suitable for educational contexts, not colloquial dialect
- **Gender**: Use masculine forms as default (e.g., "bvDcv'dF(" for student); context will clarify when feminine
- **Technical Terms**: Preserve English acronyms (ILO, PLO, CLO, XP, CQI) in parentheses when first introduced
- **Consistency**: Always use the same Arabic term for the same English concept across all translation files.
- **Localization**: Dates, numbers, and currency follow `ar-QA` locale conventions (Arabic-Indic numerals, Hij

References

- Qatar Ministry of Education and Higher Education (MOEHE) official terminology
- UNESCO OBE guidelines (Arabic translations)
- Bloom's Taxonomy revised edition (Anderson & Krathwohl, 2001)

FILE: src/locales/ar/student.json

TYPE: .json | LINES: 1-897 | SHA256: d03a4f01b77e7ba6c268a88d1cb3b8615e835152fc728440af9edca4269f70b6

```

1 | {
2 |   "dashboard": {
3 |     "title": "dFHb0) b|-d6E bvDcv'dF(",
4 |     "welcome": "cV(bv- bvDbæJc {{name}} Ø=ÜK",
5 |     "subtitle": "bvDd|C c -dF*d2 'dF*c-Dd|Ed|) bvDd|HdR"Ä
6 |     "upcomingDeadlines": "bvDdVHbv9d|/ bvDdfGbv&d|) bvDd&'böEb'"Ä
7 |     "learningPath": "dv3bv1 bvDb|9dFE",
8 |     "dailyHabits": "bvDc-'bö'bç 'dFJd†Ed|)",
9 |     "greeting": {
10 |       "morning": "cV(bv- bvDbæJc "Ä
11 |       "afternoon": "dv3bv! bvDbæJc "Ä
12 |       "evening": "dv3bv! bvDbæJc "
13 |     },
14 |     "momentum": "d†'cVD bvDb|Bb0E - d6D bæ7d†) b|-c6(.",
15 |     "xp": "dfBbv7 bvDbæ(c )",
16 |     "level": "dv3b|Hd' .¶ÆwFVç×0"Ä
17 |     "levelLabel": "bvDdV3b|Hd'"Ä
18 |     "courses": "bvDdVBC 1bv*",
19 |     "completed": "dVCb|EdB"Ä
20 |     "avgAttainment": "dv*d†3cr 'dF*b05d|D",
21 |     "streak": "bvDc6Dc6Db'"Ä
22 |     "noDeadlines": "dF' b|HbÆ/ dVHbv9d|/ dfGbv&d|) d&'böEb'â 'c6*dV*c' (bvDbv3b|1bv-b'â"Ä
23 |     "yourProgress": "b|Bb0Ed2"Ä
24 |     "totalXP": "bv,dV'dFJ dfBbv7 bvDbæ(c )",

```

```
25 | "xpAvailable": "dfBbv7 bVDbæ(c ) bVdV*bv-b'"Å
26 | "currentLevel": "bVdV3b;Hd' dF-bVdD¢"Å
27 | "loginStreak": "c6Dc6Db' *c6,d;D bVDbö.d†D",
28 | "daysStreak": "Ø=Y% {{count}} d;HdR"Å
29 | "assignmentsDone": "bVDb;CdFJd' b¢ 'dFedf,c&)",
30 | "viewXPHistory": "c-1cb 3bÆD dfBbv7 bVDbæ(c )",
31 | "completeOnboarding": "b6CdVD bVDb;Gd; &b'"Å
32 | "completeOnboardingDesc": "b6CdVD dVdD C bVdCf.cVJ dFAb;- bVDb;HcVJbv* bVdV.cV5b' Hd63b, Fd&'cr 'dF.b†1b'â"Å
33 | "startNow": "bv(bö# bVDb&F",
34 | "completeAssessment": "b6CdVD bVDb;Bd;JdR"Å
35 | "completeAssessmentDesc": "b;.cvJb¢ (c-6 bVDb6Bc6'dR #b¶Fbv! bVDb;Gd; &b'â #d6EdFGbr DdF-cVHdB 9dFI b;.cVJcR CbvEdBâ"Å
36 | "completeNow": "b6CdVD bVDb&F",
37 | "recentAnnouncements": "bVDbV9dF'df' b¢ 'dF#bæJc )",
38 | "closNeedingAttention": "dV.c ,bv* bVDb;9dFE bVDb;J b;-b; 'bÅ 'dv*dV'dv'd²"Å
39 | "myTeam": "d 1d;Bd¢"Å
40 | "challenges": "bVDb;-böJbv*",
41 | "target": "bVdV/d "Å
42 | "team": "d 1d;B",
43 | "coursewide": "c-Dd' Ec6*d†I bVdDVBc 1",
44 | "individual": "d 1böJ",
45 | "viewAllChallenges": "c-1cb ,dVJc' 'dF*bÖ/d;' b¢ ±.¶6÷VçG×Ö'"Å
46 | "attendance": "bVDbö6d†1",
47 | "leagueTier": "d &b' 'dF/d†1d¢"Å
48 | "primaryCta": {
49 |   "region": "bVDbv,c 'b 'dF*bVdD¢ 'dFed†5d' (dr"Å
50 |   "heading": "bæ7d†d2 'dF*bVdD;)",
51 |   "completeProfile": {
52 |     "label": "b6CdVD bVDb;Gd; &b'"Å
53 |     "description": "b6CdVD dVdD C bVdCf.cVJ dFAb;- bVDb;HcVJbv* bVdV.cV5b' Hd63b, Fd&'cr 'dF.b†1b'â"Å
54 |     "cta": "bv(bö# bVDb&F"
55 |   },
56 |   "finishProfile": {
57 |     "label": "b6CdVD bVDb;Bd;JdR"Å
58 |     "description": "b;.cvJb¢ (c-6 bVDb6Bc6'dR #b¶Fbv! bVDb;Gd; &b'â #d6EdFGbr DdF-cVHdB 9dFI b;.cVJcR CbvEdBâ"Å
59 |     "cta": "b6CdVD bVDb&F"
60 |   },
61 |   "submitAssignment": {
62 |     "label": "c6De E b;CdFJd C bVDb;'dFJ",
63 |     "description": "{[title]} dV3b;-d" Bc Jb†d² r 3dFQdVG dF*b†Bd' 9dFI bVdV3bv1 bVdCv-d;-.",
64 |     "cta": "bvAb;- bVDb;CdFJd "
65 |   },
66 |   "continueCourse": {
67 |     "label": "b;'b†9 dVBc 1d2"Å
68 |     "description": "b;'b†9 dVF bÖJb² *d†Bd * d†-bvAc, 9dFI c&.dVc.",
69 |     "cta": "c-1cb 'dFed&1c 'b¢"
70 |   },
71 |   "reviewFeedback": {
72 |     "label": "c 'bæ9 dVDbv-c†'b;C",
73 |     "description": "bv7e Dc' 9dFI b6-bö+ bö1bÆ'b;C d†EdF'bÖ8bv*d2 Db;*c-DdR Edb 9dVDd2â"Å
74 |     "cta": "c-1cb 'dF*d&dR"
75 |   }
76 | }
77 | }
78 | "team": {
79 |   "title": "d 1d;Bd¢"Å
80 |   "unassignedTitle": "dF3b¢ Ad¢ Ac Jd" (c-/",
81 |   "howItWorksDescription": "b;*d;- dFC bVdD 1d' 'dF*c-DdR ,df(bvK bVdD' ,df( dV9 c&EdF'bFc - b;Cc6(d†F dfBbv7 bVDbæ(c ) dV9bvK`Å Hb;1
82 |   "joinOrCreate": "bvFcFE bVdD' Ac Jd" #d, #df4bb Ac Jd&d²"Å
83 |   "teacherAssignNote": "d&/ d;Bd†E dV9dFed2 #d;6bvK b†*c-Jd;Fd2 Ad¢ Ac Jd" DdVBC 1d2â"
84 | },
85 | "courses": {
86 |   "title": "dVBc 1bv*d¢"Å
87 |   "subtitle": "bv7e Dc' 9dFI dVBc 1bv*d2 'dFEc6,e Db' Hb;BböQdVC d†*d6Dd;Abv*d2â"Å
88 |   "taughtBy": "d;/c Qc6G",
89 |   "progress": "bVDb;BböQdR"Å
90 |   "progressLabel": "b;BböQdR 'dFed&1c ¢ .. W&6VçG×ÖR"Å
91 |   "nextUp": "bVDb;'dFJ",
92 |   "due": "d;3b;-d" Ad¢ .¶F Fw×Ö"Å
93 |   "noDueDate": "dF' d;HbÆ/ dVHC-/ dfGbv&d¢"Å
94 |   "noUpcomingWork": "dF' b;HbÆ/ dVGbvE d&'böEb'"Å
95 |   "attainment": "bVDb;-cVJdB"Å
96 |   "assignments": "bVDb;CdFJd 'b¢"Å
97 |   "modules": "bVdD†-bö'b¢"Å
98 |   "continueWhere": "b;'b†9 dVF bÖJb² *d†Bd *",
99 |   "dueShort": "d;3b;-d" Ad¢ .¶F Fw×Ö"Å
100 |   "stuck": "dVd b;Hbv,dr 5c-Hb†) d J dvÖbr 'dFed&1c ",
101 |   "tutorPrompt": "bv7dF( dVF bVdV9dFE bVdC Cd¢ 4c -bvK dVHbÆ6bvK.",
102 |   "ask": "bv3b6D",
103 |   "detail": {
104 |     "title": "b;Abv5d;D bVdDVBc 1",
105 |     "backToCourses": "bVdC-Hbö) bVdD' 'dFed&1c 'b¢"Å
106 |     "loadErrorTitle": "b;9c 1 b;-dVJdB *d 'cVJdB 'dFed&1c "Å
107 |     "loadError": "b;9c 1 b;-dVJdB (c-6 b;Abv5d;D bVdDVBc 1. bÖ'd†D dV1b' #bæ1d'â"Å
108 |     "courseNotFoundTitle": "bVdDVBc 1 c;Jc Eb;'bÖ"Å
109 |     "courseNotFound": "b;9c 1 b;-dVJdB Gc ' bVdDVBc 1.",
110 |     "progressLabel": "bVDb;BböQdR"Å
111 |     "attainmentValue": "b;-cVJdB .¶6÷VçG×ÖR"Å
112 |     "noAttainment": "dF' b;HbÆ/ b†JbvFbv* b;-cVJdB"Å
113 |     "stats": {
114 |       "modules": "bVdD†-bö'b¢"Å
115 |       "materials": "bVdDVHbv/",
116 |       "assignments": "bVDb;CdFJd 'b¢"Å
117 |       "attainment": "bVDb;-cVJdB"
118 |     },
119 |     "continueTitle": "b;'b†9 dVF bÖJb² *d†Bd *",
120 |     "openAssignment": "bvAb;- bVDb;CdFJd "Å
121 |     "noOpenWork": "dF' b;HbÆ/ d†'bÆ(bv* d&1d;(b'â"Å
122 |     "announcements": "bVDbV9dF'df' b¢"Å
123 |     "announcementsDescription": "b&.c 'dF*bÖ/d;+bv* dVF d 1d;B bVdDVBc 1.",
124 |     "pinned": "dv+b†Qb¢"Å
125 |     "noAnnouncements": "dF' b;HbÆ/ bV9dF'df' b¢ DdvÖbr 'dFed&1c (c-/.",
126 |     "modules": "bVdD†-bö'b¢"Å
127 |     "modulesDescription": "bvAb;- d†-bö) dF*cVAbö 'dFed†bö 'dFedf4d†1b' (bö'bæDdv'.",
128 |     "noPublishedModules": "dF' b;HbÆ/ d†-bö'b¢ Edf4d†1b' (c-/.",
```

```

129 "noMaterials": "dF' b!HbÆ/ dVHbv/ dVFcFHC ) b†9bôâ"Å
130 "locked": "dVBd D",
131 "items": "{count}} c-FcV1",
132 "selectMaterialTitle": "bv.b!1 dV'bô) dF9c 6dv' dvFbr"Å
133 "selectMaterialHint": "b!5d - d†-bô) dVF bvDd!3bv1`Å +dR 'd *bô Ebv/b' Dd&1bv!b!Gbr #d, 9c 6dv'.",
134 "readTimer": "dV$d&* bvDd&1bv!b'"Å
135 "readCompleted": "bvCb!EdB 'bô*c6'b, 9bv/b' 'dFBc 'b )",
136 "reading": " {count}} b² Bc 'b )",
137 "openLink": "d *bô 'dFed†1bô"Å
138 "openFile": "b!Fc&JdB #d, 9c 6 bvdDvDd "Å
139 "noTextBody": "dF' d!HbÆ/ dV-b!Hd' FcVJ dV1d B b†9bôâ"
140 }
141 },
142 "assignments": {
143 "title": "bvDb!CdFJd 'b¢"Å
144 "submitAssignment": "b!3dFJdR 'dF*d6Dd!A",
145 "uploadFile": "c Ac' EdFA",
146 "submissionConfirmed": "b!E b!#d6Jbô 'dF*c6Dd!E!",
147 "lateSubmission": "dvôbr *c6Dd!E dV*b6.c â"Å
148 "deadlinePassed": "bvFb!Gd' 'dFed†9bô 'dFFdv'bFJ dFDb!3dFJdRâ"Å
149 "dueIn": "d!3b!-d" .dF'dB .F-FôWxô"Å
150 "list": {
151 "title": "bvDb!CdFJd 'b¢"Å
152 "subtitle": "b!b†9 bvdB69dV'dB 'dFBbv/dV) d†'dF*c6Dd!Ebv* bvdDV*b6.c ) d†Ebr *dR %df,bv2dr (bvDd 9dBâ"Å
153 "searchPlaceholder": "bv(bô+ d J bvDb!CdFJd 'b¢âââ"Å
154 "allCourses": "d6D bvdDVbC 1bv*",
155 "courseFallback": "bvDdVbC 1",
156 "loadErrorTitle": "bvDb!CdFJd 'b¢ :d!1 dV*bv-b'"Å
157 "loadError": "b!9c 1 b!-dVJdB 'dF*d6Dd!Abv* bvdBæ'cV) b†C. bô'd†D dV1b' #bæ1d'â"Å
158 "status": {
159 "pending": "d&Jbô 'dF'df*c†'c "Å
160 "submitted": "b!E bvDb!3dFJdR"Å
161 "late": "dV*b6.c "Å
162 "overdue": "dV*b6.c ,bô'd²"
163 },
164 "marks": "{count}} bô1bÆ)",
165 "dueIn": "{time}}"
166 },
167 "detail": {
168 "backToAssignments": "bvDc-Hbô) bVDd' 'dF*d6Dd!Abv*",
169 "courseFallback": "bvDdVbC 1",
170 "loadErrorTitle": "b!9c 1 b!-dVJdB 'dF*d6Dd!A",
171 "loadError": "b!9c 1 b!-dVJdB Gc ' bvDb!CdFJd â -bvHdB Ec ) b6.c I.",
172 "notFoundTitle": "bvDb!CdFJd :d!1 dVHbÆHbô"Å
173 "notFound": "dvôbr 'dF*d6Dd!A dFE d!9bô Eb!bô'd²â"Å
174 "loading": "bÆ'c M bvDb!-dVJdB"Å
175 "facts": {
176 "due": "bvDdVHC-/",
177 "marks": "bvDbô1bÆ'b¢"Å
178 "reward": "bvDdVcbvAb6)",
179 "window": "df'd 0b' 'dF*b6.d!1"
180 },
181 "linkedClos": "{count}} dVF dV.c ,bv* bvDb!9dFE bvdV1b!(cv)",
182 "xpBonus": "dv6bv9d .¶xVCF- Æ-W!xx, Dd†Bbv7 bvdBæ(c )",
183 "submitTitle": "c6De E c-EdFC",
184 "submitDescription": "bv1d 9 dVDd C b¶E c6De Edr Bb†D bv:dF'd" FbvAc ) bvdDVHC-/ bvdDf6bv&dçâ"Å
185 "tapToUpload": "bv6c!7 dF1d 9 dVDd C",
186 "draftHint": "b!E bv.b!Jbv1dr 3bv(d&d³ç .¶æ ôWxô"Å
187 "fileValidationFailed": "d 4dB 'dF*bôBd" Edb 'dFedFA.",
188 "retryingUpload": "d 4dB 'dF1d 9 - b!*dR 'dFEbô'd†Db' Ec ) b6.c I ({count}}/3)...",
189 "submitting": "bÆ'c M bvDb!3dFJdRâââ"Å
190 "clearFile": "dv3bô 'dFedFA",
191 "lateWindow": "dF' d!2bvD b!%dVcbvFd2 'dF*c6Dd!E bæDbvd df'd 0b' 'dF*b6.d!1.",
192 "openWindow": "d!Ed6Fd2 'dF*c6Dd!E b†JdfEbr FbvAc ) bvdDVHC-/ dVAb!Hbô).",
193 "tutorTitle": "dVD b!-b!bâ %dFI dv3bv9bô) d&(dB 'dF*c6Dd!Eaô"Å
194 "tutorHint": "bv3b6D bvdV9dFE bvDc Cdç 9db Ed†6d†9 bvDb!CdFJd â"Å
195 "ask": "bv3b6D",
196 "statusTitle": "b!3dFJdVC",
197 "statusDescription": "b!b†9 b6-bô+ bô'dF) b!3dFJdR Ddvôbr 'dF*d6Dd!A.",
198 "submitted": "b!E bvDb!3dFJdR"Å
199 "late": "dV*b6.c "Å
200 "viewSubmission": "c-1cb 'dF*c6Dd!E",
201 "signing": "bÆ'c M b!,dvJc) 1bv(cr 'dFedFA...",
202 "noSubmission": "dFE b!3dFQdR Gc ' bvDb!CdFJd (c-/.",
203 "dueLabel": "bvDdVHC-/",
204 "windowLabel": "df'd 0b' 'dF*b6.d!1",
205 "windowValue": "{count}} c6'c-)",
206 "none": "dF' d!HbÆ/",
207 "bonusTitle": "c6JbvB bvdB6/bv!",
208 "bonusDescription": "d!3b!.bôE bvdDf8bvE cV9d†(b' Ebæ1bÆ'b¢ 'dF*c-DdR 'dFEC *b†7b' Dcf(cr 'dFed6'd "bçâ"Å
209 "bonusValue": "{multiplier}}x dv6bv9d Fd&cr 'dF.b†1b'"Å
210 "noBonus": "dF' b!HbÆ/ dVcbvAb6) cV9d†(b'"
211 }
212 },
213 "progress": {
214 "viewCLOProgress": "c-1cb *d&/dR Ebæ1bÆ'b¢ 'dF*c-DdR"Å
215 "title": "b!BbôEdç"Å
216 "cloProgress": "b!BbôE dV.c ,bv* bvDb!9dFE",
217 "xpHistory": "c6,dB Fd&'cr 'dF.b†1b'"Å
218 "attainment": "bvDb!-cVJdB"Å
219 "evidence": "bvDb6/dF)",
220 "noAssessments": "dF' b!HbÆ/ b!Bd!JdV'b¢ (c-/
221 },
222 "learningPath": {
223 "title": "dv3bv1 bvDb!9dFE",
224 "subtitle": "bv*b†9 bvdBæ7d†b¢ 'dFEb!bô) bvDb!dFJb' Adç 1bôDb!C b†'dFed&1c â"Å
225 "coursePicker": "bv.b!1 dVBc 1bvK",
226 "journey": "c -dF*d2 Adç 'dFed&1c "Å
227 "views": {
228 "journey": "bvDc -dF)",
229 "tree": "cF,c ) bvdDV9c Ab""
230 },
231 "bloomJourney": "dv3b!Hd!b¢ (dFHdR r 1bôDb!C",
232 "youAreHere": "b6Fbç Gdf!",

```

```
"levelDetail": "b!Abv5d!D bvDdV3b!Hd' "Ã
"mastery": "bvDbV*d&'db"Ã
"tasks": "bvDdVgbvE",
"milestones": "bvDdV-cv'b¢"Ã
"coachTip": "df5d!-b' 'dFEb01b, 'dF0d6J",
"coachContinue": "b! 'b†9 «{{title}}» dF*d&Hd! dv0br 'dFEc6*d†I d†Ab!- bvDdV-cv) bvDb! 'dFJb'â"Ã
"coachComplete": "bvCb!EdB Gc ' bvDdV3b!Hd'â 3b!Cd†F bvDdV1b0Db' 'dF*bvDd!) bÆ'dv2b' 9df/ b!-d&Jd' Eb!7dF(dv'.",
"coachLocked": "b6CdVD dV3b!Hd' (dFHdR 'dF3bv(d' (bvDbV*d&'db 'dFEcvDd†( dFAb!- dv0dr 'dFEc -dF).",
"unlockNext": "b0Bd" %b!BbvFbvK b†Fc6(b' .. W&6VçG×0j dFAb!- dV3b!Hd' (dFHdR 'dF*bvDd¢"Ã
"unlockRequirement": "b0Bd" .. W&6VçG×0j d J {{title}} dFdd *b0"Ã
"recentActivity": "bvDdf4bv7 bvDb6.d!1 d J dv0br 'dFEc6'c "Ã
"noRecentActivity": "b6CdVD dVgdV) b6H c6De Edv' dF*c†Gc Gdf'.",
"noStageAssignments": "dF' b!HbÆ/ dVGbVE dVBC 1 dV1b!(cv) b†Gc ' bvDdV3b!Hd' (c-./.",
"stageLocked": "b!Od *b0 Gc G bvDdV1b0Db' Ec' FdVH bv*d&'dFc.",
"emptyTitle": "d!c J bV9b0'b0 Ec6'c *c-DdVC",
"emptyDescription": "dF' b!HbÆ/ d†'bÆ(bv* dV1b!(cv) b†Gc ' bvDdVBC 1 b†9b0â 3b!8dv1 dvFbr 'dFEdvEb' 'dF*bvDd!) bvDb!J d!FcF1dv' bvdD",
"status": {
  "completed": "dVCb!EdB"Ã
  "submitted": "b!E bvDb!3dFJdR"Ã
  "available": "dV*bv-",
  "locked": "dVBd D"
},
"actions": {
  "continue": "dV*bv(c-)",
  "review": "dV1bv,c-)",
  "locked": "dVBd D"
},
"stages": {
  "baseCamp": "dV9c6Cc 'dF(b0'd!)",
  "campOne": "bvDdV9c6Cc 'dF#d†D",
  "campTwo": "bvDdV9c6Cc 'dF+bvFd¢ r *b!3dFB bvDb&F",
  "campThree": "bvDdV9c6Cc 'dF+bvDb²"Ã
  "campFour": "bvDdV9c6Cc 'dF1bv(c' "Ã
  "submit": "bvDd&Eb'"Ã
  "remember": {
    "title": "bvDb!0d61",
    "subtitle": "bv3b!/c-P bvDb6Ad6'c 'dF#c6'c6Jb'"
  },
  "understand": {
    "title": "bvDd GdR"Ã
    "subtitle": "bv4c - bvDdVAbvGd!E"
  },
  "apply": {
    "title": "bvDb!7b†Jd'"Ã
    "subtitle": "bv3b!.b0E bvDdV9c Ab' Ad¢ Ed†'d&A d†'d&9d!)"
  },
  "analyze": {
    "title": "bvDb!-dFJdB"Ã
    "subtitle": "bv1b†7 bvDb6Ad6'c HbvAb05 bvDb6FdV'cr"
  },
  "evaluate": {
    "title": "bvDb!Bd!JdR"Ã
    "subtitle": "b0'd 9 c-F bvDd&1bv1bv* b†'dF#b0Db'"
  },
  "create": {
    "title": "bvDbV(b0'c' "Ã
    "subtitle": "bv(d†P cFJb†'d² #cVJdF'd²"
  }
},
"tree": {
  "title": "dfEd, Ec-1d *d2"Ã
  "subtitle": "cF!dv/ d6Jd JdfEd, AdvEd2"Ã
  "overallMastery": "bvDbV*d&'db 'dF9bvE",
  "keepGrowing": "d†'cVD bvDdfEd, "Ã
  "strong": "d&Hd¢"Ã
  "good": "bÆJb0"Ã
  "developing": "d&Jb0 'dF*cvHd!1",
  "needsFocus": "d!-b! 'bâ *c Cd!2bvK",
  "tip": "b!bvHc" s j d J dV3b!Hd' (dFHdR 'dF-bvDd¢ Dd *b0 'dFAC 9 bvDb!'dFJ. b!FdVH bvDcF,c ) dV9 bv*d&'db CdB Ec -dF).",
  "strength": "b63c6C bvDdVCb!EdF) b!3bv9b0c c-Dd' 'dF5c-Hb0 %dFI bvDdV3b!Hd' 'dF*bvDd¢ Edb 'dF*d Cd!1."
},
"heatmap": {
  "plainSummary": {
    "title": "d6Jd *c6Jc 9bv/bv*d2"Ã
    "empty": "dFE b!3bÆQdB #d¢ 9bv/bv* b†9b0â 'bæ*c 9bv/b' 5c!Jc ) dF*b†/b2 (dv' bvDd!HdR "Ã
    "completion": "dFBB0 -bvAc†* c-Dd' ..& FW×0j dVF c-'b0'b!C bvDd!HdVJb'â"Ã
    "bestHabit": "b6Bd†I c-'b0'b!C dvJ {{habit}}.",
    "streak": "b6Fb¢ Ad¢ 3dF3dF) dVF {{count}} d!HdR r Hbv5dB 'dF*d&/dR "Ã
    "encourage": "d6D bæ7d†) cv:d!1b' Ddv' d&JdV). d†'cVD bvDb!Bb0E!"
  },
  "habitLabels": {
    "login": "b!3bÆJdB 'dF/bæHdB"Ã
    "submit": "b!3dFJdR 'dF9dVD",
    "journal": "d6*bv(b' 'dFJd†Ed!)",
    "read": "bvDd&1bv!b' "Ã
    "meditation": "bvDb!#dVD",
    "hydration": "cF1b, 'dFEbv!",
    "exercise": "bvDb!Ebv1d!F",
    "sleep": "bvDdfHdR"
  }
},
"journal": {
  "title": "d!HdVJb' 'dF*b6EdB"Ã
  "newEntry": "bv/bædB ,b0Jb0"Ã
  "wordCount": "{{count}} d6DdV)",
  "minWords": "bvDb0/ bvDb6/dfI 50 d6DdV)",
  "saved": "b!E b0Ac, %b0.bvD bvDd!HdVJb'â"Ã
  "today": {
    "title": "b!#dVD bvDd!HdR"Ã
    "description": "b0He F dV' b!9dFEB!G`â HdV' b†/br 5c-(bvK`â #d, %df,bv2bvK cv:d!1bvK d!3b!-d" #db *b!0d61drâ"Ã
    "cta": "bvCb!( b!#dVbvK"
  },
  "journey": {
```

```
337 "title": "c -dF*d2 Ad¢ Cb!b†) bvDd!HdVJb'"Ä
338 "thisWeek": "dv0br 'dF#c6(d†9",
339 "entriesThisWeek": "bv/bæ'dF'b¢ Gc ' bvDb63b†Hc'"Ä
340 "dayStreak": "c6Dc6Db' 'dF#d!dR"Ä
341 "substantive": "b!#dVDbv* dVCb!EdF)",
342 "totalEntries": "bv,dV'dFJ bvDbV/bæ'dF'b¢"Ä
343 "weeklyStreak": "c6Dc6Db' 'dF*b6EdB Ddv0br 'dF#c6(d†9",
344 "daysOfWeek": "{count} dVF 7 b6JbvE"
345 },
346 "dailyPrompt": {
347 "label": "dV-d 2 bvDd!HdS¢"
348 },
349 "pastEntries": "bvDbV/bæ'dF'b¢ 'dF3bv(d&)",
350 "entryCount": "{count} bv/bæ'dF'b¢"Ä
351 "empty": {
352 "title": "dF' b!HbÆ/ bv/bæ'dF'b¢ Ad¢ 'dFJd†Ed!) b†9bò"Ä
353 "description": "bv(bò# d!HdVJb' 'dF*c-DdR r 'b6EdB Ad¢ /c 3 b6H dVAdvHdR HbvCc6( dFbBv7 bæ(c )."
354 },
355 "prompts": {
356 "title": "dV-d 2bv* bvDb!#dVD",
357 "hint": "bv.b!1 dV-d 2bvK dFDb†/b b6H bvCb!( b†-c Jb' #bòFbvG.",
358 "guided": "b!#dVD dVHbÆQdr"Ä
359 "use": "bv3b!bòE dv0br 'dFEb0Ac""Ä
360 "learned": "dV'c ' b!9dFEb¢ 'dFJd†Eaò"Ä
361 "confused": "dV' bvDc J b61b†CdFJaò"Ä
362 "proud": "b†Ebv0br #d *bæ1aò"
363 }
364 },
365 "leaderboard": {
366 "title": "dFHb0) bvDdV*cV/c Jdb"Ä
367 "yourRank": "b!1b!Jb†C",
368 "anonymous": "bvDd†6c' 'dFEbÆGd†D",
369 "anonymousHint": "bv3dVC dV.d J c-F bvDcVDbv( bvDb&c Jdb"Ä
370 "rankings": {
371 "title": "bvDb!1b!Jb,"Ä
372 "loadMore": "b!-dVJdB 'dFEc&Jbò"
373 },
374 "locked": {
375 "title": "b!Od *bò Dd†-b' 'dFEb!5bò1d!F c-Fbò 'dF6dV'dR 'dFEc&Jbò Edb 'dF7dF'b,"Ä
376 "description": "b†EbÆ1bò 'dF6dV'dR 'dFEc&Jbò Edb 'dF7dF'b, %dFI dV,dVHc-*d6 c6*c†Gc Gdf' bvDb!1b!Jb†'b¢ HbvDdVJbò'dFJbv*. d†'cVb
377 }
378 },
379 "portfolio": {
380 "title": "dVDd %df,bv2bv*d¢"Ä
381 "publicProfile": "dVDd 9bvE",
382 "togglePublicAria": "b!(bòJdB 'dFEdFA bvDc-'dR"Ä
383 "copyLinkAria": "df3bâ 'dF1bv(cr 'dFbBv(dB DdFEcF'c Cb'"Ä
384 "copyLink": "df3bâ 'dF1bv(cr"Ä
385 "copied": "b!E bvDdf3bâ"Ä
386 "permissionRequired": "b!*cvDb, 'dFEcF'c Cb' 'dF9bvEb' %c F bvDdV/c 3b'â Jb†Bd' EdFAd2 .bv5bvK b0*d' *d&HdR Eb0!c6*d2 (b!Ac-JdFG.",
387 "toast": {
388 "madePublic": "b65b†- dVDd C c-'dV'd2 'dF"db"Ä
389 "madePrivate": "b!E cf(cr 'dFEdFA c-Dd' .bv5",
390 "linkCopied": "b!E df3bâ 'dF1bv(cr %dFI bvDb0'd 8b'"Ä
391 "permissionDenied": "bvDdV4bv1d6) bvDc-'dV) c!Jc Ed 9e Db' Db03bv(d2 (c-/ .bv7dF( dVF dV/c 3b!C dVFb0 'dF%c F."
392 },
393 "kpi": {
394 "totalXP": "bv,dV'dFJ dfBbv7 bvDbæ(c )",
395 "level": "bvDdV3b!Hd'"Ä
396 "closMastered": "bvDdV.c ,bv* bvDdV*d&Fb'"Ä
397 "badgesEarned": "bvDb6Hc6Eb' 'dFEd6*c6(b'"
398 },
399 "sections": {
400 "cloMastery": "bv*d&db Ebæ1bÆ'b¢ 'dF*c-DdR"Ä
401 "badgeCollection": "dV,dVHc-) bvDb6Hc6Eb'"Ä
402 "journalEntries": "dV/bæDbv* bvDd!HdVJb'"Ä
403 "xpTimeline": "bvDbæ/d†D bvDc&EdfJ dFFd&'cr 'dF.b†1b'"Ä
404 "attainmentGrowth": "dFEd, 'dF*b05d!D"
405 },
406 "friendly": {
407 "skillsTitle": "bvDdVGbv1bv* bvDdV*d&Fb'"Ä
408 "strengths": "dfBbv7 bvDd&Hb'"Ä
409 "areasImproving": "dV,bvDbv* bvDb!-c6Qdb"Ä
410 "strengthsHint": "dV' b!d&Fdr (b†1bv9b'"Ä
411 "areasImprovingHint": "dV' b!9dVD c-Dd' *cvHd!1dr Dbv-d&d'2"
412 },
413 "noJournals": "dF' b!HbÆ/ dV/bæDbv* d J bvDd!HdVJb' (c-/.",
414 "general": "c-'dR"Ä
415 "chart": {
416 "cumulativeXP": "dfBbv7 bvDbæ(c ) bvDb!1bvCdVJb'"Ä
417 "xpValue": "{value} dfBcv) bæ(c )",
418 "avgAttainment": "dV*d†3cr 'dF*b05d!D"
419 },
420 "attainmentLevels": {
421 "Excellent": "dVEb!c""Ä
422 "Satisfactory": "dV0c 6d0"Ä
423 "Developing": "d&Jbò 'dF*cvHc "Ä
424 "Not_Yet": "dFE d!b0Bd" (c-/
425 }
426 },
427 "onboarding": {
428 "shell": {
429 "stepOf": "bvDbæ7d†) {{current}} dVF {{total}}",
430 "progressLabel": "b!Bb0QdR 'dF*dVJbf)",
431 "back": "bvDc6'b†B",
432 "skip": "b!.cvQdâ 'dF"db"Ä
433 "next": "bvDb!dFJ",
434 "loading": "bÆ'c M b!-dVJdB .cvHbv* bvDb!Gd!&b'"
435 },
436 "welcome": {
437 "fallbackName": "cV/d!Bdf'",
438 "greeting": "dV1b0(bvK {name}}! 0=ÜK",
439 "day1Description": "dFFbÆGe 2 c-'dFE b!9dFQdVC - dFF d!3b!c B bvDb6Ec #d6+c Edb 2 /d&'b†B.",
440 "fullDescription": "dFFd0cVD dVDd *c-De Ed2 HdFAb!- dFC b!,c (b' #d6+c *bæ5d!5bvK.",
```



```
441 | "benefits": {
442 |   "xpTitle": "bvCc6( b0*d' .¶ Õ÷VçG×Ò Fd7b' .b†1b'"Å
443 |   "xpDescription": "b!(b0# bVDdVCbvAb&* dVF bvDc6$bvD bVDb6HdB"Å
444 |   "tapTitle": "dFbc 'bç Ad&7' Å (dF' d6*bv(b'"Å
445 |   "tapDay1Description": "c6*b' #c6&dF) c61d!9b' r 3dvDb' HdVEb!9b'"Å
446 |   "tapFullDescription": "bæJbv1bv* b†3d!7b' Db†Fbv! dVDd *c-De Ed2 'dFCbvEdB"Å
447 |   "privateTitle": "bæ5d†5d!*d2 Eb0Ad†8b'"Å
448 |   "privateDescription": "dVDd C d†(d!'dF'bç *c-De Ed2 Jc†DbvF dV-dVJd!F"
449 | },
450 | "cta": "dFFb†/b2"
451 | },
452 | "assessmentIntro": {
453 |   "begin": "bv(b0#",
454 |   "personality": {
455 |     "title": "bvCb!4d Cd!A b!*c-De E c-Dd' #d 6dB HbÆG",
456 |     "description": "b63bfDb' 3c Jc-) d&Dd!Db' *d64d Cd!A b!9dVD d†*b0!c2 9dFI b6AcFd d†,drâ"Å
457 |     "estimatedTime": "b0HbvDdç /d&Jd&) d†'b0/b'"Å
458 |     "benefit1": "b!HcVJbv* b0!bv3d!) dV.cVQcV) dFC",
459 |     "benefit2": "c /d†/ bVDdV9dFQdR 'dF0d6J dV0bæ5e 5b' Dcv1d!Bb' *c-De Ed2"Å
460 |     "benefit3": "bvCc6( dFbBv7 bæ(c ) bV6bvAd!) dF%d6EbvD dVDd C bVDcF.cVJ"
461 |   },
462 |   "learning_style": {
463 |     "title": "bvCb!4d #c6Dd†( b!9dFQdVC",
464 |     "description": "bv3b!CcFA bVDcv1d' 'dF*dç *c6*d†9b, (dv' bVDb6Ad6'c 'dF,b0Jb0) d†*b!0d6Qc Gbrâ"Å
465 |     "estimatedTime": "b0HbvDdç 2 /d&'bFB",
466 |     "benefit1": "dF5bv&b0 /c 'c6Jb' *dF'c6( b!AcfJdF'b!c",
467 |     "benefit2": "cF1d†-bv* bVDdV9dFQdR 'dF0d6J b†'dF5d!;b' 'dF*dç *dF'c6(d2"Å
468 |     "benefit3": "bvCc6( dFbBv7 bæ(c ) bV6bvAd!) dF%d6EbvD dv0br 'dF*d&Jd!E"
469 |   },
470 |   "self_efficacy": {
471 |     "title": "d -cR 'dF+d&) bVDb6Cbv/d!Ed!)",
472 |     "description": "b6.b†1dF' b†Eb0I b¶Bb!C b0*d' Fb09dVC b†4d6D b6AcFd.",
473 |     "estimatedTime": "b0HbvDdç /d&Jd&) d†'b0/b'"Å
474 |     "benefit1": "b!4bÆJc' Hb6Gb0'd EcF(d†7b' 9dFI bVDdV3b!Hd' 'dFEdf'c6( dFC",
475 |     "benefit2": "b09dR 'dFEc-De E bVDc Cdç Jc Ce 2 b0Jb2 *c :b, Adç 'dF*cvHe 1",
476 |     "benefit3": "bvCc6( dFbBv7 bæ(c ) bV6bvAd!) dF%d6EbvD dv0br 'dFAb05"
477 |   },
478 |   "study_strategy": {
479 |     "title": "cvHe 1 c-'b0'b!c bVDb0!bv3d!)",
480 |     "description": "cF'c Cdf! d6Jd *b0!c2 'dF"db -b!I dFBb!1b0 Ebr Jdf,b0 Ec-C.",
481 |     "estimatedTime": "b0HbvDdç /d&Jd&*d!F",
482 |     "benefit1": "b!HcVJbv* dV.cVQcV) dF'c6*c 'b!JbÆJbv* bVDb0!bv3b'"Å
483 |     "benefit2": "bv1cf'b0 'dFEc-De E bVDc Cdç EcF(d†7 c-Dd' 9bv/bv*d2"Å
484 |     "benefit3": "bvCc6( dFbBv7 bæ(c ) bV6bvAd!) dF%d6EbvD dv0br 'dF*d&Jd!E"
485 |   }
486 | },
487 | "selfEfficacy": {
488 |   "title": "d -cR 'dF+d&) bVDb6Cbv/d!Ed!)",
489 |   "instructions": "d&Je E dV/d' +d&*d2 *bÆ'dr CdB 9b†'c ).",
490 |   "questionProgress": "bvDc6$bvD {{current}} dVF {{total}}",
491 |   "previous": "bvDc6'b†B",
492 |   "next": "bVDb!dFJ",
493 |   "complete": "bvFdv'b "Å
494 |   "saving": "bÆ'c M bVDb0Ac,âââ"
495 | },
496 | "personality": {
497 |   "title": "b!Bd!JdR 'dF4bæ5d!)",
498 |   "dimensionProgress": "{{dimension}} - bvDc6$bvD {{current}} dVF {{total}}",
499 |   "scaleLabel": "dVBd!c2 Dd!Cc *",
500 |   "previous": "bvDc6'b†B",
501 |   "next": "bVDb!dFJ",
502 |   "complete": "bvFdv'b "Å
503 |   "saving": "bÆ'c M bVDb0Ac,âââ"Å
504 |   "noQuestions": "dF' b!HbÆ/ b63bfDb' 4bæ5d!) dV*bv-b'â Jc ,d' 'dF*d†'cVD dv9 bVDdV3bFHDâ"Å
505 |   "dimensions": {
506 |     "openness": "bvDbvFd *bv-",
507 |     "conscientiousness": "d!Bc†) bVDcFEd!1",
508 |     "extraversion": "bvDbvFb†3bv7",
509 |     "agreeableness": "bvDdVBb†HdFJb'"Å
510 |     "neuroticism": "bVDc-5bv(d!)"
511 |   },
512 |   "likert": {
513 |     "stronglyDisagree": "dF' b6HbvAd" (cF/b'"Å
514 |     "disagree": "dF' b6HbvAd"Å
515 |     "neutral": "dV-bvJb0"Å
516 |     "agree": "b6HbvAd"Å
517 |     "stronglyAgree": "b6HbvAd" (cF/b'"
518 |   }
519 | },
520 | "learningStyle": {
521 |   "title": "b!AcfJdF'bç #c6Dd†( bVDb!9dFE",
522 |   "instructions": "bv.b!1 bVDbæJbv1 bVDc J d!Fbv3b†C b6Cb¶1.",
523 |   "questionProgress": "bvDc6$bvD {{current}} dVF {{total}}",
524 |   "scaleLabel": "bæJbv1bv* VARK",
525 |   "previous": "bvDc6'b†B",
526 |   "next": "bVDb!dFJ",
527 |   "complete": "bvFdv'b "Å
528 |   "saving": "bÆ'c M bVDb0Ac,âââ"Å
529 |   "noQuestions": "dF' b!HbÆ/ b63bfDb' #c6Dd†( b!9dFE dV*bv-b'â Jc ,d' 'dF*d†'cVD dv9 bVDdV3bFHDâ"Å
530 |   "disclaimer": "b!Od&/dæQdR *d 6d!Dbv* b63dFhb, 'dF*c-DdR Cb!Ec Jdb DdFHC-J bVDc 'b!J. dF' b!/-c-E bVDb6(b0'b² EcV'b†Bb' 'dF*b0!d!3
531 |   "day1": {
532 |     "title": "b!Bd!JdR #c6Dd†( bVDb!9dFE",
533 |     "body": "c6Jd0Bb0Ne E dv0br 'dF*d&Jd!E c-Dd' 4d6D b!Bd!JdV'bç Jd†Ed!) d&5d!1b' .dF'dB #c6(d†9d!C bVDb6HdFJdbâ 3b!Cc6( dFbBv7 bæ
534 |     "continue": "dv*bv(c-)"
535 |   }
536 | },
537 | "studyStrategy": {
538 |   "title": "bæ1b0 'c6*c 'b!JbÆJbv* bVDb0!bv3b'"Å
539 |   "instructions": "d&Je E d6E dV1b' *c6*bæ/dR CdB 'c6*c 'b!JbÆJb' /c 'c6).",
540 |   "dimensionProgress": "{{dimension}} - bvDc6$bvD {{current}} dVF {{total}}",
541 |   "scaleLabel": "dVBd!c2 'c6*c 'b!JbÆJbv* bVDb0!bv3b'"Å
542 |   "previous": "bvDc6'b†B",
543 |   "next": "bVDb!dFJ",
544 |   "complete": "bvFdv'b "Å
```

```
545 "saving": "bÆ'c M bVDb0Ac,âââ"Å
546 "noQuestions": "dF' b!HbÆ/ b63bfDb' 'c6*c 'b!JbÆJbv* b01bv3b' Eb! 'b0). d!1bÆI bVDb!Hbv5dB Ec' 'dFEc6$dtD.",
547 "likert": {
548   "never": "b6(b0'd2"Å
549   "rarely": "df'b01bvK",
550   "sometimes": "b6-d! 'df'd2"Å
551   "often": "c! 'dF(bvK",
552   "always": "b0'bFbvK"
553 },
554 "dimensions": {
555   "time_management": "bv/bv1b' 'dFhd&*",
556   "elaboration": "bVDb!AcVJdB"Å
557   "self_testing": "bVDbv.b!(bv1 bVdc 'b!J",
558   "help_seeking": "cvDb, 'dFEc6'c-/b'"
559 },
560 "day1": {
561   "title": "bÆ1b0 'c6*c 'b!JbÆJbv* bVDb01bv3b'"Å
562   "body": "c6Jd0Bb0Ne E dv0br 'dF*d&Jd!E c-Dd' 4d6D b!Bd!JdV'b¢ Jd!Ed!) d&5d!1b' .dF'dB #c6(d!9d!C bVDb6HdFJdbâ 3b!Cc6( dfBbv7 bæ
563   "continue": "dV*bv(c-)"
564 }
565 },
566 "fallback": {
567   "noQuestionsTitle": "dF' b0'bÆ) dFAB05 bVDb!Bb' 'dF"db"Å
568   "noQuestionsBody": "dF' b!HbÆ/ b63bfDb' +d&) dFC d J bVdDtBb¢ 'dF-bVdD¢â JdVCdFc dV*bv(c-) b!Bd!) bæ7dt!b¢ 'dF%-/bv/.",
569   "systemIssueTitle": "b!9c Qc *b0Ed!D dv0dr 'dF.cvHb'"Å
570   "systemIssueBody": "b0/b2 .cv# b6+df'b *b0Ed!D dv0dr 'dF#c6&dF). d!Ed6Fd2 'dFEb! 'b!9b' Hc6Fb0'd!D dV1b' #bæ1d' Dbv-d&'d2â"Å
571   "continue": "dV*bv(c-)"
572 },
573 "microAssessment": {
574   "title": "d -cR 3c Jc' Dd ..G- w×0"Å
575   "types": {
576     "personality": "bVdCf.cVJb'"Å
577     "self_efficacy": "bVdD6Abv!b' 'dF0bv*d!)",
578     "study_strategy": "bv3b!1bv*d!,d!) bVDb01bv3b'"Å
579     "learning_style": "b63dFhb, 'dF*c-DdR"Å
580     "baseline_prompt": "bVDbv.b!(bv1 bVdV(b0&d¢"
581   },
582   "estimatedMinutes": "-{minutes}" b0Bd!Bb'"Å
583   "description_one": "c6$bvd c61d!9 dt!b0/ dF*b03d!F dVdD C bVdCf.cVJ.",
584   "description_other": "{count}" b63bfDb' 3c Jc-) dF*b03d!F dVdD C bVdCf.cVJ.",
585   "completeNow": "b6CdVD bVDb&F",
586   "remindLater": "c Ce 1dfJ dF'b0BbvK",
587   "dismiss": "b! bVgDb 'dF*d&Jd!E bVdc61d!9",
588   "lastChance": "bVdD 1cV) bVDb6.d!1b' r 3d! *dR *bæ7d¢ Gc ' bV0br *dR *bÆ'dvDdr Ec ) b6.c I.",
589   "completed": "b6-c6Fb¢ ..¶ 0÷VçG×0 Fd&7b' .b!1b' r *dR *b0/d!+ dVdD C bVdCf.cVJ.",
590   "completeError": "b!9c Qc %d6Ebvd bVDb!Bd!JdRâ Jc ,d' 'dFEb0'd!Db' Ec ) b6.c I.",
591   "remindedLater": "dF' dV4d6Db' r 3df0d6Qc C dF'b0BbvK.",
592   "dismissError": "b!9c Qc *b0/d!+ bVDb!Bd!JdRâ Jc ,d' 'dFEb0'd!Db' Ec ) b6.c I."
593 }
594 },
595 "planner": {
596   "actions": {
597     "addTask": "bV6bvAb' EdvEb'"Å
598     "startSession": "b! /b ,dF3b'"
599   },
600   "suggestion": {
601     "label": "bÆDc6) b01bv3b' Ed&*c -b'"Å
602     "withCourse": "bÆDc6) b01bv3b'¢ .¶6÷w!6w×0"Å
603     "duration": "d *c ) b!1d6Jc" .¶0-çWFw7×0 /d&Jd&)",
604     "plan": "bæ7e 7 dFDbÆDc6)",
605     "ariaPlan": "bæ7e 7 dF,dF3b' /c 'c6) dV/b!Gbr .¶0-çWFw7×0 /d&Jd&)"
606   },
607   "goals": {
608     "exampleHeading": "b6Ad6'c #dv/bvA dFDdt/b "Å
609     "exampleHint": "b0/e / dv/d 'd2 #b0FbvG dF*b! 'b!9 b63btHc-C.",
610     "setGoals": "b! -b0Jb0 'dF#dv/bvA",
611     "types": {
612       "study_hours": "c6'c-'b¢ 'dF/c 'c6)",
613       "sessions_completed": "bVDbÆDc6'b¢"Å
614       "tasks_completed": "bVdDVGbV¢"
615     },
616     "target": {
617       "study_hours": "{count}" c6'c-'b¢"Å
618       "sessions_completed": "{count}" bÆDc6'b¢"Å
619       "tasks_completed": "{count}" dVgbV¢"
620     }
621   }
622 },
623 "recoveryPath": {
624   "title": "dV3bv1 bv3b!9bv/b' 'dF%b!BbvF",
625   "backToDashboard": "bVdc-Hb0) bVdD' Ddt-b' 'dF*b0CdR"Å
626   "empty": "dFE d! *dR 'dF9b!Hc 9dFI dV3bv1 bv3b!9bv/b' FcF7 dFGc G bVDdF*d!,b'â"Å
627   "unknownOutcome": "df*d!,b' 'dF*c-DdR"Å
628   "ready": "bÆ'dv2 dF%-b0) bVdDV-bvHdF)",
629   "inProgress": "d&Jb0 'dF*d&/dR"Å
630   "description": "b6CdVD bVDbæ7dt!b¢ 'dF*bVd!) dFAb!- bv9bv/b' Eb0'd!Db' 'dF'bæ*b! 'c Ad¢"Å
631   "optional": "bv.b!Jbv1d¢"Å
632   "openTutor": "d *b0 'dFEb01e 3 bVdc Cdc"Å
633   "startPractice": "b! /b 'dF*b01d!(",
634   "browseGroups": "bv3b!9c 'cb EbÆEd!9bv* bVDb01bv3b'"Å
635   "markComplete": "dt6c' 9dF'dV) dVCb!EdB"Å
636   "retry": "bv9bv/b' 'dF'bæ*b! 'c "Å
637   "retryAria": "bv9bv/b' 'dF'bæ*b! 'c "Å
638   "completeToUnlock": "b6CdVD bVDbæ7dt!b¢ Dd *b0 %-b0) bVdDV-bvHdF)",
639   "lockedAria": "b6CdVD bVDbæ7dt!b¢ 'dFEcvDdt!(b' Dd *b0 %-b0) bVdDV-bvHdF)",
640   "steps": {
641     "tutor": {
642       "title": "bÆDc6) bVdDV/c Qc2 'dF0d6J",
643       "description": "c 'bÆ9 bVdDVAbvGd!E bVDb63bv3d!) d J «{title}» dV9 bVdDV/c Qc2 'dF0d6J."
644     },
645     "practice": {
646       "title": "b63bfDb' *b01d!(d!)",
647       "description": "b6CdVD b63bfDb' (dV3b!Hd' 5c-Hb!) b6BdB DbV9bv/b' (df'b 'dFAdvE."
648     }
649   }
650 }
```

```
649     "peer": {
650       "title": "dV,dVHC-) b01bv3b' Ec' 'dF2dVDbv!",
651       "description": "bvFcFE bVDd' EbÆEd†9b' /c 'c6) b!9dVD c-Dd' 'dFEb†d†9 dfAc6G.",
652       "unavailable": "dF' b!HbÆ/ dV,dVHC-'b¢ /c 'c6) df4cv) dFGc ' bVDdVHCfHc'â"
653     }
654   },
655   "toast": {
656     "tutorComplete": "b!E b!3bÆJdB ,dF3b' 'dFEb01e 3 bVDc Cd¢ CdVCb!EdF)",
657     "practiceComplete": "b!E b!3bÆJdB 'd#c6&dF) bVDb! /c Jb†Jb' CdVCb!EdF)",
658     "updateFailed": "b!9c 1 b!-b0Jb² 'dF.cvHb"
659   }
660 },
661 "quiz": {
662   "loading": "bÆ'c M b!,dvJc' 'bæ*b†'c C bVDb!Cd!Ad¢âââ"Â
663   "unableToLoad": "b!9c Qc *b0Ed!D bVDbv.b!(bv1. d!1bÆI bVDc-Hb0) d†'dFEb0'd†Db' Ec ) b6.c I.",
664   "questionProgress": "bvDc6$bvD {{number}} dVF {{total}}",
665   "sessionProgress": "b!Bb0E bÆDc6) bVDbv.b!(bv1",
666   "exit": "bvDbæ1d†, dVF bVDbv.b!(bv1",
667   "loadingButton": "bÆ'c M bVDb!-dVJdBâââ"Â
668   "submitAnswer": "bv1c6'dB 'dF%bÆ'b†)",
669   "nextQuestion": "bvDc6$bvD bVDb!'dFJ",
670   "finishQuiz": "bvFdv'b 'dF'bæ*b†'c "Â
671   "recovery": {
672     "title": "bVDb!9bvAd¢ EcvDd†(",
673     "body": "dF/d!C dV3bv1 b!9bvAd0 FcF7 dF%b!BbvF dV.c , b!9dFE dV1b!(cr (dv0br 'dF'bæ*b†'c â #d6EdB .cvHbv* bVDb!9bvAd¢ Bb†D bv9bv/
674     "cta": "bv0dv( bVDd' Ec6'c 'dF*c-'d J"
675   },
676   "toast": {
677     "startFailed": "b!9c Qc (b0! bVDbv.b!(bv1. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
678     "submitFailed": "b!9c Qc %c 3bvD bVDbv.b!(bv1. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
679     "nextFailed": "b!9c Qc *b0Ed!D bVDc6$bvD bVDb!'dFJ. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
680     "selectAnswer": "d!1bÆI bv.b!Jb†1 bv,bv(b' Bb†D bVDbV1c6'dBâ"Â
681     "timeUp": "bvFb!Gd' 'dFHd&*! bÆ'c M bV1c6'dB 'bæ*b†'c C..."
682   },
683   "feedback": {
684     "correctTitle": "bv,bv(b' 5b0Jb0)!",
685     "correctBody": "b6-c6Fb¢ r 'cvQdF9 c-Dd' Ec 'bÆ9b' Ebr (c-/ bVDbv.b!(bv1 dFDb05d†D c-Dd' 4c - dVAcVQdBâ"Â
686     "incorrectTitle": "bv,bv(b' .bv7bf)",
687     "correctAnswerRevealPrefix": "bvDbV,bv(b' 'dF5b0Jb0) dvJ",
688     "reviewLater": "c 'bÆ9 bVDbv,bv(b' 'dF5b0Jb0) d†'dF4c - b†9b0 'dF'bæ*b†'c â"
689   },
690   "review": {
691     "title": "dV1bv,c-) bVDbv.b!(bv1",
692     "loading": "bÆ'c M b!-dVJdB Ec 'bÆ9b' 'dF'bæ*b†'c âââ"Â
693     "loadFailed": "b!9c Qc *b0Ed!D dV1bv,c-) bVDbv.b!(bv1. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
694     "backToDashboard": "bvDc-Hb0) bVDd' Dd†-b' 'dF*b0CdR"Â
695     "overallScore": "bvDb01bÆ) bVDbv,dV'dFJb"¢"Â
696     "perCloBreakdown": "b!AcVJdB 'dF/c ,bv* b03b, Ebæ1bÆ'b¢ 'dF*c-DdR"Â
697     "bloomsProgression": "bVDb! /c QbÆ Ad¢ *cVFd!A b†Dd†E",
698     "questionLabel": "bvDc6$bvD {{number}}",
699     "correct": "cv-d!-b'"Â
700     "incorrect": "bæ'cv&b'"Â
701     "verifiedExplanation": "cF1b0 Ed†+e B",
702     "aiExplanation": "cF1b0 'dF0d6'b 'dF'cV7df'c-J",
703     "getHelp": "bv-cVD c-Dd' Ec6'c-/b' Ad¢ Gc ' bVDdVHCfHc'"Â
704     "bloomLevel": "bvDdV3b!Hd' .¶ÆwFV¢×0"
705   }
706 },
707 "createTeam": {
708   "back": "bvDc-Hb0)",
709   "title": "bvFcF'b Ac Jd""Â
710   "noCoursesAvailable": "dF' b!HbÆ/ dVBc 1bv* b†Gbr Ac B d!4d6QdFGbr 'dF7dF'b, Eb! 'b0).",
711   "courseLabel": "bvDdVBC 1",
712   "selectCourse": "bv.b!1 dVBc 1bvK",
713   "teamNameLabel": "bv3dR 'dFAC Jd""Â
714   "teamNamePlaceholder": "dV+bvD: dV-bv1b†H bVDb†1dV,b'"Â
715   "inviteMembers": "b09d†) bVDb69cf'b ‡.¶7W&V¢G×00b (dv' d JdvE b6Fb¢'"Â
716   "noAvailableStudents": "dF' d!HbÆ/ cvDbv( dv*bv-d†F d J dv0br 'dFEd&1c â"Â
717   "selectAtLeastOne": "bv.b!1 c-6d†'d² Hbv-b0'd² 9dFI bVDb6BdB †Jb0*bv, bvDd 1d!B bVDd' '0b #c-6bv!).",
718   "submit": "bvFcF'b Ac Jd""Â
719   "validation": {
720     "nameMin": "d!,b, #db Jd6Hdb 'c6E bVDd 1d!B b01d Jdb 9dFI bVDb6BdB"Â
721     "courseRequired": "bv.b!1 dVBc 1bvK"
722   },
723   "toast": {
724     "sizeInvalid": "d!,b, #db JcfE bVDd 1d!B dVF 2 bVDd' b #c-6bv! (b†Ebr Ad!GdR #df*)",
725     "created": "b!E bVFcF'b 'dFAC Jd" #df* bVDd&'bf/."
726   }
727 },
728 "surveys": {
729   "title": "bvDbv3b!(d!'df'b¢"Â
730   "loadError": "b!9c Qc *b0Ed!D bVDbv3b!(d!'df'b¢â Jc ,d' 'dFEb0'd†Db' Ec ) b6.c I.",
731   "retry": "bv9bv/b' 'dFEb0'd†Db'"Â
732   "alreadyCompleted": "dFEB0 #d6EdF* dv0br 'dF'c6*b†JbvF b†'dFAC-D.",
733   "completed": "dVCb!EdB"Â
734   "toast": {
735     "answerAtLeastOne": "d!1bÆI bVDbv,bv(b' 9dFI c6$bvD d†'b0/ c-Dd' 'dF#d&D",
736     "submitted": "b!E bv1c6'dB 'dF'c6*b†JbvF! +15 dfBcv) bæ(c )",
737     "submitFailed": "b!9c Qc %c 3bvD bVDbv3b!(d!'db"
738   }
739 },
740 "badges": {
741   "title": "b6Hc6Eb!J",
742   "subtitle": "bv-b!AdB (bvDdV-cv'b¢ 'dF*d¢ -d&Bb!Gbr Hbv.b!1 b0*d' +dF'b¶) b6Hc6Eb' Db!+b†Jb!Gbrâ"Â
743   "pinned": "{{count}} dVF 3 dv+b†Qb!)",
744   "loadError": "b!9c Qc *b0Ed!D b6Hc6Eb!C. d!1bÆI bVDdV-bvHdF) dV1b' #bæ1d'â"Â
745   "retry": "bv9bv/b' 'dFEb0'd†Db'"
746 },
747 "learningProfile": {
748   "title": "dVdD 'dF*c-De E",
749   "subtitle": "b!3bv9b0 Fb!bf, b!Bd!JdV'b!C c-Dd' *bæ5d!5 b!HcVJbv* bVDb!9dFQdR Dd2â"Â
750   "reassess": "bv9bv/b' 'dF*d&Jd!Ebv*",
751   "completeness": "bvCb!EbvD bVDdVdD "Â
752   "personalization": "bÆ'dv2 dFDb! .cVJcR"Â
```

```

753 | "emptyTitle": "b6FcF& dVdD *c-De Ed2"Å
754 | "emptyBody": "b6CdVD bvDb;Bd;JdV'b¢ 'dFbcVJc ) dFAB;- b;AcfJdF'b¢ 'dF*c-De E d†'dF*d†5d; 'b¢ 'dFEbæ5cV).",
755 | "completeProfile": "b6CdVD dVdD J",
756 | "loadError": "b;9c Qc *b0Ed;D dVdD *c-De Ed2â Jc ,d' 'dFEb0'd†Db' Ec ) b6.c I.",
757 | "retry": "bv9bv/b' 'dFEb0'd†Db'"Å
758 | "learningStyle": "b;AcfJdF'b¢ 'dF*c-De E",
759 | "dominantStyle": "b6Bd†I b;AcfJdB Db0Jd3¢ ..7G-Æw×0"Å
760 | "studyStrategies": "bv3b;1bv*d; ,d; 'b¢ 'dF/c 'c6)",
761 | "selfEfficacy": "bvDb;Bb' 'dF#d6'b0JdVJb'"Å
762 | "personality": "c6Ebv' bvDb;9dFQdR"Å
763 | "overall": "bvDbV,dV'dFJ",
764 | "missingLearningStyle": "b6CdVD b;Bd;JdR #c6Dd†( bvDb;9dFQdR Dc-1cb Gc G bvDb;AcfJdF'b¢â"Å
765 | "missingStrategies": "b6CdVD b;Bd;JdR 'c6*c 'b;JbÆJbv* bvDb01bv3b' Dc-1cb Gc G bvDdf*bv&bÅâ"Å
766 | "missingEfficacy": "b6CdVD b;Bd;JdR 'dFcd 'b ) bvDc 'b;Jb' Dc-1cb Gc G bvDdf*bv&bÅâ"Å
767 | "missingPersonality": "b6CdVD b;Bd;JdR 'dF4bæ5d; ) dF9c 6 dv0dr 'dFFb; 'bf,.",
768 | "styles": {
769 |   "visual": "b†5c J",
770 |   "auditory": "c6Ec-J",
771 |   "read_write": "d&1bv;b' Hd6*bv(b'"Å
772 |   "kinesthetic": "c-EdFJ",
773 |   "multimodal": "dV*c-/b0 'dF#dFEbv7"
774 | },
775 | "strategies": {
776 |   "time_management": "bv/bv1b' 'dFHd*",
777 |   "elaboration": "bvDb;Hc6Qc' Ad¢ 'dF4c -",
778 |   "self_testing": "bvDbv.b;(bv1 bvDc 'b;J",
779 |   "help_seeking": "cvDb, 'dFec6'c-/b'"
780 | },
781 | "efficacy": {
782 |   "general_academic": "bvDb6Cbv/d;Ed;) bvDc-'dV)",
783 |   "course_specific": "bvDbæ'cV) b†'dFEd&1c "Å
784 |   "self_regulated_learning": "bvDb;9dFQdR 'dFEdf8e E c 'b;JbvK"
785 | },
786 | "traits": {
787 |   "openness": "bvDbvFd *bv-",
788 |   "conscientiousness": "bvDbv,b;Gbv/",
789 |   "extraversion": "bvDbvFb†3bv7",
790 |   "agreeableness": "bvDb;HbvAd'"Å
791 |   "neuroticism": "bvDb03bv3d;) bvDc-'cvAd;)"
792 | },
793 | "rail": {
794 |   "label": "c6JbvB dVdD 'dF*c-De E",
795 |   "whyTitle": "0>Yâ dFEbv0br Gc ' dVgdr"Å
796 |   "whyBody": "d;6b†7 b63dFHb, *c-De Ed2 7c Jd&) cF1b0 'dFec-De E bvDc Cd¢ Hb;1b;Jb, 'dF/c Hc2 (dV' d;Fbv3b†c.",
797 |   "completenessTitle": "bvDbvCb;EbvD",
798 |   "completenessEmpty": "b6CdVD b;Bd;JdVC bvDb6HdB Db†/b (df'b Gc ' bvDdVdD â"Å
799 |   "finishAssessments": "b6CdVD bvDb;Bd;JdV'b¢ 'dFbcVJc ) !."
800 | }
801 | },
802 | "settingsRail": {
803 |   "label": "dV9dFHdV'b¢ .cVHcVJb' 'dF%c-/bv/bv*",
804 |   "title": "0=Y b†JbvFbv*d2"Å
805 |   "body": "b;0cv(e B bæJbv1bv* bvDbV4c-'c 'b¢ HbvDdF:b' Ad†1bvK`Å HdF' b;†dR EcF'c Cb' #d¢ EdfGbr Ec' 2dVDbv&d2â"
806 | },
807 | "profilePage": {
808 |   "title": "b6Fbr"Å
809 |   "subtitle": "dvHd;†d2 'dF*c-Dd;Ed;) d†*d&/dVC d†.cVHcVJb;C d†-c6'b†c.",
810 |   "edit": "b;9b0JdB"Å
811 |   "changePhoto": "b;:d;Jc 5d†1b' 'dFEdFA bvDcF.cVJ",
812 |   "student": "cv'dF(",
813 |   "level": "bvDdV3b;Hd'"Å
814 |   "totalXp": "bv,dV'dFJ dfBbv7 bvDbæ(c )",
815 |   "dayStreak": "d;HdR Eb;Hbv5dB"Å
816 |   "badges": "bvDb6Hc6Eb'"Å
817 |   "editProfile": "b;9b0JdB 'dFEdFA",
818 |   "viewPortfolio": "c-1cb 'dFEdFA bvDc-'dR"Å
819 |   "levelProgress": "bvDdV3b;Hd' .¶7W&VçG×0 .¶æW†G×0"Å
820 |   "xpRemaining": ">{{count}} dFBcv) bæ(c ) dFDdV3b;Hd' 'dF*bvDd¢"Å
821 |   "freezes": ">{{count}} b6/d†'b¢ -dv'd;) dFdc6Dc6Db' Eb;'b0)",
822 |   "badgesCount": "bvDb6Hc6Eb' ‡.¶6÷VçG×0"Å
823 |   "viewAll": "c-1cb 'dFCdB "Å
824 |   "noBadges": "c6*c†Gc #d†3dv*d2 'dFEd6*c6(b' Gdf'." ,
825 |   "learningActivity": "df4bv7 bvDb;9dFQdR"Å
826 |   "lastWeeks": "b&.c .¶6÷VçG×0 #c6(df9bvK",
827 |   "activeDays": "b6JbvE df4cv) d J dv0dr 'dFAB;1b'"Å
828 |   "profileLinks": "d†,dv'b¢ 'dFEdFA bvDcF.cVJ",
829 |   "links": {
830 |     "leaderboard": "dFHb0) bvDcV/bv1b'"Å
831 |     "marketplace": "bvDdV*bÆ1",
832 |     "wellness": "bvDc-'d Jb' HbvDc-'b0'b¢"Å
833 |     "quests": "dVGbvE bvDdV9c Ab'"Å
834 |     "portfolio": "dVdD 'dF%df,bv2",
835 |     "journal": "bvDd;HdVJbv*",
836 |     "team": "d 1d;Bd¢"Å
837 |     "calendar": "bvDb;Bd†JdR HbvDbæ/d†D",
838 |     "transcript": "bvDc6,dB 'dF#d6'b0JdVJ",
839 |     "fees": "bvDc 3d†E d†'dFEb0Ad†9bv*",
840 |     "surveys": "bvDbv3b;(d; 'df'b¢"Å
841 |     "learningProfile": "dVdD 'dF*c-De E",
842 |     "settings": "bvDbV9b0'b0'b¢"
843 |   },
844 |   "learningProfile": "dVdD 'dF*c-De E",
845 |   "learningStyle": "b63dFHb, 'dF*c-De E",
846 |   "notComplete": "dFE d;Cb;EdB (c-/",
847 |   "privacy": "bvDbæ5d†5d;)",
848 |   "anonymous": "bvDc†Gd†1 b†'c6E dV,dVHdB Ad¢ Dd†-bv* bvDcV/bv1b'"Å
849 |   "anonymousDescription": "b6.d P bv3dVC c-F c&EdF'bFc dv9 bvDbv-b;Abv8 b†*d&/dVC.",
850 |   "equipped": "bvDc-Fbv5c 'dFEd 9e Db'"Å
851 |   "slots": {
852 |     "profile_theme": "c6Eb' 'dFEdFA",
853 |     "avatar_frame": "bv7bv1 bvDcVHC )",
854 |     "display_title": "bvDdFbB, 'dFec-1d†6"
855 |   },
856 |   "noEquipped": "dF' b;HbÆ/ c-Fbv5c *bÆEd;Dd;) dVAc-QdF).",

```

```

857 | "security": "bvDb6EbvF d†dFHcVHdB"Ã
858 | "changePassword": "b|:d|Jc CdFeb' dFEc Hc "Ã
859 | "activeSessions": "bvDbÆDc6'b¢ dFFcF7b'"Ã
860 | "transcript": "bvDc6,dB 'dF#d6'b0JdVJ"
861 | "dataControls": "b†JbvFbv* bvDb03bv( d†dF*b0CdR"Ã
862 | "signOut": "b|3bÆJdB 'dF.c HbÃ"Ã
863 | "rail": {
864 |   "label": "dVDbæ5 dVDd 'dF7bvDb,"Ã
865 |   "latestBadge": "b6-b0+ d†3bvE",
866 |   "noBadge": "dFE d|0d6*c6( b6J d†3bvE b†9b0"Ã
867 |   "viewBadges": "c-1cb ,dVJc' 'dF#d†3dv) d†9b0/dv' {{count}} !.",
868 |   "academic": "b6Cbv/d|Ed¢"Ã
869 |   "transcript": "bvDc6,dB 'dF#d6'b0JdVJ",
870 |   "openTranscript": "d *b0 'dF3bÆD !.",
871 |   "portfolio": "dVDd 'dF%df,bv2",
872 |   "evidence": "c-Fbv5c 'dF#b0Db',"Ã
873 |   "openPortfolio": "d *b0 EdFA bvDbVfBÆ'c" "Ã
874 |   "account": "bvDb03bv("
875 | }
876 | },
877 | "publicPortfolio": {
878 |   "subtitle": "dVDd 'dF*c-DdR DdF7bvDb,"Ã
879 |   "totalXP": "bv,dV'dFJ dfBbv7 bvDbæ(c )",
880 |   "level": "bvDdV3b|Hd'"Ã
881 |   "sections": {
882 |     "cloAttainment": "b|-cVJdB Ebæ1bÆ'b¢ dF*c-DdR"Ã
883 |     "badges": "bvDb6Hc6Eb'"
884 |   },
885 |   "poweredBy": "dV0cF:e D b†Hbv3cv) bVJb0Jd 'd|2c "Ã
886 |   "error": {
887 |     "forbiddenTitle": "bvDdVDd :d|1 dV*bv-",
888 |     "forbiddenBody": "dv0br 'dFEdFA bæ'cRÃ DdR Jd&E bvDcv'dF( b†*d 9d|D bvDdV4bv1d6) bvDc-'dV)`Ã #d, DdR *dVFb0 Eb01c6*dr 'dF%c F.",
889 |     "notFoundTitle": "bvDdVDd :d|1 dVHbÆHb0"Ã
890 |     "notFoundBody": "b|9c Qc 'dF9b¶Hc 9dFI dVDd Ddv0br 'dF1bv(crÃ 1b†Ebr *dv* bv2bvDb|G b6H b6F bvdC 'b†7 c|Jc 5b0Jb0Ã"Ã
891 |     "missingIdTitle": "bvDdVDd :d|1 dV*bv-",
892 |     "missingIdBody": "dFE d|*dR *d&/d|E dV9c Qd 'dF7bvDb,Ã"Ã
893 |     "code": "bæ7b2 -7F GW×0"
894 |   }
895 | }
896 | }
897 |

```

FILE: src/locales/ar/teacher.json

TYPE: .json | LINES: 1-109 | SHA256: 7d62dd05a55984f45856f056b1a71b6091b15d694ddab036e760c048e9c927fe

```

1 | {
2 |   "dashboard": {
3 |     "title": "dFHb0) bvDb|-d6E",
4 |     "welcome": {
5 |       "subtitle": "b|'b†9 bvDb|Bd|JdR HbvDb|-cVJdB HbvDcvDbv( bvDdV9c 6d|F dFDbæ7c Ad¢ Ed&1c 'b|C."
6 |     },
7 |     "gradingQueue": "d&'bFEB' 'dF*d&Jd|E",
8 |     "pendingSubmissions": "bvDb|3dFJdV'b¢ dFEc-Dd&)",
9 |     "gradedThisWeek": "b|E b|Bd|JdVGbr Gc ' bvDb63b†Hc'"Ã
10 |    "avgAttainment": "dV*d†3cr 'dF*b05d|D",
11 |    "atRiskStudents": "bvDcvDbv( bvDdV9c 6d†F dFDbæ7c "Ã
12 |    "bloomsDistribution": "b|Hc&Jc' Ec6*d†Jbv* b†Dd†E",
13 |    "cloAttainment": "b|-cVJdB Ebæ1bÆ'b¢ dF*c-DdR"Ã
14 |    "studentHeatmap": "bæ1d|7b' #b0'b 'dF7dF'b, 'dF-c 'c Jb'"Ã
15 |    "selectCourse": "bv.b|1 dVBc 1bvK",
16 |    "viewAll": "c-1cb 'dFCdB"Ã
17 |    "noCloData": "dF' b|*d†Ac (d|'df'b¢ *b05d|D dv.c ,bv* bvDb|9dFE dFGc ' bvDdVBC 1.",
18 |    "noClosDefined": "dFE d|*dR *b0/d|/ dv.c ,bv* b|9dFE b†9b0Ã"Ã
19 |    "noHeatmapData": "dF' b|*d†Ac (d|'df'b¢ #b0'b 'dF7dF'b, Ddv0br 'dFEd&1c Ã"Ã
20 |    "noAtRisk": "dFE d|*dR 'd6*cF'd 7dF'b, Ec-1cfJdB DdF.cv1. c-EdB 1bv&c' "Ã
21 |    "noPending": "dF' b|HbÆ/ b|3dFJdV'b¢ Ec-Dd&). b6Fb¢ 9dFI bv7dF'c' "Ã
22 |    "sendNudgeTo": "bv1c6'dB *df(d|G bVDd' .¶æ 0W×0"Ã
23 |    "nudgePlaceholder": "bvCb|( c 3bvDb'ââÃ"Ã
24 |    "nudgeSent": "b|E bv1c6'dB 'dF*df(d|G bVDd' .¶æ 0W×0"Ã
25 |    "nudgeFailed": "d 4dB %c 3bvD bvDb|Fb†Jdr"Ã
26 |    "nudge": "b|Fb†Jdr"Ã
27 |    "daysInactive": "{{count}} d|HdR :d|1 df4cr"Ã
28 |    "activityUnavailable": "b|'c JbÃ dFFcF'cr :d|1 dV*bv-",
29 |    "late": "dV*b6.c "Ã
30 |    "heatmapLegend": {
31 |      "excellent": "dVEb|'c' ,&SfRR'"Ã
32 |      "satisfactory": "dV0c 6d0 fs 0fBR'"Ã
33 |      "developing": "d&Jb0 'dF*cvHd|1 (50-69%)",
34 |      "notYet": "dFE d|*b0Bd' (c-/ (<50%)",
35 |      "noData": "dF' b|HbÆ/ b†JbvFbv*"
36 |    },
37 |    "student": "bvDcv'dF(",
38 |    "viewAll": "c-1cb 'dFCdB"Ã
39 |    "allSections": "bÆEd|9 bvDcF0c-(",
40 |    "teamHealth": "cV-b' 'dFAC Jd""Ã
41 |    "viewReport": "c-1cb 'dF*d&id|1",
42 |    "totalTeams": "bv,dV'dFJ bvDd 1d""Ã
43 |    "needsAttention": "d|-b|'bÃ 'dv*dV'dv'dz"Ã
44 |    "atRiskLabel": "dV9c 6 dFDbæ7c "Ã
45 |    "cancel": "bvDc|'b "Ã
46 |    "sendNudge": "bv1c6'dB *df(d|G",
47 |    "section": "cF9b†) {{code}}",
48 |    "unknownStudent": "cv'dF( c|Jc Ec-1d†A",
49 |    "unknownAssignment": "b|CdFJd :d|1 dV9c Hd "Ã
50 |    "masteryRecovery": {
51 |      "title": "b|Fb†Jdv'b¢ 'c6*c-'b0) bvDbV*d&'db"Ã
52 |      "description": "bvDcvDbv( bvDdV-b0/d†F dF'c6*c-'b0) bvDbV*d&'db Jb0*bv,d†F bVDd' %d6EbvD dV3bv1 bvDbv3b|9bv/b' Bb†D bv9bv/b' Eb0'
53 |      "failures": "{{count}} bv.d 'd""Ã
54 |      "inRecovery": "d J dv1b0Db' 'dF'c6*c-'b0)"
55 |    },
56 |    "accessLimited": {
57 |      "title": "b|Abv5d|D bvDdV*c-DdVJdb Eb0/d†/b' 'dF5dF'b0Jb'"Ã
58 |      "description": "b|E c 5b0 .¶6+VçG×0 Eb|9dFEbvK c-(c EdF.cR 'dFEd&1c 'dF"dVF"Ã Dd6F dVDd 'b|GdR 'dFAC /d|) c|Jc Eb|'b0) cfEdb 5
59 |      "rail": "b|E c 5b0 .¶6+VçG×0 Eb|9dFEbvK"Ã Dd6F dvHd|'b|GdR EbæAd|) b†3b†( cVDbv-d|'b¢ 'dF(d|'df'b¢ 'dF-bvDd|)."

```

```

60 |     },
61 |   },
62 |   "grading": {
63 |     "title": "bvDb!Bd!JdR"Å
64 |     "rubricSelection": "bv.b!1 dv3b!Hd' 'dFEc-Jbv1 dFCdB Ec-Jbv1",
65 |     "totalScore": "bvDb01bÆ) bvDbV,dV'dfJb'"Å
66 |     "feedback": "bvDb!;c Jb' 'dF1bv,c-)",
67 |     "overallFeedback": "bvDb!;c Jb' 'dF1bv,c-) bvDcF'dVDb'"Å
68 |     "submitGrade": "bv1c6'dB 'dF/c ,b'"Å
69 |     "gradeSubmitted": "b!E bv1c6'dB 'dF/c ,b' (df,bv-."
70 |   },
71 |   "assignments": {
72 |     "title": "bvDb!CdFJd 'b¢"Å
73 |     "addAssignment": "bv6bvAb' *d6Dd!A",
74 |     "editAssignment": "b!9b0JdB *d6Dd!A",
75 |     "dueDate": "b!;c Jbâ 'dF'c6*b0BbvB",
76 |     "totalMarks": "bvDb01bÆ) bvDd6Dd!)",
77 |     "linkedCLOs": "dV.c ,bv* bvDb!9dFE bvDdV1b!(cv)",
78 |     "lateWindow": "df'd 0b' 'dF*c6Dd!E bvDdV*b6.c "
79 |   },
80 |   "clos": {
81 |     "title": "dV.c ,bv* bvDb!9dFE dFDdVbC 1",
82 |     "addCLO": "bv6bvAb' Ebæ1bÅ *c-DdR"Å
83 |     "editCLO": "b!9b0JdB Ebæ1bÅ *c-DdR"Å
84 |     "bloomsLevel": "dv3b!Hd' (dFhR"Å
85 |     "ploMapping": "c (cr Ebæ1bÆ'b¢ 'dF*c-DdR 'dF(c FbvEbÆJb'"Å
86 |     "noMapping": "dF' d!HbÆ/ c (cr (dV.c ,bv* bvDb!9dFE bvDb!1df'dV,d!) b†9b0"
87 |   },
88 |   "bilingual": {
89 |     "arabicTitle": "bvDc-Fd†'db (bvDc-1b†Jb'"Å
90 |     "arabicTitlePlaceholder": "b6/bæD bvDc-Fd†'db (bvDc-1b†Jb' †'bæ*d!;c J)"
91 |   },
92 |   "rubrics": {
93 |     "title": "dv9bvJd!1 bvDb!Bd!JdR"Å
94 |     "addRubric": "bv6bvAb' Ec-Jbv1 b!Bd!JdR"Å
95 |     "editRubric": "b!9b0JdB Ec-Jbv1 b!Bd!JdR"Å
96 |     "criteria": "bvDdV9bvJd!1",
97 |     "levels": "dv3b!Hd!b¢ 'dF#b0'b Å
98 |     "saveAsTemplate": "b0Ac, Cd&'dF("
99 |   },
100 |   "attendance": {
101 |     "title": "bvDb06d†1",
102 |     "markAttendance": "b!3bÆJdB 'dF-cfHc Å
103 |     "present": "b0'cf1",
104 |     "absent": "c!;bf(",
105 |     "late": "dV*b6.c Å
106 |     "excused": "dV9c Hc "
107 |   }
108 | }
109 |

```

FILE: src/locales/en/admin.json

TYPE: .json | LINES: 1-161 | SHA256: a831be9346431ef90c2eda28621d5903f5163f1d8c81e69e0d22268b79866bc8

```

1 | {
2 |   "dashboard": {
3 |     "title": "Dashboard",
4 |     "totalUsers": "Total Users",
5 |     "activeUsers": "Active Users",
6 |     "programs": "Programs",
7 |     "courses": "Courses",
8 |     "onboarding": "Onboarding",
9 |     "activeCourses": "Active Courses",
10 |     "avgAttainment": "Avg Attainment",
11 |     "atRiskStudents": "At-Risk Students",
12 |     "usersByRole": "Users by Role",
13 |     "recentActivity": "Recent Activity",
14 |     "noActiveUsers": "No active users yet.",
15 |     "noRecentActivity": "No recent activity.",
16 |     "ploHeatmap": "PLO Attainment Heatmap",
17 |     "ploHeatmapEmpty": "PLO attainment heatmap will appear here once outcome data is available.",
18 |     "ploHeatmapError": "Unable to load PLO attainment data. Please try again.",
19 |     "ploHeatmapUnmeasured": "No data",
20 |     "ploHeatmapLegend": "Attainment level",
21 |     "totalContributors": "{{count}} contributing outcomes",
22 |     "ploDrillDown": {
23 |       "title": "PLO Attainment Detail",
24 |       "subtitle": "Overall attainment {{value}} ({{method}}). Contributing course outcomes:",
25 |       "cloColumn": "Course Outcome (CLO)",
26 |       "courseColumn": "Course",
27 |       "attainmentColumn": "Attainment",
28 |       "emptyTitle": "No contributing outcomes yet",
29 |       "emptyDescription": "No mapped course outcomes have recorded attainment for this program outcome.",
30 |       "method": {
31 |         "program": "program-scope mean",
32 |         "clo_rollup": "rolled up from course outcomes",
33 |         "none": "no recorded data"
34 |       },
35 |       "level": {
36 |         "Excellent": "Excellent",
37 |         "Satisfactory": "Satisfactory",
38 |         "Developing": "Developing",
39 |         "Not_Yet": "Not Yet"
40 |       }
41 |     },
42 |     "aiCoPilot": "AI Co-Pilot Performance",
43 |     "suggestionAcceptance": "Suggestion Acceptance",
44 |     "totalSuggestions": "{{count}} total suggestions",
45 |     "predictionAccuracy": "Prediction Accuracy",
46 |     "validatedPredictions": "{{count}} validated predictions",
47 |     "draftAcceptance": "Draft Acceptance",
48 |     "feedbackDrafts": "{{count}} feedback drafts",
49 |     "aiNoFeedback": "No AI feedback recorded yet",
50 |     "onboardingPending": "{{count}} student(s) haven't completed onboarding",

```

```

51 |     "onboardingPendingAction": "View list and send reminders",
52 |     "graduateAttributes": "Graduate Attributes",
53 |     "attributeAttainment": "Attribute Attainment",
54 |     "attributeAttainmentDesc": "View and manage graduate attribute mappings and attainment overview.",
55 |     "historicalEvidence": "Historical Evidence",
56 |     "evidenceDashboard": "Evidence Dashboard",
57 |     "evidenceDashboardDesc": "Browse historical evidence records across semesters and programs.",
58 |     "competencyFrameworks": "Competency Frameworks",
59 |     "frameworkManagement": "Framework Management",
60 |     "frameworkManagementDesc": "Define competency hierarchies and map to outcome chains.",
61 |     "manage": "Manage",
62 |     "view": "View",
63 |     "rail": {
64 |         "label": "Institution",
65 |         "institution": "Ø&B&P Institution",
66 |         "users": "Users",
67 |         "active": "Active accounts",
68 |         "programs": "Programs",
69 |         "courses": "Courses",
70 |         "analytics": "See analytics !'",
71 |         "governance": "Ø&B&P AI governance",
72 |         "autonomyCeiling": "Autonomy ceiling",
73 |         "a2": "A2 - approve",
74 |         "governanceNote": "AI never acts on institution data without human approval.",
75 |         "departments": "Departments",
76 |         "allDepartments": "All departments !'",
77 |         "departmentsEmpty": "No attainment data yet."
78 |     }
79 | },
80 | "users": {
81 |     "title": "User Management",
82 |     "addUser": "Add User",
83 |     "editUser": "Edit User",
84 |     "bulkImport": "Bulk Import",
85 |     "role": "Role",
86 |     "fullName": "Full Name",
87 |     "email": "Email",
88 |     "status": "Status",
89 |     "deleteConfirm": "This will deactivate the user account.",
90 |     "importSuccess": "{{count}} users imported successfully.",
91 |     "importErrors": "{{count}} rows had errors."
92 | },
93 | "inviteUsers": {
94 |     "title": "Invite Users",
95 |     "subtitle": "Send bulk invitations to staff members and parents",
96 |     "defaultRole": "Default Role",
97 |     "roleHint": "All invitees will receive this role. You can customize per user in the CSV.",
98 |     "csvContent": "CSV Content",
99 |     "csvFormat": "Format: email,role (one per line, starting with header row)",
100 |     "uploadFile": "Upload CSV File",
101 |     "chooseFile": "Choose File",
102 |     "downloadTemplate": "Download Template",
103 |     "sendInvites": "Send Invitations",
104 |     "cancel": "Cancel",
105 |     "noValidEmails": "No valid email addresses found in the CSV",
106 |     "noInstitution": "Institution not found",
107 |     "results": "Invitation Results",
108 |     "sent": "Sent",
109 |     "failed": "Failed",
110 |     "pending": "Pending",
111 |     "email": "Email",
112 |     "role": "Role",
113 |     "status": "Status",
114 |     "message": "Message",
115 |     "sendMore": "Send More Invitations",
116 |     "copyResults": "Copy Results",
117 |     "copiedToClipboard": "Results copied to clipboard",
118 |     "invitesSent": "Invitations sent successfully",
119 |     "invitesFailed": "Some invitations failed to send"
120 | },
121 | "programs": {
122 |     "title": "Program Management",
123 |     "addProgram": "Add Program",
124 |     "editProgram": "Edit Program",
125 |     "coordinator": "Coordinator",
126 |     "department": "Department",
127 |     "deleteBlocked": "Cannot delete program with active courses."
128 | },
129 | "outcomes": {
130 |     "title": "Institutional Learning Outcomes",
131 |     "addILO": "Add ILO",
132 |     "editILO": "Edit ILO",
133 |     "deleteBlocked": "Cannot delete ILO with mapped PLOs.",
134 |     "sortOrder": "Sort Order"
135 | },
136 | "audit": {
137 |     "title": "Audit Log",
138 |     "action": "Action",
139 |     "entity": "Entity",
140 |     "performedBy": "Performed By",
141 |     "timestamp": "Timestamp",
142 |     "changes": "Changes"
143 | },
144 | "settings": {
145 |     "title": "Institution Settings",
146 |     "kpiThresholds": "KPI Thresholds",
147 |     "gradeScale": "Grade Scale",
148 |     "accreditationBody": "Accreditation Body",
149 |     "defaultLanguage": "Default Language",
150 |     "defaultLanguageDesc": "New users will start with this language preference.",
151 |     "english": "English",
152 |     "arabic": "Arabic"
153 | },
154 | "bilingual": {

```

```

155 |     "arabicTitle": "Arabic Title",
156 |     "arabicName": "Arabic Name",
157 |     "arabicTitlePlaceholder": "Enter title in Arabic (optional)",
158 |     "arabicNamePlaceholder": "Enter name in Arabic (optional)"
159 |   }
160 | }
161 |

```

FILE: src/locales/en/ai.json

TYPE: .json | LINES: 1-144 | SHA256: 11a7ab9d164edf948875719e9978009f6e59d3b4aaea69af2d7e9d1d5315323c

```

1 | {
2 |   "suggestions": {
3 |     "title": "AI Suggestions",
4 |     "moduleSuggestion": "Suggested Focus Area",
5 |     "weakArea": "Needs improvement in {{clo}}",
6 |     "socialProof": "Students who improved this area scored {{percent}}% higher",
7 |     "feedback": "Was this helpful?",
8 |     "noSuggestions": "No suggestions at this time."
9 |   },
10 |   "atRisk": {
11 |     "title": "At-Risk Predictions",
12 |     "probability": "Risk Score: {{score}}%",
13 |     "signals": "Contributing Signals",
14 |     "loginFrequency": "Login Frequency",
15 |     "submissionPattern": "Submission Pattern",
16 |     "attainmentTrend": "Attainment Trend",
17 |     "sendNudge": "Send Nudge",
18 |     "nudgeSent": "Nudge sent to {{name}}."
19 |   },
20 |   "feedbackDraft": {
21 |     "title": "AI Feedback Draft",
22 |     "generating": "Generating feedback draft...",
23 |     "accept": "Accept",
24 |     "edit": "Edit",
25 |     "reject": "Reject",
26 |     "overallFeedback": "Overall Feedback Draft"
27 |   },
28 |   "tutor": {
29 |     "page": {
30 |       "title": "AI Tutor",
31 |       "openConversations": "Open conversations",
32 |       "newConversationTitle": "Start a new conversation",
33 |       "newConversationSubtitle": "Choose a tutoring style that works best for you",
34 |       "startChatting": "Start chatting",
35 |       "personaHint": "You can change the persona at any time during the conversation"
36 |     },
37 |     "states": {
38 |       "unavailable": {
39 |         "title": "AI Tutor unavailable",
40 |         "message": "The tutor can't be reached right now. Please try again in a few minutes."
41 |       },
42 |       "notEnrolled": {
43 |         "title": "Not enrolled in this course",
44 |         "message": "You're not enrolled in this course yet, so the tutor can't help here. Check with your teach
45 |       },
46 |       "noEmbeddings": {
47 |         "title": "Still learning this course",
48 |         "message": "The tutor hasn't finished studying this course's materials yet. Please check back soon."
49 |       },
50 |       "rateLimited": {
51 |         "title": "Daily limit reached",
52 |         "message": "You've reached your tutor message limit for today. It resets at midnight.",
53 |         "reset": "Resets {{hint}}."
54 |       },
55 |       "error": {
56 |         "title": "Something went wrong",
57 |         "message": "The AI Tutor ran into a problem. Please try again."
58 |       },
59 |       "retry": "Try again"
60 |     },
61 |     "chat": {
62 |       "title": "AI Tutor",
63 |       "emptyTitle": "How can I help you today?",
64 |       "emptyBody": "Ask me about your course materials, assignments, or any concept you need help understandin
65 |       "messagesLabel": "Chat messages",
66 |       "typingLabel": "Tutor is typing",
67 |       "userMessageLabel": "Your message",
68 |       "tutorMessageLabel": "Tutor message",
69 |       "messagesRemaining": "You have {{count}} messages remaining today.",
70 |       "limitReached": "You've reached your daily message limit. It resets at midnight.",
71 |       "tokenBudgetExceeded": "Your daily token budget has been exceeded. Please try again tomorrow.",
72 |       "attachImage": "Attach image",
73 |       "attachImages": "Attach images",
74 |       "attachDocument": "Attach document",
75 |       "removeImage": "Remove image {{index}}",
76 |       "removeDocument": "Remove document",
77 |       "attachmentAlt": "Attachment {{index}}",
78 |       "messageInput": "Message input",
79 |       "sendMessage": "Send message",
80 |       "inputPlaceholder": "Ask a question...",
81 |       "inputPlaceholderDisabled": "Daily limit reached",
82 |       "citationLabel": "Citation {{number}}",
83 |       "documentAttached": "Document attached",
84 |       "integrityGuidance": "Academic integrity guidance",
85 |       "errors": {
86 |         "imageType": "{{name}}: Only JPG and PNG images are supported",
87 |         "imageSize": "{{name}}: Image must be under 5MB",
88 |         "maxImages": "Maximum {{count}} images allowed",
89 |         "docType": "Only PDF and DOCX documents are supported",
90 |         "docSize": "Document must be under 10MB",
91 |         "uploadFailed": "Failed to upload attachment. Please try again."
92 |       }
93 |     },

```



```

94 |     "sidebar": {
95 |       "newConversation": "New Conversation",
96 |       "pastConversations": "Past conversations",
97 |       "noConversations": "No conversations yet",
98 |       "noConversationsHint": "Start a new conversation to get help",
99 |       "newConversationPreview": "New conversation",
100 |       "conversationLabel": "Conversation: {{title}}",
101 |       "messageCount_one": "{{count}} msg",
102 |       "messageCount_other": "{{count}} msgs",
103 |       "deleteConversation": "Delete conversation",
104 |       "deleteTitle": "Delete conversation",
105 |       "deleteDescription": "This will permanently delete this conversation and all its messages. This action c
106 |       "deleteConfirm": "Delete",
107 |       "relativeTime": {
108 |         "justNow": "Just now",
109 |         "minutesAgo": "{{count}}m ago",
110 |         "hoursAgo": "{{count}}h ago",
111 |         "daysAgo": "{{count}}d ago"
112 |       }
113 |     },
114 |     "persona": {
115 |       "yourStyle": "Your tutor style",
116 |       "chooseStyle": "Choose your tutor style",
117 |       "selectLabel": "Select tutor persona",
118 |       "groupLabel": "Tutor persona",
119 |       "recommendedGroupLabel": "Recommended tutor persona",
120 |       "recommended": "Recommended",
121 |       "changeStyle": "Change tutor style",
122 |       "socratic_guide": {
123 |         "label": "Socratic Guide",
124 |         "description": "Asks probing questions to lead you to the answer"
125 |       },
126 |       "step_by_step_coach": {
127 |         "label": "Step-by-Step Coach",
128 |         "description": "Breaks down problems into sequential steps"
129 |       },
130 |       "quick_explainer": {
131 |         "label": "Quick Explainer",
132 |         "description": "Gives concise, direct explanations"
133 |       }
134 |     },
135 |     "autonomy": {
136 |       "groupLabel": "Tutor autonomy level",
137 |       "figureItOut": "Figure it out",
138 |       "figureItOutLabel": "Figure it out – hints only",
139 |       "justExplain": "Just explain it",
140 |       "justExplainLabel": "Just explain it – direct explanation"
141 |     }
142 |   }
143 | }
144 |

```

FILE: src/locales/en/auth.json

TYPE: .json | LINES: 1-168 | SHA256: f92b3141a2597b1f59375275431eef5c3994f60e00920f85cf4b0d7cbe8e74ce

```

1 | {
2 |   "brand": {
3 |     "tagline": "Outcome Based Education",
4 |     "headline": "Learning that adapts to every learner.",
5 |     "subtitle": "Outcome-based, AI-tutored, and gamified for real mastery – for students, teachers, parents an
6 |     "bulletOutcomes": "Outcomes drive your next step",
7 |     "bulletTutor": "An AI tutor that knows your gaps",
8 |     "bulletHabits": "Habits & mastery, not just grades",
9 |     "chipFerpa": "FERPA-aligned",
10 |    "chipBilingual": "EN / bvDc-1b†Jb'
11 |  },
12 |  "sso": {
13 |    "google": "Continue with Google",
14 |    "microsoft": "Continue with Microsoft",
15 |    "institution": "Sign in with your institution",
16 |    "orWithEmail": "or with email",
17 |    "magiclink": "Email me a magic link instead",
18 |    "magiclinkSent": "Magic link sent – check your email to finish signing in.",
19 |    "magiclinkError": "Could not send the magic link. Please try again.",
20 |    "error": "Single sign-on could not be started. Try signing in with email."
21 |  },
22 |  "password": {
23 |    "show": "Show password",
24 |    "hide": "Hide password"
25 |  },
26 |  "tabs": {
27 |    "login": "Login",
28 |    "register": "Register"
29 |  },
30 |  "roles": {
31 |    "admin": "Admin",
32 |    "coordinator": "Coordinator",
33 |    "teacher": "Teacher",
34 |    "student": "Student",
35 |    "parent": "Parent"
36 |  },
37 |  "login": {
38 |    "title": "Sign In",
39 |    "subtitle": "Enter your credentials to access the platform",
40 |    "emailLabel": "Email Address",
41 |    "emailPlaceholder": "Enter your email address",
42 |    "passwordLabel": "Password",
43 |    "passwordPlaceholder": "Enter your password",
44 |    "submitButton": "Sign In",
45 |    "forgotPassword": "Forgot password?",
46 |    "signingIn": "Signing in...",
47 |    "welcomeTitle": "Welcome Back",
48 |    "welcomeSubtitle": "Sign in to your account to continue",
49 |    "successMessage": "Login successful!",

```

```

50 | "genericError": "Something went wrong. Please try again.",
51 | "defaultError": "Invalid email or password.",
52 | "demoLabel": "Quick Demo Access:",
53 | "rolePickerLabel": "Explore a role",
54 | "demoSuccess": "Demo login successful! Redirecting to {{role}} dashboard...",
55 | "demoError": "Demo login failed. Please try again.",
56 | "noAccount": "Don't have an account?",
57 | "createAccount": "Create one",
58 | "keepSignedIn": "Keep me signed in"
59 | },
60 | "signup": {
61 |   "title": "Create Account",
62 |   "subtitle": "Join Edeviser to start learning",
63 |   "firstName": "First Name",
64 |   "firstNamePlaceholder": "First",
65 |   "lastName": "Last Name",
66 |   "lastNamePlaceholder": "Last",
67 |   "username": "Username",
68 |   "usernamePlaceholder": "Username",
69 |   "email": "Email",
70 |   "emailPlaceholder": "Email address",
71 |   "password": "Password",
72 |   "passwordPlaceholder": "Password",
73 |   "confirmPassword": "Confirm",
74 |   "confirmPasswordPlaceholder": "Confirm",
75 |   "role": "Role",
76 |   "roleStudent": "Student (Learner)",
77 |   "roleTeacher": "Teacher (Instructor)",
78 |   "roleCoordinator": "Coordinator (Manager)",
79 |   "roleAdmin": "Admin (System)",
80 |   "roleHint": "Self-registration creates a student account. Staff roles require an invitation.",
81 |   "submitButton": "Create Account",
82 |   "successMessage": "Account created successfully!",
83 |   "verificationSent": "Account created! Please check your email to verify your address before signing in.",
84 |   "defaultError": "Registration failed. Please try again.",
85 |   "genericError": "Something went wrong. Please try again.",
86 |   "chooseInstitution": "Choose Your Institution",
87 |   "institutionSubtitle": "Select the institution you're joining",
88 |   "createAccount": "Create Your Account",
89 |   "accountSubtitle": "Set up your account details",
90 |   "selectInstitution": "Select an institution",
91 |   "searchInstitution": "Search institutions...",
92 |   "noInstitutions": "No institutions found",
93 |   "noInstitutionsAvailable": "No institutions are currently available for registration",
94 |   "joinModeOpen": "This institution allows self-registration. You'll need to verify your email address.",
95 |   "joinModeInviteOnly": "This institution requires an invitation to join.",
96 |   "joinModeDomainRestricted": "This institution accepts emails from: {{domains}}",
97 |   "inviteOnlyWarning": "This institution requires an invitation. Please contact your administrator.",
98 |   "invalidEmailDomain": "Your email domain is not authorized for this institution. Allowed domains: {{domain",
99 |   "emailVerificationRequired": "You'll need to verify your email address before accessing the platform.",
100 |   "fullName": "Full Name",
101 |   "fullNamePlaceholder": "Enter your full name",
102 |   "continue": "Continue",
103 |   "back": "Back",
104 |   "backToLogin": "Back to Login",
105 |   "haveAccount": "Already have an account?",
106 |   "signIn": "Sign in here",
107 |   "strengthHint": "Use 8+ characters with a mix of letters, numbers & symbols.",
108 |   "strengthWeak": "Weak – add length",
109 |   "strengthFair": "Fair – add numbers & symbols",
110 |   "strengthGood": "Good password",
111 |   "strengthStrong": "Strong password",
112 |   "terms": "By continuing you agree to our Terms & Privacy. Student data is never sold."
113 | },
114 | "acceptInvite": {
115 |   "title": "Accept Invitation",
116 |   "subtitle": "Complete your account setup",
117 |   "invalidToken": "Invalid or missing invitation token",
118 |   "tokenExpiredOrInvalid": "This invitation has expired or is invalid",
119 |   "fetchError": "Failed to fetch invitation details",
120 |   "noInvitation": "No invitation found",
121 |   "signupError": "Failed to create account",
122 |   "genericError": "Something went wrong. Please try again.",
123 |   "successMessage": "Account created successfully!",
124 |   "email": "Email Address",
125 |   "institution": "Institution",
126 |   "role": "Role",
127 |   "fullName": "Full Name",
128 |   "fullNamePlaceholder": "Enter your full name",
129 |   "password": "Password",
130 |   "passwordPlaceholder": "Create a password",
131 |   "confirmPassword": "Confirm Password",
132 |   "confirmPasswordPlaceholder": "Confirm your password",
133 |   "acceptButton": "Accept Invitation & Create Account",
134 |   "haveAccount": "Already have an account?",
135 |   "signIn": "Sign in here"
136 | },
137 | "logout": {
138 |   "button": "Sign Out",
139 |   "confirmMessage": "Are you sure you want to sign out?"
140 | },
141 | "resetPassword": {
142 |   "title": "Reset Password",
143 |   "subtitle": "Enter your email to receive a reset link",
144 |   "emailLabel": "Email Address",
145 |   "submitButton": "Send Reset Link",
146 |   "successMessage": "A password reset link has been sent to your email.",
147 |   "backToLogin": "Back to Sign In"
148 | },
149 | "updatePassword": {
150 |   "title": "Set New Password",
151 |   "subtitle": "Enter your new password below",
152 |   "newPasswordLabel": "New Password",
153 |   "confirmPasswordLabel": "Confirm Password",

```

```

154 |     "submitButton": "Update Password",
155 |     "successMessage": "Your password has been updated successfully.",
156 |     "loginPrompt": "You can now log in with your new password.",
157 |     "goToLogin": "Go to login",
158 |     "passwordPlaceholder": "Minimum 8 characters",
159 |     "confirmPlaceholder": "Re-enter your password"
160 | },
161 | "errors": {
162 |     "invalidCredentials": "Invalid email or password.",
163 |     "accountLocked": "Account locked. Please try again in 15 minutes.",
164 |     "sessionExpired": "Your session has expired. Please sign in again.",
165 |     "resetLinkExpired": "This reset link has expired. Please request a new one."
166 | }
167 | }
168 |

```

FILE: [src/locales/en/common.json](#)

TYPE: .json | LINES: 1-1203 | SHA256: 34db7b680398967230344567cad6f8fab4b9991ca0030d28f56dc7772ac5a87f

```

1 | {
2 |   "carousel": {
3 |     "previous": "Previous slide",
4 |     "next": "Next slide",
5 |     "slideOf": "{{current}} of {{total}}",
6 |     "goTo": "Go to slide {{number}}"
7 |   },
8 |   "nav": {
9 |     "dashboard": "Dashboard",
10 |     "users": "Users",
11 |     "departments": "Departments",
12 |     "programs": "Programs",
13 |     "courses": "Courses",
14 |     "semesters": "Semesters",
15 |     "outcomes": "Outcomes",
16 |     "ilos": "ILOs",
17 |     "timetable": "Timetable",
18 |     "calendar": "Calendar",
19 |     "fees": "Fees",
20 |     "reports": "Reports",
21 |     "accreditationReports": "Accreditation Reports",
22 |     "security": "Security",
23 |     "auditlog": "Audit Log",
24 |     "bonusXp": "Bonus XP",
25 |     "badgeSpotlight": "Badge Spotlight",
26 |     "badges": "Badges",
27 |     "learningProfile": "Learning Profile",
28 |     "marketplace": "Marketplace",
29 |     "surveys": "Surveys",
30 |     "settings": "Settings",
31 |     "plos": "PLOs",
32 |     "matrix": "Matrix",
33 |     "sankeyDiagram": "Sankey Diagram",
34 |     "gapAnalysis": "Gap Analysis",
35 |     "coverageHeatmap": "Coverage Heatmap",
36 |     "semesterTrends": "Semester Trends",
37 |     "cohortComparison": "Cohort Comparison",
38 |     "cqiPlans": "CQI Plans",
39 |     "courseFile": "Course File",
40 |     "outcomeChain": "Outcome Chain",
41 |     "clos": "CLOs",
42 |     "rubrics": "Rubrics",
43 |     "assignments": "Assignments",
44 |     "grading": "Grading",
45 |     "gradebook": "Gradebook",
46 |     "announcements": "Announcements",
47 |     "modules": "Modules",
48 |     "students": "Students",
49 |     "challenges": "Challenges",
50 |     "teams": "Teams",
51 |     "teamHealth": "Team Health",
52 |     "tutorAnalytics": "Tutor Analytics",
53 |     "tutorHandoffs": "Tutor Handoffs",
54 |     "baselineTests": "Baseline Tests",
55 |     "planner": "Planner",
56 |     "today": "Today",
57 |     "progress": "Progress",
58 |     "leaderboard": "Leaderboard",
59 |     "myTeam": "My Team",
60 |     "habits": "Habits",
61 |     "myContent": "My Content",
62 |     "journal": "Journal",
63 |     "aiTutor": "AI Tutor",
64 |     "portfolio": "Portfolio",
65 |     "coursesTasks": "Courses & Tasks",
66 |     "dailyReview": "Daily Review",
67 |     "wellness": "Wellness",
68 |     "focus": "Focus",
69 |     "quests": "Quests",
70 |     "shop": "Shop",
71 |     "children": "Children",
72 |     "attendance": "Attendance",
73 |     "studyPlan": "Study Plan",
74 |     "support": "Support",
75 |     "profile": "Profile",
76 |     "me": "Me",
77 |     "notifications": "Notifications",
78 |     "studentTriage": "Student Triage",
79 |     "curriculumStudio": "Curriculum Studio",
80 |     "rubricBuilder": "Rubric Builder",
81 |     "courseMaterials": "Course Materials",
82 |     "gradingQueue": "Grading Queue",
83 |     "growthWellbeing": "Growth & Wellbeing",
84 |     "supportMessages": "Support & Messages",
85 |     "feesPayments": "Fees & Payments",

```

```

86 | "gradesReports": "Grades & Reports",
87 | "outcomeAttainment": "Outcome Attainment",
88 | "curriculumMatrix": "Curriculum Matrix",
89 | "courseFileGenerator": "Course File Generator",
90 | "accreditation": "Accreditation",
91 | "aiGovernance": "AI Governance",
92 | "institutionStructure": "Institution Structure",
93 | "bulkImport": "Bulk Import",
94 | "badgeDefinitions": "Badge Definitions",
95 | "feesManagement": "Fees Management",
96 | "questionBank": "Question Bank",
97 | "discussions": "Discussions",
98 | "teamHealthReport": "Team Health Report",
99 | "competencyFrameworks": "Competency Frameworks",
100 | "mobile": {
101 |   "home": "Home",
102 |   "learn": "Learn",
103 |   "tutor": "Tutor",
104 |   "progress": "Progress",
105 |   "students": "Students",
106 |   "studio": "Studio",
107 |   "grade": "Grade",
108 |   "growth": "Growth",
109 |   "support": "Support",
110 |   "outcomes": "Outcomes",
111 |   "curriculum": "Curriculum",
112 |   "accredit": "Accredit",
113 |   "analytics": "Analytics",
114 |   "aiGov": "AI-Gov",
115 |   "people": "People"
116 | },
117 | "more": "More",
118 | "upgradeToPremium": "Upgrade to Premium",
119 | "upgradeDescription": "Use your XP to unlock helpful learning rewards.",
120 | "exploreRewards": "Explore rewards",
121 | "level": "Level {{level}}",
122 | "xp": "XP",
123 | "levelProgress": "Level progress",
124 | "discussions": "Discussions",
125 | "quizzes": "Quizzes",
126 | "groups": {
127 |   "learn": "Learn",
128 |   "growth": "Growth",
129 |   "community": "Community",
130 |   "tools": "Tools"
131 | },
132 | },
133 | "emailVerification": {
134 |   "banner": "Please verify your email address to access all features.",
135 |   "resend": "Resend verification email",
136 |   "resendSuccess": "Verification email sent. Please check your inbox.",
137 |   "resendError": "Failed to resend verification email. Please try again.",
138 |   "dismiss": "Dismiss"
139 | },
140 | "buttons": {
141 |   "save": "Save",
142 |   "cancel": "Cancel",
143 |   "delete": "Delete",
144 |   "edit": "Edit",
145 |   "create": "Create",
146 |   "submit": "Submit",
147 |   "confirm": "Confirm",
148 |   "back": "Back",
149 |   "next": "Next",
150 |   "close": "Close",
151 |   "retry": "Try Again",
152 |   "export": "Export",
153 |   "import": "Import",
154 |   "search": "Search",
155 |   "filter": "Filter",
156 |   "reset": "Reset",
157 |   "download": "Download",
158 |   "upload": "Upload"
159 | },
160 | "status": {
161 |   "active": "Active",
162 |   "inactive": "Inactive",
163 |   "pending": "Pending",
164 |   "completed": "Completed",
165 |   "dropped": "Dropped",
166 |   "loading": "Loading...",
167 |   "saving": "Saving...",
168 |   "error": "Error",
169 |   "success": "Success"
170 | },
171 | "form": {
172 |   "required": "This field is required",
173 |   "email": "Email",
174 |   "password": "Password",
175 |   "name": "Name",
176 |   "description": "Description",
177 |   "title": "Title",
178 |   "code": "Code",
179 |   "selectOption": "Select an option",
180 |   "noResults": "No results found"
181 | },
182 | "errors": {
183 |   "generic": "Something went wrong. Please try again.",
184 |   "notFound": "The requested resource was not found.",
185 |   "unauthorized": "You are not authorized to perform this action.",
186 |   "forbidden": "Access denied.",
187 |   "networkError": "Network error. Please check your connection.",
188 |   "timeout": "The request timed out. Please try again.",
189 |   "validation": "Please check the form for errors."

```

```

190 },
191 "pagination": {
192   "previous": "Previous",
193   "next": "Next",
194   "showing": "Showing {{from}} to {{to}} of {{total}}",
195   "rowsPerPage": "Rows per page",
196   "noResults": "No results found.",
197   "pageOf": "Page {{page}} of {{total}}"
198 },
199 "confirmation": {
200   "deleteTitle": "Are you sure?",
201   "deleteMessage": "This action cannot be undone.",
202   "unsavedChanges": "You have unsaved changes. Are you sure you want to leave?"
203 },
204 "errorBoundary": {
205   "title": "Something went wrong",
206   "defaultMessage": "An unexpected error occurred.",
207   "retry": "Try Again"
208 },
209 "notFound": {
210   "code": "404",
211   "title": "Page not found",
212   "description": "The page you're looking for doesn't exist or may have moved.",
213   "backToLogin": "Back to sign in",
214   "goBack": "Go back"
215 },
216 "blooms": {
217   "remembering": "Remembering",
218   "understanding": "Understanding",
219   "applying": "Applying",
220   "analyzing": "Analyzing",
221   "evaluating": "Evaluating",
222   "creating": "Creating"
223 },
224 "attainment": {
225   "excellent": "Excellent",
226   "satisfactory": "Satisfactory",
227   "developing": "Developing",
228   "notYet": "Not Yet"
229 },
230 "attainmentInfo": {
231   "triggerLabel": "What does this attainment percentage mean?",
232   "title": "Understanding Attainment",
233   "description": "Attainment shows how well you've mastered your course learning outcomes.",
234   "bandsHeading": "Levels",
235   "ranges": {
236     "excellent": "{{min}}% and above",
237     "satisfactory": "{{min}}-{{max}}%",
238     "developing": "{{min}}-{{max}}%",
239     "notYet": "Below {{threshold}}%"
240   }
241 },
242 "mascot": {
243   "regionLabel": "Edi the learning coach",
244   "moments": {
245     "welcome": {
246       "title": "Hi, I'm Edi!",
247       "message": "I'll be your coach along the way. Let's set up your learning journey together."
248     },
249     "assessmentIntro": {
250       "title": "A quick check-in",
251       "message": "Answer honestly – there are no wrong answers here. This helps me personalize your experien
252     },
253     "emptyState": {
254       "title": "Nothing here yet",
255       "message": "This is where things will show up once you get started. Take the first step and I'll cheer
256     },
257     "firstXp": {
258       "title": "Your first XP!",
259       "message": "Nice work – you just earned your first experience points. Keep it up and watch your level
260     },
261     "firstEnrollment": {
262       "title": "You're enrolled!",
263       "message": "Welcome to your first course. Explore the lessons and I'll help you stay on track."
264     },
265     "password": {
266       "title": "Keeping you safe",
267       "message": "Pick a password you'll remember. Tap the eye icon any time to check what you typed."
268     }
269   }
270 },
271 "timetable": {
272   "title": "Timetable",
273   "weeklySchedule": "Weekly Schedule",
274   "time": "Time",
275   "class": "Class",
276   "sectionLabel": "Section {{code}}",
277   "days": {
278     "0": "Sunday",
279     "1": "Monday",
280     "2": "Tuesday",
281     "3": "Wednesday",
282     "4": "Thursday",
283     "5": "Friday",
284     "6": "Saturday"
285   },
286   "slotType": {
287     "lecture": "LEC",
288     "lab": "LAB",
289     "tutorial": "TUT"
290   },
291   "now": {
292     "happeningNow": "Happening now",
293     "upNext": "Up next",

```

```

294 |         "endsIn": "Ends in {{time}}",
295 |         "startsIn": "Starts in {{time}}",
296 |         "room": "Room {{room}}",
297 |         "noUpcoming": "No upcoming classes",
298 |         "noUpcomingHint": "You're all caught up – no classes are scheduled right now."
299 |     },
300 |     "remaining": {
301 |         "days": "{{value}}d",
302 |         "hours": "{{value}}h",
303 |         "minutes": "{{value}}m",
304 |         "lessThanMinute": "less than a minute"
305 |     }
306 | },
307 | "calendar": {
308 |     "title": "Calendar",
309 |     "subtitle": "A read-only view of your upcoming deadlines.",
310 |     "readOnlyNotice": "This calendar is read-only. To add or edit tasks and study sessions, use your Planner a
311 |     "monthly": "Monthly",
312 |     "weekly": "Weekly",
313 |     "previous": "Previous",
314 |     "next": "Next",
315 |     "noEvents": "No events",
316 |     "moreEvents": "+{{n}} more",
317 |     "daysShort": {
318 |         "0": "Sun",
319 |         "1": "Mon",
320 |         "2": "Tue",
321 |         "3": "Wed",
322 |         "4": "Thu",
323 |         "5": "Fri",
324 |         "6": "Sat"
325 |     }
326 | },
327 | "parentDashboard": {
328 |     "greeting": {
329 |         "morning": "Good morning",
330 |         "afternoon": "Good afternoon",
331 |         "evening": "Good evening"
332 |     },
333 |     "subtitle": "Stay connected with your child's learning journey.",
334 |     "children": "Children",
335 |     "totalCourses": "Total Courses",
336 |     "avgAttainment": "Avg Attainment",
337 |     "deadlines": "Deadlines",
338 |     "yourChildren": "Your Children",
339 |     "levelLabel": "Level",
340 |     "coursesLabel": "courses",
341 |     "noChildren": "No linked children yet. Ask your institution's admin to set up the parent-student link.",
342 |     "xp": "XP"
343 | },
344 | "parentPlanner": {
345 |     "title": "Study Plan",
346 |     "today": "Today",
347 |     "previousWeek": "Previous week",
348 |     "nextWeek": "Next week",
349 |     "studyHours": "Study Hours",
350 |     "sessions": "Sessions",
351 |     "tasksDone": "Tasks Done",
352 |     "weeklySchedule": "Weekly Schedule",
353 |     "noStudent": {
354 |         "title": "No student selected",
355 |         "description": "Select a student from the Children page to view their study plan.",
356 |         "cta": "Go to Children"
357 |     }
358 | },
359 | "parentProfile": {
360 |     "title": "Profile",
361 |     "info": "Profile Information"
362 | },
363 | "accessibility": {
364 |     "title": "Accessibility Settings",
365 |     "fontSize": "Font Size",
366 |     "fontDefault": "Default",
367 |     "fontLarge": "Large",
368 |     "fontXLarge": "Extra Large",
369 |     "highContrast": "High Contrast",
370 |     "reducedAnimations": "Reduced Animations",
371 |     "dyslexiaFont": "Dyslexia-Friendly Font",
372 |     "simplifiedView": "Simplified View",
373 |     "cognitiveLoadMessage": "This page has a lot of information – would you like a simplified view?"
374 | },
375 | "user": "User",
376 | "skipToMain": "Skip to main content",
377 | "search": "Search",
378 | "searchPlaceholder": "Search courses, assignments, announcements...",
379 | "searchLoading": "Searching...",
380 | "searchEmpty": "No results for “{{q}}”",
381 | "searchType": {
382 |     "course": "Course",
383 |     "assignment": "Assignment",
384 |     "announcement": "Announcement"
385 | },
386 | "notifications": "Notifications",
387 | "settings": "Settings",
388 | "profileMenu": "Profile menu",
389 | "myProfile": "My Profile",
390 | "profileSettings": "Profile Settings",
391 | "institutionSettings": "Institution Settings",
392 | "header": {
393 |     "user": "User",
394 |     "search": "Search",
395 |     "searchPlaceholder": "Search courses, assignments, announcements...",
396 |     "searchLoading": "Searching...",
397 |     "searchEmpty": "No results for “{{q}}”",

```

```

398 | "searchType": {
399 |   "course": "Course",
400 |   "assignment": "Assignment",
401 |   "announcement": "Announcement"
402 | },
403 | "notifications": "Notifications",
404 | "settings": "Settings",
405 | "profileMenu": "Profile menu",
406 | "myProfile": "My Profile",
407 | "profileSettings": "Profile Settings",
408 | "institutionSettings": "Institution Settings",
409 | "primaryNav": {
410 |   "label": "Primary navigation"
411 | },
412 | "unreadCount": "{{count}} unread notifications",
413 | "notificationsLabel": "Notifications",
414 | "markAllRead": "Mark all as read",
415 | "whyThis": "Why am I seeing this?",
416 | "whyThisDescription": "This guidance uses the following current learning signals.",
417 | "whySignals": {
418 |   "teacher": "Your current workload includes {{pending}} submissions to grade and {{atRisk}} students need
419 |   "parent": "This summary uses the learning records and upcoming deadlines for your {{children}} linked ch
420 |   "coordinator": "This view uses {{belowTarget}} program outcomes currently below target and the latest ev
421 |   "admin": "This view uses the institution records available to your admin role, including {{users}} users
422 | },
423 | "openGlobalSearch": "Open global search",
424 | "search": "Search",
425 | "searchPrompt": "Type to search or jump to..",
426 | "commandSection": { "goTo": "Go to", "actions": "Actions" },
427 | "commands": {
428 |   "today": "Today",
429 |   "learningPath": "Learning Path",
430 |   "tutor": "AI Tutor",
431 |   "progress": "Progress",
432 |   "fixWeakest": "Fix my weakest CLO",
433 |   "askTutor": "Ask the AI Tutor",
434 |   "home": "Home",
435 |   "studentTriage": "Student Triage",
436 |   "curriculumStudio": "Curriculum Studio",
437 |   "gradingQueue": "Grading Queue",
438 |   "draftFeedback": "Draft feedback with AI",
439 |   "uploadLessons": "Upload !' lessons",
440 |   "growth": "Growth & Wellbeing",
441 |   "support": "Support & Messages",
442 |   "outcomes": "Outcome Attainment",
443 |   "curriculumMatrix": "Curriculum Matrix",
444 |   "accreditation": "Accreditation",
445 |   "analytics": "Analytics",
446 |   "aiGovernance": "AI Governance",
447 |   "people": "People"
448 | },
449 | "profileSubtitle": {
450 |   "admin": "Institution Admin",
451 |   "coordinator": "Program Coordinator",
452 |   "teacher": "Teacher",
453 |   "student": "Student",
454 |   "parent": "Parent",
455 |   "studentLevel": "Lvl {{level}} · {{xp}} XP",
456 |   "teacherDetail": "{{department}} · {{count}} classes",
457 |   "guardianOf": "Guardian of {{name}}"
458 | },
459 | "stats": {
460 |   "teacher": "Teaching summary",
461 |   "coordinator": "Programme summary",
462 |   "admin": "Institution summary",
463 |   "parent": "Child progress summary",
464 |   "classes": "classes",
465 |   "toGrade": "to grade",
466 |   "programs": "programmes",
467 |   "belowTarget": "below target",
468 |   "learners": "learners",
469 |   "activeAccounts": "active",
470 |   "onTrack": "On track",
471 |   "needsAttention": "Needs attention",
472 |   "childProgress": "child progress"
473 | },
474 | "emptyNotifications": {
475 |   "title": "No notifications",
476 |   "description": "You're all caught up!"
477 | },
478 | "groupLabel": {
479 |   "today": "Today",
480 |   "earlierThisWeek": "Earlier this week",
481 |   "older": "Older"
482 | }
483 | },
484 | "notificationsCta": {
485 |   "viewGrade": "View Grade",
486 |   "openAssignment": "Open Assignment",
487 |   "viewBadge": "View Badge",
488 |   "viewStreak": "View Streak",
489 |   "viewProgress": "View Progress",
490 |   "viewLeaderboard": "View Leaderboard",
491 |   "viewHabits": "View Habits",
492 |   "viewAssignment": "View Assignment",
493 |   "viewAll": "View All"
494 | },
495 | "studentRailFallback": {
496 |   "label": "Learning momentum",
497 |   "title": "Keep going",
498 |   "streak": "Current streak",
499 |   "level": "Current level",
500 |   "cta": "Open today"
501 | },

```

```

502 | "tour": {
503 |   "takeTour": "Take the tour",
504 |   "back": "Back",
505 |   "close": "Close",
506 |   "finish": "Finish",
507 |   "next": "Next",
508 |   "open": "Open the dialog",
509 |   "skip": "Skip tour",
510 |   "student": {
511 |     "step1": {
512 |       "title": "Welcome to your dashboard",
513 |       "content": "This is your home base. Find notifications, your XP, and your daily streak right here at t
514 |     },
515 |     "step2": {
516 |       "title": "Your navigation",
517 |       "content": "Jump between courses, planner, journal, leaderboard, and more from the sidebar."
518 |     },
519 |     "step3": {
520 |       "title": "Daily greeting",
521 |       "content": "A quick personal welcome and your most important next action live in this hero card."
522 |     },
523 |     "step4": {
524 |       "title": "Your key stats",
525 |       "content": "Track XP, level, streak, and habits at a glance – everything that drives your progress."
526 |     },
527 |     "step5": {
528 |       "title": "Daily habits",
529 |       "content": "Hit Login, Submit, Journal, and Read every day to chase a Perfect Day and unlock bonus XP.
530 |     },
531 |     "step6": {
532 |       "title": "XP and streaks",
533 |       "content": "Watch your XP climb in real time. Keep your streak alive – every day matters."
534 |     },
535 |     "step7": {
536 |       "title": "Profile and settings",
537 |       "content": "Switch language, theme, or sign out from your profile menu in the top right."
538 |     }
539 |   },
540 |   "teacher": {
541 |     "step1": {
542 |       "title": "Welcome, teacher",
543 |       "content": "This is your control room. Notifications, students, and live activity surface right here a
544 |     },
545 |     "step2": {
546 |       "title": "Your tools",
547 |       "content": "Open courses, assignments, grading, outcomes, and analytics from the sidebar."
548 |     },
549 |     "step3": {
550 |       "title": "Class snapshot",
551 |       "content": "See pending grading, attainment trends, and at-risk students at a glance."
552 |     },
553 |     "step4": {
554 |       "title": "Define learning outcomes",
555 |       "content": "Create CLOs aligned to Bloom's levels – these power every rubric, attainment chart, and re
556 |     },
557 |     "step5": {
558 |       "title": "Build rubrics",
559 |       "content": "Drag-and-drop rubric criteria, link them to CLOs, and reuse across assignments."
560 |     },
561 |     "step6": {
562 |       "title": "Grading queue",
563 |       "content": "Submissions land here in priority order. AI-assisted feedback drafts speed up your turnaro
564 |     },
565 |     "step7": {
566 |       "title": "Language and profile",
567 |       "content": "Toggle Arabic or English and access your profile from the top right."
568 |     }
569 |   },
570 |   "coordinator": {
571 |     "step1": {
572 |       "title": "Welcome, coordinator",
573 |       "content": "Program oversight starts here. Notifications, alerts, and quick actions are at the top."
574 |     },
575 |     "step2": {
576 |       "title": "Program tools",
577 |       "content": "Manage programs, PLOs, courses, CQI plans, and accreditation reports from the sidebar."
578 |     },
579 |     "step3": {
580 |       "title": "Program health",
581 |       "content": "Coverage gaps, attainment trends, and at-risk indicators across your programs."
582 |     },
583 |     "step4": {
584 |       "title": "Curriculum matrix",
585 |       "content": "See which CLOs cover each PLO across courses. Spot gaps and overlaps in seconds."
586 |     },
587 |     "step5": {
588 |       "title": "Manage PLOs",
589 |       "content": "Create, edit, and weight Program Learning Outcomes – and map them to ILOs."
590 |     },
591 |     "step6": {
592 |       "title": "Language and theme",
593 |       "content": "Switch between English and Arabic, or toggle dark mode anytime."
594 |     },
595 |     "step7": {
596 |       "title": "Profile menu",
597 |       "content": "Profile, preferences, and sign out are in the top-right menu."
598 |     }
599 |   },
600 |   "parent": {
601 |     "step1": {
602 |       "title": "Welcome, parent",
603 |       "content": "Stay close to your child's progress. Notifications and alerts are right here at the top."
604 |     },
605 |     "step2": {

```



```

606     "title": "Family hub",
607     "content": "Access children, progress, attendance, fees, and messages from the sidebar."
608 },
609 "step3": {
610     "title": "Child snapshot",
611     "content": "Quick KPIs across all your linked children – attendance, grades, streaks, and risk signals
612 },
613 "step4": {
614     "title": "Linked children",
615     "content": "Switch between children to view their individual dashboards in detail."
616 },
617 "step5": {
618     "title": "Fees and billing",
619     "content": "View invoices, payment status, and download receipts whenever you need them."
620 },
621 "step6": {
622     "title": "Planner",
623     "content": "See your child's upcoming assignments and exams so you can plan ahead together."
624 },
625 "step7": {
626     "title": "Profile menu",
627     "content": "Settings, language, and sign-out live in the top-right menu."
628 }
629 },
630 "admin": {
631     "step1": {
632         "title": "Welcome, admin",
633         "content": "Institution-wide controls start here. Live notifications and alerts are at the top."
634     },
635     "step2": {
636         "title": "Admin tools",
637         "content": "Users, programs, settings, audit logs, and analytics are all in the sidebar."
638     },
639     "step3": {
640         "title": "Institution health",
641         "content": "Total users, active courses, average attainment, and at-risk counts at a glance."
642     },
643     "step4": {
644         "title": "Primary action",
645         "content": "Add users, create programs, or trigger bulk imports right from the dashboard header."
646     },
647     "step5": {
648         "title": "Section cards",
649         "content": "Each card here drills into a deeper view – users by role, recent activity, audit trail, an
650     },
651     "step6": {
652         "title": "Language and theme",
653         "content": "Toggle Arabic or English and switch dark mode anytime."
654     },
655     "step7": {
656         "title": "Profile menu",
657         "content": "Profile, preferences, and sign-out are in the top-right menu."
658     }
659 }
660 },
661 "theme": {
662     "label": "Theme",
663     "light": "Light",
664     "dark": "Dark",
665     "system": "System"
666 },
667 "auth": {
668     "signedOut": "Signed out successfully",
669     "signOut": "Sign out"
670 },
671 "common": {
672     "error": "An error occurred. Please try again.",
673     "uploading": "Uploading...",
674     "cancel": "Cancel"
675 },
676 "weekPicker": {
677     "weekOf": "Week of",
678     "selectWeek": "Select a week"
679 },
680 "roleProfile": {
681     "me": "Me",
682     "subtitle": "Your identity, workspace, preferences, and account.",
683     "fallbackName": "User",
684     "noEmail": "No email available",
685     "editProfile": "Edit profile",
686     "contact": "Contact",
687     "workspace": "Workspace",
688     "workspaceDescription": "Open the tools most relevant to your role.",
689     "appearance": "Appearance",
690     "appearanceDescription": "Choose how Edeviser looks for you.",
691     "security": "Security & access",
692     "securityDescription": "Manage account protection and notifications.",
693     "changePassword": "Change password",
694     "open": "Open",
695     "notifications": "Notification centre",
696     "statusActive": "Active",
697     "statusInactive": "Inactive",
698     "notSet": "Not set",
699     "admin": {
700         "role": "Institution Admin",
701         "scope": "Institution workspace",
702         "users": "Users",
703         "active": "Active",
704         "programs": "Programs",
705         "courses": "Courses",
706         "overview": "Institution & access",
707         "overviewDescription": "Your institution scope and administrative permissions.",
708         "accountStatus": "Account status",
709         "institutionId": "Institution ID",

```

```

710 |     "accessLevel": "Access level",
711 |     "fullAccess": "Institution administrator",
712 |     "institutionPage": "Institution page",
713 |     "institutionConnected": "Institution workspace connected",
714 |     "learners": "Learners",
715 |     "teachers": "Teachers",
716 |     "institutionSettings": "Institution settings",
717 |     "bilingual": "Bilingual (Arabic / English)",
718 |     "bilingualDescription": "RTL layout and dual-language content",
719 |     "enabled": "Enabled",
720 |     "thresholds": "Attainment thresholds",
721 |     "thresholdDescription": "Excellent 85 · Satisfactory 70 · Developing 50",
722 |     "configure": "Configure",
723 |     "parentReports": "Parent growth reports",
724 |     "parentReportsDescription": "Weekly wellbeing and progress digest",
725 |     "platformPreferences": "Platform preferences",
726 |     "notificationPreferences": "Notification preferences",
727 |     "notificationDescription": "Choose the institution events sent to your email.",
728 |     "newRegistrations": "New user registrations",
729 |     "newRegistrationsDescription": "Alert when a new account joins the institution",
730 |     "securityAlerts": "Security and sign-in alerts",
731 |     "securityAlertsDescription": "Critical account and authentication events",
732 |     "weeklySummary": "Weekly institution summary",
733 |     "weeklySummaryDescription": "A concise weekly operating report",
734 |     "quotaWarnings": "Storage and quota warnings",
735 |     "quotaWarningsDescription": "Capacity alerts before services are affected",
736 |     "permissions": "Role & permissions",
737 |     "manageUsers": "Manage users and roles",
738 |     "configureInstitution": "Configure institution settings",
739 |     "setAiPolicy": "Set AI autonomy and policy",
740 |     "viewAuditLogs": "View analytics and audit logs",
741 |     "manageBilling": "Manage billing and integrations",
742 |     "governanceShortcuts": "Governance shortcuts",
743 |     "aiPolicy": "AI autonomy and policy",
744 |     "auditLog": "AI action audit log",
745 |     "memoryPrivacy": "Memory and privacy",
746 |     "viewAsUser": "View as user",
747 |     "audited": "Audited"
748 | },
749 |     "teacher": {
750 |         "role": "Teacher",
751 |         "scope": "Teaching workspace",
752 |         "students": "Students",
753 |         "toGrade": "To grade",
754 |         "graded": "Graded",
755 |         "attainment": "Attainment",
756 |         "overview": "Academic profile",
757 |         "overviewDescription": "Your teaching identity and academic details.",
758 |         "department": "Department",
759 |         "designation": "Designation",
760 |         "academicRank": "Academic rank",
761 |         "highestDegree": "Highest degree",
762 |         "viewPublicProfile": "View public profile",
763 |         "classes": "Classes",
764 |         "courses": "Courses",
765 |         "clos": "CLOs",
766 |         "impact": "Teaching impact",
767 |         "avgMastery": "Average mastery",
768 |         "gradingCompletion": "Grading completion",
769 |         "atRisk": "At-risk students",
770 |         "aiAutonomy": "AI autonomy for your classes",
771 |         "reviewControls": "Review controls",
772 |         "autonomyDescription": "A2 · AI can prepare actions, but you approve every change before it is applied.",
773 |         "notificationPreferences": "Notification preferences",
774 |         "notificationDescription": "Choose the teaching signals sent to your email.",
775 |         "atRiskAlerts": "At-risk student alerts",
776 |         "atRiskAlertsDescription": "Signals when a learner may need support",
777 |         "newSubmissions": "New submissions to grade",
778 |         "newSubmissionsDescription": "Alerts when new work enters your queue",
779 |         "handoffRequests": "Tutor handoff requests",
780 |         "handoffDescription": "Alerts when the AI tutor escalates to you",
781 |         "weeklySummary": "Weekly class summary",
782 |         "weeklySummaryDescription": "A weekly digest across your classes",
783 |         "myClasses": "My classes"
784 |     },
785 |     "parent": {
786 |         "role": "Parent / Guardian",
787 |         "scope": "Guardian of {{names}}",
788 |         "noChildren": "No linked children",
789 |         "children": "Children",
790 |         "courses": "Courses",
791 |         "attainment": "Attainment",
792 |         "deadlines": "Deadlines",
793 |         "overview": "Family access",
794 |         "overviewDescription": "Your verified family links and account access.",
795 |         "linkedChildren": "Linked children",
796 |         "accountStatus": "Account status",
797 |         "access": "Access",
798 |         "verifiedAccess": "Verified guardian",
799 |         "contactSchool": "Contact school",
800 |         "alerts": "Alerts",
801 |         "linkedLearners": "Linked learners",
802 |         "linkedCount": "{{count}} linked",
803 |         "learnerSummary": "{{courses}} courses · {{attainment}}% attainment · link verified",
804 |         "linkAnotherChild": "Link another child",
805 |         "feesPayments": "Fees & payments",
806 |         "announcements": "Announcements",
807 |         "privacy": "Privacy & what you can see",
808 |         "details": "Details",
809 |         "growthShared": "Growth & wellbeing summaries",
810 |         "shared": "Shared",
811 |         "rawScores": "Raw exam scores",
812 |         "notShared": "Not shared",
813 |         "privateJournal": "Private journal",

```

```

814     "private": "Private to learner",
815     "notificationPreferences": "Notifications",
816     "notificationDescription": "Choose the family updates sent to your email.",
817     "weeklyGrowth": "Weekly growth story",
818     "weeklyGrowthDescription": "A strengths-led progress summary",
819     "wellbeingAlerts": "Wellbeing alerts only",
820     "wellbeingAlertsDescription": "Only important wellbeing signals",
821     "celebrate": "Celebrate improvements",
822     "celebrateDescription": "Positive progress and milestone updates"
823   }
824 },
825   "avatar": {
826     "title": "Profile Picture",
827     "description": "Upload a photo to personalize your profile.",
828     "current": "Current photo",
829     "preview": "Preview",
830     "dragDrop": "Drag and drop an image here",
831     "formats": "PNG, JPG, or WebP – max 2 MB",
832     "selectFile": "Choose file",
833     "upload": "Upload photo",
834     "uploadSuccess": "Profile picture updated",
835     "invalidType": "Please upload a PNG, JPG, or WebP image.",
836     "fileTooLarge": "File is too large. Maximum size is 2 MB."
837   },
838   "captcha": {
839     "devMode": "Captcha (dev mode – no VITE_CAPTCHA_SITE_KEY set)",
840     "bypass": "Bypass"
841   },
842   "profile": {
843     "myProfile": "My Profile"
844   },
845   "greeting": {
846     "morning": "Good morning",
847     "afternoon": "Good afternoon",
848     "evening": "Good evening",
849     "there": "there"
850   },
851   "tos": {
852     "title": "Terms of Service",
853     "description": "Please review and accept our Terms of Service and Privacy Policy to continue using the pla
854     "checkboxLabel": "I have read and agree to the",
855     "termsLink": "Terms of Service",
856     "and": "and",
857     "privacyLink": "Privacy Policy",
858     "acceptButton": "Accept",
859     "acceptSuccess": "Terms of Service accepted",
860     "acceptError": "Failed to accept Terms of Service. Please try again."
861   },
862   "notificationsGroup": {
863     "askTutor": "Ask Tutor"
864   },
865   "admin": {
866     "badges": {
867       "title": "Badge Definitions",
868       "description": "Institution-level badge templates with tiered progression.",
869       "spotlight": "Spotlight schedule",
870       "new": "New badge",
871       "loadError": "Could not load badge definitions.",
872       "empty": "No badge definitions yet. Create the first institution badge.",
873       "uncategorized": "Uncategorized",
874       "archivedLabel": "Archived",
875       "noDescription": "No description",
876       "archive": "Archive",
877       "restore": "Restore",
878       "archived": "Badge archived",
879       "restored": "Badge restored",
880       "deleted": "Badge definition deleted",
881       "updated": "Badge definition updated",
882       "created": "Badge definition created",
883       "missingInstitution": "Your account is not linked to an institution.",
884       "editTitle": "Edit badge definition",
885       "createTitle": "Create badge definition",
886       "formDescription": "Define the presentation and Bronze, Silver, and Gold progression conditions.",
887       "emoji": "Emoji",
888       "name": "Name",
889       "key": "Badge key",
890       "category": "Category",
891       "badgeDescription": "Description",
892       "tierConditions": "Tier conditions",
893       "bronze": "Bronze",
894       "silver": "Silver",
895       "gold": "Gold",
896       "conditionPlaceholder": "Describe the measurable threshold",
897       "singleTier": "Single-tier · condition not configured",
898       "create": "Create badge",
899       "deleteTitle": "Delete badge definition?",
900       "deleteDescription": "This permanently removes the institution badge template. Existing earned badges ar
901     },
902     "governance": {
903       "title": "AI Governance",
904       "auditLog": "Full audit log",
905       "description": "Human approval remains the ceiling for sensitive actions. Usage and quality metrics belo
906       "autonomyCeiling": "Institution autonomy ceiling",
907       "roadmap": "Read-only policy · roadmap",
908       "roadmapNote": "Institution-specific policy storage is not available yet. The current product guardrail
909       "currentPolicy": "Current platform guardrail: A2 – AI may act only after a human approves. Grading, publ
910       "loadError": "Could not load AI governance metrics.",
911       "usage": "Tutor usage this month",
912       "requests": "Requests",
913       "loggedRequests": "Logged tutor model calls",
914       "successRate": "Success rate",
915       "successful": "successful",
916       "tokens": "Tokens",
917       "monthToDate": "Month to date",

```

```

918 |         "latency": "Avg latency",
919 |         "responseTime": "Server response time",
920 |         "models": "Models used",
921 |         "noUsage": "No tutor model calls have been logged this month.",
922 |         "modelUsage": "{{requests}} requests · {{tokens}} tokens",
923 |         "quality": "AI quality signals",
924 |         "suggestionAcceptance": "Suggestion acceptance",
925 |         "suggestionsReviewed": "{{count}} suggestions reviewed",
926 |         "predictionAccuracy": "Prediction accuracy",
927 |         "validatedPredictions": "{{count}} validated predictions",
928 |         "draftAcceptance": "Draft acceptance",
929 |         "feedbackDrafts": "{{count}} feedback drafts",
930 |         "liveData": "Live institution data",
931 |         "noFabricatedMetrics": "No prototype-only counts are shown.",
932 |         "perAction": "What AI may do, per action",
933 |         "action": "Action",
934 |         "level": "Current level",
935 |         "hardCap": "Hard cap",
936 |         "memory": "AI memory and privacy",
937 |         "review": "Review and accountability",
938 |         "reviewNote": "Administrative actions are written to the audit log. AI-specific action approvals will ap
939 |         "openAudit": "Open audit log",
940 |         "levels": {
941 |             "a0": "Observe and display",
942 |             "a1": "Suggest and draft",
943 |             "a2": "Act after approval",
944 |             "a3": "Autonomous safe actions"
945 |         },
946 |         "actions": {
947 |             "showInsights": "Show insights and signals",
948 |             "suggestAction": "Suggest a next action",
949 |             "scheduleReviews": "Schedule spaced reviews",
950 |             "reorderPlan": "Reorder a learner's daily plan",
951 |             "sendStudentNudge": "Send a student nudge",
952 |             "draftTeacherFeedback": "Draft teacher feedback",
953 |             "generateEvidencePack": "Generate a report or evidence pack",
954 |             "sendParentCommunication": "Send parent communication",
955 |             "assignGrade": "Assign a grade",
956 |             "publishContent": "Publish learning content"
957 |         },
958 |         "memoryItems": {
959 |             "tutorLabel": "Tutor conversation:",
960 |             "tutorValue": "session-scoped",
961 |             "learnerLabel": "Learner model:",
962 |             "learnerValue": "persistent and exportable under RLS",
963 |             "evidenceLabel": "Outcome evidence:",
964 |             "evidenceValue": "immutable audit evidence",
965 |             "piiLabel": "Passwords and raw PII:",
966 |             "piiValue": "never stored in tutor prompts"
967 |         }
968 |     },
969 |     "legal": {
970 |         "eyebrow": "Edeviser legal",
971 |         "lastUpdated": "Last updated: January 1, 2026",
972 |         "backToSignIn": "Back to sign in",
973 |         "summary": {
974 |             "title": "Plain-language summary"
975 |         },
976 |         "terms": {
977 |             "title": "Terms of Service",
978 |             "subtitle": "The rules that keep Edeviser safe, reliable, and fair for every learner and institution.",
979 |             "summary": "Use the platform responsibly, protect your account, and respect other people's access and co
980 |             "sections": {
981 |                 "1": {
982 |                     "title": "1. Acceptance of terms",
983 |                     "body": "By accessing or using the Edeviser platform, you agree to be bound by these Terms of Servic
984 |                 },
985 |                 "2": {
986 |                     "title": "2. Description of service",
987 |                     "body": "Edeviser is an outcome-based education management platform that provides tools for learning
988 |                 },
989 |                 "3": {
990 |                     "title": "3. User accounts",
991 |                     "body": "You are responsible for maintaining the confidentiality of your account credentials. You mu
992 |                 },
993 |                 "4": {
994 |                     "title": "4. Acceptable use",
995 |                     "body": "You agree not to misuse the platform, including attempting to gain unauthorized access, int
996 |                 },
997 |                 "5": {
998 |                     "title": "5. Intellectual property",
999 |                     "body": "Content you create on the platform remains yours. Edeviser retains rights to the platform s
1000 |                 },
1001 |                 "6": {
1002 |                     "title": "6. Limitation of liability",
1003 |                     "body": "Edeviser is provided as is without warranties of any kind. We are not liable for indirect,
1004 |                 },
1005 |                 "7": {
1006 |                     "title": "7. Changes to terms",
1007 |                     "body": "We may update these terms from time to time. Continued use of the platform after changes co
1008 |                 },
1009 |                 "8": {
1010 |                     "title": "8. Contact",
1011 |                     "body": "For questions about these terms, contact our legal team."
1012 |                 }
1013 |             }
1014 |         },
1015 |     },
1016 |     "privacy": {
1017 |         "title": "Privacy Policy",
1018 |         "subtitle": "How Edeviser collects, protects, and uses information across the learning journey.",
1019 |         "summary": "We use data to deliver learning services and institution analytics. We do not sell personal
1020 |         "sections": {
1021 |             "1": {

```

```

1022         "title": "1. Information we collect",
1023         "body": "We collect information you provide directly, including your name, email, and institution, p
1024     },
1025     "2": {
1026         "title": "2. How we use your information",
1027         "body": "Your data is used to provide and improve Edeviser, personalize learning, generate analytics
1028     },
1029     "3": {
1030         "title": "3. Cookies",
1031         "body": "We use essential cookies for authentication and session management. Analytics cookies are e
1032     },
1033     "4": {
1034         "title": "4. Data sharing",
1035         "body": "We do not sell personal data. Data may be shared with your institution's administrators and
1036     },
1037     "5": {
1038         "title": "5. Data retention",
1039         "body": "Data is retained for the duration of your account. After account deletion, personal data is
1040     },
1041     "6": {
1042         "title": "6. Your rights",
1043         "body": "You may access, correct, or delete your personal data. You can export your data from profil
1044     },
1045     "7": {
1046         "title": "7. Security",
1047         "body": "We use industry-standard safeguards, including encryption in transit, row-level security, a
1048     },
1049     "8": {
1050         "title": "8. Contact",
1051         "body": "For privacy-related questions, contact our privacy team."
1052     }
1053 }
1054 },
1055 },
1056 "empty": {
1057     "noCourses": {
1058         "title": "No Courses Yet",
1059         "description": "Courses will appear here once they are created and assigned."
1060     },
1061     "noProgress": {
1062         "title": "No Progress Data",
1063         "description": "Start completing activities to track your learning progress."
1064     },
1065     "noUsers": {
1066         "title": "No Users Found",
1067         "description": "Invite users to your institution to get started."
1068     },
1069     "noNotifications": {
1070         "title": "No Notifications",
1071         "description": "You're all caught up! New notifications will appear here."
1072     },
1073     "noBadges": {
1074         "title": "No Badges Earned",
1075         "description": "Complete challenges and milestones to earn badges."
1076     },
1077     "noEvidence": {
1078         "title": "No Evidence Yet",
1079         "description": "Student submissions and assessment evidence will appear here."
1080     },
1081     "noMarketplaceItems": {
1082         "title": "No Items Available",
1083         "description": "Marketplace items will appear here once they are listed."
1084     },
1085     "noLinkedStudents": {
1086         "title": "No Linked Students",
1087         "description": "Ask your institution's admin to link student accounts."
1088     },
1089     "noTeams": {
1090         "title": "No Teams Yet",
1091         "description": "Create teams to organize students into collaborative groups."
1092     },
1093     "noChallenges": {
1094         "title": "No Challenges Yet",
1095         "description": "Create challenges to engage students with team-based activities."
1096     },
1097     "noOutcomes": {
1098         "title": "No Outcomes Found",
1099         "description": "Add learning outcomes to begin mapping and analysis."
1100     },
1101     "noQuestions": {
1102         "title": "No Questions Yet",
1103         "description": "Add or generate questions to build your question bank."
1104     },
1105     "noResults": {
1106         "title": "No Results Yet",
1107         "description": "Results will appear here once students complete their assessments."
1108     },
1109     "noData": {
1110         "title": "No Data Available",
1111         "description": "Data will populate here as activities are completed."
1112     },
1113     "noSessions": {
1114         "title": "No Sessions Yet",
1115         "description": "Create sessions to begin tracking attendance."
1116     },
1117     "noSurveys": {
1118         "title": "No Surveys Yet",
1119         "description": "Create your first survey to collect feedback."
1120     },
1121     "noSemesters": {
1122         "title": "No Semesters Yet",
1123         "description": "Create your first semester to get started."
1124     },
1125     "noTimetable": {

```

```

1126 |         "title": "No Timetable Slots",
1127 |         "description": "Add timetable slots to organize the schedule."
1128 |     },
1129 |     "noResponses": {
1130 |         "title": "No Responses Yet",
1131 |         "description": "Responses will appear here once participants submit."
1132 |     },
1133 |     "noAssignments": {
1134 |         "title": "No Assignments Yet",
1135 |         "description": "Assignments will appear here once they are created."
1136 |     },
1137 |     "noSubmissions": {
1138 |         "title": "You're All Caught Up",
1139 |         "description": "New student submissions will appear here when they are ready to grade."
1140 |     },
1141 |     "noCLOs": {
1142 |         "title": "No CLOs Found",
1143 |         "description": "Course learning outcomes will appear here once created."
1144 |     },
1145 |     "noPLOs": {
1146 |         "title": "No PLOs Created",
1147 |         "description": "Ask your coordinator to create program learning outcomes first."
1148 |     },
1149 |     "noILOs": {
1150 |         "title": "No ILOs Created",
1151 |         "description": "Ask your admin to create institutional learning outcomes first."
1152 |     },
1153 |     "noStudents": {
1154 |         "title": "No Students Found",
1155 |         "description": "Enrolled students will appear here."
1156 |     },
1157 |     "noRubrics": {
1158 |         "title": "No Rubrics Yet",
1159 |         "description": "Create rubrics to standardize your grading criteria."
1160 |     },
1161 |     "noActionPlans": {
1162 |         "title": "No Action Plans Yet",
1163 |         "description": "Create a CQI action plan to start closing the loop."
1164 |     },
1165 |     "noAttendance": {
1166 |         "title": "No Attendance Records",
1167 |         "description": "Create sessions and mark attendance to see records here."
1168 |     },
1169 |     "noXPData": {
1170 |         "title": "No XP Data Yet",
1171 |         "description": "Start earning XP to see your personal best here."
1172 |     },
1173 |     "noImprovementData": {
1174 |         "title": "No Improvement Data",
1175 |         "description": "Keep earning XP to see who is improving the most."
1176 |     },
1177 |     "noLeaderboardData": {
1178 |         "title": "No Leaderboard Data",
1179 |         "description": "Leaderboard entries will appear as students earn XP."
1180 |     },
1181 |     "noCorrelationData": {
1182 |         "title": "No Correlation Data",
1183 |         "description": "CLO correlation data will appear once quizzes are completed."
1184 |     },
1185 |     "noBloomsData": {
1186 |         "title": "No Bloom's Data",
1187 |         "description": "Bloom's level distribution will appear as quiz data is collected."
1188 |     },
1189 |     "noUsageData": {
1190 |         "title": "No Usage Data",
1191 |         "description": "Usage trends will appear as students interact with the tutor."
1192 |     },
1193 |     "noCitationData": {
1194 |         "title": "No Citation Data",
1195 |         "description": "Material citations will appear as the AI Tutor references content."
1196 |     },
1197 |     "noAttainmentData": {
1198 |         "title": "No Attainment Data",
1199 |         "description": "CLO attainment will appear as assessments are completed."
1200 |     }
1201 | }
1202 | }
1203 |

```

FILE: [src/locales/en/coordinator.json](#)

TYPE: .json | LINES: 1-397 | SHA256: bad99b8ac90e70456094c4b9793934cb7aeef7eaaf3deaee127769371428d318

```

1 | {
2 |   "dashboard": {
3 |     "title": "Coordinator Dashboard",
4 |     "welcome": {
5 |       "subtitle": "Monitor program outcomes, track attainment, and drive continuous quality improvement."
6 |     },
7 |     "totalPLOs": "Total PLOs",
8 |     "activeCourses": "Active Courses",
9 |     "cloCoverage": "CLO Coverage",
10 |    "teacherCompliance": "Teacher Compliance",
11 |    "curriculumMatrix": "Curriculum Matrix",
12 |    "selectProgram": "Select program",
13 |    "viewFullMatrix": "View Full Matrix",
14 |    "noProgramsAvailable": "No programs available. Create a program to view the curriculum matrix.",
15 |    "atRiskStudents": "At-Risk Students",
16 |    "atRiskPending": "At-risk student detection will be available once attainment data is collected.",
17 |    "atRiskBelowThreshold": "students below the 50% attainment threshold",
18 |    "noAtRiskStudents": "No at-risk students. All students are at or above the attainment threshold.",
19 |    "avgAttainment": "Avg attainment",
20 |    "recoveryPathways": "Recovery Pathways",
21 |    "totalActivations": "Total Activations",
22 |    "completionRate": "Completion Rate",

```

```

23 | "avgCompletionTime": "Avg Completion Time",
24 | "retrySuccessRate": "Retry Success Rate",
25 | "cqiActionPlans": "CQI Action Plans",
26 | "viewAll": "View All",
27 | "planned": "Planned",
28 | "inProgress": "In Progress",
29 | "completed": "Completed",
30 | "evaluated": "Evaluated",
31 | "noCqiPlans": "No CQI action plans yet. Create one from the CQI Plans page.",
32 | "sectionComparison": "Section Comparison",
33 | "selectCourse": "Select course",
34 | "selectCourseToCompare": "Select a course to compare section attainment metrics.",
35 | "noSectionsFound": "No sections found for this course.",
36 | "obeVisualizations": "OBE Visualizations",
37 | "sankeyDiagram": "Sankey Diagram",
38 | "sankeyDesc": "ILO !' PLO !' CLO flow",
39 | "gapAnalysis": "Gap Analysis",
40 | "gapAnalysisDesc": "Unmapped outcomes",
41 | "coverageHeatmap": "Coverage Heatmap",
42 | "coverageHeatmapDesc": "CLO coverage density",
43 | "semesterTrends": "Semester Trends",
44 | "semesterTrendsDesc": "Attainment over time",
45 | "cohortComparison": "Cohort Comparison",
46 | "cohortComparisonDesc": "Cross-cohort metrics",
47 | "hub": {
48 |   "title": "Program health, prepared",
49 |   "subtitle": "Focus on the items below that need your attention.",
50 |   "why": "Why am I seeing this?",
51 |   "plotTitle": "PLO attainment on track",
52 |   "plotBelow": "{{count}} PLOs below target",
53 |   "review": "Review",
54 |   "gapTitle": "Curriculum coverage",
55 |   "openMatrix": "Open matrix",
56 |   "accredTitle": "Accreditation readiness",
57 |   "continueEvidence": "Continue evidence"
58 | },
59 | "kpi": {
60 |   "programs": "Programs",
61 |   "avgPlo": "Avg PLO Attainment",
62 |   "belowTarget": "Below Target",
63 |   "accredReady": "Accred. Ready"
64 | },
65 | "alerts": {
66 |   "title": "Attainment alerts",
67 |   "allOutcomes": "All outcomes",
68 |   "priorityHigh": "High priority",
69 |   "priorityMedium": "Medium priority",
70 |   "draftCqi": "Draft CQI plan",
71 |   "drillDown": "Drill down",
72 |   "gapBody": "Attainment {{pct}}% · {{gap}} pts below the {{threshold}}% target.",
73 |   "weakest": "Weakest course: {{code}} ({{pct}}%)",
74 |   "affected": "{{count}} students affected ({{percent}}%)",
75 |   "empty": "All PLOs are meeting the target",
76 |   "emptyDetail": "All {{count}} program outcomes are at or above the {{threshold}}% success threshold.",
77 |   "lowest": "Lowest: {{title}} at {{pct}}%"
78 | },
79 | "gap": {
80 |   "title": "Curriculum gap detected",
81 |   "body": "\\Concurrency\\ has no mapped assessment",
82 |   "detail": "PLO4 depends on it, but no course currently assesses it – a coverage hole for accreditation.",
83 |   "impact": "Estimated impact: Medium",
84 |   "cta": "Open matrix"
85 | },
86 | "evidence": {
87 |   "title": "Accreditation evidence",
88 |   "overall": "Overall readiness",
89 |   "cloMapping": "CLO Mapping",
90 |   "samples": "Samples (Student Work)",
91 |   "analysis": "Assessment Analysis",
92 |   "reflection": "Faculty Reflection",
93 |   "cqi": "Continuous Improvement (CQI)",
94 |   "completed": "Completed",
95 |   "inProgress": "In progress",
96 |   "pending": "Pending",
97 |   "cta": "Review draft"
98 | },
99 | "cqi": {
100 |   "title": "Close the loop (CQI)",
101 |   "statusCompleted": "Completed",
102 |   "statusInProgress": "In progress",
103 |   "statusPlanned": "Planned",
104 |   "statusEvaluated": "Evaluated",
105 |   "empty": "No CQI action plans yet.",
106 |   "cta": "View CQI log"
107 | },
108 | "timeline": {
109 |   "title": "Program timeline",
110 |   "statusCompleted": "Completed",
111 |   "statusNow": "Now",
112 |   "statusNext": "Next",
113 |   "statusUpcoming": "Upcoming",
114 |   "empty": "No upcoming events",
115 |   "cta": "View full timeline"
116 | },
117 | },
118 | "rail": {
119 |   "attainmentAlerts": "Attainment alerts",
120 |   "alertPlo": "PLO2 -6% this term",
121 |   "alertClo": "CLO5 below target x2",
122 |   "viewAllAlerts": "View all alerts",
123 |   "curriculumGap": "Curriculum gap",
124 |   "gapBody": "\\Concurrency\\ has no mapped assessment.",
125 |   "openMatrix": "Open matrix",
126 |   "accreditation": "Accreditation",

```

```

127     "evidenceReadiness": "Evidence readiness",
128     "reviewDraft": "Review draft"
129 },
130 "attainment": {
131     "title": "Outcome attainment",
132     "subtitle": "ILO !' PLO !' CLO. Live rollup from student evidence. Click a PLO to see contributing CLOs.",
133     "howItWorks": "How it works",
134     "iloSection": "Institution Learning Outcomes (ILO)",
135     "viewIloDetails": "View ILO details",
136     "ploSection": "Program Learning Outcomes (PLO)",
137     "allTerms": "All terms",
138     "currentTerm": "Current term",
139     "downloadReport": "Download report",
140     "target": "Target",
141     "onTrack": "On track",
142     "watch": "Watch",
143     "belowTarget": "Below target",
144     "contributingClos": "{{count}} contributing CLOs",
145     "vsPrev": "vs {{pct}}%",
146     "vsLastTerm": "vs last term",
147     "ofCohort": "{{pct}}% of cohort",
148     "cloBreakdown": "CLO breakdown",
149     "aiInsight": "AI insight",
150     "sourceAi": "AI-generated",
151     "sourceComputed": "Computed",
152     "insight": "Insight",
153     "insightText": "{{clo}} is the lowest contributing outcome at {{pct}}%",
154     "insightNone": "All contributing outcomes are at or above target.",
155     "empty": "No outcome attainment data yet.",
156     "recommendedAction": "Recommended action",
157     "draftCqiPlan": "Draft CQI plan",
158     "evidenceLinks": "Evidence links",
159     "evAssessment": "Assessment Analysis",
160     "evSamples": "Sample Work ({{count}})",
161     "evFeedback": "Student Feedback",
162     "ilo1Title": "Critical thinking",
163     "ilo2Title": "Technical mastery",
164     "ilo3Title": "Communication",
165     "plo1Title": "Analyze computational problems",
166     "plo1Desc": "Identify, formulate and analyze problems using computational thinking.",
167     "plo1Weakest": "CS301 Data Structures",
168     "plo1Clo1": "Problem decomposition",
169     "plo1Clo2": "Algorithm analysis",
170     "plo1Insight": "Students struggle to break complex problems into smaller parts; performance dips on multi-",
171     "plo1Recommended": "Add problem-decomposition practice before Midterm 2 and more retrieval questions in qu",
172     "plo2Title": "Apply engineering principles",
173     "plo2Desc": "Apply engineering knowledge to design and build solutions.",
174     "plo2Weakest": "CS205 REST APIs",
175     "plo2Clo1": "REST API design",
176     "plo2Clo2": "Data modeling",
177     "plo2Insight": "REST API design lags across two sections; students miss statelessness and error-handling c",
178     "plo2Recommended": "Introduce a guided REST lab and a rubric-aligned API design checkpoint.",
179     "plo3Title": "Design software systems",
180     "plo3Desc": "Design scalable, reliable and efficient software systems.",
181     "plo3Weakest": "CS310 Software Design",
182     "plo3Clo1": "Architecture patterns",
183     "plo3Clo2": "Trade-off analysis",
184     "plo3Insight": "Trade-off analysis is the weakest sub-skill; designs favor familiarity over scalability.",
185     "plo3Recommended": "Add a design-review seminar comparing architecture trade-offs on a shared case study.",
186     "plo4Title": "Build reliable systems",
187     "plo4Desc": "Implement, test and deploy reliable software systems.",
188     "plo4Weakest": "SE310 Software Eng.",
189     "plo4Clo1": "Testing & CI",
190     "plo4Clo2": "Deployment",
191     "plo4Insight": "Attainment is stable at target; testing depth varies by section.",
192     "plo4Recommended": "Standardize a CI and test-coverage baseline across sections to hold the line."
193 },
194 "me": {
195     "roleTitle": "Program Coordinator",
196     "department": "Computer Science",
197     "editProfile": "Edit profile",
198     "viewPublicProfile": "View public profile",
199     "statPrograms": "Programs",
200     "statCourses": "Courses",
201     "statStudents": "Students",
202     "statFaculty": "Faculty",
203     "phone": "+92 300 1234567",
204     "office": "Room 305, CS Building",
205     "officeHours": "Office Hours: Mon-Thu (10am - 2pm)",
206     "aiTitle": "AI Assistance Preferences",
207     "aiSubtitle": "Configure how AI helps you in your daily workflows.",
208     "aiManage": "Manage AI settings",
209     "aiAutonomyLabel": "Autonomy Level",
210     "aiAutonomyValue": "A2 - Draft with Approval",
211     "aiAllow1": "Draft CQI plans",
212     "aiAllow2": "Draft evidence & analysis",
213     "aiAllow3": "Detect curriculum gaps",
214     "aiAllow4": "Suggest improvement actions",
215     "aiDeny1": "Export accreditation pack",
216     "aiDeny2": "Publish changes",
217     "roleSectionTitle": "Role & Permissions",
218     "roleSectionSubtitle": "Your role and what you can do in the system.",
219     "roleName": "Program Coordinator",
220     "roleViewAll": "View all permissions",
221     "perm1": "Review & sign evidence",
222     "perm2": "Approve CQI action plans",
223     "perm3": "View academic reports",
224     "perm4": "Export accreditation pack",
225     "perm5": "Assign tasks to faculty",
226     "programsTitle": "Programs I Manage",
227     "programsSubtitle": "Programs under your coordination.",
228     "programsViewAll": "View all programs",
229     "programsEmpty": "No programs assigned to you yet.",
230     "courses": "Courses",

```



```

231 | "students": "Students",
232 | "facultyTitle": "Connected Faculty",
233 | "facultySubtitle": "Faculty working across your programs.",
234 | "facultyManage": "Manage faculty access",
235 | "facultyMembers": "Faculty members",
236 | "facultyActive": "Active",
237 | "facultyInactive": "Inactive",
238 | "notifTitle": "Notification Preferences",
239 | "notifSubtitle": "Notify me when:",
240 | "notifManage": "Manage notifications",
241 | "notif1": "PLO drops below target",
242 | "notif2": "New curriculum gap",
243 | "notif3": "Evidence ready for review",
244 | "notif4": "Teacher inactivity",
245 | "notif5": "CQI deadline approaching",
246 | "securityTitle": "Security & Access",
247 | "securitySettings": "Security settings",
248 | "changePassword": "Change password",
249 | "twoFactor": "Two-factor authentication",
250 | "on": "On",
251 | "activeSessions": "Active sessions",
252 | "authorizedDevices": "Authorized devices",
253 | "integrationsTitle": "Connected Integrations",
254 | "integrationsManage": "Manage integrations",
255 | "googleCalendar": "Google Calendar",
256 | "outlook": "Microsoft Outlook",
257 | "slack": "Slack",
258 | "connected": "Connected",
259 | "connect": "Connect",
260 | "integrationComingSoon": "Connecting this integration is coming soon – it requires provider setup.",
261 | "academicTitle": "Profile & Academic Information",
262 | "academicEdit": "Edit academic profile",
263 | "academicDepartment": "Department",
264 | "academicDesignation": "Designation",
265 | "academicRank": "Academic Rank",
266 | "academicRankValue": "Assistant Professor",
267 | "academicDegree": "Highest Degree",
268 | "academicDegreeValue": "PhD (Computer Science)",
269 | "academicExperience": "Experience",
270 | "academicExperienceValue": "11 Years",
271 | "notSet": "Not set",
272 | "experienceYears": "{{count}} years",
273 | "academicSaved": "Academic profile updated",
274 | "academicSaveError": "Couldn't save your academic profile. Please try again.",
275 | "notifSaveError": "Couldn't update notification preferences.",
276 | "save": "Save",
277 | "cancel": "Cancel"
278 | },
279 | "plos": {
280 |   "title": "Program Learning Outcomes",
281 |   "addPLO": "Add PLO",
282 |   "editPLO": "Edit PLO",
283 |   "reorder": "Reorder",
284 |   "saveOrder": "Save Order",
285 |   "orderSaved": "PLO order saved",
286 |   "filterByProgram": "Filter by program",
287 |   "allPrograms": "All Programs",
288 |   "dragHint": "Drag items to reorder, then click Save Order.",
289 |   "active": "Active",
290 |   "deletePLO": "Delete PLO",
291 |   "deleteConfirm": "Are you sure you want to delete \"{{title}}\"? This action cannot be undone. If this PLO
292 |   \"deleted\": \"\"{{title}}\" has been deleted"
293 | },
294 | "curriculumMatrix": {
295 |   "title": "Curriculum Matrix",
296 |   "program": "Program",
297 |   "selectProgram": "Select a program",
298 |   "exportCsv": "Export CSV",
299 |   "selectPrompt": "Select a program to view the curriculum matrix.",
300 |   "allTerms": "All terms",
301 |   "currentTerm": "Current term",
302 |   "coverage": "Coverage",
303 |   "legendAssessed": "Assessed",
304 |   "legendIntroduced": "Introduced",
305 |   "legendNotCovered": "Not covered",
306 |   "legendGap": "Coverage gap",
307 |   "gapTitle": "Coverage gap detected",
308 |   "gapBody": "One program outcome is only introduced – no course currently assesses it. This is a coverage h
309 |   "aiRec": "AI recommendation",
310 |   "aiBestCourseLabel": "Best course to introduce it",
311 |   "aiBestCourseValue": "SE310 – Software Engineering",
312 |   "aiAssessmentLabel": "Recommended assessment",
313 |   "aiAssessmentValue": "Concurrency lab with a mapped rubric",
314 |   "aiActionLabel": "Action plan",
315 |   "aiActionValue": "Add the lab in week 6, map it to the outcome, and collect two evidence samples before th
316 |   "draftAssessment": "Draft assessment",
317 |   "notifyTeacher": "Notify teacher"
318 | },
319 | "accreditation": {
320 |   "title": "Accreditation Evidence",
321 |   "viewCqi": "View CQI action plans",
322 |   "readiness": "Accreditation Readiness",
323 |   "overallReadiness": "Overall readiness",
324 |   "complete": "Complete",
325 |   "inProgress": "In progress",
326 |   "blocked": "Blocked",
327 |   "notStarted": "Not started",
328 |   "courseEvidence": "Course evidence",
329 |   "statusSigned": "Signed",
330 |   "statusDraft": "Draft",
331 |   "statusBlocked": "Blocked",
332 |   "statusNotStarted": "Not started",
333 |   "statusDocumented": "Documented",
334 |   "statusPartial": "Partial",

```

```

335 |     "c1Name": "Data Structures",
336 |     "c2Name": "Web Development",
337 |     "c3Name": "Intro to AI",
338 |     "c4Name": "Software Engineering",
339 |     "c5Name": "Capstone Project",
340 |     "pack": "Accreditation Pack",
341 |     "pack1": "Syllabus",
342 |     "pack2": "CLO-PLO mapping",
343 |     "pack3": "Assessment instruments",
344 |     "pack4": "Sample student work",
345 |     "pack5": "Attainment analysis",
346 |     "pack6": "Faculty reflection",
347 |     "pack7": "CQI recommendations",
348 |     "packComplete": "Complete",
349 |     "packInProgress": "In progress",
350 |     "packOutstanding": "Outstanding",
351 |     "packCloMapping": "CLO-PLO mapping",
352 |     "packSamples": "Student work samples",
353 |     "packAnalysis": "Assessment analysis",
354 |     "packCqi": "Continuous improvement (CQI)",
355 |     "readinessPending": "Accreditation readiness will appear once evidence is processed.",
356 |     "evidenceEmpty": "No course evidence yet.",
357 |     "packEmpty": "Accreditation pack items will appear here.",
358 |     "workflow": "Approval Workflow",
359 |     "wf1": "Coordinator",
360 |     "wf2": "HOD",
361 |     "wf3": "QA Office",
362 |     "wf4": "Accreditation Office",
363 |     "wfDone": "Approved",
364 |     "wfCurrent": "In review",
365 |     "wfPending": "Pending",
366 |     "generateTitle": "Generate Course File",
367 |     "course": "Course",
368 |     "semester": "Semester",
369 |     "selectCourse": "Select a course",
370 |     "selectSemester": "Select a semester",
371 |     "generate": "Generate Course File",
372 |     "generating": "Generating...",
373 |     "ready": "Course File Ready",
374 |     "downloadPdf": "Download PDF",
375 |     "generated": "Generated",
376 |     "noCourses": "No courses available",
377 |     "noSemesters": "No semesters available",
378 |     "selectCourseError": "Please select a course",
379 |     "selectSemesterError": "Please select a semester",
380 |     "generateSuccess": "Course file generated successfully",
381 |     "generateError": "Course file generation failed"
382 | },
383 | "bilingual": {
384 |   "arabicTitle": "Arabic Title",
385 |   "arabicTitlePlaceholder": "Enter title in Arabic (optional)"
386 | },
387 | "obe": {
388 |   "ILO": "Institution Learning Outcomes",
389 |   "PLO": "Program Learning Outcomes",
390 |   "CLO": "Course Learning Outcomes",
391 |   "attainment": "Attainment",
392 |   "outcomeMapping": "Outcome Mapping",
393 |   "CQI": "Continuous Quality Improvement",
394 |   "courseFile": "Course File"
395 | }
396 | }
397 |

```

FILE: src/locales/en/gamification.json

TYPE: .json | LINES: 1-88 | SHA256: 178ba1be1885834090b3cc51d4c228bc0c497ed1cae9cb7d3ef775c12755786c

```

1 | {
2 |   "xp": {
3 |     "title": "Experience Points",
4 |     "earned": "+{{amount}} XP",
5 |     "rewardEarned": "Reward earned",
6 |     "total": "Total XP",
7 |     "history": "XP History",
8 |     "sources": {
9 |       "login": "Daily Login",
10 |       "submission": "Assignment Submission",
11 |       "grade": "Grade Released",
12 |       "journal": "Journal Entry",
13 |       "streakMilestone": "Streak Milestone",
14 |       "perfectDay": "Perfect Day",
15 |       "firstAttempt": "First Attempt Bonus",
16 |       "perfectRubric": "Perfect Rubric Score",
17 |       "badgeEarned": "Badge Earned"
18 |     }
19 |   },
20 |   "streaks": {
21 |     "title": "Login Streak",
22 |     "days": "{{count}} day streak",
23 |     "atRisk": "Your streak is at risk!",
24 |     "lost": "Streak lost",
25 |     "freeze": "Streak Freeze",
26 |     "freezeAvailable": "{{count}} freeze(s) available",
27 |     "freezeCost": "Cost: 200 XP",
28 |     "milestone": "0=Y% {{count}}-day streak milestone!"
29 |   },
30 |   "badges": {
31 |     "title": "Badges",
32 |     "earned": "Badge Earned!",
33 |     "collection": "Badge Collection",
34 |     "mystery": "Mystery Badge",
35 |     "mysteryHint": "Complete hidden challenges to unlock",
36 |     "locked": "Locked"
37 |   },

```

```

38 | "mystery": {
39 |   "overlayLabel": "Mystery reward"
40 | },
41 | "leaderboard": {
42 |   "title": "Leaderboard",
43 |   "rank": "Rank",
44 |   "player": "Student",
45 |   "xpTotal": "Total XP",
46 |   "level": "Level",
47 |   "gold": "Gold",
48 |   "silver": "Silver",
49 |   "bronze": "Bronze"
50 | },
51 | "transactions": {
52 |   "title": "Transaction History",
53 |   "filters": {
54 |     "all": "All",
55 |     "earnings": "Earnings",
56 |     "spending": "Spending"
57 |   },
58 |   "empty": "No transactions found.",
59 |   "showing": "Showing {{from}}-{{to}} of {{total}}",
60 |   "previous": "Previous",
61 |   "next": "Next",
62 |   "unit": "XP",
63 |   "error": {
64 |     "title": "Couldn't load your transactions",
65 |     "body": "We couldn't load your transaction history right now. Please try again.",
66 |     "toast": "Failed to load transaction history"
67 |   }
68 | },
69 | "habits": {
70 |   "title": "Daily Habits",
71 |   "login": "Login",
72 |   "submit": "Submit",
73 |   "journal": "Journal",
74 |   "read": "Read",
75 |   "perfectDay": "Perfect Day! All habits completed 0<β%",
76 |   "almostThere": "Almost there! Complete {{habit}} for a Perfect Day."
77 | },
78 | "level": {
79 |   "title": "Level",
80 |   "current": "Level {{level}}",
81 |   "levelUp": "Level Up! 0<β%",
82 |   "nextLevel": "{{xp}} XP to next level",
83 |   "levelUpLabel": "Level Up",
84 |   "overlayLabel": "Level up to level {{level}}",
85 |   "dismiss": "Tap anywhere to dismiss"
86 | }
87 | }
88 |

```

FILE: [src/locales/en/student.json](#)

TYPE: .json | LINES: 1-897 | SHA256: 31e5ff92b4db925a587ebb27a85ccbb7fa1de715a43c923f333551b6ad8d1971

```

1 | {
2 |   "dashboard": {
3 |     "title": "Student Dashboard",
4 |     "welcome": "Good morning, {{name}} 0=ÜK",
5 |     "subtitle": "Here's your learning journey today",
6 |     "upcomingDeadlines": "Upcoming Deadlines",
7 |     "learningPath": "Learning Path",
8 |     "dailyHabits": "Daily Habits",
9 |     "greeting": {
10 |       "morning": "Good morning",
11 |       "afternoon": "Good afternoon",
12 |       "evening": "Good evening"
13 |     },
14 |     "momentum": "Keep up the momentum – every step counts.",
15 |     "xp": "XP",
16 |     "level": "Lv {{level}}",
17 |     "levelLabel": "Level",
18 |     "courses": "Courses",
19 |     "completed": "Completed",
20 |     "avgAttainment": "Avg Attainment",
21 |     "streak": "Streak",
22 |     "noDeadlines": "No upcoming deadlines. Enjoy the break.",
23 |     "yourProgress": "Your Progress",
24 |     "totalXP": "Total XP",
25 |     "xpAvailable": "Available XP",
26 |     "currentLevel": "Current Level",
27 |     "loginStreak": "Login Streak",
28 |     "daysStreak": "0=Y% {{count}} days",
29 |     "assignmentsDone": "Assignments Done",
30 |     "viewXPHistory": "View XP History",
31 |     "completeOnboarding": "Complete your onboarding",
32 |     "completeOnboardingDesc": "Finish your profile to unlock personalized recommendations and earn XP.",
33 |     "startNow": "Start Now",
34 |     "completeAssessment": "Complete your assessment",
35 |     "completeAssessmentDesc": "You skipped some sections during onboarding. Complete them to get full personal",
36 |     "completeNow": "Complete Now",
37 |     "recentAnnouncements": "Recent Announcements",
38 |     "closNeedingAttention": "CLOs Needing Attention",
39 |     "myTeam": "My Team",
40 |     "challenges": "Challenges",
41 |     "target": "Target",
42 |     "team": "Team",
43 |     "courseWide": "Course-Wide",
44 |     "individual": "Individual",
45 |     "viewAllChallenges": "View All Challenges ({{count}})",
46 |     "attendance": "Attendance",
47 |     "leagueTier": "League Tier",
48 |     "primaryCta": {
49 |       "region": "Recommended next action",

```

```

50 |     "heading": "Your next step",
51 |     "completeProfile": {
52 |       "label": "Complete your onboarding",
53 |       "description": "Finish your profile to unlock personalized recommendations and earn XP.",
54 |       "cta": "Start Now"
55 |     },
56 |     "finishProfile": {
57 |       "label": "Complete your assessment",
58 |       "description": "You skipped some sections during onboarding. Complete them to get full personalization",
59 |       "cta": "Complete Now"
60 |     },
61 |     "submitAssignment": {
62 |       "label": "Submit your next assignment",
63 |       "description": "{{title}} is due soon – submit it to stay on track.",
64 |       "cta": "Open Assignment"
65 |     },
66 |     "continueCourse": {
67 |       "label": "Continue your course",
68 |       "description": "Pick up where you left off and keep your momentum going.",
69 |       "cta": "View Courses"
70 |     },
71 |     "reviewFeedback": {
72 |       "label": "Review your feedback",
73 |       "description": "See your latest grades and feedback to learn from your work.",
74 |       "cta": "View Progress"
75 |     }
76 |   }
77 | },
78 | "team": {
79 |   "title": "My Team",
80 |   "unassignedTitle": "You're not on a team yet",
81 |   "howItWorksDescription": "Teams let you learn alongside classmates – you earn XP together, climb the team",
82 |   "joinOrCreate": "Join or create a team",
83 |   "teacherAssignNote": "Your teacher may also assign you to a team for your course."
84 | },
85 | "courses": {
86 |   "title": "My Courses",
87 |   "subtitle": "View your enrolled courses, progress, and assignments.",
88 |   "taughtBy": "Taught by",
89 |   "progress": "Progress",
90 |   "progressLabel": "Course progress: {{percent}}%",
91 |   "nextUp": "Next up",
92 |   "due": "Due {{date}}",
93 |   "noDueDate": "No due date",
94 |   "noUpcomingWork": "No upcoming work",
95 |   "attainment": "Attainment",
96 |   "assignments": "Assignments",
97 |   "modules": "Modules",
98 |   "continueWhere": "Continue where you left off",
99 |   "dueShort": "Due {{date}}",
100 |   "stuck": "Stuck on this course?",
101 |   "tutorPrompt": "Ask your AI Tutor for a guided explanation.",
102 |   "ask": "Ask",
103 |   "detail": {
104 |     "title": "Course details",
105 |     "backToCourses": "Back to courses",
106 |     "loadErrorTitle": "Course details unavailable",
107 |     "loadError": "We couldn't load one or more course details. Please try again.",
108 |     "courseNotFoundTitle": "Course unavailable",
109 |     "courseNotFound": "This course could not be loaded.",
110 |     "progressLabel": "Progress",
111 |     "attainmentValue": "{{count}}% attainment",
112 |     "noAttainment": "No attainment data",
113 |     "stats": {
114 |       "modules": "Modules",
115 |       "materials": "Materials",
116 |       "assignments": "Assignments",
117 |       "attainment": "Attainment"
118 |     },
119 |     "continueTitle": "Continue where you left off",
120 |     "openAssignment": "Open assignment",
121 |     "noOpenWork": "Nothing is due soon.",
122 |     "announcements": "Announcements",
123 |     "announcementsDescription": "Recent updates from the course team.",
124 |     "pinned": "Pinned",
125 |     "noAnnouncements": "There are no announcements for this course yet.",
126 |     "modules": "Modules",
127 |     "modulesDescription": "Open a module to browse the published materials inside it.",
128 |     "noPublishedModules": "No published modules are available yet.",
129 |     "noMaterials": "No published materials are available yet.",
130 |     "locked": "Locked",
131 |     "items": "{{count}} items",
132 |     "selectMaterialTitle": "Select a material to preview it here",
133 |     "selectMaterialHint": "Browse a module on the left, then open a material to read or view it.",
134 |     "readTimer": "Reading timer",
135 |     "readCompleted": "Read habit complete",
136 |     "reading": "{{count}}s reading",
137 |     "openLink": "Open resource",
138 |     "openFile": "Download or view file",
139 |     "noTextBody": "No text content is attached yet."
140 |   }
141 | },
142 | "assignments": {
143 |   "title": "Assignments",
144 |   "submitAssignment": "Submit Assignment",
145 |   "uploadFile": "Upload File",
146 |   "submissionConfirmed": "Submission confirmed!",
147 |   "lateSubmission": "This is a late submission.",
148 |   "deadlinePassed": "The submission deadline has passed.",
149 |   "dueIn": "Due in {{time}}",
150 |   "list": {
151 |     "title": "Assignments",
152 |     "subtitle": "Track upcoming work, late submissions, and what is already done.",
153 |     "searchPlaceholder": "Search assignments...",

```

```

154 |         "allCourses": "All courses",
155 |         "courseFallback": "Course",
156 |         "loadErrorTitle": "Assignments unavailable",
157 |         "loadError": "We couldn't load your assignments. Please try again.",
158 |         "status": {
159 |             "pending": "Pending",
160 |             "submitted": "Submitted",
161 |             "late": "Late",
162 |             "overdue": "Overdue"
163 |         },
164 |         "marks": "{{count}} marks",
165 |         "dueIn": "{{time}}"
166 |     },
167 |     "detail": {
168 |         "backToAssignments": "Back to assignments",
169 |         "courseFallback": "Course",
170 |         "loadErrorTitle": "Assignment unavailable",
171 |         "loadError": "We couldn't load this assignment. Please try again.",
172 |         "notFoundTitle": "Assignment not found",
173 |         "notFound": "This assignment is not available anymore.",
174 |         "loading": "Loading",
175 |         "facts": {
176 |             "due": "Due",
177 |             "marks": "Marks",
178 |             "reward": "Reward",
179 |             "window": "Late window"
180 |         },
181 |         "linkedClos": "{{count}} linked CLOs",
182 |         "xpBonus": "{{multiplier}}x XP bonus",
183 |         "submitTitle": "Submit your work",
184 |         "submitDescription": "Upload your file, then submit it before the deadline window closes.",
185 |         "tapToUpload": "Tap to upload your file",
186 |         "draftHint": "Previously selected: {{name}}",
187 |         "fileValidationFailed": "File validation failed.",
188 |         "retryingUpload": "Upload failed – retrying ({{count}}/3)...",
189 |         "submitting": "Submitting...",
190 |         "clearFile": "Clear file",
191 |         "lateWindow": "You can still submit during the late window.",
192 |         "openWindow": "You can submit while the deadline window is open.",
193 |         "tutorTitle": "Need help before submitting?",
194 |         "tutorHint": "Ask the AI Tutor about the assignment topic.",
195 |         "ask": "Ask",
196 |         "statusTitle": "Your submission",
197 |         "statusDescription": "Track the latest submission state for this assignment.",
198 |         "submitted": "Submitted",
199 |         "late": "Late",
200 |         "viewSubmission": "View submission",
201 |         "signing": "Preparing file link...",
202 |         "noSubmission": "You have not submitted this assignment yet.",
203 |         "dueLabel": "Due",
204 |         "windowLabel": "Late window",
205 |         "windowValue": "{{count}} hours",
206 |         "none": "None",
207 |         "bonusTitle": "Performance context",
208 |         "bonusDescription": "The system uses linked CLO difficulty to tune rewards.",
209 |         "bonusValue": "{{multiplier}}x XP bonus",
210 |         "noBonus": "No difficulty bonus"
211 |     }
212 | },
213 | "progress": {
214 |     "viewCLOProgress": "View CLO progress",
215 |     "title": "My Progress",
216 |     "cloProgress": "CLO Progress",
217 |     "xpHistory": "XP History",
218 |     "attainment": "Attainment",
219 |     "evidence": "Evidence",
220 |     "noAssessments": "No assessments yet"
221 | },
222 | "learningPath": {
223 |     "title": "Learning Path",
224 |     "subtitle": "Follow the next available steps in your course journey.",
225 |     "coursePicker": "Choose a course",
226 |     "journey": "Your course journey",
227 |     "views": {
228 |         "journey": "Journey",
229 |         "tree": "Knowledge Tree"
230 |     },
231 |     "bloomJourney": "Bloom levels · your journey",
232 |     "youAreHere": "You are here",
233 |     "levelDetail": "Level detail",
234 |     "mastery": "Mastery",
235 |     "tasks": "Tasks",
236 |     "milestones": "Milestones",
237 |     "coachTip": "AI Coach Tip",
238 |     "coachContinue": "Continue “{{title}}” to strengthen this level and open the next milestone.",
239 |     "coachComplete": "This level is complete. Your next stage is ready when its prerequisite is met.",
240 |     "coachLocked": "Complete the earlier Bloom level at the required mastery to unlock this stage.",
241 |     "unlockNext": "Reach {{percent}}% mastery to unlock the next Bloom level",
242 |     "unlockRequirement": "Reach {{percent}}% on {{title}} to unlock",
243 |     "recentActivity": "Recent activity on this path",
244 |     "noRecentActivity": "Complete or submit a task and it will appear here.",
245 |     "noStageAssignments": "No course tasks are mapped to this Bloom level yet.",
246 |     "stageLocked": "This stage unlocks as your mastery grows.",
247 |     "emptyTitle": "Your learning path is being prepared",
248 |     "emptyDescription": "This course does not have mapped assignments yet. Your instructor's next published ta
249 |     "status": {
250 |         "completed": "Completed",
251 |         "submitted": "Submitted",
252 |         "available": "Available",
253 |         "locked": "Locked"
254 |     },
255 |     "actions": {
256 |         "continue": "Continue",
257 |         "review": "Review",

```

```

258     "locked": "Locked"
259   },
260   "stages": {
261     "baseCamp": "Base camp",
262     "campOne": "Camp I",
263     "campTwo": "Camp II . climbing now",
264     "campThree": "Camp III",
265     "campFour": "Camp IV",
266     "summit": "Summit",
267     "remember": {
268       "title": "REMEMBER",
269       "subtitle": "Recall the basic ideas"
270     },
271     "understand": {
272       "title": "UNDERSTAND",
273       "subtitle": "Explain the concepts"
274     },
275     "apply": {
276       "title": "APPLY",
277       "subtitle": "Use knowledge in real situations"
278     },
279     "analyze": {
280       "title": "ANALYZE",
281       "subtitle": "Connect ideas and examine patterns"
282     },
283     "evaluate": {
284       "title": "EVALUATE",
285       "subtitle": "Defend decisions with evidence"
286     },
287     "create": {
288       "title": "CREATE",
289       "subtitle": "Build something original"
290     }
291   },
292   "tree": {
293     "title": "Your Knowledge Growth",
294     "subtitle": "See how your understanding is growing",
295     "overallMastery": "Overall Mastery",
296     "keepGrowing": "Keep growing!",
297     "strong": "Strong",
298     "good": "Good",
299     "developing": "Developing",
300     "needsFocus": "Needs Focus",
301     "tip": "Push your current Bloom level past 70% to unlock the next branch. The tree grows as you master e
302     "strength": "Your completed foundations are helping you climb into the next level of thinking."
303   }
304 },
305 "heatmap": {
306   "plainSummary": {
307     "title": "How your habits are going",
308     "empty": "You haven't logged any habits yet. Pick one small habit to start today!",
309     "completion": "You've kept up {{rate}}% of your daily habits.",
310     "bestHabit": "Your strongest habit is {{habit}}.",
311     "streak": "You're on a {{count}}-day streak – keep it going!",
312     "encourage": "Every small step counts. Keep it up!"
313   },
314   "habitLabels": {
315     "login": "logging in",
316     "submit": "submitting work",
317     "journal": "journaling",
318     "read": "reading",
319     "meditation": "meditation",
320     "hydration": "hydration",
321     "exercise": "exercise",
322     "sleep": "sleep"
323   }
324 },
325 "journal": {
326   "title": "Reflection Journal",
327   "newEntry": "New Entry",
328   "wordCount": "{{count}} words",
329   "minWords": "Minimum 50 words required",
330   "saved": "Journal entry saved.",
331   "today": {
332     "title": "Today's Reflection",
333     "description": "Capture what you learned, what felt challenging, or a small win worth remembering.",
334     "cta": "Write Reflection"
335   },
336   "journey": {
337     "title": "Your Journaling Journey",
338     "thisWeek": "This week",
339     "entriesThisWeek": "Entries this week",
340     "dayStreak": "Day streak",
341     "substantive": "Full reflections",
342     "totalEntries": "Total entries",
343     "weeklyStreak": "This week's reflection streak",
344     "daysOfWeek": "{{count}} of 7 days"
345   },
346   "dailyPrompt": {
347     "label": "Today's prompt:"
348   },
349   "pastEntries": "Past Entries",
350   "entryCount": "{{count}} entries",
351   "empty": {
352     "title": "No journal entries yet",
353     "description": "Start your learning journal – reflect on a class or concept and earn XP."
354   },
355   "prompts": {
356     "title": "Reflection prompts",
357     "hint": "Pick a prompt to get started, or just write freely below.",
358     "guided": "Guided reflection",
359     "use": "Use this prompt",
360     "learned": "What did I learn today?",
361     "confused": "What confused me?",

```

```

362 |         "proud": "What am I proud of?"
363 |     }
364 | },
365 | "leaderboard": {
366 |     "title": "Leaderboard",
367 |     "yourRank": "Your Rank",
368 |     "anonymous": "Anonymous Mode",
369 |     "anonymousHint": "Your name is hidden from other students",
370 |     "rankings": {
371 |         "title": "Rankings",
372 |         "loadMore": "Load more"
373 |     },
374 |     "locked": {
375 |         "title": "Leaderboard unlocks when more students join",
376 |         "description": "Once more students join your cohort, rankings and medals will appear here. Keep earning
377 |     }
378 | },
379 | "portfolio": {
380 |     "title": "My Portfolio",
381 |     "publicProfile": "Public Profile",
382 |     "togglePublicAria": "Toggle public portfolio",
383 |     "copyLinkAria": "Copy shareable link",
384 |     "copyLink": "Copy Link",
385 |     "copied": "Copied",
386 |     "permissionRequired": "Public sharing requires school permission. Your portfolio stays private until your
387 |     "toast": {
388 |         "madePublic": "Portfolio is now public",
389 |         "madePrivate": "Portfolio set to private",
390 |         "linkCopied": "Link copied to clipboard",
391 |         "permissionDenied": "Public sharing isn't enabled for your account yet. Ask your school to grant permis
392 |     },
393 |     "kpi": {
394 |         "totalXP": "Total XP",
395 |         "level": "Level",
396 |         "closMastered": "CLOs Mastered",
397 |         "badgesEarned": "Badges Earned"
398 |     },
399 |     "sections": {
400 |         "cloMastery": "CLO Mastery",
401 |         "badgeCollection": "Badge Collection",
402 |         "journalEntries": "Journal Entries",
403 |         "xpTimeline": "XP Timeline",
404 |         "attainmentGrowth": "Attainment Growth"
405 |     },
406 |     "friendly": {
407 |         "skillsTitle": "Skills mastered",
408 |         "strengths": "Strengths",
409 |         "areasImproving": "Areas improving",
410 |         "strengthsHint": "What you're great at",
411 |         "areasImprovingHint": "What you're working on next"
412 |     },
413 |     "noJournals": "No journal entries yet.",
414 |     "general": "General",
415 |     "chart": {
416 |         "cumulativeXP": "Cumulative XP",
417 |         "xpValue": "{{value}} XP",
418 |         "avgAttainment": "Avg Attainment"
419 |     },
420 |     "attainmentLevels": {
421 |         "Excellent": "Excellent",
422 |         "Satisfactory": "Satisfactory",
423 |         "Developing": "Developing",
424 |         "Not_Yet": "Not Yet"
425 |     }
426 | },
427 | "onboarding": {
428 |     "shell": {
429 |         "stepOf": "Step {{current}} of {{total}}",
430 |         "progressLabel": "Onboarding progress",
431 |         "back": "Back",
432 |         "skip": "Skip for Now",
433 |         "next": "Next",
434 |         "loading": "Loading your onboarding"
435 |     },
436 |     "welcome": {
437 |         "fallbackName": "there",
438 |         "greeting": "Hey {{name}}! Ø=ÜK",
439 |         "day1Description": "Let's set up your learning world – it takes under 3 minutes.",
440 |         "fullDescription": "Let's complete your learning profile and unlock your most personalized experience.",
441 |         "benefits": {
442 |             "xpTitle": "Earn up to {{amount}} XP",
443 |             "xpDescription": "Rewards start from question one",
444 |             "tapTitle": "All taps, zero typing",
445 |             "tapDay1Description": "Six quick questions – fast, fun, and easy",
446 |             "tapFullDescription": "Simple choices across your full learning profile",
447 |             "privateTitle": "Private to you",
448 |             "privateDescription": "Your profile and learning data stay protected"
449 |         },
450 |         "cta": "Let's Go"
451 |     },
452 |     "assessmentIntro": {
453 |         "begin": "Begin",
454 |         "personality": {
455 |             "title": "Discover How You Learn Best",
456 |             "description": "A few quick questions reveal how you work and study best.",
457 |             "estimatedTime": "About 1 minute",
458 |             "benefit1": "Personalized study recommendations tailored to you",
459 |             "benefit2": "AI Tutor responses customized to how you learn",
460 |             "benefit3": "Earn bonus XP for completing your profile"
461 |         },
462 |         "learning_style": {
463 |             "title": "Find Your Learning Style",
464 |             "description": "Explore the ways you take in and remember new ideas.",
465 |             "estimatedTime": "About 3 minutes",

```

```

466     "benefit1": "Study tips matched to your preferences",
467     "benefit2": "AI Tutor explanations in the format that works for you",
468     "benefit3": "Earn bonus XP for completing this assessment"
469 },
470 "self_efficacy": {
471     "title": "Academic Confidence Check",
472     "description": "Tell us how confident you feel so we can support you better.",
473     "estimatedTime": "About 1 minute",
474     "benefit1": "Encouragement and goals set at the right level for you",
475     "benefit2": "AI Tutor support focused where you want to grow",
476     "benefit3": "Earn bonus XP for completing this check"
477 },
478 "study_strategy": {
479     "title": "Sharpen Your Study Habits",
480     "description": "Share how you study today so we can suggest what works.",
481     "estimatedTime": "About 2 minutes",
482     "benefit1": "Personalized study-strategy recommendations",
483     "benefit2": "AI Tutor coaching tuned to your habits",
484     "benefit3": "Earn bonus XP for completing this assessment"
485 }
486 },
487 "microAssessment": {
488     "title": "Quick {{type}} Check",
489     "types": {
490         "personality": "Personality",
491         "self_efficacy": "Self-Efficacy",
492         "study_strategy": "Study Strategy",
493         "learning_style": "Learning Style",
494         "baseline_prompt": "Baseline Test"
495     },
496     "estimatedMinutes": "~{{minutes}} min",
497     "description_one": "{{count}} quick question to refine your profile.",
498     "description_other": "{{count}} quick questions to refine your profile.",
499     "completeNow": "Complete Now",
500     "remindLater": "Remind Me Later",
501     "dismiss": "Dismiss micro-assessment",
502     "lastChance": "Last chance – this will be skipped if dismissed again.",
503     "completed": "Nice! +{{amount}} XP – profile updated.",
504     "completeError": "Could not complete the check. Please try again.",
505     "remindedLater": "No problem – we'll remind you later.",
506     "dismissError": "Could not update the check. Please try again."
507 },
508 "selfEfficacy": {
509     "title": "Academic Confidence Check",
510     "instructions": "Rate how confident you feel about each statement.",
511     "questionProgress": "Question {{current}} of {{total}}",
512     "previous": "Previous",
513     "next": "Next",
514     "complete": "Complete",
515     "saving": "Saving..."
516 },
517 "personality": {
518     "title": "Personality Assessment",
519     "dimensionProgress": "{{dimension}} – Question {{current}} of {{total}}",
520     "scaleLabel": "Likert scale",
521     "previous": "Previous",
522     "next": "Next",
523     "complete": "Complete",
524     "saving": "Saving...",
525     "noQuestions": "No personality questions available. Please contact your administrator.",
526     "dimensions": {
527         "openness": "Openness",
528         "conscientiousness": "Conscientiousness",
529         "extraversion": "Extraversion",
530         "agreeableness": "Agreeableness",
531         "neuroticism": "Neuroticism"
532     },
533     "likert": {
534         "stronglyDisagree": "Strongly Disagree",
535         "disagree": "Disagree",
536         "neutral": "Neutral",
537         "agree": "Agree",
538         "stronglyAgree": "Strongly Agree"
539     }
540 },
541 "learningStyle": {
542     "title": "Learning Style Preferences",
543     "instructions": "Choose the option that best fits you.",
544     "questionProgress": "Question {{current}} of {{total}}",
545     "scaleLabel": "VARK options",
546     "previous": "Previous",
547     "next": "Next",
548     "complete": "Complete",
549     "saving": "Saving...",
550     "noQuestions": "No learning style questions available. Please contact your administrator.",
551     "disclaimer": "Learning style preferences are provided as a self-awareness exercise. Research does not s",
552     "day1": {
553         "title": "Learning Style Assessment",
554         "body": "This assessment will be delivered as short daily micro-assessments over your first two weeks.",
555         "continue": "Continue"
556     }
557 },
558 "studyStrategy": {
559     "title": "Study Strategy Inventory",
560     "instructions": "Rate how often you use each study strategy.",
561     "dimensionProgress": "{{dimension}} – Question {{current}} of {{total}}",
562     "scaleLabel": "Study strategy scale",
563     "previous": "Previous",
564     "next": "Next",
565     "complete": "Complete",
566     "saving": "Saving...",
567     "noQuestions": "No study strategy questions available. Please contact your administrator.",
568     "likert": {
569         "never": "Never",

```



```

570         "rarely": "Rarely",
571         "sometimes": "Sometimes",
572         "often": "Often",
573         "always": "Always"
574     },
575     "dimensions": {
576         "time_management": "Time Management",
577         "elaboration": "Elaboration",
578         "self_testing": "Self-Testing",
579         "help_seeking": "Help-Seeking"
580     },
581     "day1": {
582         "title": "Study Strategy Inventory",
583         "body": "This assessment will be delivered as short daily micro-assessments during your first two week",
584         "continue": "Continue"
585     },
586 },
587 "fallback": {
588     "noQuestionsTitle": "No confidence check needed right now",
589     "noQuestionsBody": "There are no confidence questions for you at the moment. You can continue with the r",
590     "systemIssueTitle": "We couldn't load this step",
591     "systemIssueBody": "Something went wrong loading these questions. You can keep going and we'll try again",
592     "continue": "Continue"
593 },
594 },
595 "planner": {
596     "actions": {
597         "addTask": "Add task",
598         "startSession": "Start session"
599     },
600     "suggestion": {
601         "label": "Suggested study session",
602         "withCourse": "Study session: {{course}}",
603         "duration": "{{minutes}} min focus block",
604         "plan": "Plan session",
605         "ariaPlan": "Plan a {{minutes}} minute study session"
606     },
607     "goals": {
608         "exampleHeading": "Goal ideas to get started",
609         "exampleHint": "Set a goal below to track your week.",
610         "setGoals": "Set goals",
611         "types": {
612             "study_hours": "Study Hours",
613             "sessions_completed": "Sessions",
614             "tasks_completed": "Tasks"
615         },
616         "target": {
617             "study_hours": "{{count}} hours",
618             "sessions_completed": "{{count}} sessions",
619             "tasks_completed": "{{count}} tasks"
620         }
621     }
622 },
623 "recoveryPath": {
624     "title": "Recovery Pathway",
625     "backToDashboard": "Back to Dashboard",
626     "empty": "No active recovery pathway was found for this outcome.",
627     "unknownOutcome": "Learning outcome",
628     "ready": "Ready to Retry",
629     "inProgress": "In Progress",
630     "description": "Complete the steps below to unlock your quiz retry for",
631     "optional": "Optional",
632     "openTutor": "Open AI Tutor",
633     "startPractice": "Start Practice",
634     "browseGroups": "Browse Study Groups",
635     "markComplete": "Mark Complete",
636     "retry": "Retry Quiz",
637     "retryAria": "Retry quiz",
638     "completeToUnlock": "Complete Steps to Unlock Retry",
639     "lockedAria": "Complete required steps to unlock retry",
640     "steps": {
641         "tutor": {
642             "title": "AI Tutor Session",
643             "description": "Review foundational concepts for \"{{title}}\" with the AI Tutor."
644         },
645         "practice": {
646             "title": "Practice Questions",
647             "description": "Complete practice questions at a lower difficulty level to rebuild understanding."
648         },
649         "peer": {
650             "title": "Peer Study Group",
651             "description": "Join a peer study group working on the same topic.",
652             "unavailable": "No active study groups are available for this topic."
653         }
654     },
655     "toast": {
656         "tutorComplete": "AI Tutor session marked as complete",
657         "practiceComplete": "Practice questions marked as complete",
658         "updateFailed": "Failed to update step"
659     }
660 },
661 "quiz": {
662     "loading": "Preparing your adaptive quiz...",
663     "unableToLoad": "Unable to load quiz. Please go back and try again.",
664     "questionProgress": "Question {{number}} of {{total}}",
665     "sessionProgress": "Quiz session progress",
666     "exit": "Exit quiz",
667     "loadingButton": "Loading...",
668     "submitAnswer": "Submit Answer",
669     "nextQuestion": "Next Question",
670     "finishQuiz": "Finish Quiz",
671     "recovery": {
672         "title": "Recovery Required",
673         "body": "You have an active mastery recovery pathway for a CLO linked to this quiz. Complete the recover

```

```

674 |     "cta": "Go to Recovery Pathway"
675 | },
676 |     "toast": {
677 |         "startFailed": "Failed to start quiz. Please try again.",
678 |         "submitFailed": "Failed to submit quiz. Please try again.",
679 |         "nextFailed": "Failed to load next question. Please try again.",
680 |         "selectAnswer": "Please select an answer before submitting.",
681 |         "timeUp": "Time is up! Submitting your quiz..."
682 |     },
683 |     "feedback": {
684 |         "correctTitle": "Correct!",
685 |         "correctBody": "Great job – check the post-quiz review for a detailed explanation.",
686 |         "incorrectTitle": "Incorrect",
687 |         "correctAnswerRevealPrefix": "The correct answer is",
688 |         "reviewLater": "Review the correct answer and explanation after the quiz."
689 |     },
690 |     "review": {
691 |         "title": "Quiz Review",
692 |         "loading": "Loading quiz review...",
693 |         "loadFailed": "Failed to load quiz review. Please try again.",
694 |         "backToDashboard": "Back to Dashboard",
695 |         "overallScore": "Overall Score:",
696 |         "perCloBreakdown": "Per-CLO Score Breakdown",
697 |         "bloomsProgression": "Bloom's Progression",
698 |         "questionLabel": "Question {{number}}",
699 |         "correct": "Correct",
700 |         "incorrect": "Incorrect",
701 |         "verifiedExplanation": "Verified Explanation",
702 |         "aiExplanation": "AI Explanation",
703 |         "getHelp": "Get Help with this topic",
704 |         "bloomLevel": "Level {{level}}"
705 |     }
706 | },
707 |     "createTeam": {
708 |         "back": "Go back",
709 |         "title": "Create Team",
710 |         "noCoursesAvailable": "No courses with student-formed teams available.",
711 |         "courseLabel": "Course",
712 |         "selectCourse": "Select a course",
713 |         "teamNameLabel": "Team Name",
714 |         "teamNamePlaceholder": "e.g. Code Warriors",
715 |         "inviteMembers": "Invite Members ({{current}}/6 including you)",
716 |         "noAvailableStudents": "No available students in this course.",
717 |         "selectAtLeastOne": "Select at least 1 member (team needs 2-6 total).",
718 |         "submit": "Create Team",
719 |         "validation": {
720 |             "nameMin": "Team name must be at least 2 characters",
721 |             "courseRequired": "Select a course"
722 |         },
723 |         "toast": {
724 |             "sizeInvalid": "Team must have 2-6 members (including you)",
725 |             "created": "Team created! You are the captain."
726 |         }
727 |     },
728 |     "surveys": {
729 |         "title": "Surveys",
730 |         "loadError": "We could not load surveys. Please try again.",
731 |         "retry": "Try again",
732 |         "alreadyCompleted": "You have already completed this survey.",
733 |         "completed": "Completed",
734 |         "toast": {
735 |             "answerAtLeastOne": "Please answer at least one question",
736 |             "submitted": "Survey submitted! +15 XP",
737 |             "submitFailed": "Failed to submit survey"
738 |         }
739 |     },
740 |     "badges": {
741 |         "title": "My Badges",
742 |         "subtitle": "Celebrate the milestones you have earned and choose up to three badges to pin.",
743 |         "pinned": "{{count}} of 3 pinned",
744 |         "loadError": "We could not load your badges. Please try again.",
745 |         "retry": "Try again"
746 |     },
747 |     "learningProfile": {
748 |         "title": "Learning Profile",
749 |         "subtitle": "Your assessment insights help tailor learning recommendations to you.",
750 |         "reassess": "Retake assessments",
751 |         "completeness": "Profile completeness",
752 |         "personalization": "ready for personalization",
753 |         "emptyTitle": "Build your learning profile",
754 |         "emptyBody": "Complete the short assessments to unlock learning preferences and tailored recommendations."
755 |         "completeProfile": "Complete my profile",
756 |         "loadError": "We could not load your learning profile. Please try again.",
757 |         "retry": "Try again",
758 |         "learningStyle": "Learning preferences",
759 |         "dominantStyle": "Your strongest preference: {{style}}",
760 |         "studyStrategies": "Study strategies",
761 |         "selfEfficacy": "Academic confidence",
762 |         "personality": "Learning traits",
763 |         "overall": "Overall",
764 |         "missingLearningStyle": "Complete the learning-style assessment to see these preferences.",
765 |         "missingStrategies": "Complete the study-strategies assessment to see these insights.",
766 |         "missingEfficacy": "Complete the self-efficacy assessment to see these insights.",
767 |         "missingPersonality": "Complete the personality assessment to see these insights.",
768 |         "styles": {
769 |             "visual": "Visual",
770 |             "auditory": "Auditory",
771 |             "read_write": "Read/write",
772 |             "kinesthetic": "Hands-on",
773 |             "multimodal": "Multimodal"
774 |         },
775 |         "strategies": {
776 |             "time_management": "Time management",
777 |             "elaboration": "Elaboration",

```

```

778     "self_testing": "Self-testing",
779     "help_seeking": "Help-seeking"
780 },
781 "efficacy": {
782     "general_academic": "General academic",
783     "course_specific": "Course-specific",
784     "self_regulated_learning": "Self-regulated learning"
785 },
786 "traits": {
787     "openness": "Openness",
788     "conscientiousness": "Conscientiousness",
789     "extraversion": "Extraversion",
790     "agreeableness": "Agreeableness",
791     "neuroticism": "Emotional sensitivity"
792 },
793 "rail": {
794     "label": "Learning profile context",
795     "whyTitle": "ð>ÿa Why this matters",
796     "whyBody": "Your learning style tunes how the AI Tutor explains things and how lessons are sequenced for
797     "completenessTitle": " Completeness",
798     "completenessEmpty": "Complete your first assessment to start building this profile.",
799     "finishAssessments": "Finish micro-assessments !"
800 }
801 },
802 "settingsRail": {
803     "label": "Settings privacy information",
804     "title": "ð=ÿ Your data",
805     "body": "Notification and language choices apply instantly. Nothing here is shared with classmates."
806 },
807 "profilePage": {
808     "title": "Me",
809     "subtitle": "Your learning identity, progress, privacy, and account.",
810     "edit": "Edit",
811     "changePhoto": "Change profile photo",
812     "student": "Student",
813     "level": "Level",
814     "totalXp": "Total XP",
815     "dayStreak": "day streak",
816     "badges": "Badges",
817     "editProfile": "Edit profile",
818     "viewPortfolio": "View public profile",
819     "levelProgress": "Level {{current}} !' {{next}}",
820     "xpRemaining": "{{count}} XP to the next level",
821     "freezes": "{{count}} streak freezes available",
822     "badgesCount": "Badges {{count}}",
823     "viewAll": "View all !'",
824     "noBadges": "Your earned badges will appear here.",
825     "learningActivity": "Learning activity",
826     "lastWeeks": "Last {{count}} weeks",
827     "activeDays": "active days in this period",
828     "profileLinks": "Profile destinations",
829     "links": {
830         "leaderboard": "Leaderboard",
831         "marketplace": "Marketplace",
832         "wellness": "Wellness & Habits",
833         "quests": "Knowledge Quests",
834         "portfolio": "Portfolio",
835         "journal": "Journal",
836         "team": "My Team",
837         "calendar": "Calendar & Timetable",
838         "transcript": "Transcript",
839         "fees": "Fees & Payments",
840         "surveys": "Surveys",
841         "learningProfile": "Learning Profile",
842         "settings": "Settings"
843     },
844     "learningProfile": "Learning profile",
845     "learningStyle": "Learning style",
846     "notComplete": "Not completed yet",
847     "privacy": "Privacy",
848     "anonymous": "Appear anonymous on leaderboards",
849     "anonymousDescription": "Hide your name from classmates while keeping your progress.",
850     "equipped": "Equipped",
851     "slots": {
852         "profile_theme": "Profile theme",
853         "avatar_frame": "Avatar frame",
854         "display_title": "Display title"
855     },
856     "noEquipped": "No cosmetics are equipped.",
857     "security": "Security & access",
858     "changePassword": "Change password",
859     "activeSessions": "Active sessions",
860     "transcript": "Academic transcript",
861     "dataControls": "Data & account controls",
862     "signOut": "Sign out",
863     "rail": {
864         "label": "Student profile summary",
865         "latestBadge": "Latest badge",
866         "noBadge": "No badge earned yet",
867         "viewBadges": "View all {{count}} badges !'",
868         "academic": "Academic",
869         "transcript": "Transcript",
870         "openTranscript": "Open transcript !'",
871         "portfolio": "Portfolio",
872         "evidence": "Evidence pieces",
873         "openPortfolio": "Open portfolio !'",
874         "account": "Account"
875     }
876 },
877 "publicPortfolio": {
878     "subtitle": "Student Learning Portfolio",
879     "totalXP": "Total XP",
880     "level": "Level",
881     "sections": {

```

```

882 |         "cloAttainment": "CLO Attainment",
883 |         "badges": "Badges"
884 |     },
885 |     "poweredBy": "Powered by Edeviser",
886 |     "error": {
887 |         "forbiddenTitle": "Portfolio Not Available",
888 |         "forbiddenBody": "This portfolio is private. The student has not enabled public sharing, or their school
889 |         "notFoundTitle": "Portfolio Not Found",
890 |         "notFoundBody": "We could not find a portfolio for this link. It may have been removed or the link may b
891 |         "missingIdTitle": "Portfolio Not Available",
892 |         "missingIdBody": "No student ID was provided.",
893 |         "code": "Error {{status}}"
894 |     }
895 | }
896 | }
897 |

```

FILE: src/locales/en/teacher.json

TYPE: .json | LINES: 1-109 | SHA256: aa441f1c5e652b89195703a0491c87441e48b1d8001fd55a5c3cc23e9af7d95c

```

1 | {
2 |   "dashboard": {
3 |     "title": "Dashboard",
4 |     "welcome": {
5 |       "subtitle": "Track grading, attainment, and at-risk students across your courses."
6 |     },
7 |     "gradingQueue": "Grading Queue",
8 |     "pendingSubmissions": "Pending Submissions",
9 |     "gradedThisWeek": "Graded This Week",
10 |    "avgAttainment": "Avg Attainment",
11 |    "atRiskStudents": "At-Risk Students",
12 |    "bloomsDistribution": "Bloom's Distribution",
13 |    "cloAttainment": "CLO Attainment",
14 |    "studentHeatmap": "Student Performance Heatmap",
15 |    "selectCourse": "Select course",
16 |    "viewAll": "View All",
17 |    "noCloData": "No CLO attainment data available for this course.",
18 |    "noClosDefined": "No CLOs defined yet.",
19 |    "noHeatmapData": "No student performance data available for this course.",
20 |    "noAtRisk": "No at-risk students detected. Great work!",
21 |    "noPending": "No pending submissions. You're all caught up!",
22 |    "sendNudgeTo": "Send Nudge to {{name}}",
23 |    "nudgePlaceholder": "Write a message...",
24 |    "nudgeSent": "Nudge sent to {{name}}",
25 |    "nudgeFailed": "Failed to send nudge",
26 |    "nudge": "Nudge",
27 |    "daysInactive": "{{count}}d inactive",
28 |    "activityUnavailable": "Activity date unavailable",
29 |    "late": "Late",
30 |    "heatmapLegend": {
31 |      "excellent": "Excellent (e85%)",
32 |      "satisfactory": "Satisfactory (70-84%)",
33 |      "developing": "Developing (50-69%)",
34 |      "notYet": "Not Yet (<50%)",
35 |      "noData": "No data"
36 |    },
37 |    "student": "Student",
38 |    "viewAll": "View All",
39 |    "allSections": "All Sections",
40 |    "teamHealth": "Team Health",
41 |    "viewReport": "View Report",
42 |    "totalTeams": "Total Teams",
43 |    "needsAttention": "Needs Attention",
44 |    "atRiskLabel": "At Risk",
45 |    "cancel": "Cancel",
46 |    "sendNudge": "Send Nudge",
47 |    "section": "Section {{code}}",
48 |    "unknownStudent": "Unknown Student",
49 |    "unknownAssignment": "Unknown Assignment",
50 |    "masteryRecovery": {
51 |      "title": "Mastery Recovery Alerts",
52 |      "description": "Students flagged for mastery recovery need to complete a recovery pathway before retryin
53 |      "failures": "{{count}} failures",
54 |      "inRecovery": "In Recovery"
55 |    },
56 |    "accessLimited": {
57 |      "title": "Learner details are access-limited",
58 |      "description": "{{count}} learners are flagged by the secure course aggregate, but individual profiles a
59 |      "rail": "{{count}} learners are flagged, but their identities are hidden by current data permissions."
60 |    }
61 |  },
62 |  "grading": {
63 |    "title": "Grading",
64 |    "rubricSelection": "Select rubric level for each criterion",
65 |    "totalScore": "Total Score",
66 |    "feedback": "Feedback",
67 |    "overallFeedback": "Overall Feedback",
68 |    "submitGrade": "Submit Grade",
69 |    "gradeSubmitted": "Grade submitted successfully."
70 |  },
71 |  "assignments": {
72 |    "title": "Assignments",
73 |    "addAssignment": "Add Assignment",
74 |    "editAssignment": "Edit Assignment",
75 |    "dueDate": "Due Date",
76 |    "totalMarks": "Total Marks",
77 |    "linkedCLOs": "Linked CLOs",
78 |    "lateWindow": "Late Submission Window"
79 |  },
80 |  "clos": {
81 |    "title": "Course Learning Outcomes",
82 |    "addCLO": "Add CLO",
83 |    "editCLO": "Edit CLO",
84 |    "bloomsLevel": "Bloom's Level",

```

```

85 |     "ploMapping": "PLO Mapping",
86 |     "noMapping": "No PLO mapping yet"
87 |   },
88 |   "bilingual": {
89 |     "arabicTitle": "Arabic Title",
90 |     "arabicTitlePlaceholder": "Enter title in Arabic (optional)"
91 |   },
92 |   "rubrics": {
93 |     "title": "Rubrics",
94 |     "addRubric": "Add Rubric",
95 |     "editRubric": "Edit Rubric",
96 |     "criteria": "Criteria",
97 |     "levels": "Performance Levels",
98 |     "saveAsTemplate": "Save as Template"
99 |   },
100 |   "attendance": {
101 |     "title": "Attendance",
102 |     "markAttendance": "Mark Attendance",
103 |     "present": "Present",
104 |     "absent": "Absent",
105 |     "late": "Late",
106 |     "excused": "Excused"
107 |   }
108 | }
109 |

```

FILE: src/main.tsx

TYPE: .tsx | LINES: 1-51 | SHA256: 0db61b8262b31fae1fa887b105c3b01d417739efeaf7289a54ce776295941c5c

```

1 | import React from "react";
2 | import ReactDOM from "react-dom/client";
3 | import { validateEnv } from "@lib/envValidation";
4 | import { initAnalyticsIfConsented } from "@lib/analyticsConsent";
5 | import "@lib/i18n";
6 | import App from "@App";
7 | import "@design-system/tokens.css";
8 | import "@index.css";
9 |
10 | // Validate required env vars before rendering – warns clearly if missing
11 | const envValid = validateEnv();
12 |
13 | // If env validation fails, render a visible error instead of a blank page
14 | if (!envValid) {
15 |   const root = document.getElementById("root");
16 |   if (root) {
17 |     root.innerHTML = `
18 |       <div style="font-family:system-ui;padding:2rem;max-width:600px;margin:0 auto">
19 |         <h1 style="color:#ef4444">& b Configuration Error</h1>
20 |         <p>Required environment variables are missing. Check the browser console for details.</p>
21 |         <p style="color:#64748b;font-size:0.875rem">Copy <code>.env.example</code> to <code>.env.local</code>
22 |       </div>
23 |     `;
24 |   }
25 | } else {
26 |   // Task 97.1: Initialize Sentry gated behind cookie consent
27 |   initAnalyticsIfConsented();
28 |
29 |   // Dev-only: log a11y violations to browser console via axe-core
30 |   if (import.meta.env.DEV) {
31 |     import("@axe-core/react").then((axe) => {
32 |       axe.default(React, ReactDOM, 1000);
33 |     });
34 |   }
35 |
36 |   // Task 82.3: Register service worker for PWA
37 |   if ("serviceWorker" in navigator && import.meta.env.PROD) {
38 |     window.addEventListener("load", () => {
39 |       navigator.serviceWorker.register("/sw.js").catch((err) => {
40 |         console.error("[SW] Registration failed:", err);
41 |       });
42 |     });
43 |   }
44 |
45 |   ReactDOM.createRoot(document.getElementById("root")!).render(
46 |     <React.StrictMode>
47 |       <App />
48 |     </React.StrictMode>
49 |   );
50 | }
51 |

```

FILE: src/pages/admin/AdminDashboard.tsx

TYPE: .tsx | LINES: 1-12 | SHA256: ff5f2ad6e77e9041742777ed73fff7a3bbf3dd7f45fd3ed9adbd4fcff516dbdd

```

1 | // =====
2 | // AdminDashboard – production admin dashboard (prototype rebuild)
3 | // =====
4 | // Implementation lives in the prototype-rebuilt `AdminDashboardScreen`
5 | // (src/features/admin/dashboard), re-exported here so the route path
6 | // (`@/pages/admin/AdminDashboard`) and its guard stay stable. The legacy
7 | // `AdminDashboardNew` reskin was replaced in the prototype-frontend-rebuild
8 | // (P2.5) cutover.
9 | // =====
10 |
11 | export { default } from "@features/admin/dashboard/AdminDashboardScreen";
12 |

```

FILE: src/pages/admin/AdminLayout.tsx

TYPE: .tsx | LINES: 1-14 | SHA256: 280d98a468708878befba4290b2b126cacfa62083c93334148ebccdfcb39097c

```
1 | import { Outlet } from "react-router-dom";
2 | import RoleAppShell from "@app/RoleAppShell";
3 | import AdminDashboardRail from "@features/admin/dashboard/AdminDashboardRail";
4 |
5 | const AdminLayout = () => {
6 |   return (
7 |     <RoleAppShell userRole="admin" rail={<AdminDashboardRail />}>
8 |       <Outlet />
9 |     </RoleAppShell>
10 |   );
11 | };
12 |
13 | export default AdminLayout;
14 |
```

FILE: src/pages/admin/analytics/AdminAnalyticsPage.tsx

TYPE: .tsx | LINES: 1-501 | SHA256: 4f6c679496eae14fc5a2a42fa8e76aea8fb47d543516516f5861432104f218d1

```
1 | // =====
2 | // AdminAnalyticsPage – Institution Analytics (Prototype Parity & Real Backend)
3 | // Rebuilds `prototype/admin-analytics.html` on `@/design-system` + tokens
4 | // Requirements: 1, 2, 3, 4, 5
5 | // =====
6 |
7 | import { useState } from "react";
8 | import { useTranslation } from "react-i18next";
9 | import { toast } from "sonner";
10 | import { Shimmer } from "@design-system";
11 | import {
12 |   useAdminAnalytics,
13 |   MIN_COHORT_THRESHOLD,
14 | } from "@hooks/useAdminAnalytics";
15 |
16 | const AdminAnalyticsPage = () => {
17 |   const { t } = useTranslation("common");
18 |   const [selectedProgram, setSelectedProgram] = useState<string>("all");
19 |   const { data: analytics, isLoading, error } = useAdminAnalytics();
20 |
21 |   if (isLoading) {
22 |     return (
23 |       <div className="space-y-4 no-scrollbar">
24 |         <Shimmer className="h-14 rounded-2xl" />
25 |         <Shimmer className="h-44 rounded-2xl" />
26 |         <div className="grid grid-cols-1 lg:grid-cols-2 gap-4">
27 |           <Shimmer className="h-44 rounded-2xl" />
28 |           <Shimmer className="h-44 rounded-2xl" />
29 |         </div>
30 |         <Shimmer className="h-48 rounded-2xl" />
31 |       </div>
32 |     );
33 |   }
34 |
35 |   if (error || !analytics) {
36 |     return (
37 |       <div className="rounded-2xl border border-red-200 bg-red-50 p-6 text-center text-red-700">
38 |         <p className="font-bold">
39 |           {t("common.errorLoading", "Failed to load analytics")}
40 |         </p>
41 |         <p className="text-xs mt-1">
42 |           {error instanceof Error
43 |             ? error.message
44 |             : "An unexpected error occurred."}
45 |         </p>
46 |       </div>
47 |     );
48 |   }
49 |
50 |   const {
51 |     weeklyActiveLearners,
52 |     masteryDistribution,
53 |     retentionRisk,
54 |     departments,
55 |     aiCopilotPerformance,
56 |     ploAttainment,
57 |   } = analytics;
58 |
59 |   const latestActive = weeklyActiveLearners[weeklyActiveLearners.length - 1];
60 |   const activePillLabel = `${latestActive?.activePercent ?? 0}% !`;
61 |
62 |   return (
63 |     <div className="space-y-4 no-scrollbar">
64 |       { /* Page Title & Subtitle */ }
65 |       <div>
66 |         <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
67 |           Institution analytics
68 |         </h1>
69 |         <p className="text-xs text-slate-500 dark:text-slate-400 mt-0.5">
70 |           Engagement, mastery & retention – de-identified & aggregated.
71 |         </p>
72 |       </div>
73 |
74 |       { /* 1. Engagement trend (Weekly active learners) */ }
75 |       <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04)]">
76 |         <div className="flex items-center justify-between mb-4">
77 |           <div className="flex items-center gap-2">
78 |             <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:b
79 |               0=UE
80 |             </span>
81 |             <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
82 |               Weekly active learners
```

```

83 |         </p>
84 |     </div>
85 |     <span className="inline-flex items-center rounded-full bg-emerald-50 px-2.5 py-0.5 text-xs font-bold
86 |       {activePillLabel}
87 |     </span>
88 |   </div>
89 |
90 |   {/ 5-week Bar Chart */}
91 |   <div className="flex items-end gap-2.5 h-28 border-b border-slate-100 dark:border-slate-800 pb-0">
92 |     {weeklyActiveLearners.map((pt, idx) => {
93 |       const isLatest = idx === weeklyActiveLearners.length - 1;
94 |       const barHeightPct = Math.max(10, Math.min(pt.activePercent, 100));
95 |
96 |       return (
97 |         <div
98 |           key={pt.week}
99 |           className="flex-1 flex flex-col items-center gap-1.5 h-full justify-end"
100 |         >
101 |           <div
102 |             className="w-full rounded-t transition-all"
103 |             style={{
104 |               height: `${barHeightPct}%`,
105 |               background: isLatest
106 |                 ? "linear-gradient(180deg, #14b8a6, #0382bd)"
107 |                 : "#3b82f6",
108 |             }}
109 |             title={`{pt.week}: ${pt.activeLearners} / ${pt.eligibleLearners} active (${pt.activePercent
110 |           } />
111 |           <span
112 |             className={`text-[9px] ${
113 |               isLatest
114 |                 ? "font-extrabold text-slate-700 dark:text-slate-200"
115 |                 : "text-slate-400"
116 |             }`}
117 |           >
118 |             {pt.week}
119 |           </span>
120 |         </div>
121 |       );
122 |     })}
123 |   </div>
124 |   <div className="flex items-center justify-between mt-2 text-[10px] text-slate-400">
125 |     <span>5-week trend · active learners / week</span>
126 |     <span className="italic text-slate-400 font-medium">
127 |       Real live Supabase data
128 |     </span>
129 |   </div>
130 | </div>
131 |
132 | {/ 2. Mastery Distribution & Retention Risk (2-Column Layout) */}
133 | <div className="grid grid-cols-1 lg:grid-cols-2 gap-4 items-start">
134 |   {/ Mastery Distribution */}
135 |   <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
136 |     <div className="flex items-center gap-2 mb-3">
137 |       <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:b
138 |         0<β
139 |       </span>
140 |       <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
141 |         Mastery distribution
142 |       </p>
143 |     </div>
144 |
145 |     <div className="space-y-2.5">
146 |       {[
147 |         { label: "Excellent", pct: masteryDistribution.excellentPercent },
148 |         { label: "Satisfactory",
149 |           pct: masteryDistribution.satisfactoryPercent,
150 |         },
151 |         { label: "Developing",
152 |           pct: masteryDistribution.developingPercent,
153 |         },
154 |         { label: "Not yet", pct: masteryDistribution.notYetPercent },
155 |         { label: "Unmeasured",
156 |           pct: masteryDistribution.unmeasuredPercent,
157 |         },
158 |       ]}.map((row) => (
159 |         <div key={row.label} className="flex items-center gap-2">
160 |           <span className="text-xs w-24 shrink-0 text-slate-600 dark:text-slate-400 font-medium">
161 |             {row.label}
162 |           </span>
163 |           <div className="flex-1 h-4 rounded-md bg-slate-100 dark:bg-slate-800 overflow-hidden">
164 |             <div
165 |               className="h-full bg-blue-500 transition-all"
166 |               style={{ width: `${Math.min(row.pct, 100)}%` }}
167 |             </div>
168 |             <span className="text-xs font-bold w-10 text-end text-slate-800 dark:text-slate-200">
169 |               {row.pct}%
170 |             </span>
171 |           </div>
172 |         </div>
173 |       ))}
174 |     </div>
175 |   </div>
176 |
177 | {/ Retention Risk */}
178 | <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
179 |   <div className="flex items-center gap-2 mb-3">
180 |     <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:b
181 |       0=Y;
182 |     </span>
183 |     <p className="text-sm font-bold text-slate-900 dark:text-slate-100">

```

```

187         Retention risk
188     </p>
189 </div>
190
191 <div className="space-y-2 text-sm">
192   <div className="flex items-center justify-between py-1 border-b border-slate-100 dark:border-slate-
193     <span className="text-slate-700 dark:text-slate-300 font-medium">
194       On track
195     </span>
196     <b className="text-emerald-600 font-black">
197       {retentionRisk.onTrack}
198     </b>
199   </div>
200   <div className="flex items-center justify-between py-1 border-b border-slate-100 dark:border-slate-
201     <span className="text-slate-700 dark:text-slate-300 font-medium">
202       Watch
203     </span>
204     <b className="text-amber-600 font-black">{retentionRisk.watch}</b>
205   </div>
206   <div className="flex items-center justify-between py-1">
207     <span className="text-slate-700 dark:text-slate-300 font-medium">
208       At risk
209     </span>
210     <b className="text-red-600 font-black">{retentionRisk.atRisk}</b>
211   </div>
212 </div>
213
214 <div className="mt-3 bg-amber-50/80 border border-amber-200/60 rounded-xl p-3 dark:bg-amber-950/30 d
215   <p className="text-xs text-amber-900 dark:text-amber-200 leading-relaxed font-medium">
216     {retentionRisk.atRisk} of {retentionRisk.total} learners flagged
217     at risk across course activities.{ " "}
218     <button
219       type="button"
220       onClick={() =>
221         toast.success("Outreach initiative logged", {
222           description:
223             "Outreach guidelines dispatched to department heads.",
224         })
225       }
226       className="font-bold underline text-amber-900 dark:text-amber-100 hover:text-amber-700 cursor-
227     >
228     Draft outreach
229   </button>
230 </p>
231 </div>
232 </div>
233 </div>
234
235 /* 3. Department Table */
236 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04
237   <div className="flex items-center gap-2 mb-3">
238     <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:bg-
239       0<6e
240     </span>
241     <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
242       Departments
243     </p>
244   </div>
245
246   <div className="overflow-x-auto">
247     <table className="w-full text-start text-xs border-collapse">
248       <thead>
249         <tr className="border-b border-slate-200 dark:border-slate-800 text-slate-500 dark:text-slate-40
250           <th className="pb-2 text-start">Department</th>
251           <th className="pb-2 text-center">Learners</th>
252           <th className="pb-2 text-center">Active</th>
253           <th className="pb-2 text-center">Mastery</th>
254           <th className="pb-2 text-center">Trend</th>
255         </tr>
256       </thead>
257       <tbody className="divide-y divide-slate-100 dark:divide-slate-800">
258         {departments.map((dept) => {
259           const isSuppressed =
260             dept.learners > 0 && dept.learners < MIN_COHORT_THRESHOLD;
261           const masteryTone =
262             dept.masteryPercent >= 80
263               ? "text-emerald-600"
264             : dept.masteryPercent >= 70
265               ? "text-blue-600"
266             : "text-amber-700";
267
268           return (
269             <tr
270               key={dept.departmentName}
271               className="hover:bg-slate-50/50 dark:hover:bg-slate-800/40"
272             >
273               <td className="py-2.5 font-bold text-slate-900 dark:text-slate-100">
274                 {dept.departmentName}
275               </td>
276               <td className="py-2.5 text-center font-semibold text-slate-600 dark:text-slate-300">
277                 {isSuppressed ? "< 3 (suppressed)" : dept.learners}
278               </td>
279               <td className="py-2.5 text-center font-semibold text-slate-600 dark:text-slate-300">
280                 {dept.activePercent}%
281               </td>
282               <td className="py-2.5 text-center font-black">
283                 <span className={masteryTone}>
284                   {dept.masteryPercent}%
285                 </span>
286               </td>
287               <td className="py-2.5 text-center font-black text-emerald-600">
288                 {dept.trend === "up" ? "↑" : "↓"}
289               </td>
290             </tr>

```



```

291         });
292     });
293 </tbody>
294 </table>
295 </div>
296 </div>
297
298 /* 4. AI Co-Pilot Performance */
299 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04
300 <div className="flex items-center justify-between mb-4">
301   <div className="flex items-center gap-2">
302     <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:b
303       0>Y
304     </span>
305     <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
306       AI Co-Pilot performance
307     </p>
308   </div>
309   <span className="inline-flex items-center rounded-full bg-blue-50 px-2.5 py-0.5 text-xs font-bold te
310     A2 governance
311   </span>
312 </div>
313
314 {aiCopilotPerformance.hasSufficientData ? (
315   <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
316     <div>
317       <div className="flex items-baseline justify-between">
318         <span className="text-xs font-bold text-slate-700 dark:text-slate-300">
319           Suggestion acceptance
320         </span>
321         <span className="text-lg font-black text-slate-900 dark:text-slate-100">
322           {aiCopilotPerformance.suggestionAcceptanceRate}%
323         </span>
324       </div>
325       <div className="h-2 w-full rounded-full bg-slate-100 dark:bg-slate-800 mt-2 overflow-hidden">
326         <div
327           className="h-full bg-blue-600 rounded-full"
328           style={{
329             width: `${aiCopilotPerformance.suggestionAcceptanceRate}%`,
330           }}
331         </div>
332       <p className="text-[11px] text-slate-400 mt-1">
333         {aiCopilotPerformance.suggestionTotal} module suggestions logged
334       </p>
335     </div>
336
337     <div>
338       <div className="flex items-baseline justify-between">
339         <span className="text-xs font-bold text-slate-700 dark:text-slate-300">
340           Prediction accuracy
341         </span>
342         <span className="text-lg font-black text-slate-900 dark:text-slate-100">
343           {aiCopilotPerformance.predictionAccuracyRate}%
344         </span>
345       </div>
346       <div className="h-2 w-full rounded-full bg-slate-100 dark:bg-slate-800 mt-2 overflow-hidden">
347         <div
348           className="h-full bg-blue-600 rounded-full"
349           style={{
350             width: `${aiCopilotPerformance.predictionAccuracyRate}%`,
351           }}
352         </div>
353       <p className="text-[11px] text-slate-400 mt-1">
354         {aiCopilotPerformance.predictionTotal} at-risk predictions
355       </p>
356     </div>
357
358     <div>
359       <div className="flex items-baseline justify-between">
360         <span className="text-xs font-bold text-slate-700 dark:text-slate-300">
361           Draft acceptance
362         </span>
363         <span className="text-lg font-black text-slate-900 dark:text-slate-100">
364           {aiCopilotPerformance.draftAcceptanceRate}%
365         </span>
366       </div>
367       <div className="h-2 w-full rounded-full bg-slate-100 dark:bg-slate-800 mt-2 overflow-hidden">
368         <div
369           className="h-full bg-emerald-500 rounded-full"
370           style={{
371             width: `${aiCopilotPerformance.draftAcceptanceRate}%`,
372           }}
373         </div>
374       <p className="text-[11px] text-slate-400 mt-1">
375         {aiCopilotPerformance.draftTotal} feedback drafts used
376       </p>
377     </div>
378   </div>
379 ) : (
380   <div className="rounded-xl border border-slate-200 bg-slate-50/70 p-4 text-center dark:border-slate-
381     <p className="text-xs font-bold text-slate-700 dark:text-slate-300">
382       Not enough usage data
383     </p>
384     <p className="text-[11px] text-slate-500 mt-1">
385       AI Co-Pilot metrics will populate automatically as staff generate,
386       edit, and validate suggestions.
387     </p>
388   </div>
389 )}
390 </div>
391
392
393
394

```

```

395 |         <div className="mt-3 bg-slate-50 border border-slate-100 rounded-xl p-3 dark:bg-slate-800/40 dark:bord
396 |         <p className="text-[11px] text-slate-500 dark:text-slate-400 leading-relaxed font-medium">
397 |             How often staff accept AI suggestions, how accurate at-risk
398 |             predictions proved, and how often AI feedback drafts were used – the
399 |             trust signals behind the autonomy ceiling.
400 |         </p>
401 |     </div>
402 | </div>
403 |
404 | {/* 5. PLO Attainment Heatmap */}
405 | <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04
406 | <div className="flex items-center justify-between mb-4">
407 |     <div className="flex items-center gap-2">
408 |         <span className="flex h-8 w-8 items-center justify-center rounded-xl bg-slate-100 text-base dark:b
409 |             Ø=Yüp
410 |         </span>
411 |         <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
412 |             PLO attainment heatmap
413 |         </p>
414 |     </div>
415 |     <select
416 |         value={selectedProgram}
417 |         onChange={(e) => setSelectedProgram(e.target.value)}
418 |         className="text-xs font-bold border border-slate-200 rounded-lg px-2.5 py-1 bg-white text-slate-70
419 |     >
420 |         <option value="all">Program: All</option>
421 |     </select>
422 | </div>
423 |
424 | {/* Heatmap Grid */}
425 | <div className="grid grid-cols-1 sm:grid-cols-2 md:grid-cols-4 gap-2.5">
426 |     {ploAttainment.map((plo) => {
427 |         const isUnmeasured =
428 |             plo.meanAttainment < 0 || plo.statusBand === "unmeasured";
429 |         let bgClass =
430 |             "bg-slate-100 text-slate-700 dark:bg-slate-800 dark:text-slate-300";
431 |         let textClass = "text-slate-800 dark:text-slate-100";
432 |
433 |         if (!isUnmeasured) {
434 |             if (plo.statusBand === "excellent") {
435 |                 bgClass =
436 |                     "bg-emerald-100/90 text-emerald-900 dark:bg-emerald-950/50 dark:text-emerald-200";
437 |                 textClass = "text-emerald-900 dark:text-emerald-100";
438 |             } else if (plo.statusBand === "satisfactory") {
439 |                 bgClass =
440 |                     "bg-blue-100/90 text-blue-900 dark:bg-blue-950/50 dark:text-blue-200";
441 |                 textClass = "text-blue-900 dark:text-blue-100";
442 |             } else if (plo.statusBand === "developing") {
443 |                 bgClass =
444 |                     "bg-amber-100/90 text-amber-900 dark:bg-amber-950/50 dark:text-amber-200";
445 |                 textClass = "text-amber-900 dark:text-amber-100";
446 |             } else {
447 |                 bgClass =
448 |                     "bg-red-100/90 text-red-900 dark:bg-red-950/50 dark:text-red-200";
449 |                 textClass = "text-red-900 dark:text-red-100";
450 |             }
451 |         }
452 |
453 |         return (
454 |             <div
455 |                 key={plo.ploId}
456 |                 className={`rounded-xl p-3 ${bgClass} transition-all`}
457 |             >
458 |                 <p className="text-[11px] font-bold truncate">
459 |                     {plo.ploCodeTitle}
460 |                 </p>
461 |                 <p className={`text-xl font-black mt-1 ${textClass}`}>
462 |                     {isUnmeasured ? "-" : `${plo.meanAttainment}%`}
463 |                 </p>
464 |                 <p className="text-[10px] opacity-80 mt-0.5 font-medium">
465 |                     {plo.derivationLabel}
466 |                 </p>
467 |             </div>
468 |         );
469 |     })}
470 | </div>
471 |
472 | {/* Legend */}
473 | <div className="flex flex-wrap gap-3 mt-3.5 text-[11px] text-slate-500 dark:text-slate-400 font-medium
474 | <span className="inline-flex items-center gap-1.5">
475 |     <i className="w-2.5 h-2.5 rounded-xs bg-emerald-500 inline-block" />
476 |     Excellent 85
477 | </span>
478 | <span className="inline-flex items-center gap-1.5">
479 |     <i className="w-2.5 h-2.5 rounded-xs bg-blue-500 inline-block" />
480 |     Satisfactory 70-84
481 | </span>
482 | <span className="inline-flex items-center gap-1.5">
483 |     <i className="w-2.5 h-2.5 rounded-xs bg-amber-500 inline-block" />
484 |     Developing 50-69
485 | </span>
486 | <span className="inline-flex items-center gap-1.5">
487 |     <i className="w-2.5 h-2.5 rounded-xs bg-red-500 inline-block" />
488 |     Not yet &lt;50
489 | </span>
490 | <span className="inline-flex items-center gap-1.5">
491 |     <i className="w-2.5 h-2.5 rounded-xs bg-slate-300 dark:bg-slate-600 inline-block" />
492 |     Unmeasured
493 | </span>
494 | </div>
495 | </div>
496 | </div>
497 | );
498 | };

```

```
499 |  
500 | export default AdminAnalyticsPage;  
501 |
```

FILE: src/pages/admin/AuditLogPage.tsx

TYPE: .tsx | LINES: 1-240 | SHA256: 86adbcb43dad1c8a2dfdb810c365cbb9361411542b4494cbcb7a9dfca6fb0106

[illegible]

```

98 | header: "Entity ID",
99 | cell: ({ row }) => {
100 |   <span
101 |     className="font-mono text-xs text-gray-500"
102 |     title={row.getValue<string | null>("target_id") ?? undefined}
103 |   >
104 |     {truncateAuditIdentifier(row.getValue<string | null>("target_id"))}
105 |   </span>
106 | ),
107 | },
108 | {
109 |   accessorKey: "actor_id",
110 |   header: "Actor",
111 |   cell: ({ row }) => {
112 |     <span
113 |       className="font-mono text-xs text-gray-500"
114 |       title={row.getValue<string | null>("actor_id") ?? undefined}
115 |     >
116 |       {truncateAuditIdentifier(row.getValue<string | null>("actor_id"))}
117 |     </span>
118 |   ),
119 | },
120 | {
121 |   accessorKey: "diff",
122 |   header: "Details",
123 |   cell: ({ row }) => {
124 |     const diff = row.getValue<Record<string, unknown> | null>("diff");
125 |     if (!diff) return <span className="text-gray-400"></span>;
126 |     return (
127 |       <pre
128 |         className="text-xs text-gray-600 max-w-xs truncate"
129 |         title={JSON.stringify(diff, null, 2)}
130 |       >
131 |         {JSON.stringify(diff)}
132 |       </pre>
133 |     );
134 |   },
135 | },
136 | ];

```

```

202 |         </Select>
203 |
204 |         <Select
205 |             value={entityType || "_all"}
206 |             onValueChange={(v) => {
207 |                 setEntityType(v === "_all" ? null : v);
208 |                 setPage(1);
209 |             }}
210 |         >
211 |             <SelectTrigger className="w-[160px] bg-white">
212 |                 <SelectValue placeholder="All Types" />
213 |             </SelectTrigger>
214 |             <SelectContent>
215 |                 {ENTITY_TYPE_OPTIONS.map((opt) => (
216 |                     <SelectItem key={opt.value} value={opt.value}>
217 |                         {opt.label}
218 |                     </SelectItem>
219 |                 ))}
220 |             </SelectContent>
221 |         </Select>
222 |     </div>
223 |
224 |     { /* Data Table */ }
225 |     <DataTable
226 |         columns={columns}
227 |         data={paginatedData?.data ?? []}
228 |         isLoading={isLoading}
229 |         isFetching={isFetching}
230 |         page={page}
231 |         pageSize={paginatedData?.pageSize}
232 |         totalCount={paginatedData?.count}
233 |         onPageChange={setPage}
234 |     />
235 | </div>
236 | );
237 | };
238 |
239 | export default AuditLogPage;
240 |

```

FILE: [src/pages/admin/badges/BadgeDefinitionsPage.tsx](#)

TYPE: .tsx | LINES: 1-606 | SHA256: c48fcfafbe6d2ca982b99b071838a58d9dbb127e7e227a614b56b2ea67ce4072

```

1 | import { useState } from "react";
2 | import { zodResolver } from "@hookform/resolvers/zod";
3 | import { useForm } from "react-hook-form";
4 | import { useTranslation } from "react-i18next";
5 | import { Link } from "react-router-dom";
6 | import {
7 |     Archive,
8 |     ArchiveRestore,
9 |     Loader2,
10 |     Pencil,
11 |     Plus,
12 |     Sparkles,
13 |     Trash2,
14 | } from "lucide-react";
15 | import { toast } from "sonner";
16 |
17 | import { Badge } from "@components/ui/badge";
18 | import { Button } from "@components/ui/button";
19 | import {
20 |     Dialog,
21 |     DialogContent,
22 |     DialogDescription,
23 |     DialogFooter,
24 |     DialogHeader,
25 |     DialogTitle,
26 | } from "@components/ui/dialog";
27 | import {
28 |     Form,
29 |     FormControl,
30 |     FormField,
31 |     FormItem,
32 |     FormLabel,
33 |     FormMessage,
34 | } from "@components/ui/form";
35 | import { Input } from "@components/ui/input";
36 | import { Textarea } from "@components/ui/textarea";
37 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
38 | import { PageHeader, StatePanel } from "@design-system";
39 | import { useAuth } from "@hooks/useAuth";
40 | import {
41 |     useBadgeDefinitions,
42 |     useCreateBadgeDefinition,
43 |     useDeleteBadgeDefinition,
44 |     useUpdateBadgeDefinition,
45 |     type BadgeDefinition,
46 |     type BadgeDefinitionInput,
47 | } from "@hooks/useBadgeDefinitions";
48 | import {
49 |     badgeDefinitionSchema,
50 |     type BadgeDefinitionFormValues,
51 | } from "@lib/schemas/badgeDefinition";
52 | import type { Json } from "@types/database";
53 | import { cn } from "@lib/Utils";
54 |
55 | const EMPTY_VALUES: BadgeDefinitionFormValues = {
56 |     name: "",
57 |     badge_key: "",
58 |     description: "",
59 |     emoji: "ðŸš€",
60 |     category: "",
61 |     bronze_condition: "",

```

```

62 |   silver_condition: "",
63 |   gold_condition: "",
64 | };
65 |
66 | const conditionText = (conditions: Json | null, tier: string) => {
67 |   if (
68 |     !conditions ||
69 |     typeof conditions !== "object" ||
70 |     Array.isArray(conditions)
71 |   ) {
72 |     return "";
73 |   }
74 |
75 |   const tierValue = conditions[tier];
76 |   if (typeof tierValue === "string") return tierValue;
77 |   if (tierValue && typeof tierValue === "object" && !Array.isArray(tierValue)) {
78 |     const description = tierValue.description;
79 |     if (typeof description === "string") return description;
80 |     const threshold = tierValue.threshold;
81 |     if (typeof threshold === "number" || typeof threshold === "string") {
82 |       return String(threshold);
83 |     }
84 |   }
85 |   return "";
86 | };
87 |
88 | const valuesFromDefinition = (
89 |   definition: BadgeDefinition
90 | ): BadgeDefinitionFormValues => ({
91 |   name: definition.name,
92 |   badge_key: definition.badge_key,
93 |   description: definition.description,
94 |   emoji: definition.emoji,
95 |   category: definition.category ?? "",
96 |   bronze_condition: conditionText(definition.tier_conditions, "bronze"),
97 |   silver_condition: conditionText(definition.tier_conditions, "silver"),
98 |   gold_condition: conditionText(definition.tier_conditions, "gold"),
99 | });
100 |
101 | const toInput = (values: BadgeDefinitionFormValues): BadgeDefinitionInput => ({
102 |   badge_key: values.badge_key,
103 |   name: values.name,
104 |   description: values.description,
105 |   emoji: values.emoji,
106 |   category: values.category || null,
107 |   tier_conditions: {
108 |     bronze: { description: values.bronze_condition },
109 |     silver: { description: values.silver_condition },
110 |     gold: { description: values.gold_condition },
111 |   },
112 | });
113 |
114 | const tierSummary = (
115 |   definition: BadgeDefinition,
116 |   labels: { bronze: string; silver: string; gold: string },
117 |   emptyLabel: string
118 | ) => {
119 |   const tiers = [
120 |     [">YI", labels.bronze, conditionText(definition.tier_conditions, "bronze")],
121 |     [">YH", labels.silver, conditionText(definition.tier_conditions, "silver")],
122 |     [">YG", labels.gold, conditionText(definition.tier_conditions, "gold")],
123 |   ].filter(([, , value]) => value);
124 |
125 |   if (tiers.length === 0) return emptyLabel;
126 |   return tiers
127 |     .map(([emoji, label, value]) => `${emoji} ${label}: ${value}`)
128 |     .join(" · ");
129 | };
130 |
131 | const categoryClass = (category: string | null) => {
132 |   switch (category?.toLowerCase()) {
133 |     case "academic":
134 |     case "mastery":
135 |       return "border-blue-200 bg-blue-50 text-blue-700";
136 |     case "streak":
137 |     case "habit":
138 |     case "consistency":
139 |       return "border-amber-200 bg-amber-50 text-amber-700";
140 |     case "team":
141 |     case "social":
142 |       return "border-cyan-200 bg-cyan-50 text-cyan-700";
143 |     case "mystery":
144 |       return "border-violet-200 bg-violet-50 text-violet-700";
145 |     default:
146 |       return "border-slate-200 bg-slate-50 text-slate-600";
147 |   }
148 | };
149 |
150 | const BadgeDefinitionsPage = () => {
151 |   const { t } = useTranslation("common");
152 |   const { institutionId } = useAuth();
153 |   const {
154 |     data: definitions = [],
155 |     isLoading,
156 |     isError,
157 |   } = useBadgeDefinitions(institutionId ?? undefined);
158 |   const createDefinition = useCreateBadgeDefinition();
159 |   const updateDefinition = useUpdateBadgeDefinition();
160 |   const deleteDefinition = useDeleteBadgeDefinition();
161 |   const [editorOpen, setEditorOpen] = useState(false);
162 |   const [editing, setEditing] = useState<BadgeDefinition | null>(null);
163 |   const [deleteTarget, setDeleteTarget] = useState<BadgeDefinition | null>(
164 |     null
165 |   );

```

```

166 |
167 | const form = useForm<BadgeDefinitionFormValues>({
168 |   resolver: zodResolver(badgeDefinitionSchema),
169 |   defaultValues: EMPTY_VALUES,
170 | });
171 |
172 | const openCreate = () => {
173 |   setEditing(null);
174 |   form.reset(EMPTY_VALUES);
175 |   setEditorOpen(true);
176 | };
177 |
178 | const openEdit = (definition: BadgeDefinition) => {
179 |   setEditing(definition);
180 |   form.reset(valuesFromDefinition(definition));
181 |   setEditorOpen(true);
182 | };
183 |
184 | const closeEditor = () => {
185 |   setEditorOpen(false);
186 |   setEditing(null);
187 |   form.reset(EMPTY_VALUES);
188 | };
189 |
190 | const onSubmit = (values: BadgeDefinitionFormValues) => {
191 |   if (!institutionId) {
192 |     toast.error(
193 |       t(
194 |         "admin.badges.missingInstitution",
195 |         "Your account is not linked to an institution."
196 |       )
197 |     );
198 |     return;
199 |   }
200 |
201 |   const onSuccess = () => {
202 |     toast.success(
203 |       editing
204 |         ? t("admin.badges.updated", "Badge definition updated")
205 |         : t("admin.badges.created", "Badge definition created")
206 |     );
207 |     closeEditor();
208 |   };
209 |   const onError = (error: Error) => toast.error(error.message);
210 |
211 |   if (editing) {
212 |     updateDefinition.mutate(
213 |       { id: editing.id, input: toInput(values) },
214 |       { onSuccess, onError }
215 |     );
216 |     return;
217 |   }
218 |
219 |   createDefinition.mutate(
220 |     { institutionId, input: toInput(values) },
221 |     { onSuccess, onError }
222 |   );
223 | };
224 |
225 | const toggleArchived = (definition: BadgeDefinition) => {
226 |   updateDefinition.mutate(
227 |     {
228 |       id: definition.id,
229 |       input: { is_archived: !definition.is_archived },
230 |     },
231 |     {
232 |       onSuccess: () =>
233 |         toast.success(
234 |           definition.is_archived
235 |             ? t("admin.badges.restored", "Badge restored")
236 |             : t("admin.badges.archived", "Badge archived")
237 |         ),
238 |       onError: (error) => toast.error(error.message),
239 |     }
240 |   );
241 | };
242 |
243 | const confirmDelete = () => {
244 |   if (!deleteTarget) return;
245 |   deleteDefinition.mutate(deleteTarget.id, {
246 |     onSuccess: () => {
247 |       toast.success(t("admin.badges.deleted", "Badge definition deleted"));
248 |       setDeleteTarget(null);
249 |     },
250 |     onError: (error) => toast.error(error.message),
251 |   });
252 | };
253 |
254 | const mutationPending =
255 |   createDefinition.isPending || updateDefinition.isPending;
256 |
257 | return (
258 |   <div className="space-y-4">
259 |     <div className="space-y-1">
260 |       <PageHeader
261 |         title={t("admin.badges.title", "Badge Definitions")}
262 |         action={
263 |           <div className="flex flex-wrap items-center gap-2">
264 |             <Button asChild variant="outline" size="sm">
265 |               <Link to="/admin/badges/spotlight">
266 |                 <Sparkles className="size-4" />
267 |                 {t("admin.badges.spotlight", "Spotlight schedule")}
268 |               </Link>
269 |             </Button>

```

```

270         <Button
271             type="button"
272             size="sm"
273             variant="tactile"
274             onClick={openCreate}
275         >
276             <Plus className="size-4" />
277             {t("admin.badges.new", "New badge")}
278         </Button>
279     </div>
280 }
281 />
282 <p className="text-xs text-slate-500">
283     {t(
284         "admin.badges.description",
285         "Institution-level badge templates with tiered progression."
286     )}
287 </p>
288 </div>
289
290 {isLoading ? (
291     <StatePanel variant="loading" />
292 ) : isError ? (
293     <StatePanel
294         variant="error"
295         message={t(
296             "admin.badges.loadError",
297             "Could not load badge definitions."
298         )}
299     />
300 ) : definitions.length === 0 ? (
301     <div className="rounded-xl bg-white p-6 text-center shadow-md">
302         <p className="text-sm text-slate-500">
303             {t(
304                 "admin.badges.empty",
305                 "No badge definitions yet. Create the first institution badge."
306             )}
307         </p>
308         <div className="mt-4">
309             <Button type="button" onClick={openCreate}>
310                 <Plus className="size-4" />
311                 {t("admin.badges.new", "New badge")}
312             </Button>
313         </div>
314     </div>
315 ) : (
316     <div className="grid grid-cols-1 gap-3 md:grid-cols-2">
317         {definitions.map((definition) => (
318             <article
319                 key={definition.id}
320                 className={cn(
321                     "rounded-[14px] border border-slate-200/80 bg-white p-3.5 shadow-sm transition-shadow hover:sh
322                     definition.is_archived && "opacity-55"
323                 )}
324             >
325                 <div className="flex items-start gap-3">
326                     <span
327                         className="text-2xl leading-8"
328                         role="img"
329                         aria-label={definition.name}
330                     >
331                         {definition.emoji}
332                     </span>
333                     <div className="min-w-0 flex-1">
334                         <div className="flex flex-wrap items-center gap-2">
335                             <h2 className="truncate text-sm font-bold text-slate-900">
336                                 {definition.name}
337                             </h2>
338                             <Badge
339                                 variant="outline"
340                                 className={cn(
341                                     "text-[10px] capitalize",
342                                     categoryClass(definition.category)
343                                 )}
344                             >
345                                 {definition.category ||
346                                 t("admin.badges.uncategorized", "Uncategorized")}
347                             </Badge>
348                             {definition.is_archived && (
349                                 <Badge variant="destructive" className="text-[10px]">
350                                     {t("admin.badges.archivedLabel", "Archived")}
351                                 </Badge>
352                             )}
353                         </div>
354                         <p className="mt-1 line-clamp-2 text-xs text-slate-500">
355                             {definition.description ||
356                             t("admin.badges.noDescription", "No description")}
357                         </p>
358                     </div>
359                     <Button
360                         type="button"
361                         variant="ghost"
362                         size="icon-sm"
363                         aria-label={t("common.edit", "Edit")}
364                         onClick={() => openEdit(definition)}
365                     >
366                         <Pencil className="size-3.5" />
367                     </Button>
368                 </div>
369
370                 <p className="mt-2 text-[11px] leading-5 text-slate-500">
371                     {tierSummary(
372                         definition,
373                     )}

```



```

374         bronze: t("admin.badges.bronze", "Bronze"),
375         silver: t("admin.badges.silver", "Silver"),
376         gold: t("admin.badges.gold", "Gold"),
377     },
378     t(
379         "admin.badges.singleTier",
380         "Single-tier · condition not configured"
381     )
382 )
383 </p>
384 <div className="mt-2 flex items-center justify-between border-t border-slate-100 pt-2">
385   <code className="truncate text-[10px] text-slate-400">
386     {definition.badge_key}
387   </code>
388   <div className="flex items-center gap-1">
389     <Button
390       type="button"
391       variant="ghost"
392       size="sm"
393       className="h-7 px-2 text-xs text-slate-500"
394       onClick={() => toggleArchived(definition)}
395     >
396       {definition.is_archived ? (
397         <ArchiveRestore className="size-3.5" />
398       ) : (
399         <Archive className="size-3.5" />
400       )}
401       {definition.is_archived
402         ? t("admin.badges.restore", "Restore")
403         : t("admin.badges.archive", "Archive")}
404     </Button>
405     <Button
406       type="button"
407       variant="ghost"
408       size="icon-sm"
409       className="text-slate-400 hover:text-red-600"
410       aria-label={t("common.delete", "Delete")}
411       onClick={() => setDeleteTarget(definition)}
412     >
413       <Trash2 className="size-3.5" />
414     </Button>
415   </div>
416 </div>
417 </article>
418 )}}
419 </div>
420 )}
421
422 <Dialog
423   open={editorOpen}
424   onOpenChange={(open) => (open ? setEditorOpen(true) : closeEditor())}
425 >
426   <DialogContent className="max-h-[90vh] overflow-y-auto sm:max-w-2xl">
427     <DialogHeader>
428       <DialogTitle>
429         {editing
430           ? t("admin.badges.editTitle", "Edit badge definition")
431           : t("admin.badges.createTitle", "Create badge definition")}
432       </DialogTitle>
433       <DialogDescription>
434         {t(
435           "admin.badges.formDescription",
436           "Define the presentation and Bronze, Silver, and Gold progression conditions."
437         )}
438       </DialogDescription>
439     </DialogHeader>
440
441     <Form {...form}>
442       <form
443         id="badge-definition-form"
444         onSubmit={form.handleSubmit(onSubmit)}
445         className="space-y-4"
446       >
447         <div className="grid grid-cols-[88px_minmax(0,1fr)] gap-3">
448           <FormField
449             control={form.control}
450             name="emoji"
451             render={({ field }) => (
452               <FormItem>
453                 <FormLabel>{t("admin.badges.emoji", "Emoji")}</FormLabel>
454                 <FormControl>
455                   <Input {...field} className="text-center text-xl" />
456                 </FormControl>
457                 <FormMessage />
458               </FormItem>
459             )}
460           />
461           <FormField
462             control={form.control}
463             name="name"
464             render={({ field }) => (
465               <FormItem>
466                 <FormLabel>{t("admin.badges.name", "Name")}</FormLabel>
467                 <FormControl>
468                   <Input {...field} />
469                 </FormControl>
470                 <FormMessage />
471               </FormItem>
472             )}
473           />
474         </div>
475
476         <div className="grid gap-3 sm:grid-cols-2">
477           <FormField

```

```

478         control={form.control}
479         name="badge_key"
480         render={({ field }) => (
481             <FormItem>
482                 <FormLabel>
483                     {t("admin.badges.key", "Badge key")}
484                 </FormLabel>
485                 <FormControl>
486                     <Input
487                         {...field}
488                         placeholder="perfect_week"
489                         disabled={!editing}
490                     />
491                 </FormControl>
492                 <FormMessage />
493             </FormItem>
494         )}
495     />
496     <FormField
497         control={form.control}
498         name="category"
499         render={({ field }) => (
500             <FormItem>
501                 <FormLabel>
502                     {t("admin.badges.category", "Category")}
503                 </FormLabel>
504                 <FormControl>
505                     <Input {...field} placeholder="academic" />
506                 </FormControl>
507                 <FormMessage />
508             </FormItem>
509         )}
510     />
511 </div>
512
513 <FormField
514     control={form.control}
515     name="description"
516     render={({ field }) => (
517         <FormItem>
518             <FormLabel>
519                 {t("admin.badges.badgeDescription", "Description")}
520             </FormLabel>
521             <FormControl>
522                 <Textarea {...field} rows={3} />
523             </FormControl>
524             <FormMessage />
525         </FormItem>
526     )}
527 />
528
529 <fieldset className="rounded-xl border border-slate-200 p-4">
530     <legend className="px-1 text-sm font-bold text-slate-800">
531         {t("admin.badges.tierConditions", "Tier conditions")}
532     </legend>
533     <div className="mt-1 grid gap-3">
534         {([
535             [
536                 ["bronze_condition", "0>YI", "Bronze"],
537                 ["silver_condition", "0>YH", "Silver"],
538                 ["gold_condition", "0>YG", "Gold"],
539             ] as const
540         ).map(([name, emoji, label]) => (
541             <FormField
542                 key={name}
543                 control={form.control}
544                 name={name}
545                 render={({ field }) => (
546                     <FormItem>
547                         <FormLabel>
548                             {emoji}{" "}
549                             {t(`admin.badges.${label.toLowerCase()}`, label)}
550                         </FormLabel>
551                         <FormControl>
552                             <Input
553                                 {...field}
554                                 placeholder={t(
555                                     "admin.badges.conditionPlaceholder",
556                                     "Describe the measurable threshold"
557                                 )}
558                             />
559                         </FormControl>
560                         <FormMessage />
561                     </FormItem>
562                 )}
563             />
564         )}
565     </div>
566 </fieldset>
567 </form>
568 </Form>
569
570 <DialogFooter>
571     <Button type="button" variant="outline" onClick={closeEditor}>
572         {t("common.cancel", "Cancel")}
573     </Button>
574     <Button
575         type="submit"
576         form="badge-definition-form"
577         disabled={mutationPending}
578     >
579         {mutationPending && <Loader2 className="size-4 animate-spin" />}
580         {editing
581             ? t("common.save", "Save changes")

```

```

582 |         : t("admin.badges.create", "Create badge"))}
583 |         </Button>
584 |       </DialogFooter>
585 |     </DialogContent>
586 |   </Dialog>
587 |
588 |   <ConfirmDialog
589 |     open={!deleteTarget}
590 |     onOpenChange={open => !open && setDeleteTarget(null)}
591 |     title={t("admin.badges.deleteTitle", "Delete badge definition?")}
592 |     description={t(
593 |       "admin.badges.deleteDescription",
594 |       "This permanently removes the institution badge template. Existing earned badges are not removed."
595 |     )}
596 |     confirmLabel={t("common.delete", "Delete")}
597 |     onConfirm={confirmDelete}
598 |     isPending={deleteDefinition.isPending}
599 |     variant="destructive"
600 |   />
601 | </div>
602 | );
603 | };
604 |
605 | export default BadgeDefinitionsPage;
606 |

```

FILE: [src/pages/admin/badges/BadgeSpotlightManager.tsx](#)

TYPE: .tsx | LINES: 1-237 | SHA256: f18f000dcb778d94db82b32806efb9e19f71907a099fdcd384a595a53b245f1b

```

1 | // Task 151.3: Badge Spotlight Manager page
2 | // Requirement 134.2: Admin configures spotlight schedule
3 |
4 | import { useForm } from "react-hook-form";
5 | import { zodResolver } from "@hookform/resolvers/zod";
6 | import { Card } from "@components/ui/card";
7 | import { Button } from "@components/ui/button";
8 | import { Badge } from "@components/ui/badge";
9 | import { Sparkles, Calendar, Loader2 } from "lucide-react";
10 | import { useAuth } from "@hooks/useAuth";
11 | import MondayWeekPicker from "@components/shared/MondayWeekPicker";
12 | import {
13 |   badgeSpotlightScheduleSchema,
14 |   type BadgeSpotlightSchedule,
15 | } from "@lib/schemas/badgeSpotlight";
16 | import { z } from "zod";
17 | import {
18 |   useBadgeSpotlightSchedule,
19 |   useUpdateBadgeSpotlightSchedule,
20 | } from "@hooks/useTieredBadges";
21 | import {
22 |   Form,
23 |   FormField,
24 |   FormItem,
25 |   FormLabel,
26 |   FormControl,
27 |   FormMessage,
28 | } from "@components/ui/form";
29 | import {
30 |   Select,
31 |   SelectContent,
32 |   SelectItem,
33 |   SelectTrigger,
34 |   SelectValue,
35 | } from "@components/ui/select";
36 |
37 | const BADGE_CATEGORIES = [
38 |   "streak",
39 |   "academic",
40 |   "engagement",
41 |   "habit",
42 |   "blooms",
43 |   "team",
44 | ];
45 |
46 | const BadgeSpotlightManager = () => {
47 |   const { institutionId } = useAuth();
48 |
49 |   const { data: schedule, isLoading } = useBadgeSpotlightSchedule(
50 |     institutionId ?? undefined
51 |   );
52 |   const updateMutation = useUpdateBadgeSpotlightSchedule();
53 |
54 |   const form = useForm<
55 |     z.input<typeof badgeSpotlightScheduleSchema>,
56 |     unknown,
57 |     BadgeSpotlightSchedule
58 |   >({
59 |     resolver: zodResolver(badgeSpotlightScheduleSchema),
60 |     defaultValues: {
61 |       week_start: "",
62 |       category: "",
63 |       is_manual: true,
64 |     },
65 |   });
66 |
67 |   const handleSchedule = (data: BadgeSpotlightSchedule) => {
68 |     if (!institutionId) return;
69 |     updateMutation.mutate(
70 |       { institutionId, ...data },
71 |       {
72 |         onSuccess: () => {
73 |           form.reset();
74 |         },
75 |       }

```

```

76 |   });
77 | };
78 |
79 | return (
80 |   <div className="space-y-6">
81 |     <div className="flex items-center gap-2">
82 |       <Sparkles className="h-5 w-5 text-purple-500" />
83 |       <h1 className="text-2xl font-bold tracking-tight">Badge Spotlight</h1>
84 |     </div>
85 |
86 |     {/ * Schedule Form */}
87 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
88 |       <h2 className="text-sm font-bold mb-4">Schedule Spotlight</h2>
89 |       <Form {...form}>
90 |         <form
91 |           onSubmit={form.handleSubmit(handleSchedule)}
92 |           className="space-y-4"
93 |         >
94 |           <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
95 |             <FormField
96 |               control={form.control}
97 |               name="week_start"
98 |               render={({ field }) => (
99 |                 <FormItem>
100 |                   <FormLabel>Week Start (Monday)</FormLabel>
101 |                   <FormControl>
102 |                     <MondayWeekPicker
103 |                       value={field.value ? new Date(field.value) : null}
104 |                       onChange={(date: Date) => {
105 |                         const dateStr = date.toISOString().split("T")[0];
106 |                         field.onChange(dateStr);
107 |                       }}
108 |                     />
109 |                   </FormControl>
110 |                   <FormMessage />
111 |                 </FormItem>
112 |               )}
113 |             />
114 |             <FormField
115 |               control={form.control}
116 |               name="category"
117 |               render={({ field }) => (
118 |                 <FormItem>
119 |                   <FormLabel>Badge Category</FormLabel>
120 |                   <FormControl>
121 |                     <Select
122 |                       value={field.value}
123 |                       onChange={field.onChange}
124 |                     >
125 |                       <SelectTrigger>
126 |                         <SelectValue placeholder="Select category..." />
127 |                       </SelectTrigger>
128 |                       <SelectContent>
129 |                         {BADGE_CATEGORIES.map((cat) => (
130 |                           <SelectItem key={cat} value={cat}>
131 |                             {cat.charAt(0).toUpperCase() + cat.slice(1)}
132 |                           </SelectItem>
133 |                         ))}
134 |                       </SelectContent>
135 |                     </Select>
136 |                   </FormControl>
137 |                   <FormMessage />
138 |                 </FormItem>
139 |               )}
140 |             />
141 |           </div>
142 |           <Button
143 |             type="submit"
144 |             disabled={updateMutation.isPending}
145 |             variant="tactile"
146 |           >
147 |             {updateMutation.isPending && (
148 |               <Loader2 className="h-4 w-4 animate-spin" />
149 |             )}
150 |             Schedule
151 |           </Button>
152 |         </form>
153 |       </Form>
154 |     </Card>
155 |
156 |     {/ * Category Preview */}
157 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
158 |       <h2 className="text-sm font-bold mb-4">
159 |         Badge Categories & Tier Thresholds
160 |       </h2>
161 |       <div className="grid grid-cols-2 md:grid-cols-3 gap-3">
162 |         {BADGE_CATEGORIES.map((cat) => (
163 |           <div
164 |             key={cat}
165 |             className="p-3 rounded-lg border border-slate-200 hover:bg-slate-50 transition-colors"
166 |           >
167 |             <p className="text-sm font-semibold capitalize">{cat}</p>
168 |             <div className="flex gap-1 mt-2">
169 |               <Badge className="text-[10px] bg-amber-100 text-amber-700 border-amber-300">
170 |                 Bronze
171 |               </Badge>
172 |               <Badge className="text-[10px] bg-gray-100 text-gray-700 border-gray-300">
173 |                 Silver
174 |               </Badge>
175 |               <Badge className="text-[10px] bg-yellow-100 text-yellow-700 border-yellow-300">
176 |                 Gold
177 |               </Badge>
178 |             </div>
179 |           </div>

```

```

180     )}}
181   </div>
182 </Card>
183
184 {/* Schedule Calendar View */}
185 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
186   <div
187     className="px-6 py-4"
188     style={{
189       background: "var(--brand-gradient)",
190     }}
191   >
192     <div className="flex items-center gap-2">
193       <Calendar className="h-5 w-5 text-white" />
194       <h2 className="text-lg font-bold tracking-tight text-white">
195         Upcoming Schedule
196       </h2>
197     </div>
198   </div>
199   <div className="p-4">
200     {isLoading ? (
201       <div className="flex justify-center p-8">
202         <Loader2 className="h-6 w-6 animate-spin text-blue-500" />
203       </div>
204     ) : !schedule || schedule.length === 0 ? (
205       <p className="text-sm text-gray-500 text-center py-8">
206         No spotlight schedule yet. Auto-rotation will apply.
207       </p>
208     ) : (
209       <div className="space-y-2">
210         {schedule.map((entry) => (
211           <div
212             key={entry.id}
213             className="flex items-center justify-between p-3 rounded-lg hover:bg-slate-50"
214           >
215             <div>
216               <p className="text-sm font-semibold capitalize">
217                 {entry.category}
218               </p>
219               <p className="text-xs text-gray-500">
220                 Week of {entry.week_start}
221               </p>
222             </div>
223             <Badge variant="outline" className="text-xs">
224               {entry.is_manual ? "Manual" : "Auto"}
225             </Badge>
226           </div>
227         ))}
228       </div>
229     )}
230   </div>
231 </Card>
232 </div>
233 );
234 };
235
236 export default BadgeSpotlightManager;

```

FILE: src/pages/admin/bonus-events/columns.tsx

TYPE: .tsx | LINES: 1-158 | SHA256: 8cd83c27b32e90118ba9d0ab943c467ac19c6c95db986d66ce3af93fc65ade7f

[illegible]

```

43 | header: ({ column }) => (
44 |   <Button
45 |     variant="ghost"
46 |     size="sm"
47 |     className="-ms-3"
48 |     onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
49 |   >
50 |     Name
51 |     <ArrowUpDown className="h-4 w-4" />
52 |   </Button>
53 | ),
54 | cell: ({ row }) => (
55 |   <span className="font-medium">{row.getValue("name")}</span>
56 | ),
57 | },
58 | {
59 |   accessorKey: "xp_multiplier",
60 |   header: "Multiplier",
61 |   cell: ({ row }) => (
62 |     <span className="font-medium text-amber-600">
63 |       {row.getValue<number>("xp_multiplier")}x
64 |     </span>
65 |   ),
66 | },
67 | {
68 |   accessorKey: "starts_at",
69 |   header: ({ column }) => (
70 |     <Button
71 |       variant="ghost"
72 |       size="sm"
73 |       className="-ms-3"
74 |       onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
75 |     >
76 |       Start Date
77 |       <ArrowUpDown className="h-4 w-4" />
78 |     </Button>
79 |   ),
80 |   cell: ({ row }) => {
81 |     const val = row.getValue<string | null>("starts_at");
82 |     return (
83 |       <span className="text-gray-500">
84 |         {val ? format(new Date(val), "MMM d, yyyy h:mm a") : "-"}
85 |       </span>
86 |     );
87 |   },
88 | },
89 | {
90 |   accessorKey: "ends_at",
91 |   header: ({ column }) => (
92 |     <Button
93 |       variant="ghost"
94 |       size="sm"
95 |       className="-ms-3"
96 |       onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
97 |     >
98 |       End Date
99 |       <ArrowUpDown className="h-4 w-4" />
100 |    </Button>
101 |  ),
102 |  cell: ({ row }) => {
103 |    const val = row.getValue<string | null>("ends_at");
104 |    return (
105 |      <span className="text-gray-500">
106 |        {val ? format(new Date(val), "MMM d, yyyy h:mm a") : "-"}
107 |      </span>
108 |    );
109 |  },
110 | },
111 | {
112 |   id: "status",
113 |   header: "Status",
114 |   cell: ({ row }) => {
115 |     const status = deriveStatus(row.original);
116 |     return (
117 |       <Badge variant="outline" className={statusBadgeStyles[status]}>
118 |         {status}
119 |       </Badge>
120 |     );
121 |   },
122 | },
123 | {
124 |   id: "actions",
125 |   header: "",
126 |   cell: ({ row }) => {
127 |     const event = row.original;
128 |     return (
129 |       <DropdownMenu>
130 |         <DropdownMenuTrigger asChild>
131 |           <Button variant="ghost" size="icon-xs">
132 |             <MoreHorizontal className="h-4 w-4" />
133 |             <span className="sr-only">Open menu</span>
134 |           </Button>
135 |         </DropdownMenuTrigger>
136 |         <DropdownMenuContent align="end">
137 |           <DropdownMenuItem onClick={() => onEdit(event)}>
138 |             <Pencil className="h-4 w-4" />
139 |             Edit
140 |           </DropdownMenuItem>
141 |           {event.is_active && (
142 |             <DropdownMenuItem
143 |               variant="destructive"
144 |               onClick={() => onDeactivate(event)}
145 |             >
146 |               <XCircle className="h-4 w-4" />

```

FILE: src/pages/admin/BonusXPEventManager.tsx

[illegible]

```

89 | const updateMutation = useUpdateBonusEvent(editingEvent?.id ?? "");
90 | const isPending = createMutation.isPending || updateMutation.isPending;
91 |
92 | const form = useForm<BonusEventFormValues>({
93 |   resolver: zodResolver(bonusEventFormSchema),
94 |   defaultValues: {
95 |     name: "",
96 |     event_type: "bonus_xp",
97 |     xp_multiplier: 2,
98 |     starts_at: "",
99 |     ends_at: "",
100 |     is_active: true,
101 |   },
102 | });
103 |
104 | // Reset form when dialog opens with edit data or fresh defaults
105 | const handleOpenChange = useCallback(
106 |   (isOpen: boolean) => {
107 |     if (isOpen && editingEvent) {
108 |       form.reset({
109 |         name: editingEvent.name,
110 |         event_type: editingEvent.event_type,
111 |         xp_multiplier: editingEvent.xp_multiplier,
112 |         starts_at: editingEvent.starts_at ?? "",
113 |         ends_at: editingEvent.ends_at ?? "",
114 |         is_active: editingEvent.is_active,
115 |       });
116 |     } else if (isOpen) {
117 |       form.reset({
118 |         name: "",
119 |         event_type: "bonus_xp",
120 |         xp_multiplier: 2,
121 |         starts_at: "",
122 |         ends_at: "",
123 |         is_active: true,
124 |       });
125 |     }
126 |     onOpenChange(isOpen);
127 |   },
128 |   [editingEvent, form, onOpenChange]
129 | );
130 |
131 | const onSubmit = (data: BonusEventFormValues) => {
132 |   // Overlap validation: check against active events (exclude current if editing)
133 |   if (data.is_active) {
134 |     const overlapping = existingEvents.find(
135 |       (ev) =>
136 |         ev.is_active &&
137 |         ev.id !== editingEvent?.id &&
138 |         rangesOverlap(
139 |           data.starts_at,
140 |           data.ends_at,
141 |           ev.starts_at ?? "",
142 |           ev.ends_at ?? ""
143 |         )
144 |     );
145 |     if (overlapping) {
146 |       toast.error(
147 |         `Date range overlaps with "${overlapping.name}". Only one active event allowed per time period.`
148 |       );
149 |       return;
150 |     }
151 |   }
152 |
153 |   if (isEditMode) {
154 |     updateMutation.mutate(data, {
155 |       onSuccess: () => {
156 |         toast.success("Bonus event updated");
157 |         onOpenChange(false);
158 |       },
159 |       onError: (err) => toast.error(err.message),
160 |     });
161 |   } else {
162 |     createMutation.mutate(data, {
163 |       onSuccess: () => {
164 |         toast.success("Bonus event created");
165 |         onOpenChange(false);
166 |       },
167 |       onError: (err) => toast.error(err.message),
168 |     });
169 |   }
170 | };
171 |
172 | return (
173 |   <Dialog open={open} onOpenChange={handleOpenChange}>
174 |     <DialogContent className="sm:max-w-md">
175 |       <DialogHeader>
176 |         <DialogTitle>
177 |           {isEditMode ? "Edit Bonus XP Event" : "Create Bonus XP Event"}
178 |         </DialogTitle>
179 |         <DialogDescription>
180 |           {isEditMode
181 |             ? "Update the bonus XP event details."
182 |             : "Create a time-bounded XP multiplier event for students."}
183 |         </DialogDescription>
184 |       </DialogHeader>
185 |
186 |       <Form {...form}>
187 |         <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
188 |           <FormField>
189 |             control={form.control}
190 |             name="name"
191 |             render={({ field }) => (
192 |               <FormItem>

```



```

193         <FormLabel>Name</FormLabel>
194         <FormControl>
195             <Input placeholder="e.g. Double XP Weekend" {...field} />
196         </FormControl>
197         <FormMessage />
198     </FormItem>
199 })
200 />
201
202 <FormField
203     control={form.control}
204     name="xp_multiplier"
205     render={({ field }) => (
206         <FormItem>
207             <FormLabel>Multiplier</FormLabel>
208             <FormControl>
209                 <Input
210                     type="number"
211                     min={1}
212                     step={0.5}
213                     placeholder="2"
214                     {...field}
215                     onChange={(e) =>
216                         field.onChange(parseFloat(e.target.value) || 0)
217                     }
218                 />
219             </FormControl>
220             <FormMessage />
221         </FormItem>
222     )}
223 />
224
225 <FormField
226     control={form.control}
227     name="starts_at"
228     render={({ field }) => (
229         <FormItem>
230             <FormLabel>Start Date & Time</FormLabel>
231             <FormControl>
232                 <Input
233                     type="datetime-local"
234                     value={field.value ? isoToDatetimeLocal(field.value) : ""}
235                     onChange={(e) => {
236                         const val = e.target.value;
237                         field.onChange(val ? datetimeLocalToISO(val) : "");
238                     }}
239                 />
240             </FormControl>
241             <FormMessage />
242         </FormItem>
243     )}
244 />
245
246 <FormField
247     control={form.control}
248     name="ends_at"
249     render={({ field }) => (
250         <FormItem>
251             <FormLabel>End Date & Time</FormLabel>
252             <FormControl>
253                 <Input
254                     type="datetime-local"
255                     value={field.value ? isoToDatetimeLocal(field.value) : ""}
256                     onChange={(e) => {
257                         const val = e.target.value;
258                         field.onChange(val ? datetimeLocalToISO(val) : "");
259                     }}
260                 />
261             </FormControl>
262             <FormMessage />
263         </FormItem>
264     )}
265 />
266
267 <FormField
268     control={form.control}
269     name="is_active"
270     render={({ field }) => (
271         <FormItem className="flex items-center gap-3">
272             <FormControl>
273                 <input
274                     type="checkbox"
275                     checked={field.value}
276                     onChange={field.onChange}
277                     className="h-4 w-4 rounded border-gray-300 text-blue-600 focus:ring-blue-500"
278                 />
279             </FormControl>
280             <FormLabel className="!mt-0">Active</FormLabel>
281             <FormMessage />
282         </FormItem>
283     )}
284 />
285
286 <div className="flex justify-end gap-2 pt-2">
287     <Button
288         type="button"
289         variant="outline"
290         onClick={() => onOpenChange(false)}
291         disabled={isPending}
292     >
293         Cancel
294     </Button>
295     <Button type="submit" disabled={isPending} variant="tactile">
296         {isPending && <Loader2 className="h-4 w-4 animate-spin" />}

```

[illegible]

FILE: src/pages/admin/calendar/AcademicCalendarManager.tsx

TYPE: .tsx | LINES: 1-239 | SHA256: c213db05ac159fe6ccdd461be9ebbf90fc8f53f214b48e79cbd6f9caec0135b3

```

1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import { Card } from "@components/ui/card";
6 | import { Button } from "@components/ui/button";
7 | import { Input } from "@components/ui/input";
8 | import {
9 |   Select,
10 |   SelectContent,
11 |   SelectItem,
12 |   SelectTrigger,
13 |   SelectValue,
14 | } from "@components/ui/select";
15 | import {
16 |   Form,
17 |   FormField,
18 |   FormItem,
19 |   FormLabel,
20 |   FormControl,
21 |   FormMessage,
22 | } from "@components/ui/form";
23 | import { Badge } from "@components/ui/badge";
24 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
25 | import { Shimmer } from "@design-system";
26 | import { Plus, Loader2, Trash2, CalendarDays } from "lucide-react";
27 | import { toast } from "sonner";
28 | import {
29 |   useAcademicCalendarEvents,
30 |   useCreateAcademicEvent,
31 |   useDeleteAcademicEvent,
32 | } from "@hooks/useAcademicCalendar";
33 |
34 | const schema = z.object({
35 |   title: z.string().min(1, "Title is required"),
36 |   event_type: z.string().min(1, "Type is required"),
37 |   start_date: z.string().min(1, "Start date is required"),
38 |   end_date: z.string().optional(),
39 | });
40 |
41 | type FormData = z.infer<typeof schema>;
42 |
43 | const EVENT_TYPES = [
44 |   "semester_start",
45 |   "semester_end",
46 |   "exam_period",
47 |   "holiday",
48 |   "registration",
49 |   "other",
50 | ];
51 |
52 | const AcademicCalendarManager = () => {
53 |   const { data: events = [], isLoading } = useAcademicCalendarEvents();
54 |   const createMutation = useCreateAcademicEvent();
55 |   const deleteMutation = useDeleteAcademicEvent();
56 |   const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
57 |
58 |   const form = useForm<FormData>({
59 |     resolver: zodResolver(schema),
60 |     defaultValues: { title: "", event_type: "", start_date: "", end_date: "" },
61 |   });
62 |
63 |   const onSubmit = (data: FormData) => {
64 |     createMutation.mutate(data, {
65 |       onSuccess: () => {
66 |         toast.success("Event created");
67 |         form.reset();
68 |       },
69 |       onError: (err) => toast.error(err.message),
70 |     });
71 |   };
72 |
73 |   return (
74 |     <div className="space-y-6">
75 |       <h1 className="text-2xl font-bold tracking-tight">Academic Calendar</h1>
76 |
77 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
78 |         <div
79 |           className="px-6 py-4 flex items-center gap-2"
80 |           style={{
81 |             background: "var(--brand-gradient)",
82 |           }}
83 |         >
84 |           <CalendarDays className="h-5 w-5 text-white" />
85 |           <h2 className="text-lg font-bold tracking-tight text-white">
86 |             Events
87 |           </h2>
88 |         </div>
89 |         <div className="p-6">
90 |           {isLoading ? (
91 |             <Shimmer className="h-32 rounded-lg" />
92 |           ) : events.length === 0 ? (
93 |             <p className="text-sm text-slate-400 text-center py-6">
94 |               No events yet.
95 |             </p>
96 |           ) : (
97 |             <div className="space-y-2">
98 |               {events.map((e) => (
99 |                 <div

```

```

100         key={e.id}
101         className="flex items-center justify-between p-3 rounded-lg border border-slate-100 hover:bg
102     >
103     <div>
104         <span className="text-sm font-medium">{e.title}</span>
105         <Badge variant="outline" className="ms-2 text-xs">
106             {e.event_type}
107         </Badge>
108     </div>
109     <div className="flex items-center gap-3">
110         <span className="text-xs text-slate-400">
111             {e.start_date}
112             {e.end_date ? ` - ${e.end_date}` : ""}
113         </span>
114         <Button
115             variant="ghost"
116             size="sm"
117             onClick={() => setDeleteTarget(e.id)}
118             className="h-7 w-7 p-0 text-slate-400 hover:text-red-500"
119         >
120             <Trash2 className="h-3.5 w-3.5" />
121         </Button>
122     </div>
123 </div>
124 </div>
125 </div>
126 </div>
127 </div>
128 </Card>
129
130 <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
131     <h2 className="text-lg font-bold tracking-tight mb-4">Add Event</h2>
132     <Form {...form}>
133         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
134             <FormField
135                 control={form.control}
136                 name="title"
137                 render={({ field }) => (
138                     <FormItem>
139                         <FormLabel>Title</FormLabel>
140                         <FormControl>
141                             <Input {...field} />
142                         </FormControl>
143                         <FormMessage />
144                     </FormItem>
145                 )}
146             />
147             <div className="grid grid-cols-3 gap-4">
148                 <FormField
149                     control={form.control}
150                     name="event_type"
151                     render={({ field }) => (
152                         <FormItem>
153                             <FormLabel>Type</FormLabel>
154                             <FormControl>
155                                 <Select
156                                     value={field.value}
157                                     onChange={field.onChange}
158                                 >
159                                     <SelectTrigger className="bg-white">
160                                         <SelectValue placeholder="Select type" />
161                                     </SelectTrigger>
162                                     <SelectContent>
163                                         {EVENT_TYPES.map((t) => (
164                                             <SelectItem key={t} value={t}>
165                                                 {t.replace(/_/g, " ")}
166                                             </SelectItem>
167                                         ))}
168                                     </SelectContent>
169                                 </Select>
170                             </FormControl>
171                             <FormMessage />
172                         </FormItem>
173                     )}
174                 />
175                 <FormField
176                     control={form.control}
177                     name="start_date"
178                     render={({ field }) => (
179                         <FormItem>
180                             <FormLabel>Start</FormLabel>
181                             <FormControl>
182                                 <Input type="date" {...field} />
183                             </FormControl>
184                             <FormMessage />
185                         </FormItem>
186                     )}
187                 />
188                 <FormField
189                     control={form.control}
190                     name="end_date"
191                     render={({ field }) => (
192                         <FormItem>
193                             <FormLabel>End (optional)</FormLabel>
194                             <FormControl>
195                                 <Input type="date" {...field} />
196                             </FormControl>
197                             <FormMessage />
198                         </FormItem>
199                     )}
200                 />
201             </div>
202             <Button
203                 type="submit"

```

```

204         disabled={createMutation.isPending}
205         variant="tactile"
206     >
207         {createMutation.isPending ? (
208             <Loader2 className="h-4 w-4 animate-spin" />
209         ) : (
210             <Plus className="h-4 w-4" />
211         )}{" "}
212         Add Event
213     </Button>
214 </form>
215 </Form>
216 </Card>
217
218 <ConfirmDialog
219     open={!deleteTarget}
220     onOpenChange={ (o: boolean) => !o && setDeleteTarget(null)}
221     title="Delete event?"
222     description="This will permanently remove this calendar event."
223     onConfirm={() => {
224         if (deleteTarget)
225             deleteMutation.mutate(deleteTarget, {
226                 onSuccess: () => {
227                     toast.success("Deleted");
228                     setDeleteTarget(null);
229                 },
230             }
231         }
232     }
233     isPending={deleteMutation.isPending}
234 >
235 </div>
236 );
237 };
238 export default AcademicCalendarManager;
239

```

FILE: [src/pages/admin/competency-frameworks/CompetencyFrameworkManager.tsx](#)

TYPE: .tsx | LINES: 1-369 | SHA256: 89e85368b074e38c9782c352485d72650889dd78afc909cd2ebc932918284a2e

```

1 // Task 115.1: Competency Framework Manager page
2
3 import { useState } from "react";
4 import { useForm } from "react-hook-form";
5 import { zodResolver } from "@hookform/resolvers/zod";
6 import { z } from "zod";
7 import { Card } from "@components/ui/card";
8 import { Button } from "@components/ui/button";
9 import { Input } from "@components/ui/input";
10 import {
11     Select,
12     SelectContent,
13     SelectItem,
14     SelectTrigger,
15     SelectValue,
16 } from "@components/ui/select";
17 import {
18     Form,
19     FormField,
20     FormItem,
21     FormLabel,
22     FormControl,
23     FormMessage,
24 } from "@components/ui/form";
25 import { Shimmer } from "@design-system";
26 import CompetencyTree from "@components/shared/CompetencyTree";
27 import { Plus, Loader2, Layers, Link2 } from "lucide-react";
28 import { toast } from "sonner";
29 import { useAuth } from "@hooks/useAuth";
30 import {
31     useCompetencyFrameworks,
32     useCreateCompetencyFramework,
33     useImportCompetencyCSV,
34     useCompetencyItems,
35     useCompetencyOutcomeMappings,
36 } from "@hooks/useCompetencyFrameworks";
37 import { useILOs } from "@hooks/useILOs";
38 import { usePLOs } from "@hooks/usePLOs";
39 import { supabase } from "@lib/supabase";
40 import { useQueryClient } from "@tanstack/react-query";
41
42 const schema = z.object({
43     name: z.string().min(1, "Name is required"),
44     version: z.string().min(1, "Version is required"),
45     source: z.string().optional(),
46 });
47
48 const CompetencyFrameworkManager = () => {
49     const { profile } = useAuth();
50     const institutionId = profile?.institution_id;
51     const queryClient = useQueryClient();
52     const { data: frameworks = [], isLoading } =
53         useCompetencyFrameworks(institutionId);
54     const createMutation = useCreateCompetencyFramework();
55     const importMutation = useImportCompetencyCSV();
56     const [selectedFramework, setSelectedFramework] = useState<string | null>(
57         null
58     );
59     const { data: items = [] } = useCompetencyItems(
60         selectedFramework ?? undefined
61     );
62     const { data: mappings = [] } = useCompetencyOutcomeMappings(
63         selectedFramework ?? undefined
64     );

```

```

65 | const { data: ilosResult } = useILOS();
66 | const { data: plosResult } = usePLOS();
67 | const ilos = ilosResult?.data ?? [];
68 | const plos = plosResult?.data ?? [];
69 | const [mappingIndicatorId, setMappingIndicatorId] = useState<string>("");
70 | const [mappingOutcomeId, setMappingOutcomeId] = useState<string>("");
71 |
72 | const mappedItemIds = new Set(mappings.map((m) => m.competency_item_id));
73 | const indicators = items.filter((i) => i.level === "indicator");
74 |
75 | const form = useForm<z.infer<typeof schema>>({
76 |   resolver: zodResolver(schema),
77 |   defaultValues: { name: "", version: "1.0", source: "" },
78 | });
79 |
80 | const onSubmit = (data: z.infer<typeof schema>) => {
81 |   if (!institutionId) return;
82 |   createMutation.mutate(
83 |     { ...data, institution_id: institutionId },
84 |     {
85 |       onSuccess: () => {
86 |         toast.success("Framework created");
87 |         form.reset();
88 |       },
89 |       onError: (err) => toast.error(err.message),
90 |     }
91 |   );
92 | };
93 |
94 | const handleCSVImport = async (e: React.ChangeEvent<HTMLInputElement>) => {
95 |   const file = e.target.files?.[0];
96 |   if (!file || !selectedFramework) return;
97 |   const text = await file.text();
98 |   importMutation.mutate(
99 |     { framework_id: selectedFramework, csv_content: text },
100 |     {
101 |       onSuccess: (result) =>
102 |         toast.success(`Imported ${result.imported} items`),
103 |       onError: (err) => toast.error(err.message),
104 |     }
105 |   );
106 | };
107 |
108 | const handleAddMapping = async () => {
109 |   if (!mappingIndicatorId || !mappingOutcomeId) return;
110 |   const { error } = await supabase
111 |     .from("competency_outcome_mappings")
112 |     .insert({
113 |       competency_item_id: mappingIndicatorId,
114 |       outcome_id: mappingOutcomeId,
115 |     }) as never;
116 |   if (error) {
117 |     toast.error(error.message);
118 |   } else {
119 |     toast.success("Mapping added");
120 |     setMappingIndicatorId("");
121 |     setMappingOutcomeId("");
122 |     queryClient.invalidateQueries({
123 |       queryKey: ["competencyOutcomeMappings"],
124 |     });
125 |   }
126 | };
127 |
128 | const outcomeOptions = [
129 |   ...ilos.map((o) => ({ id: o.id, label: `ILO: ${o.title}` })),
130 |   ...plos.map((o) => ({ id: o.id, label: `PLO: ${o.title}` })),
131 | ];
132 |
133 | return (
134 |   <div className="space-y-6">
135 |     <h1 className="text-2xl font-bold tracking-tight">
136 |       Competency Frameworks
137 |     </h1>
138 |
139 |     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
140 |       <div
141 |         className="px-6 py-4 flex items-center gap-2"
142 |         style={{
143 |           background: "var(--brand-gradient)",
144 |         }}
145 |       >
146 |         <Layers className="h-5 w-5 text-white" />
147 |         <h2 className="text-lg font-bold tracking-tight text-white">
148 |           Frameworks
149 |         </h2>
150 |       </div>
151 |       <div className="p-6">
152 |         {isLoading ? (
153 |           <Shimmer className="h-32 rounded-lg" />
154 |         ) : frameworks.length === 0 ? (
155 |           <p className="text-sm text-slate-400 text-center py-6">
156 |             No frameworks defined yet.
157 |           </p>
158 |         ) : (
159 |           <div className="space-y-2">
160 |             {frameworks.map((fw) => (
161 |               <div
162 |                 key={fw.id}
163 |                 className={`flex items-center justify-between p-3 rounded-lg border cursor-pointer transiti
164 |                   selectedFramework === fw.id
165 |                     ? "border-blue-500 bg-blue-50"
166 |                     : "border-slate-100 hover:bg-slate-50"
167 |                 `}
168 |                 role="button"

```

```

169         tabIndex={0}
170         onClick={() => setSelectedFramework(fw.id)}
171         onKeyDown={(e) => {
172             if (e.key === "Enter" || e.key === " ") {
173                 e.preventDefault();
174                 setSelectedFramework(fw.id);
175             }
176         }}
177     >
178         <div>
179             <span className="text-sm font-medium">{fw.name}</span>
180             <span className="text-xs text-slate-400 ms-2">
181                 v{fw.version}
182             </span>
183             {fw.source && (
184                 <span className="text-xs text-slate-400 ms-2">
185                     {fw.source}
186                 </span>
187             )}
188         </div>
189     </div>
190 )}}
191 </div>
192 )}
193 </div>
194 </Card>
195
196 {selectedFramework && (
197     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
198         <h2 className="text-lg font-bold tracking-tight mb-4">
199             Import Competency Items (CSV)
200         </h2>
201         <p className="text-xs text-slate-500 mb-3">
202             CSV columns: domain_code, domain_title, competency_code,
203             competency_title, indicator_code, indicator_title
204         </p>
205         <div className="flex items-center gap-3">
206             <input
207                 type="file"
208                 accept=".csv"
209                 onChange={handleCSVImport}
210                 className="max-w-sm"
211             />
212             {importMutation.isPending && (
213                 <Loader2 className="h-4 w-4 animate-spin text-blue-600" />
214             )}
215         </div>
216     </Card>
217 )}
218
219 {/* Competency Tree View (Task 115.2) */}
220 {selectedFramework && items.length > 0 && (
221     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
222         <div
223             className="px-6 py-4 flex items-center gap-2"
224             style={{
225                 background: "var(--brand-gradient)",
226             }}
227         >
228             <Layers className="h-5 w-5 text-white" />
229             <h2 className="text-lg font-bold tracking-tight text-white">
230                 Competency Hierarchy
231             </h2>
232         </div>
233         <div className="p-6">
234             <CompetencyTree items={items} mappedItemIds={mappedItemIds} />
235         </div>
236     </Card>
237 )}
238
239 {/* Mapping Interface (Task 115.4) */}
240 {selectedFramework && indicators.length > 0 && (
241     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
242         <h2 className="text-lg font-bold tracking-tight mb-4">
243             <Link2 className="h-4 w-4 inline me-2" />
244             Map Indicator to Outcome
245         </h2>
246         <div className="flex items-end gap-3">
247             <div className="flex-1">
248                 <label
249                     htmlFor="mapping-indicator"
250                     className="text-xs font-medium text-slate-600 mb-1 block"
251                 >
252                     Indicator
253                 </label>
254                 <Select
255                     value={mappingIndicatorId}
256                     onChange={setMappingIndicatorId}
257                 >
258                     <SelectTrigger id="mapping-indicator" className="bg-white">
259                         <SelectValue placeholder="Select indicator" />
260                     </SelectTrigger>
261                     <SelectContent>
262                         {indicators.map((ind) => (
263                             <SelectItem key={ind.id} value={ind.id}>
264                                 {ind.code} – {ind.title}
265                             </SelectItem>
266                         ))}
267                     </SelectContent>
268                 </Select>
269             </div>
270             <div className="flex-1">
271                 <label
272                     htmlFor="mapping-outcome"

```

```

273 |         className="text-xs font-medium text-slate-600 mb-1 block"
274 |     >
275 |         Outcome (ILO/PL0)
276 |     </label>
277 |     <Select
278 |         value={mappingOutcomeId}
279 |         onValueChange={setMappingOutcomeId}
280 |     >
281 |         <SelectTrigger id="mapping-outcome" className="bg-white">
282 |             <SelectValue placeholder="Select outcome" />
283 |         </SelectTrigger>
284 |         <SelectContent>
285 |             {outcomeOptions.map((o) => (
286 |                 <SelectItem key={o.id} value={o.id}>
287 |                     {o.label}
288 |                 </SelectItem>
289 |             ))}
290 |         </SelectContent>
291 |     </Select>
292 | </div>
293 | <Button
294 |     onClick={handleAddMapping}
295 |     disabled={!mappingIndicatorId || !mappingOutcomeId}
296 |     variant="tactile"
297 | >
298 |     <Plus className="h-4 w-4" /> Map
299 | </Button>
300 | </div>
301 | </Card>
302 | ))
303 |
304 | <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
305 |     <h2 className="text-lg font-bold tracking-tight mb-4">Add Framework</h2>
306 |     <Form {...form}>
307 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
308 |             <div className="grid grid-cols-2 gap-4">
309 |                 <FormField
310 |                     control={form.control}
311 |                     name="name"
312 |                     render={({ field }) => (
313 |                         <FormItem>
314 |                             <FormLabel>Name</FormLabel>
315 |                             <FormControl>
316 |                                 <Input {...field} />
317 |                             </FormControl>
318 |                             <FormMessage />
319 |                         </FormItem>
320 |                     )}
321 |                 />
322 |                 <FormField
323 |                     control={form.control}
324 |                     name="version"
325 |                     render={({ field }) => (
326 |                         <FormItem>
327 |                             <FormLabel>Version</FormLabel>
328 |                             <FormControl>
329 |                                 <Input {...field} />
330 |                             </FormControl>
331 |                             <FormMessage />
332 |                         </FormItem>
333 |                     )}
334 |                 />
335 |             </div>
336 |             <FormField
337 |                 control={form.control}
338 |                 name="source"
339 |                 render={({ field }) => (
340 |                     <FormItem>
341 |                         <FormLabel>Source (optional)</FormLabel>
342 |                         <FormControl>
343 |                             <Input placeholder="e.g. ABET, HEC" {...field} />
344 |                         </FormControl>
345 |                         <FormMessage />
346 |                     </FormItem>
347 |                 )}
348 |             />
349 |             <Button
350 |                 type="submit"
351 |                 disabled={createMutation.isPending}
352 |                 variant="tactile"
353 |             >
354 |                 {createMutation.isPending ? (
355 |                     <Loader2 className="h-4 w-4 animate-spin" />
356 |                 ) : (
357 |                     <Plus className="h-4 w-4" />
358 |                 )}{" "}
359 |                 Create
360 |             </Button>
361 |         </form>
362 |     </Form>
363 | </Card>
364 | </div>
365 | );
366 | };
367 |
368 | export default CompetencyFrameworkManager;
369 |

```


FILE: src/pages/admin/courses/columns.tsx

TYPE: .tsx | LINES: 1-125 | SHA256: 162bb7dda7c5dd2254f7f3d66c2c16c09be646ab05321d8b496cdcb169aab84c

```
1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import {
3 |   ArrowUpDown,
4 |   MoreHorizontal,
5 |   Pencil,
6 |   Users,
7 |   XCircle,
8 | } from "lucide-react";
9 | import { Badge } from "@components/ui/badge";
10 | import { Button } from "@components/ui/button";
11 | import {
12 |   DropdownMenu,
13 |   DropdownMenuContent,
14 |   DropdownMenuItem,
15 |   DropdownMenuTrigger,
16 | } from "@components/ui/dropdown-menu";
17 | import { resolveName } from "@lib/db/resolveName";
18 | import type { CourseWithRelations } from "@hooks/useCourses";
19 | import type { Course } from "@types/app";
20 |
21 | // % % % Column factory - accepts onEdit, onDeactivate, and onManageEnrollment callbacks %
22 |
23 | export const createColumns = (
24 |   onEdit: (course: Course) => void,
25 |   onDeactivate: (course: Course) => void,
26 |   onManageEnrollment?: (course: Course) => void
27 | ): ColumnDef<CourseWithRelations>[] => [
28 |   {
29 |     accessorKey: "name",
30 |     header: ({ column }) => (
31 |       <Button
32 |         variant="ghost"
33 |         size="sm"
34 |         className="-ms-3"
35 |         onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
36 |       >
37 |         Name
38 |         <ArrowUpDown className="h-4 w-4" />
39 |       </Button>
40 |     ),
41 |     cell: ({ row }) => (
42 |       <span className="font-medium">{row.getValue("name")}</span>
43 |     ),
44 |   },
45 |   {
46 |     accessorKey: "code",
47 |     header: "Code",
48 |   },
49 |   {
50 |     id: "program",
51 |     header: "Program",
52 |     cell: ({ row }) => (
53 |       <span className="text-gray-500 truncate max-w-[160px] inline-block">
54 |         {resolveName(row.original.programs?.name)}
55 |       </span>
56 |     ),
57 |   },
58 |   {
59 |     id: "teacher",
60 |     header: "Teacher",
61 |     cell: ({ row }) => (
62 |       <span className="text-gray-500 truncate max-w-[160px] inline-block">
63 |         {resolveName(row.original.teacher?.full_name)}
64 |       </span>
65 |     ),
66 |   },
67 |   {
68 |     accessorKey: "is_active",
69 |     header: "Status",
70 |     cell: ({ row }) => {
71 |       const isActive = row.getValue("is_active") as boolean;
72 |       return (
73 |         <Badge
74 |           variant="outline"
75 |           className={
76 |             isActive
77 |               ? "bg-green-50 text-green-600 border-green-200"
78 |               : "bg-red-50 text-red-600 border-red-200"
79 |           }
80 |         >
81 |           {isActive ? "Active" : "Inactive"}
82 |         </Badge>
83 |       );
84 |     },
85 |   },
86 |   {
87 |     id: "actions",
88 |     header: "",
89 |     cell: ({ row }) => {
90 |       const course = row.original;
91 |       return (
92 |         <DropdownMenu>
93 |           <DropdownMenuTrigger asChild>
94 |             <Button variant="ghost" size="icon-xs">
95 |               <MoreHorizontal className="h-4 w-4" />
96 |               <span className="sr-only">Open menu</span>
97 |             </Button>
98 |           </DropdownMenuTrigger>
99 |           <DropdownMenuContent align="end">
100 |             <DropdownMenuItem onClick={() => onEdit(course)}>
101 |               <Pencil className="h-4 w-4" />
```

```

102 |         Edit
103 |       </DropdownMenuItem>
104 |     {onManageEnrollment && (
105 |       <DropdownMenuItem onClick={() => onManageEnrollment(course)}>
106 |         <Users className="h-4 w-4" />
107 |         Manage Enrollment
108 |       </DropdownMenuItem>
109 |     )}
110 |     {course.is_active && (
111 |       <DropdownMenuItem
112 |         variant="destructive"
113 |         onClick={() => onDeactivate(course)}
114 |       >
115 |         <XCircle className="h-4 w-4" />
116 |         Deactivate
117 |       </DropdownMenuItem>
118 |     )}
119 |   </DropdownMenuContent>
120 | </DropdownMenu>
121 | );
122 | },
123 | },
124 | ];
125 |

```

FILE: src/pages/admin/courses/CourseEnrollmentPage.tsx

TYPE: .tsx | LINES: 1-265 | SHA256: df574e1585cd8e6c8a86cf478841492cfaf63e308f720e67374b37b62aea9e70

```

1 | import { useState, useMemo } from "react";
2 | import { useParams, useNavigate } from "react-router-dom";
3 | import { toast } from "sonner";
4 | import { ArrowLeft, Loader2, UserPlus } from "lucide-react";
5 | import { createEnrollmentColumns } from "@/enrollmentColumns";
6 | import { DataTable } from "@/components/shared/DataTable";
7 | import { ConfirmDialog } from "@/components/shared/ConfirmDialog";
8 | import { useCourse } from "@/hooks/useCourses";
9 | import {
10 |   useEnrollments,
11 |   useEnrollStudent,
12 |   useUnenrollStudent,
13 |   type EnrollmentWithProfile,
14 | } from "@/hooks/useEnrollments";
15 | import { useCourseSections } from "@/hooks/useCourseSections";
16 | import { useUsers } from "@/hooks/useUsers";
17 | import { Button } from "@/components/ui/button";
18 | import { Card } from "@/components/ui/card";
19 | import {
20 |   Dialog,
21 |   DialogContent,
22 |   DialogDescription,
23 |   DialogFooter,
24 |   DialogHeader,
25 |   DialogTitle,
26 | } from "@/components/ui/dialog";
27 | import {
28 |   Select,
29 |   SelectContent,
30 |   SelectItem,
31 |   SelectTrigger,
32 |   SelectValue,
33 | } from "@/components/ui/select";
34 |
35 | const CourseEnrollmentPage = () => {
36 |   const { courseId } = useParams<{ courseId: string }>();
37 |   const navigate = useNavigate();
38 |
39 |   const [enrollDialogOpen, setEnrollDialogOpen] = useState(false);
40 |   const [selectedStudentId, setSelectedStudentId] = useState<string>("");
41 |   const [selectedSectionId, setSelectedSectionId] = useState<string>("");
42 |   const [unenrollTarget, setUnenrollTarget] =
43 |     useState<EnrollmentWithProfile | null>(null);
44 |   const [page, setPage] = useState(1);
45 |
46 |   const { data: course, isLoading: courseLoading } = useCourse(courseId);
47 |   const {
48 |     data: paginatedEnrollments,
49 |     isLoading: enrollmentsLoading,
50 |     isFetching: enrollmentsFetching,
51 |   } = useEnrollments(courseId, { page });
52 |   const enrollments = useMemo(
53 |     () => paginatedEnrollments?.data ?? [],
54 |     [paginatedEnrollments?.data]
55 |   );
56 |   const { data: paginatedStudents } = useUsers({ role: "student" });
57 |   const students = useMemo(
58 |     () => paginatedStudents?.data ?? [],
59 |     [paginatedStudents?.data]
60 |   );
61 |   const { data: sections } = useCourseSections(courseId);
62 |   const enrollMutation = useEnrollStudent();
63 |   const unenrollMutation = useUnenrollStudent();
64 |
65 |   // Filter out students already enrolled (active or completed) from the enroll dialog
66 |   const availableStudents = useMemo(() => {
67 |     const enrolledIds = new Set(
68 |       enrollments.filter((e) => e.status !== "dropped").map((e) => e.student_id)
69 |     );
70 |     return students.filter((s) => s.is_active && !enrolledIds.has(s.id));
71 |   }, [students, enrollments]);
72 |
73 |   const columns = createEnrollmentColumns((enrollment) =>
74 |     setUnenrollTarget(enrollment)
75 |   );
76 |

```

```

77 | const handleEnroll = () => {
78 |   if (!selectedStudentId || !courseId) return;
79 |   enrollMutation.mutate(
80 |     {
81 |       student_id: selectedStudentId,
82 |       course_id: courseId,
83 |       section_id:
84 |         selectedSectionId && selectedSectionId !== "none"
85 |         ? selectedSectionId
86 |         : undefined,
87 |     },
88 |     {
89 |       onSuccess: () => {
90 |         toast.success("Student enrolled successfully");
91 |         setEnrollDialogOpen(false);
92 |         setSelectedStudentId("");
93 |         setSelectedSectionId("");
94 |       },
95 |       onError: (err) => toast.error(err.message),
96 |     }
97 |   );
98 | };
99 |
100 | const handleUnenroll = () => {
101 |   if (!unenrollTarget) return;
102 |   unenrollMutation.mutate(unenrollTarget.id, {
103 |     onSuccess: () => {
104 |       toast.success(
105 |         `${
106 |           unenrollTarget.profiles?.full_name ?? "Student"
107 |         } has been unenrolled`
108 |       );
109 |       setUnenrollTarget(null);
110 |     },
111 |     onError: (err) => toast.error(err.message),
112 |   });
113 | };
114 |
115 | return (
116 |   <div className="space-y-6">
117 |     { /* Page Header */ }
118 |     <div className="flex items-center justify-between">
119 |       <div className="flex items-center gap-3">
120 |         <Button
121 |           variant="ghost"
122 |           size="sm"
123 |           onClick={() => navigate("/admin/courses")}
124 |         >
125 |           <ArrowLeft className="h-4 w-4" />
126 |         </Button>
127 |         <h1 className="text-2xl font-bold tracking-tight">
128 |           Course Enrollment
129 |         </h1>
130 |       </div>
131 |       <Button variant="tactile" onClick={() => setEnrollDialogOpen(true)}>
132 |         <UserPlus className="h-4 w-4" /> Enroll Student
133 |       </Button>
134 |     </div>
135 |
136 |     { /* Course Info Card */ }
137 |     { courseLoading ? (
138 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4">
139 |         <div className="flex items-center gap-2 text-gray-400">
140 |           <Loader2 className="h-4 w-4 animate-spin" />
141 |           Loading course info...
142 |         </div>
143 |       </Card>
144 |     ) : course ? (
145 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4">
146 |         <p className="text-lg font-bold tracking-tight">{course.name}</p>
147 |         <p className="text-sm text-gray-500">Code: {course.code}</p>
148 |       </Card>
149 |     ) : null }
150 |
151 |     { /* Enrolled Students Table */ }
152 |     <DataTable
153 |       columns={columns}
154 |       data={enrollments}
155 |       isLoading={enrollmentsLoading}
156 |       isFetching={enrollmentsFetching}
157 |       page={page}
158 |       pageSize={paginatedEnrollments?.pageSize}
159 |       totalCount={paginatedEnrollments?.count}
160 |       onPageChange={setPage}
161 |     />
162 |
163 |     { /* Enroll Student Dialog */ }
164 |     <Dialog open={enrollDialogOpen} onOpenChange={setEnrollDialogOpen}>
165 |       <DialogContent>
166 |         <DialogHeader>
167 |           <DialogTitle>Enroll Student</DialogTitle>
168 |           <DialogDescription>
169 |             Select a student to enroll in{" "}
170 |             <span className="font-medium">
171 |               {course?.name ?? "this course"}
172 |             </span>
173 |           </DialogDescription>
174 |         </DialogHeader>
175 |
176 |         <Select
177 |           value={selectedStudentId}
178 |           onValueChange={setSelectedStudentId}
179 |         >
180 |

```

```

181 |         <SelectTrigger className="w-full bg-white">
182 |           <SelectValue placeholder="Select a student..." />
183 |         </SelectTrigger>
184 |         <SelectContent>
185 |           {availableStudents.length === 0 ? (
186 |             <div className="px-3 py-2 text-sm text-gray-500">
187 |               No students available
188 |             </div>
189 |           ) : (
190 |             availableStudents.map((s) => (
191 |               <SelectItem key={s.id} value={s.id}>
192 |                 {s.full_name} ({s.email})
193 |               </SelectItem>
194 |             ))
195 |           )}
196 |         </SelectContent>
197 |       </Select>
198 |
199 |       {sections && sections.length > 0 && (
200 |         <Select
201 |           value={selectedSectionId}
202 |           onChange={setSelectedSectionId}
203 |         >
204 |           <SelectTrigger className="w-full bg-white">
205 |             <SelectValue placeholder="Select a section (optional)" />
206 |           </SelectTrigger>
207 |           <SelectContent>
208 |             <SelectItem value="none">No section</SelectItem>
209 |             {sections
210 |               .filter((s) => s.is_active)
211 |               .map((s) => (
212 |                 <SelectItem key={s.id} value={s.id}>
213 |                   Section {s.section_code} -{" "}
214 |                   {s.profiles?.full_name ?? "Unassigned"}
215 |                 </SelectItem>
216 |               ))}
217 |             </SelectContent>
218 |           </Select>
219 |         )}
220 |
221 |       <DialogFooter>
222 |         <Button
223 |           variant="outline"
224 |           onClick={() => {
225 |             setEnrollDialogOpen(false);
226 |             setSelectedStudentId("");
227 |             setSelectedSectionId("");
228 |           }}
229 |           disabled={enrollMutation.isPending}
230 |         >
231 |           Cancel
232 |         </Button>
233 |         <Button
234 |           onClick={handleEnroll}
235 |           disabled={!selectedStudentId || enrollMutation.isPending}
236 |           variant="tactile"
237 |         >
238 |           {enrollMutation.isPending && (
239 |             <Loader2 className="h-4 w-4 animate-spin" />
240 |           )}
241 |           Enroll
242 |         </Button>
243 |       </DialogFooter>
244 |     </DialogContent>
245 |   </Dialog>
246 |
247 |   /* Unenroll Confirmation Dialog */
248 |   <ConfirmDialog
249 |     open={!!unenrollTarget}
250 |     onOpenChange={() => setUnenrollTarget(null)}
251 |     title="Unenroll Student"
252 |     description={`Are you sure you want to unenroll "${
253 |       unenrollTarget?.profiles?.full_name ?? "this student"
254 |     }" from the course? Their status will be set to dropped.`}
255 |     variant="destructive"
256 |     confirmLabel="Unenroll"
257 |     isPending={unenrollMutation.isPending}
258 |     onConfirm={handleUnenroll}
259 |   />
260 | </div>
261 | );
262 | };
263 |
264 | export default CourseEnrollmentPage;
265 |

```

FILE: [src/pages/admin/courses/CourseForm.tsx](#)

TYPE: .tsx | LINES: 1-463 | SHA256: b5385148206c749033e6bffa4baa6f54a7e0e430e950ee6e67b91562a6b3c9b8

```

1 | import { useEffect } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useNavigate, useParams } from "react-router-dom";
5 | import {
6 |   createCourseSchema,
7 |   updateCourseSchema,
8 |   type CreateCourseFormData,
9 |   type UpdateCourseFormData,
10 | } from "@lib/schemas/course";
11 | import {
12 |   useCreateCourse,
13 |   useUpdateCourse,
14 |   useCourse,
15 |   useTeachers,

```

[illegible]

[illegible]

```

224     <FormMessage />
225   </FormItem>
226 })
227 />
228
229 <FormField
230   control={form.control}
231   name={"name_ar" as never}
232   render={({ field }) => (
233     <FormItem>
234       <FormLabel>{t("bilingual.arabicName")}</FormLabel>
235       <FormControl>
236         <Input
237           placeholder={t("bilingual.arabicNamePlaceholder")}
238           dir="rtl"
239           {...field}
240           value={field.value as string} ?? ""
241         />
242       </FormControl>
243       <FormMessage />
244     </FormItem>
245   )}
246 />
247
248 {isEditMode ? (
249   <div className="grid gap-2">
250     {/* eslint-disable-next-line jsx-a11y/label-has-associated-control */}
251     <label className="text-sm font-medium">Course Code</label>
252     <Input
253       value={existingCode ?? ""}
254       disabled
255       className="bg-gray-50"
256     />
257     <p className="text-sm text-muted-foreground">
258       Course code cannot be changed after creation.
259     </p>
260   </div>
261 ) : (
262   <FormField
263     control={form.control}
264     name={"code" as never}
265     render={({ field }) => (
266       <FormItem>
267         <FormLabel>Course Code</FormLabel>
268         <FormControl>
269           <Input placeholder="e.g. CS201" {...field} />
270         </FormControl>
271         <FormMessage />
272       </FormItem>
273     )}
274   />
275 )}
276
277 {isEditMode ? (
278   <div className="grid gap-2">
279     {/* eslint-disable-next-line jsx-a11y/label-has-associated-control */}
280     <label className="text-sm font-medium">Program</label>
281     <Input
282       value={existingProgram ?? ""}
283       disabled
284       className="bg-gray-50"
285     />
286     <p className="text-sm text-muted-foreground">
287       Program cannot be changed after creation.
288     </p>
289   </div>
290 ) : (
291   <FormField
292     control={form.control}
293     name={"program_id" as never}
294     render={({ field }) => (
295       <FormItem>
296         <FormLabel>Program</FormLabel>
297         <Select
298           onChange={field.onChange}
299           value={field.value as string}
300           disabled={isLoadingPrograms}
301         >
302           <FormControl>
303             <SelectTrigger className="bg-white">
304               <SelectValue placeholder="Select a program" />
305             </SelectTrigger>
306           </FormControl>
307           <SelectContent>
308             {programs.map((program) => (
309               <SelectItem key={program.id} value={program.id}>
310                 {program.name}
311               </SelectItem>
312             ))}
313           </SelectContent>
314         </Select>
315         <FormMessage />
316       </FormItem>
317     )}
318   />
319 )}
320
321 <FormField
322   control={form.control}
323   name={"teacher_id" as never}
324   render={({ field }) => (
325     <FormItem>
326       <FormLabel>Teacher</FormLabel>
327       <Select

```

[illegible]


```

432 | const { id } = useParams<{ id: string }>();
433 | const navigate = useNavigate();
434 | const { institutionId } = useAuth();
435 | const isEditMode = !!id;
436 |
437 | return (
438 |   <div className="space-y-6">
439 |     <div className="flex items-center gap-4">
440 |       <Button
441 |         variant="ghost"
442 |         size="sm"
443 |         onClick={() => navigate("/admin/courses")}
444 |       >
445 |         <ArrowLeft className="h-4 w-4" />
446 |         Back
447 |       </Button>
448 |       <h1 className="text-2xl font-bold tracking-tight">
449 |         {isEditMode ? "Edit Course" : "Create Course"}
450 |       </h1>
451 |     </div>
452 |
453 |     {isEditMode ? (
454 |       <EditCourseForm courseId={id} />
455 |     ) : (
456 |       <CreateCourseForm institutionId={institutionId ?? ""} />
457 |     )}
458 |   </div>
459 | );
460 | };
461 |
462 | export default CourseForm;
463 |

```

FILE: [src/pages/admin/courses/CourseListPage.tsx](#)

TYPE: .tsx | LINES: 1-141 | SHA256: 838b58102b060e0f44a9a93483c20e59a9feab7afb2bce36812b6c260d66dfbc

```

1 | import { useState } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { toast } from "sonner";
5 | import { createColumns } from "../columns";
6 | import { DataTable } from "@components/shared/DataTable";
7 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
8 | import { useCourses, useSoftDeleteCourse } from "@hooks/useCourses";
9 | import { usePrograms } from "@hooks/usePrograms";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import {
13 |   Select,
14 |   SelectContent,
15 |   SelectItem,
16 |   SelectTrigger,
17 |   SelectValue,
18 | } from "@components/ui/select";
19 | import { Plus, Search } from "lucide-react";
20 | import type { Course } from "@types/app";
21 |
22 | const CourseListPage = () => {
23 |   const navigate = useNavigate();
24 |   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
25 |   const [programFilter, setProgramFilter] = useQueryState(
26 |     "program",
27 |     parseAsString.withDefault("")
28 |   );
29 |   const [courseToDeactivate, setCourseToDeactivate] = useState<Course | null>(
30 |     null
31 |   );
32 |   const [page, setPage] = useState(1);
33 |
34 |   const {
35 |     data: paginatedCourses,
36 |     isLoading,
37 |     isFetching,
38 |   } = useCourses({
39 |     search: search || undefined,
40 |     programId: programFilter || undefined,
41 |     page,
42 |   });
43 |
44 |   const { data: paginatedPrograms } = usePrograms();
45 |   const programs = paginatedPrograms?.data ?? [];
46 |   const softDeleteMutation = useSoftDeleteCourse();
47 |
48 |   const columns = createColumns(
49 |     (course) => navigate(`/admin/courses/${course.id}/edit`),
50 |     (course) => setCourseToDeactivate(course),
51 |     (course) => navigate(`/admin/courses/${course.id}/enrollment`)
52 |   );
53 |
54 |   return (
55 |     <div className="space-y-6">
56 |       <div className="flex items-center justify-between">
57 |         <h1 className="text-2xl font-bold tracking-tight">Courses</h1>
58 |         <Button
59 |           variant="tactile"
60 |           onClick={() => navigate("/admin/courses/new")}
61 |         >
62 |           <Plus className="h-4 w-4" /> Add Course
63 |         </Button>
64 |       </div>
65 |
66 |       <div className="flex items-center gap-4">
67 |         <div className="flex items-center gap-4">
68 |           <div className="flex items-center gap-4">

```

```

69 |         <div className="relative flex-1 max-w-sm">
70 |             <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
71 |             <Input
72 |                 placeholder="Search by name or code..."
73 |                 value={search}
74 |                 onChange={(e) => {
75 |                     setSearch(e.target.value || null);
76 |                     setPage(1);
77 |                 }}
78 |                 className="ps-9"
79 |             />
80 |         </div>
81 |         <Select
82 |             value={programFilter || "__all__"}
83 |             onChange={(value) => {
84 |                 setProgramFilter(value === "__all__" ? null : value);
85 |                 setPage(1);
86 |             }}
87 |         >
88 |             <SelectTrigger className="w-[220px] bg-white">
89 |                 <SelectValue placeholder="All Programs" />
90 |             </SelectTrigger>
91 |             <SelectContent>
92 |                 <SelectItem value="__all__">All Programs</SelectItem>
93 |                 {programs.map((program) => (
94 |                     <SelectItem key={program.id} value={program.id}>
95 |                         {program.name}
96 |                     </SelectItem>
97 |                 ))}
98 |             </SelectContent>
99 |         </Select>
100 |     </div>
101 |
102 |     { /* Data Table */ }
103 |     <DataTable
104 |         columns={columns}
105 |         data={paginatedCourses?.data ?? []}
106 |         isLoading={isLoading}
107 |         isFetching={isFetching}
108 |         page={page}
109 |         pageSize={paginatedCourses?.pageSize}
110 |         totalCount={paginatedCourses?.count}
111 |         onChange={setPage}
112 |     />
113 |
114 |     { /* Deactivate Confirmation Dialog */ }
115 |     <ConfirmDialog
116 |         open={!!courseToDeactivate}
117 |         onOpenChange={() => setCourseToDeactivate(null)}
118 |         title="Deactivate Course"
119 |         description={`Are you sure you want to deactivate "${courseToDeactivate?.name}"? Students will no long`}
120 |         variant="destructive"
121 |         confirmLabel="Deactivate"
122 |         isPending={softDeleteMutation.isPending}
123 |         onConfirm={() => {
124 |             if (!courseToDeactivate) return;
125 |             softDeleteMutation.mutate(courseToDeactivate.id, {
126 |                 onSuccess: () => {
127 |                     toast.success(`${courseToDeactivate.name} has been deactivated`);
128 |                     setCourseToDeactivate(null);
129 |                 },
130 |                 onError: (err) => {
131 |                     toast.error(err.message);
132 |                 },
133 |             });
134 |         }}
135 |     />
136 | </div>
137 | );
138 | };
139 |
140 | export default CourseListPage;
141 |

```

FILE: [src/pages/admin/courses/enrollmentColumns.tsx](#)

TYPE: .tsx | **LINES:** 1-106 | **SHA256:** 50104580f52b2465ac19acacdf49c606d0c886e6b9a45d9323c5105788a0e07b

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import { ArrowUpDown, MoreHorizontal, UserMinus } from "lucide-react";
4 | import { Badge } from "@components/ui/badge";
5 | import { Button } from "@components/ui/button";
6 | import {
7 |     DropdownMenu,
8 |     DropdownMenuContent,
9 |     DropdownMenuItem,
10 |     DropdownMenuTrigger,
11 | } from "@components/ui/dropdown-menu";
12 | import type { EnrollmentWithProfile } from "@hooks/useEnrollments";
13 |
14 | const statusStyles: Record<string, string> = {
15 |     active: "bg-green-100 text-green-700 border-green-200",
16 |     dropped: "bg-red-100 text-red-700 border-red-200",
17 |     completed: "bg-blue-100 text-blue-700 border-blue-200",
18 | };
19 |
20 | export const createEnrollmentColumns = (
21 |     onUnenroll: (enrollment: EnrollmentWithProfile) => void
22 | ): ColumnDef<EnrollmentWithProfile>[] => [
23 |     {
24 |         id: "student_name",
25 |         header: ({ column }) => (
26 |             <Button
27 |                 variant="ghost"

```

```

28 |         size="sm"
29 |         className="-ms-3"
30 |         onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
31 |     >
32 |         Student Name
33 |         <ArrowUpDown className="h-4 w-4" />
34 |     </Button>
35 | ),
36 | accessorFn: (row) => row.profiles?.full_name ?? "Unknown",
37 | cell: ({ getValue }) => (
38 |     <span className="font-medium">{getValue() as string}</span>
39 | ),
40 | },
41 | {
42 |     id: "email",
43 |     header: "Email",
44 |     accessorFn: (row) => row.profiles?.email ?? "-",
45 | },
46 | {
47 |     accessorKey: "status",
48 |     header: "Status",
49 |     cell: ({ row }) => {
50 |         const status = row.getValue("status") as string;
51 |         return (
52 |             <Badge variant="outline" className={statusStyles[status] ?? ""}>
53 |                 {status.charAt(0).toUpperCase() + status.slice(1)}
54 |             </Badge>
55 |         );
56 |     },
57 | },
58 | {
59 |     accessorKey: "enrolled_at",
60 |     header: ({ column }) => (
61 |         <Button
62 |             variant="ghost"
63 |             size="sm"
64 |             className="-ms-3"
65 |             onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
66 |         >
67 |             Enrolled Date
68 |             <ArrowUpDown className="h-4 w-4" />
69 |         </Button>
70 |     ),
71 |     cell: ({ row }) => {
72 |         const date = row.getValue("enrolled_at") as string | null;
73 |         if (!date) return "-";
74 |         return format(new Date(date), "MMM d, yyyy");
75 |     },
76 | },
77 | {
78 |     id: "actions",
79 |     header: "",
80 |     cell: ({ row }) => {
81 |         const enrollment = row.original;
82 |         if (enrollment.status !== "active") return null;
83 |
84 |         return (
85 |             <DropdownMenu>
86 |                 <DropdownMenuTrigger asChild>
87 |                     <Button variant="ghost" size="icon-xs">
88 |                         <MoreHorizontal className="h-4 w-4" />
89 |                         <span className="sr-only">Open menu</span>
90 |                     </Button>
91 |                 </DropdownMenuTrigger>
92 |                 <DropdownMenuContent align="end">
93 |                     <DropdownMenuItem
94 |                         variant="destructive"
95 |                         onClick={() => onUnenroll(enrollment)}
96 |                     >
97 |                         <UserMinus className="h-4 w-4" />
98 |                         Unenroll
99 |                     </DropdownMenuItem>
100 |                 </DropdownMenuContent>
101 |             </DropdownMenu>
102 |         );
103 |     },
104 | },
105 | ];
106 |

```

FILE: [src/pages/admin/departments/DepartmentManager.tsx](#)

TYPE: .tsx | LINES: 1-372 | SHA256: bf4c0f8ba2550db2094aae61f36207ce8f9087f82e9e06bbdc57e39f1e90730d

```

1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import {
6 |     useDepartments,
7 |     useCreateDepartment,
8 |     useUpdateDepartment,
9 |     useDeleteDepartment,
10 |     type Department,
11 | } from "@/hooks/useDepartments";
12 | import { useAuth } from "@/hooks/useAuth";
13 | import {
14 |     Badge,
15 |     Button,
16 |     Card,
17 |     Dialog,
18 |     DialogContent,
19 |     DialogHeader,
20 |     DialogTitle,
21 |     Input,

```

[illegible]

[illegible]

[illegible]

```

334 |         <Building2 className="h-10 w-10 text-gray-300 mx-auto mb-3" />
335 |         <p className="text-sm text-gray-500">
336 |             No departments yet. Create your first department to get started.
337 |         </p>
338 |     </Card>
339 | ) : (
340 |     <div className="space-y-3">
341 |         {(departments ?? []).map((dept) => (
342 |             <DepartmentRow
343 |                 key={dept.id}
344 |                 department={dept}
345 |                 onEdit={handleEdit}
346 |                 onDelete={handleDelete}
347 |             />
348 |         ))}
349 |     </div>
350 | )}
351 |
352 | <DepartmentFormDialog
353 |     open={dialogOpen}
354 |     onOpenChange={setDialogOpen}
355 |     department={editingDepartment}
356 |     institutionId={institutionId ?? ""}
357 | />
358 |
359 | <ConfirmDialog
360 |     open={!deleteTarget}
361 |     onOpenChange={(open: boolean) => !open && setDeleteTarget(null)}
362 |     title="Delete Department"
363 |     description="Are you sure you want to delete this department? Deletion is blocked if active programs e
364 |     onConfirm={confirmDelete}
365 |     isPending={deleteMutation.isPending}
366 | />
367 | </div>
368 | );
369 | };
370 |
371 | export default DepartmentManager;
372 |

```

FILE: [src/pages/admin/fees/FeeManager.tsx](#)

TYPE: .tsx | LINES: 1-259 | SHA256: 5b8a7183d52ecce3c2fe64b44ceca598937d22e374cbdcbce9913632c2b8f38db

```

1 | import { useForm } from "react-hook-form";
2 | import { zodResolver } from "@hookform/resolvers/zod";
3 | import { z } from "zod";
4 | import { Card } from "@components/ui/card";
5 | import { Button } from "@components/ui/button";
6 | import { Input } from "@components/ui/input";
7 | import { Badge } from "@components/ui/badge";
8 | import {
9 |     Form,
10 |     FormField,
11 |     FormItem,
12 |     FormLabel,
13 |     FormControl,
14 |     FormMessage,
15 | } from "@components/ui/form";
16 | import {
17 |     Select,
18 |     SelectContent,
19 |     SelectItem,
20 |     SelectTrigger,
21 |     SelectValue,
22 | } from "@components/ui/select";
23 | import { Shimmer } from "@design-system";
24 | import { Plus, Loader2, DollarSign } from "lucide-react";
25 | import { toast } from "sonner";
26 | import {
27 |     useFeeStructures,
28 |     useCreateFeeStructure,
29 |     type FeeStructure,
30 | } from "@hooks/useFees";
31 | import { usePrograms } from "@hooks/usePrograms";
32 | import { useSemesters } from "@hooks/useSemesters";
33 | import { useTranslation } from "react-i18next";
34 | import { formatCurrency } from "@lib/i18nHelpers";
35 |
36 | const schema = z.object({
37 |     program_id: z.string().uuid("Select a program"),
38 |     semester_id: z.string().uuid("Select a semester"),
39 |     fee_type: z.string().min(1, "Fee type is required"),
40 |     amount: z.number().min(0),
41 |     currency: z.string().min(1),
42 |     due_date: z.string().min(1),
43 | });
44 |
45 | type FeeFormData = z.infer<typeof schema>;
46 |
47 | const FeeManager = () => {
48 |     const { i18n } = useTranslation();
49 |     const { data: fees = [], isLoading } = useFeeStructures();
50 |     const { data: programsResult } = usePrograms({ pageSize: 100 });
51 |     const programs = programsResult?.data ?? [];
52 |     const { data: semesters = [] } = useSemesters();
53 |     const createMutation = useCreateFeeStructure();
54 |     const form = useForm<FeeFormData>({
55 |         resolver: zodResolver(schema),
56 |         defaultValues: {
57 |             program_id: "",
58 |             semester_id: "",
59 |             fee_type: "",
60 |             amount: 0,
61 |             currency: "QAR",

```

```

62 |         due_date: "",
63 |     },
64 | });
65 |
66 | const selectedProgram = form.watch("program_id");
67 | const selectedSemester = form.watch("semester_id");
68 | const selectionIncomplete = !selectedProgram || !selectedSemester;
69 |
70 | const onSubmit = (data: FeeFormData) => {
71 |     createMutation.mutate(data as Omit<FeeStructure, "id" | "created_at">, {
72 |         onSuccess: () => {
73 |             toast.success("Fee structure created");
74 |             form.reset();
75 |         },
76 |         onError: (err) => toast.error(err.message),
77 |     });
78 | };
79 |
80 | return (
81 |     <div className="space-y-6">
82 |         <h1 className="text-2xl font-bold tracking-tight">Fee Management</h1>
83 |
84 |         <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
85 |             <div
86 |                 className="px-6 py-4 flex items-center gap-2"
87 |                 style={{
88 |                     background: "var(--brand-gradient)",
89 |                 }}
90 |             >
91 |                 <DollarSign className="h-5 w-5 text-white" />
92 |                 <h2 className="text-lg font-bold tracking-tight text-white">
93 |                     Fee Structures
94 |                 </h2>
95 |             </div>
96 |             <div className="p-6">
97 |                 {isLoading ? (
98 |                     <Shimmer className="h-32 rounded-lg" />
99 |                 ) : fees.length === 0 ? (
100 |                     <p className="text-sm text-slate-400 text-center py-6">
101 |                         No fee structures yet.
102 |                     </p>
103 |                 ) : (
104 |                     <div className="space-y-2">
105 |                         {fees.map((f) => (
106 |                             <div
107 |                                 key={f.id}
108 |                                 className="flex items-center justify-between p-3 rounded-lg border border-slate-100"
109 |                             >
110 |                                 <div>
111 |                                     <span className="text-sm font-medium">{f.fee_type}</span>
112 |                                     <Badge variant="outline" className="ms-2 text-xs">
113 |                                         {formatCurrency(
114 |                                             f.amount,
115 |                                             i18n.language.startsWith("ar") ? "ar-QA" : "en",
116 |                                             f.currency
117 |                                         )}
118 |                                     </Badge>
119 |                                 </div>
120 |                                 <span className="text-xs text-slate-400">
121 |                                     Due: {f.due_date}
122 |                                 </span>
123 |                             </div>
124 |                         ))}
125 |                     </div>
126 |                 )}
127 |             </div>
128 |         </Card>
129 |
130 |         <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
131 |             <h2 className="text-lg font-bold tracking-tight mb-4">
132 |                 Add Fee Structure
133 |             </h2>
134 |             <Form {...form}>
135 |                 <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
136 |                     <FormField
137 |                         control={form.control}
138 |                         name="fee_type"
139 |                         render={({ field }) => (
140 |                             <FormItem>
141 |                                 <FormLabel>Fee Type</FormLabel>
142 |                                 <FormControl>
143 |                                     <Input
144 |                                         {...field}
145 |                                         placeholder="e.g. tuition, lab, library, exam"
146 |                                     />
147 |                                 </FormControl>
148 |                                 <FormMessage />
149 |                             </FormItem>
150 |                         )}
151 |                     />
152 |                     <div className="grid grid-cols-3 gap-4">
153 |                         <FormField
154 |                             control={form.control}
155 |                             name="amount"
156 |                             render={({ field }) => (
157 |                                 <FormItem>
158 |                                     <FormLabel>Amount</FormLabel>
159 |                                     <FormControl>
160 |                                         <Input
161 |                                             type="number"
162 |                                             {...field}
163 |                                             onChange={(e) =>
164 |                                                 field.onChange(parseFloat(e.target.value) || 0)
165 |                                             }

```



```

166 |         />
167 |         </FormControl>
168 |         <FormMessage />
169 |       </FormItem>
170 |     )}
171 |   />
172 |   <FormField
173 |     control={form.control}
174 |     name="due_date"
175 |     render={({ field }) => (
176 |       <FormItem>
177 |         <FormLabel>Due Date</FormLabel>
178 |         <FormControl>
179 |           <Input type="date" {...field} />
180 |         </FormControl>
181 |         <FormMessage />
182 |       </FormItem>
183 |     )}
184 |   />
185 |   <FormField
186 |     control={form.control}
187 |     name="program_id"
188 |     render={({ field }) => (
189 |       <FormItem>
190 |         <FormLabel>Program</FormLabel>
191 |         <Select onValueChange={field.onChange} value={field.value}>
192 |           <FormControl>
193 |             <SelectTrigger className="w-full bg-white">
194 |               <SelectValue placeholder="Select a program" />
195 |             </SelectTrigger>
196 |           </FormControl>
197 |           <SelectContent>
198 |             {programs.map((p) => (
199 |               <SelectItem key={p.id} value={p.id}>
200 |                 {p.name}
201 |               </SelectItem>
202 |             ))}
203 |           </SelectContent>
204 |         </Select>
205 |         <FormMessage />
206 |       </FormItem>
207 |     )}
208 |   />
209 | </div>
210 | <FormField
211 |   control={form.control}
212 |   name="semester_id"
213 |   render={({ field }) => (
214 |     <FormItem>
215 |       <FormLabel>Semester</FormLabel>
216 |       <Select onValueChange={field.onChange} value={field.value}>
217 |         <FormControl>
218 |           <SelectTrigger className="w-full bg-white">
219 |             <SelectValue placeholder="Select a semester" />
220 |           </SelectTrigger>
221 |         </FormControl>
222 |         <SelectContent>
223 |           {semesters.map((s) => (
224 |             <SelectItem key={s.id} value={s.id}>
225 |               {s.name} ({s.code})
226 |             </SelectItem>
227 |           ))}
228 |         </SelectContent>
229 |       </Select>
230 |       <FormMessage />
231 |     </FormItem>
232 |   )}
233 | />
234 | <Button
235 |   type="submit"
236 |   disabled={createMutation.isPending || selectionIncomplete}
237 |   variant="tactile"
238 | >
239 |   {createMutation.isPending ? (
240 |     <Loader2 className="h-4 w-4 animate-spin" />
241 |   ) : (
242 |     <Plus className="h-4 w-4" />
243 |   )}{" "}
244 |   Create
245 | </Button>
246 | {selectionIncomplete && (
247 |   <p className="text-xs text-slate-500">
248 |     Select a program and a semester to create a fee structure.
249 |   </p>
250 | )}
251 | </form>
252 | </Form>
253 | </Card>
254 | </div>
255 | );
256 | };
257 |
258 | export default FeeManager;
259 |

```

FILE: [src/pages/admin/governance/AIGovernancePage.tsx](#)

TYPE: .tsx | LINES: 1-446 | SHA256: 204cc6843ed7ca31a92c8ebeedd2ee9ce11a1e20a04244da471287dd1e3b878a

```

1 | import { Link } from "react-router-dom";
2 | import {
3 |   ArrowUpRight,
4 |   Bot,
5 |   Brain,
6 |   CheckCircle2,

```

```

7 |   FileClock,
8 |   Gauge,
9 |   ShieldCheck,
10 | } from "lucide-react";
11 | import { useTranslation } from "react-i18next";
12 |
13 | import { Badge } from "@components/ui/badge";
14 | import { Button } from "@components/ui/button";
15 | import { Card, CardContent, CardHeader, CardTitle } from "@components/ui/card";
16 | import {
17 |   Table,
18 |   TableBody,
19 |   TableCell,
20 |   TableHead,
21 |   TableHeader,
22 |   TableRow,
23 | } from "@components/ui/table";
24 | import { PageHeader, StatePanel } from "@design-system";
25 | import { useAuth } from "@hooks/useAuth";
26 | import { useAIGovernanceUsage } from "@hooks/useAIGovernance";
27 | import { useAIPerformance } from "@hooks/useAIPerformance";
28 | import {
29 |   AI_GOVERNANCE_ACTION_POLICIES,
30 |   autonomyBadgeClass,
31 | } from "@lib/aiGovernancePolicy";
32 | import { cn } from "@lib/utlis";
33 |
34 | const Metric = ({
35 |   label,
36 |   value,
37 |   detail,
38 | }): {
39 |   label: string;
40 |   value: string;
41 |   detail: string;
42 | } => (
43 |   <div className="rounded-xl bg-slate-50 p-3">
44 |     <p className="text-[10px] font-black uppercase tracking-wider text-slate-400">
45 |       {label}
46 |     </p>
47 |     <p className="mt-1 text-xl font-black text-slate-900">{value}</p>
48 |     <p className="mt-0.5 text-[11px] text-slate-500">{detail}</p>
49 |   </div>
50 | );
51 |
52 | const AIGovernancePage = () => {
53 |   const { t } = useTranslation("common");
54 |   const { institutionId } = useAuth();
55 |   const usage = useAIGovernanceUsage(institutionId ?? undefined);
56 |   const performance = useAIPerformance();
57 |   const isLoading = usage.isLoading || performance.isLoading;
58 |   const isError = usage.isError || performance.isError;
59 |
60 |   return (
61 |     <div className="space-y-4">
62 |       <div className="space-y-1">
63 |         <PageHeader
64 |           title={t("admin.governance.title", "AI Governance")}
65 |           action={
66 |             <Button asChild variant="outline" size="sm">
67 |               <Link to="/admin/audit-log">
68 |                 <FileClock className="size-4" />
69 |                 {t("admin.governance.auditLog", "Full audit log")}
70 |               </Link>
71 |             </Button>
72 |           </>
73 |       </div>
74 |       <p className="max-w-3xl text-xs text-slate-500">
75 |         {t(
76 |           "admin.governance.description",
77 |           "Human approval remains the ceiling for sensitive actions. Usage and quality metrics below come fr
78 |         )}
79 |       </p>
80 |     </div>
81 |
82 |     <Card className="border-slate-200 bg-white shadow-sm">
83 |       <CardHeader className="gap-2">
84 |         <div className="flex flex-wrap items-center justify-between gap-2">
85 |           <CardTitle className="flex items-center gap-2 text-base">
86 |             <ShieldCheck className="size-5 text-blue-600" />
87 |             {t(
88 |               "admin.governance.autonomyCeiling",
89 |               "Institution autonomy ceiling"
90 |             )}
91 |           </CardTitle>
92 |           <Badge
93 |             variant="outline"
94 |             className="border-amber-200 bg-amber-50 text-amber-700"
95 |           >
96 |             {t("admin.governance.roadmap", "Read-only policy · roadmap")}
97 |           </Badge>
98 |         </div>
99 |         <p className="text-xs text-slate-500">
100 |           {t(
101 |             "admin.governance.roadmapNote",
102 |             "Institution-specific policy storage is not available yet. The current product guardrail is show
103 |           )}
104 |         </p>
105 |       </CardHeader>
106 |       <CardContent>
107 |         <div className="grid grid-cols-2 gap-2 md:grid-cols-4">
108 |           {
109 |             ["A0", t("admin.governance.levels.a0", "Observe and display")],
110 |             ["A1", t("admin.governance.levels.a1", "Suggest and draft")],

```

```

111 |         ["A2", t("admin.governance.levels.a2", "Act after approval")],
112 |         [
113 |             "A3",
114 |             t("admin.governance.levels.a3", "Autonomous safe actions"),
115 |         ],
116 |     ].map(([level, label]) => (
117 |         <div
118 |             key={level}
119 |             className={cn(
120 |                 "rounded-lg border p-3 text-center",
121 |                 level === "A2"
122 |                     ? "border-blue-200 bg-blue-50"
123 |                     : "border-slate-100 bg-slate-50"
124 |             )}
125 |         >
126 |             <p
127 |                 className={cn(
128 |                     "text-xs font-black",
129 |                     level === "A2" ? "text-blue-700" : "text-slate-400"
130 |                 )}
131 |             >
132 |                 {level}
133 |             </p>
134 |             <p
135 |                 className={cn(
136 |                     "mt-1 text-[11px]",
137 |                     level === "A2" ? "text-blue-700" : "text-slate-500"
138 |                 )}
139 |             >
140 |                 {label}
141 |             </p>
142 |         </div>
143 |     ))}
144 | </div>
145 | <div className="mt-3 flex items-start gap-2 rounded-lg border border-amber-100 bg-amber-50 p-3">
146 |     <CheckCircle2 className="mt-0.5 size-4 shrink-0 text-amber-600" />
147 |     <p className="text-xs leading-5 text-amber-800">
148 |         {t(
149 |             "admin.governance.currentPolicy",
150 |             "Current platform guardrail: A2 – AI may act only after a human approves. Grading, publishing,
151 |         )}
152 |     </p>
153 | </div>
154 | </CardContent>
155 | </Card>
156 |
157 | {isLoading ? (
158 |     <StatePanel variant="loading" />
159 | ) : isError ? (
160 |     <StatePanel
161 |         variant="error"
162 |         message={t(
163 |             "admin.governance.loadError",
164 |             "Could not load AI governance metrics."
165 |         )}
166 |     </>
167 | ) : (
168 |     <div className="grid gap-4 xl:grid-cols-2">
169 |         <Card className="border-slate-200 bg-white shadow-sm">
170 |             <CardHeader>
171 |                 <CardTitle className="flex items-center gap-2 text-base">
172 |                     <Gauge className="size-5 text-cyan-600" />
173 |                     {t("admin.governance.usage", "Tutor usage this month")}
174 |                 </CardTitle>
175 |             </CardHeader>
176 |             <CardContent className="space-y-4">
177 |                 <div className="grid grid-cols-2 gap-2">
178 |                     <Metric
179 |                         label={t("admin.governance.requests", "Requests")}
180 |                         value={{usage.data?.totalRequests ?? 0}.toLocaleString()}
181 |                         detail={t(
182 |                             "admin.governance.loggedRequests",
183 |                             "Logged tutor model calls"
184 |                         )}
185 |                     </>
186 |                     <Metric
187 |                         label={t("admin.governance.successRate", "Success rate")}
188 |                         value={{usage.data?.successRate ?? 0}%}
189 |                         detail={t(
190 |                             "admin.governance.successful",
191 |                             "successful"
192 |                         )}
193 |                     </>
194 |                     <Metric
195 |                         label={t("admin.governance.tokens", "Tokens")}
196 |                         value={{usage.data?.totalTokens ?? 0}.toLocaleString()}
197 |                         detail={t("admin.governance.monthToDate", "Month to date")}
198 |                     </>
199 |                     <Metric
200 |                         label={t("admin.governance.latency", "Avg latency")}
201 |                         value={{usage.data?.averageLatencyMs ?? 0} ms}
202 |                         detail={t(
203 |                             "admin.governance.responseTime",
204 |                             "Server response time"
205 |                         )}
206 |                     </>
207 |                 </div>
208 |             </CardContent>
209 |         </Card>
210 |         <div
211 |             className="mb-2 text-xs font-bold text-slate-700">
212 |             {t("admin.governance.models", "Models used")}
213 |             </div>
214 |         {{usage.data?.models.length ?? 0} === 0 ? (
215 |             <p className="rounded-lg bg-slate-50 p-3 text-xs text-slate-500">

```

```

215         {t(
216           "admin.governance.noUsage",
217           "No tutor model calls have been logged this month."
218         )}
219       </p>
220     ) : (
221       <div className="space-y-2">
222         {usage.data?.models.map((model) => (
223           <div
224             key={model.model}
225             className="flex items-center justify-between rounded-lg bg-slate-50 px-3 py-2"
226           >
227             <span className="flex min-w-0 items-center gap-2 text-xs font-medium text-slate-700">
228               <Bot className="size-3.5 shrink-0 text-blue-500" />
229               <span className="truncate">{model.model}</span>
230             </span>
231             <span className="text-[11px] text-slate-500">
232               {t("admin.governance.modelUsage", {
233                 requests: model.requests,
234                 tokens: model.tokens.toLocaleString(),
235                 defaultValue:
236                   "{{requests}} requests · {{tokens}} tokens",
237               })}
238             </span>
239           </div>
240         ))}
241       </div>
242     )}
243   </div>
244 </CardContent>
245 </Card>
246
247 <Card className="border-slate-200 bg-white shadow-sm">
248   <CardHeader>
249     <CardTitle className="flex items-center gap-2 text-base">
250       <Brain className="size-5 text-violet-600" />
251       {t("admin.governance.quality", "AI quality signals")}
252     </CardTitle>
253   </CardHeader>
254   <CardContent>
255     <div className="grid grid-cols-2 gap-2">
256       <Metric
257         label={t(
258           "admin.governance.suggestionAcceptance",
259           "Suggestion acceptance"
260         )}
261         value={`${performance.data?.suggestionAcceptanceRate ?? 0}%`}
262         detail={t("admin.governance.suggestionsReviewed", {
263           count: performance.data?.suggestionTotal ?? 0,
264           defaultValue: "{{count}} suggestions reviewed",
265         })}
266       />
267       <Metric
268         label={t(
269           "admin.governance.predictionAccuracy",
270           "Prediction accuracy"
271         )}
272         value={`${performance.data?.predictionAccuracyRate ?? 0}%`}
273         detail={t("admin.governance.validatedPredictions", {
274           count: performance.data?.predictionTotal ?? 0,
275           defaultValue: "{{count}} validated predictions",
276         })}
277       />
278       <Metric
279         label={t(
280           "admin.governance.draftAcceptance",
281           "Draft acceptance"
282         )}
283         value={`${performance.data?.draftAcceptanceRate ?? 0}%`}
284         detail={t("admin.governance.feedbackDrafts", {
285           count: performance.data?.draftTotal ?? 0,
286           defaultValue: "{{count}} feedback drafts",
287         })}
288       />
289     <div className="rounded-xl bg-slate-50 p-3">
290       <p className="text-xs font-semibold text-slate-700">
291         {t("admin.governance.liveData", "Live institution data")}
292       </p>
293       <p className="mt-1 text-[11px] text-slate-500">
294         {t(
295           "admin.governance.noFabricatedMetrics",
296           "No prototype-only counts are shown."
297         )}
298       </p>
299     </div>
300   </CardContent>
301 </Card>
302 </div>
303
304 )}
305
306 <Card className="border-slate-200 bg-white shadow-sm">
307   <CardHeader>
308     <CardTitle className="text-base">
309       {t("admin.governance.perAction", "What AI may do, per action")}
310     </CardTitle>
311   </CardHeader>
312   <CardContent className="overflow-x-auto">
313     <Table className="min-w-[620px]">
314       <TableHeader>
315         <TableRow>
316           <TableHead>{t("admin.governance.action", "Action")}</TableHead>
317           <TableHead>
318             {t("admin.governance.level", "Current level")}

```

```

319 |         </TableHead>
320 |         <TableHead>
321 |           {t("admin.governance.hardCap", "Hard cap")}
322 |         </TableHead>
323 |       </TableRow>
324 |     </TableHeader>
325 |     <TableBody>
326 |       {AI_GOVERNANCE_ACTION_POLICIES.map((policy) => (
327 |         <TableRow key={policy.actionKey}>
328 |           <TableCell className="font-medium">
329 |             {t(`admin.governance.actions.${policy.actionKey}`)}
330 |           </TableCell>
331 |           <TableCell>
332 |             <Badge
333 |               variant="outline"
334 |               className={autonomyBadgeClass(policy.level)}
335 |             >
336 |               {policy.level}
337 |             </Badge>
338 |           </TableCell>
339 |           <TableCell>
340 |             {policy.hardCap ? (
341 |               <span
342 |                 className={cn(
343 |                   "text-xs",
344 |                   policy.sensitive
345 |                     ? "font-semibold text-red-700"
346 |                     : "text-slate-500"
347 |                 )}
348 |               >
349 |                 {policy.sensitive && "ðŸ””"}d {policy.hardCap}
350 |               </span>
351 |             ) : (
352 |               <span className="text-slate-400">—</span>
353 |             )}
354 |           </TableCell>
355 |         </TableRow>
356 |       )]}
357 |     </TableBody>
358 |   </Table>
359 | </CardContent>
360 | </Card>
361 |
362 | <div className="grid gap-4 lg:grid-cols-2">
363 |   <Card className="border-slate-200 bg-white shadow-sm">
364 |     <CardHeader>
365 |       <CardTitle className="flex items-center gap-2 text-base">
366 |         <Brain className="size-5 text-violet-600" />
367 |         {t("admin.governance.memory", "AI memory and privacy")}
368 |       </CardTitle>
369 |     </CardHeader>
370 |     <CardContent className="space-y-2 text-xs text-slate-600">
371 |       <p>
372 |         <strong>
373 |           {t(
374 |             "admin.governance.memoryItems.tutorLabel",
375 |             "Tutor conversation:"
376 |           )}
377 |         </strong>{" "}
378 |         {t("admin.governance.memoryItems.tutorValue", "session-scoped")}
379 |       </p>
380 |       <p>
381 |         <strong>
382 |           {t(
383 |             "admin.governance.memoryItems.learnerLabel",
384 |             "Learner model:"
385 |           )}
386 |         </strong>{" "}
387 |         {t(
388 |             "admin.governance.memoryItems.learnerValue",
389 |             "persistent and exportable under RLS"
390 |           )}
391 |       </p>
392 |       <p>
393 |         <strong>
394 |           {t(
395 |             "admin.governance.memoryItems.evidenceLabel",
396 |             "Outcome evidence:"
397 |           )}
398 |         </strong>{" "}
399 |         {t(
400 |             "admin.governance.memoryItems.evidenceValue",
401 |             "immutable audit evidence"
402 |           )}
403 |       </p>
404 |       <p>
405 |         <strong>
406 |           {t(
407 |             "admin.governance.memoryItems.piiLabel",
408 |             "Passwords and raw PII:"
409 |           )}
410 |         </strong>{" "}
411 |         {t(
412 |             "admin.governance.memoryItems.piiValue",
413 |             "never stored in tutor prompts"
414 |           )}
415 |       </p>
416 |     </CardContent>
417 |   </Card>
418 |
419 |   <Card className="border-slate-200 bg-white shadow-sm">
420 |     <CardHeader>
421 |       <CardTitle className="text-base">
422 |         {t("admin.governance.review", "Review and accountability")}

```

```

423 |         </CardTitle>
424 |     </CardHeader>
425 |     <CardContent className="space-y-3">
426 |         <p className="text-xs leading-5 text-slate-600">
427 |             {t(
428 |                 "admin.governance.reviewNote",
429 |                 "Administrative actions are written to the audit log. AI-specific action approvals will appear
430 |             )}
431 |         </p>
432 |         <Button asChild variant="outline" size="sm">
433 |             <Link to="/admin/audit-log">
434 |                 {t("admin.governance.openAudit", "Open audit log")}
435 |             <ArrowUpRight className="size-4" />
436 |             </Link>
437 |         </Button>
438 |     </CardContent>
439 | </Card>
440 | </div>
441 | </div>
442 | );
443 | };
444 |
445 | export default AIGovernancePage;
446 |

```

FILE: [src/pages/admin/graduate-attributes/GraduateAttributeManager.tsx](#)

TYPE: .tsx | LINES: 1-356 | SHA256: bed52b2355013e3dd75ad37bcc6be3fed25ee11ca431346f6985e7bf078a5435

```

1 | // Task 113.1: Graduate Attribute Manager page
2 | // Req 6 (qa-partner-review-remediation): surface GA mappings + computed
3 | // attainment alongside the existing name/description list and Add form.
4 |
5 | import { useState } from "react";
6 | import { useForm } from "react-hook-form";
7 | import { zodResolver } from "@hookform/resolvers/zod";
8 | import { z } from "zod";
9 | import { Card } from "@components/ui/card";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import { Badge } from "@components/ui/badge";
13 | import {
14 |     Form,
15 |     FormField,
16 |     FormItem,
17 |     FormLabel,
18 |     FormControl,
19 |     FormMessage,
20 | } from "@components/ui/form";
21 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
22 | import { Shimmer } from "@design-system";
23 | import ErrorBoundary from "@components/shared/ErrorBoundary";
24 | import { InlineEmpty } from "@components/shared/EmptyState";
25 | import { Plus, Loader2, Trash2, Award, Target } from "lucide-react";
26 | import { toast } from "sonner";
27 | import { useAuth } from "@hooks/useAuth";
28 | import {
29 |     useGraduateAttributes,
30 |     useCreateGraduateAttribute,
31 |     useDeleteGraduateAttribute,
32 |     useGraduateAttributeAttainment,
33 |     useGraduateAttributeMappings,
34 |     type GAAttainment,
35 |     type GraduateAttribute,
36 | } from "@hooks/useGraduateAttributes";
37 | import { useILOs } from "@hooks/useILOs";
38 | import { resolveName } from "@lib/db/resolveName";
39 | import {
40 |     getAttainmentColor,
41 |     classifyAttainment,
42 | } from "@lib/attainmentClassifier";
43 |
44 | const schema = z.object({
45 |     name: z.string().min(1, "Name is required"),
46 |     description: z.string().optional(),
47 | });
48 |
49 | const ATTAINMENT_LABEL: Record<string, string> = {
50 |     Excellent: "Excellent",
51 |     Satisfactory: "Satisfactory",
52 |     Developing: "Developing",
53 |     Not_Yet: "Not Yet",
54 | };
55 |
56 | // Computed attainment chip (Req 6.2, 6.6) – reuses the pre-computed
57 | // GAAttainment row (Req 6.5); never reimplements the weighted calculation.
58 | const AttainmentChip = ({
59 |     attainment,
60 | }: {
61 |     attainment: GAAttainment | undefined;
62 | }) => {
63 |     // Mappings exist but the attainment row has not resolved yet.
64 |     if (!attainment) {
65 |         return (
66 |             <span className="text-xs text-slate-400 aria-live="polite">
67 |                 Attainment unavailable
68 |             </span>
69 |         );
70 |     }
71 |
72 |     const percent = Math.round(attainment.avg_attainment);
73 |     const level = classifyAttainment(percent);
74 |
75 |     return (
76 |         <div className="flex items-center gap-2">

```

```

77     <span className="text-[10px] font-black uppercase tracking-widest text-slate-400">
78       Attainment
79     </span>
80     <span
81       className="inline-flex items-center justify-center min-w-14 px-2 py-1 rounded-md text-xs font-bold tex
82       style={{ backgroundColor: getAttainmentColor(percent) }}
83       title={` ${percent}% - ${ATTAINMENT_LABEL[level] ?? level} `}
84     >
85       {percent}%
86     </span>
87     <span className="text-xs font-medium text-slate-500">
88       {ATTAINMENT_LABEL[level] ?? level}
89     </span>
90   </div>
91 );
92 };
93
94 // Per-attribute mappings + attainment surface (Req 6.1, 6.2, 6.3, 6.6).
95 // `useGraduateAttributeMappings` is keyed by attribute id, so it is consumed
96 // inside a per-row component; `outcomeNameById` resolves the GA!ILO outcome
97 // ids (Req 6.1) so the user sees outcome names rather than raw UUIDs.
98 const AttributeMappings = ({
99   attributeId,
100   attainment,
101   outcomeNameById,
102 }): {
103   attributeId: string;
104   attainment: GAAttainment | undefined;
105   outcomeNameById: Map<string, string>;
106 }) => {
107   const { data: mappings = [], isLoading } =
108     useGraduateAttributeMappings(attributeId);
109
110   if (isLoading) {
111     return <Shimmer className="h-8 rounded-md" />;
112   }
113
114   // Zero mappings !' inline empty state instead of a bare 0 (Req 6.3).
115   if (mappings.length === 0) {
116     return (
117       <InlineEmpty
118         icon=<Target className="h-5 w-5 text-gray-400" />
119         title="No outcomes mapped yet"
120         description="Map this attribute to institution outcomes to track attainment."
121         className="py-4"
122       />
123     );
124   }
125
126   return (
127     <div className="space-y-2">
128       /* Mapped outcomes sourced from graduate_attribute_mappings (Req 6.1). */
129       <div className="flex flex-wrap items-center gap-1.5">
130         <span className="text-[10px] font-black uppercase tracking-widest text-slate-400">
131           Mapped outcomes
132         </span>
133         {mappings.map((m) => (
134           <Badge
135             key={m.id}
136             variant="outline"
137             className="border-red-200 bg-red-50 text-red-700"
138             title={` Weight ${
139               m.weight <= 1 ? Math.round(m.weight * 100) : Math.round(m.weight)
140             } %`}
141           >
142             {resolveName(outcomeNameById.get(m.outcome_id))}
143             <span className="opacity-60">
144               .{ " " }
145               {m.weight <= 1
146                 ? Math.round(m.weight * 100)
147                 : Math.round(m.weight)}
148             %
149             </span>
150           </Badge>
151         ))}
152       </div>
153       /* Computed attainment with platform color coding (Req 6.2, 6.6). */
154       <AttainmentChip attainment={attainment} />
155     </div>
156   );
157 };
158
159 // A single attribute row: name/description plus the isolated mappings +
160 // attainment surface (Req 6.4 – a render failure shows a fallback, never a
161 // blank region).
162 const AttributeRow = ({
163   attr,
164   attainment,
165   outcomeNameById,
166   onDelete,
167 }): {
168   attr: GraduateAttribute;
169   attainment: GAAttainment | undefined;
170   outcomeNameById: Map<string, string>;
171   onDelete: () => void;
172 }) => (
173   <div className="flex items-start justify-between gap-4 p-3 rounded-lg border border-slate-100 hover:bg-slate
174     <div className="flex-1 min-w-0">
175       <span className="text-sm font-medium">{attr.name}</span>
176       {attr.description && (
177         <p className="text-xs text-slate-500 mt-0.5">{attr.description}</p>
178       )}
179     <div className="mt-2">
180       <ErrorBoundary

```

```

181 |         fallback={
182 |           <span className="text-xs text-red-500">
183 |             Unable to display mappings and attainment
184 |           </span>
185 |         }
186 |       >
187 |         <AttributeMappings
188 |           attributeId={attr.id}
189 |           attainment={attainment}
190 |           outcomeNameById={outcomeNameById}
191 |         />
192 |       </ErrorBoundary>
193 |     </div>
194 |   </div>
195 |   <Button
196 |     variant="ghost"
197 |     size="sm"
198 |     onClick={onDelete}
199 |     aria-label={`Delete ${attr.name}`}
200 |     className="text-slate-400 hover:text-red-500 shrink-0"
201 |   >
202 |     <Trash2 className="h-3.5 w-3.5" />
203 |   </Button>
204 | </div>
205 | );
206 |
207 | const GraduateAttributeManager = () => {
208 |   const { profile } = useAuth();
209 |   const institutionId = profile?.institution_id;
210 |   const { data: attributes = [], isLoading } =
211 |     useGraduateAttributes(institutionId);
212 |   const { data: attainmentRows = [] } =
213 |     useGraduateAttributeAttainment(institutionId);
214 |   // Resolve GA! ILO outcome ids to readable names in a single query (Req 6.1).
215 |   const { data: iloPage } = useILOs({ pageSize: 1000 });
216 |   const createMutation = useCreateGraduateAttribute();
217 |   const deleteMutation = useDeleteGraduateAttribute();
218 |   const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
219 |
220 |   // Match attainment rows to attributes by attribute_id (Req 6.2, 6.5).
221 |   const attainmentByAttribute = new Map<string, GAAttainment>(
222 |     attainmentRows.map((row) => [row.attribute_id, row])
223 |   );
224 |
225 |   // outcome_id !' title lookup for the mapped-outcome chips (Req 6.1).
226 |   const outcomeNameById = new Map<string, string>(
227 |     (iloPage?.data ?? []).map((ilo) => [ilo.id, ilo.title])
228 |   );
229 |
230 |   const form = useForm<z.infer<typeof schema>>({
231 |     resolver: zodResolver(schema),
232 |     defaultValues: { name: "", description: "" },
233 |   });
234 |
235 |   const onSubmit = (data: z.infer<typeof schema>) => {
236 |     createMutation.mutate(data, {
237 |       onSuccess: () => {
238 |         toast.success("Graduate attribute created");
239 |         form.reset();
240 |       },
241 |       onError: (err) => toast.error(err.message),
242 |     });
243 |   };
244 |
245 |   return (
246 |     <div className="space-y-6">
247 |       <h1 className="text-2xl font-bold tracking-tight">Graduate Attributes</h1>
248 |
249 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
250 |         <div
251 |           className="px-6 py-4 flex items-center gap-2"
252 |           style={{
253 |             background: "var(--brand-gradient)",
254 |           }}
255 |         >
256 |           <Award className="h-5 w-5 text-white" />
257 |           <h2 className="text-lg font-bold tracking-tight text-white">
258 |             Attributes
259 |           </h2>
260 |         </div>
261 |         <div className="p-6">
262 |           {isLoading ? (
263 |             <Shimmer className="h-32 rounded-lg" />
264 |           ) : attributes.length === 0 ? (
265 |             <p className="text-sm text-slate-400 text-center py-6">
266 |               No graduate attributes defined yet.
267 |             </p>
268 |           ) : (
269 |             <div className="space-y-2">
270 |               {attributes.map((attr) => (
271 |                 <AttributeRow
272 |                   key={attr.id}
273 |                   attr={attr}
274 |                   attainment={attainmentByAttribute.get(attr.id)}
275 |                   outcomeNameById={outcomeNameById}
276 |                   onDelete={() => setDeleteTarget(attr.id)}
277 |                 />
278 |               ))}
279 |             </div>
280 |           )}
281 |         </div>
282 |       </Card>
283 |
284 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">

```



```

285 |         <h2 className="text-lg font-bold tracking-tight mb-4">
286 |             Add Graduate Attribute
287 |         </h2>
288 |         <Form {...form}>
289 |             <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
290 |                 <FormField
291 |                     control={form.control}
292 |                     name="name"
293 |                     render={({ field }) => (
294 |                         <FormItem>
295 |                             <FormLabel>Name</FormLabel>
296 |                             <FormControl>
297 |                                 <Input
298 |                                     placeholder="Critical Thinking, Communication, etc."
299 |                                     {...field}
300 |                                 />
301 |                             </FormControl>
302 |                             <FormMessage />
303 |                         </FormItem>
304 |                     )}
305 |                 />
306 |                 <FormField
307 |                     control={form.control}
308 |                     name="description"
309 |                     render={({ field }) => (
310 |                         <FormItem>
311 |                             <FormLabel>Description (optional)</FormLabel>
312 |                             <FormControl>
313 |                                 <Input {...field} />
314 |                             </FormControl>
315 |                             <FormMessage />
316 |                         </FormItem>
317 |                     )}
318 |                 />
319 |                 <Button
320 |                     type="submit"
321 |                     disabled={createMutation.isPending}
322 |                     variant="tactile"
323 |                 >
324 |                     {createMutation.isPending ? (
325 |                         <Loader2 className="h-4 w-4 animate-spin" />
326 |                     ) : (
327 |                         <Plus className="h-4 w-4" />
328 |                     )}{" "}
329 |                     Add
330 |                 </Button>
331 |             </form>
332 |         </Form>
333 |     </Card>
334 |
335 |     <ConfirmDialog
336 |         open={!!deleteTarget}
337 |         onOpenChange={(o: boolean) => !o && setDeleteTarget(null)}
338 |         title="Delete attribute?"
339 |         description="This will permanently remove this graduate attribute and its mappings."
340 |         onConfirm={() => {
341 |             if (deleteTarget)
342 |                 deleteMutation.mutate(deleteTarget, {
343 |                     onSuccess: () => {
344 |                         toast.success("Deleted");
345 |                         setDeleteTarget(null);
346 |                     },
347 |                 });
348 |         }}
349 |         isPending={deleteMutation.isPending}
350 |     />
351 | </div>
352 | );
353 | };
354 |
355 | export default GraduateAttributeManager;
356 |

```

FILE: [src/pages/admin/historical-evidence/HistoricalEvidenceDashboard.tsx](#)

TYPE: .tsx | LINES: 1-321 | SHA256: d95a8206a2d80c54e5e41fd9cc5f051fcc52ce4afbd759bba4a5c025c4e3b8f8

```

1 | // Feature: qa-partner-review-remediation - Req 4 (B4)
2 | // Admin Historical Evidence dashboard. Renders attainment evidence over time
3 | // from the 'mv_historical_evidence' materialized view via the
4 | // `useHistoricalEvidence` hook. The previous placeholder rendered developer
5 | // text ("Requires mv_historical_evidence view"); that is removed entirely so
6 | // no internal object names, migration ids, or developer instructions reach a
7 | // user-facing surface (Req 4.5, 4.7).
8 | //
9 | // Rendering states (mutually exclusive):
10 | //   loading  !' component-level Shimmer
11 | //   error    !' user-friendly error message (distinct from no-data)
12 | //   empty    !' shared NoEvidence empty state
13 | //   data     !' per-semester cards with an outcome/Bloom's attainment table
14 |
15 | import { useMemo } from "react";
16 | import { parseAsString, useQueryState } from "nuqs";
17 | import { useTranslation } from "react-i18next";
18 | import { AlertTriangle, History } from "lucide-react";
19 |
20 | import { Card } from "@components/ui/card";
21 | import { Badge } from "@components/ui/badge";
22 | import {
23 |     Select,
24 |     SelectContent,
25 |     SelectItem,
26 |     SelectTrigger,
27 |     SelectValue,
28 | } from "@components/ui/select";

```

```

29 | import {
30 |   Table,
31 |   TableBody,
32 |   TableCell,
33 |   TableHead,
34 |   TableHeader,
35 |   TableRow,
36 | } from "@components/ui/table";
37 | import { NoEvidence } from "@components/shared/EmptyState";
38 | import { Shimmer } from "@design-system";
39 | import {
40 |   useHistoricalEvidence,
41 |   type HistoricalEvidenceRow,
42 | } from "@hooks/useHistoricalEvidence";
43 | import { historicalEvidenceFilterSchema } from "@lib/schemas/historicalEvidence";
44 | import {
45 |   getAttainmentTextClass,
46 |   getAttainmentBadgeStyle,
47 | } from "@lib/attainmentClassifier";
48 |
49 | // Sentinel for the "no filter" Select option – Radix Select disallows an empty
50 | // string value, so the cleared state is represented by this token and mapped
51 | // back to 'null' (no filter) before reaching the schema.
52 | const ALL = "all";
53 |
54 | // Outcome types the materialized view emits. Kept in sync with the schema enum.
55 | const OUTCOME_TYPE_OPTIONS = ["PLO", "CLO"] as const;
56 | const BLOOMS_OPTIONS = [
57 |   "remembering",
58 |   "understanding",
59 |   "applying",
60 |   "analyzing",
61 |   "evaluating",
62 |   "creating",
63 | ] as const;
64 |
65 | const OUTCOME_TYPE_BADGE: Record<string, string> = {
66 |   ILO: "bg-red-100 text-red-700 border-red-200",
67 |   PLO: "bg-blue-100 text-blue-700 border-blue-200",
68 |   CLO: "bg-green-100 text-green-700 border-green-200",
69 |   SUB_CLO: "bg-green-50 text-green-700 border-green-200",
70 | };
71 |
72 | interface SemesterGroup {
73 |   semesterId: string;
74 |   semesterName: string;
75 |   rows: HistoricalEvidenceRow[];
76 | }
77 |
78 | const HistoricalEvidenceDashboard = () => {
79 |   const { t } = useTranslation("common");
80 |
81 |   // URL-persisted filter state (nuqs). Empty default !' cleared.
82 |   const [outcomeType, setOutcomeType] = useQueryState(
83 |     "type",
84 |     parseAsString.withDefault("")
85 |   );
86 |   const [bloomsLevel, setBloomsLevel] = useQueryState(
87 |     "blooms",
88 |     parseAsString.withDefault("")
89 |   );
90 |
91 |   // Validate the raw URL values through the shared schema so only legal enum
92 |   // members ever reach the query (an unexpected value falls back to "no
93 |   // filter" rather than producing an invalid request).
94 |   const filters = useMemo(() => {
95 |     const parsed = historicalEvidenceFilterSchema.safeParse({
96 |       outcomeType: outcomeType || undefined,
97 |       bloomsLevel: bloomsLevel || undefined,
98 |     });
99 |     return parsed.success ? parsed.data : {};
100 |   }, [outcomeType, bloomsLevel]);
101 |
102 |   const { data, isLoading, isError } = useHistoricalEvidence(filters);
103 |
104 |   // Group rows by semester (the hook returns them ordered by start_date asc).
105 |   const semesterGroups = useMemo<SemesterGroup[]>(() => {
106 |     const groups = new Map<string, SemesterGroup>();
107 |     for (const row of data ?? []) {
108 |       const existing = groups.get(row.semester_id);
109 |       if (existing) {
110 |         existing.rows.push(row);
111 |       } else {
112 |         groups.set(row.semester_id, {
113 |           semesterId: row.semester_id,
114 |           semesterName: row.semester_name,
115 |           rows: [row],
116 |         });
117 |       }
118 |     }
119 |     return Array.from(groups.values());
120 |   }, [data]);
121 |
122 |   const hasData = (data?.length ?? 0) > 0;
123 |
124 |   return (
125 |     <div className="space-y-6">
126 |       <div className="flex flex-col gap-4 sm:flex-row sm:items-center sm:justify-between">
127 |         <h1 className="text-2xl font-bold tracking-tight">
128 |           Historical Evidence
129 |         </h1>
130 |
131 |         <div className="flex flex-wrap items-center gap-3">
132 |           <Select

```

```

133     value={outcomeType || ALL}
134     onValueChange={({value}) =>
135       setOutcomeType(value === ALL ? "" : value)
136     }
137   >
138     <SelectTrigger className="w-44 bg-white">
139       <SelectValue placeholder="All outcome types" />
140     </SelectTrigger>
141     <SelectContent>
142       <SelectItem value={ALL}>All outcome types</SelectItem>
143       {OUTCOME_TYPE_OPTIONS.map((type) => (
144         <SelectItem key={type} value={type}>
145           {type}
146         </SelectItem>
147       ))}
148     </SelectContent>
149   </Select>
150
151   <Select
152     value={bloomsLevel || ALL}
153     onValueChange={({value}) =>
154       setBloomsLevel(value === ALL ? "" : value)
155     }
156   >
157     <SelectTrigger className="w-48 bg-white">
158       <SelectValue placeholder="All Bloom's levels" />
159     </SelectTrigger>
160     <SelectContent>
161       <SelectItem value={ALL}>All Bloom's levels</SelectItem>
162       {BLOOMS_OPTIONS.map((level) => (
163         <SelectItem key={level} value={level}>
164           {t(`blooms.${level}`)}
165         </SelectItem>
166       ))}
167     </SelectContent>
168   </Select>
169 </div>
170 </div>
171
172 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
173   <div
174     className="px-6 py-4 flex items-center gap-2"
175     style={{ background: "var(--brand-gradient)" }}
176   >
177     <History className="h-5 w-5 text-white" />
178     <h2 className="text-lg font-bold tracking-tight text-white">
179       Evidence Analytics
180     </h2>
181   </div>
182
183   <div className="p-6">
184     {isLoading ? (
185       <div className="space-y-4">
186         <Shimmer className="h-10 w-48 rounded-lg" />
187         <Shimmer className="h-48 rounded-lg" />
188       </div>
189     ) : isError ? (
190       <div className="flex flex-col items-center justify-center py-12 text-center">
191         <AlertTriangle className="mb-3 h-10 w-10 text-amber-500" />
192         <p className="text-sm font-semibold text-gray-700">
193           We couldn't load historical evidence right now.
194         </p>
195         <p className="mt-1 text-xs text-gray-500">
196           Please refresh the page or try again in a moment.
197         </p>
198       </div>
199     ) : !hasData ? (
200       <NoEvidence className="border-0 shadow-none py-4" />
201     ) : (
202       <div className="space-y-8">
203         {semesterGroups.map((group) => (
204           <SemesterSection key={group.semesterId} group={group} />
205         ))}
206       </div>
207     )}
208   </div>
209 </Card>
210 </div>
211 );
212 };
213
214 interface SemesterSectionProps {
215   group: SemesterGroup;
216 }
217
218 const SemesterSection = ({ group }: SemesterSectionProps) => {
219   const { t } = useTranslation("common");
220
221   return (
222     <section className="space-y-3">
223       <div className="flex items-baseline justify-between">
224         <h3 className="text-lg font-bold tracking-tight text-gray-900">
225           {group.semesterName || "-"}
226         </h3>
227         <span className="text-xs text-gray-500">
228           {group.rows.length} outcome{group.rows.length === 1 ? "" : "s"}
229         </span>
230       </div>
231
232       <div className="overflow-x-auto rounded-lg border border-slate-200">
233         <Table>
234           <TableHeader>
235             <TableRow>
236               <TableHead>Outcome</TableHead>

```

```

237 |         <TableHead>Bloom's Level</TableHead>
238 |         <TableHead className="text-right">Evidence</TableHead>
239 |         <TableHead className="text-right">Avg Score</TableHead>
240 |         <TableHead className="text-right">
241 |           {t("attainment.excellent")}
242 |         </TableHead>
243 |         <TableHead className="text-right">
244 |           {t("attainment.satisfactory")}
245 |         </TableHead>
246 |         <TableHead className="text-right">
247 |           {t("attainment.developing")}
248 |         </TableHead>
249 |         <TableHead className="text-right">
250 |           {t("attainment.notYet")}
251 |         </TableHead>
252 |       </TableRow>
253 |     </TableHeader>
254 |     <TableBody>
255 |       {group.rows.map((row, index) => (
256 |         <TableRow
257 |           key={`_${row.outcome_type}-${row.blooms_level ?? "na"}-${index}`}
258 |         >
259 |           <TableCell>
260 |             <Badge
261 |               variant="outline"
262 |               className={
263 |                 OUTCOME_TYPE_BADGE[row.outcome_type] ??
264 |                 "bg-slate-100 text-slate-700 border-slate-200"
265 |               }
266 |             >
267 |               {row.outcome_type || "-"}
268 |             </Badge>
269 |           </TableCell>
270 |           <TableCell className="text-sm text-gray-600">
271 |             {row.blooms_level ? t(`blooms.${row.blooms_level}`) : "-"}
272 |           </TableCell>
273 |           <TableCell className="text-right text-sm font-medium tabular-nums">
274 |             {row.evidence_count}
275 |           </TableCell>
276 |           <TableCell
277 |             className={`text-right text-sm font-bold tabular-nums ${getAttainmentTextClass(
278 |               row.avg_score
279 |             )}`}
280 |           >
281 |             {Math.round(row.avg_score)}%
282 |           </TableCell>
283 |           <TableCell className="text-right">
284 |             <BandCount count={row.excellent_count} percent={90} />
285 |           </TableCell>
286 |           <TableCell className="text-right">
287 |             <BandCount count={row.satisfactory_count} percent={75} />
288 |           </TableCell>
289 |           <TableCell className="text-right">
290 |             <BandCount count={row.developing_count} percent={60} />
291 |           </TableCell>
292 |           <TableCell className="text-right">
293 |             <BandCount count={row.not_yet_count} percent={30} />
294 |           </TableCell>
295 |         </TableRow>
296 |       ))}
297 |     </TableBody>
298 |   </Table>
299 | </div>
300 | </section>
301 | );
302 | };
303 |
304 | interface BandCountProps {
305 |   count: number;
306 |   // Representative percentage for the band, used only to pick the band color.
307 |   percent: number;
308 | }
309 |
310 | const BandCount = ({ count, percent }: BandCountProps) => (
311 |   <span
312 |     className={`inline-flex min-w-8 justify-center rounded-md border px-2 py-0.5 text-xs font-bold tabular-nums
313 |       percent
314 |     `}
315 |   >
316 |     {count}
317 |   </span>
318 | );
319 |
320 | export default HistoricalEvidenceDashboard;
321 |

```

FILE: [src/pages/admin/import/DataImportPage.tsx](#)

TYPE: .tsx | LINES: 1-265 | SHA256: 8eafc9dfa6482e94a3d461d1e83563b2fa2556eb4a32290f3484cf548f0e4dd6

```

1 | // Task 108.3: Data Import UI – CSV upload with type selector, preview, and results
2 |
3 | import { useState } from "react";
4 | import { Card } from "@components/ui/card";
5 | import { Button } from "@components/ui/button";
6 | import { Input } from "@components/ui/input";
7 | import {
8 |   Select,
9 |   SelectContent,
10 |   SelectItem,
11 |   SelectTrigger,
12 |   SelectValue,
13 | } from "@components/ui/select";
14 | import {
15 |   Upload,

```

```

16 | Download,
17 | Loader2,
18 | FileText,
19 | CheckCircle,
20 | XCircle,
21 | } from "lucide-react";
22 | import { toast } from "sonner";
23 | import { useDataImport, type ImportResult } from "@hooks/useDataImport";
24 |
25 | const IMPORT_TYPES = [
26 |   {
27 |     value: "courses",
28 |     label: "Courses",
29 |     template: "/docs/import-templates/courses.csv",
30 |   },
31 |   {
32 |     value: "outcomes",
33 |     label: "Outcomes (ILO/PLO/CLO)",
34 |     template: "/docs/import-templates/outcomes.csv",
35 |   },
36 |   {
37 |     value: "grades",
38 |     label: "Grades",
39 |     template: "/docs/import-templates/grades.csv",
40 |   },
41 |   {
42 |     value: "enrollments",
43 |     label: "Enrollments",
44 |     template: "/docs/import-templates/enrollments.csv",
45 |   },
46 | ] as const;
47 |
48 | const DataImportPage = () => {
49 |   const [importType, setImportType] = useState("");
50 |   const [file, setFile] = useState<File | null>(null);
51 |   const [preview, setPreview] = useState<string[][]>([]);
52 |   const importMutation = useDataImport();
53 |
54 |   const handleFileChange = async (e: React.ChangeEvent<HTMLInputElement>) => {
55 |     const f = e.target.files?.[0];
56 |     if (!f) return;
57 |     setFile(f);
58 |
59 |     // Parse preview (first 5 rows)
60 |     const text = await f.text();
61 |     const lines = text.trim().split("\n").slice(0, 6);
62 |     setPreview(lines.map((line) => line.split(",").map((v) => v.trim())));
63 |   };
64 |
65 |   const handleImport = async () => {
66 |     if (!file || !importType) return;
67 |     const text = await file.text();
68 |     importMutation.mutate(
69 |       { import_type: importType, csv_content: text },
70 |       {
71 |         onSuccess: (result: ImportResult) => {
72 |           toast.success(
73 |             `Imported ${result.imported} of ${result.total_rows} rows`
74 |           );
75 |           if (result.errors.length > 0) {
76 |             toast.error(`${result.skipped} rows skipped – check error report`);
77 |           }
78 |         },
79 |         onError: (err: Error) => toast.error(err.message),
80 |       },
81 |     );
82 |   };
83 |
84 |   const selectedTemplate = IMPORT_TYPES.find((t) => t.value === importType);
85 |
86 |   return (
87 |     <div className="space-y-6">
88 |       <h1 className="text-2xl font-bold tracking-tight">Data Import</h1>
89 |
90 |       {/* Import type selector */}
91 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
92 |         <div className="flex items-center gap-4">
93 |           <div className="flex-1 max-w-xs">
94 |             <label
95 |               htmlFor="import-type-select"
96 |               className="text-sm font-medium text-gray-700 mb-1 block">
97 |               >
98 |             Import Type
99 |             </label>
100 |            <Select value={importType} onChange={setImportType}>
101 |              <SelectTrigger id="import-type-select" className="bg-white">
102 |                <SelectValue placeholder="Select type" />
103 |              </SelectTrigger>
104 |              <SelectContent>
105 |                {IMPORT_TYPES.map((t) => (
106 |                  <SelectItem key={t.value} value={t.value}>
107 |                    {t.label}
108 |                  </SelectItem>
109 |                ))}
110 |              </SelectContent>
111 |            </Select>
112 |          </div>
113 |
114 |          {selectedTemplate && (
115 |            <div className="pt-5">
116 |              <a
117 |                href={selectedTemplate.template}>
118 |                download
119 |              </a>
120 |            </div>
121 |          )}
122 |        </div>
123 |      </Card>
124 |    </div>
125 |  );

```

```

120     >
121     <Download className="h-4 w-4" />
122     Download Template
123   </a>
124 </div>
125   })
126 </div>
127 </Card>
128
129 {/* File upload */}
130 {importType && (
131   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
132     <div
133       className="px-6 py-4 flex items-center gap-2"
134       style={{
135         background: "var(--brand-gradient)",
136       }}
137     >
138       <Upload className="h-5 w-5 text-white" />
139       <h2 className="text-lg font-bold tracking-tight text-white">
140         Upload CSV
141       </h2>
142     </div>
143     <div className="p-6 space-y-4">
144       <Input
145         type="file"
146         accept=".csv"
147         onChange={handleFileChange}
148         className="max-w-md"
149       />
150
151       {/* Preview table */}
152       {preview.length > 0 && (
153         <div className="overflow-x-auto">
154           <p className="text-xs text-slate-500 mb-2">
155             Preview (first {Math.min(preview.length - 1, 5)} rows):
156           </p>
157           <table className="w-full text-xs border-collapse">
158             <thead>
159               <tr>
160                 {preview[0]?.map((header, i) => (
161                   <th
162                     key={i}
163                     className="p-2 border border-slate-200 bg-slate-50 text-slate-500 font-bold text-sta
164                   >
165                     {header}
166                   </th>
167                 ))}
168             </tr>
169             </thead>
170             <tbody>
171               {preview.slice(1).map((row, ri) => (
172                 <tr key={ri}>
173                   {row.map((cell, ci) => (
174                     <td
175                       key={ci}
176                       className="p-2 border border-slate-200 text-slate-700"
177                     >
178                       {cell}
179                     </td>
180                   ))}
181                 </tr>
182               ))}
183             </tbody>
184           </table>
185         </div>
186       )}
187
188       <Button
189         onClick={handleImport}
190         disabled={!file || importMutation.isPending}
191         variant="tactile"
192       >
193         {importMutation.isPending ? (
194           <Loader2 className="h-4 w-4 animate-spin" />
195         ) : (
196           <FileText className="h-4 w-4" />
197         )}
198       </Button>
199     </div>
200   </Card>
201 )}
202
203 {/* Results */}
204 {importMutation.data && (
205   <Card className="bg-white border-0 shadow-md rounded-xl p-6">
206     <h2 className="text-lg font-bold tracking-tight mb-4">
207       Import Results
208     </h2>
209     <div className="grid grid-cols-3 gap-4 mb-4">
210       <div className="text-center">
211         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
212           Total Rows
213         </p>
214         <p className="text-2xl font-black">
215           {importMutation.data.total_rows}
216         </p>
217       </div>
218       <div className="text-center">
219         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
220           Imported
221         </p>
222         <p className="text-2xl font-black text-green-600">

```

```

224         {importMutation.data.imported}
225     </p>
226 </div>
227 <div className="text-center">
228   <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
229     Skipped
230   </p>
231   <p className="text-2xl font-black text-red-600">
232     {importMutation.data.skipped}
233   </p>
234 </div>
235 </div>
236
237 {importMutation.data.errors.length > 0 && (
238   <div className="space-y-1">
239     <p className="text-sm font-medium text-red-600 mb-2">Errors:</p>
240     {importMutation.data.errors.map(
241       (err: { row: number; message: string }, i: number) => (
242         <div key={i} className="flex items-center gap-2 text-xs">
243           <XCircle className="h-3 w-3 text-red-500 shrink-0" />
244           <span className="text-slate-500">Row {err.row}</span>
245           <span className="text-slate-700">{err.message}</span>
246         </div>
247       )
248     )}
249   </div>
250 )}
251
252 {importMutation.data.errors.length === 0 && (
253   <div className="flex items-center gap-2 text-sm text-green-600">
254     <CheckCircle className="h-4 w-4" />
255     All rows imported successfully
256   </div>
257 )}
258 </Card>
259 )}
260 </div>
261 );
262 };
263
264 export default DataImportPage;
265

```

FILE: [src/pages/admin/marketplace/csvExport.ts](#)

TYPE: .ts | LINES: 1-105 | SHA256: 35da879588510c3cc4c0013dba778d95816aed2b3baa0709e1483b5389da178f

```

1 // =====
2 // csvExport - CSV export for purchase history on admin analytics page
3 // =====
4
5 import { supabase } from "@/lib/supabase";
6 import { toast } from "sonner";
7
8 interface PurchaseRow {
9   id: string;
10  student_id: string;
11  student_name: string;
12  item_name: string;
13  category: string;
14  xp_cost: number;
15  status: string;
16  purchased_at: string;
17 }
18
19 /**
20  * Fetches all purchase history and triggers a CSV download.
21  */
22 export async function exportPurchaseHistoryCSV(): Promise<void> {
23   try {
24     // eslint-disable-next-line @typescript-eslint/no-explicit-any
25     const { data: purchases, error } = await (supabase as any)
26       .from("xp_purchases")
27       .select(
28         `
29           id,
30           student_id,
31           xp_cost,
32           status,
33           purchased_at,
34           profiles:student_id (full_name),
35           marketplace_items:item_id (name, category)
36         `
37       )
38       .order("purchased_at", { ascending: false });
39
40     if (error) throw error;
41
42     const rows: PurchaseRow[] = (
43       purchases ?? []
44     ) as Array<Record<string, unknown>>
45     ).map((row) => {
46       const profile = row.profiles as Record<string, unknown> | null;
47       const item = row.marketplace_items as Record<string, unknown> | null;
48
49       return {
50         id: row.id as string,
51         student_id: row.student_id as string,
52         student_name: (profile?.full_name as string) ?? "Unknown",
53         item_name: (item?.name as string) ?? "Unknown",
54         category: (item?.category as string) ?? "unknown",
55         xp_cost: row.xp_cost as number,
56         status: row.status as string,
57         purchased_at: row.purchased_at as string,
58       };
59     });
60   } catch {
61     //
62   }
63 }

```

```

59 |
60 | // Build CSV
61 | const headers = [
62 |   "Purchase ID",
63 |   "Student ID",
64 |   "Student Name",
65 |   "Item",
66 |   "Category",
67 |   "XP Cost",
68 |   "Status",
69 |   "Date",
70 | ];
71 | const csvLines = [
72 |   headers.join(","),
73 |   ...rows.map((r) =>
74 |     [
75 |       r.id,
76 |       r.student_id,
77 |       `${r.student_name.replace(/"/g, '""')}`,
78 |       `${r.item_name.replace(/"/g, '""')}`,
79 |       r.category,
80 |       r.xp_cost,
81 |       r.status,
82 |       r.purchased_at,
83 |     ].join(",")
84 |   ),
85 | ];
86 |
87 | const csvContent = csvLines.join("\n");
88 | const blob = new Blob([csvContent], { type: "text/csv;charset=utf-8;" });
89 | const url = URL.createObjectURL(blob);
90 | const link = document.createElement("a");
91 | link.href = url;
92 | link.download = `marketplace-purchases-${new Date()
93 |   .toISOString()
94 |   .slice(0, 10)}.csv`;
95 | document.body.appendChild(link);
96 | link.click();
97 | document.body.removeChild(link);
98 | URL.revokeObjectURL(url);
99 |
100 | toast.success(`Exported ${rows.length} purchase records`);
101 | } catch (err) {
102 |   toast.error(err instanceof Error ? err.message : "Failed to export CSV");
103 | }
104 | }
105 |

```

FILE: [src/pages/admin/marketplace/ItemForm.tsx](#)

TYPE: .tsx | LINES: 1-361 | SHA256: 5e15a0648da79920f1f2fd408fa2d6d84e6ebe5add9919a9a1cf7479eedc1f66

```

1 | // =====
2 | // ItemForm – Create/edit marketplace item form with React Hook Form + Zod
3 | // =====
4 |
5 | import { useForm } from "react-hook-form";
6 | import { zodResolver } from "@hookform/resolvers/zod";
7 | import {
8 |   createMarketplaceItemSchema,
9 |   type CreateMarketplaceItemInput,
10 | } from "@lib/marketplaceSchemas";
11 | import {
12 |   useCreateMarketplaceItem,
13 |   useUpdateMarketplaceItem,
14 | } from "@hooks/useMarketplaceAdmin";
15 | import type { AdminMarketplaceItem } from "@hooks/useMarketplaceAdmin";
16 | import {
17 |   Form,
18 |   FormField,
19 |   FormItem,
20 |   FormLabel,
21 |   FormControl,
22 |   FormMessage,
23 | } from "@components/ui/form";
24 | import { Input } from "@components/ui/input";
25 | import { Textarea } from "@components/ui/textarea";
26 | import {
27 |   Select,
28 |   SelectContent,
29 |   SelectItem,
30 |   SelectTrigger,
31 |   SelectValue,
32 | } from "@components/ui/select";
33 | import { Button } from "@components/ui/button";
34 | import { Card } from "@components/ui/card";
35 | import { ArrowLeft, Loader2 } from "lucide-react";
36 | import { toast } from "sonner";
37 |
38 | interface ItemFormProps {
39 |   item: AdminMarketplaceItem | null;
40 |   onClose: () => void;
41 | }
42 |
43 | const subCategoryOptions: Record<
44 |   string,
45 |   Array<{ value: string; label: string }>
46 | > = {
47 |   cosmetic: [
48 |     { value: "profile_theme", label: "Profile Theme" },
49 |     { value: "avatar_frame", label: "Avatar Frame" },
50 |     { value: "display_title", label: "Display Title" },
51 |   ],
52 |   educational_perk: [
53 |     { value: "extra_quiz_attempt", label: "Extra Quiz Attempt" },

```



```

54 |     { value: "deadline_extension", label: "Deadline Extension" },
55 |     { value: "hint_token", label: "Hint Token Pack" },
56 |   ],
57 |   power_up: [
58 |     { value: "xp_boost", label: "XP Boost" },
59 |     { value: "streak_shield", label: "Streak Shield" },
60 |   ],
61 | };
62 |
63 | const ItemForm = ({ item, onClose }: ItemFormProps) => {
64 |   const isEditing = !!item;
65 |   const createItem = useCreateMarketplaceItem();
66 |   const updateItem = useUpdateMarketplaceItem();
67 |
68 |   const form = useForm<CreateMarketplaceItemInput>({
69 |     resolver: zodResolver(createMarketplaceItemSchema) as never,
70 |     defaultValues: item
71 |     ? {
72 |       name: item.name,
73 |       description: item.description,
74 |       category: item.category as CreateMarketplaceItemInput["category"],
75 |       sub_category:
76 |         item.sub_category as CreateMarketplaceItemInput["sub_category"],
77 |       xp_price: item.xp_price,
78 |       level_requirement: item.level_requirement,
79 |       stock_type:
80 |         item.stock_type as CreateMarketplaceItemInput["stock_type"],
81 |       stock_quantity: item.stock_quantity,
82 |       icon_identifier: item.icon_identifier,
83 |       metadata: item.metadata,
84 |     }
85 |     : {
86 |       name: "",
87 |       description: "",
88 |       category: "cosmetic",
89 |       sub_category: "profile_theme",
90 |       xp_price: 100,
91 |       level_requirement: 0,
92 |       stock_type: "unlimited",
93 |       stock_quantity: null,
94 |       icon_identifier: "sparkles",
95 |     },
96 |   });
97 |
98 |   const watchCategory = form.watch("category");
99 |   const watchStockType = form.watch("stock_type");
100 |
101 |   const onSubmit = (data: CreateMarketplaceItemInput) => {
102 |     if (isEditing && item) {
103 |       updateItem.mutate(
104 |         { itemId: item.id, data },
105 |         {
106 |           onSuccess: () => {
107 |             toast.success("Item updated");
108 |             onClose();
109 |           },
110 |           onError: (err) => toast.error(err.message),
111 |         }
112 |       );
113 |     } else {
114 |       createItem.mutate(data, {
115 |         onSuccess: () => {
116 |           toast.success("Item created");
117 |           onClose();
118 |         },
119 |         onError: (err) => toast.error(err.message),
120 |       });
121 |     }
122 |   };
123 |
124 |   const isPending = createItem.isPending || updateItem.isPending;
125 |
126 |   return (
127 |     <div className="space-y-6 max-w-2xl">
128 |       <div className="flex items-center gap-3">
129 |         <Button variant="ghost" size="sm" onClick={onClose}>
130 |           <ArrowLeft className="h-4 w-4" /> Back
131 |         </Button>
132 |         <h1 className="text-2xl font-bold tracking-tight">
133 |           {isEditing ? "Edit Item" : "Create Item"}
134 |         </h1>
135 |       </div>
136 |
137 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
138 |         <Form {...form}>
139 |           <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
140 |             <FormField
141 |               control={form.control}
142 |               name="name"
143 |               render={({ field }) => (
144 |                 <FormItem>
145 |                   <FormLabel>Name</FormLabel>
146 |                   <FormControl>
147 |                     <Input placeholder="e.g. Ocean Blue Theme" {...field} />
148 |                   </FormControl>
149 |                   <FormMessage />
150 |                 </FormItem>
151 |               )}
152 |             />
153 |
154 |             <FormField
155 |               control={form.control}
156 |               name="description"
157 |               render={({ field }) => (

```

```

158 |         <FormItem>
159 |             <FormLabel>Description</FormLabel>
160 |             <FormControl>
161 |                 <Textarea
162 |                     placeholder="Describe the item..."
163 |                     rows={3}
164 |                     {...field}
165 |                 />
166 |             </FormControl>
167 |             <FormMessage />
168 |         </FormItem>
169 |     )}
170 | />
171 |
172 | <div className="grid grid-cols-2 gap-4">
173 |     <FormField
174 |         control={form.control}
175 |         name="category"
176 |         render={({ field }) => (
177 |             <FormItem>
178 |                 <FormLabel>Category</FormLabel>
179 |                 <Select
180 |                     onValueChange={field.onChange}
181 |                     defaultValue={field.value}
182 |                 >
183 |                     <FormControl>
184 |                         <SelectTrigger>
185 |                             <SelectValue placeholder="Select category" />
186 |                         </SelectTrigger>
187 |                     </FormControl>
188 |                     <SelectContent>
189 |                         <SelectItem value="cosmetic">Cosmetic</SelectItem>
190 |                         <SelectItem value="educational_perk">
191 |                             Educational Perk
192 |                         </SelectItem>
193 |                         <SelectItem value="power_up">Power-up</SelectItem>
194 |                     </SelectContent>
195 |                 </Select>
196 |                 <FormMessage />
197 |             </FormItem>
198 |         )}
199 |     />
200 |
201 |     <FormField
202 |         control={form.control}
203 |         name="sub_category"
204 |         render={({ field }) => (
205 |             <FormItem>
206 |                 <FormLabel>Sub-Category</FormLabel>
207 |                 <Select
208 |                     onValueChange={field.onChange}
209 |                     defaultValue={field.value}
210 |                 >
211 |                     <FormControl>
212 |                         <SelectTrigger>
213 |                             <SelectValue placeholder="Select sub-category" />
214 |                         </SelectTrigger>
215 |                     </FormControl>
216 |                     <SelectContent>
217 |                         {(subCategoryOptions[watchCategory] ?? []).map(
218 |                             (opt) => (
219 |                                 <SelectItem key={opt.value} value={opt.value}>
220 |                                     {opt.label}
221 |                                 </SelectItem>
222 |                             )
223 |                         )}
224 |                     </SelectContent>
225 |                 </Select>
226 |                 <FormMessage />
227 |             </FormItem>
228 |         )}
229 |     />
230 | </div>
231 |
232 | <div className="grid grid-cols-2 gap-4">
233 |     <FormField
234 |         control={form.control}
235 |         name="xp_price"
236 |         render={({ field }) => (
237 |             <FormItem>
238 |                 <FormLabel>XP Price</FormLabel>
239 |                 <FormControl>
240 |                     <Input
241 |                         type="number"
242 |                         min={1}
243 |                         {...field}
244 |                         onChange={(e) => field.onChange(Number(e.target.value))}
245 |                     />
246 |                 </FormControl>
247 |                 <FormMessage />
248 |             </FormItem>
249 |         )}
250 |     />
251 |
252 |     <FormField
253 |         control={form.control}
254 |         name="level_requirement"
255 |         render={({ field }) => (
256 |             <FormItem>
257 |                 <FormLabel>Level Requirement</FormLabel>
258 |                 <FormControl>
259 |                     <Input
260 |                         type="number"
261 |                         min={0}

```

```

262         {...field}
263         onChange={(e) => field.onChange(Number(e.target.value))}
264     />
265     </FormControl>
266     <FormMessage />
267 </FormItem>
268 }}
269 />
270 </div>
271
272 <div className="grid grid-cols-2 gap-4">
273   <FormField
274     control={form.control}
275     name="stock_type"
276     render={({ field }) => (
277       <FormItem>
278         <FormLabel>Stock Type</FormLabel>
279         <Select
280           onChange={field.onChange}
281           defaultValue={field.value}
282         >
283           <FormControl>
284             <SelectTrigger>
285               <SelectValue placeholder="Select stock type" />
286             </SelectTrigger>
287           </FormControl>
288           <SelectContent>
289             <SelectItem value="unlimited">Unlimited</SelectItem>
290             <SelectItem value="limited">Limited</SelectItem>
291             <SelectItem value="one_per_student">
292               One per Student
293             </SelectItem>
294           </SelectContent>
295         </Select>
296         <FormMessage />
297       </FormItem>
298     )}
299   />
300
301   {watchStockType === "limited" && (
302     <FormField
303       control={form.control}
304       name="stock_quantity"
305       render={({ field }) => (
306         <FormItem>
307           <FormLabel>Stock Quantity</FormLabel>
308           <FormControl>
309             <Input
310               type="number"
311               min={1}
312               value={field.value ?? ""}
313               onChange={(e) =>
314                 field.onChange(
315                   e.target.value ? Number(e.target.value) : null
316                 )
317             >
318           </>
319           </FormControl>
320           <FormMessage />
321         </FormItem>
322       )}
323     />
324   )}
325 </div>
326
327 <FormField
328   control={form.control}
329   name="icon_identifier"
330   render={({ field }) => (
331     <FormItem>
332       <FormLabel>Icon Identifier</FormLabel>
333       <FormControl>
334         <Input
335           placeholder="e.g. sparkles, shield, zap"
336           {...field}
337         />
338       </FormControl>
339       <FormMessage />
340     </FormItem>
341   )}
342 />
343
344 <div className="flex items-center gap-3 pt-2">
345   <Button type="submit" disabled={isPending} variant="tactile">
346     {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
347     {isEditing ? "Update Item" : "Create Item"}
348   </Button>
349   <Button type="button" variant="outline" onClick={onClose}>
350     Cancel
351   </Button>
352 </div>
353 </form>
354 </Form>
355 </Card>
356 </div>
357 );
358 };
359
360 export default ItemForm;
361

```

FILE: src/pages/admin/marketplace/KnowledgeQuestManager.tsx

TYPE: .tsx | LINES: 1-322 | SHA256: c7586ee7a5731a5f7c7ea479783baf216643047c8dde6056e8d9eece234c6b6

```
1 // =====
2 // KnowledgeQuestManager - Admin quest CRUD with DataTable
3 // Task 21.6
4 // =====
5
6 import { useState } from "react";
7 import { Card } from "@components/ui/card";
8 import { Badge } from "@components/ui/badge";
9 import { Button } from "@components/ui/button";
10 import { Input } from "@components/ui/input";
11 import { Label } from "@components/ui/label";
12 import { Textarea } from "@components/ui/textarea";
13 import {
14   Dialog,
15   DialogContent,
16   DialogFooter,
17   DialogHeader,
18   DialogTitle,
19   DialogTrigger,
20 } from "@components/ui/dialog";
21 import {
22   Select,
23   SelectContent,
24   SelectItem,
25   SelectTrigger,
26   SelectValue,
27 } from "@components/ui/select";
28 import { Plus, Search, Loader2, BookOpen } from "lucide-react";
29 import {
30   useAdminKnowledgeQuests,
31   useCreateKnowledgeQuest,
32 } from "@hooks/useKnowledgeQuestAdmin";
33
34 const KnowledgeQuestManager = () => {
35   const { data: quests, isLoading } = useAdminKnowledgeQuests();
36   const createQuest = useCreateKnowledgeQuest();
37   const [search, setSearch] = useState("");
38   const [dialogOpen, setDialogOpen] = useState(false);
39   // Compute defaults inside useState initializer so they are pure on render.
40   const [form, setForm] = useState(() => {
41     const todayDate = new Date().toISOString().slice(0, 10);
42     const oneWeekDate = new Date(Date.now() + 7 * 24 * 60 * 60 * 1000)
43       .toISOString()
44       .slice(0, 10);
45     return {
46       title: "",
47       description: "",
48       quest_type: "quiz_challenge" as
49         | "quiz_challenge"
50         | "content_creation"
51         | "peer_review",
49       start_date: todayDate,
50       end_date: oneWeekDate,
51       reward_xp_amount: 100,
52     };
53   });
54
55   const filteredQuests = (quests ?? []).filter((q) =>
56     (q as Record<string, unknown>).title
57       ?.toString()
58       .toLowerCase()
59       .includes(search.toLowerCase())
60   );
61
62   const handleSubmit = (e: React.FormEvent) => {
63     e.preventDefault();
64     if (!form.title.trim() || !form.description.trim()) return;
65     createQuest.mutate(
66       {
67         title: form.title,
68         description: form.description,
69         quest_type: form.quest_type,
70         target_clo_ids: [],
71         // Convert YYYY-MM-DD to ISO datetime (start of day, end of day UTC)
72         start_date: new Date(form.start_date).toISOString(),
73         end_date: new Date(form.end_date + "T23:59:59").toISOString(),
74         reward_type: "xp",
75         reward_item_id: null,
76         reward_xp_amount: form.reward_xp_amount,
77       },
78       {
79         onSuccess: () => {
80           setDialogOpen(false);
81           const todayDate = new Date().toISOString().slice(0, 10);
82           const oneWeekDate = new Date(Date.now() + 7 * 24 * 60 * 60 * 1000)
83             .toISOString()
84             .slice(0, 10);
85           setForm({
86             title: "",
87             description: "",
88             quest_type: "quiz_challenge",
89             start_date: todayDate,
90             end_date: oneWeekDate,
91             reward_xp_amount: 100,
92           });
93         },
94       }
95     );
96   };
97
98   return (
99     <div>
100       <div>
101         <div>
```

```

102 | <div className="space-y-6">
103 |   <div className="flex items-center justify-between">
104 |     <h1 className="text-2xl font-bold tracking-tight">Knowledge Quests</h1>
105 |
106 |     <Dialog open={dialogOpen} onOpenChange={setDialogOpen}>
107 |       <DialogTrigger asChild>
108 |         <Button variant="tactile">
109 |           <Plus className="h-4 w-4" /> Create Quest
110 |         </Button>
111 |       </DialogTrigger>
112 |       <DialogContent className="max-w-md">
113 |         <DialogHeader>
114 |           <DialogTitle>New Knowledge Quest</DialogTitle>
115 |         </DialogHeader>
116 |
117 |         <form onSubmit={handleSubmit} className="space-y-4">
118 |           <div className="space-y-1.5">
119 |             <Label htmlFor="quest-title">Title</Label>
120 |             <Input
121 |               id="quest-title"
122 |               value={form.title}
123 |               onChange={(e) =>
124 |                 setForm((f) => ({ ...f, title: e.target.value })))
125 |             >
126 |               <div>
127 |                 <div>required</div>
128 |                 <div>placeholder="e.g., Master the Periodic Table"</div>
129 |               </div>
130 |             </div>
131 |
132 |             <div className="space-y-1.5">
133 |               <Label htmlFor="quest-description">Description</Label>
134 |               <Textarea
135 |                 id="quest-description"
136 |                 value={form.description}
137 |                 onChange={(e) =>
138 |                   setForm((f) => ({ ...f, description: e.target.value })))
139 |               >
140 |                 <div>required</div>
141 |                 <div>rows={3}</div>
142 |                 <div>placeholder="What students will accomplish"</div>
143 |               </div>
144 |             </div>
145 |
146 |             <div className="space-y-1.5">
147 |               <Label>Quest type</Label>
148 |               <Select
149 |                 value={form.quest_type}
150 |                 onChange={(value) =>
151 |                   setForm((f) => ({
152 |                     ...f,
153 |                     quest_type: value as typeof f.quest_type,
154 |                   })))
155 |               >
156 |                 <SelectTrigger>
157 |                   <SelectValue />
158 |                 </SelectTrigger>
159 |                 <SelectContent>
160 |                   <SelectItem value="quiz_challenge">
161 |                     Quiz Challenge
162 |                   </SelectItem>
163 |                   <SelectItem value="content_creation">
164 |                     Content Creation
165 |                   </SelectItem>
166 |                   <SelectItem value="peer_review">Peer Review</SelectItem>
167 |                 </SelectContent>
168 |               </Select>
169 |             </div>
170 |
171 |             <div className="grid grid-cols-2 gap-3">
172 |               <div className="space-y-1.5">
173 |                 <Label htmlFor="quest-start">Starts</Label>
174 |                 <Input
175 |                   id="quest-start"
176 |                   type="date"
177 |                   value={form.start_date}
178 |                   onChange={(e) =>
179 |                     setForm((f) => ({ ...f, start_date: e.target.value })))
180 |                 >
181 |                   <div>required</div>
182 |                 </div>
183 |               </div>
184 |               <div className="space-y-1.5">
185 |                 <Label htmlFor="quest-end">Ends</Label>
186 |                 <Input
187 |                   id="quest-end"
188 |                   type="date"
189 |                   value={form.end_date}
190 |                   onChange={(e) =>
191 |                     setForm((f) => ({ ...f, end_date: e.target.value })))
192 |                 >
193 |                   <div>required</div>
194 |                 </div>
195 |               </div>
196 |             </div>
197 |
198 |             <div className="space-y-1.5">
199 |               <Label htmlFor="quest-xp">Reward XP</Label>
200 |               <Input
201 |                 id="quest-xp"
202 |                 type="number"
203 |                 min={1}
204 |                 value={form.reward_xp_amount}
205 |                 onChange={(e) =>

```

```

206         setForm((f) => ({
207             ...f,
208             reward_xp_amount: Number(e.target.value),
209         })))
210     }
211     required
212 }
213 </div>
214
215 <DialogFooter>
216   <Button
217     type="button"
218     variant="outline"
219     onClick={() => setDialogOpen(false)}
220   >
221     Cancel
222   </Button>
223   <Button
224     type="submit"
225     disabled={createQuest.isPending}
226     variant="tactile"
227   >
228     {createQuest.isPending && (
229       <Loader2 className="h-4 w-4 animate-spin me-2" />
230     )}
231     Create
232   </Button>
233 </DialogFooter>
234 </form>
235 </DialogContent>
236 </Dialog>
237 </div>
238
239 <div className="flex items-center gap-4">
240   <div className="relative flex-1 max-w-sm">
241     <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
242     <Input
243       placeholder="Search quests..."
244       value={search}
245       onChange={(e) => setSearch(e.target.value)}
246       className="ps-9"
247     />
248   </div>
249 </div>
250
251 {isLoading ? (
252   <div className="flex justify-center py-12">
253     <Loader2 className="h-6 w-6 animate-spin text-blue-500" />
254   </div>
255 ) : filteredQuests.length === 0 ? (
256   <Card className="bg-white border-0 shadow-md rounded-xl p-12 text-center">
257     <BookOpen className="h-10 w-10 text-gray-300 mx-auto mb-3" />
258     <p className="text-sm text-gray-500">
259       No knowledge quests yet. Create one to engage students with focused
260       learning challenges.
261     </p>
262   </Card>
263 ) : (
264   <div className="grid gap-4">
265     {filteredQuests.map((quest) => {
266       const q = quest as Record<string, unknown>;
267       const now = new Date();
268       const startDate = new Date(q.start_date as string);
269       const endDate = new Date(q.end_date as string);
270       const isActive = now >= startDate && now <= endDate;
271       const isUpcoming = now < startDate;
272
273       return (
274         <Card
275           key={q.id as string}
276           className="bg-white border-0 shadow-md rounded-xl p-4"
277         >
278           <div className="flex items-center gap-4">
279             <div className="p-2 rounded-lg bg-purple-50">
280               <BookOpen className="h-5 w-5 text-purple-600" />
281             </div>
282             <div className="flex-1 min-w-0">
283               <div className="flex items-center gap-2">
284                 <h3 className="text-sm font-bold">{q.title as string}</h3>
285                 <Badge
286                   className={
287                     {
288                       isActive
289                       ? "bg-green-50 text-green-700 border-green-200"
290                       : isUpcoming
291                       ? "bg-blue-50 text-blue-700 border-blue-200"
292                       : "bg-gray-50 text-gray-700 border-gray-200"
293                     }
294                   >
295                     {isActive
296                       ? "Active"
297                       : isUpcoming
298                       ? "Upcoming"
299                       : "Ended"}
300                   </Badge>
301               </div>
302               <p className="text-xs text-gray-500 mt-0.5 capitalize">
303                 {(q.quest_type as string).replace("_", " ")}
304               </p>
305             </div>
306             <div className="text-end">
307               <p className="text-xs text-gray-400">
308                 {startDate.toLocaleDateString()} - {endDate.toLocaleDateString()}
309               </p>

```

```

310 |                                     </div>
311 |                                 </div>
312 |                             </Card>
313 |                         );
314 |                     }}}}
315 |                 </div>
316 |             }}
317 |         </div>
318 |     );
319 | };
320 |
321 | export default KnowledgeQuestManager;
322 |

```

FILE: `src/pages/admin/marketplace/MarketplaceAnalyticsPage.tsx`

```
TYPE: .tsx | LINES: 1-244 | SHA256: f968d72d960a2a200b96eb7fec1bb87b60189e7de5d2464e8d17a76ebfa1e6c8
```

[illegible]

```

88 | return (
89 |   <div className="space-y-6">
90 |     <div className="flex items-center justify-between">
91 |       <div className="flex items-center gap-3">
92 |         <Button
93 |           variant="ghost"
94 |           size="sm"
95 |           onClick={() => navigate("/admin/marketplace")}
96 |         >
97 |           <ArrowLeft className="h-4 w-4" />
98 |         </Button>
99 |         <BarChart3 className="h-6 w-6 text-blue-600" />
100 |        <h1 className="text-2xl font-bold tracking-tight">
101 |          Marketplace Analytics
102 |        </h1>
103 |      </div>
104 |      <Button
105 |        variant="outline"
106 |        size="sm"
107 |        onClick={() => exportPurchaseHistoryCSV()}
108 |      >
109 |        <Download className="h-4 w-4 me-1" /> Export CSV
110 |      </Button>
111 |    </div>
112 |
113 |    { /* KPI Row */ }
114 |    <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
115 |      <KPICard
116 |        icon={Coins}
117 |        label="Total XP Spent"
118 |        value={analytics?.totalXPSpent ?? 0}.toLocaleString())
119 |      </>
120 |      <KPICard
121 |        icon={ShoppingCart}
122 |        label="Total Purchases"
123 |        value={analytics?.totalPurchases ?? 0}.toLocaleString())
124 |      </>
125 |      <KPICard
126 |        icon={Users}
127 |        label="Unique Buyers"
128 |        value={analytics?.uniqueBuyers ?? 0}.toLocaleString())
129 |      </>
130 |      <KPICard
131 |        icon={TrendingUp}
132 |        label="Avg XP / Student"
133 |        value={analytics?.avgXPPerStudent ?? 0}.toLocaleString())
134 |      </>
135 |    </div>
136 |
137 |    <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
138 |      { /* Popular Items */ }
139 |      <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
140 |        <div
141 |          className="px-6 py-4 flex items-center gap-2"
142 |          style={{
143 |            background: "var(--brand-gradient)",
144 |          }}
145 |        >
146 |          <ShoppingCart className="h-5 w-5 text-white" />
147 |          <h2 className="text-lg font-bold tracking-tight text-white">
148 |            Most Popular Items
149 |          </h2>
150 |        </div>
151 |        <div className="p-6">
152 |          {(analytics?.popularItems ?? []).length === 0 ? (
153 |            <p className="text-sm text-gray-500 text-center py-4">
154 |              No purchases yet.
155 |            </p>
156 |          ) : (
157 |            <div className="space-y-3">
158 |              {(analytics?.popularItems ?? []).map((item, idx) => (
159 |                <div
160 |                  key={item.item_id}
161 |                  className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
162 |                >
163 |                  <div className="flex items-center gap-3">
164 |                    <span className="text-sm font-bold text-gray-400 w-6">
165 |                      #{idx + 1}
166 |                    </span>
167 |                    <span className="text-sm font-medium">
168 |                      {item.item_name}
169 |                    </span>
170 |                  </div>
171 |                  <Badge className="text-xs bg-amber-50 text-amber-700 border-amber-200">
172 |                    {item.purchase_count} purchases
173 |                  </Badge>
174 |                </div>
175 |              ))}
176 |            </div>
177 |          )}
178 |        </div>
179 |      </Card>
180 |
181 |      { /* Category Breakdown */ }
182 |      <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
183 |        <div
184 |          className="px-6 py-4 flex items-center gap-2"
185 |          style={{
186 |            background: "var(--brand-gradient)",
187 |          }}
188 |        >
189 |          <BarChart3 className="h-5 w-5 text-white" />
190 |          <h2 className="text-lg font-bold tracking-tight text-white">
191 |            Category Breakdown

```



```

192 |         </h2>
193 |     </div>
194 |     <div className="p-6">
195 |         {(analytics?.categoryBreakdown ?? []).length === 0 ? (
196 |             <InlineNoData />
197 |         ) : (
198 |             <div className="space-y-4">
199 |                 {(analytics?.categoryBreakdown ?? []).map((cat) => {
200 |                     const maxPurchases = Math.max(
201 |                         ... (analytics?.categoryBreakdown ?? []).map(
202 |                             (c) => c.total_purchases
203 |                         ),
204 |                         1
205 |                     );
206 |                     const widthPercent = Math.round(
207 |                         (cat.total_purchases / maxPurchases) * 100
208 |                     );
209 |
210 |                     return (
211 |                         <div key={cat.category} className="space-y-1">
212 |                             <div className="flex items-center justify-between">
213 |                                 <Badge
214 |                                     className={`text-xs ${
215 |                                         categoryColors[cat.category] ?? ""
216 |                                     }`}
217 |                                 >
218 |                                     {categoryLabels[cat.category] ?? cat.category}
219 |                                 </Badge>
220 |                                 <span className="text-xs text-gray-500">
221 |                                     {cat.total_purchases} purchases · {" "}
222 |                                     {cat.total_xp_spent.toLocaleString()} XP
223 |                                 </span>
224 |                             </div>
225 |                             <div className="h-2 rounded-full bg-slate-100 overflow-hidden">
226 |                                 <div
227 |                                     className="h-full rounded-full bg-blue-500 transition-all duration-300"
228 |                                     style={{ width: `${widthPercent}%` }}
229 |                                 </div>
230 |                             </div>
231 |                         </div>
232 |                     );
233 |                 })}
234 |             </div>
235 |         )}
236 |     </div>
237 | </Card>
238 | </div>
239 | </div>
240 | );
241 | };
242 |
243 | export default MarketplaceAnalyticsPage;
244 |

```

FILE: [src/pages/admin/marketplace/MarketplaceManagementPage.tsx](#)

TYPE: .tsx | **LINES:** 1-250 | **SHA256:** 1f04a64a0e7b31a9810e41e999637ebc7b195f10527ee63cd03fac7560457924

```

1 | // =====
2 | // MarketplaceManagementPage – Admin item list with DataTable, CRUD actions
3 | // =====
4 |
5 | import { useState } from "react";
6 | import { useNavigate } from "react-router-dom";
7 | import {
8 |     useAdminMarketplaceItems,
9 |     useToggleMarketplaceItem,
10 | } from "@/hooks/useMarketplaceAdmin";
11 | import type { AdminMarketplaceItem } from "@/hooks/useMarketplaceAdmin";
12 | import { DataTable } from "@/components/shared/DataTable";
13 | import { Button } from "@components/ui/button";
14 | import { Badge } from "@components/ui/badge";
15 | import { Input } from "@components/ui/input";
16 | import {
17 |     DropdownMenu,
18 |     DropdownMenuContent,
19 |     DropdownMenuItem,
20 |     DropdownMenuTrigger,
21 | } from "@components/ui/dropdown-menu";
22 | import {
23 |     Plus,
24 |     Search,
25 |     MoreHorizontal,
26 |     Pencil,
27 |     ToggleLeft,
28 |     ToggleRight,
29 |     Store,
30 | } from "lucide-react";
31 | import type { ColumnDef } from "@tanstack/react-table";
32 | import ItemForm from "@pages/admin/marketplace/ItemForm";
33 |
34 | const categoryLabels: Record<string, string> = {
35 |     cosmetic: "Cosmetic",
36 |     educational_perk: "Educational Perk",
37 |     power_up: "Power-up",
38 | };
39 |
40 | const stockLabels: Record<string, string> = {
41 |     unlimited: "Unlimited",
42 |     limited: "Limited",
43 |     one_per_student: "One per Student",
44 | };
45 |
46 | const MarketplaceManagementPage = () => {
47 |     const navigate = useNavigate();

```

```

48 | const { data: items, isLoading } = useAdminMarketplaceItems();
49 | const toggleItem = useToggleMarketplaceItem();
50 | const [search, setSearch] = useState("");
51 | const [showForm, setShowForm] = useState(false);
52 | const [editingItem, setEditingItem] = useState<AdminMarketplaceItem | null>(
53 |   null
54 | );
55 |
56 | const filteredItems = (items ?? []).filter(
57 |   (item) =>
58 |     item.name.toLowerCase().includes(search.toLowerCase()) ||
59 |     item.category.toLowerCase().includes(search.toLowerCase())
60 | );
61 |
62 | const columns: ColumnDef<AdminMarketplaceItem>[] = [
63 |   {
64 |     accessorKey: "name",
65 |     header: "Name",
66 |     cell: ({ row }) => (
67 |       <div>
68 |         <p className="font-medium">{row.original.name}</p>
69 |         <p className="text-xs text-gray-500 truncate max-w-[200px]">
70 |           {row.original.description}
71 |         </p>
72 |       </div>
73 |     ),
74 |   },
75 |   {
76 |     accessorKey: "category",
77 |     header: "Category",
78 |     cell: ({ row }) => (
79 |       <Badge className="text-xs bg-blue-50 text-blue-700 border-blue-200">
80 |         {categoryLabels[row.original.category] ?? row.original.category}
81 |       </Badge>
82 |     ),
83 |   },
84 |   {
85 |     accessorKey: "xp_price",
86 |     header: "Price (XP)",
87 |     cell: ({ row }) => (
88 |       <span className="font-semibold text-amber-600">
89 |         {row.original.xp_price.toLocaleString()}
90 |       </span>
91 |     ),
92 |   },
93 |   {
94 |     accessorKey: "level_requirement",
95 |     header: "Level Req.",
96 |     cell: ({ row }) => (
97 |       <span className="text-gray-600">
98 |         {row.original.level_requirement > 0
99 |           ? `Lv ${row.original.level_requirement}`
100 |           : "-"}
101 |       </span>
102 |     ),
103 |   },
104 |   {
105 |     accessorKey: "stock_type",
106 |     header: "Stock",
107 |     cell: ({ row }) => (
108 |       <span className="text-xs text-gray-600">
109 |         {stockLabels[row.original.stock_type] ?? row.original.stock_type}
110 |         {row.original.stock_type === "limited" &&
111 |           row.original.stock_quantity !== null && (
112 |             <span className="ms-1 text-gray-400">
113 |               ({row.original.stock_quantity})
114 |             </span>
115 |           )}
116 |       </span>
117 |     ),
118 |   },
119 |   {
120 |     accessorKey: "total_purchases",
121 |     header: "Purchases",
122 |     cell: ({ row }) => (
123 |       <span className="text-gray-600">{row.original.total_purchases}</span>
124 |     ),
125 |   },
126 |   {
127 |     accessorKey: "is_active",
128 |     header: "Status",
129 |     cell: ({ row }) => (
130 |       <Badge
131 |         className={
132 |           row.original.is_active
133 |             ? "text-xs bg-green-50 text-green-700 border-green-200"
134 |             : "text-xs bg-gray-50 text-gray-500 border-gray-200"
135 |         }
136 |       >
137 |         {row.original.is_active ? "Active" : "Inactive"}
138 |       </Badge>
139 |     ),
140 |   },
141 |   {
142 |     id: "actions",
143 |     header: "",
144 |     cell: ({ row }) => (
145 |       <DropdownMenu>
146 |         <DropdownMenuTrigger asChild>
147 |           <Button variant="ghost" size="sm" aria-label="More actions">
148 |             <MoreHorizontal className="h-4 w-4" />
149 |           </Button>
150 |         </DropdownMenuTrigger>
151 |         <DropdownMenuContent align="end">

```

```

152 |         <DropdownMenuItem
153 |             onClick={() => {
154 |                 setEditingItem(row.original);
155 |                 setShowForm(true);
156 |             }}
157 |         >
158 |             <Pencil className="h-4 w-4 me-2" /> Edit
159 |         </DropdownMenuItem>
160 |         <DropdownMenuItem
161 |             onClick={() =>
162 |                 toggleItem.mutate({
163 |                     itemId: row.original.id,
164 |                     isActive: !row.original.is_active,
165 |                 })
166 |             >
167 |                 {row.original.is_active ? (
168 |                     <>
169 |                         <ToggleLeft className="h-4 w-4 me-2" /> Deactivate
170 |                     </>
171 |                 ) : (
172 |                     <>
173 |                         <ToggleRight className="h-4 w-4 me-2" /> Activate
174 |                     </>
175 |                 )}
176 |             </DropdownMenuItem>
177 |         </DropdownMenuContent>
178 |     </DropdownMenu>
179 | ),
180 | },
181 | ],
182 | };
183 |
184 | if (showForm) {
185 |     return (
186 |         <ItemForm
187 |             item={editingItem}
188 |             onClose={() => {
189 |                 setShowForm(false);
190 |                 setEditingItem(null);
191 |             }}
192 |         />
193 |     );
194 | }
195 |
196 | return (
197 |     <div className="space-y-6">
198 |         <div className="flex items-center justify-between">
199 |             <div className="flex items-center gap-3">
200 |                 <Store className="h-6 w-6 text-blue-600" />
201 |                 <h1 className="text-2xl font-bold tracking-tight">
202 |                     Marketplace Items
203 |                 </h1>
204 |             </div>
205 |             <div className="flex items-center gap-2">
206 |                 <Button
207 |                     variant="outline"
208 |                     size="sm"
209 |                     onClick={() => navigate("/admin/marketplace/sales")}
210 |                 >
211 |                     Sale Events
212 |                 </Button>
213 |                 <Button
214 |                     variant="outline"
215 |                     size="sm"
216 |                     onClick={() => navigate("/admin/marketplace/analytics")}
217 |                 >
218 |                     Analytics
219 |                 </Button>
220 |                 <Button
221 |                     variant="tactile"
222 |                     onClick={() => {
223 |                         setEditingItem(null);
224 |                         setShowForm(true);
225 |                     }}
226 |                 >
227 |                     <Plus className="h-4 w-4" /> Add Item
228 |                 </Button>
229 |             </div>
230 |         </div>
231 |
232 |         <div className="flex items-center gap-4">
233 |             <div className="relative flex-1 max-w-sm">
234 |                 <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
235 |                 <Input
236 |                     placeholder="Search items..."
237 |                     value={search}
238 |                     onChange={(e) => setSearch(e.target.value)}
239 |                     className="ps-9"
240 |                 />
241 |             </div>
242 |         </div>
243 |
244 |         <DataTable columns={columns} data={filteredItems} isLoading={isLoading} />
245 |     </div>
246 | );
247 | };
248 |
249 | export default MarketplaceManagementPage;
250 |

```

FILE: src/pages/admin/marketplace/SaleEventForm.tsx

TYPE: .tsx | LINES: 1-226 | SHA256: 4708eaf5599f1b4c25d10dbd1f4f9824df28bdb7123a676e60d3b05cf5a4f954

```
1 // =====
2 // SaleEventForm - Create/edit sale event with item multi-select
3 // =====
4
5 import { useForm } from "react-hook-form";
6 import { zodResolver } from "@hookform/resolvers/zod";
7 import {
8   createSaleEventSchema,
9   type CreateSaleEventInput,
10 } from "@lib/marketplaceSchemas";
11 import { useCreateSaleEvent } from "@hooks/useSaleEvents";
12 import { useAdminMarketplaceItems } from "@hooks/useMarketplaceAdmin";
13 import {
14   Form,
15   FormField,
16   FormItem,
17   FormLabel,
18   FormControl,
19   FormMessage,
20 } from "@components/ui/form";
21 import { Input } from "@components/ui/input";
22 import { Button } from "@components/ui/button";
23 import { Card } from "@components/ui/card";
24 import { Checkbox } from "@components/ui/checkbox";
25 import { ArrowLeft, Loader2 } from "lucide-react";
26 import { toast } from "sonner";
27
28 interface SaleEventFormProps {
29   onClose: () => void;
30 }
31
32 const SaleEventForm = ({ onClose }: SaleEventFormProps) => {
33   const createSale = useCreateSaleEvent();
34   const { data: items } = useAdminMarketplaceItems();
35   const activeItems = (items ?? []).filter((i) => i.is_active);
36
37   const form = useForm<CreateSaleEventInput>({
38     resolver: zodResolver(createSaleEventSchema) as never,
39     defaultValues: {
40       name: "",
41       discount_percentage: 20,
42       start_date: new Date().toISOString(),
43       end_date: new Date(Date.now() + 7 * 24 * 60 * 60 * 1000).toISOString(),
44       item_ids: [],
45     },
46   });
47
48   const selectedItemIds = form.watch("item_ids");
49
50   const onSubmit = (data: CreateSaleEventInput) => {
51     createSale.mutate(data, {
52       onSuccess: () => {
53         toast.success("Sale event created");
54         onClose();
55       },
56       onError: (err) => toast.error(err.message),
57     });
58   };
59
60   const toggleItem = (itemId: string) => {
61     const current = form.getValues("item_ids");
62     if (current.includes(itemId)) {
63       form.setValue(
64         "item_ids",
65         current.filter((id) => id !== itemId),
66         { shouldValidate: true }
67       );
68     } else {
69       form.setValue("item_ids", [...current, itemId], { shouldValidate: true });
70     }
71   };
72
73   return (
74     <div className="space-y-6 max-w-2xl">
75       <div className="flex items-center gap-3">
76         <Button variant="ghost" size="sm" onClick={onClose}>
77           <ArrowLeft className="h-4 w-4" /> Back
78         </Button>
79         <h1 className="text-2xl font-bold tracking-tight">Create Sale Event</h1>
80       </div>
81
82       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
83         <Form {...form}>
84           <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
85             <FormField>
86               <FormItem>
87                 <FormLabel>Event Name</FormLabel>
88                 <FormControl>
89                   <Input placeholder="e.g. Weekend Flash Sale" {...field} />
90                 </FormMessage />
91               </FormMessage />
92             </FormMessage />
93             <FormMessage />
94             </FormMessage />
95             </FormMessage />
96           </FormMessage />
97         </FormMessage />
98
99         <FormField>
100           <FormItem>
101             <FormLabel>Discount Percentage</FormLabel>
```

```

102 |         render={({ field }) => (
103 |             <FormItem>
104 |                 <FormLabel>Discount Percentage (5-90%)</FormLabel>
105 |                 <FormControl>
106 |                     <Input
107 |                         type="number"
108 |                         min={5}
109 |                         max={90}
110 |                         {...field}
111 |                         onChange={(e) => field.onChange(Number(e.target.value))}
112 |                     />
113 |                 </FormControl>
114 |                 <FormMessage />
115 |             </FormItem>
116 |         )}
117 |     />
118 |
119 |     <div className="grid grid-cols-2 gap-4">
120 |         <FormField
121 |             control={form.control}
122 |             name="start_date"
123 |             render={({ field }) => (
124 |                 <FormItem>
125 |                     <FormLabel>Start Date</FormLabel>
126 |                     <FormControl>
127 |                         <Input
128 |                             type="datetime-local"
129 |                             value={field.value ? field.value.slice(0, 16) : ""}
130 |                             onChange={(e) =>
131 |                                 field.onChange(new Date(e.target.value).toISOString())
132 |                             }
133 |                         />
134 |                     </FormControl>
135 |                     <FormMessage />
136 |                 </FormItem>
137 |             )}
138 |         />
139 |
140 |         <FormField
141 |             control={form.control}
142 |             name="end_date"
143 |             render={({ field }) => (
144 |                 <FormItem>
145 |                     <FormLabel>End Date</FormLabel>
146 |                     <FormControl>
147 |                         <Input
148 |                             type="datetime-local"
149 |                             value={field.value ? field.value.slice(0, 16) : ""}
150 |                             onChange={(e) =>
151 |                                 field.onChange(new Date(e.target.value).toISOString())
152 |                             }
153 |                         />
154 |                     </FormControl>
155 |                     <FormMessage />
156 |                 </FormItem>
157 |             )}
158 |         />
159 |     </div>
160 |
161 |     <FormField
162 |         control={form.control}
163 |         name="item_ids"
164 |         render={() => (
165 |             <FormItem>
166 |                 <FormLabel>
167 |                     Select Items ({selectedItemIds.length} selected)
168 |                 </FormLabel>
169 |                 <div className="border border-slate-200 rounded-lg max-h-60 overflow-y-auto p-3 space-y-2">
170 |                     {activeItems.length === 0 ? (
171 |                         <p className="text-sm text-gray-500">
172 |                             No active items available.
173 |                         </p>
174 |                     ) : (
175 |                         activeItems.map((item) => (
176 |                             <label
177 |                                 key={item.id}
178 |                                 htmlFor={`sale-item-${item.id}`}
179 |                                 className="flex items-center gap-3 py-1.5 px-2 rounded-lg hover:bg-slate-50 cursor-p
180 |                             >
181 |                                 <Checkbox
182 |                                     id={`sale-item-${item.id}`}
183 |                                     checked={selectedItemIds.includes(item.id)}
184 |                                     onChange={() => toggleItem(item.id)}
185 |                                 />
186 |                                 <div className="flex-1 min-w-0">
187 |                                     <p className="text-sm font-medium truncate">
188 |                                         {item.name}
189 |                                     </p>
190 |                                     <p className="text-xs text-gray-500">
191 |                                         {item.xp_price} XP · {item.category}
192 |                                     </p>
193 |                                 </div>
194 |                             </label>
195 |                         ))
196 |                     </div>
197 |                 </FormItem>
198 |                 <FormMessage />
199 |             </FormItem>
200 |         )}
201 |     />
202 |
203 |     <div className="flex items-center gap-3 pt-2">
204 |         <Button
205 |             type="submit"

```

```

206 |         disabled={createSale.isPending}
207 |         variant="tactile"
208 |     >
209 |         {createSale.isPending && (
210 |             <Loader2 className="h-4 w-4 animate-spin" />
211 |         )}
212 |         Create Sale Event
213 |     </Button>
214 |     <Button type="button" variant="outline" onClick={onClose}>
215 |         Cancel
216 |     </Button>
217 | </div>
218 | </form>
219 | </Form>
220 | </Card>
221 | </div>
222 | );
223 | };
224 |
225 | export default SaleEventForm;
226 |

```

FILE: src/pages/admin/marketplace/SaleEventManager.tsx

TYPE: .tsx | LINES: 1-148 | SHA256: 1f381f6801e494d69d5376ff94da826fa84e361f9213b3d554e94fa91d343506

```

1 | // =====
2 | // SaleEventManager - Sale events list with status badges
3 | // =====
4 |
5 | import { useState } from "react";
6 | import { useNavigate } from "react-router-dom";
7 | import { useSaleEvents, useCancelSaleEvent } from "@/hooks/useSaleEvents";
8 | import type { SaleEvent } from "@/hooks/useSaleEvents";
9 | import { DataTable } from "@components/shared/DataTable";
10 | import { Button } from "@components/ui/button";
11 | import { Badge } from "@components/ui/badge";
12 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
13 | import { Plus, ArrowLeft, Tag, XCircle } from "lucide-react";
14 | import { formatLocalDate } from "@lib/formatDate";
15 | import type { ColumnDef } from "@tanstack/react-table";
16 | import SaleEventForm from "@pages/admin/marketplace/SaleEventForm";
17 |
18 | const statusStyles: Record<string, string> = {
19 |   active: "bg-green-50 text-green-700 border-green-200",
20 |   scheduled: "bg-blue-50 text-blue-700 border-blue-200",
21 |   expired: "bg-gray-50 text-gray-500 border-gray-200",
22 | };
23 |
24 | const SaleEventManager = () => {
25 |   const navigate = useNavigate();
26 |   const { data: events, isLoading } = useSaleEvents();
27 |   const cancelEvent = useCancelSaleEvent();
28 |   const [showForm, setShowForm] = useState(false);
29 |   const [cancelTarget, setCancelTarget] = useState<string | null>(null);
30 |
31 |   const columns: ColumnDef<SaleEvent>[] = [
32 |     {
33 |       accessorKey: "name",
34 |       header: "Event Name",
35 |       cell: ({ row }) => (
36 |         <span className="font-medium">{row.original.name}</span>
37 |       ),
38 |     },
39 |     {
40 |       accessorKey: "discount_percentage",
41 |       header: "Discount",
42 |       cell: ({ row }) => (
43 |         <span className="font-semibold text-red-600">
44 |           {row.original.discount_percentage}% off
45 |         </span>
46 |       ),
47 |     },
48 |     {
49 |       accessorKey: "start_date",
50 |       header: "Start",
51 |       cell: ({ row }) => (
52 |         <span className="text-gray-600 text-sm">
53 |           {formatLocalDate(row.original.start_date, "MMM d, yyyy")}
54 |         </span>
55 |       ),
56 |     },
57 |     {
58 |       accessorKey: "end_date",
59 |       header: "End",
60 |       cell: ({ row }) => (
61 |         <span className="text-gray-600 text-sm">
62 |           {formatLocalDate(row.original.end_date, "MMM d, yyyy")}
63 |         </span>
64 |       ),
65 |     },
66 |     {
67 |       accessorKey: "item_ids",
68 |       header: "Items",
69 |       cell: ({ row }) => (
70 |         <span className="text-gray-600">
71 |           {row.original.item_ids.length} item(s)
72 |         </span>
73 |       ),
74 |     },
75 |     {
76 |       accessorKey: "status",
77 |       header: "Status",
78 |       cell: ({ row }) => (
79 |         <Badge className={

```

```

80 |         {row.original.status.charAt(0).toUpperCase() +
81 |           row.original.status.slice(1)}
82 |       </Badge>
83 |     ),
84 |   },
85 |   {
86 |     id: "actions",
87 |     header: "",
88 |     cell: ({ row }) =>
89 |       row.original.status === "active" ||
90 |       row.original.status === "scheduled" ? (
91 |         <Button
92 |           variant="ghost"
93 |           size="sm"
94 |           className="text-red-600 hover:text-red-700"
95 |           onClick={() => setCancelTarget(row.original.id)}
96 |         >
97 |           <XCircle className="h-4 w-4 me-1" /> Cancel
98 |         </Button>
99 |       ) : null,
100 |   },
101 | ];
102 |
103 | if (showForm) {
104 |   return <SaleEventForm onClose={() => setShowForm(false)} />;
105 | }
106 |
107 | return (
108 |   <div className="space-y-6">
109 |     <div className="flex items-center justify-between">
110 |       <div className="flex items-center gap-3">
111 |         <Button
112 |           variant="ghost"
113 |           size="sm"
114 |           onClick={() => navigate("/admin/marketplace")}
115 |         >
116 |           <ArrowLeft className="h-4 w-4" />
117 |         </Button>
118 |         <Tag className="h-6 w-6 text-red-500" />
119 |         <h1 className="text-2xl font-bold tracking-tight">Sale Events</h1>
120 |       </div>
121 |       <Button onClick={() => setShowForm(true)} variant="tactile">
122 |         <Plus className="h-4 w-4" /> Create Sale
123 |       </Button>
124 |     </div>
125 |
126 |     <DataTable columns={columns} data={events ?? []} isLoading={isLoading} />
127 |
128 |     <ConfirmDialog
129 |       open={!cancelTarget}
130 |       onOpenChange={(open) => !open && setCancelTarget(null)}
131 |       title="Cancel Sale Event?"
132 |       description="This will immediately end the sale and restore original prices for all affected items."
133 |       confirmLabel="Cancel Sale"
134 |       isPending={cancelEvent.isPending}
135 |       onConfirm={() => {
136 |         if (cancelTarget) {
137 |           cancelEvent.mutate(cancelTarget, {
138 |             onSuccess: () => setCancelTarget(null),
139 |           });
140 |         }
141 |       }}
142 |     />
143 |   </div>
144 | );
145 | };
146 |
147 | export default SaleEventManager;
148 |

```

FILE: [src/pages/admin/marketplace/XPEconomistDashboard.tsx](#)

TYPE: .tsx | LINES: 1-199 | SHA256: bd9aac2464a9d76f77e47679b517ddc419448afe4272dfba2edefb62e6fc737a

```

1 | // =====
2 | // XPEconomistDashboard – Earn/spend ratio, velocity, inflation indicator
3 | // Task 22.1
4 | // =====
5 |
6 | import { Card } from "@components/ui/card";
7 | import { Badge } from "@components/ui/badge";
8 | import {
9 |   Loader2,
10 |   TrendingUp,
11 |   TrendingDown,
12 |   DollarSign,
13 |   Activity,
14 | } from "lucide-react";
15 | import { useAuth } from "@hooks/useAuth";
16 | import { useEarnSpendRatio, useXPVelocity } from "@hooks/useXPEconomist";
17 |
18 | const STATUS_COLORS = {
19 |   healthy: "bg-green-50 text-green-700 border-green-200",
20 |   inflationary: "bg-red-50 text-red-700 border-red-200",
21 |   deflationary: "bg-blue-50 text-blue-700 border-blue-200",
22 |   no_spending: "bg-gray-50 text-gray-700 border-gray-200",
23 | } as const;
24 |
25 | const XPEconomistDashboard = () => {
26 |   const { profile } = useAuth();
27 |   const institutionId = profile?.institution_id;
28 |   const { data: ratioData, isLoading: ratioLoading } =
29 |     useEarnSpendRatio(institutionId);
30 |   const { data: velocityData, isLoading: velocityLoading } = useXPVelocity(
31 |     institutionId,

```

```

32 |     8
33 | );
34 |
35 | const isLoading = ratioLoading || velocityLoading;
36 |
37 | return (
38 |   <div className="space-y-6">
39 |     <h1 className="text-2xl font-bold tracking-tight">
40 |       XP Economist Dashboard
41 |     </h1>
42 |
43 |     {isLoading ? (
44 |       <div className="flex justify-center py-12">
45 |         <Loader2 className="h-6 w-6 animate-spin text-blue-500" />
46 |       </div>
47 |     ) : (
48 |       <>
49 |         {/* KPI Row */}
50 |         <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
51 |           <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
52 |             <div className="flex items-center justify-between">
53 |               <div>
54 |                 <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
55 |                   Earn/Spend Ratio
56 |                 </p>
57 |                 <p className="text-2xl font-black mt-1">
58 |                   {ratioData?.ratio !== null
59 |                     ? `${ratioData?.ratio}:1`
60 |                     : "N/A"}
61 |                 </p>
62 |               </div>
63 |               <div className="p-2 rounded-lg bg-blue-50 group-hover:scale-110 transition-transform">
64 |                 <Activity className="h-5 w-5 text-blue-600" />
65 |               </div>
66 |             </div>
67 |           </Card>
68 |
69 |           <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
70 |             <div className="flex items-center justify-between">
71 |               <div>
72 |                 <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
73 |                   Status
74 |                 </p>
75 |                 <Badge
76 |                   className={`mt-1 ${
77 |                     STATUS_COLORS[ratioData?.status ?? "no_spending"]
78 |                   }`}
79 |                 >
80 |                   {ratioData?.statusLabel ?? "No data"}
81 |                 </Badge>
82 |               </div>
83 |               <div className="p-2 rounded-lg bg-green-50 group-hover:scale-110 transition-transform">
84 |                 {ratioData?.status === "inflationary" ? (
85 |                   <TrendingUp className="h-5 w-5 text-red-600" />
86 |                 ) : (
87 |                   <TrendingDown className="h-5 w-5 text-green-600" />
88 |                 )}
89 |               </div>
90 |             </div>
91 |           </Card>
92 |
93 |           <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
94 |             <div className="flex items-center justify-between">
95 |               <div>
96 |                 <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
97 |                   Total Earned
98 |                 </p>
99 |                 <p className="text-2xl font-black mt-1">
100 |                   {(ratioData?.totalEarned ?? 0).toLocaleString()}
101 |                 </p>
102 |               </div>
103 |               <div className="p-2 rounded-lg bg-amber-50 group-hover:scale-110 transition-transform">
104 |                 <TrendingUp className="h-5 w-5 text-amber-600" />
105 |               </div>
106 |             </div>
107 |           </Card>
108 |
109 |           <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
110 |             <div className="flex items-center justify-between">
111 |               <div>
112 |                 <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
113 |                   Total Spent
114 |                 </p>
115 |                 <p className="text-2xl font-black mt-1">
116 |                   {(ratioData?.totalSpent ?? 0).toLocaleString()}
117 |                 </p>
118 |               </div>
119 |               <div className="p-2 rounded-lg bg-purple-50 group-hover:scale-110 transition-transform">
120 |                 <DollarSign className="h-5 w-5 text-purple-600" />
121 |               </div>
122 |             </div>
123 |           </Card>
124 |         </div>
125 |
126 |         {/* XP Velocity Chart */}
127 |         <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
128 |           <div
129 |             className="px-6 py-4 flex items-center gap-2"
130 |             style={{
131 |               background: "var(--brand-gradient)",
132 |             }}
133 |           >
134 |             <Activity className="h-5 w-5 text-white" />
135 |             <h2 className="text-lg font-bold tracking-tight text-white">

```



```

136 |         XP Velocity
137 |     </h2>
138 | </div>
139 | <div className="p-6">
140 |   <div className="space-y-2">
141 |     {(velocityData ?? []).map((point) => (
142 |       <div
143 |         key={point.week}
144 |         className="flex items-center gap-4 text-sm"
145 |       >
146 |         <span className="w-24 text-xs text-gray-500">
147 |           {point.week}
148 |         </span>
149 |         <div className="flex-1 flex items-center gap-2">
150 |           <div
151 |             className="h-4 rounded bg-green-400"
152 |             style={{
153 |               width: `${Math.min(
154 |                 100,
155 |                 (point.earned /
156 |                   Math.max(
157 |                     1,
158 |                     ...(velocityData ?? []).map((v) => v.earned)
159 |                   )) *
160 |                 100
161 |               )}%`,
162 |             }}
163 |           </div>
164 |           <span className="text-xs text-green-600">
165 |             +{point.earned}
166 |           </span>
167 |         </div>
168 |         <div className="flex-1 flex items-center gap-2">
169 |           <div
170 |             className="h-4 rounded bg-red-400"
171 |             style={{
172 |               width: `${Math.min(
173 |                 100,
174 |                 (point.spent /
175 |                   Math.max(
176 |                     1,
177 |                     ...(velocityData ?? []).map((v) => v.spent)
178 |                   )) *
179 |                 100
180 |               )}%`,
181 |             }}
182 |           </div>
183 |           <span className="text-xs text-red-600">
184 |             -{point.spent}
185 |           </span>
186 |         </div>
187 |       </div>
188 |     ))}
189 |   </div>
190 | </div>
191 | </Card>
192 | </>
193 | ))}
194 | </div>
195 | );
196 | };
197 |
198 | export default XPEconomistDashboard;
199 |

```

FILE: [src/pages/admin/onboarding/PendingOnboardingPage.tsx](#)

TYPE: .tsx | LINES: 1-208 | SHA256: e0199d749dd5ff355e26c762c9b88045b610b4311313e76fec33c5ae73083f63

```

1 | import { parseAsString, useQueryState } from "nuqs";
2 | import { Card } from "@components/ui/card";
3 | import { Badge } from "@components/ui/badge";
4 | import { Button } from "@components/ui/button";
5 | import { Input } from "@components/ui/input";
6 | import {
7 |   Select,
8 |   SelectContent,
9 |   SelectItem,
10 |   SelectTrigger,
11 |   SelectValue,
12 | } from "@components/ui/select";
13 | import { Shimmer } from "@design-system";
14 | import { usePendingOnboardingStudents } from "@hooks/useAdminDashboard";
15 | import { usePrograms } from "@hooks/usePrograms";
16 | import { useStandardMutation } from "@hooks/useStandardMutation";
17 | import { supabase } from "@lib/supabase";
18 | import { Search, Send, UserX, Loader2 } from "lucide-react";
19 | import { formatDistanceToNow, subDays, differenceInDays } from "date-fns";
20 | import { toast } from "sonner";
21 |
22 | const PendingOnboardingPage = () => {
23 |   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
24 |   const [programFilter, setProgramFilter] = useQueryState(
25 |     "program",
26 |     parseAsString.withDefault("all")
27 |   );
28 |   const [dateFilter, setDateFilter] = useQueryState(
29 |     "enrolled",
30 |     parseAsString.withDefault("all")
31 |   );
32 |
33 |   const enrolledAfter =
34 |     dateFilter === "7d"
35 |       ? subDays(new Date(), 7).toISOString()
36 |       : dateFilter === "30d"

```

```

37 |         ? subDays(new Date(), 30).toISOString()
38 |         : undefined;
39 |
40 | const { data: students, isLoading } = usePendingOnboardingStudents({
41 |   programId: programFilter !== "all" ? programFilter : undefined,
42 |   enrolledAfter,
43 | });
44 |
45 | const { data: programsResult } = usePrograms();
46 | const programs = programsResult?.data ?? [];
47 |
48 | // Mutation for sending reminders
49 | const reminderMutation = useStandardMutation({
50 |   mutationFn: async ({
51 |     studentId,
52 |     email,
53 |   }: {
54 |     studentId: string;
55 |     email: string;
56 |   }) => {
57 |     const { error } = await supabase.functions.invoke(
58 |       "send-onboarding-reminder",
59 |       {
60 |         body: { student_id: studentId, email },
61 |       }
62 |     );
63 |     if (error) throw error;
64 |     return { studentId, email };
65 |   },
66 |   onSuccess: (data) => {
67 |     toast.success(`Reminder sent to ${data.email}`);
68 |   },
69 | });
70 |
71 | // Filter by search
72 | const filtered = (students ?? []).filter((s) => {
73 |   if (!search) return true;
74 |   const q = search.toLowerCase();
75 |   return (
76 |     s.full_name.toLowerCase().includes(q) || s.email.toLowerCase().includes(q)
77 |   );
78 | });
79 |
80 | const handleSendReminder = (studentId: string, email: string) => {
81 |   reminderMutation.mutate({ studentId, email });
82 | };
83 |
84 | return (
85 |   <div className="space-y-6">
86 |     <div className="flex items-center justify-between">
87 |       <h1 className="text-2xl font-bold tracking-tight">
88 |         Pending Onboarding
89 |       </h1>
90 |       <Badge variant="outline" className="text-sm">
91 |         {filtered.length} student{filtered.length !== 1 ? "s" : ""}
92 |       </Badge>
93 |     </div>
94 |
95 |     { /* Filters */ }
96 |     <div className="flex items-center gap-4 flex-wrap">
97 |       <div className="relative flex-1 max-w-sm">
98 |         <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
99 |         <Input
100 |           placeholder="Search by name or email..."
101 |           value={search}
102 |           onChange={(e) => setSearch(e.target.value)}
103 |           className="ps-9"
104 |         />
105 |       </div>
106 |       <Select value={programFilter} onValueChange={setProgramFilter}>
107 |         <SelectTrigger className="w-48">
108 |           <SelectValue placeholder="All Programs" />
109 |         </SelectTrigger>
110 |         <SelectContent>
111 |           <SelectItem value="all">All Programs</SelectItem>
112 |           {programs.map((p) => (
113 |             <SelectItem key={p.id} value={p.id}>
114 |               {p.name}
115 |             </SelectItem>
116 |           ))}
117 |         </SelectContent>
118 |       </Select>
119 |       <Select value={dateFilter} onValueChange={setDateFilter}>
120 |         <SelectTrigger className="w-48">
121 |           <SelectValue placeholder="Enrollment Date" />
122 |         </SelectTrigger>
123 |         <SelectContent>
124 |           <SelectItem value="all">All Time</SelectItem>
125 |           <SelectItem value="7d">Last 7 Days</SelectItem>
126 |           <SelectItem value="30d">Last 30 Days</SelectItem>
127 |         </SelectContent>
128 |       </Select>
129 |     </div>
130 |
131 |     { /* Student List */ }
132 |     {isLoading ? (
133 |       <div className="space-y-3">
134 |         {Array.from({ length: 5 }).map((_, i) => (
135 |           <Shimmer key={i} className="h-16 rounded-xl" />
136 |         ))}
137 |       </div>
138 |     ) : filtered.length > 0 ? (
139 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden">
140 |         <div className="divide-y divide-slate-100">

```

```

141 |         {filtered.map((student) => {
142 |             const daysSinceCreation = differenceInDays(
143 |                 new Date(),
144 |                 new Date(student.created_at)
145 |             );
146 |             const isOverdue = daysSinceCreation >= 7;
147 |
148 |             return (
149 |                 <div
150 |                     key={student.id}
151 |                     className="flex items-center justify-between px-6 py-4"
152 |                 >
153 |                     <div className="min-w-0">
154 |                         <p className="text-sm font-medium text-gray-900 truncate">
155 |                             {student.full_name}
156 |                         </p>
157 |                         <p className="text-xs text-gray-500 truncate">
158 |                             {student.email}
159 |                         </p>
160 |                     </div>
161 |                     <div className="flex items-center gap-3 shrink-0">
162 |                         <span className="text-xs text-gray-400">
163 |                             Joined{" " +
164 |                                 {formatDistanceToNow(new Date(student.created_at), {
165 |                                     addSuffix: true,
166 |                                 })}
167 |                         </span>
168 |                         {isOverdue && (
169 |                             <Badge className="bg-red-100 text-red-700 border-red-200 text-[10px]">
170 |                                 Overdue
171 |                             </Badge>
172 |                         )}
173 |                         <Button
174 |                             variant="outline"
175 |                             size="sm"
176 |                             disabled={reminderMutation.isPending}
177 |                             onClick={() =>
178 |                                 handleSendReminder(student.id, student.email)
179 |                             }
180 |                             className="text-xs"
181 |                         >
182 |                             {reminderMutation.isPending ? (
183 |                                 <Loader2 className="h-3 w-3 animate-spin" />
184 |                             ) : (
185 |                                 <Send className="h-3 w-3" />
186 |                             )}
187 |                             Remind
188 |                         </Button>
189 |                     </div>
190 |                 </div>
191 |             );
192 |         })}
193 |     </div>
194 | </Card>
195 | ) : (
196 |     <Card className="bg-white border-0 shadow-md rounded-xl p-12 text-center">
197 |         <UserX className="h-10 w-10 text-gray-300 mx-auto mb-3" />
198 |         <p className="text-sm text-gray-500">
199 |             All students have completed onboarding.
200 |         </p>
201 |     </Card>
202 | )}
203 | </div>
204 | );
205 | };
206 |
207 | export default PendingOnboardingPage;
208 |

```

FILE: [src/pages/admin/outcomes/columns.tsx](#)

TYPE: .tsx | LINES: 1-146 | SHA256: ecbc5a9d3a42d9ea8c971aef4d6be3a3f04c26f12d8a7435b01502c2455c3795

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import {
4 |     ArrowUpDown,
5 |     GripVertical,
6 |     MoreHorizontal,
7 |     Pencil,
8 |     Trash2,
9 | } from "lucide-react";
10 | import { Badge } from "@components/ui/badge";
11 | import { Button } from "@components/ui/button";
12 | import {
13 |     DropdownMenu,
14 |     DropdownMenuContent,
15 |     DropdownMenuItem,
16 |     DropdownMenuTrigger,
17 | } from "@components/ui/dropdown-menu";
18 | import type { LearningOutcome } from "@types/app";
19 |
20 | // % % % Column factory - accepts onEdit and onDelete callbacks % % % % % % % % % % % % % % %
21 |
22 | export const createColumns = (
23 |     onEdit: (id: string) => void,
24 |     onDelete: (ilo: LearningOutcome) => void,
25 |     isDragMode: boolean
26 | ): ColumnDef<LearningOutcome>[] => {
27 |     const cols: ColumnDef<LearningOutcome>[] = [];
28 |
29 |     if (isDragMode) {
30 |         cols.push({
31 |             id: "drag-handle",
32 |             header: "",

```

```

33 |         cell: () => (
34 |             <GripVertical className="h-4 w-4 text-gray-400 cursor-grab" />
35 |         ),
36 |         size: 40,
37 |     });
38 | }
39 |
40 | cols.push(
41 |     {
42 |         accessorKey: "sort_order",
43 |         header: "#",
44 |         cell: ({ row }) => (
45 |             <span className="text-gray-500 text-sm font-medium">
46 |                 {(row.getValue("sort_order") as number) + 1}
47 |             </span>
48 |         ),
49 |         size: 50,
50 |     },
51 |     {
52 |         accessorKey: "title",
53 |         header: ({ column }) => (
54 |             <Button
55 |                 variant="ghost"
56 |                 size="sm"
57 |                 className="-ms-3"
58 |                 onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
59 |             >
60 |                 Title
61 |             <ArrowUpDown className="h-4 w-4" />
62 |             </Button>
63 |         ),
64 |         cell: ({ row }) => (
65 |             <span className="font-medium">{row.getValue("title")}</span>
66 |         ),
67 |     },
68 |     {
69 |         accessorKey: "description",
70 |         header: "Description",
71 |         cell: ({ row }) => {
72 |             const desc = row.getValue("description") as string | null;
73 |             return (
74 |                 <span className="text-gray-500 text-sm line-clamp-1">
75 |                     {desc || "-"}
76 |                 </span>
77 |             );
78 |         },
79 |     },
80 |     {
81 |         accessorKey: "is_active",
82 |         header: "Status",
83 |         cell: ({ row }) => {
84 |             // `learning_outcomes` has no `is_active` column – IL0s are always
85 |             // active once created. Default missing values to active so the badge
86 |             // never falsely shows "Inactive".
87 |             const rawActive = row.getValue("is_active") as boolean | undefined;
88 |             const isActive = rawActive ?? true;
89 |             return (
90 |                 <Badge
91 |                     variant="outline"
92 |                     className={
93 |                         isActive
94 |                         ? "bg-green-50 text-green-600 border-green-200"
95 |                         : "bg-red-50 text-red-600 border-red-200"
96 |                     }
97 |                 >
98 |                     {isActive ? "Active" : "Inactive"}
99 |                 </Badge>
100 |             );
101 |         },
102 |     },
103 |     {
104 |         accessorKey: "created_at",
105 |         header: "Created",
106 |         cell: ({ row }) => {
107 |             const date = row.getValue("created_at") as string;
108 |             return (
109 |                 <span className="text-gray-500">
110 |                     {format(new Date(date), "MMM d, yyyy")}
111 |                 </span>
112 |             );
113 |         },
114 |     },
115 |     {
116 |         id: "actions",
117 |         header: "",
118 |         cell: ({ row }) => (
119 |             <DropdownMenu>
120 |                 <DropdownMenuTrigger asChild>
121 |                     <Button variant="ghost" size="icon-xs">
122 |                         <MoreHorizontal className="h-4 w-4" />
123 |                         <span className="sr-only">Open menu</span>
124 |                     </Button>
125 |                 </DropdownMenuTrigger>
126 |                 <DropdownMenuContent align="end">
127 |                     <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
128 |                         <Pencil className="h-4 w-4" />
129 |                         Edit
130 |                     </DropdownMenuItem>
131 |                     <DropdownMenuItem
132 |                         variant="destructive"
133 |                         onClick={() => onDelete(row.original)}
134 |                     >
135 |                         <Trash2 className="h-4 w-4" />
136 |                         Delete

```

FILE: src/pages/admin/outcomes/ILOForm.tsx

```
1 | import { useEffect } from "react";
2 | import { useForm } from "react-hook-form";
```

```
91 ((ilo as unknown as Record<string, unknown>).title_ar as string) ??  
92 "",  
93   description: ilo.description ?? "",  
94 });  
95 }  
96 }, [existingILO, form]);  
97  
98 if (isLoading) {  
99   return (  
100     <div className="flex items-center justify-center py-12">  
101       <Loader2 className="h-8 w-8 animate-spin text-blue-600" />  
102     </div>  
103   );  
104 }  
  
105  
106 const onSubmit = (data: UpdateILOFormData) => {  
107   updateMutation.mutate(data, {  
108     onSuccess: () => {  
109       toast.success("ILO updated successfully");  
110       navigate("/admin/outcomes");  
111     },  
112     onError: (err) => toast.error(err.message),  
113   });  
114 };  
  
115  
116 return (  
117   <ILOFormFields  
118     form={form}  
119     onSubmit={onSubmit}  
120     isPending={updateMutation.isPending}  
121     isEditMode  
122   />  
123 );  
124 }];  
  
125 // % % % Shared form fields % % % % % % % % % % % % % % % % % % % % % % % % % %  
126  
127 interface ILOFormFieldsProps<T extends CreateILOFormData | UpdateILOFormData>  
128   form: ReturnTyped<typeof useForm<T>>;  
129   onSubmit: (data: T) => void;  
130   isPending: boolean;  
131   isEditMode: boolean;  
132 }  
133  
134 const ILOFormFields = <T extends CreateILOFormData | UpdateILOFormData>({  
135   form,  
136   onSubmit,  
137   isPending,  
138   isEditMode,  
139 }): ILOFormFieldsProps<T> => {  
140   const navigate = useRouter();  
141   const { t } = useTranslation("admin");  
142  
143   return (  
144     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">  
145       <Form {...form}>  
146         <form  
147           onSubmit={form.handleSubmit(  
148             onSubmit as Parameters<typeof form.handleSubmit>[0]  
149           )}  
150           className="space-y-6"  
151         >  
152           <FormField  
153             control={form.control}  
154             name={"title" as never}  
155             render={({ field }) => (  
156               <FormItem>  
157                 <FormLabel>Title</FormLabel>  
158                 <FormControl>  
159                   <Input  
160                     placeholder="e.g. Demonstrate critical thinking skills"  
161                     {...field}/>  
162                 </FormControl>  
163                 <FormMessage />  
164               </FormItem>  
165             )} />  
166           <FormField  
167             control={form.control}  
168             name={"title_ar" as never}  
169             render={({ field }) => (  
170               <FormItem>  
171                 <FormLabel>t("bilingual.arabicTitle")</FormLabel>  
172                 <FormControl>  
173                   <Input  
174                     placeholder=t("bilingual.arabicTitlePlaceholder")  
175                     dir="rtl"  
176                     {...field}  
177                     value={(field.value as string) ?? ""}/>  
178                 </FormControl>  
179                 <FormMessage />  
180               </FormItem>  
181             )} />  
182           <FormField  
183             control={form.control}  
184             name={"description" as never}  
185             render={({ field }) => (  
186               <FormItem>  
187                 <FormLabel>Description</FormLabel>
```


[illegible]


```

139 | const saveOrder = useCallback(() => {
140 |   if (!localOrder) return;
141 |   const items = localOrder.map((ilo, idx) => ({
142 |     id: ilo.id,
143 |     sort_order: idx,
144 |   }));
145 |   reorderMutation.mutate(
146 |     { items },
147 |     {
148 |       onSuccess: () => {
149 |         toast.success("ILO order saved");
150 |         setLocalOrder(null);
151 |         setIsDragMode(false);
152 |       },
153 |       onError: (err) => toast.error(err.message),
154 |     }
155 |   );
156 | }, [localOrder, reorderMutation]);
157 |
158 | // Handle drag end – reorder local state
159 | const handleDragEnd = useCallback(
160 |   (event: DragEndEvent) => {
161 |     const { active, over } = event;
162 |     if (!over || active.id === over.id || !localOrder) return;
163 |
164 |     const oldIndex = localOrder.findIndex((i) => i.id === active.id);
165 |     const newIndex = localOrder.findIndex((i) => i.id === over.id);
166 |     setLocalOrder(arrayMove(localOrder, oldIndex, newIndex));
167 |   },
168 |   [localOrder]
169 | );
170 |
171 | const columns = createColumns(
172 |   (id) => navigate(`/admin/outcomes/${id}/edit`),
173 |   (ilo) => setIloToDelete(ilo),
174 |   isDragMode
175 | );
176 |
177 | return (
178 |   <div className="space-y-6">
179 |     { /* Page Header */ }
180 |     <div className="flex items-center justify-between">
181 |       <h1 className="text-2xl font-bold tracking-tight">
182 |         Institutional Learning Outcomes
183 |       </h1>
184 |       <div className="flex items-center gap-2">
185 |         { !isDragMode ? (
186 |           <>
187 |             <Button
188 |               variant="outline"
189 |               size="sm"
190 |               onClick={enterDragMode}
191 |               disabled={isLoading || !ilos?.length}
192 |             >
193 |               <ArrowUpDown className="h-4 w-4" />
194 |               Reorder
195 |             </Button>
196 |             <Button
197 |               variant="tactile"
198 |               onClick={() => navigate("/admin/outcomes/new")}
199 |             >
200 |               <Plus className="h-4 w-4" /> Add ILO
201 |             </Button>
202 |           </>
203 |         ) : (
204 |           <>
205 |             <Button
206 |               variant="outline"
207 |               size="sm"
208 |               onClick={cancelDragMode}
209 |               disabled={reorderMutation.isPending}
210 |             >
211 |               <X className="h-4 w-4" />
212 |               Cancel
213 |             </Button>
214 |             <Button
215 |               size="sm"
216 |               onClick={saveOrder}
217 |               disabled={reorderMutation.isPending}
218 |               variant="tactile"
219 |             >
220 |               {reorderMutation.isPending ? (
221 |                 <Loader2 className="h-4 w-4 animate-spin" />
222 |               ) : (
223 |                 <Check className="h-4 w-4" />
224 |               )}
225 |               Save Order
226 |             </Button>
227 |           </>
228 |         )}
229 |       </div>
230 |     </div>
231 |
232 |     { /* Soft limit warning (Req 12.4) */ }
233 |     { isAtLimit && (
234 |       <div className="flex items-center gap-2 rounded-lg border border-amber-200 bg-amber-50 px-4 py-3 text-
235 |         <AlertTriangle className="h-4 w-4 shrink-0" />
236 |         <span>
237 |           You have reached the recommended limit of {ILO_SOFT_LIMIT} ILOs.
238 |           Consider consolidating outcomes before adding more.
239 |         </span>
240 |       </div>
241 |     )}
242 |   )}

```

```

243 |     { /* Content */
244 |     {isLoading ? (
245 |       <div className="space-y-3">
246 |         {Array.from({ length: 5 }).map((_, i) => (
247 |           <Shimmer key={i} className="h-14 rounded-lg" />
248 |         ))}
249 |       </div>
250 |     ) : isDragMode ? (
251 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4">
252 |         <p className="text-xs text-gray-500 mb-3">
253 |           Drag items to reorder, then click Save Order.
254 |         </p>
255 |         <DndContext
256 |           sensors={sensors}
257 |           collisionDetection={closestCenter}
258 |           onDragEnd={handleDragEnd}
259 |         >
260 |           <SortableContext
261 |             items={displayItems.map((i) => i.id)}
262 |             strategy={verticalListSortingStrategy}
263 |           >
264 |             <div className="space-y-2">
265 |               {displayItems.map((ilo, idx) => (
266 |                 <SortableRow key={ilo.id} ilo={ilo} index={idx} />
267 |               ))}
268 |             </div>
269 |           </SortableContext>
270 |         </DndContext>
271 |       </Card>
272 |     ) : (
273 |       <DataTable
274 |         columns={columns}
275 |         data={displayItems}
276 |         isLoading={false}
277 |         isFetching={isFetching}
278 |         page={page}
279 |         pageSize={paginatedILOs?.pageSize}
280 |         totalCount={paginatedILOs?.count}
281 |         onPageChange={setPage}
282 |       />
283 |     )}
284 |   { /* Delete Confirmation Dialog */
285 |   <ConfirmDialog
286 |     open={!iloToDelete}
287 |     onOpenChange={() => setIloToDelete(null)}
288 |     title="Delete ILO"
289 |     description={`Are you sure you want to delete "${iloToDelete?.title}"? This action cannot be undone. I`}
290 |     variant="destructive"
291 |     confirmLabel="Delete"
292 |     isPending={deleteMutation.isPending}
293 |     onConfirm={() => {
294 |       if (!iloToDelete) return;
295 |       deleteMutation.mutate(iloToDelete.id, {
296 |         onSuccess: () => {
297 |           toast.success(`${iloToDelete.title} has been deleted`);
298 |           setIloToDelete(null);
299 |         },
300 |         onError: (err) => {
301 |           toast.error(err.message);
302 |           setIloToDelete(null);
303 |         },
304 |       )},
305 |   }}
306 | />
307 | </div>
308 | );
309 | };
310 |
311 | export default ILOListPage;
312 |
313 |

```

FILE: [src/pages/admin/programs/columns.tsx](#)

TYPE: .tsx | LINES: 1-145 | SHA256: 06266f40a790b8067116703f72821ea8aa17bbf05d00c8bf40aefffebfa41ef6

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import {
4 |   ArrowUpDown,
5 |   MoreHorizontal,
6 |   Pencil,
7 |   UserCheck,
8 |   UserX,
9 | } from "lucide-react";
10 | import { Badge } from "@components/ui/badge";
11 | import { Button } from "@components/ui/button";
12 | import {
13 |   DropdownMenu,
14 |   DropdownMenuContent,
15 |   DropdownMenuItem,
16 |   DropdownMenuTrigger,
17 | } from "@components/ui/dropdown-menu";
18 | import type { Program } from "@types/app";
19 |
20 | // % % % Column factory - accepts onEdit and onDeactivate callbacks % % % % % % % % % %
21 |
22 | export const createColumns = (
23 |   onEdit: (id: string) => void,
24 |   onDeactivate: (program: Program) => void
25 | ): ColumnDef<Program>[] => [
26 |   {
27 |     accessorKey: "name",
28 |     header: ({ column }) => (
29 |       <Button

```

```

30         variant="ghost"
31         size="sm"
32         className="-ms-3"
33         onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
34     >
35         Name
36         <ArrowUpDown className="h-4 w-4" />
37     </Button>
38 ),
39 cell: ({ row }) => (
40     <span className="font-medium">{row.getValue("name")}</span>
41 ),
42 },
43 {
44     accessorKey: "code",
45     header: ({ column }) => (
46         <Button
47             variant="ghost"
48             size="sm"
49             className="-ms-3"
50             onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
51         >
52             Code
53             <ArrowUpDown className="h-4 w-4" />
54         </Button>
55     ),
56 },
57 {
58     accessorKey: "coordinator_id",
59     header: "Coordinator",
60     cell: ({ row }) => {
61         const coordinatorId = row.getValue("coordinator_id") as string | null;
62         return (
63             <Badge
64                 variant="outline"
65                 className={
66                     coordinatorId
67                     ? "bg-blue-50 text-blue-600 border-blue-200"
68                     : "bg-gray-50 text-gray-500 border-gray-200"
69                 }
70             >
71                 {coordinatorId ? "Assigned" : "Unassigned"}
72             </Badge>
73         );
74     },
75 },
76 {
77     accessorKey: "is_active",
78     header: "Status",
79     cell: ({ row }) => {
80         const isActive = row.getValue("is_active") as boolean;
81         return (
82             <Badge
83                 variant="outline"
84                 className={
85                     isActive
86                     ? "bg-green-50 text-green-600 border-green-200"
87                     : "bg-red-50 text-red-600 border-red-200"
88                 }
89             >
90                 {isActive ? "Active" : "Inactive"}
91             </Badge>
92         );
93     },
94 },
95 {
96     accessorKey: "created_at",
97     header: "Created",
98     cell: ({ row }) => {
99         const date = row.getValue("created_at") as string;
100         return (
101             <span className="text-gray-500">
102                 {format(new Date(date), "MMM d, yyyy")}
103             </span>
104         );
105     },
106 },
107 {
108     id: "actions",
109     header: "",
110     cell: ({ row }) => {
111         const isActive = row.original.is_active;
112         return (
113             <DropdownMenu>
114                 <DropdownMenuTrigger asChild>
115                     <Button variant="ghost" size="icon-xs">
116                         <MoreHorizontal className="h-4 w-4" />
117                         <span className="sr-only">Open menu</span>
118                     </Button>
119                 </DropdownMenuTrigger>
120                 <DropdownMenuContent align="end">
121                     <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
122                         <Pencil className="h-4 w-4" />
123                         Edit
124                     </DropdownMenuItem>
125                     {isActive ? (
126                         <DropdownMenuItem
127                             variant="destructive"
128                             onClick={() => onDeactivate(row.original)}
129                         >
130                             <UserX className="h-4 w-4" />
131                             Deactivate
132                         </DropdownMenuItem>
133                     ) : (

```

TYPE: .tsx | LINES: 1-400 | SHA256: 0a212ad875657eabf82b13226c509a8ee4d4349650a24df6edd1d0bb120f5f88

```

46 const CreateProgramForm = ({ institutionId }: { institutionId: string }) => {
47   const navigate = useNavigate();
48   const createMutation = useCreateProgram();
49   const { data: coordinators = [], isLoading: isLoadingCoordinators } =
50     useCoordinators();
51   const { data: departments = [], isLoading: isLoadingDepartments } =
52     useDepartments();
53
54   const form = useForm<CreateProgramFormData>({
55     resolver: zodResolver(createProgramSchema),
56     defaultValues: {
57       name: "",
58       code: "",
59       description: "",
60       institution_id: institutionId,
61     },
62   });
63
64   const onSubmit = (data: CreateProgramFormData) => {
65     createMutation.mutate(
66       { ...data, institution_id: institutionId },
67       {
68         onSuccess: () => {
69           toast.success("Program created successfully");
70           navigate("/admin/programs");
71         },
72         onError: (err) => toast.error(err.message),
73       },
74     );
75   };
76
77   return (
78     <ProgramFormFields
79       form={form}
80       onSubmit={onSubmit}
81       isPending={createMutation.isPending}
82       isEditMode={false}
83       coordinators={coordinators}
84       isLoadingCoordinators={isLoadingCoordinators}
85       departments={departments}
86       isLoadingDepartments={isLoadingDepartments}
87     />
88   );

```

[illegible]

```

193 | <Form {...form}>
194 |   <form
195 |     onSubmit={form.handleSubmit(
196 |       onSubmit as Parameters<typeof form.handleSubmit>[0]
197 |     )}
198 |     className="space-y-6"
199 |   >
200 |     <FormField
201 |       control={form.control}
202 |       name={"name" as never}
203 |       render={({ field }) => (
204 |         <FormItem>
205 |           <FormLabel>Program Name</FormLabel>
206 |           <FormControl>
207 |             <Input
208 |               placeholder="e.g. Bachelor of Computer Science"
209 |               {...field}
210 |             />
211 |           </FormControl>
212 |           <FormMessage />
213 |         </FormItem>
214 |       )}
215 |     />
216 |
217 |     <FormField
218 |       control={form.control}
219 |       name={"name_ar" as never}
220 |       render={({ field }) => (
221 |         <FormItem>
222 |           <FormLabel>{t("bilingual.arabicName")}</FormLabel>
223 |           <FormControl>
224 |             <Input
225 |               placeholder={t("bilingual.arabicNamePlaceholder")}
226 |               dir="rtl"
227 |               {...field}
228 |               value={(field.value as string) ?? ""}
229 |             />
230 |           </FormControl>
231 |           <FormMessage />
232 |         </FormItem>
233 |       )}
234 |     />
235 |
236 |     {isEditMode ? (
237 |       <div className="grid gap-2">
238 |         {/* eslint-disable-next-line jsx-a11y/label-has-associated-control */}
239 |         <label className="text-sm font-medium">Program Code</label>
240 |         <Input
241 |           value={existingCode ?? ""}
242 |           disabled
243 |           className="bg-gray-50"
244 |         />
245 |         <p className="text-sm text-muted-foreground">
246 |           Program code cannot be changed after creation.
247 |         </p>
248 |       </div>
249 |     ) : (
250 |       <FormField
251 |         control={form.control}
252 |         name={"code" as never}
253 |         render={({ field }) => (
254 |           <FormItem>
255 |             <FormLabel>Program Code</FormLabel>
256 |             <FormControl>
257 |               <Input placeholder="e.g. BSCS" {...field} />
258 |             </FormControl>
259 |             <FormMessage />
260 |           </FormItem>
261 |         )}
262 |       />
263 |     )}
264 |
265 |     <FormField
266 |       control={form.control}
267 |       name={"description" as never}
268 |       render={({ field }) => (
269 |         <FormItem>
270 |           <FormLabel>Description</FormLabel>
271 |           <FormControl>
272 |             <Textarea
273 |               placeholder="Brief description of the program..."
274 |               className="min-h-[100px] resize-y"
275 |               {...field}
276 |             />
277 |           </FormControl>
278 |           <FormMessage />
279 |         </FormItem>
280 |       )}
281 |     />
282 |
283 |     <FormField
284 |       control={form.control}
285 |       name={"coordinator_id" as never}
286 |       render={({ field }) => (
287 |         <FormItem>
288 |           <FormLabel>Coordinator</FormLabel>
289 |           <Select
290 |             onChange={(value) =>
291 |               field.onChange(value === "__none__" ? undefined : value)
292 |             }
293 |             value={(field.value as string) ?? "__none__"}
294 |             disabled={isLoadingCoordinators}
295 |           >
296 |             <FormControl>

```

[illegible]

FILE: src/pages/admin/programs/ProgramListPage.tsx

TYPE: .tsx | LINES: 1-107 | SHA256: dd2034cdb9b7db2eff13f61497702f728dc21c972ea45027c84e3788495d0bb2

```
1 | import { useState } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { toast } from "sonner";
5 | import { createColumns } from "../columns";
6 | import { DataTable } from "@components/shared/DataTable";
7 | import { NoCourses } from "@components/shared/EmptyState";
8 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
9 | import { usePrograms, useSoftDeleteProgram } from "@hooks/usePrograms";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import { Plus, Search } from "lucide-react";
13 | import type { Program } from "@types/app";
14 |
15 | const ProgramListPage = () => {
16 |   const navigate = useNavigate();
17 |   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
18 |   const [programToDeactivate, setProgramToDeactivate] =
19 |     useState<Program | null>(null);
20 |   const [page, setPage] = useState(1);
21 |
22 |   const {
23 |     data: paginatedData,
24 |     isLoading,
25 |     isFetching,
26 |   } = usePrograms({
27 |     search: search || undefined,
28 |     page,
29 |   });
30 |
31 |   const softDeleteMutation = useSoftDeleteProgram();
32 |
33 |   const columns = createColumns(
34 |     (id) => navigate(`/admin/programs/${id}/edit`),
35 |     (program) => setProgramToDeactivate(program)
36 |   );
37 |
38 |   return (
39 |     <div className="space-y-6">
40 |       {/* Page Header */}
41 |       <div className="flex items-center justify-between">
42 |         <h1 className="text-2xl font-bold tracking-tight">Programs</h1>
43 |         <Button
44 |           variant="tactile"
45 |           onClick={() => navigate("/admin/programs/new")}
46 |         >
47 |           <Plus className="h-4 w-4" /> Add Program
48 |         </Button>
49 |       </div>
50 |
51 |       {/* Filters */}
52 |       <div className="flex items-center gap-4">
53 |         <div className="relative flex-1 max-w-sm">
54 |           <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
55 |           <Input
56 |             placeholder="Search by name or code..."
57 |             value={search}
58 |             onChange={(e) => {
59 |               setSearch(e.target.value || null);
60 |               setPage(1);
61 |             }}
62 |             className="ps-9"
63 |           />
64 |         </div>
65 |       </div>
66 |
67 |       {/* Data Table */}
68 |       <DataTable
69 |         columns={columns}
70 |         data={paginatedData?.data ?? []}
71 |         isLoading={isLoading}
72 |         isFetching={isFetching}
73 |         page={page}
74 |         pageSize={paginatedData?.pageSize}
75 |         totalCount={paginatedData?.count}
76 |         onPageChange={setPage}
77 |         emptyState={<NoCourses />}
78 |       />
79 |
80 |       {/* Deactivate Confirmation Dialog */}
81 |       <ConfirmDialog
82 |         open={!programToDeactivate}
83 |         onOpenChange={() => setProgramToDeactivate(null)}
84 |         title="Deactivate Program"
85 |         description={`Are you sure you want to deactivate "${programToDeactivate?.name}"? This will not affect`}
86 |         variant="destructive"
87 |         confirmLabel="Deactivate"
88 |         isPending={softDeleteMutation.isPending}
89 |         onConfirm={() => {
90 |           if (!programToDeactivate) return;
91 |           softDeleteMutation.mutate(programToDeactivate.id, {
92 |             onSuccess: () => {
93 |               toast.success(`${programToDeactivate.name} has been deactivated`);
94 |               setProgramToDeactivate(null);
95 |             },
96 |             onError: (err) => {
97 |               toast.error(err.message);
98 |             },
99 |           });
100 |         }}
101 |       />
```



```

102 |     </div>
103 |   );
104 | };
105 |
106 | export default ProgramListPage;
107 |

```

FILE: src/pages/admin/reports/AdminAccreditationReportsPage.tsx

TYPE: .tsx | LINES: 1-593 | SHA256: 01f38c85afb60efacb8d14a28e43a1b02f88cffe0ee8bd1c5a7dcf5f2ffd2a3f

```

1 | // =====
2 | // AdminAccreditationReportsPage - Exact Prototype Parity & Real Backend
3 | // =====
4 |
5 | import React, { useState } from "react";
6 | import {
7 |   FileText,
8 |   CheckCircle2,
9 |   Download,
10 |   Loader2,
11 |   Sparkles,
12 |   Layers,
13 |   FileCheck,
14 | } from "lucide-react";
15 | import {
16 |   Button,
17 |   Badge,
18 |   PCard,
19 |   SectionHeader,
20 |   Shimmer,
21 | } from "@design-system";
22 | import {
23 |   useAdminPrograms,
24 |   useAdminSemesters,
25 |   useAdminAccreditationSummary,
26 |   useAccreditationApprovalStages,
27 |   useAccreditationCQIPPlans,
28 |   useAccreditationReportHistory,
29 |   useGenerateAdminAccreditationReport,
30 |   getSignedReportDownloadUrl,
31 |   type ReportTemplate,
32 | } from "@hooks/useAdminAccreditationReports";
33 |
34 | export const AdminAccreditationReportsPage: React.FC = () => {
35 |   const [selectedProgramId, setSelectedProgramId] = useState<string>("");
36 |   const [selectedSemesterId, setSelectedSemesterId] = useState<string>("");
37 |   const [selectedTemplate, setSelectedTemplate] = useState<ReportTemplate>("ABET");
38 |   const [isGenerating, setIsGenerating] = useState(false);
39 |   const [lastGeneratedUrl, setLastGeneratedUrl] = useState<string | null>(null);
40 |
41 |   const programsQuery = useAdminPrograms();
42 |   const semestersQuery = useAdminSemesters();
43 |
44 |   const effectiveProgramId =
45 |     selectedProgramId || (programsQuery.data && programsQuery.data.length > 0 ? programsQuery.data[0]?.id ?? "
46 |
47 |   const summaryQuery = useAdminAccreditationSummary(effectiveProgramId);
48 |   const stagesQuery = useAccreditationApprovalStages(effectiveProgramId);
49 |   const cqiQuery = useAccreditationCQIPPlans(effectiveProgramId);
50 |   const historyQuery = useAccreditationReportHistory();
51 |   const generateMutation = useGenerateAdminAccreditationReport();
52 |
53 |   const summary = summaryQuery.data ?? {
54 |     readinessPercent: 82,
55 |     documented: 2,
56 |     partial: 1,
57 |     blocked: 1,
58 |     notStarted: 1,
59 |     courses: [],
60 |     packChecklist: [],
61 |   };
62 |
63 |   const stages = stagesQuery.data ?? [];
64 |   const cqiPlans = cqiQuery.data ?? [];
65 |   const reportHistory = historyQuery.data ?? [];
66 |
67 |   const handleExportPack = async () => {
68 |     if (!effectiveProgramId) return;
69 |     setIsGenerating(true);
70 |     setLastGeneratedUrl(null);
71 |
72 |     try {
73 |       const result = await generateMutation.mutateAsync({
74 |         program_id: effectiveProgramId,
75 |         semester_id: selectedSemesterId || undefined,
76 |         template: selectedTemplate,
77 |       });
78 |
79 |       setLastGeneratedUrl(result.download_url);
80 |       window.open(result.download_url, "_blank");
81 |     } catch (err) {
82 |       console.error("Report generation failed:", err);
83 |     } finally {
84 |       setIsGenerating(false);
85 |     }
86 |   };
87 |
88 |   const handleDownloadHistoryItem = async (storagePath: string) => {
89 |     const signedUrl = await getSignedReportDownloadUrl(storagePath);
90 |     window.open(signedUrl, "_blank");
91 |   };
92 |
93 |   return (
94 |     <div className="space-y-6 pb-12">

```

```

    { /* % % Page Title & Subtitle % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % */ }
    <div className="flex flex-col md:flex-row md:items-center md:justify-between gap-4">
      <div>
        <h1 className="text-2xl font-black tracking-tight text-slate-900">
          Accreditation reports & evidence
        </h1>
        <p className="text-xs text-slate-500 mt-1">
          AI assembles course files & evidence from live data. You review and sign off.
        </p>
      </div>

      { /* Filters Toolbar */ }
      <div className="flex flex-wrap items-center gap-2">
        { /* Program Selector */ }
        <select
          value={effectiveProgramId}
          onChange={(e) => setSelectedProgramId(e.target.value)}
          className="text-xs font-semibold bg-white border border-slate-200 rounded-lg px-3 py-2 text-slate-
        >
          {programsQuery.isLoading ? (
            <option>Loading programs...</option>
          ) : (
            programsQuery.data?.map((p) => (
              <option key={p.id} value={p.id}>
                {p.name} ({p.code})
              </option>
            ))
          )}
        </select>

        { /* Semester Selector */ }
        <select
          value={selectedSemesterId}
          onChange={(e) => setSelectedSemesterId(e.target.value)}
          className="text-xs font-semibold bg-white border border-slate-200 rounded-lg px-3 py-2 text-slate-
        >
          <option value="">All Semesters</option>
          {semestersQuery.data?.map((s) => (
            <option key={s.id} value={s.id}>
              {s.name} ({s.academic_year})
            </option>
          ))}
        </select>

        { /* Framework Template Selector */ }
        <select
          value={selectedTemplate}
          onChange={(e) => setSelectedTemplate(e.target.value as ReportTemplate)}
          className="text-xs font-bold bg-white border border-slate-200 rounded-lg px-3 py-2 text-sky-700 sh
        >
          <option value="ABET">ABET Framework</option>
          <option value="HEC">HEC Template</option>
          <option value="Generic">Generic OBE Report</option>
        </select>
      </div>
    </div>

    { /* % % Readiness Hero Card % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % */ }
    <PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
      <div className="flex flex-col md:flex-row md:items-center gap-5">
        { /* Readiness Ring */ }
        <div className="relative h-20 w-20 shrink-0 mx-auto md:mx-0">
          <svg className="h-20 w-20 -rotate-90" viewBox="0 0 36 36">
            <circle
              cx="18"
              cy="18"
              r="16"
              fill="none"
              stroke="#eef2f6"
              strokeWidth="3.5"
            />
            <circle
              cx="18"
              cy="18"
              r="16"
              fill="none"
              stroke="#0382bd"
              strokeWidth="3.5"
              strokeLinecap="round"
              strokeDasharray="100"
              strokeDashoffset={100 - summary.readinessPercent}
            />
          </svg>
          <div className="absolute inset-0 flex items-center justify-center text-lg font-black text-sky-600"
            {summary.readinessPercent}%
          </div>
        </div>

        { /* Headline Description */ }
        <div className="flex-1 text-center md:text-left">
          <p className="text-sm font-bold text-slate-900">Evidence readiness</p>
          <p className="text-xs text-slate-500 mt-1 max-w-2xl">
            Live status across all required evidence. One blocker (Concurrency gap) stands between you and a
          </p>
        </div>
      </div>

      { /* Status Tiles Grid */ }
      <div className="grid grid-cols-2 md:grid-cols-4 gap-3 mt-5">
        <div className="rounded-xl p-3 bg-emerald-50 border border-emerald-200 flex flex-col">
          <b className="text-lg font-black text-emerald-700">{summary.documented}</b>
          <span className="text-[10px] font-extrabold uppercase tracking-wider text-emerald-600 mt-1">
            Complete
          </span>
        </div>

```

```

</div>
<div className="rounded-xl p-3 bg-sky-50 border border-sky-200 flex flex-col">
  <b className="text-lg font-black text-sky-700">{summary.partial}</b>
  <span className="text-[10px] font-extrabold uppercase tracking-wider text-sky-600 mt-1">
    In progress
  </span>
</div>

<div className="rounded-xl p-3 bg-rose-50 border border-rose-200 flex flex-col">
  <b className="text-lg font-black text-rose-700">{summary.blocked}</b>
  <span className="text-[10px] font-extrabold uppercase tracking-wider text-rose-600 mt-1">
    Blocked
  </span>
</div>

<div className="rounded-xl p-3 bg-slate-50 border border-slate-200 flex flex-col">
  <b className="text-lg font-black text-slate-600">{summary.notStarted}</b>
  <span className="text-[10px] font-extrabold uppercase tracking-wider text-slate-500 mt-1">
    Not started
  </span>
</div>
</div>
</PCard>

/* % % % 2-Column Main Layout % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % */
<div className="grid grid-cols-1 lg:grid-cols-3 gap-6 items-start">
  { /* Left 2 Columns: Course Files & CQI Action Plans */ }
  <div className="lg:col-span-2 space-y-6">
    { /* Course Files Card */ }
    <PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
      <SectionHeader
        title="Course files"
        icon={Layers}
        action={
          <span className="text-xs font-bold text-slate-400">
            {summary.courses.length} tracked
          </span>
        }
      />
    <div className="space-y-3 mt-4">
      {summaryQuery.isLoading ? (
        <Shimmer className="h-16 w-full rounded-xl" />
      ) : summary.courses.length === 0 ? (
        <p className="text-xs text-slate-500 italic py-4">
          No courses found for selected program.
        </p>
      ) : (
        summary.courses.map((course) => (
          <div
            key={course.id}
            className={`flex items-center gap-3 border p-3 rounded-xl transition-colors ${
              course.status === "blocked"
                ? "border-rose-200 bg-rose-50/40"
                : "border-slate-100 bg-white"
            }`}
          >
            <span className="text-xl">
              {course.status === "blocked"
                ? "ðŸ’”"
                : course.status === "not_started"
                  ? "ðŸ’”"
                  : "ðŸ’”"}
            </span>

            <div className="flex-1 min-w-0">
              <p className="text-sm font-bold text-slate-900 truncate">
                {course.code} · {course.name}
              </p>
              <p className="text-xs text-slate-500 truncate mt-0.5">
                {course.subtitle}
              </p>
            </div>

            <div className="flex items-center gap-2">
              {course.status === "documented" && (
                <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-emerald-100 text-em
                  Signed off
                </span>
              )}
              {course.status === "partial" && (
                <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-amber-100 text-ambe
                  Draft ready
                </span>
              )}
              {course.status === "blocked" && (
                <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-rose-100 text-rose-
                  Blocked
                </span>
              )}
              {course.status === "not_started" && (
                <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-slate-100 text-slat
                  Not started
                </span>
              )}
            </div>

            {course.status === "partial" && (
              <Button
                variant="tactile"
                size="sm"
                className="text-xs font-bold py-1 px-3"
              >
                Review
              </Button>
            )}
          </div>
        ))
      >
    </div>
  </div>

```

```

    </Button>
  }}
  {course.status === "not_started" && (
    <Button
      variant="tactile"
      size="sm"
      className="text-xs font-bold py-1 px-3"
    >
      Start
    </Button>
  )}
</div>
</div>
))
</div>
</PCard>

{/* CQI Action Plans Card */}
<PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
  <SectionHeader
    title="CQI action plans"
    icon={Sparkles}
    action={
      <button className="text-xs font-bold text-sky-600 hover:text-sky-700">
        + AI draft
      </button>
    }
  >
  </div>
  <div className="overflow-x-auto mt-4">
    <table className="w-full text-left border-collapse">
      <thead>
        <tr className="border-b border-slate-100 text-[11px] font-extrabold uppercase text-slate-400">
          <th className="py-2.5 px-3">Action</th>
          <th className="py-2.5 px-3">Outcome</th>
          <th className="py-2.5 px-3">Status</th>
        </tr>
      </thead>
      <tbody>
        <tbody className="divide-y divide-slate-100 text-xs">
          {cqiPlans.map((plan) => (
            <tr key={plan.id} className="hover:bg-slate-50/60">
              <td className="py-3 px-3 font-semibold text-slate-900">
                {plan.action_title}
              </td>
              <td className="py-3 px-3 font-bold text-slate-600">
                {plan.target_outcome}
              </td>
              <td className="py-3 px-3">
                {plan.status === "completed" && (
                  <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-emerald-100 text-emerald-600">
                    Completed
                  </span>
                )}
                {plan.status === "in_progress" && (
                  <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-amber-100 text-amber-600">
                    In progress
                  </span>
                )}
                {plan.status === "planned" && (
                  <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-sky-100 text-sky-600">
                    Planned
                  </span>
                )}
              </td>
            </tr>
          )}
        </tbody>
      </tbody>
    </table>
  </div>
</PCard>

{/* Report Job History Card */}
<PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
  <SectionHeader
    title="Generated report history"
    icon={FileCheck}
  >
  </div>
  <div className="overflow-x-auto mt-4">
    <table className="w-full text-left border-collapse">
      <thead>
        <tr className="border-b border-slate-100 text-[11px] font-extrabold uppercase text-slate-400">
          <th className="py-2.5 px-3">Program</th>
          <th className="py-2.5 px-3">Template</th>
          <th className="py-2.5 px-3">Date</th>
          <th className="py-2.5 px-3">Status</th>
          <th className="py-2.5 px-3 text-right">Download</th>
        </tr>
      </thead>
      <tbody>
        <tbody className="divide-y divide-slate-100 text-xs">
          {reportHistory.length === 0 ? (
            <tr>
              <td colspan={5} className="py-4 text-center text-slate-400 italic">
                No report history found.
              </td>
            </tr>
          ) : (
            reportHistory.map((item) => (
              <tr key={item.id} className="hover:bg-slate-50/60">
                <td className="py-3 px-3 font-semibold text-slate-900">
                  {item.program_name}
                </td>
                <td className="py-3 px-3">

```

```

407         <Badge variant="secondary" className="text-[10px] font-bold">
408             {item.template}
409         </Badge>
410     </td>
411     <td className="py-3 px-3 text-slate-500">
412         {new Date(item.created_at).toLocaleDateString()}
413     </td>
414     <td className="py-3 px-3">
415         <span className="px-2.5 py-1 text-[11px] font-bold rounded-full bg-emerald-100 text-
416             Completed
417         </span>
418     </td>
419     <td className="py-3 px-3 text-right">
420         <button
421             onClick={() => handleDownloadHistoryItem(item.storage_path)}
422             className="inline-flex items-center gap-1 text-xs font-bold text-sky-600 hover:tex
423         >
424             <Download className="h-3.5 w-3.5" /> PDF
425         </button>
426     </td>
427 </tr>
428 ))
429 }}
430 </tbody>
431 </table>
432 </div>
433 </PCard>
434 </div>
435
436 {/* Right Rail Column: Checklist & Workflow */}
437 <div className="space-y-6">
438     {/* Pack Checklist Card */}
439     <PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
440         <SectionHeader title="Accreditation pack checklist" icon={FileText} />
441
442         <div className="space-y-2.5 mt-4">
443             <div className="flex items-center gap-2 text-xs">
444                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
445
446                 </span>
447                 <span className="flex-1 font-semibold text-slate-800">
448                     Syllabi & course files
449                 </span>
450                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
451             </div>
452
453             <div className="flex items-center gap-2 text-xs">
454                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
455
456                 </span>
457                 <span className="flex-1 font-semibold text-slate-800">
458                     CLO !" PLO mappings
459                 </span>
460                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
461             </div>
462
463             <div className="flex items-center gap-2 text-xs">
464                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
465
466                 </span>
467                 <span className="flex-1 font-semibold text-slate-800">
468                     Assessment instruments
469                 </span>
470                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
471             </div>
472
473             <div className="flex items-center gap-2 text-xs">
474                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
475
476                 </span>
477                 <span className="flex-1 font-semibold text-slate-800">
478                     Sample student work
479                 </span>
480                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
481             </div>
482
483             <div className="flex items-center gap-2 text-xs">
484                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
485
486                 </span>
487                 <span className="flex-1 font-semibold text-slate-800">
488                     Attainment analysis
489                 </span>
490                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
491             </div>
492
493             <div className="flex items-center gap-2 text-xs">
494                 <span className="h-5 w-5 rounded-md bg-emerald-100 text-emerald-700 flex items-center justify-
495
496                 </span>
497                 <span className="flex-1 font-semibold text-slate-800">
498                     Faculty reflections
499                 </span>
500                 <span className="text-[11px] font-bold text-emerald-600">Ready</span>
501             </div>
502
503             <div className="flex items-center gap-2 text-xs">
504                 <span className="h-5 w-5 rounded-md bg-amber-100 text-amber-700 flex items-center justify-cent
505
506                 </span>
507                 <span className="flex-1 font-semibold text-slate-800">
508                     CQI recommendations
509                 </span>
510                 <span className="text-[11px] font-bold text-amber-600">Outstanding</span>

```

```

511 |         </div>
512 |     </div>
513 | </PCard>
514 |
515 | { /* 4-Stage Approval Workflow Card */ }
516 | <PCard className="p-5 bg-white border border-slate-200/80 shadow-xs rounded-2xl">
517 |   <SectionHeader title="Approval workflow" icon={CheckCircle2} />
518 |
519 |   <div className="grid grid-cols-4 gap-1 mt-4 text-center">
520 |     {stages.map((st) => {
521 |       <div key={st.id} className="flex flex-col items-center">
522 |         <div
523 |           className={`h-7 w-7 rounded-full flex items-center justify-center text-xs font-extrabold $
524 |             st.status === "done"
525 |               ? "bg-emerald-600 text-white"
526 |               : st.status === "current"
527 |               ? "bg-sky-600 text-white shadow-xs ring-4 ring-sky-100"
528 |               : "bg-slate-200 text-slate-500"
529 |             `}
530 |         >
531 |           {st.status === "done" ? "" : st.sort_order}
532 |         </div>
533 |         <p className="text-[11px] font-extrabold text-slate-900 mt-2 leading-tight">
534 |           {st.label}
535 |         </p>
536 |         <p className="text-[9px] font-bold text-slate-400 mt-0.5">
537 |           {st.status === "done"
538 |             ? "Draft signed"
539 |             : st.status === "current"
540 |             ? "In review"
541 |             : "Pending"}
542 |         </p>
543 |       </div>
544 |     )})
545 |   </div>
546 |
547 |   <p className="text-[11px] text-slate-500 mt-4 pt-3 border-t border-slate-100">
548 |     Currently with the <b>Head of Department</b>. Resolve the Concurrency blocker to unlock QA sign-
549 |   </p>
550 | </PCard>
551 |
552 | { /* Full-width Export Action Button */ }
553 | <div className="space-y-2">
554 |   <Button
555 |     variant="tactile"
556 |     size="lg"
557 |     onClick={handleExportPack}
558 |     disabled={isGenerating}
559 |     className="w-full py-3.5 text-sm font-bold shadow-md"
560 |   >
561 |     {isGenerating ? (
562 |       <
563 |         <Loader2 className="h-4 w-4 animate-spin me-2" />
564 |         Generating Accreditation Pack...
565 |       </>
566 |     ) : (
567 |       <>ÜÄ Export accreditation pack</>
568 |     )}
569 |   </Button>
570 |
571 |   {lastGeneratedUrl && (
572 |     <a
573 |       href={lastGeneratedUrl}
574 |       target="_blank"
575 |       rel="noreferrer"
576 |       className="block text-center text-xs font-bold text-emerald-600 hover:text-emerald-700 py-1"
577 |     >
578 |       ' Report generated! Download PDF !'
579 |     </a>
580 |   )}
581 |
582 |   <p className="text-center text-[11px] text-slate-400">
583 |     Pack generates automatically once the last blocker (CQI recommendations) is resolved.
584 |   </p>
585 | </div>
586 | </div>
587 | </div>
588 | </div>
589 | );
590 | };
591 |
592 | export default AdminAccreditationReportsPage;
593 |

```

FILE: src/pages/admin/reports/ReportGeneratorPage.tsx

TYPE: .tsx | LINES: 1-343 | SHA256: 689a31422fb6ff55ec4aa463fc7b6b6cf592784c3b650f3608f52d25b3990fe7

```

1 | import { useState } from "react";
2 | import { Card } from "@components/ui/card";
3 | import { Button } from "@components/ui/button";
4 | import { Label } from "@components/ui/label";
5 | import { Input } from "@components/ui/input";
6 | import {
7 |   Select,
8 |   SelectContent,
9 |   SelectItem,
10 |   SelectTrigger,
11 |   SelectValue,
12 | } from "@components/ui/select";
13 | import { Shimmer } from "@design-system";
14 | import { usePrograms } from "@hooks/usePrograms";
15 | import { useSemesters } from "@hooks/useSemesters";
16 | import { useProgramAccreditations } from "@hooks/useInstitutionSettings";
17 | import {

```

[illegible]

```

122 toast.success('Report link sent to ${emailTo}');
123 }
124 },
125 onError: (err) => {
126   toast.error(
127     err instanceof Error ? err.message : "Report generation failed"
128   );
129 },
130 },
131 );
132 };
133
134 const handleDownload = () => {
135   if (lastResult?.download_url) {
136     window.open(lastResult.download_url, "_blank");
137   }
138 };
139
140 const isLoading = programsLoading || semestersLoading;
141
142 return (
143   <div className="space-y-6">
144     <div className="flex items-center justify-between">
145       <h1 className="text-2xl font-bold tracking-tight">
146         Accreditation Reports
147       </h1>
148     </div>
149
150     {/ Report Configuration Card */}
151     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
152       <div
153         className="px-6 py-4 flex items-center gap-2"
154         style={{
155           background: "var(--brand-gradient)",
156         }}
157       >
158         <FileText className="h-5 w-5 text-white" />
159         <h2 className="text-lg font-bold tracking-tight text-white">
160           Generate Report
161         </h2>
162       </div>
163       <div className="p-6 space-y-6">
164         {isLoading ? (
165           <div className="space-y-4">
166             <Shimmer className="h-10 rounded-lg" />
167             <Shimmer className="h-10 rounded-lg" />
168             <Shimmer className="h-10 rounded-lg" />
169           </div>
170         ) : (
171           <>
172             {/ Program Selector */}
173             <div className="space-y-2">
174               <Label htmlFor="program-select">Program</Label>
175               <Select value={programId} onChange={handleProgramChange}>
176                 <SelectTrigger id="program-select" className="bg-white">
177                   <SelectValue placeholder="Select a program" />
178                 </SelectTrigger>
179                 <SelectContent>
180                   {programs.map((p) => (
181                     <SelectItem key={p.id} value={p.id}>
182                       {p.code} – {p.name}
183                     </SelectItem>
184                   ))}
185                   {programs.length === 0 && (
186                     <SelectItem value="__none" disabled>
187                       No programs available
188                     </SelectItem>
189                   )}
190                 </SelectContent>
191               </Select>
192             </div>
193
194             {/ Semester Selector */}
195             <div className="space-y-2">
196               <Label htmlFor="semester-select">Semester (optional)</Label>
197               <Select value={semesterId} onChange={setSemesterId}>
198                 <SelectTrigger id="semester-select" className="bg-white">
199                   <SelectValue placeholder="All semesters" />
200                 </SelectTrigger>
201                 <SelectContent>
202                   <SelectItem value="all">All semesters</SelectItem>
203                   {(semesters ?? []).map((s) => (
204                     <SelectItem key={s.id} value={s.id}>
205                       {s.name}
206                     </SelectItem>
207                   ))}
208                 </SelectContent>
209               </Select>
210             </div>
211
212             {/ Template Selector */}
213             <div className="space-y-2">
214               <Label htmlFor="template-select">Report Template</Label>
215               <Select
216                 value={template}
217                 onChange={(v) => setTemplate(v as ReportTemplate)}
218               >
219                 <SelectTrigger id="template-select" className="bg-white">
220                   <SelectValue />
221                 </SelectTrigger>
222                 <SelectContent>
223                   {TEMPLATE_OPTIONS.map((t) => (
224                     <SelectItem key={t.value} value={t.value}>
225                       <span className="font-medium">{t.label}</span>

```



```

226         <span className="text-xs text-gray-500 ms-2">
227             - {t.description}
228         </span>
229     </SelectItem>
230   )}}
231 </SelectContent>
232 </Select>
233 {programAccreditations && programAccreditations.length > 0 && (
234   <p className="text-xs text-gray-500">
235     This program has accreditations:{" "}
236     {programAccreditations
237       .map((a) => a.accreditation_body)
238       .join(", ")}
239     . Using &quot;{ploLabel}&quot;; naming convention.
240   </p>
241 )}
242 </div>
243
244 {/* Email Delivery (optional) */}
245 <div className="space-y-2">
246   <Label htmlFor="email-input">Email delivery (optional)</Label>
247   <div className="flex items-center gap-2">
248     <Mail className="h-4 w-4 text-gray-400 shrink-0" />
249     <Input
250       id="email-input"
251       type="email"
252       placeholder="recipient@institution.edu"
253       value={emailTo}
254       onChange={(e) => setEmailTo(e.target.value)}
255     />
256   </div>
257   <p className="text-xs text-gray-500">
258     If provided, a download link will be emailed after generation.
259   </p>
260 </div>
261
262 {/* Generate Button */}
263 <Button
264   onClick={handleGenerate}
265   disabled={generateMutation.isPending || !programId}
266   variant="tactile"
267   >
268   {generateMutation.isPending ? (
269     <Loader2 className="h-4 w-4 animate-spin" />
270   ) : (
271     <FileText className="h-4 w-4" />
272   )}
273   {generateMutation.isPending
274     ? "Generating..."
275     : "Generate Report"}
276 </Button>
277 </>
278 )}
279 </div>
280 </Card>
281
282 {/* Result Card */}
283 {lastResult && (
284   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
285     <div
286       className="px-6 py-4 flex items-center gap-2"
287       style={{
288         background: "var(--brand-gradient)",
289       }}
290     >
291       <CheckCircle2 className="h-5 w-5 text-white" />
292       <h2 className="text-lg font-bold tracking-tight text-white">
293         Report Ready
294       </h2>
295     </div>
296     <div className="p-6 space-y-4">
297       <div className="grid grid-cols-2 md:grid-cols-4 gap-4 text-sm">
298         <div>
299           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
300             Program
301           </p>
302           <p className="font-semibold mt-1">{lastResult.program_name}</p>
303         </div>
304         <div>
305           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
306             Template
307           </p>
308           <p className="font-semibold mt-1">{lastResult.template}</p>
309         </div>
310         <div>
311           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
312             {PLO_NAMING[lastResult.template] ?? "PLOS"}
313           </p>
314           <p className="font-semibold mt-1">{lastResult.plo_count}</p>
315         </div>
316         <div>
317           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
318             ILOs
319           </p>
320           <p className="font-semibold mt-1">{lastResult.ilo_count}</p>
321         </div>
322       </div>
323
324       <div className="flex items-center gap-3">
325         <Button onClick={handleDownload} variant="tactile">
326           <Download className="h-4 w-4" />
327           Download PDF
328         </Button>
329         {lastResult.semester && (

```

```
330 |         <span className="text-xs text-gray-500">
331 |             Semester: {lastResult.semester}
332 |         </span>
333 |     )}
334 | </div>
335 | </div>
336 | </Card>
337 | }
338 | </div>
339 | );
340 | };
341 |
342 | export default ReportGeneratorPage;
343 |
```

FILE: src/pages/admin/semesters/SemesterManager.tsx

TYPE: .tsx | LINES: 1-384 | SHA256: 9ef280abdd5f138d2ba396d67627c1b868fc2c224c05a963b328192a8da943f9

[illegible]

```

87 |         end_date: semester?.end_date ?? "",
88 |         is_active: semester?.is_active ?? false,
89 |     },
90 | });
91 |
92 | const onSubmit = (data: SemesterFormData) => {
93 |     if (isEdit) {
94 |         updateMutation.mutate(data, {
95 |             onSuccess: () => {
96 |                 onOpenChange(false);
97 |                 form.reset();
98 |             },
99 |         });
100 |     } else {
101 |         createMutation.mutate(
102 |             { ...data, institution_id: institutionId },
103 |             {
104 |                 onSuccess: () => {
105 |                     onOpenChange(false);
106 |                     form.reset();
107 |                 },
108 |             },
109 |         );
110 |     }
111 | };
112 |
113 | const isPending = createMutation.isPending || updateMutation.isPending;
114 |
115 | return (
116 |     <Dialog open={open} onOpenChange={onOpenChange}>
117 |         <DialogContent className="sm:max-w-md">
118 |             <DialogHeader>
119 |                 <DialogTitle>
120 |                     {isEdit ? "Edit Semester" : "Create Semester"}
121 |                 </DialogTitle>
122 |             </DialogHeader>
123 |             <Form {...form}>
124 |                 <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
125 |                     <FormField>
126 |                         control={form.control}
127 |                         name="name"
128 |                         render={({ field }) => (
129 |                             <FormItem>
130 |                                 <FormLabel>Name</FormLabel>
131 |                                 <FormControl>
132 |                                     <Input placeholder="e.g. Fall 2025" {...field} />
133 |                                 </FormControl>
134 |                                 <FormMessage />
135 |                             </FormItem>
136 |                         )}
137 |                     </FormField>
138 |                     <FormField>
139 |                         control={form.control}
140 |                         name="code"
141 |                         render={({ field }) => (
142 |                             <FormItem>
143 |                                 <FormLabel>Code</FormLabel>
144 |                                 <FormControl>
145 |                                     <Input
146 |                                         placeholder="e.g. F25"
147 |                                         {...field}
148 |                                         disabled={isEdit}
149 |                                     />
150 |                                 </FormControl>
151 |                                 <FormMessage />
152 |                             </FormItem>
153 |                         )}
154 |                     </FormField>
155 |                     <div className="grid grid-cols-2 gap-4">
156 |                         <FormField>
157 |                             control={form.control}
158 |                             name="start_date"
159 |                             render={({ field }) => (
160 |                                 <FormItem>
161 |                                     <FormLabel>Start Date</FormLabel>
162 |                                     <FormControl>
163 |                                         <Input type="date" {...field} />
164 |                                     </FormControl>
165 |                                     <FormMessage />
166 |                                 </FormItem>
167 |                             )}
168 |                         </FormField>
169 |                         <FormField>
170 |                             control={form.control}
171 |                             name="end_date"
172 |                             render={({ field }) => (
173 |                                 <FormItem>
174 |                                     <FormLabel>End Date</FormLabel>
175 |                                     <FormControl>
176 |                                         <Input type="date" {...field} />
177 |                                     </FormControl>
178 |                                     <FormMessage />
179 |                                 </FormItem>
180 |                             )}
181 |                         </FormField>
182 |                     </div>
183 |                     <FormField>
184 |                         control={form.control}
185 |                         name="is_active"
186 |                         render={({ field }) => (
187 |                             <FormItem className="flex items-center justify-between rounded-lg border p-3">
188 |                                 <FormLabel className="text-sm font-medium">
189 |                                     Active Semester
190 |                                 </FormLabel>

```

[illegible]

```

295 | const toggleMutation = useToggleSemesterActive();
296 |
297 | const [dialogOpen, setDialogOpen] = useState(false);
298 | const [editingSemester, setEditingSemester] = useState<Semester | null>(null);
299 | const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
300 |
301 | const handleEdit = (semester: Semester) => {
302 |   setEditingSemester(semester);
303 |   setDialogOpen(true);
304 | };
305 |
306 | const handleCreate = () => {
307 |   setEditingSemester(null);
308 |   setDialogOpen(true);
309 | };
310 |
311 | const handleDelete = (id: string) => {
312 |   setDeleteTarget(id);
313 | };
314 |
315 | const confirmDelete = () => {
316 |   if (deleteTarget) {
317 |     deleteMutation.mutate(deleteTarget, {
318 |       onSuccess: () => setDeleteTarget(null),
319 |     });
320 |   }
321 | };
322 |
323 | const handleToggleActive = (id: string, is_active: boolean) => {
324 |   if (!is_active) {
325 |     toast.info("Deactivated semester data preserved as read-only");
326 |   }
327 |   toggleMutation.mutate({ id, is_active });
328 | };
329 |
330 | return (
331 |   <div className="space-y-6">
332 |     <PageHeader
333 |       title="Semesters"
334 |       action={
335 |         <Button onClick={handleCreate} variant="tactile">
336 |           <Plus className="h-4 w-4" /> Add Semester
337 |         </Button>
338 |       }
339 |     />
340 |
341 |     {isLoading ? (
342 |       <div className="space-y-3">
343 |         {Array.from({ length: 3 }).map((_, i) => (
344 |           <Shimmer key={i} className="h-20 rounded-xl" />
345 |         ))}
346 |       </div>
347 |     ) : (semesters ?? []).length === 0 ? (
348 |       <NoSemesters />
349 |     ) : (
350 |       <div className="space-y-3">
351 |         {(semesters ?? []).map((semester) => (
352 |           <SemesterRow
353 |             key={semester.id}
354 |             semester={semester}
355 |             onEdit={handleEdit}
356 |             onDelete={handleDelete}
357 |             onToggleActive={handleToggleActive}
358 |             isToggling={toggleMutation.isPending}
359 |           />
360 |         ))}
361 |       </div>
362 |     )}
363 |
364 |     <SemesterFormDialog
365 |       open={dialogOpen}
366 |       onOpenChange={setDialogOpen}
367 |       semester={editingSemester}
368 |       institutionId={institutionId ?? ""}
369 |     />
370 |
371 |     <ConfirmDialog
372 |       open={!!deleteTarget}
373 |       onOpenChange={(open: boolean) => !open && setDeleteTarget(null)}
374 |       title="Delete Semester"
375 |       description="Are you sure you want to delete this semester? This action cannot be undone."
376 |       onConfirm={confirmDelete}
377 |       isPending={deleteMutation.isPending}
378 |     />
379 |   </div>
380 | );
381 | };
382 |
383 | export default SemesterManager;
384 |

```

FILE: [src/pages/admin/settings/AdminProfilePage.tsx](#)

TYPE: .tsx | LINES: 1-276 | SHA256: 36c6d658b087e31a3d16eba5c8dd2c03aeebe87da9715e9685a7743c85c1f7f9

```

1 | import { BarChart3, Building2, ShieldCheck, Users } from "lucide-react";
2 | import { Link } from "react-router-dom";
3 | import { useTranslation } from "react-i18next";
4 | import { useAuth } from "@hooks/useAuth";
5 | import { useAdminDashboardAggregate } from "@hooks/useAdminDashboardAggregate";
6 | import { Button } from "@components/ui/button";
7 | import { Badge } from "@components/ui/badge";
8 | import RoleProfileSurface, {
9 |   ProfileSectionCard,
10 |   ProfileSettingRow,

```

```

11 | } from "@components/shared/RoleProfileSurface";
12 | import RoleProfileAccountPanels from "@components/shared/RoleProfileAccountPanels";
13 | import EmailPreferencesSection from "@components/shared/EmailPreferencesSection";
14 |
15 | const AdminProfilePage = () => {
16 |   const { t } = useTranslation("common");
17 |   const { profile } = useAuth();
18 |   const aggregate = useAdminDashboardAggregate(profile?.institution_id);
19 |   const kpis = aggregate.data;
20 |   const learnerCount = kpis?.usersByRole.student ?? 0;
21 |   const teacherCount = kpis?.usersByRole.teacher ?? 0;
22 |
23 |   return (
24 |     <RoleProfileSurface
25 |       roleLabel={t("roleProfile.admin.role")}
26 |       scopeLabel={t("roleProfile.admin.scope")}
27 |       isLoading={aggregate.isPending}
28 |       primaryActionLabel={t("roleProfile.admin.institutionPage")}
29 |       primaryActionHref="/admin/institution"
30 |       contactRows={[
31 |         {
32 |           emoji: "ðŸ‘ª",
33 |           label: profile?.email || t("roleProfile.noEmail"),
34 |           href: profile?.email ? `mailto:${profile.email}` : undefined,
35 |         },
36 |         {
37 |           emoji: "ðŸ“Œ",
38 |           label: profile?.institution_id
39 |             ? t("roleProfile.admin.institutionConnected")
40 |             : t("roleProfile.notSet"),
41 |         },
42 |         {
43 |           emoji: "ðŸ‘ª",
44 |           label: t("roleProfile.admin.fullAccess"),
45 |         },
46 |       ]}
47 |       stats={[
48 |         {
49 |           emoji: "ðŸ“œ",
50 |           value: learnerCount,
51 |           label: t("roleProfile.admin.learners"),
52 |           tone: "green",
53 |         },
54 |         {
55 |           emoji: "ðŸ“Œ ðŸ“œ",
56 |           value: teacherCount,
57 |           label: t("roleProfile.admin.teachers"),
58 |           tone: "amber",
59 |         },
60 |         {
61 |           emoji: "ðŸ“œ",
62 |           value: kpis?.totalPrograms ?? 0,
63 |           label: t("roleProfile.admin.programs"),
64 |           tone: "teal",
65 |         },
66 |         {
67 |           emoji: "ðŸ“œ",
68 |           value: kpis?.totalCourses ?? 0,
69 |           label: t("roleProfile.admin.courses"),
70 |           tone: "blue",
71 |         },
72 |       ]}
73 |       overviewTitle={t("roleProfile.admin.overview")}
74 |       overviewDescription={t("roleProfile.admin.overviewDescription")}
75 |       overviewRows={[]}
76 |       links={[]}
77 |     >
78 |     <div className="grid gap-5 lg:grid-cols-2">
79 |       <ProfileSectionCard
80 |         emoji="ðŸ“œ"
81 |         title={t("roleProfile.admin.institutionSettings")}
82 |       >
83 |         <ProfileSettingRow
84 |           title={t("roleProfile.admin.bilingual")}
85 |           description={t("roleProfile.admin.bilingualDescription")}
86 |           trailing={
87 |             <Badge className="bg-emerald-50 text-emerald-700 hover:bg-emerald-50">
88 |               {t("roleProfile.admin.enabled")}
89 |             </Badge>
90 |           )
91 |         />
92 |         <ProfileSettingRow
93 |           title={t("roleProfile.admin.thresholds")}
94 |           description={t("roleProfile.admin.thresholdDescription")}
95 |           trailing={
96 |             <Button asChild variant="outline" size="sm">
97 |               <Link to="/admin/settings">
98 |                 {t("roleProfile.admin.configure")}
99 |               </Link>
100 |             </Button>
101 |           )
102 |         />
103 |         <ProfileSettingRow
104 |           title={t("roleProfile.admin.parentReports")}
105 |           description={t("roleProfile.admin.parentReportsDescription")}
106 |           trailing={
107 |             <Badge className="bg-emerald-50 text-emerald-700 hover:bg-emerald-50">
108 |               {t("roleProfile.admin.enabled")}
109 |             </Badge>
110 |           )
111 |         />
112 |         <ProfileSettingRow
113 |           title={t("roleProfile.admin.accountStatus")}
114 |           trailing={

```

```

115         <Badge variant="secondary">
116             {profile?.is_active
117               ? t("roleProfile.statusActive")
118               : t("roleProfile.statusInactive")}
119         </Badge>
120     }
121 </>
122 </ProfileSectionCard>
123
124 <RoleProfileAccountPanels
125   appearanceTitle={t("roleProfile.admin.platformPreferences")}
126 </>
127 </div>
128
129 <div className="grid gap-5 lg:grid-cols-2">
130   <EmailPreferencesSection
131     title={t("roleProfile.admin.notificationPreferences")}
132     description={t("roleProfile.admin.notificationDescription")}
133     items={[
134       {
135         key: "new_assignment",
136         label: t("roleProfile.admin.newRegistrations"),
137         description: t("roleProfile.admin.newRegistrationsDescription"),
138       },
139       {
140         key: "streak_risk",
141         label: t("roleProfile.admin.securityAlerts"),
142         description: t("roleProfile.admin.securityAlertsDescription"),
143       },
144       {
145         key: "weekly_summary",
146         label: t("roleProfile.admin.weeklySummary"),
147         description: t("roleProfile.admin.weeklySummaryDescription"),
148       },
149       {
150         key: "notification_digest",
151         label: t("roleProfile.admin.quotaWarnings"),
152         description: t("roleProfile.admin.quotaWarningsDescription"),
153       },
154     ]}
155   </>
156
157   <ProfileSectionCard
158     emoji="👤"
159     title={t("roleProfile.admin.permissions")}
160   >
161     {[
162       t("roleProfile.admin.manageUsers"),
163       t("roleProfile.admin.configureInstitution"),
164       t("roleProfile.admin.setAiPolicy"),
165       t("roleProfile.admin.viewAuditLogs"),
166       t("roleProfile.admin.manageBilling"),
167     ].map((permission) => (
168       <div
169         key={permission}
170         className="flex min-h-12 items-center gap-3 border-b border-slate-100 px-4 py-3 last:border-b-0"
171       >
172         <span className="inline-flex size-5 items-center justify-center rounded-md bg-emerald-50 text-xs"
173         >
174           </span>
175         <span className="text-sm font-medium text-slate-700">
176           {permission}
177         </span>
178       </div>
179     ))}
180   </ProfileSectionCard>
181 </div>
182
183 <div className="grid gap-5 lg:grid-cols-2">
184   <ProfileSectionCard
185     emoji="👤"
186     title={t("roleProfile.admin.governanceShortcuts")}
187   >
188     {[
189       {
190         emoji: "🔒",
191         label: t("roleProfile.admin.aiPolicy"),
192         badge: "A2",
193         to: "/admin/security",
194       },
195       {
196         emoji: "🔍",
197         label: t("roleProfile.admin.auditLog"),
198         badge: t("roleProfile.admin.audited"),
199         to: "/admin/security",
200       },
201       {
202         emoji: "🔒",
203         label: t("roleProfile.admin.memoryPrivacy"),
204         badge: "",
205         to: "/admin/security",
206       },
207       {
208         emoji: "👤",
209         label: t("roleProfile.admin.viewAsUser"),
210         badge: t("roleProfile.admin.audited"),
211         to: "/admin/users",
212       },
213     ]}.map((item) => (
214       <Link
215         key={`-${item.to}-${item.label}`}
216         to={item.to}
217         className="flex min-h-14 items-center gap-3 border-b border-slate-100 px-4 py-3 transition-color"
218       >

```

```

219 |         <span aria-hidden="true">{item.emoji}</span>
220 |         <span className="min-w-0 flex-1 text-sm font-semibold text-slate-800">
221 |             {item.label}
222 |         </span>
223 |         {item.badge ? (
224 |             <Badge variant="secondary">{item.badge}</Badge>
225 |         ) : (
226 |             <span className="text-slate-300" aria-hidden="true">
227 |                 !
228 |             </span>
229 |         )}
230 |     </Link>
231 | )}}
232 | </ProfileSectionCard>
233 |
234 | <ProfileSectionCard emoji="ðŸ“”" title={t("roleProfile.workspace")}>
235 |     {[
236 |         {
237 |             icon: Users,
238 |             label: t("nav.users"),
239 |             to: "/admin/users",
240 |         },
241 |         {
242 |             icon: BarChart3,
243 |             label: t("nav.reports"),
244 |             to: "/admin/reports",
245 |         },
246 |         {
247 |             icon: ShieldCheck,
248 |             label: t("nav.security"),
249 |             to: "/admin/security",
250 |         },
251 |         {
252 |             icon: Building2,
253 |             label: t("nav.departments"),
254 |             to: "/admin/departments",
255 |         },
256 |     ]}.map(({ icon: Icon, label, to }) => (
257 |         <Link
258 |             key={to}
259 |             to={to}
260 |             className="flex min-h-14 items-center gap-3 border-b border-slate-100 px-4 py-3 text-sm font-sem
261 |         >
262 |             <Icon className="size-4 text-blue-600" aria-hidden="true" />
263 |             {label}
264 |             <span className="ms-auto text-slate-300" aria-hidden="true">
265 |                 !
266 |             </span>
267 |         </Link>
268 |     )}}
269 | </ProfileSectionCard>
270 | </div>
271 | </RoleProfileSurface>
272 | );
273 | };
274 |
275 | export default AdminProfilePage;
276 |

```

FILE: [src/pages/admin/settings/InstitutionSettings.tsx](#)

TYPE: .tsx | LINES: 1-625 | SHA256: 9c3e5e7a1c2a6b829174d325c62841abb31c3cf2ee2dbf9634df397fd9d69575

```

1 | import { useEffect } from "react";
2 | import { useForm, useFieldArray } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import {
5 |     institutionSettingsSchema,
6 |     type InstitutionSettingsFormData,
7 | } from "@lib/schemas/institutionSettings";
8 | import {
9 |     useInstitutionSettings,
10 |    useUpsertInstitutionSettings,
11 | } from "@hooks/useInstitutionSettings";
12 | import {
13 |     Form,
14 |     FormField,
15 |     FormItem,
16 |     FormLabel,
17 |     FormControl,
18 |     FormDescription,
19 |     FormMessage,
20 | } from "@components/ui/form";
21 | import { Input } from "@components/ui/input";
22 | import { Button } from "@components/ui/button";
23 | import { Card } from "@components/ui/card";
24 | import {
25 |     Select,
26 |     SelectContent,
27 |     SelectItem,
28 |     SelectTrigger,
29 |     SelectValue,
30 | } from "@components/ui/select";
31 | import { GradientCardHeader, Shimmer } from "@design-system";
32 | import ProgramAccreditationManager from "@components/shared/ProgramAccreditationManager";
33 | import { Switch } from "@components/ui/switch";
34 | import { useTranslation } from "react-i18next";
35 | import {
36 |     Loader2,
37 |     Settings,
38 |     GraduationCap,
39 |     Plus,
40 |     Trash2,
41 |     Flame,
42 |     Trophy,

```



```

43 |   Globe,
44 | } from "lucide-react";
45 | import { DEFAULT_GRADE_SCALES, type AccreditationBody } from "@types/app";
46 | import { DEFAULT_LEAGUE_THRESHOLDS } from "@lib/leagueTier";
47 |
48 | const ACCREDITATION_BODIES: Array<{ value: AccreditationBody; label: string }> =
49 | [
50 |   { value: "HEC", label: "HEC – Higher Education Commission" },
51 |   { value: "QQA", label: "QQA – Quality Assurance Authority" },
52 |   {
53 |     value: "ABET",
54 |     label: "ABET – Accreditation Board for Engineering & Technology",
55 |   },
56 |   {
57 |     value: "NCAAA",
58 |     label: "NCAAA – National Commission for Academic Accreditation",
59 |   },
60 |   {
61 |     value: "AACSB",
62 |     label: "AACSB – Association to Advance Collegiate Schools of Business",
63 |   },
64 |   { value: "Generic", label: "Generic – General Format" },
65 | ];
66 |
67 | const InstitutionSettings = () => {
68 |   const { t } = useTranslation("admin");
69 |   const { data: settings, isLoading } = useInstitutionSettings();
70 |   const mutation = useUpsertInstitutionSettings();
71 |
72 |   const form = useForm<InstitutionSettingsFormData>({
73 |     resolver: zodResolver(institutionSettingsSchema),
74 |     defaultValues: {
75 |       attainment_thresholds: {
76 |         excellent: 85,
77 |         satisfactory: 70,
78 |         developing: 50,
79 |       },
80 |       success_threshold: 70,
81 |       accreditation_body: "Generic",
82 |       grade_scales: DEFAULT_GRADE_SCALES,
83 |       streak_sabbatical_enabled: false,
84 |       league_thresholds: DEFAULT_LEAGUE_THRESHOLDS,
85 |       default_language: "en",
86 |     },
87 |   });
88 |
89 |   const { fields, append, remove } = useFieldArray({
90 |     control: form.control,
91 |     name: "grade_scales",
92 |   });
93 |
94 |   useEffect(() => {
95 |     if (settings) {
96 |       form.reset({
97 |         attainment_thresholds: settings.attainment_thresholds,
98 |         success_threshold: settings.success_threshold,
99 |         accreditation_body: settings.accreditation_body,
100 |         grade_scales: settings.grade_scales,
101 |         streak_sabbatical_enabled: settings.streak_sabbatical_enabled ?? false,
102 |         league_thresholds:
103 |           settings.league_thresholds ?? DEFAULT_LEAGUE_THRESHOLDS,
104 |         default_language: (settings.default_language === "ar" ? "ar" : "en") as
105 |           | "en"
106 |           | "ar",
107 |       });
108 |     }
109 |   }, [settings, form]);
110 |
111 |   const onSubmit = (data: InstitutionSettingsFormData) => {
112 |     // Validate threshold ordering: developing < satisfactory < excellent
113 |     const { excellent, satisfactory, developing } = data.attainment_thresholds;
114 |     if (developing >= satisfactory || satisfactory >= excellent) {
115 |       form.setError("attainment_thresholds.developing", {
116 |         message:
117 |           "Thresholds must satisfy: developing < satisfactory < excellent",
118 |       });
119 |       return;
120 |     }
121 |
122 |     mutation.mutate(data);
123 |   };
124 |
125 |   if (isLoading) {
126 |     return (
127 |       <div className="space-y-6">
128 |         <Shimmer className="h-8 w-64 rounded-lg" />
129 |         <Shimmer className="h-96 rounded-xl" />
130 |       </div>
131 |     );
132 |   }
133 |
134 |   return (
135 |     <div className="space-y-6">
136 |       <h1 className="text-2xl font-bold tracking-tight">
137 |         Institution Settings
138 |       </h1>
139 |
140 |       <Form {...form}>
141 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
142 |           { /* Attainment Thresholds Card */ }
143 |           <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
144 |             <GradientCardHeader icon={Settings} title="Attainment Thresholds" />
145 |             <div className="p-6 space-y-4">
146 |               <p className="text-sm text-gray-500">

```

```

147 |         Configure the percentage thresholds for attainment level
148 |         classification across all dashboards, reports, and AI
149 |         predictions.
150 |     </p>
151 |     <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
152 |         <FormField
153 |             control={form.control}
154 |             name="attainment_thresholds.excellent"
155 |             render={({ field }) => (
156 |                 <FormItem>
157 |                     <FormLabel>Excellent ("e")</FormLabel>
158 |                     <FormControl>
159 |                         <Input
160 |                             type="number"
161 |                             min={0}
162 |                             max={100}
163 |                             {...field}
164 |                             onChange={(e) =>
165 |                                 field.onChange(Number(e.target.value))
166 |                             }
167 |                             data-testid="threshold-excellent"
168 |                         />
169 |                     </FormControl>
170 |                     <FormDescription>Default: 85%</FormDescription>
171 |                     <FormMessage />
172 |                 </FormItem>
173 |             )}
174 |         />
175 |         <FormField
176 |             control={form.control}
177 |             name="attainment_thresholds.satisfactory"
178 |             render={({ field }) => (
179 |                 <FormItem>
180 |                     <FormLabel>Satisfactory ("e")</FormLabel>
181 |                     <FormControl>
182 |                         <Input
183 |                             type="number"
184 |                             min={0}
185 |                             max={100}
186 |                             {...field}
187 |                             onChange={(e) =>
188 |                                 field.onChange(Number(e.target.value))
189 |                             }
190 |                             data-testid="threshold-satisfactory"
191 |                         />
192 |                     </FormControl>
193 |                     <FormDescription>Default: 70%</FormDescription>
194 |                     <FormMessage />
195 |                 </FormItem>
196 |             )}
197 |         />
198 |         <FormField
199 |             control={form.control}
200 |             name="attainment_thresholds.developing"
201 |             render={({ field }) => (
202 |                 <FormItem>
203 |                     <FormLabel>Developing ("e")</FormLabel>
204 |                     <FormControl>
205 |                         <Input
206 |                             type="number"
207 |                             min={0}
208 |                             max={100}
209 |                             {...field}
210 |                             onChange={(e) =>
211 |                                 field.onChange(Number(e.target.value))
212 |                             }
213 |                             data-testid="threshold-developing"
214 |                         />
215 |                     </FormControl>
216 |                     <FormDescription>Default: 50%</FormDescription>
217 |                     <FormMessage />
218 |                 </FormItem>
219 |             )}
220 |         />
221 |     </div>
222 |
223 |     <FormField
224 |         control={form.control}
225 |         name="success_threshold"
226 |         render={({ field }) => (
227 |             <FormItem className="max-w-xs">
228 |                 <FormLabel>Success Threshold (%)</FormLabel>
229 |                 <FormControl>
230 |                     <Input
231 |                         type="number"
232 |                         min={0}
233 |                         max={100}
234 |                         {...field}
235 |                         onChange={(e) => field.onChange(Number(e.target.value))}
236 |                         data-testid="success-threshold"
237 |                     />
238 |                 </FormControl>
239 |                 <FormDescription>
240 |                     Percentage of students who must achieve Satisfactory or
241 |                     above for a PLO to be considered "met"; Default:
242 |                     70%
243 |                 </FormDescription>
244 |                 <FormMessage />
245 |             </FormItem>
246 |         )}
247 |     />
248 | </div>
249 | </Card>
250 |

```

```

251 |     { /* Accreditation Body Card */ }
252 |     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
253 |       <GradientCardHeader
254 |         icon={GraduationCap}
255 |         title="Accreditation Body"
256 |       />
257 |       <div className="p-6">
258 |         <FormField
259 |           control={form.control}
260 |           name="accreditation_body"
261 |           render={({ field }) => (
262 |             <FormItem className="max-w-md">
263 |               <FormLabel>Primary Accreditation Body</FormLabel>
264 |               <Select onChange={field.onChange} value={field.value}>
265 |                 <FormControl>
266 |                   <SelectTrigger
267 |                     className="bg-white"
268 |                     data-testid="accreditation-body-select"
269 |                   >
270 |                     <SelectValue placeholder="Select accreditation body" />
271 |                   </SelectTrigger>
272 |                 </FormControl>
273 |                 <SelectContent>
274 |                   {ACCREDTATION_BODIES.map((body) => (
275 |                     <SelectItem key={body.value} value={body.value}>
276 |                       {body.label}
277 |                     </SelectItem>
278 |                   ))}
279 |                 </SelectContent>
280 |               </Select>
281 |               <FormDescription>
282 |                 Determines the default report template and PLO naming
283 |                 conventions.
284 |               </FormDescription>
285 |               <FormMessage />
286 |             </FormItem>
287 |           )}
288 |         />
289 |       </div>
290 |     </Card>
291 |
292 |     { /* Grade Scales Card */ }
293 |     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
294 |       <GradientCardHeader icon={GraduationCap} title="Grade Scales" />
295 |       <div className="p-6 space-y-4">
296 |         <p className="text-sm text-gray-500">
297 |           Configure letter grade mapping for the gradebook. Each row
298 |           defines a letter grade with its percentage range and GPA points.
299 |         </p>
300 |
301 |         <div className="space-y-3">
302 |           {fields.map((field, index) => (
303 |             <div
304 |               key={field.id}
305 |               className="grid grid-cols-5 gap-3 items-end"
306 |             >
307 |               <FormField
308 |                 control={form.control}
309 |                 name={`grade_scales.${index}.letter`}
310 |                 render={({ field: f }) => (
311 |                   <FormItem>
312 |                     {index === 0 && <FormLabel>Letter</FormLabel>}
313 |                     <FormControl>
314 |                       <Input
315 |                         {...f}
316 |                         placeholder="A"
317 |                         data-testid={`grade-letter-${index}`}
318 |                       />
319 |                     </FormControl>
320 |                     <FormMessage />
321 |                   </FormItem>
322 |                 )}
323 |               />
324 |               <FormField
325 |                 control={form.control}
326 |                 name={`grade_scales.${index}.min_percent`}
327 |                 render={({ field: f }) => (
328 |                   <FormItem>
329 |                     {index === 0 && <FormLabel>Min %</FormLabel>}
330 |                     <FormControl>
331 |                       <Input
332 |                         type="number"
333 |                         min={0}
334 |                         max={100}
335 |                         {...f}
336 |                         onChange={(e) =>
337 |                           f.onChange(Number(e.target.value))
338 |                         }
339 |                         data-testid={`grade-min-${index}`}
340 |                       />
341 |                     </FormControl>
342 |                     <FormMessage />
343 |                   </FormItem>
344 |                 )}
345 |               />
346 |               <FormField
347 |                 control={form.control}
348 |                 name={`grade_scales.${index}.max_percent`}
349 |                 render={({ field: f }) => (
350 |                   <FormItem>
351 |                     {index === 0 && <FormLabel>Max %</FormLabel>}
352 |                     <FormControl>
353 |                       <Input
354 |                         type="number"

```

```

355         min={0}
356         max={100}
357         {...f}
358         onChange={(e) =>
359             f.onChange(Number(e.target.value))
360         }
361         data-testid={`grade-max-${index}`}
362     />
363     </FormControl>
364     <FormMessage />
365 </FormItem>
366 )}
367 />
368 <FormField
369     control={form.control}
370     name={`grade_scales.${index}.gpa_points`}
371     render={({ field: f }) => (
372         <FormItem>
373             {index === 0 && <FormLabel>GPA</FormLabel>}
374             <FormControl>
375                 <Input
376                     type="number"
377                     min={0}
378                     max={4}
379                     step={0.1}
380                     {...f}
381                     onChange={(e) =>
382                         f.onChange(Number(e.target.value))
383                     }
384                     data-testid={`grade-gpa-${index}`}
385                 />
386             </FormControl>
387             <FormMessage />
388         </FormItem>
389     )}
390 />
391 <Button
392     type="button"
393     variant="ghost"
394     size="sm"
395     onClick={() => remove(index)}
396     disabled={fields.length <= 1}
397     className="text-red-500 hover:text-red-700"
398     data-testid={`grade-remove-${index}`}
399 >
400     <Trash2 className="h-4 w-4" />
401 </Button>
402 </div>
403 )}
404 </div>
405
406 <Button
407     type="button"
408     variant="outline"
409     size="sm"
410     onClick={() =>
411         append({
412             letter: "",
413             min_percent: 0,
414             max_percent: 0,
415             gpa_points: 0,
416         })
417     }
418     data-testid="add-grade-scale"
419 >
420     <Plus className="h-4 w-4" />
421     Add Grade
422 </Button>
423 </div>
424 </Card>
425
426 {/* Streak Sabbatical Card – Requirement 125.3, 125.4 */}
427 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
428     <GradientCardHeader icon={Flame} title="Streak Sabbatical" />
429     <div className="p-6 space-y-4">
430         <FormField
431             control={form.control}
432             name="streak_sabbatical_enabled"
433             render={({ field }) => (
434                 <FormItem className="flex items-center justify-between rounded-lg border border-slate-200 p-
435                     <div className="space-y-0.5">
436                         <FormLabel className="text-sm font-medium">
437                             Enable Streak Sabbatical
438                         </FormLabel>
439                         <FormDescription className="text-xs text-gray-500">
440                             When enabled, weekends (Saturday & Sunday) will not
441                             count toward streak requirements. Changes apply from the
442                             next calendar day.
443                         </FormDescription>
444                     </div>
445                     <FormControl>
446                         <Switch
447                             checked={field.value}
448                             onChange={field.onChange}
449                             data-testid="streak-sabbatical-toggle"
450                         />
451                     </FormControl>
452                 </FormItem>
453             )}
454         />
455     </div>
456 </Card>
457
458 {/* League Tier Thresholds Card – Requirement 132.5 */}

```

```

459 | <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
460 |   <GradientCardHeader icon={Trophy} title="League Tier Thresholds" />
461 |   <div className="p-6 space-y-4">
462 |     <p className="text-sm text-gray-500">
463 |       Configure the cumulative XP thresholds for each League Tier.
464 |       Students are assigned to tiers based on their total XP.
465 |     </p>
466 |     <div className="grid grid-cols-1 md:grid-cols-4 gap-4">
467 |       <FormField>
468 |         <control={form.control}>
469 |           <name="league_thresholds.bronze">
470 |             <render={({ field }) => (
471 |               <FormItem>
472 |                 <FormLabel>Bronze ("e XP)</FormLabel>
473 |                 <FormControl>
474 |                   <input
475 |                     type="number"
476 |                     min={0}
477 |                     {...field}
478 |                     onChange={(e) =>
479 |                       field.onChange(Number(e.target.value))
480 |                     }
481 |                     data-testid="league-bronze"
482 |                   />
483 |                 </FormControl>
484 |                 <FormDescription>Default: 0</FormDescription>
485 |                 <FormMessage />
486 |               </FormItem>
487 |             )}
488 |           />
489 |         <FormField>
490 |           <control={form.control}>
491 |             <name="league_thresholds.silver">
492 |               <render={({ field }) => (
493 |                 <FormItem>
494 |                   <FormLabel>Silver ("e XP)</FormLabel>
495 |                   <FormControl>
496 |                     <input
497 |                       type="number"
498 |                       min={0}
499 |                       {...field}
500 |                       onChange={(e) =>
501 |                         field.onChange(Number(e.target.value))
502 |                       }
503 |                       data-testid="league-silver"
504 |                     />
505 |                   </FormControl>
506 |                   <FormDescription>Default: 500</FormDescription>
507 |                   <FormMessage />
508 |                 </FormItem>
509 |               )}
510 |             />
511 |           <FormField>
512 |             <control={form.control}>
513 |               <name="league_thresholds.gold">
514 |                 <render={({ field }) => (
515 |                   <FormItem>
516 |                     <FormLabel>Gold ("e XP)</FormLabel>
517 |                     <FormControl>
518 |                       <input
519 |                         type="number"
520 |                         min={0}
521 |                         {...field}
522 |                         onChange={(e) =>
523 |                           field.onChange(Number(e.target.value))
524 |                         }
525 |                         data-testid="league-gold"
526 |                       />
527 |                     </FormControl>
528 |                     <FormDescription>Default: 1500</FormDescription>
529 |                     <FormMessage />
530 |                   </FormItem>
531 |                 )}
532 |               />
533 |             <FormField>
534 |               <control={form.control}>
535 |                 <name="league_thresholds.diamond">
536 |                   <render={({ field }) => (
537 |                     <FormItem>
538 |                       <FormLabel>Diamond ("e XP)</FormLabel>
539 |                       <FormControl>
540 |                         <input
541 |                           type="number"
542 |                           min={0}
543 |                           {...field}
544 |                           onChange={(e) =>
545 |                             field.onChange(Number(e.target.value))
546 |                           }
547 |                           data-testid="league-diamond"
548 |                         />
549 |                       </FormControl>
550 |                       <FormDescription>Default: 4000</FormDescription>
551 |                       <FormMessage />
552 |                     </FormItem>
553 |                   )}
554 |                 />
555 |               </div>
556 |             </div>
557 |           </Card>
558 |
559 |   {/* Default Language Card */}
560 |   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
561 |     <GradientCardHeader
562 |       icon={Globe}

```

```

563 |         title={t("settings.defaultLanguage")}
564 |       />
565 |     <div className="p-6">
566 |       <FormField
567 |         control={form.control}
568 |         name="default_language"
569 |         render={({ field }) => (
570 |           <FormItem className="max-w-md">
571 |             <FormLabel>{t("settings.defaultLanguage")}</FormLabel>
572 |             <Select
573 |               onChange={field.onChange}
574 |               value={field.value ?? "en"}
575 |             >
576 |               <FormControl>
577 |                 <SelectTrigger
578 |                   className="bg-white"
579 |                   data-testid="default-language-select"
580 |                 >
581 |                   <SelectValue
582 |                     placeholder={t("settings.defaultLanguage")}
583 |                   />
584 |                 </SelectTrigger>
585 |               </FormControl>
586 |               <SelectContent>
587 |                 <SelectItem value="en">
588 |                   {t("settings.english")}
589 |                 </SelectItem>
590 |                 <SelectItem value="ar">
591 |                   {t("settings.arabic")}
592 |                 </SelectItem>
593 |               </SelectContent>
594 |             </Select>
595 |             <FormDescription>
596 |               {t("settings.defaultLanguageDesc")}
597 |             </FormDescription>
598 |             <FormMessage />
599 |           </FormItem>
600 |         )}
601 |       />
602 |     </div>
603 |   </Card>
604 |
605 |   {/* Submit */}
606 |   <Button
607 |     type="submit"
608 |     disabled={mutation.isPending}
609 |     variant="tactile"
610 |     data-testid="save-settings"
611 |   >
612 |     {mutation.isPending && <Loader2 className="h-4 w-4 animate-spin" />}
613 |     Save Settings
614 |   </Button>
615 | </form>
616 | </Form>
617 |
618 | {/* Program Accreditations Section */}
619 | <ProgramAccreditationManager />
620 | </div>
621 | );
622 | };
623 |
624 | export default InstitutionSettings;
625 |

```

FILE: src/pages/admin/settings/WellnessXpSettingsPage.tsx

TYPE: .tsx | LINES: 1-129 | SHA256: c75efb9c997182b9728f77136eda92b1b3aa6af8ebb299ac5b35b3d5596a5234

```

1 | import { useForm } from "react-hook-form";
2 | import { zodResolver } from "@hookform/resolvers/zod";
3 | import { z } from "zod";
4 | import { wellnessXpAmountSchema } from "@lib/schemas/wellnessXpAmount";
5 | import {
6 |   useWellnessXpConfig,
7 |   useUpdateWellnessXpAmount,
8 | } from "@hooks/useWellnessXpConfig";
9 | import {
10 |   Form,
11 |   FormField,
12 |   FormItem,
13 |   FormLabel,
14 |   FormControl,
15 |   FormDescription,
16 |   FormMessage,
17 | } from "@components/ui/form";
18 | import { Input } from "@components/ui/input";
19 | import { Button } from "@components/ui/button";
20 | import { Card } from "@components/ui/card";
21 | import { Loader2, Heart } from "lucide-react";
22 | import { Shimmer } from "@design-system";
23 | import { useEffect } from "react";
24 |
25 | const formSchema = z.object({
26 |   wellness_xp_amount: wellnessXpAmountSchema,
27 | });
28 |
29 | type WellnessXpFormData = z.infer<typeof formSchema>;
30 |
31 | const WellnessXpSettingsPage = () => {
32 |   const { data: currentXp, isLoading } = useWellnessXpConfig();
33 |   const mutation = useUpdateWellnessXpAmount();
34 |
35 |   const form = useForm<WellnessXpFormData>({
36 |     resolver: zodResolver(formSchema),
37 |     defaultValues: { wellness_xp_amount: 5 },

```

```

38 | });
39 |
40 | useEffect(() => {
41 |   if (currentXp !== undefined) {
42 |     form.reset({ wellness_xp_amount: currentXp });
43 |   }
44 | }, [currentXp, form]);
45 |
46 | const onSubmit = (data: WellnessXpFormData) => {
47 |   mutation.mutate(data.wellness_xp_amount, {
48 |     onSuccess: () => {
49 |       form.reset({ wellness_xp_amount: data.wellness_xp_amount });
50 |     },
51 |   });
52 | };
53 |
54 | if (isLoading) {
55 |   return (
56 |     <div className="space-y-6">
57 |       <Shimmer className="h-8 w-64 rounded-lg" />
58 |       <Shimmer className="h-48 rounded-xl" />
59 |     </div>
60 |   );
61 | }
62 |
63 | return (
64 |   <div className="space-y-6">
65 |     <h1 className="text-2xl font-bold tracking-tight">Wellness Settings</h1>
66 |
67 |     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
68 |       <div
69 |         className="px-6 py-4 flex items-center gap-2"
70 |         style={{
71 |           background: "var(--brand-gradient)",
72 |         }}
73 |       >
74 |         <Heart className="h-5 w-5 text-white" />
75 |         <h2 className="text-lg font-bold tracking-tight text-white">
76 |           Wellness XP Configuration
77 |         </h2>
78 |       </div>
79 |       <div className="p-6">
80 |         <Form {...form}>
81 |           <form
82 |             onSubmit={form.handleSubmit(onSubmit)}
83 |             className="space-y-6 max-w-md"
84 |           >
85 |             <FormField
86 |               control={form.control}
87 |               name="wellness_xp_amount"
88 |               render={({ field }) => (
89 |                 <FormItem>
90 |                   <FormLabel>Wellness XP per Completion</FormLabel>
91 |                   <FormControl>
92 |                     <Input
93 |                       type="number"
94 |                       min={0}
95 |                       max={25}
96 |                       step={1}
97 |                       {...field}
98 |                       onChange={(e) => field.onChange(Number(e.target.value))}
99 |                       data-testid="wellness-xp-input"
100 |                     </Input>
101 |                   </FormControl>
102 |                   <FormDescription>
103 |                     XP awarded each time a student completes a wellness habit
104 |                     (0-25). Setting this to 0 disables XP for wellness habits.
105 |                   </FormDescription>
106 |                   <FormMessage />
107 |                 </FormItem>
108 |               )}
109 |             </Form>
110 |             <Button
111 |               type="submit"
112 |               disabled={mutation.isPending}
113 |               variant="tactile"
114 |             >
115 |               {mutation.isPending && (
116 |                 <Loader2 className="h-4 w-4 animate-spin" />
117 |               )}
118 |               Save
119 |             </Button>
120 |           </form>
121 |         </div>
122 |       </Card>
123 |     </div>
124 |   );
125 | };
126 |
127 | export default WellnessXpSettingsPage;
128 |
129 |

```

FILE: [src/pages/admin/surveys/SurveyManager.tsx](#)

TYPE: .tsx | LINES: 1-569 | SHA256: b6b33fe8c6150e1f443c39dde52f749896caf85476d92c5b8e75bb702f78c2bb

```

1 | import { useState } from "react";
2 | import { useForm, useFieldArray, useWatch } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import { toast } from "sonner";
6 | import {
7 |   Plus,
8 |   Loader2,

```

[illegible]


```

113 |
114 | interface SurveyFormDialogProps {
115 |   open: boolean;
116 |   onOpenChange: (open: boolean) => void;
117 |   editSurveyId?: string;
118 | }
119 |
120 | const SurveyFormDialog = ({
121 |   open,
122 |   onOpenChange,
123 |   editSurveyId,
124 | }: SurveyFormDialogProps) => {
125 |   const { user, institutionId } = useAuth();
126 |   const { data: existingSurvey } = useSurvey(editSurveyId);
127 |   const { data: existingQuestions } = useSurveyQuestions(editSurveyId);
128 |   const createSurvey = useCreateSurvey();
129 |   const updateSurvey = useUpdateSurvey();
130 |   const createQuestion = useCreateSurveyQuestion();
131 |   const deleteQuestion = useDeleteSurveyQuestion();
132 |
133 |   const form = useForm<SurveyFormData>({
134 |     resolver: zodResolver(surveySchema),
135 |     defaultValues: {
136 |       title: "",
137 |       type: "course_exit",
138 |       is_active: true,
139 |       questions: [{ question_text: "", question_type: "likert", options: "" }],
140 |     },
141 |     values:
142 |       editSurveyId && existingSurvey
143 |       ? {
144 |         title: existingSurvey.title,
145 |         type: existingSurvey.type,
146 |         is_active: existingSurvey.is_active,
147 |         questions: (existingQuestions ?? []).map((q) => ({
148 |           question_text: q.question_text,
149 |           question_type: q.question_type,
150 |           options: q.options?.join(", ") ?? "",
151 |         })),
152 |       }
153 |       : undefined,
154 |   });
155 |
156 |   const { fields, append, remove } = useFieldArray({
157 |     control: form.control,
158 |     name: "questions",
159 |   });
160 |
161 |   const isPending =
162 |     createSurvey.isPending ||
163 |     updateSurvey.isPending ||
164 |     createQuestion.isPending ||
165 |     deleteQuestion.isPending;
166 |
167 |   const onSubmit = async (data: SurveyFormData) => {
168 |     if (!user?.id || !institutionId) return;
169 |
170 |     try {
171 |       if (editSurveyId) {
172 |         await updateSurvey.mutateAsync({
173 |           id: editSurveyId,
174 |           title: data.title,
175 |           type: data.type,
176 |           is_active: data.is_active,
177 |           performedBy: user.id,
178 |         });
179 |
180 |         // Delete old questions and re-create
181 |         for (const q of existingQuestions ?? []) {
182 |           await deleteQuestion.mutateAsync({
183 |             id: q.id,
184 |             surveyId: editSurveyId,
185 |           });
186 |         }
187 |         for (let i = 0; i < data.questions.length; i++) {
188 |           const q = data.questions[i];
189 |           const options =
190 |             q.question_type === "mcq" && q.options
191 |             ? q.options
192 |               .split(",")
193 |               .map((o) => o.trim())
194 |               .filter(Boolean)
195 |             : null;
196 |           await createQuestion.mutateAsync({
197 |             survey_id: editSurveyId,
198 |             question_text: q.question_text,
199 |             question_type: q.question_type,
200 |             options,
201 |             sort_order: i + 1,
202 |           });
203 |         }
204 |         toast.success("Survey updated");
205 |       } else {
206 |         const survey = await createSurvey.mutateAsync({
207 |           institution_id: institutionId,
208 |           title: data.title,
209 |           type: data.type,
210 |           target_outcomes: [],
211 |           is_active: data.is_active,
212 |           performedBy: user.id,
213 |         });
214 |
215 |         for (let i = 0; i < data.questions.length; i++) {
216 |           const q = data.questions[i];

```

```

217 |         const options =
218 |             q.question_type === "mcq" && q.options
219 |             ? q.options
220 |                 .split(",")
221 |                 .map((o) => o.trim())
222 |                 .filter(Boolean)
223 |             : null;
224 |         await createQuestion.mutateAsync({
225 |             survey_id: survey.id,
226 |             question_text: q.question_text,
227 |             question_type: q.question_type,
228 |             options,
229 |             sort_order: i + 1,
230 |         });
231 |     }
232 |     toast.success("Survey created");
233 | }
234 | onOpenChange(false);
235 | form.reset();
236 | } catch (err) {
237 |     toast.error(err instanceof Error ? err.message : "Failed to save survey");
238 | }
239 | };
240 |
241 | return (
242 |     <Dialog open={open} onOpenChange={onOpenChange}>
243 |         <DialogContent className="max-w-2xl max-h-[85vh] overflow-y-auto">
244 |             <DialogHeader>
245 |                 <DialogTitle>
246 |                     {editSurveyId ? "Edit Survey" : "Create Survey"}
247 |                 </DialogTitle>
248 |             </DialogHeader>
249 |             <Form {...form}>
250 |                 <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
251 |                     <FormField>
252 |                         control={form.control}
253 |                         name="title"
254 |                         render={({ field }) => (
255 |                             <FormItem>
256 |                                 <FormLabel>Title</FormLabel>
257 |                                 <FormControl>
258 |                                     <Input
259 |                                         {...field}
260 |                                         placeholder="e.g. Course Exit Survey – Fall 2025"
261 |                                     />
262 |                                 </FormControl>
263 |                                 <FormMessage />
264 |                             </FormItem>
265 |                         )}
266 |                     </FormField>
267 |
268 |                     <div className="grid grid-cols-2 gap-4">
269 |                         <FormField>
270 |                             control={form.control}
271 |                             name="type"
272 |                             render={({ field }) => (
273 |                                 <FormItem>
274 |                                     <FormLabel>Survey Type</FormLabel>
275 |                                     <Select onValueChange={field.onChange} value={field.value}>
276 |                                         <FormControl>
277 |                                             <SelectTrigger className="bg-white">
278 |                                                 <SelectValue />
279 |                                             </SelectTrigger>
280 |                                         </FormControl>
281 |                                         <SelectContent>
282 |                                             <SelectItem value="course_exit">Course Exit</SelectItem>
283 |                                             <SelectItem value="graduate_exit">
284 |                                                 Graduate Exit
285 |                                             </SelectItem>
286 |                                             <SelectItem value="employer">Employer</SelectItem>
287 |                                         </SelectContent>
288 |                                     </Select>
289 |                                     <FormMessage />
290 |                                 </FormItem>
291 |                             )}
292 |                         </div>
293 |
294 |                         <FormField>
295 |                             control={form.control}
296 |                             name="is_active"
297 |                             render={({ field }) => (
298 |                                 <FormItem>
299 |                                     <FormLabel>Status</FormLabel>
300 |                                     <Select
301 |                                         onValueChange={(v) => field.onChange(v === "true")}
302 |                                         value={String(field.value)}
303 |                                     >
304 |                                         <FormControl>
305 |                                             <SelectTrigger className="bg-white">
306 |                                                 <SelectValue />
307 |                                             </SelectTrigger>
308 |                                         </FormControl>
309 |                                         <SelectContent>
310 |                                             <SelectItem value="true">Published</SelectItem>
311 |                                             <SelectItem value="false">Draft</SelectItem>
312 |                                         </SelectContent>
313 |                                     </Select>
314 |                                     <FormMessage />
315 |                                 </FormItem>
316 |                             )}
317 |                         </div>
318 |                     </div>
319 |                 </form>
320 |             </Form>

```

[illegible]

```

425 | const updateSurvey = useUpdateSurvey();
426 |
427 | const [dialogOpen, setDialogOpen] = useState(false);
428 | const [editId, setEditId] = useState<string | undefined>();
429 | const [deleteTarget, setDeleteTarget] = useState<Survey | null>(null);
430 |
431 | const handleEdit = (survey: Survey) => {
432 |   setEditId(survey.id);
433 |   setDialogOpen(true);
434 | };
435 |
436 | const handleCreate = () => {
437 |   setEditId(undefined);
438 |   setDialogOpen(true);
439 | };
440 |
441 | const handleToggleActive = async (survey: Survey) => {
442 |   if (!user?.id) return;
443 |   try {
444 |     await updateSurvey.mutateAsync({
445 |       id: survey.id,
446 |       is_active: !survey.is_active,
447 |       performedBy: user.id,
448 |     });
449 |     toast.success(
450 |       survey.is_active ? "Survey unpublished" : "Survey published"
451 |     );
452 |   } catch (err) {
453 |     toast.error(
454 |       err instanceof Error ? err.message : "Failed to update survey"
455 |     );
456 |   }
457 | };
458 |
459 | const handleDelete = async () => {
460 |   if (!deleteTarget || !user?.id) return;
461 |   try {
462 |     await deleteSurvey.mutateAsync({
463 |       id: deleteTarget.id,
464 |       performedBy: user.id,
465 |     });
466 |     toast.success("Survey deleted");
467 |     setDeleteTarget(null);
468 |   } catch (err) {
469 |     toast.error(
470 |       err instanceof Error ? err.message : "Failed to delete survey"
471 |     );
472 |   }
473 | };
474 |
475 | return (
476 |   <div className="space-y-6">
477 |     <div className="flex items-center justify-between">
478 |       <h1 className="text-2xl font-bold tracking-tight">Surveys</h1>
479 |       <Button onClick={handleCreate} variant="tactile">
480 |         <Plus className="h-4 w-4" /> Create Survey
481 |       </Button>
482 |     </div>
483 |
484 |     {isLoading ? (
485 |       <div className="space-y-4">
486 |         {Array.from({ length: 3 }).map((_, i) => (
487 |           <div key={i} className="h-20 rounded-xl animate-shimmer" />
488 |         ))}
489 |       </div>
490 |     ) : !surveys?.length ? (
491 |       <NoSurveys />
492 |     ) : (
493 |       <div className="space-y-3">
494 |         {surveys.map((survey) => (
495 |           <Card
496 |             key={survey.id}
497 |             className="bg-white border-0 shadow-md rounded-xl p-4"
498 |           >
499 |             <div className="flex items-center justify-between">
500 |               <div className="space-y-1">
501 |                 <div className="flex items-center gap-2">
502 |                   <h3 className="text-sm font-bold">{survey.title}</h3>
503 |                   <Badge
504 |                     variant={survey.is_active ? "default" : "secondary"}
505 |                     className="text-xs"
506 |                   >
507 |                     {survey.is_active ? "Published" : "Draft"}
508 |                   </Badge>
509 |                 </div>
510 |                 <p className="text-xs text-gray-500">
511 |                   {SURVEY_TYPE_LABELS[survey.type]} · Created{" "}
512 |                   {new Date(survey.created_at).toLocaleDateString()}
513 |                 </p>
514 |               </div>
515 |               <div className="flex items-center gap-1">
516 |                 <Button
517 |                   variant="ghost"
518 |                   size="sm"
519 |                   onClick={() => handleToggleActive(survey)}
520 |                   title={survey.is_active ? "Unpublish" : "Publish"}
521 |                 >
522 |                   {survey.is_active ? (
523 |                     <EyeOff className="h-4 w-4" />
524 |                   ) : (
525 |                     <Eye className="h-4 w-4" />
526 |                   )}
527 |                 </Button>
528 |                 <Button

```



```

60 | }
61 |
62 | const QuestionResult = ({
63 |   question,
64 |   responses,
65 |   index,
66 | }: QuestionResultProps) => {
67 |   const questionResponses = responses.filter(
68 |     (r) => r.question_id === question.id
69 |   );
70 |   const totalResponses = questionResponses.length;
71 |
72 |   if (question.question_type === "likert") {
73 |     const data = aggregateLikert(responses, question.id);
74 |     const avg =
75 |       totalResponses > 0
76 |       ? questionResponses.reduce((sum, r) => {
77 |         const idx = (LIKERT_LABELS as readonly string[]).indexOf(
78 |           r.response_value
79 |         );
80 |         return sum + (idx >= 0 ? idx + 1 : 0);
81 |       }, 0) / totalResponses
82 |       : 0;
83 |
84 |     return (
85 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4 space-y-3">
86 |         <div className="flex items-start justify-between">
87 |           <p className="text-sm font-medium">
88 |             Q{index + 1}. {question.question_text}
89 |           </p>
90 |           <Badge variant="secondary" className="text-xs shrink-0 ms-2">
91 |             Avg: {avg.toFixed(1)}/5
92 |           </Badge>
93 |         </div>
94 |         <div className="h-48">
95 |           <ResponsiveContainer width="100%" height="100%">
96 |             <BarChart data={data}>
97 |               <CartesianGrid strokeDasharray="3 3" />
98 |               <XAxis dataKey="label" tick={{ fontSize: 10 }} />
99 |               <YAxis allowDecimals={false} />
100 |               <Tooltip />
101 |               <Bar dataKey="count" fill="#3b82f6" radius={[4, 4, 0, 0]} />
102 |             </BarChart>
103 |           </ResponsiveContainer>
104 |         </div>
105 |         <p className="text-xs text-gray-500">
106 |           {totalResponses} response{totalResponses !== 1 ? "s" : ""}
107 |         </p>
108 |       </Card>
109 |     );
110 |   }
111 |
112 |   if (question.question_type === "mcq") {
113 |     const data = aggregateMCQ(responses, question.id);
114 |
115 |     return (
116 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4 space-y-3">
117 |         <p className="text-sm font-medium">
118 |           Q{index + 1}. {question.question_text}
119 |         </p>
120 |         <div className="h-48">
121 |           <ResponsiveContainer width="100%" height="100%">
122 |             <PieChart>
123 |               <Pie
124 |                 data={data}
125 |                 dataKey="count"
126 |                 nameKey="option"
127 |                 cx="50%"
128 |                 cy="50%"
129 |                 outerRadius={70}
130 |                 label={({ name, value }: { name?: string; value?: number }) =>
131 |                   `${name ?? ""} (${value ?? 0})`
132 |                 }
133 |               >
134 |                 {data.map((_, i) => (
135 |                   <Cell key={i} fill={PIE_COLORS[i % PIE_COLORS.length]} />
136 |                 ))}
137 |               </Pie>
138 |               <Legend />
139 |               <Tooltip />
140 |             </PieChart>
141 |           </ResponsiveContainer>
142 |         </div>
143 |         <p className="text-xs text-gray-500">
144 |           {totalResponses} response{totalResponses !== 1 ? "s" : ""}
145 |         </p>
146 |       </Card>
147 |     );
148 |   }
149 |
150 |   // Text responses
151 |   return (
152 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4 space-y-3">
153 |       <p className="text-sm font-medium">
154 |         Q{index + 1}. {question.question_text}
155 |       </p>
156 |       <div className="max-h-48 overflow-y-auto space-y-2">
157 |         {questionResponses.length === 0 ? (
158 |           <InlineNoResponses />
159 |         ) : (
160 |           questionResponses.map((r) => (
161 |             <div
162 |               key={r.id}
163 |               className="bg-slate-50 rounded-lg px-3 py-2 text-xs text-gray-700"

```

[illegible]

```

268 |         <div
269 |             className="px-6 py-4 flex items-center gap-2"
270 |             style={{
271 |                 background: "var(--brand-gradient)",
272 |             }}
273 |         >
274 |             <ClipboardList className="h-5 w-5 text-white" />
275 |             <h2 className="text-lg font-bold tracking-tight text-white">
276 |                 Question Breakdown
277 |             </h2>
278 |         </div>
279 |         <div className="p-6 space-y-4">
280 |             {(questions ?? []).map((q, i) => (
281 |                 <QuestionResult
282 |                     key={q.id}
283 |                     question={q}
284 |                     responses={responses ?? []}
285 |                     index={i}
286 |                 />
287 |             ))}
288 |             {!questions?.length && <InlineNoQuestions />}
289 |         </div>
290 |     </Card>
291 | </>
292 | )}
293 | </div>
294 | );
295 | };
296 |
297 | export default SurveyResultsPage;
298 |

```

FILE: [src/pages/admin/timetable/TimetableManager.tsx](#)

TYPE: .tsx | LINES: 1-419 | SHA256: 6a31d7e91652f1536e8756017822b54ddb1583ae07b95ef6f0073ee5b15fdb1

```

1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import { Card } from "@components/ui/card";
6 | import { Button } from "@components/ui/button";
7 | import { Input } from "@components/ui/input";
8 | import { Badge } from "@components/ui/badge";
9 | import {
10 |   Form,
11 |   FormField,
12 |   FormItem,
13 |   FormLabel,
14 |   FormControl,
15 |   FormMessage,
16 | } from "@components/ui/form";
17 | import {
18 |   Select,
19 |   SelectContent,
20 |   SelectItem,
21 |   SelectTrigger,
22 |   SelectValue,
23 | } from "@components/ui/select";
24 | import {
25 |   Dialog,
26 |   DialogContent,
27 |   DialogHeader,
28 |   DialogTitle,
29 |   DialogTrigger,
30 | } from "@components/ui/dialog";
31 | import { Clock, Plus, Trash2, Loader2 } from "lucide-react";
32 | import { toast } from "sonner";
33 | import { Shimmer } from "@design-system";
34 | import { InlineNoTimetable } from "@components/shared/EmptyState";
35 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
36 | import {
37 |   useSectionTimetableSlots,
38 |   useCreateTimetableSlot,
39 |   useDeleteTimetableSlot,
40 | } from "@hooks/useTimetable";
41 | import { useQuery } from "@tanstack/react-query";
42 | import { supabase } from "@lib/supabase";
43 | import { queryKeys } from "@lib/queryKeys";
44 |
45 | const DAYS = [
46 |   "Sunday",
47 |   "Monday",
48 |   "Tuesday",
49 |   "Wednesday",
50 |   "Thursday",
51 |   "Friday",
52 |   "Saturday",
53 | ];
54 |
55 | const SLOT_TYPE_STYLES: Record<string, string> = {
56 |   lecture: "bg-blue-100 text-blue-700",
57 |   lab: "bg-green-100 text-green-700",
58 |   tutorial: "bg-purple-100 text-purple-700",
59 | };
60 |
61 | const timetableSlotSchema = z.object({
62 |   section_id: z.string().min(1, "Section is required"),
63 |   day_of_week: z.number().min(0).max(6),
64 |   start_time: z.string().min(1, "Start time is required"),
65 |   end_time: z.string().min(1, "End time is required"),
66 |   room: z.string().optional(),
67 |   slot_type: z.enum(["lecture", "lab", "tutorial"]),
68 | });
69 |

```



```

70 | type TimetableSlotFormData = z.infer<typeof timetableSlotSchema>;
71 |
72 | /** Fetch all sections with course info for the dropdown. */
73 | const useSectionsWithCourses = () => {
74 |   return useQuery({
75 |     queryKey: queryKeys.courseSections.lists(),
76 |     queryFn: async () => {
77 |       const { data, error } = await supabase
78 |         .from("course_sections")
79 |         .select("id, section_code, course_id, courses(name)")
80 |         .order("section_code");
81 |       if (error) throw error;
82 |       return (data ?? []).map((s) => ({
83 |         id: s.id,
84 |         label: `${
85 |           (s.courses as { name: string } | null)?.name ?? "Course"
86 |         } - Section ${s.section_code}`,
87 |         course_name: (s.courses as { name: string } | null)?.name ?? "",
88 |         section_code: s.section_code,
89 |       }));
90 |     },
91 |     staleTime: 5 * 60_000,
92 |   });
93 | };
94 |
95 | const TimetableManager = () => {
96 |   const [selectedSection, setSelectedSection] = useState<string>("");
97 |   const [dialogOpen, setDialogOpen] = useState(false);
98 |   const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
99 |
100 |   const { data: sections = [], isLoading: sectionsLoading } =
101 |     useSectionsWithCourses();
102 |   const { data: slots = [], isLoading: slotsLoading } =
103 |     useSectionTimetableSlots(selectedSection || undefined);
104 |   const createSlot = useCreateTimetableSlot();
105 |   const deleteSlot = useDeleteTimetableSlot();
106 |
107 |   const form = useForm<TimetableSlotFormData>({
108 |     resolver: zodResolver(timetableSlotSchema),
109 |     defaultValues: {
110 |       section_id: "",
111 |       day_of_week: 1,
112 |       start_time: "09:00",
113 |       end_time: "10:00",
114 |       room: "",
115 |       slot_type: "lecture",
116 |     },
117 |   });
118 |
119 |   const onSubmit = (data: TimetableSlotFormData) => {
120 |     createSlot.mutate(
121 |       {
122 |         section_id: data.section_id,
123 |         day_of_week: data.day_of_week,
124 |         start_time: data.start_time,
125 |         end_time: data.end_time,
126 |         room: data.room || undefined,
127 |         slot_type: data.slot_type,
128 |       },
129 |       {
130 |         onSuccess: () => {
131 |           toast.success("Timetable slot created");
132 |           setDialogOpen(false);
133 |           form.reset();
134 |         },
135 |         onError: (err) => toast.error(err.message),
136 |       }
137 |     );
138 |   };
139 |
140 |   const handleDelete = () => {
141 |     if (!deleteTarget) return;
142 |     deleteSlot.mutate(deleteTarget, {
143 |       onSuccess: () => {
144 |         toast.success("Slot deleted");
145 |         setDeleteTarget(null);
146 |       },
147 |       onError: (err) => toast.error(err.message),
148 |     });
149 |   };
150 |
151 |   return (
152 |     <div className="space-y-6">
153 |       <div className="flex items-center justify-between">
154 |         <h1 className="text-2xl font-bold tracking-tight">
155 |           Timetable Management
156 |         </h1>
157 |         <Dialog open={dialogOpen} onOpenChange={setDialogOpen}>
158 |           <DialogTrigger asChild>
159 |             <Button variant="tactile">
160 |               <Plus className="h-4 w-4" /> Add Slot
161 |             </Button>
162 |           </DialogTrigger>
163 |           <DialogContent>
164 |             <DialogHeader>
165 |               <DialogTitle>Add Timetable Slot</DialogTitle>
166 |             </DialogHeader>
167 |             <Form {...form}>
168 |               <form
169 |                 onSubmit={form.handleSubmit(onSubmit)}
170 |                 className="space-y-4">
171 |                 <FormField
172 |                   control={form.control}
173 |

```

```

174     name="section_id"
175     render={({ field }) => (
176       <FormItem>
177         <FormLabel>Section</FormLabel>
178         <Select
179           onChange={field.onChange}
180           value={field.value}
181         >
182           <FormControl>
183             <SelectTrigger>
184               <SelectValue placeholder="Select section" />
185             </SelectTrigger>
186           </FormControl>
187           <SelectContent>
188             {sections.map((s) => (
189               <SelectItem key={s.id} value={s.id}>
190                 {s.label}
191               </SelectItem>
192             ))}
193           </SelectContent>
194         </Select>
195         <FormMessage />
196       </FormItem>
197     )}
198   />
199   <FormField
200     control={form.control}
201     name="day_of_week"
202     render={({ field }) => (
203       <FormItem>
204         <FormLabel>Day</FormLabel>
205         <Select
206           onChange={(v) => field.onChange(Number(v))}
207           value={String(field.value)}
208         >
209           <FormControl>
210             <SelectTrigger>
211               <SelectValue />
212             </SelectTrigger>
213           </FormControl>
214           <SelectContent>
215             {DAYS.map((d, i) => (
216               <SelectItem key={i} value={String(i)}>
217                 {d}
218               </SelectItem>
219             ))}
220           </SelectContent>
221         </Select>
222         <FormMessage />
223       </FormItem>
224     )}
225   />
226   <div className="grid grid-cols-2 gap-4">
227     <FormField
228       control={form.control}
229       name="start_time"
230       render={({ field }) => (
231         <FormItem>
232           <FormLabel>Start Time</FormLabel>
233           <FormControl>
234             <Input type="time" {...field} />
235           </FormControl>
236           <FormMessage />
237         </FormItem>
238       )}
239     />
240     <FormField
241       control={form.control}
242       name="end_time"
243       render={({ field }) => (
244         <FormItem>
245           <FormLabel>End Time</FormLabel>
246           <FormControl>
247             <Input type="time" {...field} />
248           </FormControl>
249           <FormMessage />
250         </FormItem>
251       )}
252     />
253   </div>
254   <FormField
255     control={form.control}
256     name="room"
257     render={({ field }) => (
258       <FormItem>
259         <FormLabel>Room (optional)</FormLabel>
260         <FormControl>
261           <Input placeholder="e.g. Room 301" {...field} />
262         </FormControl>
263         <FormMessage />
264       </FormItem>
265     )}
266   />
267   <FormField
268     control={form.control}
269     name="slot_type"
270     render={({ field }) => (
271       <FormItem>
272         <FormLabel>Slot Type</FormLabel>
273         <Select
274           onChange={field.onChange}
275           value={field.value}
276         >
277           <FormControl>

```

```

278         <SelectTrigger>
279         <SelectValue />
280       </SelectTrigger>
281     </FormControl>
282     <SelectContent>
283       <SelectItem value="lecture">Lecture</SelectItem>
284       <SelectItem value="lab">Lab</SelectItem>
285       <SelectItem value="tutorial">Tutorial</SelectItem>
286     </SelectContent>
287   </Select>
288   <FormMessage />
289 </FormItem>
290 )}
291 />
292 <Button
293   type="submit"
294   disabled={createSlot.isPending}
295   variant="tactile"
296   className="w-full"
297 >
298   {createSlot.isPending && (
299     <Loader2 className="h-4 w-4 animate-spin" />
300   )}
301   Create Slot
302 </Button>
303 </form>
304 </Form>
305 </DialogContent>
306 </Dialog>
307 </div>
308
309 {/ * Section filter */}
310 <Card className="bg-white border-0 shadow-md rounded-xl p-4">
311   <div className="flex items-center gap-4">
312     <label
313       htmlFor="section-filter"
314       className="text-sm font-medium text-gray-600"
315     >
316       Filter by Section:
317     </label>
318     {sectionsLoading ? (
319       <Shimmer className="h-9 w-64 rounded-lg" />
320     ) : (
321       <Select value={selectedSection} onChange={setSelectedSection}>
322         <SelectTrigger className="w-72">
323           <SelectValue placeholder="All sections" />
324         </SelectTrigger>
325         <SelectContent>
326           {sections.map((s) => (
327             <SelectItem key={s.id} value={s.id}>
328               {s.label}
329             </SelectItem>
330           ))}
331         </SelectContent>
332       </Select>
333     )}
334   </div>
335 </Card>
336
337 {/ * Slots list */}
338 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
339   <div
340     className="px-6 py-4 flex items-center gap-2"
341     style={{
342       background: "var(--brand-gradient)",
343     }}
344   >
345     <Clock className="h-5 w-5 text-white" />
346     <h2 className="text-lg font-bold tracking-tight text-white">
347       Timetable Slots
348     </h2>
349   </div>
350   <div className="p-6">
351     {slotsLoading ? (
352       <Shimmer className="h-40 rounded-lg" />
353     ) : !selectedSection ? (
354       <p className="text-sm text-gray-500 text-center py-8">
355         Select a section to view and manage its timetable slots.
356       </p>
357     ) : slots.length === 0 ? (
358       <InlineNoTimetable />
359     ) : (
360       <div className="space-y-2">
361         {slots.map((slot) => (
362           <div
363             key={slot.id}
364             className="flex items-center justify-between py-3 px-4 border border-slate-100 rounded-lg ho
365           >
366             <div className="flex items-center gap-3">
367               <span className="text-sm font-semibold text-slate-700 w-24">
368                 {DAYS[slot.day_of_week]}
369               </span>
370               <span className="text-sm text-slate-600 font-mono">
371                 {slot.start_time?.slice(0, 5)} - {" "}
372                 {slot.end_time?.slice(0, 5)}
373               </span>
374             <Badge
375               className={`text-[10px] ${
376                 SLOT_TYPE_STYLES[slot.slot_type] ??
377                 "bg-gray-100 text-gray-700"
378               }}`
379             >
380               {slot.slot_type}
381             </Badge>

```

```

382 |         {slot.room && (
383 |             <span className="text-xs text-slate-400">
384 |                 {slot.room}
385 |             </span>
386 |         )}
387 |     </div>
388 |     <Button
389 |         variant="ghost"
390 |         size="sm"
391 |         onClick={() => setDeleteTarget(slot.id)}
392 |         className="text-red-500 hover:text-red-700 hover:bg-red-50"
393 |     >
394 |         <Trash2 className="h-4 w-4" />
395 |     </Button>
396 | </div>
397 |     )})}
398 | </div>
399 | )}
400 | </div>
401 | </Card>
402 |
403 | <ConfirmDialog
404 |     open={!deleteTarget}
405 |     onOpenChange={(open: boolean) => {
406 |         if (!open) setDeleteTarget(null);
407 |     }}
408 |     title="Delete Timetable Slot"
409 |     description="Are you sure you want to delete this timetable slot? This action cannot be undone."
410 |     onConfirm={handleDelete}
411 |     confirmLabel="Delete"
412 |     variant="destructive"
413 | />
414 | </div>
415 | );
416 | };
417 |
418 | export default TimetableManager;
419 |

```

FILE: [src/pages/admin/users/BulkImportPage.tsx](#)

TYPE: .tsx | LINES: 1-403 | SHA256: 4abfff267b4ad236303bdfcee18e7b302718bbe386e5df2f8c32d447b165c860

```

1 | import { useState, useCallback } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { csvRowSchema, type CSVRowData } from "@lib/schemas/bulkImport";
4 | import {
5 |     useBulkImportUsers,
6 |     type BulkImportResult,
7 | } from "@hooks/useBulkImport";
8 | import { Card } from "@components/ui/card";
9 | import { Button } from "@components/ui/button";
10 | import { Badge } from "@components/ui/badge";
11 | import {
12 |     Table,
13 |     TableBody,
14 |     TableCell,
15 |     TableHead,
16 |     TableHeader,
17 |     TableRow,
18 | } from "@components/ui/table";
19 | import {
20 |     ArrowLeft,
21 |     Upload,
22 |     FileUp,
23 |     Loader2,
24 |     CheckCircle2,
25 |     XCircle,
26 |     AlertTriangle,
27 | } from "lucide-react";
28 | import { toast } from "sonner";
29 |
30 | const MAX_ROWS = 1000;
31 |
32 | interface ParsedRow {
33 |     rowNumber: number;
34 |     data: Record<string, string>;
35 |     parsed: CSVRowData | null;
36 |     errors: string[];
37 |     isValid: boolean;
38 | }
39 |
40 | type Step = "upload" | "preview" | "result";
41 |
42 | /** Simple CSV parser - handles quoted fields */
43 | const parseCSV = (text: string): Array<Record<string, string>> => {
44 |     const lines = text.trim().split("\n");
45 |     if (lines.length < 2) return [];
46 |
47 |     const headerLine = lines[0] ?? "";
48 |     const headers = headerLine.split(",").map((h) =>
49 |         h
50 |             .trim()
51 |             .toLowerCase()
52 |             .replace(/^[\'"]|[\']$/g, "")
53 |     );
54 |
55 |     return lines
56 |         .slice(1)
57 |         .filter((line) => line.trim())
58 |         .map((line) => {
59 |             const values = line
60 |                 .split(",")
61 |                 .map((v) => v.trim().replace(/^[\'"]|[\']$/g, ""));
62 |             const row: Record<string, string> = {};

```

```

63 |         headers.forEach((header, i) => {
64 |             row[header] = values[i] ?? "";
65 |         });
66 |         return row;
67 |     });
68 | };
69 |
70 | /** Validate rows against Zod schema */
71 | const validateRows = (rawRows: Array<Record<string, string>>): ParsedRow[] => {
72 |     return rawRows.map((data, index) => {
73 |         const result = csvRowSchema.safeParse({
74 |             email: data.email ?? "",
75 |             full_name: data.full_name ?? "",
76 |             role: data.role ?? "",
77 |             program_id: data.program_id || undefined,
78 |         });
79 |
80 |         if (result.success) {
81 |             return {
82 |                 rowNumber: index + 2,
83 |                 data,
84 |                 parsed: result.data,
85 |                 errors: [],
86 |                 isValid: true,
87 |             };
88 |         }
89 |
90 |         const errors = result.error.issues.map(
91 |             (issue) => `${issue.path.join(".")}: ${issue.message}`
92 |         );
93 |         return { rowNumber: index + 2, data, parsed: null, errors, isValid: false };
94 |     });
95 | };
96 |
97 | const BulkImportPage = () => {
98 |     const navigate = useNavigate();
99 |     const [step, setStep] = useState<Step>("upload");
100 |     const [parsedRows, setParsedRows] = useState<ParsedRow[]>([]);
101 |     const [importResult, setImportResult] = useState<BulkImportResult | null>(
102 |         null
103 |     );
104 |     const [isDragOver, setIsDragOver] = useState(false);
105 |     const importMutation = useBulkImportUsers();
106 |
107 |     const handleFile = useCallback((file: File) => {
108 |         if (!file.name.endsWith(".csv")) {
109 |             toast.error("Please upload a CSV file");
110 |             return;
111 |         }
112 |
113 |         const reader = new FileReader();
114 |         reader.onload = (e) => {
115 |             const text = e.target?.result as string;
116 |             const rawRows = parseCSV(text);
117 |
118 |             if (rawRows.length === 0) {
119 |                 toast.error("CSV file is empty or has no data rows");
120 |                 return;
121 |             }
122 |
123 |             if (rawRows.length > MAX_ROWS) {
124 |                 toast.error(
125 |                     `CSV exceeds maximum of ${MAX_ROWS} rows. Found ${rawRows.length} rows.`
126 |                 );
127 |                 return;
128 |             }
129 |
130 |             const validated = validateRows(rawRows);
131 |             setParsedRows(validated);
132 |             setStep("preview");
133 |         };
134 |         reader.readAsText(file);
135 |     }, []);
136 |
137 |     const handleDrop = useCallback(
138 |         (e: React.DragEvent) => {
139 |             e.preventDefault();
140 |             setIsDragOver(false);
141 |             const file = e.dataTransfer.files[0];
142 |             if (file) handleFile(file);
143 |         },
144 |         [handleFile]
145 |     );
146 |
147 |     const handleFileInput = useCallback(
148 |         (e: React.ChangeEvent<HTMLInputElement>) => {
149 |             const file = e.target.files?.[0];
150 |             if (file) handleFile(file);
151 |         },
152 |         [handleFile]
153 |     );
154 |
155 |     const validRows = parsedRows.filter((r) => r.isValid);
156 |     const invalidRows = parsedRows.filter((r) => !r.isValid);
157 |
158 |     const handleImport = () => {
159 |         if (validRows.length === 0) return;
160 |
161 |         const rows = validRows.map((r) => r.parsed!);
162 |         importMutation.mutate(rows, {
163 |             onSuccess: (result) => {
164 |                 setImportResult(result);
165 |                 setStep("result");
166 |                 toast.success(`${result.created} users imported successfully`);

```

```

167     },
168     onError: (err) => {
169       toast.error(err.message);
170     },
171   });
172 };
173
174 const handleReset = () => {
175   setStep("upload");
176   setParsedRows([]);
177   setImportResult(null);
178 };
179
180 return (
181   <div className="space-y-6">
182     {/* Header */}
183     <div className="flex items-center gap-4">
184       <Button
185         variant="ghost"
186         size="sm"
187         onClick={() => navigate("/admin/users")}
188       >
189       <ArrowLeft className="h-4 w-4" /> Back
190     </Button>
191     <h1 className="text-2xl font-bold tracking-tight">Bulk Import Users</h1>
192   </div>
193
194   {/* Step: Upload */}
195   {step === "upload" && (
196     <Card className="bg-white border-0 shadow-md rounded-xl p-8">
197       <div
198         className={`border-2 border-dashed rounded-xl p-12 text-center transition-colors ${
199           isDragOver ? "border-blue-500 bg-blue-50" : "border-slate-300"
200         }`}
201         onDragOver={(e) => {
202           e.preventDefault();
203           setIsDragOver(true);
204         }}
205         onDragLeave={() => setIsDragOver(false)}
206         onDrop={handleDrop}
207       >
208         <FileUp className="h-12 w-12 text-slate-400 mx-auto mb-4" />
209         <p className="text-sm font-medium text-slate-700 mb-1">
210           Drag and drop a CSV file here, or click to browse
211         </p>
212         <p className="text-xs text-slate-500 mb-4">
213           Required columns: email, full_name, role. Optional: program_id.
214           Max {MAX_ROWS} rows.
215         </p>
216         <label htmlFor="csv-file-input">
217           <span className="sr-only">Choose CSV file</span>
218           <Button variant="outline" asChild>
219             <span>
220               <Upload className="h-4 w-4" /> Choose File
221             </span>
222           </Button>
223           <input
224             id="csv-file-input"
225             type="file"
226             accept=".csv"
227             className="hidden"
228             onChange={handleFileInput}
229           />
230         </label>
231       </div>
232     </Card>
233   )}
234
235   {/* Step: Preview */}
236   {step === "preview" && (
237     <div className="space-y-4">
238       {/* Summary */}
239       <div className="flex items-center gap-4">
240         <Badge
241           variant="outline"
242           className="bg-green-50 text-green-600 border-green-200"
243         >
244           {validRows.length} valid
245         </Badge>
246         <Badge
247           variant="outline"
248           className="bg-red-50 text-red-600 border-red-200"
249         >
250           {invalidRows.length} invalid
251         </Badge>
252         <span className="text-sm text-slate-500">
253           {parsedRows.length} total rows
254         </span>
255       </div>
256
257       {/* Preview Table */}
258       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden">
259         <div className="max-h-96 overflow-auto">
260           <Table>
261             <TableHeader>
262               <TableRow>
263                 <TableHead className="w-16">Row</TableHead>
264                 <TableHead>Email</TableHead>
265                 <TableHead>Full Name</TableHead>
266                 <TableHead>Role</TableHead>
267                 <TableHead>Program ID</TableHead>
268                 <TableHead className="w-24">Status</TableHead>
269                 <TableHead>Errors</TableHead>
270               </TableRow>

```

```

271 |         </TableHeader>
272 |         <TableBody>
273 |             {parsedRows.map((row) => (
274 |                 <TableRow
275 |                     key={row.rowNumber}
276 |                     className={row.isValid ? "" : "bg-red-50/50"}
277 |                 >
278 |                     <TableCell className="text-slate-500">
279 |                         {row.rowNumber}
280 |                     </TableCell>
281 |                     <TableCell>{row.data.email}</TableCell>
282 |                     <TableCell>{row.data.full_name}</TableCell>
283 |                     <TableCell>{row.data.role}</TableCell>
284 |                     <TableCell className="text-xs text-slate-500">
285 |                         {row.data.program_id || "-"}
286 |                     </TableCell>
287 |                     <TableCell>
288 |                         {row.isValid ? (
289 |                             <Badge
290 |                                 variant="outline"
291 |                                 className="bg-green-50 text-green-600 border-green-200"
292 |                             >
293 |                                 <CheckCircle2 className="h-3 w-3" /> Valid
294 |                             </Badge>
295 |                         ) : (
296 |                             <Badge
297 |                                 variant="outline"
298 |                                 className="bg-red-50 text-red-600 border-red-200"
299 |                             >
300 |                                 <XCircle className="h-3 w-3" /> Invalid
301 |                             </Badge>
302 |                         )}
303 |                     </TableCell>
304 |                     <TableCell className="text-xs text-red-600">
305 |                         {row.errors.join("; ")}
306 |                     </TableCell>
307 |                 </TableRow>
308 |             )}
309 |         </TableBody>
310 |     </Table>
311 | </div>
312 | </Card>
313 |
314 | {/* Actions */}
315 | <div className="flex items-center gap-3">
316 |     <Button
317 |         onClick={handleImport}
318 |         disabled={validRows.length === 0 || importMutation.isPending}
319 |         variant="tactile"
320 |     >
321 |         {importMutation.isPending && (
322 |             <Loader2 className="h-4 w-4 animate-spin" />
323 |         )}
324 |         Import {validRows.length} Valid Users
325 |     </Button>
326 |     <Button
327 |         variant="outline"
328 |         onClick={handleReset}
329 |         disabled={importMutation.isPending}
330 |     >
331 |         Cancel
332 |     </Button>
333 | </div>
334 |
335 | {/* Warning for invalid rows */}
336 | {invalidRows.length > 0 && (
337 |     <div className="flex items-start gap-2 p-3 rounded-lg bg-amber-50 text-amber-800 text-sm">
338 |         <AlertTriangle className="h-4 w-4 mt-0.5 shrink-0" />
339 |         <span>
340 |             {invalidRows.length} invalid rows will be skipped. Only valid
341 |             rows will be imported.
342 |         </span>
343 |     </div>
344 | )}
345 | </div>
346 | )}
347 |
348 | {/* Step: Result */}
349 | {step === "result" && importResult && (
350 |     <Card className="bg-white border-0 shadow-md rounded-xl p-8">
351 |         <div className="text-center space-y-4">
352 |             <CheckCircle2 className="h-12 w-12 text-green-500 mx-auto" />
353 |             <h2 className="text-lg font-bold">Import Complete</h2>
354 |             <p className="text-sm text-slate-600">
355 |                 {importResult.created} users created successfully.
356 |                 {importResult.errors.length > 0 &&
357 |                     `${importResult.errors.length} rows had server-side errors.`}
358 |             </p>
359 |         </div>
360 |     </Card>
361 |
362 |     {/* Server-side errors */}
363 |     {importResult.errors.length > 0 && (
364 |         <div className="mt-6">
365 |             <h3 className="text-sm font-semibold mb-2">Server Errors</h3>
366 |             <div className="max-h-48 overflow-auto rounded-lg border border-red-200">
367 |                 <Table>
368 |                     <TableHeader>
369 |                         <TableRow>
370 |                             <TableHead className="w-16">Row</TableHead>
371 |                             <TableHead>Error</TableHead>
372 |                         </TableRow>
373 |                     </TableHeader>
374 |                     <TableBody>
375 |                         {importResult.errors.map((err) => (

```

```

375 |         <TableRow key={err.row}>
376 |             <TableCell>{err.row}</TableCell>
377 |             <TableCell className="text-sm text-red-600">
378 |                 {err.message}
379 |             </TableCell>
380 |         </TableRow>
381 |     </tbody>
382 | </TableBody>
383 | </Table>
384 | </div>
385 | </div>
386 | )}
387 |
388 | <div className="flex items-center gap-3 mt-6 justify-center">
389 |     <Button onClick={() => navigate("/admin/users")} variant="tactile">
390 |         View Users
391 |     </Button>
392 |     <Button variant="outline" onClick={handleReset}>
393 |         Import More
394 |     </Button>
395 | </div>
396 | </Card>
397 | </div>
398 | </div>
399 | );
400 | };
401 |
402 | export default BulkImportPage;
403 |

```

FILE: src/pages/admin/users/columns.tsx

TYPE: .tsx | LINES: 1-148 | SHA256: 86b4c403eeb1b4f13af5eb66a1e346740af3769d52607dea9989f69151b772f6

[illegible]


```

72 |         return (
73 |             <Badge variant="outline" className={roleBadgeStyles[role]}>
74 |                 {role.charAt(0).toUpperCase() + role.slice(1)}
75 |             </Badge>
76 |         );
77 |     },
78 | },
79 | {
80 |     accessorKey: "is_active",
81 |     header: "Status",
82 |     cell: ({ row }) => {
83 |         const isActive = row.getValue("is_active") as boolean;
84 |         return (
85 |             <Badge
86 |                 variant="outline"
87 |                 className={
88 |                     isActive
89 |                     ? "bg-green-50 text-green-600 border-green-200"
90 |                     : "bg-red-50 text-red-600 border-red-200"
91 |                 }
92 |             >
93 |                 {isActive ? "Active" : "Inactive"}
94 |             </Badge>
95 |         );
96 |     },
97 | },
98 | {
99 |     accessorKey: "created_at",
100 |    header: "Created",
101 |    cell: ({ row }) => {
102 |        const date = row.getValue("created_at") as string;
103 |        return (
104 |            <span className="text-gray-500">
105 |                {format(new Date(date), "MMM d, yyyy")}
106 |            </span>
107 |        );
108 |    },
109 | },
110 | {
111 |     id: "actions",
112 |     header: "",
113 |     cell: ({ row }) => {
114 |         const isActive = row.original.is_active;
115 |         return (
116 |             <DropdownMenu>
117 |                 <DropdownMenuTrigger asChild>
118 |                     <Button variant="ghost" size="icon-xs">
119 |                         <MoreHorizontal className="h-4 w-4" />
120 |                         <span className="sr-only">Open menu</span>
121 |                     </Button>
122 |                 </DropdownMenuTrigger>
123 |                 <DropdownMenuContent align="end">
124 |                     <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
125 |                         <Pencil className="h-4 w-4" />
126 |                         Edit
127 |                     </DropdownMenuItem>
128 |                     {isActive ? (
129 |                         <DropdownMenuItem
130 |                             variant="destructive"
131 |                             onClick={() => onDeactivate(row.original)}
132 |                         >
133 |                             <UserX className="h-4 w-4" />
134 |                             Deactivate
135 |                         </DropdownMenuItem>
136 |                     ) : (
137 |                         <DropdownMenuItem disabled>
138 |                             <UserCheck className="h-4 w-4" />
139 |                             Reactivate
140 |                         </DropdownMenuItem>
141 |                     )}
142 |                 </DropdownMenuContent>
143 |             </DropdownMenu>
144 |         );
145 |     },
146 | },
147 | ];
148 |

```

FILE: src/pages/admin/users/InviteUsersPage.tsx

TYPE: .tsx | LINES: 1-431 | SHA256: e7d2cd737152945e69be9c19b8828c333d759e1a6002900d3a586ab91f0f1a2f

```

1 | import { useState } from "react";
2 | import { useTranslation } from "react-i18next";
3 | import { useForm } from "react-hook-form";
4 | import { zodResolver } from "@hookform/resolvers/zod";
5 | import { z } from "zod";
6 | import { useAuth } from "@hooks/useAuth";
7 | import { useInviteUsers } from "@hooks/useInviteUsers";
8 | import { Button } from "@components/ui/button";
9 | import { Card } from "@components/ui/card";
10 | import {
11 |     Form,
12 |     FormControl,
13 |     FormField,
14 |     FormItem,
15 |     FormLabel,
16 |     FormMessage,
17 | } from "@components/ui/form";
18 | import { Textarea } from "@components/ui/textarea";
19 | import {
20 |     Select,
21 |     SelectContent,
22 |     SelectItem,
23 |     SelectTrigger,

```

```

24 |   SelectValue,
25 | } from "@components/ui/select";
26 | import { Badge } from "@components/ui/badge";
27 | import {
28 |   Loader2,
29 |   Upload,
30 |   CheckCircle2,
31 |   AlertTriangle,
32 |   Copy,
33 | } from "lucide-react";
34 | import { toast } from "sonner";
35 |
36 | interface InviteRow {
37 |   email: string;
38 |   role: string;
39 |   status: "pending" | "sent" | "failed";
40 |   error?: string;
41 | }
42 |
43 | const inviteSchema = z.object({
44 |   csvContent: z
45 |     .string()
46 |     .min(1, "Please paste CSV content or upload a file")
47 |     .refine((val) => {
48 |       const lines = val.trim().split("\n");
49 |       return lines.length > 1; // At least header + 1 row
50 |     }, "CSV must contain at least one data row"),
51 | });
52 |
53 | type InviteFormData = z.infer<typeof inviteSchema>;
54 |
55 | const InviteUsersPage = () => {
56 |   const { t } = useTranslation("admin");
57 |   const { institutionId } = useAuth();
58 |   const { inviteUsers, isPending: isSending } = useInviteUsers();
59 |
60 |   const [inviteRows, setInviteRows] = useState<InviteRow[]>([]);
61 |   const [showResults, setShowResults] = useState(false);
62 |   const [selectedRole, setSelectedRole] = useState<string>("teacher");
63 |
64 |   const form = useForm<InviteFormData>({
65 |     resolver: zodResolver(inviteSchema),
66 |     defaultValues: {
67 |       csvContent: "",
68 |     },
69 |   });
70 |
71 |   const parseCSV = (content: string): InviteRow[] => {
72 |     const lines = content.trim().split("\n");
73 |     const rows: InviteRow[] = [];
74 |
75 |     // Skip header row (first line)
76 |     for (let i = 1; i < lines.length; i++) {
77 |       const line = lines[i];
78 |       if (!line) continue;
79 |
80 |       const trimmedLine = line.trim();
81 |       if (!trimmedLine) continue;
82 |
83 |       const parts = trimmedLine.split(",").map((s) => s.trim());
84 |       const email = parts[0];
85 |       if (email && email.includes("@") && selectedRole) {
86 |         rows.push({
87 |           email,
88 |           role: selectedRole,
89 |           status: "pending",
90 |         });
91 |       }
92 |     }
93 |
94 |     return rows;
95 |   };
96 |
97 |   const onSubmit = async (data: InviteFormData) => {
98 |     const rows = parseCSV(data.csvContent);
99 |
100 |     if (rows.length === 0) {
101 |       toast.error(t("inviteUsers.noValidEmails"));
102 |       return;
103 |     }
104 |
105 |     setInviteRows(rows.map((r) => ({ ...r, status: "pending" })));
106 |     setShowResults(true);
107 |
108 |     if (!institutionId) {
109 |       toast.error(t("inviteUsers.noInstitution"));
110 |       return;
111 |     }
112 |
113 |     // Send invites
114 |     const invites = rows.map((r) => ({
115 |       email: r.email,
116 |       role: r.role as
117 |         | "admin"
118 |         | "coordinator"
119 |         | "teacher"
120 |         | "student"
121 |         | "parent",
122 |     }));
123 |
124 |     try {
125 |       await inviteUsers({
126 |         institution_id: institutionId,
127 |         invites,

```

```

128 |     });
129 |
130 |     // Update rows with success status
131 |     const updatedRows = rows.map((row) => ({
132 |       ...row,
133 |       status: "sent" as const,
134 |     }));
135 |     setInviteRows(updatedRows);
136 |     toast.success(t("inviteUsers.invitesSent"));
137 |   } catch (error) {
138 |     const updatedRows = rows.map((row) => ({
139 |       ...row,
140 |       status: "failed" as const,
141 |       error: error instanceof Error ? error.message : "Unknown error",
142 |     }));
143 |     setInviteRows(updatedRows);
144 |     toast.error(t("inviteUsers.invitesFailed"));
145 |   }
146 | };
147 |
148 | const handleFileUpload = (e: React.ChangeEvent<HTMLInputElement>) => {
149 |   const file = e.target.files?.[0];
150 |   if (!file) return;
151 |
152 |   const reader = new FileReader();
153 |   reader.onload = (event) => {
154 |     const content = event.target?.result as string;
155 |     form.setValue("csvContent", content);
156 |   };
157 |   reader.readAsText(file);
158 | };
159 |
160 | const downloadTemplate = () => {
161 |   const template =
162 |     "email,role\nteacher@example.com,teacher\ncoordinator@example.com,coordinator";
163 |   const blob = new Blob([template], { type: "text/csv" });
164 |   const url = window.URL.createObjectURL(blob);
165 |   const a = document.createElement("a");
166 |   a.href = url;
167 |   a.download = "invite-template.csv";
168 |   a.click();
169 |   window.URL.revokeObjectURL(url);
170 | };
171 |
172 | const successCount = inviteRows.filter((r) => r.status === "sent").length;
173 | const failureCount = inviteRows.filter((r) => r.status === "failed").length;
174 |
175 | return (
176 |   <div className="space-y-6">
177 |     <div>
178 |       <h1 className="text-2xl font-bold tracking-tight">
179 |         {t("inviteUsers.title")}
180 |       </h1>
181 |       <p className="text-sm text-gray-600 mt-1">
182 |         {t("inviteUsers.subtitle")}
183 |       </p>
184 |     </div>
185 |
186 |     <div>
187 |       <div className="bg-white border-0 shadow-md rounded-xl p-6">
188 |         <Form {...form}>
189 |           <form
190 |             onSubmit={form.handleSubmit(onSubmit)}
191 |             className="space-y-6"
192 |             noValidate
193 |           >
194 |             <div>
195 |               <div className="space-y-2">
196 |                 <label className="text-sm font-medium text-gray-700">
197 |                   {t("inviteUsers.defaultRole")}
198 |                 </label>
199 |                 <select value={selectedRole} onChange={setSelectedRole}>
200 |                   <selectTrigger className="rounded-lg border-gray-200 bg-gray-50/50">
201 |                     <selectValue />
202 |                   </selectTrigger>
203 |                   <selectContent>
204 |                     <selectItem value="teacher">
205 |                       {t("roles.teacher")}
206 |                     </selectItem>
207 |                     <selectItem value="coordinator">
208 |                       {t("roles.coordinator")}
209 |                     </selectItem>
210 |                     <selectItem value="admin">{t("roles.admin")}</selectItem>
211 |                     <selectItem value="parent">{t("roles.parent")}</selectItem>
212 |                   </selectContent>
213 |                 </select>
214 |                 <p className="text-xs text-gray-500">
215 |                   {t("inviteUsers.roleHint")}
216 |                 </p>
217 |               </div>
218 |
219 |               <div>
220 |                 <div>
221 |                   <FormField
222 |                     control={form.control}
223 |                     name="csvContent"
224 |                     render={({ field }) => (
225 |                       <FormItem>
226 |                         <FormLabel>{t("inviteUsers.csvContent")}</FormLabel>
227 |                         <FormControl>
228 |                           <Textarea
229 |                             placeholder={`email,role\nteacher@example.com,teacher\ncoordinator@example.com,coordin
230 |                               className="rounded-lg border-gray-200 bg-gray-50/50 focus:bg-white focus:border-[#14b8
231 |                                 {...field}

```

```

232         />
233     </FormControl>
234     <FormMessage />
235     <p className="text-xs text-gray-500 mt-2">
236         {t("inviteUsers.csvFormat")}
237     </p>
238 </FormItem>
239 )}
240 />
241
242 {/* File upload */}
243 <div className="space-y-2">
244     <label className="text-sm font-medium text-gray-700">
245         {t("inviteUsers.uploadFile")}
246     </label>
247     <div className="flex items-center gap-2">
248         <input
249             type="file"
250             accept=".csv"
251             onChange={handleFileUpload}
252             className="hidden"
253             id="csv-upload"
254         />
255         <label
256             htmlFor="csv-upload"
257             className="flex items-center gap-2 px-4 py-2 rounded-lg border border-gray-200 bg-gray-50"
258         >
259             <Upload className="h-4 w-4" />
260             <span className="text-sm font-medium">
261                 {t("inviteUsers.chooseFile")}
262             </span>
263         </label>
264         <Button
265             type="button"
266             variant="outline"
267             size="sm"
268             onClick={downloadTemplate}
269             className="rounded-lg"
270         >
271             {t("inviteUsers.downloadTemplate")}
272         </Button>
273     </div>
274 </div>
275
276 {/* Action buttons */}
277 <div className="flex gap-3 pt-4">
278     <Button
279         type="button"
280         variant="outline"
281         className="flex-1 rounded-lg"
282         onClick={() => {
283             form.reset();
284             setShowResults(false);
285         }}
286     >
287         {t("inviteUsers.cancel")}
288     </Button>
289     <Button
290         type="submit"
291         variant="tactile"
292         className="flex-1 font-bold"
293         disabled={isSending}
294     >
295         {isSending && (
296             <Loader2 className="h-4 w-4 animate-spin me-2" />
297         )}
298         {t("inviteUsers.sendInvites")}
299     </Button>
300 </div>
301 </form>
302 </Form>
303 </Card>
304 ) : (
305 <Card className="bg-white border-0 shadow-md rounded-xl p-6">
306     {/* Results summary */}
307     <div className="space-y-4">
308         <div className="flex items-center justify-between">
309             <h2 className="text-lg font-bold">{t("inviteUsers.results")}</h2>
310             <div className="flex gap-2">
311                 <Badge
312                     variant="secondary"
313                     className="bg-green-50 text-green-700 border-green-200"
314                 >
315                     <CheckCircle2 className="h-3 w-3 me-1" />
316                     {successCount} {t("inviteUsers.sent")}
317                 </Badge>
318                 {failureCount > 0 && (
319                     <Badge
320                         variant="destructive"
321                         className="bg-red-50 text-red-700 border-red-200"
322                     >
323                         <AlertTriangle className="h-3 w-3 me-1" />
324                         {failureCount} {t("inviteUsers.failed")}
325                     </Badge>
326                 )}
327             </div>
328         </div>
329
330         {/* Results table */}
331         <div className="overflow-x-auto">
332             <table className="w-full text-sm">
333                 <thead>
334                     <tr className="border-b border-gray-200">
335                         <th className="text-left py-2 px-3 font-medium text-gray-700">

```

```

336         {t("inviteUsers.email")}}
337     </th>
338     <th className="text-left py-2 px-3 font-medium text-gray-700">
339         {t("inviteUsers.role")}}
340     </th>
341     <th className="text-left py-2 px-3 font-medium text-gray-700">
342         {t("inviteUsers.status")}}
343     </th>
344     <th className="text-left py-2 px-3 font-medium text-gray-700">
345         {t("inviteUsers.message")}}
346     </th>
347 </tr>
348 </thead>
349 <tbody>
350     {inviteRows.map((row, idx) => (
351         <tr
352             key={idx}
353             className="border-b border-gray-100 hover:bg-gray-50"
354         >
355             <td className="py-3 px-3 text-gray-900">{row.email}</td>
356             <td className="py-3 px-3 text-gray-600 capitalize">
357                 {t(`roles.${row.role}`)}
358             </td>
359             <td className="py-3 px-3">
360                 {row.status === "sent" && (
361                     <Badge className="bg-green-50 text-green-700 border-green-200">
362                         <CheckCircle2 className="h-3 w-3 me-1" />
363                         {t("inviteUsers.sent")}
364                     </Badge>
365                 )}
366                 {row.status === "failed" && (
367                     <Badge
368                         variant="destructive"
369                         className="bg-red-50 text-red-700 border-red-200"
370                     >
371                         <AlertTriangle className="h-3 w-3 me-1" />
372                         {t("inviteUsers.failed")}
373                     </Badge>
374                 )}
375                 {row.status === "pending" && (
376                     <Badge
377                         variant="secondary"
378                         className="bg-gray-100 text-gray-700"
379                     >
380                         {t("inviteUsers.pending")}
381                     </Badge>
382                 )}
383             </td>
384             <td className="py-3 px-3 text-gray-600 text-xs">
385                 {row.error || "-"}
386             </td>
387         </tr>
388     )})
389 </tbody>
390 </table>
391 </div>
392
393     {/* Action buttons */}
394     <div className="flex gap-3 pt-4">
395         <Button
396             type="button"
397             variant="outline"
398             className="flex-1 rounded-lg"
399             onClick={() => {
400                 form.reset();
401                 setShowResults(false);
402                 setInviteRows([]);
403             }}
404         >
405             {t("inviteUsers.sendMore")}
406         </Button>
407         <Button
408             type="button"
409             variant="outline"
410             className="flex-1 rounded-lg"
411             onClick={() => {
412                 const csv = inviteRows
413                     .map((r) => `${r.email},${r.role}`)
414                     .join("\n");
415                 navigator.clipboard.writeText(csv);
416                 toast.success(t("inviteUsers.copiedToClipboard"));
417             }}
418         >
419             <Copy className="h-4 w-4 me-2" />
420             {t("inviteUsers.copyResults")}
421         </Button>
422     </div>
423 </div>
424 </Card>
425 )}
426 </div>
427 );
428 };
429
430 export default InviteUsersPage;
431

```

FILE: src/pages/admin/users/ParentInvitePage.tsx

TYPE: .tsx | LINES: 1-266 | SHA256: ec416b587f8d2dd4ca94ffd10be4a506079b6d3ecd3a50cfc58e25fa01ae3292

```
1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import { Card } from "@components/ui/card";
6 | import { Button } from "@components/ui/button";
7 | import { Input } from "@components/ui/input";
8 | import {
9 |   Form,
10 |   FormField,
11 |   FormItem,
12 |   FormLabel,
13 |   FormControl,
14 |   FormMessage,
15 | } from "@components/ui/form";
16 | import {
17 |   Select,
18 |   SelectContent,
19 |   SelectItem,
20 |   SelectTrigger,
21 |   SelectValue,
22 | } from "@components/ui/select";
23 | import { Loader2, Plus, UserPlus } from "lucide-react";
24 | import { toast } from "sonner";
25 | import { supabase } from "@lib/supabase";
26 | import { logAuditEvent } from "@lib/auditLogger";
27 | import { useAuth } from "@hooks/useAuth";
28 | import { Shimmer } from "@design-system";
29 | import { useQuery } from "@tanstack/react-query";
30 |
31 | const schema = z.object({
32 |   parent_email: z.string().email("Valid email required"),
33 |   parent_name: z.string().min(1, "Name is required"),
34 |   student_id: z.string().min(1, "Student is required"),
35 |   relationship: z.string().min(1, "Relationship is required"),
36 | });
37 |
38 | type FormData = z.infer<typeof schema>;
39 |
40 | const useStudents = () => {
41 |   return useQuery({
42 |     queryKey: ["students-for-parent-invite"],
43 |     queryFn: async () => {
44 |       const { data, error } = await supabase
45 |         .from("profiles")
46 |         .select("id, full_name, email")
47 |         .eq("role", "student")
48 |         .order("full_name");
49 |       if (error) throw error;
50 |       return (data ?? []) as Array<{
51 |         id: string;
52 |         full_name: string;
53 |         email: string;
54 |       }>;
55 |     },
56 |   });
57 | };
58 |
59 | const ParentInvitePage = () => {
60 |   const { user, institutionId } = useAuth();
61 |   const { data: students = [], isLoading: studentsLoading } = useStudents();
62 |   const [isPending, setIsPending] = useState(false);
63 |
64 |   const form = useForm<FormData>({
65 |     resolver: zodResolver(schema),
66 |     defaultValues: {
67 |       parent_email: "",
68 |       parent_name: "",
69 |       student_id: "",
70 |       relationship: "parent",
71 |     },
72 |   });
73 |
74 |   const onSubmit = async (data: FormData) => {
75 |     setIsPending(true);
76 |     try {
77 |       // Create parent profile via admin API
78 |       const { data: authData, error: authErr } =
79 |         await supabase.auth.admin.createUser({
80 |           email: data.parent_email,
81 |           email_confirm: true,
82 |           user_metadata: {
83 |             full_name: data.parent_name,
84 |             role: "parent",
85 |             institution_id: institutionId,
86 |           },
87 |         });
88 |       if (authErr) throw new Error(authErr.message);
89 |
90 |       const parentId = authData.user?.id;
91 |       if (!parentId) throw new Error("Failed to create parent user");
92 |
93 |       // Create profile record
94 |       const { error: profileErr } = await supabase.from("profiles").upsert({
95 |         id: parentId,
96 |         email: data.parent_email,
97 |         full_name: data.parent_name,
98 |         role: "parent",
99 |         institution_id: institutionId ?? "",
100 |       });
101 |       if (profileErr) throw new Error(profileErr.message);
```

```

102 // Create parent-student link
103 const { error: linkErr } = await supabase
104   .from("parent_student_links")
105   .insert({
106     parent_id: parentId,
107     student_id: data.student_id,
108     relationship: data.relationship,
109     verified: true,
110   });
111 if (linkErr) throw new Error(linkErr.message);
112
113 await logAuditEvent({
114   action: "create",
115   entity_type: "parent_invite",
116   entity_id: parentId,
117   changes: {
118     parent_email: data.parent_email,
119     student_id: data.student_id,
120   },
121   performed_by: user?.id ?? "",
122 });
123
124 toast.success("Parent invited and linked to student");
125 form.reset();
126 } catch (err) {
127   toast.error((err as Error).message);
128 } finally {
129   setIsPending(false);
130 }
131 };
132
133 return (
134   <div className="space-y-6">
135     <div className="flex items-center justify-between">
136       <h1 className="text-2xl font-bold tracking-tight">
137         Invite Parent / Guardian
138       </h1>
139     </div>
140
141     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
142       <div
143         className="px-6 py-4 flex items-center gap-2"
144         style={{
145           background: "var(--brand-gradient)",
146         }}
147       >
148         <UserPlus className="h-5 w-5 text-white" />
149         <h2 className="text-lg font-bold tracking-tight text-white">
150           New Parent Invite
151         </h2>
152       </div>
153       <div className="p-6">
154         <p className="text-sm text-slate-500 mb-6">
155           Create a parent account and link it to a student. The parent will
156           receive read-only access to their child's academic data.
157         </p>
158         {studentsLoading ? (
159           <Shimmer className="h-32 rounded-lg" />
160         ) : (
161           <Form {...form}>
162             <form
163               onSubmit={form.handleSubmit(onSubmit)}
164               className="space-y-4 max-w-xl"
165             >
166               <FormField
167                 control={form.control}
168                 name="parent_name"
169                 render={({ field }) => (
170                   <FormItem>
171                     <FormLabel>Parent Name</FormLabel>
172                     <FormControl>
173                       <Input placeholder="Full name" {...field} />
174                     </FormControl>
175                     <FormMessage />
176                   </FormItem>
177                 )}
178               />
179               <FormField
180                 control={form.control}
181                 name="parent_email"
182                 render={({ field }) => (
183                   <FormItem>
184                     <FormLabel>Parent Email</FormLabel>
185                     <FormControl>
186                       <Input
187                         type="email"
188                         placeholder="parent@example.com"
189                         {...field}
190                       />
191                     </FormControl>
192                     <FormMessage />
193                   </FormItem>
194                 )}
195               />
196               <FormField
197                 control={form.control}
198                 name="student_id"
199                 render={({ field }) => (
200                   <FormItem>
201                     <FormLabel>Link to Student</FormLabel>
202                     <Select
203                       value={field.value}
204                       onChange={field.onChange}
205
```

```

206 |         >
207 |         <FormControl>
208 |           <SelectTrigger className="bg-white">
209 |             <SelectValue placeholder="Select student" />
210 |           </SelectTrigger>
211 |         </FormControl>
212 |         <SelectContent>
213 |           {students.map((s) => (
214 |             <SelectItem key={s.id} value={s.id}>
215 |               {s.full_name} ({s.email})
216 |             </SelectItem>
217 |           ))}
218 |         </SelectContent>
219 |       </Select>
220 |       <FormMessage />
221 |     </FormItem>
222 |   )}
223 | </>
224 | <FormField
225 |   control={form.control}
226 |   name="relationship"
227 |   render={({ field }) => (
228 |     <FormItem>
229 |       <FormLabel>Relationship</FormLabel>
230 |       <Select
231 |         value={field.value}
232 |         onChange={field.onChange}
233 |       >
234 |         <FormControl>
235 |           <SelectTrigger className="bg-white">
236 |             <SelectValue />
237 |           </SelectTrigger>
238 |         </FormControl>
239 |         <SelectContent>
240 |           <SelectItem value="parent">Parent</SelectItem>
241 |           <SelectItem value="guardian">Guardian</SelectItem>
242 |         </SelectContent>
243 |       </Select>
244 |       <FormMessage />
245 |     </FormItem>
246 |   )}
247 | </>
248 | <Button type="submit" disabled={isPending} variant="tactile">
249 |   {isPending ? (
250 |     <Loader2 className="h-4 w-4 animate-spin" />
251 |   ) : (
252 |     <Plus className="h-4 w-4" />
253 |   )}
254 |   Invite Parent
255 | </Button>
256 | </form>
257 | </Form>
258 |   )}
259 | </div>
260 | </Card>
261 | </div>
262 | );
263 | };
264 |
265 | export default ParentInvitePage;
266 |

```

FILE: [src/pages/admin/users/UserForm.tsx](#)

TYPE: .tsx | LINES: 1-299 | SHA256: 34266db27bd5be47f878e07e4e67333da500530249adaa05bac2b9cef97caf68

```

1 | import { useEffect } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useNavigate, useParams } from "react-router-dom";
5 | import {
6 |   createUserSchema,
7 |   updateUserSchema,
8 |   type CreateUserFormData,
9 |   type UpdateUserFormData,
10 | } from "@lib/schemas/user";
11 | import { useCreateUser, useUpdateUser, useUser } from "@hooks/useUsers";
12 | import { useAuth } from "@hooks/useAuth";
13 | import {
14 |   Form,
15 |   FormField,
16 |   FormItem,
17 |   FormLabel,
18 |   FormControl,
19 |   FormMessage,
20 | } from "@components/ui/form";
21 | import { Input } from "@components/ui/input";
22 | import {
23 |   Select,
24 |   SelectContent,
25 |   SelectItem,
26 |   SelectTrigger,
27 |   SelectValue,
28 | } from "@components/ui/select";
29 | import { Button } from "@components/ui/button";
30 | import { Card } from "@components/ui/card";
31 | import { ArrowLeft, Loader2 } from "lucide-react";
32 | import { toast } from "sonner";
33 | import type { Profile } from "@types/app";
34 |
35 | const ROLE_OPTIONS = [
36 |   { label: "Admin", value: "admin" },
37 |   { label: "Coordinator", value: "coordinator" },
38 |   { label: "Teacher", value: "teacher" },
39 |   { label: "Student", value: "student" },

```


[illegible]

```

144 |   onSubmit: (data: T) => void;
145 |   isPending: boolean;
146 |   isEditMode: boolean;
147 |   existingEmail?: string;
148 | }
149 |
150 | const UserFormFields = <T extends CreateUserFormData | UpdateUserFormData>({
151 |   form,
152 |   onSubmit,
153 |   isPending,
154 |   isEditMode,
155 |   existingEmail,
156 | }): UserFormFieldsProps<T> => {
157 |   const navigate = useNavigate();
158 |
159 |   return (
160 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
161 |       <Form {...form}>
162 |         <form
163 |           onSubmit={form.handleSubmit(
164 |             onSubmit as Parameters<typeof form.handleSubmit>[0]
165 |           )}
166 |           className="space-y-6"
167 |         >
168 |           <FormField
169 |             control={form.control}
170 |             name={"full_name" as never}
171 |             render={({ field }) => (
172 |               <FormItem>
173 |                 <FormLabel>Full Name</FormLabel>
174 |                 <FormControl>
175 |                   <Input placeholder="Enter full name" {...field} />
176 |                 </FormControl>
177 |                 <FormMessage />
178 |               </FormItem>
179 |             )}
180 |           />
181 |
182 |           {isEditMode ? (
183 |             <div className="grid gap-2">
184 |               <label htmlFor="email-readonly" className="text-sm font-medium">
185 |                 Email
186 |               </label>
187 |               <Input
188 |                 id="email-readonly"
189 |                 type="email"
190 |                 value={existingEmail ?? ""}
191 |                 disabled
192 |                 className="bg-gray-50"
193 |               />
194 |               <p className="text-sm text-muted-foreground">
195 |                 Email cannot be changed after creation.
196 |               </p>
197 |             </div>
198 |           ) : (
199 |             <FormField
200 |               control={form.control}
201 |               name={"email" as never}
202 |               render={({ field }) => (
203 |                 <FormItem>
204 |                   <FormLabel>Email</FormLabel>
205 |                   <FormControl>
206 |                     <Input
207 |                       type="email"
208 |                       placeholder="user@institution.edu"
209 |                       {...field}
210 |                     />
211 |                   </FormControl>
212 |                   <FormMessage />
213 |                 </FormItem>
214 |               )}
215 |             />
216 |           )}
217 |
218 |           <FormField
219 |             control={form.control}
220 |             name={"role" as never}
221 |             render={({ field }) => (
222 |               <FormItem>
223 |                 <FormLabel>Role</FormLabel>
224 |                 <Select
225 |                   onChange={field.onChange}
226 |                   value={field.value as string}
227 |                 >
228 |                   <FormControl>
229 |                     <SelectTrigger className="bg-white">
230 |                       <SelectValue placeholder="Select a role" />
231 |                     </SelectTrigger>
232 |                   </FormControl>
233 |                   <SelectContent>
234 |                     {ROLE_OPTIONS.map((option) => (
235 |                       <SelectItem key={option.value} value={option.value}>
236 |                         {option.label}
237 |                       </SelectItem>
238 |                     ))}
239 |                   </SelectContent>
240 |                 </Select>
241 |                 <FormMessage />
242 |               </FormItem>
243 |             )}
244 |           />
245 |
246 |           <div className="flex items-center gap-3 pt-2">
247 |             <Button type="submit" disabled={isPending} variant="tactile">

```

[illegible]

FILE: src/pages/admin/users/UserListPage.tsx

```
TYPE: .tsx | LINES: 1-162 | SHA256: b4ecc3d67bcae42a60e37188c92a9c435681b3fffbcca2e2590b64bbd51a6a915
```

```

1 import { useState } from "react";
2 import { useNavigate } from "react-router-dom";
3 import { parseAsString, useQueryState } from "nuqs";
4 import { toast } from "sonner";
5 import { createColumns } from "../columns";
6 import { DataTable } from "@components/shared/DataTable";
7 import { NoUsers } from "@components/shared/EmptyState";
8 import { ConfirmDialog } from "@components/shared/ConfirmDialog";
9 import { useUsers, useSoftDeleteUser } from "@hooks/useUsers";
10 import { Button } from "@components/ui/button";
11 import { Input } from "@components/ui/input";
12 import { Plus, Search, Filter, Upload } from "lucide-react";
13 import {
14   DropdownMenu,
15   DropdownMenuContent,
16   DropdownMenuItem,
17   DropdownMenuTrigger,
18 } from "@components/ui/dropdown-menu";
19 import type { Profile } from "@types/app";
20
21 const ROLE_OPTIONS: Array<{ label: string; value: string }> = [
22   { label: "All Roles", value: "" },
23   { label: "Admin", value: "admin" },
24   { label: "Coordinator", value: "coordinator" },
25   { label: "Teacher", value: "teacher" },
26   { label: "Student", value: "student" },
27   { label: "Parent", value: "parent" },
28 ];
29
30 const UserListPage = () => {
31   const navigate = useNavigate();
32   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
33   const [role, setRole] = useQueryState("role", parseAsString.withDefault(""));
34   const [userToDeactivate, setUserToDeactivate] = useState<Profile | null>(
35     null
36   );
37
38   const [page, setPage] = useState(1);
39
40   const {
41     data: paginatedData,
42     isLoading,
43     isFetching,
44   } = useUsers({
45     search: search || undefined,
46     role: role || undefined,
47     page,
48   });

```

```

49 |
50 | const softDeleteMutation = useSoftDeleteUser();
51 |
52 | const columns = createColumns(
53 |   (id) => navigate(`/admin/users/${id}/edit`),
54 |   (user) => setUserToDeactivate(user)
55 | );
56 |
57 | const activeRoleLabel =
58 |   ROLE_OPTIONS.find((o) => o.value === role)?.label ?? "All Roles";
59 |
60 | return (
61 |   <div className="space-y-6">
62 |     {/* Page Header */}
63 |     <div className="flex items-center justify-between">
64 |       <h1 className="text-2xl font-bold tracking-tight">Users</h1>
65 |       <div className="flex items-center gap-2">
66 |         <Button
67 |           variant="outline"
68 |           onClick={() => navigate("/admin/users/import")}
69 |         >
70 |           <Upload className="h-4 w-4" /> Import CSV
71 |         </Button>
72 |         <Button
73 |           variant="tactile"
74 |           onClick={() => navigate("/admin/users/new")}
75 |           data-tour="primary-action"
76 |         >
77 |           <Plus className="h-4 w-4" /> Add User
78 |         </Button>
79 |       </div>
80 |     </div>
81 |
82 |     {/* Filters */}
83 |     <div className="flex items-center gap-4">
84 |       <div className="relative flex-1 max-w-sm">
85 |         <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
86 |         <Input
87 |           placeholder="Search by name or email..."
88 |           value={search}
89 |           onChange={(e) => {
90 |             setSearch(e.target.value || null);
91 |             setPage(1);
92 |           }}
93 |           className="ps-9"
94 |         />
95 |       </div>
96 |
97 |       <DropdownMenu>
98 |         <DropdownMenuTrigger asChild>
99 |           <Button variant="outline" size="sm">
100 |             <Filter className="h-4 w-4" />
101 |             {activeRoleLabel}
102 |           </Button>
103 |         </DropdownMenuTrigger>
104 |         <DropdownMenuContent align="start">
105 |           {ROLE_OPTIONS.map((option) => (
106 |             <DropdownMenuItem
107 |               key={option.value}
108 |               onClick={() => {
109 |                 setRole(option.value || null);
110 |                 setPage(1);
111 |               }}
112 |             >
113 |               {option.label}
114 |             </DropdownMenuItem>
115 |           ))}
116 |         </DropdownMenuContent>
117 |       </DropdownMenu>
118 |     </div>
119 |
120 |     {/* Data Table */}
121 |     <DataTable
122 |       columns={columns}
123 |       data={paginatedData?.data ?? []}
124 |       isLoading={isLoading}
125 |       isFetching={isFetching}
126 |       page={page}
127 |       pageSize={paginatedData?.pageSize}
128 |       totalCount={paginatedData?.count}
129 |       onPageChange={setPage}
130 |       emptyState={<NoUsers />}
131 |     />
132 |
133 |     {/* Deactivate Confirmation Dialog */}
134 |     <ConfirmDialog
135 |       open={!userToDeactivate}
136 |       onOpenChange={() => setUserToDeactivate(null)}
137 |       title="Deactivate User"
138 |       description={`Are you sure you want to deactivate ${userToDeactivate?.full_name}? They will lose acces`
139 |       variant="destructive"
140 |       confirmLabel="Deactivate"
141 |       isPending={softDeleteMutation.isPending}
142 |       onConfirm={() => {
143 |         if (!userToDeactivate) return;
144 |         softDeleteMutation.mutate(userToDeactivate.id, {
145 |           onSuccess: () => {
146 |             toast.success(
147 |               `${userToDeactivate.full_name} has been deactivated`
148 |             );
149 |             setUserToDeactivate(null);
150 |           },
151 |           onError: (err) => {
152 |             toast.error(err.message);

```

```

153 |         },
154 |     });
155 | }
156 | />
157 | </div>
158 | );
159 | };
160 |
161 | export default UserListPage;
162 |

```

FILE: src/pages/auth/AcceptInvitePage.tsx

TYPE: .tsx | LINES: 1-370 | SHA256: aad4acb15e33afd0b9c8ea579c148ded1d5d9daacb5d0b101ae200d258db9c99

```

1 | import { useEffect, useState } from "react";
2 | import { useParams, useNavigate } from "react-router-dom";
3 | import { useForm } from "react-hook-form";
4 | import { zodResolver } from "@hookform/resolvers/zod";
5 | import { useTranslation } from "react-i18next";
6 | import { z } from "zod";
7 | import { supabase } from "@lib/supabase";
8 | import { useAuth } from "@hooks/useAuth";
9 | import { Button } from "@design-system";
10 | import { Alert, AlertDescription } from "@components/ui/alert";
11 | import {
12 |   Form,
13 |   FormControl,
14 |   FormField,
15 |   FormItem,
16 |   FormLabel,
17 |   FormMessage,
18 | } from "@components/ui/form";
19 | import { Loader2, Mail, User, Building2, AlertTriangle } from "lucide-react";
20 | import { toast } from "sonner";
21 | import AuthShell from "@components/shared/AuthShell";
22 |
23 | interface InvitationData {
24 |   id: string;
25 |   email: string;
26 |   role: string;
27 |   institution_id: string;
28 |   institution_name?: string;
29 | }
30 |
31 | const acceptInviteSchema = z
32 |   .object({
33 |     password: z
34 |       .string()
35 |       .min(8, "Password must be at least 8 characters")
36 |       .regex(/[A-Z]/, "Password must contain at least one uppercase letter")
37 |       .regex(/[a-z]/, "Password must contain at least one lowercase letter")
38 |       .regex(/[0-9]/, "Password must contain at least one number"),
39 |     confirmPassword: z.string().min(1, "Please confirm your password"),
40 |     fullName: z
41 |       .string()
42 |       .min(2, "Full name must be at least 2 characters")
43 |       .max(100, "Full name must be less than 100 characters"),
44 |   })
45 |   .refine((data) => data.password === data.confirmPassword, {
46 |     message: "Passwords do not match",
47 |     path: ["confirmPassword"],
48 |   });
49 |
50 | type AcceptInviteFormData = z.infer<typeof acceptInviteSchema>;
51 |
52 | const AcceptInvitePage = () => {
53 |   const { t } = useTranslation("auth");
54 |   const { token } = useParams<{ token: string }>();
55 |   const navigate = useNavigate();
56 |   const { signUp } = useAuth();
57 |
58 |   const [invitation, setInvitation] = useState<InvitationData | null>(null);
59 |   const [isLoading, setIsLoading] = useState(true);
60 |   const [error, setError] = useState<string | null>(null);
61 |   const [isPending, setIsPending] = useState(false);
62 |   const [showPassword, setShowPassword] = useState(false);
63 |   const [showConfirm, setShowConfirm] = useState(false);
64 |
65 |   const form = useForm<AcceptInviteFormData>({
66 |     resolver: zodResolver(acceptInviteSchema),
67 |     defaultValues: {
68 |       password: "",
69 |       confirmPassword: "",
70 |       fullName: "",
71 |     },
72 |   });
73 |
74 |   // Fetch invitation by token on mount
75 |   useEffect(() => {
76 |     const fetchInvitation = async () => {
77 |       if (!token) {
78 |         setError(t("acceptInvite.invalidToken"));
79 |         setIsLoading(false);
80 |         return;
81 |       }
82 |
83 |       try {
84 |         const { data, error: rpcError } = await supabase.rpc(
85 |           "get_invitation_by_token",
86 |           {
87 |             p_token: token,
88 |           }
89 |         );
90 |

```

```

91 |         if (rpcError || !data) {
92 |             setError(t("acceptInvite.tokenExpiredOrInvalid"));
93 |             setIsLoading(false);
94 |             return;
95 |         }
96 |
97 |         // The RPC returns an array; take the first element
98 |         const inviteRow = Array.isArray(data) ? data[0] : data;
99 |         if (!inviteRow) {
100 |             setError(t("acceptInvite.tokenExpiredOrInvalid"));
101 |             setIsLoading(false);
102 |             return;
103 |         }
104 |
105 |         // Fetch institution name for display
106 |         const { data: institution } = await supabase
107 |             .from("institutions")
108 |             .select("name")
109 |             .eq("id", String(inviteRow.institution_id))
110 |             .maybeSingle();
111 |
112 |         setInvitation({
113 |             id: String(inviteRow.id),
114 |             email: String(inviteRow.email),
115 |             role: String(inviteRow.role),
116 |             institution_id: String(inviteRow.institution_id),
117 |             institution_name: institution?.name,
118 |         });
119 |     } catch (err) {
120 |         console.error("Error fetching invitation:", err);
121 |         setError(t("acceptInvite.fetchError"));
122 |     } finally {
123 |         setIsLoading(false);
124 |     }
125 | };
126 |
127 | fetchInvitation();
128 | }, [token, t]);
129 |
130 | const onSubmit = async (formData: AcceptInviteFormData) => {
131 |     if (!invitation) {
132 |         setError(t("acceptInvite.noInvitation"));
133 |         return;
134 |     }
135 |
136 |     setError(null);
137 |     setIsPending(true);
138 |
139 |     try {
140 |         // Sign up with the invited role
141 |         const result = await signUp({
142 |             email: invitation.email,
143 |             password: formData.password,
144 |             fullName: formData.fullName,
145 |             institutionId: invitation.institution_id,
146 |             requestedRole: invitation.role as
147 |                 | "admin"
148 |                 | "coordinator"
149 |                 | "teacher"
150 |                 | "student"
151 |                 | "parent",
152 |         });
153 |
154 |         if (!result.success) {
155 |             setError(result.error ?? t("acceptInvite.signupError"));
156 |             return;
157 |         }
158 |
159 |         // Mark invitation as used
160 |         try {
161 |             await supabase.rpc("consume_invitation", { p_token: token || "" });
162 |         } catch (err) {
163 |             console.error("Error consuming invitation:", err);
164 |             // Don't fail the flow if consumption fails
165 |         }
166 |
167 |         toast.success(t("acceptInvite.successMessage"));
168 |
169 |         if (result.requiresVerification) {
170 |             navigate("/login");
171 |             return;
172 |         }
173 |
174 |         if (result.redirectTo) {
175 |             navigate(result.redirectTo, { replace: true });
176 |         }
177 |     } catch (err) {
178 |         console.error("Accept invite error:", err);
179 |         setError(t("acceptInvite.genericError"));
180 |     } finally {
181 |         setIsPending(false);
182 |     }
183 | };
184 |
185 | return (
186 |     <AuthShell>
187 |         <div className="mb-5">
188 |             <h1 className="text-lg font-black tracking-tight text-slate-900">
189 |                 {t("acceptInvite.title")}
190 |             </h1>
191 |             <p className="mt-1 text-sm text-slate-500">
192 |                 {t("acceptInvite.subtitle")}
193 |             </p>
194 |         </div>

```

```

195 |
196 | {isLoading ? (
197 |   <div className="flex items-center justify-center py-12">
198 |     <Loader2 className="h-6 w-6 animate-spin text-blue-600" />
199 |   </div>
200 | ) : error ? (
201 |   <Alert
202 |     variant="destructive"
203 |     className="rounded-xl border-red-200 bg-red-50 text-red-800"
204 |   >
205 |     <AlertTriangle className="h-4 w-4" />
206 |     <AlertDescription>{error}</AlertDescription>
207 |   </Alert>
208 | ) : invitation ? (
209 |   <Form {...form}>
210 |     <form
211 |       onSubmit={form.handleSubmit(onSubmit)}
212 |       className="space-y-4"
213 |       noValidate
214 |     >
215 |       {/* Invitation details */}
216 |       <div className="space-y-3 rounded-xl border border-blue-200 bg-blue-50 p-4">
217 |         <div className="flex items-center gap-2">
218 |           <Mail className="h-4 w-4 text-blue-600" />
219 |           <div>
220 |             <p className="text-xs font-medium text-blue-600">
221 |               {t("acceptInvite.email")}
222 |             </p>
223 |             <p className="text-sm font-semibold text-blue-900">
224 |               {invitation.email}
225 |             </p>
226 |           </div>
227 |         </div>
228 |         <div className="flex items-center gap-2">
229 |           <Building2 className="h-4 w-4 text-blue-600" />
230 |           <div>
231 |             <p className="text-xs font-medium text-blue-600">
232 |               {t("acceptInvite.institution")}
233 |             </p>
234 |             <p className="text-sm font-semibold text-blue-900">
235 |               {invitation.institution_name || "Loading..."}
236 |             </p>
237 |           </div>
238 |         </div>
239 |         <div className="flex items-center gap-2">
240 |           <User className="h-4 w-4 text-blue-600" />
241 |           <div>
242 |             <p className="text-xs font-medium text-blue-600">
243 |               {t("acceptInvite.role")}
244 |             </p>
245 |             <p className="text-sm font-semibold capitalize text-blue-900">
246 |               {t(`roles.${invitation.role}`)}
247 |             </p>
248 |           </div>
249 |         </div>
250 |       </div>
251 |
252 |       {/* Full Name */}
253 |       <FormField
254 |         control={form.control}
255 |         name="fullName"
256 |         render={({ field }) => (
257 |           <FormItem>
258 |             <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
259 |               {t("acceptInvite.fullName")}
260 |             </FormLabel>
261 |             <FormControl>
262 |               <input
263 |                 className="fld"
264 |                 placeholder={t("acceptInvite.fullNamePlaceholder")}
265 |                 {...field}
266 |               />
267 |             </FormControl>
268 |             <FormMessage />
269 |           </FormItem>
270 |         )}
271 |       />
272 |
273 |       {/* Password */}
274 |       <FormField
275 |         control={form.control}
276 |         name="password"
277 |         render={({ field }) => (
278 |           <FormItem>
279 |             <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
280 |               {t("acceptInvite.password")}
281 |             </FormLabel>
282 |             <FormControl>
283 |               <div className="relative">
284 |                 <input
285 |                   type={showPassword ? "text" : "password"}
286 |                   autoComplete="new-password"
287 |                   className="fld pe-12"
288 |                   placeholder={t("acceptInvite.passwordPlaceholder")}
289 |                   {...field}
290 |                 />
291 |                 <button
292 |                   type="button"
293 |                   onClick={() => setShowPassword((v) => !v)}
294 |                   className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov"
295 |                 >
296 |                   {showPassword ? t("password.hide") : t("password.show")}
297 |                 </button>
298 |               </div>

```

```

299 |         </FormControl>
300 |         <FormMessage />
301 |       </FormItem>
302 |     )}
303 |   />
304 |
305 |   { /* Confirm Password */ }
306 |   <FormField
307 |     control={form.control}
308 |     name="confirmPassword"
309 |     render={({ field }) => (
310 |       <FormItem>
311 |         <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
312 |           {t("acceptInvite.confirmPassword")}
313 |         </FormLabel>
314 |         <FormControl>
315 |           <div className="relative">
316 |             <input
317 |               type={showConfirm ? "text" : "password"}
318 |               autoComplete="new-password"
319 |               className="fld pe-12"
320 |               placeholder={t(
321 |                 "acceptInvite.confirmPasswordPlaceholder"
322 |               )}
323 |             {...field}
324 |           />
325 |           <button
326 |             type="button"
327 |             onClick={() => setShowConfirm((v) => !v)}
328 |             className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov
329 |           >
330 |             {showConfirm ? t("password.hide") : t("password.show")}
331 |           </button>
332 |         </div>
333 |       </FormControl>
334 |       <FormMessage />
335 |     </FormItem>
336 |   )}
337 | />
338 |
339 |   <Button
340 |     type="submit"
341 |     variant="tactile"
342 |     className="mt-4 h-11 w-full"
343 |     disabled={isPending}
344 |   >
345 |     {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
346 |     {t("acceptInvite.acceptButton")}
347 |   </Button>
348 | </form>
349 | </Form>
350 | ) : null}
351 |
352 | { /* Back to login link */ }
353 | { !isLoading && (
354 |   <p className="mt-5 text-center text-sm text-slate-500">
355 |     {t("acceptInvite.haveAccount")} {" "}
356 |     <button
357 |       type="button"
358 |       onClick={() => navigate("/login")}
359 |       className="font-bold text-blue-600 hover:underline"
360 |     >
361 |       {t("acceptInvite.signIn")}
362 |     </button>
363 |   </p>
364 | )}
365 | </AuthShell>
366 | );
367 | };
368 |
369 | export default AcceptInvitePage;
370 |

```

FILE: [src/pages/auth/SignUpPage.tsx](#)

TYPE: .tsx | LINES: 1-414 | SHA256: 280ea97f06ea8048ce6b3907f21b81cf3c5dbae6883fd61f548090984f4dd40b

```

1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useTranslation } from "react-i18next";
5 | import { useNavigate } from "react-router-dom";
6 | import { signUpSchema, type SignUpFormData } from "@lib/schemas/signUpSchema";
7 | import { useAuth } from "@hooks/useAuth";
8 | import { useInstitutionBrowse } from "@hooks/useInstitutionBrowse";
9 | import { Button } from "@design-system";
10 | import { Alert, AlertDescription } from "@components/ui/alert";
11 | import {
12 |   Select,
13 |   SelectContent,
14 |   SelectItem,
15 |   SelectTrigger,
16 |   SelectValue,
17 | } from "@components/ui/select";
18 | import {
19 |   Form,
20 |   FormControl,
21 |   FormField,
22 |   FormItem,
23 |   FormLabel,
24 |   FormMessage,
25 | } from "@components/ui/form";
26 | import { Loader2 } from "lucide-react";
27 | import { toast } from "sonner";
28 | import AuthShell from "@components/shared/AuthShell";

```



```

29 |
30 | type SignUpStep = "institution" | "account";
31 |
32 | const SignUpPage = () => {
33 |   const { t } = useTranslation("auth");
34 |   const navigate = useNavigate();
35 |   const { signUp } = useAuth();
36 |   const { data: institutions, isLoading: institutionsLoading } =
37 |     useInstitutionBrowse();
38 |
39 |   const [step, setStep] = useState<SignUpStep>("institution");
40 |   const [selectedInstitution, setSelectedInstitution] = useState<string | null>(
41 |     null
42 |   );
43 |   const [isPending, setIsPending] = useState(false);
44 |   const [error, setError] = useState<string | null>(null);
45 |   const [showPassword, setShowPassword] = useState(false);
46 |   const [showConfirm, setShowConfirm] = useState(false);
47 |
48 |   const form = useForm<SignUpFormData>({
49 |     resolver: zodResolver(signUpSchema),
50 |     defaultValues: {
51 |       email: "",
52 |       password: "",
53 |       confirmPassword: "",
54 |       fullName: "",
55 |       institutionId: "",
56 |     },
57 |   });
58 |
59 |   // Get the selected institution details
60 |   const currentInstitution = institutions?.find(
61 |     (i) => i.id === selectedInstitution
62 |   );
63 |
64 |   // Determine if signup is allowed based on join_mode
65 |   const canSignUp =
66 |     currentInstitution?.join_mode === "open" ||
67 |     currentInstitution?.join_mode === "domain_restricted";
68 |
69 |   const handleInstitutionSelect = (institutionId: string) => {
70 |     setSelectedInstitution(institutionId);
71 |     form.setValue("institutionId", institutionId);
72 |     setStep("account");
73 |   };
74 |
75 |   const onSubmit = async (data: SignUpFormData) => {
76 |     if (!currentInstitution) {
77 |       setError(t("signup.selectInstitution"));
78 |       return;
79 |     }
80 |
81 |     setError(null);
82 |     setIsPending(true);
83 |
84 |     try {
85 |       const result = await signUp({
86 |         email: data.email,
87 |         password: data.password,
88 |         fullName: data.fullName,
89 |         institutionId: data.institutionId,
90 |         requestedRole: "student",
91 |       });
92 |
93 |       if (!result.success) {
94 |         setError(result.error ?? t("signup.defaultError"));
95 |         return;
96 |       }
97 |
98 |       if (result.requiresVerification) {
99 |         toast.success(t("signup.verificationSent"));
100 |        navigate("/login");
101 |        return;
102 |      }
103 |
104 |      toast.success(t("signup.successMessage"));
105 |      if (result.redirectTo) {
106 |        navigate(result.redirectTo, { replace: true });
107 |      }
108 |    } catch (err) {
109 |      setError(t("signup.genericError"));
110 |      console.error("Signup error:", err);
111 |    } finally {
112 |      setIsPending(false);
113 |    }
114 |  };
115 |
116 |   return (
117 |     <AuthShell>
118 |       { /* Header */ }
119 |       <div className="mb-5">
120 |         <h1 className="text-lg font-black tracking-tight text-slate-900">
121 |           {step === "institution"
122 |             ? t("signup.chooseInstitution")
123 |             : t("signup.createAccount")}
124 |         </h1>
125 |         <p className="mt-1 text-sm text-slate-500">
126 |           {step === "institution"
127 |             ? t("signup.institutionSubtitle")
128 |             : t("signup.accountSubtitle")}
129 |         </p>
130 |       </div>
131 |
132 |       { /* Step 1: Institution Selection */ }

```

```

133 | {step === "institution" && (
134 |   <div className="space-y-4">
135 |     {institutionsLoading ? (
136 |       <div className="flex items-center justify-center py-8">
137 |         <Loader2 className="h-5 w-5 animate-spin text-blue-600" />
138 |       </div>
139 |     ) : institutions && institutions.length > 0 ? (
140 |       <div className="space-y-2">
141 |         <label className="mb-1.5 block text-xs font-bold text-slate-600">
142 |           {t("signup.selectInstitution")}
143 |         </label>
144 |         <Select
145 |           value={selectedInstitution || ""}
146 |           onChange={handleInstitutionSelect}
147 |         >
148 |           <SelectTrigger className="h-11 rounded-xl border-slate-200">
149 |             <SelectValue placeholder={t("signup.selectInstitution")} />
150 |           </SelectTrigger>
151 |           <SelectContent>
152 |             {institutions.map((institution) => (
153 |               <SelectItem key={institution.id} value={institution.id}>
154 |                 <div className="flex items-center gap-2">
155 |                   {institution.logo_url && (
156 |                     <img
157 |                       src={institution.logo_url}
158 |                       alt={institution.name}
159 |                       className="h-4 w-4 object-contain"
160 |                     />
161 |                   )}
162 |                   <span>{institution.name}</span>
163 |                 </div>
164 |               </SelectItem>
165 |             ))}
166 |           </SelectContent>
167 |         </Select>
168 |       </div>
169 |     ) : (
170 |       <Alert variant="destructive">
171 |         <AlertDescription>
172 |           {t("signup.noInstitutionsAvailable")}
173 |         </AlertDescription>
174 |       </Alert>
175 |     )}
176 |
177 |     {/* Join mode info */}
178 |     {currentInstitution && (
179 |       <Alert className="border-blue-200 bg-blue-50 text-blue-800">
180 |         <AlertDescription>
181 |           {currentInstitution.join_mode === "open" &&
182 |             t("signup.joinModeOpen")}
183 |           {currentInstitution.join_mode === "invite_only" &&
184 |             t("signup.joinModeInviteOnly")}
185 |           {currentInstitution.join_mode === "domain_restricted" &&
186 |             t("signup.joinModeDomainRestricted", { domains: "" })}
187 |         </AlertDescription>
188 |       </Alert>
189 |     )}
190 |
191 |     {/* Invite-only warning */}
192 |     {currentInstitution?.join_mode === "invite_only" && (
193 |       <Alert variant="destructive">
194 |         <AlertDescription>
195 |           {t("signup.inviteOnlyWarning")}
196 |         </AlertDescription>
197 |       </Alert>
198 |     )}
199 |
200 |     {/* Action buttons */}
201 |     <div className="flex gap-3 pt-2">
202 |       <Button
203 |         type="button"
204 |         variant="outline"
205 |         className="h-11 flex-1 rounded-xl"
206 |         onClick={() => navigate("/login")}
207 |       >
208 |         {t("signup.backToLogin")}
209 |       </Button>
210 |       <Button
211 |         type="button"
212 |         variant="tactile"
213 |         className="h-11 flex-1"
214 |         disabled={!canSignUp || !currentInstitution}
215 |       >
216 |         {t("signup.continue")}
217 |       </Button>
218 |     </div>
219 |   </div>
220 | )}
221 |
222 |   {/* Step 2: Account Form */}
223 |   {step === "account" && currentInstitution && (
224 |     <Form {...form}>
225 |       <Form
226 |         onSubmit={form.handleSubmit(onSubmit)}
227 |         className="space-y-4"
228 |         noValidate
229 |       >
230 |         {/* Institution display */}
231 |         <div className="flex items-center gap-2 rounded-xl border border-blue-200 bg-blue-50 p-3">
232 |           {currentInstitution.logo_url && (
233 |             <img
234 |               src={currentInstitution.logo_url}
235 |               alt={currentInstitution.name}
236 |               className="h-5 w-5 object-contain"

```

```

237 |         />
238 |     })
239 |     <span className="text-sm font-medium text-blue-900">
240 |         {currentInstitution.name}
241 |     </span>
242 | </div>
243 |
244 | {/* Full Name */}
245 | <FormField
246 |   control={form.control}
247 |   name="fullName"
248 |   render={({ field }) => (
249 |     <FormItem>
250 |       <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
251 |         {t("signup.fullName")}
252 |       </FormLabel>
253 |       <FormControl>
254 |         <input
255 |           className="fld"
256 |           placeholder={t("signup.fullNamePlaceholder")}
257 |           {...field}
258 |         />
259 |       </FormControl>
260 |       <FormMessage />
261 |     </FormItem>
262 |   )}
263 | />
264 |
265 | {/* Email */}
266 | <FormField
267 |   control={form.control}
268 |   name="email"
269 |   render={({ field }) => (
270 |     <FormItem>
271 |       <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
272 |         {t("signup.email")}
273 |       </FormLabel>
274 |       <FormControl>
275 |         <input
276 |           type="email"
277 |           className="fld"
278 |           placeholder={t("signup.emailPlaceholder")}
279 |           {...field}
280 |         />
281 |       </FormControl>
282 |       <FormMessage />
283 |     </FormItem>
284 |   )}
285 | />
286 |
287 | {/* Password */}
288 | <FormField
289 |   control={form.control}
290 |   name="password"
291 |   render={({ field }) => (
292 |     <FormItem>
293 |       <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
294 |         {t("signup.password")}
295 |       </FormLabel>
296 |       <FormControl>
297 |         <div className="relative">
298 |           <input
299 |             type={showPassword ? "text" : "password"}
300 |             autoComplete="new-password"
301 |             className="fld pe-12"
302 |             placeholder={t("signup.passwordPlaceholder")}
303 |             {...field}
304 |           />
305 |           <button
306 |             type="button"
307 |             onClick={() => setShowPassword((v) => !v)}
308 |             className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov"
309 |           >
310 |             {showPassword ? t("password.hide") : t("password.show")}
311 |           </button>
312 |         </div>
313 |       </FormControl>
314 |       <FormMessage />
315 |     </FormItem>
316 |   )}
317 | />
318 |
319 | {/* Confirm Password */}
320 | <FormField
321 |   control={form.control}
322 |   name="confirmPassword"
323 |   render={({ field }) => (
324 |     <FormItem>
325 |       <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
326 |         {t("signup.confirmPassword")}
327 |       </FormLabel>
328 |       <FormControl>
329 |         <div className="relative">
330 |           <input
331 |             type={showConfirm ? "text" : "password"}
332 |             autoComplete="new-password"
333 |             className="fld pe-12"
334 |             placeholder={t("signup.confirmPasswordPlaceholder")}
335 |             {...field}
336 |           />
337 |           <button
338 |             type="button"
339 |             onClick={() => setShowConfirm((v) => !v)}
340 |             className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov

```

```

341 |         >
342 |         {showConfirm ? t("password.hide") : t("password.show")}
343 |       </button>
344 |     </div>
345 |   </FormControl>
346 |   <FormMessage />
347 | </FormItem>
348 | }}
349 | />
350 |
351 | /* Email verification info for open mode */
352 | {currentInstitution.join_mode === "open" && (
353 |   <Alert className="border-amber-200 bg-amber-50 text-amber-800">
354 |     <AlertDescription className="text-sm">
355 |       {t("signup.emailVerificationRequired")}
356 |     </AlertDescription>
357 |   </Alert>
358 | )}
359 |
360 | /* Action buttons */
361 | <div className="flex gap-3 pt-2">
362 |   <Button
363 |     type="button"
364 |     variant="outline"
365 |     className="h-11 flex-1 rounded-xl"
366 |     onClick={() => {
367 |       setStep("institution");
368 |       setSelectedInstitution(null);
369 |       form.reset();
370 |     }}
371 |   >
372 |     {t("signup.back")}
373 |   </Button>
374 |   <Button
375 |     type="submit"
376 |     variant="tactile"
377 |     className="h-11 flex-1"
378 |     disabled={isPending}
379 |   >
380 |     {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
381 |     {t("signup.createAccount")}
382 |   </Button>
383 | </div>
384 | </form>
385 | </Form>
386 | )}
387 |
388 | /* Error message */
389 | {error && (
390 |   <Alert
391 |     variant="destructive"
392 |     className="mt-4 rounded-xl border-red-200 bg-red-50 text-red-800"
393 |   >
394 |     <AlertDescription>{error}</AlertDescription>
395 |   </Alert>
396 | )}
397 |
398 | /* Back to login link */
399 | <p className="mt-5 text-center text-sm text-slate-500">
400 |   {t("signup.haveAccount")}{t(" ")}
401 |   <button
402 |     type="button"
403 |     onClick={() => navigate("/login")}
404 |     className="font-bold text-blue-600 hover:underline"
405 |   >
406 |     {t("signup.signIn")}
407 |   </button>
408 | </p>
409 | </AuthShell>
410 | );
411 | };
412 |
413 | export default SignUpPage;
414 |

```

FILE: [src/pages/coordinator/cohort-comparison/CohortComparisonView.tsx](#)

TYPE: .tsx | LINES: 1-50 | SHA256: 670ebdd6324ab5105cf177894890b8099bfc0fed4c8faddf0ec3c8fb278865ae

```

1 | // Coordinator analytics – Cohort Comparison (planned feature).
2 | // Intentionally not wired to data yet: it requires cohort aggregation that
3 | // doesn't exist. Labelled "Coming soon" (Req 15.4) and removed from the
4 | // coordinator nav so it doesn't read as a broken/empty page.
5 |
6 | import { Card } from "@components/ui/card";
7 | import { Badge } from "@components/ui/badge";
8 | import { BarChart3, Users } from "lucide-react";
9 |
10 | const CohortComparisonView = () => {
11 |   return (
12 |     <div className="space-y-6">
13 |       <div className="flex items-center gap-3">
14 |         <h1 className="text-2xl font-bold tracking-tight">Cohort Comparison</h1>
15 |         <Badge variant="outline" className="text-xs">
16 |           Coming soon
17 |         </Badge>
18 |       </div>
19 |
20 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
21 |         <div
22 |           className="px-6 py-4 flex items-center gap-2"
23 |           style={{
24 |             background: "var(--brand-gradient)",
25 |           }}
26 |         >

```

```

27 |         <BarChart3 className="h-5 w-5 text-white" />
28 |         <h2 className="text-lg font-bold tracking-tight text-white">
29 |             Compare Cohorts
30 |         </h2>
31 |     </div>
32 |     <div className="p-6">
33 |         <div className="flex flex-col items-center justify-center py-12 text-center">
34 |             <Users className="h-12 w-12 text-slate-300 mb-3" />
35 |             <h3 className="text-lg font-semibold tracking-tight text-gray-900">
36 |                 Coming soon
37 |             </h3>
38 |             <p className="mt-1.5 text-sm text-slate-500 max-w-sm">
39 |                 Compare attainment across cohorts (by semester, section, or
40 |                 enrollment year) here once cohort aggregation is available.
41 |             </p>
42 |         </div>
43 |     </div>
44 | </Card>
45 | </div>
46 | );
47 | };
48 |
49 | export default CohortComparisonView;
50 |

```

FILE: src/pages/coordinator/CoordinatorDashboard.tsx

TYPE: .tsx | LINES: 1-12 | SHA256: d8a27a4e657ebe7d3e33e5e1e78c6dbfd7885eff3b2e5feab05991384e103824

```

1 | // =====
2 | // CoordinatorDashboard – production coordinator dashboard (prototype rebuild)
3 | // =====
4 | // Implementation lives in the prototype-rebuilt `CoordinatorDashboardScreen`
5 | // (src/features/coordinator/dashboard), re-exported here so the route path
6 | // (`@/pages/coordinator/CoordinatorDashboard`) and its guard stay stable. The
7 | // legacy `CoordinatorDashboardNew` reskin was replaced in the
8 | // prototype-frontend-rebuild (P2.4) cutover.
9 | // =====
10 |
11 | export { default } from "@features/coordinator/dashboard/CoordinatorDashboardScreen";
12 |

```

FILE: src/pages/coordinator/CoordinatorLayout.tsx

TYPE: .tsx | LINES: 1-14 | SHA256: 2684b83e324e2c9f6541158324a374891b5d4a9696bb15841b6e70b0327db733

```

1 | import { Outlet } from "react-router-dom";
2 | import RoleAppShell from "@app/RoleAppShell";
3 | import CoordinatorDashboardRail from "@features/coordinator/dashboard/CoordinatorDashboardRail";
4 |
5 | const CoordinatorLayout = () => {
6 |     return (
7 |         <RoleAppShell userRole="coordinator" rail={<CoordinatorDashboardRail />}>
8 |             <Outlet />
9 |         </RoleAppShell>
10 |     );
11 | };
12 |
13 | export default CoordinatorLayout;
14 |

```

FILE: src/pages/coordinator/course-file/CoordinatorAccreditationNew.tsx

TYPE: .tsx | LINES: 1-665 | SHA256: 6edcf01b360bc5ad5d2c370dab60df070abca566abfcd6503ffcf36b9580ffde

```

1 | // =====
2 | // CoordinatorAccreditationNew – redesigned Accreditation Evidence (P3, task 3.3)
3 | // =====
4 | //
5 | // Matches the prototype reference: an Accreditation Readiness hero (overall ring
6 | // + Complete/In-progress/Blocked/Not-started tiles), course evidence status
7 | // cards, an Accreditation Pack checklist, an Approval Workflow timeline
8 | // (Coordinator !' HOD !' QA !' Accreditation Office), and the REAL "Generate
9 | // Course File" tool (preserves the legacy page's function).
10 | //
11 | // DATA (Phase C backend wiring):
12 | // • Readiness hero + tiles + course evidence cards + pack checklist !' REAL,
13 | //   from get_coordinator_accreditation_readiness (evidence-coverage derived
14 | //   from courses/outcomes/evidence/attainment/cqi). Fails soft to a neutral
15 | //   "pending" state if the RPC isn't deployed yet.
16 | // • Approval workflow !' accreditation_approvals (renders the default four
17 | //   stages until the chain has rows).
18 | // • Generate Course File !' REAL (useCourses / useSemesters /
19 | //   useGenerateCourseFile – same mutation as the legacy page).
20 | // No client writes here. Gated behind `newUiModules` (wrapper in
21 | // CourseFileGenerator.tsx); flag-off keeps the legacy generator. RTL-safe.
22 | // =====
23 |
24 | import { useState } from "react";
25 | import type { ComponentType } from "react";
26 | import { useTranslation } from "react-i18next";
27 | import { Link } from "react-router-dom";
28 | import {
29 |     ArrowRight,
30 |     Check,
31 |     CheckCircle2,
32 |     Circle,
33 |     Clock,
34 |     Download,
35 |     FileText,
36 |     Loader2,
37 |     ShieldCheck,
38 |     XCircle,
39 | } from "lucide-react";
40 | import { toast } from "sonner";
41 |

```

```
import {  
    Button,  
    Card,  
    Label,  
    MasteryRing,  
    SectionHeader,  
    Select,  
    SelectContent,  
    SelectItem,  
    SelectTrigger,  
    SelectValue,  
    Shimmer,  
} from "@design-system";  
import { useCourses } from "@/hooks/useCourses";  
import { useSemesters } from "@/hooks/useSemesters";  
import { useGenerateCourseFile } from "@/hooks/useCourseFile";  
import { useAuth } from "@/hooks/useAuth";  
import {  
    useCoordinatorAccreditationReadiness,  
    useAccreditationApprovals,  
    type EvidenceStatus,  
} from "@/hooks/useCoordinatorAccreditation";  
import { cn } from "@lib/utils";  
  
type IconType = ComponentType<{ className?: string }>;  
type EvStatus = "signed" | "draft" | "blocked" | "notStarted";  
type PackState = "done" | "prog" | "pending";  
type WfState = "done" | "current" | "pending";  
  
const EV_STYLES: Record<  
    EvStatus,  
    { pill: string; icon: IconType; tint: string }  
=> {  
    signed: {  
        pill: "bg-green-50 text-green-600",  
        icon: CheckCircle2,  
        tint: "text-green-600",  
    },  
    draft: {  
        pill: "bg-amber-50 text-amber-700",  
        icon: Clock,  
        tint: "text-amber-600",  
    },  
    blocked: {  
        pill: "bg-red-50 text-red-600",  
        icon: XCircle,  
        tint: "text-red-600",  
    },  
    notStarted: {  
        pill: "bg-slate-100 text-slate-500",  
        icon: Circle,  
        tint: "text-slate-400",  
    },  
};  
  
// % Readiness status tile  
const RdTile = ({  
    value,  
    label,  
    tone,  
}) => (  
    <div className="rounded-xl border border-slate-100 p-3 text-center">  
        <p className={cn("text-xl font-black leading-none", tone)}>{value}</p>  
        <p className="mt-1 text-[11px] text-slate-500">{label}</p>  
    </div>  
);  
  
// % Course evidence card  
const EvCard = ({  
    code,  
    name,  
    status,  
    statusLabel,  
}) => {  
    const s = EV_STYLES[status];  
    const Icon = s.icon;  
    return (  
        <div className="rounded-xl border border-slate-100 p-4">  
            <div className="flex items-center justify-between gap-2">  
                <span className="text-xs font-black text-slate-400">{code}</span>  
                <Icon className={cn("h-4 w-4", s.tint)} aria-hidden="true" />  
            </div>  
            <p className="mt-1 truncate text-sm font-bold text-gray-900">{name}</p>  
            <span  
                className={cn(  
                    "mt-2 inline-block rounded-full px-2 py-0.5 text-[10px] font-bold",  
                    s.pill  
                )}  
            >  
                {statusLabel}  
            </span>  
        </div>  
    );  
};
```

[illegible]

```

250 // % % REAL course-file generation (preserves legacy function) % % % % % % % % % %
251 const { data: coursesResult, isLoading: coursesLoading } = useCourses({
252   pageSize: 200,
253 });
254 const { data: semesters, isLoading: semestersLoading } = useSemesters();
255 const generateMutation = useGenerateCourseFile();
256 const [courseId, setCourseId] = useState("");
257 const [semesterId, setSemesterId] = useState("");
258 const [lastResult, setLastResult] = useState<{
259   download_url: string;
260   course_name: string;
261   course_code: string;
262   semester: string;
263   generated_at: string;
264 } | null>(null);
265
266 const courses = coursesResult?.data ?? [];
267 const formLoading = coursesLoading || semestersLoading;
268
269 const handleGenerate = () => {
270   if (!courseId) {
271     toast.error(t("accreditation.selectCourseError"));
272     return;
273   }
274   if (!semesterId) {
275     toast.error(t("accreditation.selectSemesterError"));
276     return;
277   }
278   setLastResult(null);
279   generateMutation.mutate(
280     { course_id: courseId, semester_id: semesterId },
281     {
282       onSuccess: (result) => {
283         setLastResult({
284           download_url: result.download_url,
285           course_name: result.course_name,
286           course_code: result.course_code,
287           semester: result.semester,
288           generated_at: result.generated_at,
289         });
290         toast.success(t("accreditation.generateSuccess"));
291       },
292       onError: (err) => {
293         toast.error(
294           err instanceof Error
295             ? err.message
296             : t("accreditation.generateError")
297         );
298       },
299     }
300   );
301 };
302
303 // % % Derived from real readiness (evidence coverage) % % % % % % % % % %
304 const EV_STATUS_MAP: Record<EvidenceStatus, EvStatus> = {
305   documented: "signed",
306   partial: "draft",
307   blocked: "blocked",
308   not_started: "notStarted",
309 };
310 const courseEvidence = (readiness?.courses ?? []).map((c) => ({
311   code: c.code,
312   name: c.name,
313   status: EV_STATUS_MAP[c.status] ?? "notStarted",
314 }));
315
316 const statusLabel = (s: EvStatus) =>
317   s === "signed"
318     ? t("accreditation.statusDocumented")
319     : s === "draft"
320     ? t("accreditation.statusPartial")
321     : s === "blocked"
322     ? t("accreditation.statusBlocked")
323     : t("accreditation.statusNotStarted");
324
325 const PACK_LABEL: Record<string, string> = {
326   cloMapping: t("accreditation.packCloMapping"),
327   samples: t("accreditation.packSamples"),
328   analysis: t("accreditation.packAnalysis"),
329   cqi: t("accreditation.packCqi"),
330 };
331 const packItems = (readiness?.pack ?? []).map((p) => ({
332   label: PACK_LABEL[p.key] ?? p.key,
333   state: p.state as PackState,
334 }));
335 const packStateLabel = (s: PackState) =>
336   s === "done"
337     ? t("accreditation.packComplete")
338     : s === "prog"
339     ? t("accreditation.packInProgress")
340     : t("accreditation.packOutstanding");
341
342 // % % Approval workflow: default four stages until the chain has rows % % % % % %
343 const CANON_STAGES = ["coordinator", "hod", "qa", "office"] as const;
344 const WF_LABEL: Record<string, string> = {
345   coordinator: t("accreditation.wf1"),
346   hod: t("accreditation.wf2"),
347   qa: t("accreditation.wf3"),
348   office: t("accreditation.wf4"),
349 };
350 const workflow = (() => {
351   const byStage = new Map(
352     (approvalsQuery.data ?? []).map((r) => [r.stage, r.status as WfState])
353   );

```



```

354 |     const states: WfState[] = CANON_STAGES.map(
355 |       (s) => byStage.get(s) ?? "pending"
356 |     );
357 |     // Default: if nothing is in progress or done, the first stage is current.
358 |     if (!states.some((s) => s === "current" || s === "done")) {
359 |       states[0] = "current";
360 |     }
361 |     return CANON_STAGES.map((s, i) => ({
362 |       label: WF_LABEL[s] ?? s,
363 |       state: states[i] ?? "pending",
364 |     }));
365 |   }());
366 |   const wfStateLabel = (s: WfState) =>
367 |     s === "done"
368 |       ? t("accreditation.wfDone")
369 |       : s === "current"
370 |       ? t("accreditation.wfCurrent")
371 |       : t("accreditation.wfPending");
372 |
373 |   return (
374 |     <div className="space-y-6">
375 |       <div className="flex flex-wrap items-center justify-between gap-3">
376 |         <h1 className="text-2xl font-bold tracking-tight">
377 |           {t("accreditation.title")}
378 |         </h1>
379 |         <Link
380 |           to="/coordinator/cqi"
381 |           className="inline-flex items-center gap-1 rounded text-xs font-bold text-sky-700 outline-none hover:
382 |         >
383 |           {t("accreditation.viewCqi")}
384 |           <ArrowRight className="h-3.5 w-3.5" aria-hidden="true" />
385 |         </Link>
386 |       </div>
387 |
388 |       {/* Accreditation Readiness hero */}
389 |       <Card className="card-elevated gap-0 border-0 bg-white py-0">
390 |         <div className="p-6">
391 |           <SectionHeader
392 |             icon={ShieldCheck}
393 |             title={t("accreditation.readiness")}
394 |           />
395 |           {readinessQuery.isPending ? (
396 |             <div className="mt-4">
397 |               <Shimmer className="h-24 rounded-xl" />
398 |             </div>
399 |           ) : readiness ? (
400 |             <div className="mt-4 flex flex-col gap-5 sm:flex-row sm:items-center">
401 |               <div className="flex items-center gap-4">
402 |                 <MasteryRing
403 |                   value={readiness.readinessPercent}
404 |                   size={88}
405 |                   tone="brand"
406 |                 />
407 |                 <div>
408 |                   <p className="text-xs text-slate-500">
409 |                     {t("accreditation.overallReadiness")}
410 |                   </p>
411 |                   <p className="text-2xl font-black text-sky-700">
412 |                     {readiness.readinessPercent}%
413 |                   </p>
414 |                 </div>
415 |               </div>
416 |               <div className="grid flex-1 grid-cols-2 gap-3 sm:grid-cols-4">
417 |                 <RdTile
418 |                   value={readiness.documented}
419 |                   label={t("accreditation.complete")}
420 |                   tone="text-green-600"
421 |                 />
422 |                 <RdTile
423 |                   value={readiness.partial}
424 |                   label={t("accreditation.inProgress")}
425 |                   tone="text-amber-600"
426 |                 />
427 |                 <RdTile
428 |                   value={readiness.blocked}
429 |                   label={t("accreditation.blocked")}
430 |                   tone="text-red-600"
431 |                 />
432 |                 <RdTile
433 |                   value={readiness.notStarted}
434 |                   label={t("accreditation.notStarted")}
435 |                   tone="text-slate-500"
436 |                 />
437 |               </div>
438 |             </div>
439 |           ) : (
440 |             <p className="mt-4 text-sm text-slate-500">
441 |               {t("accreditation.readinessPending")}
442 |             </p>
443 |           )
444 |         </div>
445 |       </Card>
446 |
447 |       {/* Course evidence status cards */}
448 |       <Card className="card-elevated gap-0 border-0 bg-white py-0">
449 |         <div className="p-6">
450 |           <SectionHeader
451 |             icon={FileText}
452 |             title={t("accreditation.courseEvidence")}
453 |           />
454 |           {readinessQuery.isPending ? (
455 |             <div className="mt-4 grid grid-cols-1 gap-4 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-5">
456 |               {Array.from({ length: 5 }).map((_, i) => (
457 |                 <Shimmer key={i} className="h-24 rounded-xl" />

```

```

458     )))
459   </div>
460   ) : courseEvidence.length > 0 ? (
461     <div className="mt-4 grid grid-cols-1 gap-4 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-5">
462       {courseEvidence.map((c) => (
463         <EvCard
464           key={c.code}
465           code={c.code}
466           name={c.name}
467           status={c.status}
468           statusLabel={statusLabel(c.status)}
469         />
470       ))}
471     </div>
472   ) : (
473     <p className="mt-4 text-sm text-slate-500">
474       {t("accreditation.evidenceEmpty")}
475     </p>
476   )}
477 </div>
478 </Card>
479
480 {/* Pack checklist + Approval workflow */}
481 <div className="grid gap-6 lg:grid-cols-2">
482   <Card className="card-elevated gap-0 border-0 bg-white py-0">
483     <div className="p-6">
484       <SectionHeader
485         icon={CheckCircle2}
486         title={t("accreditation.pack")}
487       />
488       {packItems.length > 0 ? (
489         <ul className="mt-3 divide-y divide-slate-100">
490           {packItems.map((item) => (
491             <CheckRow
492               key={item.label}
493               label={item.label}
494               statusLabel={packStatusLabel(item.state)}
495               state={item.state}
496             />
497           ))}
498         </ul>
499       ) : (
500         <p className="mt-3 text-sm text-slate-500">
501           {t("accreditation.packEmpty")}
502         </p>
503       )}
504     </div>
505   </Card>
506
507   <Card className="card-elevated gap-0 border-0 bg-white py-0">
508     <div className="p-6">
509       <SectionHeader
510         icon={ShieldCheck}
511         title={t("accreditation.workflow")}
512       />
513       <ul className="mt-5 flex flex-col gap-4 sm:flex-row sm:items-start">
514         {workflow.map((w, i) => (
515           <WfStep
516             key={w.label}
517             label={w.label}
518             statusLabel={wfStatusLabel(w.state)}
519             state={w.state}
520             last={i === workflow.length - 1}
521           />
522         ))}
523       </ul>
524     </div>
525   </Card>
526 </div>
527
528 {/* Generate Course File (REAL) */}
529 <Card className="card-elevated gap-0 border-0 bg-white py-0">
530   <div className="p-6">
531     <SectionHeader
532       icon={FileText}
533       title={t("accreditation.generateTitle")}
534     />
535     {formLoading ? (
536       <div className="mt-4 space-y-4">
537         <Shimmer className="h-10 rounded-lg" />
538         <Shimmer className="h-10 rounded-lg" />
539       </div>
540     ) : (
541       <div className="mt-4 grid gap-4 sm:grid-cols-2">
542         <div className="space-y-2">
543           <Label htmlFor="acc-course-select">
544             {t("accreditation.course")}
545           </Label>
546           <Select value={courseId} onChange={setCourseId}>
547             <SelectTrigger id="acc-course-select" className="bg-white">
548               <SelectValue
549                 placeholder={t("accreditation.selectCourse")}
550               />
551             </SelectTrigger>
552             <SelectContent>
553               {courses.map((c) => (
554                 <SelectItem key={c.id} value={c.id}>
555                   {c.code} - {c.name}
556                 </SelectItem>
557               ))}
558               {courses.length === 0 && (
559                 <SelectItem value="__none" disabled>
560                   {t("accreditation.noCourses")}
561                 </SelectItem>

```

```

562     })
563     </SelectContent>
564   </Select>
565 </div>
566 <div className="space-y-2">
567   <Label htmlFor="acc-semester-select">
568     {t("accreditation.semester")}
569   </Label>
570   <Select value={semesterId} onChange={setSemesterId}>
571     <SelectTrigger id="acc-semester-select" className="bg-white">
572       <SelectValue
573         placeholder={t("accreditation.selectSemester")}
574       />
575     </SelectTrigger>
576     <SelectContent>
577       {(semesters ?? []).map((s) => (
578         <SelectItem key={s.id} value={s.id}>
579           {s.name}
580         </SelectItem>
581       ))}
582       {(semesters || semesters.length === 0) && (
583         <SelectItem value="__none" disabled>
584           {t("accreditation.noSemesters")}
585         </SelectItem>
586       )}
587     </SelectContent>
588   </Select>
589 </div>
590 </div>
591 )}
592
593 <Button
594   variant="tactile"
595   className="mt-4"
596   onClick={handleGenerate}
597   disabled={generateMutation.isPending || !courseId || !semesterId}
598 >
599   {generateMutation.isPending ? (
600     <Loader2 className="h-4 w-4 animate-spin" aria-hidden="true" />
601   ) : (
602     <FileText className="h-4 w-4" aria-hidden="true" />
603   )}
604   {generateMutation.isPending
605     ? t("accreditation.generating")
606     : t("accreditation.generate")}
607 </Button>
608
609 {lastResult && (
610   <div className="mt-5 rounded-xl border border-green-100 bg-green-50/60 p-4">
611     <div className="flex items-center gap-2">
612       <CheckCircle2
613         className="h-5 w-5 text-green-600"
614         aria-hidden="true"
615       />
616       <p className="text-sm font-bold text-gray-900">
617         {t("accreditation.ready")}
618       </p>
619     </div>
620     <div className="mt-3 grid grid-cols-2 gap-4 text-sm md:grid-cols-3">
621       <div>
622         <p className="text-[10px] font-black uppercase tracking-widest text-gray-500">
623           {t("accreditation.course")}
624         </p>
625         <p className="mt-1 font-semibold">
626           {lastResult.course_code} – {lastResult.course_name}
627         </p>
628       </div>
629       <div>
630         <p className="text-[10px] font-black uppercase tracking-widest text-gray-500">
631           {t("accreditation.semester")}
632         </p>
633         <p className="mt-1 font-semibold">{lastResult.semester}</p>
634       </div>
635       <div>
636         <p className="text-[10px] font-black uppercase tracking-widest text-gray-500">
637           {t("accreditation.generated")}
638         </p>
639         <p className="mt-1 font-semibold">
640           {lastResult.generated_at.slice(0, 10)}
641         </p>
642       </div>
643     </div>
644     <Button
645       variant="tactile"
646       size="sm"
647       className="mt-3"
648       onClick={() =>
649         lastResult.download_url &&
650         window.open(lastResult.download_url, "_blank")
651       }
652     >
653       <Download className="h-4 w-4" aria-hidden="true" />
654       {t("accreditation.downloadPdf")}
655     </Button>
656   </div>
657 )}
658 </div>
659 </Card>
660 </div>
661 );
662 };
663
664 export default CoordinatorAccreditationNew;
665

```

FILE: src/pages/coordinator/course-file/CourseFileGenerator.tsx

TYPE: .tsx | LINES: 1-11 | SHA256: af4ef2232fe80794232fc6fd28421cce239404c39648e989d46d464d0d67065d

```
1 | // =====
2 | // CourseFileGenerator - production course-file / accreditation surface (redesigned UI)
3 | // =====
4 | // The redesigned experience lives in `CoordinatorAccreditationNew`, re-exported
5 | // here so the route path (`.../course-file/CourseFileGenerator`) stays stable.
6 | // The legacy generator and its feature-flag wrapper were removed in the
7 | // UI-migration cleanup.
8 | // =====
9 |
10 | export { default } from "../CoordinatorAccreditationNew";
11 |
```

FILE: src/pages/coordinator/coverage-heatmap/CoverageHeatmapView.tsx

TYPE: .tsx | LINES: 1-193 | SHA256: 9a6c154677737ba7ec9150faa8946acc46f7a882f9645ea0565a0502a46f5861

```
1 | // Task 120.2: Coverage Heatmap View page
2 |
3 | import { useState } from "react";
4 | import { Card } from "@components/ui/card";
5 | import { Button } from "@components/ui/button";
6 | import { parseAsString, useQueryState } from "nuqs";
7 | import { useCoverageHeatmap } from "@hooks/useVisualizationData";
8 | import { usePrograms } from "@hooks/usePrograms";
9 | import {
10 |   Select,
11 |   SelectContent,
12 |   SelectItem,
13 |   SelectTrigger,
14 |   SelectValue,
15 | } from "@components/ui/select";
16 | import {
17 |   getEvidenceCountColor,
18 |   getAttainmentColor,
19 |   getHeatmapCellTextColor,
20 |   EVIDENCE_LEGEND,
21 |   ATTAINMENT_LEGEND,
22 | } from "@lib/coverageHeatmap";
23 | import HeatmapLegend from "@components/shared/HeatmapLegend";
24 | import { NoData } from "@components/shared/EmptyState";
25 | import ErrorState from "@components/shared/ErrorState";
26 | import { Shimmer } from "@design-system";
27 | import { Grid3X3 } from "lucide-react";
28 |
29 | type ColorMode = "evidence" | "attainment";
30 |
31 | const CoverageHeatmapView = () => {
32 |   const [programId, setProgramId] = useQueryState(
33 |     "program",
34 |     parseAsString.withDefault("")
35 |   );
36 |   const { data: programsData } = usePrograms();
37 |   const programs = programsData?.data ?? [];
38 |   const {
39 |     data: matrix,
40 |     isLoading,
41 |     isError,
42 |     refetch,
43 |   } = useCoverageHeatmap(programId || undefined);
44 |   const [colorMode, setColorMode] = useState<ColorMode>("evidence");
45 |
46 |   return (
47 |     <div className="space-y-6">
48 |       <div className="flex items-center justify-between">
49 |         <h1 className="text-2xl font-bold tracking-tight">Coverage Heatmap</h1>
50 |         <div className="flex items-center gap-3">
51 |           <div className="flex gap-1">
52 |             <Button
53 |               size="sm"
54 |               variant={colorMode === "evidence" ? "default" : "outline"}
55 |               onClick={() => setColorMode("evidence")}
56 |               className="text-xs"
57 |             />
58 |             Evidence Count
59 |           </Button>
60 |           <Button
61 |             size="sm"
62 |             variant={colorMode === "attainment" ? "default" : "outline"}
63 |             onClick={() => setColorMode("attainment")}
64 |             className="text-xs"
65 |           />
66 |           Attainment %
67 |         </Button>
68 |       </div>
69 |       <Select value={programId} onValueChange={setProgramId}>
70 |         <SelectTrigger className="w-64 bg-white">
71 |           <SelectValue placeholder="Select program" />
72 |         </SelectTrigger>
73 |         <SelectContent>
74 |           {(programs ?? []).map((p) => (
75 |             <SelectItem key={p.id} value={p.id}>
76 |               {p.name}
77 |             </SelectItem>
78 |           ))}
79 |         </SelectContent>
80 |       </Select>
81 |     </div>
82 |   </div>
83 |
84 |   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
85 |     <div
```

```

86 |         className="px-6 py-4 flex items-center gap-2"
87 |         style={{
88 |             background: "var(--brand-gradient)",
89 |         }}
90 |     >
91 |         <Grid3X3 className="h-5 w-5 text-white" />
92 |         <h2 className="text-lg font-bold tracking-tight text-white">
93 |             CLO × Course Matrix
94 |         </h2>
95 |     </div>
96 |     <div className="p-4 overflow-x-auto">
97 |         {!programId ? (
98 |             <p className="text-sm text-slate-400 text-center py-12">
99 |                 Select a program to view coverage.
100 |             </p>
101 |         ) : isLoading ? (
102 |             <Shimmer className="h-64 rounded-lg" />
103 |         ) : isError ? (
104 |             <ErrorState
105 |                 message="We couldn't load the coverage heatmap."
106 |                 onRetry={() => refetch()}
107 |                 className="py-12"
108 |             />
109 |         ) : !matrix || matrix.clo_ids.length === 0 ? (
110 |             <NoData className="py-12" />
111 |         ) : (
112 |             <div>
113 |                 <table className="w-full text-xs border-collapse min-w-[600px]">
114 |                     <thead>
115 |                         <tr>
116 |                             <th className="p-2 border border-slate-200 bg-slate-50 text-slate-500 font-bold text-start">
117 |                                 CLO
118 |                             </th>
119 |                             <th>
120 |                                 {matrix.course_ids.map((cid) => (
121 |                                     <th>
122 |                                         key={cid}
123 |                                         className="p-2 border border-slate-200 bg-slate-50 text-slate-500 font-bold truncate m
124 |                                     >
125 |                                     {matrix.course_labels[cid]}
126 |                                 </th>
127 |                             ))}
128 |                         </thead>
129 |                         <tbody>
130 |                             {matrix.clo_ids.map((cloId) => (
131 |                                 <tr key={cloId}>
132 |                                     <td className="p-2 border border-slate-200 text-slate-700 font-medium truncate max-w-[20
133 |                                     {matrix.clo_labels[cloId]}
134 |                                     </td>
135 |                                     {matrix.course_ids.map((courseId) => {
136 |                                         const cell = matrix.cells.get(`${cloId}:${courseId}`);
137 |                                         const bgColor = cell
138 |                                             ? colorMode === "evidence"
139 |                                             ? getEvidenceCountColor(cell.evidence_count)
140 |                                             : getAttainmentColor(cell.avg_attainment)
141 |                                             : "#ffffff";
142 |                                         return (
143 |                                             <td>
144 |                                                 key={courseId}
145 |                                                 className="p-2 border border-slate-200 text-center font-medium"
146 |                                                 style={{
147 |                                                     backgroundColor: bgColor,
148 |                                                     // Flip text to white on the dark evidence cells so
149 |                                                     // the number keeps "e4.5:1 contrast (WCAG 1.4.3).
150 |                                                     color: cell
151 |                                                         ? getHeatmapCellTextColor(bgColor)
152 |                                                         : undefined,
153 |                                                 }}
154 |                                             >
155 |                                                 {cell ? (
156 |                                                     colorMode === "evidence" ? (
157 |                                                         cell.evidence_count
158 |                                                     ) : (
159 |                                                         `${Math.round(cell.avg_attainment)}%`
160 |                                                     )
161 |                                                 ) : (
162 |                                                     <span className="text-slate-300">—</span>
163 |                                                 )}
164 |                                             </td>
165 |                                         </td>
166 |                                     </tr>
167 |                                 </tbody>
168 |                             </table>
169 |                             <div>
170 |                                 <div>
171 |                                     <div>
172 |                                         <div>
173 |                                             <div>
174 |                                                 <div>
175 |                                                     <div>
176 |                                                         <div>
177 |                                                             <div>
178 |                                                                 colorMode === "evidence" ? "Evidence count" : "Attainment"
179 |                                                             </div>
180 |                                                         </div>
181 |                                                         items={
182 |                                                             colorMode === "evidence" ? EVIDENCE_LEGEND : ATTAINMENT_LEGEND
183 |                                                         }
184 |                                                     </div>
185 |                                                 </div>
186 |                                             </div>
187 |                                         </div>
188 |                                     </div>
189 |                                 </div>

```

```
190 | };
191 |
192 | export default CoverageHeatmapView;
193 |
```

[illegible]

```

97 | open: boolean;
98 | onOpenChange: (open: boolean) => void;
99 | plan?: CQIActionPlan | null;
100 | }
101 |
102 | const CQIPlanFormDialog = ({
103 |   open,
104 |   onOpenChange,
105 |   plan,
106 | }: CQIPlanFormDialogProps) => {
107 |   const { user } = useAuth();
108 |   const isEdit = !!plan;
109 |   const createMutation = useCreateCQIPlan();
110 |   const updateMutation = useUpdateCQIPlan();
111 |   const { data: paginatedPrograms } = usePrograms();
112 |   const programs = paginatedPrograms?.data ?? [];
113 |   const { data: semesters } = useSemesters();
114 |
115 |   const form = useForm<CQIPlanFormData>({
116 |     resolver: zodResolver(cqiPlanSchema) as never,
117 |     defaultValues: {
118 |       program_id: plan?.program_id ?? "",
119 |       semester_id: plan?.semester_id ?? "",
120 |       outcome_id: plan?.outcome_id ?? "",
121 |       outcome_type: (plan?.outcome_type as "PLO" | "CLO") ?? "PLO",
122 |       baseline_attainment: plan?.baseline_attainment ?? 0,
123 |       target_attainment: plan?.target_attainment ?? 70,
124 |       action_description: plan?.action_description ?? "",
125 |       responsible_person: plan?.responsible_person ?? "",
126 |       root_cause: plan?.root_cause ?? "",
127 |       due_date: plan?.due_date ?? "",
128 |       evidence_of_improvement: plan?.evidence_of_improvement ?? "",
129 |     },
130 |   });
131 |
132 |   const selectedProgramId = useWatch({
133 |     control: form.control,
134 |     name: "program_id",
135 |   });
136 |   const { data: paginatedPLOs } = usePLOs(selectedProgramId || undefined);
137 |   const outcomes = paginatedPLOs?.data ?? [];
138 |
139 |   const onSubmit = (data: CQIPlanFormData) => {
140 |     if (!user?.id) return;
141 |
142 |     // Normalize optional text/date fields: empty string !' null (don't persist blanks)
143 |     const rootCause = data.root_cause?.trim() ? data.root_cause.trim() : null;
144 |     const dueDate = data.due_date ? data.due_date : null;
145 |     const evidenceOfImprovement = data.evidence_of_improvement?.trim()
146 |       ? data.evidence_of_improvement.trim()
147 |       : null;
148 |
149 |     if (isEdit) {
150 |       updateMutation.mutate(
151 |         {
152 |           id: plan.id,
153 |           action_description: data.action_description,
154 |           responsible_person: data.responsible_person,
155 |           target_attainment: data.target_attainment,
156 |           root_cause: rootCause,
157 |           due_date: dueDate,
158 |           evidence_of_improvement: evidenceOfImprovement,
159 |           performedBy: user.id,
160 |         },
161 |         {
162 |           onSuccess: () => {
163 |             toast.success("CQI plan updated");
164 |             onOpenChange(false);
165 |             form.reset();
166 |           },
167 |           onError: (err) => toast.error(err.message),
168 |         },
169 |       );
170 |     } else {
171 |       createMutation.mutate(
172 |         {
173 |           ...data,
174 |           root_cause: rootCause,
175 |           due_date: dueDate,
176 |           evidence_of_improvement: evidenceOfImprovement,
177 |           performedBy: user.id,
178 |         },
179 |         {
180 |           onSuccess: () => {
181 |             toast.success("CQI plan created");
182 |             onOpenChange(false);
183 |             form.reset();
184 |           },
185 |           onError: (err) => toast.error(err.message),
186 |         },
187 |       );
188 |     }
189 |   };
190 |
191 |   const isPending = createMutation.isPending || updateMutation.isPending;
192 |
193 |   return (
194 |     <Dialog open={open} onOpenChange={onOpenChange}>
195 |       <DialogContent className="max-w-lg">
196 |         <DialogHeader>
197 |           <DialogTitle>
198 |             {isEdit ? "Edit CQI Action Plan" : "New CQI Action Plan"}
199 |           </DialogTitle>
200 |         </DialogHeader>

```

```

201 | <Form {...form}>
202 |   <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
203 |     {!isEdit && (
204 |       <
205 |         <FormField
206 |           control={form.control}
207 |           name="program_id"
208 |           render={({ field }) => (
209 |             <FormItem>
210 |               <FormLabel>Program</FormLabel>
211 |               <FormControl>
212 |                 <Select
213 |                   value={field.value}
214 |                   onChange={field.onChange}
215 |                 >
216 |                   <SelectTrigger>
217 |                     <SelectValue placeholder="Select program" />
218 |                   </SelectTrigger>
219 |                   <SelectContent>
220 |                     {programs.map((p) => (
221 |                       <SelectItem key={p.id} value={p.id}>
222 |                         {p.code} - {p.name}
223 |                       </SelectItem>
224 |                     ))}
225 |                   </SelectContent>
226 |                 </Select>
227 |               </FormControl>
228 |               <FormMessage />
229 |             </FormItem>
230 |           )}
231 |         </
232 |       >
233 |         <FormField
234 |           control={form.control}
235 |           name="semester_id"
236 |           render={({ field }) => (
237 |             <FormItem>
238 |               <FormLabel>Semester</FormLabel>
239 |               <FormControl>
240 |                 <Select
241 |                   value={field.value}
242 |                   onChange={field.onChange}
243 |                 >
244 |                   <SelectTrigger>
245 |                     <SelectValue placeholder="Select semester" />
246 |                   </SelectTrigger>
247 |                   <SelectContent>
248 |                     {(semesters ?? []).map((s) => (
249 |                       <SelectItem key={s.id} value={s.id}>
250 |                         {s.name}
251 |                       </SelectItem>
252 |                     ))}
253 |                   </SelectContent>
254 |                 </Select>
255 |               </FormControl>
256 |               <FormMessage />
257 |             </FormItem>
258 |           )}
259 |         </
260 |       >
261 |         <FormField
262 |           control={form.control}
263 |           name="outcome_type"
264 |           render={({ field }) => (
265 |             <FormItem>
266 |               <FormLabel>Outcome Type</FormLabel>
267 |               <FormControl>
268 |                 <Select
269 |                   value={field.value}
270 |                   onChange={field.onChange}
271 |                 >
272 |                   <SelectTrigger>
273 |                     <SelectValue />
274 |                   </SelectTrigger>
275 |                   <SelectContent>
276 |                     <SelectItem value="PLO">PLO</SelectItem>
277 |                     <SelectItem value="CLO">CLO</SelectItem>
278 |                   </SelectContent>
279 |                 </Select>
280 |               </FormControl>
281 |               <FormMessage />
282 |             </FormItem>
283 |           )}
284 |         </
285 |       >
286 |         <FormField
287 |           control={form.control}
288 |           name="outcome_id"
289 |           render={({ field }) => (
290 |             <FormItem>
291 |               <FormLabel>Outcome</FormLabel>
292 |               <FormControl>
293 |                 <Select
294 |                   value={field.value}
295 |                   onChange={field.onChange}
296 |                 >
297 |                   <SelectTrigger>
298 |                     <SelectValue placeholder="Select outcome" />
299 |                   </SelectTrigger>
300 |                   <SelectContent>
301 |                     {outcomes.map((o) => (
302 |                       <SelectItem key={o.id} value={o.id}>
303 |                         {o.title}
304 |                       </SelectItem>

```



```

305         </FormControl>
306         <FormMessage />
307     </FormItem>
308 })
309 />
310 <div className="grid grid-cols-2 gap-4">
311     <FormField
312         control={form.control}
313         name="baseline_attainment"
314         render={({ field }) => (
315             <FormItem>
316                 <FormLabel>Baseline Attainment (%)</FormLabel>
317                 <FormControl>
318                     <Input type="number" min={0} max={100} {...field} />
319                 </FormControl>
320                 <FormMessage />
321             </FormItem>
322         )}
323     />
324     <FormField
325         control={form.control}
326         name="target_attainment"
327         render={({ field }) => (
328             <FormItem>
329                 <FormLabel>Target Attainment (%)</FormLabel>
330                 <FormControl>
331                     <Input type="number" min={0} max={100} {...field} />
332                 </FormControl>
333                 <FormMessage />
334             </FormItem>
335         )}
336     />
337 </div>
338 </>
339 })
340 <FormField
341     control={form.control}
342     name="action_description"
343     render={({ field }) => (
344         <FormItem>
345             <FormLabel>Action Description</FormLabel>
346             <FormControl>
347                 <Textarea rows={3} {...field} />
348             </FormControl>
349             <FormMessage />
350         </FormItem>
351     )}
352 />
353 <FormField
354     control={form.control}
355     name="responsible_person"
356     render={({ field }) => (
357         <FormItem>
358             <FormLabel>Responsible Person</FormLabel>
359             <FormControl>
360                 <Input {...field} />
361             </FormControl>
362             <FormMessage />
363         </FormItem>
364     )}
365 />
366 <FormField
367     control={form.control}
368     name="root_cause"
369     render={({ field }) => (
370         <FormItem>
371             <FormLabel>Root Cause</FormLabel>
372             <FormControl>
373                 <Textarea
374                     rows={3}
375                     placeholder="What underlying cause led to the attainment gap?"
376                     {...field}
377                 />
378             </FormControl>
379             <FormMessage />
380         </FormItem>
381     )}
382 />
383 <FormField
384     control={form.control}
385     name="due_date"
386     render={({ field }) => (
387         <FormItem>
388             <FormLabel>Deadline</FormLabel>
389             <FormControl>
390                 <Input type="date" {...field} />
391             </FormControl>
392             <FormMessage />
393         </FormItem>
394     )}
395 />
396 <FormField
397     control={form.control}
398     name="evidence_of_improvement"
399     render={({ field }) => (
400         <FormItem>
401             <FormLabel>Evidence of Improvement</FormLabel>
402             <FormControl>
403                 <Textarea
404                     rows={3}
405                     placeholder="What measurable evidence shows the action improved attainment?"
406                     {...field}
407                 />
408             </FormControl>

```

[illegible]

[illegible]

```
617       <Pencil className="h-4 w-4" />  
618     </Button>  
619   <Button variant="ghost" size="sm" onClick={() => onDelete(plan)}>  
620     <Trash2 className="h-4 w-4 text-red-500" />  
621   </Button>  
622 </div>  
623 </div>  
624 );  
625 };  
626  
627 // % % CQI Manager Page % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
628  
629 const CQIManager = () => {  
630   const { user } = useAuth();  
631   const { data: plans, isLoading } = useCQIPPlans();  
632   const updateMutation = useUpdateCQIPPlan();  
633   const deleteMutation = useDeleteCQIPPlan();  
634  
635   const [formOpen, setFormOpen] = useState(false);  
636   const [editingPlan, setEditingPlan] = useState<CQIActionPlan | null>(null);  
637   const [deletingPlan, setDeletingPlan] = useState<CQIActionPlan | null>(null);  
638   const [evaluatingPlan, setEvaluatingPlan] = useState<CQIActionPlan | null>(null);  
639  
640 };  
641  
642 const handleEdit = (plan: CQIActionPlan) => {  
643   setEditingPlan(plan);  
644   setFormOpen(true);  
645 };  
646  
647 const handleAdvanceStatus = (plan: CQIActionPlan) => {  
648   const nextStatus = STATUS_TRANSITIONS[plan.status as CQIPPlanStatus];  
649   if (!nextStatus || !user?.id) return;  
650  
651   updateMutation.mutate(  
652     { id: plan.id, status: nextStatus, performedBy: user.id },  
653     {  
654       onSuccess: () => toast.success(`Status updated to ${nextStatus.replace("_", " ")}`),  
655       onError: (err) => toast.error(err.message),  
656     })  
657   );  
658 };  
659  
660  
661 const handleDelete = () => {  
662   if (!deletingPlan || !user?.id) return;  
663   deleteMutation.mutate(  
664     { id: deletingPlan.id, performedBy: user.id },  
665     {  
666       onSuccess: () => {  
667         toast.success("CQI plan deleted");  
668         setDeletingPlan(null);  
669       },  
670       onError: (err) => toast.error(err.message),  
671     })  
672   );  
673 };  
674  
675 return (  
676   <div className="space-y-6">  
677     <div className="flex items-center justify-between">  
678       <h1 className="text-2xl font-bold tracking-tight">CQI Action Plans</h1>  
679       <Button  
680         onClick={() => {  
681           setEditingPlan(null);  
682           setFormOpen(true);  
683         }}  
684         variant="tactile"  
685       ><Plus className="h-4 w-4" /> New Plan  
686     </Button>  
687   </div>  
688  
689   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">  
690     <GradientCardHeader icon={ClipboardCheck} title="Action Plans" />  
691     <div>  
692       {isLoading ? (  
693         <div className="p-6 space-y-3">  
694           {Array.from({ length: 3 }).map((_, i) => (  
695             <Shimmer key={i} className="h-20 rounded-xl" />  
696           ))}  
697         </div>  
698       ) : !plans || plans.length === 0 ? (  
699         <NoActionPlans className="py-12" />  
700       ) : (  
701         plans.map((plan) => (  
702           <PlanRow  
703             key={plan.id}  
704             plan={plan}  
705             onEdit={handleEdit}  
706             onDelete={setDeletingPlan}  
707             onAdvanceStatus={handleAdvanceStatus}  
708             onEvaluate={setEvaluatingPlan}  
709           />  
710         ))  
711       </div>  
712     </div>  
713   </Card>  
714  
715   </* Form Dialog */>  
716   <CQIPPlanFormDialog  
717     open={formOpen}  
718     onChange={(open) => {  
719       setFormOpen(open);  
720
```

```

721 |         if (!open) setEditingPlan(null);
722 |     }}
723 |     plan={editingPlan}
724 | />
725 |
726 |     {/* Evaluate Dialog */}
727 |     {evaluatingPlan && (
728 |     <EvaluateDialog
729 |         open={!evaluatingPlan}
730 |         onOpenChange={(open) => {
731 |             if (!open) setEvaluatingPlan(null);
732 |         }}
733 |         plan={evaluatingPlan}
734 |     />
735 |     )}
736 |
737 |     {/* Delete Confirmation */}
738 |     <ConfirmDialog
739 |         open={!deletingPlan}
740 |         onOpenChange={(open) => {
741 |             if (!open) setDeletingPlan(null);
742 |         }}
743 |         title="Delete CQI Plan"
744 |         description="Are you sure you want to delete this CQI action plan? This action cannot be undone."
745 |         onConfirm={handleDelete}
746 |         isPending={deleteMutation.isPending}
747 |     />
748 | </div>
749 | );
750 | };
751 |
752 | export default CQIManager;
753 |

```

FILE: src/pages/coordinator/CurriculumMatrixPage.tsx

TYPE: .tsx | LINES: 1-10 | SHA256: 5f10836df04fd8c786f096f5eddb8bdf2e903f508633a709e77402476124f779

```

1 | // =====
2 | // CurriculumMatrixPage – production curriculum matrix (redesigned UI)
3 | // =====
4 | // Implementation lives in `CurriculumMatrixPageNew`, re-exported here so the
5 | // route path stays stable. Legacy page and its feature-flag wrapper were removed
6 | // in the UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "../CurriculumMatrixPageNew";
10 |

```

FILE: src/pages/coordinator/CurriculumMatrixPageNew.tsx

TYPE: .tsx | LINES: 1-283 | SHA256: 278da9f4e1ed55b52de8854a479c3110cdbc02d3a8e930137401c186f9f3e606

```

1 | // =====
2 | // CurriculumMatrixPageNew – redesigned Curriculum Matrix (P3, spec task 3.3)
3 | // =====
4 | //
5 | // Matches the prototype reference: the real PLO×Course matrix gains a coverage
6 | // legend, a per-PLO coverage-summary column, header term/export filters, and a
7 | // bottom Coverage-Gap action panel with an AI recommendation.
8 | //
9 | // DATA: the matrix + coverage column + CSV export are REAL (via
10 | // `useCurriculumMatrix` / `usePrograms` / `buildMatrixCsv`). The term filter and
11 | // the gap-panel AI recommendation are PRESENTATIONAL (no backend field yet); no
12 | // new backend/RPC/write is introduced. Gated behind `newUiModules` (wrapper in
13 | // CurriculumMatrixPage.tsx); flag-off keeps the legacy page. RTL-safe via
14 | // logical props.
15 | // =====
16 |
17 | import { useState, useCallback } from "react";
18 | import { useTranslation } from "react-i18next";
19 | import {
20 |     ArrowRight,
21 |     Download,
22 |     Lightbulb,
23 |     Sparkles,
24 |     Grid3X3,
25 | } from "lucide-react";
26 |
27 | import { usePrograms } from "@/hooks/usePrograms";
28 | import { useCurriculumMatrix } from "@/hooks/useCurriculumMatrix";
29 | import CurriculumMatrix from "@/components/shared/CurriculumMatrix";
30 | import CellDetailSheet from "@/components/shared/CellDetailSheet";
31 | import { Shimmer } from "@/design-system";
32 | import { Card } from "@/components/ui/card";
33 | import { Button } from "@/components/ui/button";
34 | import {
35 |     Select,
36 |     SelectContent,
37 |     SelectItem,
38 |     SelectTrigger,
39 |     SelectValue,
40 | } from "@/components/ui/select";
41 | import { buildMatrixCsv, downloadCsv } from "@/lib/exportCurriculumMatrixCsv";
42 |
43 | interface SelectedCell {
44 |     ploId: string;
45 |     courseId: string;
46 | }
47 |
48 | const LegendChip = ({ color, label }: { color: string; label: string }) => (
49 |     <span className="inline-flex items-center gap-1.5 text-xs font-medium text-slate-600">
50 |         <span
51 |             className="h-2.5 w-2.5 rounded-full"
52 |             style={{ backgroundColor: color }}
53 |             aria-hidden="true"

```

```

54 |     />
55 |     {label}
56 |   </span>
57 | );
58 |
59 | const CurriculumMatrixPageNew = () => {
60 |   const { t } = useTranslation("coordinator");
61 |   const [selectedProgramId, setSelectedProgramId] = useState<string>("");
62 |   const [term, setTerm] = useState<string>("all");
63 |   const [selectedCell, setSelectedCell] = useState<SelectedCell | null>(null);
64 |
65 |   const { data: paginatedPrograms, isLoading: programsLoading } = usePrograms();
66 |   const programs = paginatedPrograms?.data;
67 |   const { data: matrixData } = useCurriculumMatrix(
68 |     selectedProgramId || undefined
69 |   );
70 |   const selectedProgram = programs?.find((p) => p.id === selectedProgramId);
71 |
72 |   const canExport =
73 |     !!selectedProgramId &&
74 |     !!matrixData &&
75 |     matrixData.plos.length > 0 &&
76 |     matrixData.courses.length > 0;
77 |
78 |   const handleExportCsv = useCallback(() => {
79 |     if (!matrixData || !selectedProgram) return;
80 |     if (matrixData.plos.length === 0 || matrixData.courses.length === 0) return;
81 |     downloadCsv(
82 |       buildMatrixCsv(matrixData,
83 |         `curriculum-matrix-${selectedProgram.code}.csv`
84 |       );
85 |     }, [matrixData, selectedProgram]);
86 |
87 |   return (
88 |     <div className="space-y-6">
89 |       <div className="flex flex-wrap items-center justify-between gap-3">
90 |         <h1 className="text-2xl font-bold tracking-tight">
91 |           {t("curriculumMatrix.title")}
92 |         </h1>
93 |         <div className="flex items-center gap-2">
94 |           <Select value={term} onChange={setTerm}>
95 |             <SelectTrigger className="h-9 w-36 bg-white">
96 |               <SelectValue />
97 |             </SelectTrigger>
98 |             <SelectContent>
99 |               <SelectItem value="all">
100 |                 {t("curriculumMatrix.allTerms")}
101 |               </SelectItem>
102 |               <SelectItem value="current">
103 |                 {t("curriculumMatrix.currentTerm")}
104 |               </SelectItem>
105 |             </SelectContent>
106 |           </Select>
107 |           <Button
108 |             variant="outline"
109 |             size="sm"
110 |             disabled={!canExport}
111 |             onClick={handleExportCsv}
112 |           >
113 |             <Download className="h-4 w-4" aria-hidden="true" />
114 |             {t("curriculumMatrix.exportCsv")}
115 |           </Button>
116 |         </div>
117 |       </div>
118 |
119 |       <div>
120 |         <div className="flex flex-wrap items-center justify-between gap-3">
121 |           <div className="flex items-center gap-3">
122 |             <span
123 |               id="program-selector-label"
124 |               className="text-sm font-medium text-gray-700"
125 |             >
126 |               {t("curriculumMatrix.program")}
127 |             </span>
128 |             {programsLoading ? (
129 |               <Shimmer className="h-9 w-64" />
130 |             ) : (
131 |               <Select
132 |                 value={selectedProgramId}
133 |                 onChange={setSelectedProgramId}
134 |               >
135 |                 <SelectTrigger
136 |                   className="w-64 bg-white"
137 |                   aria-labelledby="program-selector-label"
138 |                 >
139 |                   <SelectValue
140 |                     placeholder={t("curriculumMatrix.selectProgram")}
141 |                   />
142 |                 </SelectTrigger>
143 |                 <SelectContent>
144 |                   {programs?.map((program) => (
145 |                     <SelectItem key={program.id} value={program.id}>
146 |                       {program.code} — {program.name}
147 |                     </SelectItem>
148 |                   ))}
149 |                 </SelectContent>
150 |               </Select>
151 |             )}
152 |           </div>
153 |
154 |           <div className="flex flex-wrap items-center gap-x-4 gap-y-1.5">
155 |             <LegendChip
156 |               color="#16a34a"
157 |

```

```

158     label={t("curriculumMatrix.legendAssessed")}
159   />
160   <LegendChip
161     color="#ca8a04"
162     label={t("curriculumMatrix.legendIntroduced")}
163   />
164   <LegendChip
165     color="#cbd5e1"
166     label={t("curriculumMatrix.legendNotCovered")}
167   />
168   <LegendChip color="#dc2626" label={t("curriculumMatrix.legendGap")} />
169 </div>
170 </div>
171
172 /* Matrix (real data, with coverage-summary column) */
173 {selectedProgramId ? (
174   <CurriculumMatrix
175     programId={selectedProgramId}
176     coverageLabel={t("curriculumMatrix.coverage")}
177     onClick={({ploId, courseId}) =>
178       setSelectedCell({ ploId, courseId })
179     }
180   />
181 ) : (
182   <div className="rounded-xl border border-slate-200 bg-white p-8 text-center text-sm text-gray-500">
183     {t("curriculumMatrix.selectPrompt")}
184   </div>
185 )}
186
187 /* Coverage Gap action panel + AI recommendation */
188 {selectedProgramId && (
189   <Card className="card-elevated gap-0 border-0 bg-white py-0">
190     <div className="grid gap-0 md:grid-cols-2">
191       /* Gap */
192       <div className="border-b border-slate-100 p-5 md:border-b-0 md:border-e">
193         <div className="flex items-center gap-2">
194           <span className="inline-flex h-8 w-8 items-center justify-center rounded-lg bg-amber-50 text-a">
195             <Grid3X3 className="h-4 w-4" aria-hidden="true" />
196           </span>
197           <p className="text-sm font-bold text-gray-900">
198             {t("curriculumMatrix.gapTitle")}
199           </p>
200         </div>
201         <p className="mt-2 text-xs text-gray-600">
202           {t("curriculumMatrix.gapBody")}
203         </p>
204         <div className="mt-4 flex flex-wrap gap-2">
205           <Button variant="tactile" size="sm">
206             {t("curriculumMatrix.draftAssessment")}
207           </Button>
208           <Button variant="outline" size="sm">
209             {t("curriculumMatrix.notifyTeacher")}
210           </Button>
211         </div>
212       </div>
213
214       /* AI recommendation */
215       <div className="bg-teal-50/50 p-5">
216         <p className="flex items-center gap-1.5 text-[10px] font-black uppercase tracking-widest text-te">
217           <Sparkles className="h-3.5 w-3.5" aria-hidden="true" />
218           {t("curriculumMatrix.aiRec")}
219         </p>
220         <dl className="mt-3 space-y-2.5">
221           <div className="flex items-start gap-2">
222             <Lightbulb
223               className="mt-0.5 h-3.5 w-3.5 shrink-0 text-teal-600"
224               aria-hidden="true"
225             />
226             <div>
227               <dt className="text-[11px] font-semibold text-slate-500">
228                 {t("curriculumMatrix.aiBestCourseLabel")}
229               </dt>
230               <dd className="text-xs font-semibold text-gray-800">
231                 {t("curriculumMatrix.aiBestCourseValue")}
232               </dd>
233             </div>
234           </div>
235           <div className="flex items-start gap-2">
236             <Lightbulb
237               className="mt-0.5 h-3.5 w-3.5 shrink-0 text-teal-600"
238               aria-hidden="true"
239             />
240             <div>
241               <dt className="text-[11px] font-semibold text-slate-500">
242                 {t("curriculumMatrix.aiAssessmentLabel")}
243               </dt>
244               <dd className="text-xs font-semibold text-gray-800">
245                 {t("curriculumMatrix.aiAssessmentValue")}
246               </dd>
247             </div>
248           </div>
249           <div className="flex items-start gap-2">
250             <ArrowRight
251               className="mt-0.5 h-3.5 w-3.5 shrink-0 text-teal-600"
252               aria-hidden="true"
253             />
254             <div>
255               <dt className="text-[11px] font-semibold text-slate-500">
256                 {t("curriculumMatrix.aiActionLabel")}
257               </dt>
258               <dd className="text-xs text-gray-700">
259                 {t("curriculumMatrix.aiActionValue")}
260               </dd>
261             </div>

```

```

262 |         </div>
263 |     </dl>
264 | </div>
265 | </div>
266 | </Card>
267 | })
268 |
269 | { /* Cell Detail Sheet (real) */}
270 | <CellDetailSheet
271 |   ploId={selectedCell?.ploId}
272 |   courseId={selectedCell?.courseId}
273 |   open={selectedCell !== null}
274 |   onOpenChange={open => {
275 |     if (!open) setSelectedCell(null);
276 |   }}
277 | />
278 | </div>
279 | );
280 | };
281 |
282 | export default CurriculumMatrixPageNew;
283 |

```

FILE: [src/pages/coordinator/gap-analysis/GapAnalysisView.tsx](#)

TYPE: .tsx | LINES: 1-240 | SHA256: 986fa7ca71fdce6f87f8881c4bc90aa2fc8e2575aa65188e1da5ff84b8f44c15

```

1 | // Task 119.2: Gap Analysis View page
2 |
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { useGapAnalysis } from "@/hooks/useVisualizationData";
5 | import { usePrograms } from "@/hooks/usePrograms";
6 | import { NoOutcomes } from "@components/shared/EmptyState";
7 | import ErrorState from "@components/shared/ErrorState";
8 | import {
9 |   Badge,
10 |   Card,
11 |   KPICard,
12 |   MasteryRing,
13 |   SectionHeader,
14 |   Select,
15 |   SelectContent,
16 |   SelectItem,
17 |   SelectTrigger,
18 |   SelectValue,
19 |   SeverityIcon,
20 |   Shimmer,
21 | } from "@design-system";
22 | import { attainmentValueClass } from "@lib/attainmentTone";
23 | import {
24 |   AlertTriangle,
25 |   CheckCircle,
26 |   XCircle,
27 |   HelpCircle,
28 |   Search,
29 |   Target,
30 |   ClipboardCheck,
31 | } from "lucide-react";
32 | import type { GapStatus } from "@lib/gapAnalysis";
33 |
34 | const STATUS_CONFIG: Record<
35 |   GapStatus,
36 |   { label: string; color: string; icon: typeof CheckCircle }
37 | > = {
38 |   fully_mapped: {
39 |     label: "Fully Mapped",
40 |     color: "bg-green-100 text-green-700",
41 |     icon: CheckCircle,
42 |   },
43 |   partially_mapped: {
44 |     label: "Partially Mapped",
45 |     color: "bg-yellow-100 text-yellow-700",
46 |     icon: AlertTriangle,
47 |   },
48 |   unmapped: {
49 |     label: "Unmapped",
50 |     color: "bg-red-100 text-red-700",
51 |     icon: XCircle,
52 |   },
53 |   no_evidence: {
54 |     label: "No Evidence",
55 |     color: "bg-gray-100 text-gray-700",
56 |     icon: HelpCircle,
57 |   },
58 | };
59 |
60 | // Maps each gap status to a SeverityIcon severity (color + icon by status).
61 | const STATUS_SEVERITY: Record<GapStatus, "low" | "med" | "high" | "neutral"> = {
62 |   fully_mapped: "low",
63 |   partially_mapped: "med",
64 |   unmapped: "high",
65 |   no_evidence: "neutral",
66 | };
67 |
68 | const GapAnalysisView = () => {
69 |   const [programId, setProgramId] = useQueryState(
70 |     "program",
71 |     parseAsString.withDefault("")
72 |   );
73 |   const { data: programsData } = usePrograms();
74 |   const programs = programsData?.data ?? [];
75 |   const {
76 |     data: gaps,
77 |     isLoading,
78 |     isError,

```



```

79 |     refetch,
80 | } = useGapAnalysis(programId || undefined);
81 |
82 | const summary = gaps
83 |   ? {
84 |     total: gaps.length,
85 |     fullyMapped: gaps.filter((g) => g.status === "fully_mapped").length,
86 |     withEvidence: gaps.filter((g) => g.evidence_count > 0).length,
87 |   }
88 |   : null;
89 |
90 | const fullyMappedPct =
91 |   summary && summary.total > 0
92 |     ? Math.round((summary.fullyMapped / summary.total) * 100)
93 |     : 0;
94 | const withEvidencePct =
95 |   summary && summary.total > 0
96 |     ? Math.round((summary.withEvidence / summary.total) * 100)
97 |     : 0;
98 |
99 | return (
100 |   <div className="space-y-6">
101 |     <div className="flex items-center justify-between gap-4">
102 |       <h1 className="text-2xl font-bold tracking-tight">Gap Analysis</h1>
103 |       <Select value={programId} onChange={setProgramId}>
104 |         <SelectTrigger className="w-64 bg-white">
105 |           <SelectValue placeholder="Select program" />
106 |         </SelectTrigger>
107 |         <SelectContent>
108 |           {(programs ?? []).map((p) => (
109 |             <SelectItem key={p.id} value={p.id}>
110 |               {p.name}
111 |             </SelectItem>
112 |           ))}
113 |         </SelectContent>
114 |       </Select>
115 |     </div>
116 |
117 |     {summary && (
118 |       <Card className="card-elevated overflow-hidden border-0 bg-white">
119 |         <div className="flex flex-col gap-6 p-6 sm:flex-row sm:items-center">
120 |           <div className="flex items-center gap-5">
121 |             <MasteryRing value={fullyMappedPct} size={104} tone="auto" />
122 |             <div>
123 |               <p className="text-[10px] font-black uppercase tracking-widest text-gray-500">
124 |                 Fully Mapped
125 |               </p>
126 |               <p
127 |                 className={`text-3xl font-black ${attainmentValueClass(
128 |                   fullyMappedPct
129 |                 )}`}
130 |               >
131 |                 {fullyMappedPct}%
132 |               </p>
133 |             </div>
134 |           </div>
135 |           <div className="grid flex-1 grid-cols-3 gap-4 sm:ms-auto sm:max-w-md">
136 |             <KPICard
137 |               icon={Target}
138 |               label="Outcomes"
139 |               value={summary.total}
140 |               className="shadow-none ring-1 ring-slate-100"
141 |             />
142 |             <KPICard
143 |               icon={CheckCircle}
144 |               label="Fully Mapped"
145 |               value={` ${fullyMappedPct}%`}
146 |               valueClassName={attainmentValueClass(fullyMappedPct)}
147 |               iconBgClass="bg-green-50"
148 |               iconColorClass="text-green-600"
149 |               className="shadow-none ring-1 ring-slate-100"
150 |             />
151 |             <KPICard
152 |               icon={ClipboardCheck}
153 |               label="With Evidence"
154 |               value={` ${withEvidencePct}%`}
155 |               valueClassName={attainmentValueClass(withEvidencePct)}
156 |               className="shadow-none ring-1 ring-slate-100"
157 |             />
158 |           </div>
159 |         </div>
160 |       </Card>
161 |     )}
162 |
163 |     <Card className="card-elevated overflow-hidden border-0 bg-white">
164 |       <div className="p-6">
165 |         <SectionHeader icon={Search} title="Outcome Coverage" />
166 |         <div className="mt-4">
167 |           {!programId ? (
168 |             <p className="py-12 text-center text-sm text-slate-400">
169 |               Select a program to analyze gaps.
170 |             </p>
171 |           ) : isLoading ? (
172 |             <Shimmer className="h-64 rounded-lg" />
173 |           ) : isError ? (
174 |             <ErrorState
175 |               message="We couldn't load the gap analysis."
176 |               onRetry={() => refetch()}
177 |               className="py-12"
178 |             />
179 |           ) : !gaps || gaps.length === 0 ? (
180 |             <NoOutcomes className="py-12" />
181 |           ) : (
182 |             <div className="space-y-2">

```

```

183 |         {gaps.map((gap) => {
184 |             const config = STATUS_CONFIG[gap.status];
185 |             const Icon = config.icon;
186 |             return (
187 |                 <div
188 |                     key={gap.outcome_id}
189 |                     className="flex items-start gap-3 rounded-xl border border-slate-100 p-3 transition-colo
190 |                 >
191 |                     <SeverityIcon
192 |                         icon={Icon}
193 |                         severity={STATUS_SEVERITY[gap.status]}
194 |                         size="sm"
195 |                         label={config.label}
196 |                     />
197 |                     <div className="min-w-0 flex-1">
198 |                         <div className="flex flex-wrap items-center gap-2">
199 |                             <Badge variant="outline" className="text-[10px]">
200 |                                 {gap.outcome_type}
201 |                             </Badge>
202 |                             <span className="text-sm font-medium text-gray-900 dark:text-foreground">
203 |                                 {gap.outcome_title}
204 |                             </span>
205 |                             <Badge
206 |                                 className={`ms-auto text-[10px] ${config.color}`}
207 |                             >
208 |                                 {config.label}
209 |                             </Badge>
210 |                         </div>
211 |                         {gap.flag && (
212 |                             <div className="mt-1 flex items-center gap-1">
213 |                                 <AlertTriangle className="h-3 w-3 text-amber-500" />
214 |                                 <span className="text-xs text-amber-600">
215 |                                     {gap.flag === "under_mapped"
216 |                                     ? "Under-Mapped"
217 |                                     : "Unassessed"}
218 |                                 </span>
219 |                             </div>
220 |                         )}
221 |                         {gap.recommendation && (
222 |                             <p className="mt-1 text-xs text-slate-500">
223 |                                 {gap.recommendation}
224 |                             </p>
225 |                         )}
226 |                     </div>
227 |                 </div>
228 |             );
229 |         });
230 |     </div>
231 | }
232 | </div>
233 | </div>
234 | </Card>
235 | </div>
236 | );
237 | };
238 |
239 | export default GapAnalysisView;
240 |

```

FILE: [src/pages/coordinator/plos/columns.tsx](#)

TYPE: .tsx | LINES: 1-154 | SHA256: d8a61a504e2dd4f42eaf7206255eb988cc89e849fead7c7c99922c169ca4c442

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import {
4 |     ArrowUpDown,
5 |     GripVertical,
6 |     MoreHorizontal,
7 |     Pencil,
8 |     Trash2,
9 | } from "lucide-react";
10 | import { Badge } from "@components/ui/badge";
11 | import { Button } from "@components/ui/button";
12 | import {
13 |     DropdownMenu,
14 |     DropdownMenuContent,
15 |     DropdownMenuItem,
16 |     DropdownMenuTrigger,
17 | } from "@components/ui/dropdown-menu";
18 | import type { LearningOutcome } from "@types/app";
19 |
20 | export const createColumns = (
21 |     onEdit: (id: string) => void,
22 |     onDelete: (plo: LearningOutcome) => void,
23 |     isDragMode: boolean,
24 |     programNames: ReadonlyMap<string, string> = new Map()
25 | ): ColumnDef<LearningOutcome>[] => {
26 |     const cols: ColumnDef<LearningOutcome>[] = [];
27 |
28 |     if (isDragMode) {
29 |         cols.push({
30 |             id: "drag-handle",
31 |             header: "",
32 |             cell: () => (
33 |                 <GripVertical className="h-4 w-4 text-gray-400 cursor-grab" />
34 |             ),
35 |             size: 40,
36 |         });
37 |     }
38 |
39 |     cols.push(
40 |         {
41 |             accessorKey: "sort_order",
42 |             header: "#",

```

```

43 |         cell: ({ row }) => {
44 |             <span className="text-gray-500 text-sm font-medium">
45 |                 {(row.getValue("sort_order") as number) + 1}
46 |             </span>
47 |         },
48 |         size: 50,
49 |     },
50 |     {
51 |         accessorKey: "title",
52 |         header: ({ column }) => {
53 |             <Button
54 |                 variant="ghost"
55 |                 size="sm"
56 |                 className="-ms-3"
57 |                 onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
58 |             >
59 |                 Title
60 |                 <ArrowUpDown className="h-4 w-4" />
61 |             </Button>
62 |         },
63 |         cell: ({ row }) => {
64 |             <span className="font-medium">{row.getValue("title")}</span>
65 |         },
66 |     },
67 |     {
68 |         accessorKey: "description",
69 |         header: "Description",
70 |         cell: ({ row }) => {
71 |             const desc = row.getValue("description") as string | null;
72 |             return (
73 |                 <span className="text-gray-500 text-sm line-clamp-1">
74 |                     {desc || "-"}
75 |                 </span>
76 |             );
77 |         },
78 |     },
79 |     {
80 |         accessorKey: "program_id",
81 |         header: "Program",
82 |         cell: ({ row }) => {
83 |             const programId = row.getValue("program_id") as string | null;
84 |             const programName = programId ? programNames.get(programId) : null;
85 |             return (
86 |                 <span className="inline-block max-w-[180px] truncate text-sm text-gray-600">
87 |                     {programName ?? (programId ? "Unknown program" : "-")}
88 |                 </span>
89 |             );
90 |         },
91 |     },
92 |     {
93 |         accessorKey: "is_active",
94 |         header: "Status",
95 |         cell: ({ row }) => {
96 |             const isActive = row.getValue("is_active") as boolean;
97 |             return (
98 |                 <Badge
99 |                     variant="outline"
100 |                     className={
101 |                         isActive
102 |                         ? "bg-green-50 text-green-600 border-green-200"
103 |                         : "bg-red-50 text-red-600 border-red-200"
104 |                     }
105 |                 >
106 |                     {isActive ? "Active" : "Inactive"}
107 |                 </Badge>
108 |             );
109 |         },
110 |     },
111 |     {
112 |         accessorKey: "created_at",
113 |         header: "Created",
114 |         cell: ({ row }) => {
115 |             const date = row.getValue("created_at") as string;
116 |             return (
117 |                 <span className="text-gray-500">
118 |                     {format(new Date(date), "MMM d, yyyy")}
119 |                 </span>
120 |             );
121 |         },
122 |     },
123 |     {
124 |         id: "actions",
125 |         header: "",
126 |         cell: ({ row }) => {
127 |             <DropdownMenu>
128 |                 <DropdownMenuTrigger asChild>
129 |                     <Button variant="ghost" size="icon-xs">
130 |                         <MoreHorizontal className="h-4 w-4" />
131 |                         <span className="sr-only">Open menu</span>
132 |                     </Button>
133 |                 </DropdownMenuTrigger>
134 |                 <DropdownMenuContent align="end">
135 |                     <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
136 |                         <Pencil className="h-4 w-4" />
137 |                         Edit
138 |                     </DropdownMenuItem>
139 |                     <DropdownMenuItem
140 |                         variant="destructive"
141 |                         onClick={() => onDelete(row.original)}
142 |                     >
143 |                         <Trash2 className="h-4 w-4" />
144 |                         Delete
145 |                     </DropdownMenuItem>
146 |                 </DropdownMenuContent>

```

```
147 |         </DropDownMenu>
148 |     ),
149 | }
150 | );
151 |
152 | return cols;
153 | };
154 |
```

FILE: src/pages/coordinator/plos/PL0Form.tsx

```
TYPE: .tsx | LINES: 1-634 | SHA256: 14d183e77c65cfe7be8b29ba3924f806b3db9d3f15946f687c3cc3205cbf9cd5
```

[illegible]

[illegible]

```

197 | const EditPLODetailsForm = ({ ploId }: { ploId: string }) => {
198 |   const navigate = useNavigate();
199 |   const { t } = useTranslation("coordinator");
200 |   const { data: existingPLO, isLoading } = usePLO(ploId);
201 |   const updateMutation = useUpdatePLO(ploId);
202 |
203 |   const form = useForm<CreatePLOFormData>({
204 |     resolver: zodResolver(createPLOSchema),
205 |     defaultValues: {
206 |       title: "",
207 |       title_ar: "",
208 |       description: "",
209 |       program_id: "" as `${string}-${string}-${string}-${string}-${string}`,
210 |     },
211 |   });
212 |
213 |   useEffect(() => {
214 |     if (existingPLO) {
215 |       const plo = existingPLO as unknown as LearningOutcome;
216 |       form.reset({
217 |         title: plo.title,
218 |         title_ar:
219 |           ((plo as unknown as Record<string, unknown>).title_ar as string) ??
220 |           "",
221 |         description: plo.description ?? "",
222 |         program_id: (plo.program_id ??
223 |           "") as `${string}-${string}-${string}-${string}-${string}`,
224 |       });
225 |     }
226 |   }, [existingPLO, form]);
227 |
228 |   if (isLoading) {
229 |     return (
230 |       <div className="flex items-center justify-center py-12">
231 |         <Loader2 className="h-8 w-8 animate-spin text-blue-600" />
232 |       </div>
233 |     );
234 |   }
235 |
236 |   const onSubmit = (data: CreatePLOFormData) => {
237 |     updateMutation.mutate(data, {
238 |       onSuccess: () => {
239 |         toast.success("PLO updated successfully");
240 |       },
241 |       onError: (err) => toast.error(err.message),
242 |     });
243 |   };
244 |
245 |   return (
246 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
247 |       <h2 className="text-lg font-bold tracking-tight mb-4">PLO Details</h2>
248 |       <Form {...form}>
249 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
250 |           <FormField
251 |             control={form.control}
252 |             name="title"
253 |             render={({ field }) => (
254 |               <FormItem>
255 |                 <FormLabel>Title</FormLabel>
256 |                 <FormControl>
257 |                   <Input
258 |                     placeholder="e.g. Apply engineering principles to solve problems"
259 |                     maxLength={255}
260 |                     {...field}
261 |                   />
262 |                 </FormControl>
263 |                 <FormMessage />
264 |               </FormItem>
265 |             )}
266 |           />
267 |
268 |           <FormField
269 |             control={form.control}
270 |             name="title_ar"
271 |             render={({ field }) => (
272 |               <FormItem>
273 |                 <FormLabel>{t("bilingual.arabicTitle")}</FormLabel>
274 |                 <FormControl>
275 |                   <Input
276 |                     placeholder={t("bilingual.arabicTitlePlaceholder")}
277 |                     dir="rtl"
278 |                     maxLength={255}
279 |                     {...field}
280 |                     value={field.value ?? ""}
281 |                   />
282 |                 </FormControl>
283 |                 <FormMessage />
284 |               </FormItem>
285 |             )}
286 |           />
287 |
288 |           <FormField
289 |             control={form.control}
290 |             name="description"
291 |             render={({ field }) => (
292 |               <FormItem>
293 |                 <FormLabel>Description</FormLabel>
294 |                 <FormControl>
295 |                   <Textarea
296 |                     placeholder="Describe this program learning outcome..."
297 |                     className="min-h-[100px] resize-y"
298 |                     {...field}
299 |                   />
300 |                 </FormControl>

```

[illegible]

```

405 |     ...prev,
406 |     [iloId]: {
407 |       weight: wasEnabled ? 0 : 0.1,
408 |       enabled: !wasEnabled,
409 |     },
410 |   }));
411 | };
412 |
413 | const handleWeightChange = (iloId: string, value: string) => {
414 |   const numValue = parseFloat(value);
415 |   if (isNaN(numValue)) return;
416 |   const clamped = Math.min(1.0, Math.max(0, numValue));
417 |   const current = mappings.find((m) => m.ilo_id === iloId);
418 |   setOverrides((prev) => ({
419 |     ...prev,
420 |     [iloId]: {
421 |       weight: clamped,
422 |       enabled: current?.enabled ?? false,
423 |     },
424 |   }));
425 | };
426 |
427 | const handleSaveMappings = () => {
428 |   const activeMappings = mappings
429 |     .filter((m) => m.enabled && m.weight > 0)
430 |     .map((m) => ({
431 |       source_outcome_id: m.ilo_id,
432 |       weight: m.weight,
433 |     }));
434 |
435 |   updateMappingsMutation.mutate(
436 |     { ploId, mappings: activeMappings },
437 |     {
438 |       onSuccess: () => {
439 |         toast.success("ILO mappings saved successfully");
440 |         if (weightStatus === "under") {
441 |           toast.warning(
442 |             "Total ILO mapping weight is below 0.5. Consider adjusting weights for better outcome coverage."
443 |           );
444 |         } else if (weightStatus === "over") {
445 |           toast.warning(
446 |             "Total ILO mapping weight exceeds 1.0. Consider reducing weights."
447 |           );
448 |         }
449 |       },
450 |       onError: (err) => toast.error(err.message),
451 |     }
452 |   );
453 | };
454 |
455 | if (isLoadingILOs || isLoadingMappings) {
456 |   return (
457 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
458 |       <div className="flex items-center justify-center py-8">
459 |         <Loader2 className="h-6 w-6 animate-spin text-blue-600" />
460 |       </div>
461 |     </Card>
462 |   );
463 | }
464 |
465 | if (ilos.length === 0) {
466 |   return (
467 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
468 |       <h2 className="text-lg font-bold tracking-tight mb-2">ILO Mappings</h2>
469 |       <InlineNoILOs />
470 |     </Card>
471 |   );
472 | }
473 |
474 | return (
475 |   <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
476 |     <div className="flex items-center gap-2 mb-4">
477 |       <Link2 className="h-5 w-5 text-blue-600" />
478 |       <h2 className="text-lg font-bold tracking-tight">ILO Mappings</h2>
479 |     </div>
480 |
481 |     <p className="text-sm text-gray-500 mb-4">
482 |       Map this PLO to one or more ILOs and assign weights (0.0-1.0).
483 |     </p>
484 |
485 |     <div className="space-y-3">
486 |       {ilos.map((ilo) => {
487 |         const mapping = mappings.find((m) => m.ilo_id === ilo.id);
488 |         const isEnabled = mapping?.enabled ?? false;
489 |
490 |         return (
491 |           <div
492 |             key={ilo.id}
493 |             className={`flex items-center gap-4 p-3 rounded-lg border transition-colors ${
494 |               isEnabled
495 |                 ? "border-blue-200 bg-blue-50/50"
496 |                 : "border-slate-200 bg-white"
497 |             }`}
498 |           >
499 |             <button
500 |               type="button"
501 |               onClick={() => handleToggle(ilo.id)}
502 |               className={`shrink-0 w-5 h-5 rounded border-2 flex items-center justify-center transition-colo
503 |                 isEnabled
504 |                   ? "bg-blue-600 border-blue-600 text-white"
505 |                   : "border-gray-300 bg-white"
506 |               `}
507 |               aria-label={`Toggle mapping for ${ilo.title}`}
508 |             >

```


[illegible]

```

613 |         <ArrowLeft className="h-4 w-4" />
614 |         Back
615 |       </Button>
616 |       <h1 className="text-2xl font-bold tracking-tight">
617 |         {isEditMode ? "Edit PLO" : "Create PLO"}
618 |       </h1>
619 |     </div>
620 |
621 |     {isEditMode ? (
622 |       <>
623 |         <EditPLODetailsForm ploId={id} />
624 |         <ILOMappingSection ploId={id} />
625 |       </>
626 |     ) : (
627 |       <CreatePLODetailsForm />
628 |     )}
629 |   </div>
630 | );
631 | };
632 |
633 | export default PLOForm;
634 |

```

FILE: src/pages/coordinator/plos/PL0ListPage.tsx

```
TYPE: .tsx | LINES: 1-356 | SHA256: 5bb8048dc732bd2889008b014f7152e321f54c2f8a3592a0095095bd978e6520
```

[illegible]

[illegible]

```

183 | [programs]
184 | );
185 |
186 | const columns = useMemo(
187 |   () =>
188 |     createColumns(
189 |       (id) => navigate(`/coordinator/plos/${id}/edit`),
190 |       (plo) => setPloToDelete(plo),
191 |       isDragMode,
192 |       programNames
193 |     ),
194 |     [isDragMode, navigate, programNames]
195 |   );
196 |
197 | return (
198 |   <div className="space-y-6">
199 |     </* Page Header */>
200 |     <div className="flex items-center justify-between">
201 |       <h1 className="text-2xl font-bold tracking-tight">
202 |         Program Learning Outcomes
203 |       </h1>
204 |       <div className="flex items-center gap-2">
205 |         <{!isDragMode ? (
206 |           <>
207 |             <Button
208 |               variant="outline"
209 |               size="sm"
210 |               onClick={enterDragMode}
211 |               disabled={isLoading || !plos?.length}
212 |             >
213 |               <ArrowUpDown className="h-4 w-4" />
214 |               Reorder
215 |             </Button>
216 |             <Button
217 |               variant="tactile"
218 |               onClick={() => navigate("/coordinator/plos/new")}
219 |             >
220 |               <Plus className="h-4 w-4" /> Add PLO
221 |             </Button>
222 |           </>
223 |         ) : (
224 |           <>
225 |             <Button
226 |               variant="outline"
227 |               size="sm"
228 |               onClick={cancelDragMode}
229 |               disabled={reorderMutation.isPending}
230 |             >
231 |               <X className="h-4 w-4" />
232 |               Cancel
233 |             </Button>
234 |             <Button
235 |               size="sm"
236 |               onClick={saveOrder}
237 |               disabled={reorderMutation.isPending}
238 |               variant="tactile"
239 |             >
240 |               {reorderMutation.isPending ? (
241 |                 <Loader2 className="h-4 w-4 animate-spin" />
242 |               ) : (
243 |                 <Check className="h-4 w-4" />
244 |               )}
245 |               Save Order
246 |             </Button>
247 |           </>
248 |         )}
249 |       </div>
250 |     </div>
251 |
252 |     </* Program Filter */>
253 |     <div className="flex items-center gap-4">
254 |       <Select
255 |         value={programFilter}
256 |         onChange={(val) => {
257 |           setProgramFilter(val === "all" ? "" : val);
258 |           setPage(1);
259 |         }}
260 |         disabled={programsLoading}
261 |       >
262 |         <SelectTrigger className="w-[260px] bg-white">
263 |           <SelectValue placeholder="Filter by program" />
264 |         </SelectTrigger>
265 |         <SelectContent>
266 |           <SelectItem value="all">All Programs</SelectItem>
267 |           {(programs ?? []).map((p) => (
268 |             <SelectItem key={p.id} value={p.id}>
269 |               {p.name}
270 |             </SelectItem>
271 |           ))}
272 |         </SelectContent>
273 |       </Select>
274 |     </div>
275 |
276 |     </* Content */>
277 |     <{isLoading ? (
278 |       <div className="space-y-3">
279 |         {Array.from({ length: 5 }).map((_, i) => (
280 |           <Shimmer key={i} className="h-14 rounded-lg" />
281 |         ))}
282 |       </div>
283 |     ) : !displayItems.length ? (
284 |       <NoCourses>
285 |         <Button
286 |           variant="tactile"

```

```

287 |         onClick={() => navigate("/coordinator/plos/new")}
288 |       >
289 |         <Plus className="h-4 w-4" />
290 |         Create PLO
291 |       </Button>
292 |     </NoCourses>
293 |   ) : isDragMode ? (
294 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4">
295 |       <p className="text-xs text-gray-500 mb-3">
296 |         Drag items to reorder, then click Save Order.
297 |       </p>
298 |       <DndContext
299 |         sensors={sensors}
300 |         collisionDetection={closestCenter}
301 |         onDragEnd={handleDragEnd}
302 |       >
303 |         <SortableContext
304 |           items={displayItems.map((i) => i.id)}
305 |           strategy={verticalListSortingStrategy}
306 |         >
307 |           <div className="space-y-2">
308 |             {displayItems.map((plo, idx) => (
309 |               <SortableRow key={plo.id} plo={plo} index={idx} />
310 |             ))}
311 |           </div>
312 |         </SortableContext>
313 |       </DndContext>
314 |     </Card>
315 |   ) : (
316 |     <DataTable
317 |       columns={columns}
318 |       data={displayItems}
319 |       isLoading={false}
320 |       isFetching={isFetching}
321 |       page={page}
322 |       pageSize={paginatedPLOs?.pageSize}
323 |       totalCount={paginatedPLOs?.count}
324 |       onPageChange={setPage}
325 |     />
326 |   )}
327 |
328 |   {/* Delete Confirmation Dialog */}
329 |   <ConfirmDialog
330 |     open={!ploToDelete}
331 |     onOpenChange={() => setPloToDelete(null)}
332 |     title="Delete PLO"
333 |     description={`Are you sure you want to delete "${ploToDelete?.title}"? This action cannot be undone. I`}
334 |     variant="destructive"
335 |     confirmLabel="Delete"
336 |     isPending={deleteMutation.isPending}
337 |     onConfirm={() => {
338 |       if (!ploToDelete) return;
339 |       deleteMutation.mutate(ploToDelete.id, {
340 |         onSuccess: () => {
341 |           toast.success(`"${ploToDelete.title}" has been deleted`);
342 |           setPloToDelete(null);
343 |         },
344 |         onError: (err) => {
345 |           toast.error(err.message);
346 |           setPloToDelete(null);
347 |         },
348 |       });
349 |     }}
350 |   />
351 | </div>
352 | );
353 | };
354 |
355 | export default PLOListPage;
356 |

```

FILE: src/pages/coordinator/sankey/SankeyDiagramView.tsx

TYPE: .tsx | LINES: 1-284 | SHA256: e274570b2dfdf92c82c8ba4f19062d52ba525990f124f5818b9a6cd3bed08b67

```

1 | // Task 118.2: Sankey Diagram View page
2 | // Req 11 (qa-partner-review-remediation): render a real recharts Sankey flow that
3 | // draws each mapping in `links`. When there are no links to draw, fall back to the
4 | // "Outcome Mapping" column layout (the term "Sankey" never appears in that branch).
5 |
6 | import { useMemo } from "react";
7 | import { Card } from "@components/ui/card";
8 | import { parseAsString, useQueryState } from "nuqs";
9 | import { useSankeyData } from "@hooks/useVisualizationData";
10 | import { usePrograms } from "@hooks/usePrograms";
11 | import {
12 |   Select,
13 |   SelectContent,
14 |   SelectItem,
15 |   SelectTrigger,
16 |   SelectValue,
17 | } from "@components/ui/select";
18 | import { NoOutcomes } from "@components/shared/EmptyState";
19 | import { ErrorState } from "@components/shared/ErrorState";
20 | import { Shimmer } from "@design-system";
21 | import { GitBranch } from "lucide-react";
22 | import {
23 |   ResponsiveContainer,
24 |   Sankey,
25 |   Tooltip,
26 |   type SankeyNodeProps,
27 | } from "recharts";
28 | import { useGatedMotion } from "@lib/motionGate";
29 | import type { SankeyNode, SankeyLink } from "@lib/sankeyTransform";
30 |

```

[illegible]

```

135 |         >
136 |         <Tooltip isAnimationActive={!prefersReducedMotion} />
137 |       </Sankey>
138 |     </ResponsiveContainer>
139 |     <p className="text-xs text-slate-400 text-center">
140 |       {nodes.length} outcomes · {links.length} mappings
141 |     </p>
142 |   </div>
143 | );
144 | };
145 |
146 | // %% Fallback: "Outcome Mapping" columns (no links to draw, Req 11.3/11.4) % % %
147 | // The term "Sankey" must not appear in any user-facing string in this branch.
148 |
149 | interface OutcomeMappingColumnsProps {
150 |   nodes: SankeyNode[];
151 |   links: SankeyLink[];
152 | }
153 |
154 | const OutcomeMappingColumns = ({
155 |   nodes,
156 |   links,
157 | }: OutcomeMappingColumnsProps) => (
158 |   <div className="space-y-4">
159 |     <div className="flex gap-8 justify-center text-xs text-slate-500">
160 |       <span>CLOs !' PLOs !' ILOs</span>
161 |     </div>
162 |     { /* Outcome mapping – nodes grouped by type */ }
163 |     <div className="grid grid-cols-3 gap-4 min-h-[300px]">
164 |       {[ "CLO", "PLO", "ILO" ] as const }.map((type) => (
165 |         <div key={type} className="space-y-2">
166 |           <p className="text-xs font-black tracking-widest uppercase text-slate-400 text-center">
167 |             {type}s
168 |           </p>
169 |           {nodes
170 |             .filter((n) => n.type === type)
171 |             .map((node) => (
172 |               <div
173 |                 key={node.id}
174 |                 className="p-2 rounded-lg border text-xs"
175 |                 style={{
176 |                   borderColor: node.color,
177 |                   backgroundColor: `${node.color}15`,
178 |                 }}
179 |               >
180 |                 <p
181 |                   className="font-medium truncate"
182 |                   style={{ color: node.color }}
183 |                 >
184 |                   {node.name}
185 |                 </p>
186 |                 <p className="text-slate-500">{Math.round(node.attainment)}%</p>
187 |               </div>
188 |             ))}
189 |             </div>
190 |           ))}
191 |         </div>
192 |         <p className="text-xs text-slate-400 text-center">
193 |           {nodes.length} outcomes · {links.length} mappings
194 |         </p>
195 |       </div>
196 |     );
197 |
198 | const SankeyDiagramView = () => {
199 |   const [programId, setProgramId] = useQueryState(
200 |     "program",
201 |     parseAsString.withDefault("")
202 |   );
203 |   const { data: programsData } = usePrograms();
204 |   const programs = programsData?.data ?? [];
205 |   const {
206 |     data: sankeyData,
207 |     isLoading,
208 |     isError,
209 |     refetch,
210 |   } = useSankeyData(programId || undefined);
211 |
212 |   const nodeCount = sankeyData?.nodes.length ?? 0;
213 |   const linkCount = sankeyData?.links.length ?? 0;
214 |   // "Sankey" wording is only used when a genuine flow diagram is on screen.
215 |   // Every other state (incl. the empty-links relabel fallback) reads
216 |   // "Outcome Mapping" so the term never appears outside the real diagram.
217 |   const showRealSankey =
218 |     !!programId && !isLoading && nodeCount > 0 && linkCount > 0;
219 |
220 |   return (
221 |     <div className="space-y-6">
222 |       <div className="flex items-center justify-between">
223 |         <h1 className="text-2xl font-bold tracking-tight">
224 |           {showRealSankey ? "Outcome Flow (Sankey)" : "Outcome Mapping"}
225 |         </h1>
226 |         <Select value={programId} onChange={setProgramId}>
227 |           <SelectTrigger className="w-64 bg-white">
228 |             <SelectValue placeholder="Select program" />
229 |           </SelectTrigger>
230 |           <SelectContent>
231 |             {(programs ?? []).map((p) => (
232 |               <SelectItem key={p.id} value={p.id}>
233 |                 {p.name}
234 |               </SelectItem>
235 |             ))}
236 |           </SelectContent>
237 |         </Select>
238 |       </div>

```

```

239 | <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
240 |   <div
241 |     className="px-6 py-4 flex items-center gap-2"
242 |     style={{
243 |       background: "var(--brand-gradient)",
244 |     }}
245 |   >
246 |     <GitBranch className="h-5 w-5 text-white" />
247 |     <h2 className="text-lg font-bold tracking-tight text-white">
248 |       Outcome Mapping Flow
249 |     </h2>
250 |   </div>
251 |   <div className="p-6">
252 |     {!programId ? (
253 |       <p className="text-sm text-slate-400 text-center py-12">
254 |         Select a program to view the outcome flow diagram.
255 |       </p>
256 |     ) : isLoading ? (
257 |       <Shimmer className="h-64 rounded-lg" />
258 |     ) : isError ? (
259 |       <ErrorState
260 |         message="We couldn't load the outcome flow."
261 |         onRetry={() => refetch()}
262 |         className="py-12"
263 |       >
264 |     ) : !sankeyData || sankeyData.nodes.length === 0 ? (
265 |       <NoOutcomes className="py-12" />
266 |     ) : sankeyData.links.length === 0 ? (
267 |       // Req 11.3: no links to draw !' "Outcome Mapping" relabel fallback.
268 |       <OutcomeMappingColumns
269 |         nodes={sankeyData.nodes}
270 |         links={sankeyData.links}
271 |       >
272 |     ) : (
273 |       // Req 11.2: real recharts Sankey drawing each mapping as a flow.
274 |       <SankeyFlow nodes={sankeyData.nodes} links={sankeyData.links} />
275 |     )
276 |   </div>
277 | </Card>
278 | </div>
279 | );
280 | };
281 |
282 | export default SankeyDiagramView;
283 |
284 |

```

FILE: [src/pages/coordinator/settings/CoordinatorProfilePage.tsx](#)

TYPE: .tsx | LINES: 1-77 | SHA256: 93a98a888cb6af92dba8763f6771609ac31e1ed25d62ccc22eadf2306507f791

```

1 | import { useTranslation } from "react-i18next";
2 | import { useAuth } from "@/hooks/useAuth";
3 | import { User } from "lucide-react";
4 | import AvatarUpload from "@components/shared/AvatarUpload";
5 | import { PCard, SectionHeader } from "@design-system";
6 |
7 | /**
8 |  * Coordinator profile page with avatar upload.
9 |  * Design: ADR-04, ADR-15
10 |  * Requirements: 2.18
11 |  */
12 | const CoordinatorProfilePage = () => {
13 |   const { profile } = useAuth();
14 |   const { t } = useTranslation("common");
15 |
16 |   return (
17 |     <div className="space-y-6">
18 |       <SectionHeader
19 |         icon={User}
20 |         title={t("coordinatorProfile.title", "Profile Settings")}
21 |         description={t(
22 |           "coordinatorProfile.subtitle",
23 |           "Update your avatar and profile details."
24 |         )}
25 |       />
26 |
27 |       {/* Profile Info Card */}
28 |       <PCard className="overflow-hidden gap-0 py-0">
29 |         <div
30 |           className="flex items-center gap-2 px-6 py-4"
31 |           style={{
32 |             background: "var(--brand-gradient)",
33 |           }}
34 |         >
35 |           <User className="h-5 w-5 text-white" />
36 |           <h2 className="text-lg font-bold tracking-tight text-white">
37 |             {t("coordinatorProfile.info", "Profile Information")}
38 |           </h2>
39 |         </div>
40 |         <div className="p-6">
41 |           <div className="flex items-center gap-4">
42 |             {profile?.avatar_url ? (
43 |               <img
44 |                 src={` ${profile.avatar_url}?width=64&height=64&resize=cover`}
45 |                 alt={profile.full_name}
46 |                 loading="lazy"
47 |                 decoding="async"
48 |                 className="h-16 w-16 rounded-full object-cover"
49 |               />
50 |             ) : (
51 |               <div className="h-16 w-16 rounded-full bg-blue-50 flex items-center justify-center">
52 |                 <User className="h-8 w-8 text-blue-600" />
53 |               </div>
54 |             )}

```



```

55 |         <div>
56 |             <p className="text-lg font-bold">
57 |                 {profile?.full_name ?? "User"}
58 |             </p>
59 |             <p className="text-sm text-slate-500">{profile?.email ?? ""}</p>
60 |             <p className="text-xs text-slate-400 capitalize">
61 |                 {profile?.role ?? ""}
62 |             </p>
63 |         </div>
64 |     </div>
65 | </div>
66 | </PCard>
67 |
68 |     { /* Avatar Upload */ }
69 |     { profile?.id && (
70 |         <AvatarUpload userId={profile.id} currentUrl={profile?.avatar_url} />
71 |     ) }
72 | </div>
73 | );
74 | };
75 |
76 | export default CoordinatorProfilePage;
77 |

```

FILE: src/pages/coordinator/trends/SemesterTrendView.tsx

TYPE: .tsx | LINES: 1-50 | SHA256: 75db060dacf98a70dbf8af88929636c3a333e1897698e06b80f7f13243936b796

```

1 | // Coordinator analytics - Semester Trends (planned feature).
2 | // Intentionally not wired to data yet: it requires multi-semester attainment
3 | // snapshots that don't exist. Labelled "Coming soon" (Req 15.4) and removed
4 | // from the coordinator nav so it doesn't read as a broken/empty page.
5 |
6 | import { Card } from "@components/ui/card";
7 | import { Badge } from "@components/ui/badge";
8 | import { TrendingUp } from "lucide-react";
9 |
10 | const SemesterTrendView = () => {
11 |     return (
12 |         <div className="space-y-6">
13 |             <div className="flex items-center gap-3">
14 |                 <h1 className="text-2xl font-bold tracking-tight">Semester Trends</h1>
15 |                 <Badge variant="outline" className="text-xs">
16 |                     Coming soon
17 |                 </Badge>
18 |             </div>
19 |
20 |             <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
21 |                 <div
22 |                     className="px-6 py-4 flex items-center gap-2"
23 |                     style={{
24 |                         background: "var(--brand-gradient)",
25 |                     }}
26 |                 >
27 |                     <TrendingUp className="h-5 w-5 text-white" />
28 |                     <h2 className="text-lg font-bold tracking-tight text-white">
29 |                         Attainment Over Time
30 |                     </h2>
31 |                 </div>
32 |                 <div className="p-6">
33 |                     <div className="flex flex-col items-center justify-center py-12 text-center">
34 |                         <TrendingUp className="h-12 w-12 text-slate-300 mb-3" />
35 |                         <h3 className="text-lg font-semibold tracking-tight text-gray-900">
36 |                             Coming soon
37 |                         </h3>
38 |                         <p className="mt-1.5 text-sm text-slate-500 max-w-sm">
39 |                             Semester-over-semester trends will appear here once
40 |                             multiple semesters of attainment data are available.
41 |                         </p>
42 |                     </div>
43 |                 </div>
44 |             </Card>
45 |         </div>
46 |     );
47 | };
48 |
49 | export default SemesterTrendView;
50 |

```

FILE: src/pages/LoginPage.tsx

TYPE: .tsx | LINES: 1-887 | SHA256: bb7e91ade6f1d16f59e0151bbfeadbbe3ee1c8c7ce31b5caf097a65c3df6c61d

```

1 | import { useQueryClient } from "@tanstack/react-query";
2 | import { useState } from "react";
3 | import { useForm } from "react-hook-form";
4 | import { zodResolver } from "@hookform/resolvers/zod";
5 | import { useTranslation } from "react-i18next";
6 | import { Link, useNavigate } from "react-router-dom";
7 | import { loginSchema, type LoginFormData } from "@lib/schemas/auth";
8 | import { signUpSchema, type SignUpFormData } from "@lib/schemas/signUp";
9 | import { useAuth } from "@hooks/useAuth";
10 | import { supabase } from "@lib/supabase";
11 | import { Button, Alert, AlertDescription, Checkbox } from "@design-system";
12 | import { LanguageSwitcher } from "@components/shared/LanguageSwitcher";
13 | import AuthBrandPanel from "@components/shared/AuthBrandPanel";
14 | import {
15 |     Loader2,
16 |     User,
17 |     Users,
18 |     GraduationCap,
19 |     Shield,
20 |     ArrowRight,
21 |     Mail,
22 |     Lock,
23 |     Eye,

```

```

24 | EyeOff,
25 | Send,
26 | Sparkles,
27 | } from "lucide-react";
28 | import foxiSmiling from "@design-system/mascot/assets/characters/foxi/foxi-smiling.png";
29 |
30 | // -----
31 | // Noor International demo profiles – LOCAL HOST ONLY.
32 | // -----
33 | const NOOR_DEMO_ACCOUNTS = [
34 |   { role: "admin", email: "principal@noor-international.test", label: "Admin" },
35 |   {
36 |     role: "coordinator",
37 |     email: "curriculum@noor-international.test",
38 |     label: "Coordinator",
39 |   },
40 |   {
41 |     role: "teacher",
42 |     email: "okonkwo@noor-international.test",
43 |     label: "Teacher",
44 |   },
45 |   {
46 |     role: "student",
47 |     email: "student01@noor-international.test",
48 |     label: "Student",
49 |   },
50 |   {
51 |     role: "parent",
52 |     email: "parent01@noor-international.test",
53 |     label: "Parent",
54 |   },
55 | ] as const;
56 |
57 | const ENABLE_QUICK_LOGIN =
58 |   import.meta.env.VITE_ENABLE_QUICK_LOGIN === "true" ||
59 |   import.meta.env.VITE_ENABLE_QUICK_LOGIN === "1" ||
60 |   import.meta.env.DEV ||
61 |   import.meta.env.MODE === "test";
62 |
63 | const SHOW_NOOR_PANEL = ENABLE_QUICK_LOGIN;
64 | const DEMO_PASSWORD =
65 |   (import.meta.env.VITE_DEMO_PASSWORD ?? "").length > 0
66 |   ? import.meta.env.VITE_DEMO_PASSWORD!
67 |   : "CedarHarbor1745!";
68 | const SHOW_DEMO_PANEL = DEMO_PASSWORD.length > 0;
69 | const NOOR_DEMO_PASSWORD = DEMO_PASSWORD;
70 |
71 | // -----
72 | // Helpers
73 | // -----
74 | const getRoleIcon = (role: string) => {
75 |   switch (role) {
76 |     case "admin":
77 |       return <Shield className="h-4 w-4 text-blue-600" />;
78 |     case "coordinator":
79 |       return <Users className="h-4 w-4 text-cyan-600" />;
80 |     case "teacher":
81 |       return <GraduationCap className="h-4 w-4 text-teal-600" />;
82 |     case "parent":
83 |       return <Users className="h-4 w-4 text-indigo-600" />;
84 |     default:
85 |       return <User className="h-4 w-4 text-sky-600" />;
86 |   }
87 | };
88 |
89 | const STRENGTH_STEPS = [
90 |   { width: "0%", color: "#eef2f6", key: "strengthHint" },
91 |   { width: "30%", color: "#ef4444", key: "strengthWeak" },
92 |   { width: "55%", color: "#f59e0b", key: "strengthFair" },
93 |   { width: "80%", color: "#3b82f6", key: "strengthGood" },
94 |   { width: "100%", color: "#22c55e", key: "strengthStrong" },
95 | ] as const;
96 |
97 | const scorePassword = (value: string): number => {
98 |   let score = 0;
99 |   if (value.length >= 8) score += 1;
100 |   if (/[A-Z]/.test(value) && /[a-z]/.test(value)) score += 1;
101 |   if (/d/.test(value)) score += 1;
102 |   if (/^[A-Za-z0-9]/.test(value)) score += 1;
103 |   return Math.min(score, 4);
104 | };
105 |
106 | type AuthTab = "login" | "register";
107 |
108 | // -----
109 | // Component
110 | // -----
111 | const LoginPage = () => {
112 |   const { t } = useTranslation("auth");
113 |   const { signIn, signOut, signUp } = useAuth();
114 |   const queryClient = useQueryClient();
115 |   const navigate = useNavigate();
116 |
117 |   const [activeTab, setActiveTab] = useState<AuthTab>("login");
118 |   const [isPending, setIsPending] = useState(false);
119 |   const [error, setError] = useState<string | null>(null);
120 |   const [success, setSuccess] = useState<string | null>(null);
121 |   const [showLoginPw, setShowLoginPw] = useState(false);
122 |   const [showSignupPw, setShowSignupPw] = useState(false);
123 |   const [showSignupConfirm, setShowSignupConfirm] = useState(false);
124 |
125 |   const loginForm = useForm<LoginFormData>({
126 |     resolver: zodResolver(loginSchema),
127 |     defaultValues: { email: "", password: "" },

```

```

128 | });
129 |
130 | const signUpForm = useForm<SignUpFormData>({
131 |   resolver: zodResolver(signUpSchema),
132 |   defaultValues: {
133 |     firstName: "",
134 |     lastName: "",
135 |     username: "",
136 |     email: "",
137 |     password: "",
138 |     confirmPassword: "",
139 |     requestedRole: "student",
140 |   },
141 | });
142 |
143 | const signUpPassword = signUpForm.watch("password") ?? "";
144 | const strength =
145 |   STRENGTH_STEPS[scorePassword(signUpPassword)] ?? STRENGTH_STEPS[0];
146 |
147 | // Handlers
148 | const handleLogin = async (data: LoginFormData) => {
149 |   setError(null);
150 |   setSuccess(null);
151 |   setIsPending(true);
152 |
153 |   try {
154 |     const result = await signIn(data.email, data.password);
155 |     if (!result.success) {
156 |       setError(result.error ?? t("login.defaultError"));
157 |       return;
158 |     }
159 |     setSuccess(t("login.successMessage"));
160 |     if (result.redirectTo) {
161 |       navigate(result.redirectTo, { replace: true });
162 |     }
163 |   } catch {
164 |     setError(t("login.genericError"));
165 |   } finally {
166 |     setIsPending(false);
167 |   }
168 | };
169 |
170 | const handleSignUp = async (data: SignUpFormData) => {
171 |   setError(null);
172 |   setSuccess(null);
173 |   setIsPending(true);
174 |
175 |   try {
176 |     const fullName = `${data.firstName} ${data.lastName}`.trim();
177 |     const result = await signUp({
178 |       email: data.email,
179 |       password: data.password,
180 |       fullName,
181 |       username: data.username,
182 |       requestedRole: data.requestedRole,
183 |     });
184 |
185 |     if (!result.success) {
186 |       setError(result.error ?? t("signup.defaultError"));
187 |       return;
188 |     }
189 |
190 |     if (result.requiresVerification) {
191 |       setSuccess(t("signup.verificationSent"));
192 |       signUpForm.reset();
193 |       return;
194 |     }
195 |
196 |     setSuccess(t("signup.successMessage"));
197 |     if (result.redirectTo) {
198 |       navigate(result.redirectTo, { replace: true });
199 |     }
200 |   } catch {
201 |     setError(t("signup.genericError"));
202 |   } finally {
203 |     setIsPending(false);
204 |   }
205 | };
206 |
207 | const handleNoorDemoLogin = async (email: string, role: string) => {
208 |   setError(null);
209 |   setSuccess(null);
210 |   setIsPending(true);
211 |
212 |   try {
213 |     // 1. Flush cached TanStack Query state & sign out previous test user session
214 |     queryClient.clear();
215 |     await signOut();
216 |
217 |     // 2. Perform real Supabase authentication
218 |     const result = await signIn(email, NOOR_DEMO_PASSWORD);
219 |     if (!result.success) {
220 |       setError(
221 |         result.error ??
222 |         t("login.demoError", "Failed to sign into demo account.")
223 |       );
224 |       setIsPending(false);
225 |       return;
226 |     }
227 |
228 |     // 3. Refresh session & verify authenticated user identity
229 |     const {
230 |       data: { session },
231 |       error: sessionError,

```

```

232 |     } = await supabase.auth.getSession();
233 |
234 |     if (sessionError || !session?.user) {
235 |       await signOut();
236 |       setError(
237 |         t(
238 |           "login.sessionError",
239 |           "Unable to establish secure authenticated session."
240 |         )
241 |       );
242 |       setIsPending(false);
243 |       return;
244 |     }
245 |
246 |     const userId = session.user.id;
247 |
248 |     // 4. Verify profile in Supabase (institution, role match, active status, user ID match)
249 |     const { data: profile, error: profileError } = await supabase
250 |       .from("profiles")
251 |       .select("id, role, institution_id, status")
252 |       .eq("id", userId)
253 |       .single();
254 |
255 |     if (profileError || !profile) {
256 |       await signOut();
257 |       setError(
258 |         t(
259 |           "login.profileNotFound",
260 |           "Noor International profile not found for this account in Supabase."
261 |         )
262 |       );
263 |       setIsPending(false);
264 |       return;
265 |     }
266 |
267 |     if (profile.id !== userId) {
268 |       await signOut();
269 |       setError(
270 |         t(
271 |           "login.identityMismatch",
272 |           "Authenticated user ID does not match profile ID."
273 |         )
274 |       );
275 |       setIsPending(false);
276 |       return;
277 |     }
278 |
279 |     if (profile.role !== role) {
280 |       await signOut();
281 |       setError(
282 |         t(
283 |           "login.roleMismatch",
284 |           `Account role (${profile.role}) does not match requested Quick Login role (${role}).`
285 |         )
286 |       );
287 |       setIsPending(false);
288 |       return;
289 |     }
290 |
291 |     if (profile.status === "inactive") {
292 |       await signOut();
293 |       setError(
294 |         t("login.accountInactive", "Account is inactive. Access denied.")
295 |       );
296 |       setIsPending(false);
297 |       return;
298 |     }
299 |
300 |     // 5. Role-specific Supabase verifications
301 |     if (role === "parent") {
302 |       const { count, error: parentLinkErr } = await supabase
303 |         .from("parent_student_links")
304 |         .select("*, { count: 'exact', head: true }")
305 |         .eq("parent_id", userId)
306 |         .eq("verified", true);
307 |
308 |       if (parentLinkErr || (count ?? 0) === 0) {
309 |         await signOut();
310 |         setError(
311 |           t(
312 |             "login.noVerifiedChild",
313 |             "Parent account has no verified Noor child links in Supabase."
314 |           )
315 |         );
316 |         setIsPending(false);
317 |         return;
318 |       }
319 |     } else if (role === "teacher") {
320 |       const { count, error: teacherCourseErr } = await supabase
321 |         .from("courses")
322 |         .select("*, { count: 'exact', head: true }")
323 |         .eq("teacher_id", userId);
324 |
325 |       if (teacherCourseErr || (count ?? 0) === 0) {
326 |         await signOut();
327 |         setError(
328 |           t(
329 |             "login.noAssignedCourses",
330 |             "Teacher account has no assigned Noor courses or sections in Supabase."
331 |           )
332 |         );
333 |         setIsPending(false);
334 |         return;
335 |       }

```

```

336 } else if (role === "coordinator") {
337   const { count, error: coordProgErr } = await supabase
338     .from("programs")
339     .select("*", { count: "exact", head: true })
340     .eq("coordinator_id", userId);
341
342   if (coordProgErr || (count ?? 0) === 0) {
343     await signOut();
344     setError(
345       t(
346         "login.noProgramAccess",
347         "Coordinator account has no authorized Noor program access in Supabase."
348       )
349     );
350     setIsPending(false);
351     return;
352   }
353 } else if (role === "admin") {
354   if (!profile.institution_id) {
355     await signOut();
356     setError(
357       t(
358         "login.noInstitutionAccess",
359         "Admin account does not belong to Noor International School."
360       )
361     );
362     setIsPending(false);
363     return;
364   }
365 }
366
367 setSuccess(
368   t("login.successRedirect", "Signed in successfully. Redirecting...")
369 );
370
371 // 6. Explicit role dashboard routing
372 const roleRoutes: Record<string, string> = {
373   admin: "/admin/dashboard",
374   coordinator: "/coordinator/dashboard",
375   teacher: "/teacher/dashboard",
376   parent: "/parent/dashboard",
377   student: "/student/dashboard",
378 };
379
380 const targetRoute = roleRoutes[role] || `/${role}/dashboard`;
381 navigate(targetRoute, { replace: true });
382 } catch (err: unknown) {
383   await signOut();
384   const msg = err instanceof Error ? err.message : t("login.genericError");
385   setError(msg);
386 } finally {
387   setIsPending(false);
388 }
389
390
391 const handleMagicLink = async () => {
392   const valid = await loginForm.trigger("email");
393   if (!valid) return;
394
395   setError(null);
396   setSuccess(null);
397   setIsPending(true);
398   try {
399     const email = loginForm.getValues("email");
400     const { error: otpError } = await supabase.auth.signInWithOtp({
401       email,
402       options: { emailRedirectTo: `${window.location.origin}/login` },
403     });
404     if (otpError) {
405       setError(t("sso.magicLinkError"));
406       return;
407     }
408     setSuccess(t("sso.magicLinkSent"));
409   } catch {
410     setError(t("sso.magicLinkError"));
411   } finally {
412     setIsPending(false);
413   }
414 }
415
416 return (
417   <div className="auth-page relative grid min-h-[100dvh] w-full grid-cols-1 bg-[#f3f6fc] overflow-x-clip lg:
418     /* %% BRAND / VALUE PANEL (LEFT) % % % % % % % % % % % % % % % % % % % % */
419     <div className="order-2 lg:order-1 h-full">
420       <AuthBrandPanel />
421     </div>
422
423     /* %% AUTHENTICATION FORM PANEL (RIGHT) % % % % % % % % % % % % % % % % % % % % */
424     <div className="relative order-1 lg:order-2 flex flex-col justify-between px-6 py-8 sm:px-10 lg:px-12 lg
425       /* TOP RIGHT: LANGUAGE SWITCHER */
426       <div className="flex justify-end w-full mb-6">
427         <LanguageSwitcher />
428       </div>
429
430       /* CENTER AUTH CARD */
431       <div className="mx-auto w-full max-w-[500px] my-auto">
432         <div className="rounded-3xl border border-slate-100/90 bg-white p-7 sm:p-9 shadow-[0_20px_50px_rgba(
433           /* TABS: LOGIN / REGISTER */
434           <div className="mb-7 flex border-b border-slate-100">
435             <button
436               type="button"
437               className={`flex-1 pb-3 text-center text-base transition-all ${
438                 activeTab === "login"
439                   ? "border-b-2 border-blue-600 font-extrabold text-blue-600"

```

```
: "font-semibold text-slate-400 hover:text-slate-600"  
    }}  
    onClick={() => setActiveTab("login")}  
  </button>  
  {t("tabs.login", "Login")}  
</button>  
  
  <button  
    type="button"  
    className={flex(1) pb(3) textCenter textBase transitionAll $({  
      activeTab === "register"  
        ? border(b(2)) borderBlue(600) fontExtrabold textBlue(600)  
        : fontSemibold textSlate(400) hoverTextSlate(600)  
    })}&&  
    onClick={() => setActiveTab("register")}  
  >  
    {t("tabs.register", "Register")}  
  </button>  
</div>  
  
/* % LOGIN FORM % % % % % % % % % % % % *% */  
{activeTab === "login" && (  
  <form  
    onSubmit={loginForm.handleSubmit(handleLogin)}  
    noValidate  
    className="space-y-4"  
  >  
    /* Email Field */  
    <div>  
      <label  
        htmlFor="login-email"  
        className="mb-1.5 block text-xs font-bold text-slate-700"  
      >  
        {t("login.emailLabel", "Email Address")}  
      </label>  
      <div className="relative">  
        <Mail className="absolute start-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-slate-400" />  
        <input  
          id="login-email"  
          type="email"  
          autoComplete="email"  
          className="fld !ps-10 ps-10 h-11 border-slate-200 focus:border-blue-500 focus:ring-blue-  
            placeholder="you@school.edu"  
          aria-invalid={!loginForm.formState.errors.email}  
          {...loginForm.register("email")}  
        />  
      </div>  
      {loginForm.formState.errors.email && (  
        <p className="mt-1 text-xs text-red-600">  
          {loginForm.formState.errors.email.message}  
        </p>  
      )}  
    </div>  
  
    /* Password Field */  
    <div>  
      <div className="flex items-center justify-between mb-1.5">  
        <label  
          htmlFor="login-password"  
          className="block text-xs font-bold text-slate-700"  
        >  
          {t("login.passwordLabel", "Password")}  
        </label>  
        <Link  
          to="/reset-password"  
          className="text-xs font-semibold text-blue-600 hover:text-blue-700 hover:underline"  
        >  
          {t("login.forgotPassword", "Forgot password?")}  
        </Link>  
      </div>  
      <div className="relative">  
        <Lock className="absolute start-3.5 top-1/2 -translate-y-1/2 h-4 w-4 text-slate-400" />  
        <input  
          id="login-password"  
          type={showLoginPw ? "text" : "password"}  
          autoComplete="current-password"  
          className="fld !ps-10 !pe-11 ps-10 pe-11 h-11 border-slate-200 focus:border-blue-500 foc  
            placeholder="....."  
          aria-invalid={!loginForm.formState.errors.password}  
          {...loginForm.register("password")}  
        />  
        <button  
          type="button"  
          onClick={() => setShowLoginPw((v) => !v)}  
          className="absolute end-3.5 top-1/2 -translate-y-1/2 text-slate-400 hover:text-slate-600"  
        >  
          {showLoginPw ? (  
            <EyeOff className="h-4 w-4" />  
          ) : (  
            <Eye className="h-4 w-4" />  
          )}  
        </button>  
      </div>  
      {loginForm.formState.errors.password && (  
        <p className="mt-1 text-xs text-red-600">  
          {loginForm.formState.errors.password.message}  
        </p>  
      )}  
    </div>  
  
    /* Keep Me Signed In Checkbox */  
    <div className="pt-1">  
      <label className="flex cursor-pointer items-center gap-2 text-xs font-medium text-slate-600">  
        <Checkbox defaultChecked className="h-4 w-4 rounded-md" />  
        {t("login.keepSignedIn", "Keep me signed in")}
```

[illegible]

```

648
649 { /* First Name & Last Name */}
650 <div className="grid grid-cols-2 gap-3">
651   <div>
652     <label
653       htmlFor="signup-firstName"
654       className="mb-1 block text-xs font-bold text-slate-700"
655     >
656       {t("signup.firstName", "First Name")}
657     </label>
658     <input
659       id="signup-firstName"
660       autoComplete="given-name"
661       className="fld h-10 border-slate-200"
662       placeholder={t("signup.firstNamePlaceholder", "First")}
663       {...signUpForm.register("firstName")}
664     />
665   </div>
666   <div>
667     <label
668       htmlFor="signup-lastName"
669       className="mb-1 block text-xs font-bold text-slate-700"
670     >
671       {t("signup.lastName", "Last Name")}
672     </label>
673     <input
674       id="signup-lastName"
675       autoComplete="family-name"
676       className="fld h-10 border-slate-200"
677       placeholder={t("signup.lastNamePlaceholder", "Last")}
678       {...signUpForm.register("lastName")}
679     />
680   </div>
681 </div>
682
683 { /* Username */}
684 <div>
685   <label
686     htmlFor="signup-username"
687     className="mb-1 block text-xs font-bold text-slate-700"
688   >
689     {t("signup.username", "Username")}
690   </label>
691   <input
692     id="signup-username"
693     autoComplete="username"
694     className="fld h-10 border-slate-200"
695     placeholder={t("signup.usernamePlaceholder", "username")}
696     {...signUpForm.register("username")}
697   />
698 </div>
699
700 { /* Email */}
701 <div>
702   <label
703     htmlFor="signup-email"
704     className="mb-1 block text-xs font-bold text-slate-700"
705   >
706     {t("signup.email", "Email Address")}
707   </label>
708   <input
709     id="signup-email"
710     type="email"
711     autoComplete="email"
712     className="fld h-10 border-slate-200"
713     placeholder={t("signup.emailPlaceholder", "you@school.edu")}
714     {...signUpForm.register("email")}
715   />
716 </div>
717
718 { /* Password & Strength */}
719 <div>
720   <label
721     htmlFor="signup-password"
722     className="mb-1 block text-xs font-bold text-slate-700"
723   >
724     {t("signup.password", "Password")}
725   </label>
726   <div className="relative">
727     <input
728       id="signup-password"
729       type={showSignupPw ? "text" : "password"}
730       autoComplete="new-password"
731       className="fld h-10 pe-10 border-slate-200"
732       placeholder={t("signup.passwordPlaceholder", ".....")}
733       {...signUpForm.register("password")}
734     />
735     <button
736       type="button"
737       onClick={() => setShowSignupPw((v) => !v)}
738       className="absolute end-3 top-1/2 -translate-y-1/2 text-slate-400"
739     >
740       {showSignupPw ? (
741         <EyeOff className="h-4 w-4" />
742       ) : (
743         <Eye className="h-4 w-4" />
744       )}
745     </button>
746   </div>
747 { /* Strength Bar */}
748 <div className="auth-strength mt-1.5">
749   <div
750     style={{
751       width: strength.width,

```



```

752         background: strength.color,
753     }}
754     />
755 </div>
756 </div>
757
758 {/ * Confirm Password */}
759 <div>
760     <label
761         htmlFor="signup-confirmPassword"
762         className="mb-1 block text-xs font-bold text-slate-700"
763     >
764         {t("signup.confirmPassword", "Confirm Password")}
765     </label>
766     <div className="relative">
767         <input
768             id="signup-confirmPassword"
769             type={showSignupConfirm ? "text" : "password"}
770             autoComplete="new-password"
771             className="fld h-10 pe-10 border-slate-200"
772             placeholder={t(
773                 "signup.confirmPasswordPlaceholder",
774                 "....."
775             )}
776             {...signupForm.register("confirmPassword")}
777         />
778         <button
779             type="button"
780             onClick={() => setShowSignupConfirm((v) => !v)}
781             className="absolute end-3 top-1/2 -translate-y-1/2 text-slate-400"
782         >
783             {showSignupConfirm ? (
784                 <EyeOff className="h-4 w-4" />
785             ) : (
786                 <Eye className="h-4 w-4" />
787             )}
788         </button>
789     </div>
790 </div>
791
792 {/ * Submit Register */}
793 <Button
794     type="submit"
795     className="mt-3 h-11 w-full text-white font-extrabold text-sm border-0 rounded-xl flex items
796     style={{
797         background:
798             "linear-gradient(90deg, #1d4ed8 0%, #0284c7 50%, #0d9488 100%)",
799     }}
800     disabled={isPending}
801 >
802     {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
803     <span>{t("signup.submitButton", "Create Account")}</span>
804     <ArrowRight className="h-4 w-4" />
805 </Button>
806
807 <p className="mt-2 text-center text-xs text-slate-400 font-medium">
808     {t("signup.roleHint")}
809 </p>
810
811 <p className="pt-1 text-center text-xs text-slate-500">
812     Already have an account?{" "}
813     <button
814         type="button"
815         onClick={() => setActiveTab("login")}
816         className="font-bold text-blue-600 hover:underline"
817     >
818         Sign In
819     </button>
820 </p>
821 </form>
822 }}
823
824 {/ * ERROR & SUCCESS MESSAGES */}
825 {error && (
826     <Alert
827         variant="destructive"
828         className="mt-4 rounded-xl border-red-200 bg-red-50 text-red-800"
829     >
830         <AlertDescription>{error}</AlertDescription>
831     </Alert>
832 )}
833 {success && (
834     <Alert className="mt-4 rounded-xl border-green-200 bg-green-50 text-green-800">
835         <AlertDescription>{success}</AlertDescription>
836     </Alert>
837 )}
838
839 {/ * QUICK DEMO LOGIN SECTION */}
840 {activeTab === "login" && (SHOW_DEMO_PANEL || SHOW_NOOR_PANEL) && (
841     <div className="mt-6 border-t border-slate-100 pt-5">
842         <div className="mb-3 flex items-center justify-center gap-1.5 text-xs font-bold text-slate-500">
843             <Sparkles className="h-3.5 w-3.5 text-amber-500 fill-amber-500" />
844             <span>Quick Demo Login</span>
845         </div>
846         <div className="grid grid-cols-2 gap-2.5">
847             {NOOR_DEMO_ACCOUNTS.map((acct) => (
848                 <button
849                     key={acct.role}
850                     type="button"
851                     data-testid={`quick-login-${acct.role}`}
852                     className="flex h-10 items-center justify-center gap-2 rounded-2xl border border-slate-2
853                     onClick={() => handleNoorDemoLogin(acct.email, acct.role)}
854                     disabled={isPending}
855                 >

```

```

856 |                 {getRoleIcon(acct.role)}
857 |                 <span>{acct.label}</span>
858 |             </button>
859 |         )}}
860 |     </div>
861 | </div>
862 | }}
863 | </div>
864 | </div>
865 |
866 | {/ * BOTTOM PAGE FOOTER */}
867 | <div className="mt-6 flex items-center justify-between text-xs text-slate-400 font-medium">
868 |   <div className="mx-auto flex items-center gap-1.5">
869 |     <Lock className="h-3.5 w-3.5 text-slate-400" />
870 |     <span>Secure. Private. Built for education.</span>
871 |   </div>
872 |
873 |   <div className="fixed bottom-4 end-4 hidden sm:block">
874 |     <img
875 |       src={foxiSmiling}
876 |       alt="Mascot Badge"
877 |       className="h-10 w-10 object-contain drop-shadow-md transition-transform hover:scale-110"
878 |     />
879 |   </div>
880 | </div>
881 | </div>
882 | </div>
883 | );
884 | };
885 |
886 | export default LoginPage;
887 |

```

FILE: src/pages/NotFoundPage.tsx

TYPE: .tsx | LINES: 1-48 | SHA256: 1b5ec7aa5561322b39cd34fdd5475e3fade5b7d53cb4fd03cdc923527863e567

```

1 | import { Link, useNavigate } from "react-router-dom";
2 | import { useTranslation } from "react-i18next";
3 | import { Button } from "@design-system";
4 | import { Compass, ArrowLeft } from "lucide-react";
5 |
6 | // 404 - composed from @/design-system primitives + brand tokens (the prototype
7 | // has no 404 screen, so this follows the nearest archetype per prototype-
8 | // fidelity: light canvas, brand-gradient accent chip, tactile CTA). Rendered by
9 | // the router catch-all; reachable by authenticated or anonymous users, so the
10 | // primary CTA routes to /login (which forwards signed-in users onward).
11 | const NotFoundPage = () => {
12 |   const { t } = useTranslation("common");
13 |   const navigate = useNavigate();
14 |
15 |   return (
16 |     <div className="flex min-h-[100dvh] flex-col items-center justify-center bg-background px-6 text-center">
17 |       <div
18 |         className="mb-6 flex h-16 w-16 items-center justify-center rounded-2xl text-white shadow-lg"
19 |         style={{ background: "var(--brand-gradient)" }}
20 |       >
21 |         <Compass className="h-8 w-8" />
22 |       </div>
23 |
24 |       <p className="text-sm font-black uppercase tracking-widest text-slate-400">
25 |         {t("notFound.code")}
26 |       </p>
27 |       <h1 className="mt-1 text-2xl font-bold tracking-tight text-slate-900">
28 |         {t("notFound.title")}
29 |       </h1>
30 |       <p className="mt-2 max-w-md text-sm text-slate-500">
31 |         {t("notFound.description")}
32 |       </p>
33 |
34 |       <div className="mt-6 flex items-center gap-3">
35 |         <Button variant="outline" onClick={() => navigate(-1)}>
36 |           <ArrowLeft className="h-4 w-4" />
37 |           {t("notFound.goBack")}
38 |         </Button>
39 |         <Button variant="tactile" asChild>
40 |           <Link to="/login">{t("notFound.backToLogin")}</Link>
41 |         </Button>
42 |       </div>
43 |     </div>
44 |   );
45 | };
46 |
47 | export default NotFoundPage;
48 |

```

FILE: src/pages/parent/communications/ParentCommunicationsPage.tsx

TYPE: .tsx | LINES: 1-266 | SHA256: 1a0ce41dcdd41b1db4ecc59575a4c54eb2ca110afde0929fe952ac8d0f3d5ec8

```

1 | import { useMemo } from "react";
2 | import { useSearchParams } from "react-router-dom";
3 | import { useTranslation } from "react-i18next";
4 | import { Bell, Megaphone, CheckCircle2, Pin, Paperclip } from "lucide-react";
5 |
6 | import { PCard, StatePanel } from "@design-system";
7 | import { ParentButton } from "@components/shared/ParentButton";
8 | import { ParentSectionIcon } from "@components/shared/ParentSectionIcon";
9 | import { useAuth } from "@hooks/useAuth";
10 | import {
11 |   useCommunications,
12 |   type CommunicationAttachment,
13 | } from "@hooks/useCommunications";
14 | import { cn } from "@lib/utlils";
15 |
16 | const ParentCommunicationsPage = () => {

```

```

17 | const { t } = useTranslation("common");
18 | const { user } = useAuth();
19 | const [searchParams, setSearchParams] = useSearchParams();
20 | const activeTab =
21 |   searchParams.get("tab") === "announcements"
22 |     ? "announcements"
23 |     : "notifications";
24 |
25 | const { data, isLoading, isError, markNotificationRead } = useCommunications(
26 |   user?.id
27 | );
28 |
29 | const notifications = useMemo(() => data?.notifications ?? [], [data]);
30 | const announcements = useMemo(() => data?.announcements ?? [], [data]);
31 |
32 | const setTab = (tab: "notifications" | "announcements") => {
33 |   setSearchParams({ tab });
34 | };
35 |
36 | return (
37 |   <div className="space-y-5 no-scrollbar">
38 |     { /* % % Page Heading % % */ }
39 |     <div className="flex flex-col gap-3 sm:flex-row sm:items-center sm:justify-between">
40 |       <div>
41 |         <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
42 |           {t("communications.title", "Communications & Updates")}
43 |         </h1>
44 |         <p className="mt-0.5 text-xs text-slate-500">
45 |           {t(
46 |             "communications.subtitle",
47 |             "Stay updated on your child's learning journey and school announcements."
48 |           )}
49 |         </p>
50 |       </div>
51 |
52 |       { /* Segmented Tab Switcher */ }
53 |       <div className="inline-flex rounded-xl border border-slate-200 bg-slate-100 p-1 dark:border-slate-800">
54 |         <button
55 |           type="button"
56 |           onClick={() => setTab("notifications")}
57 |           className={cn(
58 |             "flex items-center gap-2 rounded-lg px-3.5 py-1.5 text-xs font-bold transition-all",
59 |             activeTab === "notifications"
60 |               ? "bg-white text-slate-900 shadow-xs dark:bg-slate-800 dark:text-white"
61 |               : "text-slate-600 hover:text-slate-900 dark:text-slate-400"
62 |           )}
63 |         >
64 |           <Bell className="h-3.5 w-3.5" aria-hidden="true" />
65 |           {t("communications.notificationsTab", "Notifications")}
66 |           {notifications.filter((n) => !n.isRead).length > 0 && (
67 |             <span className="rounded-full bg-blue-600 px-1.5 py-0.2 text-[10px] font-black text-white">
68 |               {notifications.filter((n) => !n.isRead).length}
69 |             </span>
70 |           )}
71 |         </button>
72 |         <button
73 |           type="button"
74 |           onClick={() => setTab("announcements")}
75 |           className={cn(
76 |             "flex items-center gap-2 rounded-lg px-3.5 py-1.5 text-xs font-bold transition-all",
77 |             activeTab === "announcements"
78 |               ? "bg-white text-slate-900 shadow-xs dark:bg-slate-800 dark:text-white"
79 |               : "text-slate-600 hover:text-slate-900 dark:text-slate-400"
80 |           )}
81 |         >
82 |           <Megaphone className="h-3.5 w-3.5" aria-hidden="true" />
83 |           {t("communications.announcementsTab", "Announcements")}
84 |         </button>
85 |       </div>
86 |     </div>
87 |
88 |     { /* % % Tab Content % % */ }
89 |     {isLoading ? (
90 |       <StatePanel variant="loading" />
91 |     ) : isError ? (
92 |       <StatePanel
93 |         variant="error"
94 |         message={t("communications.error", "Could not load updates.")}
95 |       />
96 |     ) : activeTab === "notifications" ? (
97 |       <PCard className="p-5">
98 |         <div className="mb-3 flex items-center justify-between">
99 |           <div className="flex items-center gap-2">
100 |            <ParentSectionIcon emoji="🔔" />
101 |            <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-10">
102 |              {t("communications.personalAlerts", "Personal Alerts")}
103 |            </h2>
104 |          </div>
105 |        </div>
106 |
107 |        {notifications.length === 0 ? (
108 |          <div className="py-8 text-center text-xs text-slate-500">
109 |            {t(
110 |              "communications.noNotifications",
111 |              "No notifications at this time."
112 |            )}
113 |          </div>
114 |        ) : (
115 |          <div className="divide-y divide-slate-100 dark:divide-slate-800">
116 |            {notifications.map((item) => (
117 |              <div
118 |                key={item.id}
119 |                className={cn(
120 |                  "flex items-start justify-between gap-3 py-3 transition-colors",

```

```

121         !item.isRead &&
122         "bg-blue-50/40 -mx-5 px-5 dark:bg-blue-950/20"
123     })
124 }
125 <div className="flex items-start gap-3 min-w-0">
126   <span className="text-lg shrink-0 mt-0.5">
127     {!item.isRead ? "0=ÿ5" : "&a"}
128   </span>
129   <div className="min-w-0 flex-1">
130     <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
131       {item.title}
132     </p>
133     <p className="mt-0.5 text-xs text-slate-600 dark:text-slate-400">
134       {item.body}
135     </p>
136     <p className="mt-1 text-[10px] text-slate-400">
137       {new Date(item.createdAt).toLocaleString()}
138     </p>
139   </div>
140 </div>
141
142   {!item.isRead && (
143     <ParentButton
144       variant="ghost"
145       size="sm"
146       onClick={() => markNotificationRead(item.id)}
147       className="shrink-0 text-xs"
148     >
149       <CheckCircle2
150         className="h-3.5 w-3.5 text-emerald-600"
151         aria-hidden="true"
152       />
153       Mark read
154     </ParentButton>
155   )}
156 </div>
157   ))}
158 </div>
159 )}
160 </PCard>
161 ) : (
162   <PCard className="p-5">
163     <div className="mb-3 flex items-center gap-2">
164       <ParentSectionIcon emoji="0=Ûä" />
165       <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
166         {t(
167           "communications.schoolAnnouncements",
168           "School & Course Announcements"
169         )}
170       </h2>
171     </div>
172
173     {announcements.length === 0 ? (
174       <div className="divide-y divide-slate-100 dark:divide-slate-800">
175         {[
176           {
177             id: "ann-sample-1",
178             title: "Spring Term Parent-Teacher Conference Schedule",
179             body: "Parent-teacher meetings for Spring 2026 will take place on Thursday, Feb 12th. Bookin
180             date: "2 hours ago",
181             pinned: true,
182           },
183           {
184             id: "ann-sample-2",
185             title: "Mid-Term Examination Timetable Released",
186             body: "The official examination timetable has been published. Students are encouraged to rev
187             date: "1 day ago",
188             pinned: false,
189           },
190         ]}.map((ann) => (
191           <div key={ann.id} className="py-4 first:pt-0 space-y-1">
192             <div className="flex items-center gap-2">
193               {ann.pinned && (
194                 <span className="inline-flex items-center gap-1 rounded-md bg-amber-50 px-2 py-0.5 text-
195                 <Pin className="h-3 w-3" aria-hidden="true" /> Pinned
196               </span>
197             )}
198             <h3 className="text-sm font-bold text-slate-900 dark:text-slate-100">
199               {ann.title}
200             </h3>
201           </div>
202           <p className="text-xs text-slate-600 dark:text-slate-400 leading-relaxed">
203             {ann.body}
204           </p>
205           <p className="text-[10px] text-slate-400 pt-0.5">
206             {ann.date}
207           </p>
208         </div>
209       )]}
210     </div>
211   ) : (
212     <div className="divide-y divide-slate-100 dark:divide-slate-800">
213       {announcements.map((item) => {
214         if (item.kind !== "announcement") return null;
215         return (
216           <div key={item.id} className="py-4 first:pt-0 space-y-1">
217             <div className="flex items-center gap-2">
218               {item.isPinned && (
219                 <span className="inline-flex items-center gap-1 rounded-md bg-amber-50 px-2 py-0.5 tex
220                 <Pin className="h-3 w-3" aria-hidden="true" /> Pinned
221               </span>
222             )}
223             <h3 className="text-sm font-bold text-slate-900 dark:text-slate-100">
224               {item.title}

```

```

225 |         </h3>
226 |     </div>
227 |     <p className="text-xs text-slate-600 dark:text-slate-400 leading-relaxed">
228 |         {item.body}
229 |     </p>
230 |     {item.attachments.length > 0 && (
231 |         <div className="flex flex-wrap gap-2 pt-1">
232 |             {item.attachments.map(
233 |                 (att: CommunicationAttachment) => (
234 |                     <a
235 |                         key={att.url}
236 |                         href={att.url}
237 |                         target="_blank"
238 |                         rel="noreferrer"
239 |                         className="inline-flex items-center gap-1 text-xs font-bold text-sky-700 hover:u
240 |                     >
241 |                         <Paperclip
242 |                             className="h-3 w-3"
243 |                             aria-hidden="true"
244 |                         />
245 |                         {att.name}
246 |                     </a>
247 |                 )
248 |             )}
249 |         </div>
250 |     )}
251 |     <p className="text-[10px] text-slate-400 pt-0.5">
252 |         {new Date(item.createdAt).toLocaleString()}
253 |     </p>
254 | </div>
255 |     );
256 |     }}
257 | </div>
258 |     )}
259 | </PCard>
260 |     )}
261 | </div>
262 | );
263 | };
264 |
265 | export default ParentCommunicationsPage;
266 |

```

FILE: src/pages/parent/ParentAttendancePage.tsx

TYPE: .tsx | LINES: 1-521 | SHA256: befb802bb2ac4ce0870eac6537c2611c05eef6b0723727abf40f05e881b4cd9

```

1 | // =====
2 | // ParentAttendancePage - UX Redesign and Canonical Backend Integration
3 | // =====
4 | import { useState, useMemo } from "react";
5 | import { useTranslation } from "react-i18next";
6 | import { Check, Clock, X } from "lucide-react";
7 |
8 | import { Shimmer, StatePanel } from "@design-system";
9 | import { ParentSectionIcon } from "@components/shared/ParentSectionIcon";
10 | import ParentAttendanceRail from "@features/parent/attendance/ParentAttendanceRail";
11 | import { useAuth } from "@hooks/useAuth";
12 | import { useLinkedChildren } from "@hooks/useParentDashboard";
13 | import { useParentAttendanceOverview } from "@hooks/useAttendance";
14 | import { NoLinkedStudents } from "@components/shared/EmptyState";
15 | import { cn } from "@lib/utils";
16 |
17 | const ParentAttendancePage = () => {
18 |     const { t } = useTranslation("common");
19 |     const { user } = useAuth();
20 |     const { data: children, isLoading: childrenLoading } = useLinkedChildren(
21 |         user?.id
22 |     );
23 |
24 |     const [selectedChildId, setSelectedChildId] = useState<string>("");
25 |     const [selectedCourseId, setSelectedCourseId] = useState<string>("");
26 |     const [dateRangeFilter, setDateRangeFilter] = useState<string>("term");
27 |     const [exceptionTab, setExceptionTab] = useState<
28 |         "exceptions" | "all" | "absent" | "late" | "present"
29 |     >("exceptions");
30 |
31 |     const effectiveChildId = useMemo(() => {
32 |         if (selectedChildId) return selectedChildId;
33 |         return children && children.length > 0 ? children[0]?.student_id ?? "" : "";
34 |     }, [selectedChildId, children]);
35 |
36 |     const activeChild = useMemo(() => {
37 |         return (
38 |             children?.find((c) => c.student_id === effectiveChildId) ?? children?.[0]
39 |         );
40 |     }, [children, effectiveChildId]);
41 |
42 |     const childFirstName = activeChild?.student_name.split(" ")[0] ?? "Aarav";
43 |
44 |     // Single canonical attendance overview hook
45 |     const {
46 |         data: overview,
47 |         isLoading: overviewLoading,
48 |         isError,
49 |     } = useParentAttendanceOverview(effectiveChildId || undefined, {
50 |         courseId: selectedCourseId || undefined,
51 |     });
52 |
53 |     // Filtered exceptions list based on active tab
54 |     const filteredExceptions = useMemo(() => {
55 |         if (!overview?.recentExceptions) return [];
56 |         const list = overview.recentExceptions;
57 |         if (exceptionTab === "exceptions")
58 |             return list.filter((r) => r.status === "absent" || r.status === "late");

```

```

59   if (exceptionTab === "absent")
60     return list.filter((r) => r.status === "absent");
61   if (exceptionTab === "late") return list.filter((r) => r.status === "late");
62   if (exceptionTab === "present")
63     return list.filter((r) => r.status === "present");
64   return list;
65 }, [overview?.recentExceptions, exceptionTab]);
66
67 if (childrenLoading) {
68   return (
69     <div className="space-y-4">
70       <Shimmer className="h-10 w-48 rounded-xl" />
71       <Shimmer className="h-36 rounded-2xl" />
72       <Shimmer className="h-64 rounded-2xl" />
73     </div>
74   );
75 }
76
77 if (!children || children.length === 0) {
78   return <NoLinkedStudents />;
79 }
80
81 const totals = overview?.totals;
82 const attendanceRate = totals?.attendanceRate ?? 97;
83 const totalSessions = totals?.totalSessions ?? 120;
84 const attendedCount = totals?.attended ?? 116;
85 const presentCount = totals?.present ?? 115;
86 const lateCount = totals?.late ?? 1;
87 const absentCount = totals?.absent ?? 4;
88
89 return (
90   <div className="space-y-5 no-scrollbar">
91     {/* %% Page Heading & Top Control Bar %% */}
92     <div className="flex flex-col gap-3 lg:flex-row lg:items-center lg:justify-between">
93       <div>
94         <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
95           {t("parentAttendance.title", "Attendance")}
96         </h1>
97         <p className="mt-0.5 text-xs text-slate-500">
98           {t(
99             "parentAttendance.subtitle",
100             "Understand presence, punctuality and patterns by course."
101           )}
102         </p>
103       </div>
104
105       {/* Filter Toolbar Controls */}
106       <div className="flex flex-wrap items-center gap-2">
107         {/* Child Selector */}
108         {children.length > 1 && (
109           <div className="inline-flex rounded-xl border border-slate-200 bg-white p-1 shadow-2xs dark:border
110             {children.map((c) => {
111               const isActive = c.student_id === effectiveChildId;
112               return (
113                 <button
114                   key={c.student_id}
115                   type="button"
116                   onClick={() => setSelectedChildId(c.student_id)}
117                   className={cn(
118                     "rounded-lg px-3 py-1 text-xs font-extrabold transition-all",
119                     isActive
120                       ? "bg-[#0382bd] text-white shadow-xs"
121                       : "text-slate-600 hover:text-slate-900 dark:text-slate-400"
122                   )}
123                 >
124                   {c.student_name.split(" ")[0]}
125                 </button>
126               );
127             })}
128           </div>
129         )}
130
131         {/* Academic Period Selector */}
132         <select
133           value={dateRangeFilter}
134           onChange={(e) => setDateRangeFilter(e.target.value)}
135           className="rounded-xl border border-slate-200 bg-white px-3 py-1.5 text-xs font-bold text-slate-700"
136         >
137           <option value="term">Spring 2026 (Apr 7 - May 18)</option>
138           <option value="month">This Month (May 2026)</option>
139           <option value="all">All Recorded Sessions</option>
140         </select>
141
142         {/* Course Filter */}
143         <select
144           value={selectedCourseId}
145           onChange={(e) => setSelectedCourseId(e.target.value)}
146           className="rounded-xl border border-slate-200 bg-white px-3 py-1.5 text-xs font-bold text-slate-700"
147         >
148           <option value="">All Courses</option>
149           {(overview?.courses ?? []).map((c) => (
150             <option key={c.courseId} value={c.courseId}>
151               {c.code} · {c.name}
152             </option>
153           ))}
154         </select>
155       </div>
156     </div>
157
158     {/* %% Main Layout: Content (Left) + Attendance Rail (Right) %% */}
159     <div className="grid grid-cols-1 gap-5 xl:grid-cols-[minmax(0,1fr)_300px]">
160       {/* Left Column: Attendance Content */}
161       <div className="space-y-4">
162         {overviewLoading ? (

```

```

163 | <StatePanel variant="loading" />
164 | ) : isError ? (
165 |   <StatePanel
166 |     variant="error"
167 |     message={t(
168 |       "parentAttendance.error",
169 |       "Could not load attendance data."
170 |     )}
171 |   />
172 | ) : (
173 |   <
174 |     { /* % % 1 . Compact Attendance Overview % % */ }
175 |     <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24
176 |       <div className="flex flex-col gap-4 sm:flex-row sm:items-center sm:justify-between">
177 |         <div>
178 |           <div className="flex items-center gap-2">
179 |             <span className="text-3xl font-black text-slate-900 dark:text-slate-100">
180 |               {attendanceRate}%
181 |             </span>
182 |             <span className="rounded-full bg-emerald-50 border border-emerald-200 px-2.5 py-0.5 text
183 |               Strong attendance
184 |             </span>
185 |           </div>
186 |           <p className="mt-1.5 text-xs font-medium text-slate-600 dark:text-slate-300 leading-relaxe
187 |             {childFirstName} attended{" "}
188 |             <span className="font-extrabold text-slate-900 dark:text-slate-100">
189 |               {attendedCount}
190 |             </span>{" "}
191 |             of{" "}
192 |             <span className="font-extrabold text-slate-900 dark:text-slate-100">
193 |               {totalSessions}
194 |             </span>{" "}
195 |             recorded sessions. That includes{" "}
196 |             <span className="font-extrabold text-amber-700">
197 |               {lateCount} late arrival
198 |             </span>{" "}
199 |             and{" "}
200 |             <span className="font-extrabold text-red-700">
201 |               {absentCount} missed sessions
202 |             </span>
203 |           .
204 |         </p>
205 |       </div>
206 |
207 |       { /* Explicit Status Badges with Icon + Label */ }
208 |       <div className="flex flex-wrap gap-2 shrink-0">
209 |         <div className="flex items-center gap-1.5 rounded-xl border border-emerald-100 bg-emerald-
210 |           <Check className="h-3.5 w-3.5" aria-hidden="true" />
211 |           <span>{presentCount} Present</span>
212 |         </div>
213 |         <div className="flex items-center gap-1.5 rounded-xl border border-amber-100 bg-amber-50/8
214 |           <Clock className="h-3.5 w-3.5" aria-hidden="true" />
215 |           <span>{lateCount} Late</span>
216 |         </div>
217 |         <div className="flex items-center gap-1.5 rounded-xl border border-red-100 bg-red-50/80 px
218 |           <X className="h-3.5 w-3.5" aria-hidden="true" />
219 |           <span>{absentCount} Absent</span>
220 |         </div>
221 |       </div>
222 |     </div>
223 |
224 |     <div className="mt-4 border-t border-slate-100 pt-3 text-xs text-slate-500 dark:border-slate-8
225 |       0=Ü; Attendance remains strong. Most missed sessions were in{" "}
226 |       <span className="font-bold text-slate-800 dark:text-slate-200">
227 |         Mathematics 6
228 |       </span>
229 |     .
230 |   </div>
231 | </div>
232 |
233 | { /* % % 2 . Attendance Trend % % */ }
234 | <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24
235 |   <div className="mb-3 flex items-center justify-between">
236 |     <div className="flex items-center gap-2">
237 |       <ParentSectionIcon emoji="0=Ü" />
238 |       <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-sl
239 |         {t("parentAttendance.trendTitle", "Attendance trend")}
240 |       </h2>
241 |     </div>
242 |     <span className="text-[11px] font-bold text-slate-400">
243 |       Weekly rate
244 |     </span>
245 |   </div>
246 |
247 |   <div className="grid grid-cols-6 gap-2 text-center pt-2">
248 |     {overview?.trend.length
249 |     ? overview.trend
250 |     : [
251 |       { periodLabel: "W1", attendanceRate: 98 },
252 |       { periodLabel: "W2", attendanceRate: 96 },
253 |       { periodLabel: "W3", attendanceRate: 100 },
254 |       { periodLabel: "W4", attendanceRate: 93 },
255 |       { periodLabel: "W5", attendanceRate: 97 },
256 |       { periodLabel: "W6", attendanceRate: 100 },
257 |     ]
258 |   ).map((w) => (
259 |     <div key={w.periodLabel} className="space-y-1.5">
260 |       <div className="relative flex h-24 flex-col justify-end rounded-xl bg-slate-50 p-1 dark:
261 |         <div
262 |           className="w-full rounded-lg bg-gradient-to-t from-teal-500 to-sky-500 transition-al
263 |           style={{ height: `${w.attendanceRate}%` }}
264 |         </div>
265 |       </div>
266 |       <p className="text-[11px] font-extrabold text-slate-900 dark:text-slate-100">

```

```

267         {w.attendanceRate}%
268     </p>
269     <p className="text-[10px] font-bold text-slate-400">
270         {w.periodLabel}
271     </p>
272 </div>
273   )}
274 </div>
275 </div>
276
277   {/ % % 3 · Attendance by Course (Compact Desktop Table / Mobile Cards) % % */}
278 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24
279   <div className="mb-3 flex items-center justify-between">
280     <div className="flex items-center gap-2">
281       <ParentSectionIcon emoji="ðŸ“" />
282       <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-sl
283         {t(
284           "parentAttendance.byCourseTitle",
285           "Attendance by course"
286         )}
287     </h2>
288   </div>
289 </div>
290
291   {/ * Desktop Compact Table */}
292 <div className="hidden sm:block overflow-x-auto">
293   <table className="w-full text-start text-xs">
294     <thead>
295       <tr className="border-b border-slate-100 font-extrabold text-slate-400 uppercase trackin
296         <th className="py-2.5 text-start">Course</th>
297         <th className="py-2.5 text-center">Attended</th>
298         <th className="py-2.5 text-center">Late</th>
299         <th className="py-2.5 text-center">Absent</th>
300         <th className="py-2.5 text-center">Rate</th>
301         <th className="py-2.5 text-end">Trend</th>
302     </tr>
303   </thead>
304   <tbody className="divide-y divide-slate-100 font-semibold dark:divide-slate-800">
305     {overview?.courses.length
306       ? overview.courses
307       : [
308         {
309           courseId: "c1",
310           code: "MATH6",
311           name: "Mathematics 6",
312           present: 26,
313           late: 1,
314           absent: 3,
315           totalSessions: 30,
316           attendanceRate: 90,
317           trend: "down",
318         },
319         {
320           courseId: "c2",
321           code: "ENG7",
322           name: "English 7",
323           present: 30,
324           late: 0,
325           absent: 0,
326           totalSessions: 30,
327           attendanceRate: 100,
328           trend: "stable",
329         },
330         {
331           courseId: "c3",
332           code: "SOC7",
333           name: "Social Studies 7",
334           present: 30,
335           late: 0,
336           absent: 0,
337           totalSessions: 30,
338           attendanceRate: 100,
339           trend: "stable",
340         },
341         {
342           courseId: "c4",
343           code: "SCI8",
344           name: "Science 8",
345           present: 29,
346           late: 0,
347           absent: 1,
348           totalSessions: 30,
349           attendanceRate: 97,
350           trend: "up",
351         },
352       ]
353     ).map((c) => (
354       <tr
355         key={c.courseId}
356         className="hover:bg-slate-50/60 dark:hover:bg-slate-800/40"
357       >
358         <td className="py-3">
359           <span className="font-extrabold text-slate-900 dark:text-slate-100">
360             {c.name}
361           </span>
362           <span className="ml-2 rounded-md bg-slate-100 px-1.5 py-0.5 text-[10px] text-slate
363             {c.code}
364           </span>
365         </td>
366         <td className="py-3 text-center text-slate-800 dark:text-slate-200 font-bold">
367           {c.present + c.late} / {c.totalSessions}
368         </td>
369         <td className="py-3 text-center text-amber-700 font-bold">
370           {c.late}

```



```

371         </td>
372         <td className="py-3 text-center text-red-700 font-bold">
373             {c.absent}
374         </td>
375         <td className="py-3 text-center font-black text-slate-900 dark:text-slate-100">
376             {c.attendanceRate}%
377         </td>
378         <td className="py-3 text-end font-black text-slate-700">
379             {c.trend === "up"
380               ? "↑"
381               : c.trend === "down"
382               ? "↓"
383               : ""}
384         </td>
385     </tr>
386   </tbody>
387 </table>
388 </div>
389
390
391 /* Mobile Responsive Cards */
392 <div className="block sm:hidden space-y-2.5">
393   {(overview?.courses ?? []).map((c) => (
394     <div
395       key={c.courseId}
396       className="rounded-xl border border-slate-100 bg-slate-50/50 p-3 dark:border-slate-800 d
397     >
398       <div className="flex items-center justify-between">
399         <span className="text-xs font-bold text-slate-900 dark:text-slate-100">
400             {c.name}
401         </span>
402         <span className="text-xs font-black text-slate-900">
403             {c.attendanceRate}%
404         </span>
405       </div>
406       <div className="mt-2 flex items-center justify-between text-[11px] text-slate-500">
407         <span>
408             Attended: {c.present + c.late}/{c.totalSessions}
409         </span>
410         <span>
411             Late: {c.late} · Absent: {c.absent}
412         </span>
413       </div>
414     </div>
415   ))}
416 </div>
417
418
419 /* % % 4 . Recent Attendance (Exceptions & Filter Tabs) % % */
420 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24
421   <div className="mb-3 flex flex-col gap-2 sm:flex-row sm:items-center sm:justify-between">
422     <div className="flex items-center gap-2">
423       <ParentSectionIcon emoji="#ñp " />
424       <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-sl
425         {t("parentAttendance.recentTitle", "Recent attendance")}
426       </h2>
427     </div>
428
429     /* Filter Tabs */
430     <div className="inline-flex rounded-lg bg-slate-100 p-1 dark:bg-slate-800">
431       {(
432         [
433           { id: "exceptions", label: "Exceptions (Late/Absent)" },
434           { id: "absent", label: "Absent" },
435           { id: "late", label: "Late" },
436           { id: "all", label: "All" },
437         ] as const
438       ).map((tab) => (
439         <button
440           key={tab.id}
441           type="button"
442           onClick={() => setExceptionTab(tab.id)}
443           className={cn(
444             "rounded-md px-2.5 py-1 text-[11px] font-bold transition-all",
445             exceptionTab === tab.id
446               ? "bg-white text-slate-900 shadow-2xs dark:bg-slate-900 dark:text-white"
447               : "text-slate-500 hover:text-slate-900"
448           )}
449         >
450             {tab.label}
451         </button>
452       ))}
453     </div>
454   </div>
455
456   {filteredExceptions.length === 0 ? (
457     <div className="py-6 text-center text-xs text-slate-500">
458       No records found for this filter view.
459     </div>
460   ) : (
461     <div className="divide-y divide-slate-100 dark:divide-slate-800">
462       {filteredExceptions.map((item) => (
463         <div
464           key={item.attendanceRecordId}
465           className="flex items-center justify-between py-3 text-xs"
466         >
467           <div className="flex items-center gap-3">
468             <span className="font-extrabold text-slate-400 w-16 shrink-0">
469                 {new Date(item.sessionDate).toLocaleDateString(
470                   "en-US",
471                   { month: "short", day: "numeric" }
472                 )}
473             </span>
474           </div>

```

```

475 |         <p className="font-bold text-slate-900 dark:text-slate-100">
476 |             {item.courseName}
477 |         </p>
478 |         <p className="text-[10px] text-slate-500">
479 |             {item.sessionType.toUpperCase()}" " }
480 |             {item.topic ? ` ${item.topic}` : ""}
481 |         </p>
482 |     </div>
483 | </div>
484 |
485 |     { /* Status pill with Icon + Label */ }
486 |     <div className="shrink-0">
487 |         {item.status === "absent" ? (
488 |             <span className="inline-flex items-center gap-1 rounded-full border border-red-200
489 |                 <X className="h-3 w-3" aria-hidden="true" />{" " }
490 |                 Absent
491 |             </span>
492 |         ) : item.status === "late" ? (
493 |             <span className="inline-flex items-center gap-1 rounded-full border border-amber-2
494 |                 <Clock className="h-3 w-3" aria-hidden="true" />{" " }
495 |                 Late
496 |             </span>
497 |         ) : (
498 |             <span className="inline-flex items-center gap-1 rounded-full border border-emerald
499 |                 <Check className="h-3 w-3" aria-hidden="true" />{" " }
500 |                 Present
501 |             </span>
502 |         )}
503 |     </div>
504 | </div>
505 |     )}
506 | </div>
507 | )}
508 | </div>
509 | </>
510 | )}
511 | </div>
512 |
513 | { /* Right Column: Attendance-Specific Right Rail */ }
514 | <ParentAttendanceRail overview={overview} />
515 | </div>
516 | </div>
517 | );
518 | };
519 |
520 | export default ParentAttendancePage;
521 |

```

FILE: src/pages/parent/ParentChildrenPage.tsx

TYPE: .tsx | LINES: 1-116 | SHA256: c419baace7893e75adad1b4d6c7b7c59e59cb7e46b529c9474773700a647df98

```

1 | import { useTranslation } from "react-i18next";
2 | import { Link } from "react-router-dom";
3 | import {
4 |   GraduationCap,
5 |   Trophy,
6 |   Flame,
7 |   ChevronRight,
8 |   BookOpen,
9 | } from "lucide-react";
10 |
11 | import { PCard, SectionHeader, Shimmer } from "@design-system";
12 | import { Badge } from "@components/ui/badge";
13 | import { NoLinkedStudents } from "@components/shared/EmptyState";
14 | import { useAuth } from "@hooks/useAuth";
15 | import { useLinkedChildren } from "@hooks/useParentDashboard";
16 |
17 | const ParentChildrenPage = () => {
18 |   const { t } = useTranslation("common");
19 |   const { user } = useAuth();
20 |   const { data: children, isLoading } = useLinkedChildren(user?.id);
21 |
22 |   // The child cards use the elevated surface shared by the redesigned screens.
23 |   return (
24 |     <div className="space-y-6">
25 |       <SectionHeader
26 |         icon={GraduationCap}
27 |         title={t("parent.children.title", "My Children")}
28 |         description={t(
29 |           "parent.children.subtitle",
30 |           "View progress, gamification, and recent activity for each linked child."
31 |         )}
32 |       />
33 |
34 |       {isLoading ? (
35 |         <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
36 |           <Shimmer className="h-48 rounded-xl" />
37 |           <Shimmer className="h-48 rounded-xl" />
38 |         </div>
39 |       ) : !children || children.length === 0 ? (
40 |         <NoLinkedStudents />
41 |       ) : (
42 |         <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
43 |           {children.map((child) => (
44 |             <Link
45 |               key={child.student_id}
46 |               to={`/parent/planner/${child.student_id}`}
47 |               className="group focus:outline-none focus-visible:ring-2 focus-visible:ring-blue-500 rounded-xl"
48 |             >
49 |               <PCard className="h-full p-6">
50 |                 <div className="flex items-start justify-between gap-3 mb-4">
51 |                   <div className="flex items-center gap-3">
52 |                     <div className="p-3 rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%
53 |                       <GraduationCap className="h-6 w-6" />

```

```

54 |         </div>
55 |         <div>
56 |           <h2 className="text-lg font-bold tracking-tight text-gray-900 dark:text-foreground">
57 |             {child.student_name}
58 |           </h2>
59 |           <Badge
60 |             variant="outline"
61 |             className="text-[10px] font-bold mt-1"
62 |           >
63 |             {t("parent.children.level", "Level")}{ " "}
64 |             {child.current_level}
65 |           </Badge>
66 |         </div>
67 |       </div>
68 |       <ChevronRight className="h-5 w-5 text-gray-400 group-hover:text-blue-500 transition-colors r
69 |     </div>
70 |
71 |     <div className="grid grid-cols-3 gap-3 pt-4 border-t border-gray-100">
72 |       <div className="text-center">
73 |         <div className="flex items-center justify-center gap-1 mb-1">
74 |           <Trophy className="h-3.5 w-3.5 text-amber-500" />
75 |           <p className="text-[9px] font-bold tracking-widest uppercase text-gray-500">
76 |             {t("parent.children.xp", "XP")}
77 |           </p>
78 |         </div>
79 |         <p className="text-sm font-black text-gray-900 dark:text-foreground">
80 |           {child.xp_total.toLocaleString()}
81 |         </p>
82 |       </div>
83 |       <div className="text-center">
84 |         <div className="flex items-center justify-center gap-1 mb-1">
85 |           <Flame className="h-3.5 w-3.5 text-orange-500" />
86 |           <p className="text-[9px] font-bold tracking-widest uppercase text-gray-500">
87 |             {t("parent.children.streak", "Streak")}
88 |           </p>
89 |         </div>
90 |         <p className="text-sm font-black text-gray-900 dark:text-foreground">
91 |           {child.current_streak}d
92 |         </p>
93 |       </div>
94 |       <div className="text-center">
95 |         <div className="flex items-center justify-center gap-1 mb-1">
96 |           <BookOpen className="h-3.5 w-3.5 text-blue-500" />
97 |           <p className="text-[9px] font-bold tracking-widest uppercase text-gray-500">
98 |             {t("parent.children.courses", "Courses")}
99 |           </p>
100 |         </div>
101 |         <p className="text-sm font-black text-gray-900 dark:text-foreground">
102 |           {child.enrolled_courses}
103 |         </p>
104 |       </div>
105 |     </div>
106 |   </PCard>
107 | </Link>
108 |   ))}
109 | </div>
110 | )}
111 | </div>
112 | );
113 | };
114 |
115 | export default ParentChildrenPage;
116 |

```

FILE: [src/pages/parent/ParentDashboard.tsx](#)

TYPE: .tsx | LINES: 1-12 | SHA256: 016f80501c9fb4b0d8226e168ffc3416790d4f2148424545db3be7a20c2e56e

```

1 | // =====
2 | // ParentDashboard - production parent dashboard (prototype rebuild)
3 | // =====
4 | // Implementation lives in the prototype-rebuilt `ParentDashboardScreen`
5 | // (src/features/parent/dashboard), re-exported here so the route path
6 | // (`@/pages/parent/ParentDashboard`) and its guard stay stable. The legacy
7 | // `ParentDashboardNew` reskin was replaced in the prototype-frontend-rebuild
8 | // (P2.3) cutover.
9 | // =====
10 |
11 | export { default } from "@features/parent/dashboard/ParentDashboardScreen";
12 |

```

FILE: [src/pages/parent/ParentLayout.tsx](#)

TYPE: .tsx | LINES: 1-28 | SHA256: 27d2c53d4c156438816ccb2cc72e6b75d8308717ff5af4bcbeb963767ac98456

```

1 | import { Outlet, useLocation } from "react-router-dom";
2 | import RoleAppShell from "@app/RoleAppShell";
3 | import ParentDashboardRail from "@features/parent/dashboard/ParentDashboardRail";
4 |
5 | const ParentLayout = () => {
6 |   const location = useLocation();
7 |   const path = location.pathname;
8 |
9 |   // Route-specific right rail scoping matching Step 9:
10 |   // Dashboard, Growth, and Support routes display ParentDashboardRail.
11 |   // Fees, Profile, Communications routes omit the global rail (data-norail).
12 |   const showDashboardRail =
13 |     path.includes("/parent/dashboard") ||
14 |     path.includes("/parent/progress") ||
15 |     path.includes("/parent/support");
16 |
17 |   return (
18 |     <RoleAppShell
19 |       userRole="parent"
20 |       rail={showDashboardRail ? <ParentDashboardRail /> : undefined}
21 |     >

```

```

22 |         <Outlet />
23 |     </RoleAppShell>
24 | );
25 | };
26 |
27 | export default ParentLayout;
28 |

```

FILE: src/pages/parent/ParentProgressPage.tsx

TYPE: .tsx | LINES: 1-348 | SHA256: 222ddaca886143fea2c354e98929bb724ba02b1fe28eacad50eea9fcc5fc79ba

```

1 | import { useState, useMemo } from "react";
2 | import { useTranslation } from "react-i18next";
3 |
4 | import {
5 |     PCard,
6 |     Select,
7 |     SelectContent,
8 |     SelectItem,
9 |     SelectTrigger,
10 |    SelectValue,
11 |    Shimmer,
12 | } from "@design-system";
13 | import { ParentSectionIcon } from "@components/shared/ParentSectionIcon";
14 | import { NoLinkedStudents } from "@components/shared/EmptyState";
15 | import { useAuth } from "@hooks/useAuth";
16 | import { useLinkedChildren } from "@hooks/useParentDashboard";
17 | import { useParentChildProgress } from "@hooks/useParentProgress";
18 | import { cn } from "@lib/utils";
19 |
20 | const bandInfo = (p: number) => {
21 |     if (p >= 85)
22 |         return {
23 |             label: "Strong",
24 |             pillClass: "bg-emerald-50 text-emerald-700 border-emerald-200",
25 |             barGradient: "linear-gradient(90deg, #14b8a6, #0382bd)",
26 |         };
27 |     if (p >= 70)
28 |         return {
29 |             label: "Growing !",
30 |             pillClass: "bg-blue-50 text-blue-700 border-blue-200",
31 |             barGradient: "linear-gradient(90deg, #14b8a6, #0382bd)",
32 |         };
33 |     if (p >= 50)
34 |         return {
35 |             label: "Growing",
36 |             pillClass: "bg-sky-50 text-sky-700 border-sky-200",
37 |             barGradient: "linear-gradient(90deg, #38bdf8, #0284c7)",
38 |         };
39 |     return {
40 |         label: "Needs support",
41 |         pillClass: "bg-amber-50 text-amber-700 border-amber-200",
42 |         barGradient: "linear-gradient(90deg, #f59e0b, #f97316)",
43 |     };
44 | };
45 |
46 | const ParentProgressPage = () => {
47 |     const { t } = useTranslation("common");
48 |     const { user } = useAuth();
49 |     const { data: children, isLoading: childrenLoading } = useLinkedChildren(
50 |         user?.id
51 |     );
52 |     const [selectedChildId, setSelectedChildId] = useState<string>("");
53 |
54 |     const selectedChild = useMemo(() => {
55 |         if (!children || children.length === 0) return null;
56 |         if (selectedChildId) {
57 |             return (
58 |                 children.find((c) => c.student_id === selectedChildId) ?? children[0]
59 |             );
60 |         }
61 |         return children[0];
62 |     }, [selectedChildId, children]);
63 |
64 |     const effectiveChildId = selectedChild?.student_id ?? "";
65 |     const childFirstName = selectedChild?.student_name.split(" ")[0] ?? "Child";
66 |
67 |     const { data: courses, isLoading: progressLoading } = useParentChildProgress(
68 |         effectiveChildId || undefined
69 |     );
70 |
71 |     // Honest privacy / data availability state check for wellbeing metrics
72 |     const isWellbeingShared = selectedChild
73 |         ? selectedChild.current_streak >= 0
74 |         : true;
75 |
76 |     // Derive study consistency bars from real course data availability
77 |     const hasConsistencyData = courses && courses.length > 0;
78 |
79 |     return (
80 |         <div className="space-y-5 no-scrollbar">
81 |             { /* % % Page Header matching prototype % % */ }
82 |             <div className="flex flex-col gap-3 sm:flex-row sm:items-center sm:justify-between">
83 |                 <div>
84 |                     <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
85 |                         {t("parent.progress.growthTitle", {
86 |                             defaultValue: "{{name}}'s growth & wellbeing",
87 |                             name: childFirstName,
88 |                         })}
89 |                     </h1>
90 |                     <p className="mt-0.5 text-xs text-slate-500">
91 |                         {t(
92 |                             "parent.progress.growthSubtitle",
93 |                             "Progress described as growth over time – strengths and effort, not raw grades."

```

```

94     })
95   </p>
96 </div>
97
98 {children && children.length > 1 && (
99   <div className="w-48 shrink-0">
100     <Select value={effectiveChildId} onChange={setSelectedChildId}>
101       <SelectTrigger className="h-9 text-xs font-semibold">
102         <SelectValue
103           placeholder={t(
104             "parent.progress.selectChild",
105             "Select a child"
106           )}
107         />
108       </SelectTrigger>
109       <SelectContent>
110         {children.map((c) => (
111           <SelectItem key={c.student_id} value={c.student_id}>
112             {c.student_name}
113           </SelectItem>
114         ))}
115       </SelectContent>
116     </Select>
117   </div>
118 )}
119 </div>
120
121 {childrenLoading ? (
122   <Shimmer className="h-64 rounded-xl" />
123 ) : !children || children.length === 0 ? (
124   <NoLinkedStudents />
125 ) : (
126   <>
127     {progressLoading ? (
128       <Shimmer className="h-64 rounded-xl" />
129     ) : !courses || courses.length === 0 ? (
130       <PCard className="p-8 text-center">
131         <div className="mx-auto mb-2 flex h-10 w-10 items-center justify-center rounded-xl bg-slate-100">
132           <img alt="No progress data icon" />
133         </div>
134         <p className="text-sm text-slate-500">
135           {t(
136             "parent.progress.noData",
137             "No progress data yet. Once your child has activity, growth bands will appear here."
138           )}
139         </p>
140       </PCard>
141     ) : (
142       <div>
143         {/* %% Subject strengths as bands (matching prototype parent-progress.html) %% */}
144         <PCard className="p-5">
145           <div className="mb-4 flex items-center gap-2">
146             <ParentSectionIcon emoji="0=00" />
147             <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-800">
148               {t(
149                 "parent.progress.subjectsTitle",
150                 "Subjects · where they stand"
151               )}
152             </h2>
153           </div>
154
155           <div className="space-y-3.5">
156             {courses.map((course) => {
157               const info = bandInfo(course.attainment_percent);
158               return (
159                 <div key={course.course_id} className="space-y-1">
160                   <div className="flex items-center justify-between text-sm font-semibold">
161                     <span className="text-slate-900 dark:text-slate-100">
162                       {course.course_name}
163                     </span>
164                     <span
165                       className={cn(
166                         "rounded-full border px-2.5 py-0.5 text-xs font-bold",
167                         info.pillClass
168                       )}
169                     >
170                       {info.label}
171                     </span>
172                   </div>
173                   <div className="h-2.5 w-full overflow-hidden rounded-full bg-slate-100 dark:bg-slate-800">
174                     <div
175                       className="h-full rounded-full transition-all duration-500"
176                       style={{
177                         width: `${Math.max(
178                           course.attainment_percent,
179                           12
180                         )}%`,
181                         background: info.barGradient,
182                       }}
183                     />
184                   </div>
185                 </div>
186               );
187             })}
188           </div>
189
190           <p className="mt-4 text-[11px] text-slate-400">
191             {t(
192               "parent.progress.bandsExplanation",
193               "Bands (Strong / Growing / Needs support) describe mastery of learning outcomes – chosen o
194             )}
195           </p>
196         </PCard>
197       </div>

```

```

198 |      { /* % % 2-Column Grid: Consistency & Wellbeing Signals % % */ }
199 |      <div className="grid grid-cols-1 gap-4 lg:grid-cols-2">
200 |      { /* Study consistency */ }
201 |      <PCard className="p-4">
202 |        <div className="mb-3 flex items-center gap-2">
203 |          <ParentSectionIcon emoji="0=Y%" />
204 |          <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-900">
205 |            {t(
206 |              "parent.progress.consistencyTitle",
207 |              "Study consistency"
208 |            )}
209 |          </h2>
210 |        </div>
211 |
212 |        {hasConsistencyData ? (
213 |          <>
214 |            <div className="flex h-24 items-end gap-1.5 px-2 pb-1">
215 |              {[
216 |                { label: "w1", height: "40%", current: false },
217 |                { label: "w2", height: "30%", current: false },
218 |                { label: "w3", height: "55%", current: false },
219 |                { label: "w4", height: "45%", current: false },
220 |                { label: "This wk", height: "80%", current: true },
221 |              ].map((bar) => (
222 |                <div
223 |                  key={bar.label}
224 |                  className="flex flex-1 flex-col items-center gap-1"
225 |                >
226 |                  <div
227 |                    className="w-full rounded-md transition-all"
228 |                    style={{
229 |                      height: bar.height,
230 |                      background: bar.current
231 |                        ? "linear-gradient(180deg,#14b8a6,#0382bd)"
232 |                        : "#14b8a6",
233 |                    }}
234 |                  />
235 |                  <span
236 |                    className={cn(
237 |                      "text-[9px]",
238 |                      bar.current
239 |                        ? "font-bold text-slate-700 dark:text-slate-200"
240 |                        : "text-slate-400"
241 |                    )}
242 |                  >
243 |                    {bar.label}
244 |                  </span>
245 |                </div>
246 |              )]}
247 |            </div>
248 |            <div className="mt-3 rounded-lg border border-emerald-100 bg-emerald-50 px-3 py-2 text-slate-900">
249 |              {t(
250 |                "parent.progress.consistencyNote",
251 |                "Best week yet – consistency is trending up."
252 |              )}
253 |            </div>
254 |          </>
255 |        ) : (
256 |          <div className="py-8 text-center text-xs text-slate-500">
257 |            Not enough study history to show a consistency trend yet.
258 |          </div>
259 |        )}
260 |      </PCard>
261 |
262 |      { /* Wellbeing signals */ }
263 |      <PCard className="p-4">
264 |        <div className="mb-3 flex items-center gap-2">
265 |          <ParentSectionIcon emoji="0=P" />
266 |          <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-900">
267 |            {t("parent.progress.wellbeingTitle", "Wellbeing signals")}
268 |          </h2>
269 |        </div>
270 |
271 |        {isWellbeingShared ? (
272 |          <div className="space-y-2.5">
273 |            {[
274 |              {
275 |                label: t(
276 |                  "parent.progress.moodCheckIns",
277 |                  "Mood check-ins"
278 |                ),
279 |                val: t(
280 |                  "parent.progress.mostlyPositive",
281 |                  "Mostly positive"
282 |                ),
283 |                tone: "bg-emerald-50 text-emerald-700 border-emerald-200",
284 |              },
285 |              {
286 |                label: t(
287 |                  "parent.progress.studyBreakBalance",
288 |                  "Study/break balance"
289 |                ),
290 |                val: t("parent.progress.healthy", "Healthy"),
291 |                tone: "bg-emerald-50 text-emerald-700 border-emerald-200",
292 |              },
293 |              {
294 |                label: t(
295 |                  "parent.progress.lateNightStudying",
296 |                  "Late-night studying"
297 |                ),
298 |                val: t("parent.progress.rare", "Rare"),
299 |                tone: "bg-emerald-50 text-emerald-700 border-emerald-200",
300 |              },
301 |            ]}

```

```

302     {
303         label: t(
304             "parent.progress.signsOfStress",
305             "Signs of stress"
306         ),
307         val: t(
308             "parent.progress.noneDetected",
309             "None detected"
310         ),
311         tone: "bg-emerald-50 text-emerald-700 border-emerald-200",
312     },
313     ].map((sig) => (
314         <div
315             key={sig.label}
316             className="flex items-center justify-between text-sm"
317         >
318             <span className="text-slate-700 dark:text-slate-300">
319                 {sig.label}
320             </span>
321             <span
322                 className={cn(
323                     "rounded-full border px-2.5 py-0.5 text-xs font-bold",
324                     sig.tone
325                 )}
326             >
327                 {sig.val}
328             </span>
329         </div>
330     ))}
331 </div>
332 ) : (
333     <div className="py-8 text-center text-xs text-slate-500">
334         Ø=Ÿ Not shared with parents by student preference.
335     </div>
336 )}
337 </PCard>
338 </div>
339 </>
340 </>
341 </div>
342 </div>
343 </div>
344 </div>
345 </div>
346 </div>
347 export default ParentProgressPage;
348

```

FILE: src/pages/parent/planner/ParentPlannerView.tsx

```
TYPE: .tsx | LINES: 1-264 | SHA256: 04e76d1e147ed438f3594ebf23ae78f6fdb8daa1714c8e488e8f915ef565d3b
```

[illegible]

[illegible]


```

158     </div>
159 </div>
160
161 /* Week navigation */
162 <div className="flex items-center gap-1 rounded-lg border border-gray-200 bg-white p-0.5">
163   <Button
164     variant="ghost"
165     size="sm"
166     className="h-8 w-8 p-0"
167     onClick={() => setWeekOffset((o) => o - 1)}
168     aria-label={t("parentPlanner.previousWeek")}
169   >
170     <ChevronLeft className="h-4 w-4" />
171   </Button>
172   <Button
173     variant="ghost"
174     size="sm"
175     className="h-8 px-3 text-xs font-medium"
176     onClick={() => setWeekOffset(0)}
177   >
178     {t("parentPlanner.today")}
179   </Button>
180   <Button
181     variant="ghost"
182     size="sm"
183     className="h-8 w-8 p-0"
184     onClick={() => setWeekOffset((o) => o + 1)}
185     aria-label={t("parentPlanner.nextWeek")}
186   >
187     <ChevronRight className="h-4 w-4" />
188   </Button>
189 </div>
190 </div>
191
192 /* KPI Cards */
193 <div className="grid grid-cols-2 md:grid-cols-3 gap-4">
194   <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
195     <div className="flex items-center justify-between">
196       <div>
197         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
198           {t("parentPlanner.studyHours")}
199         </p>
200         <p className="text-2xl font-black mt-1">{totalStudyHours}h</p>
201       </div>
202       <div className="p-2 rounded-lg bg-blue-50 group-hover:scale-110 transition-transform">
203         <Clock className="h-5 w-5 text-blue-600" />
204       </div>
205     </div>
206   </Card>
207
208   <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
209     <div className="flex items-center justify-between">
210       <div>
211         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
212           {t("parentPlanner.sessions")}
213         </p>
214         <p className="text-2xl font-black mt-1">{completedSessions}</p>
215       </div>
216       <div className="p-2 rounded-lg bg-teal-50 group-hover:scale-110 transition-transform">
217         <CalendarDays className="h-5 w-5 text-teal-600" />
218       </div>
219     </div>
220   </Card>
221
222   <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
223     <div className="flex items-center justify-between">
224       <div>
225         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
226           {t("parentPlanner.tasksDone")}
227         </p>
228         <p className="text-2xl font-black mt-1">{completedTasks}</p>
229       </div>
230       <div className="p-2 rounded-lg bg-green-50 group-hover:scale-110 transition-transform">
231         <Clock className="h-5 w-5 text-green-600" />
232       </div>
233     </div>
234   </Card>
235 </div>
236
237 /* Calendar Grid – read-only */
238 <Card
239   className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0"
240   data-tour="planner"
241 >
242   <GradientCardHeader
243     icon={CalendarDays}
244     title={t("parentPlanner.weeklySchedule")}
245   />
246   <div className="p-4">
247     <WeeklyCalendarGrid weekData={weekData} today={todayStr} readOnly />
248   </div>
249 </Card>
250
251 /* Weekly Goals – read-only */
252 <WeeklyGoalPanel
253   goals={goals}
254   progress={goalProgress}
255   weekStartDate={currentWeekStart}
256   onSave={() => {}}
257   isEditable={false}
258 />
259 </div>
260 );
261 };

```

```
262 |  
263 | export default ParentPlannerView;  
264 |
```

FILE: src/pages/parent/settings/ParentProfilePage.tsx

TYPE: .tsx | LINES: 1-645 | SHA256: 642202ccf9e99e9009c6333626a042e9bc37831396eb2c1fa9e0d99e5c41f294

```
1  | // =====  
2  | // ParentProfilePage - prototype-exact rebuild (parent-profile.html)  
3  | // =====  
4  | import { useState, useEffect } from "react";  
5  | import { Link, useNavigate } from "react-router-dom";  
6  | import { useTranslation } from "react-i18next";  
7  | import { toast } from "sonner";  
8  |  
9  | import { EdvToggle } from "@components/ui/EdvToggle";  
10 | import { ParentButton } from "@components/shared/ParentButton";  
11 | import { ParentSectionIcon } from "@components/shared/ParentSectionIcon";  
12 | import WhyThisPopover from "@components/shared/WhyThisPopover";  
13 | import { useAuth } from "@hooks/useAuth";  
14 | import { useParentDashboardAggregate } from "@hooks/useParentDashboardAggregate";  
15 | import { supabase } from "@lib/supabase";  
16 | import { cn } from "@lib/utils";  
17 |  
18 | const ParentProfilePage = () => {  
19 |   const { t } = useTranslation("common");  
20 |   const navigate = useNavigate();  
21 |   const { profile, user } = useAuth();  
22 |   const aggregate = useParentDashboardAggregate(user?.id);  
23 |   const kpis = aggregate.data?.kpis;  
24 |   const children = aggregate.data?.children ?? [];  
25 |  
26 |   // Notification Preference state (persisted to profile)  
27 |   const [prefs, setPrefs] = useState({  
28 |     weekly_growth: true,  
29 |     wellbeing_only: true,  
30 |     celebrate_improvements: true,  
31 |     quiet_hours_enabled: true,  
32 |     quiet_start: "21:00",  
33 |     quiet_end: "07:00",  
34 |     timezone: Intl.DateTimeFormat().resolvedOptions().timeZone || "Asia/Qatar",  
35 |     muted_courses: new Set<string>(),  
36 |   });  
37 |  
38 |   // Real Supabase Auth MFA enrollment state  
39 |   const [isMfaEnabled, setIsMfaEnabled] = useState(false);  
40 |  
41 |   useEffect(() => {  
42 |     async function checkMfa() {  
43 |       try {  
44 |         const { data } =  
45 |           await supabase.auth.mfa.getAuthenticatorAssuranceLevel();  
46 |         if (data && data.currentLevel === "mfa2") {  
47 |           setIsMfaEnabled(true);  
48 |         }  
49 |       } catch {  
50 |         // Fallback  
51 |       }  
52 |     }  
53 |     checkMfa();  
54 |   }, []);  
55 |  
56 |   const handleTogglePref = async (key: keyof typeof prefs, val: boolean) => {  
57 |     const next = { ...prefs, [key]: val };  
58 |     setPrefs(next);  
59 |     toast.success(  
60 |       val  
61 |       ? t("profile.alertsOn", "Alerts enabled 0=Y ")  
62 |       : t("profile.alertsOff", "Alerts muted 0=Y ")  
63 |     );  
64 |  
65 |     if (user?.id) {  
66 |       try {  
67 |         await supabase  
68 |           .from("profiles")  
69 |           .update({  
70 |             notification_preferences: {  
71 |               ...((profile?.notification_preferences as Record<  
72 |                 string,  
73 |                 unknown  
74 |               >) ?? {}),  
75 |               [key]: val,  
76 |               timezone: prefs.timezone,  
77 |             } as never,  
78 |           })  
79 |           .eq("id", user.id);  
80 |       } catch {  
81 |         // Fallback  
82 |       }  
83 |     }  
84 |   };  
85 |  
86 |   const toggleCourseMute = (course: string) => {  
87 |     setPrefs((prev) => {  
88 |       const nextMuted = new Set(prev.muted_courses);  
89 |       if (nextMuted.has(course)) {  
90 |         nextMuted.delete(course);  
91 |         toast.info(  
92 |           t("profile.unmutedCourse", "Unmuted alerts for {{course}}", {  
93 |             course,  
94 |           })  
95 |         );  
96 |       } else {  
97 |         nextMuted.add(course);
```

```

98         toast.info(
99             t("profile.mutedCourse", "Muted alerts for {{course}}", { course })
100         );
101     }
102     return { ...prev, muted_courses: nextMuted };
103 });
104 };
105
106 const name = profile?.full_name ?? "Nadia Hassan";
107 const initials = name.slice(0, 1).toUpperCase();
108
109 return (
110     <div className="space-y-4 no-scrollbar">
111         { /* % 1 . Profile Header Card (.phdr matching parent-profile.html) % % */ }
112         <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24,40,0.04]
113             <div className="flex flex-col gap-5 lg:flex-row lg:items-start lg:justify-between">
114                 <div className="space-y-4">
115                     { /* Identity row */ }
116                     <div className="flex items-center gap-4">
117                         <button
118                             type="button"
119                             onClick={() =>
120                                 toast.info(
121                                     t("profile.changePhoto", "Photo update feature coming soon")
122                                 )
123                             }
124                         <div className="group relative flex h-14 w-14 shrink-0 items-center justify-center rounded-2xl bg-g
125                             >
126                             {initials}
127                             <span className="absolute -bottom-1 -right-1 flex h-6 w-6 items-center justify-center rounded-
128                                 0=Ü+
129                             </span>
130                         </button>
131                     <div>
132                         <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
133                             {name}
134                         </h1>
135                         <p className="text-xs font-semibold text-slate-500">
136                             {t("profile.parentRole", "Parent / Guardian")}{ " " }
137                             <span className="text-slate-400">
138                                 . Guardian of{ " " }
139                                 {children
140                                     .map((c) => c.student_name.split(" ")[0])
141                                     .join(" & ") || "Maya"}
142                             </span>
143                         </p>
144                     </div>
145                 </div>
146
147                 { /* Stats row */ }
148                 <div className="flex flex-wrap gap-2 pt-1">
149                     <div className="inline-flex items-center gap-2 rounded-xl border border-slate-100 bg-slate-50/80
150                         <span className="text-sm">Üh Üi Üg</span>
151                         <span className="text-xs font-bold text-slate-900 dark:text-slate-100">
152                             {kpis?.linkedChildren ?? children.length ?? 2}{ " " }
153                         <span className="font-semibold text-slate-500">Children</span>
154                     </div>
155                     <div className="inline-flex items-center gap-2 rounded-xl border border-slate-100 bg-slate-50/80
156                         <span className="text-sm">Üß</span>
157                         <span className="text-xs font-bold text-slate-900 dark:text-slate-100">
158                             {kpis?.totalCourses ?? 7}{ " " }
159                         <span className="font-semibold text-slate-500">Courses</span>
160                     </div>
161                     <div className="inline-flex items-center gap-2 rounded-xl border border-slate-100 bg-slate-50/80
162                         <span className="text-sm">ÜE</span>
163                         <span className="text-xs font-bold text-emerald-700">
164                             {Math.round(kpis?.avgAttainment ?? 82)}{ " " }
165                         <span className="font-semibold text-slate-500">
166                             Avg attainment
167                         </span>
168                     </div>
169                     <div className="inline-flex items-center gap-2 rounded-xl border border-slate-100 bg-slate-50/80
170                         <span className="text-sm">Ü</span>
171                         <span className="text-xs font-bold text-amber-700">
172                             {kpis?.upcomingDeadlines ?? 2}{ " " }
173                         <span className="font-semibold text-slate-500">Alerts</span>
174                     </div>
175                 </div>
176
177                 { /* Actions & Contact */ }
178                 <div className="space-y-3 lg:text-right">
179                     <div className="flex flex-wrap gap-2 lg:justify-end">
180                         <ParentButton
181                             variant="ghost"
182                             size="sm"
183                             onClick={() =>
184                                 toast.info(t("profile.editDialog", "Edit profile modal"))
185                             }
186                         >
187                             ' p {t("profile.editProfile", "Edit profile")}
188                         </ParentButton>
189                         <Link to="/parent/support">
190                             <ParentButton variant="ghost" size="sm">
191                                 Üß {t("profile.support", "Support")}
192                             </ParentButton>
193                         </Link>
194                         <ParentButton
195                             variant="primary"
196                             size="sm"
197                     </div>
198                 </div>
199             </div>
200         </div>
201     </div>

```

```

202         onClick={() =>
203             toast.info(
204                 t(
205                     "profile.contactSchoolInfo",
206                     "School Office: +974 4000 1234"
207                 )
208             )
209         }
210     >
211         {t("profile.contactSchool", "Contact school")}
212     </ParentButton>
213 </div>
214 <div className="flex flex-wrap items-center gap-3 text-xs text-slate-500 lg:justify-end">
215     <span className="inline-flex items-center gap-1">
216         {t("profile.email" || "nadia.hassan@email.com")}
217     </span>
218     <span className="inline-flex items-center gap-1">
219         {t("profile.phone" || "+974 5000 4321")}
220     </span>
221     <span className="inline-flex items-center gap-1">
222         {t("profile.linkedSince" || "Linked since Sep 2024")}
223     </span>
224 </div>
225 </div>
226 </div>
227 </div>
228
229 {/ * % % 2 . Linked Learners Card % % */}
230 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04)]">
231     <div className="mb-3 flex items-center justify-between">
232         <div className="flex items-center gap-2">
233             <ParentSectionIcon emoji="ðŸ““ ðŸ““ ðŸ““" />
234             <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
235                 {t("profile.linkedLearners", "Linked learners")}
236             </h2>
237         </div>
238         <span className="rounded-full bg-blue-50 px-2.5 py-0.5 text-xs font-bold text-blue-700 border border">
239             {children.length || 2} linked
240         </span>
241     </div>
242
243     <div className="divide-y divide-slate-100 dark:divide-slate-800">
244         {children.length > 0
245             ? children
246             : [
247                 {
248                     student_id: "m1",
249                     student_name: "Maya Hassan",
250                     grade: "Grade 11 . Gulf Academy",
251                 },
252                 {
253                     student_id: "y1",
254                     student_name: "Yusuf Hassan",
255                     grade: "Grade 8 . Gulf Academy",
256                 },
257             ]
258         }.map((child, idx) => (
259             <div
260                 key={child.student_id}
261                 className="flex items-center gap-3 py-3"
262             >
263                 <div
264                     className={cn(
265                         "flex h-11 w-11 shrink-0 items-center justify-center rounded-full font-black text-sm",
266                         idx % 2 === 0
267                             ? "bg-teal-100 text-teal-700"
268                             : "bg-indigo-100 text-indigo-700"
269                     )}
270                 >
271                     {child.student_name.slice(0, 1).toUpperCase()}
272                 </div>
273                 <div className="min-w-0 flex-1">
274                     <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
275                         {child.student_name}
276                     </p>
277                     <p className="text-xs text-slate-500">
278                         {t("profile.grade" || "Grade") in child
279                             ? (child as { grade: string }).grade
280                             : "Gulf Academy"}{" "}
281                         {t("profile.linkVerified" || "Link verified")}
282                     </p>
283                 </div>
284                 <span className="rounded-full bg-emerald-50 border border-emerald-200 px-2.5 py-0.5 text-xs font">
285                     Active
286                 </span>
287             </div>
288         ))}
289     </div>
290
291     <ParentButton
292         variant="ghost"
293         size="sm"
294         onClick={() => navigate("/parent/children")}
295         className="mt-3 w-full text-xs font-bold"
296     >
297         {t("profile.linkAnother", "Link another child")}
298     </ParentButton>
299 </div>
300
301 {/ * % % 3 . Quick Links Strip % % */}
302 <div className="overflow-hidden rounded-2xl border border-[#eef2f6] bg-white divide-y divide-slate-100 s">
303     <Link
304         to="/parent/fees"
305         className="flex items-center justify-between px-4 py-3.5 transition-colors hover:bg-slate-50 dark:ho

```

```

306 >
307 <span className="flex items-center gap-3 text-sm font-semibold text-slate-800 dark:text-slate-200">
308   <span className="text-lg">0=0</span>
309   {t("profile.feesPayments", "Fees & Payments")}
310 </span>
311 <span className="text-xs text-slate-400">!'</span>
312 </Link>
313 <Link
314   to="/parent/communications?tab=announcements"
315   className="flex items-center justify-between px-4 py-3.5 transition-colors hover:bg-slate-50 dark:ho
316 >
317   <span className="flex items-center gap-3 text-sm font-semibold text-slate-800 dark:text-slate-200">
318     <span className="text-lg">0=0</span>
319     {t("profile.announcements", "Announcements")}
320   </span>
321   <span className="text-xs text-slate-400">!'</span>
322 </Link>
323 </div>
324
325 {/ * % % 4 . 2-Column Grid: Privacy & Notification Preferences % % */}
326 <div className="grid grid-cols-1 gap-4 lg:grid-cols-2">
327   {/ * Privacy & what you can see */}
328   <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
329     <div className="mb-3 flex items-center justify-between">
330       <div className="flex items-center gap-2">
331         <ParentSectionIcon emoji="0=Y " />
332         <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-10
333           {t("profile.privacyTitle", "Privacy & what you can see")}
334       </h2>
335     </div>
336     <WhyThisPopover
337       title="Parent Privacy & Consent"
338       reasons=[
339         "You see growth, wellbeing signals and strengths – never raw exam scores or her private journa
340       ]
341     </WhyThisPopover>
342   </div>
343
344   <div className="space-y-2.5">
345     {[
346       {
347         label: t(
348           "profile.growthSummary",
349           "Growth & wellbeing summaries"
350         ),
351         status: "Shared",
352         pill: "bg-emerald-50 text-emerald-700 border-emerald-200",
353       },
354       {
355         label: t("profile.rawScores", "Raw exam scores"),
356         status: "Not shared",
357         pill: "bg-blue-50 text-blue-700 border-blue-200",
358       },
359       {
360         label: t("profile.privateJournal", "Private journal"),
361         status: "Private to Maya",
362         pill: "bg-blue-50 text-blue-700 border-blue-200",
363       },
364       {
365         label: t("profile.tutorConvos", "Tutor conversations"),
366         status: "Private to Maya",
367         pill: "bg-blue-50 text-blue-700 border-blue-200",
368       },
369       {
370         label: t("profile.teacherFeedback", "Teacher feedback"),
371         status: "Shared",
372         pill: "bg-emerald-50 text-emerald-700 border-emerald-200",
373       },
374       {
375         label: t("profile.attendanceRecord", "Attendance record"),
376         status: "Shared",
377         pill: "bg-emerald-50 text-emerald-700 border-emerald-200",
378       },
379     ]}.map((item) => (
380       <div
381         key={item.label}
382         className="flex items-center justify-between text-sm"
383       >
384         <span className="text-slate-700 dark:text-slate-300">
385           {item.label}
386         </span>
387         <span
388           className={cn(
389             "rounded-full border px-2.5 py-0.5 text-xs font-bold",
390             item.pill
391           )}
392       >
393         {item.status}
394       </span>
395     </div>
396   ))}
397 </div>
398 </div>
399
400 {/ * Notification preferences (exact prototype EdvToggle switches) */}
401 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
402   <div className="mb-3 flex items-center gap-2">
403     <ParentSectionIcon emoji="0=Y " />
404     <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100"
405       {t("profile.notificationsTitle", "Notifications")}
406     </h2>
407   </div>
408
409   <div className="space-y-3">

```

```

410 <div className="flex items-center justify-between py-1">
411 <div>
412 <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
413   {t("profile.weeklyGrowthStory", "Weekly growth story")}
414 </p>
415 <p className="text-xs text-slate-400">
416   Digest delivered every Sunday
417 </p>
418 </div>
419 <EdvToggle
420   checked={prefs.weekly_growth}
421   onCheckedChange={(val) =>
422     handleTogglePref("weekly_growth", val)
423   }
424 </>
425 </div>
426
427 <div className="flex items-center justify-between border-t border-slate-100 pt-2.5 dark:border-sla
428 <div>
429 <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
430   {t("profile.wellbeingAlertsOnly", "Wellbeing alerts only")}
431 </p>
432 <p className="text-xs text-slate-400">
433   Important habit and focus alerts
434 </p>
435 </div>
436 <EdvToggle
437   checked={prefs.wellbeing_only}
438   onCheckedChange={(val) =>
439     handleTogglePref("wellbeing_only", val)
440   }
441 </>
442 </div>
443
444 <div className="flex items-center justify-between border-t border-slate-100 pt-2.5 dark:border-sla
445 <div>
446 <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
447   {t("profile.celebrateImprovements", "Celebrate improvements")}
448 </p>
449 <p className="text-xs text-slate-400">
450   Milestone reached celebrations
451 </p>
452 </div>
453 <EdvToggle
454   checked={prefs.celebrate_improvements}
455   onCheckedChange={(val) =>
456     handleTogglePref("celebrate_improvements", val)
457   }
458 </>
459 </div>
460
461 <div className="flex items-center justify-between border-t border-slate-100 pt-2.5 dark:border-sla
462 <div>
463 <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
464   {t("profile.quietHours", "Quiet hours")}
465 </p>
466 <p className="text-xs text-slate-400">
467   Pause non-urgent alerts overnight ({prefs.timezone})
468 </p>
469 </div>
470 <EdvToggle
471   checked={prefs.quiet_hours_enabled}
472   onCheckedChange={(val) =>
473     handleTogglePref("quiet_hours_enabled", val)
474   }
475 </>
476 </div>
477
478 {prefs.quiet_hours_enabled && (
479 <div className="flex items-center gap-2 border-t border-slate-100 pt-2.5 text-xs text-slate-500
480 <span>From</span>
481 <input
482   type="time"
483   value={prefs.quiet_start}
484   onChange={(e) =>
485     setPrefs({ ...prefs, quiet_start: e.target.value })
486   }
487   className="rounded-lg border border-slate-200 px-2 py-1 font-bold text-slate-800 dark:border
488 </>
489 <span>to</span>
490 <input
491   type="time"
492   value={prefs.quiet_end}
493   onChange={(e) =>
494     setPrefs({ ...prefs, quiet_end: e.target.value })
495   }
496   className="rounded-lg border border-slate-200 px-2 py-1 font-bold text-slate-800 dark:border
497 </>
498 </div>
499 )}
500
501 <div className="border-t border-slate-100 pt-2.5 dark:border-slate-800">
502 <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
503   Mute course alerts
504 </p>
505 <p className="text-xs text-slate-400 mb-2">
506   Stop notifications for a specific course
507 </p>
508 <div className="flex flex-wrap gap-2">
509   {[ "Databases", "Writing", "Math" ].map((course) => {
510     const isMuted = prefs.muted_courses.has(course);
511     return (
512       <button
513         key={course}

```

```

514         type="button"
515         onClick={() => toggleCourseMute(course)}
516         className={cn(
517             "rounded-xl border px-3 py-1 text-xs font-bold transition-colors",
518             isMuted
519               ? "border-amber-300 bg-amber-50 text-amber-800"
520               : "border-slate-200 bg-slate-50 text-slate-700 hover:bg-slate-100 dark:border-slate-
521             })
522         >
523         {course} {isMuted ? "ðŸ" : ""}
524       </button>
525     );
526   });
527 </div>
528 </div>
529 </div>
530 </div>
531 </div>
532
533 /* %% 5 . Security & Access %% */
534 <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.04
535 <div className="mb-3 flex items-center gap-2">
536   <ParentSectionIcon emoji="ðŸ" />
537   <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
538     {t("profile.securityTitle", "Security & access")}
539   </h2>
540 </div>
541
542 <div className="space-y-3 divide-y divide-slate-100 dark:divide-slate-800">
543   <div className="flex items-center justify-between pt-2">
544     <div>
545       <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
546         Change password
547       </p>
548       <p className="text-xs text-slate-400">
549         Last changed 2 months ago
550       </p>
551     </div>
552     <ParentButton
553       variant="ghost"
554       size="sm"
555       onClick={() => toast.info("Opening password change...")}
556     >
557       Change
558     </ParentButton>
559   </div>
560
561   <div className="flex items-center justify-between pt-3">
562     <span className="text-sm font-semibold text-slate-800 dark:text-slate-200">
563       Two-factor authentication
564     </span>
565     <span
566       className={cn(
567         "rounded-full border px-2.5 py-0.5 text-xs font-bold",
568         isMfaEnabled
569           ? "border-emerald-200 bg-emerald-50 text-emerald-700"
570           : "border-slate-200 bg-slate-50 text-slate-600"
571       )}
572     >
573       {isMfaEnabled ? "Enabled" : "Disabled"}
574     </span>
575   </div>
576
577   <div className="flex items-center justify-between pt-3">
578     <div>
579       <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
580         Active sessions
581       </p>
582       <p className="text-xs text-slate-400">1 device signed in</p>
583     </div>
584     <ParentButton
585       variant="ghost"
586       size="sm"
587       onClick={() => toast.info("Reviewing active sessions...")}
588     >
589       Review
590     </ParentButton>
591   </div>
592
593   <div className="flex items-center justify-between pt-3">
594     <div>
595       <p className="text-sm font-semibold text-slate-800 dark:text-slate-200">
596         Export my data
597       </p>
598       <p className="text-xs text-slate-400">
599         Download your account data as CSV
600       </p>
601     </div>
602     <ParentButton
603       variant="ghost"
604       size="sm"
605       onClick={() =>
606         toast.success("Preparing account data export CSV...")
607       }
608     >
609       Export
610     </ParentButton>
611   </div>
612
613   <div className="flex items-center justify-between pt-3">
614     <div>
615       <p className="text-sm font-bold text-red-600">
616         Delete my account
617       </p>

```

```

618 |         <p className="text-xs text-slate-400">
619 |             Anonymize profile & PII (cannot be undone)
620 |         </p>
621 |     </div>
622 |     <ParentButton
623 |       variant="danger"
624 |       size="sm"
625 |       onClick={() => {
626 |         if (
627 |           window.confirm(
628 |             "Delete your account? This anonymizes your profile and cannot be undone."
629 |           )
630 |         ) {
631 |           toast.error("Account deletion requested");
632 |         }
633 |       }}
634 |     > Delete
635 |   </ParentButton>
636 | </div>
637 | </div>
638 | </div>
639 | </div>
640 | );
641 | };
642 | };
643 |
644 | export default ParentProfilePage;
645 |

```

FILE: [src/pages/parent/support/ParentSupportPage.tsx](#)

TYPE: .tsx | LINES: 1-285 | SHA256: 0382bbc3fe12ffdcfa52c07544ad6a32f0ce3e37476b13999ab0ff1ac31fc69c

```

1 | import { useState, useMemo } from "react";
2 | import { useTranslation } from "react-i18next";
3 | import { toast } from "sonner";
4 | import { Send, Sparkles } from "lucide-react";
5 |
6 | import { Shimmer } from "@design-system";
7 | import { ParentButton } from "@components/shared/ParentButton";
8 | import { ParentSectionIcon } from "@components/shared/ParentSectionIcon";
9 | import { useAuth } from "@hooks/useAuth";
10 | import { useParentDashboardAggregate } from "@hooks/useParentDashboardAggregate";
11 | import { NoLinkedStudents } from "@components/shared/EmptyState";
12 | import { supabase } from "@lib/supabase";
13 |
14 | const DEFAULT_MESSAGE =
15 |   "Hi Prof. Ahmed, I noticed Maya is doing really well in databases – is there a way to keep that momentum goi
16 |
17 | const AI_STARTERS = [
18 |   "Hi teacher, I'd love to know how Maya is participating in group activities this week.",
19 |   "Hi! Maya enjoyed the recent project. What is one area we can practice together at home?",
20 |   "Hello! I wanted to check if there are any upcoming deadlines or milestones we should prepare for.",
21 | ];
22 |
23 | const ParentSupportPage = () => {
24 |   const { t } = useTranslation("common");
25 |   const { user } = useAuth();
26 |   const aggregate = useParentDashboardAggregate(user?.id);
27 |   const children = useMemo(
28 |     () => aggregate.data?.children ?? [],
29 |     [aggregate.data]
30 |   );
31 |
32 |   const [message, setMessage] = useState(DEFAULT_MESSAGE);
33 |   const [starterIdx, setStarterIdx] = useState(0);
34 |   const [savedIdeas, setSavedIdeas] = useState<Set<string>>(() => {
35 |     try {
36 |       const stored = localStorage.getItem("parent_saved_support_ideas");
37 |       return stored ? new Set(JSON.parse(stored)) : new Set();
38 |     } catch {
39 |       return new Set();
40 |     }
41 |   });
42 |
43 |   const selectedChild = children[0];
44 |   const name = selectedChild?.student_name
45 |     ? selectedChild.student_name.split(" ")[0]
46 |     : "Child";
47 |
48 |   const handleSaveIdea = (ideaId: string, ideaLabel: string) => {
49 |     setSavedIdeas((prev) => {
50 |       const next = new Set(prev);
51 |       if (next.has(ideaId)) {
52 |         next.delete(ideaId);
53 |         toast.info(t("parent.support.unsaved", "Idea removed from saved list"));
54 |       } else {
55 |         next.add(ideaId);
56 |         toast.success(
57 |           t("parent.support.saved", "Saved: {{label}} +P", { label: ideaLabel })
58 |         );
59 |       }
60 |       try {
61 |         localStorage.setItem(
62 |           "parent_saved_support_ideas",
63 |           JSON.stringify(Array.from(next))
64 |         );
65 |       } catch {
66 |         // Fallback
67 |       }
68 |       return next;
69 |     });
70 |   };
71 |
72 |   const handleSuggest = () => {

```



```

73 |     const nextIdx = (starterIdx + 1) % AI_STARTERS.length;
74 |     setStarterIdx(nextIdx);
75 |     const nextMsg = AI_STARTERS[nextIdx] ?? DEFAULT_MESSAGE;
76 |     setMessage(nextMsg);
77 |     toast.success(
78 |       t("parent.support.suggested", "'( AI suggested a message starter")
79 |     );
80 |   };
81 | };
82 | const handleSend = async () => {
83 |   if (!message.trim()) return;
84 |
85 |   if (user?.id) {
86 |     try {
87 |       await supabase.from("notifications").insert({
88 |         user_id: user.id,
89 |         title: "Teacher Message Sent ' p ",
90 |         body: message,
91 |         type: "teacher_message",
92 |         is_read: true,
93 |       } as never);
94 |     } catch {
95 |       // Fallback silently
96 |     }
97 |   }
98 |
99 |   toast.success(t("parent.support.sent", "' p Message sent to teacher"));
100 |   setMessage("");
101 | };
102 |
103 | if (aggregate.isLoading) {
104 |   return (
105 |     <div className="space-y-4">
106 |       <Shimmer className="h-32 rounded-2xl" />
107 |       <Shimmer className="h-48 rounded-2xl" />
108 |     </div>
109 |   );
110 | }
111 |
112 | if (children.length === 0) {
113 |   return <NoLinkedStudents />;
114 | }
115 |
116 | return (
117 |   <div className="space-y-5 no-scrollbar">
118 |     </* % % Heading % % */>
119 |     <div>
120 |       <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
121 |         {t("parent.support.title", {
122 |           defaultValue: "Ways to support {{name}}",
123 |           name,
124 |         })}
125 |       </h1>
126 |       <p className="mt-0.5 text-xs text-slate-500">
127 |         {t(
128 |           "parent.support.subtitle",
129 |           "Small, specific actions – matched to where she is this week."
130 |         )}
131 |       </p>
132 |     </div>
133 |
134 |     </* % % At-home ideas % % */>
135 |     <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24,40,0.04)]">
136 |       <div className="mb-3 flex items-center gap-2">
137 |         <ParentSectionIcon emoji="ðŸ’Š" />
138 |         <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
139 |           {t("parent.support.atHomeTitle", "At-home ideas")}
140 |         </h2>
141 |       </div>
142 |
143 |       <div className="space-y-2.5">
144 |         {[
145 |           {
146 |             id: "idea-teach-back",
147 |             icon: "ðŸ’Š",
148 |             title: t("parent.support.teachBackTitle", "Ask her to teach you"),
149 |             desc: t(
150 |               "parent.support.teachBackDesc",
151 |               "Explain one database idea to me." Retrieval practice + it shows you care."
152 |             ),
153 |           },
154 |           {
155 |             id: "idea-math-encourage",
156 |             icon: "ðŸ’Š",
157 |             title: t("parent.support.mathTitle", "Gentle math encouragement"),
158 |             desc: t(
159 |               "parent.support.mathDesc",
160 |               "Math is her growing edge – celebrate effort over getting it right."
161 |             ),
162 |           },
163 |           {
164 |             id: "idea-evening-rhythm",
165 |             icon: "ðŸ’Š",
166 |             title: t("parent.support.eveningsTitle", "Protect her evenings"),
167 |             desc: t(
168 |               "parent.support.eveningsDesc",
169 |               "Her rhythm is healthy – keeping a consistent stop-time helps it stick."
170 |             ),
171 |           },
172 |         ]}.map((idea) => {
173 |           const isSaved = savedIdeas.has(idea.id);
174 |           return (
175 |             <div
176 |               key={idea.id}

```

```

177         className="flex items-start gap-3 rounded-xl border border-slate-100 bg-slate-50/50 p-3 dark:b
178     >
179     <span className="text-xl">{idea.icon}</span>
180     <div className="min-w-0 flex-1">
181         <p className="text-sm font-bold text-slate-900 dark:text-slate-100">
182             {idea.title}
183         </p>
184         <p className="text-xs text-slate-500">{idea.desc}</p>
185     </div>
186     <ParentButton
187         variant={isSaved ? "secondary" : "ghost"}
188         size="sm"
189         onClick={() => handleSaveIdea(idea.id, idea.title)}
190         className="h-auto px-2.5 py-1 text-xs font-bold"
191     >
192         {isSaved ? "& Saved" : t("common.save", "Save")}
193     </ParentButton>
194 </div>
195     });
196     }}}
197 </div>
198 </div>
199
200 /* %% 2-Column Grid: Message Teacher & Helpful Reads %% */
201 <div className="grid grid-cols-1 gap-4 lg:grid-cols-2">
202     /* Message the teacher */
203     <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
204         <div className="mb-1 flex items-center gap-2">
205             <ParentSectionIcon emoji="p" />
206             <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
207                 {t("parent.support.messageTitle", "Message the teacher")}
208             </h2>
209         </div>
210         <p className="mb-2.5 text-xs font-semibold text-slate-500">
211             Prof. Ahmed · Computer Science
212         </p>
213         <textarea
214             value={message}
215             onChange={(e) => setMessage(e.target.value)}
216             rows={3}
217             className="w-full rounded-xl border border-slate-200 bg-white p-3 text-sm text-slate-900 shadow-xs
218             placeholder={t(
219                 "parent.support.placeholder",
220                 "Write a note... (AI can suggest a starter)"
221             )}
222         />
223         <div className="mt-2.5 flex items-center gap-2">
224             <ParentButton variant="primary" size="sm" onClick={handleSend}>
225                 <Send className="h-3.5 w-3.5" aria-hidden="true" />
226                 {t("common.send", "Send")}
227             </ParentButton>
228             <ParentButton variant="ghost" size="sm" onClick={handleSuggest}>
229                 <Sparkles
230                     className="h-3.5 w-3.5 text-amber-500"
231                     aria-hidden="true"
232                 />
233                 {t("parent.support.suggestBtn", "Suggest")}
234             </ParentButton>
235         </div>
236     </div>
237
238     /* Helpful reads */
239     <div className="rounded-[20px] border border-[#eef2f6] bg-white p-4 shadow-[0_1px_2px_rgba(16,24,40,0.
240         <div className="mb-3 flex items-center gap-2">
241             <ParentSectionIcon emoji="ðŸ“œ" />
242             <h2 className="text-xs font-extrabold uppercase tracking-wider text-slate-900 dark:text-slate-100">
243                 {t("parent.support.readsTitle", "Helpful reads")}
244             </h2>
245         </div>
246         <div className="space-y-2">
247             {[
248                 {
249                     icon: "ðŸ“œ",
250                     title: t(
251                         "parent.support.read1",
252                         "How to praise effort, not just results"
253                     ),
254                 },
255                 {
256                     icon: "ðŸ“š",
257                     title: t(
258                         "parent.support.read2",
259                         "Why 'teach-back' helps memory"
260                     ),
261                 },
262             ]}.map((item) => (
263                 <button
264                     key={item.title}
265                     type="button"
266                     onClick={() =>
267                         toast.info(t("parent.support.openingGuide", "Opening guide..."))
268                     }
269                     className="flex w-full items-center gap-3 rounded-lg border border-transparent p-2.5 text-star
270                 >
271                     <span className="text-lg">{item.icon}</span>
272                     <span className="text-sm font-semibold text-slate-800 dark:text-slate-200">
273                         {item.title}
274                     </span>
275                 </button>
276             ))
277         </div>
278     </div>
279 </div>
280 </div>

```

```

281 | });
282 | };
283 |
284 | export default ParentSupportPage;
285 |

```

FILE: src/pages/public/LegalPage.tsx

TYPE: .tsx | LINES: 1-158 | SHA256: 7cb7dcb1a6a60257d64294e9fc70354c6871cccb320f113f36dbe5aa81b43a4f

```

1 | import {
2 |   ArrowLeft,
3 |   BookOpenText,
4 |   Mail,
5 |   Scale,
6 |   ShieldCheck,
7 | } from "lucide-react";
8 | import { useTranslation } from "react-i18next";
9 | import { Link } from "react-router-dom";
10 |
11 | import { Button } from "@components/ui/button";
12 | import { Card, CardContent } from "@components/ui/card";
13 | import { LanguageSwitcher } from "@components/shared/LanguageSwitcher";
14 | import { cn } from "@lib/utlis";
15 |
16 | export type LegalPageKind = "terms" | "privacy";
17 |
18 | const SECTION_COUNTS: Record<LegalPageKind, number> = {
19 |   terms: 8,
20 |   privacy: 8,
21 | };
22 |
23 | const CONTACT_EMAIL: Record<LegalPageKind, string> = {
24 |   terms: "legal@edeviser.com",
25 |   privacy: "privacy@edeviser.com",
26 | };
27 |
28 | export const LegalPage = ({ kind }: { kind: LegalPageKind }) => {
29 |   const { t } = useTranslation("common");
30 |   const isTerms = kind === "terms";
31 |   const Icon = isTerms ? Scale : ShieldCheck;
32 |   const otherKind: LegalPageKind = isTerms ? "privacy" : "terms";
33 |   const sections = Array.from(
34 |     { length: SECTION_COUNTS[kind] },
35 |     (_, index) => index + 1
36 |   );
37 |
38 |   return (
39 |     <div className="min-h-screen bg-[radial-gradient(circle_at_top,#eff6ff_0%,#f8fafc_40%,#f8fafc_100%)] text-
40 |       <header className="border-b border-slate-200/80 bg-white/90 backdrop-blur">
41 |         <div className="mx-auto flex min-h-16 max-w-6xl items-center justify-between gap-4 px-4 sm:px-6">
42 |           <Button asChild variant="ghost" className="h-auto gap-2 px-1">
43 |             <Link to="/login">
44 |               <span className="grid size-9 place-items-center rounded-xl bg-gradient-to-br from-blue-600 to-cy
45 |                 E
46 |               </span>
47 |               <span className="text-lg font-black tracking-tight">
48 |                 Edeviser
49 |               </span>
50 |             </Link>
51 |           </Button>
52 |           <LanguageSwitcher />
53 |         </div>
54 |       </header>
55 |
56 |       <div className="mx-auto grid max-w-6xl gap-6 px-4 py-8 sm:px-6 lg:grid-cols-[minmax(0,1fr)_260px] lg:ite
57 |         <div className="min-w-0">
58 |           <div className="mb-6 flex items-start gap-4">
59 |             <span
60 |               className={cn(
61 |                 "grid size-12 shrink-0 place-items-center rounded-2xl border shadow-sm",
62 |                 isTerms
63 |                   ? "border-blue-100 bg-blue-50 text-blue-600"
64 |                   : "border-cyan-100 bg-cyan-50 text-cyan-600"
65 |               )}
66 |             >
67 |               <Icon className="size-6" />
68 |             </span>
69 |             <div>
70 |               <p className="text-xs font-black uppercase tracking-[0.18em] text-blue-600">
71 |                 {t("legal.eyebrow")}
72 |               </p>
73 |               <h1 className="mt-1 text-3xl font-black tracking-tight sm:text-4xl">
74 |                 {t(`legal.${kind}.title`)}
75 |               </h1>
76 |               <p className="mt-2 max-w-2xl text-sm leading-6 text-slate-600">
77 |                 {t(`legal.${kind}.subtitle`)}
78 |               </p>
79 |               <p className="mt-2 text-xs text-slate-400">
80 |                 {t("legal.lastUpdated")}
81 |               </p>
82 |             </div>
83 |           </div>
84 |
85 |           <Card className="border-slate-200/80 bg-white shadow-sm">
86 |             <CardContent className="space-y-0 p-0">
87 |               {sections.map((section, index) => (
88 |                 <section
89 |                   key={section}
90 |                   className={cn(
91 |                     "px-5 py-6 sm:px-7",
92 |                     index > 0 && "border-t border-slate-100"
93 |                   )}
94 |                 >
95 |                   <h2 className="text-base font-black tracking-tight text-slate-900">

```

```

96 |         {t(`legal.${kind}.sections.${section}.title`)}
97 |       </h2>
98 |       <p className="mt-2 text-sm leading-7 text-slate-600">
99 |         {t(`legal.${kind}.sections.${section}.body`)}
100 |       </p>
101 |       {section === SECTION_COUNTS[kind] && (
102 |         <Button
103 |           asChild
104 |           variant="link"
105 |           size="sm"
106 |           className="mt-2 h-auto gap-2 px-0 text-blue-600"
107 |         >
108 |           <a href={`mailto:${CONTACT_EMAIL[kind]}`} >
109 |             <Mail className="size-4" />
110 |             {CONTACT_EMAIL[kind]}
111 |           </a>
112 |         </Button>
113 |       )}
114 |     </section>
115 |   )}
116 | </CardContent>
117 | </Card>
118 | </div>
119 |
120 | <aside className="space-y-3 lg:sticky lg:top-6">
121 |   <Card className="border-slate-200/80 bg-white shadow-sm">
122 |     <CardContent className="p-5">
123 |       <BookOpenText className="size-5 text-blue-600" />
124 |       <h2 className="mt-3 text-sm font-black">
125 |         {t("legal.summary.title")}
126 |       </h2>
127 |       <p className="mt-2 text-xs leading-5 text-slate-500">
128 |         {t(`legal.${kind}.summary`)}
129 |       </p>
130 |     </CardContent>
131 |   </Card>
132 |
133 |   <Button
134 |     asChild
135 |     variant="outline"
136 |     className="h-auto w-full justify-between py-3"
137 |   >
138 |     <Link to={`/${otherKind}`} >
139 |       {t(`legal.${otherKind}.title`)}
140 |       <ArrowLeft className="size-4 rtl:rotate-180" />
141 |     </Link>
142 |   </Button>
143 |   <Button
144 |     asChild
145 |     variant="ghost"
146 |     className="h-auto w-full justify-between py-3 text-slate-600"
147 |   >
148 |     <Link to="/login">
149 |       {t("legal.backToSignIn")}
150 |       <ArrowLeft className="size-4 rtl:rotate-180" />
151 |     </Link>
152 |   </Button>
153 | </aside>
154 | </div>
155 | </div>
156 | );
157 | };
158 |

```

FILE: src/pages/public/PrivacyPage.tsx

TYPE: .tsx | LINES: 1-8 | SHA256: 643358ed73ea7b96966a8b5d771ef68e34d4a2a2dc0827b1bcb62aaa29f60a96

```

1 | import { LegalPage } from "@pages/public/LegalPage";
2 |
3 | const PrivacyPage = () => {
4 |   return <LegalPage kind="privacy" />;
5 | };
6 |
7 | export default PrivacyPage;
8 |

```

FILE: src/pages/public/PublicPortfolio.tsx

TYPE: .tsx | LINES: 1-274 | SHA256: 26a5046bb2236ff161cd4e9ef91657dd29b43af4c6174794a83a2bbfbba4fb74

```

1 | // =====
2 | // PublicPortfolio - Unauthenticated, read-only portfolio view
3 | // Route: /portfolio/:student_id
4 | //
5 | // Task 24.2: Enforce 403/404 on the public portfolio route (R24.3 / 24.3a / 24.4).
6 | //
7 | // Access control is decided at the DATA LAYER: `usePortfolioAccess` calls the
8 | // `portfolio_public_access` SECURITY DEFINER RPC, which returns an authorization
9 | // discriminator (`authorized` | `forbidden` | `not_found`) WITHOUT leaking any
10 | // portfolio content. `mapPortfolioAccessToRoute` translates that discriminator
11 | // into the route outcome:
12 | //   - `authorized` !' render the portfolio
13 | //   - `forbidden` !' 403 (exists but not authorized - never collapsed into a 404)
14 | //   - `not_found` !' 404 (no such portfolio)
15 | //
16 | // The portfolio content query (`usePublicPortfolio`) is gated so it only runs
17 | // once the request is authorized, and it ALWAYS runs under RLS regardless - so
18 | // unauthorized content can never be returned even if the client misbehaves.
19 | // =====
20 |
21 | import { useParams } from "react-router-dom";
22 | import { useTranslation } from "react-i18next";
23 | import { Card } from "@components/ui/card";
24 | import { usePortfolioAccess, usePublicPortfolio } from "@hooks/usePortfolio";
25 | import {

```

```

26 | mapPortfolioAccessToRoute,
27 | type PortfolioAccessStatus,
28 | } from "@lib/portfolioAccess";
29 | import { GradientCardHeader } from "@design-system";
30 | import {
31 |   InlineNoAttainmentData,
32 |   InlineNoBadges,
33 | } from "@components/shared/EmptyState";
34 | import { Award, BookOpen, ShieldCheck } from "lucide-react";
35 | import { cn } from "@lib/Utils";
36 | import { format } from "date-fns";
37 | import type { AttainmentLevel } from "@types/app";
38 |
39 | const ATTAINMENT_STYLES: Record<AttainmentLevel, string> = {
40 |   Excellent: "text-green-600 bg-green-50",
41 |   Satisfactory: "text-blue-600 bg-blue-50",
42 |   Developing: "text-yellow-600 bg-yellow-50",
43 |   Not_Yet: "text-red-600 bg-red-50",
44 | };
45 |
46 | interface PortfolioNoticeProps {
47 |   title: string;
48 |   body: string;
49 |   /** Optional HTTP-style status code to surface (e.g. 403, 404). */
50 |   status?: 403 | 404;
51 | }
52 |
53 | /**
54 |  * Centered, content-free notice panel used for the missing-id / 403 / 404
55 |  * states. Never renders any protected portfolio content.
56 |  */
57 | const PortfolioNotice = ({ title, body, status }: PortfolioNoticeProps) => {
58 |   const { t } = useTranslation("student");
59 |   return (
60 |     <div className="min-h-screen bg-slate-50 flex items-center justify-center p-6">
61 |       <Card className="bg-white border-0 shadow-md rounded-xl p-8 text-center max-w-md">
62 |         <ShieldCheck className="h-12 w-12 text-gray-300 mx-auto mb-4" />
63 |         <h2 className="text-lg font-bold text-gray-700">{title}</h2>
64 |         <p className="text-sm text-gray-500 mt-2">{body}</p>
65 |         {status !== undefined && (
66 |           <p className="text-xs font-black tracking-widest uppercase text-gray-300 mt-4">
67 |             {t("publicPortfolio.error.code", { status })}
68 |           </p>
69 |         )}
70 |       </Card>
71 |     </div>
72 |   );
73 | };
74 |
75 | const PortfolioShimmer = () => {
76 |   <div className="min-h-screen bg-slate-50 p-6">
77 |     <div className="max-w-3xl mx-auto space-y-6">
78 |       <div className="h-8 w-48 rounded-lg animate-shimmer" />
79 |       <div className="h-64 rounded-xl animate-shimmer" />
80 |     </div>
81 |   </div>
82 | );
83 |
84 | const PublicPortfolio = () => {
85 |   const { t } = useTranslation("student");
86 |   const { student_id } = useParams<{ student_id: string }>();
87 |
88 |   // Data-layer access discriminator (403 vs 404 without leaking content).
89 |   const {
90 |     data: accessStatus,
91 |     isLoading: isAccessLoading,
92 |     isError: isAccessError,
93 |   } = usePortfolioAccess(student_id);
94 |
95 |   // Conservatively treat an unresolved/failed discriminator as `forbidden`
96 |   // (!' 403, never renders) so a malformed or failed response can never expose
97 |   // protected content. Mirrors `parsePortfolioAccessStatus`.
98 |   const status: PortfolioAccessStatus = isAccessError
99 |     ? "forbidden"
100 |     : accessStatus ?? "forbidden";
101 |   const outcome = mapPortfolioAccessToRoute(status);
102 |
103 |   // Content query is gated on authorization; it still runs under RLS regardless.
104 |   const { data, isLoading: isContentLoading } = usePublicPortfolio(student_id, {
105 |     enabled: outcome.kind === "render",
106 |   });
107 |
108 |   // No id in the URL: nothing to resolve.
109 |   if (!student_id) {
110 |     return (
111 |       <PortfolioNotice
112 |         title={t("publicPortfolio.error.missingIdTitle")}
113 |         body={t("publicPortfolio.error.missingIdBody")}
114 |       />
115 |     );
116 |   }
117 |
118 |   // Resolving the access discriminator.
119 |   if (isAccessLoading) {
120 |     return <PortfolioShimmer />;
121 |   }
122 |
123 |   // 403 Forbidden – the portfolio exists but is not authorized for public view.
124 |   if (outcome.kind === "error" && outcome.status === 403) {
125 |     return (
126 |       <PortfolioNotice
127 |         title={t("publicPortfolio.error.forbiddenTitle")}
128 |         body={t("publicPortfolio.error.forbiddenBody")}
129 |         status={403}

```

```

130 |     />
131 |   };
132 | }
133 |
134 | // 404 Not Found - no portfolio exists for this id.
135 | if (outcome.kind === "error" && outcome.status === 404) {
136 |   return (
137 |     <PortfolioNotice
138 |       title={t("publicPortfolio.error.notFoundTitle")}
139 |       body={t("publicPortfolio.error.notFoundBody")}
140 |       status={404}
141 |     />
142 |   );
143 | }
144 |
145 | // Authorized: render the portfolio content (loaded under RLS).
146 | if (isLoading) {
147 |   return <PortfolioShimmer />;
148 | }
149 |
150 | // Defense-in-depth: authorized but RLS returned no content - deny rather than
151 | // render an empty shell.
152 | if (!data) {
153 |   return (
154 |     <PortfolioNotice
155 |       title={t("publicPortfolio.error.forbiddenTitle")}
156 |       body={t("publicPortfolio.error.forbiddenBody")}
157 |       status={403}
158 |     />
159 |   );
160 | }
161 |
162 | return (
163 |   <div className="min-h-screen bg-slate-50 p-6">
164 |     <div className="max-w-3xl mx-auto space-y-6">
165 |       { /* Hero */ }
166 |       <Card
167 |         className="border-0 shadow-lg rounded-xl overflow-hidden text-white"
168 |         style={{
169 |           background:
170 |             "linear-gradient(135deg, #0f172a 0%, #1e3a8a 50%, #312e81 100%)",
171 |         }}
172 |       >
173 |         <div className="p-6">
174 |           <h1 className="text-2xl font-bold tracking-tight">
175 |             {data.full_name}
176 |           </h1>
177 |           <p className="text-sm text-white/70 mt-1">
178 |             {t("publicPortfolio.subtitle")}
179 |           </p>
180 |           <div className="flex gap-6 mt-4">
181 |             <div>
182 |               <p className="text-[10px] font-black tracking-widest uppercase text-white/50">
183 |                 {t("publicPortfolio.totalXP")}
184 |               </p>
185 |               <p className="text-xl font-black text-amber-400">
186 |                 {data.totalXP.toLocaleString()}
187 |               </p>
188 |             </div>
189 |             <div>
190 |               <p className="text-[10px] font-black tracking-widest uppercase text-white/50">
191 |                 {t("publicPortfolio.level")}
192 |               </p>
193 |               <p className="text-xl font-black">{data.level}</p>
194 |             </div>
195 |           </div>
196 |         </div>
197 |       </Card>
198 |
199 |       { /* CLO Attainment Levels */ }
200 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
201 |         <GradientCardHeader
202 |           icon={BookOpen}
203 |           title={t("publicPortfolio.sections.cloAttainment")}
204 |         />
205 |         <div className="p-6">
206 |           {data.clos.length === 0 ? (
207 |             <InlineNoAttainmentData />
208 |           ) : (
209 |             <div className="space-y-2">
210 |               {data.clos.map((clo, i) => (
211 |                 <div
212 |                   key={i}
213 |                   className="flex items-center justify-between rounded-lg border border-slate-100 p-3"
214 |                 >
215 |                   <span className="text-sm font-medium text-gray-800 truncate">
216 |                     {clo.clo_title}
217 |                   </span>
218 |                   <span
219 |                     className={cn(
220 |                       "inline-flex items-center rounded-full px-2.5 py-0.5 text-xs font-bold shrink-0",
221 |                       ATTAINMENT_STYLES[clo.attainment_level]
222 |                     )}
223 |                   >
224 |                     {clo.attainment_level.replace("_", " ")}
225 |                   </span>
226 |                 </div>
227 |               ))}
228 |             </div>
229 |           )}
230 |         </div>
231 |       </Card>
232 |
233 |       { /* Badge Collection */ }

```

```

234 |         <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
235 |             <GradientCardHeader
236 |                 icon={Award}
237 |                 title={t("publicPortfolio.sections.badges")}
238 |             />
239 |             <div className="p-6">
240 |                 {data.badges.length === 0 ? (
241 |                     <InlineNoBadges />
242 |                 ) : (
243 |                     <div className="grid grid-cols-3 sm:grid-cols-4 md:grid-cols-5 gap-4">
244 |                         {data.badges.map((b) => (
245 |                             <Card
246 |                                 key={b.badge_key}
247 |                                 className="bg-white border-0 shadow-md rounded-xl p-4 flex flex-col items-center text-cent
248 |                             >
249 |                                 <span className="text-3xl" aria-hidden="true">
250 |                                     {b.emoji}
251 |                                 </span>
252 |                                 <span className="text-xs font-bold tracking-wide">
253 |                                     {b.badge_name}
254 |                                 </span>
255 |                                 <span className="text-[10px] text-gray-500">
256 |                                     {format(new Date(b.awarded_at), "MMM d, yyyy")}
257 |                                 </span>
258 |                             </Card>
259 |                         ))}
260 |                     </div>
261 |                 )}
262 |             </div>
263 |         </Card>
264 |
265 |         <p className="text-center text-xs text-gray-400">
266 |             {t("publicPortfolio.poweredBy")}
267 |         </p>
268 |     </div>
269 | </div>
270 | );
271 | };
272 |
273 | export default PublicPortfolio;
274 |

```

FILE: src/pages/public/TermsPage.tsx

TYPE: .tsx | LINES: 1-8 | SHA256: 94f21d9980b89375d4685ea04fbbcbdf74cc68a0590bffffd08f40bac31ad933a

```

1 | import { LegalPage } from "@pages/public/LegalPage";
2 |
3 | const TermsPage = () => {
4 |     return <LegalPage kind="terms" />;
5 | };
6 |
7 | export default TermsPage;
8 |

```

FILE: src/pages/ResetPasswordPage.tsx

TYPE: .tsx | LINES: 1-125 | SHA256: 52f215179d36f27b8375a6601488c107a037e801dfa75e19b149dd7e93bcc052

```

1 | import { useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useTranslation } from "react-i18next";
5 | import {
6 |     resetPasswordSchema,
7 |     type ResetPasswordFormData,
8 | } from "@lib/schemas/auth";
9 | import { useAuth } from "@hooks/useAuth";
10 | import {
11 |     Form,
12 |     FormField,
13 |     FormItem,
14 |     FormLabel,
15 |     FormControl,
16 |     FormMessage,
17 | } from "@components/ui/form";
18 | import { Button } from "@design-system";
19 | import { Loader2, ArrowLeft, CheckCircle2 } from "lucide-react";
20 | import { Link } from "react-router-dom";
21 | import AuthShell from "@components/shared/AuthShell";
22 |
23 | const ResetPasswordPage = () => {
24 |     const { t } = useTranslation("auth");
25 |     const { resetPassword } = useAuth();
26 |     const [isSubmitted, setIsSubmitted] = useState(false);
27 |     const [isPending, setIsPending] = useState(false);
28 |
29 |     const form = useForm<ResetPasswordFormData>({
30 |         resolver: zodResolver(resetPasswordSchema),
31 |         defaultValues: { email: "" },
32 |     });
33 |
34 |     const onSubmit = async (data: ResetPasswordFormData) => {
35 |         setIsPending(true);
36 |         try {
37 |             await resetPassword(data.email);
38 |             setIsSubmitted(true);
39 |         } catch {
40 |             // Show generic success message even on error to prevent email enumeration
41 |             setIsSubmitted(true);
42 |         } finally {
43 |             setIsPending(false);
44 |         }
45 |     };
46 |
47 |     return (

```

```

48 | <AuthShell>
49 |   <div className="mb-5">
50 |     <h1 className="text-lg font-black tracking-tight text-slate-900">
51 |       {t("resetPassword.title")}
52 |     </h1>
53 |     <p className="mt-1 text-sm text-slate-500">
54 |       {isSubmitted
55 |         ? t("resetPassword.successMessage")
56 |         : t("resetPassword.subtitle")}
57 |     </p>
58 |   </div>
59 |
60 |   {isSubmitted ? (
61 |     <div className="space-y-6 text-center">
62 |       <div className="mx-auto flex h-12 w-12 items-center justify-center rounded-full bg-green-50">
63 |         <CheckCircle2 className="h-6 w-6 text-green-600" />
64 |       </div>
65 |       <p className="text-sm text-slate-600">
66 |         {t("resetPassword.successMessage")}
67 |       </p>
68 |       <Link
69 |         to="/login"
70 |         className="inline-flex items-center gap-2 text-sm font-bold text-blue-600 hover:underline"
71 |       >
72 |         <ArrowLeft className="h-4 w-4" />
73 |         {t("resetPassword.backToLogin")}
74 |       </Link>
75 |     </div>
76 |   ) : (
77 |     <Form {...form}>
78 |       <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
79 |         <FormField
80 |           control={form.control}
81 |           name="email"
82 |           render={({ field }) => (
83 |             <FormItem>
84 |               <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
85 |                 {t("resetPassword.emailLabel")}
86 |               </FormLabel>
87 |               <FormControl>
88 |                 <input
89 |                   type="email"
90 |                   className="fld"
91 |                   placeholder="you@institution.edu"
92 |                   {...field}
93 |                 />
94 |               </FormControl>
95 |               <FormMessage />
96 |             </FormItem>
97 |           )}
98 |         />
99 |         <Button
100 |           type="submit"
101 |           variant="tactile"
102 |           disabled={isPending}
103 |           className="h-12 w-full"
104 |         >
105 |           {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
106 |           {t("resetPassword.submitButton")}
107 |         </Button>
108 |         <div className="text-center">
109 |           <Link
110 |             to="/login"
111 |             className="inline-flex items-center gap-2 text-sm font-bold text-blue-600 hover:underline"
112 |           >
113 |             <ArrowLeft className="h-4 w-4" />
114 |             {t("resetPassword.backToLogin")}
115 |           </Link>
116 |         </div>
117 |       </form>
118 |     </Form>
119 |   )}
120 | </AuthShell>
121 | );
122 | };
123 |
124 | export default ResetPasswordPage;
125 |

```

FILE: src/pages/shared/CalendarView.tsx

TYPE: .tsx | LINES: 1-325 | SHA256: f4e4d49ff98e70fab84f5ac2f47283989db86c2fb52677c960d0aac772c15f4

```

1 | import { useState, useMemo } from "react";
2 | import { useTranslation } from "react-i18next";
3 | import { Card } from "@components/ui/card";
4 | import { Button } from "@components/ui/button";
5 | import { Badge } from "@components/ui/badge";
6 | import { Tabs, TabList, TabTrigger } from "@components/ui/tabs";
7 | import { ChevronLeft, ChevronRight, Calendar, Lock } from "lucide-react";
8 | import { useCalendarEvents, type CalendarEvent } from "@hooks/useCalendar";
9 | import { dedupeCalendarEvents } from "@lib/calendarDeadlines";
10 | import { Shimmer } from "@design-system";
11 | import ErrorState from "@components/shared/ErrorState";
12 |
13 | type ViewMode = "monthly" | "weekly";
14 |
15 | const CalendarView = () => {
16 |   const { t, i18n } = useTranslation("common");
17 |   const now = new Date();
18 |   const [month, setMonth] = useState(now.getMonth() + 1);
19 |   const [year, setYear] = useState(now.getFullYear());
20 |   const [viewMode, setViewMode] = useState<ViewMode>("monthly");
21 |   const [selectedWeekStart, setSelectedWeekStart] = useState<Date>(() => {
22 |     const d = new Date(now);

```



```

23 |     d.setDate(d.getDate() - d.getDay());
24 |     return d;
25 | });
26 |
27 | const {
28 |     data: rawEvents = [],
29 |     isLoading,
30 |     isError,
31 |     refetch,
32 | } = useCalendarEvents(month, year);
33 |
34 | // R21.4: present a deadline consistently across surfaces – a single logical
35 | // deadline must never be listed twice even if it arrives from more than one
36 | // source. Dedup is pure and lives in `src/lib/calendarDeadlines.ts`.
37 | const events = useMemo(() => dedupeCalendarEvents(rawEvents), [rawEvents]);
38 |
39 | const locale = i18n.language === "ar" ? "ar" : "en-US";
40 | const dayShortLabels = useMemo(
41 |     () => [0, 1, 2, 3, 4, 5, 6].map((d) => t(`calendar.daysShort.${d}`)),
42 |     [t]
43 | );
44 |
45 | const firstDay = new Date(year, month - 1, 1).getDay();
46 | const daysInMonth = new Date(year, month, 0).getDate();
47 |
48 | const prev = () => {
49 |     if (viewMode === "monthly") {
50 |         if (month === 1) {
51 |             setMonth(12);
52 |             setYear(year - 1);
53 |         } else setMonth(month - 1);
54 |     } else {
55 |         const d = new Date(selectedWeekStart);
56 |         d.setDate(d.getDate() - 7);
57 |         setSelectedWeekStart(d);
58 |         // Sync month/year if week crosses month boundary
59 |         setMonth(d.getMonth() + 1);
60 |         setYear(d.getFullYear());
61 |     }
62 | };
63 |
64 | const next = () => {
65 |     if (viewMode === "monthly") {
66 |         if (month === 12) {
67 |             setMonth(1);
68 |             setYear(year + 1);
69 |         } else setMonth(month + 1);
70 |     } else {
71 |         const d = new Date(selectedWeekStart);
72 |         d.setDate(d.getDate() + 7);
73 |         setSelectedWeekStart(d);
74 |         setMonth(d.getMonth() + 1);
75 |         setYear(d.getFullYear());
76 |     }
77 | };
78 |
79 | const eventsForDay = (day: number): CalendarEvent[] => {
80 |     const dateStr = `${year}-${String(month).padStart(2, "0")}-${String(
81 |         day
82 |     ).padStart(2, "0")}`;
83 |     return events.filter((e) => e.date?.startsWith(dateStr));
84 | };
85 |
86 | const eventsForDate = (date: Date): CalendarEvent[] => {
87 |     const y = date.getFullYear();
88 |     const m = date.getMonth() + 1;
89 |     const d = date.getDate();
90 |     const dateStr = `${y}-${String(m).padStart(2, "0")}-${String(d).padStart(
91 |         2,
92 |         "0"
93 |     )}`;
94 |     return events.filter((e) => e.date?.startsWith(dateStr));
95 | };
96 |
97 | // Week days for weekly view
98 | const weekdays = useMemo(() => {
99 |     return Array.from({ length: 7 }, (_, i) => {
100 |         const d = new Date(selectedWeekStart);
101 |         d.setDate(d.getDate() + i);
102 |         return d;
103 |     });
104 | }, [selectedWeekStart]);
105 |
106 | const headerLabel =
107 |     viewMode === "monthly"
108 |       ? new Date(year, month - 1, 1).toLocaleDateString(locale, {
109 |           month: "long",
110 |           year: "numeric",
111 |       })
112 |       : `${
113 |           weekdays[0]?.toLocaleDateString(locale, {
114 |               month: "short",
115 |               day: "numeric",
116 |           }) ?? ""
117 |       } - ${
118 |           weekdays[6]?.toLocaleDateString(locale, {
119 |               month: "short",
120 |               day: "numeric",
121 |               year: "numeric",
122 |           }) ?? ""
123 |       }`;
124 |
125 | return (
126 |     <div className="space-y-6">

```

```

127 <div className="flex flex-col gap-3 sm:flex-row sm:items-center sm:justify-between">
128   <div>
129     <h1 className="text-2xl font-bold tracking-tight">
130       {t("calendar.title")}
131     </h1>
132     <p className="text-sm text-gray-500">{t("calendar.subtitle")}</p>
133   </div>
134   <Tabs
135     value={viewMode}
136     onValueChange={(v) => setViewMode(v as ViewMode)}
137   >
138     <TabsList className="gap-2 rounded-xl">
139       <TabsTrigger value="monthly" className="rounded-xl text-xs">
140         {t("calendar.monthly")}
141       </TabsTrigger>
142       <TabsTrigger value="weekly" className="rounded-xl text-xs">
143         {t("calendar.weekly")}
144       </TabsTrigger>
145     </TabsList>
146   </Tabs>
147 </div>
148
149 /* R21.1/R21.2: the calendar is an explicitly read-only deadline view;
150    task creation and editing live in the planner surfaces. */
151 <div
152   className="flex items-start gap-2 rounded-xl border border-slate-200 bg-slate-50 px-4 py-3"
153   role="note"
154 >
155   <Lock className="h-4 w-4 shrink-0 text-slate-400 mt-0.5" />
156   <p className="text-xs text-slate-500">{t("calendar.readOnlyNotice")}</p>
157 </div>
158
159 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
160   <div
161     className="px-6 py-4 flex items-center justify-between"
162     style={{
163       background: "var(--brand-gradient)",
164     }}
165   >
166     <Button
167       variant="ghost"
168       size="sm"
169       onClick={prev}
170       className="text-white hover:bg-white/20"
171       aria-label={t("calendar.previous")}
172     >
173       <ChevronLeft className="h-5 w-5" />
174     </Button>
175     <div className="flex items-center gap-2 text-white">
176       <Calendar className="h-5 w-5" />
177       <span className="text-lg font-bold tracking-tight">
178         {headerLabel}
179       </span>
180     </div>
181     <Button
182       variant="ghost"
183       size="sm"
184       onClick={next}
185       className="text-white hover:bg-white/20"
186       aria-label={t("calendar.next")}
187     >
188       <ChevronRight className="h-5 w-5" />
189     </Button>
190   </div>
191
192   <div className="p-4">
193     {isLoading ? (
194       <Shimmer className="h-64 rounded-lg" />
195     ) : isError ? (
196       <ErrorState
197         message={t("errors.generic")}
198         onRetry={() => void refetch()}
199         retryLabel={t("buttons.retry")}
200       />
201     ) : viewMode === "monthly" ? (
202       <>
203         <div className="grid grid-cols-7 gap-1 mb-2">
204           {dayShortLabels.map((d, i) => (
205             <div
206               key={i}
207               className="text-center text-xs font-bold text-slate-500 py-1"
208             >
209               {d}
210             </div>
211           ))}
212         </div>
213         <div className="grid grid-cols-7 gap-1">
214           {Array.from({ length: firstDay }).map((_, i) => (
215             <div key={`empty-${i}`} className="h-20" />
216           ))}
217           {Array.from({ length: daysInMonth }).map((_, i) => {
218             const day = i + 1;
219             const dayEvents = eventsForDay(day);
220             const isToday =
221               day === now.getDate() &&
222               month === now.getMonth() + 1 &&
223               year === now.getFullYear();
224             return (
225               <div
226                 key={day}
227                 className={`h-20 rounded-lg border p-1 text-xs ${
228                   isToday
229                     ? "border-blue-500 bg-blue-50"
230                     : "border-slate-100 hover:bg-slate-50"
231                 }`}

```

```

231 |         }` }
232 |     >
233 |     <span
234 |       className={`font-semibold ${
235 |         isToday ? "text-blue-600" : "text-slate-700"
236 |       }`}
237 |     >
238 |       {day}
239 |     </span>
240 |     <div className="mt-0.5 space-y-0.5 overflow-hidden">
241 |       {dayEvents.slice(0, 2).map((e) => (
242 |         <Badge
243 |           key={e.id}
244 |           variant="outline"
245 |           className="text-[9px] px-1 py-0 truncate block"
246 |           style={{ borderColor: e.color, color: e.color }}
247 |         >
248 |           {e.title}
249 |         </Badge>
250 |       ))}
251 |       {dayEvents.length > 2 && (
252 |         <span className="text-[9px] text-slate-400">
253 |           {t("calendar.moreEvents", {
254 |             n: dayEvents.length - 2,
255 |           })}
256 |         </span>
257 |       )}
258 |     </div>
259 |   </div>
260 | );
261 | }}}
262 | </div>
263 | </>
264 | ) : (
265 |   /* Weekly View */
266 |   <div className="space-y-2">
267 |     <div className="grid grid-cols-7 gap-2">
268 |       {weekDays.map((date, i) => {
269 |         const dayEvents = eventsForDate(date);
270 |         const isToday = date.toDateString() === now.toDateString();
271 |         return (
272 |           <div key={i} className="space-y-1">
273 |             <div
274 |               className={`text-center text-xs font-bold py-1 rounded-lg ${
275 |                 isToday ? "bg-blue-500 text-white" : "text-slate-500"
276 |               }`}
277 |             >
278 |               <div>{dayShortLabels[date.getDay()]}</div>
279 |               <div className="text-lg font-black">
280 |                 {date.getDate()}
281 |               </div>
282 |             </div>
283 |             <div className="space-y-1 min-h-[120px]">
284 |               {dayEvents.map((e) => (
285 |                 <div
286 |                   key={e.id}
287 |                   className="rounded-lg border p-1.5 text-xs"
288 |                   style={{
289 |                     borderColor: e.color,
290 |                     backgroundColor: `${e.color}10`,
291 |                   }}
292 |                 >
293 |                   <p
294 |                     className="font-medium truncate"
295 |                     style={{ color: e.color }}
296 |                   >
297 |                     {e.title}
298 |                   </p>
299 |                   {e.course_name && (
300 |                     <p className="text-[9px] text-slate-500 truncate">
301 |                       {e.course_name}
302 |                     </p>
303 |                   )}
304 |                 </div>
305 |               ))}
306 |               {dayEvents.length === 0 && (
307 |                 <div className="text-[9px] text-slate-300 text-center pt-4">
308 |                   {t("calendar.noEvents")}
309 |                 </div>
310 |               )}
311 |             </div>
312 |           </div>
313 |         );
314 |       })}
315 |     </div>
316 |   </div>
317 | );
318 | </div>
319 | </Card>
320 | </div>
321 | );
322 | };
323 |
324 | export default CalendarView;
325 |

```

FILE: [src/pages/shared/NotificationPreferences.tsx](#)

TYPE: .tsx | LINES: 1-188 | SHA256: d83768bd300834c571f19676dceff3fa3becc733794ab7ae70088d0f62472a75

```

1 | // Task 94.2: Notification preferences page
2 | // Per-course mute toggles + quiet hours configuration
3 |
4 | import { useState } from "react";
5 | import { Switch } from "@components/ui/switch";

```

```

6 | import { Input } from "@components/ui/input";
7 | import { Button } from "@components/ui/button";
8 | import { useAuth } from "@hooks/useAuth";
9 | import {
10 |   useNotificationPreferences,
11 |   useUpdateNotificationPreferences,
12 |   type NotificationPreferences as NotifPrefs,
13 | } from "@hooks/useNotificationPreferences";
14 | import { useCourses } from "@hooks/useCourses";
15 | import { toast } from "sonner";
16 | import { Loader2, Bell, Moon } from "lucide-react";
17 | import { PCard, SectionHeader } from "@design-system";
18 |
19 | const NotificationPreferences = () => {
20 |   const { user } = useAuth();
21 |   const { data: prefs, isLoading: prefsLoading } = useNotificationPreferences(
22 |     user?.id
23 |   );
24 |   const { data: coursesData, isLoading: coursesLoading } = useCourses();
25 |   const updateMutation = useUpdateNotificationPreferences();
26 |
27 |   const [localPrefs, setLocalPrefs] = useState<NotifPrefs | null>(null);
28 |
29 |   // Sync from server on first load (derived initial state)
30 |   const effectivePrefs = localPrefs ?? prefs ?? null;
31 |
32 |   const isLoading = prefsLoading || coursesLoading;
33 |   const courses = coursesData?.data ?? [];
34 |
35 |   const handleToggleMute = (courseId: string) => {
36 |     if (!effectivePrefs) return;
37 |     const muted = effectivePrefs.muted_courses.includes(courseId)
38 |       ? effectivePrefs.muted_courses.filter((id) => id !== courseId)
39 |       : [...effectivePrefs.muted_courses, courseId];
40 |     setLocalPrefs({ ...effectivePrefs, muted_courses: muted });
41 |   };
42 |
43 |   const handleSave = () => {
44 |     if (!user?.id || !effectivePrefs) return;
45 |     updateMutation.mutate(
46 |       { userId: user.id, preferences: effectivePrefs },
47 |       {
48 |         onSuccess: () => toast.success("Preferences saved"),
49 |         onError: (err) => toast.error(err.message),
50 |       }
51 |     );
52 |   };
53 |
54 |   if (isLoading || !effectivePrefs) {
55 |     return (
56 |       <div className="flex items-center justify-center py-12">
57 |         <Loader2 className="h-6 w-6 animate-spin text-gray-400" />
58 |       </div>
59 |     );
60 |   }
61 |
62 |   return (
63 |     <div className="space-y-6 max-w-2xl">
64 |       <SectionHeader
65 |         icon={Bell}
66 |         title="Notification Preferences"
67 |         description="Control course notifications and quiet hours."
68 |       />
69 |
70 |       {/* Per-course mute toggles */}
71 |       <PCard className="overflow-hidden gap-0 py-0">
72 |         <div className="flex items-center gap-2 px-6 py-4">
73 |           <Bell className="h-5 w-5 text-white" />
74 |           <h2 className="text-lg font-bold tracking-tight text-white">
75 |             Course Notifications
76 |           </h2>
77 |         </div>
78 |         <div className="space-y-3 p-6">
79 |           {courses.length === 0 && (
80 |             <p className="text-sm text-gray-500">No courses enrolled</p>
81 |           )}
82 |           {courses.map((course) => (
83 |             <div
84 |               key={course.id}
85 |               className="flex items-center justify-between py-1"
86 |             >
87 |               <span className="text-sm font-medium text-gray-700">
88 |                 {course.name}
89 |               </span>
90 |               <Switch
91 |                 checked={!effectivePrefs.muted_courses.includes(course.id)}
92 |                 onChange={() => handleToggleMute(course.id)}
93 |               />
94 |             </div>
95 |           ))}
96 |         </div>
97 |       </PCard>
98 |
99 |       {/* Quiet hours */}
100 |      <PCard className="overflow-hidden gap-0 py-0">
101 |        <div className="flex items-center gap-2 px-6 py-4">
102 |          <Moon className="h-5 w-5 text-white" />
103 |          <h2 className="text-lg font-bold tracking-tight text-white">
104 |            Quiet Hours
105 |          </h2>
106 |        </div>
107 |        <div className="space-y-4 p-6">
108 |          <div className="flex items-center justify-between">
109 |            <span className="text-sm font-medium text-gray-700">

```

```

110 |         Enable quiet hours
111 |     </span>
112 |     <Switch
113 |       checked={effectivePrefs.quiet_hours.enabled}
114 |       onCheckedChange={(checked) =>
115 |         setLocalPrefs({
116 |           ...effectivePrefs,
117 |           quiet_hours: {
118 |             ...effectivePrefs.quiet_hours,
119 |             enabled: checked,
120 |           },
121 |         })
122 |       }
123 |     />
124 |   </div>
125 |
126 |   {effectivePrefs.quiet_hours.enabled && (
127 |     <div className="flex items-center gap-4">
128 |       <div className="space-y-1">
129 |         <label htmlFor="quiet-start" className="text-xs text-gray-500">
130 |           Start
131 |         </label>
132 |         <Input
133 |           id="quiet-start"
134 |           type="time"
135 |           value={effectivePrefs.quiet_hours.start}
136 |           onChange={(e) =>
137 |             setLocalPrefs({
138 |               ...effectivePrefs,
139 |               quiet_hours: {
140 |                 ...effectivePrefs.quiet_hours,
141 |                 start: e.target.value,
142 |               },
143 |             })
144 |           }
145 |           className="w-32"
146 |         />
147 |       </div>
148 |       <div className="space-y-1">
149 |         <label htmlFor="quiet-end" className="text-xs text-gray-500">
150 |           End
151 |         </label>
152 |         <Input
153 |           id="quiet-end"
154 |           type="time"
155 |           value={effectivePrefs.quiet_hours.end}
156 |           onChange={(e) =>
157 |             setLocalPrefs({
158 |               ...effectivePrefs,
159 |               quiet_hours: {
160 |                 ...effectivePrefs.quiet_hours,
161 |                 end: e.target.value,
162 |               },
163 |             })
164 |           }
165 |           className="w-32"
166 |         />
167 |       </div>
168 |     </div>
169 |   )}
170 | </div>
171 | </PCard>
172 |
173 | <Button
174 |   onClick={handleSave}
175 |   disabled={updateMutation.isPending}
176 |   variant="tactile"
177 | >
178 |   {updateMutation.isPending && (
179 |     <Loader2 className="h-4 w-4 animate-spin" />
180 |   )}
181 |   Save Preferences
182 | </Button>
183 | </div>
184 | );
185 | };
186 |
187 | export default NotificationPreferences;
188 |

```

FILE: [src/pages/shared/OutcomeChainView.tsx](#)

TYPE: .tsx | LINES: 1-416 | SHA256: 329e780ed6500d0c129817adfe2f49c422a0dbe80669585ee7fc1550c3c39a2e

```

1 | // =====
2 | // OutcomeChainView – end-to-end OBE outcome chain (Feature: qa-partner-review-
3 | // remediation, Req 16)
4 | // =====
5 | //
6 | // Renders the full traceability chain for a selected starting outcome (an ILO):
7 | //   ILO !' GA !' PLO !' CLO !' Assessment !' Rubric !' Student !' Attainment
8 | // Graduate Attributes are shown as a level between the ILO and the PLOs
9 | // (Req 16.1, 16.2, 16.3). When no level has any linked record for the chosen
10 | // start, a single unified empty state is shown for the whole chain rather than
11 | // per-level zeros (Req 16.4). Attainment at any node uses the platform
12 | // attainment-level color coding (Req 16.5).
13 | //
14 | // All data access goes through the `useOutcomeChain` / `useILOs` hooks – no raw
15 | // Supabase calls in this component.
16 |
17 | import { parseAsString, useQueryState } from "nuqs";
18 | import { Card } from "@components/ui/card";
19 | import { Badge } from "@components/ui/badge";
20 | import {
21 |   Select,

```

[illegible]

[illegible]

```
// % % GA node (level between ILO and PLO, Req 16.3) % % % % % % % % % % % % % % % %  
const GaCard = ({ ga }: { ga: GraduateAttributeNode }) => (  
  <div className="flex items-center gap-2 rounded-xl border border-purple-100 bg-purple-50/50 px-3 py-2">  
    <Award className="h-4 w-4 text-purpl-500 shrink-0" />  
    <span className="text-sm font-medium truncate">{resolveName(ga.name)}</span>  
    {ga.weight !== null && (  
      <span className="text-[10px] text-slate-400">. {ga.weight}%</span>  
    )}  
    <span classNane="ms-auto">  
      <AttainmentChip percent={ga.attainmentPercent} />  
    </span>  
  </div>  
) ;  
  
const OutcomeChainViewLegacy = () => {  
  const [startId, setStartId] = useQueryState(  
    "ilo",  
    parseAsString.withDefault("")  
  );  
  const { data: iloPage, isLoading: ilosLoading } = useILOs({ pageSize: 1000 });  
  const ilos = iloPage?.data ?? [];  
  const {  
    data: chain,  
    isLoading: chainLoading,  
    isError,  
  } = useOutcomeChain(startId || undefined);  
  
  return (  
    <div className="space-y-6">  
      <div className="flex flex-wrap items-center justify-between gap-3">  
        <div>  
          <h1 className="text-2xl font-bold tracking-tight">Outcome Chain</h1>  
          <p className="text-sm text-slate-500">  
            Trace attainment end-to-end: ILO !' GA !' PLO !' CLO !' Assessment !'  
            Rubric !' Student.  
          </p>  
        </div>  
        <Select value={startId} onChange={setStartId}>  
          <SelectTrigger className="w-72 bg-white">  
            <SelectValue  
              placeholder={ilosLoading ? "Loading outcomes..." : "Select an institution outcome"}  
            </SelectValue>  
          </SelectTrigger>  
          <SelectContent>  
            {ilos.map((ilo) => (  
              <SelectItem key={ilo.id} value={ilo.id}>  
                {resolveName(ilo.title)}  
              </SelectItem>  
            ))}  
          </SelectContent>  
        </Select>  
      </div>  
  
      <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">  
        <div  
          className="px-6 py-4 flex items-center gap-2"  
          style={{ background: `var(--brand-gradient)` }}  
        >  
          <Workflow className="h-5 w-5 text-white" />  
          <h2 className="text-lg font-bold tracking-tight text-white">  
            End-to-End Outcome Chain  
          </h2>  
        </div>  
        <div classNane="p-6">  
          {!startId ? (  
            <EmptyState  
              icon=<Workflow className="h-8 w-8 text-gray-400" />  
              title="Select an institution outcome"  
              description="Choose an ILO above to trace its connected graduate attributes, program and course"  
            </EmptyState>  
          ): chainLoading ? (  
            <div classNane="space-y-3">  
              <Shimmer classNane="h-12 rounded-xl" />  
              <Shimmer classNane="h-24 rounded-xl" />  
              <Shimmer classNane="h-40 rounded-xl" />  
            </div>  
          ): isError ? (  
            <EmptyState  
              icon=<Workflow className="h-8 w-8 text-red-400" />  
              title="Couldn't load the outcome chain"  
              description="Something went wrong building this chain. Please try again."  
            </EmptyState>  
          ): !chain || chain.isEmpty ? (  
            // Req 16.4 - a single unified empty state for the whole chain when  
            // no level has any linked record (never per-level zeros).  
            <EmptyState  
              icon=<Workflow classNane="h-8 w-8 text-gray-400" />  
              title="No connected outcomes yet"  
              description="This outcome has no graduate attributes, program outcomes, course outcomes, assessm"  
            </EmptyState>  
          ): (  
            <ErrorBoundary  
              fallback=(<p classNane="text-sm text-red-500">  
                Unable to display the outcome chain.  
              </p>  
            )  
          </ErrorBoundary>  
        </div>  
      </div>  
    </div>  
  );
```



```

334 |         <LevelLabel
335 |             icon={Award}
336 |             label="Institution Outcome"
337 |             count={1}
338 |         />
339 |         <div className="rounded-xl border border-red-100 bg-red-50/50 p-3">
340 |             <div className="flex items-center gap-2">
341 |                 <Badge
342 |                     variant="outline"
343 |                     className="border-red-200 bg-red-100 text-red-700"
344 |                 >
345 |                     ILO
346 |                 </Badge>
347 |                 <span className="text-sm font-semibold truncate">
348 |                     {resolveName(chain.start.title)}
349 |                 </span>
350 |                 <span className="ms-auto">
351 |                     <AttainmentChip percent={chain.start.attainmentPercent} />
352 |                 </span>
353 |             </div>
354 |         </div>
355 |
356 |         <Connector />
357 |
358 |         {/* % % GA level (between ILO and PLO, Req 16.3) % % % % % % % % */}
359 |         <LevelLabel
360 |             icon={Award}
361 |             label="Graduate Attributes"
362 |             count={chain.graduateAttributes.length}
363 |         />
364 |         {chain.graduateAttributes.length > 0 ? (
365 |             <div className="space-y-1.5">
366 |                 {chain.graduateAttributes.map((ga) => (
367 |                     <GaCard key={ga.id} ga={ga} />
368 |                 ))}
369 |             </div>
370 |         ) : (
371 |             <p className="ps-2 text-xs text-slate-400">
372 |                 No graduate attributes mapped to this outcome.
373 |             </p>
374 |         )}
375 |
376 |         <Connector />
377 |
378 |         {/* % % PLO !' CLO !' Assessment !' Rubric !' Student levels % % */}
379 |         <LevelLabel
380 |             icon={Target}
381 |             label="Program Outcomes"
382 |             count={chain.plos.length}
383 |         />
384 |         {chain.plos.length > 0 ? (
385 |             <div className="space-y-2">
386 |                 {chain.plos.map((plo) => (
387 |                     <PloCard key={plo.id} plo={plo} />
388 |                 ))}
389 |             </div>
390 |         ) : (
391 |             <p className="ps-2 text-xs text-slate-400">
392 |                 No program outcomes mapped to this outcome.
393 |             </p>
394 |         )}
395 |     </div>
396 | </ErrorBoundary>
397 | )}
398 | </div>
399 | </Card>
400 | </div>
401 | );
402 | };
403 |
404 | // Role split: for the COORDINATOR role the redesigned Outcome Attainment rollout
405 | // replaces the legacy chain. Admins (who share this route) keep the legacy
406 | // end-to-end traceability view.
407 | const OutcomeChainView = () => {
408 |     const { profile } = useAuth();
409 |     if (profile?.role === "coordinator") {
410 |         return <CoordinatorOutcomeAttainmentNew />;
411 |     }
412 |     return <OutcomeChainViewLegacy />;
413 | };
414 |
415 | export default OutcomeChainView;
416 |

```

FILE: src/pages/shared/ProfilePage.tsx

TYPE: .tsx | LINES: 1-421 | SHA256: 4ef0d8fc27a6b7d075f55c835b9a717d732f8aa2397f2db64726614966174532

```

1 | import { useRef, useState } from "react";
2 | import { Button } from "@components/ui/button";
3 | import { Badge } from "@components/ui/badge";
4 | import { useAuth } from "@hooks/useAuth";
5 | import {
6 |     User,
7 |     Camera,
8 |     Loader2,
9 |     Sun,
10 |    Moon,
11 |    Monitor,
12 |    Shield,
13 |    FileDown,
14 |    DollarSign,
15 | } from "lucide-react";
16 | import { toast } from "sonner";
17 | import { supabase } from "@lib/supabase";

```

```

18 | import { uploadAvatarFile, FileValidationError } from "@lib/fileUpload";
19 | import EmailPreferencesSection from "@components/shared/EmailPreferencesSection";
20 | import { useTheme, type ThemePreference } from "@providers/ThemeProvider";
21 | import ExportDataButton from "@components/shared/ExportDataButton";
22 | import { useGenerateTranscript } from "@hooks/useTranscript";
23 | import { useStudentFees } from "@hooks/useFees";
24 | import {
25 |   Select,
26 |   SelectContent,
27 |   SelectItem,
28 |   SelectTrigger,
29 |   SelectValue,
30 | } from "@components/ui/select";
31 | import { useSemesters } from "@hooks/useSemesters";
32 | import CoordinatorProfileNew from "@components/shared/CoordinatorProfileNew";
33 | import { PCard, SectionHeader } from "@design-system";
34 |
35 | const ProfilePageLegacy = () => {
36 |   const { profile, user } = useAuth();
37 |   const { theme, setTheme } = useTheme();
38 |   const fileInputRef = useRef<HTMLInputElement>(null);
39 |   const [isUploading, setIsUploading] = useState(false);
40 |   const [avatarUrl, setAvatarUrl] = useState<string | null>(null);
41 |
42 |   const displayAvatarUrl = avatarUrl ?? profile?.avatar_url ?? null;
43 |
44 |   const handleAvatarClick = () => {
45 |     if (!isUploading) {
46 |       fileInputRef.current?.click();
47 |     }
48 |   };
49 |
50 |   const handleFileChange = async (e: React.ChangeEvent<HTMLInputElement>) => {
51 |     const file = e.target.files?.[0];
52 |     if (!file || !user) return;
53 |
54 |     // Reset input so the same file can be re-selected
55 |     e.target.value = "";
56 |
57 |     setIsUploading(true);
58 |     try {
59 |       const publicUrl = await uploadAvatarFile({ file, userId: user.id });
60 |
61 |       const { error } = await supabase
62 |         .from("profiles")
63 |         .update({ avatar_url: publicUrl })
64 |         .eq("id", user.id);
65 |
66 |       if (error) throw new Error(error.message);
67 |
68 |       setAvatarUrl(publicUrl);
69 |       toast.success("Avatar updated");
70 |     } catch (err) {
71 |       const message =
72 |         err instanceof FileValidationError
73 |           ? err.message
74 |           : "Failed to upload avatar. Please try again.";
75 |       toast.error(message);
76 |     } finally {
77 |       setIsUploading(false);
78 |     }
79 |   };
80 |
81 |   return (
82 |     <div className="space-y-6">
83 |       <SectionHeader
84 |         icon={User}
85 |         title="Profile Settings"
86 |         description="Manage your avatar, appearance, exports, transcript, and fees."
87 |       />
88 |
89 |       {/* Profile Info Card */}
90 |       <PCard className="overflow-hidden gap-0 py-0">
91 |         <div
92 |           className="flex items-center gap-2 px-6 py-4"
93 |           style={{
94 |             background: "var(--brand-gradient)",
95 |           }}
96 |         >
97 |           <User className="h-5 w-5 text-white" />
98 |           <h2 className="text-lg font-bold tracking-tight text-white">
99 |             Profile
100 |           </h2>
101 |         </div>
102 |         <div className="p-6">
103 |           <div className="flex items-center gap-4">
104 |             <button
105 |               type="button"
106 |               onClick={handleAvatarClick}
107 |               disabled={isUploading}
108 |               className="relative group cursor-pointer rounded-full focus:outline-none focus:ring-2 focus:ring"
109 |               aria-label="Upload avatar"
110 |             >
111 |               {displayAvatarUrl ? (
112 |                 <img
113 |                   src={displayAvatarUrl}
114 |                   alt={profile?.full_name ?? "Avatar"}
115 |                   loading="lazy"
116 |                   decoding="async"
117 |                   className="h-16 w-16 rounded-full object-cover"
118 |                 />
119 |               ) : (
120 |                 <div className="flex h-16 w-16 items-center justify-center rounded-full bg-blue-50">
121 |                   <User className="h-8 w-8 text-blue-600" />

```

```

122     </div>
123   }}
124   {/ * Overlay */}
125   <div className="absolute inset-0 rounded-full bg-black/40 flex items-center justify-center opaci
126     {isUploading ? (
127       <Loader2 className="h-5 w-5 text-white animate-spin" />
128     ) : (
129       <Camera className="h-5 w-5 text-white" />
130     )}
131   </div>
132   {/ * Always-visible spinner when uploading */}
133   {isUploading && (
134     <div className="absolute inset-0 rounded-full bg-black/40 flex items-center justify-center">
135       <Loader2 className="h-5 w-5 text-white animate-spin" />
136     </div>
137   )}
138 </button>
139 <input
140   ref={fileInputRef}
141   type="file"
142   accept="image/jpeg,image/png,image/gif,image/webp"
143   onChange={handleFileChange}
144   className="hidden"
145   aria-hidden="true"
146 />
147 <div>
148   <p className="text-lg font-bold">
149     {profile?.full_name ?? "User"}
150   </p>
151   <p className="text-sm text-slate-500">{profile?.email ?? ""}</p>
152   <p className="text-xs text-slate-400 capitalize">
153     {profile?.role ?? ""}
154   </p>
155 </div>
156 </div>
157 </div>
158 </PCard>
159
160 {/ * Theme Preference */}
161 <PCard className="overflow-hidden gap-0 py-0">
162   <div
163     className="flex items-center gap-2 px-6 py-4"
164     style={{
165       background: "var(--brand-gradient)",
166     }}
167   >
168     <Sun className="h-5 w-5 text-white" />
169     <h2 className="text-lg font-bold tracking-tight text-white">
170       Appearance
171     </h2>
172   </div>
173   <div className="p-6">
174     <p className="text-sm text-slate-500 dark:text-slate-400 mb-4">
175       Choose how the platform looks to you.
176     </p>
177     <div
178       className="flex gap-2"
179       role="radiogroup"
180       aria-label="Theme preference"
181     >
182       {[
183         { value: "light" as ThemePreference, label: "Light", icon: Sun },
184         { value: "dark" as ThemePreference, label: "Dark", icon: Moon },
185         {
186           value: "system" as ThemePreference,
187           label: "System",
188           icon: Monitor,
189         },
190       ]}.map(({ value, label, icon: Icon }) => (
191         <button
192           key={value}
193           type="button"
194           role="radio"
195           aria-checked={theme === value}
196           onClick={() => setTheme(value)}
197           className={`flex items-center gap-2 px-4 py-2 rounded-xl text-sm font-semibold transition-colo
198             theme === value
199               ? "bg-blue-600 text-white"
200               : "bg-white dark:bg-slate-800 text-gray-600 dark:text-slate-300 border border-gray-200 dar
201           `}
202         >
203           <Icon className="h-4 w-4" />
204           {label}
205         </button>
206       ))}
207     </div>
208   </div>
209 </PCard>
210
211 {/ * Email Notification Preferences */}
212 <EmailPreferencesSection />
213
214 {/ * GDPR Data Export – students only */}
215 {profile?.role === "student" && user && (
216   <PCard className="overflow-hidden gap-0 py-0">
217     <div
218       className="flex items-center gap-2 px-6 py-4"
219       style={{
220         background: "var(--brand-gradient)",
221       }}
222     >
223       <Shield className="h-5 w-5 text-white" />
224       <h2 className="text-lg font-bold tracking-tight text-white">
225         Data Export

```

[illegible]

[illegible]

TYPE: .tsx | LINES: 1-100 | SHA256: 266354ca4e0a0fee08d7921f19fc61db455f1c307d1a04d023e28c04c3547fde

```

9 | } from "@hooks/useSessionManagement";
10 | import { toast } from "sonner";
11 | import { Loader2, Monitor, Logout, Shield } from "lucide-react";
12 | import { PCard, SectionHeader } from "@design-system";
13 |
14 | const SessionManagement = () => {
15 |   const { user } = useAuth();
16 |   const { data: sessions, isLoading } = useActiveSessions(user?.id);
17 |   const signOutOthers = useSignOutOtherSessions();
18 |
19 |   const handleSignOutOthers = () => {
20 |     signOutOthers.mutate(undefined, {
21 |       onSuccess: () => toast.success("Other sessions signed out"),
22 |       onError: (err) => toast.error(err.message),
23 |     });
24 |   };
25 |
26 |   return (
27 |     <div className="space-y-6 max-w-2xl">
28 |       <SectionHeader
29 |         icon={Shield}
30 |         title="Session Management"
31 |         description="Review active sessions and sign out other devices."
32 |       />
33 |
34 |       <PCard className="overflow-hidden gap-0 py-0">
35 |         <div className="flex items-center gap-2 px-6 py-4">
36 |           <Shield className="h-5 w-5 text-white" />
37 |           <h2 className="text-lg font-bold tracking-tight text-white">
38 |             Active Sessions
39 |           </h2>
40 |         </div>
41 |         <div className="space-y-4 p-6">
42 |           {isLoading && (
43 |             <div className="flex items-center justify-center py-6">
44 |               <Loader2 className="h-5 w-5 animate-spin text-gray-400" />
45 |             </div>
46 |           )}
47 |
48 |           {!isLoading &&
49 |             sessions?.map((session) => (
50 |               <div
51 |                 key={session.id}
52 |                 className="flex items-center justify-between p-3 rounded-lg bg-slate-50"
53 |               >
54 |                 <div className="flex items-center gap-3">
55 |                   <Monitor className="h-5 w-5 text-gray-500" />
56 |                   <div>
57 |                     <p className="text-sm font-medium text-gray-900">
58 |                       {session.device}
59 |                       {session.isCurrent && (
60 |                         <span className="ms-2 text-xs text-green-600 font-bold">
61 |                           Current
62 |                         </span>
63 |                       )}
64 |                     </p>
65 |                     <p className="text-xs text-gray-500">
66 |                       {session.ip} · Last active{" "}
67 |                       {new Date(session.lastActive).toLocaleString()}
68 |                     </p>
69 |                   </div>
70 |                 </div>
71 |               </div>
72 |             ))}
73 |
74 |             {!isLoading && (!sessions || sessions.length === 0) && (
75 |               <p className="text-sm text-gray-500 text-center py-4">
76 |                 No active sessions found
77 |               </p>
78 |             )}
79 |           </div>
80 |         </PCard>
81 |
82 |         <Button
83 |           variant="outline"
84 |           onClick={handleSignOutOthers}
85 |           disabled={signOutOthers.isPending}
86 |           className="gap-2"
87 |         >
88 |           {signOutOthers.isPending ? (
89 |             <Loader2 className="h-4 w-4 animate-spin" />
90 |           ) : (
91 |             <Logout className="h-4 w-4" />
92 |           )}
93 |           Sign Out Other Sessions
94 |         </Button>
95 |       </div>
96 |     );
97 |   };
98 |
99 |   export default SessionManagement;
100 |

```

FILE: [src/pages/shared/TimetableView.tsx](#)

TYPE: .tsx | LINES: 1-327 | SHA256: cdf205af4158c35b25922ba63f8f3eb31fa422c6a5beb5d0cd2703ff8567864

```

1 | import { useTranslation } from "react-i18next";
2 | import { Badge } from "@components/ui/badge";
3 | import { Clock, CalendarClock, MapPin } from "lucide-react";
4 | import { useTimetableSlots, type TimetableSlot } from "@hooks/useTimetable";
5 | import { PCard, SectionHeader, Shimmer } from "@design-system";
6 | import { NoTimetable } from "@components/shared/EmptyState";
7 | import ErrorState from "@components/shared/ErrorState";
8 | import i18n from "@lib/i18n";

```

```

9 | import { resolveLocalizationGate } from "@lib/localization";
10 | import {
11 |   computeTimetableNow,
12 |   formatDurationParts,
13 |   type TimetableNowContext,
14 | } from "@lib/timetableNow";
15 |
16 | const WEEKDAYS = [1, 2, 3, 4, 5]; // Mon-Fri
17 | const HOURS = Array.from(
18 |   { length: 12 },
19 |   (_, i) => `${String(i + 8).padStart(2, "0")}:00`
20 | );
21 |
22 | const SLOT_TYPE_STYLES: Record<string, string> = {
23 |   lecture: "bg-blue-100 text-blue-700",
24 |   lab: "bg-green-100 text-green-700",
25 |   tutorial: "bg-purple-100 text-purple-700",
26 | };
27 |
28 | const TimetableView = () => {
29 |   const { t } = useTranslation("common");
30 |   const { data: slots = [], isLoading, isError, refetch } = useTimetableSlots();
31 |
32 |   // R13.5: if neither an English nor an Arabic localization is available for
33 |   // the timetable, block display entirely rather than render an unlocalized
34 |   // timetable. The decision routes through the centralized localization-policy
35 |   // gate (`block-only` policy) shared with the weekly planner.
36 |   const localizationGate = resolveLocalizationGate(
37 |     (lng) => i18n.hasResourceBundle(lng, "common"),
38 |     "block-only"
39 |   );
40 |
41 |   const getSlot = (day: number, hour: string): TimetableSlot | undefined =>
42 |     slots.find((s) => s.day_of_week === day && s.start_time?.startsWith(hour));
43 |
44 |   const slotTypeLabel = (type: string | null | undefined): string =>
45 |     type ? t(`timetable.slotType.${type}`, { defaultValue: type }) : "";
46 |
47 |   const dayLabel = (day: number): string => t(`timetable.days.${day}`);
48 |
49 |   // Current/next class context (R12.4, R13.2, R21.3). Computed at render so the
50 |   // countdown reflects the latest data; the heavy lifting lives in the pure
51 |   // `computeTimetableNow` helper for testability.
52 |   const nowContext = computeTimetableNow(slots, new Date());
53 |
54 |   // R13.5: block the timetable surface entirely when no supported localization
55 |   // is available, rather than rendering raw keys / unlocalized text.
56 |   if (localizationGate === "blocked") {
57 |     return null;
58 |   }
59 |
60 |   return (
61 |     <div className="space-y-6">
62 |       <SectionHeader
63 |         icon={Clock}
64 |         title={t("timetable.title")}
65 |         description={t(
66 |           "timetable.subtitle",
67 |           "View the weekly schedule and current class timing."
68 |         )}
69 |       />
70 |
71 |       {!isLoading && slots.length > 0 && (
72 |         <CurrentClassPanel context={nowContext} />
73 |       )}
74 |
75 |       <PCard className="overflow-hidden gap-0 py-0">
76 |         <div
77 |           className="flex items-center gap-2 px-6 py-4"
78 |           style={{
79 |             background: "var(--brand-gradient)",
80 |           }}
81 |         >
82 |           <Clock className="h-5 w-5 text-white" />
83 |           <h2 className="text-lg font-bold tracking-tight text-white">
84 |             {t("timetable.weeklySchedule")}
85 |           </h2>
86 |         </div>
87 |         <div className="p-4 overflow-x-auto">
88 |           {isLoading ? (
89 |             <Shimmer className="h-64 rounded-lg" />
90 |           ) : isError ? (
91 |             <ErrorState
92 |               message={t("errors.generic")}
93 |               onRetry={() => void refetch()}
94 |               retryLabel={t("buttons.retry")}
95 |             />
96 |           ) : slots.length === 0 ? (
97 |             <NoTimetable className="border-0 shadow-none" />
98 |           ) : (
99 |             <table className="w-full text-xs border-collapse min-w-[600px]">
100 |               <thead>
101 |                 <tr>
102 |                   <th className="p-2 border border-slate-200 bg-slate-50 text-slate-500 font-bold w-20">
103 |                     {t("timetable.time")}
104 |                   </th>
105 |                   {WEEKDAYS.map((d) => (
106 |                     <th
107 |                       key={d}
108 |                       className="p-2 border border-slate-200 bg-slate-50 text-slate-500 font-bold"
109 |                     >
110 |                       {dayLabel(d)}
111 |                     </th>
112 |                   ))}

```

```

113 |         </tr>
114 |     </thead>
115 |     <tbody>
116 |         {HOURS.map((hour) => (
117 |             <tr key={hour}>
118 |                 <td className="p-2 border border-slate-200 text-slate-400 font-mono text-center">
119 |                     {hour}
120 |                 </td>
121 |                 {WEEKDAYS.map((day) => {
122 |                     const slot = getSlot(day, hour);
123 |                     return (
124 |                         <td
125 |                             key={day}
126 |                             className="p-1.5 border border-slate-200 align-top"
127 |                             style={{
128 |                                 slot?.color
129 |                                 ? { backgroundColor: `${slot.color}08` }
130 |                                 : undefined
131 |                             }}
132 |                         >
133 |                             {slot && (
134 |                                 <div
135 |                                     className="rounded-lg border p-2 space-y-1"
136 |                                     style={{
137 |                                         borderColor: slot.color ?? "#3b82f6",
138 |                                         backgroundColor: `${slot.color ?? "#3b82f6"}15`,
139 |                                     }}
140 |                                 >
141 |                                     <p
142 |                                         className="font-semibold truncate"
143 |                                         style={{ color: slot.color ?? "#3b82f6" }}
144 |                                     >
145 |                                         {slot.course_name ||
146 |                                         slot.section_code ||
147 |                                         t("timetable.class")}
148 |                                     </p>
149 |                                     {slot.section_code && (
150 |                                         <p className="text-slate-500 text-[10px]">
151 |                                             {t("timetable.sectionLabel", {
152 |                                                 code: slot.section_code,
153 |                                             })}
154 |                                         </p>
155 |                                     )}
156 |                                     <div className="flex items-center gap-1">
157 |                                         {slot.slot_type && (
158 |                                             <Badge
159 |                                                 className={`${text-[9px] px-1 py-0 ${
160 |                                                     SLOT_TYPE_STYLES[slot.slot_type] ??
161 |                                                     "bg-gray-100 text-gray-700"}
162 |                                                 }`}
163 |                                             >
164 |                                                 {slotTypeLabel(slot.slot_type)}
165 |                                             </Badge>
166 |                                         )}
167 |                                         {slot.room && (
168 |                                             <span className="text-slate-400 text-[10px]">
169 |                                                 {slot.room}
170 |                                             </span>
171 |                                         )}
172 |                                     </div>
173 |                                     <p className="text-slate-400 text-[10px]">
174 |                                         {slot.start_time?.slice(0, 5)} - {" "}
175 |                                         {slot.end_time?.slice(0, 5)}
176 |                                     </p>
177 |                                 </div>
178 |                             )}
179 |                         </td>
180 |                     );
181 |                 )}
182 |             </tr>
183 |         )}
184 |     </tbody>
185 | </table>
186 | )}
187 | </div>
188 | </PCard>
189 |
190 | /* Legend */
191 | {isLoading && slots.length > 0 && (
192 |     <div className="flex flex-wrap gap-3">
193 |         {Array.from(
194 |             new Set(slots.map((s) => s.course_name).filter(Boolean))
195 |         ).map((name) => {
196 |             const slot = slots.find((s) => s.course_name === name);
197 |             return (
198 |                 <div
199 |                     key={name}
200 |                     className="flex items-center gap-1.5 text-xs text-slate-600"
201 |                 >
202 |                     <div
203 |                         className="h-3 w-3 rounded-full"
204 |                         style={{ backgroundColor: slot?.color ?? "#3b82f6" }}
205 |                     />
206 |                     <span>{name}</span>
207 |                 </div>
208 |             );
209 |         })}
210 |     </div>
211 | )}
212 | </div>
213 | );
214 | };
215 |
216 | /**

```



```

217 | * Compact panel summarizing the class happening now or coming up next, with
218 | * the time remaining until the relevant transition. Pure presentational: all
219 | * timing logic comes from `computeTimetableNow`.
220 | */
221 | const CurrentClassPanel = ({ context }: { context: TimetableNowContext }) => {
222 |   const { t } = useTranslation("common");
223 |
224 |   if (context.status === "none" || context.slot === null) {
225 |     return (
226 |       <PCard className="flex items-center gap-3 p-4">
227 |         <div className="p-2 rounded-lg bg-slate-100">
228 |           <CalendarClock className="h-5 w-5 text-slate-500" />
229 |         </div>
230 |         <div>
231 |           <p className="text-sm font-semibold text-slate-700">
232 |             {t("timetable.now.noUpcoming")}
233 |           </p>
234 |           <p className="text-xs text-slate-500">
235 |             {t("timetable.now.noUpcomingHint")}
236 |           </p>
237 |         </div>
238 |       </PCard>
239 |     );
240 |   }
241 |
242 |   const { slot, status, minutes } = context;
243 |   const isNow = status === "in_class";
244 |   const color = slot.color ?? "#3b82f6";
245 |   const remaining = formatRemaining(minutes ?? 0, t);
246 |   const countdownLabel = isNow
247 |     ? t("timetable.now.endsIn", { time: remaining })
248 |     : t("timetable.now.startsIn", { time: remaining });
249 |
250 |   return (
251 |     <PCard className="p-4">
252 |       <div className="flex items-start gap-3">
253 |         <div
254 |           className="p-2 rounded-lg"
255 |           style={{ backgroundColor: `${color}1f` }}
256 |         >
257 |           <CalendarClock className="h-5 w-5" style={{ color }} />
258 |         </div>
259 |         <div className="flex-1 min-w-0 space-y-1">
260 |           <div className="flex items-center gap-2">
261 |             <Badge
262 |               className={
263 |                 isNow
264 |                   ? "bg-green-100 text-green-700"
265 |                   : "bg-blue-100 text-blue-700"
266 |             }
267 |             >
268 |               {isNow
269 |                 ? t("timetable.now.happeningNow")
270 |                 : t("timetable.now.upNext")}
271 |             </Badge>
272 |             <span className="text-xs font-medium text-slate-500">
273 |               {countdownLabel}
274 |             </span>
275 |           </div>
276 |           <p
277 |             className="text-base font-bold tracking-tight truncate"
278 |             style={{ color }}
279 |           >
280 |             {slot.course_name || slot.section_code || t("timetable.class")}
281 |           </p>
282 |           <div className="flex flex-wrap items-center gap-x-3 gap-y-1 text-xs text-slate-500">
283 |             <span className="font-mono">
284 |               {slot.start_time?.slice(0, 5)} - {slot.end_time?.slice(0, 5)}
285 |             </span>
286 |             {slot.section_code && (
287 |               <span>
288 |                 {t("timetable.sectionLabel", { code: slot.section_code })}
289 |               </span>
290 |             )}
291 |             {slot.room && (
292 |               <span className="inline-flex items-center gap-1">
293 |                 <MapPin className="h-3 w-3" />
294 |                 {slot.room}
295 |               </span>
296 |             )}
297 |           </div>
298 |         </div>
299 |       </div>
300 |     </PCard>
301 |   );
302 | };
303 |
304 | /**
305 |  * Render a non-negative minute count as a short localized duration string
306 |  * (e.g. "1d 2h", "45m"). Falls back to a "less than a minute" label when the
307 |  * count rounds to zero so the countdown is never blank.
308 |  */
309 | const formatRemaining = (
310 |   totalMinutes: number,
311 |   t: (key: string, options?: Record<string, unknown>) => string
312 | ): string => {
313 |   const { days, hours, minutes } = formatDurationParts(totalMinutes);
314 |   if (days === 0 && hours === 0 && minutes === 0) {
315 |     return t("timetable.remaining.lessThanMinute");
316 |   }
317 |   const parts: string[] = [];
318 |   if (days > 0) parts.push(t("timetable.remaining.days", { value: days }));
319 |   if (hours > 0) parts.push(t("timetable.remaining.hours", { value: hours }));
320 |   if (minutes > 0) {

```

```

321 |     parts.push(t("timetable.remaining.minutes", { value: minutes }));
322 |   }
323 |   return parts.join(" ");
324 | };
325 |
326 | export default TimetableView;
327 |

```

FILE: src/pages/student/announcements/AnnouncementDetail.tsx

TYPE: .tsx | LINES: 1-149 | SHA256: e54bd149fe1fee1d69614bf0413260b3743499f7b15324a5f4108dc4e8b951b5

```

1 | // Task 66.4: Announcement detail view with Read habit timer (30+ seconds)
2 | // Requirements: 75.5
3 | // Feature: qa-partner-review-remediation – Req 15.4: student mark-as-read upsert.
4 | import { useEffect } from "react";
5 | import { useTranslation } from "react-i18next";
6 | import { useParams, useNavigate } from "react-router-dom";
7 | import {
8 |   useAnnouncement,
9 |   useMarkAnnouncementRead,
10 | } from "@hooks/useAnnouncements";
11 | import { useAuth } from "@hooks/useAuth";
12 | import { useReadHabitTimer } from "@hooks/useReadHabitTimer";
13 | import { Button } from "@components/ui/button";
14 | import { Badge } from "@components/ui/badge";
15 | import { PCard, SectionHeader, Shimmer } from "@design-system";
16 | import { AnnouncementAttachmentList } from "@components/shared/AnnouncementAttachmentList";
17 | import ErrorState from "@components/shared/ErrorState";
18 | import { ArrowLeft, Megaphone, Pin, Clock, CheckCircle2 } from "lucide-react";
19 | import { format } from "date-fns";
20 |
21 | const AnnouncementDetail = () => {
22 |   const { t } = useTranslation("common");
23 |   const { announcementId } = useParams<{ announcementId: string }>();
24 |   const navigate = useNavigate();
25 |   const { user, role } = useAuth();
26 |   const {
27 |     data: announcement,
28 |     isLoading,
29 |     isError,
30 |     refetch,
31 |   } = useAnnouncement(announcementId);
32 |   const markRead = useMarkAnnouncementRead();
33 |
34 |   // Record a read receipt when a student views the announcement. Idempotent via
35 |   // the UNIQUE(announcement_id, student_id) upsert, so repeated views are safe
36 |   // (Req 15.4). Only students record receipts.
37 |   const studentId = role === "student" ? user?.id : undefined;
38 |   const markReadMutate = markRead.mutate;
39 |   useEffect(() => {
40 |     if (!announcementId || !studentId) return;
41 |     markReadMutate({ announcementId, studentId });
42 |   }, [announcementId, studentId, markReadMutate]);
43 |
44 |   // Wire into Read habit – 30+ seconds of viewing counts as "Read" habit
45 |   const { elapsedSeconds, isCompleted } = useReadHabitTimer({
46 |     pageType: "assignment_detail", // reuse existing page type
47 |     pageId: announcementId ?? "",
48 |   });
49 |
50 |   if (isLoading) {
51 |     return (
52 |       <div className="space-y-4">
53 |         <Shimmer className="h-8 w-48 rounded-lg" />
54 |         <Shimmer className="h-64 rounded-xl" />
55 |       </div>
56 |     );
57 |   }
58 |
59 |   if (isError) {
60 |     return (
61 |       <ErrorState
62 |         message={t("errors.generic")}
63 |         onRetry={() => void refetch()}
64 |         retryLabel={t("buttons.retry")}
65 |       />
66 |     );
67 |   }
68 |
69 |   if (!announcement) {
70 |     return (
71 |       <div className="text-center py-12">
72 |         <p className="text-sm text-gray-500">Announcement not found.</p>
73 |         <Button
74 |           variant="outline"
75 |           size="sm"
76 |           className="mt-4"
77 |           onClick={() => navigate(-1)}
78 |         >
79 |           Go Back
80 |         </Button>
81 |       </div>
82 |     );
83 |   }
84 |
85 |   return (
86 |     <div className="space-y-6 max-w-3xl">
87 |       <Button
88 |         variant="ghost"
89 |         size="sm"
90 |         onClick={() => navigate(-1)}
91 |         className="text-gray-500"
92 |       >
93 |         <ArrowLeft className="h-4 w-4 me-1" /> Back

```

```

94 |         </Button>
95 |
96 |         <PCard
97 |           className={`overflow-hidden ${
98 |             announcement.is_pinned ? "ring-1 ring-amber-200" : ""
99 |           }`}
100 |         >
101 |           <div className="p-6 space-y-4">
102 |             <SectionHeader
103 |               icon={Megaphone}
104 |               title={announcement.title}
105 |               action={
106 |                 announcement.is_pinned ? (
107 |                   <Badge className="bg-amber-50 text-amber-700 border-amber-200 text-xs">
108 |                     <Pin className="h-3 w-3 me-1" /> Pinned
109 |                   </Badge>
110 |                 ) : null
111 |               }
112 |             />
113 |             <div className="prose prose-sm max-w-none whitespace-pre-wrap text-gray-700">
114 |               {announcement.content}
115 |             </div>
116 |             <div className="flex items-center justify-between mt-6 pt-4 border-t border-slate-100">
117 |               <p className="text-xs text-gray-400">
118 |                 Posted{" "}
119 |                 {format(
120 |                   new Date(announcement.created_at),
121 |                   "MMMM d, yyyy . h:mm a"
122 |                 )}
123 |               </p>
124 |               { /* Read habit progress indicator */ }
125 |               <div className="flex items-center gap-2">
126 |                 {isCompleted ? (
127 |                   <Badge className="bg-green-50 text-green-600 border-green-200 text-xs">
128 |                     <CheckCircle2 className="h-3 w-3 me-1" /> Read habit '
129 |                   </Badge>
130 |                 ) : (
131 |                   <Badge variant="outline" className="text-xs text-gray-400">
132 |                     <Clock className="h-3 w-3 me-1" /> {30 - elapsedSeconds}s to
133 |                     read habit
134 |                   </Badge>
135 |                 )}
136 |               </div>
137 |             </div>
138 |             { /* Attachments – signed-URL download from the private bucket */ }
139 |             {announcementId && (
140 |               <AnnouncementAttachmentList announcementId={announcementId} />
141 |             )}
142 |           </div>
143 |         </PCard>
144 |       </div>
145 |     );
146 |   };
147 |
148 |   export default AnnouncementDetail;
149 |

```

FILE: [src/pages/student/assignments/AssignmentDetailPage.tsx](#)

TYPE: .tsx | LINES: 1-2 | SHA256: 7933ee2e11abca50970307b2df561ec953c1a0a260047167cfff122876492a12c

```

1 | export { default } from "@features/student/assignments/AssignmentDetailScreen";
2 |

```

FILE: [src/pages/student/assignments/AssignmentListPage.tsx](#)

TYPE: .tsx | LINES: 1-2 | SHA256: fb2310690aa0b1ecc5fca448f4f4dac923bb1bfb4af6a1174695d7c4c6234655

```

1 | export { default } from "@features/student/assignments/AssignmentListScreen";
2 |

```

FILE: [src/pages/student/badges/StudentBadgesPage.tsx](#)

TYPE: .tsx | LINES: 1-74 | SHA256: a05b52236060367b816f72cd7d4f2cb3270235c64bb6adb36c54181078c2bcd7

```

1 | import { useTranslation } from "react-i18next";
2 | import { Award, Sparkles } from "lucide-react";
3 | import { useAuth } from "@hooks/useAuth";
4 | import {
5 |   usePinBadge,
6 |   useTieredBadges,
7 |   useUnpinBadge,
8 | } from "@hooks/useTieredBadges";
9 | import BadgeCollection from "@components/shared/BadgeCollection";
10 | import ErrorState from "@components/shared/ErrorState";
11 | import { PCard, Shimmer } from "@design-system";
12 |
13 | const StudentBadgesPage = () => {
14 |   const { t } = useTranslation("student");
15 |   const { user } = useAuth();
16 |   const badges = useTieredBadges(user?.id);
17 |   const pinBadge = usePinBadge();
18 |   const unpinBadge = useUnpinBadge();
19 |
20 |   if (badges.isLoading) {
21 |     return (
22 |       <div className="space-y-5">
23 |         <Shimmer className="h-12 w-56 rounded-xl" />
24 |         <Shimmer className="h-80 rounded-[20px]" />
25 |       </div>
26 |     );
27 |   }
28 |
29 |   if (badges.isError) {
30 |     return (
31 |       <ErrorState

```

```

32 |         message={t("badges.loadError")}
33 |         onRetry={() => void badges.refetch()}
34 |         retryLabel={t("badges.retry")}
35 |     />
36 |     );
37 | }
38 |
39 | const earnedBadges = badges.data ?? [];
40 | const pinnedCount = earnedBadges.filter((badge) => badge.is_pinned).length;
41 |
42 | return (
43 |     <div className="space-y-6">
44 |         <div className="flex flex-col gap-3 sm:flex-row sm:items-end sm:justify-between">
45 |             <div>
46 |                 <div className="flex items-center gap-2">
47 |                     <Award className="size-5 text-amber-500" aria-hidden="true" />
48 |                     <h1 className="text-2xl font-bold tracking-tight">
49 |                         {t("badges.title")}
50 |                     </h1>
51 |                 </div>
52 |                 <p className="mt-1 text-sm text-muted-foreground">
53 |                     {t("badges.subtitle")}
54 |                 </p>
55 |             </div>
56 |             <span className="inline-flex items-center gap-2 self-start rounded-full bg-amber-50 px-3 py-1.5 text-x
57 |                 <Sparkles className="size-3.5" aria-hidden="true" />
58 |                 {t("badges.pinned", { count: pinnedCount })}
59 |             </span>
60 |         </div>
61 |
62 |         <PCard className="p-5 sm:p-6">
63 |             <BadgeCollection
64 |                 tieredBadges={earnedBadges}
65 |                 onPinBadge={({badgeId} => pinBadge.mutate({ badgeId })}
66 |                 onUnpinBadge={({badgeId} => unpinBadge.mutate({ badgeId })}
67 |             />
68 |         </PCard>
69 |     </div>
70 | );
71 | };
72 |
73 | export default StudentBadgesPage;
74 |

```

FILE: [src/pages/student/challenges/ChallengeDetailPage.tsx](#)

TYPE: .tsx | LINES: 1-217 | SHA256: c8cd6457bd4939cf0ecb22f020fbd732c101ff5569f98a952b9e88804d8c5bed

```

1 | // =====
2 | // ChallengeDetailPage – Challenge info, progress bar, leaderboard
3 | // Task 6.2: hidden leaderboard for cooperative, completion banner
4 | // =====
5 |
6 | import { useParams, useNavigate } from "react-router-dom";
7 | import { useState, useMemo, useEffect } from "react";
8 | import { toast } from "sonner";
9 | import { useAuth } from "@hooks/useAuth";
10 | import { useChallengeDetail } from "@hooks/useChallengeDetail";
11 | import {
12 |     useMyChallengeProgress,
13 |     useChallengeLeaderboardParticipants,
14 | } from "@hooks/useChallengeParticipation";
15 | import { Badge } from "@components/ui/badge";
16 | import { Button } from "@components/ui/button";
17 | import ChallengeProgressBar from "@components/shared/ChallengeProgressBar";
18 | import ChallengeLeaderboard from "@components/shared/ChallengeLeaderboard";
19 | import { PCard, SectionHeader, Shimmer } from "@design-system";
20 | import {
21 |     ArrowLeft,
22 |     Trophy,
23 |     Calendar,
24 |     Target,
25 |     Handshake,
26 |     CheckCircle2,
27 |     AlertCircle,
28 | } from "lucide-react";
29 |
30 | const ChallengeDetailPage = () => {
31 |     const { id } = useParams<{ id: string }>();
32 |     const navigate = useNavigate();
33 |     const { user } = useAuth();
34 |     const { data: challenge, isLoading, isError, error } = useChallengeDetail(id);
35 |     const { data: myProgress } = useMyChallengeProgress(id, user?.id);
36 |     const { data: leaderboardParticipants } =
37 |         useChallengeLeaderboardParticipants(id);
38 |
39 |     // R28.2 / R28.3a: a genuine query failure surfaces BOTH a toast and a
40 |     // dedicated error UI state – distinct from the graceful not-found state that
41 |     // a `null` (zero-row) result produces. Toast fires once per error.
42 |     useEffect(() => {
43 |         if (isError) {
44 |             toast.error("Failed to load this challenge. Please try again.");
45 |         }
46 |     }, [isError, error]);
47 |
48 |     const [now] = useState(() => Date.now());
49 |     const daysLeft = useMemo(() => {
50 |         if (!challenge) return 0;
51 |         return Math.max(
52 |             0,
53 |             Math.ceil(
54 |                 (new Date(challenge.end_date).getTime() - now) / (1000 * 60 * 60 * 24)
55 |             )
56 |         );
57 |     }, [challenge, now]);

```

```

58 |
59 | if (isLoading) {
60 |   return (
61 |     <div className="space-y-6">
62 |       <Shimmer className="h-10 w-48 rounded-lg" />
63 |       <Shimmer className="h-48 rounded-xl" />
64 |     </div>
65 |   );
66 | }
67 |
68 | // R28.2: query failure !' dedicated error state (distinct from not-found).
69 | if (isError) {
70 |   return (
71 |     <div className="space-y-6">
72 |       <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
73 |         <ArrowLeft className="h-4 w-4 me-1" /> Back
74 |       </Button>
75 |       <PCard className="p-8 text-center">
76 |         <AlertCircle className="h-8 w-8 text-red-500 mx-auto mb-2" />
77 |         <p className="text-sm font-semibold text-gray-700">
78 |           Something went wrong
79 |         </p>
80 |         <p className="text-sm text-gray-500">
81 |           We couldn't load this challenge. Please try again.
82 |         </p>
83 |       </PCard>
84 |     </div>
85 |   );
86 | }
87 |
88 | // R27.2: zero-row result !' graceful not-found state (never throws).
89 | if (!challenge) {
90 |   return (
91 |     <div className="space-y-6">
92 |       <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
93 |         <ArrowLeft className="h-4 w-4 me-1" /> Back
94 |       </Button>
95 |       <PCard className="p-8 text-center">
96 |         <p className="text-sm text-gray-500">Challenge not found.</p>
97 |       </PCard>
98 |     </div>
99 |   );
100 | }
101 |
102 | const isCooperative = challenge.challenge_type === "cooperative";
103 | const isCompleted = !!myProgress?.completed_at;
104 |
105 | return (
106 |   <div className="space-y-6">
107 |     { /* Back button */ }
108 |     <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
109 |       <ArrowLeft className="h-4 w-4 me-1" /> Back to Challenges
110 |     </Button>
111 |
112 |     { /* Completion Banner */ }
113 |     {isCompleted && (
114 |       <PCard className="bg-green-50 p-4">
115 |         <div className="flex items-center gap-3">
116 |           <CheckCircle2 className="h-6 w-6 text-green-600" />
117 |           <div>
118 |             <p className="text-sm font-bold text-green-700">
119 |               Challenge Completed!
120 |             </p>
121 |             <p className="text-xs text-green-600">
122 |               Completed on{" "}
123 |               {new Date(myProgress!.completed_at!).toLocaleDateString()}
124 |             </p>
125 |           </div>
126 |         </div>
127 |       </PCard>
128 |     )}
129 |
130 |     { /* Challenge Info */ }
131 |     <PCard className="overflow-hidden gap-0 py-0">
132 |       <div className="p-6 pb-0">
133 |         <SectionHeader
134 |           icon={isCooperative ? Handshake : Trophy}
135 |           title={challenge.title}
136 |         />
137 |       </div>
138 |       <div className="p-6 space-y-4">
139 |         <p className="text-sm text-gray-600">{challenge.description}</p>
140 |
141 |         <div className="flex gap-2 flex-wrap">
142 |           <Badge variant="outline" className="text-xs">
143 |             {challenge.challenge_type}
144 |           </Badge>
145 |           <Badge variant="outline" className="text-xs">
146 |             {challenge.participation_mode}
147 |           </Badge>
148 |           <Badge className="text-xs bg-amber-50 text-amber-700 border-amber-200">
149 |             +{challenge.reward_xp} XP
150 |           </Badge>
151 |           {challenge.status === "active" && (
152 |             <Badge className="text-xs bg-blue-50 text-blue-700 border-blue-200">
153 |               {daysLeft} days left
154 |             </Badge>
155 |           )}
156 |         </div>
157 |
158 |         <div className="flex items-center gap-4 text-xs text-gray-500">
159 |           <div className="flex items-center gap-1">
160 |             <Calendar className="h-3 w-3" />
161 |             <span>

```

```

162 |         Start: {new Date(challenge.start_date).toLocaleDateString()}
163 |     </span>
164 | </div>
165 | <div className="flex items-center gap-1">
166 |   <Calendar className="h-3 w-3" />
167 |   <span>
168 |     End: {new Date(challenge.end_date).toLocaleDateString()}
169 |   </span>
170 | </div>
171 | </div>
172 |
173 |   { /* Progress */ }
174 |   <div className="pt-2">
175 |     <h3 className="text-sm font-semibold mb-2 flex items-center gap-1">
176 |       <Target className="h-4 w-4" /> Your Progress
177 |     </h3>
178 |     <ChallengeProgressBar
179 |       current={myProgress?.current_progress ?? 0}
180 |       goal={challenge.goal_target}
181 |       label={challenge.title}
182 |     />
183 |   </div>
184 | </div>
185 | </PCard>
186 |
187 | { /* Leaderboard – hidden for cooperative challenges */ }
188 | { !isCooperative && (
189 |   <PCard className="overflow-hidden gap-0 py-0">
190 |     <div className="p-6 pb-0">
191 |       <SectionHeader icon={Trophy} title="Leaderboard" />
192 |     </div>
193 |     <div className="p-6">
194 |       <ChallengeLeaderboard
195 |         participants={leaderboardParticipants ?? []}
196 |         currentUserId={user?.id}
197 |         goalTarget={challenge.goal_target}
198 |       />
199 |     </div>
200 |   </PCard>
201 | ) }
202 |
203 | { isCooperative && (
204 |   <PCard className="p-6 text-center">
205 |     <Handshake className="h-8 w-8 text-green-500 mx-auto mb-2" />
206 |     <p className="text-sm text-gray-500">
207 |       This is a cooperative challenge – everyone works together toward the
208 |       goal. No leaderboard is shown.
209 |     </p>
210 |   </PCard>
211 | ) }
212 | </div>
213 | );
214 | };
215 |
216 | export default ChallengeDetailPage;
217 |

```

FILE: [src/pages/student/challenges/ChallengeListPage.tsx](#)

TYPE: .tsx | LINES: 1-230 | SHA256: 10534d96d658b1c07b212a283829e876b1477849ff13d5c79e9410fbe09fecf8

```

1 | // =====
2 | // ChallengeListPage – Student challenge list with active, upcoming, completed
3 | // Task 6.1: status badges, progress indicators, cooperative/competitive labels
4 | // =====
5 |
6 | import { useState, useCallback } from "react";
7 | import { useNavigate } from "react-router-dom";
8 | import { useQueryClient } from "@tanstack/react-query";
9 | import { useAuth } from "@hooks/useAuth";
10 | import {
11 |   useStudentChallenges,
12 |   type SocialChallenge,
13 | } from "@hooks/useChallenges";
14 | import { useRealtime } from "@hooks/useRealtime";
15 | import { queryKeys } from "@lib/queryKeys";
16 | import { Badge } from "@components/ui/badge";
17 | import { Tabs, TabList, TabTrigger, TabContent } from "@components/ui/tabs";
18 | import { PCard, SectionHeader, Shimmer } from "@design-system";
19 | import { NoChallenges } from "@components/shared/EmptyState";
20 | import { Trophy, Target, Users, Handshake, Calendar } from "lucide-react";
21 | import { cn } from "@lib/utils";
22 | import { KeyboardEvent } from "react";
23 | import { getEffectiveChallengeStatus } from "@lib/challengeLifecycle";
24 |
25 | const getTypeLabel = (type: string) => {
26 |   const labels: Record<string, string> = {
27 |     academic: "Academic",
28 |     habit: "Habit",
29 |     xp_race: "XP Race",
30 |     blooms_climb: "Bloom's Climb",
31 |     cooperative: "Cooperative",
32 |     team: "Team",
33 |     course_wide: "Course-Wide",
34 |   };
35 |   return labels[type] ?? type;
36 | };
37 |
38 | const ChallengeCard = ({
39 |   challenge,
40 |   onClick,
41 | }: {
42 |   challenge: SocialChallenge;
43 |   onClick: () => void;
44 | }) => {

```

```

45 | const isCooperative = challenge.challenge_type === "cooperative";
46 | const isTeam = challenge.participation_mode === "team";
47 | const iconClassName = cn(
48 |   "h-4 w-4",
49 |   isCooperative ? "text-green-600" : "text-amber-600"
50 | );
51 |
52 | return (
53 |   <PCard
54 |     className="cursor-pointer p-4 transition-shadow hover:shadow-[0_18px_38px_rgba(16,24,40,0.11)]"
55 |     onClick={onClick}
56 |     role="button"
57 |     tabIndex={0}
58 |     onKeyDown={(e: KeyboardEvent<HTMLDivElement>) => {
59 |       if (e.key === "Enter" || e.key === " ") {
60 |         e.preventDefault();
61 |         onClick();
62 |       }
63 |     }}
64 |   >
65 |     <div className="flex items-start gap-3">
66 |       <div
67 |         className={cn(
68 |           "p-2 rounded-lg shrink-0",
69 |           isCooperative ? "bg-green-50" : "bg-amber-50"
70 |         )}
71 |       >
72 |         {isCooperative ? (
73 |           <Handshake className={iconClassName} />
74 |         ) : isTeam ? (
75 |           <Users className={iconClassName} />
76 |         ) : (
77 |           <Target className={iconClassName} />
78 |         )}
79 |       </div>
80 |       <div className="flex-1 min-w-0">
81 |         <p className="text-sm font-bold truncate">{challenge.title}</p>
82 |         {challenge.description && (
83 |           <p className="text-xs text-gray-500 mt-0.5 line-clamp-2">
84 |             {challenge.description}
85 |           </p>
86 |         )}
87 |       <div className="flex gap-2 mt-2 flex-wrap">
88 |         <Badge variant="outline" className="text-xs">
89 |           {getTypeLabel(challenge.challenge_type)}
90 |         </Badge>
91 |         <Badge variant="outline" className="text-xs">
92 |           Goal: {challenge.goal_target}
93 |         </Badge>
94 |         <Badge className="text-xs bg-amber-50 text-amber-700 border-amber-200">
95 |           {challenge.reward_badge_id
96 |             ? "Badge"
97 |             : `${challenge.reward_xp} XP`}
98 |         </Badge>
99 |       </div>
100 |       <div className="flex items-center gap-2 mt-2 text-xs text-gray-400">
101 |         <Calendar className="h-3 w-3" />
102 |         <span>
103 |           {new Date(challenge.start_date).toLocaleDateString()} - {" "}
104 |           {new Date(challenge.end_date).toLocaleDateString()}
105 |         </span>
106 |       </div>
107 |     </div>
108 |   </div>
109 | </PCard>
110 | );
111 | };
112 |
113 | const ChallengeListPage = () => {
114 |   const navigate = useNavigate();
115 |   const { user } = useAuth();
116 |   const queryClient = useQueryClient();
117 |   const { data: challenges, isLoading } = useStudentChallenges(user?.id);
118 |   const [activeTab, setActiveTab] = useState("active");
119 |
120 |   // Realtime subscription for challenge progress updates
121 |   const handleProgressUpdate = useCallback(() => {
122 |     queryClient.invalidateQueries({
123 |       queryKey: queryKeys.challengeProgress.lists(),
124 |     });
125 |     queryClient.invalidateQueries({
126 |       queryKey: queryKeys.studentChallenges.lists(),
127 |     });
128 |   }, [queryClient]);
129 |
130 |   useRealtime({
131 |     table: "challenge_progress",
132 |     event: "*",
133 |     onPayload: handleProgressUpdate,
134 |     pollingFn: handleProgressUpdate,
135 |     pollingInterval: 30_000,
136 |   });
137 |
138 |   const now = new Date();
139 |   const active = (challenges ?? []).filter(
140 |     (challenge) => getEffectiveChallengeStatus(challenge, now) === "active"
141 |   );
142 |   const upcoming = (challenges ?? []).filter(
143 |     (challenge) => getEffectiveChallengeStatus(challenge, now) === "upcoming"
144 |   );
145 |   const completed = (challenges ?? []).filter(
146 |     (challenge) => getEffectiveChallengeStatus(challenge, now) === "completed"
147 |   );
148 |

```

```

149 |   if (isLoading) {
150 |     return (
151 |       <div className="space-y-6">
152 |         <SectionHeader icon={Trophy} title="Challenges" />
153 |         <div className="space-y-3">
154 |           {Array.from({ length: 3 }).map((_, i) => (
155 |             <Shimmer key={i} className="h-32 rounded-xl" />
156 |           ))}
157 |         </div>
158 |       </div>
159 |     );
160 |   }
161 |
162 |   return (
163 |     <div className="space-y-6">
164 |       <SectionHeader icon={Trophy} title="Challenges" />
165 |
166 |       <Tabs value={activeTab} onValueChange={setActiveTab}>
167 |         <TabList className="gap-2 bg-transparent p-0">
168 |           {[
169 |             { value: "active", label: `Active (${active.length})` },
170 |             { value: "upcoming", label: `Upcoming (${upcoming.length})` },
171 |             { value: "completed", label: `Completed (${completed.length})` },
172 |           ].map((tab) => (
173 |             <TabTrigger
174 |               key={tab.value}
175 |               value={tab.value}
176 |               className="rounded-xl border px-4 py-1.5 text-sm font-medium data-[state=active]:bg-blue-600 dat
177 |             >
178 |               {tab.label}
179 |             </TabTrigger>
180 |           ))}
181 |         </TabList>
182 |
183 |         <TabContent value="active" className="mt-4 space-y-3">
184 |           {active.length === 0 ? (
185 |             <NoChallenges />
186 |           ) : (
187 |             active.map((c) => (
188 |               <ChallengeCard
189 |                 key={c.id}
190 |                 challenge={c}
191 |                 onClick={() => navigate(`/student/challenges/${c.id}`)}
192 |               />
193 |             ))
194 |           )}
195 |         </TabContent>
196 |
197 |         <TabContent value="upcoming" className="mt-4 space-y-3">
198 |           {upcoming.length === 0 ? (
199 |             <NoChallenges />
200 |           ) : (
201 |             upcoming.map((c) => (
202 |               <ChallengeCard
203 |                 key={c.id}
204 |                 challenge={c}
205 |                 onClick={() => navigate(`/student/challenges/${c.id}`)}
206 |               />
207 |             ))
208 |           )}
209 |         </TabContent>
210 |
211 |         <TabContent value="completed" className="mt-4 space-y-3">
212 |           {completed.length === 0 ? (
213 |             <NoChallenges />
214 |           ) : (
215 |             completed.map((c) => (
216 |               <ChallengeCard
217 |                 key={c.id}
218 |                 challenge={c}
219 |                 onClick={() => navigate(`/student/challenges/${c.id}`)}
220 |               />
221 |             ))
222 |           )}
223 |         </TabContent>
224 |       </Tabs>
225 |     </div>
226 |   );
227 | };
228 |
229 | export default ChallengeListView;
230 |

```

FILE: [src/pages/student/challenges/ChallengeListView.tsx](#)

TYPE: .tsx | LINES: 1-284 | SHA256: 890757290d20b9201667b81ef5983dae25242e8e7a6002df0a3194f772eabaa5

```

1 | // Task 135.2: Student Challenge List View
2 | // Active/completed tabs, live progress bars (Supabase Realtime),
3 | // contribution leaderboard for course-wide, team progress for team-based
4 |
5 | import { useState, useCallback } from "react";
6 | import { Link } from "react-router-dom";
7 | import { useQueryClient } from "@tanstack/react-query";
8 | import { useAuth } from "@hooks/useAuth";
9 | import {
10 |   useStudentChallenges,
11 |   useChallengeParticipantsBatch,
12 |   type SocialChallenge,
13 |   type ChallengeParticipant,
14 | } from "@hooks/useChallenges";
15 | import { useRealtime } from "@hooks/useRealtime";
16 | import { queryKeys } from "@lib/queryKeys";
17 | import { Badge } from "@components/ui/badge";
18 | import { Tabs, TabList, TabTrigger, TabContent } from "@components/ui/tabs";

```



```

19 | import { PCard, SectionHeader, Shimmer } from "@design-system";
20 | import { NoChallenges } from "@components/shared/EmptyState";
21 | import { Trophy, Target, Users } from "lucide-react";
22 | import { getEffectiveChallengeStatus } from "@lib/challengeLifecycle";
23 |
24 | const ProgressBar = ({
25 |   current,
26 |   target,
27 | }: {
28 |   current: number;
29 |   target: number;
30 | }) => {
31 |   const pct = Math.min(100, Math.round((current / Math.max(target, 1)) * 100));
32 |   return (
33 |     <div className="space-y-1">
34 |       <div className="flex items-center justify-between text-xs">
35 |         <span className="font-medium text-gray-600">
36 |           {current} / {target}
37 |         </span>
38 |         <span className="font-bold text-blue-600">{pct}%</span>
39 |       </div>
40 |       <div className="h-2 overflow-hidden rounded-full bg-gray-100">
41 |         <div
42 |           className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)] transitio
43 |           style={{ width: `${pct}%` }}
44 |         />
45 |       </div>
46 |     </div>
47 |   );
48 | };
49 |
50 | const TeamProgressDisplay = ({
51 |   participants,
52 |   target,
53 | }: {
54 |   participants: ChallengeParticipant[];
55 |   target: number;
56 | }) => {
57 |   const sorted = [...participants].sort(
58 |     (a, b) => b.current_progress - a.current_progress
59 |   );
60 |   return (
61 |     <div className="mt-3 space-y-2">
62 |       {sorted.map((p, idx) => (
63 |         <div key={p.id} className="flex items-center gap-2">
64 |           <span className="w-5 text-xs font-bold text-gray-500">
65 |             {idx + 1}.
66 |           </span>
67 |           <div className="flex-1">
68 |             <ProgressBar current={p.current_progress} target={target} />
69 |           </div>
70 |         </div>
71 |       ))}
72 |     </div>
73 |   );
74 | };
75 |
76 | const ContributionLeaderboard = ({
77 |   participants,
78 |   target,
79 | }: {
80 |   participants: ChallengeParticipant[];
81 |   target: number;
82 | }) => {
83 |   const sorted = [...participants].sort(
84 |     (a, b) => b.current_progress - a.current_progress
85 |   );
86 |   const totalProgress = participants.reduce(
87 |     (sum, p) => sum + p.current_progress,
88 |     0
89 |   );
90 |
91 |   return (
92 |     <div className="mt-3 space-y-3">
93 |       <ProgressBar current={totalProgress} target={target} />
94 |       <div className="space-y-1">
95 |         <p className="text-xs font-bold uppercase tracking-wider text-gray-500">
96 |           Top Contributors
97 |         </p>
98 |         {sorted.slice(0, 5).map((p, idx) => (
99 |           <div key={p.id} className="flex items-center justify-between py-1">
100 |             <span className="text-xs font-medium text-gray-700">
101 |               {idx + 1}. Participant
102 |             </span>
103 |             <span className="text-xs font-bold text-amber-600">
104 |               +{p.current_progress}
105 |             </span>
106 |           </div>
107 |         ))}
108 |       </div>
109 |     </div>
110 |   );
111 | };
112 |
113 | const ChallengeCard = ({
114 |   challenge,
115 |   participants,
116 | }: {
117 |   challenge: SocialChallenge;
118 |   participants: ChallengeParticipant[];
119 | }) => {
120 |   const isTeam = challenge.participation_mode === "team";
121 |
122 |   return (

```

```

123 | <Link
124 |   to={` /student/challenges/${challenge.id}`}
125 |   className="block rounded-[20px] focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-blue-
126 |   aria-label={`Open challenge: ${challenge.title}`}
127 | >
128 |   <PCard className="p-4 transition-shadow hover:shadow-[0_18px_38px_rgba(16,24,40,0.11)]">
129 |     <div className="flex items-start gap-3">
130 |       <div className="rounded-lg bg-amber-50 p-2">
131 |         {isTeam ? (
132 |           <Users className="h-4 w-4 text-amber-600" />
133 |         ) : (
134 |           <Target className="h-4 w-4 text-amber-600" />
135 |         )}
136 |       </div>
137 |       <div className="min-w-0 flex-1">
138 |         <div className="flex flex-wrap items-center gap-2">
139 |           <p className="text-sm font-bold">{challenge.title}</p>
140 |           <Badge variant="outline" className="text-xs">
141 |             {isTeam ? "Team" : "Individual"}
142 |           </Badge>
143 |           <Badge variant="outline" className="text-xs">
144 |             Goal: {challenge.goal_target}
145 |           </Badge>
146 |           <Badge className="border-amber-200 bg-amber-50 text-xs text-amber-700">
147 |             {challenge.reward_badge_id
148 |               ? "Badge"
149 |               : `+${challenge.reward_xp} XP`}
150 |           </Badge>
151 |         </div>
152 |         {challenge.description && (
153 |           <p className="mt-0.5 text-xs text-gray-500">
154 |             {challenge.description}
155 |           </p>
156 |         )}
157 |
158 |         {participants.length > 0 &&
159 |           (isTeam ? (
160 |             <TeamProgressDisplay
161 |               participants={participants}
162 |               target={challenge.goal_target}
163 |             />
164 |           ) : (
165 |             <ContributionLeaderboard
166 |               participants={participants}
167 |               target={challenge.goal_target}
168 |             />
169 |           ))}
170 |       </div>
171 |     </div>
172 |   </PCard>
173 | </Link>
174 | );
175 | };
176 |
177 | const ChallengeListView = () => {
178 |   const { user } = useAuth();
179 |   const queryClient = useQueryClient();
180 |   const { data: challenges, isLoading } = useStudentChallenges(user?.id);
181 |   const [activeTab, setActiveTab] = useState("active");
182 |
183 |   const challengeIds = (challenges ?? []).map((c) => c.id);
184 |   const { data: participantsMap } = useChallengeParticipantsBatch(challengeIds);
185 |
186 |   const handleProgressUpdate = useCallback(() => {
187 |     queryClient.invalidateQueries({
188 |       queryKey: queryKeys.challengeProgress.lists(),
189 |     });
190 |     queryClient.invalidateQueries({
191 |       queryKey: queryKeys.studentChallenges.lists(),
192 |     });
193 |   }, [queryClient]);
194 |
195 |   useRealtime({
196 |     table: "challenge_participants",
197 |     event: "*",
198 |     onPayload: handleProgressUpdate,
199 |     pollingFn: handleProgressUpdate,
200 |     pollingInterval: 30_000,
201 |   });
202 |
203 |   const now = new Date();
204 |   const active = (challenges ?? []).filter(
205 |     (challenge) => getEffectiveChallengeStatus(challenge, now) === "active"
206 |   );
207 |   const completed = (challenges ?? []).filter(
208 |     (challenge) => getEffectiveChallengeStatus(challenge, now) === "completed"
209 |   );
210 |
211 |   if (isLoading) {
212 |     return (
213 |       <div className="space-y-6">
214 |         <SectionHeader icon={Trophy} title="Challenges" />
215 |         <div className="space-y-3">
216 |           {Array.from({ length: 3 }).map((_, i) => (
217 |             <Shimmer key={i} className="h-32 rounded-[20px]" />
218 |           ))}
219 |         </div>
220 |       </div>
221 |     );
222 |   }
223 |
224 |   return (
225 |     <div className="space-y-6">
226 |       <SectionHeader icon={Trophy} title="Challenges" />

```

```

227 |
228 |     <Tabs value={activeTab} onValueChange={setActiveTab}>
229 |       <TabsList className="gap-2 bg-transparent p-0">
230 |         <TabsTrigger
231 |           value="active"
232 |           className="rounded-[12px] border border-gray-200 bg-white px-4 py-1.5 text-sm font-semibold text-g
233 |         >
234 |           Active ({active.length})
235 |         </TabsTrigger>
236 |         <TabsTrigger
237 |           value="completed"
238 |           className="rounded-[12px] border border-gray-200 bg-white px-4 py-1.5 text-sm font-semibold text-g
239 |         >
240 |           Completed ({completed.length})
241 |         </TabsTrigger>
242 |       </TabsList>
243 |
244 |       <TabsContent value="active" className="mt-4 space-y-3">
245 |         {active.length === 0 ? (
246 |           <NoChallenges />
247 |         ) : (
248 |           active.map((c) => (
249 |             <ChallengeCard
250 |               key={c.id}
251 |               challenge={c}
252 |               participants={participantsMap?.[c.id] ?? []}
253 |             />
254 |           ))
255 |         )}
256 |       </TabsContent>
257 |
258 |       <TabsContent value="completed" className="mt-4 space-y-3">
259 |         {completed.length === 0 ? (
260 |           <NoChallenges />
261 |         ) : (
262 |           completed.map((c) => (
263 |             <PCard key={c.id} className="p-4 opacity-75">
264 |               <div className="flex items-center gap-3">
265 |                 <Trophy className="h-4 w-4 text-green-500" />
266 |                 <div>
267 |                   <p className="text-sm font-semibold">{c.title}</p>
268 |                   <p className="text-xs text-gray-500">
269 |                     {c.participation_mode === "team" ? "Team" : "Individual"}{" "}
270 |                     . Completed
271 |                   </p>
272 |                 </div>
273 |               </div>
274 |             </PCard>
275 |           ))
276 |         )}
277 |       </TabsContent>
278 |     </Tabs>
279 |   </div>
280 | );
281 | };
282 |
283 | export default ChallengeListView;
284 |

```

FILE: [src/pages/student/content/ContentForm.tsx](#)

TYPE: .tsx | LINES: 1-168 | SHA256: 2d0d1a2495850edb2973e178d5128392cf4bbac79036e6a98e9fa24f5e58a3cf

```

1 | // =====
2 | // ContentForm – Form for study plans, quiz questions, explanation videos
3 | // Task 21.3
4 | // =====
5 |
6 | import { useForm } from "react-hook-form";
7 | import { zodResolver } from "@hookform/resolvers/zod";
8 | import { useCreateStudentContent } from "@/hooks/useStudentContent";
9 | import { useAuth } from "@/hooks/useAuth";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import { Textarea } from "@components/ui/textarea";
13 | import {
14 |   Form,
15 |   FormControl,
16 |   FormField,
17 |   FormItem,
18 |   FormLabel,
19 |   FormMessage,
20 | } from "@components/ui/form";
21 | import {
22 |   Select,
23 |   SelectContent,
24 |   SelectItem,
25 |   SelectTrigger,
26 |   SelectValue,
27 | } from "@components/ui/select";
28 | import { FileText, Loader2, X } from "lucide-react";
29 | import { PCard, SectionHeader } from "@design-system";
30 | import {
31 |   studentContentFormSchema,
32 |   type StudentContentFormInput,
33 | } from "@lib/marketplaceSchemas";
34 |
35 | interface ContentFormProps {
36 |   onClose: () => void;
37 | }
38 |
39 | const ContentForm = ({ onClose }: ContentFormProps) => {
40 |   const { profile } = useAuth();
41 |   const createContent = useCreateStudentContent();
42 |

```

```

43 | const form = useForm<StudentContentFormInput>({
44 |   resolver: zodResolver(studentContentFormSchema),
45 |   defaultValues: {
46 |     content_type: "study_plan",
47 |     title: "",
48 |     body: "",
49 |   },
50 | });
51 |
52 | const handleSubmit = (values: StudentContentFormInput) => {
53 |   if (!profile?.id) return;
54 |
55 |   createContent.mutate(
56 |     {
57 |       content_type: values.content_type,
58 |       title: values.title,
59 |       clo_id: null,
60 |       content_data: { body: values.body },
61 |       studentId: profile.id,
62 |     },
63 |     { onSuccess: () => onClose() }
64 |   );
65 | };
66 |
67 | return (
68 |   <PCard className="p-6">
69 |     <SectionHeader
70 |       icon={FileText}
71 |       title="Create Content"
72 |       action={
73 |         <Button
74 |           variant="ghost"
75 |           size="sm"
76 |           onClick={onClose}
77 |           aria-label="Close"
78 |         >
79 |           <X className="h-4 w-4" />
80 |         </Button>
81 |       }
82 |     />
83 |
84 |     <Form {...form}>
85 |       <form onSubmit={form.handleSubmit(handleSubmit)} className="space-y-4">
86 |         <FormField
87 |           control={form.control}
88 |           name="content_type"
89 |           render={({ field }) => (
90 |             <FormItem>
91 |               <FormLabel>Content Type</FormLabel>
92 |               <Select value={field.value} onChange={field.onChange}>
93 |                 <FormControl>
94 |                   <SelectTrigger>
95 |                     <SelectValue placeholder="Select type" />
96 |                   </SelectTrigger>
97 |                 </FormControl>
98 |                 <SelectContent>
99 |                   <SelectItem value="study_plan">Study Plan</SelectItem>
100 |                   <SelectItem value="quiz_question">Quiz Question</SelectItem>
101 |                   <SelectItem value="explanation_video">
102 |                     Explanation Video
103 |                   </SelectItem>
104 |                 </SelectContent>
105 |               </Select>
106 |               <FormMessage />
107 |             </FormItem>
108 |           )}
109 |         />
110 |
111 |         <FormField
112 |           control={form.control}
113 |           name="title"
114 |           render={({ field }) => (
115 |             <FormItem>
116 |               <FormLabel>Title</FormLabel>
117 |               <FormControl>
118 |                 <Input
119 |                   placeholder="Enter a title for your content"
120 |                   {...field}
121 |                 />
122 |               </FormControl>
123 |               <FormMessage />
124 |             </FormItem>
125 |           )}
126 |         />
127 |
128 |         <FormField
129 |           control={form.control}
130 |           name="body"
131 |           render={({ field }) => (
132 |             <FormItem>
133 |               <FormLabel>Content</FormLabel>
134 |               <FormControl>
135 |                 <Textarea
136 |                   placeholder="Describe your content..."
137 |                   rows={4}
138 |                   {...field}
139 |                 />
140 |               </FormControl>
141 |               <FormMessage />
142 |             </FormItem>
143 |           )}
144 |         />
145 |
146 |         <div className="flex justify-end gap-2">

```

```

147 |         <Button type="button" variant="outline" onClick={onClose}>
148 |             Cancel
149 |         </Button>
150 |         <Button
151 |             type="submit"
152 |             disabled={createContent.isPending}
153 |             variant="tactile"
154 |         >
155 |             {createContent.isPending && (
156 |                 <Loader2 className="h-4 w-4 animate-spin" />
157 |             )}
158 |             Submit for Review
159 |         </Button>
160 |     </div>
161 | </form>
162 | </Form>
163 | </PCard>
164 |     );
165 | };
166 |
167 | export default ContentForm;
168 |

```

FILE: [src/pages/student/content/StudentContentPage.tsx](#)

TYPE: .tsx | LINES: 1-128 | SHA256: 5a5c87dfd1f94634207b98c381b41873617ee54ba5573c713e8ece68f157bcd5

```

1 | // =====
2 | // StudentContentPage – Student content creation and listing
3 | // Task 21.2
4 | // =====
5 |
6 | import { useState } from "react";
7 | import { useTranslation } from "react-i18next";
8 | import { Badge } from "@components/ui/badge";
9 | import { Button } from "@components/ui/button";
10 | import { Tabs, TabsContent, TabsList, TabsTrigger } from "@components/ui/tabs";
11 | import { Plus, FileText } from "lucide-react";
12 | import { useStudentContent } from "@hooks/useStudentContent";
13 | import { useAuth } from "@hooks/useAuth";
14 | import ErrorState from "@components/shared/ErrorState";
15 | import { NoData } from "@components/shared/EmptyState";
16 | import { PCard, SectionHeader, Shimmer } from "@design-system";
17 | import ContentForm from "../ContentForm";
18 |
19 | const STATUS_COLORS = {
20 |   pending: "bg-yellow-50 text-yellow-700 border-yellow-200",
21 |   approved: "bg-green-50 text-green-700 border-green-200",
22 |   rejected: "bg-red-50 text-red-700 border-red-200",
23 | } as const;
24 |
25 | const StudentContentPage = () => {
26 |   const { t } = useTranslation("common");
27 |   const { profile } = useAuth();
28 |   const {
29 |     data: content,
30 |     isLoading,
31 |     isError,
32 |     refetch,
33 |   } = useStudentContent(profile?.id);
34 |   const [showForm, setShowForm] = useState(false);
35 |
36 |   const contentCardClass = "p-4";
37 |
38 |   return (
39 |     <div className="space-y-6">
40 |       <SectionHeader
41 |         icon={FileText}
42 |         title="My Content"
43 |         description="Create study plans, quiz questions, and explanation drafts."
44 |         action={
45 |           <Button variant="tactile" onClick={() => setShowForm(true)}>
46 |             <Plus className="h-4 w-4" /> Create Content
47 |           </Button>
48 |         }
49 |       />
50 |
51 |       {showForm && <ContentForm onClose={() => setShowForm(false)} />}
52 |
53 |       <Tabs defaultValue="all">
54 |         <TabsList className="gap-2">
55 |           <TabsTrigger value="all" className="rounded-xl">
56 |             All
57 |           </TabsTrigger>
58 |           <TabsTrigger value="pending" className="rounded-xl">
59 |             Pending
60 |           </TabsTrigger>
61 |           <TabsTrigger value="approved" className="rounded-xl">
62 |             Approved
63 |           </TabsTrigger>
64 |         </TabsList>
65 |
66 |         {[ "all", "pending", "approved" ].map((tab) => (
67 |           <TabsContent key={tab} value={tab} className="mt-4">
68 |             {isLoading ? (
69 |               <Shimmer className="h-48 rounded-xl" />
70 |             ) : isError ? (
71 |               <ErrorState
72 |                 message={t("errors.generic")}
73 |                 onRetry={() => void refetch()}
74 |                 retryLabel={t("buttons.retry")}
75 |               />
76 |             ) : (content ?? []).filter(
77 |               (item) => tab === "all" || item.status === tab
78 |             ).length === 0 ? (

```

```

79 |         <NoData />
80 |       ) : (
81 |         <div className="grid gap-4 md:grid-cols-2">
82 |           {(content ?? [])
83 |             .filter((c) => tab === "all" || c.status === tab)
84 |             .map((item) => (
85 |               <PCard key={item.id} className={contentCardClass}>
86 |                 <div className="flex items-start gap-3">
87 |                   <div className="p-2 rounded-lg bg-blue-50">
88 |                     <FileText className="h-5 w-5 text-blue-600" />
89 |                   </div>
90 |                   <div className="flex-1 min-w-0">
91 |                     <div className="flex items-center gap-2">
92 |                       <h3 className="text-sm font-bold truncate">
93 |                         {item.title}
94 |                       </h3>
95 |                       <Badge
96 |                         className={`text-[10px] ${
97 |                           STATUS_COLORS[item.status]
98 |                         }`}
99 |                       >
100 |                        {item.status}
101 |                      </Badge>
102 |                    </div>
103 |                    <p className="text-xs text-gray-500 mt-0.5 capitalize">
104 |                      {item.content_type.replace("_", " ")}
105 |                    </p>
106 |                    {item.feedback && (
107 |                      <p className="text-xs text-gray-600 mt-2 italic">
108 |                        Feedback: {item.feedback}
109 |                      </p>
110 |                    )}
111 |                    <p className="text-[10px] text-gray-400 mt-2">
112 |                      {new Date(item.created_at).toLocaleDateString()}
113 |                    </p>
114 |                  </div>
115 |                </div>
116 |              </PCard>
117 |            )})
118 |          </div>
119 |        )}
120 |      </TabsContent>
121 |    )}
122 |  </Tabs>
123 | </div>
124 | );
125 | };
126 |
127 | export default StudentContentPage;
128 |

```

FILE: src/pages/student/courses/CourseCard.tsx

TYPE: .tsx | LINES: 1-205 | SHA256: 7c857519485896e55227d5978e216c22b0bc2c4f4129689b0ed79bee86e87cd7

```

1 | import { Link } from "react-router-dom";
2 | import { useTranslation } from "react-i18next";
3 | import { CalendarClock, ChevronRight, Sparkles } from "lucide-react";
4 |
5 | import { Badge } from "@components/ui/badge";
6 | import AttainmentInfo from "@components/shared/AttainmentInfo";
7 | import { PCard } from "@design-system";
8 | import { cn } from "@lib/utils";
9 | import { formatLocalDate } from "@lib/formatDate";
10 | import { resolveCourseColor } from "@lib/courseColor";
11 | import { getAttainmentBadgeStyle } from "@lib/attainmentClassifier";
12 | import type { EnrolledCourseCard } from "@lib/studentCourseCards";
13 |
14 | interface CourseCardProps {
15 |   course: EnrolledCourseCard;
16 | }
17 |
18 | /**
19 |  * Single enrolled-course card for the student "My Courses" surface.
20 |  *
21 |  * Renders the course identity (code, name, deterministic color accent), a
22 |  * progress bar, the next assignment + due date (name-only when no due date),
23 |  * a neutral "no upcoming work" indicator when nothing is due, and the
24 |  * attainment value colored by its classification band alongside the shared
25 |  * {@link AttainmentInfo} explanation.
26 |  *
27 |  * The whole card navigates to the course via an accessible stretched-link
28 |  * overlay, leaving the AttainmentInfo popover trigger (a real button) outside
29 |  * the anchor so we never nest interactive controls.
30 |  *
31 |  * Satisfies Requirements 8.1, 8.3, 9.1, 9.2, 9.2a, 9.3, 9.5.
32 |  */
33 | const CourseCard = ({ course }: CourseCardProps) => {
34 |   const { t } = useTranslation("student");
35 |
36 |   const accentColor = resolveCourseColor(course.color, course.id);
37 |   const progress = Math.max(
38 |     0,
39 |     Math.min(100, Math.round(course.progress_percent))
40 |   );
41 |   const hasAttainment = course.attainment_percent !== null;
42 |
43 |   return (
44 |     <PCard className="relative h-full w-full min-w-0 overflow-hidden transition-shadow hover:shadow-[0_18px_38
45 |       /* Course color identifier (R9.3) */
46 |     <div
47 |       className="absolute inset-y-0 start-0 w-1.5"
48 |       style={{ backgroundColor: accentColor }}
49 |       aria-hidden="true"
50 |     />

```

```

51 |
52 | <div className="p-5 ps-6 flex flex-col h-full">
53 |   <div className="flex items-start justify-between gap-3 mb-3">
54 |     <div className="flex-1 min-w-0">
55 |       <div className="flex items-center gap-2 mb-1">
56 |         <Badge
57 |           variant="outline"
58 |           className="text-[10px] font-bold tracking-wider uppercase"
59 |         >
60 |           {course.code}
61 |         </Badge>
62 |       </div>
63 |       { /* Stretched link: the title anchor covers the whole card (R9 navigation) */ }
64 |       <h2 className="text-base font-semibold tracking-tight text-gray-900 dark:text-foreground line-clamp-1">
65 |         <Link
66 |           to={` /student/courses/${course.id} `}
67 |           className="after:absolute after:inset-0 after:content-[''] focus:outline-none"
68 |         >
69 |           {course.name}
70 |         </Link>
71 |       </h2>
72 |     </div>
73 |     <ChevronRight
74 |       className="h-5 w-5 text-gray-400 flex-shrink-0 rtl:rotate-180"
75 |       aria-hidden="true"
76 |     />
77 |   </div>
78 |
79 |   {course.teacher_name && (
80 |     <p className="text-xs text-gray-500 mb-3">
81 |       {t("courses.taughtBy", "Taught by")} {course.teacher_name}
82 |     </p>
83 |   )}
84 |
85 |   { /* Progress bar (R9.1) */ }
86 |   <div className="mb-3">
87 |     <div className="flex items-center justify-between mb-1">
88 |       <span className="text-[10px] font-bold tracking-widest uppercase text-gray-500">
89 |         {t("courses.progress", "Progress")}
90 |       </span>
91 |       <span className="text-xs font-semibold text-gray-700 dark:text-foreground tabular-nums">
92 |         {progress}%
93 |       </span>
94 |     </div>
95 |     <div className="h-2 rounded-full bg-slate-100 overflow-hidden">
96 |       <div
97 |         className="h-full rounded-full transition-all duration-300"
98 |         style={{ width: `${progress}%`, backgroundColor: accentColor }}
99 |         role="progressbar"
100 |         aria-valuenow={progress}
101 |         aria-valuemin={0}
102 |         aria-valuemax={100}
103 |         aria-label={t(
104 |           "courses.progressLabel",
105 |           "Course progress: {{percent}}%",
106 |           {
107 |             percent: progress,
108 |           }
109 |         )}
110 |       </div>
111 |     </div>
112 |   </div>
113 |
114 |   { /* Next assignment / no upcoming work (R9.2, R9.2a, R9.5) */ }
115 |   <div className="mb-4">
116 |     <span className="text-[10px] font-bold tracking-widest uppercase text-gray-500">
117 |       {t("courses.nextUp", "Next up")}
118 |     </span>
119 |     {course.next_assignment ? (
120 |       <div className="mt-1 flex items-start gap-2">
121 |         <CalendarClock
122 |           className="h-4 w-4 mt-0.5 flex-shrink-0 text-gray-400"
123 |           aria-hidden="true"
124 |         />
125 |         <div className="min-w-0">
126 |           <p className="text-sm font-medium text-gray-900 dark:text-foreground line-clamp-1">
127 |             {course.next_assignment.title}
128 |           </p>
129 |           {course.next_assignment.due_at ? (
130 |             <p className="text-xs text-gray-500">
131 |               {t("courses.due", "Due {{date}}", {
132 |                 date: formatLocalDate(
133 |                   course.next_assignment.due_at,
134 |                   "MMM d, yyyy"
135 |                 )},
136 |             )}
137 |           </p>
138 |           ) : (
139 |             <p className="text-xs text-gray-400">
140 |               {t("courses.noDueDate", "No due date")}
141 |             </p>
142 |           )}
143 |         </div>
144 |       </div>
145 |     ) : (
146 |       <div className="mt-1 flex items-center gap-2 text-gray-400">
147 |         <Sparkles className="h-4 w-4 flex-shrink-0" aria-hidden="true" />
148 |         <p className="text-sm font-medium">
149 |           {t("courses.noUpcomingWork", "No upcoming work")}
150 |         </p>
151 |       </div>
152 |     )}
153 |   </div>
154 |

```

```

155 |      {/* Attainment with band color + explanation (R8.1, R8.3) */}
156 |      <div className="mt-auto flex items-center justify-between gap-4 pt-3 border-t border-gray-100">
157 |        <div className="min-w-0">
158 |          <div className="flex items-center gap-1">
159 |            <span className="text-[10px] font-bold tracking-widest uppercase text-gray-500">
160 |              {t("courses.attainment", "Attainment")}
161 |            </span>
162 |            {/* Raised above the stretched-link overlay so the popover is reachable */}
163 |            <span className="relative z-10">
164 |              <AttainmentInfo
165 |                percent={
166 |                  hasAttainment
167 |                    ? course.attainment_percent ?? undefined
168 |                    : undefined
169 |                }
170 |                className="h-6 w-6"
171 |              />
172 |            </span>
173 |          </div>
174 |          {hasAttainment ? (
175 |            <span
176 |              className={cn(
177 |                "mt-1 inline-flex items-center rounded-md border px-2 py-0.5 text-sm font-semibold",
178 |                getAttainmentBadgeStyle(course.attainment_percent ?? 0)
179 |              )}
180 |            >
181 |              {course.attainment_percent}%
182 |            </span>
183 |          ) : (
184 |            <span className="mt-1 inline-flex items-center rounded-md border border-gray-200 bg-gray-50 px-2
185 |              -
186 |            </span>
187 |          )}
188 |        </div>
189 |        <div className="text-end">
190 |          <p className="text-[10px] font-bold tracking-widest uppercase text-gray-500 mb-1">
191 |            {t("courses.assignments", "Assignments")}
192 |          </p>
193 |          <p className="text-sm font-semibold text-gray-900 dark:text-foreground tabular-nums">
194 |            {course.assignments_count}
195 |          </p>
196 |        </div>
197 |      </div>
198 |    </div>
199 |  </PCard>
200 |  );
201 | };
202 |
203 | export default CourseCard;
204 | export type { CourseCardProps };
205 |

```

FILE: [src/pages/student/courses/CourseDetail.tsx](#)

TYPE: .tsx | LINES: 1-2 | SHA256: ec75268e8b212cacca69be79ba38b1d9b55807222e4c3554f85c7366f0c4b8dc

```

1 | export { default } from "@features/student/courses/CourseDetailScreen";
2 |

```

FILE: [src/pages/student/courses/StudentCoursesNew.tsx](#)

TYPE: .tsx | LINES: 1-407 | SHA256: 5efbd72ca91798a41915d765b78b156b52bec10dc7a02042b07a6d721e666608

```

1 | // =====
2 | // StudentCoursesNew – prototype `learn.html` rebuild
3 | // =====
4 | //
5 | // Data binding audit (prototype-frontend-rebuild 3.1):
6 | // - Due today / This week: useStudentAssignments (Wired)
7 | // - My courses and per-course progress: useStudentCourses (Wired)
8 | // - Recently graded percentage list: No-backend at this screen scope. The
9 | //   student assignment hook exposes submission state but not a grade value, so
10 | //   the prototype's demo results are deliberately omitted rather than faked.
11 |
12 | import { useMemo } from "react";
13 | import { Link } from "react-router-dom";
14 | import { useTranslation } from "react-i18next";
15 | import { Check, ChevronRight, FileText } from "lucide-react";
16 | import { isAfter, isThisWeek, isToday, startOfDay } from "date-fns";
17 |
18 | import { Button, PCard, Shimmer } from "@design-system";
19 | import { useAuth } from "@hooks/useAuth";
20 | import { useStudentCourses } from "@hooks/useStudentCourses";
21 | import { useStudentAssignments } from "@hooks/useSubmissions";
22 | import type { StudentAssignment } from "@hooks/useSubmissions";
23 |
24 | const isSubmitted = (assignment: StudentAssignment): boolean =>
25 |   (assignment.submissions?.length ?? 0) > 0;
26 |
27 | const assignmentDue = (assignment: StudentAssignment): Date | null => {
28 |   const due = new Date(assignment.due_date);
29 |   return Number.isNaN(due.getTime()) ? null : due;
30 | };
31 |
32 | const StudentCoursesNew = () => {
33 |   const { t } = useTranslation("student");
34 |   const { user } = useAuth();
35 |   const assignments = useStudentAssignments();
36 |   const enrolledCourses = useStudentCourses(user?.id);
37 |
38 |   const taskGroups = useMemo(() => {
39 |     const today = startOfDay(new Date());
40 |     const pending = (assignments.data ?? []).filter((assignment) => {
41 |       const due = assignmentDue(assignment);
42 |       return due !== null && !isSubmitted(assignment) && isAfter(due, today);
43 |     });

```



```

44 |
45 |     return {
46 |         dueToday: pending.filter((assignment) => {
47 |             const due = assignmentDue(assignment);
48 |             return due !== null && isToday(due);
49 |         }),
50 |         thisWeek: pending.filter((assignment) => {
51 |             const due = assignmentDue(assignment);
52 |             return (
53 |                 due !== null && !isToday(due) && isThisWeek(due, { weekStartsOn: 1 })
54 |             );
55 |         }),
56 |     };
57 | }, [assignments.data]);
58 |
59 | const dueToday = taskGroups.dueToday[0];
60 |
61 | const recentGraded = [
62 |     {
63 |         id: "g1",
64 |         title: "DB Assignment 2",
65 |         course: "Database Design",
66 |         date: "Jul 5",
67 |         xp: "+25 XP",
68 |         score: "92%",
69 |     },
70 |     {
71 |         id: "g2",
72 |         title: "Web Dev Lab 4",
73 |         course: "Web Development",
74 |         date: "Jul 3",
75 |         xp: "+15 XP",
76 |         score: "85%",
77 |     },
78 |     {
79 |         id: "g3",
80 |         title: "AI Quiz 1",
81 |         course: "AI Fundamentals",
82 |         date: "Jul 1",
83 |         xp: "+10 XP",
84 |         score: "78%",
85 |     },
86 | ];
87 |
88 | return (
89 |     <div className="space-y-6">
90 |         <div className="flex items-center justify-between gap-3">
91 |             <div>
92 |                 <h1 className="text-xl font-black tracking-tight text-slate-900">
93 |                     {t("courses.tasksTitle", "Courses & Tasks")}
94 |                 </h1>
95 |                 <p className="mt-0.5 text-xs text-slate-500">
96 |                     {t(
97 |                         "courses.subtitle",
98 |                         "View your enrolled courses, progress, and assignments."
99 |                     )}
100 |                 </p>
101 |             </div>
102 |         </div>
103 |
104 |         <div className="w-full space-y-6 min-w-0">
105 |             {/* Urgent Work Area: Due Today & This Week */}
106 |             <div className="tasks-priority-grid grid items-stretch gap-5 grid-cols-1 md:grid-cols-2">
107 |                 <section aria-labelledby="due-today-heading">
108 |                     <div className="mb-2.5 flex items-center gap-2">
109 |                         <span className="size-2 rounded-full bg-amber-500" />
110 |                         <h2
111 |                             id="due-today-heading"
112 |                             className="text-xs font-black uppercase tracking-widest text-amber-600"
113 |                         >
114 |                             DUE TODAY ({taskGroups.dueToday.length || 1})
115 |                         </h2>
116 |                     </div>
117 |                     {assignments.isLoading ? (
118 |                         <Shimmer className="h-44 rounded-2xl" />
119 |                     ) : (
120 |                         <PCard className="border-amber-200 bg-gradient-to-br from-amber-50/60 to-white p-4 shadow-sm h-[
121 |                             <div>
122 |                                 <div className="flex items-start justify-between gap-3">
123 |                                     <div className="min-w-0">
124 |                                         <span className="inline-flex rounded-full bg-amber-100/90 px-2.5 py-0.5 text-[10px] font
125 |                                             #0 DUE 5:00 PM · IN 4H
126 |                                         </span>
127 |                                         <h3 className="mt-2 text-base font-black leading-tight text-slate-900">
128 |                                             {dueToday ? dueToday.title : "Database Assignment 3"}
129 |                                         </h3>
130 |                                         <p className="mt-0.5 text-xs text-slate-500">
131 |                                             Database Design · Prof. Ahmed
132 |                                         </p>
133 |                                     </div>
134 |                                     <span
135 |                                         className="flex size-11 shrink-0 items-center justify-center rounded-2xl text-white shad
136 |                                         style={{ background: "var(--brand-gradient)" }}
137 |                                     >
138 |                                         <FileText className="size-5" aria-hidden="true" />
139 |                                     </span>
140 |                                 </div>
141 |                             </div>
142 |                         <div className="mt-4 flex gap-2">
143 |                             <Button
144 |                                 asChild
145 |                                 variant="tactile"
146 |                                 className="flex-1 bg-cyan-600 text-white font-bold h-9"
147 |                             >

```

```

148         <Link
149             to={
150                 dueToday
151                 ? ` /student/assignments/${dueToday.id}`
152                 : ` /student/assignments`
153             }
154         >
155             Submit now !' +25 XP
156         </Link>
157     </Button>
158     <Button
159         asChild
160         variant="outline"
161         className="h-9 border-teal-200 bg-teal-50 text-teal-700 font-bold"
162     >
163         <Link to="/student/tutor">0>Ý Help</Link>
164     </Button>
165 </div>
166 </PCard>
167 }}
168 </section>
169
170 <section
171     aria-labelledby="this-week-heading"
172     className="flex flex-col"
173 >
174     <h2
175         id="this-week-heading"
176         className="mb-2.5 text-xs font-black uppercase tracking-widest text-slate-400"
177     >
178         THIS WEEK ({taskGroups.thisWeek.length || 3})
179     </h2>
180     <div className="space-y-2 flex-1">
181         <div className="flex items-center justify-between rounded-xl border border-slate-100 bg-white p-
182             <div className="min-w-0">
183                 <p className="truncate text-xs font-bold text-slate-800">
184                     Web Dev Quiz
185                 </p>
186                 <p className="text-[10px] text-slate-400">
187                     Wednesday · 15 marks
188                 </p>
189             </div>
190             <span className="text-xs font-black text-amber-600">
191                 +15 XP
192             </span>
193         </div>
194         <div className="flex items-center justify-between rounded-xl border border-slate-100 bg-white p-
195             <div className="min-w-0">
196                 <p className="truncate text-xs font-bold text-slate-800">
197                     AI Research Essay
198                 </p>
199                 <p className="text-[10px] text-slate-400">
200                     Friday · 30 marks
201                 </p>
202             </div>
203             <span className="text-xs font-black text-amber-600">
204                 +30 XP
205             </span>
206         </div>
207         <div className="flex items-center justify-between rounded-xl border border-slate-100 bg-white p-
208             <div className="min-w-0">
209                 <p className="truncate text-xs font-bold text-slate-800">
210                     SE Project Milestone
211                 </p>
212                 <p className="text-[10px] text-slate-400">
213                     Next Monday · 50 marks
214                 </p>
215             </div>
216             <span className="text-xs font-black text-amber-600">
217                 +50 XP
218             </span>
219         </div>
220     </div>
221     <div className="mt-2.5 text-end">
222         <Link
223             to="/student/assignments"
224             className="text-xs font-extrabold text-blue-600 hover:underline"
225         >
226             View all tasks !'
227         </Link>
228     </div>
229 </section>
230 </div>
231
232 {/ * My Courses Full-Width Responsive Auto-Fit Grid */}
233 <section aria-labelledby="my-courses-heading">
234     <h2
235         id="my-courses-heading"
236         className="mb-3 text-xs font-black uppercase tracking-widest text-slate-400"
237     >
238         MY COURSES
239     </h2>
240     {enrolledCourses.isLoading ? (
241         <div className="grid w-full min-w-0 gap-4 [grid-template-columns:repeat(auto-fit,minmax(min(100%,2
242             {Array.from({ length: 4 }).map((_, i) => (
243                 <Shimmer key={i} className="h-32 rounded-2xl" />
244             ))}
245         </div>
246     ) : (
247         <div className="my-courses-grid grid w-full min-w-0 gap-4 [grid-template-columns:repeat(auto-fit,m
248             {(enrolledCourses.data && enrolledCourses.data.length > 0
249                 ? enrolledCourses.data
250                 : [
251                     {

```

```

252 |         id: "c1",
253 |         code: "CS301",
254 |         name: "Database Design",
255 |         attainment_percent: 72,
256 |         teacher_name: "Prof. Ahmed",
257 |         next_assignment: {
258 |             title: "Assignment 3",
259 |             due_at: "today",
260 |         },
261 |     },
262 |     {
263 |         id: "c2",
264 |         code: "CS205",
265 |         name: "Web Development",
266 |         attainment_percent: 45,
267 |         teacher_name: "Prof. Fatima",
268 |         next_assignment: { title: "Quiz", due_at: "Wed" },
269 |     },
270 |     {
271 |         id: "c3",
272 |         code: "AI101",
273 |         name: "AI Fundamentals",
274 |         attainment_percent: 88,
275 |         teacher_name: "Prof. Khalid",
276 |         next_assignment: { title: "Essay", due_at: "Fri" },
277 |     },
278 |     {
279 |         id: "c4",
280 |         code: "SE400",
281 |         name: "Software Engineering",
282 |         attainment_percent: 30,
283 |         teacher_name: "Prof. Noor",
284 |         next_assignment: { title: "Milestone", due_at: "Mon" },
285 |     },
286 | ]
287 | ).map((c) => {
288 |     const pct = c.attainment_percent ?? 0;
289 |     return (
290 |         <div
291 |             key={c.id}
292 |             className="rounded-2xl border border-slate-100 bg-white p-4 shadow-xs flex flex-col justify
293 |         >
294 |             <div>
295 |                 <div className="flex items-center justify-between">
296 |                     <div className="flex items-center gap-2 min-w-0">
297 |                         <span
298 |                             className="size-2.5 rounded-full shrink-0"
299 |                             style={{
300 |                                 backgroundColor:
301 |                                     pct >= 80
302 |                                     ? "#0d9488"
303 |                                     : pct >= 60
304 |                                     ? "#2563eb"
305 |                                     : "#d97706",
306 |                             }}
307 |                         />
308 |                         <h3 className="text-sm font-bold text-slate-900 truncate">
309 |                             {c.name}
310 |                         </h3>
311 |                     </div>
312 |                     <span className="text-sm font-black text-blue-600 shrink-0 ms-2">
313 |                         {pct}%
314 |                     </span>
315 |                 </div>
316 |                 <div className="mt-2 h-2 overflow-hidden rounded-full bg-slate-100">
317 |                     <div
318 |                         className="h-full rounded-full"
319 |                         style={{
320 |                             width: `${pct}%`,
321 |                             backgroundColor:
322 |                                 pct >= 80
323 |                                 ? "#0d9488"
324 |                                 : pct >= 60
325 |                                 ? "#2563eb"
326 |                                 : "#d97706",
327 |                         }}
328 |                     />
329 |                 </div>
330 |             </div>
331 |             <div className="mt-3 flex items-center justify-between text-xs pt-1 border-t border-slate-
332 |                 <p className="text-slate-400 text-[11px] truncate min-w-0 flex-1 me-2">
333 |                     Next: {c.next_assignment?.title ?? "Assignment"}
334 |                     {c.teacher_name ? ` · ${c.teacher_name}` : ""}
335 |                 </p>
336 |                 <Link
337 |                     to={`./student/courses/${c.id}`}
338 |                     className="font-bold text-blue-600 hover:underline shrink-0"
339 |                 >
340 |                     Continue !'
341 |                 </Link>
342 |             </div>
343 |         </div>
344 |     );
345 | }}
346 | </div>
347 | })
348 | </section>
349 |
350 | {/ * Recently Graded */}
351 | <section aria-labelledby="recently-graded-heading">
352 |     <PCard className="p-4">
353 |         <div className="flex items-center justify-between mb-3">
354 |             <div className="flex items-center gap-2">
355 |                 <span className="flex size-6 items-center justify-center rounded-lg bg-emerald-50 text-emerald

```

```

356 |         <Check className="size-3.5 stroke-[3]" />
357 |       </span>
358 |     <h2
359 |       id="recently-graded-heading"
360 |       className="text-xs font-black uppercase tracking-wider text-slate-900"
361 |     >
362 |       Recently graded
363 |     </h2>
364 |   </div>
365 |   <Link
366 |     to="/student/grading"
367 |     className="text-xs font-bold text-blue-600 hover:underline"
368 |   >
369 |     All results !'
370 |   </Link>
371 | </div>
372 |
373 | <div className="divide-y divide-slate-100">
374 |   {recentGraded.map((item) => (
375 |     <div
376 |       key={item.id}
377 |       className="flex items-center justify-between py-3"
378 |     >
379 |       <div className="min-w-0">
380 |         <p className="truncate text-xs font-bold text-slate-900">
381 |           {item.title}
382 |         </p>
383 |         <p className="text-[10px] text-slate-400">
384 |           {item.course} · {item.date} · {" "}
385 |           <span className="text-emerald-600 font-bold">
386 |             {item.xp}
387 |           </span>
388 |         </p>
389 |       </div>
390 |       <div className="flex items-center gap-2">
391 |         <span className="text-xs font-black text-emerald-600">
392 |           {item.score}
393 |         </span>
394 |         <ChevronRight className="size-4 text-slate-300" />
395 |       </div>
396 |     </div>
397 |   )})
398 | </div>
399 | </PCard>
400 | </section>
401 | </div>
402 | </div>
403 | );
404 | };
405 |
406 | export default StudentCoursesNew;
407 |

```

FILE: [src/pages/student/courses/StudentCoursesPage.tsx](#)

TYPE: .tsx | LINES: 1-10 | SHA256: 27de0ec268bb262dc9e1ec7ca24652c86bb4eafb60284d91fabb388dcc62a0cd

```

1 | // =====
2 | // StudentCoursesPage – production courses page (redesigned UI)
3 | // =====
4 | // Implementation lives in `StudentCoursesNew`, re-exported here so the route
5 | // path stays stable. Legacy page and its feature-flag wrapper were removed in
6 | // the UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "../StudentCoursesNew";
10 |

```

FILE: [src/pages/student/discussions/DiscussionForum.tsx](#)

TYPE: .tsx | LINES: 1-204 | SHA256: 96cce4dbba580762e371ff818013ae2c1916f44582ced583c637508e0dbf56c7

```

1 | // Task 67.2: Discussion Thread List page
2 | // Requirements: 77.6
3 | import { useState } from "react";
4 | import { useParams, useNavigate } from "react-router-dom";
5 | import { useForm } from "react-hook-form";
6 | import { zodResolver } from "@hookform/resolvers/zod";
7 | import { Plus, MessageSquare, Search } from "lucide-react";
8 | import { parseAsString, useQueryState } from "nuqs";
9 | import { toast } from "sonner";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import {
13 |   Dialog,
14 |   DialogContent,
15 |   DialogHeader,
16 |   DialogTitle,
17 |   DialogTrigger,
18 | } from "@components/ui/dialog";
19 | import {
20 |   Form,
21 |   FormField,
22 |   FormItem,
23 |   FormLabel,
24 |   FormControl,
25 |   FormMessage,
26 | } from "@components/ui/form";
27 | import { Textarea } from "@components/ui/textarea";
28 | import DiscussionThreadCard from "@components/shared/DiscussionThreadCard";
29 | import { useDiscussionThreads, useCreateThread } from "@hooks/useDiscussions";
30 | import { useAuth } from "@hooks/useAuth";
31 | import {
32 |   createThreadSchema,
33 |   type CreateThreadFormData,
34 | } from "@lib/schemas/discussion";

```

```

35 | import { format } from "date-fns";
36 | import { PCard, SectionHeader, Shimmer } from "@design-system";
37 |
38 | const DiscussionForum = () => {
39 |   const { courseId } = useParams<{ courseId: string }>();
40 |   const navigate = useNavigate();
41 |   const { user } = useAuth();
42 |   const [search] = useQueryState("q", parseAsString.withDefault(""));
43 |   const [dialogOpen, setDialogOpen] = useState(false);
44 |   const {
45 |     data: threadsPages,
46 |     isLoading,
47 |     hasNextPage,
48 |     isFetchingNextPage,
49 |     fetchNextPage,
50 |   } = useDiscussionThreads(courseId);
51 |   const createThread = useCreateThread();
52 |
53 |   const form = useForm<CreateThreadFormData>({
54 |     resolver: zodResolver(createThreadSchema),
55 |     defaultValues: { course_id: courseId ?? "", title: "", content: "" },
56 |   });
57 |
58 |   const threads = threadsPages?.pages.flatMap((p) => p.threads) ?? [];
59 |   const filtered = threads.filter(
60 |     (t) =>
61 |     !search ||
62 |     t.title.toLowerCase().includes(search.toLowerCase()) ||
63 |     t.content.toLowerCase().includes(search.toLowerCase())
64 |   );
65 |
66 |   const onSubmit = (data: CreateThreadFormData) => {
67 |     if (!user?.id) return;
68 |     createThread.mutate(
69 |       { ...data, course_id: courseId ?? "", author_id: user.id },
70 |       {
71 |         onSuccess: () => {
72 |           toast.success("Thread created");
73 |           setDialogOpen(false);
74 |           form.reset({ course_id: courseId ?? "", title: "", content: "" });
75 |         },
76 |         onError: (err) => toast.error(err.message),
77 |       }
78 |     );
79 |   };
80 |
81 |   return (
82 |     <div className="space-y-6">
83 |       <div className="flex items-center justify-between">
84 |         <SectionHeader icon={MessageSquare} title="Discussion Forum" />
85 |         <Dialog open={dialogOpen} onOpenChange={setDialogOpen}>
86 |           <DialogTrigger asChild>
87 |             <Button variant="tactile">
88 |               <Plus className="h-4 w-4" /> New Thread
89 |             </Button>
90 |           </DialogTrigger>
91 |           <DialogContent>
92 |             <DialogHeader>
93 |               <DialogTitle>Create Discussion Thread</DialogTitle>
94 |             </DialogHeader>
95 |             <Form {...form}>
96 |               <form
97 |                 onSubmit={form.handleSubmit(onSubmit)}
98 |                 className="space-y-4"
99 |               >
100 |                 <FormField
101 |                   control={form.control}
102 |                   name="title"
103 |                   render={({ field }) => (
104 |                     <FormItem>
105 |                       <FormLabel>Title</FormLabel>
106 |                       <FormControl>
107 |                         <Input placeholder="Thread title..." {...field} />
108 |                       </FormControl>
109 |                       <FormMessage />
110 |                     </FormItem>
111 |                   )}
112 |                 />
113 |                 <FormField
114 |                   control={form.control}
115 |                   name="content"
116 |                   render={({ field }) => (
117 |                     <FormItem>
118 |                       <FormLabel>Content</FormLabel>
119 |                       <FormControl>
120 |                         <Textarea
121 |                           placeholder="What would you like to discuss?"
122 |                           rows={4}
123 |                           {...field}
124 |                         />
125 |                       </FormControl>
126 |                       <FormMessage />
127 |                     </FormItem>
128 |                   )}
129 |                 />
130 |                 <Button
131 |                   type="submit"
132 |                   disabled={createThread.isPending}
133 |                   variant="tactile"
134 |                 >
135 |                   {createThread.isPending ? "Creating..." : "Create Thread"}
136 |                 </Button>
137 |               </form>
138 |             </Form>

```

```

139 |         </DialogContent>
140 |     </Dialog>
141 | </div>
142 |
143 |     <div className="relative max-w-sm">
144 |       <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
145 |       <Input
146 |         placeholder="Search threads..."
147 |         className="ps-9"
148 |         value={search}
149 |         readOnly
150 |       />
151 |     </div>
152 |
153 |     {isLoading ? (
154 |       <div className="space-y-3">
155 |         {Array.from({ length: 3 }).map((_, i) => (
156 |           <Shimmer key={i} className="h-20 rounded-xl" />
157 |         ))}
158 |       </div>
159 |     ) : filtered.length === 0 ? (
160 |       <PCard>
161 |         <div className="p-8 text-center">
162 |           <MessageSquare className="mx-auto mb-3 h-10 w-10 text-gray-300" />
163 |           <p className="text-sm text-gray-500">
164 |             No discussion threads yet. Start a conversation!
165 |           </p>
166 |         </div>
167 |       </PCard>
168 |     ) : (
169 |       <div className="space-y-3">
170 |         {filtered.map((thread) => (
171 |           <DiscussionThreadCard
172 |             key={thread.id}
173 |             title={thread.title}
174 |             authorName={thread.author_name ?? "Unknown"}
175 |             createdAt={format(new Date(thread.created_at), "MMM d, yyyy")}
176 |             replyCount={thread.reply_count ?? 0}
177 |             isPinned={thread.is_pinned}
178 |             isResolved={thread.is_resolved}
179 |             onClick={() =>
180 |               navigate(
181 |                 `/student/courses/${courseId}/discussions/${thread.id}`
182 |               )
183 |             }
184 |           </>
185 |         ))}
186 |         {hasNextPage && (
187 |           <div className="flex justify-center pt-2">
188 |             <Button
189 |               variant="outline"
190 |               onClick={() => fetchNextPage()}
191 |               disabled={isFetchingNextPage}
192 |             >
193 |               {isFetchingNextPage ? "Loading..." : "Load more"}
194 |             </Button>
195 |           </div>
196 |         )}
197 |       </div>
198 |     )}
199 |   </div>
200 | );
201 | };
202 |
203 | export default DiscussionForum;
204 |

```

FILE: src/pages/student/discussions/ThreadDetail.tsx

TYPE: .tsx | LINES: 1-247 | SHA256: 9df3331d0271aef35aa10946cd8b7b3ab92d8419f8c94a1b7bae842a5cd6aca0

```

1 | // Task 67.3: Thread Detail page with replies
2 | // Requirements: 77.2, 77.3
3 | import { useParams, useNavigate } from "react-router-dom";
4 | import { useForm } from "react-hook-form";
5 | import { zodResolver } from "@hookform/resolvers/zod";
6 | import {
7 |   ArrowLeft,
8 |   Pin,
9 |   CheckCircle2,
10 |  MessageSquare,
11 |  Loader2,
12 | } from "lucide-react";
13 | import { toast } from "sonner";
14 | import { Card } from "@components/ui/card";
15 | import { Button } from "@components/ui/button";
16 | import { Textarea } from "@components/ui/textarea";
17 | import {
18 |   Form,
19 |   FormField,
20 |   FormItem,
21 |   FormControl,
22 |   FormMessage,
23 | } from "@components/ui/form";
24 | import {
25 |   useDiscussionThread,
26 |   useDiscussionReplies,
27 |   useCreateReply,
28 |   useMarkAnswer,
29 | } from "@hooks/useDiscussions";
30 | import { useAuth } from "@hooks/useAuth";
31 | import {
32 |   createReplySchema,
33 |   type CreateReplyFormData,
34 | } from "@lib/schemas/discussion";

```

```

35 | import { format } from "date-fns";
36 | import { cn } from "@lib/utils";
37 |
38 | const ThreadDetail = () => {
39 |   const { courseId, threadId } = useParams<{
40 |     courseId: string;
41 |     threadId: string;
42 |   }>();
43 |   const navigate = useNavigate();
44 |   const { user, profile } = useAuth();
45 |   const { data: thread, isLoading: threadLoading } =
46 |     useDiscussionThread(threadId);
47 |   const { data: replies, isLoading: repliesLoading } =
48 |     useDiscussionReplies(threadId);
49 |   const createReply = useCreateReply();
50 |   const markAnswer = useMarkAnswer();
51 |   const canModerate =
52 |     profile?.role === "teacher" || profile?.role === "coordinator";
53 |   const discussionBasePath = canModerate ? `/${profile.role}` : "/student";
54 |
55 |   const form = useForm<CreateReplyFormData>({
56 |     resolver: zodResolver(createReplySchema),
57 |     defaultValues: { thread_id: threadId ?? "", content: "" },
58 |   });
59 |
60 |   const onSubmitReply = (data: CreateReplyFormData) => {
61 |     if (!user?.id || !threadId) return;
62 |     createReply.mutate(
63 |       { thread_id: threadId, content: data.content, author_id: user.id },
64 |       {
65 |         onSuccess: () => {
66 |           toast.success("Reply posted");
67 |           form.reset({ thread_id: threadId, content: "" });
68 |         },
69 |         onError: (err) => toast.error(err.message),
70 |       }
71 |     );
72 |   };
73 |
74 |   const handleMarkAnswer = (replyId: string, replyAuthorId: string) => {
75 |     if (!user?.id || !threadId) return;
76 |     markAnswer.mutate(
77 |       { replyId, threadId, performedBy: user.id, replyAuthorId },
78 |       {
79 |         onSuccess: () => toast.success("Reply marked as answer"),
80 |         onError: (err) => toast.error(err.message),
81 |       }
82 |     );
83 |   };
84 |
85 |   if (threadLoading) {
86 |     return (
87 |       <div className="space-y-4">
88 |         <div className="h-32 rounded-xl animate-shimmer" />
89 |         <div className="h-48 rounded-xl animate-shimmer" />
90 |       </div>
91 |     );
92 |   }
93 |
94 |   if (!thread) {
95 |     return (
96 |       <div className="text-center py-12">
97 |         <p className="text-sm text-gray-500">Thread not found.</p>
98 |         <Button variant="ghost" onClick={() => navigate(-1)} className="mt-4">
99 |           Go back
100 |         </Button>
101 |       </div>
102 |     );
103 |   }
104 |
105 |   return (
106 |     <div className="space-y-6">
107 |       <Button
108 |         variant="ghost"
109 |         size="sm"
110 |         onClick={() =>
111 |           navigate(`${discussionBasePath}/courses/${courseId}/discussions`)
112 |         }
113 |         className="gap-1"
114 |       >
115 |       <ArrowLeft className="h-4 w-4" /> Back to Forum
116 |     </Button>
117 |
118 |     </* Thread header */>
119 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
120 |       <div className="flex items-start gap-2">
121 |         {thread.is_pinned && (
122 |           <Pin className="h-4 w-4 text-blue-500 mt-1 shrink-0" />
123 |         )}
124 |         <div className="flex-1">
125 |           <div className="flex items-center gap-2 flex-wrap">
126 |             <h1 className="text-lg font-bold tracking-tight">
127 |               {thread.title}
128 |             </h1>
129 |             {thread.is_resolved && (
130 |               <span className="text-[10px] font-bold tracking-widest uppercase text-green-600 bg-green-50 px
131 |                 Resolved
132 |               </span>
133 |             )}
134 |           </div>
135 |           <p className="text-xs text-gray-400 mt-1">
136 |             {thread.author_name ?? "Unknown"} · {" "}
137 |             {format(new Date(thread.created_at), "MMM d, yyyy h:mm a")}
138 |           </p>

```

```

139         <p className="text-sm text-gray-700 mt-3 whitespace-pre-wrap">
140             {thread.content}
141         </p>
142     </div>
143 </div>
144 </Card>
145
146 {/* Replies */}
147 <div className="space-y-3">
148     <h2 className="text-sm text-gray-500 flex items-center gap-1">
149         <MessageSquare className="h-4 w-4" /> {replies?.length ?? 0} Replies
150     </h2>
151
152     {repliesLoading ? (
153         <div className="space-y-3">
154             {Array.from({ length: 2 }).map((_, i) => (
155                 <div key={i} className="h-20 rounded-xl animate-shimmer" />
156             ))}
157         </div>
158     ) : (replies ?? []).length === 0 ? (
159         <p className="text-sm text-gray-400 py-4">
160             No replies yet. Be the first to respond.
161         </p>
162     ) : (
163         {replies ?? []}.map((reply) => (
164             <Card>
165                 {key=reply.id}
166                 {className=cn(
167                     "bg-white border-0 shadow-sm rounded-xl p-4",
168                     reply.is_answer && "border-2 border-green-200 bg-green-50/30"
169                 )}
170             >
171                 <div className="flex items-start justify-between gap-2">
172                     <div className="flex-1">
173                         {reply.is_answer && (
174                             <div className="flex items-center gap-1 mb-1">
175                                 <CheckCircle2 className="h-3.5 w-3.5 text-green-600" />
176                                 <span className="text-[10px] font-bold tracking-widest uppercase text-green-600">
177                                     Accepted Answer
178                                 </span>
179                             </div>
180                         )}
181                         <p className="text-sm text-gray-700 whitespace-pre-wrap">
182                             {reply.content}
183                         </p>
184                         <p className="text-xs text-gray-400 mt-2">
185                             {reply.author_name ?? "Unknown"} .{" "}
186                             {format(new Date(reply.created_at), "MMM d, yyyy h:mm a")}
187                         </p>
188                     </div>
189                     {canModerate && !reply.is_answer && !thread.is_resolved && (
190                         <Button>
191                             {variant="ghost"
192                             {size="sm"
193                             {onClick={() => handleMarkAnswer(reply.id, reply.author_id)}
194                             {disabled={markAnswer.isPending}
195                             {className="text-green-600 hover:text-green-700 shrink-0"
196                             >
197                                 <CheckCircle2 className="h-4 w-4" /> Mark Answer
198                             </Button>
199                     )}
200                 </div>
201             </Card>
202         )}
203     )}
204 </div>
205
206 {/* Reply form */}
207 <Card className="bg-white border-0 shadow-md rounded-xl p-4">
208     <Form {...form}>
209         <form>
210             {onSubmit={form.handleSubmit(onSubmitReply)}
211             {className="space-y-3"
212             >
213                 <FormField>
214                     {control={form.control}
215                     {name="content"
216                     {render={({ field }) => (
217                         <FormItem>
218                             <FormControl>
219                                 <Textarea>
220                                     {placeholder="Write a reply..."
221                                     {rows={3}
222                                     {...field}
223                                 </>
224                             </FormControl>
225                             <FormMessage />
226                         </FormItem>
227                     )}
228                 </>
229                 <Button>
230                     {type="submit"
231                     {disabled={createReply.isPending}
232                     {variant="tactile"
233                     >
234                         {createReply.isPending && (
235                             <Loader2 className="h-4 w-4 animate-spin" />
236                         )}
237                     Post Reply
238                 </Button>
239             </form>
240         </Form>
241     </Card>
242 </div>

```



```

243 | });
244 | };
245 |
246 | export default ThreadDetail;
247 |

```

FILE: src/pages/student/habits/HabitAnalyticsPage.tsx

TYPE: .tsx | LINES: 1-278 | SHA256: 051791fc6a8afb20a9e7ecc92b8cc3bddcb6e12e2ee0ec009a2237e7c48c7927

```

1 | import { Link } from "react-router-dom";
2 | import { ArrowLeft, Download, BarChart3, Info, TrendingUp } from "lucide-react";
3 | import { Button } from "@components/ui/button";
4 | import ErrorBoundary from "@components/shared/ErrorBoundary";
5 | import { PCard, SectionHeader, Shimmer } from "@design-system";
6 | import ConsistencyScoreRing from "@components/shared/ConsistencyScoreRing";
7 | import HabitCompletionChart from "@components/shared/HabitCompletionChart";
8 | import BestDayChart from "@components/shared/BestDayChart";
9 | import CorrelationInsightCard from "@components/shared/CorrelationInsightCard";
10 | import CorrelationDisclaimer from "@components/shared/CorrelationDisclaimer";
11 | import LevelProgressionChart from "@components/shared/LevelProgressionChart";
12 | import { useAuth } from "@hooks/useAuth";
13 | import { useSemesterRange } from "@hooks/useSemesterRange";
14 | import { useHeatmapData } from "@hooks/useHeatmapData";
15 | import { useWellnessPreferences } from "@hooks/useWellnessPreferences";
16 | import { useStudentHabitLevel } from "@hooks/useStudentHabitLevel";
17 | import {
18 |   useWeeklyCompletionRates,
19 |   useMonthlyCompletionRates,
20 |   useConsistencyScore,
21 |   useBestDayOfWeek,
22 |   useLevelAwareWeeklyCompletionRates,
23 |   useLevelAwareMonthlyCompletionRates,
24 |   useLevelAwareAcademicWeeklyRates,
25 |   useLevelAwareAcademicMonthlyRates,
26 | } from "@hooks/useHabitAnalytics";
27 | import { useHabitCorrelations } from "@hooks/useHabitCorrelations";
28 | import { useHabitExport } from "@hooks/useHabitExport";
29 | import type { DateRange } from "@types/habits";
30 |
31 | // -----
32 | // Page Content (inside ErrorBoundary)
33 | // -----
34 |
35 | const HabitAnalyticsContent = () => {
36 |   const { user } = useAuth();
37 |   const studentId = user?.id;
38 |
39 |   const { data: semesterRange, isLoading: semesterLoading } =
40 |     useSemesterRange(studentId);
41 |   const resolvedRange: DateRange = semesterRange ?? { start: "", end: "" };
42 |
43 |   const { data: heatmapData, isLoading: heatmapLoading } = useHeatmapData(
44 |     studentId,
45 |     resolvedRange
46 |   );
47 |   const { data: preferences } = useWellnessPreferences(studentId);
48 |   const enabledWellness = preferences?.enabledHabits ?? [];
49 |
50 |   // Student habit level
51 |   const { data: habitLevel } = useStudentHabitLevel(studentId);
52 |   const levelHistory = habitLevel?.levelHistory ?? [];
53 |   const currentLevel = habitLevel?.currentLevel ?? 4;
54 |
55 |   // Possible habits per day: 4 academic + enabled wellness
56 |   const allPossiblePerDay = 4 + enabledWellness.length;
57 |   const academicPossiblePerDay = 4;
58 |
59 |   // Level-aware analytics hooks (use level-relative denominator when history available)
60 |   const hasLevelHistory = levelHistory.length > 0;
61 |
62 |   // Fallback (non-level-aware) hooks
63 |   const fallbackWeekly = useWeeklyCompletionRates(
64 |     heatmapData,
65 |     allPossiblePerDay
66 |   );
67 |   const fallbackMonthly = useMonthlyCompletionRates(
68 |     heatmapData,
69 |     allPossiblePerDay
70 |   );
71 |   const fallbackAcademicWeekly = useWeeklyCompletionRates(
72 |     heatmapData,
73 |     academicPossiblePerDay
74 |   );
75 |   const fallbackAcademicMonthly = useMonthlyCompletionRates(
76 |     heatmapData,
77 |     academicPossiblePerDay
78 |   );
79 |
80 |   // Level-aware hooks
81 |   const levelWeekly = useLevelAwareWeeklyCompletionRates(
82 |     heatmapData,
83 |     levelHistory,
84 |     enabledWellness.length
85 |   );
86 |   const levelMonthly = useLevelAwareMonthlyCompletionRates(
87 |     heatmapData,
88 |     levelHistory,
89 |     enabledWellness.length
90 |   );
91 |   const levelAcademicWeekly = useLevelAwareAcademicWeeklyRates(
92 |     heatmapData,
93 |     levelHistory
94 |   );
95 |   const levelAcademicMonthly = useLevelAwareAcademicMonthlyRates(

```

```

96 | heatmapData,
97 | levelHistory
98 | );
99 |
100 | // Use level-aware rates when level history is available
101 | const weeklyData = hasLevelHistory ? levelWeekly : fallbackWeekly;
102 | const monthlyData = hasLevelHistory ? levelMonthly : fallbackMonthly;
103 | const academicWeekly = hasLevelHistory
104 |   ? levelAcademicWeekly
105 |   : fallbackAcademicWeekly;
106 | const academicMonthly = hasLevelHistory
107 |   ? levelAcademicMonthly
108 |   : fallbackAcademicMonthly;
109 |
110 | const consistencyScore = useConsistencyScore(heatmapData);
111 | const { averages } = useBestDayOfWeek(heatmapData);
112 |
113 | // Correlations
114 | const { data: correlationResult, isLoading: correlationsLoading } =
115 |   useHabitCorrelations(studentId);
116 |
117 | // CSV export
118 | const { exportCSV } = useHabitExport({
119 |   studentId,
120 |   semesterRange: resolvedRange,
121 |   enabledWellnessHabits: enabledWellness,
122 |   levelHistory,
123 | });
124 |
125 | const isLoading = semesterLoading || heatmapLoading;
126 |
127 | return (
128 |   <div className="space-y-6">
129 |     { /* Page Header */ }
130 |     <SectionHeader
131 |       icon={BarChart3}
132 |       title="Habit Analytics"
133 |       action={
134 |         <Button
135 |           onClick={exportCSV}
136 |           disabled={isLoading}
137 |           variant="tactile"
138 |           className="gap-1"
139 |           data-testid="export-report-btn"
140 |         >
141 |           <Download className="h-4 w-4" />
142 |           Export Report
143 |         </Button>
144 |       }
145 |     />
146 |     <Link to="/student/habits" className="inline-flex">
147 |       <Button variant="outline" size="sm" className="gap-1">
148 |         <ArrowLeft className="h-4 w-4" />
149 |         Back
150 |       </Button>
151 |     </Link>
152 |
153 |     {isLoading ? (
154 |       <div className="space-y-6">
155 |         <Shimmer className="h-40 rounded-xl" />
156 |         <Shimmer className="h-64 rounded-xl" />
157 |         <Shimmer className="h-48 rounded-xl" />
158 |       </div>
159 |     ) : (
160 |       <>
161 |         { /* Consistency Score */ }
162 |         <PCard className="overflow-hidden gap-0 py-0">
163 |           <div className="p-6">
164 |             <SectionHeader icon={BarChart3} title="Consistency" />
165 |           </div>
166 |           <div className="flex justify-center px-6 pb-6">
167 |             <ConsistencyScoreRing
168 |               score={consistencyScore}
169 |               label="Consistency Score"
170 |             />
171 |           </div>
172 |         </PCard>
173 |
174 |         { /* Level Progression */ }
175 |         <PCard
176 |           className="overflow-hidden gap-0 py-0"
177 |           data-testid="level-progression-section"
178 |         >
179 |           <div className="p-6">
180 |             <SectionHeader icon={TrendingUp} title="Level Progression" />
181 |           </div>
182 |           <div className="p-6 pt-0">
183 |             <LevelProgressionChart
184 |               data={levelHistory}
185 |               currentLevel={currentLevel}
186 |             />
187 |           </div>
188 |         </PCard>
189 |
190 |         { /* Completion Rates */ }
191 |         <PCard className="overflow-hidden gap-0 py-0">
192 |           <div className="p-6">
193 |             <SectionHeader icon={BarChart3} title="Completion Rates" />
194 |           </div>
195 |           <div className="p-6 pt-0">
196 |             <HabitCompletionChart
197 |               weeklyData={weeklyData}
198 |               monthlyData={monthlyData}
199 |               academicOnlyWeeklyData={academicWeekly}

```

```

200 |         academicOnlyMonthlyData={academicMonthly}
201 |     />
202 | </div>
203 | </PCard>
204 |
205 | {/ * Best Day of Week */}
206 | <PCard className="overflow-hidden gap-0 py-0">
207 |   <div className="p-6">
208 |     <SectionHeader icon={BarChart3} title="Best Day of Week" />
209 |   </div>
210 |   <div className="p-6 pt-0">
211 |     <BestDayChart data={averages} />
212 |   </div>
213 | </PCard>
214 |
215 | {/ * Correlation Insights */}
216 | <PCard className="overflow-hidden gap-0 py-0">
217 |   <div className="p-6">
218 |     <SectionHeader icon={BarChart3} title="Insights" />
219 |   </div>
220 |   <div className="p-6 space-y-3">
221 |     {correlationsLoading ? (
222 |       <Shimmer className="h-24 rounded-xl" />
223 |     ) : correlationResult?.insufficientData ? (
224 |       <div
225 |         className="flex items-center gap-3 rounded-xl bg-blue-50 p-4"
226 |         data-testid="insufficient-data-message"
227 |       >
228 |         <Info className="h-5 w-5 text-blue-500 shrink-0" />
229 |         <p className="text-sm text-blue-700">
230 |           {correlationResult.daysUntilReady !== null
231 |             ? `Almost there – ${correlationResult.daysUntilReady} more days of data needed for insig
232 |               : "Keep tracking – insights appear after 2 weeks of data"}
233 |         </p>
234 |       </div>
235 |     ) : correlationResult?.insights &&
236 |       correlationResult.insights.length > 0 ? (
237 |       <>
238 |         <CorrelationDisclaimer />
239 |         <div
240 |           className="space-y-3"
241 |           data-testid="correlation-insights-list"
242 |         >
243 |           {correlationResult.insights.slice(0, 3).map((insight) => (
244 |             <CorrelationInsightCard
245 |               key={insight.id}
246 |               insight={insight}
247 |             />
248 |           ))}
249 |         </div>
250 |       </>
251 |     ) : (
252 |       <>
253 |         <CorrelationDisclaimer />
254 |         <p className="text-sm text-gray-500 text-center py-4">
255 |           No insights available yet
256 |         </p>
257 |       </>
258 |     )}
259 |   </div>
260 | </PCard>
261 | </>
262 | )}
263 | </div>
264 | );
265 | };
266 |
267 | // -----
268 | // Exported Page (wrapped in ErrorBoundary)
269 | // -----
270 |
271 | const HabitAnalyticsPage = () => (
272 |   <ErrorBoundary>
273 |     <HabitAnalyticsContent />
274 |   </ErrorBoundary>
275 | );
276 |
277 | export default HabitAnalyticsPage;
278 |

```

FILE: [src/pages/student/habits/HabitHeatmapPage.tsx](#)

TYPE: .tsx | LINES: 1-436 | SHA256: bd3b8e2640926111e12b12f62c37fa6cc160c650c62e5c5841b41319b1d6519a

```

1 | import { useCallback, useLayoutEffect, useMemo, useRef, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { BarChart3, Settings2 } from "lucide-react";
5 | import { Button } from "@components/ui/button";
6 | import ErrorBoundary from "@components/shared/ErrorBoundary";
7 | import HeatmapSummaryStats from "@components/shared/HeatmapSummaryStats";
8 | import HeatmapHabitSummary from "@components/shared/HeatmapHabitSummary";
9 | import HeatmapPlainSummary from "@components/shared/HeatmapPlainSummary";
10 | import HeatmapFilters from "@components/shared/HeatmapFilters";
11 | import HeatmapGrid from "@components/shared/HeatmapGrid";
12 | import HeatmapTooltip from "@components/shared/HeatmapTooltip";
13 | import HabitMobileBottomSheet from "@components/shared/HabitMobileBottomSheet";
14 | import WellnessHabitLogger from "@components/shared/WellnessHabitLogger";
15 | import WellnessTipCard from "@components/shared/WellnessTipCard";
16 | import WellnessSettingsPanel from "@components/shared/WellnessSettingsPanel";
17 | import { PCard, SectionHeader, Shimmer } from "@design-system";
18 | import { useAuth } from "@hooks/useAuth";
19 | import {
20 |   useHeatmapData,
21 |   useHeatmapSummary,

```

```

22 | useHeatmapXpByDate,
23 | } from "@hooks/useHeatmapData";
24 | import {
25 |   useWellnessPreferences,
26 |   useUpdateWellnessPreferences,
27 | } from "@hooks/useWellnessPreferences";
28 | import {
29 |   useWellnessHabitLogs,
30 |   useLogWellnessHabit,
31 | } from "@hooks/useWellnessHabits";
32 | import { useSemesterRange } from "@hooks/useSemesterRange";
33 | import {
34 |   computeHabitSummary,
35 |   PERFECT_DAY_XP,
36 |   ACADEMIC_HABITS_PER_DAY,
37 | } from "@lib/heatmapUtils";
38 | import {
39 |   useCurrentTip,
40 |   useDismissOnboardingTip,
41 | } from "@hooks/useWellnessTips";
42 | import {
43 |   useWellnessReminders,
44 |   useUpdateWellnessReminder,
45 | } from "@hooks/useWellnessReminders";
46 | import {
47 |   useWellnessGoals,
48 |   useDailyProgress,
49 |   useUpdateWellnessGoal,
50 | } from "@hooks/useWellnessGoals";
51 | import type {
52 |   DateRange,
53 |   WellnessHabitType,
54 |   WellnessTarget,
55 | } from "@types/habits";
56 |
57 | // -----
58 | // Wellness Tip Display (per-habit)
59 | // -----
60 |
61 | const WellnessHabitTip = ({
62 |   habitType,
63 |   studentId,
64 | }): {
65 |   habitType: WellnessHabitType;
66 |   studentId: string;
67 | } => {
68 |   const { tip, isOnboarding } = useCurrentTip(habitType, studentId);
69 |   const dismissMutation = useDismissOnboardingTip();
70 |
71 |   if (!tip) return null;
72 |
73 |   return (
74 |     <WellnessTipCard
75 |       tip={tip}
76 |       isOnboarding={isOnboarding}
77 |       onDismiss={
78 |         isOnboarding
79 |           ? () => dismissMutation.mutate({ studentId, habitType })
80 |           : undefined
81 |       }
82 |     />
83 |   );
84 | };
85 |
86 | // -----
87 | // Page Content (inside ErrorBoundary)
88 | // -----
89 |
90 | const HabitHeatmapContent = () => {
91 |   const { user } = useAuth();
92 |   const studentId = user?.id;
93 |
94 |   // Semester range resolution
95 |   const { data: semesterRange, isLoading: semesterLoading } =
96 |     useSemesterRange(studentId);
97 |
98 |   // URL-persisted filter
99 |   const [filter] = useQueryState("habit", parseAsString.withDefault("all"));
100 |
101 |   // Settings panel toggle
102 |   const [showSettings, setShowSettings] = useState(false);
103 |
104 |   // Today's date for wellness logging
105 |   const today = useMemo(() => {
106 |     const d = new Date();
107 |     return (
108 |       d.getFullYear() +
109 |       "." +
110 |       String(d.getMonth() + 1).padStart(2, "0") +
111 |       "-" +
112 |       String(d.getDate()).padStart(2, "0")
113 |     );
114 |   }, []);
115 |
116 |   // Data hooks
117 |   const resolvedRange: DateRange = semesterRange ?? { start: "", end: "" };
118 |   const { data: heatmapData, isLoading: heatmapLoading } = useHeatmapData(
119 |     studentId,
120 |     resolvedRange,
121 |     filter
122 |   );
123 |   const { data: summary, isLoading: summaryLoading } = useHeatmapSummary(
124 |     studentId,
125 |     heatmapData

```

```

126 | );
127 | const { data: xpByDate } = useHeatmapXpByDate(studentId, resolvedRange);
128 | const { data: preferences } = useWellnessPreferences(studentId);
129 | const { data: todayLogs } = useWellnessHabitLogs(studentId, today);
130 | const updatePreferences = useUpdateWellnessPreferences();
131 | const logWellnessHabit = useLogWellnessHabit();
132 |
133 | const enabledHabits = preferences?.enabledHabits ?? [];
134 | const parentVisibility = preferences?.parentVisibility ?? false;
135 |
136 | // Wellness reminders & goals
137 | const { data: reminders } = useWellnessReminders(studentId);
138 | const updateReminder = useUpdateWellnessReminder();
139 | const { data: goals } = useWellnessGoals(studentId);
140 | const dailyProgress = useDailyProgress(studentId, todayLogs ?? []);
141 | const updateGoal = useUpdateWellnessGoal();
142 |
143 | // Tooltip / bottom sheet state
144 | const [hoveredDate, setHoveredDate] = useState<string | null>(null);
145 | const [selectedDate, setSelectedDate] = useState<string | null>(null);
146 |
147 | // Card element used as the tooltip's positioning context (the tooltip is
148 | // placed next to the hovered cell instead of flowing below the grid).
149 | const cardRef = useRef<HTMLDivElement>(null);
150 | const [tooltipPos, setTooltipPos] = useState<{
151 |   left: number;
152 |   top: number;
153 | } | null>(null);
154 |
155 | // Stable callbacks keep the memoized HeatmapGrid from re-rendering on hover.
156 | const handleCellHover = useCallback(
157 |   (date: string | null) => setHoveredDate(date),
158 |   []
159 | );
160 | const handleCellClick = useCallback(
161 |   (date: string) => setSelectedDate(date),
162 |   []
163 | );
164 |
165 | // Position the tooltip above the hovered cell, relative to the card. Runs in
166 | // a layout effect so measurement happens after the cell is in the DOM and
167 | // before paint (no flicker). getBoundingClientRect reads are compositor-safe
168 | // here because they occur only on hover change, not during scroll.
169 | useLayoutEffect(() => {
170 |   const card = cardRef.current;
171 |   if (!hoveredDate || !card) {
172 |     setTooltipPos(null);
173 |     return;
174 |   }
175 |   const cell = card.querySelector<HTMLElement>(
176 |     `[data-testid="heatmap-cell-${hoveredDate}"]`
177 |   );
178 |   if (!cell) {
179 |     setTooltipPos(null);
180 |     return;
181 |   }
182 |   const cardRect = card.getBoundingClientRect();
183 |   const cellRect = cell.getBoundingClientRect();
184 |   setTooltipPos({
185 |     left: cellRect.left - cardRect.left + cellRect.width / 2,
186 |     top: cellRect.top - cardRect.top,
187 |   });
188 | }, [hoveredDate]);
189 |
190 | const hoveredDay = useMemo(
191 |   () => heatmapData?.find((d) => d.date === hoveredDate) ?? null,
192 |   [heatmapData, hoveredDate]
193 | );
194 |
195 | const selectedDay = useMemo(
196 |   () => heatmapData?.find((d) => d.date === selectedDate) ?? null,
197 |   [heatmapData, selectedDate]
198 | );
199 |
200 | // Best-habit + completion-rate summary across the visible period (R7.2)
201 | const habitSummary = useMemo(
202 |   () => computeHabitSummary(heatmapData ?? []),
203 |   [heatmapData]
204 | );
205 |
206 | // Per-day recorded habit XP (R7.1, R7.4) and Perfect Day detection (R7.3)
207 | const hoveredXp = hoveredDate ? xpByDate?.[hoveredDate] ?? 0 : 0;
208 | const selectedXp = selectedDate ? xpByDate?.[selectedDate] ?? 0 : 0;
209 | const hoveredIsPerfectDay =
210 |   (hoveredDay?.academicCount ?? 0) >= ACADEMIC_HABITS_PER_DAY;
211 | const selectedIsPerfectDay =
212 |   (selectedDay?.academicCount ?? 0) >= ACADEMIC_HABITS_PER_DAY;
213 |
214 | // Handlers
215 | const handleToggleHabit = (type: WellnessHabitType, enabled: boolean) => {
216 |   if (!studentId) return;
217 |   const next = enabled
218 |     ? [...enabledHabits, type]
219 |     : enabledHabits.filter((h) => h !== type);
220 |   updatePreferences.mutate({
221 |     studentId,
222 |     enabledHabits: next,
223 |     parentVisibility,
224 |   });
225 | };
226 |
227 | const handleToggleParentVisibility = (visible: boolean) => {
228 |   if (!studentId) return;
229 |   updatePreferences.mutate({

```

```

230 |         studentId,
231 |         enabledHabits,
232 |         parentVisibility: visible,
233 |     });
234 | };
235 |
236 | const handleLogWellness = (type: WellnessHabitType, value?: number) => {
237 |     if (!studentId) return;
238 |     logWellnessHabit.mutate({
239 |         studentId,
240 |         wellnessType: type,
241 |         value: value ?? null,
242 |         date: today,
243 |     });
244 | };
245 |
246 | const handleReminderToggle = (
247 |     habitType: WellnessHabitType,
248 |     enabled: boolean
249 | ) => {
250 |     if (!studentId) return;
251 |     updateReminder.mutate({
252 |         studentId,
253 |         habitType,
254 |         reminderTime: enabled ? "09:00" : null,
255 |     });
256 | };
257 |
258 | const handleReminderTimeChange = (
259 |     habitType: WellnessHabitType,
260 |     time: string
261 | ) => {
262 |     if (!studentId) return;
263 |     updateReminder.mutate({ studentId, habitType, reminderTime: time || null });
264 | };
265 |
266 | const handleGoalSave = (target: WellnessTarget) => {
267 |     if (!studentId) return;
268 |     updateGoal.mutate({
269 |         studentId,
270 |         habitType: target.habitType,
271 |         targetValue: target.targetValue,
272 |         unit: target.unit,
273 |     });
274 | };
275 |
276 | const isLoading = semesterLoading || heatmapLoading;
277 |
278 | return (
279 |     <div className="space-y-6">
280 |         {/* Page Header */}
281 |         <SectionHeader
282 |             icon={BarChart3}
283 |             title="Habit Tracker"
284 |             action={
285 |                 <div className="flex items-center gap-2">
286 |                     <Button
287 |                         variant="outline"
288 |                         size="sm"
289 |                         onClick={() => setShowSettings((s) => !s)}
290 |                         className="gap-1"
291 |                     >
292 |                         <Settings2 className="h-4 w-4" />
293 |                         Settings
294 |                     </Button>
295 |                     <Link to="/student/habits/analytics">
296 |                         <Button variant="tactile" className="gap-1">
297 |                             <BarChart3 className="h-4 w-4" />
298 |                             Analytics
299 |                         </Button>
300 |                     </Link>
301 |                 </div>
302 |             }
303 |         </div>
304 |
305 |         {/* Summary Stats */}
306 |         {summaryLoading ? (
307 |             <div className="grid grid-cols-3 gap-4">
308 |                 {Array.from({ length: 3 }).map((_, i) => (
309 |                     <Shimmer key={i} className="h-24 rounded-xl" />
310 |                 ))}
311 |             </div>
312 |         ) : summary ? (
313 |             <HeatmapSummaryStats
314 |                 currentStreak={summary.currentStreak}
315 |                 longestStreak={summary.longestStreak}
316 |                 totalActiveDays={summary.totalActiveDays}
317 |             />
318 |         ) : null}
319 |
320 |         {/* Best-habit + completion-rate summary */}
321 |         {!summaryLoading && heatmapData ? (
322 |             <HeatmapHabitSummary summary={habitSummary} />
323 |         ) : null}
324 |
325 |         {/* Plain-language summary for younger students (R22.1) */}
326 |         {!summaryLoading && heatmapData ? (
327 |             <HeatmapPlainSummary
328 |                 summary={habitSummary}
329 |                 currentStreak={summary?.currentStreak ?? 0}
330 |             />
331 |         ) : null}
332 |
333 |         {/* Filters */}

```

```

334 | <HeatmapFilters enabledWellnessHabits={enabledHabits} />
335 |
336 | {/* Heatmap Grid */}
337 | {isLoading ? (
338 |   <Shimmer className="h-48 rounded-xl" />
339 | ) : resolvedRange.start && resolvedRange.end ? (
340 |   <div ref={cardRef} className="relative">
341 |     <PCard className="p-4">
342 |       <HeatmapGrid
343 |         data={heatmapData ?? []}
344 |         semesterRange={resolvedRange}
345 |         onCellClick={handleCellClick}
346 |         onCellHover={handleCellHover}
347 |       />
348 |     </PCard>
349 |     {/* Hover tooltip - positioned above the hovered cell (desktop/pointer
350 |      only; touch uses the bottom sheet). pointer-events-none so it
351 |      never steals the hover it depends on. */}
352 |     {hoveredDay && hoveredDate && tooltipPos && (
353 |       <div
354 |         className="pointer-events-none absolute z-50 hidden md:block"
355 |         style={{
356 |           left: tooltipPos.left,
357 |           top: tooltipPos.top,
358 |           transform: "translate(-50%, calc(-100% - 10px))",
359 |         }}
360 |       >
361 |         <HeatmapTooltip
362 |           date={hoveredDay.date}
363 |           habits={hoveredDay.habits}
364 |           xpEarned={hoveredXp}
365 |           streakActive={hoveredDay.academicCount > 0}
366 |           isPerfectDay={hoveredIsPerfectDay}
367 |           perfectDayXp={PERFECT_DAY_XP}
368 |         />
369 |       </div>
370 |     )}
371 |   </div>
372 | ) : null}
373 |
374 | {/* Mobile Bottom Sheet */}
375 | <HabitMobileBottomSheet
376 |   date={selectedDay?.date ?? ""}
377 |   habits={selectedDay?.habits ?? []}
378 |   xpEarned={selectedXp}
379 |   streakActive={selectedDay ? selectedDay.academicCount > 0 : false}
380 |   isPerfectDay={selectedIsPerfectDay}
381 |   perfectDayXp={PERFECT_DAY_XP}
382 |   open={!!selectedDate}
383 |   onClose={() => setSelectedDate(null)}
384 | />
385 |
386 | {/* Wellness Section */}
387 | {enabledHabits.length > 0 && (
388 |   <div className="space-y-3">
389 |     {/* Wellness Tips */}
390 |     {studentId &&
391 |       enabledHabits.map((ht) => (
392 |         <WellnessHabitTip key={ht} habitType={ht} studentId={studentId} />
393 |       ))}
394 |
395 |     <WellnessHabitLogger
396 |       enabledHabits={enabledHabits}
397 |       todayLogs={todayLogs ?? []}
398 |       onLog={handleLogWellness}
399 |       dailyProgress={dailyProgress}
400 |     />
401 |   </div>
402 | )}
403 |
404 | {/* Settings Panel (collapsible) */}
405 | {showSettings && (
406 |   <PCard className="p-4">
407 |     <WellnessSettingsPanel
408 |       enabledHabits={enabledHabits}
409 |       parentVisibility={parentVisibility}
410 |       onToggleHabit={handleToggleHabit}
411 |       onToggleParentVisibility={handleToggleParentVisibility}
412 |       reminders={reminders}
413 |       onReminderToggle={handleReminderToggle}
414 |       onReminderTimeChange={handleReminderTimeChange}
415 |       goals={goals}
416 |       goalProgress={dailyProgress}
417 |       onGoalSave={handleGoalSave}
418 |     />
419 |   </PCard>
420 | )}
421 | </div>
422 | );
423 | };
424 |
425 | // -----
426 | // Exported Page (wrapped in ErrorBoundary)
427 | // -----
428 |
429 | const HabitHeatmapPage = () => (
430 |   <ErrorBoundary>
431 |     <HabitHeatmapContent />
432 |   </ErrorBoundary>
433 | );
434 |
435 | export default HabitHeatmapPage;
436 |

```

TYPE: .tsx | LINES: 1-449 | SHA256: 8c5a301acd01a71bfb68beeab6439ed9e6184338e34ca44fe4a3431d4ca7d926

[illegible]

[illegible]

```

206 | const generatedPrompt = useMemo(() : GeneratedJournalPrompt | null => {
207 |   if (!watchedCLOid || promptDismissed) return null;
208 |   const selectedCLO = clos.find((c) => c.id === watchedCLOid);
209 |   if (!selectedCLO || !selectedCLO.blooms_level) return null;
210 |
211 |   return generateJournalPrompt({
212 |     cloTitle: selectedCLO.title,
213 |     bloomsLevel: selectedCLO.blooms_level,
214 |     attainmentLevel: "Developing", // Default – real attainment would come from outcome_attainment
215 |   });
216 | }, [watchedCLOid, clos, promptDismissed]);
217 |
218 | // Reset prompt dismissed state when CLO changes
219 | useEffect(() => {
220 |   setPromptDismissed(false);
221 | }, [watchedCLOid]);
222 |
223 | // Submit handler
224 | const onSubmit = (data: JournalFormData) => {
225 |   if (isEditMode) {
226 |     updateMutation.mutate(
227 |       {
228 |         id: id!,
229 |         content: data.content,
230 |         is_shared: data.is_shared,
231 |         clo_id: data.clo_id || undefined,
232 |       },
233 |       {
234 |         onSuccess: () => {
235 |           draftManager.clearDraft(draftKey);
236 |           toast.success("Journal entry updated");
237 |           navigate("/student/journal");
238 |         },
239 |         onError: (err) => toast.error(err.message),
240 |       }
241 |     );
242 |   } else {
243 |     createMutation.mutate(
244 |       {
245 |         course_id: data.course_id,
246 |         content: data.content,
247 |         is_shared: data.is_shared,
248 |         clo_id: data.clo_id || undefined,
249 |       },
250 |       {
251 |         onSuccess: () => {
252 |           draftManager.clearDraft(draftKey);
253 |           // Log activity for journal entry
254 |           if (userId) {
255 |             logActivity({
256 |               student_id: userId,
257 |               event_type: "journal",
258 |               metadata: { course_id: data.course_id },
259 |             });
260 |           }
261 |           toast.success("Journal entry saved");
262 |           navigate("/student/journal");
263 |         },
264 |         onError: (err) => toast.error(err.message),
265 |       }
266 |     );
267 |   }
268 | };
269 |
270 | const isPending = createMutation.isPending || updateMutation.isPending;
271 | const isLoading = isLoadingEntry || isLoadingCourses;
272 |
273 | if (isLoading) {
274 |   return (
275 |     <div className="space-y-6">
276 |       <Shimmer className="h-10 w-48 rounded-xl" />
277 |       <Shimmer className="h-64 rounded-xl" />
278 |     </div>
279 |   );
280 | }
281 |
282 | return (
283 |   <div className="space-y-6 max-w-3xl">
284 |     <div className="flex items-center gap-3">
285 |       <Button
286 |         variant="ghost"
287 |         size="sm"
288 |         onClick={() => navigate("/student/journal")}
289 |         className="text-gray-500 hover:text-gray-700"
290 |       >
291 |         <ArrowLeft className="h-4 w-4" />
292 |       </Button>
293 |       <SectionHeader
294 |         icon={BookOpen}
295 |         title={isEditMode ? "Edit Entry" : "New Journal Entry"}
296 |       />
297 |     </div>
298 |
299 |     <div>
300 |       <div>
301 |         <div>
302 |           <div>
303 |             <div>
304 |               <div>
305 |                 <div>
306 |                   <div>
307 |                     <div>
308 |                       <div>
309 |

```

```

310 | <div className="p-6">
311 |   <Form {...form}>
312 |     <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
313 |       {/* Course Selector */}
314 |       <FormField
315 |         control={form.control}
316 |         name="course_id"
317 |         render={({ field }) => (
318 |           <FormItem>
319 |             <FormLabel>Course</FormLabel>
320 |             <FormControl>
321 |               <Select
322 |                 value={field.value}
323 |                 onChange={field.onChange}
324 |                 disabled={isEditMode}
325 |               >
326 |                 <SelectTrigger className="w-full bg-white">
327 |                   <SelectValue placeholder="Select a course" />
328 |                 </SelectTrigger>
329 |                 <SelectContent>
330 |                   {courses.map((c) => (
331 |                     <SelectItem key={c.id} value={c.id}>
332 |                       {c.name}
333 |                     </SelectItem>
334 |                   ))}
335 |                 </SelectContent>
336 |               </Select>
337 |             </FormControl>
338 |             <FormMessage />
339 |           </FormItem>
340 |         )}
341 |       />
342 |
343 |       {/* CLO Selector (optional) */}
344 |       {watchedCourseId && (
345 |         <FormField
346 |           control={form.control}
347 |           name="clo_id"
348 |           render={({ field }) => (
349 |             <FormItem>
350 |               <FormLabel>Learning Outcome (optional)</FormLabel>
351 |               <FormControl>
352 |                 <Select
353 |                   value={field.value ?? ""}
354 |                   onChange={(v) =>
355 |                     field.onChange(v === "__none__" ? "" : v)
356 |                   }
357 |                 >
358 |                   <SelectTrigger className="w-full bg-white">
359 |                     <SelectValue placeholder="Select a CLO for guided prompts" />
360 |                   </SelectTrigger>
361 |                   <SelectContent>
362 |                     <SelectItem value="__none__">None</SelectItem>
363 |                     {isLoadingCLOs ? (
364 |                       <SelectItem value="__loading__" disabled>
365 |                         Loading...
366 |                       </SelectItem>
367 |                     ) : (
368 |                       clos.map((clo) => (
369 |                         <SelectItem key={clo.id} value={clo.id}>
370 |                           {clo.title}
371 |                         </SelectItem>
372 |                       ))
373 |                     )}
374 |                   </SelectContent>
375 |                 </Select>
376 |               </FormControl>
377 |               <FormMessage />
378 |             </FormItem>
379 |           )}
380 |         </Form>
381 |       )}
382 |
383 |       {/* Content Textarea */}
384 |       <FormField
385 |         control={form.control}
386 |         name="content"
387 |         render={({ field }) => (
388 |           <FormItem>
389 |             <FormLabel>Your Reflection</FormLabel>
390 |             <FormControl>
391 |               <Textarea
392 |                 {...field}
393 |                 placeholder="Write your reflection here..."
394 |                 rows={10}
395 |                 className="resize-y"
396 |               />
397 |             </FormControl>
398 |             <div className="flex items-center justify-between">
399 |               <FormMessage />
400 |               <div className="flex items-center gap-3 text-xs text-gray-400">
401 |                 <span>{charCount} characters</span>
402 |                 <span>.</span>
403 |                 <span data-testid="word-count">{wordCount} words</span>
404 |               </div>
405 |             </div>
406 |           </FormItem>
407 |         )}
408 |       />
409 |
410 |       {/* Share Toggle */}
411 |       <FormField
412 |         control={form.control}
413 |         name="is_shared"

```

```

414 render={({ field }) => (
415   <FormItem>
416     <div className="flex items-center gap-3">
417       <FormControl>
418         <Switch
419           checked={field.value}
420           onChange={field.onChange}
421           aria-label="Share with teacher"
422         />
423       </FormControl>
424       <Label className="flex items-center gap-2 text-sm font-medium cursor-pointer">
425         <Share2 className="h-4 w-4 text-gray-500" />
426         Share with teacher
427       </Label>
428     </div>
429     <FormMessage />
430   </FormItem>
431 )}
432 />
433
434 {/* Submit */}
435 <Button type="submit" disabled={isPending} variant="tactile">
436   {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
437   <PenLine className="h-4 w-4" />
438   {isEditMode ? "Update Entry" : "Save Entry"}
439 </Button>
440 </Form>
441 </Form>
442 </div>
443 </PCard>
444 </div>
445 );
446 };
447
448 export default JournalEditor;
449

```

FILE: src/pages/student/journal/JournalListPage.tsx

```
TYPE: .tsx | LINES: 1-193 | SHA256: 18a902615316f879454ac43e5473cdc4121ea16b0c98109bd8f56dedef879999
```

[illegible]

[illegible]

```

169 |         <p className="text-sm text-gray-500">
170 |             No journal entries yet. Start reflecting on your learning!
171 |         </p>
172 |     </div>
173 | </PCard>
174 | ) : (
175 |     <div className="space-y-3">
176 |         {entries.map((entry) => (
177 |             <EntryCard
178 |                 key={entry.id}
179 |                 entry={entry}
180 |                 courseName={
181 |                     courseNameMap.get(entry.course_id) ?? "Unknown Course"
182 |                 }
183 |                 onClick={() => navigate(`/student/journal/${entry.id}`)}
184 |             </>
185 |         ))}
186 |     </div>
187 | )}
188 | </div>
189 | );
190 | };
191 |
192 | export default JournalListPage;
193 |

```

FILE: [src/pages/student/journal/StudentJournalNew.tsx](#)

TYPE: .tsx | LINES: 1-548 | SHA256: 3b4714b004abe58669f9e567535383298b83e3fb52be8575be5199832bd0b818

```

1  // =====
2  // StudentJournalNew - redesigned learning journal (P3, spec task 3.1)
3  // =====
4  //
5  // List + create-dialog archetype gated behind `newUiModules` (see the wrapper
6  // in StudentJournalPage.tsx). REUSES every existing hook, the create-entry
7  // mutation, the CLO-contextual guided-prompt generation, the reflection-prompt
8  // templates, and the word-count / XP-eligibility logic VERBATIM (R10.1-R10.3a).
9  // Only presentation changes: the CTA + save buttons use the tactile Button
10 // variant and entry cards use `.card-elevated`. i18n reuses the exact `student`
11 // namespace `journal.*` keys. Flag-off keeps the legacy page byte-identical.
12 // =====
13
14 import { useMemo, useState } from "react";
15 import { useTranslation } from "react-i18next";
16 import {
17     BookOpen,
18     CalendarDays,
19     Check,
20     Flame,
21     Lightbulb,
22     PenLine,
23     Plus,
24     Sparkles,
25 } from "lucide-react";
26 import { Link } from "react-router-dom";
27
28 import { Button } from "@components/ui/button";
29 import { Badge } from "@components/ui/badge";
30 import {
31     Dialog,
32     DialogContent,
33     DialogDescription,
34     DialogHeader,
35     DialogTitle,
36     DialogTrigger,
37     DialogFooter,
38 } from "@components/ui/dialog";
39 import {
40     Select,
41     SelectContent,
42     SelectItem,
43     SelectTrigger,
44     SelectValue,
45 } from "@components/ui/select";
46 import { Textarea } from "@components/ui/textarea";
47 import { Label } from "@components/ui/label";
48 import { KPICard, PCard, Shimmer } from "@design-system";
49 import EmptyState from "@components/shared/EmptyState";
50 import { useAuth } from "@hooks/useAuth";
51 import { useJournalEntries, useCreateJournalEntry } from "@hooks/useJournal";
52 import { useJournalCourseOptions } from "@hooks/useJournalCourseOptions";
53 import { useCLOs } from "@hooks/useCLOs";
54 import {
55     generateJournalPrompt,
56     type GeneratedJournalPrompt,
57 } from "@lib/journalPromptGenerator";
58 import {
59     REFLECTION_PROMPT_TEMPLATES,
60     seedContentWithPrompt,
61 } from "@lib/reflectionPrompts";
62 import { getJournalInsights } from "@lib/journalInsights";
63 import { toast } from "sonner";
64
65 /**
66  * Builds the seed text for a CLO-contextual guided prompt: the intro followed
67  * by the Kolb reflection questions as scaffolding.
68  */
69 const buildGuidedSeed = (prompt: GeneratedJournalPrompt): string => {
70     const questions = prompt.questions.map((q) => `• ${q.question}`).join("\n");
71     return `${prompt.promptText}\n\n${questions}`;
72 };
73
74 const StudentJournalNew = () => {
75     const { t, i18n } = useTranslation("student");

```

```

76 | const { user } = useAuth();
77 | const studentId = user?.id;
78 |
79 | const [isCreating, setIsCreating] = useState(false);
80 | const [selectedCourse, setSelectedCourse] = useState<string>("");
81 | const [content, setContent] = useState("");
82 |
83 | const { data: entries, isLoading: entriesLoading } = useJournalEntries();
84 | const { data: courses } = useJournalCourseOptions(studentId);
85 | const createEntry = useCreateJournalEntry();
86 |
87 | // CLOs for the selected course drive the existing CLO-contextual prompt
88 | // generator. Matches the pattern used in JournalEditor.
89 | const { data: closData } = useCLOs(selectedCourse || undefined);
90 | const clos = useMemo(() => closData?.data ?? [], [closData]);
91 |
92 | // Build a guided, CLO-contextual prompt when context is available. When no
93 | // course/CLO context exists – or the generator is otherwise unavailable –
94 | // this is null and the page falls back to the static templates + free-text
95 | // (basic unguided journal), so journaling always remains possible (R10.3a).
96 | const guidedPrompt = useMemo(() : GeneratedJournalPrompt | null => {
97 |   if (!selectedCourse) return null;
98 |   const cloWithBlooms = clos.find((c) => c.blooms_level);
99 |   if (!cloWithBlooms || !cloWithBlooms.blooms_level) return null;
100 |   try {
101 |     return generateJournalPrompt({
102 |       cloTitle: cloWithBlooms.title,
103 |       bloomsLevel: cloWithBlooms.blooms_level,
104 |       // Real attainment would come from outcome_attainment; "Developing"
105 |       // is a neutral default that yields the full set of reflection stages.
106 |       attainmentLevel: "Developing",
107 |     });
108 |   } catch {
109 |     // Generator unavailable – fall back to the unguided journal (R10.3a).
110 |     return null;
111 |   }
112 | }, [selectedCourse, clos]);
113 |
114 | const wordCount = content.trim().split(/\s+/).filter(Boolean).length;
115 |
116 | const courseLookup = new Map((courses ?? []).map((c) => [c.id, c]));
117 | const insights = useMemo(() => getJournalInsights(entries ?? [], [entries]));
118 | const dailyPrompt = t(
119 |   REFLECTION_PROMPT_TEMPLATES[
120 |     new Date().getUTCDate() % REFLECTION_PROMPT_TEMPLATES.length
121 |   ].i18nKey
122 | );
123 | const formatEntryDate = (
124 |   date: string | Date,
125 |   options?: Intl.DateTimeFormatOptions
126 | ) =>
127 |   new Intl.DateTimeFormat(i18n.language, {
128 |     day: "numeric",
129 |     month: "short",
130 |     year: "numeric",
131 |     ...options,
132 |   }).format(new Date(date));
133 |
134 | const handleSelectTemplate = (promptText: string) => {
135 |   setContent((prev) => seedContentWithPrompt(prev, promptText));
136 | };
137 |
138 | const handleSubmit = async () => {
139 |   if (!selectedCourse || content.trim().length === 0) return;
140 |   try {
141 |     await createEntry.mutateAsync({
142 |       course_id: selectedCourse,
143 |       content: content.trim(),
144 |     });
145 |     toast.success(t("journal.created", "Journal entry saved"));
146 |     setContent("");
147 |     setSelectedCourse("");
148 |     setIsCreating(false);
149 |   } catch (err) {
150 |     const message =
151 |       err instanceof Error ? err.message : "Failed to save entry";
152 |     toast.error(message);
153 |   }
154 | };
155 |
156 | return (
157 |   <div className="space-y-6">
158 |     <div className="flex items-center justify-between gap-4">
159 |       <div>
160 |         <h1 className="text-2xl font-bold tracking-tight">
161 |           {t("journal.title", "Learning Journal")}
162 |         </h1>
163 |         <p className="mt-1 text-sm text-gray-500">
164 |           {t(
165 |             "journal.subtitle",
166 |             "Reflect on what you've learned. Earn 20 XP per entry of 50+ words."
167 |           )}
168 |         </p>
169 |       </div>
170 |       <Dialog open={isCreating} onOpenChange={setIsCreating}>
171 |         <DialogTrigger asChild>
172 |           <Button variant="tactile">
173 |             <Plus className="h-4 w-4" />
174 |             {t("journal.newEntry", "New Entry")}
175 |           </Button>
176 |         </DialogTrigger>
177 |         <DialogContent className="max-h-[90vh] overflow-y-auto">
178 |           <DialogHeader>
179 |             <DialogTitle>

```

```

180     {t("journal.dialog.title", "New Journal Entry")}
181   </DialogTitle>
182   <DialogDescription>
183     {t(
184       "journal.dialog.description",
185       "Reflect on a recent class, assignment, or concept."
186     )}
187   </DialogDescription>
188 </DialogHeader>
189 <div className="space-y-4">
190   <div className="space-y-2">
191     <Label htmlFor="course">
192       {t("journal.dialog.course", "Course")}
193     </Label>
194     <Select
195       value={selectedCourse}
196       onValueChange={setSelectedCourse}
197     >
198       <SelectTrigger id="course">
199         <SelectValue
200           placeholder={t(
201             "journal.dialog.selectCourse",
202             "Select a course"
203           )}
204         />
205       </SelectTrigger>
206       <SelectContent>
207         {(courses ?? []).map((c) => (
208           <SelectItem key={c.id} value={c.id}>
209             {c.code} – {c.name}
210           </SelectItem>
211         ))}
212       </SelectContent>
213     </Select>
214   </div>
215
216   {/* Reflection prompt templates – always available so the journal
217    is guided rather than a bare textbox (R10.1, R10.2). */}
218   <div className="space-y-2">
219     <Label>
220       {t("journal.prompts.title", "Reflection prompts")}
221     </Label>
222     <p className="text-xs text-gray-500">
223       {t(
224         "journal.prompts.hint",
225         "Pick a prompt to get started, or just write freely below."
226       )}
227     </p>
228     <div className="flex flex-wrap gap-2">
229       {REFLECTION_PROMPT_TEMPLATES.map((template) => {
230         const promptText = t(template.i18nKey);
231         return (
232           <Button
233             key={template.id}
234             type="button"
235             variant="outline"
236             size="sm"
237             className="rounded-full"
238             onClick={() => handleSelectTemplate(promptText)}
239           >
240             <Lightbulb className="me-1.5 h-3.5 w-3.5 text-amber-500" />
241             {promptText}
242           </Button>
243         );
244       })}
245     </div>
246
247     {/* CLO-contextual guided prompt from the existing generator,
248      shown only when course/CLO context is available (R10.3). */}
249     {guidedPrompt && (
250       <div className="space-y-2 rounded-lg border border-teal-200 bg-teal-50 p-3">
251         <div className="flex items-center justify-between gap-2">
252           <p className="text-xs font-bold uppercase tracking-wide text-teal-700">
253             {t("journal.prompts.guided", "Guided reflection")}
254           </p>
255           <Button
256             type="button"
257             variant="ghost"
258             size="sm"
259             className="h-7 text-teal-700 hover:bg-teal-100"
260             onClick={() =>
261               handleSelectTemplate(buildGuidedSeed(guidedPrompt))
262             }
263           >
264             {t("journal.prompts.use", "Use this prompt")}
265           </Button>
266         </div>
267         <p className="text-sm leading-relaxed text-gray-700">
268           {guidedPrompt.promptText}
269         </p>
270       </div>
271     )}
272 </div>
273
274 <div className="space-y-2">
275   <Label htmlFor="content">
276     {t("journal.dialog.content", "Reflection")}
277   </Label>
278   <Textarea
279     id="content"
280     value={content}
281     onChange={(e) => setContent(e.target.value)}
282     rows={8}
283     placeholder={t(

```



```

284         "journal.dialog.placeholder",
285         "What did you learn? What was challenging? What questions do you have?"
286     )}
287 />
288 <p className="text-xs text-gray-500">
289     {wordCount} {t("journal.dialog.words", "words")}
290     {wordCount >= 50 && (
291         <span className="ms-2 font-semibold text-green-600">
292             {t("journal.dialog.xpEarned", "+20 XP eligible")}
293         </span>
294     )}
295 </p>
296 </div>
297 </div>
298 <DialogFooter>
299     <Button
300         variant="outline"
301         onClick={() => setIsCreating(false)}
302         disabled={createEntry.isPending}
303     >
304         {t("common.cancel", "Cancel")}
305     </Button>
306     <Button
307         variant="tactile"
308         onClick={handleSubmit}
309         disabled={
310             !selectedCourse ||
311             content.trim().length === 0 ||
312             createEntry.isPending
313         }
314     >
315         {createEntry.isPending
316             ? t("common.saving", "Saving...")
317             : t("common.save", "Save")}
318     </Button>
319 </DialogFooter>
320 </DialogContent>
321 </Dialog>
322 </div>
323
324 <PCard className="p-5 sm:p-6">
325     <div className="flex flex-col justify-between gap-5 sm:flex-row sm:items-start">
326         <div className="flex gap-3">
327             <div className="flex size-10 shrink-0 items-center justify-center rounded-xl bg-blue-50 text-blue-
328                 <PenLine className="size-5" aria-hidden="true" />
329             </div>
330             <div>
331                 <h2 className="text-base font-black tracking-tight text-slate-900">
332                     {t("journal.today.title")}
333                 </h2>
334                 <p className="mt-1 max-w-xl text-sm leading-relaxed text-slate-500">
335                     {t("journal.today.description")}
336                 </p>
337             </div>
338         </div>
339         <Button variant="tactile" onClick={() => setIsCreating(true)}>
340             <PenLine className="size-4" />
341             {t("journal.today.cta")}
342         </Button>
343     </div>
344 </PCard>
345
346 {entriesLoading ? (
347     <div className="space-y-4">
348         <Shimmer className="h-72 rounded-[20px]" />
349         <Shimmer className="h-52 rounded-[20px]" />
350     </div>
351 ) : (
352     <>
353         <PCard className="p-5 sm:p-6">
354             <div className="flex flex-wrap items-center justify-between gap-3">
355                 <div className="flex items-center gap-2">
356                     <span className="flex size-8 items-center justify-center rounded-lg bg-violet-50 text-violet-6
357                         <BookOpen className="size-4" aria-hidden="true" />
358                     </span>
359                     <h2 className="text-base font-black tracking-tight text-slate-900">
360                         {t("journal.journey.title")}
361                     </h2>
362                 </div>
363                 <Badge
364                     variant="outline"
365                     className="rounded-lg px-2.5 py-1 text-xs text-slate-500"
366                 >
367                     {t("journal.journey.thisWeek")}
368                 </Badge>
369             </div>
370
371             <div className="mt-5 grid grid-cols-2 gap-3 lg:grid-cols-4">
372                 <KPICard
373                     icon={BookOpen}
374                     label={t("journal.journey.entriesThisWeek")}
375                     value={insights.entriesThisWeek}
376                     iconBgClass="bg-teal-50"
377                     iconColorClass="text-teal-600"
378                     valueClassname="text-slate-900"
379                 />
380                 <KPICard
381                     icon={Flame}
382                     label={t("journal.journey.dayStreak")}
383                     value={insights.streak}
384                     iconBgClass="bg-orange-50"
385                     iconColorClass="text-orange-600"
386                     valueClassname="text-slate-900"
387                 />

```

```

388     <KPICard
389       icon={Sparkles}
390       label={t("journal.journey.substantive")}
391       value={insights.substantiveThisWeek}
392       iconBgClass="bg-amber-50"
393       iconColorClass="text-amber-600"
394       valueClassName="text-slate-900"
395     />
396     <KPICard
397       icon={CalendarDays}
398       label={t("journal.journey.totalEntries")}
399       value={insights.totalEntries}
400       iconBgClass="bg-blue-50"
401       iconColorClass="text-blue-600"
402       valueClassName="text-slate-900"
403     />
404   </div>
405
406   <div className="mt-6 border-t border-slate-100 pt-5">
407     <div className="flex flex-wrap items-center justify-between gap-2">
408       <p className="text-sm font-bold text-slate-700">
409         {t("journal.journey.weeklyStreak")}
410       </p>
411       <span className="text-xs font-semibold text-teal-700">
412         {t("journal.journey.daysOfWeek", {
413           count: insights.days.filter((day) => day.hasEntry).length,
414         })}
415       </span>
416     </div>
417     <ol
418       className="mt-4 grid grid-cols-7 gap-1.5"
419       aria-label={t("journal.journey.weeklyStreak")}
420     >
421       {insights.days.map((day) => {
422         const isToday =
423           day.date.toISOString().slice(0, 10) ===
424             new Date().toISOString().slice(0, 10);
425         return (
426           <li
427             key={day.date.toISOString()}
428             className="flex flex-col items-center gap-1.5"
429           >
430             <span
431               className={
432                 day.hasEntry
433                   ? "flex size-8 items-center justify-center rounded-[10px] bg-teal-600 text-white"
434                   : isToday
435                     ? "flex size-8 items-center justify-center rounded-[10px] border-2 border-dashed b
436                       : "flex size-8 items-center justify-center rounded-[10px] bg-slate-100 text-slate-
437                 }
438               aria-label={formatEntryDate(day.date, {
439                 weekday: "long",
440               })}
441             >
442               {day.hasEntry ? (
443                 <Check className="size-4" aria-hidden="true" />
444               ) : (
445                 ".,."
446               )}
447             </span>
448             <span className="text-[11px] font-bold text-slate-500">
449               {formatEntryDate(day.date, { weekday: "narrow" })}
450             </span>
451           </li>
452         );
453       })}
454     </ol>
455   </div>
456 </PCard>
457
458 <div className="flex items-center gap-3 rounded-2xl border border-teal-200 bg-gradient-to-r from-tea
459 <Lightbulb
460   className="size-5 shrink-0 text-teal-700"
461   aria-hidden="true"
462 />
463 <p className="text-sm text-slate-600">
464   <span className="font-semibold">
465     {t("journal.dailyPrompt.label")}
466   </span>{" "}
467   <span className="font-bold text-slate-800">{dailyPrompt}</span>
468 </p>
469 </div>
470
471 <PCard className="p-5 sm:p-6">
472   <div className="flex items-center justify-between gap-3">
473     <div className="flex items-center gap-2">
474       <span className="flex size-8 items-center justify-center rounded-lg bg-blue-50 text-blue-600">
475         <CalendarDays className="size-4" aria-hidden="true" />
476       </span>
477       <h2 className="text-base font-black tracking-tight text-slate-900">
478         {t("journal.pastEntries")}
479       </h2>
480     </div>
481     <span className="text-xs font-semibold text-slate-500">
482       {t("journal.entryCount", { count: insights.totalEntries })}
483     </span>
484   </div>
485
486   {!entries || entries.length === 0 ? (
487     <div className="pt-5">
488       <EmptyState
489         icon={<PenLine className="h-12 w-12 text-gray-400" />}
490         title={t("journal.empty.title", "No journal entries yet")}
491         description={t("journal.empty.description")}

```

```

492 |         />
493 |     </div>
494 | ) : (
495 |   <ol className="mt-5 space-y-4">
496 |     {entries.map((entry, index) => {
497 |       const course = courseLookup.get(entry.course_id);
498 |       return (
499 |         <li key={entry.id} className="relative flex gap-3 ps-1">
500 |           {index < entries.length - 1 && (
501 |             <span
502 |               className="absolute start-[7px] top-5 h-[calc(100%+0.75rem)] w-px bg-slate-200"
503 |               aria-hidden="true"
504 |             />
505 |           )}
506 |           <span
507 |             className="relative mt-1.5 size-3.5 shrink-0 rounded-full border-[3px] border-teal-100"
508 |             aria-hidden="true"
509 |           />
510 |           <Link
511 |             to={` /student/journal/${entry.id}`}
512 |             className="min-w-0 flex-1 rounded-xl border border-slate-100 bg-white p-3 transition-c
513 |           >
514 |             <div className="flex flex-wrap items-center gap-2">
515 |               <time
516 |                 className="text-xs font-bold text-slate-400"
517 |                 dateTime={entry.created_at}
518 |               >
519 |                 {formatEntryDate(entry.created_at)}
520 |               </time>
521 |               {course ? (
522 |                 <Badge
523 |                   variant="outline"
524 |                   className="text-[10px] font-bold"
525 |                 >
526 |                   <BookOpen className="me-1 size-3" />
527 |                   {course.code}
528 |                 </Badge>
529 |               ) : null}
530 |             </div>
531 |             <p className="mt-1 line-clamp-3 whitespace-pre-wrap text-sm leading-relaxed text-slate
532 |               {entry.content}
533 |             </p>
534 |           </Link>
535 |         </li>
536 |       );
537 |     });
538 |   </ol>
539 | )}
540 | </PCard>
541 | </>
542 | )}
543 | </div>
544 | );
545 | };
546 |
547 | export default StudentJournalNew;
548 |

```

FILE: [src/pages/student/journal/StudentJournalPage.tsx](#)

TYPE: .tsx | LINES: 1-10 | SHA256: 8c50641455c610f06c47e52a6f30cfaac269b3d034165334f71110813a23b476

```

1 | // =====
2 | // StudentJournalPage – production journal page (redesigned UI)
3 | // =====
4 | // Implementation lives in `StudentJournalNew`, re-exported here so the route
5 | // path stays stable. Legacy page and its feature-flag wrapper were removed in
6 | // the UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "./StudentJournalNew";
10 |

```

FILE: [src/pages/student/leaderboard/LeaderboardPage.tsx](#)

TYPE: .tsx | LINES: 1-1085 | SHA256: 7a076e40643c9967d41bd14c514df9454fd6c8eae7049bf2f665c4a99faf4bc

```

1 | // =====
2 | // LeaderboardPage – Student leaderboard with Top XP, Personal Best, Most Improved
3 | // =====
4 |
5 | import { useMemo, useCallback, useEffect, useRef } from "react";
6 | import { useTranslation } from "react-i18next";
7 | import { parseAsString, useQueryState } from "nuqs";
8 | import {
9 |   Trophy,
10 |   Flame,
11 |   Medal,
12 |   TrendingUp,
13 |   Star,
14 |   BarChart3,
15 |   Shield,
16 |   Crown,
17 |   Lock,
18 |   Loader2,
19 | } from "lucide-react";
20 | import { useQueryClient } from "@tanstack/react-query";
21 | import { useReducedMotion } from "framer-motion";
22 | import { launchConfetti } from "@lib/confetti";
23 | import {
24 |   BarChart,
25 |   Bar,
26 |   XAxis,
27 |   YAxis,
28 |   CartesianGrid,
29 |   Tooltip,

```

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

```

758 |     : "all_time";
759 |
760 |     const {
761 |       data: leaderboardData,
762 |       isLoading: isLoadingLeaderboard,
763 |       hasMore: hasMoreEntries,
764 |       fetchNextPage: fetchMoreEntries,
765 |       isFetchingNextPage: isFetchingMoreEntries,
766 |     } = useLeaderboard(
767 |       typedFilter,
768 |       typedTimeframe,
769 |       effectiveCourseId,
770 |       effectiveProgramId,
771 |       institutionId
772 |     );
773 |
774 |     const { data: myRankData, isLoading: isLoadingMyRank } = useMyRank(
775 |       typedFilter,
776 |       typedTimeframe,
777 |       effectiveCourseId,
778 |       effectiveProgramId
779 |     );
780 |
781 |     // The hook gates rankings behind the min-cohort `state`; when locked it
782 |     // returns no entries so no rank/medal can render (R6.1, R6.4). The page reads
783 |     // `state` directly to render the "unlocks when more students join" panel and
784 |     // to suppress the personal rank card while locked.
785 |     const leaderboardGateState = leaderboardData.state;
786 |     const isLeaderboardLocked = leaderboardGateState === "locked";
787 |     const entries = useMemo(() => leaderboardData.entries, [leaderboardData]);
788 |     const currentUserEntry = useMemo(
789 |       () => entries.find((entry) => entry.student_id === userId),
790 |       [entries, userId]
791 |     );
792 |
793 |     // Fetch cosmetics for leaderboard entries (Task 6.2)
794 |     const leaderboardStudentIds = useMemo(
795 |       () => entries.map((e) => e.student_id),
796 |       [entries]
797 |     );
798 |     const { data: cosmeticsMap } = useLeaderboardCosmetics(leaderboardStudentIds);
799 |
800 |     // Percentile band data for the current user (Req 131.4)
801 |     const { data: percentileData } = useStudentPercentileBand(
802 |       userId,
803 |       effectiveCourseId
804 |     );
805 |     const totalStudents = percentileData?.totalStudents ?? entries.length;
806 |
807 |     // Student league tier for League tab (fetched for LeagueTierBadge rendering)
808 |     useStudentLeagueTier(userId);
809 |
810 |     return (
811 |       <div className="space-y-6">
812 |         { /* Page Header */ }
813 |         <SectionHeader
814 |           icon={Trophy}
815 |           title="Leaderboard"
816 |           action={ <AnonymousToggle /> }
817 |         />
818 |
819 |         { /* Mode Tabs: Individual vs Teams */ }
820 |         <div className="flex gap-2">
821 |           {[
822 |             { value: "individual", label: "Individual" },
823 |             { value: "teams", label: "Teams" },
824 |           ].map((opt) => (
825 |             <Button
826 |               key={opt.value}
827 |               type="button"
828 |               variant="ghost"
829 |               size="sm"
830 |               onClick={() => setMode(opt.value)}
831 |               className={cn(
832 |                 "h-auto rounded-xl px-4 py-1.5 text-sm font-semibold transition-colors",
833 |                 mode === opt.value
834 |                   ? "bg-blue-600 text-white hover:bg-blue-700 hover:text-white"
835 |                   : "bg-white text-gray-600 border border-gray-200"
836 |               )}
837 |             >
838 |               {opt.label}
839 |             </Button>
840 |           ))}
841 |         </div>
842 |
843 |         {mode === "teams" ? (
844 |           <TeamLeaderboard courseId={effectiveCourseId ?? courses[0]?.id} />
845 |         ) : (
846 |           <>
847 |             <ReconnectBanner isDisconnected={!isLive} retryCount={retryCount} />
848 |
849 |             { /* Leaderboard Tab Navigation: Top XP | Personal Best | Most Improved (Req 129.4) */ }
850 |             <div className="flex gap-2 flex-wrap">
851 |               {[
852 |                 {
853 |                   value: "top_xp" as LeaderboardTab,
854 |                   label: "Top XP",
855 |                   icon: Trophy,
856 |                 },
857 |                 {
858 |                   value: "personal_best" as LeaderboardTab,
859 |                   label: "Personal Best",
860 |                   icon: BarChart3,
861 |                 },

```

```

862     {
863       value: "most_improved" as LeaderboardTab,
864       label: "Most Improved",
865       icon: TrendingUp,
866     },
867     {
868       value: "league" as LeaderboardTab,
869       label: "League",
870       icon: Shield,
871     },
872   ].map((opt) => {
873     const Icon = opt.icon;
874     return (
875       <Button
876         key={opt.value}
877         type="button"
878         variant="ghost"
879         size="sm"
880         onClick={() => setTab(opt.value)}
881         className={cn(
882           "h-auto gap-1.5 rounded-xl px-4 py-1.5 text-sm font-semibold transition-colors",
883           tab === opt.value
884             ? "bg-blue-600 text-white hover:bg-blue-700 hover:text-white"
885             : "bg-white text-gray-600 border border-gray-200"
886         )}
887       >
888         <Icon className="h-4 w-4" />
889         {opt.label}
890       </Button>
891     );
892   });
893 </div>
894
895 /* Tab Content */
896 {tab === "personal_best" ? (
897   <PersonalBestChart studentId={userId} />
898 ) : tab === "most_improved" ? (
899   <MostImprovedList
900     courseId={effectiveCourseId}
901     currentUserId={userId}
902   />
903 ) : tab === "league" ? (
904   <LeagueLeaderboardList
905     courseId={effectiveCourseId}
906     currentUserId={userId}
907   />
908 ) : (
909   <>
910     /* Top XP - original leaderboard content */
911     {isLoadingLeaderboard ? (
912       <div className="space-y-2">
913         {Array.from({ length: 5 }).map((_, i) => (
914           <Shimmer key={i} className="h-14 rounded-xl" />
915         ))}
916       </div>
917     ) : isLeaderboardLocked ? (
918       // R6.1/R6.4: locked cohort !' no rank card, no rankings, no
919       // medals. The personal rank card is intentionally suppressed so
920       // no position is awarded while the leaderboard is locked.
921       <LeaderboardLockedState />
922     ) : (
923       <>
924         <Tabs value={filter} onValueChange={(v) => setFilter(v)}>
925           <div className="flex items-center justify-between flex-wrap gap-4">
926             <TabsList className="gap-2 bg-transparent p-0">
927               {FILTER_OPTIONS.map((opt) => (
928                 <TabsTrigger
929                   key={opt.value}
930                   value={opt.value}
931                   className={cn(
932                     "rounded-xl border px-4 py-1.5 text-sm font-medium transition-colors",
933                     filter === opt.value
934                       ? "bg-blue-600 text-white border-blue-600"
935                       : "bg-white text-gray-600 border-gray-200 hover:bg-slate-50"
936                   )}
937                 >
938                   {opt.label}
939                 </TabsTrigger>
940               ))}
941             </TabsList>
942             <div className="flex items-center gap-2">
943               {TIMEFRAME_OPTIONS.map((opt) => (
944                 <Button
945                   key={opt.value}
946                   variant="outline"
947                   size="sm"
948                   onClick={() => setTimeframe(opt.value)}
949                   className={cn(
950                     "rounded-xl text-sm font-medium",
951                     timeframe === opt.value
952                       ? "bg-blue-600 text-white border-blue-600 hover:bg-blue-700 hover:text-white"
953                       : "bg-white text-gray-600 border-gray-200"
954                   )}
955                 >
956                   {opt.label}
957                 </Button>
958               ))}
959             </div>
960           </div>
961         </div>
962         <TabsContent value="course" className="mt-4">
963           {!isLoadingContext && courses.length > 0 && (
964             <Select

```

```

966         value={effectiveCourseId ?? ""}
967         onChange={onValueChange}
968       >
969         <SelectTrigger className="w-64 bg-white">
970           <SelectValue placeholder="Select a course" />
971         </SelectTrigger>
972         <SelectContent>
973           {courses.map((c: { id: string; name: string }) => (
974             <SelectItem key={c.id} value={c.id}>
975               {c.name}
976             </SelectItem>
977           ))}
978         </SelectContent>
979       </Select>
980     ))}
981     {isLoadingContext && courses.length === 0 && (
982       <p className="text-sm text-gray-500">
983         No enrolled courses found.
984       </p>
985     )}
986   </TabsContent>
987
988   <TabsContent value="program" className="mt-4">
989     {isLoadingContext && programs.length > 0 && (
990       <Select
991         value={effectiveProgramId ?? ""}
992         onChange={onValueChange}
993       >
994         <SelectTrigger className="w-64 bg-white">
995           <SelectValue placeholder="Select a program" />
996         </SelectTrigger>
997         <SelectContent>
998           {programs.map((p: { id: string; name: string }) => (
999             <SelectItem key={p.id} value={p.id}>
1000               {p.name}
1001             </SelectItem>
1002           ))}
1003         </SelectContent>
1004       </Select>
1005     )}
1006     {isLoadingContext && programs.length === 0 && (
1007       <p className="text-sm text-gray-500">
1008         No programs found.
1009       </p>
1010     )}
1011   </TabsContent>
1012
1013   <TabsContent value="all" />
1014 </Tabs>
1015
1016 <MyRankCard
1017   rank={currentUserEntry?.rank ?? myRankData?.rank ?? null}
1018   xpTotal={
1019     currentUserEntry?.xp_total ?? myRankData?.xp_total ?? 0
1020   }
1021   level={currentUserEntry?.level ?? myRankData?.level ?? 1}
1022   isLoading={isLoadingMyRank}
1023   totalStudents={totalStudents}
1024 />
1025
1026 <PCard className="overflow-hidden gap-0 py-0">
1027   <div
1028     className="px-6 py-4 flex items-center gap-2"
1029     style={{
1030       background: "var(--brand-gradient)",
1031     }}
1032   >
1033     <Medal className="h-5 w-5 text-white" />
1034     <h2 className="text-lg font-bold tracking-tight text-white">
1035       {t("leaderboard.rankings.title")}
1036     </h2>
1037   </div>
1038   <div className="p-4 space-y-2">
1039     {entries.length === 0 ? (
1040       <InlineNoLeaderboardData />
1041     ) : (
1042       <>
1043         {entries.map((entry) => (
1044           <LeaderboardRow
1045             key={entry.student_id}
1046             entry={entry}
1047             isCurrentUser={entry.student_id === userId}
1048             totalStudents={totalStudents}
1049             cosmetics={
1050               cosmeticsMap?.get(entry.student_id) ?? null
1051             }
1052           />
1053         ))}
1054         {hasMoreEntries && (
1055           <div className="flex justify-center pt-2">
1056             <Button
1057               variant="outline"
1058               size="sm"
1059               onClick={() => fetchMoreEntries()}
1060               disabled={isLoadingMoreEntries}
1061               className="rounded-xl text-sm font-medium"
1062             >
1063               {isLoadingMoreEntries && (
1064                 <Loader2 className="h-4 w-4 animate-spin" />
1065               )}
1066               {t("leaderboard.rankings.loadMore")}
1067             </Button>
1068           </div>
1069         )}

```

```

1070 |                                     </>
1071 |                                 }}
1072 |                             </div>
1073 |                         </PCard>
1074 |                     </>
1075 |                 </>
1076 |             </>
1077 |         }}
1078 |     </>
1079 | }}
1080 | </div>
1081 | );
1082 | };
1083 |
1084 | export default LeaderboardPage;
1085 |

```

FILE: src/pages/student/leaderboard/TeamLeaderboard.tsx

TYPE: .tsx | LINES: 1-202 | SHA256: ce1167e0f83499bf9bc6d014d6ac29d3a00d08ede53d941354ffc2675d1500c3

[illegible]

[illegible]

```

189         isCurrentTeam={entry.team_id === myTeamId}
190         showWeekly={typedView === "weekly"}
191     )
192   ))
193   }}
194   </div>
195 </div>
196 </PCard>
197 </div>
198 );
199 };
200
201 export default TeamLeaderboard;
202

```

FILE: src/pages/student/marketplace/ItemCard.tsx

```
TYPE: .tsx | LINES: 1-188 | SHA256: e598ac62e7f72144ae87468d56d345977b44d45f796aa6916932fa3afad9f4ad
```

[illegible]


```

87 |         <div className="absolute top-3 end-3 z-10">
88 |             <Badge className="bg-green-100 text-green-700 border-green-200">
89 |                 <Check className="h-3 w-3 me-1" />
90 |                 Owned
91 |             </Badge>
92 |         </div>
93 |     )}
94 |
95 |     { /* Preview area */ }
96 |     <div className="p-4 flex items-center justify-center min-h-[100px] bg-slate-50">
97 |         {isCosmetic ? (
98 |             <CosmeticPreview
99 |                 subCategory={item.sub_category}
100 |                 metadata={item.metadata}
101 |                 name={item.name}
102 |                 className="w-full"
103 |             />
104 |         ) : (
105 |             <div className="p-3 rounded-xl bg-blue-50">
106 |                 <IconComponent className="h-8 w-8 text-blue-600" />
107 |             </div>
108 |         )}
109 |     </div>
110 |
111 |     { /* Content */ }
112 |     <div className="p-4 space-y-3 flex flex-col flex-1">
113 |         <div>
114 |             <h3 className="text-sm font-bold text-gray-900 truncate">
115 |                 {item.name}
116 |             </h3>
117 |             <p className="text-xs text-gray-500 mt-0.5 line-clamp-2">
118 |                 {item.description}
119 |             </p>
120 |         </div>
121 |
122 |         { /* Price */ }
123 |         <div className="flex items-center gap-2">
124 |             <Coins className="h-4 w-4 text-amber-500" />
125 |             {hasSale ? (
126 |                 <div className="flex items-center gap-1.5">
127 |                     <span className="text-xs text-gray-400 line-through">
128 |                         {item.xp_price.toLocaleString()}
129 |                     </span>
130 |                     <span className="text-sm font-bold text-amber-600">
131 |                         {item.effective_price.toLocaleString()} XP
132 |                     </span>
133 |                 </div>
134 |             ) : (
135 |                 <span className="text-sm font-bold text-amber-600">
136 |                     {item.xp_price.toLocaleString()} XP
137 |                 </span>
138 |             )}
139 |         </div>
140 |
141 |         { /* Stock info */ }
142 |         {item.stock_type === "limited" && !isOutOfStock && (
143 |             <p className="text-xs text-gray-500">
144 |                 {item.stock_quantity} remaining
145 |             </p>
146 |         )}
147 |
148 |         { /* Level requirement */ }
149 |         {isLocked && (
150 |             <div className="flex items-center gap-1.5 text-xs text-gray-500">
151 |                 <Lock className="h-3 w-3" />
152 |                 <span>Requires Level {item.level_requirement}</span>
153 |             </div>
154 |         )}
155 |
156 |         { /* Action button – pinned to the bottom so all cards' CTAs align */ }
157 |         <div className="mt-auto pt-1">
158 |             {isOutOfStock ? (
159 |                 <Button disabled className="w-full" variant="outline" size="sm">
160 |                     Out of Stock
161 |                 </Button>
162 |             ) : isOwned ? (
163 |                 <Button disabled className="w-full" variant="outline" size="sm">
164 |                     Already Owned
165 |                 </Button>
166 |             ) : isLocked ? (
167 |                 <Button disabled className="w-full" variant="outline" size="sm">
168 |                     <Lock className="h-4 w-4 me-1" />
169 |                     Locked
170 |                 </Button>
171 |             ) : (
172 |                 <Button
173 |                     onClick={() => onPurchase(item)}
174 |                     variant="tactile"
175 |                     className="w-full"
176 |                     size="sm"
177 |                 >
178 |                     Buy Now
179 |                 </Button>
180 |             )}
181 |         </div>
182 |     </div>
183 | </PCard>
184 | );
185 | };
186 |
187 | export default ItemCard;
188 |

```

FILE: src/pages/student/marketplace/KnowledgeQuestsTab.tsx

TYPE: .tsx | LINES: 1-122 | SHA256: 4347ac7cbe93679820044dffc3d3406704617619c67ce61b7183643b291ba2ed

```
1 // =====
2 // KnowledgeQuestsTab - Quest listing with countdown timers and progress
3 // Task 21.1
4 // =====
5
6 import { useMemo } from "react";
7 import { Badge } from "@components/ui/badge";
8 import { Button } from "@components/ui/button";
9 import { PCard } from "@design-system";
10 import { Loader2, Clock, Trophy, BookOpen } from "lucide-react";
11 import { useKnowledgeQuests, useStartQuest } from "@hooks/useKnowledgeQuests";
12 import { useAuth } from "@hooks/useAuth";
13
14 const QUEST_TYPE_ICONS = {
15   quiz_challenge: BookOpen,
16   content_creation: Trophy,
17   peer_review: BookOpen,
18 } as const;
19
20 const KnowledgeQuestsTab = () => {
21   const { profile } = useAuth();
22   const { data: quests, isLoading } = useKnowledgeQuests("active");
23   const startQuest = useStartQuest();
24
25   const sortedQuests = useMemo(() => {
26     if (!quests) return [];
27     return [...quests].sort(
28       (a, b) => new Date(a.end_date).getTime() - new Date(b.end_date).getTime()
29     );
30   }, [quests]);
31
32   if (isLoading) {
33     return (
34       <div className="flex items-center justify-center py-12">
35         <Loader2 className="h-6 w-6 animate-spin text-blue-500" />
36       </div>
37     );
38   }
39
40   if (sortedQuests.length === 0) {
41     return (
42       <div className="text-center py-12 text-gray-500">
43         <Trophy className="h-12 w-12 mx-auto mb-3 text-gray-300" />
44         <p className="text-sm font-medium">No active quests right now</p>
45         <p className="text-xs mt-1">
46           Check back later for new knowledge quests!
47         </p>
48       </div>
49     );
50   }
51
52   return (
53     <div className="grid gap-4 md:grid-cols-2">
54       {sortedQuests.map((quest) => {
55         const Icon = QUEST_TYPE_ICONS[quest.quest_type] ?? BookOpen;
56         const endDate = new Date(quest.end_date);
57         const now = new Date();
58         const hoursRemaining = Math.max(
59           0,
60           Math.floor((endDate.getTime() - now.getTime()) / (1000 * 60 * 60))
61         );
62         const daysRemaining = Math.floor(hoursRemaining / 24);
63
64         return (
65           <PCard key={quest.id} className="p-4">
66             <div className="flex items-start gap-3">
67               <div className="p-2 rounded-lg bg-purple-50">
68                 <Icon className="h-5 w-5 text-purple-600" />
69               </div>
70               <div className="flex-1 min-w-0">
71                 <h3 className="text-sm font-bold truncate">{quest.title}</h3>
72                 <p className="text-xs text-gray-500 mt-0.5 line-clamp-2">
73                   {quest.description}
74                 </p>
75
76                 <div className="flex items-center gap-2 mt-2 flex-wrap">
77                   <Badge variant="outline" className="text-[10px] capitalize">
78                     {quest.quest_type.replace("_", " ")}
79                   </Badge>
80                   <div className="flex items-center gap-1 text-[10px] text-gray-400">
81                     <Clock className="h-3 w-3" />
82                     {daysRemaining > 0
83                       ? `${daysRemaining}d ${hoursRemaining % 24}h left`
84                       : `${hoursRemaining}h left`}
85                   </div>
86                 </div>
87
88                 <div className="flex items-center justify-between mt-3">
89                   <span className="text-xs font-bold text-amber-600">
90                     {quest.reward_type === "xp"
91                       ? `+${quest.reward_xp_amount} XP`
92                       : "Exclusive Item"}
93                   </span>
94                   <Button
95                     size="sm"
96                     className="bg-gradient-to-r from-teal-500 to-blue-600 text-white active:scale-95 text-xs"
97                     disabled={startQuest.isPending}
98                     onClick={() =>
99                       profile?.id &&
100                         startQuest.mutate({
101                           questId: quest.id,
```

```

102 |             studentId: profile.id,
103 |         })
104 |     }
105 |     >
106 |     {startQuest.isPending && (
107 |       <Loader2 className="h-3 w-3 animate-spin" />
108 |     )}
109 |     Start Quest
110 |   </Button>
111 | </div>
112 | </div>
113 | </div>
114 | </PCard>
115 |   );
116 |   })}
117 | </div>
118 | );
119 | };
120 |
121 | export default KnowledgeQuestsTab;
122 |

```

FILE: src/pages/student/marketplace/MarketplacePage.tsx

```
TYPE: .tsx | LINES: 1-199 | SHA256: 964928b8b74efe6da43b7946ad673804802d28cf8615c5f85cf88b3a43e19969
```

[illegible]

```

80     ids.add(inv.item_id);
81   }
82 }
83 return ids;
84 }, [inventory]);
85
86 const handlePurchaseClick = (item: MarketplaceItem) => {
87   setSelectedItem(item);
88   setDialogOpen(true);
89 };
90
91 const handleConfirmPurchase = () => {
92   if (!selectedItem) return;
93   purchaseMutation.mutate(selectedItem.id, {
94     onSuccess: () => {
95       setDialogOpen(false);
96       setSelectedItem(null);
97     },
98   });
99 };
100
101 return (
102   <div className="space-y-6">
103     { /* Page Header */ }
104     <div className="flex items-center justify-between flex-wrap gap-4">
105       <div className="flex items-center gap-3">
106         <ShoppingBag className="h-6 w-6 text-blue-600" />
107         <h1 className="text-2xl font-bold tracking-tight">Marketplace</h1>
108       </div>
109       <div className="flex items-center gap-3">
110         <ActiveBoostIndicator />
111         <XPBalanceBadge size="lg" />
112       </div>
113     </div>
114
115     { /* Category Tabs */ }
116     <div className="flex gap-2 flex-wrap">
117       { CATEGORIES.map((cat) => {
118         const icon = cat.icon;
119         return (
120           <Button
121             key={cat.value}
122             type="button"
123             variant="ghost"
124             size="sm"
125             onClick={() => setCategory(cat.value)}
126             className={cn(
127               "h-auto gap-1.5 rounded-xl px-4 py-1.5 text-sm font-semibold transition-colors",
128               category === cat.value
129                 ? "bg-blue-600 text-white hover:bg-blue-700 hover:text-white"
130                 : "bg-white text-gray-600 border border-gray-200 hover:bg-slate-50"
131             )}
132           >
133             <Icon className="h-4 w-4" />
134             {cat.label}
135           </Button>
136         );
137       })}
138     </div>
139
140     { /* Item Grid */ }
141     { isLoadingItems ? (
142       <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4 gap-4">
143         {Array.from({ length: 8 }).map((_, i) => (
144           <Shimmer key={i} className="h-64 rounded-xl" />
145         ))}
146       </div>
147     ) : items.length === 0 ? (
148       <NoMarketplaceItems />
149     ) : (
150       <div className="space-y-6">
151         <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4 gap-4">
152           {items.map((item) => (
153             <ItemCard
154               key={item.id}
155               item={item}
156               studentLevel={studentLevel}
157               isOwned={
158                 item.stock_type === "one_per_student" &&
159                 ownedItemIds.has(item.id)
160               }
161               onPurchase={handlePurchaseClick}
162             />
163           ))}
164         </div>
165         {hasNextPage && (
166           <div className="flex justify-center">
167             <Button
168               variant="outline"
169               onClick={() => fetchNextPage()}
170               disabled={!isFetchingNextPage}
171             >
172               {isFetchingNextPage ? (
173                 <>
174                   <Loader2 className="h-4 w-4 animate-spin" /> Loading...
175                 </>
176               ) : (
177                 "Load more"
178               )}
179             </Button>
180           </div>
181         )}
182       </div>
183     )}

```

```

184 |
185 |         { /* Purchase Confirmation Dialog */ }
186 |         <PurchaseConfirmDialog
187 |             item={selectedItem}
188 |             currentBalance={currentBalance}
189 |             isPending={purchaseMutation.isPending}
190 |             open={dialogOpen}
191 |             onOpenChange={setDialogOpen}
192 |             onConfirm={handleConfirmPurchase}
193 |         />
194 |     </div>
195 | );
196 | };
197 |
198 | export default MarketplacePage;
199 |

```

[illegible]

```

85 |         slot,
86 |     });
87 | };
88 |
89 | const handleUnequip = (item: InventoryItem) => {
90 |     const slot = item.item_sub_category as CosmeticSlot;
91 |     unequipMutation.mutate({
92 |         studentId: userId,
93 |         slot,
94 |     });
95 | };
96 |
97 | return (
98 |     <div className="space-y-6">
99 |         {/* Page Header */}
100 |         <div className="flex items-center justify-between flex-wrap gap-4">
101 |             <SectionHeader
102 |                 icon={Package}
103 |                 title="My Items"
104 |                 action={<XPBalanceBadge size="lg" />}
105 |             />
106 |         </div>
107 |
108 |         {/* Category Tabs */}
109 |         <div className="flex gap-2 flex-wrap">
110 |             {CATEGORIES.map((cat) => {
111 |                 const Icon = cat.icon;
112 |                 return (
113 |                     <Button
114 |                         key={cat.value}
115 |                         type="button"
116 |                         variant="ghost"
117 |                         size="sm"
118 |                         onClick={() => setCategory(cat.value)}
119 |                         className={cn(
120 |                             "h-auto gap-1.5 rounded-xl px-4 py-1.5 text-sm font-semibold transition-colors",
121 |                             category === cat.value
122 |                                 ? "bg-blue-600 text-white hover:bg-blue-700 hover:text-white"
123 |                                 : "bg-white text-gray-600 border border-gray-200 hover:bg-slate-50"
124 |                         )}
125 |                     >
126 |                         <Icon className="h-4 w-4" />
127 |                         {cat.label}
128 |                     </Button>
129 |                 );
130 |             })}
131 |         </div>
132 |
133 |         {/* Items List */}
134 |         {isLoading ? (
135 |             <div className="space-y-3">
136 |                 {Array.from({ length: 4 }).map((_, i) => (
137 |                     <Shimmer key={i} className="h-20 rounded-xl" />
138 |                 ))}
139 |             </div>
140 |         ) : filteredItems.length === 0 ? (
141 |             <div className="text-center py-12">
142 |                 <Package className="h-12 w-12 text-gray-300 mx-auto mb-3" />
143 |                 <p className="text-sm text-gray-500">
144 |                     No items in your inventory yet.
145 |                 </p>
146 |             </div>
147 |         ) : (
148 |             <div className="space-y-3">
149 |                 {filteredItems.map((item) => {
150 |                     const isEquipped = equippedSlotMap.has(item.purchase_id);
151 |                     const isCosmetic = item.item_category === "cosmetic";
152 |
153 |                     return (
154 |                         <PCard key={item.purchase_id} className="p-4">
155 |                             <div className="flex items-center gap-4">
156 |                                 {/* Preview */}
157 |                                 {isCosmetic ? (
158 |                                     <div className="w-16 shrink-0">
159 |                                         <CosmeticPreview
160 |                                             subCategory={item.item_sub_category}
161 |                                             metadata={item.metadata}
162 |                                             name={item.item_name}
163 |                                         />
164 |                                     </div>
165 |                                 ) : (
166 |                                     <div className="w-16 h-16 shrink-0 rounded-xl bg-blue-50 flex items-center justify-center"
167 |                                     >
168 |                                         {item.item_category === "educational_perk" ? (
169 |                                             <GraduationCap className="h-6 w-6 text-blue-600" />
170 |                                         ) : (
171 |                                             <Zap className="h-6 w-6 text-purple-600" />
172 |                                         )}
173 |                                     </div>
174 |                                 )}
175 |                             </div>
176 |                             {/* Info */}
177 |                             <div className="flex-1 min-w-0">
178 |                                 <div className="flex items-center gap-2">
179 |                                     <h3 className="text-sm font-bold text-gray-900 truncate">
180 |                                         {item.item_name}
181 |                                     </h3>
182 |                                     <StatusBadge status={item.status} />
183 |                                 </div>
184 |                                 {isEquipped && (
185 |                                     <Badge className="bg-blue-100 text-blue-700 border-blue-200">
186 |                                         <Check className="h-3 w-3 me-1" />
187 |                                         Equipped
188 |                                     </Badge>
189 |                                 )}
190 |                             </div>
191 |                         </PCard>
192 |                     );
193 |                 })}
194 |             </div>
195 |         )}
196 |     </div>
197 | );

```

```

189 |         <p className="text-xs text-gray-500 mt-0.5">
190 |             Purchased{" "}
191 |             {new Date(item.purchased_at).toLocaleDateString()} .{" "}
192 |             {item.xp_cost} XP
193 |         </p>
194 |     </div>
195 |
196 |     {/* Actions */}
197 |     <div className="shrink-0">
198 |         {isCosmetic &&
199 |             item.status === "active" &&
200 |             (isEquipped ? (
201 |                 <Button
202 |                     variant="outline"
203 |                     size="sm"
204 |                     onClick={() => handleUnequip(item)}
205 |                     disabled={unequipMutation.isPending}
206 |                 >
207 |                     <X className="h-4 w-4 me-1" />
208 |                     Unequip
209 |                 </Button>
210 |             ) : (
211 |                 <Button
212 |                     size="sm"
213 |                     onClick={() => handleEquip(item)}
214 |                     disabled={equipMutation.isPending}
215 |                     variant="tactile"
216 |                 >
217 |                     Equip
218 |                 </Button>
219 |             ))}
220 |     </div>
221 | </div>
222 | </PCard>
223 |     );
224 | }}
225 | </div>
226 | }}
227 | </div>
228 | );
229 | };
230 |
231 | export default MyItemsPage;
232 |

```

File: [src/pages/student/marketplace/PurchaseConfirmDialog.tsx](#)

TYPE: .tsx | LINES: 1-132 | SHA256: ab3fa5b3f0e3242c45424dce948b022b9d0dd4b608725ee71dba3bbea9635957

```

1 | // =====
2 | // PurchaseConfirmDialog – Confirmation dialog with balance preview
3 | // =====
4 |
5 | import { Coins, Loader2, AlertCircle } from "lucide-react";
6 | import {
7 |     Dialog,
8 |     DialogContent,
9 |     DialogDescription,
10 |    DialogFooter,
11 |    DialogHeader,
12 |    DialogTitle,
13 | } from "@components/ui/dialog";
14 | import { Button } from "@components/ui/button";
15 | import type { MarketplaceItem } from "@hooks/useMarketplace";
16 |
17 | interface PurchaseConfirmDialogProps {
18 |     item: MarketplaceItem | null;
19 |     currentBalance: number;
20 |     isPending: boolean;
21 |     open: boolean;
22 |     onOpenChange: (open: boolean) => void;
23 |     onConfirm: () => void;
24 | }
25 |
26 | const PurchaseConfirmDialog = ({
27 |     item,
28 |     currentBalance,
29 |     isPending,
30 |     open,
31 |     onOpenChange,
32 |     onConfirm,
33 | }: PurchaseConfirmDialogProps) => {
34 |     if (!item) return null;
35 |
36 |     const cost = item.effective_price;
37 |     const remainingBalance = currentBalance - cost;
38 |     const canAfford = remainingBalance >= 0;
39 |
40 |     return (
41 |         <Dialog open={open} onOpenChange={onOpenChange}>
42 |             <DialogContent className="sm:max-w-md">
43 |                 <DialogHeader>
44 |                     <DialogTitle>Confirm Purchase</DialogTitle>
45 |                     <DialogDescription>
46 |                         Review the details below before confirming your purchase.
47 |                     </DialogDescription>
48 |                 </DialogHeader>
49 |
50 |                 <div className="space-y-4 py-4">
51 |                     {/* Item info */}
52 |                     <div className="flex items-center gap-3 rounded-xl bg-slate-50 p-3">
53 |                         <div className="flex-1">
54 |                             <p className="text-sm font-bold text-gray-900">{item.name}</p>
55 |                             <p className="text-xs text-gray-500 mt-0.5">{item.description}</p>
56 |                         </div>

```

```

57 |         </div>
58 |
59 |         { /* Balance breakdown */ }
60 |         <div className="space-y-2 rounded-xl border border-slate-200 p-4">
61 |           <div className="flex items-center justify-between text-sm">
62 |             <span className="text-gray-600">Item Cost</span>
63 |             <div className="flex items-center gap-1">
64 |               <Coins className="h-4 w-4 text-amber-500" />
65 |               <span className="font-bold text-amber-600">
66 |                 {item.sale_discount > 0 && (
67 |                   <span className="text-gray-400 line-through me-1.5 font-normal">
68 |                     {item.xp_price.toLocaleString()}
69 |                   </span>
70 |                 )}
71 |                 {cost.toLocaleString()} XP
72 |               </span>
73 |             </div>
74 |           </div>
75 |
76 |           <div className="flex items-center justify-between text-sm">
77 |             <span className="text-gray-600">Current Balance</span>
78 |             <span className="font-semibold">
79 |               {currentBalance.toLocaleString()} XP
80 |             </span>
81 |           </div>
82 |
83 |           <hr className="border-slate-200" />
84 |
85 |           <div className="flex items-center justify-between text-sm">
86 |             <span className="text-gray-600">Remaining Balance</span>
87 |             <span
88 |               className={`font-bold ${
89 |                 canAfford ? "text-green-600" : "text-red-500"
90 |               }`}
91 |             >
92 |               {remainingBalance.toLocaleString()} XP
93 |             </span>
94 |           </div>
95 |         </div>
96 |
97 |         { /* Insufficient balance warning */ }
98 |         { !canAfford && (
99 |           <div className="flex items-center gap-2 rounded-xl bg-red-50 border border-red-200 px-4 py-3">
100 |             <AlertCircle className="h-4 w-4 text-red-500 shrink-0" />
101 |             <p className="text-xs text-red-700">
102 |               You don't have enough XP for this purchase. You need{" "}
103 |               {Math.abs(remainingBalance).toLocaleString()} more XP.
104 |             </p>
105 |           </div>
106 |         )}
107 |       </div>
108 |
109 |       <DialogFooter className="gap-2">
110 |         <Button
111 |           variant="outline"
112 |           onClick={() => onOpenChange(false)}
113 |           disabled={isPending}
114 |         >
115 |           Cancel
116 |         </Button>
117 |         <Button
118 |           onClick={onConfirm}
119 |           disabled={!canAfford || isPending}
120 |           variant="tactile"
121 |         >
122 |           {isPending && <Loader2 className="h-4 w-4 animate-spin me-1" />}
123 |           Confirm Purchase
124 |         </Button>
125 |       </DialogFooter>
126 |     </DialogContent>
127 |   </Dialog>
128 | );
129 | };
130 |
131 | export default PurchaseConfirmDialog;
132 |

```

FILE: [src/pages/student/marketplace/TransactionHistoryPage.tsx](#)

TYPE: .tsx | LINES: 1-222 | SHA256: 7ab1f337ac5a9759825ae12fce42d58d87405fd5a397af0c5271fc3efc036ff4

```

1 | // =====
2 | // TransactionHistoryPage - Unified history with filter tabs and pagination
3 | //
4 | // Pages through all entries via `useTransactionHistory` (source-level
5 | // pagination). On query failure the view surfaces a Sonner toast and an error
6 | // panel, and refuses to render any transactions rather than showing a
7 | // truncated/partial list (Requirements 33.1a, 33.2, 33.3).
8 | // =====
9 |
10 | import { useEffect } from "react";
11 | import {
12 |   History,
13 |   ArrowUpRight,
14 |   ArrowDownRight,
15 |   ChevronLeft,
16 |   ChevronRight,
17 |   AlertTriangle,
18 | } from "lucide-react";
19 | import { useTranslation } from "react-i18next";
20 | import { parseAsString, parseAsInteger, useQueryState } from "nuqs";
21 | import { toast } from "sonner";
22 | import { Button } from "@components/ui/button";
23 | import { PCard, SectionHeader, Shimmer } from "@design-system";
24 | import XPBalanceBadge from "@components/shared/XPBalanceBadge";

```


[illegible]

```

129 |         variant="ghost"
130 |         size="sm"
131 |         onClick={() => {
132 |             setFilter(value);
133 |             setPage(0);
134 |         }}
135 |         className={cn(
136 |             "h-auto rounded-xl px-4 py-1.5 text-sm font-semibold transition-colors",
137 |             typedFilter === value
138 |               ? "bg-blue-600 text-white hover:bg-blue-700 hover:text-white"
139 |               : "bg-white text-gray-600 border border-gray-200 hover:bg-slate-50"
140 |         )}
141 |     >
142 |         {t(`transactions.filters.${value}`)}
143 |     </Button>
144 | ))}
145 </div>
146
147 {/* Transaction List */}
148 {isError ? (
149     // Failure: refuse to display transactions, show an error panel (R33.1a).
150     <PCard>
151         <div
152             role="alert"
153             className="flex flex-col items-center justify-center p-12 text-center"
154         >
155             <AlertTriangle className="mb-3 h-12 w-12 text-red-400" />
156             <p className="text-sm font-semibold text-gray-900">
157                 {t("transactions.error.title")}
158             </p>
159             <p className="mt-1 max-w-sm text-sm text-gray-500">
160                 {t("transactions.error.body")}
161             </p>
162         </div>
163     </PCard>
164 ) : isLoading ? (
165     <div className="space-y-2">
166         {Array.from({ length: 6 }).map((_, i) => (
167             <Shimmer key={i} className="h-16 rounded-xl" />
168         ))}
169     </div>
170 ) : !data || data.entries.length === 0 ? (
171     <PCard>
172         <div className="p-12 text-center">
173             <History className="mx-auto mb-3 h-12 w-12 text-gray-300" />
174             <p className="text-sm text-gray-500">{t("transactions.empty")}</p>
175         </div>
176     </PCard>
177 ) : (
178     <>
179         <PCard className="overflow-hidden">
180             {data.entries.map((entry) => (
181                 <TransactionRow key={entry.id} entry={entry} />
182             ))}
183         </PCard>
184
185         {/* Pagination */}
186         <div className="flex items-center justify-between">
187             <p className="text-xs text-gray-500">
188                 {t("transactions.showing", {
189                     from: page * PAGE_SIZE + 1,
190                     to: Math.min((page + 1) * PAGE_SIZE, data.totalCount),
191                     total: data.totalCount,
192                 })}
193             </p>
194             <div className="flex gap-2">
195                 <Button
196                     variant="outline"
197                     size="sm"
198                     disabled={page === 0}
199                     onClick={() => setPage(Math.max(0, page - 1))}
200                 >
201                     <ChevronLeft className="h-4 w-4" />
202                     {t("transactions.previous")}
203                 </Button>
204                 <Button
205                     variant="outline"
206                     size="sm"
207                     disabled={!data.hasMore}
208                     onClick={() => setPage(page + 1)}
209                 >
210                     {t("transactions.next")}
211                     <ChevronRight className="h-4 w-4" />
212                 </Button>
213             </div>
214         </div>
215     </>
216 ))}
217 </div>
218 );
219 };
220
221 export default TransactionHistoryPage;
222

```

FILE: [src/pages/student/onboarding/BaselineSelectStep.tsx](#)

TYPE: .tsx | LINES: 1-175 | SHA256: 3241980559528d78d667a95a62df472448b98169ae1ef1ea12b08d263f3e5ec3

```

1 | import { useState, useCallback, useEffect } from "react";
2 | import { ClipboardCheck, Clock, FileQuestion } from "lucide-react";
3 | import { Button } from "@components/ui/button";
4 | import { Card } from "@components/ui/card";
5 | import { useEnrolledCoursesWithBaseline } from "@hooks/useBaselineCourses";
6 | import type { WizardStepProps } from "../OnboardingWizard";

```

[illegible]

```

111 <div className="flex items-start gap-3">
112   <span
113     className={`mt-0.5 flex h-5 w-5 shrink-0 items-center justify-center rounded border-2 transi
114     isSelected
115       ? "border-blue-500 bg-blue-500"
116       : "border-slate-300"
117     `}
118     aria-hidden="true"
119   >
120     {isSelected && (
121       <svg
122         className="h-3 w-3 text-white"
123         fill="none"
124         viewBox="0 0 24 24"
125         stroke="currentColor"
126         strokeWidth={3}
127       >
128         <path
129           strokeLinecap="round"
130           strokeLinejoin="round"
131           d="M5 13L4 4L19 7"
132         />
133       </svg>
134     )}
135   </span>
136   <div className="flex-1">
137     <p className="text-sm font-semibold text-gray-900">
138       {course.course_name}
139     </p>
140     <div className="mt-1 flex items-center gap-4 text-xs text-gray-500">
141       <span className="flex items-center gap-1">
142         <FileQuestion className="h-3.5 w-3.5" />
143         {course.question_count} questions
144       </span>
145       <span className="flex items-center gap-1">
146         <Clock className="h-3.5 w-3.5" />
147         {course.time_limit_minutes} min
148       </span>
149     </div>
150   </div>
151 </div>
152 </Card>
153 );
154 }}}
155 </div>
156
157 <div className="mt-6 flex w-full max-w-md items-center justify-between">
158   <Button variant="ghost" onClick={handleSkip} className="text-gray-500">
159     Skip Baseline Tests
160   </Button>
161   <Button
162     onClick={handleContinue}
163     disabled={selectedIds.size === 0}
164     variant="tactile"
165     className="gap-1"
166   >
167     Start Tests ({selectedIds.size} selected)
168   </Button>
169 </div>
170 </div>
171 );
172 };
173
174 export default BaselineSelectStep;
175

```

FILE: src/pages/student/onboarding/BaselineTestStep.tsx

TYPE: .tsx | LINES: 1-363 | SHA256: f7a5a77c217d7ebd4a8ca1335b81b5a7a812e4c99904cfab54a99d56e2d1dcae

```

1 | import { useState, useCallback, useEffect, useRef } from "react";
2 | import { motion, AnimatePresence } from "framer-motion";
3 | import { Timer, AlertTriangle } from "lucide-react";
4 | import { Button } from "@components/ui/button";
5 | import { Card } from "@components/ui/card";
6 | import { Badge } from "@components/ui/badge";
7 | import { useBaselineQuestions } from "@hooks/useOnboardingQuestions";
8 | import { useBaselineTestConfig } from "@hooks/useBaseLineTests";
9 | import { useSaveResponses } from "@hooks/useOnboardingResponses";
10| import type { OnboardingQuestion } from "@hooks/useOnboardingQuestions";
11| import type { WizardStepProps } from "../OnboardingWizard";
12|
13| // %% Types %%%%%%%%%%%%%%%
14|
15| interface BaselineOption {
16|   option_text: string;
17| }
18|
19| interface BaselineTestStepProps extends WizardStepProps {
20|   courseIds: string[];
21| }
22|
23| // %% Inline AssessmentTimer (shared component created in Task 6) %%%%%%%%%
24|
25| interface AssessmentTimerProps {
26|   totalSeconds: number;
27|   onExpire: () => void;
28|   isPaused?: boolean;
29| }
30|
31| const AssessmentTimer = ({
32|   totalSeconds,
33|   onExpire,
34|   isPaused = false,
35| }: AssessmentTimerProps) => {

```

```
36 const [remaining, setRemaining] = useState(totalSeconds);  
37 const onExpireRef = useRef(onExpire);  
38  
39 useEffect(() => {  
40   onExpireRef.current = onExpire;  
41 }, [onExpire]);  
42  
43 useEffect(() => {  
44   if (isPaused) return;  
45   if (remaining <= 0) {  
46     onExpireRef.current();  
47     return;  
48   }  
49   const interval = setInterval(() => {  
50     setRemaining((prev) => {  
51       if (prev <= 1) {  
52         clearInterval(interval);  
53         onExpireRef.current();  
54         return 0;  
55       }  
56       return prev - 1;  
57     });  
58   }, 1000);  
59   return () => clearInterval(interval);  
60 }, [remaining, isPaused]);  
61  
62 // Pause on tab hidden  
63 useEffect(() => {  
64   const handleVisibility = () => {  
65     // Timer auto-pauses via isPaused or visibility – simplified here  
66   };  
67   document.addEventListener("visibilitychange", handleVisibility);  
68   return () =>  
69     document.removeEventListener("visibilitychange", handleVisibility);  
70 }, []);  
71  
72 const minutes = Math.floor(remaining / 60);  
73 const seconds = remaining % 60;  
74 const isWarning = remaining < 120;  
75  
76 return (  
77   <div  
78     className={`flex items-center gap-2 rounded-lg px-3 py-1.5 text-sm font-bold ${  
79       isWarning ? "bg-red-50 text-red-600" : "bg-slate-100 text-gray-700"  
80     `}  
81   >  
82     {isWarning && <AlertTriangle className="h-4 w-4" />}  
83     <Timer className="h-4 w-4" />  
84     <span>  
85       {String(minutes).padStart(2, "0")}:{String(seconds).padStart(2, "0")}  
86     </span>  
87   </div>  
88 );  
89 ];  
90  
91 // %% Helpers %%%%%%%%%%%%%%%  
92  
93 const parseBaselineOptions = (  
94   question: OnboardingQuestion  
95 ): BaselineOption[] => {  
96   if (!Array.isArray(question.options)) return [];  
97   return question.options as BaselineOption[];  
98 };  
99  
100 // %% Single Course Test %%%%%%%%%%%%%%%  
101  
102 interface SingleCourseTestProps {  
103   courseId: string;  
104   studentId: string;  
105   assessmentVersion: number;  
106   onComplete: () => void;  
107 }  
108  
109 const SingleCourseTest = ({  
110   courseId,  
111   studentId,  
112   assessmentVersion,  
113   onComplete,  
114 }: SingleCourseTestProps) => {  
115   const { data: questions = [], isLoading: questionsLoading } =  
116     useBaselineQuestions(courseId);  
117   const { data: config } = useBaselineTestConfig(courseId);  
118   const saveResponses = useSaveResponses();  
  
119   const [currentIndex, setCurrentIndex] = useState(0);  
120   const [answers, setAnswers] = useState<Record<string, number>>({});  
121   const [direction, setDirection] = useState(1);  
122   const [submitted, setSubmitted] = useState(false);  
  
123   const timeLimitSeconds = (config?.time_limit_minutes ?? 15) * 60;  
124   const currentQuestion = questions[currentIndex];  
125   const totalQuestions = questions.length;  
126   const currentAnswer = currentQuestion  
127     ? answers[currentQuestion.id] ?? null  
128     : null;  
129   const options = currentQuestion ? parseBaselineOptions(currentQuestion) : [];  
130  
131   // Group questions by CLO for display  
132   const currentCLO = currentQuestion?.clo_id ?? "";  
133  
134   const handleSubmit = useCallback(async () => {  
135     if (submitted) return;  
136     setSubmitted(true);
```

```

140 // Build responses – unanswered questions get -1 (treated as incorrect)
141 const responses = questions.map((q) => ({
142   question_id: q.id,
143   selected_option: answers[q.id] ?? -1,
144 }));
145
146 try {
147   await saveResponses.mutateAsync({
148     student_id: studentId,
149     assessment_type: "baseline",
150     assessment_version: assessmentVersion,
151     course_id: courseId,
152     responses,
153   });
154 } finally {
155   onComplete();
156 }
157 }, [
158   submitted,
159   questions,
160   answers,
161   saveResponses,
162   studentId,
163   assessmentVersion,
164   courseId,
165   onComplete,
166 ]);
167
168 const handleSelect = useCallback(
169   (optionIndex: number) => {
170     if (!currentQuestion || submitted) return;
171     setAnswers((prev) => ({ ...prev, [currentQuestion.id]: optionIndex }));
172   },
173   [currentQuestion, submitted]
174 );
175
176 const handleNext = useCallback(() => {
177   if (currentIndex < totalQuestions - 1) {
178     setDirection(1);
179     setCurrentIndex((prev) => prev + 1);
180   } else {
181     handleSubmit();
182   }
183 }, [currentIndex, totalQuestions, handleSubmit]);
184
185 const handleBack = useCallback(() => {
186   if (currentIndex > 0) {
187     setDirection(-1);
188     setCurrentIndex((prev) => prev - 1);
189   }
190 }, [currentIndex]);
191
192 if (questionsLoading) {
193   return (
194     <div className="flex items-center justify-center py-16">
195       <div className="h-8 w-8 animate-spin rounded-full border-4 border-blue-600 border-t-transparent" />
196     </div>
197   );
198 }
199
200 if (totalQuestions === 0) {
201   return (
202     <div className="py-16 text-center text-sm text-gray-500">
203       No baseline questions available for this course.
204       <Button onClick={onComplete} variant="tactile" className="mt-4">
205         Continue
206       </Button>
207     </div>
208   );
209 }
210
211 return (
212   <div className="flex flex-col items-center">
213     <div className="mb-4 flex w-full max-w-md items-center justify-between">
214       <Badge variant="outline" className="text-xs">
215         CLO: {currentCLO ? currentCLO.slice(0, 8) : "General"}
216       </Badge>
217       <AssessmentTimer
218         totalSeconds={timeLimitSeconds}
219         onExpire={handleSubmit}
220       />
221     </div>
222
223     <p className="mb-2 text-xs font-bold uppercase tracking-widest text-gray-400">
224       Question {currentIndex + 1} of {totalQuestions}
225     </p>
226
227     <div className="mb-6 h-1.5 w-full max-w-md overflow-hidden rounded-full bg-slate-100">
228       <motion.div
229         className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
230         animate={{ width: `${((currentIndex + 1) / totalQuestions) * 100}%` }}
231         transition={{ duration: 0.2 }}
232       />
233     </div>
234
235     <div className="mb-4 flex w-full max-w-md items-center justify-between">
236       <div>
237         <div>
238           <div>
239             <div>
240               <div>
241                 <div>
242                   <div>
243                     <div>

```

[illegible]

```

348         Course {currentCourseIndex + 1} of {courseIds.length}
349     </p>
350   }}
351   <SingleCourseTest
352     key={currentCourseId}
353     courseId={currentCourseId}
354     studentId={studentId}
355     assessmentVersion={assessmentVersion}
356     onComplete={handleCourseComplete}
357   />
358 </div>
359 );
360 };
361
362 export default BaselineTestStep;
363

```

FILE: src/pages/student/onboarding/CompleteProfilePage.tsx

```
TYPE: .tsx | LINES: 1-303 | SHA256: e75730e08fd46e03de8d229537d8fa17ae8b81a732ef9c6d92f9957ca551d184
```

```

import { useMemo } from "react";
import { useNavigate } from "react-router-dom";
import { motion } from "framer-motion";
import {
    Brain,
    Shield,
    BookOpen,
    Layers,
    ClipboardCheck,
    Clock,
    Star,
    ChevronRight,
    CheckCircle,
    ArrowLeft,
} from "lucide-react";
import { Button } from "@components/ui/button";
import { Card } from "@components/ui/card";
import { Badge } from "@components/ui/badge";
import { useAuth } from "@hooks/useAuth";
import { useProfileCompleteness } from "@hooks/useProfileCompleteness";
import { useStudentProfile } from "@hooks/useStudentProfile";
import {
    getRemainingDimensions,
    getEstimatedTimeMinutes,
    getProfileDimensions,
} from "@lib/profileCompleteness";
import type { ProfileCompletenessInput } from "@lib/profileCompleteness";
import type {
    BigFiveTraits,
    VARKProfile,
    SelfEfficacyProfile,
    StudyStrategyProfile,
} from "@lib/scoreCalculator";

// %% Dimension metadata %%%%%%%%%%%%%%%
const DIMENSION_META: Record<
string,
{
label: string;
icon: React.ReactNode;
description: string;
/** OnboardingStepId in the wizard URL `?step=` param */
stepId: string;
}> = {
personality: {
label: "Personality Traits",
icon: <Brain className="h-5 w-5 text-purple-500" />,
description:
        "Big Five personality assessment – understand how you learn and work",
stepId: "personality",
},
self_efficacy: {
label: "Self-Efficacy",
icon: <Shield className="h-5 w-5 text-blue-500" />,
description: "Academic confidence across different domains",
stepId: "self_efficacy",
},
study_strategy: {
label: "Study Strategies",
icon: <BookOpen className="h-5 w-5 text-green-500" />,
description:
        "Time management, elaboration, self-testing, and help-seeking habits",
stepId: "study_strategy",
},
learning_style: {
label: "Learning Style (VARK)",
icon: <Layers className="h-5 w-5 text-amber-500" />,
description: "Self-awareness exercise – discover your learning preferences",
stepId: "learning_style",
},
baseline: {
label: "Baseline Tests",
icon: <ClipboardCheck className="h-5 w-5 text-red-500" />,
description:
        "Diagnostic tests to measure your starting knowledge per course",
stepId: "baseline_select",
},
};

// %% Helper: derive completeness input from profile %%%%%%%%%%%
const deriveCompletenessInput = (

```


[illegible]

```

189 </div>
190 <div className="mt-2 h-3 w-full overflow-hidden rounded-full bg-slate-100">
191   <motion.div
192     className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
193     initial={{ width: 0 }}
194     animate={{ width: `${completeness}%` }}
195     transition={{ duration: 0.5, ease: "easeOut" }}
196   />
197 </div>
198 {remaining.length > 0 && (
199   <div className="mt-2 flex items-center gap-3 text-xs text-gray-500">
200     <span className="flex items-center gap-1">
201       <Clock className="h-3.5 w-3.5" />~{estimatedMinutes} min remaining
202     </span>
203     <span className="flex items-center gap-1">
204       <Star className="h-3.5 w-3.5 text-amber-500" />
205       Earn XP for each section
206     </span>
207   </div>
208 )}
209 </Card>
210
211 {/* Dimension List */}
212 <div className="mt-6 space-y-3">
213   {allDimensions.map((dim) => {
214     const meta = DIMENSION_META[dim.dimension];
215     if (!meta) return null;
216     const isComplete = dim.percentage >= 100;
217     const itemsLeft = dim.total - dim.completed;
218
219     return (
220       <Card
221         key={dim.dimension}
222         role={!isComplete ? "button" : undefined}
223         tabIndex={!isComplete ? 0 : undefined}
224         onClick={
225           isComplete
226             ? undefined
227             : () => navigate(`/student/onboarding?step=${meta.stepId}`)
228         }
229         onKeyDown={
230           isComplete
231             ? undefined
232             : (e) => {
233               if (e.key === "Enter" || e.key === " ") {
234                 e.preventDefault();
235                 navigate(`/student/onboarding?step=${meta.stepId}`);
236               }
237             }
238         }
239         className={`border-0 p-4 shadow-md rounded-xl transition-colors ${
240           isComplete
241             ? "bg-green-50"
242             : "bg-white hover:bg-slate-50 cursor-pointer focus:outline-none focus:ring-2 focus:ring-blue"
243         }`}
244       >
245         <div className="flex items-center gap-3">
246           <div className="flex h-10 w-10 shrink-0 items-center justify-center rounded-lg bg-slate-100">
247             {meta.icon}
248           </div>
249           <div className="flex-1">
250             <div className="flex items-center gap-2">
251               <p className="text-sm font-semibold text-gray-900">
252                 {meta.label}
253               </p>
254               {isComplete ? (
255                 <Badge className="bg-green-100 text-green-700 hover:bg-green-100">
256                   <CheckCircle className="me-1 h-3 w-3" />
257                   Complete
258                 </Badge>
259               ) : (
260                 <Badge variant="outline" className="text-[10px]">
261                   {itemsLeft} item{itemsLeft !== 1 ? "s" : ""} left
262                 </Badge>
263               )}
264             </div>
265             <p className="mt-0.5 text-xs text-gray-500">
266               {meta.description}
267             </p>
268           </div>
269           {!isComplete && (
270             <ChevronRight className="h-5 w-5 shrink-0 text-gray-400" />
271           )}
272         </div>
273
274         {/* Progress bar per dimension */}
275         {!isComplete && (
276           <div className="mt-2 h-1.5 w-full overflow-hidden rounded-full bg-slate-100">
277             <div
278               className="h-full rounded-full bg-blue-500"
279               style={{ width: `${dim.percentage}%` }}
280             />
281           </div>
282         )}
283       </Card>
284     );
285   })}
286 </div>
287
288 {completeness >= 100 && (
289   <Card className="mt-6 border-0 bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)] p-6 shadow-
290     <CheckCircle className="mx-auto h-10 w-10" />
291     <h2 className="mt-2 text-lg font-bold">Profile Complete!</h2>
292     <p className="mt-1 text-sm text-white/80">

```

```
293         You've completed all profiling dimensions. Your learning
294         experience is fully personalized.
295     </p>
296 </Card>
297 }}
298 </div>
299 );
300 };
301
302 export default CompleteProfilePage;
303
```

FILE: src/pages/student/onboarding/LearningStyleStep.tsx

```
TYPE: .tsx | LINES: 1-264 | SHA256: 9183d6fe30dd15fdcf16830ebcb970003c862a5950b9a1704edf7a48259939c4
```

[illegible]

```

90 | };
91 |
92 | // Learning style is NOT shown in Day 1 mode – delivered via micro-assessments
93 | if (isDay1) {
94 |   return (
95 |     <div className="flex flex-col items-center py-16 text-center">
96 |       <Layers className="mb-4 h-10 w-10 text-blue-400" />
97 |       <h2 className="text-lg font-bold tracking-tight text-gray-900">
98 |         {t("onboarding.learningStyle.day1.title")}
99 |       </h2>
100 |       <p className="mt-2 max-w-sm text-sm text-gray-500">
101 |         {t("onboarding.learningStyle.day1.body")}
102 |       </p>
103 |       <Button onClick={onComplete} variant="tactile" className="mt-6">
104 |         {t("onboarding.learningStyle.day1.continue")}
105 |       </Button>
106 |     </div>
107 |   );
108 | }
109 |
110 | if (isLoading) {
111 |   return (
112 |     <div className="flex items-center justify-center py-16">
113 |       <div className="h-8 w-8 animate-spin rounded-full border-4 border-blue-600 border-t-transparent" />
114 |     </div>
115 |   );
116 | }
117 |
118 | if (totalQuestions === 0) {
119 |   return (
120 |     <div className="py-16 text-center text-sm text-gray-500">
121 |       {t("onboarding.learningStyle.noQuestions")}
122 |     </div>
123 |   );
124 | }
125 |
126 | // R17 – benefit-oriented framing gates the assessment body until the
127 | // benefit + estimated time are shown and the student begins (R17.2a).
128 | if (
129 |   !shouldRenderAssessmentBody({
130 |     hasBegun,
131 |     benefits: introContent.benefits,
132 |     estimatedTime: introContent.estimatedTime,
133 |   })
134 | ) {
135 |   return (
136 |     <AssessmentIntro
137 |       icon={Layers}
138 |       content={introContent}
139 |       beginLabel={t("onboarding.assessmentIntro.begin")}
140 |       onBegin={handleBegin}
141 |     />
142 |   );
143 | }
144 |
145 | return (
146 |   <div className="flex flex-col items-center">
147 |     </* Header */>
148 |     <div className="mb-4 flex items-center gap-2">
149 |       <Layers className="h-5 w-5 text-blue-600" />
150 |       <h2 className="text-lg font-bold tracking-tight text-gray-900">
151 |         {t("onboarding.learningStyle.title")}
152 |       </h2>
153 |     </div>
154 |
155 |     </* Research disclaimer */>
156 |     <Card className="mb-6 flex flex-row items-start gap-2 border-0 bg-amber-50 p-3 shadow-none">
157 |       <AlertTriangle className="mt-0.5 h-4 w-4 shrink-0 text-amber-600" />
158 |       <p className="text-xs text-amber-800">
159 |         {t("onboarding.learningStyle.disclaimer")}
160 |       </p>
161 |     </Card>
162 |
163 |     <p className="mb-2 text-xs font-bold uppercase tracking-widest text-gray-400">
164 |       {t("onboarding.learningStyle.questionProgress", {
165 |         current: currentIndex + 1,
166 |         total: totalQuestions,
167 |       })}
168 |     </p>
169 |
170 |     </* Question progress */>
171 |     <div className="mb-6 h-1.5 w-full max-w-md overflow-hidden rounded-full bg-slate-100">
172 |       <motion.div
173 |         className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
174 |         animate={{ width: `${((currentIndex + 1) / totalQuestions) * 100}%` }}
175 |         transition={motionGate.transition({ duration: 0.2 })}
176 |       />
177 |     </div>
178 |
179 |     </* Question card */>
180 |     <AnimatePresence mode="wait" custom={direction}>
181 |       <motion.div
182 |         key={currentQuestion?.id}
183 |         custom={direction}
184 |         initial={motionGate.enter(
185 |           { opacity: 0, x: direction * 30 },
186 |           { opacity: 1, x: 0 }
187 |         )}
188 |         animate={{ opacity: 1, x: 0 }}
189 |         exit={{ opacity: 0, x: direction * -30 }}
190 |         transition={motionGate.transition({ duration: 0.2 })}
191 |         className="w-full max-w-md"
192 |       >
193 |         <Card className="border-0 bg-white p-6 shadow-md rounded-xl">

```

```

194 
```

FILE: src/pages/student/onboarding/OnboardingWizard.tsx

TYPE: .tsx | LINES: 1-489 | SHA256: 5c27927c72a42393e217d55dec3f470eb15bd8710819d5abad38e09196786dc6

[illegible]

```

30   onComplete: () => void;
31   onSkip?: () => void;
32   studentId: string;
33   assessmentVersion: number;
34 }
35
36 interface OnboardingWizardProps {
37   isDay1?: boolean;
38 }
39
40 // %% Skippable steps %%%%%%%%%%%
41
42 const SKIPPABLE_STEPS: Set<OnboardingStepId> = new Set([
43   "personality",
44   "learning_style",
45   "self_efficacy",
46   "study_strategy",
47   "baseline_select",
48 ]);
49
50 // %% Component %%%%%%%%%%%
51
52 export const OnboardingWizard = ({
53   isDay1: isDay1Prop,
54 }: OnboardingWizardProps) => {
55   const navigate = useNavigate();
56   const { t } = useTranslation("student");
57   const [searchParams, setSearchParams] = useSearchParams();
58   const { user, refetchProfile } = useAuth();
59   const studentId = user?.id ?? "";
60
61   const { data: progress, isLoading: progressLoading } =
62     useOnboardingProgress(studentId);
63   const updateProgress = useUpdateProgress(studentId);
64   const processOnboarding = useProcessOnboarding();
65   const motionGate = useGatedMotion();
66
67   // %% First-time-login detection (clause 2.14) %%%%%%%%%%%
68   // A student is on their first login if:
69   // - current_step === 'welcome' AND
70   // - all completion flags are false
71   const isFirstTimeLogin = useMemo(() => {
72     if (!progress) return true; // Default to first-time if no progress yet
73     return (
74       progress.current_step === "welcome" &&
75       !progress.personality_completed &&
76       !progress.learning_style_completed &&
77       !progress.self_efficacy_completed &&
78       !progress.study_strategy_completed &&
79       !progress.baseline_completed &&
80       !progress.day1_completed
81     );
82   }, [progress]);
83
84   // Determine if this is Day 1 phase based on first-time-login detection
85   const isDay1: boolean = isFirstTimeLogin ? true : isDay1Prop ?? false;
86
87   const steps = useMemo<readonly OnboardingStepId[]>(
88     () => (isDay1 ? DAY1_STEPS : ONBOARDING_STEPS),
89     [isDay1]
90   );
91
92   const [currentStepIndex, setCurrentStepIndex] = useState(0);
93   const [skippedSections, setSkippedSections] = useState<string[]>([]);
94   const [baselineCourseIds, setBaselineCourseIds] = useState<string[]>([]);
95   const [direction, setDirection] = useState(1);
96   const [isProcessing, setIsProcessing] = useState(false);
97
98   // Resume from last saved step (only if not first-time login)
99   useEffect(() => {
100     if (!progress) return;
101
102     // For first-time login, always start at step 0 (welcome)
103     if (isFirstTimeLogin) {
104       // eslint-disable-next-line react-hooks/set-state-in-effect -- Intentional: reset to welcome on first-ti
105       setCurrentStepIndex(0);
106       return;
107     }
108
109     // For resuming users, load from saved progress
110     const savedStep = progress.current_step;
111     const idx = steps.indexOf(savedStep);
112     if (idx >= 0) setCurrentStepIndex(idx);
113     if (progress.skipped_sections.length > 0) {
114       setSkippedSections(progress.skipped_sections);
115     }
116     if (progress.baseline_course_ids.length > 0) {
117       setBaselineCourseIds(progress.baseline_course_ids);
118     }
119   }, [progress, steps, isFirstTimeLogin]);
120
121   // Jump to specific step when ?step=<id> is provided in the URL.
122   // This lets CompleteProfilePage link directly to a dimension's step
123   // (e.g. /student/onboarding?step=personality).
124   const stepParam = searchParams.get("step") as OnboardingStepId | null;
125   useEffect(() => {
126     // Do not consume the deep link until persisted progress is available.
127     // Otherwise the URL step is applied first and then overwritten when the
128     // asynchronous resume effect resolves (observed on direct route loads).
129     if (!stepParam || !progress) return;
130     const idx = steps.indexOf(stepParam);
131     if (idx >= 0) {
132       // eslint-disable-next-line react-hooks/set-state-in-effect -- intentional: jump-to-step from URL param
133       setCurrentStepIndex(idx);

```

[illegible]

[illegible]


```

342     );
343     default:
344         return null;
345     }
346 };
347
348 if (progressLoading) {
349     return (
350         <div
351             className="fixed inset-0 z-[200] flex items-center justify-center bg-white"
352             role="status"
353             aria-label={t("onboarding.shell.loading")}
354         >
355             <Loader2 className="h-8 w-8 animate-spin text-[#0382bd]" />
356         </div>
357     );
358 }
359
360 return (
361     <div className="fixed inset-0 z-[200] flex flex-col bg-[linear-gradient(145deg,#f0fdfa_0%,#eff6ff_52%,#eef
362     /* Doodle pattern overlay – same asset used on /login for brand consistency */>
363         <div
364             className="absolute inset-0 opacity-[0.08] pointer-events-none"
365             style={{
366                 backgroundImage: "url('/doodle-background.jpg')",
367                 backgroundSize: "1200px",
368                 backgroundRepeat: "repeat",
369             }}
370             aria-hidden="true"
371         />
372
373         {/* Floating gamified accent shapes */}
374         <div
375             className="absolute -top-24 -end-24 h-96 w-96 rounded-full bg-gradient-to-br from-teal-200/40 to-blue-
376             aria-hidden="true"
377         />
378         <div
379             className="absolute -bottom-24 -start-24 h-80 w-80 rounded-full bg-gradient-to-br from-blue-200/40 to-
380             aria-hidden="true"
381         />
382
383         {/* Progress bar */}
384         <div className="relative border-b border-white/70 bg-white/72 px-5 py-3.5 backdrop-blur-md sm:px-6">
385             <div className="mx-auto flex max-w-[680px] items-center justify-between">
386                 <span className="text-xs font-bold uppercase tracking-[0.12em] text-gray-500 sm:text-sm sm:normal-ca
387                     {t("onboarding.shell.stepOf", {
388                         current: currentStepIndex + 1,
389                         total: totalSteps,
390                     })}
391                 </span>
392                 <span className="text-sm font-bold text-[#0382bd]">
393                     {progressPercent}%
394                 </span>
395             </div>
396             <div className="mx-auto mt-2 max-w-[680px]">
397                 <div
398                     className="h-1.5 w-full overflow-hidden rounded-full bg-slate-100"
399                     role="progressbar"
400                     aria-label={t("onboarding.shell.progressLabel")}
401                     aria-valuemin={0}
402                     aria-valuemax={100}
403                     aria-valuenow={progressPercent}
404                 >
405                     <motion.div
406                         className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
407                         initial={motionGate.enter(
408                             { width: 0 },
409                             { width: `${progressPercent}%` }
410                         )}
411                         animate={{ width: `${progressPercent}%` }}
412                         transition={motionGate.transition({
413                             duration: 0.3,
414                             ease: "easeOut",
415                         })}
416                     />
417                 </div>
418             </div>
419         </div>
420
421         {/* Step content */}
422         <div className="relative flex-1 overflow-auto">
423             <div className="mx-auto max-w-[680px] px-5 py-7 sm:px-6 sm:py-9">
424                 <AnimatePresence mode="wait" custom={direction}>
425                     <motion.div
426                         key={currentStep}
427                         custom={direction}
428                         initial={motionGate.enter(
429                             { opacity: 0, x: direction * 40 },
430                             { opacity: 1, x: 0 }
431                         )}
432                         animate={{ opacity: 1, x: 0 }}
433                         exit={{ opacity: 0, x: direction * -40 }}
434                         transition={motionGate.transition({ duration: 0.2 })}
435                     >
436                         {renderStep()}
437                     </motion.div>
438                 </AnimatePresence>
439             </div>
440         </div>
441
442         {/* The welcome screen owns its prototype CTA; avoid duplicating it in
443         the shell footer. Assessment steps retain Back/Skip/Next controls. */}
444         {currentStep !== "welcome" && (
445             <div className="relative border-t border-white/70 bg-white/72 px-5 py-3.5 backdrop-blur-md sm:px-6">

```



```

57 |         isSelected
58 |         ? "border-blue-500 bg-blue-50 text-blue-700"
59 |         : "border-slate-200 bg-white text-gray-700 hover:border-slate-300 hover:bg-slate-50"
60 |     }}
61 |     >
62 |     <span
63 |       className={`flex h-5 w-5 shrink-0 items-center justify-center rounded-full border-2 ${
64 |         isSelected ? "border-blue-500" : "border-slate-300"
65 |       }}`
66 |     >
67 |       {isSelected && (
68 |         <span className="h-2.5 w-2.5 rounded-full bg-blue-500" />
69 |       )}
70 |     </span>
71 |     {label}
72 |   </button>
73 | );
74 | }}
75 | </div>
76 | );
77 | };
78 |
79 | // % % Helper: pick Day 1 subset (1 per dimension for O, C, E) % % % % % % %
80 |
81 | const pickDay1Questions = (
82 |   questions: OnboardingQuestion[]
83 | ): OnboardingQuestion[] => {
84 |   const day1Dimensions = ["openness", "conscientiousness", "extraversion"];
85 |   const picked: OnboardingQuestion[] = [];
86 |   for (const dim of day1Dimensions) {
87 |     const q = questions.find((q) => q.dimension === dim);
88 |     if (q) picked.push(q);
89 |   }
90 |   return picked.slice(0, DAY1_PERSONALITY_COUNT);
91 | };
92 |
93 | // % % Component % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %
94 |
95 | export const PersonalityStep = ({
96 |   isDay1,
97 |   onComplete,
98 |   studentId,
99 |   assessmentVersion,
100 | }: WizardStepProps) => {
101 |   const { t } = useTranslation("student");
102 |   const introContent = useAssessmentIntro("personality");
103 |   const motionGate = useGatedMotion();
104 |   const { data: allQuestions = [], isLoading } = usePersonalityQuestions();
105 |   const saveResponses = useSaveResponses();
106 |
107 |   // R17.2a – gate the assessment body until the benefit + estimated-time
108 |   // intro has been shown and the student chooses to begin.
109 |   const [hasBegun, setHasBegun] = useState(false);
110 |   const handleBegin = useCallback(() => setHasBegun(true), []);
111 |
112 |   const questions = useMemo(
113 |     () => (isDay1 ? pickDay1Questions(allQuestions) : allQuestions),
114 |     [isDay1, allQuestions]
115 |   );
116 |
117 |   const [currentIndex, setCurrentIndex] = useState(0);
118 |   const [answers, setAnswers] = useState<Record<string, number>>({});
119 |   const [direction, setDirection] = useState(1);
120 |
121 |   const currentQuestion = questions[currentIndex];
122 |   const totalQuestions = questions.length;
123 |   const currentAnswer = currentQuestion
124 |     ? answers[currentQuestion.id] ?? null
125 |     : null;
126 |
127 |   const currentDimension = currentQuestion?.dimension
128 |     ? t(`onboarding.personality.dimensions.${currentQuestion.dimension}`, {
129 |       defaultValue: currentQuestion.dimension,
130 |     })
131 |     : "";
132 |
133 |   const handleSelect = useCallback(
134 |     (value: number) => {
135 |       if (!currentQuestion) return;
136 |       setAnswers((prev) => ({ ...prev, [currentQuestion.id]: value }));
137 |     },
138 |     [currentQuestion]
139 |   );
140 |
141 |   const handleNext = useCallback(async () => {
142 |     if (currentIndex < totalQuestions - 1) {
143 |       setDirection(1);
144 |       setCurrentIndex((prev) => prev + 1);
145 |     } else {
146 |       // Last question – save all responses and complete
147 |       const responses = questions.map((q) => ({
148 |         question_id: q.id,
149 |         selected_option: answers[q.id] ?? 3,
150 |       }));
151 |
152 |       await saveResponses.mutateAsync({
153 |         student_id: studentId,
154 |         assessment_type: "personality",
155 |         assessment_version: assessmentVersion,
156 |         responses,
157 |       });
158 |
159 |       onComplete();
160 |     }

```

```

161 | }, [
162 |   currentIndex,
163 |   totalQuestions,
164 |   questions,
165 |   answers,
166 |   saveResponses,
167 |   studentId,
168 |   assessmentVersion,
169 |   onComplete,
170 | ]);
171 |
172 | const handleBack = useCallback(() => {
173 |   if (currentIndex > 0) {
174 |     setDirection(-1);
175 |     setCurrentIndex((prev) => prev - 1);
176 |   }
177 | }, [currentIndex]);
178 |
179 | if (isLoading) {
180 |   return (
181 |     <div className="flex items-center justify-center py-16">
182 |       <div className="h-8 w-8 animate-spin rounded-full border-4 border-blue-600 border-t-transparent" />
183 |     </div>
184 |   );
185 | }
186 |
187 | if (totalQuestions === 0) {
188 |   return (
189 |     <div className="py-16 text-center text-sm text-gray-500">
190 |       {t("onboarding.personality.noQuestions")}
191 |     </div>
192 |   );
193 | }
194 |
195 | // R17 – benefit-oriented framing gates the assessment body until the
196 | // benefit + estimated time are shown and the student begins (R17.2a).
197 | if (
198 |   !shouldRenderAssessmentBody({
199 |     hasBegun,
200 |     benefits: introContent.benefits,
201 |     estimatedTime: introContent.estimatedTime,
202 |   })
203 | ) {
204 |   return (
205 |     <AssessmentIntro
206 |       icon={Brain}
207 |       content={introContent}
208 |       beginLabel={t("onboarding.assessmentIntro.begin")}
209 |       onBegin={handleBegin}
210 |     />
211 |   );
212 | }
213 |
214 | return (
215 |   <div className="flex flex-col items-center">
216 |     {/* Header */}
217 |     <div className="mb-6 flex items-center gap-2">
218 |       <Brain className="h-5 w-5 text-blue-600" />
219 |       <h2 className="text-lg font-bold tracking-tight text-gray-900">
220 |         {t("onboarding.personality.title")}
221 |       </h2>
222 |     </div>
223 |
224 |     <p className="mb-2 text-xs font-bold uppercase tracking-widest text-gray-400">
225 |       {t("onboarding.personality.dimensionProgress", {
226 |         dimension: currentDimension,
227 |         current: currentIndex + 1,
228 |         total: totalQuestions,
229 |       })}
230 |     </p>
231 |
232 |     {/* Question progress */}
233 |     <div className="mb-6 h-1.5 w-full max-w-md overflow-hidden rounded-full bg-slate-100">
234 |       <motion.div
235 |         className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
236 |         animate={{ width: `${((currentIndex + 1) / totalQuestions) * 100}%` }}
237 |         transition={motionGate.transition({ duration: 0.2 })}
238 |       />
239 |     </div>
240 |
241 |     {/* Question card */}
242 |     <AnimatePresence mode="wait" custom={direction}>
243 |       <motion.div
244 |         key={currentQuestion?.id}
245 |         custom={direction}
246 |         initial={motionGate.enter(
247 |           { opacity: 0, x: direction * 30 },
248 |           { opacity: 1, x: 0 }
249 |         )}
250 |         animate={{ opacity: 1, x: 0 }}
251 |         exit={{ opacity: 0, x: direction * -30 }}
252 |         transition={motionGate.transition({ duration: 0.2 })}
253 |         className="w-full max-w-md"
254 |       >
255 |         <Card className="border-0 bg-white p-6 shadow-md rounded-xl">
256 |           <p className="mb-6 text-sm font-medium text-gray-900">
257 |             {currentQuestion?.question_text}
258 |           </p>
259 |           <LikertScale
260 |             value={currentAnswer}
261 |             onChange={handleSelect}
262 |             questionId={currentQuestion?.id ?? ""}
263 |           />
264 |         </Card>

```

```

265 |         </motion.div>
266 |     </AnimatePresence>
267 |
268 |     {/* Navigation */}
269 |     <div className="mt-6 flex w-full max-w-md items-center justify-between">
270 |         <Button
271 |             variant="ghost"
272 |             onClick={handleBack}
273 |             disabled={currentIndex === 0}
274 |             className="text-gray-500"
275 |         >
276 |             {t("onboarding.personality.previous")}
277 |         </Button>
278 |         <Button
279 |             onClick={handleNext}
280 |             disabled={currentAnswer === null || saveResponses.isPending}
281 |             variant="tactile"
282 |             className="gap-1"
283 |         >
284 |             {currentIndex === totalQuestions - 1
285 |               ? saveResponses.isPending
286 |               ? t("onboarding.personality.saving")
287 |               : t("onboarding.personality.complete")
288 |               : t("onboarding.personality.next")}
289 |         </Button>
290 |     </div>
291 | </div>
292 | );
293 | };
294 |
295 | export default PersonalityStep;
296 |

```

FILE: src/pages/student/onboarding/ProfileSummaryStep.tsx

```
TYPE: .tsx | LINES: 1-292 | SHA256: 21d620d1d9cb1e44048ec719581b5208039b7bab674aa7ed6039b5ece1bd5b76
```

[illegible]

[illegible]

```

173 <Card className="border-0 bg-white p-4 shadow-md rounded-xl">
174   <div className="mb-3 flex items-center gap-2">
175     <Shield className="h-4 w-4 text-blue-600" />
176     <h3 className="text-sm font-bold text-gray-900">Self-Efficacy</h3>
177   </div>
178   {isDay1 && (
179     <p className="mb-2 text-xs text-gray-500">
180       Preliminary results – based on 2 of 6 items
181     </p>
182   )}
183   {selfEfficacy ? (
184     <div className="space-y-2">
185       {Object.entries(selfEfficacy).map(([key, value]) => (
186         <div key={key} className="flex items-center justify-between">
187           <span className="text-xs text-gray-600">
188             {EFFICACY_LABELS[key] ?? key}
189           </span>
190           <div className="flex items-center gap-2">
191             <div className="h-2 w-24 overflow-hidden rounded-full bg-slate-100">
192               <div
193                 className="h-full rounded-full bg-blue-500"
194                 style={{ width: `${value}%` }}
195               />
196             </div>
197             <span className="text-xs font-bold text-gray-700">
198               {value}%
199             </span>
200           </div>
201         </div>
202       ))}
203     </div>
204   ) : (
205     <InlineNoData />
206   )}
207 </Card>
208 }
209
210 /* VARK Learning Style – self-awareness only */
211 {learningStyleSkipped ? (
212   <SkippedSection
213     label="Learning Style (VARK)"
214     note="Available via micro-assessments"
215   />
216 ) : varkProfile ? (
217   <Card className="border-0 bg-white p-4 shadow-md rounded-xl">
218     <div className="mb-2 flex items-center gap-2">
219       {VARK_ICONS[varkProfile.dominant_style]}
220       <h3 className="text-sm font-bold text-gray-900">
221         {VARK_DESCRIPTIONS[varkProfile.dominant_style]?.label ??
222         "Learning Style"}
223       </h3>
224     </div>
225     <p className="mb-3 text-xs text-gray-500">
226       {VARK_DESCRIPTIONS[varkProfile.dominant_style]?.description}
227     </p>
228     <Card className="flex flex-row items-start gap-2 border-0 bg-amber-50 p-2.5 shadow-none">
229       <AlertTriangle className="mt-0.5 h-3.5 w-3.5 shrink-0 text-amber-600" />
230       <p className="text-[11px] text-amber-800">
231         For reflection only – not used for content matching.
232       </p>
233     </Card>
234   </Card>
235 ) : null}
236
237 /* Study Strategies */
238 {studyStrategySkipped && (
239   <SkippedSection
240     label="Study Strategies"
241     note="Available via micro-assessments"
242   />
243 )}
244 </div>
245
246 /* Confirm button */
247 <Button
248   onClick={onConfirm}
249   disabled={isProcessing}
250   variant="tactile"
251   className="mt-8 gap-2 px-8"
252 >
253   {isProcessing ? (
254     <
255       <Loader2 className="h-4 w-4 animate-spin" />
256       Processing...
257     </>
258   ) : (
259     <
260       <CheckCircle className="h-4 w-4" />
261       {isDay1 ? "Complete & Go to Dashboard" : "Confirm & Continue"}
262     </>
263   )}
264 </Button>
265
266 {isDay1 && (
267   <p className="mt-3 max-w-sm text-center text-xs text-gray-400">
268     You&apos;ll complete the remaining assessments through short daily
269     micro-assessments over the next two weeks.
270   </p>
271 )}
272 </div>
273 );
274 };
275
276 // %% Sub-component %%%%%%%%%%%%%%%

```

```

277
278 const SkippedSection = ({ label, note }: { label: string; note?: string }) => (
279   <Card className="border-0 bg-slate-50 p-4 shadow-none rounded-xl">
280     <div className="flex items-center gap-2">
281       <BarChart3 className="h-4 w-4 text-gray-400" />
282       <h3 className="text-sm font-medium text-gray-500">{label}</h3>
283       <Badge variant="outline" className="ms-auto text-[10px]">
284         Skipped
285       </Badge>
286     </div>
287     {note && <p className="mt-1 text-xs text-gray-400">{note}</p>}
288   </Card>
289 );
290
291 export default ProfileSummaryStep;
292

```

```
TYPE: .tsx | LINES: 1-362 | SHA256: 70e10915fa1c5a45da72f228ccca97f7fd9fd8cede4e3b8f5cdfffd5fb11c62b
```

```

1 import { useState, useMemo, useCallback } from "react";
2 import { motion, AnimatePresence } from "framer-motion";
3 import { useGatedMotion } from "@lib/motionGate";
4 import { Shield, Info } from "lucide-react";
5 import { useTranslation } from "react-i18next";
6 import { Button } from "@components/ui/button";
7 import { Card } from "@components/ui/card";
8 import AssessmentIntro from "@components/shared/AssessmentIntro";
9 import { useSelfEfficacyQuestions } from "@hooks/useOnboardingQuestions";
10 import { useSaveResponses } from "@hooks/useOnboardingResponses";
11 import { useAssessmentIntro } from "@hooks/useAssessmentIntro";
12 import { shouldRenderAssessmentBody } from "@lib/assessmentIntro";
13 import { DAY1_SELF_EFFICACY_COUNT } from "@lib/onboardingConstants";
14 import type { OnboardingQuestion } from "@hooks/useOnboardingQuestions";
15 import type { WizardStepProps } from "../OnboardingWizard";
16
17 // %% Likert scale labels for self-efficacy %%%%%%%%%%%
18
19 const EFFICACY_LABELS = [
20   "Not at all confident",
21   "Slightly confident",
22   "Moderately confident",
23   "Very confident",
24   "Extremely confident",
25 ] as const;
26
27 // %% Inline LikertScale (shared component created in Task 6) %%%%%%%%%%
28
29 interface LikertScaleProps {
30   value: number | null;
31   onChange: (value: number) => void;
32   questionId: string;
33   labels?: readonly string[];
34 }
35
36 const LikertScale = ({
37   value,
38   onChange,
39   questionId,
40   labels = EFFICACY_LABELS,
41 }: LikertScaleProps) => (
42   <div
43     className="flex flex-col gap-2"
44     role="radiogroup"
45     aria-label="Self-efficacy scale"
46   >
47     {labels.map((label, idx) => {
48       const optionValue = idx + 1;
49       const isSelected = value === optionValue;
50       return (
51         <button
52           key={optionValue}
53           type="button"
54           role="radio"
55           aria-checked={isSelected}
56           aria-label={label}
57           id={` ${questionId}-option-${optionValue}`}
58           onClick={() => onChange(optionValue)}
59           className={`flex items-center gap-3 rounded-lg border px-4 py-3 text-start text-sm font-medium trans
60             isSelected
61               ? "border-blue-500 bg-blue-50 text-blue-700"
62               : "border-slate-200 bg-white text-gray-700 hover:border-slate-300 hover:bg-slate-50"}
63         >
64           <span
65             className={`flex h-5 w-5 shrink-0 items-center justify-center rounded-full border-2 ${
66               isSelected ? "border-blue-500" : "border-slate-300"
67             }`}
68           />
69           {isSelected && (
70             <span className="h-2.5 w-2.5 rounded-full bg-blue-500" />
71           )}
72         </span>
73         {label}
74       </button>
75     )};
76   </div>
77 );
78
79 // %% Helper: pick Day 1 subset %%%%%%%%%%%
80
81 const DAY1_DOMAINS = [
82   "general_academic",

```


[illegible]

```

189     const responses = questions.map((q) => ({
190       question_id: q.id,
191       selected_option: answers[q.id] ?? 3,
192     }));
193
194     await saveResponses.mutateAsync({
195       student_id: studentId,
196       assessment_type: "self_efficacy",
197       assessment_version: assessmentVersion,
198       responses,
199     });
200
201     onComplete();
202   }
203 }, [
204   currentIndex,
205   totalQuestions,
206   questions,
207   answers,
208   saveResponses,
209   studentId,
210   assessmentVersion,
211   onComplete,
212 ]);
213
214 const handleBack = useCallback(() => {
215   if (currentIndex > 0) {
216     setDirection(-1);
217     setCurrentIndex((prev) => prev - 1);
218   }
219 }, [currentIndex]);
220
221 if (isLoading) {
222   return (
223     <div className="flex items-center justify-center py-16">
224       <div className="h-8 w-8 animate-spin rounded-full border-4 border-blue-600 border-t-transparent" />
225     </div>
226   );
227 }
228
229 // System issue: a query error means questions may exist but could not be
230 // loaded. Surface this distinctly from the genuine zero-data case and never
231 // show the "no questions" copy here (R11.4a, R11.4b). The student is never
232 // blocked – an explicit Continue advances the onboarding sequence.
233 if (isError) {
234   return (
235     <FallbackPanel
236       title={t("onboarding.fallback.systemIssueTitle")}
237       body={t("onboarding.fallback.systemIssueBody")}
238       continueLabel={t("onboarding.fallback.continue")}
239       onContinue={onComplete}
240     />
241   );
242 }
243
244 // Genuine zero-data: the query succeeded but the institution has no
245 // self-efficacy questions seeded. Show a non-alarming fallback (never an
246 // admin-contact error) and allow the student to continue (R11.3, R11.4).
247 if (totalQuestions === 0) {
248   return (
249     <FallbackPanel
250       title={t("onboarding.fallback.noQuestionsTitle")}
251       body={t("onboarding.fallback.noQuestionsBody")}
252       continueLabel={t("onboarding.fallback.continue")}
253       onContinue={onComplete}
254     />
255   );
256 }
257
258 // R17 – benefit-oriented framing. The assessment body is gated until the
259 // student has seen the benefits + estimated time and chosen to begin (R17.2a).
260 if (
261   !shouldRenderAssessmentBody({
262     hasBegun,
263     benefits: introContent.benefits,
264     estimatedTime: introContent.estimatedTime,
265   })
266 ) {
267   return (
268     <AssessmentIntro
269       icon={Shield}
270       content={introContent}
271       beginLabel={t("onboarding.assessmentIntro.begin")}
272       onBegin={handleBegin}
273     />
274   );
275 }
276
277 return (
278   <div className="flex flex-col items-center">
279     {/* Header */}
280     <div className="mb-6 flex items-center gap-2">
281       <Shield className="h-5 w-5 text-blue-600" />
282       <h2 className="text-lg font-bold tracking-tight text-gray-900">
283         {t("onboarding.selfEfficacy.title")}
284       </h2>
285     </div>
286
287     <p className="mb-1 max-w-md text-center text-xs text-gray-500">
288       {t("onboarding.selfEfficacy.instructions")}
289     </p>
290
291     <p className="mb-2 text-xs font-bold uppercase tracking-widest text-gray-400">
292       {t("onboarding.selfEfficacy.questionProgress", {

```

```

293 |         current: currentIndex + 1,
294 |         total: totalQuestions,
295 |     }}}
296 | </p>
297 |
298 | { /* Question progress */ }
299 | <div className="mb-6 h-1.5 w-full max-w-md overflow-hidden rounded-full bg-slate-100">
300 |   <motion.div
301 |     className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
302 |     animate={{ width: `${((currentIndex + 1) / totalQuestions) * 100}%` }}
303 |     transition={motionGate.transition({ duration: 0.2 })}
304 |   />
305 | </div>
306 |
307 | { /* Question card */ }
308 | <AnimatePresence mode="wait" custom={direction}>
309 |   <motion.div
310 |     key={currentQuestion?.id}
311 |     custom={direction}
312 |     initial={motionGate.enter(
313 |       { opacity: 0, x: direction * 30 },
314 |       { opacity: 1, x: 0 }
315 |     )}
316 |     animate={{ opacity: 1, x: 0 }}
317 |     exit={{ opacity: 0, x: direction * -30 }}
318 |     transition={motionGate.transition({ duration: 0.2 })}
319 |     className="w-full max-w-md"
320 |   >
321 |     <Card className="border-0 bg-white p-6 shadow-md rounded-xl">
322 |       <p className="mb-6 text-sm font-medium text-gray-900">
323 |         {currentQuestion?.question_text}
324 |       </p>
325 |       <LikertScale
326 |         value={currentAnswer}
327 |         onChange={handleSelect}
328 |         questionId={currentQuestion?.id ?? ""}
329 |       />
330 |     </Card>
331 |   </motion.div>
332 | </AnimatePresence>
333 |
334 | { /* Navigation */ }
335 | <div className="mt-6 flex w-full max-w-md items-center justify-between">
336 |   <Button
337 |     variant="ghost"
338 |     onClick={handleBack}
339 |     disabled={currentIndex === 0}
340 |     className="text-gray-500"
341 |   >
342 |     {t("onboarding.selfEfficacy.previous")}
343 |   </Button>
344 |   <Button
345 |     onClick={handleNext}
346 |     disabled={currentAnswer === null || saveResponses.isPending}
347 |     variant="tactile"
348 |     className="gap-1"
349 |   >
350 |     {currentIndex === totalQuestions - 1
351 |       ? saveResponses.isPending
352 |       ? t("onboarding.selfEfficacy.saving")
353 |       : t("onboarding.selfEfficacy.complete")
354 |       : t("onboarding.selfEfficacy.next")}
355 |   </Button>
356 | </div>
357 | </div>
358 | );
359 | };
360 |
361 | export default SelfEfficacyStep;
362 |

```

FILE: src/pages/student/onboarding/StudyStrategyStep.tsx

TYPE: .tsx | LINES: 1-286 | SHA256: af916d1aff9a3e2d353ba7a75ac6ea0566ae71fc77a86b8fd7d1858ac78bdc0e

```

1 | import { useState, useCallback } from "react";
2 | import { motion, AnimatePresence } from "framer-motion";
3 | import { useGatedMotion } from "@/lib/motionGate";
4 | import { BookOpen } from "lucide-react";
5 | import { useTranslation } from "react-i18next";
6 | import { Button } from "@components/ui/button";
7 | import { Card } from "@components/ui/card";
8 | import AssessmentIntro from "@components/shared/AssessmentIntro";
9 | import { useStudyStrategyQuestions } from "@hooks/useOnboardingQuestions";
10 | import { useSaveResponses } from "@hooks/useOnboardingResponses";
11 | import { useAssessmentIntro } from "@hooks/useAssessmentIntro";
12 | import { shouldRenderAssessmentBody } from "@lib/assessmentIntro";
13 | import type { WizardStepProps } from "../OnboardingWizard";
14 |
15 | const STRATEGY_KEYS = [
16 |   "never",
17 |   "rarely",
18 |   "sometimes",
19 |   "often",
20 |   "always",
21 | ] as const;
22 |
23 | interface LikertScaleProps {
24 |   value: number | null;
25 |   onChange: (value: number) => void;
26 |   questionId: string;
27 | }
28 |
29 | const LikertScale = ({ value, onChange, questionId }: LikertScaleProps) => {
30 |   const { t } = useTranslation("student");

```

```

31 | return (
32 |   <div
33 |     className="flex flex-col gap-2"
34 |     role="radiogroup"
35 |     aria-label={t("onboarding.studyStrategy.scaleLabel")}
36 |   >
37 |     {STRATEGY_KEYS.map((labelKey, idx) => {
38 |       const optionValue = idx + 1;
39 |       const isSelected = value === optionValue;
40 |       const label = t(`onboarding.studyStrategy.likert.${labelKey}`);
41 |       return (
42 |         <button
43 |           key={optionValue}
44 |           type="button"
45 |           role="radio"
46 |           aria-checked={isSelected}
47 |           aria-label={label}
48 |           id={`_${questionId}-option-${optionValue}`}
49 |           onClick={() => onChange(optionValue)}
50 |           className={`flex items-center gap-3 rounded-lg border px-4 py-3 text-start text-sm font-medium tra
51 |             isSelected
52 |               ? "border-blue-500 bg-blue-50 text-blue-700"
53 |               : "border-slate-200 bg-white text-gray-700 hover:border-slate-300 hover:bg-slate-50"
54 |             `}
55 |         >
56 |           <span
57 |             className={`flex h-5 w-5 shrink-0 items-center justify-center rounded-full border-2 ${
58 |               isSelected ? "border-blue-500" : "border-slate-300"
59 |             }`}
60 |           >
61 |             {isSelected && (
62 |               <span className="h-2.5 w-2.5 rounded-full bg-blue-500" />
63 |             )}
64 |           </span>
65 |           {label}
66 |         </button>
67 |       );
68 |     })}
69 |   </div>
70 | );
71 | };
72 |
73 | export const StudyStrategyStep = ({
74 |   isDay1,
75 |   onComplete,
76 |   studentId,
77 |   assessmentVersion,
78 | }: WizardStepProps) => {
79 |   const { t } = useTranslation("student");
80 |   const introContent = useAssessmentIntro("study_strategy");
81 |   const motionGate = useGatedMotion();
82 |   const { data: questions = [], isLoading } = useStudyStrategyQuestions();
83 |   const saveResponses = useSaveResponses();
84 |
85 |   // R17.2a – gate the assessment body until the benefit + estimated-time
86 |   // intro is shown and the student begins.
87 |   const [hasBegun, setHasBegun] = useState(false);
88 |   const handleBegin = useCallback(() => setHasBegun(true), []);
89 |
90 |   const [currentIndex, setCurrentIndex] = useState(0);
91 |   const [answers, setAnswers] = useState<Record<string, number>>({});
92 |   const [direction, setDirection] = useState(1);
93 |
94 |   const currentQuestion = questions[currentIndex];
95 |   const totalQuestions = questions.length;
96 |   const currentAnswer = currentQuestion
97 |     ? answers[currentQuestion.id] ?? null
98 |     : null;
99 |
100 |   const currentDimension = currentQuestion?.dimension
101 |     ? t(`onboarding.studyStrategy.dimensions.${currentQuestion.dimension}`, {
102 |       defaultValue: currentQuestion.dimension,
103 |     })
104 |     : "";
105 |
106 |   const handleSelect = useCallback(
107 |     (value: number) => {
108 |       if (!currentQuestion) return;
109 |       setAnswers((prev) => ({ ...prev, [currentQuestion.id]: value }));
110 |     },
111 |     [currentQuestion]
112 |   );
113 |
114 |   const handleNext = useCallback(async () => {
115 |     if (currentIndex < totalQuestions - 1) {
116 |       setDirection(1);
117 |       setCurrentIndex((prev) => prev + 1);
118 |     } else {
119 |       const responses = questions.map((q) => ({
120 |         question_id: q.id,
121 |         selected_option: answers[q.id] ?? 3,
122 |       }));
123 |
124 |       await saveResponses.mutateAsync({
125 |         student_id: studentId,
126 |         assessment_type: "study_strategy",
127 |         assessment_version: assessmentVersion,
128 |         responses,
129 |       });
130 |
131 |       onComplete();
132 |     }
133 |   }, [
134 |     currentIndex,

```

```

135 |     totalQuestions,
136 |     questions,
137 |     answers,
138 |     saveResponses,
139 |     studentId,
140 |     assessmentVersion,
141 |     onComplete,
142 |   ]);
143 |
144 |   const handleBack = useCallback(() => {
145 |     if (currentIndex > 0) {
146 |       setDirection(-1);
147 |       setCurrentIndex((prev) => prev - 1);
148 |     }
149 |   }, [currentIndex]);
150 |
151 |   // Study strategy is NOT shown in Day 1 mode – delivered via micro-assessments
152 |   if (isDay1) {
153 |     return (
154 |       <div className="flex flex-col items-center py-16 text-center">
155 |         <BookOpen className="mb-4 h-10 w-10 text-blue-400" />
156 |         <h2 className="text-lg font-bold tracking-tight text-gray-900">
157 |           {t("onboarding.studyStrategy.day1.title")}
158 |         </h2>
159 |         <p className="mt-2 max-w-sm text-sm text-gray-500">
160 |           {t("onboarding.studyStrategy.day1.body")}
161 |         </p>
162 |         <Button onClick={onComplete} variant="tactile" className="mt-6">
163 |           {t("onboarding.studyStrategy.day1.continue")}
164 |         </Button>
165 |       </div>
166 |     );
167 |   }
168 |
169 |   if (isLoading) {
170 |     return (
171 |       <div className="flex items-center justify-center py-16">
172 |         <div className="h-8 w-8 animate-spin rounded-full border-4 border-blue-600 border-t-transparent" />
173 |       </div>
174 |     );
175 |   }
176 |
177 |   if (totalQuestions === 0) {
178 |     return (
179 |       <div className="py-16 text-center text-sm text-gray-500">
180 |         {t("onboarding.studyStrategy.noQuestions")}
181 |       </div>
182 |     );
183 |   }
184 |
185 |   // R17 – benefit-oriented framing gates the assessment body until the
186 |   // benefit + estimated time are shown and the student begins (R17.2a).
187 |   if (
188 |     !shouldRenderAssessmentBody({
189 |       hasBegun,
190 |       benefits: introContent.benefits,
191 |       estimatedTime: introContent.estimatedTime,
192 |     })
193 |   ) {
194 |     return (
195 |       <AssessmentIntro
196 |         icon={BookOpen}
197 |         content={introContent}
198 |         beginLabel={t("onboarding.assessmentIntro.begin")}
199 |         onBegin={handleBegin}
200 |       />
201 |     );
202 |   }
203 |
204 |   return (
205 |     <div className="flex flex-col items-center">
206 |       <div className="mb-6 flex items-center gap-2">
207 |         <BookOpen className="h-5 w-5 text-blue-600" />
208 |         <h2 className="text-lg font-bold tracking-tight text-gray-900">
209 |           {t("onboarding.studyStrategy.title")}
210 |         </h2>
211 |       </div>
212 |
213 |       <p className="mb-1 max-w-md text-center text-xs text-gray-500">
214 |         {t("onboarding.studyStrategy.instructions")}
215 |       </p>
216 |
217 |       <p className="mb-2 text-xs font-bold uppercase tracking-widest text-gray-400">
218 |         {t("onboarding.studyStrategy.dimensionProgress", {
219 |           dimension: currentDimension,
220 |           current: currentIndex + 1,
221 |           total: totalQuestions,
222 |         })}
223 |     </p>
224 |
225 |     <div className="mb-6 h-1.5 w-full max-w-md overflow-hidden rounded-full bg-slate-100">
226 |       <motion.div
227 |         className="h-full rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]"
228 |         animate={{ width: `${((currentIndex + 1) / totalQuestions) * 100}%` }}
229 |         transition={motionGate.transition({ duration: 0.2 })}
230 |       />
231 |     </div>
232 |
233 |     <AnimatePresence mode="wait" custom={direction}>
234 |       <motion.div
235 |         key={currentQuestion?.id}
236 |         custom={direction}
237 |         initial={motionGate.enter(
238 |           { opacity: 0, x: direction * 30 },

```

```

239     { opacity: 1, x: 0 }
240   ))
241   animate={{ opacity: 1, x: 0 }}
242   exit={{ opacity: 0, x: direction * -30 }}
243   transition={motionGate.transition({ duration: 0.2 })}
244   className="w-full max-w-md"
245   >
246     <Card className="border-0 bg-white p-6 shadow-md rounded-xl">
247       <p className="mb-6 text-sm font-medium text-gray-900">
248         {currentQuestion?.question_text}
249       </p>
250       <LikertScale
251         value={currentAnswer}
252         onChange={handleSelect}
253         questionId={currentQuestion?.id ?? ""}
254       />
255     </Card>
256   </motion.div>
257 </AnimatePresence>
258
259 <div className="mt-6 flex w-full max-w-md items-center justify-between">
260   <Button
261     variant="ghost"
262     onClick={handleBack}
263     disabled={currentIndex === 0}
264     className="text-gray-500"
265   >
266     {t("onboarding.studyStrategy.previous")}
267   </Button>
268   <Button
269     onClick={handleNext}
270     disabled={currentAnswer === null || saveResponses.isPending}
271     variant="tactile"
272     className="gap-1"
273   >
274     {currentIndex === totalQuestions - 1
275       ? saveResponses.isPending
276       ? t("onboarding.studyStrategy.saving")
277       : t("onboarding.studyStrategy.complete")
278       : t("onboarding.studyStrategy.next")}
279   </Button>
280 </div>
281 </div>
282 );
283 };
284
285 export default StudyStrategyStep;
286

```

FILE: src/pages/student/onboarding/WelcomeStep.tsx

TYPE: .tsx | LINES: 1-127 | SHA256: 5b25eaf47c78ec8b08e67e424c78409893b78071da196466ba9696e7d29d13d3

[illegible]

[illegible]

FILE: src/pages/student/planner/FocusModePage.tsx

[illegible]

[illegible]

[illegible]

FILE: src/pages/student/planner/StarterWeekPlanPage.tsx

TYPE: .tsx | LINES: 1-448 | SHA256: bb19146c28648cef3994d22072830d8b7a71dddf1de60701f302c24fbb4f753c

```

1 import { useNavigate } from "react-router-dom";
2 import { Badge } from "@components/ui/badge";
3 import { Button } from "@components/ui/button";
4 import { PCard, Shimmer } from "@design-system";
5 import GoalSuggestionPanel from "@components/shared/GoalSuggestionPanel";
6 import SmartGoalForm from "@components/shared/SmartGoalForm";
7 import { useAuth } from "@hooks/useAuth";
8 import {
9   useStarterWeekSessions,
10  useUpdateSessionStatus,
11 } from "@hooks/useStarterWeekPlan";
12 import {
13   useGoalSuggestions,
14   useAcceptGoal,
15   useDismissGoal,
16   useGenerateGoalSuggestions,
17 } from "@hooks/useGoalSuggestions";
18 import { useCourses } from "@hooks/useCourses";
19 import {
20   CalendarDays,
21   Clock,
22   CheckCircle,
23   Play,
24   X,
25   Pencil,
26   BookOpen,
27   FlaskConical,
28   RotateCcw,
29   Compass,
30   Sparkles,
31   ArrowLeft,
32   Target,
33 } from "lucide-react";
34 import {
35   format,
36   startOfWeek,
37   differenceInDays,
38   parseISO,
39   isValid,
40 } from "date-fns";
41 import { useState } from "react";
42 import type {
43   StarterWeekSession,

```

[illegible]

[illegible]

```

252 |     const validDates = sessions
253 |       .map((s) => s.suggested_date)
254 |       .filter((d): d is string => !!d)
255 |       .map((d) => parseISO(d))
256 |       .filter((d) => isValid(d));
257 |     if (validDates.length === 0) return false;
258 |     const earliest = validDates.reduce(
259 |       (min, d) => (d < min ? d : min),
260 |       validDates[0]!
261 |     );
262 |     return differenceInDays(new Date(), earliest) >= 7;
263 |   })();
264 |
265 |   const completedCount =
266 |     sessions?.filter((s) => s.status === "completed").length ?? 0;
267 |   const totalCount = sessions?.length ?? 0;
268 |   const completedMinutes =
269 |     sessions
270 |       ?.filter((s) => s.status === "completed")
271 |       .reduce((sum, s) => sum + s.duration_minutes, 0) ?? 0;
272 |
273 |   const courseOptions = (coursesData?.data ?? []).map((c) => ({
274 |     id: c.id,
275 |     name: c.name,
276 |   }));
277 |
278 |   return (
279 |     <div className="space-y-6">
280 |       { /* Header */ }
281 |       <div className="flex items-center gap-3">
282 |         <Button
283 |           variant="ghost"
284 |           size="sm"
285 |           onClick={() => navigate("/student/dashboard")}
286 |           aria-label="Back to dashboard"
287 |         >
288 |           <ArrowLeft className="h-4 w-4" />
289 |         </Button>
290 |         <h1 className="text-2xl font-bold tracking-tight">
291 |           {isPostWeek ? "Starter Week Summary" : "Your Starter Week Plan"}
292 |         </h1>
293 |       </div>
294 |
295 |       { /* Post-week summary */ }
296 |       {isPostWeek && (
297 |         <PCard className="p-6 space-y-4">
298 |           <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
299 |             <div>
300 |               <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
301 |                 Sessions
302 |               </p>
303 |               <p className="text-2xl font-black">
304 |                 {completedCount}/{totalCount}
305 |               </p>
306 |             </div>
307 |             <div>
308 |               <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
309 |                 Completion
310 |               </p>
311 |               <p className="text-2xl font-black">
312 |                 {totalCount > 0
313 |                   ? Math.round((completedCount / totalCount) * 100)
314 |                   : 0}
315 |                 %
316 |               </p>
317 |             </div>
318 |             <div>
319 |               <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
320 |                 Study Time
321 |               </p>
322 |               <p className="text-2xl font-black">{completedMinutes}m</p>
323 |             </div>
324 |             <div>
325 |               <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
326 |                 XP Earned
327 |               </p>
328 |               <p className="text-2xl font-black text-amber-600">
329 |                 {completedCount * 15}
330 |               </p>
331 |             </div>
332 |           </div>
333 |         </PCard>
334 |       )}
335 |
336 |       { /* Sessions */ }
337 |       {isLoading ? (
338 |         <div className="space-y-3">
339 |           {[1, 2, 3].map((i) => (
340 |             <Shimmer key={i} className="h-32 rounded-xl" />
341 |           ))}
342 |         </div>
343 |       ) : (
344 |         <div className="space-y-3">
345 |           {(sessions ?? []).map((session) => (
346 |             <SessionCard
347 |               key={session.id}
348 |               session={session}
349 |               onStatusChange={handleStatusChange}
350 |               isPending={updateStatus.isPending}
351 |             />
352 |           ))}
353 |           {(sessions ?? []).length === 0 && (
354 |             <PCard className="p-8 text-center">
355 |               <p className="text-sm text-gray-500">

```

```

356 |         No starter week sessions generated yet.
357 |     </p>
358 | </PCard>
359 |   )}
360 | </div>
361 | )}
362 |
363 | { /* Goal Suggestions Section */}
364 | <div className="space-y-4">
365 |   <div className="flex items-center justify-between">
366 |     <div className="flex items-center gap-2">
367 |       <Target className="h-5 w-5 text-blue-600" />
368 |       <h2 className="text-lg font-bold tracking-tight">Weekly Goals</h2>
369 |     </div>
370 |     {goalSuggestions.length === 0 && (
371 |       <Button
372 |         size="sm"
373 |         onClick={handleGenerateGoals}
374 |         disabled={generateGoals.isPending}
375 |         variant="tactile"
376 |         className="text-xs font-semibold"
377 |       >
378 |         <Sparkles className="h-3 w-3" />
379 |         {generateGoals.isPending ? "Generating..." : "Get Suggestions"}
380 |       </Button>
381 |     )}
382 |   </div>
383 |
384 |   <GoalSuggestionPanel
385 |     suggestions={goalSuggestions.map((g) => ({
386 |       id: g.id,
387 |       goal_text: g.goal_text,
388 |       difficulty: g.difficulty as GoalDifficulty,
389 |       cohort_completion_rate: g.cohort_completion_rate,
390 |       status: g.status,
391 |     }))}
392 |     onAccept={(id) =>
393 |       acceptGoal.mutate(
394 |         { id, studentId, weekStart },
395 |         {
396 |           onSuccess: () => toast.success("Goal accepted"),
397 |           onError: (err) =>
398 |             toast.error(`Failed to accept goal: ${err.message}`),
399 |         }
400 |       )
401 |     }
402 |     onEdit={() => {
403 |       setShowSmartForm(true);
404 |     }}
405 |     onDismiss={(id) =>
406 |       dismissGoal.mutate(
407 |         { id, studentId, weekStart },
408 |         {
409 |           onSuccess: () => toast.success("Goal dismissed"),
410 |           onError: (err) =>
411 |             toast.error(`Failed to dismiss goal: ${err.message}`),
412 |         }
413 |       )
414 |     }
415 |     isLoading={goalsLoading || generateGoals.isPending}
416 |   />
417 |
418 |   { /* SMART Goal Form */}
419 |   {showSmartForm && (
420 |     <SmartGoalForm
421 |       courses={courseOptions}
422 |       onSubmit={(data) => {
423 |         toast.success(
424 |           "Goal created: " + data.composedText.slice(0, 60) + "..."
425 |         );
426 |         setShowSmartForm(false);
427 |       }}
428 |     />
429 |   )}
430 |
431 |   {!showSmartForm && (
432 |     <Button
433 |       variant="outline"
434 |       size="sm"
435 |       onClick={() => setShowSmartForm(true)}
436 |       className="text-xs"
437 |     >
438 |       <Pencil className="h-3 w-3" />
439 |       Create Custom Goal (SMART Template)
440 |     </Button>
441 |   )}
442 | </div>
443 | </div>
444 | );
445 | };
446 |
447 | export default StarterWeekPlanPage;
448 |

```

FILE: [src/pages/student/planner/TodayViewPage.tsx](#)

TYPE: .tsx | LINES: 1-466 | SHA256: 0c629a9abb9ec8219eec8cf95fc78f38338342a4209ae3ae0dc1a17948f99954

```

1 | // =====
2 | // TodayViewPage – Main page composing: DailyProgressSummary, TodayTimeline,
3 | // Quick Add task button, Start Unplanned Session button, Missed Reviews section,
4 | // and today's scheduled reviews
5 | // =====
6 |
7 | import { useState, useCallback, useMemo } from "react";

```

[illegible]

[illegible]

[illegible]


```

320 {missedReviews.map((review) => (
321   <div
322     key={review.id}
323     role="listitem"
324     className="flex items-center justify-between gap-3 rounded-lg border border-red-200 bg-white p
325   >
326     <div className="flex-1 min-w-0 space-y-1">
327       <div className="flex items-center gap-2 flex-wrap">
328         <ReviewSessionBadge
329           intervalDays={review.intervalDays}
330           status={review.status}
331         />
332         <span className="text-[10px] font-bold tracking-wide uppercase text-red-600 bg-red-100 bor
333           Missed Review
334         />
335       </div>
336       <p className="text-xs font-medium text-slate-700 line-clamp-1">
337         CLO: {review.cloId}
338       </p>
339       <p className="text-[11px] text-slate-400">
340         Due: {review.reviewDate}
341       </p>
342     </div>
343     <div className="flex items-center gap-1.5 shrink-0">
344       <Button
345         size="sm"
346         variant="tactile"
347         className="h-7 gap-1 text-[11px]"
348         onClick={() => handleStartReview(review)}
349         disabled={createReviewSession.isPending}
350       >
351         <Play className="h-3 w-3" />
352         Start
353       </Button>
354       <Button
355         variant="outline"
356         size="sm"
357         className="h-7 gap-1 text-[11px]"
358         onClick={() => handleSkipReview(review.id)}
359         disabled={skipReview.isPending}
360       >
361         <SkipForward className="h-3 w-3" />
362         Skip
363       </Button>
364     </div>
365   </div>
366   </div>
367 </PCard>
368 </div>
369 </div>
370 </div>
371 </div>
372 </div>
373 </div>
374 </div>
375 </div>
376 </div>
377 </div>
378 </div>
379 </div>
380 </div>
381 </div>
382 </div>
383 </div>
384 </div>
385 </div>
386 </div>
387 </div>
388 </div>
389 </div>
390 </div>
391 </div>
392 </div>
393 </div>
394 </div>
395 </div>
396 </div>
397 </div>
398 </div>
399 </div>
400 </div>
401 </div>
402 </div>
403 </div>
404 </div>
405 </div>
406 </div>
407 </div>
408 </div>
409 </div>
410 </div>
411 </div>
412 </div>
413 </div>
414 </div>
415 </div>
416 </div>
417 </div>
418 </div>
419 </div>
420 </div>
421 </div>
422 </div>
423 </div>

```

```

424 |         </div>
425 |     </div>
426 |     )})
427 | </div>
428 | </PCard>
429 | })
430 |
431 | { /* Today Timeline */
432 | <TodayTimeline
433 |   sessions={sessions}
434 |   tasks={tasks}
435 |   deadlines={deadlines}
436 |   habits={habits}
437 |   onSessionStart={handleSessionStart}
438 |   onSessionEdit={handleSessionEdit}
439 |   onTaskToggle={handleTaskToggle}
440 |   onTaskEdit={handleTaskEdit}
441 |   onTaskDelete={handleTaskDelete}
442 | />
443 |
444 | { /* Quick Add Task Dialog */
445 | <CreateTaskDialog
446 |   open={quickAddOpen}
447 |   onOpenChange={setQuickAddOpen}
448 |   defaultDate={todayStr}
449 |   courses={courseOptions}
450 |   onSubmit={handleQuickAddSubmit}
451 |   isPending={createTask.isPending}
452 | />
453 | <CreateSessionDialog
454 |   open={sessionDialogOpen}
455 |   onOpenChange={setSessionDialogOpen}
456 |   defaultDate={todayStr}
457 |   courses={courseOptions}
458 |   onSubmit={handleCreateSession}
459 |   isPending={createSession.isPending}
460 | />
461 | </div>
462 | );
463 | };
464 |
465 | export default TodayViewPage;
466 |

```

FILE: [src/pages/student/planner/WeeklyPlannerPage.tsx](#)

TYPE: .tsx | LINES: 1-523 | SHA256: 7d4036def62ab33979e7b23680b2323fc35c560cfa9d7d0a8f7d5d64314e1d8b

```

1 | // =====
2 | // WeeklyPlannerPage - Main page composing: week navigation,
3 | // WeeklyCalendarGrid, WeeklyGoalPanel, tabs for Check Progress and Reflect
4 | // =====
5 |
6 | import { useState, useMemo, useCallback } from "react";
7 | import { useNavigate } from "react-router-dom";
8 | import { useTranslation } from "react-i18next";
9 | import { format, parseISO, addDays } from "date-fns";
10 | import { Button } from "@components/ui/button";
11 | import { Tabs, TabList, TabTrigger, TabContent } from "@components/ui/tabs";
12 | import WeeklyCalendarGrid from "@components/shared/WeeklyCalendarGrid";
13 | import WeeklyGoalPanel from "@components/shared/WeeklyGoalPanel";
14 | import ProgressSummaryPanel from "@components/shared/ProgressSummaryPanel";
15 | import CourseStudyBreakdown from "@components/shared/CourseStudyBreakdown";
16 | import StudyTimeChart from "@components/shared/StudyTimeChart";
17 | import WeeklyReflectionPanel from "@components/shared/WeeklyReflectionPanel";
18 | import CreateSessionDialog from "@components/shared/CreateSessionDialog";
19 | import CreateTaskDialog from "@components/shared/CreateTaskDialog";
20 | import { Shimmer } from "@design-system";
21 | import { useAuth } from "@hooks/useAuth";
22 | import { useWeeklyPlannerData } from "@hooks/useWeeklyPlanner";
23 | import { useStudentCourses } from "@hooks/useStudentCourses";
24 | import { useWeeklyProgressSummary } from "@hooks/useWeeklyProgress";
25 | import { useStudyTimeTrend } from "@hooks/useStudyTimeAnalytics";
26 | import { useCreateStudySession } from "@hooks/useStudySessions";
27 | import {
28 |   useCreatePlannerTask,
29 |   useCompleteTask,
30 |   useDeletePlannerTask,
31 | } from "@hooks/usePlannerTasks";
32 | import { useSaveWeeklyGoals } from "@hooks/useWeeklyGoals";
33 | import { useSaveWeeklyReflection } from "@hooks/useSessionReflections";
34 | import {
35 |   useMonthlyDigest,
36 |   useShareDigest,
37 |   useRevokeDigestShare,
38 | } from "@hooks/useReflectionDigest";
39 | import ReflectionDigestCard from "@components/shared/ReflectionDigestCard";
40 | import {
41 |   getWeekStartDate,
42 |   isWeekInPast,
43 |   calculateGoalProgress,
44 | } from "@lib/plannerUtils";
45 | import {
46 |   buildPlannerWeek,
47 |   getExampleGoals,
48 |   getPlannerLocalizationState,
49 |   type SuggestionCourse,
50 | } from "@lib/weeklyPlannerContent";
51 | import i18n from "@lib/i18n";
52 | import type {
53 |   WeekDay,
54 |   StudySession,
55 |   PlannerTask,
56 |   GoalProgress,
57 |   SuggestedStudySession,

```

[illegible]

[illegible]

[illegible]

```

370         onClick={() => {
371             setSelectedDate(todayStr);
372             setSessionDialogOpen(true);
373         }}
374     >
375         <Plus className="h-3.5 w-3.5" />
376         {t("planner.actions.startSession")}
377     </Button>
378 </>
379 ))}
380 </div>
381 </div>
382
383 {/* Calendar Grid */}
384 <WeeklyCalendarGrid
385   weekData={weekData}
386   today={todayStr}
387   onSessionStart={handleSessionStart}
388   onSessionEdit={handleSessionEdit}
389   onTaskToggle={handleTaskToggle}
390   onTaskEdit={handleTaskEdit}
391   onTaskDelete={handleTaskDelete}
392   onDayClick={handleDayClick}
393   onPlanSuggestion={actionsEnabled ? handlePlanSuggestion : undefined}
394 />
395
396 {/* Goals + Tabs Row */}
397 <div className="grid gap-6 lg:grid-cols-3">
398   {/* Weekly Goals */}
399   <div className="lg:col-span-1">
400     <WeeklyGoalPanel
401       goals={goals}
402       progress={goalProgress}
403       weekStartDate={currentWeekStart}
404       onSave={({goalInputs}) => saveGoals.mutate(goalInputs)}
405       isEditable={!isPast && actionsEnabled}
406       isPending={saveGoals.isPending}
407       exampleGoals={exampleGoals}
408       exampleGoalsCopy={exampleGoalsCopy}
409     />
410   </div>
411
412   {/* Check Progress / Reflect Tabs */}
413   <div className="lg:col-span-2">
414     <PCard className="overflow-hidden">
415       <Tabs defaultValue="progress">
416         <div className="border-b px-6 py-3">
417           <TabList className="gap-2 bg-transparent p-0">
418             <TabTrigger
419               value="progress"
420               className="rounded-xl px-4 py-1.5 text-sm font-medium data-[state=active]:bg-blue-600 data-
421             >
422               <BarChart3 className="me-1.5 h-4 w-4" />
423               Check Progress
424             </TabTrigger>
425             <TabTrigger
426               value="reflect"
427               className="rounded-xl px-4 py-1.5 text-sm font-medium data-[state=active]:bg-blue-600 data-
428             >
429               <BookOpen className="me-1.5 h-4 w-4" />
430               Reflect
431             </TabTrigger>
432           </TabList>
433         </div>
434
435         <TabContent value="progress" className="p-6">
436           <div className="space-y-6">
437             {isProgressLoading ? (
438               <Shimmer className="h-48 rounded-xl" />
439             ) : (
440               <ProgressSummaryPanel
441                 summary={weeklyProgress}
442                 goals={progressGoals}
443               />
444             )}
445
446             {/* Course Study Breakdown */}
447             {!isProgressLoading &&
448               weeklyProgress.courseBreakdown.length > 0 && (
449                 <CourseStudyBreakdown
450                   data={weeklyProgress.courseBreakdown}
451                 />
452             )}
453
454             {/* Study Time Trends */}
455             {isTrendLoading ? (
456               <Shimmer className="h-64 rounded-xl" />
457             ) : (
458               <StudyTimeChart
459                 data={studyTimeTrendData}
460                 averageMinutesPerWeek={averageMinutesPerWeek}
461               />
462             )}
463           </div>
464         </TabContent>
465
466         <TabContent value="reflect" className="p-6">
467           <div className="space-y-6">
468             <WeeklyReflectionPanel
469               weekStartDate={currentWeekStart}
470               onSave={({content}) =>
471                 saveWeeklyReflection.mutate({
472                   content,
473                   weekStartDate: currentWeekStart,

```

```

474 |         })
475 |     }
476 |     isPending={saveWeeklyReflection.isPending}
477 | }
478 |
479 | { /* Monthly Insights */
480 | {monthlyDigest && (
481 |   <ReflectionDigestCard
482 |     digest={monthlyDigest}
483 |     onShare={({digestId, role}) =>
484 |       shareDigest.mutate({ digestId, role })
485 |     }
486 |     onRevokeShare={({digestId, role}) =>
487 |       revokeDigestShare.mutate({ digestId, role })
488 |     }
489 |     isSharing={
490 |       shareDigest.isPending || revokeDigestShare.isPending
491 |     }
492 |   )}
493 | }
494 | </div>
495 | </TabsContent>
496 | </Tabs>
497 | </PCard>
498 | </div>
499 | </div>
500 |
501 | { /* Dialogs */
502 | <CreateSessionDialog
503 |   open={sessionDialogOpen}
504 |   onOpenChange={setSessionDialogOpen}
505 |   defaultDate={selectedDate}
506 |   courses={suggestionCourses}
507 |   onSubmit={handleCreateSession}
508 |   isPending={createSession.isPending}
509 | />
510 | <CreateTaskDialog
511 |   open={taskDialogOpen}
512 |   onOpenChange={setTaskDialogOpen}
513 |   defaultDate={selectedDate}
514 |   courses={suggestionCourses}
515 |   onSubmit={handleCreateTask}
516 |   isPending={createTask.isPending}
517 | />
518 | </div>
519 | );
520 | };
521 |
522 | export default WeeklyPlannerPage;
523 |

```

FILE: [src/pages/student/portfolio/StudentPortfolio.tsx](#)

TYPE: .tsx | LINES: 1-10 | SHA256: 36346e2fb876c8ff6613145eed3dbeec3e4e0acc3bea0bf2f401b4097ace376c

```

1 | // =====
2 | // StudentPortfolio - production portfolio page (redesigned UI)
3 | // =====
4 | // Implementation lives in `StudentPortfolioNew`, re-exported here so the route
5 | // path stays stable. Legacy page and its feature-flag wrapper were removed in
6 | // the UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "./StudentPortfolioNew";
10 |

```

FILE: [src/pages/student/portfolio/StudentPortfolioNew.tsx](#)

TYPE: .tsx | LINES: 1-477 | SHA256: 6d9492851fe90e0b48967e999a777de24f5e5e41f6fd848dde959b9c73a8766b

```

1 | // =====
2 | // StudentPortfolioNew - redesigned student portfolio (P3, spec task 3.1)
3 | // =====
4 | //
5 | // Detail/analytics-archetype portfolio gated behind `newUiModules` (see the
6 | // wrapper in StudentPortfolio.tsx). REUSES every existing hook and handler
7 | // verbatim - `usePortfolio`, `usePortfolioSharingPermission`,
8 | // `useTogglePortfolioPublic` (mutation), `useApproachableWording` - including the
9 | // R24.1/R24.2 admin-permission gate on public sharing, the copy-link flow, and
10 | // the friendly strengths/areas-improving grouping. Only presentation changes:
11 | // the `GradientCardHeader` bars become `SectionHeader` chips inside
12 | // `card-elevated` cards, and the KPI row uses the shared `KPICard`. i18n reuses
13 | // the exact `student` namespace `portfolio.*` keys. Flag-off keeps the legacy
14 | // page byte-identical.
15 | // =====
16 |
17 | import { useMemo, useState } from "react";
18 | import { useTranslation } from "react-i18next";
19 | import { Label, PCard, Switch } from "@design-system";
20 | import { useAuth } from "@hooks/useAuth";
21 | import {
22 |   usePortfolio,
23 |   usePortfolioSharingPermission,
24 |   useTogglePortfolioPublic,
25 |   type PortfolioCLO,
26 | } from "@hooks/usePortfolio";
27 | import { useApproachableWording } from "@hooks/useApproachableWording";
28 | import { KPICard, SectionHeader } from "@design-system";
29 | import BloomsPill from "@components/shared/BloomsPill";
30 | import {
31 |   InlineNoAttainmentData,
32 |   InlineNoBadges,
33 |   InlineNoXPData,
34 |   InlineNoSemesters,
35 | } from "@components/shared/EmptyState";
36 | import {

```

```

37 | Award,
38 | BookOpen,
39 | PenLine,
40 | TrendingUp,
41 | BarChart3,
42 | Copy,
43 | Check,
44 | Lock,
45 | } from "lucide-react";
46 | import {
47 |   LineChart,
48 |   Line,
49 |   XAxis,
50 |   YAxis,
51 |   CartesianGrid,
52 |   Tooltip,
53 |   ResponsiveContainer,
54 |   BarChart,
55 |   Bar,
56 | } from "recharts";
57 | import { format } from "date-fns";
58 | import { toast } from "sonner";
59 | import { cn } from "@lib/utills";
60 | import type { AttainmentLevel } from "@types/app";
61 |
62 | const ATTAINMENT_STYLES: Record<AttainmentLevel, string> = {
63 |   Excellent: "text-green-600 bg-green-50",
64 |   Satisfactory: "text-blue-600 bg-blue-50",
65 |   Developing: "text-yellow-600 bg-yellow-50",
66 |   Not_Yet: "text-red-600 bg-red-50",
67 | };
68 |
69 | const CloRow = ({ clo }: { clo: PortfolioCLO }) => {
70 |   const { t } = useTranslation("student");
71 |   return (
72 |     <div className="flex items-center justify-between gap-3 rounded-lg border border-slate-100 p-3">
73 |       <div className="flex min-w-0 items-center gap-2">
74 |         <BloomsPill level={clo.blooms_level} />
75 |         <span className="truncate text-sm font-medium text-gray-800">
76 |           {clo.clo_title}
77 |         </span>
78 |       </div>
79 |       <span
80 |         className={cn(
81 |           "inline-flex shrink-0 items-center rounded-full px-2.5 py-0.5 text-xs font-bold",
82 |           ATTAINMENT_STYLES[clo.attainment_level]
83 |         )}
84 |       >
85 |         {t(`portfolio.attainmentLevels.${clo.attainment_level}`)} (
86 |           {clo.attainment_percent}%
87 |         </span>
88 |     </div>
89 |   );
90 | };
91 |
92 | const StudentPortfolioNew = () => {
93 |   const { t } = useTranslation("student");
94 |   const tw = useApproachableWording("student");
95 |   const { user, profile } = useAuth();
96 |   const studentId = user?.id;
97 |   const { data, isLoading } = usePortfolio(studentId);
98 |   const { data: sharingPermitted = false } =
99 |     usePortfolioSharingPermission(studentId);
100 |   const toggleMutation = useTogglePortfolioPublic();
101 |   const [copied, setCopied] = useState(false);
102 |   const isPublic = profile?.portfolio_public ?? false;
103 |
104 |   const handleTogglePublic = () => {
105 |     if (!studentId) return;
106 |     const nextPublic = !isPublic;
107 |
108 |     // R24.1/R24.2: enabling public sharing requires admin-granted permission.
109 |     // Without it, keep the portfolio private and explain that school permission
110 |     // is required rather than attempting (and silently failing) the toggle.
111 |     if (nextPublic && !sharingPermitted) {
112 |       toast.error(t("portfolio.toast.permissionDenied"));
113 |       return;
114 |     }
115 |
116 |     toggleMutation.mutate(
117 |       { userId: studentId, isPublic: nextPublic },
118 |       {
119 |         onSuccess: (result) =>
120 |           toast.success(
121 |             result.isPublic
122 |               ? t("portfolio.toast.madePublic")
123 |               : t("portfolio.toast.madePrivate")
124 |             ),
125 |         onError: (err) => toast.error(err.message),
126 |       }
127 |     );
128 |   };
129 |
130 |   const handleCopyLink = () => {
131 |     if (!studentId) return;
132 |     const url = `${window.location.origin}/portfolio/${studentId}`;
133 |     navigator.clipboard.writeText(url);
134 |     setCopied(true);
135 |     toast.success(t("portfolio.toast.linkCopied"));
136 |     setTimeout(() => setCopied(false), 2000);
137 |   };
138 |
139 |   const cloList = useMemo(() => data?.clos ?? [], [data?.clos]);
140 |   const closByCourse = useMemo(() => {

```



```

141 |     const map = new Map<string, typeof cloList>();
142 |     for (const clo of cloList) {
143 |         const existing = map.get(clo.course_name) ?? [];
144 |         existing.push(clo);
145 |         map.set(clo.course_name, existing);
146 |     }
147 |     return Array.from(map.entries());
148 | }, [cloList]);
149 |
150 | // Younger-student grouping (R22.2): "Strengths" are outcomes the student is
151 | // meeting (Excellent/Satisfactory); "Areas improving" are the rest.
152 | const splitByFriendlyGroup = (clos: typeof cloList) => {
153 |     const strengths = clos.filter(
154 |         (c) =>
155 |             c.attainment_level === "Excellent" ||
156 |             c.attainment_level === "Satisfactory"
157 |     );
158 |     const areasImproving = clos.filter(
159 |         (c) =>
160 |             c.attainment_level === "Developing" || c.attainment_level === "Not_Yet"
161 |     );
162 |     return { strengths, areasImproving };
163 | };
164 |
165 | if (isLoading) {
166 |     return (
167 |         <div className="space-y-6">
168 |             <div className="h-8 w-48 rounded-lg animate-shimmer" />
169 |             <div className="grid grid-cols-2 gap-4 md:grid-cols-4">
170 |                 {Array.from({ length: 4 }).map((_, i) => (
171 |                     <div key={i} className="h-24 rounded-xl animate-shimmer" />
172 |                 ))}
173 |             </div>
174 |             <div className="h-64 rounded-xl animate-shimmer" />
175 |         </div>
176 |     );
177 | }
178 |
179 | return (
180 |     <div className="space-y-6">
181 |         <div className="flex flex-wrap items-center justify-between gap-4">
182 |             <h1 className="text-2xl font-bold tracking-tight">
183 |                 {t("portfolio.title")}
184 |             </h1>
185 |             <div className="flex items-center gap-4">
186 |                 <div className="flex items-center gap-2">
187 |                     <Switch
188 |                         id="portfolio-public"
189 |                         checked={isPublic}
190 |                         onChange={handleTogglePublic}
191 |                         disabled={toggleMutation.isPending}
192 |                         aria-label={t("portfolio.togglePublicAria")}
193 |                     />
194 |                     <Label
195 |                         htmlFor="portfolio-public"
196 |                         className="text-sm font-medium text-gray-600"
197 |                     >
198 |                         {t("portfolio.publicProfile")}
199 |                     </Label>
200 |                 </div>
201 |                 {isPublic && (
202 |                     <button
203 |                         onClick={handleCopyLink}
204 |                         className="flex items-center gap-1.5 text-sm font-medium text-blue-600 transition-colors hover:t
205 |                         aria-label={t("portfolio.copyLinkAria")}
206 |                     >
207 |                         {copied ? (
208 |                             <Check className="h-4 w-4" />
209 |                         ) : (
210 |                             <Copy className="h-4 w-4" />
211 |                         )}
212 |                         {copied ? t("portfolio.copied") : t("portfolio.copyLink")}
213 |                     </button>
214 |                 )}
215 |             </div>
216 |         </div>
217 |
218 |         {!isPublic && !sharingPermitted && (
219 |             <div
220 |                 role="note"
221 |                 className="flex items-start gap-2 rounded-xl border border-amber-200 bg-amber-50 p-4 text-sm font-me
222 |             >
223 |                 <Lock className="mt-0.5 h-4 w-4 shrink-0" aria-hidden="true" />
224 |                 <span>{t("portfolio.permissionRequired")}</span>
225 |             </div>
226 |         )}
227 |
228 |         {/* KPI row */}
229 |         <div className="grid grid-cols-2 gap-4 md:grid-cols-4">
230 |             <KPICard
231 |                 icon={TrendingUp}
232 |                 label={t("portfolio.kpi.totalXP")}
233 |                 value={{data?.totalXP ?? 0}.toLocaleString()}
234 |                 iconBgClass="bg-amber-50"
235 |                 iconColorClass="text-amber-500"
236 |                 valueClassName="text-amber-600"
237 |             />
238 |             <KPICard
239 |                 icon={Award}
240 |                 label={t("portfolio.kpi.level")}
241 |                 value={data?.level ?? 1}
242 |             />
243 |             <KPICard
244 |                 icon={BookOpen}

```

```

245     label={t("portfolio.kpi.closMastered")}
246     value={data?.clos.length ?? 0}
247   />
248   <KPICard
249     icon={Award}
250     label={t("portfolio.kpi.badgesEarned")}
251     value={data?.badges.length ?? 0}
252     iconBgClass="bg-green-50"
253     iconColorClass="text-green-600"
254   />
255 </div>
256
257 {/* Skills by course */}
258 <PCard className="overflow-hidden">
259   <div className="p-6">
260     <SectionHeader
261       icon={BookOpen}
262       title={tw("portfolio.friendly.skillsTitle")}
263     />
264     <div className="mt-4 space-y-6">
265       {closByCourse.length === 0 && <InlineNoAttainmentData />}
266       {closByCourse.map(([courseName, clos]) => {
267         const { strengths, areasImproving } = splitByFriendlyGroup(clos);
268         return (
269           <div key={courseName}>
270             <h3 className="mb-3 text-sm font-bold text-gray-700">
271               {courseName}
272             </h3>
273             <div className="space-y-4">
274               {strengths.length > 0 && (
275                 <div>
276                   <p className="text-xs font-bold uppercase tracking-wide text-green-700">
277                     {tw("portfolio.friendly.strengths")}
278                   </p>
279                   <p className="mb-2 text-xs text-gray-500">
280                     {tw("portfolio.friendly.strengthsHint")}
281                   </p>
282                   <div className="space-y-2">
283                     {strengths.map((clo) => (
284                       <CloRow key={clo.clo_id} clo={clo} />
285                     ))}
286                   </div>
287                 </div>
288               )}
289               {areasImproving.length > 0 && (
290                 <div>
291                   <p className="text-xs font-bold uppercase tracking-wide text-yellow-700">
292                     {tw("portfolio.friendly.areasImproving")}
293                   </p>
294                   <p className="mb-2 text-xs text-gray-500">
295                     {tw("portfolio.friendly.areasImprovingHint")}
296                   </p>
297                   <div className="space-y-2">
298                     {areasImproving.map((clo) => (
299                       <CloRow key={clo.clo_id} clo={clo} />
300                     ))}
301                   </div>
302                 </div>
303               )}
304             </div>
305           </div>
306         );
307       })}
308     </div>
309   </div>
310 </PCard>
311
312 {/* Badge collection */}
313 <PCard className="overflow-hidden">
314   <div className="p-6">
315     <SectionHeader
316       icon={Award}
317       title={t("portfolio.sections.badgeCollection")}
318     />
319     <div className="mt-4">
320       {(data?.badges ?? []).length === 0 ? (
321         <InlineNoBadges />
322       ) : (
323         <div className="grid grid-cols-3 gap-4 sm:grid-cols-4 md:grid-cols-5">
324           {data?.badges.map((b) => (
325             <PCard
326               key={b.badge_key}
327               className="flex flex-col items-center gap-2 rounded-xl border-0 border-s-4 border-s-amber-
328             >
329               <span className="text-3xl" aria-hidden="true">
330                 {b.emoji}
331               </span>
332               <span className="text-xs font-bold tracking-wide">
333                 {b.badge_name}
334               </span>
335               <span className="text-[10px] text-gray-500">
336                 {format(new Date(b.awarded_at), "MMM d, yyyy")}
337               </span>
338             </PCard>
339           ))}
340         </div>
341       )}
342     </div>
343   </div>
344 </PCard>
345
346 {/* Journal entries */}
347 <PCard className="overflow-hidden">
348   <div className="p-6">

```

```

349 |         <SectionHeader
350 |             icon={PenLine}
351 |             title={t("portfolio.sections.journalEntries")}
352 |         />
353 |         <div className="mt-4">
354 |             {(data?.journals ?? []).length === 0 ? (
355 |                 <p className="text-sm text-gray-400">
356 |                     {t("portfolio.noJournals")}
357 |                 </p>
358 |             ) : (
359 |                 <div className="space-y-3">
360 |                     {data?.journals.map((j) => (
361 |                         <div
362 |                             key={j.id}
363 |                             className="flex items-center justify-between rounded-lg border border-slate-100 p-3"
364 |                         >
365 |                             <div className="min-w-0">
366 |                                 <p className="truncate text-sm font-medium text-gray-800">
367 |                                     {j.content_preview}
368 |                                 </p>
369 |                                 <p className="text-xs text-gray-500">
370 |                                     {j.course_name ?? t("portfolio.general")}
371 |                                 </p>
372 |                             </div>
373 |                             <span className="shrink-0 text-xs text-gray-400">
374 |                                 {format(new Date(j.created_at), "MMM d, yyyy")}
375 |                             </span>
376 |                         </div>
377 |                     ))}
378 |                 </div>
379 |             )}
380 |         </div>
381 |     </div>
382 | </PCard>
383 |
384 |     { /* XP timeline */ }
385 |     <PCard className="overflow-hidden">
386 |         <div className="p-6">
387 |             <SectionHeader
388 |                 icon={TrendingUp}
389 |                 title={t("portfolio.sections.xpTimeline")}
390 |             />
391 |             <div className="mt-4">
392 |                 {(data?.xpTimeline ?? []).length === 0 ? (
393 |                     <InlineNoXPData />
394 |                 ) : (
395 |                     <ResponsiveContainer width="100%" height={280}>
396 |                         <LineChart data={data?.xpTimeline}>
397 |                             <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
398 |                             <XAxis
399 |                                 dataKey="date"
400 |                                 tick={{ fontSize: 11, fill: "#64748b" }}
401 |                                 tickFormatter={(v) =>
402 |                                     format(new Date(v as string), "MMM d")
403 |                                 }
404 |                             />
405 |                             <YAxis tick={{ fontSize: 11, fill: "#64748b" }} />
406 |                             <Tooltip
407 |                                 labelFormatter={(v) =>
408 |                                     format(new Date(v as string), "MMM d, yyyy")
409 |                                 }
410 |                                 formatter={(value) => [
411 |                                     t("portfolio.chart.xpValue", {
412 |                                         value: Number(value).toLocaleString(),
413 |                                     }),
414 |                                     t("portfolio.chart.cumulativeXP"),
415 |                                 ]}
416 |                             />
417 |                             <Line
418 |                                 type="monotone"
419 |                                 dataKey="cumulative_xp"
420 |                                 stroke="#3b82f6"
421 |                                 strokeWidth={2}
422 |                                 dot={false}
423 |                                 activeDot={{ r: 4 }}
424 |                             />
425 |                         </LineChart>
426 |                     </ResponsiveContainer>
427 |                 )}
428 |             </div>
429 |         </div>
430 |     </PCard>
431 |
432 |     { /* Attainment growth */ }
433 |     <PCard className="overflow-hidden">
434 |         <div className="p-6">
435 |             <SectionHeader
436 |                 icon={BarChart3}
437 |                 title={t("portfolio.sections.attainmentGrowth")}
438 |             />
439 |             <div className="mt-4">
440 |                 {(data?.semesterAttainments ?? []).length === 0 ? (
441 |                     <InlineNoSemesters />
442 |                 ) : (
443 |                     <ResponsiveContainer width="100%" height={260}>
444 |                         <BarChart data={data?.semesterAttainments}>
445 |                             <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
446 |                             <XAxis
447 |                                 dataKey="semester_name"
448 |                                 tick={{ fontSize: 11, fill: "#64748b" }}
449 |                             />
450 |                             <YAxis
451 |                                 domain={[0, 100]}
452 |                                 tick={{ fontSize: 11, fill: "#64748b" }}

```

```

453 |         tickFormatter={(v) => `${v}%`}
454 |       />
455 |       <Tooltip
456 |         formatter={(value) => [
457 |           `${value}%`,
458 |           t("portfolio.chart.avgAttainment"),
459 |         ]}
460 |       />
461 |       <Bar
462 |         dataKey="average_attainment"
463 |         fill="#14b8a6"
464 |         radius={[6, 6, 0, 0]}
465 |       />
466 |     </BarChart>
467 |   </ResponsiveContainer>
468 | )}
469 | </div>
470 | </div>
471 | </PCard>
472 | </div>
473 | );
474 | };
475 |
476 | export default StudentPortfolioNew;
477 |

```

FILE: src/pages/student/profile/LearningProfilePage.tsx

TYPE: .tsx | LINES: 1-309 | SHA256: 0c0dcec6d3cbfa3933c0dd2daf2db3838fc71efa4345033610ef14b691f03762

```

1 | import { useTranslation } from "react-i18next";
2 | import { BarChart3, Brain, Compass, RefreshCw, Sparkles } from "lucide-react";
3 | import { Link } from "react-router-dom";
4 | import { Button } from "@components/ui/button";
5 | import ErrorState from "@components/shared/ErrorState";
6 | import { PCard, Shimmer } from "@design-system";
7 | import { useAuth } from "@hooks/useAuth";
8 | import { useStudentProfile } from "@hooks/useStudentProfile";
9 |
10 | interface ScoreItemProps {
11 |   label: string;
12 |   value: number;
13 | }
14 |
15 | const ScoreItem = ({ label, value }: ScoreItemProps) => (
16 |   <div className="space-y-1.5">
17 |     <div className="flex items-center justify-between gap-3 text-xs">
18 |       <span className="font-medium text-slate-600">{label}</span>
19 |       <span className="font-bold text-slate-900">{Math.round(value)}%</span>
20 |     </div>
21 |     <ProfileProgress
22 |       value={value}
23 |       ariaLabel={` ${label}: ${Math.round(value)}%`}
24 |     />
25 |   </div>
26 | );
27 |
28 | const LearningProfilePage = () => {
29 |   const { t } = useTranslation("student");
30 |   const { user } = useAuth();
31 |   const profile = useStudentProfile(user?.id ?? "");
32 |   const data = profile.data;
33 |
34 |   if (profile.isLoading) {
35 |     return (
36 |       <div className="space-y-5">
37 |         <Shimmer className="h-12 w-64 rounded-xl" />
38 |         <Shimmer className="h-72 rounded-[20px]" />
39 |       </div>
40 |     );
41 |   }
42 |
43 |   if (profile.isError) {
44 |     return (
45 |       <ErrorState
46 |         message={t("learningProfile.loadError")}
47 |         onRetry={() => void profile.refetch()}
48 |         retryLabel={t("learningProfile.retry")}
49 |       />
50 |     );
51 |   }
52 |
53 |   if (!data) {
54 |     return (
55 |       <PCard className="mx-auto max-w-2xl p-6 text-center sm:p-8">
56 |         <Brain className="mx-auto size-9 text-teal-600" aria-hidden="true" />
57 |         <h1 className="mt-3 text-xl font-bold tracking-tight">
58 |           {t("learningProfile.emptyTitle")}
59 |         </h1>
60 |         <p className="mx-auto mt-2 max-w-md text-sm text-muted-foreground">
61 |           {t("learningProfile.emptyBody")}
62 |         </p>
63 |         <Button asChild variant="tactile" className="mt-5">
64 |           <Link to="/student/onboarding/complete-profile">
65 |             {t("learningProfile.completeProfile")}
66 |           </Link>
67 |         </Button>
68 |       </PCard>
69 |     );
70 |   }
71 |
72 |   const learningStyle = data.learning_style;
73 |   const selfEfficacy = data.self_efficacy;
74 |   const studyStrategies = data.study_strategies;
75 |   const traits = data.personality_traits;

```

```

76 |
77 | return (
78 |   <div className="space-y-6">
79 |     <div className="flex flex-col gap-4 sm:flex-row sm:items-end sm:justify-between">
80 |       <div>
81 |         <div className="flex items-center gap-2">
82 |           <Compass className="size-5 text-teal-600" aria-hidden="true" />
83 |           <h1 className="text-2xl font-bold tracking-tight">
84 |             {t("learningProfile.title")}
85 |           </h1>
86 |         </div>
87 |         <p className="mt-1 text-sm text-muted-foreground">
88 |           {t("learningProfile.subtitle")}
89 |         </p>
90 |       </div>
91 |       <Button asChild variant="outline" size="sm">
92 |         <Link to="/student/settings/reassessment">
93 |           <RefreshCw className="size-4" aria-hidden="true" />
94 |           {t("learningProfile.reassess")}
95 |         </Link>
96 |       </Button>
97 |     </div>
98 |
99 |     <PCard className="border-teal-200 bg-gradient-to-br from-teal-50 to-white p-5 sm:p-6">
100 |       <div className="flex items-start gap-3">
101 |         <span className="flex size-10 shrink-0 items-center justify-center rounded-xl bg-white text-teal-700">
102 |           <Sparkles className="size-5" aria-hidden="true" />
103 |         </span>
104 |         <div className="min-w-0 flex-1">
105 |           <p className="text-xs font-bold uppercase tracking-wider text-teal-700">
106 |             {t("learningProfile.completeness")}
107 |           </p>
108 |           <div className="mt-1 flex items-baseline gap-2">
109 |             <span className="text-3xl font-black tracking-tight text-slate-900">
110 |               {Math.round(data.profile_completeness)}%
111 |             </span>
112 |             <span className="text-sm text-slate-600">
113 |               {t("learningProfile.personalization")}
114 |             </span>
115 |           </div>
116 |           <ProfileProgress
117 |             className="mt-3 bg-white"
118 |             value={data.profile_completeness}
119 |             ariaLabel={t("learningProfile.completeness")}
120 |           />
121 |         </div>
122 |       </div>
123 |     </PCard>
124 |
125 |     <div className="grid gap-5 lg:grid-cols-2">
126 |       <ProfileSection
127 |         icon={<Brain className="size-5" aria-hidden="true" />}
128 |         title={t("learningProfile.learningStyle")}
129 |       >
130 |         {learningStyle ? (
131 |           <>
132 |             <p className="text-sm font-bold text-slate-900">
133 |               {t("learningProfile.dominantStyle", {
134 |                 style: t(
135 |                   "learningProfile.styles.${learningStyle.dominant_style}"
136 |                 )},
137 |             )}
138 |             </p>
139 |             <div className="mt-4 space-y-3">
140 |               <ScoreItem
141 |                 label={t("learningProfile.styles.visual")}
142 |                 value={learningStyle.visual}
143 |               />
144 |               <ScoreItem
145 |                 label={t("learningProfile.styles.auditory")}
146 |                 value={learningStyle.auditory}
147 |               />
148 |               <ScoreItem
149 |                 label={t("learningProfile.styles.read_write")}
150 |                 value={learningStyle.read_write}
151 |               />
152 |               <ScoreItem
153 |                 label={t("learningProfile.styles.kinesthetic")}
154 |                 value={learningStyle.kinesthetic}
155 |               />
156 |             </div>
157 |           </>
158 |         ) : (
159 |           <MissingSection
160 |             message={t("learningProfile.missingLearningStyle")}
161 |           />
162 |         )}
163 |     </ProfileSection>
164 |
165 |     <ProfileSection
166 |       icon={<BarChart3 className="size-5" aria-hidden="true" />}
167 |       title={t("learningProfile.studyStrategies")}
168 |     >
169 |       {studyStrategies ? (
170 |         <div className="space-y-3">
171 |           <ScoreItem
172 |             label={t("learningProfile.strategies.time_management")}
173 |             value={studyStrategies.time_management}
174 |           />
175 |           <ScoreItem
176 |             label={t("learningProfile.strategies.elaboration")}
177 |             value={studyStrategies.elaboration}
178 |           />
179 |           <ScoreItem

```

```

180         label={t("learningProfile.strategies.self_testing")}
181         value={studyStrategies.self_testing}
182     />
183     <ScoreItem
184         label={t("learningProfile.strategies.help_seeking")}
185         value={studyStrategies.help_seeking}
186     />
187 </div>
188 ) : (
189     <MissingSection message={t("learningProfile.missingStrategies")} />
190 )}
191 </ProfileSection>
192
193 <ProfileSection
194     icon={<Sparkles className="size-5" aria-hidden="true" />}
195     title={t("learningProfile.selfEfficacy")}
196 >
197     {selfEfficacy ? (
198         <div className="space-y-3">
199             <ScoreItem
200                 label={t("learningProfile.overall")}
201                 value={selfEfficacy.overall}
202             />
203             <ScoreItem
204                 label={t("learningProfile.efficacy.general_academic")}
205                 value={selfEfficacy.general_academic}
206             />
207             <ScoreItem
208                 label={t("learningProfile.efficacy.course_specific")}
209                 value={selfEfficacy.course_specific}
210             />
211             <ScoreItem
212                 label={t("learningProfile.efficacy.self_regulated_learning")}
213                 value={selfEfficacy.self_regulated_learning}
214             />
215         </div>
216     ) : (
217         <MissingSection message={t("learningProfile.missingEfficacy")} />
218     )}
219 </ProfileSection>
220
221 <ProfileSection
222     icon={<Brain className="size-5" aria-hidden="true" />}
223     title={t("learningProfile.personality")}
224 >
225     {traits ? (
226         <div className="space-y-3">
227             <ScoreItem
228                 label={t("learningProfile.traits.openness")}
229                 value={traits.openness}
230             />
231             <ScoreItem
232                 label={t("learningProfile.traits.conscientiousness")}
233                 value={traits.conscientiousness}
234             />
235             <ScoreItem
236                 label={t("learningProfile.traits.extraversion")}
237                 value={traits.extraversion}
238             />
239             <ScoreItem
240                 label={t("learningProfile.traits.agreeableness")}
241                 value={traits.agreeableness}
242             />
243             <ScoreItem
244                 label={t("learningProfile.traits.neuroticism")}
245                 value={traits.neuroticism}
246             />
247         </div>
248     ) : (
249         <MissingSection message={t("learningProfile.missingPersonality")} />
250     )}
251 </ProfileSection>
252 </div>
253 </div>
254 );
255 };
256
257 const ProfileSection = ({
258     icon,
259     title,
260     children,
261 }): {
262     icon: React.ReactNode;
263     title: string;
264     children: React.ReactNode;
265 } => (
266     <PCard className="p-5 sm:p-6">
267         <div className="mb-5 flex items-center gap-3">
268             <span className="flex size-9 items-center justify-center rounded-lg bg-slate-100 text-slate-700">
269                 {icon}
270             </span>
271             <h2 className="font-black tracking-tight text-slate-900">{title}</h2>
272         </div>
273         {children}
274     </PCard>
275 );
276
277 const MissingSection = ({ message }: { message: string }) => (
278     <p className="text-sm text-muted-foreground">{message}</p>
279 );
280
281 const ProfileProgress = ({
282     value,
283     ariaLabel,

```

```

284 |     className = "",
285 |   }: {
286 |     value: number;
287 |     ariaLabel: string;
288 |     className?: string;
289 |   }) => {
290 |     const boundedValue = Math.max(0, Math.min(100, value));
291 |     return (
292 |       <div
293 |         className={`h-2 overflow-hidden rounded-full bg-slate-100 ${className}`}
294 |         role="progressbar"
295 |         aria-label={ariaLabel}
296 |         aria-valuemin={0}
297 |         aria-valuemax={100}
298 |         aria-valuenow={boundedValue}
299 |       >
300 |         <div
301 |           className="h-full rounded-full bg-gradient-to-r from-teal-500 to-blue-500 transition-[width]"
302 |           style={{ width: `${boundedValue}%` }}
303 |         />
304 |       </div>
305 |     );
306 |   };
307 |
308 | export default LearningProfilePage;
309 |

```

FILE: src/pages/student/progress/CL0Progress.tsx

TYPE: .tsx | LINES: 1-207 | SHA256: bebb58504d0aab9f29dcdd0c11d12954afe7de0fbb48d1a65afc61b374db7084

[illegible]

[illegible]


```

179 |                 animate={{ height: "auto", opacity: 1 }}
180 |                 exit={{ height: 0, opacity: 0 }}
181 |                 transition={{ duration: 0.25, ease: "easeInOut" }}
182 |                 className="overflow-hidden"
183 |             >
184 |                 <div className="mt-2 ms-2 border-s-2 border-slate-200 ps-3">
185 |                     <EvidencePanel
186 |                         cloId={entry.clo_id}
187 |                         studentId={studentId}
188 |                     />
189 |                 </div>
190 |             </motion.div>
191 |         )}
192 |     </AnimatePresence>
193 | </div>
194 |     );
195 | });
196 | })
197 | </div>
198 | </div>
199 | </PCard>
200 | </motion.div>
201 | )))
202 | </div>
203 | );
204 | };
205 |
206 | export default CLOProgress;
207 |

```

FILE: [src/pages/student/progress/LearningPath.tsx](#)

TYPE: .tsx | LINES: 1-959 | SHA256: 70bc698b74a4fbc8dc8fed17b0485b6be0dc29f33261a34390f1ef1e76b150ea

```

1 | import { useMemo, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import { useTranslation } from "react-i18next";
4 | import { motion } from "framer-motion";
5 | import {
6 |     Check,
7 |     CheckCircle2,
8 |     Clock3,
9 |     GitBranch,
10 |     Lock,
11 |     Map as MapIcon,
12 |     Mountain,
13 |     Play,
14 |     Sparkles,
15 |     TreePine,
16 | } from "lucide-react";
17 |
18 | import { Badge } from "@components/ui/badge";
19 | import { Button } from "@components/ui/button";
20 | import {
21 |     Select,
22 |     SelectContent,
23 |     SelectItem,
24 |     SelectTrigger,
25 |     SelectValue,
26 | } from "@components/ui/select";
27 | import { PCard, Shimmer } from "@design-system";
28 | import { useLearningPath } from "@hooks/useLearningPath";
29 | import type { LearningPathNode } from "@hooks/useLearningPath";
30 | import {
31 |     buildBloomStageSummaries,
32 |     type BloomStageSummary,
33 | } from "@lib/learningPathPresentation";
34 | import type { BloomsLevel } from "@lib/schemas/clo";
35 | import { cn } from "@lib/utils";
36 |
37 | type PathView = "journey" | "tree";
38 |
39 | interface BloomDefinition {
40 |     key: BloomsLevel;
41 |     campKey: string;
42 |     titleKey: string;
43 |     subtitleKey: string;
44 |     emoji: string;
45 |     environment: string;
46 |     titleColor: string;
47 | }
48 |
49 | export interface BloomStage extends BloomDefinition, BloomStageSummary {}
50 |
51 | const BLOOM_DEFINITIONS: readonly BloomDefinition[] = [
52 |     {
53 |         key: "remembering",
54 |         campKey: "learningPath.stages.baseCamp",
55 |         titleKey: "learningPath.stages.remember.title",
56 |         subtitleKey: "learningPath.stages.remember.subtitle",
57 |         emoji: "ðŸŒŸ",
58 |         environment: "bg-green-50",
59 |         titleColor: "text-green-700",
60 |     },
61 |     {
62 |         key: "understanding",
63 |         campKey: "learningPath.stages.campOne",
64 |         titleKey: "learningPath.stages.understand.title",
65 |         subtitleKey: "learningPath.stages.understand.subtitle",
66 |         emoji: "âš¶",
67 |         environment: "bg-teal-50",
68 |         titleColor: "text-teal-700",
69 |     },
70 |     {
71 |         key: "applying",

```

```

72 |     campKey: "learningPath.stages.campTwo",
73 |     titleKey: "learningPath.stages.apply.title",
74 |     subtitleKey: "learningPath.stages.apply.subtitle",
75 |     emoji: "🧐",
76 |     environment: "bg-cyan-50",
77 |     titleColor: "text-cyan-800",
78 |   },
79 |   {
80 |     key: "analyzing",
81 |     campKey: "learningPath.stages.campThree",
82 |     titleKey: "learningPath.stages.analyze.title",
83 |     subtitleKey: "learningPath.stages.analyze.subtitle",
84 |     emoji: "🧮",
85 |     environment: "bg-blue-50",
86 |     titleColor: "text-blue-700",
87 |   },
88 |   {
89 |     key: "evaluating",
90 |     campKey: "learningPath.stages.campFour",
91 |     titleKey: "learningPath.stages.evaluate.title",
92 |     subtitleKey: "learningPath.stages.evaluate.subtitle",
93 |     emoji: "🧐",
94 |     environment: "bg-sky-100",
95 |     titleColor: "text-blue-800",
96 |   },
97 |   {
98 |     key: "creating",
99 |     campKey: "learningPath.stages.summit",
100 |     titleKey: "learningPath.stages.create.title",
101 |     subtitleKey: "learningPath.stages.create.subtitle",
102 |     emoji: "🧐",
103 |     environment: "bg-blue-100",
104 |     titleColor: "text-blue-900",
105 |   },
106 | ] as const;
107
108 | const TREE_POSITIONS = [
109 |   { left: "50%", top: "84%" },
110 |   { left: "31%", top: "66%" },
111 |   { left: "68%", top: "54%" },
112 |   { left: "32%", top: "39%" },
113 |   { left: "67%", top: "24%" },
114 |   { left: "50%", top: "10%" },
115 | ] as const;
116
117 | const PathProgress = ({
118 |   value,
119 |   className,
120 | }): {
121 |   value: number;
122 |   className?: string;
123 | }) => (
124 |   <div
125 |     role="progressbar"
126 |     aria-valuemin={0}
127 |     aria-valuemax={100}
128 |     aria-valuenow={value}
129 |     className={cn("h-2 overflow-hidden rounded-full bg-slate-100", className)}
130 |   >
131 |     <div
132 |       className="h-full rounded-full bg-[image:var(--brand-gradient)] transition-[width]"
133 |       style={{ width: `${Math.min(Math.max(value, 0), 100)}%` }}
134 |     />
135 |   </div>
136 | );
137
138 | const buildPresentedStages = (nodes: LearningPathNode[]): BloomStage[] => {
139 |   const summaries = new Map(
140 |     buildBloomStageSummaries(nodes).map((summary) => [summary.key, summary])
141 |   );
142 |   return BLOOM_DEFINITIONS.flatMap((definition) => {
143 |     const summary = summaries.get(definition.key);
144 |     return summary ? [{ ...definition, ...summary }] : [];
145 |   });
146 | };
147
148 | const NodeStatusBadge = ({
149 |   status,
150 | }): {
151 |   status: LearningPathNode["status"];
152 | }) => {
153 |   const { t } = useTranslation("student");
154 |   const config: Record<
155 |     LearningPathNode["status"],
156 |     { label: string; className: string }
157 |   > = {
158 |     graded: {
159 |       label: t("learningPath.status.completed"),
160 |       className: "border-green-200 bg-green-50 text-green-700",
161 |     },
162 |     submitted: {
163 |       label: t("learningPath.status.submitted"),
164 |       className: "border-blue-200 bg-blue-50 text-blue-700",
165 |     },
166 |     available: {
167 |       label: t("learningPath.status.available"),
168 |       className: "border-teal-200 bg-teal-50 text-teal-700",
169 |     },
170 |     locked: {
171 |       label: t("learningPath.status.locked"),
172 |       className: "border-slate-200 bg-slate-100 text-slate-500",
173 |     },
174 |   };
175 | };

```

```

176 | return (
177 |   <Badge
178 |     variant="outline"
179 |     className={cn("shrink-0 text-[10px]", config[status].className)}
180 |   >
181 |     {config[status].label}
182 |   </Badge>
183 | );
184 | };
185 |
186 | const AssignmentCard = ({ node }: { node: LearningPathNode }) => {
187 |   const { t } = useTranslation("student");
188 |   const isLocked = node.status === "locked";
189 |   const isComplete = node.status === "graded";
190 |
191 |   return (
192 |     <div
193 |       className={cn(
194 |         "mt-3 flex flex-col gap-3 rounded-[14px] border bg-white p-3 shadow-sm sm:flex-row sm:items-center",
195 |         isLocked && "border-slate-200 bg-white/70 opacity-70",
196 |         isComplete && "border-green-200"
197 |       )}
198 |     >
199 |       <span
200 |         className={cn(
201 |           "flex size-9 shrink-0 items-center justify-center rounded-xl",
202 |           isComplete
203 |             ? "bg-green-100 text-green-700"
204 |             : isLocked
205 |               ? "bg-slate-100 text-slate-400"
206 |               : "bg-teal-100 text-teal-700"
207 |         )}
208 |       >
209 |         {isComplete ? (
210 |           <Check className="size-4" aria-hidden="true" />
211 |         ) : isLocked ? (
212 |           <Lock className="size-4" aria-hidden="true" />
213 |         ) : (
214 |           <Play className="size-4" aria-hidden="true" />
215 |         )}
216 |       </span>
217 |       <div className="min-w-0 flex-1">
218 |         <div className="flex flex-wrap items-center gap-2">
219 |           <p className="truncate text-sm font-black text-slate-900">
220 |             {node.title}
221 |           </p>
222 |           <NodeStatusBadge status={node.status} />
223 |         </div>
224 |         {node.attainment_percent !== null && !isLocked ? (
225 |           <div className="mt-2 flex items-center gap-2">
226 |             <PathProgress
227 |               value={node.attainment_percent}
228 |               className="h-1.5 flex-1"
229 |             />
230 |             <span className="text-[11px] font-black text-slate-500">
231 |               {node.attainment_percent}%
232 |             </span>
233 |           </div>
234 |         ) : null}
235 |         {isLocked && node.prerequisite ? (
236 |           <p className="mt-1 text-[11px] leading-snug text-slate-500">
237 |             {t("learningPath.unlockRequirement", {
238 |               title: node.prerequisite.clo_title,
239 |               percent: node.prerequisite.required_attainment,
240 |             })}
241 |           </p>
242 |         ) : null}
243 |       </div>
244 |       {isLocked ? (
245 |         <Button
246 |           type="button"
247 |           variant="outline"
248 |           size="sm"
249 |           disabled
250 |           className="shrink-0"
251 |         >
252 |           <Lock className="size-3.5" aria-hidden="true" />
253 |           {t("learningPath.actions.locked")}
254 |         </Button>
255 |       ) : (
256 |         <Button
257 |           asChild
258 |           size="sm"
259 |           variant={isComplete ? "outline" : "default"}
260 |           className="shrink-0"
261 |         >
262 |           <Link to={`/${student}/assignments/${node.assignment_id}`}>
263 |             {isComplete
264 |               ? t("learningPath.actions.review")
265 |               : t("learningPath.actions.continue")}
266 |           </Link>
267 |         </Button>
268 |       )}
269 |     </div>
270 |   );
271 | };
272 |
273 | const JourneyStage = ({
274 |   stage,
275 |   index,
276 |   isLast,
277 |   isSelected,
278 |   onSelect,
279 | }): {

```

```

280 | stage: BloomStage;
281 | index: number;
282 | isLast: boolean;
283 | isSelected?: boolean;
284 | onSelect?: () => void;
285 | }) => {
286 |   const { t } = useTranslation("student");
287 |
288 |   return (
289 |     <motion.div
290 |       initial={{ opacity: 0, y: 8 }}
291 |       animate={{ opacity: 1, y: 0 }}
292 |       transition={{ delay: index * 0.04 }}
293 |       className="flex gap-4"
294 |     >
295 |       <div className="flex shrink-0 flex-col items-center">
296 |         <button
297 |           type="button"
298 |           onClick={onSelect}
299 |           className={cn(
300 |             "relative z-10 flex size-11 items-center justify-center rounded-full text-sm font-black transition
301 |             stage.status === 'done' && 'bg-green-100 text-green-600",
302 |             stage.status === 'current' &&
303 |             "bg-[image:var(--brand-gradient)] text-white shadow-[0_0_5px_rgba(20,184,166,0.16)]",
304 |             stage.status === 'locked' && "bg-slate-100 text-slate-400",
305 |             isSelected && "ring-4 ring-teal-500/30"
306 |           )}
307 |         >
308 |           {stage.status === "done" ? (
309 |             <Check className="size-5" aria-hidden="true" />
310 |           ) : (
311 |             index + 1
312 |           )}
313 |         </button>
314 |         {!isLast ? (
315 |           <span
316 |             className={cn(
317 |               "min-h-6 w-[3px] flex-1",
318 |               stage.status === "done" ? "bg-green-300" : "bg-slate-200"
319 |             )}
320 |             aria-hidden="true"
321 |           />
322 |         ) : null}
323 |       </div>
324 |       <div
325 |         role="button"
326 |         tabIndex={0}
327 |         onClick={onSelect}
328 |         onKeyDown={(e) => {
329 |           if (e.key === "Enter" || e.key === " ") {
330 |             e.preventDefault();
331 |             onSelect?.();
332 |           }
333 |         }}
334 |         className={cn(
335 |           "mb-3 min-w-0 flex-1 cursor-pointer rounded-[14px] px-4 py-3 transition-all hover:shadow-md",
336 |           stage.environment,
337 |           isSelected && "ring-2 ring-teal-500 shadow-md"
338 |         )}
339 |       >
340 |         <div className="flex flex-wrap items-start justify-between gap-2">
341 |           <div>
342 |             <p className="text-[9px] font-black uppercase tracking-[0.1em] text-teal-700">
343 |               {stage.emoji} {t(stage.campKey)}
344 |             </p>
345 |             <h3
346 |               className={cn(
347 |                 "mt-0.5 text-sm font-black tracking-wide",
348 |                 stage.titleColor
349 |               )}
350 |             >
351 |               {t(stage.titleKey)}
352 |             </h3>
353 |             <p className="text-xs text-slate-500">{t(stage.subtitleKey)}</p>
354 |           </div>
355 |           {stage.status === "current" ? (
356 |             <Badge className="border border-teal-200 bg-teal-100 text-[10px] text-teal-700">
357 |               {t("learningPath.youAreHere")}
358 |             </Badge>
359 |           ) : stage.status === "done" ? (
360 |             <Badge className="border border-green-200 bg-green-100 text-[10px] text-green-700">
361 |               {t("learningPath.status.completed")}
362 |             </Badge>
363 |           ) : (
364 |             <Lock
365 |               className="size-4 text-slate-400"
366 |               aria-label={t("learningPath.status.locked")}
367 |             />
368 |           )}
369 |         </div>
370 |         {stage.nodes.map((node) => (
371 |           <AssignmentCard key={node.assignment_id} node={node} />
372 |         ))}
373 |         {stage.nodes.length === 0 ? (
374 |           <p className="mt-3 rounded-xl border border-dashed border-slate-200 bg-white/60 px-3 py-2 text-xs te
375 |             {stage.status === "locked"
376 |               ? t("learningPath.stageLocked")
377 |               : t("learningPath.noStageAssignments")}
378 |           </p>
379 |         ) : null}
380 |       </div>
381 |     </motion.div>
382 |   );
383 | };

```

```

384 |
385 | export const StageDetail = ({
386 |   stage,
387 |   stageIndex = 2,
388 | }): {
389 |   stage: BloomStage;
390 |   stageIndex?: number;
391 | }) => {
392 |   const { t } = useTranslation("student");
393 |   const completed = stage.nodes.filter(
394 |     (node) => node.status === "graded"
395 |   ).length;
396 |   const available = stage.nodes.find(
397 |     (node) => node.status === "available" || node.status === "submitted"
398 |   );
399 |
400 |   return (
401 |     <PCard className="p-5 shadow-md border-teal-100/80 rounded-2xl bg-white">
402 |       <div className="flex items-start justify-between">
403 |         <div>
404 |           <p className="text-[10px] font-extrabold uppercase tracking-[0.15em] text-slate-400">
405 |             LEVEL {stageIndex + 1}
406 |           </p>
407 |           <h2 className="text-xl font-black tracking-tight uppercase text-slate-900 mt-0.5">
408 |             {t(stage.titleKey)}
409 |           </h2>
410 |           <p className="text-xs font-medium text-slate-500 mt-0.5">
411 |             {t(stage.subtitleKey)}
412 |           </p>
413 |         </div>
414 |         <span className="flex size-11 items-center justify-center rounded-2xl bg-teal-50 text-2xl text-teal-70">
415 |           {stage.emoji}
416 |         </span>
417 |       </div>
418 |
419 |       <div className="mt-4 grid grid-cols-2 gap-2.5">
420 |         <div className="rounded-xl border border-slate-100 bg-slate-50/80 p-3">
421 |           <p className="text-[9px] font-black uppercase tracking-wider text-slate-400">
422 |             #ñp ESTIMATED TIME
423 |           </p>
424 |           <p className="mt-1 text-sm font-black text-slate-800">3 - 5 hrs</p>
425 |         </div>
426 |         <div className="rounded-xl border border-slate-100 bg-slate-50/80 p-3">
427 |           <p className="text-[9px] font-black uppercase tracking-wider text-slate-400">
428 |             Ø=ÜE MASTERED BY YOU
429 |           </p>
430 |           <p className="mt-1 text-sm font-black text-teal-600">
431 |             {stage.attainment}%
432 |           </p>
433 |         </div>
434 |       </div>
435 |
436 |       <div className="mt-4 border-t border-slate-100 pt-3.5">
437 |         <p className="text-xs font-black text-slate-800 uppercase tracking-wider">
438 |           CONCEPTS IN THIS LEVEL
439 |         </p>
440 |         <div className="mt-2.5 space-y-2">
441 |           {stage.nodes.length > 0 ? (
442 |             stage.nodes.map((node) => (
443 |               <div
444 |                 key={node.assignment_id}
445 |                 className="flex items-center gap-2.5 text-xs"
446 |               >
447 |                 <span
448 |                   className={cn(
449 |                     "flex size-5 items-center justify-center rounded-full shrink-0",
450 |                     node.status === "graded"
451 |                       ? "bg-emerald-500 text-white"
452 |                       : node.status === "locked"
453 |                       ? "bg-slate-100 text-slate-400"
454 |                       : "border-2 border-teal-500 bg-teal-50 text-teal-700"
455 |                   )}
456 |                 >
457 |                   {node.status === "graded" ? (
458 |                     <Check className="size-3 stroke-[3] aria-hidden="true" />
459 |                   ) : node.status === "locked" ? (
460 |                     <Lock className="size-2.5" aria-hidden="true" />
461 |                   ) : (
462 |                     <span className="size-1.5 rounded-full bg-teal-500" />
463 |                   )}
464 |                 </span>
465 |                 <span className="min-w-0 flex-1 truncate font-semibold text-slate-700">
466 |                   {node.title}
467 |                 </span>
468 |                 {node.status === "available" || node.status === "submitted" ? (
469 |                   <Badge className="border border-teal-200 bg-teal-50 text-[9px] text-teal-700">
470 |                     In progress
471 |                   </Badge>
472 |                 ) : null}
473 |               </div>
474 |             ))
475 |           ) : (
476 |             <p className="text-xs text-slate-500">
477 |               {t("learningPath.noStageAssignments")}
478 |             </p>
479 |           )}
480 |         </div>
481 |       </div>
482 |
483 |       <div className="mt-4 rounded-2xl border border-teal-200/60 bg-gradient-to-br from-teal-50/90 to-cyan-50/">
484 |         <div className="flex items-center gap-2 text-xs font-black text-teal-800">
485 |           <Sparkles className="size-4 text-teal-600" aria-hidden="true" />
486 |           <span>AI Coach Tip</span>
487 |         </div>

```

```

488 |         <p className="mt-1.5 text-xs leading-relaxed text-slate-600 font-medium">
489 |             {available
490 |               ? `You're doing great! Focus on completing "${
491 |                 available.title
492 |               }" to strengthen your ${t(stage.titleKey)} level.`
493 |               : stage.status === "done"
494 |               ? "This level is complete. Your next stage is ready when its prerequisite is met."
495 |               : t("learningPath.coachLocked")}
496 |         </p>
497 |       </div>
498 |
499 |       <div className="mt-4 border-t border-slate-100 pt-3">
500 |         <p className="text-[9px] font-black uppercase tracking-wider text-slate-400 mb-2">
501 |           YOUR PROGRESS IN LEVEL {stageIndex + 1}
502 |         </p>
503 |         <div className="grid grid-cols-3 gap-2 rounded-xl bg-slate-50 p-2 text-center">
504 |           <div>
505 |             <p className="text-xs font-black text-slate-800">
506 |               {completed}/{stage.nodes.length || 5}
507 |             </p>
508 |             <p className="text-[8px] font-bold uppercase text-slate-400">
509 |               CONCEPTS
510 |             </p>
511 |           </div>
512 |           <div>
513 |             <p className="text-xs font-black text-teal-600">
514 |               {stage.attainment}%
515 |             </p>
516 |             <p className="text-[8px] font-bold uppercase text-slate-400">
517 |               MASTERY
518 |             </p>
519 |           </div>
520 |           <div>
521 |             <p className="text-xs font-black text-emerald-600">+18%</p>
522 |             <p className="text-[8px] font-bold uppercase text-slate-400">
523 |               IMPROVE
524 |             </p>
525 |           </div>
526 |         </div>
527 |       </div>
528 |     </PCard>
529 |   );
530 | };
531 |
532 | export const BloomOverviewCard = ({ stages }: { stages: BloomStage[] }) => {
533 |   const { t } = useTranslation("student");
534 |   const overallMastery = Math.round(
535 |     stages.reduce((acc, s) => acc + s.attainment, 0) / (stages.length || 1)
536 |   );
537 |
538 |   return (
539 |     <PCard className="p-4 border-slate-200/80 bg-white/90 shadow-sm rounded-2xl">
540 |       <div className="flex items-center justify-between gap-2 mb-3">
541 |         <div className="flex items-center gap-2">
542 |           <span className="text-sm">0</span>
543 |           <h3 className="text-xs font-black uppercase tracking-wider text-slate-900">
544 |             {t("learningPath.bloomMasteryOverview", "Bloom's Mastery Summary")}
545 |           </h3>
546 |         </div>
547 |         <Badge
548 |           variant="outline"
549 |           className="border-teal-200 bg-teal-50 text-[10px] font-bold text-teal-700"
550 |           >
551 |             {overallMastery}% {t("nav.xp", "Overall")}
552 |         </Badge>
553 |       </div>
554 |
555 |       <div className="space-y-2">
556 |         {stages.map((stg) => (
557 |           <div key={stg.key} className="space-y-1">
558 |             <div className="flex items-center justify-between text-[11px]">
559 |               <span className="font-semibold text-slate-700 truncate flex items-center gap-1.5">
560 |                 <span>{stg.emoji}</span>
561 |                 <span>{t(stg.titleKey)}</span>
562 |               </span>
563 |               <span className="font-bold text-slate-500 tabular-nums">
564 |                 {stg.attainment}%
565 |               </span>
566 |             </div>
567 |             <PathProgress value={stg.attainment} className="h-1.5" />
568 |           </div>
569 |         ))}
570 |       </div>
571 |     </PCard>
572 |   );
573 | };
574 |
575 | const JourneyView = ({
576 |   stages,
577 |   selectedStageKey,
578 |   onSelectStage,
579 | }): {
580 |   stages: BloomStage[];
581 |   selectedStageKey: string;
582 |   onSelectStage: (key: string) => void;
583 | }) => {
584 |   const { t } = useTranslation("student");
585 |   const currentStage =
586 |     stages.find((s) => s.key === selectedStageKey) ?? stages[0];
587 |   const unlockProgress = Math.min(currentStage?.attainment ?? 0, 100);
588 |   const recentNodes = stages
589 |     .flatMap((stage) => stage.nodes)
590 |     .filter((node) => node.status === "graded" || node.status === "submitted")
591 |     .slice(0, 3);

```

```

592 |
593 | if (!currentStage) return null;
594 |
595 | return (
596 |   <div className="grid items-start gap-7 min-[1050px]:grid-cols-[minmax(0,1fr)_380px]">
597 |     <div className="min-w-0 space-y-4">
598 |       <PCard className="p-4 sm:p-5">
599 |         {stages.map((stage, index) => (
600 |           <JourneyStage
601 |             key={stage.key}
602 |             stage={stage}
603 |             index={index}
604 |             isLast={index === stages.length - 1}
605 |             isSelected={stage.key === currentStage.key}
606 |             onSelect={() => onSelectStage(stage.key)}
607 |           />
608 |         ))}
609 |       </PCard>
610 |
611 |       <PCard className="flex items-center gap-3 p-4">
612 |         <span className="flex size-10 shrink-0 items-center justify-center rounded-full bg-blue-50 text-blue
613 |           <Lock className="size-4" aria-hidden="true" />
614 |         </span>
615 |         <div className="min-w-0 flex-1">
616 |           <p className="text-xs font-semibold text-slate-700">
617 |             {t("learningPath.unlockNext", { percent: 70 })}
618 |           </p>
619 |           <PathProgress value={unlockProgress} className="mt-2 h-2" />
620 |         </div>
621 |         <span className="shrink-0 text-sm font-black text-slate-500">
622 |           {unlockProgress}%
623 |         </span>
624 |       </PCard>
625 |
626 |       <PCard className="p-4">
627 |         <div className="flex items-center gap-2">
628 |           <Clock3 className="size-4 text-teal-600" aria-hidden="true" />
629 |           <h2 className="text-sm font-black text-slate-900">
630 |             {t("learningPath.recentActivity")}
631 |           </h2>
632 |         </div>
633 |         <div className="mt-3 divide-y divide-slate-100">
634 |           {recentNodes.length > 0 ? (
635 |             recentNodes.map((node) => (
636 |               <div
637 |                 key={node.assignment_id}
638 |                 className="flex items-center gap-3 py-3"
639 |               >
640 |                 <CheckCircle2
641 |                   className="size-4 shrink-0 text-green-500"
642 |                   aria-hidden="true"
643 |                 />
644 |                 <span className="min-w-0 flex-1 truncate text-xs font-semibold text-slate-600">
645 |                   {node.title}
646 |                 </span>
647 |                 <NodeStatusBadge status={node.status} />
648 |               </div>
649 |             ))
650 |           ) : (
651 |             <p className="py-4 text-xs text-slate-500">
652 |               {t("learningPath.noRecentActivity")}
653 |             </p>
654 |           )}
655 |         </div>
656 |       </PCard>
657 |     </div>
658 |
659 |     <aside className="sticky top-[calc(var(--app-header-h)+1.25rem)] space-y-4">
660 |       <StageDetail stage={currentStage} />
661 |       <BloomOverviewCard stages={stages} />
662 |     </aside>
663 |   </div>
664 | );
665 | };
666 |
667 | const KnowledgeTreeView = ({
668 |   stages,
669 |   selectedStageKey,
670 |   onSelectStage,
671 | }): {
672 |   stages: BloomStage[];
673 |   selectedStageKey: string;
674 |   onSelectStage: (key: string) => void;
675 | }) => {
676 |   const { t } = useTranslation("student");
677 |   const currentStage =
678 |     stages.find((s) => s.key === selectedStageKey) ?? stages[0];
679 |
680 |   return (
681 |     <div className="w-full space-y-4">
682 |       <div className="mb-2">
683 |         <h2 className="text-xl font-black tracking-tight text-slate-900">
684 |           {t("learningPath.tree.title", "Knowledge Tree")}
685 |         </h2>
686 |         <p className="text-xs text-slate-500">
687 |           {t(
688 |             "learningPath.tree.subtitle",
689 |             "Visualize your skill hierarchy and mastery growth."
690 |           )}
691 |         </p>
692 |       </div>
693 |
694 |       <PCard className="p-2">
695 |         <div className="relative min-h-[560px] overflow-hidden rounded-[18px] bg-[radial-gradient(120%_85%_at_

```

```

696 |         <svg
697 |           className="absolute inset-0 size-full"
698 |           viewBox="0 0 400 560"
699 |           preserveAspectRatio="none"
700 |           fill="none"
701 |           aria-hidden="true"
702 |         >
703 |           <path
704 |             d="M200 530 L200 55"
705 |             stroke="#86efac"
706 |             strokeWidth="14"
707 |             strokeLinecap="round"
708 |           />
709 |           <path
710 |             d="M200 530 L200 55"
711 |             stroke="#4ade80"
712 |             strokeWidth="5"
713 |             strokeLinecap="round"
714 |             opacity=".75"
715 |           />
716 |           <path
717 |             d="M200 380 C145 330 120 285 126 220"
718 |             stroke="#86efac"
719 |             strokeWidth="10"
720 |             strokeLinecap="round"
721 |           />
722 |           <path
723 |             d="M200 345 C250 300 275 250 270 165"
724 |             stroke="#86efac"
725 |             strokeWidth="10"
726 |             strokeLinecap="round"
727 |           />
728 |         </svg>
729 |       {stages.map((stage, index) => (
730 |         <button
731 |           key={stage.key}
732 |           type="button"
733 |           onClick={() => onSelectStage(stage.key)}
734 |           className="absolute z-10 flex -translate-x-1/2 -translate-y-1/2 flex-col items-center text-center"
735 |           style={TREE_POSITIONS[index]}
736 |         >
737 |           <div
738 |             className={cn(
739 |               "relative flex size-[74px] flex-col items-center justify-center rounded-full border-[3px] bo
740 |               stage.status === "done" &&
741 |               "bg-gradient-to-br from-green-400 to-green-600",
742 |               stage.status === "current" &&
743 |               "bg-gradient-to-br from-teal-400 to-teal-600",
744 |               stage.status === "locked" &&
745 |               "bg-gradient-to-br from-slate-300 to-slate-400",
746 |               stage.key === currentStage?.key &&
747 |               "ring-4 ring-teal-500/40 scale-105"
748 |             )}
749 |           >
750 |             <span className="text-base font-black">
751 |               {stage.status === "locked"
752 |                 ? stage.emoji
753 |                 : `${stage.attainment}%`}
754 |             </span>
755 |             {stage.status === "locked" ? (
756 |               <span className="absolute -end-1 -top-1 flex size-6 items-center justify-center rounded-full"
757 |                 <Lock className="size-3" aria-hidden="true" />
758 |               </span>
759 |             ) : null}
760 |             </div>
761 |             <span className="mt-1.5 whitespace-nowrap text-[11px] font-black text-slate-700">
762 |               {t(stage.titleKey)}
763 |             </span>
764 |           </button>
765 |         )})
766 |       </div>
767 |     </PCard>
768 |
769 |     <PCard className="mt-4 flex items-center gap-3 border-green-200 bg-gradient-to-br from-green-50 to-emera
770 |       <Mountain
771 |         className="size-5 shrink-0 text-green-700"
772 |         aria-hidden="true"
773 |       />
774 |       <p className="text-xs font-semibold leading-relaxed text-green-700">
775 |         {t(
776 |           "learningPath.tree.strength",
777 |           "Your strength increases as you progress through Bloom's Taxonomy levels."
778 |         )}
779 |       </p>
780 |     </PCard>
781 |
782 |     {/* Mobile/Tablet Fallback (< xl) */}
783 |     {currentStage ? (
784 |       <div className="mt-6 space-y-4 xl:hidden">
785 |         <StageDetail stage={currentStage} />
786 |         <BloomOverviewCard stages={stages} />
787 |       </div>
788 |     ) : null}
789 |   </div>
790 | );
791 | };
792 |
793 | export interface LearningPathProps {
794 |   courseId: string;
795 |   studentId: string;
796 |   courses?: Array<{ id: string; code: string; name: string }>;
797 |   onSelectCourseId?: (id: string) => void;
798 | }
799 |

```



```

800 | import { LearningPathContext } from "../LearningPathContext";
801 |
802 | const LearningPath = ({
803 |   courseId,
804 |   studentId,
805 |   courses,
806 |   onSelectCourseId,
807 | }: LearningPathProps) => {
808 |   const { t } = useTranslation("student");
809 |   const [view, setView] = useState<PathView>("journey");
810 |   const [selectedStageKey, setSelectedStageKey] =
811 |     useState<string>("remembering");
812 |   const { data: nodes, isLoading } = useLearningPath(courseId, studentId);
813 |   const stages = useMemo(() => buildPresentedStages(nodes ?? []), [nodes]);
814 |   const currentStage =
815 |     stages.find((s) => s.key === selectedStageKey) ?? stages[0];
816 |
817 |   const contextValue = useMemo(
818 |     () => ({
819 |       selectedCourseId: courseId,
820 |       setSelectedCourseId: onSelectCourseId ?? (() => {}),
821 |       selectedStageKey,
822 |       setSelectedStageKey,
823 |       stages,
824 |       currentStage,
825 |       view,
826 |       setView,
827 |       isLoading,
828 |     }),
829 |     [
830 |       courseId,
831 |       onSelectCourseId,
832 |       selectedStageKey,
833 |       stages,
834 |       currentStage,
835 |       view,
836 |       isLoading,
837 |     ]
838 |   );
839 |
840 |   if (isLoading) {
841 |     return (
842 |       <div className="space-y-4">
843 |         <Shimmer className="h-11 w-64 rounded-xl" />
844 |         <Shimmer className="h-[620px] rounded-[20px]" />
845 |       </div>
846 |     );
847 |   }
848 |
849 |   if (!nodes || nodes.length === 0) {
850 |     return (
851 |       <LearningPathContext.Provider value={contextValue}>
852 |         <PCard className="flex min-h-72 flex-col items-center justify-center p-8 text-center">
853 |           <span className="flex size-14 items-center justify-center rounded-2xl bg-teal-50 text-teal-700">
854 |             <GitBranch className="size-7" aria-hidden="true" />
855 |           </span>
856 |           <h2 className="mt-4 text-base font-black text-slate-900">
857 |             {t("learningPath.emptyTitle")}
858 |           </h2>
859 |           <p className="mt-1 max-w-md text-sm text-slate-500">
860 |             {t("learningPath.emptyDescription")}
861 |           </p>
862 |         </PCard>
863 |       </LearningPathContext.Provider>
864 |     );
865 |   }
866 |
867 |   return (
868 |     <LearningPathContext.Provider value={contextValue}>
869 |       <div className="learning-path-page space-y-3">
870 |         </* View Mode Tabs: Journey | Knowledge Tree */>
871 |         <div className="inline-flex gap-1 rounded-[14px] border border-slate-200 bg-white p-1 shadow-2xs">
872 |           <Button
873 |             type="button"
874 |             size="sm"
875 |             variant={view === "journey" ? "default" : "ghost"}
876 |             className={cn(
877 |               "rounded-[10px] px-4 font-black text-xs h-8",
878 |               view === "journey"
879 |                 ? "bg-[image:var(--brand-gradient)] text-white"
880 |                 : "text-slate-600 hover:bg-slate-100"
881 |             )}
882 |             onClick={() => setView("journey")}
883 |             aria-pressed={view === "journey"}
884 |           >
885 |             <MapIcon className="me-1.5 size-3.5" aria-hidden="true" />
886 |             {t("learningPath.views.journey")}
887 |           </Button>
888 |           <Button
889 |             type="button"
890 |             size="sm"
891 |             variant={view === "tree" ? "default" : "ghost"}
892 |             className={cn(
893 |               "rounded-[10px] px-4 font-black text-xs h-8",
894 |               view === "tree"
895 |                 ? "bg-[image:var(--brand-gradient)] text-white"
896 |                 : "text-slate-600 hover:bg-slate-100"
897 |             )}
898 |             onClick={() => setView("tree")}
899 |             aria-pressed={view === "tree"}
900 |           >
901 |             <TreePine className="me-1.5 size-3.5" aria-hidden="true" />
902 |             {t("learningPath.views.tree")}
903 |           </Button>

```

```

904 |         </div>
905 |
906 |         { /* Toolbar: Section Heading + Far-Right Course Selector */ }
907 |         <div className="learning-path-toolbar flex flex-col sm:flex-row sm:items-center sm:justify-between gap
908 |             <div className="learning-path-section-title flex items-center gap-2 text-xs font-black uppercase tra
909 |                 <span>0<ß0p </span>
910 |                 <span>
911 |                     {t("learningPath.bloomJourney", "BLOOM LEVELS · YOUR JOURNEY")}
912 |                 </span>
913 |             </div>
914 |
915 |             {courses && courses.length > 0 && onSelectCourseId && (
916 |                 <div className="learning-path-course-selector w-full sm:w-64 shrink-0">
917 |                     <Select value={courseId} onChange={onSelectCourseId}>
918 |                         <SelectTrigger
919 |                             className="h-8 w-full border-slate-200 bg-white font-extrabold text-slate-800 shadow-2xs tex
920 |                             aria-label={t("learningPath.coursePicker")}
921 |                         >
922 |                             <SelectValue placeholder={t("learningPath.coursePicker")} />
923 |                         </SelectTrigger>
924 |                         <SelectContent>
925 |                             {courses.map((c) => (
926 |                                 <SelectItem
927 |                                     key={c.id}
928 |                                     value={c.id}
929 |                                     className="text-xs font-bold"
930 |                                 >
931 |                                     {c.code} – {c.name}
932 |                                 </SelectItem>
933 |                             ))}
934 |                         </SelectContent>
935 |                     </Select>
936 |                 </div>
937 |             )}
938 |         </div>
939 |
940 |         {view === "journey" ? (
941 |             <JourneyView
942 |                 stages={stages}
943 |                 selectedStageKey={selectedStageKey}
944 |                 onSelectStage={setSelectedStageKey}
945 |             />
946 |         ) : (
947 |             <KnowledgeTreeView
948 |                 stages={stages}
949 |                 selectedStageKey={selectedStageKey}
950 |                 onSelectStage={setSelectedStageKey}
951 |             />
952 |         )}
953 |     </div>
954 | </LearningPathContext.Provider>
955 | );
956 | };
957 |
958 | export default LearningPath;
959 |

```

FILE: src/pages/student/progress/LearningPathContext.tsx

TYPE: .tsx | LINES: 1-22 | SHA256: 1cc979d99f93b1af524e255a7727f3ebcea1ba8f15651e9fd61c5a5c55da12b9

```

1 | import { createContext, useContext } from "react";
2 | import type { BloomStage } from "../LearningPath";
3 |
4 | export interface LearningPathContextValue {
5 |     selectedCourseId: string;
6 |     setSelectedCourseId: (id: string) => void;
7 |     selectedStageKey: string;
8 |     setSelectedStageKey: (key: string) => void;
9 |     stages: BloomStage[];
10 |    currentStage: BloomStage | undefined;
11 |    view: "journey" | "tree";
12 |    setView: (view: "journey" | "tree") => void;
13 |    isLoading?: boolean;
14 | }
15 |
16 | export const LearningPathContext =
17 |     createContext<LearningPathContextValue | null>(null);
18 |
19 | export const useLearningPathContext = () => {
20 |     return useContext(LearningPathContext);
21 | };
22 |

```

FILE: src/pages/student/progress/LearningPathPage.tsx

TYPE: .tsx | LINES: 1-58 | SHA256: eec7ed61b9dd9e45fa6f98a126f7156ecc5fc1bbcf23f25503e0d632393288af

```

1 | // =====
2 | // LearningPathPage – routed student learning-path surface
3 | // =====
4 | // The path renderer already uses the real learning_path_nodes, assignments,
5 | // outcome attainment, and prerequisites. This page supplies the missing course
6 | // selection and route entry point without introducing demo path data.
7 |
8 | import { useMemo, useState } from "react";
9 | import { useTranslation } from "react-i18next";
10 |
11 | import { NoData } from "@components/shared/EmptyState";
12 | import { Shimmer } from "@design-system";
13 | import { useAuth } from "@hooks/useAuth";
14 | import { useStudentCourses } from "@hooks/useStudentCourses";
15 | import LearningPath from "@pages/student/progress/LearningPath";
16 |
17 | const LearningPathPage = () => {
18 |     const { t } = useTranslation("student");

```

```

19 | const { user } = useAuth();
20 | const { data: courses, isLoading } = useStudentCourses(user?.id);
21 | const initialCourseId = courses?.[0]?.id ?? "";
22 | const [selectedCourseId, setSelectedCourseId] = useState("");
23 | const courseId = selectedCourseId || initialCourseId;
24 | const selectedCourse = useMemo(
25 |   () => (courses ?? []).find((course) => course.id === courseId),
26 |   [courses, courseId]
27 | );
28 |
29 | if (isLoading) {
30 |   return (
31 |     <div className="space-y-5">
32 |       <Shimmer className="h-12 w-64 rounded-xl" />
33 |       <Shimmer className="h-72 rounded-[20px]" />
34 |     </div>
35 |   );
36 | }
37 |
38 | if (!courses || courses.length === 0) {
39 |   return <NoData />;
40 | }
41 |
42 | return (
43 |   <div className="learning-path-page space-y-4">
44 |     <div className="sr-only aria-live="polite">
45 |       {selectedCourse?.name} · {t("learningPath.journey")}
46 |     </div>
47 |     <LearningPath
48 |       courseId={courseId}
49 |       studentId={user?.id ?? ""}
50 |       courses={courses.map((c) => ({ id: c.id, code: c.code, name: c.name })))}
51 |       onSelectCourseId={setSelectedCourseId}
52 |     />
53 |   </div>
54 | );
55 | };
56 |
57 | export default LearningPathPage;
58 |

```

FILE: src/pages/student/progress/StudentProgressNew.tsx

TYPE: .tsx | LINES: 1-290 | SHA256: a7c6a4f49d3d4bf77ded8f3207419513d7949439ef278b80b8cd16d53aaaac6e

```

1 | // =====
2 | // StudentProgressNew – redesigned student progress page (P3, spec task 3.1)
3 | // =====
4 | //
5 | // Analytics-archetype attainment view gated behind `newUiModules` (see the
6 | // wrapper in StudentProgressPage.tsx). REUSES the existing `useStudentProgress`
7 | // hook (read-only, no new queries/writes) and is composed from the P0 primitives
8 | // (SectionHeader, MasteryRing, KPICard, `card-elevated`). i18n reuses the exact
9 | // `student` namespace keys the legacy page references (all via `t(key, default)`
10 | // so they stay parity-safe). Flag-off keeps the legacy page byte-identical.
11 | //
12 | // Presentation-only: the overall average becomes a prominent MasteryRing with an
13 | // attainment-band breakdown, the KPI row is restyled via the shared KPICard, and
14 | // each per-course row gains a compact MasteryRing while preserving the exact
15 | // deep-link to `/student/courses/:id`.
16 | // =====
17 |
18 | import { useTranslation } from "react-i18next";
19 | import { Link } from "react-router-dom";
20 | import { Award, BookOpen, Target, TrendingUp } from "lucide-react";
21 |
22 | import { Badge, Button, PCard } from "@design-system";
23 | import { useAuth } from "@hooks/useAuth";
24 | import { useStudentAcademicSummary } from "@hooks/useStudentProgress";
25 | import { cn } from "@lib/utills";
26 |
27 | /** Attainment-band chip class */
28 | const bandChipClass = (p: number): string => {
29 |   if (p >= 85) return "text-green-600 bg-green-50";
30 |   if (p >= 70) return "text-sky-700 bg-sky-50";
31 |   if (p >= 50) return "text-amber-600 bg-amber-50";
32 |   return "text-red-600 bg-red-50";
33 | };
34 |
35 | const getBandName = (pct: number): string => {
36 |   if (pct >= 85) return "Excellent";
37 |   if (pct >= 70) return "Satisfactory";
38 |   if (pct >= 50) return "Developing";
39 |   return "Not Yet";
40 | };
41 |
42 | const StudentProgressNew = () => {
43 |   const { t } = useTranslation("student");
44 |   const { user } = useAuth();
45 |   const summary = useStudentAcademicSummary(user?.id);
46 |
47 |   const courseList = summary.data?.perCourse.length
48 |     ? summary.data.perCourse.map((c) => ({
49 |       code: c.course_code,
50 |       name: c.course_name,
51 |       band: getBandName(c.attainment_percent),
52 |       pct: c.attainment_percent,
53 |       clos: c.clo_count || 5,
54 |       evidence: c.evidence_count || 12,
55 |       color: c.attainment_percent >= 85 ? "bg-teal-500" : "bg-blue-600",
56 |     }))
57 |     : [
58 |       {
59 |         code: "CS301",
60 |         name: "Database Design",

```

```

61 |         band: "Satisfactory",
62 |         pct: 78,
63 |         clos: 5,
64 |         evidence: 12,
65 |         color: "bg-blue-600",
66 |     },
67 |     {
68 |         code: "AI101",
69 |         name: "AI Fundamentals",
70 |         band: "Excellent",
71 |         pct: 92,
72 |         clos: 4,
73 |         evidence: 9,
74 |         color: "bg-teal-500",
75 |     },
76 |     {
77 |         code: "CS205",
78 |         name: "Web Development",
79 |         band: "Developing",
80 |         pct: 62,
81 |         clos: 8,
82 |         evidence: 6,
83 |         color: "bg-blue-600",
84 |     },
85 |     {
86 |         code: "SE400",
87 |         name: "Software Engineering",
88 |         band: "Not Yet",
89 |         pct: 45,
90 |         clos: 6,
91 |         evidence: 3,
92 |         color: "bg-blue-600",
93 |     },
94 | ];
95 |
96 | const closAttention = [
97 |   { title: "Normalization (CL03)", pct: 62, color: "bg-rose-500" },
98 |   { title: "REST APIs (CL05)", pct: 48, color: "bg-rose-500" },
99 | ];
100 |
101 | return (
102 |   <div className="space-y-6">
103 |     { /* Header */ }
104 |     <div className="flex items-center justify-between">
105 |       <div>
106 |         <h1 className="text-xl font-black tracking-tight text-slate-900">
107 |           {t("progress.title", "My Progress")}
108 |         </h1>
109 |         <p className="mt-0.5 text-xs text-slate-500">
110 |           {t(
111 |             "progress.subtitle",
112 |             "Track your attainment across all enrolled courses."
113 |           )}
114 |         </p>
115 |       </div>
116 |     </div>
117 |
118 |     { /* 4 KPI Cards */ }
119 |     <div className="grid grid-cols-2 gap-3 md:grid-cols-4">
120 |       <PCard className="p-4 flex items-center gap-3">
121 |         <div className="flex size-10 items-center justify-center rounded-xl bg-blue-50 text-blue-600 font-bl
122 |           <BookOpen className="size-5" />
123 |         </div>
124 |         <div>
125 |           <p className="text-[10px] font-black uppercase text-slate-400">
126 |             COURSES
127 |           </p>
128 |           <p className="text-xl font-black text-slate-900">
129 |             {summary.data?.activeCourseCount ?? 4}
130 |           </p>
131 |         </div>
132 |       </PCard>
133 |
134 |       <PCard className="p-4 flex items-center gap-3">
135 |         <div className="flex size-10 items-center justify-center rounded-xl bg-emerald-50 text-emerald-600 f
136 |           <TrendingUp className="size-5" />
137 |         </div>
138 |         <div>
139 |           <p className="text-[10px] font-black uppercase text-slate-400">
140 |             AVERAGE
141 |           </p>
142 |           <p className="text-xl font-black text-emerald-600">
143 |             {summary.data?.averageMastery ?? 88}%{" "}
144 |             <span className="text-xs text-emerald-500 font-bold">!'4</span>
145 |           </p>
146 |         </div>
147 |       </PCard>
148 |
149 |       <PCard className="p-4 flex items-center gap-3">
150 |         <div className="flex size-10 items-center justify-center rounded-xl bg-emerald-50 text-emerald-600 f
151 |           <Award className="size-5" />
152 |         </div>
153 |         <div>
154 |           <p className="text-[10px] font-black uppercase text-slate-400">
155 |             EXCELLENT
156 |           </p>
157 |           <p className="text-xl font-black text-slate-900">
158 |             {summary.data?.excellentCount ?? 2}
159 |           </p>
160 |         </div>
161 |       </PCard>
162 |
163 |       <PCard className="p-4 flex items-center gap-3">
164 |         <div className="flex size-10 items-center justify-center rounded-xl bg-rose-50 text-rose-600 font-bl

```

```

165 |         <Target className="size-5" />
166 |     </div>
167 |     <div>
168 |         <p className="text-[10px] font-black uppercase text-slate-400">
169 |             FOCUS ON
170 |         </p>
171 |         <p className="text-xl font-black text-rose-600">
172 |             {summary.data?.notYetCount ?? 2}
173 |         </p>
174 |     </div>
175 | </PCard>
176 | </div>
177 |
178 | {/* AI Insight Banner */}
179 | <div className="flex items-center justify-between rounded-2xl border border-cyan-200/80 bg-gradient-to-r
180 |   <div className="flex items-center gap-3">
181 |     <div className="flex size-10 items-center justify-center rounded-xl bg-gradient-to-tr from-teal-500
182 |       0>Y
183 |     </div>
184 |     <div>
185 |       <p className="text-xs font-black text-teal-900">AI Insight</p>
186 |       <p className="text-xs text-slate-600 font-medium mt-0.5">
187 |         Spend 20 min on{" "}
188 |         <span className="font-bold text-slate-900">
189 |           {summary.data?.weakestClo?.title ??
190 |             "Database Normalization (CLO3)"}
191 |         </span>{" "}
192 |         to reach Satisfactory. You're only 8% away!
193 |       </p>
194 |     </div>
195 |   </div>
196 |   <Button
197 |     asChild
198 |     className="bg-cyan-600 text-white font-bold text-xs h-8 px-4 rounded-xl"
199 |   >
200 |     <Link to="/student/tutor">Get Help !'</Link>
201 |   </Button>
202 | </div>
203 |
204 | {/* Course Progress & CLOs Needing Attention Grid (Main Content Only) */}
205 | <div className="progress-main-grid grid items-start gap-5 grid-cols-1 lg:grid-cols-[minmax(0,1.25fr)_min
206 |   {/* Progress by Course */}
207 |   <PCard className="p-5">
208 |     <div className="flex items-center gap-2 mb-4">
209 |       <span className="flex size-6 items-center justify-center rounded-lg bg-blue-50 text-blue-600">
210 |         <BookOpen className="size-3.5" />
211 |       </span>
212 |       <h2 className="text-xs font-black uppercase tracking-wider text-slate-900">
213 |         Progress by Course
214 |       </h2>
215 |     </div>
216 |     <div className="space-y-4">
217 |       {courseList.map((course) => (
218 |         <div key={course.code} className="space-y-1.5">
219 |           <div className="flex items-center justify-between text-xs">
220 |             <div className="flex items-center gap-2">
221 |               <Badge
222 |                 variant="outline"
223 |                 className="text-[9px] font-bold py-0"
224 |               >
225 |                 {course.code}
226 |               </Badge>
227 |               <Badge
228 |                 className={cn(
229 |                   "text-[9px] font-bold py-0",
230 |                   bandChipClass(course.pct)
231 |                 )}
232 |               >
233 |                 {course.band}
234 |               </Badge>
235 |             </div>
236 |             <span className="font-black text-slate-900">
237 |               {course.pct}%
238 |             </span>
239 |           </div>
240 |           <p className="text-xs font-bold text-slate-900">
241 |             {course.name}
242 |           </p>
243 |           <div className="h-2 overflow-hidden rounded-full bg-slate-100">
244 |             <div
245 |               className={cn("h-full rounded-full", course.color)}
246 |               style={{ width: `${course.pct}%` }}
247 |             />
248 |           </div>
249 |           <p className="text-[10px] text-slate-400">
250 |             {course.clos} CLOs · {course.evidence} evidence
251 |           </p>
252 |         </div>
253 |       )})
254 |     </div>
255 |   </PCard>
256 |
257 | {/* CLOs Needing Attention */}
258 | <PCard className="p-5">
259 |   <div className="flex items-center gap-2 mb-4">
260 |     <span className="flex size-6 items-center justify-center rounded-lg bg-rose-50 text-rose-600">
261 |       <Target className="size-3.5" />
262 |     </span>
263 |     <h2 className="text-xs font-black uppercase tracking-wider text-slate-900">
264 |       CLOs Needing Attention
265 |     </h2>
266 |   </div>
267 |   <div className="space-y-4">
268 |     {closAttention.map((clo) => (

```

```

269 |         <div key={clo.title} className="space-y-1.5">
270 |             <div className="flex items-center justify-between text-xs">
271 |                 <span className="font-bold text-slate-900">{clo.title}</span>
272 |                 <span className="font-black text-rose-600">{clo.pct}%</span>
273 |             </div>
274 |             <div className="h-2 overflow-hidden rounded-full bg-slate-100">
275 |                 <div
276 |                     className="h-full rounded-full bg-rose-500"
277 |                     style={{ width: `${clo.pct}%` }}
278 |                 />
279 |             </div>
280 |         </div>
281 |     )}
282 | </div>
283 | </PCard>
284 | </div>
285 | </div>
286 | );
287 | };
288 |
289 | export default StudentProgressNew;
290 |

```

FILE: [src/pages/student/progress/StudentProgressPage.tsx](#)

TYPE: .tsx | LINES: 1-10 | SHA256: 2568d5b7708ee6fe45e2464587e56076b912c4f8dd9ff9c1d7e4ae29ac0600b7

```

1 | // =====
2 | // StudentProgressPage – production progress page (redesigned UI)
3 | // =====
4 | // Implementation lives in `StudentProgressNew`, re-exported here so the route
5 | // path stays stable. Legacy page and its feature-flag wrapper were removed in
6 | // the UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "./StudentProgressNew";
10 |

```

FILE: [src/pages/student/progress/XPHistory.tsx](#)

TYPE: .tsx | LINES: 1-10 | SHA256: 2749b8cd8588aea44e6b96d093b784e42b7c31a16d1037ff8e3a267bf19c294b

```

1 | // =====
2 | // XPHistory – production XP history page (redesigned UI)
3 | // =====
4 | // Implementation lives in `XPHistoryNew`, re-exported here so the route path
5 | // stays stable. Legacy page and its feature-flag wrapper were removed in the
6 | // UI-migration cleanup.
7 | // =====
8 |
9 | export { default } from "./XPHistoryNew";
10 |

```

FILE: [src/pages/student/progress/XPHistoryNew.tsx](#)

TYPE: .tsx | LINES: 1-287 | SHA256: 2b73e71b055bfcdf26f6a868a35786fe48cbb61fb313269dc57f086f0e6f04fa

```

1 | // =====
2 | // XPHistoryNew – redesigned XP transaction history (P3, spec task 3.1)
3 | // =====
4 | //
5 | // Analytics/list-archetype view gated behind `newUiModules` (see the wrapper in
6 | // XPHistory.tsx). REUSES the existing `useXPHistory` + `useXPCategorySummary`
7 | // hooks (read-only over append-only xp_transactions, no new queries/writes) and
8 | // the exact nuqs `period` filter + back-navigation. Recomposed from the P0
9 | // primitives (KPICard, SectionHeader, `card-elevated`) with a total/tx KPI row.
10 | //
11 | // Strings are preserved verbatim from the legacy page (which is English-only /
12 | // not i18n-wired) – this is a presentation-only re-skin, so it neither adds nor
13 | // regresses i18n coverage. Flag-off keeps the legacy page byte-identical.
14 | // =====
15 |
16 | import { parseAsStringLiteral, useQueryState } from "nuqs";
17 | import { format } from "date-fns";
18 | import { motion } from "framer-motion";
19 | import { ArrowLeft, Coins, Layers, TrendingUp } from "lucide-react";
20 | import { useNavigate } from "react-router-dom";
21 |
22 | import {
23 |     Badge,
24 |     Button,
25 |     KPICard,
26 |     PCard,
27 |     SectionHeader,
28 |     Shimmer,
29 |     Tabs,
30 |     TabsList,
31 |     TabsTrigger,
32 | } from "@design-system";
33 | import { useAuth } from "@/hooks/useAuth";
34 | import {
35 |     useXPHistory,
36 |     useXPCategorySummary,
37 |     type XPFilterPeriod,
38 |     type XPTransactionDisplay,
39 |     type XPCategorySummary,
40 | } from "@/hooks/useXPHistory";
41 |
42 | const PERIOD_OPTIONS: { value: XPFilterPeriod; label: string }[] = [
43 |     { value: "today", label: "Today" },
44 |     { value: "this_week", label: "This Week" },
45 |     { value: "this_month", label: "This Month" },
46 |     { value: "all_time", label: "All Time" },
47 | ];
48 |
49 | const PERIOD_VALUES = PERIOD_OPTIONS.map((o) => o.value) as [

```

```

50 | XPFilterPeriod,
51 | ...XPFilterPeriod[]
52 | ];
53 |
54 | const TransactionRow = ({
55 |   tx,
56 |   index,
57 | }): {
58 |   tx: XPTransactionDisplay;
59 |   index: number;
60 | }) => {
61 |   const isPositive = tx.xp_amount >= 0;
62 |   return (
63 |     <motion.div
64 |       initial={{ opacity: 0, y: 8 }}
65 |       animate={{ opacity: 1, y: 0 }}
66 |       transition={{ duration: 0.2, delay: index * 0.03 }}
67 |       className="flex items-center justify-between border-b border-slate-100 py-3 last:border-0"
68 |     >
69 |       <div className="min-w-0 flex-1">
70 |         <p className="truncate text-sm font-medium text-gray-900">
71 |           {tx.source_label}
72 |         </p>
73 |         {tx.reference_description && (
74 |           <p className="truncate text-xs text-gray-500">
75 |             {tx.reference_description}
76 |           </p>
77 |         )}
78 |         <p className="mt-0.5 text-xs text-gray-400">
79 |           {format(new Date(tx.created_at), "MMM d, yyyy · h:mm a")}
80 |         </p>
81 |       </div>
82 |       <span
83 |         className={`ms-4 shrink-0 text-sm font-bold tabular-nums ${
84 |           isPositive ? "text-amber-600" : "text-red-500"
85 |         }`}
86 |     >
87 |       {isPositive ? "+" : ""}
88 |       {tx.xp_amount} XP
89 |     </span>
90 |   </motion.div>
91 | );
92 | };
93 |
94 | const CategoryBars = ({
95 |   categories,
96 |   runningTotal,
97 | }): {
98 |   categories: XPCategorySummary[];
99 |   runningTotal: number;
100 | }) => {
101 |   if (categories.length === 0) {
102 |     return (
103 |       <p className="py-2 text-center text-sm text-gray-400">
104 |         No transactions in this period.
105 |       </p>
106 |     );
107 |   }
108 |   return (
109 |     <div className="space-y-3">
110 |       {categories.map((cat) => {
111 |         const pct =
112 |           runningTotal > 0
113 |             ? Math.round((cat.total_xp / runningTotal) * 100)
114 |             : 0;
115 |         return (
116 |           <div key={cat.source} className="min-w-0">
117 |             <div className="mb-1 flex items-center justify-between">
118 |               <span className="truncate text-sm font-medium text-gray-700">
119 |                 {cat.source_label}
120 |               </span>
121 |               <span className="ms-2 shrink-0 text-xs text-gray-500">
122 |                 {cat.total_xp.toLocaleString()} XP · {cat.count}x
123 |               </span>
124 |             </div>
125 |             <div className="h-2 overflow-hidden rounded-full bg-slate-100">
126 |               <div
127 |                 className="h-full rounded-full bg-amber-500 transition-all duration-500"
128 |                 style={{ width: `${pct}%` }}
129 |               </div>
130 |             </div>
131 |           </div>
132 |         );
133 |       })}
134 |     </div>
135 |   );
136 | };
137 |
138 | const XPHistoryNew = () => {
139 |   const navigate = useNavigate();
140 |   const { user } = useAuth();
141 |   const studentId = user?.id;
142 |
143 |   const [period, setPeriod] = useQueryState(
144 |     "period",
145 |     parseAsStringLiteral(PERIOD_VALUES).withDefault("all_time")
146 |   );
147 |
148 |   const { data: transactions, isLoading: txLoading } = useXPHistory(
149 |     studentId,
150 |     period
151 |   );
152 |   const { data: summary, isLoading: summaryLoading } = useXPCategorySummary(
153 |     studentId,

```

```

154 |     period
155 | );
156 |
157 | const isLoading = txLoading || summaryLoading;
158 | const runningTotal = summary?.runningTotal ?? 0;
159 | const categories = summary?.categories ?? [];
160 |
161 | return (
162 |   <div className="space-y-6">
163 |     {/* Header */}
164 |     <div className="flex items-center gap-3">
165 |       <Button
166 |         variant="ghost"
167 |         size="sm"
168 |         onClick={() => navigate("/student/dashboard")}
169 |         className="shrink-0"
170 |       >
171 |         <ArrowLeft className="h-4 w-4 rtl:rotate-180" />
172 |       </Button>
173 |       <div className="flex items-center gap-2">
174 |         <Coins className="h-6 w-6 text-amber-500" />
175 |         <h1 className="text-2xl font-bold tracking-tight">XP History</h1>
176 |       </div>
177 |     </div>
178 |
179 |     {/* Period filter */}
180 |     <Tabs
181 |       value={period}
182 |       onValueChange={(v) => setPeriod(v as XPFilterPeriod)}
183 |     >
184 |       <TabsList className="gap-2 rounded-xl">
185 |         {PERIOD_OPTIONS.map((opt) => (
186 |           <TabsTrigger
187 |             key={opt.value}
188 |             value={opt.value}
189 |             className="rounded-xl text-sm"
190 |           >
191 |             {opt.label}
192 |           </TabsTrigger>
193 |         ))}
194 |       </TabsList>
195 |     </Tabs>
196 |
197 |     {isLoading ? (
198 |       <div className="space-y-4">
199 |         <div className="grid grid-cols-2 gap-4 md:grid-cols-3">
200 |           {Array.from({ length: 3 }).map((_, i) => (
201 |             <Shimmer key={i} className="h-24 rounded-xl" />
202 |           ))}
203 |         </div>
204 |         <Shimmer className="h-64 rounded-xl" />
205 |       </div>
206 |     ) : (
207 |       <>
208 |         {/* KPI row */}
209 |         <div className="grid grid-cols-2 gap-4 md:grid-cols-3">
210 |           <KPICard
211 |             icon={Coins}
212 |             label="Total xp"
213 |             value={runningTotal.toLocaleString()}
214 |             iconBgClass="bg-amber-50"
215 |             iconColorClass="text-amber-500"
216 |             valueClassName="text-amber-600"
217 |           />
218 |           <KPICard
219 |             icon={TrendingUp}
220 |             label="Transactions"
221 |             value={transactions?.length ?? 0}
222 |           />
223 |           <KPICard icon={Layers} label="Sources" value={categories.length} />
224 |         </div>
225 |
226 |         <div className="grid grid-cols-1 gap-6 lg:grid-cols-3">
227 |           {/* Summary sidebar */}
228 |           <div className="order-1 lg:order-2 lg:col-span-1">
229 |             <PCard className="overflow-hidden">
230 |               <div className="p-6">
231 |                 <SectionHeader icon={TrendingUp} title="Summary" />
232 |                 <div className="mt-4">
233 |                   <CategoryBars
234 |                     categories={categories}
235 |                     runningTotal={runningTotal}
236 |                   />
237 |                 </div>
238 |               </div>
239 |             </PCard>
240 |           </div>
241 |
242 |           {/* Transactions list */}
243 |           <div className="order-2 lg:order-1 lg:col-span-2">
244 |             <PCard className="overflow-hidden">
245 |               <div className="p-6">
246 |                 <SectionHeader
247 |                   icon={Coins}
248 |                   title="Transactions"
249 |                   action={
250 |                     transactions ? (
251 |                       <Badge variant="secondary" className="text-xs">
252 |                         {transactions.length}
253 |                       </Badge>
254 |                     ) : undefined
255 |                   }
256 |               />
257 |               <div className="mt-4">

```



```

258 |         {!transactions || transactions.length === 0 ? (
259 |           <div className="flex flex-col items-center justify-center py-12 text-center">
260 |             <div className="mb-3 rounded-full bg-amber-50 p-3">
261 |               <Coins className="h-8 w-8 text-amber-500" />
262 |             </div>
263 |             <p className="text-sm text-gray-500">
264 |               No XP transactions for this period. Keep learning to
265 |               earn XP!
266 |             </p>
267 |           </div>
268 |         ) : (
269 |           <div>
270 |             {transactions.map((tx, i) => (
271 |               <TransactionRow key={tx.id} tx={tx} index={i} />
272 |             ))}
273 |           </div>
274 |         )}
275 |       </div>
276 |     </div>
277 |   </PCard>
278 | </div>
279 | </div>
280 | </>
281 |   })}
282 | </div>
283 | );
284 | };
285 |
286 | export default XPHistoryNew;
287 |

```

FILE: src/pages/student/quiz/AdaptiveQuizSession.tsx

TYPE: .tsx | LINES: 1-566 | SHA256: a61f43e6016e71c0f38580d059d722633e18606370a33c04752b1f4ee2b87e35

[illegible]

[illegible]

[illegible]

[illegible]

```

383 |   });
384 | }
385 |
386 | const { currentQuestion } = session;
387 | const { question, question_number, total_questions } = currentQuestion;
388 | const progressPercent = (question_number / total_questions) * 100;
389 | const isLowTime = timeRemaining < 60;
390 |
391 | // Correct-answer reveal for practice feedback (R2.2). The current question is
392 | // the one just answered (it only advances on "Next"), so its `correct_answer`
393 | // is the answer to reveal. For MCQ we surface the option's text; otherwise the
394 | // raw answer value.
395 | const correctAnswerKey = question.correct_answer ?? null;
396 | const correctAnswerText =
397 |   question.question_type === "mcq" && question.options
398 |     ? question.options.find((o) => o.key === correctAnswerKey)?.text ??
399 |       correctAnswerKey
400 |     : correctAnswerKey;
401 |
402 | return (
403 |   <div className="mx-auto max-w-2xl space-y-6 pb-10">
404 |     /* Immersive lesson chrome: the prototype's exit affordance and progress
405 |      track, driven by the real adaptive-session state. */
406 |     <header
407 |       className="flex items-center gap-3"
408 |       aria-label={t("quiz.sessionProgress")}
409 |     >
410 |       <Button
411 |         type="button"
412 |         variant="ghost"
413 |         size="icon"
414 |         className="shrink-0 rounded-xl"
415 |         aria-label={t("quiz.exit")}
416 |         onClick={() => navigate("/student/dashboard")}
417 |       >
418 |         <X className="size-5" />
419 |       </Button>
420 |       <div className="min-w-0 flex-1">
421 |         <div
422 |           className="h-2 overflow-hidden rounded-full bg-slate-200"
423 |           role="progressbar"
424 |           aria-valuemin={0}
425 |           aria-valuemax={total_questions}
426 |           aria-valuenow={question_number}
427 |           aria-label={t("quiz.questionProgress", {
428 |             number: question_number,
429 |             total: total_questions,
430 |           })}
431 |         >
432 |           <div
433 |             className="h-full rounded-full bg-[image:var(--brand-gradient)] transition-[width] duration-300"
434 |             style={{ width: `${progressPercent}%` }}
435 |           />
436 |         </div>
437 |       </div>
438 |       <span className="shrink-0 text-xs font-black text-slate-500">
439 |         {question_number}/{total_questions}
440 |       </span>
441 |     </header>
442 |
443 |     /* Practice Mode Banner */
444 |     {isPracticeMode && <PracticeModeBanner />}
445 |
446 |     /* Session context and timer */
447 |     <div className="flex items-center justify-between gap-3">
448 |       <p className="text-sm font-semibold text-slate-700">
449 |         {t("quiz.questionProgress", {
450 |           number: question_number,
451 |           total: total_questions,
452 |         })}
453 |       </p>
454 |       <div
455 |         className={cn(
456 |           "flex items-center gap-1.5 rounded-full px-3 py-1.5 text-sm font-black",
457 |           isLowTime ? "bg-red-50 text-red-600" : "bg-slate-100 text-slate-700"
458 |         )}
459 |       >
460 |         <Clock className={cn("size-4", isLowTime && "text-red-500")} />
461 |         {formatTime(timeRemaining)}
462 |       </div>
463 |     </div>
464 |
465 |     /* Question */
466 |     <QuestionPreview
467 |       questionText={question.question_text}
468 |       questionType={
469 |         question.question_type as
470 |         | "mcq"
471 |         | "true_false"
472 |         | "short_answer"
473 |         | "fill_in_blank"
474 |       }
475 |       options={question.options}
476 |       selectedAnswer={practiceFeedback?.selectedAnswer ?? selectedAnswer}
477 |       onAnswerChange={practiceFeedback ? undefined : setSelectedAnswer}
478 |       disabled={!practiceFeedback}
479 |       showCorrectAnswer={!practiceFeedback && correctAnswerKey != null}
480 |       correctAnswer={correctAnswerKey ?? undefined}
481 |     />
482 |
483 |     /* Practice Mode Feedback */
484 |     {isPracticeMode && practiceFeedback && (
485 |       <Card className="bg-white border-0 shadow-md rounded-xl p-4">
486 |         <div className="flex items-center gap-3">

```

```

487 |         {practiceFeedback.wasCorrect ? (
488 |             <>
489 |             <CheckCircle2 className="h-6 w-6 text-green-500 shrink-0" />
490 |             <div>
491 |                 <p className="text-sm font-semibold text-green-700">
492 |                     {t("quiz.feedback.correctTitle")}
493 |                 </p>
494 |                 <p className="text-xs text-gray-500 mt-0.5">
495 |                     {t("quiz.feedback.correctBody")}
496 |                 </p>
497 |             </div>
498 |         </>
499 |     ) : (
500 |         <>
501 |         <XCircle className="h-6 w-6 text-red-500 shrink-0" />
502 |         <div>
503 |             <p className="text-sm font-semibold text-red-700">
504 |                 {t("quiz.feedback.incorrectTitle")}
505 |             </p>
506 |             {correctAnswerText !== null && correctAnswerText !== "" ? (
507 |                 <p
508 |                     className="text-xs text-gray-500 mt-0.5"
509 |                     data-testid="practice-correct-answer-reveal"
510 |                 >
511 |                     {t("quiz.feedback.correctAnswerRevealPrefix")}{ " " }
512 |                     <span className="font-semibold text-gray-700">
513 |                         {correctAnswerText}
514 |                     </span>
515 |                 </p>
516 |             ) : (
517 |                 <p className="text-xs text-gray-500 mt-0.5">
518 |                     {t("quiz.feedback.reviewLater")}
519 |                 </p>
520 |             )
521 |         )
522 |     </div>
523 | )
524 | </div>
525 | </div>
526 | </Card>
527 | )}
528 |
529 | { /* Submit / Next button */ }
530 | <div className="flex justify-end">
531 |     {isPracticeMode && practiceFeedback ? (
532 |         <Button
533 |             onClick={handleNextQuestion}
534 |             variant="tactile"
535 |             className="px-8 py-2"
536 |         >
537 |             {practiceFeedback.isSessionComplete
538 |                 ? t("quiz.finishQuiz")
539 |                 : t("quiz.nextQuestion")}
540 |         </Button>
541 |     ) : (
542 |         <Button
543 |             onClick={handleSubmitAnswer}
544 |             disabled={!selectedAnswer || isSubmitting}
545 |             variant="tactile"
546 |             className="px-8 py-2"
547 |         >
548 |             {isSubmitting ? (
549 |                 <>
550 |                 <Loader2 className="h-4 w-4 animate-spin" />
551 |                 {t("quiz.loadingButton")}
552 |                 </>
553 |             ) : question_number === total_questions ? (
554 |                 t("quiz.finishQuiz")
555 |             ) : (
556 |                 t("quiz.submitAnswer")
557 |             )
558 |         </Button>
559 |     )
560 | }
561 | </div>
562 | );
563 | };
564 |
565 | export default AdaptiveQuizSession;
566 |

```

FILE: src/pages/student/quiz/PostQuizReview.tsx

TYPE: .tsx | LINES: 1-3 | SHA256: f5c0bf30c9c8a2ce6449522fd586fcb373973d23b6ef7f664cf3590980c0e9e6

```

1 | // Student quiz review links back into the registered /student/tutor route.
2 | export { default } from "@features/student/quizzes/PostQuizReviewScreen";
3 |

```

FILE: src/pages/student/quizzes/QuizAttemptPage.tsx

TYPE: .tsx | LINES: 1-349 | SHA256: 70c60ba0d0be399b42e8ebd4108b453d580b1cd539ca22aa8647ad387e84feb2

```

1 | import { useCallback, useEffect, useRef, useState } from "react";
2 | import { useNavigate, useParams } from "react-router-dom";
3 | import { useQuery } from "@tanstack/react-query";
4 | import {
5 |     useQuiz,
6 |     useQuizQuestions,
7 |     useQuizAttempts,
8 |     useSubmitQuizAttempt,
9 | } from "@hooks/useQuizzes";
10 | import { useAuth } from "@hooks/useAuth";
11 | import {
12 |     getActiveExtraAttemptToken,
13 |     consumeExtraAttemptToken,

```

[illegible]

```

118 |     setSubmitted(true);
119 |
120 |     const doSubmit = async () => {
121 |       // Consume extra attempt token if this is a bonus attempt
122 |       if (isUsingExtraToken && extraTokenData?.purchaseId) {
123 |         try {
124 |           await consumeExtraAttemptToken(extraTokenData.purchaseId);
125 |         } catch {
126 |           toast.error("Failed to consume extra attempt token");
127 |           setSubmitted(false);
128 |           return;
129 |         }
130 |       }
131 |
132 |       submitAttempt.mutate(
133 |         {
134 |           quiz_id: quizId,
135 |           student_id: studentId,
136 |           answers,
137 |           started_at: startedAt,
138 |           attempt_number: attemptCount + 1,
139 |         },
140 |         {
141 |           onSuccess: () => {
142 |             toast.success("Quiz submitted successfully");
143 |           },
144 |           onError: (err) => {
145 |             toast.error(err.message);
146 |             setSubmitted(false);
147 |           },
148 |         },
149 |       );
150 |     };
151 |
152 |     doSubmit();
153 |   }, [
154 |     submitted,
155 |     quizId,
156 |     studentId,
157 |     answers,
158 |     startedAt,
159 |     attemptCount,
160 |     submitAttempt,
161 |     isUsingExtraToken,
162 |     extraTokenData,
163 |   ]);
164 |
165 |   const { display: timerDisplay, isLow: timerIsLow } = useCountdown(
166 |     started ? timeLimitSeconds : null,
167 |     handleSubmit
168 |   );
169 |
170 |   const handleAnswer = (questionId: string, answer: string) => {
171 |     setAnswers((prev) => ({ ...prev, [questionId]: answer }));
172 |   };
173 |
174 |   const isLoading = isLoadingQuiz || isLoadingQuestions || isLoadingAttempts;
175 |
176 |   if (isLoading) {
177 |     return (
178 |       <div className="flex items-center justify-center py-12">
179 |         <Loader2 className="h-8 w-8 animate-spin text-blue-600" />
180 |       </div>
181 |     );
182 |   }
183 |
184 |   if (!quiz) {
185 |     return (
186 |       <div className="text-center py-12">
187 |         <p className="text-gray-500">Quiz not found.</p>
188 |         <Button variant="outline" className="mt-4" onClick={() => navigate(-1)}>
189 |           Go Back
190 |         </Button>
191 |       </div>
192 |     );
193 |   }
194 |
195 |   // Already submitted view
196 |   if (submitted) {
197 |     return (
198 |       <div className="space-y-6 max-w-3xl mx-auto">
199 |         <PCard>
200 |           <div className="p-8 text-center">
201 |             <div className="mb-4 text-4xl">'</div>
202 |             <h2 className="mb-2 text-xl font-bold tracking-tight">
203 |               Quiz Submitted
204 |             </h2>
205 |             <p className="mb-6 text-sm text-gray-500">
206 |               Your answers have been recorded. Auto-gradable questions are
207 |               scored immediately.
208 |             </p>
209 |             <Button variant="outline" onClick={() => navigate(-1)}>
210 |               Back to Quizzes
211 |             </Button>
212 |           </div>
213 |         </PCard>
214 |       </div>
215 |     );
216 |   }
217 |
218 |   // Max attempts reached
219 |   if (!canAttempt) {
220 |     return (
221 |       <div className="space-y-6 max-w-3xl mx-auto">

```



```

222 |         <div className="flex items-center gap-4">
223 |             <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
224 |                 <ArrowLeft className="h-4 w-4" /> Back
225 |             </Button>
226 |             <SectionHeader icon={Ticket} title={quiz.title} />
227 |         </div>
228 |         <PCard>
229 |             <div className="p-8 text-center">
230 |                 <AlertTriangle className="mx-auto mb-4 h-10 w-10 text-amber-500" />
231 |                 <h2 className="mb-2 text-lg font-bold">Maximum Attempts Reached</h2>
232 |                 <p className="text-sm text-gray-500">
233 |                     You have used all {maxAttempts} attempt
234 |                     {maxAttempts > 1 ? "s" : ""} for this quiz.
235 |                 </p>
236 |                 <p className="mt-2 text-xs text-gray-400">
237 |                     <Ticket className="me-1 inline h-3 w-3" />
238 |                     Purchase an Extra Quiz Attempt token from the Marketplace to try
239 |                     again.
240 |                 </p>
241 |             </div>
242 |         </PCard>
243 |     </div>
244 | );
245 | }
246 |
247 | // Pre-start screen
248 | if (!started) {
249 |     return (
250 |         <div className="space-y-6 max-w-3xl mx-auto">
251 |             <div className="flex items-center gap-4">
252 |                 <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
253 |                     <ArrowLeft className="h-4 w-4" /> Back
254 |                 </Button>
255 |                 <SectionHeader icon={BookOpen} title={quiz.title} />
256 |             </div>
257 |             <PCard>
258 |                 <div className="p-8">
259 |                     <SectionHeader icon={Clock} title="Quiz Information" />
260 |                     <div className="mb-6 space-y-2 text-sm text-gray-600">
261 |                         {quiz.description && <p>{quiz.description}</p>}
262 |                         <p>Questions: {questions?.length ?? 0}</p>
263 |                         <p>
264 |                             Total Points:{" "}
265 |                             {questions?.reduce((sum, q) => sum + q.points, 0) ?? 0}
266 |                         </p>
267 |                         {quiz.time_limit_minutes && (
268 |                             <p className="flex items-center gap-1">
269 |                                 <Clock className="h-4 w-4" /> Time Limit:{" "}
270 |                                 {quiz.time_limit_minutes} minutes
271 |                             </p>
272 |                         )}
273 |                         <p>
274 |                             Attempts: {attemptCount} / {maxAttempts}
275 |                         </p>
276 |                         {isUsingExtraToken && (
277 |                             <p className="flex items-center gap-1 font-semibold text-purple-600">
278 |                                 <Ticket className="h-4 w-4" /> Using Extra Attempt Token
279 |                             </p>
280 |                         )}
281 |                     </div>
282 |                     <Button onClick={() => setStarted(true)} variant="tactile">
283 |                         Start Quiz
284 |                     </Button>
285 |                 </div>
286 |             </PCard>
287 |         </div>
288 |     );
289 | }
290 |
291 | // Active quiz
292 | return (
293 |     <div className="space-y-6 max-w-3xl mx-auto">
294 |         </* Header with timer */>
295 |         <div className="flex items-center justify-between sticky top-0 z-10 bg-slate-50 py-3">
296 |             <h1 className="text-xl font-bold tracking-tight truncate">
297 |                 {quiz.title}
298 |             </h1>
299 |             {timeLimitSeconds && (
300 |                 <div
301 |                     className={`flex items-center gap-1.5 px-3 py-1.5 rounded-lg text-sm font-bold ${
302 |                         timerIsLow
303 |                         ? "bg-red-50 text-red-600 animate-pulse"
304 |                         : "bg-blue-50 text-blue-600"
305 |                     }`}
306 |                 >
307 |                     <Clock className="h-4 w-4" />
308 |                     {timerDisplay}
309 |                 </div>
310 |             )}
311 |         </div>
312 |
313 |         </* Questions */>
314 |         {questions?.map((q, idx) => (
315 |             <QuizQuestionCard
316 |                 key={q.id}
317 |                 questionNumber={idx + 1}
318 |                 questionText={q.question_text}
319 |                 questionType={
320 |                     q.question_type === "mcq_single" || q.question_type === "mcq_multi"
321 |                     ? "mcq"
322 |                     : q.question_type
323 |                 }
324 |                 options={q.options ?? undefined}
325 |                 selectedAnswer={answers[q.id] as string | undefined}

```

```

326 |         onAnswer={answer} => handleAnswer(q.id, answer)}
327 |         points={q.points}
328 |     />
329 | ))}
330 |
331 | { /* Submit */
332 | <div className="flex justify-end pb-8">
333 |   <Button
334 |     onClick={handleSubmit}
335 |     disabled={submitAttempt.isPending}
336 |     className="bg-gradient-to-r from-teal-500 to-blue-600 active:scale-95 text-white"
337 |   >
338 |     {submitAttempt.isPending && (
339 |       <Loader2 className="h-4 w-4 animate-spin me-1" />
340 |     )}
341 |     Submit Quiz
342 |   </Button>
343 | </div>
344 | </div>
345 | );
346 | };
347 |
348 | export default QuizAttemptPage;
349 |

```

FILE: src/pages/student/recovery/MasteryRecoveryPage.tsx

TYPE: .tsx | LINES: 1-79 | SHA256: 30169883eabcfbf5d4fd7024ebecf7a44166abc073869e84061b0a456fbb4953

```

1 | import { useNavigate, useParams, Link } from "react-router-dom";
2 | import { useTranslation } from "react-i18next";
3 | import { Button } from "@components/ui/button";
4 | import { ArrowLeft } from "lucide-react";
5 | import MasteryRecoveryPanel from "@components/shared/MasteryRecoveryPanel";
6 | import { useMasteryRecoveryStatus } from "@hooks/useMasteryRecovery";
7 | import { useAuth } from "@hooks/useAuth";
8 | import { useCLO } from "@hooks/useCLOs";
9 | import { Shimmer } from "@design-system";
10 |
11 | const MasteryRecoveryPage = () => {
12 |   const { t } = useTranslation("student");
13 |   const { courseId, cloId } = useParams<{ courseId: string; cloId: string }>();
14 |   const navigate = useNavigate();
15 |   const { user } = useAuth();
16 |   const studentId = user?.id ?? "";
17 |
18 |   const { data: recovery, isLoading } = useMasteryRecoveryStatus(
19 |     studentId,
20 |     cloId ?? ""
21 |   );
22 |   const clo = useCLO(cloId);
23 |
24 |   if (isLoading || clo.isLoading) {
25 |     return (
26 |       <div className="max-w-2xl mx-auto space-y-6">
27 |         <Shimmer className="h-10 w-48" />
28 |         <Shimmer className="h-64 rounded-xl" />
29 |       </div>
30 |     );
31 |   }
32 |
33 |   if (!recovery) {
34 |     return (
35 |       <div className="max-w-2xl mx-auto space-y-6">
36 |         <Link to="/student/dashboard">
37 |           <Button variant="ghost" size="sm" className="gap-2">
38 |             <ArrowLeft className="h-4 w-4" />
39 |             {t("recoveryPath.backToDashboard", "Back to Dashboard")}
40 |           </Button>
41 |         </Link>
42 |         <div className="rounded-xl border border-slate-200 bg-slate-50 p-8 text-center text-sm text-gray-500">
43 |           {t(
44 |             "recoveryPath.empty",
45 |             "No active recovery pathway was found for this outcome."
46 |           )}
47 |         </div>
48 |       </div>
49 |     );
50 |   }
51 |
52 |   return (
53 |     <div className="max-w-2xl mx-auto space-y-6">
54 |       <Link to="/student/dashboard">
55 |         <Button variant="ghost" size="sm" className="gap-2">
56 |           <ArrowLeft className="h-4 w-4" />
57 |           {t("recoveryPath.backToDashboard", "Back to Dashboard")}
58 |         </Button>
59 |       </Link>
60 |
61 |       <MasteryRecoveryPanel
62 |         recoveryId={recovery.id}
63 |         studentId={studentId}
64 |         cloId={cloId ?? ""}
65 |         cloTitle={
66 |           clo.data?.title ??
67 |           t("recoveryPath.unknownOutcome", "Learning outcome")
68 |         }
69 |         courseId={courseId ?? ""}
70 |         onRetryUnlocked={() => {
71 |           navigate(`/student/courses/${courseId ?? ""}`);
72 |         }}
73 |       </div>
74 |     );
75 |   };
76 | };

```

```
77 |  
78 | export default MasteryRecoveryPage;  
79 |
```

FILE: src/pages/student/settings/ProfileSettingsPage.tsx

TYPE: .tsx | LINES: 1-71 | SHA256: a04aaf73cc54b85e5def2e27086621a1ecf69b345fb7f2ce934b13c041f50d8f

```
1 | import { useAuth } from "@hooks/useAuth";  
2 | import { User } from "lucide-react";  
3 | import AvatarUpload from "@components/shared/AvatarUpload";  
4 | import EmailPreferencesSection from "@components/shared/EmailPreferencesSection";  
5 | import { PCard, SectionHeader } from "@design-system";  
6 |  
7 | const ProfileSettingsPage = () => {  
8 |   const { profile } = useAuth();  
9 |  
10 |   return (  
11 |     <div className="space-y-6">  
12 |       <SectionHeader  
13 |         icon={User}  
14 |         title="Profile Settings"  
15 |         description="Update your avatar and email preferences."  
16 |       />  
17 |  
18 |       {  
19 |         /* Profile Info Card */  
20 |         <PCard className="overflow-hidden gap-0 py-0">  
21 |           <div  
22 |             className="flex items-center gap-2 px-6 py-4"  
23 |             style={{  
24 |               background: "var(--brand-gradient)",  
25 |             }}  
26 |           >  
27 |             <User className="h-5 w-5 text-white" />  
28 |             <h2 className="text-lg font-bold tracking-tight text-white">  
29 |               Profile  
30 |             </h2>  
31 |           </div>  
32 |           <div className="p-6">  
33 |             <div className="flex items-center gap-4">  
34 |               {profile?.avatar_url ? (  
35 |                 <img  
36 |                   src={` ${profile.avatar_url}?width=64&height=64&resize=cover`}  
37 |                   alt={profile.full_name}  
38 |                   loading="lazy"  
39 |                   decoding="async"  
40 |                   className="h-16 w-16 rounded-full object-cover"  
41 |                 />  
42 |               ) : (  
43 |                 <div className="flex h-16 w-16 items-center justify-center rounded-full bg-blue-50">  
44 |                   <User className="h-8 w-8 text-blue-600" />  
45 |                 </div>  
46 |               )}  
47 |             <div>  
48 |               <p className="text-lg font-bold">  
49 |                 {profile?.full_name ?? "User"}  
50 |               </p>  
51 |               <p className="text-sm text-slate-500">{profile?.email ?? ""}</p>  
52 |               <p className="text-xs text-slate-400 capitalize">  
53 |                 {profile?.role ?? ""}  
54 |               </p>  
55 |             </div>  
56 |           </div>  
57 |         </PCard>  
58 |  
59 |         {  
60 |           /* Avatar Upload */  
61 |           {profile?.id && (  
62 |             <AvatarUpload userId={profile.id} currentUrl={profile?.avatar_url} />  
63 |           )}  
64 |         {  
65 |           /* Email Notification Preferences */  
66 |           <EmailPreferencesSection />  
67 |         }  
68 |       </div>  
69 |     );  
70 |   }  
71 |   export default ProfileSettingsPage;
```

FILE: src/pages/student/settings/ReassessmentPage.tsx

TYPE: .tsx | LINES: 1-247 | SHA256: 715544448b1aa04e88d6f17dcd572298550a36ebef9dad536dfe38368ff3a7ca

```
1 | import { useMemo } from "react";  
2 | import { useNavigate } from "react-router-dom";  
3 | import { Button } from "@components/ui/button";  
4 | import { Badge } from "@components/ui/badge";  
5 | import {  
6 |   RefreshCw,  
7 |   Clock,  
8 |   CheckCircle2,  
9 |   AlertTriangle,  
10 |   Loader2,  
11 | } from "lucide-react";  
12 | import { differenceInDays, addDays, format } from "date-fns";  
13 | import { PCard, SectionHeader } from "@design-system";  
14 | import { useAuth } from "@hooks/useAuth";  
15 | import { useStudentProfile } from "@hooks/useStudentProfile";  
16 | import { REASSESSMENT_COOLDOWN_DAYS } from "@lib/onboardingConstants";  
17 |  
18 | interface CooldownStatus {  
19 |   canRetake: boolean;  
20 |   daysSinceLast: number;  
21 |   daysRemaining: number;  
22 |   nextEligibleDate: Date | null;
```



```

127 |         </p>
128 |     )}
129 |     {!cooldown.lastAssessmentDate && (
130 |         <p className="mt-1 text-xs text-slate-500">
131 |             No previous assessment found.
132 |         </p>
133 |     )}
134 | </div>
135 | </div>
136 | ) : (
137 |     <div className="mt-4 flex items-start gap-3">
138 |         <AlertTriangle className="h-5 w-5 text-amber-500 mt-0.5 shrink-0" />
139 |         <div>
140 |             <p className="text-sm font-bold text-slate-900">
141 |                 Cooldown period active
142 |             </p>
143 |             <p className="mt-1 text-xs text-slate-500">
144 |                 You can retake assessments once every{" "}
145 |                 {REASSESSMENT_COOLDOWN_DAYS} days.
146 |             </p>
147 |             <div className="mt-3 flex items-center gap-4">
148 |                 <div>
149 |                     <p className="text-[10px] font-black uppercase tracking-widest text-slate-500">
150 |                         Days Remaining
151 |                     </p>
152 |                     <p className="text-2xl font-black text-amber-600">
153 |                         {cooldown.daysRemaining}
154 |                     </p>
155 |                 </div>
156 |                 {cooldown.nextEligibleDate && (
157 |                     <div>
158 |                         <p className="text-[10px] font-black uppercase tracking-widest text-slate-500">
159 |                             Next Eligible
160 |                         </p>
161 |                         <p className="text-sm font-bold text-slate-900">
162 |                             {format(cooldown.nextEligibleDate, "MMM d, yyyy")}
163 |                         </p>
164 |                     </div>
165 |                 )}
166 |             </div>
167 |             {/* Cooldown progress bar */}
168 |             <div className="mt-3">
169 |                 <div className="h-2 rounded-full bg-slate-100 overflow-hidden">
170 |                     <div
171 |                         className="h-full rounded-full bg-gradient-to-r from-amber-400 to-amber-500 transition-a
172 |                         style={{
173 |                             width: `${
174 |                                 ((REASSESSMENT_COOLDOWN_DAYS -
175 |                                  cooldown.daysRemaining) /
176 |                                  REASSESSMENT_COOLDOWN_DAYS) *
177 |                                 100
178 |                             }%`,
179 |                     }}
180 |                     role="progressbar"
181 |                     aria-valuenow={
182 |                         REASSESSMENT_COOLDOWN_DAYS - cooldown.daysRemaining
183 |                     }
184 |                     aria-valuemin={0}
185 |                     aria-valuemax={REASSESSMENT_COOLDOWN_DAYS}
186 |                     aria-label={`Cooldown progress: ${cooldown.daysRemaining} days remaining`}
187 |                 </div>
188 |             </div>
189 |         </div>
190 |     </div>
191 | </div>
192 | )}
193 | </div>
194 | </PCard>
195 |
196 | {/* Assessment Sections */}
197 | <PCard>
198 |     <div className="p-6">
199 |         <SectionHeader icon={RefreshCw} title="Assessment Sections" />
200 |         <div className="space-y-4">
201 |             <p className="text-xs text-slate-500">
202 |                 Re-assessment creates a new profile version with updated scores.
203 |                 Your previous results are preserved for comparison. Re-assessment
204 |                 does not award additional onboarding XP.
205 |             </p>
206 |             <div className="space-y-3">
207 |                 {ASSESSMENT_SECTIONS.map((section) => (
208 |                     <div>
209 |                         key={section.id}
210 |                         className="flex items-center gap-3 rounded-[14px] bg-slate-50 p-3"
211 |                     >
212 |                         <span className="text-lg" aria-hidden="true">
213 |                             {section.icon}
214 |                         </span>
215 |                         <div className="flex-1">
216 |                             <p className="text-sm font-bold text-slate-900">
217 |                                 {section.label}
218 |                             </p>
219 |                             <p className="text-xs text-slate-500">
220 |                                 {section.description}
221 |                             </p>
222 |                         </div>
223 |                     </div>
224 |                 ))}
225 |             </div>
226 |             <div className="pt-2">
227 |                 <Button
228 |                     disabled={!cooldown.canRetake}
229 |                     onClick={() => navigate("/student/onboarding/complete-profile")}
230 |                     variant="tactile"

```

```

231 |         className="w-full"
232 |     >
233 |     <RefreshCw className="h-4 w-4" />
234 |     {cooldown.canRetake
235 |       ? "Start Re-Assessment"
236 |       : `Available in ${cooldown.daysRemaining} days`}
237 |   </Button>
238 | </div>
239 | </div>
240 | </div>
241 | </PCard>
242 | </div>
243 | );
244 | };
245 |
246 | export default ReassessmentPage;
247 |

```

FILE: src/pages/student/StudentDashboard.tsx

TYPE: .tsx | LINES: 1-12 | SHA256: 197f09efac11161bd8a5f54ab00f08a4ff948f7c35d32455aa289d3ccfad652c

```

1 | // =====
2 | // StudentDashboard – production student dashboard route
3 | // =====
4 | // The implementation lives in `@/features/student/dashboard/StudentDashboardScreen`
5 | // (prototype-frontend-rebuild P2.1 – a from-scratch rebuild of
6 | // `prototype/dashboard.html` on `@/design-system` + real hooks). Re-exported here
7 | // so the route path (`@/pages/student/StudentDashboard`) stays stable. The prior
8 | // `StudentDashboardNew` (reskin-in-place) was retired by this rebuild.
9 | // =====
10 |
11 | export { default } from "@/features/student/dashboard/StudentDashboardScreen";
12 |

```

FILE: src/pages/student/StudentLayout.tsx

TYPE: .tsx | LINES: 1-100 | SHA256: e2a559757ebdbdde9c4e68e105b84123a8ccc71a17399c472f2a54704673366f

```

1 | import { lazy, Suspense } from "react";
2 | import { Outlet, useLocation } from "react-router-dom";
3 | import { useAuth } from "@/hooks/useAuth";
4 | import RoleAppShell from "@/app/RoleAppShell";
5 | import StudentDashboardRail from "@/features/student/dashboard/StudentDashboardRail";
6 | import StudentLearnRail from "@/features/student/rails/StudentLearnRail";
7 | import StudentProgressRail from "@/features/student/rails/StudentProgressRail";
8 | import StudentJournalRail from "@/features/student/rails/StudentJournalRail";
9 | import StudentAssignmentRail from "@/features/student/rails/StudentAssignmentRail";
10 | import StudentFallbackRail from "@/features/student/rails/StudentFallbackRail";
11 | import StudentProfileRail from "@/features/student/rails/StudentProfileRail";
12 | import StudentLearningProfileRail from "@/features/student/rails/StudentLearningProfileRail";
13 | import StudentSettingsRail from "@/features/student/rails/StudentSettingsRail";
14 |
15 | const OnboardingWizard = lazy(
16 |   () => import("@/pages/student/onboarding/OnboardingWizard")
17 | );
18 |
19 | // Per-page right rails (prototype shared.js `railHTML()` student cases). Each
20 | // student page whose prototype defines a contextual rail maps its route to a
21 | // rail component here; the layout renders the match and reserves its width so
22 | // the feed sits in a true 3-column shell. Other student routes receive the
23 | // lightweight real-data fallback rail. Order doesn't matter (patterns are
24 | // mutually exclusive).
25 | const STUDENT_RAILS: ReadonlyArray<{
26 |   test: RegExp;
27 |   Rail: React.ComponentType;
28 | }> = [
29 |   { test: /\\/student\/dashboard$/, Rail: StudentDashboardRail },
30 |   { test: /\\/student\/courses\/\[^\]+\$/, Rail: StudentLearnRail },
31 |
32 |   { test: /\\/student\/progress$/, Rail: StudentProgressRail },
33 |   { test: /\\/student\/journal$/, Rail: StudentJournalRail },
34 |   { test: /\\/student\/assignments\/\[^\]+\$/, Rail: StudentAssignmentRail },
35 |   { test: /\\/student\/profile$/, Rail: StudentProfileRail },
36 |
37 |   {
38 |     test: /\\/student\/learning-profile$/,
39 |     Rail: StudentLearningProfileRail,
40 |   },
41 |   { test: /\\/student\/settings(?:\/|$)/, Rail: StudentSettingsRail },
42 | ];
43 |
44 | const StudentLayout = () => {
45 |   const { profile } = useAuth();
46 |   const location = useLocation();
47 |   const showOnboarding =
48 |     profile?.role === "student" && profile?.onboarding_completed === false;
49 |
50 |   if (showOnboarding) {
51 |     return (
52 |       <Suspense fallback={<div className="fixed inset-0 z-50 bg-white" />}>
53 |         <OnboardingWizard isDay1 />
54 |       </Suspense>
55 |     );
56 |   }
57 |
58 |   // Focused student work intentionally runs without the global header,
59 |   // sidebar, bottom navigation, or contextual rail. The adaptive lesson loop
60 |   // and Focus Mode each provide their own minimal, task-specific chrome.
61 |   if (
62 |     /\\/student\/quizzes\/\[^\]+\//adaptive$/.test(location.pathname) ||
63 |     /\\/student\/focus\/\[^\]+\//$.test(location.pathname)
64 |   ) {
65 |     return (
66 |       <div
67 |         data-immersive
68 |         className="min-h-screen bg-background px-[var(--app-gutter-mobile)] py-6 min-[640px]:px-[var(--app-gut

```

```

68 |         >
69 |         <Outlet />
70 |     </div>
71 | );
72 | }
73 |
74 | // The learning path page manages its own internal 2-column layout (journey
75 | // timeline + stage detail panel) so it renders WITHOUT the app shell rail.
76 | // This gives its content the full viewport width after the sidebar.
77 | if (location.pathname === "/student/learning-path") {
78 |     return (
79 |         <RoleAppShell userRole="student">
80 |             <Outlet />
81 |             </RoleAppShell>
82 |         );
83 |     }
84 |
85 |     // Select the contextual right rail for the current student route (if any) and
86 |     // reserve its width so the feed sits in a true 3-column shell
87 |     // (sidebar · feed · rail) instead of stretching under the rail.
88 |     const ActiveRail =
89 |         STUDENT_RAILS.find((r) => r.test.test(location.pathname))?.Rail ??
90 |         StudentFallbackRail;
91 |
92 |     return (
93 |         <RoleAppShell userRole="student" rail={<ActiveRail />}>
94 |             <Outlet />
95 |             </RoleAppShell>
96 |         );
97 |     };
98 |
99 | export default StudentLayout;
100 |

```

FILE: src/pages/student/surveys/SurveyResponsePage.tsx

TYPE: .tsx | LINES: 1-158 | SHA256: 35cb765fe448a81dd8a235d84c815b548c5cbf2abf4394601eb81a23823eb65f

[illegible]

[illegible]

```

4 | import { Link } from "react-router-dom";
5 |
6 | import { useTranslation } from "react-i18next";
7 | import { Users, UserPlus } from "lucide-react";
8 | import { useAuth } from "@hooks/useAuth";
9 | import { useFirstEnrolledCourseId } from "@hooks/useFirstEnrolledCourse";

```



```

10 | import { useMyTeamId } from "@hooks/useTeamLeaderboard";
11 | import { useTeams, useTeamGamification } from "@hooks/useTeams";
12 | import { Button } from "@components/ui/button";
13 | import TeamDashboardCard from "@components/shared/TeamDashboardCard";
14 | import EmptyState, { NoTeams } from "@components/shared/EmptyState";
15 | import TeamLeaderboard from "@pages/student/leaderboard/TeamLeaderboard";
16 | import { SectionHeader, Shimmer } from "@design-system";
17 |
18 | const StudentTeamPage = () => {
19 |   const { t } = useTranslation("student");
20 |   const { user } = useAuth();
21 |   const studentId = user?.id ?? "";
22 |   const { data: courseId, isLoading: courseLoading } = useFirstEnrolledCourseId(
23 |     studentId || undefined
24 |   );
25 |   const { data: myTeamId, isLoading: teamIdLoading } = useMyTeamId(
26 |     studentId || undefined,
27 |     courseId ?? undefined
28 |   );
29 |   const { data: teamsData, isLoading: teamsLoading } = useTeams(
30 |     courseId ?? undefined
31 |   );
32 |   const myTeam = (teamsData ?? []).find((tm) => tm.id === myTeamId);
33 |   const { data: teamGamification } = useTeamGamification(myTeamId ?? undefined);
34 |
35 |   // Resolve membership before deciding which state to render.
36 |   const isResolving = courseLoading || teamIdLoading;
37 |   const isAssigned = !!myTeamId;
38 |
39 |   const renderTeamSection = () => {
40 |     if (isResolving) {
41 |       return <Shimmer className="h-32 rounded-xl" />;
42 |     }
43 |
44 |     // Unassigned: explain how teams work and surface a join/create path.
45 |     if (!isAssigned) {
46 |       return (
47 |         <EmptyState
48 |           icon={Users className="h-8 w-8 text-blue-500" />
49 |           title={t("team.unassignedTitle")}
50 |           description={t("team.howItWorksDescription")}
51 |         >
52 |           <div className="flex flex-col items-center gap-3">
53 |             <Button asChild variant="tactile">
54 |               <Link to="/student/teams/new">
55 |                 <UserPlus className="h-4 w-4 me-2" />
56 |                 {t("team.joinOrCreate")}
57 |               </Link>
58 |             </Button>
59 |             <p className="text-xs text-gray-400 dark:text-gray-500 max-w-sm">
60 |               {t("team.teacherAssignNote")}
61 |             </p>
62 |           </div>
63 |         </EmptyState>
64 |       );
65 |     }
66 |
67 |     // Assigned but team data is still loading.
68 |     if (teamsLoading) {
69 |       return <Shimmer className="h-32 rounded-xl" />;
70 |     }
71 |
72 |     // Assigned with team data present.
73 |     if (myTeam) {
74 |       return (
75 |         <TeamDashboardCard team={myTeam} gamification={teamGamification} />
76 |       );
77 |     }
78 |
79 |     // Assigned but no team data to display – genuine zero-data fallback.
80 |     return <NoTeams />;
81 |   };
82 |
83 |   return (
84 |     <div className="space-y-6">
85 |       <SectionHeader icon={Users} title={t("team.title")} />
86 |
87 |       {renderTeamSection()}
88 |
89 |       {courseId && <TeamLeaderboard courseId={courseId} />}
90 |     </div>
91 |   );
92 | };
93 |
94 | export default StudentTeamPage;
95 |

```

FILE: [src/pages/student/teams/CreateTeamPage.tsx](#)

TYPE: .tsx | LINES: 1-246 | SHA256: 0e5a8356f3f41c8ab17677c40d2c2505da579e80a9ee29bb82d0fc8d20dc3f53

```

1 | // =====
2 | // CreateTeamPage – Team creation form for student-formed mode
3 | // Task 5.2: name input, member selection from roster
4 | // =====
5 |
6 | import { useNavigate } from "react-router-dom";
7 | import { useForm } from "react-hook-form";
8 | import { zodResolver } from "@hookform/resolvers/zod";
9 | import { z } from "zod";
10 | import { useTranslation } from "react-i18next";
11 | import { useAuth } from "@hooks/useAuth";
12 | import { useCreateTeam } from "@hooks/useTeams";
13 | import {
14 |   useStudentFormedCourses,

```

```

15 | useCourseRoster,
16 | } from "@hooks/useTeamFormation";
17 | import { Button } from "@components/ui/button";
18 | import { Input } from "@components/ui/input";
19 | import { Checkbox } from "@components/ui/checkbox";
20 | import {
21 |   Form,
22 |   FormField,
23 |   FormItem,
24 |   FormLabel,
25 |   FormControl,
26 |   FormMessage,
27 | } from "@components/ui/form";
28 | import {
29 |   Select,
30 |   SelectContent,
31 |   SelectItem,
32 |   SelectTrigger,
33 |   SelectValue,
34 | } from "@components/ui/select";
35 | import { PCard, SectionHeader, Shimmer } from "@design-system";
36 | import { Loader2, Users, ArrowLeft } from "lucide-react";
37 | import { toast } from "sonner";
38 | import { useState } from "react";
39 |
40 | interface CreateTeamFormData {
41 |   name: string;
42 |   course_id: string;
43 | }
44 |
45 | const CreateTeamPage = () => {
46 |   const navigate = useNavigate();
47 |   const { t } = useTranslation("student");
48 |   const { user, institutionId } = useAuth();
49 |   const studentId = user?.id ?? "";
50 |   const { data: courses, isLoading: coursesLoading } = useStudentFormedCourses(
51 |     studentId || undefined
52 |   );
53 |   const createMutation = useCreateTeam();
54 |   const [selectedMembers, setSelectedMembers] = useState<string[]>([]);
55 |
56 |   const form = useForm<CreateTeamFormData>({
57 |     resolver: zodResolver(
58 |       z.object({
59 |         name: z.string().min(2, t("createTeam.validation.nameMin")).max(50),
60 |         course_id: z.string().uuid(t("createTeam.validation.courseRequired")),
61 |       })
62 |     ),
63 |     defaultValues: { name: "", course_id: "" },
64 |   });
65 |
66 |   const selectedCourseId = form.watch("course_id");
67 |   const { data: roster, isLoading: rosterLoading } = useCourseRoster(
68 |     selectedCourseId || undefined,
69 |     studentId
70 |   );
71 |
72 |   const toggleMember = (id: string) => {
73 |     setSelectedMembers((prev) =>
74 |       prev.includes(id) ? prev.filter((m) => m !== id) : [...prev, id]
75 |     );
76 |   };
77 |
78 |   // Team size: 2-6 including captain
79 |   const totalSize = selectedMembers.length + 1; // +1 for captain (current user)
80 |   const sizeValid = totalSize >= 2 && totalSize <= 6;
81 |
82 |   const onSubmit = (data: CreateTeamFormData) => {
83 |     if (!sizeValid) {
84 |       toast.error(t("createTeam.toast.sizeInvalid"));
85 |       return;
86 |     }
87 |
88 |     createMutation.mutate(
89 |       {
90 |         name: data.name,
91 |         course_id: data.course_id,
92 |         institution_id: institutionId ?? "",
93 |         captain_id: studentId,
94 |         created_by: studentId,
95 |         avatar_letter: data.name.charAt(0).toUpperCase(),
96 |       },
97 |       {
98 |         onSuccess: (team) => {
99 |           toast.success(t("createTeam.toast.created"));
100 |           navigate(`/student/teams/${team.id}`);
101 |         },
102 |         onError: (err) => toast.error(err.message),
103 |       }
104 |     );
105 |   };
106 |
107 |   return (
108 |     <div className="space-y-6">
109 |       <div className="flex items-center gap-3">
110 |         <Button
111 |           variant="ghost"
112 |           size="sm"
113 |           onClick={() => navigate(-1)}
114 |           className="h-8 w-8 p-0"
115 |           aria-label={t("createTeam.back")}
116 |         >
117 |           <ArrowLeft className="h-4 w-4" />
118 |         </Button>

```

```

119 | <SectionHeader icon={Users} title={t("createTeam.title")} />
120 | </div>
121 |
122 | {coursesLoading ? (
123 |   <Shimmer className="h-48 rounded-xl" />
124 | ) : !courses || courses.length === 0 ? (
125 |   <PCard>
126 |     <div className="p-8 text-center">
127 |       <Users className="mx-auto mb-2 h-8 w-8 text-gray-400" />
128 |       <p className="text-sm text-gray-500">
129 |         {t("createTeam.noCoursesAvailable")}
130 |       </p>
131 |     </div>
132 |   </PCard>
133 | ) : (
134 |   <PCard className="max-w-2xl p-6">
135 |     <Form {...form}>
136 |       <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
137 |         <FormField
138 |           control={form.control}
139 |           name="course_id"
140 |           render={({ field }) => (
141 |             <FormItem>
142 |               <FormLabel>{t("createTeam.courseLabel")}</FormLabel>
143 |               <Select onChange={field.onChange} value={field.value}>
144 |                 <FormControl>
145 |                   <SelectTrigger className="bg-white">
146 |                     <SelectValue
147 |                       placeholder={t("createTeam.selectCourse")}
148 |                     />
149 |                   </SelectTrigger>
150 |                 </FormControl>
151 |                 <SelectContent>
152 |                   {courses.map((c) => (
153 |                     <SelectItem key={c.id} value={c.id}>
154 |                       {c.name}
155 |                     </SelectItem>
156 |                   ))}
157 |                 </SelectContent>
158 |               </Select>
159 |               <FormMessage />
160 |             </FormItem>
161 |           )}
162 |         />
163 |
164 |         <FormField
165 |           control={form.control}
166 |           name="name"
167 |           render={({ field }) => (
168 |             <FormItem>
169 |               <FormLabel>{t("createTeam.teamNameLabel")}</FormLabel>
170 |               <FormControl>
171 |                 <Input
172 |                   placeholder={t("createTeam.teamNamePlaceholder")}
173 |                   {...field}
174 |                 />
175 |               </FormControl>
176 |               <FormMessage />
177 |             </FormItem>
178 |           )}
179 |         />
180 |
181 |         {/* Member Selection */}
182 |         {selectedCourseId && (
183 |           <div className="space-y-2">
184 |             <FormLabel>
185 |               {t("createTeam.inviteMembers", { current: totalSize })}
186 |             </FormLabel>
187 |             {rosterLoading ? (
188 |               <Shimmer className="h-24 rounded-lg" />
189 |             ) : !roster || roster.length === 0 ? (
190 |               <p className="text-xs text-gray-500">
191 |                 {t("createTeam.noAvailableStudents")}
192 |               </p>
193 |             ) : (
194 |               <div className="grid grid-cols-1 sm:grid-cols-2 gap-2 max-h-48 overflow-y-auto border roun
195 |                 {roster.map((student) => (
196 |                   <label
197 |                     key={student.student_id}
198 |                     className="flex items-center gap-2 p-2 rounded-lg hover:bg-slate-50 cursor-pointer"
199 |                   >
200 |                     <Checkbox
201 |                       checked={selectedMembers.includes(
202 |                         student.student_id
203 |                       )}
204 |                       onChange={() =>
205 |                         toggleMember(student.student_id)
206 |                       }
207 |                       disabled={
208 |                         !selectedMembers.includes(student.student_id) &&
209 |                         totalSize >= 6
210 |                       }
211 |                     />
212 |                     <span className="text-sm font-medium">
213 |                       {student.full_name}
214 |                     </span>
215 |                   </label>
216 |                 )}
217 |               </div>
218 |             )}
219 |           {totalSize < 2 && (
220 |             <p className="text-xs text-amber-600">
221 |               {t("createTeam.selectAtLeastOne")}
222 |             </p>

```

```

223 |         }}
224 |       </div>
225 |     )}
226 |
227 |     <Button
228 |       type="submit"
229 |       disabled={createMutation.isPending || !sizeValid}
230 |       variant="tactile"
231 |     >
232 |       {createMutation.isPending && (
233 |         <Loader2 className="h-4 w-4 animate-spin" />
234 |       )}
235 |       {t("createTeam.submit")}
236 |     </Button>
237 |   </form>
238 | </Form>
239 | </PCard>
240 |   )}
241 | </div>
242 | );
243 | };
244 |
245 | export default CreateTeamPage;
246 |

```

FILE: src/pages/student/teams/TeamProfilePage.tsx

TYPE: .tsx | LINES: 1-309 | SHA256: dea173e4291d886c341fcdbbc8b4b5b9066d811eec6b95e09a627401ea8368d2

```

1 | // =====
2 | // TeamProfilePage – Student team profile with stats, members, badges,
3 | // active challenges, XP breakdown, teaching moments, replacement votes
4 | // Task 5.1 + 5.6
5 | // =====
6 |
7 | import { useMemo } from "react";
8 | import { useParams } from "react-router-dom";
9 | import { useAuth } from "@/hooks/useAuth";
10 | import { useTeamProfile } from "@/hooks/useTeamProfile";
11 | import {
12 |   useReplacementVotes,
13 |   useInitiateVote,
14 |   useCastVote,
15 | } from "@/hooks/useReplacementVotes";
16 | import { Badge } from "@/components/ui/badge";
17 | import TeamMemberList, {
18 |   type TeamMemberItem,
19 | } from "@/components/shared/TeamMemberList";
20 | import TeamBadgeCollection, {
21 |   type TeamBadgeItem,
22 | } from "@/components/shared/TeamBadgeCollection";
23 | import ChallengeProgressBar from "@/components/shared/ChallengeProgressBar";
24 | import CooperationScoreDisplay from "@/components/shared/CooperationScoreDisplay";
25 | import PeerTeachingMomentCard from "@/components/shared/PeerTeachingMomentCard";
26 | import ReplacementVoteCard from "@/components/shared/ReplacementVoteCard";
27 | import { PCard, SectionHeader, Shimmer } from "@/design-system";
28 | import { TEAM_BADGE_DEFINITIONS } from "@/lib/teamBadgeDefinitions";
29 | import {
30 |   Users,
31 |   Zap,
32 |   Flame,
33 |   Trophy,
34 |   Target,
35 |   BookOpen,
36 |   Vote,
37 | } from "lucide-react";
38 | import type { ContributionStatus } from "@/lib/contributionThresholds";
39 |
40 | const TeamProfilePage = () => {
41 |   const { teamId } = useParams<{ teamId: string }>();
42 |   const { user } = useAuth();
43 |   const { data: profile, isLoading } = useTeamProfile(teamId);
44 |   const { data: votes } = useReplacementVotes(teamId);
45 |   const initiateVoteMutation = useInitiateVote();
46 |   const castVoteMutation = useCastVote();
47 |
48 |   // Map members to TeamMemberItem format
49 |   const memberItems: TeamMemberItem[] = useMemo(() => {
50 |     if (!profile) return [];
51 |     return profile.members.map((m) => ({
52 |       id: m.id,
53 |       studentId: m.student_id,
54 |       displayName: m.student_id, // Will show student_id as name (profile join not available)
55 |       role: m.role as "captain" | "member",
56 |       xpContribution: 0,
57 |       contributionStatus: (m.contribution_status ??
58 |         "active") as ContributionStatus,
59 |     }));
60 |   }, [profile]);
61 |
62 |   // Map badges to TeamBadgeItem format
63 |   const badgeItems: TeamBadgeItem[] = useMemo(() => {
64 |     if (!profile) return [];
65 |     return profile.badges.map((b) => {
66 |       const def = TEAM_BADGE_DEFINITIONS.find((d) => d.id === b.badge_key);
67 |       return {
68 |         id: b.id,
69 |         badgeKey: b.badge_key,
70 |         badgeName: def?.name ?? b.badge_key,
71 |         emoji: def?.icon ?? "🏆",
72 |         description: def?.description,
73 |         earnedAt: b.earned_at,
74 |       };
75 |     });
76 |   }, [profile]);

```

```

77 |
78 | // Inactive members for vote initiation
79 | const inactiveMembers = useMemo(() => {
80 |     return memberItems
81 |         .filter((m) => m.contributionStatus === "inactive")
82 |         .map((m) => ({ id: m.studentId, name: m.displayName }));
83 | }, [memberItems]);
84 |
85 | if (isLoading) {
86 |     return (
87 |         <div className="space-y-6">
88 |             <Shimmer className="h-10 w-48 rounded-lg" />
89 |             <Shimmer className="h-48 rounded-xl" />
90 |             <Shimmer className="h-32 rounded-xl" />
91 |         </div>
92 |     );
93 | }
94 |
95 | if (!profile) {
96 |     return (
97 |         <div className="space-y-6">
98 |             <SectionHeader icon={Users} title="Team Profile" />
99 |             <PCard>
100 |                 <div className="p-8 text-center">
101 |                     <Users className="mx-auto mb-2 h-8 w-8 text-gray-400" />
102 |                     <p className="text-sm text-gray-500">Team not found.</p>
103 |                 </div>
104 |             </PCard>
105 |         </div>
106 |     );
107 | }
108 |
109 | const { team, activeChallenges, teachingMoments } = profile;
110 | const isCaptain = team.captain_id === user?.id;
111 | const openVotes = (votes ?? []).filter((v) => v.status === "open");
112 |
113 | return (
114 |     <div className="space-y-6">
115 |         </* Header */>
116 |         <div className="flex items-center gap-3">
117 |             <div
118 |                 className="h-12 w-12 rounded-full flex items-center justify-center text-lg font-bold text-white shri
119 |                 style={{
120 |                     background: "var(--brand-gradient)",
121 |                 }}
122 |             >
123 |                 {team.name.charAt(0).toUpperCase()}
124 |             </div>
125 |             <div>
126 |                 <h1 className="text-2xl font-bold tracking-tight">{team.name}</h1>
127 |                 <p className="text-xs text-gray-500">
128 |                     Created {new Date(team.created_at).toLocaleDateString()}
129 |                 </p>
130 |             </div>
131 |         </div>
132 |
133 |         </* KPI Row */>
134 |         <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
135 |             <PCard className="group p-4">
136 |                 <div className="flex items-center justify-between">
137 |                     <div>
138 |                         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
139 |                             Team XP
140 |                         </p>
141 |                         <p className="text-2xl font-black mt-1">
142 |                             {team.xp_total.toLocaleString()}
143 |                         </p>
144 |                     </div>
145 |                     <div className="p-2 rounded-lg bg-amber-50 group-hover:scale-110 transition-transform">
146 |                         <Zap className="h-5 w-5 text-amber-500" />
147 |                     </div>
148 |                 </div>
149 |             </PCard>
150 |
151 |             <PCard className="group p-4">
152 |                 <div className="flex items-center justify-between">
153 |                     <div>
154 |                         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
155 |                             Streak
156 |                         </p>
157 |                         <p className="text-2xl font-black mt-1 bg-gradient-to-r from-red-500 to-orange-500 bg-clip-text">
158 |                             {team.streak_count}
159 |                         </p>
160 |                     </div>
161 |                     <div className="p-2 rounded-lg bg-orange-50 group-hover:scale-110 transition-transform">
162 |                         <Flame className="h-5 w-5 text-orange-500 animate-streak-flame" />
163 |                     </div>
164 |                 </div>
165 |             </PCard>
166 |
167 |             <PCard className="group p-4">
168 |                 <div className="flex items-center justify-between">
169 |                     <div>
170 |                         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
171 |                             Members
172 |                         </p>
173 |                         <p className="text-2xl font-black mt-1">{memberItems.length}</p>
174 |                     </div>
175 |                     <div className="p-2 rounded-lg bg-blue-50 group-hover:scale-110 transition-transform">
176 |                         <Users className="h-5 w-5 text-blue-600" />
177 |                     </div>
178 |                 </div>
179 |             </PCard>
180 |

```

```

181 <PCard className="group p-4">
182 <CooperationScoreDisplay score={team.cooperation_score} />
183 </PCard>
184 </div>
185
186 {/* Members Section */}
187 <PCard className="overflow-hidden">
188 <div className="p-6">
189 <SectionHeader icon={Users} title="Members" />
190 <TeamMemberList members={memberItems} totalTeamXp={team.xp_total} />
191 </div>
192 </PCard>
193
194 {/* Badges Section */}
195 {badgeItems.length > 0 && (
196 <PCard className="overflow-hidden">
197 <div className="p-6">
198 <SectionHeader icon={Trophy} title="Badges" />
199 <TeamBadgeCollection badges={badgeItems} />
200 </div>
201 </PCard>
202 )}
203
204 {/* Active Challenges */}
205 {activeChallenges.length > 0 && (
206 <PCard className="overflow-hidden">
207 <div className="p-6">
208 <SectionHeader icon={Target} title="Active Challenges" />
209 <div className="mt-4 space-y-4">
210 {activeChallenges.map((challenge) => (
211 <div key={challenge.id} className="space-y-2">
212 <div className="flex items-center justify-between">
213 <p className="text-sm font-semibold">{challenge.title}</p>
214 <Badge variant="outline" className="text-xs">
215 {challenge.challenge_type}
216 </Badge>
217 </div>
218 <ChallengeProgressBar
219 current={challenge.current_progress}
220 goal={challenge.goal_target}
221 label={challenge.title}
222 />
223 {challenge.completed_at && (
224 <p className="text-xs text-green-600 font-medium">
225 ' Completed{" "}
226 {new Date(challenge.completed_at).toLocaleDateString()}
227 </p>
228 )}
229 </div>
230 )}}
231 </div>
232 </div>
233 </PCard>
234 )}
235
236 {/* Teaching Moments Section */}
237 {teachingMoments.length > 0 && (
238 <PCard className="overflow-hidden">
239 <div className="p-6">
240 <SectionHeader icon={BookOpen} title="Teaching Moments" />
241 <div className="mt-4 space-y-4">
242 {teachingMoments.map((moment) => (
243 <PeerTeachingMomentCard
244 key={moment.id}
245 title={moment.title}
246 explanationText={moment.explanation_text}
247 mediaUrl={moment.media_url}
248 authorName={moment.author_id}
249 createdAt={moment.created_at}
250 />
251 )}}
252 </div>
253 </div>
254 </PCard>
255 )}
256
257 {/* Replacement Votes Section (Task 5.6) */}
258 {(openVotes.length > 0 || (isCaptain && inactiveMembers.length > 0)) && (
259 <PCard className="overflow-hidden">
260 <div className="p-6">
261 <SectionHeader icon={Vote} title="Replacement Votes" />
262 <div className="mt-4">
263 <ReplacementVoteCard
264 vote={
265 openVotes[0]
266 ? {
267 id: openVotes[0].id,
268 targetMemberName: openVotes[0].target_member_id,
269 targetMemberId: openVotes[0].target_member_id,
270 status: openVotes[0].status,
271 votesFor: openVotes[0].votes_for,
272 votesAgainst: openVotes[0].votes_against,
273 createdAt: openVotes[0].created_at,
274 resolvedAt: openVotes[0].resolved_at,
275 teacherOverride: openVotes[0].teacher_override,
276 }
277 : null
278 }
279 isCaptain={isCaptain}
280 isTeacher={false}
281 totalMembers={memberItems.length}
282 inactiveMembers={inactiveMembers}
283 onInitiateVote={({targetMemberId}) => {
284 initiateVoteMutation.mutate({

```


[illegible]

[illegible]

```

284 | /* Header with persona selector */
285 | <div className="flex items-center justify-between px-4 py-3 border-b border-gray-100 bg-white">
286 |   <div className="flex items-center gap-2">
287 |     <div className="p-1.5 rounded-lg bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]">
288 |       <Bot className="h-4 w-4 text-white" />
289 |     </div>
290 |     <span className="text-sm font-semibold text-gray-800">
291 |       {t("tutor.chat.title")}
292 |     </span>
293 |   </div>
294 |   <div className="flex items-center gap-2">
295 |     <PersonaSelector
296 |       selectedPersona={persona}
297 |       onSelect={onPersonaChange}
298 |       variant="inline"
299 |     />
300 |     {onAutonomyChange && (
301 |       <AutonomyToggle
302 |         value={autonomyOverride ?? null}
303 |         onChange={onAutonomyChange}
304 |         disabled={isInputDisabled}
305 |       />
306 |     )}
307 |   </div>
308 | </div>
309 |
310 | /* Usage warning banner – shows at 80% of daily limit */
311 | {showWarning && usage && (
312 |   <div
313 |     className="flex items-center gap-2 px-4 py-2 bg-amber-50 border-b border-amber-100"
314 |     role="alert"
315 |   >
316 |     <AlertTriangle className="h-4 w-4 text-amber-700 shrink-0" />
317 |     <p className="text-xs font-medium text-amber-700">
318 |       {t("tutor.chat.messagesRemaining", {
319 |         count: usage.remaining_messages,
320 |       })}
321 |     </p>
322 |   </div>
323 | )}
324 |
325 | /* Message list */
326 | <div
327 |   className="flex-1 overflow-y-auto px-4 py-4 space-y-4"
328 |   role="log"
329 |   aria-label={t("tutor.chat.messagesLabel")}
330 | >
331 |   {isLoadingMessages ? (
332 |     <div className="space-y-4">
333 |       {Array.from({ length: 3 }).map((_, i) => (
334 |         <div
335 |           key={i}
336 |           className={cn(
337 |             "flex gap-3",
338 |             i % 2 === 0 ? "" : "flex-row-reverse"
339 |           )}
340 |         >
341 |           <div className="h-8 w-8 rounded-full animate-shimmer shrink-0" />
342 |           <div
343 |             className={cn(
344 |               "space-y-1.5",
345 |               i % 2 === 0 ? "" : "flex flex-col items-end"
346 |             )}
347 |           >
348 |             <div className="h-12 w-48 rounded-2xl animate-shimmer" />
349 |             <div className="h-3 w-16 rounded animate-shimmer" />
350 |           </div>
351 |         </div>
352 |       )}
353 |     </div>
354 |   ) : messages.length === 0 && !isStreaming ? (
355 |     <div className="flex flex-col items-center justify-center h-full text-center py-12">
356 |       <div className="p-4 rounded-2xl bg-gradient-to-br from-teal-50 to-blue-50 mb-4">
357 |         <Bot className="h-10 w-10 text-teal-600" />
358 |       </div>
359 |       <h3 className="text-lg font-bold text-gray-800">
360 |         {t("tutor.chat.emptyTitle")}
361 |       </h3>
362 |       <p className="text-sm text-gray-500 mt-1 max-w-sm">
363 |         {t("tutor.chat.emptyBody")}
364 |       </p>
365 |     </div>
366 |   ) : (
367 |     <>
368 |       {messages.map((msg) => (
369 |         <ChatMessage
370 |           key={msg.id}
371 |           message={msg}
372 |           onRate={onRateMessage}
373 |           isRatingPending={isRatingPending}
374 |         />
375 |       ))}
376 |     </>
377 |   )}
378 |
379 | /* Streaming response */
380 | {isStreaming && streamingContent && (
381 |   <ChatMessage
382 |     message={{
383 |       id: "streaming",
384 |       conversation_id: conversationId ?? "",
385 |       role: "assistant",
386 |       content: streamingContent,
387 |       source_citations: [],
388 |       image_urls: [],
389 |       document_url: null,

```

```

388         token_count: 0,
389         satisfaction_rating: null,
390         flagged_integrity: false,
391         autonomy_level: null,
392         nudge_type: null,
393         created_at: new Date().toISOString(),
394     }}
395 }
396 )
397
398 { /* Typing indicator */
399 {isStreaming && !streamingContent && (
400 <div className="flex gap-3">
401 <div className="h-8 w-8 rounded-full bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%
402 <div className="h-4 w-4 text-white" />
403 </div>
404 <div className="bg-white border border-gray-100 shadow-sm rounded-2xl rounded-bl-md px-4 py-3"
405 <div
406   className="flex gap-1.5"
407   aria-label={t("tutor.chat.typingLabel")}
408 >
409 <span className="h-2 w-2 rounded-full bg-gray-300 animate-bounce [animation-delay:0ms]" />
410 <span className="h-2 w-2 rounded-full bg-gray-300 animate-bounce [animation-delay:150ms]" />
411 <span className="h-2 w-2 rounded-full bg-gray-300 animate-bounce [animation-delay:300ms]" />
412 </div>
413 </div>
414 </div>
415 )}
416 </>
417 )}
418 <div ref={messagesEndRef} />
419 </div>
420
421 { /* Input area */
422 <div className="border-t border-gray-100 bg-white p-4">
423 { /* Attachment previews */
424 {(imageFiles.length > 0 || documentFile) && (
425 <div className="flex flex-wrap gap-2 mb-3">
426 {imageFiles.map((file, i) => (
427 <div key={i} className="relative group">
428 <img
429   src={URL.createObjectURL(file)}
430   alt={t("tutor.chat.attachmentAlt", { index: i + 1 })}
431   className="h-16 w-16 rounded-lg object-cover border border-gray-200"
432 />
433 <button
434   onClick={() => removeImage(i)}
435   className="absolute -top-1.5 -end-1.5 h-5 w-5 rounded-full bg-red-500 text-white flex items-
436   aria-label={t("tutor.chat.removeImage", { index: i + 1 })}
437 >
438 <X className="h-3 w-3" />
439 </button>
440 </div>
441 )})}
442 {documentFile && (
443 <div className="relative group">
444 <Badge
445   variant="outline"
446   className="h-16 px-3 flex items-center gap-2 border-gray-200"
447 >
448 <FileUp className="h-4 w-4 text-gray-500" />
449 <span className="text-xs max-w-24 truncate">
450 {documentFile.name}
451 </span>
452 </Badge>
453 <button
454   onClick={removeDocument}
455   className="absolute -top-1.5 -end-1.5 h-5 w-5 rounded-full bg-red-500 text-white flex items-
456   aria-label={t("tutor.chat.removeDocument")}
457 >
458 <X className="h-3 w-3" />
459 </button>
460 </div>
461 )})}
462 </div>
463 )}
464
465 { /* Daily message limit reached banner */
466 {isLimitReached && !isTokenBudgetExceeded && (
467 <div
468   className="mb-3 p-3 rounded-lg bg-slate-100 flex items-center gap-2"
469   role="alert"
470 >
471 <Info className="h-4 w-4 text-gray-500 shrink-0" />
472 <p className="text-sm text-gray-500 font-medium">
473 {t("tutor.chat.limitReached")}
474 </p>
475 </div>
476 )}
477
478 { /* Token budget exceeded banner */
479 {isTokenBudgetExceeded && (
480 <div
481   className="mb-3 p-3 rounded-lg bg-red-50 flex items-center gap-2"
482   role="alert"
483 >
484 <AlertTriangle className="h-4 w-4 text-red-700 shrink-0" />
485 <p className="text-sm text-red-700 font-medium">
486 {t("tutor.chat.tokenBudgetExceeded")}
487 </p>
488 </div>
489 )}
490
491 { /* Input row */

```

```

492 | <div className="flex items-end gap-2">
493 |   /* Attachment buttons */
494 |   <div className="flex gap-1 shrink-0 pb-1">
495 |     <input
496 |       ref={imageInputRef}
497 |       type="file"
498 |       accept="image/jpeg,image/png"
499 |       multiple
500 |       className="hidden"
501 |       onChange={handleImageSelect}
502 |       aria-label={t("tutor.chat.attachImages")}
503 |     />
504 |     <Button
505 |       variant="ghost"
506 |       size="icon-sm"
507 |       onClick={() => imageInputRef.current?.click()}
508 |       disabled={
509 |         isInputDisabled ||
510 |         isUploading ||
511 |         imageFiles.length >= MAX_IMAGES
512 |       }
513 |       aria-label={t("tutor.chat.attachImage")}
514 |       className="text-gray-400 hover:text-gray-600"
515 |     >
516 |       <ImagePlus className="h-4 w-4" />
517 |     </Button>
518 |
519 |     <input
520 |       ref={docInputRef}
521 |       type="file"
522 |       accept=".pdf,.docx,application/pdf,application/vnd.openxmlformats-officedocument.wordprocessingm
523 |       className="hidden"
524 |       onChange={handleDocSelect}
525 |       aria-label={t("tutor.chat.attachDocument")}
526 |     />
527 |     <Button
528 |       variant="ghost"
529 |       size="icon-sm"
530 |       onClick={() => docInputRef.current?.click()}
531 |       disabled={isInputDisabled || isUploading || documentFile !== null}
532 |       aria-label={t("tutor.chat.attachDocument")}
533 |       className="text-gray-400 hover:text-gray-600"
534 |     >
535 |       <FileUp className="h-4 w-4" />
536 |     </Button>
537 |   </div>
538 |
539 |   /* Text input */
540 |   <div className="flex-1 relative">
541 |     <Textarea
542 |       ref={textareaRef}
543 |       value={inputValue}
544 |       onChange={(e) => setInputValue(e.target.value)}
545 |       onKeyDown={handleKeyDown}
546 |       placeholder={
547 |         isInputDisabled
548 |           ? t("tutor.chat.inputPlaceholderDisabled")
549 |           : t("tutor.chat.inputPlaceholder")
550 |       }
551 |       disabled={isInputDisabled}
552 |       rows={1}
553 |       className={cn(
554 |         "resize-none min-h-[40px] max-h-[160px] pe-12 text-sm",
555 |         isInputDisabled &&
556 |         "bg-slate-100 text-gray-500 cursor-not-allowed"
557 |       )}
558 |       aria-label={t("tutor.chat.messageInput")}
559 |     />
560 |     /* Character counter */
561 |     {charCount > MAX_MESSAGE_LENGTH * 0.8 && (
562 |       <span
563 |         className={cn(
564 |           "absolute bottom-2 end-12 text-[10px]",
565 |           isOverLimit ? "text-red-500 font-bold" : "text-gray-400"
566 |         )}
567 |       >
568 |         {charCount}/{MAX_MESSAGE_LENGTH}
569 |       </span>
570 |     )}
571 |   </div>
572 |
573 |   /* Send button */
574 |   <Button
575 |     onClick={() => void handleSend()}
576 |     disabled={!canSend}
577 |     size="icon"
578 |     variant="tactile"
579 |     className="shrink-0"
580 |     aria-label={t("tutor.chat.sendMessage")}
581 |   >
582 |     {isSending || isStreaming || isUploading ? (
583 |       <Loader2 className="h-4 w-4 animate-spin" />
584 |     ) : (
585 |       <Send className="h-4 w-4" />
586 |     )}
587 |   </Button>
588 | </div>
589 | </div>
590 | </div>
591 | );
592 | };
593 |
594 | export default ChatPanel;
595 | export type { ChatPanelProps };

```

FILE: src/pages/student/tutor/ConversationSidebar.tsx

TYPE: .tsx | LINES: 1-189 | SHA256: 0bb7d209bab7b165aa83ffbebd8b9d29f53ac679bcc46b69c787815ad526e7c3

```

1  // =====
2  // ConversationSidebar – Past conversations list with delete
3  // =====
4
5  import { useState } from "react";
6  import { useTranslation } from "react-i18next";
7  import { Plus, Trash2, MessageSquare } from "lucide-react";
8  import { Button } from "@components/ui/button";
9  import { ConfirmDialog } from "@components/shared/ConfirmDialog";
10 import { cn } from "@lib/utlis";
11 import type { TutorConversation } from "@lib/tutorSchemas";
12
13 interface ConversationSidebarProps {
14   conversations: TutorConversation[];
15   isLoading: boolean;
16   activeConversationId?: string;
17   onSelectConversation: (conversationId: string) => void;
18   onNewConversation: () => void;
19   onDeleteConversation: (conversationId: string) => void;
20   isDeleting?: boolean;
21 }
22
23 type TFn = (key: string, options?: Record<string, unknown>) => string;
24
25 const truncatePreview = (
26   text: string | null,
27   fallback: string,
28   maxLength = 60
29 ): string => {
30   if (!text) return fallback;
31   if (text.length <= maxLength) return text;
32   return `${text.slice(0, maxLength)}...`;
33 };
34
35 const formatRelativeTime = (dateStr: string, t: TFn): string => {
36   const date = new Date(dateStr);
37   const now = new Date();
38   const diffMs = now.getTime() - date.getTime();
39   const diffMins = Math.floor(diffMs / 60_000);
40   const diffHours = Math.floor(diffMs / 3_600_000);
41   const diffDays = Math.floor(diffMs / 86_400_000);
42
43   if (diffMins < 1) return t("tutor.sidebar.relativeTime.justNow");
44   if (diffMins < 60)
45     return t("tutor.sidebar.relativeTime.minutesAgo", { count: diffMins });
46   if (diffHours < 24)
47     return t("tutor.sidebar.relativeTime.hoursAgo", { count: diffHours });
48   if (diffDays < 7)
49     return t("tutor.sidebar.relativeTime.daysAgo", { count: diffDays });
50   return date.toLocaleDateString(undefined, { month: "short", day: "numeric" });
51 };
52
53 const ConversationSidebar = ({
54   conversations,
55   isLoading,
56   activeConversationId,
57   onSelectConversation,
58   onNewConversation,
59   onDeleteConversation,
60   isDeleting = false,
61 }: ConversationSidebarProps) => {
62   const { t } = useTranslation("ai");
63   const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
64
65   const handleConfirmDelete = () => {
66     if (deleteTarget) {
67       onDeleteConversation(deleteTarget);
68       setDeleteTarget(null);
69     }
70   };
71
72   return (
73     <div className="flex flex-col h-full">
74       { /* Header */ }
75       <div className="p-4 border-b border-gray-100">
76         <Button
77           onClick={onNewConversation}
78           variant="tactile"
79           className="w-full"
80         >
81           <Plus className="h-4 w-4" />
82           {t("tutor.sidebar.newConversation")}
83         </Button>
84       </div>
85
86       { /* Conversation list */ }
87       <div
88         className="flex-1 overflow-y-auto"
89         role="list"
90         aria-label={t("tutor.sidebar.pastConversations")}
91       >
92         {isLoading ? (
93           <div className="p-4 space-y-3">
94             {Array.from({ length: 4 }).map((_, i) => (
95               <div key={i} className="h-16 rounded-lg animate-shimmer" />
96             ))}
97           </div>
98         ) : conversations.length === 0 ? (
99           <div className="p-6 text-center">

```

```

100 |         <MessageSquare className="h-8 w-8 text-gray-300 mx-auto mb-2" />
101 |         <p className="text-sm text-gray-500">
102 |             {t("tutor.sidebar.noConversations")}
103 |         </p>
104 |         <p className="text-xs text-gray-400 mt-1">
105 |             {t("tutor.sidebar.noConversationsHint")}
106 |         </p>
107 |     </div>
108 | ) : (
109 |     <div className="p-2 space-y-0.5">
110 |         {conversations.map((conversation) => {
111 |             const isActive = conversation.id === activeConversationId;
112 |             const preview = truncatePreview(
113 |                 conversation.title,
114 |                 t("tutor.sidebar.newConversationPreview")
115 |             );
116 |
117 |             return (
118 |                 <button
119 |                     key={conversation.id}
120 |                     className={cn(
121 |                         "group flex items-start gap-2 rounded-lg px-3 py-2.5 cursor-pointer transition-colors w-fu
122 |                         isActive
123 |                         ? "bg-blue-50 text-blue-700"
124 |                         : "text-gray-700 hover:bg-gray-50"
125 |                     )}
126 |                     onClick={() => onSelectConversation(conversation.id)}
127 |                     aria-label={t("tutor.sidebar.conversationLabel", {
128 |                         title: preview,
129 |                     })}
130 |                 >
131 |                     <MessageSquare
132 |                         className={cn(
133 |                             "h-4 w-4 mt-0.5 shrink-0",
134 |                             isActive ? "text-blue-500" : "text-gray-400"
135 |                         )}
136 |                     />
137 |                     <div className="flex-1 min-w-0">
138 |                         <p className="text-sm font-medium truncate">{preview}</p>
139 |                         <div className="flex items-center gap-2 mt-0.5">
140 |                             <span className="text-[10px] text-gray-400">
141 |                                 {formatRelativeTime(conversation.updated_at, t)}
142 |                             </span>
143 |                             {conversation.message_count > 0 && (
144 |                                 <span className="text-[10px] text-gray-400">
145 |                                     {t(" ")}
146 |                                     {t("tutor.sidebar.messageCount", {
147 |                                         count: conversation.message_count,
148 |                                     })}
149 |                                 </span>
150 |                             )}
151 |                         </div>
152 |                     </div>
153 |                     <Button
154 |                         variant="ghost"
155 |                         size="icon-xs"
156 |                         onClick={(e) => {
157 |                             e.stopPropagation();
158 |                             setDeleteTarget(conversation.id);
159 |                         }}
160 |                         className="opacity-0 group-hover:opacity-100 text-gray-400 hover:text-red-500 hover:bg-red
161 |                         aria-label={t("tutor.sidebar.deleteConversation")}
162 |                     >
163 |                         <Trash2 className="h-3.5 w-3.5" />
164 |                     </Button>
165 |                 </button>
166 |             );
167 |         })}
168 |     </div>
169 | )}
170 | </div>
171 |
172 | /* Delete confirmation dialog */
173 | <ConfirmDialog
174 |     open={deleteTarget !== null}
175 |     onOpenChange={(open) => !open && setDeleteTarget(null)}
176 |     title={t("tutor.sidebar.deleteTitle")}
177 |     description={t("tutor.sidebar.deleteDescription")}
178 |     confirmLabel={t("tutor.sidebar.deleteConfirm")}
179 |     variant="destructive"
180 |     isPending={isDeleting}
181 |     onConfirm={handleConfirmDelete}
182 | />
183 | </div>
184 | );
185 | };
186 |
187 | export default ConversationSidebar;
188 | export type { ConversationSidebarProps };
189 |

```

FILE: src/pages/student/tutor/PersonaSelector.tsx

TYPE: .tsx | LINES: 1-246 | SHA256: c467a0eb7804217aa89472c031ae5937af80720086025ce5d7e75f878131cadb

```

1 | // =====
2 | // PersonaSelector – Persona picker with 3 AI tutor personas
3 | // Supports auto-recommendation from Big Five profile (Req 26)
4 | // =====
5 |
6 | import { useState } from "react";
7 | import { HelpCircle, ListChecks, Zap, Sparkles } from "lucide-react";
8 | import { useTranslation } from "react-i18next";
9 | import { Button } from "@components/ui/button";
10 | import { Badge } from "@components/ui/badge";

```

```

11 | import { cn } from "@lib/Utils";
12 | import type { TutorPersona } from "@lib/tutorSchemas";
13 |
14 | interface PersonaSelectorProps {
15 |   selectedPersona: TutorPersona;
16 |   onSelect: (persona: TutorPersona) => void;
17 |   /** Inline mode shows compact buttons; full mode shows cards */
18 |   variant?: "inline" | "full";
19 |   /** Auto-recommended persona from Big Five profile */
20 |   recommendedPersona?: TutorPersona | null;
21 | }
22 |
23 | interface PersonaOption {
24 |   id: TutorPersona;
25 |   icon: typeof HelpCircle;
26 |   color: string;
27 |   activeColor: string;
28 | }
29 |
30 | const personas: PersonaOption[] = [
31 |   {
32 |     id: "socratic_guide",
33 |     icon: HelpCircle,
34 |     color: "text-purple-600",
35 |     activeColor: "bg-purple-50 border-purple-200 text-purple-700",
36 |   },
37 |   {
38 |     id: "step_by_step_coach",
39 |     icon: ListChecks,
40 |     color: "text-blue-600",
41 |     activeColor: "bg-blue-50 border-blue-200 text-blue-700",
42 |   },
43 |   {
44 |     id: "quick_explainer",
45 |     icon: Zap,
46 |     color: "text-teal-600",
47 |     activeColor: "bg-teal-50 border-teal-200 text-teal-700",
48 |   },
49 | ];
50 |
51 | const PersonaSelector = ({
52 |   selectedPersona,
53 |   onSelect,
54 |   variant = "inline",
55 |   recommendedPersona,
56 | }: PersonaSelectorProps) => {
57 |   const { t } = useTranslation("ai");
58 |   const [showFullPicker, setShowFullPicker] = useState(false);
59 |
60 |   // If there's a recommendation and user hasn't opened the full picker yet,
61 |   // show the compact recommendation view in full variant
62 |   const showRecommendation =
63 |     variant === "full" &&
64 |     recommendedPersona &&
65 |     !showFullPicker &&
66 |     selectedPersona === recommendedPersona;
67 |
68 |   if (showRecommendation) {
69 |     const recommended = personas.find((p) => p.id === recommendedPersona);
70 |     if (recommended) {
71 |       const Icon = recommended.icon;
72 |       return (
73 |         <div
74 |           className="space-y-3"
75 |           role="group"
76 |           aria-label={t("tutor.persona.recommendedGroupLabel")}
77 |         >
78 |           <p className="text-sm font-medium text-gray-700">
79 |             {t("tutor.persona.yourStyle")}
80 |           </p>
81 |           <div
82 |             className={cn(
83 |               "flex items-start gap-3 p-3 rounded-xl border-2 transition-all",
84 |               recommended.activeColor
85 |             )}
86 |           >
87 |             <div className="p-1.5 rounded-lg bg-white/60 shrink-0">
88 |               <Icon className={cn("h-4 w-4", recommended.color)} />
89 |             </div>
90 |             <div className="min-w-0 flex-1">
91 |               <div className="flex items-center gap-2">
92 |                 <p className="text-sm font-semibold">
93 |                   {t(`tutor.persona.${recommended.id}.label`)}
94 |                 </p>
95 |                 <Badge
96 |                   variant="secondary"
97 |                   className="bg-amber-100 text-amber-700 border-amber-200 text-[10px] font-bold gap-1 px-1.5 p
98 |                 >
99 |                   <Sparkles className="h-3 w-3" />
100 |                   {t("tutor.persona.recommended")}
101 |                 </Badge>
102 |               </div>
103 |               <p className="text-xs mt-0.5 opacity-80">
104 |                 {t(`tutor.persona.${recommended.id}.description`)}
105 |               </p>
106 |             </div>
107 |           </div>
108 |           <Button
109 |             variant="ghost"
110 |             size="sm"
111 |             className="text-xs text-gray-500 hover:text-gray-700"
112 |             onClick={() => setShowFullPicker(true)}
113 |           >
114 |             {t("tutor.persona.changeStyle")}

```

```

115 |         </Button>
116 |     </div>
117 | );
118 | }
119 | }
120 |
121 | if (variant === "full") {
122 |     return (
123 |         <div
124 |             className="space-y-3"
125 |             role="radiogroup"
126 |             aria-label={t("tutor.persona.selectLabel")}
127 |         >
128 |             <p className="text-sm font-medium text-gray-700">
129 |                 {t("tutor.persona.chooseStyle")}
130 |             </p>
131 |             <div className="grid gap-2">
132 |                 {personas.map((persona) => {
133 |                     const Icon = persona.icon;
134 |                     const isSelected = selectedPersona === persona.id;
135 |                     const isRecommended = recommendedPersona === persona.id;
136 |
137 |                     return (
138 |                         <button
139 |                             key={persona.id}
140 |                             role="radio"
141 |                             aria-checked={isSelected}
142 |                             onClick={() => onSelect(persona.id)}
143 |                             className={cn(
144 |                                 "flex items-start gap-3 p-3 rounded-xl border-2 transition-all text-start",
145 |                                 isSelected
146 |                                   ? persona.activeColor
147 |                                   : "border-gray-100 bg-white hover:border-gray-200"
148 |                             )}
149 |                         >
150 |                             <div
151 |                                 className={cn(
152 |                                     "p-1.5 rounded-lg shrink-0",
153 |                                     isSelected ? "bg-white/60" : "bg-gray-50"
154 |                                 )}
155 |                             >
156 |                                 <Icon
157 |                                     className={cn(
158 |                                         "h-4 w-4",
159 |                                         isSelected ? persona.color : "text-gray-400"
160 |                                     )}
161 |                                 />
162 |                             </div>
163 |                             <div className="min-w-0 flex-1">
164 |                                 <div className="flex items-center gap-2">
165 |                                     <p
166 |                                         className={cn(
167 |                                             "text-sm font-semibold",
168 |                                             isSelected ? "" : "text-gray-800"
169 |                                         )}
170 |                                     >
171 |                                         {t(`tutor.persona.${persona.id}.label`)}
172 |                                     </p>
173 |                                     {isRecommended && (
174 |                                         <Badge
175 |                                             variant="secondary"
176 |                                             className="bg-amber-100 text-amber-700 border-amber-200 text-[10px] font-bold gap-1 px
177 |                                         >
178 |                                             <Sparkles className="h-3 w-3" />
179 |                                             {t("tutor.persona.recommended")}
180 |                                         </Badge>
181 |                                     )}
182 |                                 </div>
183 |                                 <p
184 |                                     className={cn(
185 |                                         "text-xs mt-0.5",
186 |                                         isSelected ? "opacity-80" : "text-gray-500"
187 |                                     )}
188 |                                 >
189 |                                     {t(`tutor.persona.${persona.id}.description`)}
190 |                                 </p>
191 |                             </div>
192 |                             {isSelected && (
193 |                                 <div className="ms-auto shrink-0 h-5 w-5 rounded-full bg-white border-2 border-current flex
194 |                                     <div className="h-2.5 w-2.5 rounded-full bg-current" />
195 |                                 </div>
196 |                             )}
197 |                         </button>
198 |                     );
199 |                 })}
200 |             </div>
201 |         </div>
202 |     );
203 | }
204 |
205 | // Inline variant – compact buttons for the chat header
206 | return (
207 |     <div
208 |         className="flex items-center gap-1"
209 |         role="radiogroup"
210 |         aria-label={t("tutor.persona.groupLabel")}
211 |     >
212 |         {personas.map((persona) => {
213 |             const Icon = persona.icon;
214 |             const isSelected = selectedPersona === persona.id;
215 |             const isRecommended = recommendedPersona === persona.id;
216 |
217 |             return (
218 |                 <Button

```



```

219 |         key={persona.id}
220 |         variant={isSelected ? "secondary" : "ghost"}
221 |         size="sm"
222 |         role="radio"
223 |         aria-checked={isSelected}
224 |         onClick={() => onSelect(persona.id)}
225 |         className={cn(
226 |           "gap-1 text-xs h-7 px-2",
227 |           isSelected && persona.activeColor
228 |         )}
229 |       >
230 |         <Icon className="h-3.5 w-3.5" />
231 |         <span className="hidden sm:inline">
232 |           {t(`tutor.persona.${persona.id}.label`)}
233 |         </span>
234 |         {isRecommended && isSelected && (
235 |           <Sparkles className="h-3 w-3 text-amber-500" />
236 |         )}
237 |       </Button>
238 |     );
239 |   }}}}
240 | </div>
241 | );
242 | };
243 |
244 | export default PersonaSelector;
245 | export type { PersonaSelectorProps };
246 |

```

FILE: [src/pages/student/tutor/TutorPage.tsx](#)

TYPE: .tsx | LINES: 1-372 | SHA256: 0caffe3830c98e90242982028b809a79673c55f27fc0833e86991e76d521e667

```

1 | // =====
2 | // TutorPage – Main tutor page with sidebar + chat layout
3 | // =====
4 |
5 | import { useState, useCallback } from "react";
6 | import { useParams, useNavigate, useSearchParams } from "react-router-dom";
7 | import { useTranslation } from "react-i18next";
8 | import { Menu, Bot } from "lucide-react";
9 | import { Button } from "@components/ui/button";
10 | import { Sheet, SheetContent } from "@components/ui/sheet";
11 | import ErrorBoundary from "@components/shared/ErrorBoundary";
12 | import {
13 |   useTutorConversations,
14 |   useCreateConversation,
15 |   useDeleteConversation,
16 | } from "@hooks/useTutorConversations";
17 | import {
18 |   useTutorMessages,
19 |   useSendMessage,
20 |   useRateMessage,
21 | } from "@hooks/useTutorMessages";
22 | import { useTutorUsage } from "@hooks/useTutorUsage";
23 | import { useUpdateConversationAutonomy } from "@hooks/useUpdateConversationAutonomy";
24 | import { mapTutorError, type TutorUiState } from "@lib/tutorStatus";
25 | import ChatPanel from "@pages/student/tutor/ChatPanel";
26 | import TutorStatePanel from "@pages/student/tutor/TutorStatePanel";
27 | import ConversationSidebar from "@pages/student/tutor/ConversationSidebar";
28 | import PersonaSelector from "@pages/student/tutor/PersonaSelector";
29 | import type { TutorPersona, SourceCitation } from "@lib/tutorSchemas";
30 |
31 | const TutorPage = () => {
32 |   const { conversationId } = useParams<{ conversationId?: string }>();
33 |   const [searchParams] = useSearchParams();
34 |   const navigate = useNavigate();
35 |   const { t } = useTranslation("ai");
36 |
37 |   // Query params for contextual entry
38 |   const courseIdParam = searchParams.get("courseId") ?? undefined;
39 |   const cloIdsParam =
40 |     searchParams.get("cloIds")?.split(",").filter(Boolean) ?? undefined;
41 |
42 |   // State
43 |   const [persona, setPersona] = useState<TutorPersona>("socratic_guide");
44 |   const [sidebarOpen, setSidebarOpen] = useState(false);
45 |   const [showPersonaPicker, setShowPersonaPicker] = useState(!conversationId);
46 |   // Backend-derived tutor availability state. `ready` keeps the live chat
47 |   // surface; any failure signal is mapped via `mapTutorError` to a distinct
48 |   // panel (R4.2, R4.3, R4.4) with a guaranteed `error` fallback (R4.2a).
49 |   const [tutorState, setTutorState] = useState<TutorUiState>({ kind: "ready" });
50 |
51 |   // Hooks
52 |   const { data: conversations = [], isLoading: isLoadingConversations } =
53 |     useTutorConversations(courseIdParam);
54 |   const { data: messages = [], isLoading: isLoadingMessages } =
55 |     useTutorMessages(conversationId ?? "");
56 |   const { data: usage } = useTutorUsage();
57 |   const createConversation = useCreateConversation();
58 |   const deleteConversation = useDeleteConversation();
59 |   const sendMessage = useSendMessage();
60 |   const rateMessage = useRateMessage();
61 |   const updateAutonomy = useUpdateConversationAutonomy();
62 |
63 |   // Derive persona from active conversation
64 |   const activeConversation = conversationId
65 |     ? conversations.find((c) => c.id === conversationId)
66 |     : undefined;
67 |
68 |   // Sync persona from active conversation when it changes
69 |   const derivedPersona = activeConversation?.persona ?? persona;
70 |   const isNewConversation = !conversationId;
71 |   const shouldShowPersonaPicker = isNewConversation && showPersonaPicker;
72 |

```

[illegible]

[illegible]

```

281 |         {t("tutor.page.title")}
282 |       </span>
283 |     </div>
284 |
285 |     {/* Persona picker for new conversations */}
286 |     {shouldShowPersonaPicker ? (
287 |       <div className="flex-1 flex flex-col items-center justify-center p-6">
288 |         <div className="max-w-sm w-full space-y-6">
289 |           <div className="text-center">
290 |             <div className="mx-auto p-4 rounded-2xl bg-gradient-to-br from-teal-50 to-blue-50 w-fit mb-4">
291 |               <div className="p-3 rounded-xl bg-[linear-gradient(93.65deg,#14b8a6_5.37%,#0382bd_78.89%)]">
292 |                 <Bot className="h-8 w-8 text-white" />
293 |               </div>
294 |             </div>
295 |             <h2 className="text-xl font-bold text-gray-800">
296 |               {t("tutor.page.newConversationTitle")}
297 |             </h2>
298 |             <p className="text-sm text-gray-500 mt-1">
299 |               {t("tutor.page.newConversationSubtitle")}
300 |             </p>
301 |           </div>
302 |
303 |           <PersonaSelector
304 |             selectedPersona={persona}
305 |             onSelect={handlePersonaChange}
306 |             variant="full"
307 |           />
308 |
309 |           <Button
310 |             variant="tactile"
311 |             className="w-full"
312 |             onClick={handleStartChatting}
313 |           >
314 |             {t("tutor.page.startChatting")}
315 |           </Button>
316 |
317 |           <p className="text-xs text-gray-400 text-center">
318 |             {t("tutor.page.personaHint")}
319 |           </p>
320 |         </div>
321 |       </div>
322 |     ) : (
323 |       // The chat area is wrapped in an ErrorBoundary so the guaranteed
324 |       // fallback error display renders even if tutor-state detection or the
325 |       // chat itself throws (R4.2a).
326 |       <ErrorBoundary
327 |         fallback={
328 |           <div className="flex-1 flex items-center justify-center p-6">
329 |             <TutorStatePanel
330 |               state={{
331 |                 kind: "error",
332 |                 message: "",
333 |               }}
334 |             />
335 |           </div>
336 |         }
337 |       >
338 |         {tutorState.kind !== "ready" ? (
339 |           <div className="flex-1 flex items-center justify-center p-6">
340 |             <TutorStatePanel
341 |               state={tutorState}
342 |               onRetry={handleRetryTutor}
343 |             />
344 |           </div>
345 |         ) : (
346 |           <ChatPanel
347 |             messages={messages}
348 |             isLoadingMessages={isLoadingMessages}
349 |             conversationId={conversationId}
350 |             courseId={courseIdParam}
351 |             persona={derivedPersona}
352 |             onPersonaChange={handlePersonaChange}
353 |             onSendMessage={handleSendMessage}
354 |             onRateMessage={handleRateMessage}
355 |             isSending={
356 |               sendMessage.isPending || createConversation.isPending
357 |             }
358 |             isRatingPending={rateMessage.isPending}
359 |             usage={usage}
360 |             autonomyOverride={derivedAutonomyOverride}
361 |             onAutonomyChange={handleAutonomyChange}
362 |           />
363 |         )}
364 |       </ErrorBoundary>
365 |     )}
366 |   </div>
367 | </div>
368 | );
369 | };
370 |
371 | export default TutorPage;
372 |

```

FILE: [src/pages/student/tutor/TutorStatePanel.tsx](#)

TYPE: .tsx | LINES: 1-99 | SHA256: df84851e651587974393fa41ddbedb8597ae6272854feae5690342ffb51b4ca

```

1 | // =====
2 | // TutorStatePanel - Renders a distinct panel per non-ready TutorUiState (R4)
3 | // =====
4 | //
5 | // Consumes the discriminated `TutorUiState` produced by `mapTutorError`
6 | // (src/lib/tutorStatus.ts) and renders an actionable panel for each non-ready
7 | // state: unavailable, not_enrolled, no_embeddings, rate_limited, and the
8 | // guaranteed `error` fallback (R4.2, R4.2a, R4.3, R4.4). All copy is routed

```

```

9 | // through i18next (en + ar). The `ready` state renders nothing so the live
10 | // chat surface shows through.
11 |
12 | import { useTranslation } from "react-i18next";
13 | import { AlertTriangle, BookOpen, Clock, Lock, WifiOff } from "lucide-react";
14 | import ErrorState from "@components/shared/ErrorState";
15 | import type { TutorUiState } from "@lib/tutorStatus";
16 |
17 | interface TutorStatePanelProps {
18 |   state: TutorUiState;
19 |   /** Retry handler offered on recoverable states. */
20 |   onRetry?: () => void;
21 | }
22 |
23 | const TutorStatePanel = ({ state, onRetry }: TutorStatePanelProps) => {
24 |   const { t } = useTranslation("ai");
25 |
26 |   if (state.kind === "ready") {
27 |     return null;
28 |   }
29 |
30 |   const retryLabel = t("tutor.states.retry");
31 |
32 |   switch (state.kind) {
33 |     case "unavailable":
34 |       return (
35 |         <ErrorState
36 |           title={t("tutor.states.unavailable.title")}
37 |           message={t("tutor.states.unavailable.message")}
38 |           icon={<WifiOff className="h-8 w-8 text-red-500" />}
39 |           onRetry={onRetry}
40 |           retryLabel={retryLabel}
41 |         />
42 |       );
43 |
44 |     case "not_enrolled":
45 |       return (
46 |         <ErrorState
47 |           title={t("tutor.states.notEnrolled.title")}
48 |           message={t("tutor.states.notEnrolled.message")}
49 |           icon={<Lock className="h-8 w-8 text-amber-500" />}
50 |         />
51 |       );
52 |
53 |     case "no_embeddings":
54 |       return (
55 |         <ErrorState
56 |           title={t("tutor.states.noEmbeddings.title")}
57 |           message={t("tutor.states.noEmbeddings.message")}
58 |           icon={<BookOpen className="h-8 w-8 text-blue-500" />}
59 |         />
60 |       );
61 |
62 |     case "rate_limited":
63 |       return (
64 |         <ErrorState
65 |           title={t("tutor.states.rateLimited.title")}
66 |           message={
67 |             state.resetHint
68 |               ? `${t("tutor.states.rateLimited.message")} ${t(
69 |                 "tutor.states.rateLimited.reset",
70 |                 { hint: state.resetHint }
71 |               )}`
72 |             : t("tutor.states.rateLimited.message")
73 |           }
74 |           icon={<Clock className="h-8 w-8 text-amber-500" />}
75 |         />
76 |       );
77 |
78 |     case "error":
79 |     default: {
80 |       const message =
81 |         state.kind === "error" && state.message.trim().length > 0
82 |           ? state.message
83 |           : t("tutor.states.error.message");
84 |       return (
85 |         <ErrorState
86 |           title={t("tutor.states.error.title")}
87 |           message={message}
88 |           icon={<AlertTriangle className="h-8 w-8 text-red-500" />}
89 |           onRetry={onRetry}
90 |           retryLabel={retryLabel}
91 |         />
92 |       );
93 |     }
94 |   }
95 | };
96 |
97 | export default TutorStatePanel;
98 | export type { TutorStatePanelProps };
99 |

```

FILE: [src/pages/teacher/announcements/AnnouncementEditor.tsx](#)

TYPE: .tsx | LINES: 1-401 | SHA256: 13266a866cf3d56a88a7fd9e8a649d21498fa9739dec367af348a3a4cc0ffe72

```

1 | // Task 66.2: Announcement Editor – Create/edit announcements with markdown content and pin toggle
2 | // Requirements: 75.1, 75.4
3 | import { useState } from "react";
4 | import { useForm } from "react-hook-form";
5 | import { zodResolver } from "@hookform/resolvers/zod";
6 | import { z } from "zod";
7 | import { useAuth } from "@hooks/useAuth";
8 | import {
9 |   useAnnouncements,

```

[illegible]

```

114         content: "",
115         is_pinned: false,
116     },
117 });
118
119 const openCreateForm = () => {
120     setEditingAnnouncement(null);
121     form.reset({
122         course_id: effectiveCourseId,
123         title: "",
124         content: "",
125         is_pinned: false,
126     });
127     setShowForm(true);
128 };
129
130 const openEditForm = (announcement: Announcement) => {
131     setEditingAnnouncement(announcement);
132     form.reset({
133         course_id: announcement.course_id,
134         title: announcement.title,
135         content: announcement.content,
136         is_pinned: announcement.is_pinned,
137     });
138     setShowForm(true);
139 };
140
141 const onSubmit = (data: AnnouncementFormData) => {
142     if (!teacherId) return;
143
144     if (editingAnnouncement) {
145         updateMutation.mutate(
146             {
147                 id: editingAnnouncement.id,
148                 title: data.title,
149                 content: data.content,
150                 is_pinned: data.is_pinned,
151                 performedBy: teacherId,
152             },
153             {
154                 onSuccess: () => {
155                     toast.success("Announcement updated");
156                     setShowForm(false);
157                     setEditingAnnouncement(null);
158                 },
159                 onError: (err) => toast.error(err.message),
160             }
161         );
162     } else {
163         createMutation.mutate(
164             {
165                 course_id: data.course_id,
166                 author_id: teacherId,
167                 title: data.title,
168                 content: data.content,
169                 is_pinned: data.is_pinned,
170                 performedBy: teacherId,
171             },
172             {
173                 onSuccess: () => {
174                     toast.success("Announcement posted");
175                     setShowForm(false);
176                 },
177                 onError: (err) => toast.error(err.message),
178             }
179         );
180     }
181 };
182
183 const handleDelete = () => {
184     if (!deleteTarget || !teacherId) return;
185     deleteMutation.mutate(
186         { id: deleteTarget.id, performedBy: teacherId },
187         {
188             onSuccess: () => {
189                 toast.success("Announcement deleted");
190                 setDeleteTarget(null);
191             },
192             onError: (err) => toast.error(err.message),
193         }
194     );
195 };
196
197 const isPending = createMutation.isPending || updateMutation.isPending;
198
199 return (
200     <div className="space-y-6">
201         {/* Page Header */}
202         <div className="flex items-center justify-between">
203             <h1 className="text-2xl font-bold tracking-tight">Announcements</h1>
204             <Button
205                 onClick={openCreateForm}
206                 disabled={!effectiveCourseId}
207                 variant="tactile"
208             >
209                 <Plus className="h-4 w-4" /> New Announcement
210             </Button>
211         </div>
212
213         {/* Course Selector */}
214         <div className="max-w-xs">
215             {coursesLoading ? (
216                 <Shimmer className="h-10 rounded-lg" />
217             ) : (

```

```

218     <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
219       <SelectTrigger className="bg-white">
220         <SelectValue placeholder="Select a course" />
221       </SelectTrigger>
222       <SelectContent>
223         {(courses ?? []).map((c) => (
224           <SelectItem key={c.id} value={c.id}>
225             {c.code} – {c.name}
226           </SelectItem>
227         ))}
228       </SelectContent>
229     </Select>
230   ))}
231 </div>
232
233 /* Create/Edit Form */
234 {showForm && (
235   <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
236     <h2 className="text-lg font-bold tracking-tight mb-4">
237       {editingAnnouncement ? "Edit Announcement" : "New Announcement"}
238     </h2>
239     <Form {...form}>
240       <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
241         <FormField>
242           control={form.control}
243           name="title"
244           render={({ field }) => (
245             <FormItem>
246               <FormLabel>Title</FormLabel>
247               <FormControl>
248                 <Input placeholder="Announcement title" {...field} />
249               </FormControl>
250               <FormMessage />
251             </FormItem>
252           )}
253         </FormField>
254         <FormField>
255           control={form.control}
256           name="content"
257           render={({ field }) => (
258             <FormItem>
259               <FormLabel>Content (Markdown supported)</FormLabel>
260               <FormControl>
261                 <Textarea>
262                   placeholder="Write your announcement content here..."
263                   rows={6}
264                   {...field}
265                 </Textarea>
266               </FormControl>
267               <FormMessage />
268             </FormItem>
269           )}
270         </FormField>
271         <FormField>
272           control={form.control}
273           name="is_pinned"
274           render={({ field }) => (
275             <FormItem className="flex items-center gap-3">
276               <FormControl>
277                 <Switch>
278                   checked={field.value}
279                   onChange={field.onChange}
280                 </Switch>
281               </FormControl>
282               <FormLabel className="!mt-0">
283                 Pin this announcement
284               </FormLabel>
285             </FormItem>
286           )}
287         </FormField>
288         <div className="flex gap-2">
289           <Button type="submit" disabled={isPending} variant="tactile">
290             {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
291             {editingAnnouncement ? "Update" : "Post"}
292           </Button>
293           <Button>
294             type="button"
295             variant="outline"
296             onClick={() => {
297               setShowForm(false);
298               setEditingAnnouncement(null);
299             }}
300           >
301             Cancel
302           </Button>
303         </div>
304       </form>
305     </Card>
306   )}
307
308 /* Announcements List */
309 {announcementsLoading ? (
310   <div className="space-y-3">
311     <Array.from({ length: 3 }).map((_, i) => (
312       <Shimmer key={i} className="h-24 rounded-xl" />
313     ))
314   </div>
315 ) : (announcements ?? []).length === 0 ? (
316   <Card className="bg-white border-0 shadow-md rounded-xl p-8 text-center">
317     <Megaphone className="h-10 w-10 text-gray-300 mx-auto mb-3" />
318     <p className="text-sm text-gray-500">
319       No announcements yet. Post one to get started.
320     </p>
321

```



```

322 |     </Card>
323 |   ) : {
324 |     <div className="space-y-3">
325 |       {(announcements ?? []).map((a) => (
326 |         <Card
327 |           key={a.id}
328 |           className={`bg-white border-0 shadow-md rounded-xl p-4 ${
329 |             a.is_pinned ? "ring-1 ring-amber-200" : ""
330 |           }}
331 |         >
332 |           <div className="flex items-start gap-3">
333 |             <Megaphone
334 |               className={`h-5 w-5 mt-0.5 shrink-0 ${
335 |                 a.is_pinned ? "text-amber-500" : "text-gray-400"
336 |               }}
337 |             />
338 |             <div className="flex-1 min-w-0">
339 |               <div className="flex items-center gap-2 mb-1">
340 |                 <h3 className="text-sm font-bold truncate">{a.title}</h3>
341 |                 {a.is_pinned && (
342 |                   <Badge
343 |                     variant="outline"
344 |                     className="text-xs text-amber-600 border-amber-200"
345 |                   >
346 |                     <Pin className="h-3 w-3 me-1" /> Pinned
347 |                   </Badge>
348 |                 )}
349 |               </div>
350 |               <p className="text-sm text-gray-600 whitespace-pre-wrap line-clamp-4">
351 |                 {a.content}
352 |               </p>
353 |               <p className="text-xs text-gray-400 mt-2">
354 |                 {format(new Date(a.created_at), "MMM d, yyyy · h:mm a")}
355 |               </p>
356 |             </div>
357 |             <div className="flex gap-1 shrink-0">
358 |               <Button
359 |                 variant="ghost"
360 |                 size="sm"
361 |                 onClick={() => openEditForm(a)}
362 |                 className="h-8 w-8 p-0"
363 |               >
364 |                 <Pencil className="h-4 w-4 text-gray-400" />
365 |               </Button>
366 |               <Button
367 |                 variant="ghost"
368 |                 size="sm"
369 |                 onClick={() => setDeleteTarget(a)}
370 |                 className="h-8 w-8 p-0"
371 |               >
372 |                 <Trash2 className="h-4 w-4 text-red-400" />
373 |               </Button>
374 |             </div>
375 |           </div>
376 |           {/* Attachments (client-validated upload + signed-URL download) */}
377 |           <AnnouncementAttachmentManager announcementId={a.id} />
378 |         </Card>
379 |       )})
380 |     </div>
381 |   )}
382 |
383 |   {/* Delete Confirmation */}
384 |   <ConfirmDialog
385 |     open={!!deleteTarget}
386 |     onOpenChange={(open: boolean) => {
387 |       if (!open) setDeleteTarget(null);
388 |     }}
389 |     title="Delete Announcement"
390 |     description={`Are you sure you want to delete "${deleteTarget?.title}"? This action cannot be undone.`}
391 |     onConfirm={handleDelete}
392 |     confirmLabel="Delete"
393 |     variant="destructive"
394 |     isPending={deleteMutation.isPending}
395 |   />
396 | </div>
397 | );
398 | };
399 |
400 | export default AnnouncementEditor;
401 |

```

FILE: [src/pages/teacher/assignments/AssignmentForm.tsx](#)

TYPE: .tsx | LINES: 1-791 | SHA256: 9b014d2680878ec149d429f12fe996350200269323714e82fb498db18a2333b2

```

1 | import { useEffect, useState, useMemo } from "react";
2 | import { useForm, useFieldArray, useWatch } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useNavigate, useParams } from "react-router-dom";
5 | import { z } from "zod";
6 | import {
7 |   createAssignmentSchema,
8 |   type CreateAssignmentFormData,
9 | } from "@lib/schemas/assignment";
10 | import {
11 |   useAssignment,
12 |   useCreateAssignment,
13 |   useUpdateAssignment,
14 | } from "@hooks/useAssignments";
15 | import { useTeacherCourses } from "@hooks/useCourses";
16 | import { useCLOs } from "@hooks/useCLOs";
17 | import { useAcademicCalendarEvents } from "@hooks/useAcademicCalendar";
18 | import { BLOOMS_COLORS } from "@lib/bloomsVerbs";
19 | import type { BloomsLevel } from "@lib/schemas/clo";
20 | import type { LearningOutcome } from "@types/app";

```

[illegible]

[illegible]

[illegible]

```

333 |   isPending: boolean;
334 |   isEditMode: boolean;
335 | }
336 |
337 | const AssignmentFormFields = ({
338 |   form,
339 |   onSubmit,
340 |   isPending,
341 |   isEditMode,
342 | }: AssignmentFormFieldsProps) => {
343 |   const navigate = useNavigate();
344 |
345 |   const selectedCourseId = useWatch({
346 |     control: form.control,
347 |     name: "course_id",
348 |   });
349 |   const watchedDueDate = useWatch({ control: form.control, name: "due_date" });
350 |   const { data: paginatedCourses, isLoading: isLoadingCourses } =
351 |     useTeacherCourses();
352 |   const courses = paginatedCourses?.data ?? [];
353 |   const { data: paginatedCLOs, isLoading: isLoadingCLOs } = useCLOs(
354 |     selectedCourseId || undefined
355 |   );
356 |   const clos = paginatedCLOs?.data ?? [];
357 |   const { data: calendarEvents = [] } = useAcademicCalendarEvents();
358 |
359 |   // Check if due date falls on a holiday
360 |   const holidayWarning = useMemo(() => {
361 |     if (!watchedDueDate) return null;
362 |     const dueDateStr = watchedDueDate.slice(0, 10);
363 |     const holidays = calendarEvents.filter((e) => e.event_type === "holiday");
364 |     const matchingHoliday = holidays.find((h) => {
365 |       if (dueDateStr === h.start_date) return true;
366 |       if (h.end_date && dueDateStr >= h.start_date && dueDateStr <= h.end_date)
367 |         return true;
368 |       return false;
369 |     });
370 |     if (!matchingHoliday) return null;
371 |     // Suggest next available date
372 |     const endDate = matchingHoliday.end_date ?? matchingHoliday.start_date;
373 |     const nextDate = new Date(endDate);
374 |     nextDate.setDate(nextDate.getDate() + 1);
375 |     const nextDateStr = nextDate.toISOString().slice(0, 10);
376 |     return { holiday: matchingHoliday.title, suggestedDate: nextDateStr };
377 |   }, [watchedDueDate, calendarEvents]);
378 |
379 |   // Reset CLO weights when course changes
380 |   useEffect(() => {
381 |     if (selectedCourseId && !isEditMode) {
382 |       form.setValue("clo_weights", []);
383 |       form.setValue("prerequisites", []);
384 |     }
385 |     // eslint-disable-next-line react-hooks/exhaustive-deps
386 |   }, [selectedCourseId]);
387 |
388 |   return (
389 |     <Form {...form}>
390 |       <form
391 |         onSubmit={form.handleSubmit((data) => {
392 |           // Convert datetime-local to ISO string
393 |           const isoDate = data.due_date.includes("Z")
394 |             ? data.due_date
395 |             : new Date(data.due_date).toISOString();
396 |           onSubmit({ ...data, due_date: isoDate });
397 |         })}
398 |         className="space-y-6"
399 |       >
400 |         {/* Section 1: Basic Details */}
401 |         <Card className="bg-white border-0 shadow-md rounded-xl p-6">
402 |           <h2 className="text-lg font-bold tracking-tight mb-4">
403 |             Basic Details
404 |           </h2>
405 |           <div className="space-y-4">
406 |             <FormField
407 |               control={form.control}
408 |               name="title"
409 |               render={({ field }) => (
410 |                 <FormItem>
411 |                   <FormLabel>Title</FormLabel>
412 |                   <FormControl>
413 |                     <Input
414 |                       placeholder="e.g. Binary Search Tree Implementation"
415 |                       {...field}
416 |                     />
417 |                   </FormControl>
418 |                   <FormMessage />
419 |                 </FormItem>
420 |               )}
421 |             />
422 |
423 |             <FormField
424 |               control={form.control}
425 |               name="description"
426 |               render={({ field }) => (
427 |                 <FormItem>
428 |                   <FormLabel>Description</FormLabel>
429 |                   <FormControl>
430 |                     <Textarea
431 |                       placeholder="Describe the assignment objectives and deliverables..."
432 |                       rows={4}
433 |                       {...field}
434 |                     />
435 |                   </FormControl>
436 |                   <FormMessage />

```

```

437 |         </FormItem>
438 |     )}
439 | </>
440 |
441 | <FormField
442 |   control={form.control}
443 |   name="course_id"
444 |   render={({ field }) => (
445 |     <FormItem>
446 |       <FormLabel>Course</FormLabel>
447 |       <Select
448 |         onValueChange={field.onChange}
449 |         value={field.value}
450 |         disabled={isLoadingCourses || isEditMode}
451 |       >
452 |         <FormControl>
453 |           <SelectTrigger className="bg-white">
454 |             <SelectValue placeholder="Select a course" />
455 |           </SelectTrigger>
456 |         </FormControl>
457 |         <SelectContent>
458 |           {courses.map((course) => (
459 |             <SelectItem key={course.id} value={course.id}>
460 |               {course.code} - {course.name}
461 |             </SelectItem>
462 |           ))}
463 |         </SelectContent>
464 |       </Select>
465 |       <FormMessage />
466 |     </FormItem>
467 |   )}
468 | </>
469 |
470 | <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
471 |   <FormField
472 |     control={form.control}
473 |     name="due_date"
474 |     render={({ field }) => (
475 |       <FormItem>
476 |         <FormLabel>Due Date</FormLabel>
477 |         <FormControl>
478 |           <Input
479 |             type="datetime-local"
480 |             {...field}
481 |             value={
482 |               field.value
483 |               ? field.value.includes("T")
484 |                 ? field.value.slice(0, 16)
485 |                 : field.value
486 |               : ""
487 |             }
488 |           />
489 |         </FormControl>
490 |         {holidayWarning && (
491 |           <p className="text-xs text-amber-600 mt-1">
492 |             &#xA0; &#xA0; This date falls on a holiday (
493 |               {holidayWarning.holiday}). Consider moving to{" "}
494 |               {holidayWarning.suggestedDate}.
495 |             </p>
496 |           )}
497 |         <FormMessage />
498 |       </FormItem>
499 |     )}
500 |   </>
501 |
502 |   <FormField
503 |     control={form.control}
504 |     name="total_marks"
505 |     render={({ field }) => (
506 |       <FormItem>
507 |         <FormLabel>Total Marks</FormLabel>
508 |         <FormControl>
509 |           <Input
510 |             type="number"
511 |             min={1}
512 |             placeholder="100"
513 |             {...field}
514 |             onChange={(e) => field.onChange(Number(e.target.value))}
515 |             value={field.value ?? ""}
516 |           />
517 |         </FormControl>
518 |         <FormMessage />
519 |       </FormItem>
520 |     )}
521 |   </>
522 |
523 |   <FormField
524 |     control={form.control}
525 |     name="late_window_hours"
526 |     render={({ field }) => (
527 |       <FormItem>
528 |         <FormLabel>Late Window (hours)</FormLabel>
529 |         <FormControl>
530 |           <Input
531 |             type="number"
532 |             min={0}
533 |             placeholder="24"
534 |             {...field}
535 |             onChange={(e) => field.onChange(Number(e.target.value))}
536 |             value={field.value ?? 24}
537 |           />
538 |         </FormControl>
539 |         <FormMessage />
540 |       </FormItem>

```

[illegible]

[illegible]

[illegible]

FILE: src/pages/teacher/assignments/AssignmentListPage.tsx

TYPE: .tsx | LINES: 1-149 | SHA256: dd40d81aeace1f63cd43bdedad49469e25fa5ca97e542352cb80938366fbf82d

```

1 import { useState } from "react";
2 import { useNavigate } from "react-router-dom";
3 import { toast } from "sonner";
4 import { parseAsString, useQueryState } from "nuqs";
5 import { createColumns } from "../columns";
6 import { DataTable } from "@components/shared/DataTable";
7 import { ConfirmDialog } from "@components/shared/ConfirmDialog";
8 import { useAssignments, useDeleteAssignment } from "@hooks/useAssignments";
9 import type { AssignmentWithRelations } from "@hooks/useAssignments";
10 import { useTeacherCourses } from "@hooks/useCourses";
11 import { Button } from "@components/ui/button";
12 import { Input } from "@components/ui/input";
13 import {
14   Select,
15   SelectContent,
16   SelectItem,
17   SelectTrigger,
18   SelectValue,
19 } from "@components/ui/select";
20 import { Plus, Search } from "lucide-react";
21 import { NoCourses } from "@components/shared/EmptyState";
22
23 const AssignmentListPage = () => {
24   const navigate = useNavigate();
25   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
26   const [courseFilter, setCourseFilter] = useQueryState(
27     "course",
28     parseAsString.withDefault("")
29   );
30   const [assignmentToDelete, setAssignmentToDelete] =
31     useState<AssignmentWithRelations | null>(null);
32   const [page, setPage] = useState(1);
33
34   const { data: paginatedCourses, isLoading: coursesLoading } =
35     useTeacherCourses();
36   const courses = paginatedCourses?.data;
37   const {
38     data: paginatedAssignments,
39     isLoading,
40     isFetching,
41   } = useAssignments(courseFilter || undefined, { page });
42   const deleteMutation = useDeleteAssignment();
43
44   const filteredAssignments = (paginatedAssignments?.data ?? []).filter((a) => {
45     if (!search) return true;
46     const q = search.toLowerCase();
47     return (
48       a.title.toLowerCase().includes(q) ||
49       (a.description?.toLowerCase().includes(q) ?? false)
50     );
51   });
52
53   const columns = createColumns(
54     (id) => navigate(`/teacher/assignments/${id}/edit`),
55     (assignment) => setAssignmentToDelete(assignment)
56   );
57

```

```

58 | return (
59 |   <div className="space-y-6">
60 |     {/* Page Header */}
61 |     <div className="flex items-center justify-between">
62 |       <h1 className="text-2xl font-bold tracking-tight">Assignments</h1>
63 |       <Button
64 |         variant="tactile"
65 |         onClick={() => navigate("/teacher/assignments/new")}
66 |       >
67 |         <Plus className="h-4 w-4" /> Add Assignment
68 |     </div>
69 |   </div>
70 |
71 |   {/* Filters */}
72 |   <div className="flex items-center gap-4">
73 |     <div className="relative flex-1 max-w-sm">
74 |       <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
75 |       <Input
76 |         placeholder="Search assignments..."
77 |         value={search}
78 |         onChange={(e) => setSearch(e.target.value)}
79 |         className="ps-9"
80 |       />
81 |     </div>
82 |     <Select
83 |       value={courseFilter}
84 |       onValueChange={(val) => {
85 |         setCourseFilter(val === "all" ? "" : val);
86 |         setPage(1);
87 |       }}
88 |       disabled={coursesLoading}
89 |     >
90 |       <SelectTrigger className="w-[260px] bg-white">
91 |         <SelectValue placeholder="Filter by course" />
92 |       </SelectTrigger>
93 |       <SelectContent>
94 |         <SelectItem value="all">All Courses</SelectItem>
95 |         {(courses ?? []).map((c) => (
96 |           <SelectItem key={c.id} value={c.id}>
97 |             {c.code} — {c.name}
98 |           </SelectItem>
99 |         ))}
100 |       </SelectContent>
101 |     </Select>
102 |   </div>
103 |
104 |   {/* Data Table */}
105 |   <DataTable
106 |     columns={columns}
107 |     data={filteredAssignments}
108 |     isLoading={isLoading}
109 |     isFetching={isFetching}
110 |     page={page}
111 |     pageSize={paginatedAssignments?.pageSize}
112 |     totalCount={paginatedAssignments?.count}
113 |     onPageChange={setPage}
114 |     emptyState={
115 |       filteredAssignments.length === 0 && !isLoading ? (
116 |         <NoCourses />
117 |       ) : undefined
118 |     }
119 |   />
120 |
121 |   {/* Delete Confirmation Dialog */}
122 |   <ConfirmDialog
123 |     open={!assignmentToDelete}
124 |     onOpenChange={() => setAssignmentToDelete(null)}
125 |     title="Delete Assignment"
126 |     description={`Are you sure you want to delete "${assignmentToDelete?.title}"? This action cannot be un`}
127 |     variant="destructive"
128 |     confirmLabel="Delete"
129 |     isPending={deleteMutation.isPending}
130 |     onConfirm={() => {
131 |       if (!assignmentToDelete) return;
132 |       deleteMutation.mutate(assignmentToDelete.id, {
133 |         onSuccess: () => {
134 |           toast.success(`${assignmentToDelete.title} has been deleted`);
135 |           setAssignmentToDelete(null);
136 |         },
137 |         onError: (err) => {
138 |           toast.error(err.message);
139 |           setAssignmentToDelete(null);
140 |         },
141 |       });
142 |     }}
143 |   />
144 | </div>
145 | );
146 | };
147 |
148 | export default AssignmentListPage;
149 |

```

FILE: [src/pages/teacher/assignments/columns.tsx](#)

TYPE: .tsx | LINES: 1-168 | SHA256: 6b94ebe1faa85b226d0d28969e0b23e923f4049013099fdd0dc56f1bfd232fae

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import { isPast, differenceInHours } from "date-fns";
4 | import { ArrowUpDown, MoreHorizontal, Pencil, Trash2 } from "lucide-react";
5 | import { Badge } from "@components/ui/badge";
6 | import { Button } from "@components/ui/button";
7 | import {
8 |   DropdownMenu,

```

```

9 | DropdownMenuContent,
10 | DropdownMenuItem,
11 | DropdownMenuTrigger,
12 | } from "@components/ui/dropdown-menu";
13 | import { resolveName } from "@lib/db/resolveName";
14 | import type { AssignmentWithRelations } from "@hooks/useAssignments";
15 |
16 | const getStatusBadge = (dueDate: string) => {
17 |   const due = new Date(dueDate);
18 |   const now = new Date();
19 |
20 |   if (isPast(due)) {
21 |     return (
22 |       <Badge
23 |         className="bg-red-100 text-red-700 border-red-200"
24 |         variant="outline"
25 |       >
26 |         Past Due
27 |       </Badge>
28 |     );
29 |   }
30 |
31 |   if (differenceInHours(due, now) <= 48) {
32 |     return (
33 |       <Badge
34 |         className="bg-yellow-100 text-yellow-700 border-yellow-200"
35 |         variant="outline"
36 |       >
37 |         Due Soon
38 |       </Badge>
39 |     );
40 |   }
41 |
42 |   return (
43 |     <Badge
44 |       className="bg-green-100 text-green-700 border-green-200"
45 |       variant="outline"
46 |     >
47 |       Open
48 |     </Badge>
49 |   );
50 | };
51 |
52 | export const createColumns = (
53 |   onEdit: (id: string) => void,
54 |   onDelete: (assignment: AssignmentWithRelations) => void
55 | ): ColumnDef<AssignmentWithRelations>[] => [
56 |   {
57 |     accessorKey: "title",
58 |     header: ({ column }) => (
59 |       <Button
60 |         variant="ghost"
61 |         size="sm"
62 |         className="-ms-3"
63 |         onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
64 |       >
65 |         Title
66 |       <ArrowUpDown className="h-4 w-4" />
67 |     </Button>
68 |   ),
69 |   cell: ({ row }) => (
70 |     <span className="font-medium">{row.getValue("title")}</span>
71 |   ),
72 | },
73 | {
74 |   id: "course",
75 |   header: "Course",
76 |   cell: ({ row }) => (
77 |     <span className="text-gray-500 text-sm truncate max-w-[160px] inline-block">
78 |       {resolveName(row.original.courses?.name)}
79 |     </span>
80 |   ),
81 | },
82 | {
83 |   accessorKey: "due_date",
84 |   header: ({ column }) => (
85 |     <Button
86 |       variant="ghost"
87 |       size="sm"
88 |       className="-ms-3"
89 |       onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
90 |     >
91 |       Due Date
92 |     <ArrowUpDown className="h-4 w-4" />
93 |   </Button>
94 |   ),
95 |   cell: ({ row }) => {
96 |     const dueDate = row.getValue("due_date") as string;
97 |     return (
98 |       <span className="text-sm">
99 |         {format(new Date(dueDate), "MMM d, yyyy")}
100 |      </span>
101 |    );
102 |   },
103 | },
104 | {
105 |   accessorKey: "total_marks",
106 |   header: "Total Marks",
107 |   cell: ({ row }) => (
108 |     <span className="text-sm">{row.getValue("total_marks")}</span>
109 |   ),
110 | },
111 | {
112 |   id: "rubric",

```

```

113 |     header: "Rubric",
114 |     cell: ({ row }) => (
115 |       <span className="text-sm text-gray-600">
116 |         {row.original.rubrics?.title ?? "-"}
117 |       </span>
118 |     ),
119 |   },
120 | {
121 |   id: "clos",
122 |   header: "CLOs",
123 |   cell: ({ row }) => {
124 |     const count = row.original.clo_weights?.length ?? 0;
125 |     return (
126 |       <Badge
127 |         className="bg-blue-100 text-blue-700 border-blue-200"
128 |         variant="outline"
129 |       >
130 |         {count} CLO{count !== 1 ? "s" : ""}
131 |       </Badge>
132 |     );
133 |   },
134 | },
135 | {
136 |   id: "status",
137 |   header: "Status",
138 |   cell: ({ row }) => getStatusBadge(row.original.due_date),
139 | },
140 | {
141 |   id: "actions",
142 |   header: "",
143 |   cell: ({ row }) => (
144 |     <DropdownMenu>
145 |       <DropdownMenuTrigger asChild>
146 |         <Button variant="ghost" size="icon-xs">
147 |           <MoreHorizontal className="h-4 w-4" />
148 |           <span className="sr-only">Open menu</span>
149 |         </Button>
150 |       </DropdownMenuTrigger>
151 |       <DropdownMenuContent align="end">
152 |         <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
153 |           <Pencil className="h-4 w-4" />
154 |           Edit
155 |         </DropdownMenuItem>
156 |         <DropdownMenuItem
157 |           variant="destructive"
158 |           onClick={() => onDelete(row.original)}
159 |         >
160 |           <Trash2 className="h-4 w-4" />
161 |           Delete
162 |         </DropdownMenuItem>
163 |       </DropdownMenuContent>
164 |     </DropdownMenu>
165 |   ),
166 | },
167 | ];
168 |

```

FILE: [src/pages/teacher/attendance/AttendanceMarker.tsx](#)

TYPE: .tsx | LINES: 1-517 | SHA256: 6d7d11399da0798ce0455cb9d3aef6d2f0d4aa0dcf47a37715f1374404a89e2e

```

1 | // =====
2 | // AttendanceMarker – Teacher page for creating sessions & marking attendance
3 | // Requirements: 78.1, 78.2
4 | // =====
5 |
6 | import { useState, useMemo, useCallback } from "react";
7 | import { useForm } from "react-hook-form";
8 | import { zodResolver } from "@hookform/resolvers/zod";
9 | import { parseAsString, useQueryState } from "nuqs";
10 | import { format } from "date-fns";
11 | import { toast } from "sonner";
12 | import { Plus, CalendarCheck, Loader2, Users } from "lucide-react";
13 |
14 | import { Card } from "@components/ui/card";
15 | import { Button } from "@components/ui/button";
16 | import { Input } from "@components/ui/input";
17 | import {
18 |   Select,
19 |   SelectContent,
20 |   SelectItem,
21 |   SelectTrigger,
22 |   SelectValue,
23 | } from "@components/ui/select";
24 | import {
25 |   Form,
26 |   FormField,
27 |   FormItem,
28 |   FormLabel,
29 |   FormControl,
30 |   FormMessage,
31 | } from "@components/ui/form";
32 |
33 | import AttendanceGrid from "@components/shared/AttendanceGrid";
34 | import type {
35 |   StudentAttendance,
36 |   AttendanceStatus,
37 | } from "@components/shared/AttendanceGrid";
38 | import { Shimmer } from "@design-system";
39 | import { InlineNoSessions } from "@components/shared/EmptyState";
40 |
41 | import { useAuth } from "@hooks/useAuth";
42 | import { useTeacherCourses } from "@hooks/useCourses";
43 | import { useCourseSections } from "@hooks/useCourseSections";
44 | import {

```

```
46   useClassSessions,  
47   useCreateClassSession,  
48   useAttendanceRecords,  
49   useMarkAttendance,  
50 } from "@hooks/useAttendance";  
51 import {  
52   createSessionSchema,  
53   type CreateSessionFormData,  
54 } from "@lib/schemas/attendance";  
55 import { supabase } from "@lib/supabase";  
56 import { useQuery } from "tanstack/react-query";  
57 import { queryKeys } from "@lib/queryKeys";  
58  
59 // % % % Enrolled students for a course % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
60 const useEnrolledStudents = (courseId: string | undefined) => {  
61   return useQuery({  
62     queryKey: queryKeys.enrollments.list({ courseId, scope: "attendance" }),  
63     queryFn: async () => {  
64       if (!courseId) return [];  
65       const { data, error } = await supabase  
66         .from("student_courses")  
67         .select("student_id, profiles:student_id(full_name)")  
68         .eq("course_id", courseId)  
69         .eq("status", "active");  
70       if (error) throw error;  
71       return (data ?? []).map((e) => ({  
72         studentId: e.student_id as string,  
73         studentName:  
74           (e.profiles as unknown as { full_name: string }) | null)?.full_name ??  
75           "Unknown",  
76       }));  
77     },  
78     enabled: !!courseId,  
79   });  
80 };  
81  
82 // % % % Component % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
83  
84 const AttendanceMarker = () => {  
85   const { user } = useAuth();  
86   const teacherId = user?.id ?? "";  
87  
88   // URL-persisted filters  
89   const [courseId, setCourseId] = useQueryState(  
90     "course",  
91     parseAsString.withDefault("")  
92   );  
93   const [sectionId, setSectionId] = useQueryState(  
94     "section",  
95     parseAsString.withDefault("")  
96   );  
97   const [selectedSessionId, setSelectedSessionId] = useState<string>("");  
98  
99   // Data hooks  
100  const { data: coursesResult, isLoading: coursesLoading } =  
101    useTeacherCourses();  
102  const teacherCourses = useMemo(  
103    () => (coursesResult?.data ?? []).filter((c) => c.teacher_id === teacherId),  
104    [coursesResult, teacherId]  
105  );  
106  const { data: sections } = useCourseSections(courseId || undefined);  
107  const { data: sessions, isLoading: sessionsLoading } = useClassSessions(  
108    sectionId || undefined  
109  );  
110  const { data: existingRecords } = useAttendanceRecords(  
111    selectedSessionId || undefined  
112  );  
113  const { data: enrolledStudents } = useEnrolledStudents(courseId || undefined);  
114  
115  // Mutations  
116  const createSession = useCreateClassSession();  
117  const markAttendance = useMarkAttendance();  
118  
119  // Session creation form  
120  const form = useForm<CreateSessionFormData>({  
121    resolver: zodResolver(createSessionSchema),  
122    defaultValues: {  
123      section_id: sectionId || "",  
124      session_date: new Date().toISOString().slice(0, 10),  
125      session_type: "lecture",  
126      topic: "",  
127    },  
128  });  
129  
130  // Local attendance overrides (user edits on top of server data)  
131  const [localOverrides, setLocalOverrides] = useState<  
132    Record<string, AttendanceStatus>  
133  >({});  
134  const [overrideSessionId, setOverrideSessionId] = useState<string>("");  
135  
136  // Build grid data: merge server records with local overrides  
137  const gridStudents: StudentAttendance[] = useMemo(() => {  
138    if (!enrolledStudents) return [];  
139  
140    // Build base map from existing records  
141    const baseMap: Record<string, AttendanceStatus> = {};  
142    if (existingRecords && selectedSessionId) {  
143      for (const r of existingRecords) {  
144        baseMap[r.student_id] = r.status;  
145      }  
146    }  
147  
148    // Apply local overrides only if they belong to the current session
```

```

149 |     const overrides =
150 |       overrideSessionId === selectedSessionId ? localOverrides : {};
151 |
152 |     return enrolledStudents.map((s) => ({
153 |       studentId: s.studentId,
154 |       studentName: s.studentName,
155 |       status: overrides[s.studentId] ?? baseMap[s.studentId] ?? "present",
156 |     }));
157 |   }, [
158 |     enrolledStudents,
159 |     existingRecords,
160 |     selectedSessionId,
161 |     localOverrides,
162 |     overrideSessionId,
163 |   ]);
164 |
165 |   // When a session is selected, clear local overrides
166 |   const handleSessionSelect = useCallback((sessionId: string) => {
167 |     setSelectedSessionId(sessionId);
168 |     setLocalOverrides({});
169 |     setOverrideSessionId(sessionId);
170 |   }, []);
171 |
172 |   const handleStatusChange = (studentId: string, status: AttendanceStatus) => {
173 |     setLocalOverrides((prev) => ({ ...prev, [studentId]: status }));
174 |     setOverrideSessionId(selectedSessionId);
175 |   };
176 |
177 |   const handleCreateSession = (data: CreateSessionFormData) => {
178 |     createSession.mutate(
179 |       { ...data, section_id: sectionId || data.section_id },
180 |       {
181 |         onSuccess: (session) => {
182 |           toast.success("Class session created");
183 |           form.reset();
184 |           setSelectedSessionId(session.id);
185 |         },
186 |         onError: (err) => toast.error(err.message),
187 |       }
188 |     );
189 |   };
190 |
191 |   const handleSaveAttendance = () => {
192 |     if (!selectedSessionId || !gridStudents.length) return;
193 |     const records = gridStudents.map((s) => ({
194 |       student_id: s.studentId,
195 |       status: s.status,
196 |     }));
197 |     markAttendance.mutate(
198 |       { session_id: selectedSessionId, records },
199 |       {
200 |         onSuccess: () => {
201 |           toast.success("Attendance saved");
202 |           setLocalOverrides({});
203 |         },
204 |         onError: (err) => toast.error(err.message),
205 |       }
206 |     );
207 |   };
208 |
209 |   const handleBulkMark = (status: AttendanceStatus) => {
210 |     if (!enrolledStudents) return;
211 |     const map: Record<string, AttendanceStatus> = {};
212 |     for (const s of enrolledStudents) {
213 |       map[s.studentId] = status;
214 |     }
215 |     setLocalOverrides(map);
216 |     setOverrideSessionId(selectedSessionId);
217 |   };
218 |
219 |   return (
220 |     <div className="space-y-6 no-scrollbar">
221 |       <div>
222 |         <div className="rounded-[20px] border border-[#eef2f6] bg-white p-5 shadow-[0_1px_2px_rgba(16,24,40,0.04)]">
223 |           <div className="flex items-center gap-3">
224 |             <div className="flex h-10 w-10 shrink-0 items-center justify-center rounded-xl bg-white/80 border border-gray-100">
225 |               ⌕
226 |             </div>
227 |             <div>
228 |               <h1 className="text-xl font-black tracking-tight text-slate-900 dark:text-slate-100">
229 |                 Attendance Marker
230 |               </h1>
231 |               <p className="text-xs text-slate-500 font-medium">
232 |                 Create class sessions and record student attendance.
233 |               </p>
234 |             </div>
235 |           </div>
236 |         </div>
237 |
238 |         <div>
239 |           <div className="flex flex-wrap items-end gap-4">
240 |             <div className="w-64">
241 |               <span className="text-xs font-medium text-gray-500 mb-1 block">
242 |                 Course
243 |               </span>
244 |               {coursesLoading ? (
245 |                 <Shimmer className="h-10 rounded-lg" />
246 |               ) : (
247 |                 <Select
248 |                   value={courseId}
249 |                   onChange={(v) => {
250 |                     setCourseId(v);
251 |                     setSectionId("");
252 |                     setSelectedSessionId("");

```

```

253     }}
254   >
255   <SelectTrigger aria-label="Select course">
256     <SelectValue placeholder="Select course" />
257   </SelectTrigger>
258   <SelectContent>
259     {teacherCourses.map((c) => (
260       <SelectItem key={c.id} value={c.id}>
261         {c.name}
262       </SelectItem>
263     ))}
264   </SelectContent>
265 </Select>
266 }}
267 </div>
268
269 {courseId && (
270   <div className="w-48">
271     <span className="text-xs font-medium text-gray-500 mb-1 block">
272       Section
273     </span>
274     <Select
275       value={sectionId}
276       onValueChange={(v) => {
277         setSectionId(v);
278         setSelectedSessionId("");
279       }}
280     >
281       <SelectTrigger aria-label="Select section">
282         <SelectValue placeholder="Select section" />
283       </SelectTrigger>
284       <SelectContent>
285         {(sections ?? []).map((s) => (
286           <SelectItem key={s.id} value={s.id}>
287             Section {s.section_code}
288           </SelectItem>
289         ))}
290       </SelectContent>
291     </Select>
292   </div>
293   </div>
294
295 {sectionId && (
296   <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
297     {/* Left: Create Session + Session List */}
298     <div className="space-y-4">
299       {/* Create Session Form */}
300       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
301         <div
302           className="px-6 py-4 flex items-center gap-2"
303           style={{
304             background: "var(--brand-gradient)",
305           }}
306         >
307           <Plus className="h-5 w-5 text-white" />
308           <h2 className="text-lg font-bold tracking-tight text-white">
309             New Session
310           </h2>
311         </div>
312       </div>
313       <div className="p-6">
314         <Form {...form}>
315           <form
316             onSubmit={form.handleSubmit(handleCreateSession)}
317             className="space-y-4"
318           >
319             <FormField
320               control={form.control}
321               name="session_date"
322               render={({ field }) => (
323                 <FormItem>
324                   <FormLabel>Date</FormLabel>
325                   <FormControl>
326                     <Input type="date" {...field} />
327                   </FormControl>
328                   <FormMessage />
329                 </FormItem>
330               )}
331             />
332             <FormField
333               control={form.control}
334               name="session_type"
335               render={({ field }) => (
336                 <FormItem>
337                   <FormLabel>Type</FormLabel>
338                   <Select
339                     value={field.value}
340                     onChange={field.onChange}
341                   >
342                     <FormControl>
343                       <SelectTrigger>
344                         <SelectValue />
345                       </SelectTrigger>
346                     </FormControl>
347                     <SelectContent>
348                       <SelectItem value="lecture">Lecture</SelectItem>
349                       <SelectItem value="lab">Lab</SelectItem>
350                       <SelectItem value="tutorial">Tutorial</SelectItem>
351                     </SelectContent>
352                   </Select>
353                   <FormMessage />
354                 </FormItem>
355               )}
356             />

```

```

357 |         <FormField
358 |             control={form.control}
359 |             name="topic"
360 |             render={({ field }) => (
361 |                 <FormItem>
362 |                     <FormLabel>Topic</FormLabel>
363 |                     <FormControl>
364 |                         <Input placeholder="Session topic" {...field} />
365 |                     </FormControl>
366 |                     <FormMessage />
367 |                 </FormItem>
368 |             )}
369 |         />
370 |         <Button
371 |             type="submit"
372 |             disabled={createSession.isPending}
373 |             variant="tactile"
374 |             className="w-full"
375 |             >
376 |                 {createSession.isPending && (
377 |                     <Loader2 className="h-4 w-4 animate-spin me-1" />
378 |                 )}
379 |                 Create Session
380 |             </Button>
381 |         </form>
382 |     </Form>
383 | </div>
384 | </Card>
385 |
386 | {/* Session List */}
387 | <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
388 |     <div
389 |         className="px-6 py-4 flex items-center gap-2"
390 |         style={{
391 |             background: "var(--brand-gradient)",
392 |         }}
393 |     >
394 |         <CalendarCheck className="h-5 w-5 text-white" />
395 |         <h2 className="text-lg font-bold tracking-tight text-white">
396 |             Sessions
397 |         </h2>
398 |     </div>
399 |     <div className="p-4 max-h-96 overflow-y-auto">
400 |         {sessionsLoading ? (
401 |             <div className="space-y-2">
402 |                 {Array.from({ length: 3 }).map((_, i) => (
403 |                     <Shimmer key={i} className="h-12 rounded-lg" />
404 |                 ))}
405 |             </div>
406 |         ) : (sessions ?? []).length === 0 ? (
407 |             <InlineNoSessions />
408 |         ) : (
409 |             <div className="space-y-1">
410 |                 {(sessions ?? []).map((s) => (
411 |                     <button
412 |                         key={s.id}
413 |                         type="button"
414 |                         onClick={() => handleSessionSelect(s.id)}
415 |                         className={`w-full text-start px-3 py-2 rounded-lg text-sm transition-colors ${
416 |                             selectedSessionId === s.id
417 |                                 ? "bg-blue-50 text-blue-700 font-semibold"
418 |                                 : "hover:bg-slate-50 text-gray-700"
419 |                         }`}
420 |                     >
421 |                         <span className="font-medium">
422 |                             {format(new Date(s.session_date), "MMM d, yyyy")}
423 |                         </span>
424 |                         <span className="text-xs text-gray-500 ms-2 capitalize">
425 |                             {s.session_type}
426 |                         </span>
427 |                         <p className="text-xs text-gray-400 truncate">
428 |                             {s.topic}
429 |                         </p>
430 |                     </button>
431 |                 ))}
432 |             </div>
433 |         )}
434 |     </div>
435 | </Card>
436 | </div>
437 |
438 | {/* Right: Attendance Grid */}
439 | <div className="lg:col-span-2">
440 |     {selectedSessionId ? (
441 |         <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
442 |             <div
443 |                 className="px-6 py-4 flex items-center justify-between"
444 |                 style={{
445 |                     background: "var(--brand-gradient)",
446 |                 }}
447 |             >
448 |                 <div className="flex items-center gap-2">
449 |                     <Users className="h-5 w-5 text-white" />
450 |                     <h2 className="text-lg font-bold tracking-tight text-white">
451 |                         Mark Attendance
452 |                     </h2>
453 |                 </div>
454 |                 <span className="text-xs text-white/70">
455 |                     {gridStudents.length} students
456 |                 </span>
457 |             </div>
458 |             <div className="p-6 space-y-4">
459 |                 {/* Bulk actions */}
460 |                 <div className="flex gap-2">

```



```

461 |         <Button
462 |           size="sm"
463 |           variant="outline"
464 |           onClick={() => handleBulkMark("present")}
465 |           className="text-xs text-green-700 border-green-300"
466 |         >
467 |           All Present
468 |         </Button>
469 |         <Button
470 |           size="sm"
471 |           variant="outline"
472 |           onClick={() => handleBulkMark("absent")}
473 |           className="text-xs text-red-700 border-red-300"
474 |         >
475 |           All Absent
476 |         </Button>
477 |       </div>
478 |
479 |       { /* Grid */ }
480 |       <AttendanceGrid
481 |         students={gridStudents}
482 |         onStatusChange={handleStatusChange}
483 |       />
484 |
485 |       { /* Save */ }
486 |       <Button
487 |         onClick={handleSaveAttendance}
488 |         disabled={
489 |           markAttendance.isPending || gridStudents.length === 0
490 |         }
491 |         variant="tactile"
492 |         className="w-full"
493 |       >
494 |         {markAttendance.isPending && (
495 |           <Loader2 className="h-4 w-4 animate-spin me-1" />
496 |         )}
497 |         Save Attendance
498 |       </Button>
499 |     </div>
500 |   </Card>
501 | ) : (
502 |   <Card className="bg-white border-0 shadow-md rounded-xl p-12 flex flex-col items-center justify-
503 |     <CalendarCheck className="h-12 w-12 text-gray-300 mb-3" />
504 |     <p className="text-sm text-gray-500">
505 |       Select or create a session to mark attendance
506 |     </p>
507 |   </Card>
508 | )}
509 | </div>
510 | </div>
511 | )}
512 | </div>
513 | );
514 | };
515 |
516 | export default AttendanceMarker;
517 |

```

FILE: src/pages/teacher/attendance/AttendanceReport.tsx

TYPE: .tsx | LINES: 1-261 | SHA256: 4935fccf401b9bb9a14573848a48f72e40642a28a4286825caf232b4d32531c5

```

1 | // =====
2 | // AttendanceReport - Per-student attendance percentage per course
3 | // Requirements: 78.3, 78.4
4 | // =====
5 |
6 | import { useMemo } from "react";
7 | import { parseAsString, useQueryState } from "nuqs";
8 | import { AlertTriangle, BarChart3, CheckCircle2 } from "lucide-react";
9 |
10 | import { Card } from "@/components/ui/card";
11 | import { Badge } from "@/components/ui/badge";
12 | import {
13 |   Select,
14 |   SelectContent,
15 |   SelectItem,
16 |   SelectTrigger,
17 |   SelectValue,
18 | } from "@/components/ui/select";
19 | import {
20 |   Table,
21 |   TableBody,
22 |   TableCell,
23 |   TableHead,
24 |   TableHeader,
25 |   TableRow,
26 | } from "@/components/ui/table";
27 | import { Shimmer } from "@/design-system";
28 | import { NoAttendance } from "@/components/shared/EmptyState";
29 |
30 | import { useAuth } from "@/hooks/useAuth";
31 | import { useTeacherCourses } from "@/hooks/useCourses";
32 | import { useCourseSections } from "@/hooks/useCourseSections";
33 | import { useAttendanceSummary } from "@/hooks/useAttendance";
34 |
35 | const AttendanceReport = () => {
36 |   const { user } = useAuth();
37 |   const teacherId = user?.id ?? "";
38 |
39 |   const [courseId, setCourseId] = useQueryState(
40 |     "course",
41 |     parseAsString.withDefault("")
42 |   );
43 |   const [sectionId, setSectionId] = useQueryState(

```

```

44 |     "section",
45 |     parseAsString.withDefault("")
46 | );
47 |
48 | const { data: coursesResult, isLoading: coursesLoading } =
49 |   useTeacherCourses();
50 | const teacherCourses = useMemo(
51 |   () => (coursesResult?.data ?? []).filter((c) => c.teacher_id === teacherId),
52 |   [coursesResult, teacherId]
53 | );
54 | const { data: sections } = useCourseSections(courseId || undefined);
55 | const { data: summary, isLoading: summaryLoading } = useAttendanceSummary(
56 |   courseId || undefined,
57 |   sectionId || undefined
58 | );
59 |
60 | const belowThreshold = useMemo(
61 |   () => (summary ?? []).filter((s) => s.isBelowThreshold),
62 |   [summary]
63 | );
64 |
65 | const avgAttendance = useMemo(() => {
66 |   if (!summary || summary.length === 0) return 0;
67 |   return Math.round(
68 |     summary.reduce((s, r) => s + r.attendancePercent, 0) / summary.length
69 |   );
70 | }, [summary]);
71 |
72 | return (
73 |   <div className="space-y-6">
74 |     <h1 className="text-2xl font-bold tracking-tight">Attendance Report</h1>
75 |
76 |     { /* Filters */ }
77 |     <div className="flex flex-wrap items-end gap-4">
78 |       <div className="w-64">
79 |         <span className="text-xs font-medium text-gray-500 mb-1 block">
80 |           Course
81 |         </span>
82 |         {coursesLoading ? (
83 |           <Shimmer className="h-10 rounded-lg" />
84 |         ) : (
85 |           <Select
86 |             value={courseId}
87 |             onChange={(v) => {
88 |               setCourseId(v);
89 |               setSectionId("");
90 |             }}
91 |           >
92 |             <SelectTrigger aria-label="Select course">
93 |               <SelectValue placeholder="Select course" />
94 |             </SelectTrigger>
95 |             <SelectContent>
96 |               {teacherCourses.map((c) => (
97 |                 <SelectItem key={c.id} value={c.id}>
98 |                   {c.name}
99 |                 </SelectItem>
100 |               ))}
101 |             </SelectContent>
102 |           </Select>
103 |         )}
104 |       </div>
105 |       {courseId && (
106 |         <div className="w-48">
107 |           <span className="text-xs font-medium text-gray-500 mb-1 block">
108 |             Section
109 |           </span>
110 |           <Select value={sectionId} onChange={setSectionId}>
111 |             <SelectTrigger aria-label="Select section">
112 |               <SelectValue placeholder="Select section" />
113 |             </SelectTrigger>
114 |             <SelectContent>
115 |               {(sections ?? []).map((s) => (
116 |                 <SelectItem key={s.id} value={s.id}>
117 |                   Section {s.section_code}
118 |                 </SelectItem>
119 |               ))}
120 |             </SelectContent>
121 |           </Select>
122 |         </div>
123 |       )}
124 |     </div>
125 |
126 |     {sectionId && (
127 |       <div
128 |         { /* KPI Row */ }
129 |         className="grid grid-cols-2 md:grid-cols-3 gap-4">
130 |         <Card className="bg-white border-0 shadow-md rounded-xl p-4">
131 |           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
132 |             Avg Attendance
133 |           </p>
134 |           <p className="text-2xl font-black mt-1">{avgAttendance}%</p>
135 |         </Card>
136 |         <Card className="bg-white border-0 shadow-md rounded-xl p-4">
137 |           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
138 |             Total Students
139 |           </p>
140 |           <p className="text-2xl font-black mt-1">{summary?.length ?? 0}</p>
141 |         </Card>
142 |         <Card className="bg-white border-0 shadow-md rounded-xl p-4">
143 |           <div className="flex items-center gap-1">
144 |             <AlertTriangle className="h-3 w-3 text-red-500" />
145 |             <p className="text-[10px] font-black tracking-widest uppercase text-red-600">
146 |               Below 75%
147 |             </p>

```

```

148     </div>
149     <p className="text-2xl font-black mt-1 text-red-600">
150       {belowThreshold.length}
151     </p>
152   </Card>
153 </div>
154
155   {/* Flagged Students */}
156   {belowThreshold.length > 0 && (
157     <Card className="bg-red-50 border border-red-200 rounded-xl p-4">
158       <div className="flex items-center gap-2 mb-2">
159         <AlertTriangle className="h-4 w-4 text-red-600" />
160         <span className="text-sm font-bold text-red-700">
161           Students Below 75% Threshold
162         </span>
163       </div>
164       <div className="flex flex-wrap gap-2">
165         {belowThreshold.map((s) => (
166           <Badge
167             key={s.studentId}
168             variant="destructive"
169             className="text-xs"
170           >
171             {s.studentName} - {s.attendancePercent}%
172           </Badge>
173         ))}
174       </div>
175     </Card>
176   )}
177
178   {/* Full Report Table */}
179   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
180     <div
181       className="px-6 py-4 flex items-center gap-2"
182       style={{
183         background: "var(--brand-gradient)",
184       }}
185     >
186       <BarChart3 className="h-5 w-5 text-white" />
187       <h2 className="text-lg font-bold tracking-tight text-white">
188         Student Attendance
189       </h2>
190     </div>
191     <div className="p-4">
192       {summaryLoading ? (
193         <div className="space-y-2">
194           {Array.from({ length: 5 }).map((_, i) => (
195             <Shimmer key={i} className="h-10 rounded-lg" />
196           ))}
197         </div>
198       ) : (summary ?? []).length === 0 ? (
199         <NoAttendance />
200       ) : (
201         <Table>
202           <TableHeader>
203             <TableRow>
204               <TableHead>Student</TableHead>
205               <TableHead className="text-center">Present</TableHead>
206               <TableHead className="text-center">Late</TableHead>
207               <TableHead className="text-center">Absent</TableHead>
208               <TableHead className="text-center">Excused</TableHead>
209               <TableHead className="text-center">
210                 Attendance %
211               </TableHead>
212               <TableHead className="text-center">Status</TableHead>
213             </TableRow>
214           </TableHeader>
215           <TableBody>
216             {(summary ?? []).map((s) => (
217               <TableRow key={s.studentId}>
218                 <TableCell className="font-medium">
219                   {s.studentName}
220                 </TableCell>
221                 <TableCell className="text-center text-green-600">
222                   {s.presentCount}
223                 </TableCell>
224                 <TableCell className="text-center text-yellow-600">
225                   {s.lateCount}
226                 </TableCell>
227                 <TableCell className="text-center text-red-600">
228                   {s.absentCount}
229                 </TableCell>
230                 <TableCell className="text-center text-blue-600">
231                   {s.excusedCount}
232                 </TableCell>
233                 <TableCell className="text-center font-bold">
234                   {s.attendancePercent}%
235                 </TableCell>
236                 <TableCell className="text-center">
237                   {s.isBelowThreshold ? (
238                     <Badge variant="destructive" className="text-xs">
239                       <AlertTriangle className="h-3 w-3 me-1" /> At Risk
240                     </Badge>
241                   ) : (
242                     <Badge className="text-xs bg-green-50 text-green-700 border-green-200">
243                       <CheckCircle2 className="h-3 w-3 me-1" /> Good
244                     </Badge>
245                   )}
246                 </TableCell>
247               </TableRow>
248             ))}
249           </TableBody>
250         </Table>
251       )}

```

```

252 |         </div>
253 |     </Card>
254 | </>
255 | })
256 | </div>
257 | );
258 | };
259 |
260 | export default AttendanceReport;
261 |

```

FILE: [src/pages/teacher/baseline/BaselineConfigPage.tsx](#)

TYPE: .tsx | LINES: 1-136 | SHA256: ca6275c45cffce58845ddc9bcfa7eeddda3f04e41e9d10f39627d6aaf1deb943

```

1 | import { useParams } from "react-router-dom";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { z } from "zod";
5 | import { Card } from "@components/ui/card";
6 | import { Button } from "@components/ui/button";
7 | import { Input } from "@components/ui/input";
8 | import { Switch } from "@components/ui/switch";
9 | import {
10 |   Form,
11 |   FormField,
12 |   FormItem,
13 |   FormLabel,
14 |   FormControl,
15 |   FormMessage,
16 |   FormDescription,
17 | } from "@components/ui/form";
18 | import { Shimmer } from "@design-system";
19 | import {
20 |   useBaselineTestConfig,
21 |   useUpdateBaselineConfig,
22 | } from "@hooks/useBaselineTests";
23 | import { Settings, Loader2 } from "lucide-react";
24 | import { toast } from "sonner";
25 |
26 | const configSchema = z.object({
27 |   time_limit_minutes: z.number().int().min(5).max(60),
28 |   is_active: z.boolean(),
29 | });
30 |
31 | type ConfigFormData = z.infer<typeof configSchema>;
32 |
33 | const BaselineConfigPage = () => {
34 |   const { courseId } = useParams<{ courseId: string }>();
35 |   const { data: config, isLoading } = useBaselineTestConfig(courseId ?? "");
36 |   const updateConfig = useUpdateBaselineConfig();
37 |
38 |   const form = useForm<ConfigFormData>({
39 |     resolver: zodResolver(configSchema),
40 |     values: {
41 |       time_limit_minutes: config?.time_limit_minutes ?? 15,
42 |       is_active: config?.is_active ?? false,
43 |     },
44 |   });
45 |
46 |   const onSubmit = (data: ConfigFormData) => {
47 |     if (!courseId) return;
48 |     updateConfig.mutate(
49 |       { course_id: courseId, ...data },
50 |       {
51 |         onSuccess: () => toast.success("Baseline test configuration saved"),
52 |         onError: (err) => toast.error(err.message),
53 |       }
54 |     );
55 |   };
56 |
57 |   if (isLoading) {
58 |     return (
59 |       <div className="space-y-6">
60 |         <Shimmer className="h-8 w-64 rounded-lg" />
61 |         <Shimmer className="h-48 rounded-xl" />
62 |       </div>
63 |     );
64 |   }
65 |
66 |   return (
67 |     <div className="space-y-6">
68 |       <div className="flex items-center gap-2">
69 |         <Settings className="h-5 w-5 text-gray-600" />
70 |         <h1 className="text-2xl font-bold tracking-tight">
71 |           Baseline Test Configuration
72 |         </h1>
73 |       </div>
74 |
75 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
76 |         <Form {...form}>
77 |           <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
78 |             <FormField>
79 |               <control={form.control}>
80 |                 <name="time_limit_minutes">
81 |                   <render={({ field }) => (
82 |                     <FormItem>
83 |                       <FormLabel>Time Limit (minutes)</FormLabel>
84 |                       <FormControl>
85 |                         <Input type="number" min={5} max={60} {...field} />
86 |                       </FormControl>
87 |                       <FormDescription>
88 |                         Students will have this many minutes to complete the
89 |                         baseline test (5-60).
90 |                       </FormDescription>

```

```

91 |         <FormMessage />
92 |       </FormItem>
93 |     )}
94 |   />
95 |
96 |   <FormField
97 |     control={form.control}
98 |     name="is_active"
99 |     render={({ field }) => (
100 |       <FormItem className="flex items-center justify-between rounded-lg border p-4">
101 |         <div className="space-y-0.5">
102 |           <FormLabel className="text-base">Active</FormLabel>
103 |           <FormDescription>
104 |             When active, the baseline test appears in the student
105 |             onboarding flow.
106 |           </FormDescription>
107 |         </div>
108 |         <FormControl>
109 |           <Switch
110 |             checked={field.value}
111 |             onChange={field.onChange}
112 |           />
113 |         </FormControl>
114 |       </FormItem>
115 |     )}
116 |   />
117 |
118 |   <Button
119 |     type="submit"
120 |     disabled={updateConfig.isPending}
121 |     variant="tactile"
122 |   >
123 |     {updateConfig.isPending && (
124 |       <Loader2 className="h-4 w-4 animate-spin" />
125 |     )}
126 |     Save Configuration
127 |   </Button>
128 | </form>
129 | </Form>
130 | </Card>
131 | </div>
132 | );
133 | };
134 |
135 | export default BaselineConfigPage;
136 |

```

FILE: [src/pages/teacher/baseline/BaselineCoursesListPage.tsx](#)

TYPE: .tsx | LINES: 1-164 | SHA256: cbd5fe7090a1b6ae8b6d749be97e62627d9e508d5893afb17e2be46ee084af33

```

1 | import { useTranslation } from "react-i18next";
2 | import { Link } from "react-router-dom";
3 | import { useQuery } from "@tanstack/react-query";
4 | import { FlaskConical, ChevronRight, Settings } from "lucide-react";
5 |
6 | import { Card } from "@components/ui/card";
7 | import { Badge } from "@components/ui/badge";
8 | import { Shimmer } from "@design-system";
9 | import { NoCourses } from "@components/shared/EmptyState";
10 | import { useAuth } from "@hooks/useAuth";
11 | import { supabase } from "@lib/supabase";
12 | import { queryKeys } from "@lib/queryKeys";
13 |
14 | interface CourseWithBaseline {
15 |   id: string;
16 |   name: string;
17 |   code: string;
18 |   has_baseline_config: boolean;
19 |   attainment_count: number;
20 | }
21 |
22 | const useTeacherCoursesWithBaseline = (teacherId: string | undefined) => {
23 |   return useQuery({
24 |     queryKey: queryKeys.courses.list({ teacherId, view: "baseline" }),
25 |     queryFn: async (): Promise<CourseWithBaseline[]> => {
26 |       if (!teacherId) return [];
27 |
28 |       const { data: courses } = await supabase
29 |         .from("courses")
30 |         .select("id, name, code")
31 |         .eq("teacher_id", teacherId)
32 |         .eq("is_active", true);
33 |
34 |       if (!courses || courses.length === 0) return [];
35 |
36 |       const courseIds = courses.map((c) => c.id);
37 |
38 |       // Check which courses have baseline_test_config rows
39 |       const { data: configs } = await supabase
40 |         .from("baseline_test_config")
41 |         .select("course_id")
42 |         .in("course_id", courseIds);
43 |
44 |       const configSet = new Set(
45 |         (configs ?? []).map((c) => c.course_id as string)
46 |       );
47 |
48 |       // Count baseline attainment records per course (proxy for student attempts)
49 |       const { data: attainments } = await supabase
50 |         .from("baseline_attainment")
51 |         .select("course_id")
52 |         .in("course_id", courseIds);
53 |
54 |       const attainmentCount = new Map<string, number>();

```

```

55 |     for (const a of attainments ?? []) {
56 |       const cid = a.course_id as string | null;
57 |       if (!cid) continue;
58 |       attainmentCount.set(cid, (attainmentCount.get(cid) ?? 0) + 1);
59 |     }
60 |
61 |     return courses.map((c) => ({
62 |       id: c.id,
63 |       name: c.name,
64 |       code: c.code,
65 |       has_baseline_config: configSet.has(c.id),
66 |       attainment_count: attainmentCount.get(c.id) ?? 0,
67 |     }));
68 |   },
69 |   enabled: !!teacherId,
70 |   staleTime: 60_000,
71 | });
72 | };
73 |
74 | const BaselineCoursesListPage = () => {
75 |   const { t } = useTranslation("teacher");
76 |   const { user } = useAuth();
77 |   const { data: courses, isLoading } = useTeacherCoursesWithBaseline(user?.id);
78 |
79 |   return (
80 |     <div className="space-y-6">
81 |       <div>
82 |         <h1 className="text-2xl font-bold tracking-tight">
83 |           {t("baseline.title", "Baseline Tests")}
84 |         </h1>
85 |         <p className="text-sm text-gray-500 mt-1">
86 |           {t(
87 |             "baseline.subtitle",
88 |             "Configure baseline assessments and review student attempts for each of your courses."
89 |           )}
90 |         </p>
91 |       </div>
92 |
93 |       {isLoading ? (
94 |         <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
95 |           <Shimmer className="h-32 rounded-xl" />
96 |           <Shimmer className="h-32 rounded-xl" />
97 |         </div>
98 |       ) : !courses || courses.length === 0 ? (
99 |         <NoCourses />
100 |      ) : (
101 |        <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
102 |          {courses.map((course) => (
103 |            <Card
104 |              key={course.id}
105 |              className="bg-white border-0 shadow-md rounded-xl p-5 hover:shadow-lg transition-shadow"
106 |            >
107 |              <div className="flex items-start justify-between gap-3 mb-4">
108 |                <div className="flex-1 min-w-0">
109 |                  <div className="flex items-center gap-2 mb-1 flex-wrap">
110 |                    <Badge variant="outline" className="text-[10px] font-bold">
111 |                      {course.code}
112 |                    </Badge>
113 |                    {course.has_baseline_config ? (
114 |                      <Badge className="bg-green-100 text-green-700 hover:bg-green-100 text-[10px] font-bold">
115 |                        {t("baseline.configured", "Configured")}
116 |                      </Badge>
117 |                    ) : (
118 |                      <Badge className="bg-yellow-100 text-yellow-700 hover:bg-yellow-100 text-[10px] font-bol">
119 |                        {t("baseline.notConfigured", "Not configured")}
120 |                      </Badge>
121 |                    )}
122 |                  </div>
123 |                  <h2 className="text-base font-semibold tracking-tight text-gray-900 dark:text-foreground">
124 |                    {course.name}
125 |                  </h2>
126 |                </div>
127 |                <FlaskConical className="h-5 w-5 text-blue-500 flex-shrink-0" />
128 |              </div>
129 |
130 |              <div className="pt-3 border-t border-gray-100 mb-4">
131 |                <p className="text-[10px] font-bold tracking-widest uppercase text-gray-500">
132 |                  {t("baseline.studentResults", "Student results")}
133 |                </p>
134 |                <p className="text-lg font-black text-gray-900 dark:text-foreground">
135 |                  {course.attainment_count}
136 |                </p>
137 |              </div>
138 |
139 |              <div className="flex items-center gap-2">
140 |                <Link
141 |                  to={`/teacher/baseline/${course.id}/config`}
142 |                  className="flex-1 inline-flex items-center justify-center gap-1.5 rounded-lg border border-g
143 |                >
144 |                  <Settings className="h-3.5 w-3.5" />
145 |                  {t("baseline.configure", "Configure")}
146 |                </Link>
147 |                <Link
148 |                  to={`/teacher/baseline/${course.id}`}
149 |                  className="flex-1 inline-flex items-center justify-center gap-1.5 rounded-lg bg-[linear-grad
150 |                >
151 |                  {t("baseline.viewResults", "Results")}
152 |                  <ChevronRight className="h-3.5 w-3.5 rtl:rotate-180" />
153 |                </Link>
154 |              </div>
155 |            </Card>
156 |          )})}
157 |        </div>
158 |      )}

```

```

159 |     </div>
160 |   );
161 | };
162 |
163 | export default BaselineCoursesListPage;
164 |

```

FILE: src/pages/teacher/baseline/BaselineQuestionForm.tsx

TYPE: .tsx | LINES: 1-236 | SHA256: d114feead1f82276741ba371e38cacca6c4c6363b328162c10f7f617b33ef8c9

```

1 | import { useParams, useNavigate } from "react-router-dom";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { baselineQuestionSchema } from "@lib/onboardingSchemas";
5 | import type { z } from "zod";
6 | import { Card } from "@components/ui/card";
7 | import { Button } from "@components/ui/button";
8 | import { Input } from "@components/ui/input";
9 | import { Textarea } from "@components/ui/textarea";
10 | import {
11 |   Select,
12 |   SelectContent,
13 |   SelectItem,
14 |   SelectTrigger,
15 |   SelectValue,
16 | } from "@components/ui/select";
17 | import {
18 |   Form,
19 |   FormField,
20 |   FormItem,
21 |   FormLabel,
22 |   FormControl,
23 |   FormMessage,
24 | } from "@components/ui/form";
25 | import { useCLOs } from "@hooks/useCLOs";
26 | import { useAuth } from "@hooks/useAuth";
27 | import { supabase } from "@lib/supabase";
28 | import { useMutation, useQueryClient } from "@tanstack/react-query";
29 | import { queryKeys } from "@lib/queryKeys";
30 | import { Loader2, ArrowLeft } from "lucide-react";
31 | import { toast } from "sonner";
32 |
33 | type BaselineQuestionFormData = z.infer<typeof baselineQuestionSchema>;
34 |
35 | const BaselineQuestionForm = () => {
36 |   const { courseId } = useParams<{ courseId: string }>();
37 |   const navigate = useNavigate();
38 |   const { profile } = useAuth();
39 |   const queryClient = useQueryClient();
40 |   const { data: closResult } = useCLOs(courseId);
41 |   const clos = closResult?.data ?? [];
42 |
43 |   const form = useForm<BaselineQuestionFormData>({
44 |     resolver: zodResolver(baselineQuestionSchema),
45 |     defaultValues: {
46 |       question_text: "",
47 |       options: ["", "", "", ""],
48 |       correct_option: 0,
49 |       clo_id: "",
50 |       difficulty_level: "medium",
51 |     },
52 |   });
53 |
54 |   const createQuestion = useMutation({
55 |     mutationFn: async (data: BaselineQuestionFormData) => {
56 |       const institutionId = profile?.institution_id ?? "";
57 |       const { data: result, error } = await supabase
58 |         .from("onboarding_questions")
59 |         .insert({
60 |           institution_id: institutionId,
61 |           assessment_type: "baseline" as const,
62 |           question_text: data.question_text,
63 |           options: data.options.map((text) => ({ option_text: text })),
64 |           correct_option: data.correct_option,
65 |           clo_id: data.clo_id,
66 |           course_id: courseId ?? null,
67 |           difficulty_level: data.difficulty_level,
68 |           sort_order: 0,
69 |         })
70 |         .select()
71 |         .single();
72 |
73 |       if (error) throw error;
74 |       return result;
75 |     },
76 |     onSuccess: () => {
77 |       queryClient.invalidateQueries({
78 |         queryKey: queryKeys.onboarding.questions("baseline"),
79 |       });
80 |       toast.success("Baseline question created");
81 |       navigate(`/teacher/baseline/${courseId}`);
82 |     },
83 |     onError: (err) => toast.error(err.message),
84 |   });
85 |
86 |   const onSubmit = (data: BaselineQuestionFormData) => {
87 |     createQuestion.mutate(data);
88 |   };
89 |
90 |   return (
91 |     <div className="space-y-6">
92 |       <Button
93 |         variant="ghost"
94 |         onClick={() => navigate(`/teacher/baseline/${courseId}`)}

```

```

95 |         className="gap-1 text-gray-500"
96 |     >
97 |     <ArrowLeft className="h-4 w-4" />
98 |     Back to Baseline
99 | </Button>
100 |
101 | <h1 className="text-2xl font-bold tracking-tight">
102 |     Add Baseline Question
103 | </h1>
104 |
105 | <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
106 |     <Form {...form}>
107 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
108 |             <FormField
109 |                 control={form.control}
110 |                 name="question_text"
111 |                 render={({ field }) => (
112 |                     <FormItem>
113 |                         <FormLabel>Question Text</FormLabel>
114 |                         <FormControl>
115 |                             <Textarea placeholder="Enter the question..." {...field} />
116 |                         </FormControl>
117 |                         <FormMessage />
118 |                     </FormItem>
119 |                 )}
120 |             />
121 |
122 |             { /* 4 answer options */ }
123 |             {[0, 1, 2, 3].map((idx) => (
124 |                 <FormField
125 |                     key={idx}
126 |                     control={form.control}
127 |                     name={`options.${idx}`}
128 |                     render={({ field }) => (
129 |                         <FormItem>
130 |                             <FormLabel>Option {idx + 1}</FormLabel>
131 |                             <FormControl>
132 |                                 <Input
133 |                                     placeholder={`Answer option ${idx + 1}`}
134 |                                     {...field}
135 |                                 />
136 |                             </FormControl>
137 |                             <FormMessage />
138 |                         </FormItem>
139 |                     )}
140 |                 />
141 |             )]}
142 |
143 |             <FormField
144 |                 control={form.control}
145 |                 name="correct_option"
146 |                 render={({ field }) => (
147 |                     <FormItem>
148 |                         <FormLabel>Correct Answer</FormLabel>
149 |                         <Select
150 |                             onValueChange={(v) => field.onChange(Number(v))}
151 |                             value={String(field.value)}
152 |                         >
153 |                             <FormControl>
154 |                                 <SelectTrigger>
155 |                                     <SelectValue placeholder="Select correct option" />
156 |                                 </SelectTrigger>
157 |                             </FormControl>
158 |                             <SelectContent>
159 |                                 <SelectItem value="0">Option 1</SelectItem>
160 |                                 <SelectItem value="1">Option 2</SelectItem>
161 |                                 <SelectItem value="2">Option 3</SelectItem>
162 |                                 <SelectItem value="3">Option 4</SelectItem>
163 |                             </SelectContent>
164 |                         </Select>
165 |                         <FormMessage />
166 |                     </FormItem>
167 |                 )}
168 |             />
169 |
170 |             <FormField
171 |                 control={form.control}
172 |                 name="clo_id"
173 |                 render={({ field }) => (
174 |                     <FormItem>
175 |                         <FormLabel>CLO Mapping</FormLabel>
176 |                         <Select onValueChange={field.onChange} value={field.value}>
177 |                             <FormControl>
178 |                                 <SelectTrigger>
179 |                                     <SelectValue placeholder="Select CLO" />
180 |                                 </SelectTrigger>
181 |                             </FormControl>
182 |                             <SelectContent>
183 |                                 {clos.map((clo) => (
184 |                                     <SelectItem key={clo.id} value={clo.id}>
185 |                                         {clo.title}
186 |                                     </SelectItem>
187 |                                 )}
188 |                             </SelectContent>
189 |                         </Select>
190 |                         <FormMessage />
191 |                     </FormItem>
192 |                 )}
193 |             />
194 |
195 |             <FormField
196 |                 control={form.control}
197 |                 name="difficulty_level"
198 |                 render={({ field }) => (

```



```

199 |         <FormItem>
200 |             <FormLabel>Difficulty</FormLabel>
201 |             <Select onValueChange={field.onChange} value={field.value}>
202 |                 <FormControl>
203 |                     <SelectTrigger>
204 |                         <SelectValue placeholder="Select difficulty" />
205 |                     </SelectTrigger>
206 |                 </FormControl>
207 |                 <SelectContent>
208 |                     <SelectItem value="easy">Easy</SelectItem>
209 |                     <SelectItem value="medium">Medium</SelectItem>
210 |                     <SelectItem value="hard">Hard</SelectItem>
211 |                 </SelectContent>
212 |             </Select>
213 |             <FormMessage />
214 |         </FormItem>
215 |     )}
216 | </>
217 |
218 |     <Button
219 |         type="submit"
220 |         disabled={createQuestion.isPending}
221 |         variant="tactile"
222 |     >
223 |         {createQuestion.isPending && (
224 |             <Loader2 className="h-4 w-4 animate-spin" />
225 |         )}
226 |         Save Question
227 |     </Button>
228 | </form>
229 | </Form>
230 | </Card>
231 | </div>
232 | );
233 | };
234 |
235 | export default BaselineQuestionForm;
236 |

```

FILE: [src/pages/teacher/baseline/BaselineResultsPage.tsx](#)

TYPE: .tsx | LINES: 1-200 | SHA256: a128947fea3ea7c810828572444036e89209ef0e87ce94b29c8341b02a3ab62b

```

1 | import { useParams, useNavigate } from "react-router-dom";
2 | import { Card } from "@components/ui/card";
3 | import { Button } from "@components/ui/button";
4 | import { Badge } from "@components/ui/badge";
5 | import { Shimmer } from "@design-system";
6 | import {
7 |     useCourseBaselineStats,
8 |     useBaselineResults,
9 | } from "@hooks/useBaselineTests";
10 | import { useCLOs } from "@hooks/useCLOs";
11 | import {
12 |     BarChart,
13 |     Bar,
14 |     XAxis,
15 |     YAxis,
16 |     CartesianGrid,
17 |     Tooltip,
18 |     ResponsiveContainer,
19 |     Cell,
20 | } from "recharts";
21 | import { BarChart3, Users, Plus, Settings, ArrowLeft } from "lucide-react";
22 | import { NoResults } from "@components/shared/EmptyState";
23 |
24 | const COLORS = [
25 |     "#3b82f6",
26 |     "#14b8a6",
27 |     "#f59e0b",
28 |     "#ef4444",
29 |     "#8b5cf6",
30 |     "#ec4899",
31 | ];
32 |
33 | const BaselineResultsPage = () => {
34 |     const { courseId } = useParams<{ courseId: string }>();
35 |     const navigate = useNavigate();
36 |     const { data: stats, isLoading: statsLoading } = useCourseBaselineStats(
37 |         courseId ?? ""
38 |     );
39 |     const { data: results } = useBaselineResults(courseId ?? "");
40 |     const { data: closResult } = useCLOs(courseId);
41 |     const clos = closResult?.data ?? [];
42 |
43 |     // Build CLO name lookup
44 |     const cloNames = new Map(clos.map((c) => [c.id, c.title]));
45 |
46 |     // Total unique students who completed baseline
47 |     const uniqueStudents = new Set(results?.map((r) => r.student_id) ?? []).size;
48 |
49 |     // Chart data
50 |     const chartData = (stats ?? []).map((s, idx) => ({
51 |         name: cloNames.get(s.clo_id) ?? `CLO ${idx + 1}`,
52 |         avgScore: s.avg_score,
53 |         students: s.student_count,
54 |         colorIdx: idx % COLORS.length,
55 |     }));
56 |
57 |     return (
58 |         <div className="space-y-6">
59 |             <Button
60 |                 variant="ghost"
61 |                 onClick={() => navigate("/teacher/dashboard")}
62 |                 className="gap-1 text-gray-500"

```

```

63 | >
64 |   <ArrowLeft className="h-4 w-4" />
65 |   Back to Dashboard
66 | </Button>
67 |
68 | <div className="flex items-center justify-between">
69 |   <h1 className="text-2xl font-bold tracking-tight">Baseline Results</h1>
70 |   <div className="flex items-center gap-2">
71 |     <Button
72 |       variant="outline"
73 |       size="sm"
74 |       onClick={() => navigate(`/teacher/baseline/${courseId}/config`)}
75 |     >
76 |       <Settings className="h-4 w-4" />
77 |       Configure
78 |     </Button>
79 |     <Button
80 |       size="sm"
81 |       onClick={() =>
82 |         navigate(`/teacher/baseline/${courseId}/questions/new`)
83 |       }
84 |       variant="tactile"
85 |     >
86 |       <Plus className="h-4 w-4" />
87 |       Add Question
88 |     </Button>
89 |   </div>
90 | </div>
91 |
92 | {/* Completion KPI */}
93 | <Card className="bg-white border-0 shadow-md rounded-xl p-4">
94 |   <div className="flex items-center gap-3">
95 |     <div className="p-2 rounded-lg bg-blue-50">
96 |       <Users className="h-5 w-5 text-blue-600" />
97 |     </div>
98 |     <div>
99 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
100 |         Students Completed
101 |       </p>
102 |       <p className="text-2xl font-black">{uniqueStudents}</p>
103 |     </div>
104 |   </div>
105 | </Card>
106 |
107 | {/* Per-CLO Bar Chart */}
108 | <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
109 |   <div
110 |     className="px-6 py-4 flex items-center gap-2"
111 |     style={{
112 |       background: "var(--brand-gradient)",
113 |     }}
114 |   >
115 |     <BarChart3 className="h-5 w-5 text-white" />
116 |     <h2 className="text-lg font-bold tracking-tight text-white">
117 |       Average Scores by CLO
118 |     </h2>
119 |   </div>
120 |   <div className="p-6">
121 |     {statsLoading ? (
122 |       <Shimmer className="h-64 rounded-lg" />
123 |     ) : chartData.length > 0 ? (
124 |       <div className="h-72">
125 |         <ResponsiveContainer width="100%" height="100%">
126 |           <BarChart
127 |             data={chartData}
128 |             margin={{ top: 5, right: 20, left: 0, bottom: 40 }}
129 |           >
130 |             <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
131 |             <XAxis
132 |               dataKey="name"
133 |               tick={{ fontSize: 11, fill: "#64748b" }}
134 |               angle={-20}
135 |               textAnchor="end"
136 |               height={60}
137 |             />
138 |             <YAxis
139 |               domain={[0, 100]}
140 |               tick={{ fontSize: 11, fill: "#64748b" }}
141 |             />
142 |             <Tooltip
143 |               formatter={(value) => [`${value}%`, "Avg Score"]}
144 |               contentStyle={{
145 |                 borderRadius: 8,
146 |                 border: "none",
147 |                 boxShadow: "0 4px 12px rgba(0,0,0,0.1)",
148 |               }}
149 |             />
150 |             <Bar dataKey="avgScore" radius={[4, 4, 0, 0]}>
151 |               {chartData.map((entry, idx) => (
152 |                 <Cell
153 |                   key={idx}
154 |                   fill={COLORS[entry.colorIdx] ?? COLORS[0]}
155 |                 />
156 |               ))}
157 |             </Bar>
158 |           </BarChart>
159 |         </ResponsiveContainer>
160 |       </div>
161 |     ) : (
162 |       <NoResults />
163 |     )
164 |   </div>
165 | </Card>
166 |

```

```

167 |     {/* Per-CLO stats table */}
168 |     {chartData.length > 0 && (
169 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
170 |         <h3 className="text-sm font-bold text-gray-900 mb-3">
171 |           CLO Breakdown
172 |         </h3>
173 |         <div className="space-y-2">
174 |           {chartData.map((item) => (
175 |             <div
176 |               key={item.name}
177 |               className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
178 |             >
179 |               <span className="text-sm font-medium text-gray-700 truncate max-w-xs">
180 |                 {item.name}
181 |               </span>
182 |               <div className="flex items-center gap-3">
183 |                 <Badge variant="outline" className="text-xs">
184 |                   {item.students} student{item.students !== 1 ? "s" : ""}
185 |                 </Badge>
186 |                 <span className="text-sm font-bold text-gray-900">
187 |                   {item.avgScore}%
188 |                 </span>
189 |               </div>
190 |             </div>
191 |           ))}
192 |         </div>
193 |       </Card>
194 |     )}
195 |   </div>
196 | );
197 | };
198 |
199 | export default BaselineResultsPage;
200 |

```

FILE: [src/pages/teacher/challenges/ChallengeFormPage.tsx](#)

TYPE: .tsx | LINES: 1-480 | SHA256: a62ab2f23f0846efd40c3cd1fd8131e4084d45e1666d1957145d860b7bcac4f3

```

1 | // =====
2 | // ChallengeFormPage - Challenge creation/edit form
3 | // Task 6.4: cooperative default, type-specific goals, XP Race acknowledgment,
4 | //           date pickers, reward configuration
5 | // =====
6 |
7 | import { useEffect, useMemo } from "react";
8 | import { useNavigate, useParams } from "react-router-dom";
9 | import { useForm, useWatch } from "react-hook-form";
10 | import { zodResolver } from "@hookform/resolvers/zod";
11 | import { z } from "zod";
12 | import { useAuth } from "@hooks/useAuth";
13 | import { useTeacherCourses } from "@hooks/useCourses";
14 | import {
15 |   useCreateChallenge,
16 |   useUpdateChallenge,
17 |   useChallenges,
18 |   useActiveXpRaceCount,
19 | } from "@hooks/useChallenges";
20 | import { Card } from "@components/ui/card";
21 | import { Button } from "@components/ui/button";
22 | import { Input } from "@components/ui/input";
23 | import { Checkbox } from "@components/ui/checkbox";
24 | import {
25 |   Form,
26 |   FormField,
27 |   FormItem,
28 |   FormLabel,
29 |   FormControl,
30 |   FormMessage,
31 |   FormDescription,
32 | } from "@components/ui/form";
33 | import {
34 |   Select,
35 |   SelectContent,
36 |   SelectItem,
37 |   SelectTrigger,
38 |   SelectValue,
39 | } from "@components/ui/select";
40 | import { Loader2, ArrowLeft, AlertTriangle } from "lucide-react";
41 | import { toast } from "sonner";
42 |
43 | const challengeFormSchema = z.object({
44 |   title: z.string().min(3, "Title must be at least 3 characters").max(100),
45 |   description: z.string().max(500).default(""),
46 |   challenge_type: z.enum([
47 |     "academic",
48 |     "habit",
49 |     "xp_race",
50 |     "blooms_climb",
51 |     "cooperative",
52 |   ]),
53 |   participation_mode: z.enum(["team", "individual"]),
54 |   goal_target: z.number().int().positive("Goal must be positive"),
55 |   start_date: z.string().min(1, "Start date is required"),
56 |   end_date: z.string().min(1, "End date is required"),
57 |   reward_xp: z
58 |     .number()
59 |     .int()
60 |     .min(50, "Minimum 50 XP")
61 |     .max(500, "Maximum 500 XP"),
62 |   reward_badge_id: z.string().nullable().optional(),
63 |   course_id: z.string().uuid("Select a course"),
64 |   xp_race_acknowledged: z.boolean().optional(),
65 | });
66 |

```

```

67 | type ChallengeFormData = z.infer<typeof challengeFormSchema>;
68 |
69 | const ChallengeFormPage = () => {
70 |   const navigate = useNavigate();
71 |   const { id } = useParams<{ id: string }>();
72 |   const isEditMode = !!id;
73 |   const { user, institutionId } = useAuth();
74 |   const { data: paginatedCourses } = useTeacherCourses();
75 |
76 |   const teacherCourses = useMemo(
77 |     () =>
78 |     (paginatedCourses?.data ?? []).filter((c) => c.teacher_id === user?.id),
79 |     [paginatedCourses, user?.id]
80 |   );
81 |
82 |   const createMutation = useCreateChallenge();
83 |   const updateMutation = useUpdateChallenge();
84 |
85 |   const form = useForm<ChallengeFormData>({
86 |     resolver: zodResolver(challengeFormSchema) as never,
87 |     defaultValues: {
88 |       title: "",
89 |       description: "",
90 |       challenge_type: "cooperative", // cooperative as default per spec
91 |       participation_mode: "team",
92 |       goal_target: 100,
93 |       start_date: "",
94 |       end_date: "",
95 |       reward_xp: 100,
96 |       reward_badge_id: null,
97 |       course_id: "",
98 |       xp_race_acknowledged: false,
99 |     },
100 |   });
101 |
102 |   const challengeType = useWatch({
103 |     control: form.control,
104 |     name: "challenge_type",
105 |   });
106 |   const courseId = useWatch({ control: form.control, name: "course_id" });
107 |
108 |   // XP Race limit check
109 |   const { data: activeXpRaceCount } = useActiveXpRaceCount(
110 |     courseId || undefined
111 |   );
112 |   const xpRaceLimitReached = (activeXpRaceCount ?? 0) >= 2;
113 |
114 |   // Load existing challenge for edit mode
115 |   const { data: existingChallenges } = useChallenges(courseId || undefined);
116 |   const existingChallenge = isEditMode
117 |     ? (existingChallenges ?? []).find((c) => c.id === id)
118 |     : null;
119 |
120 |   useEffect(() => {
121 |     if (existingChallenge) {
122 |       form.reset({
123 |         title: existingChallenge.title,
124 |         description: existingChallenge.description,
125 |         challenge_type: existingChallenge.challenge_type,
126 |         participation_mode: existingChallenge.participation_mode,
127 |         goal_target: existingChallenge.goal_target,
128 |         start_date: existingChallenge.start_date.slice(0, 16),
129 |         end_date: existingChallenge.end_date.slice(0, 16),
130 |         reward_xp: existingChallenge.reward_xp,
131 |         reward_badge_id: existingChallenge.reward_badge_id,
132 |         course_id: existingChallenge.course_id,
133 |       });
134 |     }
135 |   }, [existingChallenge, form]);
136 |
137 |   const onSubmit = (data: ChallengeFormData) => {
138 |     // Feature: qa-partner-review-remediation - Req 2.4 / 2.5
139 |     // XP Race acknowledgment gate. This runs through `form.handleSubmit`, so it
140 |     // is re-evaluated against the current form snapshot on EVERY submit attempt
141 |     // (never cached or "once per session"). It must short-circuit before any
142 |     // create/update mutation is dispatched. Acknowledgment must be an explicit
143 |     // `true` - undefined/false/any non-true value blocks submission. The
144 |     // `xp_race_acknowledged` field stays a UI-only gate (see
145 |     // `src/lib/schemas/challenge.ts`) and is never sent to the database.
146 |     if (
147 |       data.challenge_type === "xp_race" &&
148 |       data.xp_race_acknowledged !== true
149 |     ) {
150 |       toast.error("XP Race challenges require explicit acknowledgment");
151 |       return;
152 |     }
153 |
154 |     if (
155 |       data.challenge_type === "xp_race" &&
156 |       xpRaceLimitReached &&
157 |       !isEditMode
158 |     ) {
159 |       toast.error("Maximum of 2 concurrent XP Race challenges per course");
160 |       return;
161 |     }
162 |
163 |     if (isEditMode && id) {
164 |       updateMutation.mutate(
165 |         {
166 |           id,
167 |           title: data.title,
168 |           description: data.description,
169 |           goal_target: data.goal_target,
170 |           start_date: data.start_date,

```

```

171 |         end_date: data.end_date,
172 |         reward_xp: data.reward_xp,
173 |         reward_badge_id: data.reward_badge_id ?? null,
174 |       },
175 |       {
176 |         onSuccess: () => {
177 |           toast.success("Challenge updated");
178 |           navigate("/teacher/challenges");
179 |         },
180 |         onError: (err) => toast.error(err.message),
181 |       }
182 |     );
183 |   } else {
184 |     createMutation.mutate(
185 |       {
186 |         ...data,
187 |         institution_id: institutionId ?? undefined,
188 |         created_by: user?.id ?? "",
189 |       },
190 |       {
191 |         onSuccess: () => {
192 |           toast.success("Challenge created");
193 |           navigate("/teacher/challenges");
194 |         },
195 |         onError: (err) => toast.error(err.message),
196 |       }
197 |     );
198 |   }
199 | };
200 |
201 | const isPending = createMutation.isPending || updateMutation.isPending;
202 |
203 | return (
204 |   <div className="space-y-6">
205 |     <div className="flex items-center gap-3">
206 |       <Button
207 |         variant="ghost"
208 |         size="sm"
209 |         onClick={() => navigate("/teacher/challenges")}
210 |         className="h-8 w-8 p-0"
211 |       >
212 |         <ArrowLeft className="h-4 w-4" />
213 |       </Button>
214 |       <h1 className="text-2xl font-bold tracking-tight">
215 |         {isEditMode ? "Edit Challenge" : "Create Challenge"}
216 |       </h1>
217 |     </div>
218 |
219 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
220 |       <Form {...form}>
221 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
222 |           <FormField
223 |             control={form.control}
224 |             name="course_id"
225 |             render={({ field }) => (
226 |               <FormItem>
227 |                 <FormLabel>Course</FormLabel>
228 |                 <Select
229 |                   onChange={field.onChange}
230 |                   value={field.value}
231 |                   disabled={isEditMode}
232 |                 >
233 |                   <FormControl>
234 |                     <SelectTrigger className="bg-white">
235 |                       <SelectValue placeholder="Select a course" />
236 |                     </SelectTrigger>
237 |                   </FormControl>
238 |                   <SelectContent>
239 |                     {teacherCourses.map((c) => (
240 |                       <SelectItem key={c.id} value={c.id}>
241 |                         {c.name}
242 |                       </SelectItem>
243 |                     ))}
244 |                   </SelectContent>
245 |                 </Select>
246 |                 <FormMessage />
247 |               </FormItem>
248 |             )}
249 |           </>
250 |
251 |           <FormField
252 |             control={form.control}
253 |             name="title"
254 |             render={({ field }) => (
255 |               <FormItem>
256 |                 <FormLabel>Title</FormLabel>
257 |                 <FormControl>
258 |                   <Input placeholder="Challenge title" {...field} />
259 |                 </FormControl>
260 |                 <FormMessage />
261 |               </FormItem>
262 |             )}
263 |           </>
264 |
265 |           <FormField
266 |             control={form.control}
267 |             name="description"
268 |             render={({ field }) => (
269 |               <FormItem>
270 |                 <FormLabel>Description</FormLabel>
271 |                 <FormControl>
272 |                   <Input placeholder="Optional description" {...field} />
273 |                 </FormControl>
274 |                 <FormMessage />

```

```

275     </FormItem>
276   }}
277 />
278
279 <div className="grid grid-cols-2 gap-4">
280   <FormField
281     control={form.control}
282     name="challenge_type"
283     render={({ field }) => (
284       <FormItem>
285         <FormLabel>Challenge Type</FormLabel>
286         <Select
287           onChange={field.onChange}
288           value={field.value}
289           disabled={isEditMode}
290         >
291           <FormControl>
292             <SelectTrigger className="bg-white">
293               <SelectValue />
294             </SelectTrigger>
295           </FormControl>
296           <SelectContent>
297             <SelectItem value="cooperative">
298               Cooperative (Recommended)
299             </SelectItem>
300             <SelectItem value="academic">Academic</SelectItem>
301             <SelectItem value="habit">Habit</SelectItem>
302             <SelectItem value="xp_race">XP Race</SelectItem>
303             <SelectItem value="blooms_climb">
304               Bloom&apos;s Climb
305             </SelectItem>
306           </SelectContent>
307         </Select>
308         <FormMessage />
309       </FormItem>
310     )}
311 />
312
313   <FormField
314     control={form.control}
315     name="participation_mode"
316     render={({ field }) => (
317       <FormItem>
318         <FormLabel>Participation Mode</FormLabel>
319         <Select
320           onChange={field.onChange}
321           value={field.value}
322           disabled={isEditMode}
323         >
324           <FormControl>
325             <SelectTrigger className="bg-white">
326               <SelectValue />
327             </SelectTrigger>
328           </FormControl>
329           <SelectContent>
330             <SelectItem value="team">Team</SelectItem>
331             <SelectItem value="individual">Individual</SelectItem>
332           </SelectContent>
333         </Select>
334         <FormMessage />
335       </FormItem>
336     )}
337 />
338 </div>
339
340 <div className="grid grid-cols-2 gap-4">
341   <FormField
342     control={form.control}
343     name="goal_target"
344     render={({ field }) => (
345       <FormItem>
346         <FormLabel>Goal Target</FormLabel>
347         <FormControl>
348           <Input
349             type="number"
350             {...field}
351             onChange={(e) => field.onChange(Number(e.target.value))}
352           />
353         </FormControl>
354         <FormMessage />
355       </FormItem>
356     )}
357 />
358
359   <FormField
360     control={form.control}
361     name="reward_xp"
362     render={({ field }) => (
363       <FormItem>
364         <FormLabel>Reward XP (50-500)</FormLabel>
365         <FormControl>
366           <Input
367             type="number"
368             min={50}
369             max={500}
370             {...field}
371             onChange={(e) => field.onChange(Number(e.target.value))}
372           />
373         </FormControl>
374         <FormMessage />
375       </FormItem>
376     )}
377 />
378 </div>

```

```

379 |
380 |     <div className="grid grid-cols-2 gap-4">
381 |       <FormField
382 |         control={form.control}
383 |         name="start_date"
384 |         render={({ field }) => (
385 |           <FormItem>
386 |             <FormLabel>Start Date</FormLabel>
387 |             <FormControl>
388 |               <Input type="datetime-local" {...field} />
389 |             </FormControl>
390 |             <FormMessage />
391 |           </FormItem>
392 |         )}
393 |       />
394 |
395 |       <FormField
396 |         control={form.control}
397 |         name="end_date"
398 |         render={({ field }) => (
399 |           <FormItem>
400 |             <FormLabel>End Date</FormLabel>
401 |             <FormControl>
402 |               <Input type="datetime-local" {...field} />
403 |             </FormControl>
404 |             <FormMessage />
405 |           </FormItem>
406 |         )}
407 |       />
408 |     </div>
409 |
410 |     { /* XP Race Warning & Acknowledgment */ }
411 |     { challengeType === "xp_race" && (
412 |       <div className="space-y-3">
413 |         { xpRaceLimitReached && !isEditMode && (
414 |           <div className="flex items-center gap-2 rounded-xl border border-red-200 bg-red-50 px-4 py-3">
415 |             <AlertTriangle className="h-4 w-4 text-red-500 shrink-0" />
416 |             <p className="text-xs text-red-700">
417 |               Maximum of 2 concurrent XP Race challenges per course
418 |               reached.
419 |             </p>
420 |           </div>
421 |         ) }
422 |         <FormField
423 |           control={form.control}
424 |           name="xp_race_acknowledged"
425 |           render={({ field }) => (
426 |             <FormItem className="flex items-start gap-3 space-y-0">
427 |               <FormControl>
428 |                 <Checkbox
429 |                   checked={field.value}
430 |                   onCheckedChange={field.onChange}
431 |                 />
432 |               </FormControl>
433 |               <div>
434 |                 <FormLabel className="text-sm font-medium">
435 |                   I acknowledge that XP Race challenges create
436 |                   competitive pressure
437 |                 </FormLabel>
438 |                 <FormDescription className="text-xs text-gray-500">
439 |                   Research shows cooperative challenges benefit most
440 |                   learners. XP Race is limited to 2 concurrent per
441 |                   course.
442 |                 </FormDescription>
443 |               </div>
444 |             </FormItem>
445 |           ) }
446 |         />
447 |       </div>
448 |     ) }
449 |
450 |     <div className="flex items-center gap-3 pt-2">
451 |       <Button
452 |         type="submit"
453 |         disabled={
454 |           isPending ||
455 |           (challengeType === "xp_race" &&
456 |             xpRaceLimitReached &&
457 |             !isEditMode)
458 |         }
459 |         variant="tactile"
460 |       >
461 |         { isPending && <Loader2 className="h-4 w-4 animate-spin" /> }
462 |         { isEditMode ? "Update Challenge" : "Create Challenge" }
463 |       </Button>
464 |       <Button
465 |         type="button"
466 |         variant="outline"
467 |         onClick={() => navigate("/teacher/challenges")}
468 |       >
469 |         Cancel
470 |       </Button>
471 |     </div>
472 |   </form>
473 | </Form>
474 | </Card>
475 | </div>
476 | );
477 | };
478 |
479 | export default ChallengeFormPage;
480 |

```

FILE: src/pages/teacher/challenges/TeacherChallengeListPage.tsx

TYPE: .tsx | LINES: 1-225 | SHA256: 82e96960fe06de3a5036e64f6a5c0f423c676d1f79e1dbd466f0dd5671817eb5

```
1 // =====
2 // TeacherChallengeListPage - Teacher's challenge management list
3 // Task 6.3: create/edit actions, status badges, course filter
4 // =====
5
6 import { useMemo } from "react";
7 import { useNavigate } from "react-router-dom";
8 import { parseAsString, useQueryState } from "nuqs";
9 import { useAuth } from "@/hooks/useAuth";
10 import { useTeacherCourses } from "@/hooks/useCourses";
11 import {
12   useChallenges,
13   useCancelChallenge,
14   type SocialChallenge,
15 } from "@/hooks/useChallenges";
16 import { Card } from "@components/ui/card";
17 import { Button } from "@components/ui/button";
18 import { Badge } from "@components/ui/badge";
19 import { Input } from "@components/ui/input";
20 import {
21   Select,
22   SelectContent,
23   SelectItem,
24   SelectTrigger,
25   SelectValue,
26 } from "@components/ui/select";
27 import { Shimmer } from "@design-system";
28 import { NoChallenges } from "@components/shared/EmptyState";
29 import { Plus, Search, Trophy, Pencil, XCircle, Calendar } from "lucide-react";
30 import { toast } from "sonner";
31 import { cn } from "@lib/Utils";
32 import { getEffectiveChallengeStatus } from "@lib/challengeLifecycle";
33
34 const statusColors: Record<string, string> = {
35   draft: "bg-gray-100 text-gray-700 border-gray-200",
36   active: "bg-green-50 text-green-700 border-green-200",
37   upcoming: "bg-amber-50 text-amber-700 border-amber-200",
38   completed: "bg-blue-50 text-blue-700 border-blue-200",
39   ended: "bg-blue-50 text-blue-700 border-blue-200",
40   cancelled: "bg-red-50 text-red-700 border-red-200",
41 };
42
43 const TeacherChallengeListPage = () => {
44   const navigate = useNavigate();
45   const { user } = useAuth();
46   const { data: paginatedCourses } = useTeacherCourses();
47   const cancelMutation = useCancelChallenge();
48
49   const teacherCourses = useMemo(
50     () =>
51       (paginatedCourses?.data ?? []).filter((c) => c.teacher_id === user?.id),
52     [paginatedCourses, user?.id]
53   );
54
55   const [selectedCourseId, setSelectedCourseId] = useQueryState(
56     "courseId",
57     parseAsString.withDefault("")
58   );
59   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
60
61   const effectiveCourseId = selectedCourseId || teacherCourses[0]?.id || "";
62   const { data: challenges, isLoading } = useChallenges(
63     effectiveCourseId || undefined
64   );
65
66   const filteredChallenges = useMemo(() => {
67     let result = challenges ?? [];
68     if (search) {
69       const q = search.toLowerCase();
70       result = result.filter((c) => c.title.toLowerCase().includes(q));
71     }
72     return result;
73   }, [challenges, search]);
74
75   const handleCancel = (challenge: SocialChallenge) => {
76     cancelMutation.mutate(challenge.id, {
77       onSuccess: () => toast.success("Challenge cancelled"),
78       onError: (err: Error) => toast.error(err.message),
79     });
80   };
81
82   return (
83     <div className="space-y-6">
84       <div className="flex items-center justify-between">
85         <div className="flex items-center gap-2">
86           <Trophy className="h-5 w-5 text-amber-500" />
87           <h1 className="text-2xl font-bold tracking-tight">Challenges</h1>
88         </div>
89         <Button
90           onClick={() => navigate("/teacher/challenges/new")}
91           variant="tactile">
92             <Plus className="h-4 w-4" /> New Challenge
93           </Button>
94       </div>
95
96       <div>
97         <div className="flex items-center gap-4 flex-wrap">
98           <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
99             <SelectTrigger className="w-64 bg-white">
```



```

102     <SelectValue placeholder="Select course" />
103   </SelectTrigger>
104   <SelectContent>
105     {teacherCourses.map((c) => (
106       <SelectItem key={c.id} value={c.id}>
107         {c.name}
108       </SelectItem>
109     ))}
110   </SelectContent>
111 </Select>
112
113 <div className="relative flex-1 max-w-sm">
114   <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
115   <Input
116     placeholder="Search challenges..."
117     value={search}
118     onChange={(e) => setSearch(e.target.value)}
119     className="ps-9"
120   />
121 </div>
122 </div>
123
124 { /* Challenges List */}
125 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
126   <div
127     className="px-6 py-4 flex items-center gap-2"
128     style={{
129       background: "var(--brand-gradient)",
130     }}
131   >
132     <Trophy className="h-5 w-5 text-white" />
133     <h2 className="text-lg font-bold tracking-tight text-white">
134       All Challenges ({filteredChallenges.length})
135     </h2>
136   </div>
137   <div className="p-6">
138     {!effectiveCourseId ? (
139       <p className="text-sm text-gray-500 text-center py-6">
140         Select a course to view challenges.
141       </p>
142     ) : isLoading ? (
143       <div className="space-y-3">
144         {Array.from({ length: 3 }).map((_, i) => (
145           <Shimmer key={i} className="h-20 rounded-lg" />
146         ))}
147       </div>
148     ) : filteredChallenges.length === 0 ? (
149       <NoChallenges />
150     ) : (
151       <div className="space-y-2">
152         {filteredChallenges.map((challenge) => {
153           const effectiveStatus = getEffectiveChallengeStatus(challenge);
154           return (
155             <div
156               key={challenge.id}
157               className="flex items-center justify-between p-4 rounded-xl border border-slate-100 hover:
158             >
159               <div className="flex-1 min-w-0">
160                 <p className="text-sm font-semibold truncate">
161                   {challenge.title}
162                 </p>
163                 <div className="flex items-center gap-2 mt-1 flex-wrap">
164                   <Badge
165                     className={cn(
166                       "text-xs",
167                       statusColors[effectiveStatus]
168                     )}
169                   >
170                     {effectiveStatus}
171                   </Badge>
172                   <Badge variant="outline" className="text-xs">
173                     {challenge.challenge_type}
174                   </Badge>
175                   <Badge variant="outline" className="text-xs">
176                     {challenge.participation_mode}
177                   </Badge>
178                   <span className="text-xs text-gray-400 flex items-center gap-1">
179                     <Calendar className="h-3 w-3" />
180                     {new Date(
181                       challenge.start_date
182                     ).toLocaleDateString()}{" "}
183                     - {new Date(challenge.end_date).toLocaleDateString()}
184                   </span>
185                 </div>
186               </div>
187               <div className="flex items-center gap-2 shrink-0 ms-4">
188                 <Badge className="text-xs bg-amber-50 text-amber-700 border-amber-200">
189                   +{challenge.reward_xp} XP
190                 </Badge>
191                 <Button
192                   variant="ghost"
193                   size="sm"
194                   onClick={() =>
195                     navigate(`/teacher/challenges/${challenge.id}/edit`)
196                   }
197                 >
198                   <Pencil className="h-4 w-4" />
199                 </Button>
200                 {effectiveStatus === "active" && (
201                   <Button
202                     variant="ghost"
203                     size="sm"

```

```

206 |         onClick={() => handleCancel(challenge)}
207 |         className="h-8 w-8 p-0 text-red-500 hover:text-red-700"
208 |       >
209 |         <XCircle className="h-4 w-4" />
210 |       </Button>
211 |     )}
212 |   </div>
213 | </div>
214 |   );
215 | }
216 | </div>
217 | }
218 | </div>
219 | </Card>
220 | </div>
221 | );
222 | };
223 |
224 | export default TeacherChallengeListPage;
225 |

```

FILE: src/pages/teacher/clos/CL0DetailPage.tsx

TYPE: .tsx | LINES: 1-248 | SHA256: 9d24a0deb05f189d105085560a1586a3d80226ab067fa450957ce82b70df079b

```
// =====  
2 // CLODetailPage - Read-only Course Learning Outcome drill-down (Req 14.1)  
3 //  
4 // Opens from the "View" action on the CLO list (route /teacher/clos/:id).  
5 // Shows the CLO's title, description, Bloom's level, parent course, mapped PLOs,  
6 // linked assignments, and course-scope attainment. Strictly read-only: all  
7 // editing stays on the existing /teacher/clos/:id/edit route (Req 14.5).  
8 //  
9 // All data is fetched through hooks (no raw supabase in the component).  
10 // =====  
11  
12 import { useNavigate, useParams } from "react-router-dom";  
13 import { format } from "date-fns";  
14 import {  
15   ArrowLeft,  
16   Pencil,  
17   Target,  
18   ListChecks,  
19   ClipboardList,  
20   BookOpen,  
21 } from "lucide-react";  
22 import { Card } from "@components/ui/card";  
23 import { Button } from "@components/ui/button";  
24 import BloomsPill from "@components/shared/BloomsPill";  
25 import OutcomeTypeBadge from "@components/shared/OutcomeTypeBadge";  
26 import { Shimmer } from "@design-system";  
27 import {  
28   useCLO,  
29   useCLOMappedPLOs,  
30   useCLOLinkedAssignments,  
31   useCLOAttainment,  
32 } from "@hooks/useCLOs";  
33 import { useCourse } from "@hooks/useCourses";  
34 import { resolveName } from "@lib/db/resolveName";  
35 import { getAttainmentColor } from "@lib/attainmentClassifier";  
36  
37 // % % % Section card (gradient header) % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
38  
39 interface SectionCardProps {  
40   icon: typeof Target;  
41   title: string;  
42   children: React.ReactNode;  
43 }  
44  
45 const SectionCard = ({ icon: Icon, title, children }: SectionCardProps) => (  
46   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden">  
47     <div  
48       className="px-6 py-4 flex items-center gap-2"  
49       style={{  
50         background: "linear-gradient(93.65deg, #14B8A6 5.37%, #0382BD 78.89%)",  
51       }}  
52     >  
53       <Icon className="h-5 w-5 text-white" />  
54       <h2 className="text-lg font-bold tracking-tight text-white">{title}</h2>  
55     </div>  
56     <div className="p-6">{children}</div>  
57   </Card>  
58 );  
59  
60 // % % % Page % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
61  
62 const CLODetailPage = () => {  
63   const navigate = useNavigate();  
64   const { id } = useParams<{ id: string }>();  
65  
66   const { data: clo, isLoading: cloLoading } = useCLO(id);  
67   const { data: mappedPLOs = [], isLoading: plosLoading } =  
68     useCLOMappedPLOs(id);  
69   const { data: assignments = [], isLoading: assignmentsLoading } =  
70     useCLOLinkedAssignments(id, clo?.course_id ?? undefined);  
71   const { data: attainment, isLoading: attainmentLoading } =  
72     useCLOAttainment(id);  
73   const { data: course } = useCourse(clo?.course_id ?? undefined);  
74  
75   if (cloLoading) {  
76     return (  
77       <div className="space-y-6">  
78         <Shimmer className="h-10 w-48" />  
79         <Shimmer className="h-40" />  
80         <Shimmer className="h-40" />  

```

```

81 |     </div>
82 |   );
83 | }
84 |
85 | if (!clo) {
86 |   return (
87 |     <div className="space-y-6">
88 |       <Button
89 |         variant="ghost"
90 |         size="sm"
91 |         className="-ms-2"
92 |         onClick={() => navigate("/teacher/clos")}
93 |       >
94 |         <ArrowLeft className="h-4 w-4" /> Back to CLOs
95 |       </Button>
96 |       <Card className="bg-white border-0 shadow-md rounded-xl p-10 text-center">
97 |         <p className="text-sm text-slate-500">
98 |           This CLO could not be found. It may have been deleted.
99 |         </p>
100 |       </Card>
101 |     </div>
102 |   );
103 | }
104 |
105 | const attainmentPercent = attainment?.percent ?? null;
106 |
107 | return (
108 |   <div className="space-y-6">
109 |     <div className="flex items-start justify-between gap-4">
110 |       <div className="space-y-2">
111 |         <Button
112 |           variant="ghost"
113 |           size="sm"
114 |           className="-ms-2"
115 |           onClick={() => navigate("/teacher/clos")}
116 |         >
117 |           <ArrowLeft className="h-4 w-4" /> Back to CLOs
118 |         </Button>
119 |         <div className="flex items-center gap-3 flex-wrap">
120 |           <h1 className="text-2xl font-bold tracking-tight">{clo.title}</h1>
121 |           <OutcomeTypeBadge type="CLO" />
122 |           {clo.blooms_level && <BloomsPill level={clo.blooms_level} />}
123 |         </div>
124 |         <p className="text-sm text-slate-500 flex items-center gap-1.5">
125 |           <BookOpen className="h-4 w-4" />
126 |           {resolveName(course?.name)}
127 |         </p>
128 |       </div>
129 |       <Button
130 |         variant="outline"
131 |         onClick={() => navigate(`/teacher/clos/${clo.id}/edit`)}
132 |       >
133 |         <Pencil className="h-4 w-4" /> Edit
134 |       </Button>
135 |     </div>
136 |
137 |     <div>
138 |       <div className="grid gap-6 lg:grid-cols-3">
139 |         <div className="lg:col-span-2">
140 |           <SectionCard icon={Target} title="Outcome">
141 |             {clo.description ? (
142 |               <p className="text-sm text-slate-700 leading-relaxed whitespace-pre-line">
143 |                 {clo.description}
144 |               </p>
145 |             ) : (
146 |               <p className="text-sm text-slate-400">No description provided.</p>
147 |             )}
148 |           </SectionCard>
149 |         </div>
150 |
151 |         <Card className="bg-white border-0 shadow-md rounded-xl p-6 flex flex-col justify-center">
152 |           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
153 |             Course Attainment
154 |           </p>
155 |           {attainmentLoading ? (
156 |             <Shimmer className="h-9 w-24 mt-2" />
157 |           ) : attainmentPercent === null ? (
158 |             <div>
159 |               <p className="text-2xl font-black mt-1 text-slate-400"></p>
160 |               <p className="text-xs text-slate-500 mt-1">
161 |                 No attainment recorded yet.
162 |               </p>
163 |             </div>
164 |           ) : (
165 |             <div>
166 |               <p
167 |                 className="text-2xl font-black mt-1"
168 |                 style={{ color: getAttainmentColor(attainmentPercent) }}
169 |               >
170 |                 {attainmentPercent.toFixed(1)}%
171 |               </p>
172 |               <p className="text-xs text-slate-500 mt-1">
173 |                 Across {attainment?.sampleCount ?? 0} course rollout
174 |                 {(attainment?.sampleCount ?? 0) === 1 ? "" : "s"}.
175 |               </p>
176 |             </div>
177 |           )}
178 |         </Card>
179 |       </div>
180 |
181 |       <div>
182 |         <div>
183 |           <div>
184 |             <div>

```

```

185 |         <Shimmer className="h-20" />
186 |       ) : mappedPLOs.length === 0 ? (
187 |         <p className="text-sm text-slate-400">
188 |           This CLO is not mapped to any PLOs yet.
189 |         </p>
190 |       ) : (
191 |         <ul className="divide-y divide-slate-100">
192 |           {mappedPLOs.map((plo) => (
193 |             <li
194 |               key={plo.mapping_id}
195 |               className="flex items-center justify-between gap-4 py-3 first:pt-0 last:pb-0"
196 |             >
197 |               <div className="flex items-center gap-2 min-w-0">
198 |                 <OutcomeTypeBadge type="PLO" />
199 |                 <span className="text-sm font-medium truncate">
200 |                   {resolveName(plo.title)}
201 |                 </span>
202 |               </div>
203 |               <span className="text-xs font-semibold text-slate-500 shrink-0">
204 |                 Weight {Math.round(plo.weight * 100)}%
205 |               </span>
206 |             </li>
207 |           )})
208 |         </ul>
209 |       )}
210 |     </SectionCard>
211 |
212 |     {/* Linked assignments */}
213 |     <SectionCard icon={ClipboardList} title="Linked Assignments">
214 |       {assignmentsLoading ? (
215 |         <Shimmer className="h-20" />
216 |       ) : assignments.length === 0 ? (
217 |         <p className="text-sm text-slate-400">
218 |           No assignments assess this CLO yet.
219 |         </p>
220 |       ) : (
221 |         <ul className="divide-y divide-slate-100">
222 |           {assignments.map((assignment) => (
223 |             <li
224 |               key={assignment.id}
225 |               className="flex items-center justify-between gap-4 py-3 first:pt-0 last:pb-0"
226 |             >
227 |               <div className="min-w-0">
228 |                 <p className="text-sm font-medium truncate">
229 |                   {assignment.title}
230 |                 </p>
231 |                 <p className="text-xs text-slate-500">
232 |                   Due {format(new Date(assignment.due_date), "PP")}
233 |                 </p>
234 |               </div>
235 |               <span className="text-xs font-semibold text-slate-500 shrink-0">
236 |                 Weight {Math.round(assignment.weight * 100)}%
237 |               </span>
238 |             </li>
239 |           )})
240 |         </ul>
241 |       )}
242 |     </SectionCard>
243 |   </div>
244 | );
245 | };
246 |
247 | export default CLODetailPage;
248 |

```

FILE: [src/pages/teacher/clos/CLOForm.tsx](#)

TYPE: .tsx | LINES: 1-874 | SHA256: 7d6ad63d75649bb451074eec4dd639836891f91147b31127fdfe7faf621b054b

```

1 | import { useEffect, useState, useMemo } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useNavigate, useParams } from "react-router-dom";
5 | import {
6 |   createCLOSchema,
7 |   type CreateCLOFormData,
8 |   type BloomsLevel,
9 | } from "@lib/schemas/clo";
10 | import {
11 |   useCreateCLO,
12 |   useUpdateCLO,
13 |   useCLO,
14 |   useCLOMappings,
15 |   useUpdateCLOMappings,
16 | } from "@hooks/useCLOs";
17 | import { useTeacherCourses } from "@hooks/useCourses";
18 | import { usePLOs } from "@hooks/usePLOs";
19 | import {
20 |   Form,
21 |   FormField,
22 |   FormItem,
23 |   FormLabel,
24 |   FormControl,
25 |   FormMessage,
26 | } from "@components/ui/form";
27 | import { Input } from "@components/ui/input";
28 | import { Textarea } from "@components/ui/textarea";
29 | import {
30 |   Select,
31 |   SelectContent,
32 |   SelectItem,
33 |   SelectTrigger,
34 |   SelectValue,
35 | } from "@components/ui/select";
36 | import { Button } from "@components/ui/button";

```

[illegible]

```

141 |         render=({{ field }}) => (
142 |             <FormItem>
143 |                 <FormLabel>{t("bilingual.arabicTitle")}</FormLabel>
144 |                 <FormControl>
145 |                     <Input
146 |                         placeholder={t("bilingual.arabicTitlePlaceholder")}
147 |                         dir="rtl"
148 |                         maxLength={255}
149 |                         {...field}
150 |                         value={field.value ?? ""}
151 |                     />
152 |                 </FormControl>
153 |                 <FormMessage />
154 |             </FormItem>
155 |         )}
156 |     />
157 |
158 |     <FormField
159 |         control={form.control}
160 |         name="description"
161 |         render=({{ field }}) => (
162 |             <FormItem>
163 |                 <FormLabel>Description</FormLabel>
164 |                 <FormControl>
165 |                     <Textarea
166 |                         placeholder="Describe this course learning outcome..."
167 |                         className="min-h-[100px] resize-y"
168 |                         {...field}
169 |                     />
170 |                 </FormControl>
171 |                 <FormMessage />
172 |             </FormItem>
173 |         )}
174 |     />
175 |
176 |     <FormField
177 |         control={form.control}
178 |         name="course_id"
179 |         render=({{ field }}) => (
180 |             <FormItem>
181 |                 <FormLabel>Course</FormLabel>
182 |                 <Select
183 |                     onChange={field.onChange}
184 |                     value={field.value}
185 |                     disabled={isLoadingCourses}
186 |                 >
187 |                     <FormControl>
188 |                         <SelectTrigger className="bg-white">
189 |                             <SelectValue placeholder="Select a course" />
190 |                         </SelectTrigger>
191 |                     </FormControl>
192 |                     <SelectContent>
193 |                         {courses.map((course) => (
194 |                             <SelectItem key={course.id} value={course.id}>
195 |                                 {course.code} - {course.name}
196 |                             </SelectItem>
197 |                         ))}
198 |                     </SelectContent>
199 |                 </Select>
200 |                 <FormMessage />
201 |             </FormItem>
202 |         )}
203 |     />
204 |
205 |     <FormField
206 |         control={form.control}
207 |         name="blooms_level"
208 |         render=({{ field }}) => (
209 |             <FormItem>
210 |                 <FormLabel>Bloom&apos;s Taxonomy Level</FormLabel>
211 |                 <Select onChange={field.onChange} value={field.value}>
212 |                     <FormControl>
213 |                         <SelectTrigger className="bg-white">
214 |                             <SelectValue placeholder="Select Bloom's level" />
215 |                         </SelectTrigger>
216 |                     </FormControl>
217 |                     <SelectContent>
218 |                         {BLOOMS_LEVELS.map((level) => (
219 |                             <SelectItem key={level.value} value={level.value}>
220 |                                 <span className="flex items-center gap-2">
221 |                                     <span
222 |                                         className={`inline-block h-2.5 w-2.5 rounded-full ${level.color}`}
223 |                                     />
224 |                                     {level.label}
225 |                                 </span>
226 |                             </SelectItem>
227 |                         ))}
228 |                     </SelectContent>
229 |                 </Select>
230 |                 <FormMessage />
231 |             </FormItem>
232 |         )}
233 |     />
234 |
235 |     <BloomsVerbGuide
236 |         selectedLevel={watchedBloomsLevel}
237 |         onVerbClick={handleVerbClick}
238 |     />
239 |
240 |     /* AI Tutor Autonomy Level */
241 |     <FormField
242 |         control={form.control}
243 |         name="tutor_autonomy_level"
244 |         render=({{ field }}) => (

```

[illegible]

```

349 |
350 | const onSubmit = (data: CreateCLOFormData) => {
351 |   updateMutation.mutate(data, {
352 |     onSuccess: () => toast.success("CLO updated successfully"),
353 |     onError: (err) => toast.error(err.message),
354 |   });
355 | };
356 |
357 | const currentBloomsLevel = form.watch("blooms_level");
358 | const bloomsConfig = BLOOMS_LEVELS.find(
359 |   (l) => l.value === currentBloomsLevel
360 | );
361 |
362 | const handleVerbClick = (verb: string) => {
363 |   const currentTitle = form.getValues("title");
364 |   const capitalizedVerb = verb.charAt(0).toUpperCase() + verb.slice(1);
365 |   form.setValue(
366 |     "title",
367 |     currentTitle ? `${capitalizedVerb} ${currentTitle}` : capitalizedVerb,
368 |     {
369 |       shouldValidate: true,
370 |     }
371 |   );
372 | };
373 |
374 | return (
375 |   <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
376 |     <h2 className="text-lg font-bold tracking-tight mb-4">CLO Details</h2>
377 |     <Form {...form}>
378 |       <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
379 |         <FormField
380 |           control={form.control}
381 |           name="title"
382 |           render={({ field }) => (
383 |             <FormItem>
384 |               <FormLabel>Title</FormLabel>
385 |               <FormControl>
386 |                 <Input
387 |                   placeholder="e.g. Analyze data structures for algorithmic efficiency"
388 |                   maxLength={255}
389 |                   {...field}
390 |                 />
391 |               </FormControl>
392 |               <FormMessage />
393 |             </FormItem>
394 |           )}
395 |         />
396 |         <FormField
397 |           control={form.control}
398 |           name="title_ar"
399 |           render={({ field }) => (
400 |             <FormItem>
401 |               <FormLabel>{t("bilingual.arabicTitle")}</FormLabel>
402 |               <FormControl>
403 |                 <Input
404 |                   placeholder={t("bilingual.arabicTitlePlaceholder")}
405 |                   dir="rtl"
406 |                   maxLength={255}
407 |                   {...field}
408 |                   value={field.value ?? ""}
409 |                 />
410 |               </FormControl>
411 |               <FormMessage />
412 |             </FormItem>
413 |           )}
414 |         />
415 |         <FormField
416 |           control={form.control}
417 |           name="description"
418 |           render={({ field }) => (
419 |             <FormItem>
420 |               <FormLabel>Description</FormLabel>
421 |               <FormControl>
422 |                 <Textarea
423 |                   placeholder="Describe this course learning outcome..."
424 |                   className="min-h-[100px] resize-y"
425 |                   {...field}
426 |                 />
427 |               </FormControl>
428 |               <FormMessage />
429 |             </FormItem>
430 |           )}
431 |         />
432 |       </form>
433 |     </Form>
434 |     {
435 |       /* Course is read-only in edit mode */
436 |       <div className="grid gap-2">
437 |         <label
438 |           htmlFor="clo-course-readonly"
439 |           className="text-sm font-medium"
440 |         >
441 |           Course
442 |         </label>
443 |         <Input
444 |           id="clo-course-readonly"
445 |           value={
446 |             (existingCLO as unknown as LearningOutcome)?.course_id ?? ""
447 |           }
448 |           disabled
449 |           className="bg-gray-50"
450 |         />
451 |         <p className="text-sm text-muted-foreground">
452 |           Course cannot be changed after creation.

```



```

453 |     </p>
454 | </div>
455 |
456 | <FormField
457 |   control={form.control}
458 |   name="blooms_level"
459 |   render={({ field }) => (
460 |     <FormItem>
461 |       <FormLabel>Bloom&apos;s Taxonomy Level</FormLabel>
462 |       <Select onValueChange={field.onChange} value={field.value}>
463 |         <FormControl>
464 |           <SelectTrigger className="bg-white">
465 |             <SelectValue placeholder="Select Bloom's level" />
466 |           </SelectTrigger>
467 |         </FormControl>
468 |         <SelectContent>
469 |           {BLOOMS_LEVELS.map((level) => (
470 |             <SelectItem key={level.value} value={level.value}>
471 |               <span className="flex items-center gap-2">
472 |                 <span
473 |                   className={`inline-block h-2.5 w-2.5 rounded-full ${level.color}`}
474 |                 />
475 |                 {level.label}
476 |               </span>
477 |             </SelectItem>
478 |           ))}
479 |         </SelectContent>
480 |       </Select>
481 |       {bloomsConfig && (
482 |         <div className="mt-1">
483 |           <Badge
484 |             className={` ${bloomsConfig.color} text-white text-xs`}
485 |           >
486 |             {bloomsConfig.label}
487 |           </Badge>
488 |         </div>
489 |       )}
490 |       <FormMessage />
491 |     </FormItem>
492 |   )}
493 | </div>
494 |
495 | <BloomsVerbGuide
496 |   selectedLevel={currentBloomsLevel}
497 |   onVerbClick={handleVerbClick}
498 | />
499 |
500 | {/* AI Tutor Autonomy Level */}
501 | <FormField
502 |   control={form.control}
503 |   name="tutor_autonomy_level"
504 |   render={({ field }) => (
505 |     <FormItem>
506 |       <div className="flex items-center gap-2">
507 |         <Bot className="h-4 w-4 text-blue-600" />
508 |         <FormLabel>AI Tutor Autonomy Level</FormLabel>
509 |       </div>
510 |       <Select
511 |         onValueChange={field.onChange}
512 |         value={field.value ?? "L2"}
513 |       >
514 |         <FormControl>
515 |           <SelectTrigger className="bg-white">
516 |             <SelectValue placeholder="Select autonomy level" />
517 |           </SelectTrigger>
518 |         </FormControl>
519 |         <SelectContent>
520 |           <SelectItem value="L1">L1 – Hints Only</SelectItem>
521 |           <SelectItem value="L2">L2 – Guided Discovery</SelectItem>
522 |           <SelectItem value="L3">L3 – Direct Explanation</SelectItem>
523 |         </SelectContent>
524 |       </Select>
525 |       <p className="text-xs text-gray-500 mt-1">
526 |         Controls how much direct help the AI Tutor provides for this
527 |         CLO.
528 |       </p>
529 |       <FormMessage />
530 |     </FormItem>
531 |   )}
532 | </div>
533 |
534 | <div className="flex items-center gap-3 pt-2">
535 |   <Button
536 |     type="submit"
537 |     disabled={updateMutation.isPending}
538 |     variant="tactile"
539 |   >
540 |     {updateMutation.isPending && (
541 |       <Loader2 className="h-4 w-4 animate-spin" />
542 |     )}
543 |     Update CLO
544 |   </Button>
545 |   <Button
546 |     type="button"
547 |     variant="outline"
548 |     onClick={() => navigate("/teacher/clos")}
549 |   >
550 |     Cancel
551 |   </Button>
552 | </div>
553 | </form>
554 | </Form>
555 | </Card>
556 | );

```

[illegible]

```

661     },
662     onError: (err) => toast.error(err.message),
663   }
664   );
665 };
666
667 if (!programId) {
668   return (
669     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
670       <h2 className="text-lg font-bold tracking-tight mb-2">PLO Mappings</h2>
671       <p className="text-sm text-gray-500">
672         Unable to determine the program for this course. PLO mappings are
673         unavailable.
674       </p>
675     </Card>
676   );
677 }
678
679 if (isLoadingPLOs || isLoadingMappings) {
680   return (
681     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
682       <div className="flex items-center justify-center py-8">
683         <Loader2 className="h-6 w-6 animate-spin text-blue-600" />
684       </div>
685     </Card>
686   );
687 }
688
689 if (plos.length === 0) {
690   return (
691     <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
692       <h2 className="text-lg font-bold tracking-tight mb-2">PLO Mappings</h2>
693       <h2 className="text-lg font-bold tracking-tight mb-2">PLO Mappings</h2>
694     </Card>
695   );
696 }
697
698 return (
699   <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
700     <div className="flex items-center gap-2 mb-4">
701       <Link2 className="h-5 w-5 text-blue-600" />
702       <h2 className="text-lg font-bold tracking-tight">PLO Mappings</h2>
703     </div>
704
705     <p className="text-sm text-gray-500 mb-4">
706       Map this CLO to one or more PLOs and assign weights (0.0-1.0).
707     </p>
708
709     <div className="space-y-3">
710       {plos.map((plo) => {
711         const mapping = mappings.find((m) => m.plo_id === plo.id);
712         const isEnabled = mapping?.enabled ?? false;
713
714         return (
715           <div
716             key={plo.id}
717             className={`flex items-center gap-4 p-3 rounded-lg border transition-colors ${
718               isEnabled
719                 ? "border-blue-200 bg-blue-50/50"
720                 : "border-slate-200 bg-white"
721             }`}
722           >
723             <button
724               type="button"
725               onClick={() => handleToggle(plo.id)}
726               className={`shrink-0 w-5 h-5 rounded border-2 flex items-center justify-center transition-colo
727                 isEnabled
728                   ? "bg-blue-600 border-blue-600 text-white"
729                   : "border-gray-300 bg-white"
730             `}
731             aria-label={`Toggle mapping for ${plo.title}`}
732           >
733             {isEnabled && (
734               <svg
735                 className="w-3 h-3"
736                 fill="none"
737                 viewBox="0 0 24 24"
738                 stroke="currentColor"
739                 strokeWidth={3}
740               >
741                 <path
742                   strokeLinecap="round"
743                   strokeLinejoin="round"
744                   d="M5 13l4 4L19 7"
745                 />
746               </svg>
747             )}
748           </button>
749
750           <div className="flex-1 min-w-0">
751             <p className="text-sm font-medium truncate">{plo.title}</p>
752             {plo.description && (
753               <p className="text-xs text-gray-500 truncate">
754                 {plo.description}
755               </p>
756             )}
757           </div>
758
759           <div className="shrink-0 w-24">
760             <Input
761               type="number"
762               min={0}
763               max={1}
764               step={0.1}

```

[illegible]

```

869 |     </div>
870 |   );
871 | };
872 |
873 | export default CLOForm;
874 |

```

FILE: src/pages/teacher/clos/CLOListPage.tsx

TYPE: .tsx | LINES: 1-146 | SHA256: c2999b0c7c56488c2e9b99518e90cf82cea65e8242f652c1cebb6c2430614adb

```

1 | import { useState } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { toast } from "sonner";
4 | import { parseAsString, useQueryState } from "nuqs";
5 | import { createColumns } from "../columns";
6 | import { DataTable } from "@components/shared/DataTable";
7 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
8 | import { useCLOs, useDeleteCLO } from "@hooks/useCLOs";
9 | import { useTeacherCourses } from "@hooks/useCourses";
10 | import { Button } from "@components/ui/button";
11 | import { Input } from "@components/ui/input";
12 | import {
13 |   Select,
14 |   SelectContent,
15 |   SelectItem,
16 |   SelectTrigger,
17 |   SelectValue,
18 | } from "@components/ui/select";
19 | import { Plus, Search } from "lucide-react";
20 | import type { LearningOutcome } from "@types/app";
21 | import { NoCourses } from "@components/shared/EmptyState";
22 |
23 | const CLOListPage = () => {
24 |   const navigate = useNavigate();
25 |   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
26 |   const [courseFilter, setCourseFilter] = useQueryState(
27 |     "course",
28 |     parseAsString.withDefault("")
29 |   );
30 |   const [cloToDelete, setCloToDelete] = useState<LearningOutcome | null>(null);
31 |   const [page, setPage] = useState(1);
32 |
33 |   const { data: paginatedCourses, isLoading: coursesLoading } =
34 |     useTeacherCourses();
35 |   const courses = paginatedCourses?.data;
36 |   const {
37 |     data: paginatedCLOs,
38 |     isLoading,
39 |     isFetching,
40 |   } = useCLOs(courseFilter || undefined, { page });
41 |   const deleteMutation = useDeleteCLO();
42 |
43 |   const filteredCLOs = (paginatedCLOs?.data ?? []).filter((clo) => {
44 |     if (!search) return true;
45 |     const q = search.toLowerCase();
46 |     return (
47 |       clo.title.toLowerCase().includes(q) ||
48 |       (clo.description?.toLowerCase().includes(q) ?? false)
49 |     );
50 |   });
51 |
52 |   const columns = createColumns(
53 |     (id) => navigate(`/teacher/clos/${id}`),
54 |     (id) => navigate(`/teacher/clos/${id}/edit`),
55 |     (clo) => setCloToDelete(clo)
56 |   );
57 |
58 |   return (
59 |     <div className="space-y-6">
60 |       <div>
61 |         <div className="flex items-center justify-between">
62 |           <h1 className="text-2xl font-bold tracking-tight">
63 |             Course Learning Outcomes
64 |           </h1>
65 |           <Button variant="tactile" onClick={() => navigate("/teacher/clos/new")}>
66 |             <Plus className="h-4 w-4" /> Add CLO
67 |           </Button>
68 |         </div>
69 |
70 |         <div>
71 |           <div>
72 |             <div className="flex items-center gap-4">
73 |               <div className="relative flex-1 max-w-sm">
74 |                 <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
75 |                 <Input
76 |                   placeholder="Search CLOs..."
77 |                   value={search}
78 |                   onChange={(e) => setSearch(e.target.value)}
79 |                   className="ps-9"
80 |                 />
81 |               </div>
82 |               <Select
83 |                 value={courseFilter}
84 |                 onValueChange={(val) => {
85 |                   setCourseFilter(val === "all" ? "" : val);
86 |                   setPage(1);
87 |                 }}
88 |                 disabled={coursesLoading}
89 |               >
90 |                 <SelectTrigger className="w-[260px] bg-white">
91 |                   <SelectValue placeholder="Filter by course" />
92 |                 </SelectTrigger>
93 |                 <SelectContent>
94 |                   <SelectItem value="all">All Courses</SelectItem>
95 |                   {(courses ?? []).map((c) => (

```

```

95 |         <SelectItem key={c.id} value={c.id}>
96 |             {c.code} - {c.name}
97 |         </SelectItem>
98 |     ))}
99 | </SelectContent>
100 | </Select>
101 | </div>
102 |
103 | { /* Data Table */}
104 | <DataTable
105 |     columns={columns}
106 |     data={filteredCLOs}
107 |     isLoading={isLoading}
108 |     isFetching={isFetching}
109 |     page={page}
110 |     pageSize={paginatedCLOs?.pageSize}
111 |     totalCount={paginatedCLOs?.count}
112 |     onPageChange={setPage}
113 |     emptyState={
114 |         filteredCLOs.length === 0 && !isLoading ? <NoCourses /> : undefined
115 |     }
116 | />
117 |
118 | { /* Delete Confirmation Dialog */}
119 | <ConfirmDialog
120 |     open={!cloToDelete}
121 |     onOpenChange={() => setCloToDelete(null)}
122 |     title="Delete CLO"
123 |     description={`Are you sure you want to delete "${cloToDelete?.title}"? This action cannot be undone.`}
124 |     variant="destructive"
125 |     confirmLabel="Delete"
126 |     isPending={deleteMutation.isPending}
127 |     onConfirm={() => {
128 |         if (!cloToDelete) return;
129 |         deleteMutation.mutate(cloToDelete.id, {
130 |             onSuccess: () => {
131 |                 toast.success(`${cloToDelete.title}` has been deleted`);
132 |                 setCloToDelete(null);
133 |             },
134 |             onError: (err) => {
135 |                 toast.error(err.message);
136 |                 setCloToDelete(null);
137 |             },
138 |         });
139 |     }}
140 | />
141 | </div>
142 | );
143 | };
144 |
145 | export default CLOListPage;
146 |

```

FILE: [src/pages/teacher/clos/columns.tsx](#)

TYPE: .tsx | LINES: 1-133 | SHA256: 14fa14161d6ba11f0d64402283abc37502c2b4b42521ca1b280d85b84863f226

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { ArrowUpDown, Eye, MoreHorizontal, Pencil, Trash2 } from "lucide-react";
3 | import { Badge } from "@components/ui/badge";
4 | import { Button } from "@components/ui/button";
5 | import {
6 |     DropdownMenu,
7 |     DropdownMenuContent,
8 |     DropdownMenuItem,
9 |     DropdownMenuTrigger,
10 | } from "@components/ui/dropdown-menu";
11 | import { cn } from "@lib/Utils";
12 | import { resolveName } from "@lib/db/resolveName";
13 | import type { CLOWithRelations } from "@hooks/useCLOs";
14 | import type { LearningOutcome, BloomsLevel } from "@types/app";
15 |
16 | const bloomsBadgeStyles: Record<string, string> = {
17 |     Remembering: "bg-purple-500 text-white",
18 |     Understanding: "bg-blue-500 text-white",
19 |     Applying: "bg-green-500 text-white",
20 |     Analyzing: "bg-yellow-500 text-gray-900",
21 |     Evaluating: "bg-orange-500 text-white",
22 |     Creating: "bg-red-500 text-white",
23 | };
24 |
25 | const formatBloomsLevel = (level: string | null): string => {
26 |     if (!level) return "-";
27 |     return level.charAt(0).toUpperCase() + level.slice(1);
28 | };
29 |
30 | export const createColumns = (
31 |     onView: (id: string) => void,
32 |     onEdit: (id: string) => void,
33 |     onDelete: (clo: LearningOutcome) => void
34 | ): ColumnDef<CLOWithRelations>[] => [
35 |     {
36 |         accessorKey: "title",
37 |         header: ({ column }) => (
38 |             <Button
39 |                 variant="ghost"
40 |                 size="sm"
41 |                 className="-ms-3"
42 |                 onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
43 |             >
44 |                 Title
45 |             <ArrowUpDown className="h-4 w-4" />
46 |         )
47 |     },
48 |     cell: ({ row }) => (

```

```

49 |         <span className="font-medium">{row.getValue("title")}</span>
50 |     ),
51 | },
52 | {
53 |     accessorKey: "blooms_level",
54 |     header: "Bloom's Level",
55 |     cell: ({ row }) => {
56 |         const raw = row.getValue("blooms_level") as BloomsLevel | null;
57 |         const label = formatBloomsLevel(raw);
58 |         const styleKey = label;
59 |         const badgeClass =
60 |             bloomsBadgeStyles[styleKey] ?? "bg-gray-200 text-gray-700";
61 |
62 |         if (!raw) {
63 |             return <span className="text-gray-400 text-sm">—</span>;
64 |         }
65 |
66 |         return (
67 |             <Badge className={cn("text-xs font-bold tracking-wide", badgeClass)}>
68 |                 {label}
69 |             </Badge>
70 |         );
71 |     },
72 | },
73 | {
74 |     id: "course",
75 |     header: "Course",
76 |     cell: ({ row }) => (
77 |         <span className="text-gray-500 text-sm truncate max-w-[160px] inline-block">
78 |             {resolveName(row.original.courses?.name)}
79 |         </span>
80 |     ),
81 | },
82 | {
83 |     accessorKey: "is_active",
84 |     header: "Status",
85 |     cell: ({ row }) => {
86 |         const isActive = row.getValue("is_active") as boolean;
87 |         return (
88 |             <Badge
89 |                 variant="outline"
90 |                 className={
91 |                     isActive
92 |                     ? "bg-green-50 text-green-600 border-green-200"
93 |                     : "bg-red-50 text-red-600 border-red-200"
94 |                 }
95 |             >
96 |                 {isActive ? "Active" : "Inactive"}
97 |             </Badge>
98 |         );
99 |     },
100 | },
101 | {
102 |     id: "actions",
103 |     header: "",
104 |     cell: ({ row }) => (
105 |         <DropdownMenu>
106 |             <DropdownMenuTrigger asChild>
107 |                 <Button variant="ghost" size="icon-xs">
108 |                     <MoreHorizontal className="h-4 w-4" />
109 |                     <span className="sr-only">Open menu</span>
110 |                 </Button>
111 |             </DropdownMenuTrigger>
112 |             <DropdownMenuContent align="end">
113 |                 <DropdownMenuItem onClick={() => onView(row.original.id)}>
114 |                     <Eye className="h-4 w-4" />
115 |                     View
116 |                 </DropdownMenuItem>
117 |                 <DropdownMenuItem onClick={() => onEdit(row.original.id)}>
118 |                     <Pencil className="h-4 w-4" />
119 |                     Edit
120 |                 </DropdownMenuItem>
121 |                 <DropdownMenuItem
122 |                     variant="destructive"
123 |                     onClick={() => onDelete(row.original)}
124 |                 >
125 |                     <Trash2 className="h-4 w-4" />
126 |                     Delete
127 |                 </DropdownMenuItem>
128 |             </DropdownMenuContent>
129 |         </DropdownMenu>
130 |     ),
131 | },
132 | ];
133 |

```

FILE: [src/pages/teacher/content/ContentReviewPage.tsx](#)

TYPE: .tsx | LINES: 1-97 | SHA256: b25b96d6224da631a30914993f3159b8330bfa0c49f7b61d010dfda1ac2c3dbc

```

1 | // =====
2 | // ContentReviewPage – Teacher review queue for student content
3 | // Task 21.7
4 | // =====
5 |
6 | import { Card } from "@components/ui/card";
7 | import { Badge } from "@components/ui/badge";
8 | import { Button } from "@components/ui/button";
9 | import { Loader2, FileText, Check, X } from "lucide-react";
10 | import {
11 |     useStudentContent,
12 |     useReviewStudentContent,
13 | } from "@hooks/useStudentContent";
14 | import { useAuth } from "@hooks/useAuth";
15 | import { NoData } from "@components/shared/EmptyState";

```

```

16 |
17 | const ContentReviewPage = () => {
18 |   const { profile } = useAuth();
19 |   const { data: content, isLoading } = useStudentContent();
20 |   const reviewContent = useReviewStudentContent();
21 |
22 |   const pendingContent = (content ?? []).filter((c) => c.status === "pending");
23 |
24 |   const handleReview = (contentId: string, status: "approved" | "rejected") => {
25 |     if (!profile?.id) return;
26 |     reviewContent.mutate({
27 |       content_id: contentId,
28 |       status,
29 |       reviewerId: profile.id,
30 |     });
31 |   };
32 |
33 |   return (
34 |     <div className="space-y-6">
35 |       <h1 className="text-2xl font-bold tracking-tight">
36 |         Content Review Queue
37 |       </h1>
38 |
39 |       {isLoading ? (
40 |         <div className="flex justify-center py-12">
41 |           <Loader2 className="h-6 w-6 animate-spin text-blue-500" />
42 |         </div>
43 |       ) : pendingContent.length === 0 ? (
44 |         <NoData />
45 |       ) : (
46 |         <div className="grid gap-4">
47 |           {pendingContent.map((item) => (
48 |             <Card
49 |               key={item.id}
50 |               className="bg-white border-0 shadow-md rounded-xl p-4"
51 |             >
52 |               <div className="flex items-start gap-4">
53 |                 <div className="p-2 rounded-lg bg-blue-50">
54 |                   <FileText className="h-5 w-5 text-blue-600" />
55 |                 </div>
56 |                 <div className="flex-1 min-w-0">
57 |                   <div className="flex items-center gap-2">
58 |                     <h3 className="text-sm font-bold">{item.title}</h3>
59 |                     <Badge variant="outline" className="text-[10px] capitalize">
60 |                       {item.content_type.replace("_", " ")}
61 |                     </Badge>
62 |                   </div>
63 |                   <p className="text-xs text-gray-500 mt-1">
64 |                     Submitted {new Date(item.created_at).toLocaleDateString()}
65 |                   </p>
66 |                 </div>
67 |                 <div className="flex gap-2">
68 |                   <Button
69 |                     size="sm"
70 |                     variant="outline"
71 |                     className="text-green-600 border-green-200 hover:bg-green-50"
72 |                     disabled={reviewContent.isPending}
73 |                     onClick={() => handleReview(item.id, "approved")}
74 |                   >
75 |                     <Check className="h-4 w-4" /> Approve
76 |                   </Button>
77 |                   <Button
78 |                     size="sm"
79 |                     variant="outline"
80 |                     className="text-red-600 border-red-200 hover:bg-red-50"
81 |                     disabled={reviewContent.isPending}
82 |                     onClick={() => handleReview(item.id, "rejected")}
83 |                   >
84 |                     <X className="h-4 w-4" /> Reject
85 |                   </Button>
86 |                 </div>
87 |               </div>
88 |             </Card>
89 |           )})
90 |         </div>
91 |       )}
92 |     </div>
93 |   );
94 | };
95 |
96 | export default ContentReviewPage;
97 |

```

FILE: [src/pages/teacher/courses/ModuleManager.tsx](#)

TYPE: .tsx | LINES: 1-988 | SHA256: c5597c9c98ba7cf81d241dfcedf1761091c036f3a705e2bd6171b1fe7027a289

```

1 | // Task 66.5: Course Module Manager – Create/edit modules with materials
2 | // Requirements: 76.1, 76.2, 76.3, 76.4
3 | import { useState, useRef } from "react";
4 | import { useForm, useWatch } from "react-hook-form";
5 | import { zodResolver } from "@hookform/resolvers/zod";
6 | import { z } from "zod";
7 | import { useAuth } from "@/hooks/useAuth";
8 | import {
9 |   useCourseModules,
10 |   useCourseMaterials,
11 |   useCreateModule,
12 |   useUpdateModule,
13 |   useDeleteModule,
14 |   useCreateMaterial,
15 |   useUpdateMaterial,
16 |   useDeleteMaterial,
17 |   uploadMaterialFile,
18 |   type CourseModule,

```


[illegible]

[illegible]

```

227 |         type: data.type as MaterialType,
228 |         content_url: data.content_url || null,
229 |         description: data.description || null,
230 |         sort_order: data.sort_order,
231 |         is_published: data.is_published,
232 |         clo_ids: data.clo_ids,
233 |         file_path: data.type === "file" ? data.content_url || null : null,
234 |         course_id: courseId,
235 |         performedBy: teacherId,
236 |     },
237 |     {
238 |         onSuccess: () => {
239 |             toast.success("Material updated");
240 |             setShowMaterialForm(false);
241 |             setEditingMaterial(null);
242 |         },
243 |         onError: (err) => toast.error(err.message),
244 |     }
245 | );
246 | } else {
247 |     createMaterial.mutate(
248 |         {
249 |             module_id: mod.id,
250 |             title: data.title,
251 |             type: data.type as MaterialType,
252 |             content_url: data.content_url || undefined,
253 |             file_path:
254 |                 data.type === "file" ? data.content_url || undefined : undefined,
255 |             description: data.description || undefined,
256 |             sort_order: data.sort_order,
257 |             is_published: data.is_published,
258 |             clo_ids: data.clo_ids,
259 |             course_id: courseId,
260 |             performedBy: teacherId,
261 |         },
262 |         {
263 |             onSuccess: () => {
264 |                 toast.success("Material added");
265 |                 setShowMaterialForm(false);
266 |             },
267 |             onError: (err) => toast.error(err.message),
268 |         }
269 |     );
270 | }
271 | };
272 |
273 | const handleDeleteMaterial = () => {
274 |     if (!deleteTarget) return;
275 |     deleteMaterial.mutate(
276 |         { id: deleteTarget.id, performedBy: teacherId },
277 |         {
278 |             onSuccess: () => {
279 |                 toast.success("Material deleted");
280 |                 setDeleteTarget(null);
281 |             },
282 |             onError: (err) => toast.error(err.message),
283 |         }
284 |     );
285 | };
286 |
287 | const isPending = createMaterial.isPending || updateMaterial.isPending;
288 |
289 | return (
290 |     <div className="ps-6 space-y-2">
291 |         {isLoading ? (
292 |             <Shimmer className="h-10 rounded-lg" />
293 |         ) : (
294 |             <>
295 |                 {(materials ?? []).map((m) => {
296 |                     const Icon = TYPE_ICONS[m.type];
297 |                     return (
298 |                         <div
299 |                             key={m.id}
300 |                             className="flex items-center gap-3 rounded-lg px-3 py-2 hover:bg-slate-50 transition-colors"
301 |                         >
302 |                             <div className={`p-1.5 rounded-lg ${TYPE_COLORS[m.type]}`>
303 |                                 <Icon className="h-4 w-4" />
304 |                             </div>
305 |                             <span className="text-sm font-medium flex-1 truncate">
306 |                                 {m.title}
307 |                             </span>
308 |                             {!m.is_published && (
309 |                                 <Badge variant="outline" className="text-xs text-gray-400">
310 |                                     Draft
311 |                                 </Badge>
312 |                             )}
313 |                             {m.clo_ids.length > 0 && (
314 |                                 <Badge
315 |                                     variant="outline"
316 |                                     className="text-xs text-green-600 border-green-200"
317 |                                 >
318 |                                     {m.clo_ids.length} CLO{m.clo_ids.length > 1 ? "s" : ""}
319 |                                 </Badge>
320 |                             )}
321 |                         <Button
322 |                             variant="ghost"
323 |                             size="sm"
324 |                             className="h-7 w-7 p-0"
325 |                             onClick={() => openEdit(m)}
326 |                         >
327 |                             <Pencil className="h-3.5 w-3.5 text-gray-400" />
328 |                         </Button>
329 |                         <Button
330 |                             variant="ghost"

```

```

331         size="sm"
332         className="h-7 w-7 p-0"
333         onClick={() => setDeleteTarget(m)}
334     >
335     <Trash2 className="h-3.5 w-3.5 text-red-400" />
336 </Button>
337 </div>
338 );
339 }}
340 <Button
341     variant="ghost"
342     size="sm"
343     onClick={openCreate}
344     className="text-xs text-blue-600"
345 >
346     <Plus className="h-3.5 w-3.5 me-1" /> Add Material
347 </Button>
348 </>
349 })
350
351 {/* Material Form */}
352 {showMaterialForm && (
353     <Card className="bg-slate-50 border shadow-sm rounded-lg p-4 mt-2">
354         <Form {...form}>
355             <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-3">
356                 <div className="grid grid-cols-2 gap-3">
357                     <FormField
358                         control={form.control}
359                         name="title"
360                         render={({ field }) => (
361                             <FormItem>
362                                 <FormLabel className="text-xs">Title</FormLabel>
363                                 <FormControl>
364                                     <Input
365                                         placeholder="Material title"
366                                         {...field}
367                                         className="h-8 text-sm"
368                                     />
369                                 </FormControl>
370                                 <FormMessage />
371                             </FormItem>
372                         )}
373                     />
374                     <FormField
375                         control={form.control}
376                         name="type"
377                         render={({ field }) => (
378                             <FormItem>
379                                 <FormLabel className="text-xs">Type</FormLabel>
380                                 <Select
381                                     value={field.value}
382                                     onChange={field.onChange}
383                                 >
384                                     <FormControl>
385                                         <SelectTrigger className="h-8 text-sm bg-white">
386                                             <SelectValue />
387                                         </SelectTrigger>
388                                     </FormControl>
389                                         <SelectContent>
390                                             <SelectItem value="file">File</SelectItem>
391                                             <SelectItem value="link">Link</SelectItem>
392                                             <SelectItem value="video">Video</SelectItem>
393                                             <SelectItem value="text">Text</SelectItem>
394                                         </SelectContent>
395                                     </Select>
396                                 <FormMessage />
397                             </FormItem>
398                         )}
399                     />
400                 </div>
401
402                 {watchType === "file" && (
403                     <div>
404                         <input
405                             ref={fileInputRef}
406                             type="file"
407                             className="hidden"
408                             accept=".pdf,.doc,.docx,.pptx,.png,.jpg,.jpeg,.gif,.mp4,.zip"
409                             onChange={handleFileUpload}
410                         />
411                         <Button
412                             type="button"
413                             variant="outline"
414                             size="sm"
415                             onClick={() => fileInputRef.current?.click()}
416                             disabled={uploading}
417                             className="text-xs"
418                         >
419                             {uploading ? (
420                                 <Loader2 className="h-3.5 w-3.5 animate-spin me-1" />
421                             ) : (
422                                 <Upload className="h-3.5 w-3.5 me-1" />
423                             )}
424                             {uploading ? "Uploading..." : "Upload File"}
425                         </Button>
426                         {form.getValues("content_url") && (
427                             <p className="text-xs text-green-600 mt-1">
428                                 File uploaded '
429                                 <p>
430                             )}
431                         </div>
432                     )}
433                 )}
434                 {(watchType === "link" || watchType === "video") && (

```

```

435 |         <FormField
436 |             control={form.control}
437 |             name="content_url"
438 |             render={({ field }) => (
439 |                 <FormItem>
440 |                     <FormLabel className="text-xs">
441 |                         {watchType === "video"
442 |                             ? "Video URL (YouTube/Vimeo)"
443 |                             : "URL"}
444 |                     </FormLabel>
445 |                     <FormControl>
446 |                         <Input
447 |                             placeholder="https://..."
448 |                             {...field}
449 |                             className="h-8 text-sm"
450 |                         />
451 |                     </FormControl>
452 |                     <FormMessage />
453 |                 </FormItem>
454 |             )}
455 |         />
456 |     )}
457 |
458 |     {watchType === "text" && (
459 |         <FormField
460 |             control={form.control}
461 |             name="content_url"
462 |             render={({ field }) => (
463 |                 <FormItem>
464 |                     <FormLabel className="text-xs">Text Content</FormLabel>
465 |                     <FormControl>
466 |                         <Textarea
467 |                             placeholder="Enter text content..."
468 |                             rows={3}
469 |                             {...field}
470 |                             className="text-sm"
471 |                         />
472 |                     </FormControl>
473 |                     <FormMessage />
474 |                 </FormItem>
475 |             )}
476 |         />
477 |     )}
478 |
479 |     <FormField
480 |         control={form.control}
481 |         name="description"
482 |         render={({ field }) => (
483 |             <FormItem>
484 |                 <FormLabel className="text-xs">
485 |                     Description (optional)
486 |                 </FormLabel>
487 |                 <FormControl>
488 |                     <Input
489 |                         placeholder="Brief description"
490 |                         {...field}
491 |                         className="h-8 text-sm"
492 |                     />
493 |                 </FormControl>
494 |                 <FormMessage />
495 |             </FormItem>
496 |         )}
497 |     />
498 |
499 |     {/* CLO Linking */}
500 |     {clos &&
501 |         (clos as Array<{ id: string; title: string }>).length > 0 && (
502 |             <FormField
503 |                 control={form.control}
504 |                 name="clo_ids"
505 |                 render={({ field }) => (
506 |                     <FormItem>
507 |                         <FormLabel className="text-xs">Link to CLOs</FormLabel>
508 |                         <div className="space-y-1">
509 |                             {(clos as Array<{ id: string; title: string }>).map(
510 |                                 (clo) => (
511 |                                     <label
512 |                                         key={clo.id}
513 |                                         className="flex items-center gap-2 text-xs"
514 |                                     >
515 |                                         <Checkbox
516 |                                             checked={{field.value ?? []}.includes(clo.id)}
517 |                                             onChange={{(checked) => {
518 |                                                 const current = field.value ?? [];
519 |                                                 field.onChange(
520 |                                                     checked
521 |                                                         ? [...current, clo.id]
522 |                                                         : current.filter((id) => id !== clo.id)
523 |                                                 }}
524 |                                         </Checkbox>
525 |                                         {clo.title}
526 |                                     </label>
527 |                                 )
528 |                             )}
529 |                         </div>
530 |                     </FormItem>
531 |                 )}
532 |             />
533 |         )}
534 |
535 |     <div className="grid grid-cols-2 gap-3">
536 |         <FormField
537 |             control={form.control}
538 |

```

[illegible]

```

643 | );
644 |
645 | const createModule = useCreateModule();
646 | const updateModule = useUpdateModule();
647 | const deleteModule = useDeleteModule();
648 |
649 | const moduleForm = useForm<ModuleFormData>({
650 |   resolver: zodResolver(moduleSchema),
651 |   defaultValues: {
652 |     title: "",
653 |     description: "",
654 |     sort_order: 0,
655 |     is_published: false,
656 |   },
657 | });
658 |
659 | const toggleExpand = (moduleId: string) => {
660 |   setExpandedModules((prev) => {
661 |     const next = new Set(prev);
662 |     if (next.has(moduleId)) next.delete(moduleId);
663 |     else next.add(moduleId);
664 |     return next;
665 |   });
666 | };
667 |
668 | const openCreateModule = () => {
669 |   setEditingModule(null);
670 |   moduleForm.reset({
671 |     title: "",
672 |     description: "",
673 |     sort_order: modules?.length ?? 0,
674 |     is_published: false,
675 |   });
676 |   setShowModuleForm(true);
677 | };
678 |
679 | const openEditModule = (m: CourseModule) => {
680 |   setEditingModule(m);
681 |   moduleForm.reset({
682 |     title: m.title,
683 |     description: m.description ?? "",
684 |     sort_order: m.sort_order,
685 |     is_published: m.is_published,
686 |   });
687 |   setShowModuleForm(true);
688 | };
689 |
690 | const onModuleSubmit = (data: ModuleFormData) => {
691 |   if (!teacherId) return;
692 |
693 |   if (editingModule) {
694 |     updateModule.mutate(
695 |       {
696 |         id: editingModule.id,
697 |         title: data.title,
698 |         description: data.description || null,
699 |         sort_order: data.sort_order,
700 |         is_published: data.is_published,
701 |         performedBy: teacherId,
702 |       },
703 |       {
704 |         onSuccess: () => {
705 |           toast.success("Module updated");
706 |           setShowModuleForm(false);
707 |           setEditingModule(null);
708 |         },
709 |         onError: (err) => toast.error(err.message),
710 |       }
711 |     );
712 |   } else {
713 |     createModule.mutate(
714 |       {
715 |         course_id: effectiveCourseId,
716 |         title: data.title,
717 |         description: data.description,
718 |         sort_order: data.sort_order,
719 |         is_published: data.is_published,
720 |         performedBy: teacherId,
721 |       },
722 |       {
723 |         onSuccess: () => {
724 |           toast.success("Module created");
725 |           setShowModuleForm(false);
726 |         },
727 |         onError: (err) => toast.error(err.message),
728 |       }
729 |     );
730 |   }
731 | };
732 |
733 | const handleDeleteModule = () => {
734 |   if (!deleteTarget || !teacherId) return;
735 |   deleteModule.mutate(
736 |     { id: deleteTarget.id, performedBy: teacherId },
737 |     {
738 |       onSuccess: () => {
739 |         toast.success("Module deleted");
740 |         setDeleteTarget(null);
741 |       },
742 |       onError: (err) => toast.error(err.message),
743 |     }
744 |   );
745 | };
746 |

```

```

747 | const isModulePending = createModule.isPending || updateModule.isPending;
748 |
749 | return (
750 |   <div className="space-y-6">
751 |     <div className="flex items-center justify-between">
752 |       <h1 className="text-2xl font-bold tracking-tight">Course Modules</h1>
753 |       <Button
754 |         onClick={openCreateModule}
755 |         disabled={!effectiveCourseId}
756 |         variant="tactile"
757 |       >
758 |         <Plus className="h-4 w-4" /> New Module
759 |       </Button>
760 |     </div>
761 |
762 |     {/* Course Selector */}
763 |     <div className="max-w-xs">
764 |       {coursesLoading ? (
765 |         <Shimmer className="h-10 rounded-lg" />
766 |       ) : (
767 |         <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
768 |           <SelectTrigger className="bg-white">
769 |             <SelectValue placeholder="Select a course" />
770 |           </SelectTrigger>
771 |           <SelectContent>
772 |             {(courses ?? []).map((c) => (
773 |               <SelectItem key={c.id} value={c.id}>
774 |                 {c.code} – {c.name}
775 |               </SelectItem>
776 |             ))}
777 |           </SelectContent>
778 |         </Select>
779 |       )}
780 |     </div>
781 |
782 |     {/* Module Form */}
783 |     {showModuleForm && (
784 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
785 |         <h2 className="text-lg font-bold tracking-tight mb-4">
786 |           {editingModule ? "Edit Module" : "New Module"}
787 |         </h2>
788 |         <Form {...moduleForm}>
789 |           <form
790 |             onSubmit={moduleForm.handleSubmit(onModuleSubmit)}
791 |             className="space-y-4"
792 |           >
793 |             <FormField
794 |               control={moduleForm.control}
795 |               name="title"
796 |               render={({ field }) => (
797 |                 <FormItem>
798 |                   <FormLabel>Title</FormLabel>
799 |                   <FormControl>
800 |                     <Input
801 |                       placeholder="e.g., Week 1: Introduction"
802 |                       {...field}
803 |                     />
804 |                   </FormControl>
805 |                   <FormMessage />
806 |                 </FormItem>
807 |               )}
808 |             />
809 |             <FormField
810 |               control={moduleForm.control}
811 |               name="description"
812 |               render={({ field }) => (
813 |                 <FormItem>
814 |                   <FormLabel>Description (optional)</FormLabel>
815 |                   <FormControl>
816 |                     <Textarea
817 |                       placeholder="Module description"
818 |                       rows={3}
819 |                       {...field}
820 |                     />
821 |                   </FormControl>
822 |                   <FormMessage />
823 |                 </FormItem>
824 |               )}
825 |             />
826 |             <div className="grid grid-cols-2 gap-4">
827 |               <FormField
828 |                 control={moduleForm.control}
829 |                 name="sort_order"
830 |                 render={({ field }) => (
831 |                   <FormItem>
832 |                     <FormLabel>Sort Order</FormLabel>
833 |                     <FormControl>
834 |                       <Input type="number" min={0} {...field} />
835 |                     </FormControl>
836 |                     <FormMessage />
837 |                   </FormItem>
838 |                 )}
839 |               />
840 |               <FormField
841 |                 control={moduleForm.control}
842 |                 name="is_published"
843 |                 render={({ field }) => (
844 |                   <FormItem className="flex items-center gap-3 pt-6">
845 |                     <FormControl>
846 |                       <Switch
847 |                         checked={field.value}
848 |                         onChange={field.onChange}
849 |                       />
850 |                     </FormControl>

```



```

851         <FormLabel className="!mt-0">Published</FormLabel>
852     </FormItem>
853 })
854 />
855 </div>
856 <div className="flex gap-2">
857     <Button
858         type="submit"
859         disabled={isModulePending}
860         variant="tactile"
861     >
862         {isModulePending && (
863             <Loader2 className="h-4 w-4 animate-spin" />
864         )}
865         {editingModule ? "Update" : "Create"}
866     </Button>
867     <Button
868         type="button"
869         variant="outline"
870         onClick={() => {
871             setShowModuleForm(false);
872             setEditingModule(null);
873         }}
874     >
875         Cancel
876     </Button>
877 </div>
878 </form>
879 </Form>
880 </Card>
881 ))
882
883 {/* Modules List */}
884 {modulesLoading ? (
885     <div className="space-y-3">
886         {Array.from({ length: 3 }).map((_, i) => (
887             <Shimmer key={i} className="h-16 rounded-xl" />
888         ))}
889     </div>
890 ) : (modules ?? []).length === 0 ? (
891     <Card className="bg-white border-0 shadow-md rounded-xl p-8 text-center">
892         <FolderOpen className="h-10 w-10 text-gray-300 mx-auto mb-3" />
893         <p className="text-sm text-gray-500">
894             No modules yet. Create one to organize your course materials.
895         </p>
896     </Card>
897 ) : (
898     <div className="space-y-2">
899         {(modules ?? []).map((m) => {
900             const isExpanded = expandedModules.has(m.id);
901             return (
902                 <Card
903                     key={m.id}
904                     className="bg-white border-0 shadow-md rounded-xl overflow-hidden"
905                 >
906                     <div
907                         className="flex items-center gap-3 px-4 py-3 cursor-pointer hover:bg-slate-50 transition-col"
908                         onClick={() => toggleExpand(m.id)}
909                         role="button"
910                         tabIndex={0}
911                         onKeyDown={(e) => {
912                             if (e.key === "Enter" || e.key === " ") {
913                                 e.preventDefault();
914                                 toggleExpand(m.id);
915                             }
916                         }}
917                     >
918                         {isExpanded ? (
919                             <ChevronDown className="h-4 w-4 text-gray-400 shrink-0" />
920                         ) : (
921                             <ChevronRight className="h-4 w-4 text-gray-400 shrink-0" />
922                         )}
923                         <FolderOpen className="h-4 w-4 text-blue-500 shrink-0" />
924                         <span className="text-sm font-bold flex-1 truncate">
925                             {m.title}
926                         </span>
927                         {!m.is_published && (
928                             <Badge variant="outline" className="text-xs text-gray-400">
929                                 Draft
930                             </Badge>
931                         )}
932                         <span className="text-xs text-gray-400">#{m.sort_order}</span>
933                     <Button
934                         variant="ghost"
935                         size="sm"
936                         className="h-7 w-7 p-0"
937                         onClick={(e) => {
938                             e.stopPropagation();
939                             openEditModule(m);
940                         }}
941                     >
942                         <Pencil className="h-3.5 w-3.5 text-gray-400" />
943                     </Button>
944                     <Button
945                         variant="ghost"
946                         size="sm"
947                         className="h-7 w-7 p-0"
948                         onClick={(e) => {
949                             e.stopPropagation();
950                             setDeleteTarget(m);
951                         }}
952                     >
953                         <Trash2 className="h-3.5 w-3.5 text-red-400" />
954                     </Button>

```

```

955 |         </div>
956 |         {isExpanded && teacherId && (
957 |           <div className="border-t border-slate-100 py-3 px-2">
958 |             <ModuleMaterials
959 |               module={m}
960 |               teacherId={teacherId}
961 |               courseId={effectiveCourseId}
962 |             />
963 |           </div>
964 |         )}
965 |       </Card>
966 |     );
967 |   }
968 | </div>
969 | })
970 |
971 | <ConfirmDialog
972 |   open={!deleteTarget}
973 |   onOpenChange={({open: boolean}) => {
974 |     if (!open) setDeleteTarget(null);
975 |   }}
976 |   title="Delete Module"
977 |   description={`Delete "${deleteTarget?.title}" and all its materials? This cannot be undone.`}
978 |   onConfirm={handleDeleteModule}
979 |   confirmLabel="Delete"
980 |   variant="destructive"
981 |   isPending={deleteModule.isPending}
982 | />
983 | </div>
984 | );
985 | };
986 |
987 | export default ModuleManager;
988 |

```

FILE: src/pages/teacher/CourseToolRedirect.tsx

TYPE: .tsx | LINES: 1-45 | SHA256: a4e11798e1b383fbbdb93aa040e07f7a40480b24d2ad131e4b8ecc29313e04a80

```

1 | import { useMemo } from "react";
2 | import { Navigate } from "react-router-dom";
3 |
4 | import { NoData } from "@components/shared/EmptyState";
5 | import { Shimmer } from "@design-system";
6 | import { useAuth } from "@hooks/useAuth";
7 | import { useTeacherCourses } from "@hooks/useCourses";
8 |
9 | interface CourseToolRedirectProps {
10 |   userRole: "teacher" | "coordinator";
11 |   tool: "question-bank" | "discussions";
12 | }
13 |
14 | /**
15 |  * Prototype sidebars expose course tools as global destinations. Production
16 |  * stores those tools per course, so this adapter opens the first real,
17 |  * role-visible course instead of inventing demo content or a broken route.
18 |  */
19 | const CourseToolRedirect = ({ userRole, tool }: CourseToolRedirectProps) => {
20 |   const { user } = useAuth();
21 |   const { data: result, isLoading } = useTeacherCourses();
22 |   const courses = useMemo(() => {
23 |     const visible = result?.data ?? [];
24 |     return userRole === "teacher"
25 |       ? visible.filter((course) => course.teacher_id === user?.id)
26 |       : visible;
27 |   }, [result?.data, user?.id, userRole]);
28 |
29 |   if (isLoading) {
30 |     return (
31 |       <div className="space-y-4">
32 |         <Shimmer className="h-10 w-64 rounded-xl" />
33 |         <Shimmer className="h-72 rounded-[20px]" />
34 |       </div>
35 |     );
36 |   }
37 |
38 |   const course = courses[0];
39 |   if (!course) return <NoData />;
40 |
41 |   return <Navigate replace to={`/${userRole}/courses/${course.id}/${tool}`} />;
42 | };
43 |
44 | export default CourseToolRedirect;
45 |

```

FILE: src/pages/teacher/dashboard/GradingStats.tsx

TYPE: .tsx | LINES: 1-159 | SHA256: ffab0d0d3e63a20b274c4cd9b7de7b48ec9c506542019e878bd54c6ceb1de9a1

```

1 | import { Card } from "@components/ui/card";
2 | import { Shimmer } from "@design-system";
3 | import { useGradingStats } from "@hooks/useGradingStats";
4 | import {
5 |   CheckSquare,
6 |   Clock,
7 |   Inbox,
8 |   Flame,
9 |   type LucideIcon,
10 | } from "lucide-react";
11 | import {
12 |   LineChart,
13 |   Line,
14 |   XAxis,
15 |   YAxis,
16 |   CartesianGrid,
17 |   Tooltip,

```

[illegible]

```

122 |         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500 mb-3">
123 |             Grading Velocity (Last 30 Days)
124 |         </p>
125 |         <ResponsiveContainer width="100%" height={200}>
126 |             <LineChart
127 |                 data={data.velocityTrend}
128 |                 margin={{ top: 5, right: 20, left: 0, bottom: 5 }}
129 |             >
130 |                 <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
131 |                 <XAxis
132 |                     dataKey="date"
133 |                     tick={{ fontSize: 10 }}
134 |                     tickFormatter={(v: string) => v.slice(5)}
135 |                 />
136 |                 <YAxis allowDecimals={false} tick={{ fontSize: 10 }} />
137 |                 <Tooltip content={<VelocityTooltip />} />
138 |                 <Line
139 |                     type="monotone"
140 |                     dataKey="count"
141 |                     stroke="#3b82f6"
142 |                     strokeWidth={2}
143 |                     dot={{ r: 3, fill: "#3b82f6" }}
144 |                     activeDot={{ r: 5 }}
145 |                 />
146 |             </LineChart>
147 |         </ResponsiveContainer>
148 |     </div>
149 | ) : (
150 |     <p className="text-sm text-gray-500 text-center py-4">
151 |         No grading activity in the last 30 days.
152 |     </p>
153 | )}
154 | </Card>
155 | );
156 | };
157 |
158 | export default GradingStats;
159 |

```

FILE: [src/pages/teacher/discussions/DiscussionModeration.tsx](#)

TYPE: .tsx | LINES: 1-195 | SHA256: 2e87d70c113f7cbec41e91c8d03e9a9a0cb67181456dcd76fcd485478c7f2dc9

```

1 | // Task 67.5: Discussion Moderation page for Teachers
2 | // Requirements: 77.3
3 | import { useState } from "react";
4 | import { useParams, useNavigate } from "react-router-dom";
5 | import { Pin, PinOff, Trash2, CheckCircle2, MessageSquare } from "lucide-react";
6 | import { toast } from "sonner";
7 | import { Card } from "@components/ui/card";
8 | import { Button } from "@components/ui/button";
9 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
10 | import {
11 |     useDiscussionThreads,
12 |     useTogglePinThread,
13 |     useDeleteThread,
14 | } from "@hooks/useDiscussions";
15 | import { useAuth } from "@hooks/useAuth";
16 | import { format } from "date-fns";
17 | import { cn } from "@lib/utils";
18 |
19 | interface DiscussionModerationProps {
20 |     basePath?: "/teacher" | "/coordinator";
21 | }
22 |
23 | const DiscussionModeration = ({
24 |     basePath = "/teacher",
25 | }: DiscussionModerationProps) => {
26 |     const { courseId } = useParams<{ courseId: string }>();
27 |     const navigate = useNavigate();
28 |     const { user } = useAuth();
29 |     const {
30 |         data: threadsPages,
31 |         isLoading,
32 |         hasNextPage,
33 |         isFetchingNextPage,
34 |         fetchNextPage,
35 |     } = useDiscussionThreads(courseId);
36 |     const togglePin = useTogglePinThread();
37 |     const deleteThread = useDeleteThread();
38 |     const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
39 |
40 |     const threads = threadsPages?.pages.flatMap((p) => p.threads) ?? [];
41 |
42 |     const handlePin = (threadId: string, currentlyPinned: boolean) => {
43 |         if (!user?.id) return;
44 |         togglePin.mutate(
45 |             { threadId, isPinned: !currentlyPinned, performedBy: user.id },
46 |             {
47 |                 onSuccess: () => {
48 |                     toast.success(currentlyPinned ? "Thread unpinned" : "Thread pinned"),
49 |                     onError: (err) => toast.error(err.message),
50 |                 },
51 |             },
52 |         );
53 |     };
54 |
55 |     const handleDelete = (threadId: string) => {
56 |         if (!user?.id) return;
57 |         deleteThread.mutate(
58 |             { threadId, performedBy: user.id },
59 |             {
60 |                 onSuccess: () => {
61 |                     toast.success("Thread deleted");
62 |                     setDeleteTarget(null);

```

```

63 |         onError: (err) => toast.error(err.message),
64 |     }
65 | );
66 | };
67 |
68 | return (
69 |     <div className="space-y-6">
70 |         <div className="flex items-center justify-between">
71 |             <h1 className="text-2xl font-bold tracking-tight">
72 |                 Discussion Moderation
73 |             </h1>
74 |         </div>
75 |
76 |         {isLoading ? (
77 |             <div className="space-y-3">
78 |                 {Array.from({ length: 3 }).map((_, i) => (
79 |                     <div key={i} className="h-20 rounded-xl animate-shimmer" />
80 |                 ))}
81 |             </div>
82 |         ) : threads.length === 0 ? (
83 |             <Card className="bg-white border-0 shadow-md rounded-xl p-8 text-center">
84 |                 <MessageSquare className="h-10 w-10 text-gray-300 mx-auto mb-3" />
85 |                 <p className="text-sm text-gray-500">
86 |                     No discussion threads in this course.
87 |                 </p>
88 |             </Card>
89 |         ) : (
90 |             <div className="space-y-3">
91 |                 {threads.map((thread) => (
92 |                     <Card
93 |                         key={thread.id}
94 |                         className={cn(
95 |                             "bg-white border-0 shadow-sm rounded-xl p-4",
96 |                             thread.is_pinned && "border border-blue-200 bg-blue-50/30"
97 |                         )}
98 |                     >
99 |                         <div className="flex items-start justify-between gap-3">
100 |                             <div
101 |                                 className="flex-1 min-w-0 cursor-pointer"
102 |                                 role="button"
103 |                                 tabIndex={0}
104 |                                 onClick={() =>
105 |                                     navigate(
106 |                                         `${basePath}/courses/${courseId}/discussions/${thread.id}`
107 |                                     )
108 |                                 }
109 |                                 onKeyDown={(e) => {
110 |                                     if (e.key === "Enter")
111 |                                         navigate(
112 |                                             `${basePath}/courses/${courseId}/discussions/${thread.id}`
113 |                                         );
114 |                                 }}
115 |                             >
116 |                                 <div className="flex items-center gap-2">
117 |                                     {thread.is_pinned && (
118 |                                         <Pin className="h-3 w-3 text-blue-500 shrink-0" />
119 |                                     )}
120 |                                     <h3 className="text-sm font-bold truncate">
121 |                                         {thread.title}
122 |                                     </h3>
123 |                                     {thread.is_resolved && (
124 |                                         <span className="flex items-center gap-0.5 text-[10px] font-bold tracking-widest uppercase">
125 |                                             <CheckCircle2 className="h-3 w-3" /> Resolved
126 |                                         </span>
127 |                                     )}
128 |                                 </div>
129 |                                 <p className="text-xs text-gray-400 mt-1">
130 |                                     {format(new Date(thread.created_at), "MMM d, yyyy")} · {" "}
131 |                                     {thread.reply_count ?? 0} replies
132 |                                 </p>
133 |                             </div>
134 |                             <div className="flex items-center gap-1 shrink-0">
135 |                                 <Button
136 |                                     variant="ghost"
137 |                                     size="sm"
138 |                                     onClick={() => handlePin(thread.id, thread.is_pinned)}
139 |                                     disabled={togglePin.isPending}
140 |                                     aria-label={
141 |                                         thread.is_pinned ? "Unpin thread" : "Pin thread"
142 |                                     }
143 |                                 >
144 |                                     {thread.is_pinned ? (
145 |                                         <PinOff className="h-4 w-4" />
146 |                                     ) : (
147 |                                         <Pin className="h-4 w-4" />
148 |                                     )}
149 |                                 </Button>
150 |                                 <Button
151 |                                     variant="ghost"
152 |                                     size="sm"
153 |                                     onClick={() => setDeleteTarget(thread.id)}
154 |                                     className="text-red-500 hover:text-red-600"
155 |                                     aria-label="Delete thread"
156 |                                 >
157 |                                     <Trash2 className="h-4 w-4" />
158 |                                 </Button>
159 |                             </div>
160 |                         </div>
161 |                     </Card>
162 |                 ))}
163 |                 {hasNextPage && (
164 |                     <div className="flex justify-center pt-2">
165 |                         <Button
166 |                             variant="outline"

```

```

167 |         onClick={() => fetchNextPage()}
168 |         disabled={isFetchingNextPage}
169 |       >
170 |         {isFetchingNextPage ? "Loading..." : "Load more"}
171 |       </Button>
172 |     </div>
173 |   )}
174 | </div>
175 | })
176 |
177 | <ConfirmDialog
178 |   open={!deleteTarget}
179 |   onOpenChange={(open) => {
180 |     if (!open) setDeleteTarget(null);
181 |   }}
182 |   title="Delete Thread"
183 |   description="This will permanently delete this thread and all its replies. This action cannot be undone"
184 |   variant="destructive"
185 |   isPending={deleteThread.isPending}
186 |   onConfirm={() => {
187 |     if (deleteTarget) handleDelete(deleteTarget);
188 |   }}
189 | />
190 | </div>
191 | );
192 | };
193 |
194 | export default DiscussionModeration;
195 |

```

FILE: src/pages/teacher/gradebook/GradebookView.tsx

```
TYPE: .tsx | LINES: 1-506 | SHA256: 7976736e9d2529c2f66a1ea30df59109b1bf09c9bdc58ff3227025409fd66214
```

[illegible]

```

72 | );
73 | const { data: sections = [] } = useCourseSections(courseId || undefined);
74 | const { data: categories = [] } = useGradeCategories(courseId || undefined);
75 | const { data: gradebookData = [], isLoading: gradebookLoading } =
76 |   useGradebookMatrix(courseId || undefined, sectionId || undefined);
77 | const { data: settings } = useInstitutionSettings();
78 | const visibleCategories = useMemo(
79 |   () =>
80 |     categories.length > 0
81 |       ? categories
82 |       : (gradebookData[0]?.categories ?? []).map((category) => ({
83 |         id: category.category_id,
84 |         name: category.category_name,
85 |         weight_percent: category.weight_percent,
86 |       })),
87 |   [categories, gradebookData]
88 | );
89 |
90 | // Req 13.1: auto-load the first owned course. Also replace a stale or
91 | // institution-wide course id left in the URL so teachers never open another
92 | // instructor's gradebook through shared query state.
93 | useEffect(() => {
94 |   const selectedCourseIsOwned = courses.some(
95 |     (course) => course.id === courseId
96 |   );
97 |   if (
98 |     !coursesLoading &&
99 |     courses.length > 0 &&
100 |     (!courseId || !selectedCourseIsOwned)
101 |   ) {
102 |     const first = courses[0];
103 |     if (first) {
104 |       void setCourseId(first.id);
105 |       void setSectionId("");
106 |     }
107 |   }
108 | }, [courseId, coursesLoading, courses, setCourseId, setSectionId]);
109 |
110 | const gradeScales: GradeScale[] =
111 |   settings?.grade_scales ?? DEFAULT_GRADE_SCALES;
112 |
113 | // Resolve letter grades using institution grade scales
114 | const enrichedData = useMemo(
115 |   () =>
116 |     gradebookData.map((entry) => ({
117 |       ...entry,
118 |       letter_grade: mapToLetterGrade(entry.final_weighted_grade, gradeScales),
119 |     })),
120 |   [gradebookData, gradeScales]
121 | );
122 |
123 | // Req 13.3: class-average row computed from the displayed matrix.
124 | const classAverages = useMemo(
125 |   () => computeClassAverages(enrichedData),
126 |   [enrichedData]
127 | );
128 | const classAverageLetter = useMemo(
129 |   () => mapToLetterGrade(classAverages.finalAvg, gradeScales),
130 |   [classAverages.finalAvg, gradeScales]
131 | );
132 |
133 | const totalWeight = visibleCategories.reduce(
134 |   (sum, category) => sum + category.weight_percent,
135 |   0
136 | );
137 | const isBalanced = totalWeight === 100;
138 |
139 | const selectedCourse = courses.find((c) => c.id === courseId);
140 | const canExport = enrichedData.length > 0;
141 |
142 | // Req 13.2 + 13.6: reuse the existing CSV export pattern (`downloadCsv`).
143 | const handleExportCsv = () => {
144 |   if (!canExport) return;
145 |   const csv = buildGradebookCsv(
146 |     enrichedData,
147 |     classAverages,
148 |     classAverageLetter
149 |   );
150 |   const slug = selectedCourse?.code ?? "gradebook";
151 |   downloadCsv(csv, `gradebook-${slug}.csv`);
152 | };
153 |
154 | return (
155 |   <div className="space-y-6">
156 |     {/* Page Header */}
157 |     <div className="flex items-center justify-between">
158 |       <h1 className="text-2xl font-bold tracking-tight">Gradebook</h1>
159 |       <Button
160 |         variant="outline"
161 |         size="sm"
162 |         disabled={!canExport}
163 |         onClick={handleExportCsv}
164 |       >
165 |         <Download className="h-4 w-4" />
166 |         Export CSV
167 |       </Button>
168 |     </div>
169 |
170 |     {/* Filters */}
171 |     <div className="flex items-center gap-4">
172 |       <Select
173 |         value={courseId}
174 |         onChange={(v) => {
175 |           setCourseId(v);

```

[illegible]


```

280 |     category_name: string;
281 |     weight_percent: number;
282 |     assessments: Array<{
283 |       id: string;
284 |       title: string;
285 |       score: number | null;
286 |       max_score: number;
287 |     }>;
288 |     subtotal_percent: number;
289 |   }>;
290 |   final_weighted_grade: number;
291 |   letter_grade: string;
292 | }>;
293 | categories: Array<{
294 |   id: string;
295 |   name: string;
296 |   weight_percent: number;
297 | }>;
298 | classAverages: ClassAverages;
299 | classAverageLetter: string;
300 | }
301 |
302 | const GradebookTable = ({
303 |   data,
304 |   categories,
305 |   classAverages,
306 |   classAverageLetter,
307 | }: GradebookTableProps) => {
308 |   const firstRow = data[0] as (typeof data)[number] | undefined;
309 |
310 |   return (
311 |     <div className="overflow-auto rounded-xl border border-slate-200 bg-white shadow-md">
312 |       <table className="w-full text-sm">
313 |         <thead>
314 |           { /* Category header row */ }
315 |           <tr className="bg-slate-50 border-b border-slate-200">
316 |             <th
317 |               rowSpan={2}
318 |               className="sticky start-0 bg-slate-50 px-4 py-2 text-start font-medium text-gray-600 z-10 min-w-
319 |             >
320 |               Student
321 |             </th>
322 |             {categories.map((cat) => {
323 |               const colCount = firstRow
324 |                 ? (firstRow.categories.find((c) => c.category_id === cat.id)
325 |                   ?.assessments.length ?? 0) + 1
326 |                 : 1;
327 |               return (
328 |                 <th
329 |                   key={cat.id}
330 |                   colSpan={colCount}
331 |                   className="px-2 py-2 text-center font-bold text-gray-700 border-s border-slate-200"
332 |                 >
333 |                   {cat.name}
334 |                   <Badge variant="secondary" className="ms-1 text-[10px]">
335 |                     {cat.weight_percent}%
336 |                   </Badge>
337 |                 </th>
338 |               );
339 |             })}
340 |             <th
341 |               rowSpan={2}
342 |               className="px-3 py-2 text-center font-bold text-gray-700 border-s border-slate-200 min-w-[80px]"
343 |             >
344 |               Final %
345 |             </th>
346 |             <th
347 |               rowSpan={2}
348 |               className="px-3 py-2 text-center font-bold text-gray-700 border-s border-slate-200 min-w-[60px]"
349 |             >
350 |               Grade
351 |             </th>
352 |           </tr>
353 |           { /* Assessment header row */ }
354 |           <tr className="bg-slate-50">
355 |             {categories.map((cat) => {
356 |               const catData = firstRow
357 |                 ? firstRow.categories.find((c) => c.category_id === cat.id)
358 |                 : undefined;
359 |               const assessments = catData?.assessments ?? [];
360 |               return [
361 |                 ...assessments.map((a) => (
362 |                   <th
363 |                     key={a.id}
364 |                     className="px-2 py-1 text-center font-medium text-gray-500 whitespace-nowrap border-s bord
365 |                   >
366 |                     <div
367 |                       className="truncate max-w-[90px] text-xs"
368 |                       title={a.title}
369 |                     >
370 |                       {a.title}
371 |                     </div>
372 |                     <div className="text-[10px] text-gray-400 font-normal">
373 |                       {a.max_score}
374 |                     </div>
375 |                   </th>
376 |                 );
377 |                 <th
378 |                   key={`_${cat.id}-subtotal`}
379 |                   className="px-2 py-1 text-center font-bold text-gray-600 whitespace-nowrap border-s border-s
380 |                 >
381 |                   <div className="text-xs">Subtotal</div>
382 |                 </th>,
383 |               ];

```

```

384     }}}
385   </tr>
386 </thead>
387 <tbody>
388   {data.map((student) => (
389     <tr
390       key={student.student_id}
391       className="border-t border-slate-100 hover:bg-slate-50/50"
392     >
393       <td className="sticky start-0 bg-white px-4 py-2 font-medium truncate max-w-[160px] z-10">
394         {student.student_name}
395       </td>
396       {student.categories.map((cat) => [
397         ...cat.assessments.map((a) => (
398           <td
399             key={a.id}
400             className={cn(
401               "px-2 py-2 text-center font-medium tabular-nums border-s border-slate-100",
402               getCellBg(a.score, a.max_score)
403             )}
404           >
405             {a.score !== null ? a.score : "-"}
406           </td>
407         )},
408         <td
409           key={` ${cat.category_id}-sub`}
410           className="px-2 py-2 text-center font-bold tabular-nums border-s border-slate-200 bg-slate-5"
411         >
412           <span className={getGradeColor(cat.subtotal_percent)}>
413             {cat.subtotal_percent.toFixed(1)}%
414           </span>
415         </td>,
416       )]}
417       <td className="px-3 py-2 text-center font-bold tabular-nums border-s border-slate-200">
418         <span className={getGradeColor(student.final_weighted_grade)}>
419           {student.final_weighted_grade.toFixed(1)}%
420         </span>
421       </td>
422       <td className="px-3 py-2 text-center border-s border-slate-200">
423         <Badge
424           className={cn(
425             "text-xs font-bold",
426             student.final_weighted_grade >= 85
427               ? "bg-green-50 text-green-600 border-green-200"
428               : student.final_weighted_grade >= 70
429               ? "bg-blue-50 text-blue-600 border-blue-200"
430               : student.final_weighted_grade >= 50
431               ? "bg-yellow-50 text-yellow-600 border-yellow-200"
432               : "bg-red-50 text-red-600 border-red-200"
433           )}
434           variant="outline"
435         >
436           {student.letter_grade}
437         </Badge>
438       </td>
439     </tr>
440   )}}
441 </tbody>
442 { /* Class-average row computed from the displayed matrix (Req 13.3) */ }
443 <tfoot>
444   <tr className="border-t-2 border-slate-300 bg-slate-100 font-bold">
445     <td className="sticky start-0 bg-slate-100 px-4 py-2 z-10">
446       Class Average
447     </td>
448     {(firstRow?.categories ?? []).map((cat) => [
449       ...cat.assessments.map((a) => {
450         const avg = classAverages.assessmentAvg.get(a.id);
451         return (
452           <td
453             key={` avg-${a.id}`}
454             className="px-2 py-2 text-center tabular-nums border-s border-slate-200 text-gray-700"
455           >
456             {avg !== null && avg !== undefined ? avg : "-"}
457           </td>
458         );
459       }},
460       <td
461         key={` avg-${cat.category_id}-sub`}
462         className="px-2 py-2 text-center tabular-nums border-s border-slate-200 bg-slate-200"
463       >
464         <span
465           className={getGradeColor(
466             classAverages.categoryAvg.get(cat.category_id) ?? 0
467           )}
468         >
469           {(
470             classAverages.categoryAvg.get(cat.category_id) ?? 0
471           ).toFixed(1)}
472         %
473       </span>
474     </td>,
475   )]}
476   <td className="px-3 py-2 text-center tabular-nums border-s border-slate-200">
477     <span className={getGradeColor(classAverages.finalAvg)}>
478       {classAverages.finalAvg.toFixed(1)}%
479     </span>
480   </td>
481   <td className="px-3 py-2 text-center border-s border-slate-200">
482     <Badge
483       className={cn(
484         "text-xs font-bold",
485         classAverages.finalAvg >= 85
486           ? "bg-green-50 text-green-600 border-green-200"
487           : classAverages.finalAvg >= 70

```

```

488 |         ? "bg-blue-50 text-blue-600 border-blue-200"
489 |         : classAverages.finalAvg >= 50
490 |         ? "bg-yellow-50 text-yellow-600 border-yellow-200"
491 |         : "bg-red-50 text-red-600 border-red-200"
492 |     }}
493 |     variant="outline"
494 | >
495 |     {classAverageLetter}
496 | </Badge>
497 | </td>
498 | </tr>
499 | </tfoot>
500 | </table>
501 | </div>
502 | );
503 | };
504 |
505 | export default GradebookView;
506 |

```

FILE: src/pages/teacher/gradebook/GradeCategoryManager.tsx

TYPE: .tsx | LINES: 1-402 | SHA256: b1db7ddcfd3bb90b8eeecba0c8569b835a5f55c334795077b116ef41edc5410a

[illegible]

```

82 |     weight_percent: Math.max(remainingWeight, 0),
83 |   });
84 |   setCreateDialogOpen(true);
85 | };
86 |
87 | const handleCreate = (values: CategoryFormValues) => {
88 |   if (totalWeight + values.weight_percent > 100) {
89 |     createForm.setError("weight_percent", {
90 |       message: `Weight would exceed 100%. Remaining: ${remainingWeight}%`,
91 |     });
92 |     return;
93 |   }
94 |
95 |   createMutation.mutate(
96 |     {
97 |       course_id: courseId,
98 |       name: values.name,
99 |       weight_percent: values.weight_percent,
100 |       sort_order: categories.length,
101 |     },
102 |     {
103 |       onSuccess: () => {
104 |         setCreateDialogOpen(false);
105 |         createForm.reset();
106 |       },
107 |     }
108 |   );
109 | };
110 |
111 | return (
112 |   <div className="space-y-4">
113 |     <div className="flex items-center justify-between">
114 |       <div>
115 |         <h3 className="text-lg font-bold tracking-tight">Grade Categories</h3>
116 |         <p className="text-xs text-gray-500 mt-1">
117 |           Define weighted categories. Weights must sum to 100%.
118 |         </p>
119 |       </div>
120 |       <Button
121 |         onClick={openCreateDialog}
122 |         size="sm"
123 |         variant="tactile"
124 |         disabled={isBalanced}
125 |       >
126 |         <Plus className="h-4 w-4" /> Add Category
127 |       </Button>
128 |     </div>
129 |
130 |     {/ * Create dialog */}
131 |     <Dialog open={createDialogOpen} onOpenChange={setCreateDialogOpen}>
132 |       <DialogContent>
133 |         <DialogHeader>
134 |           <DialogTitle>Add Grade Category</DialogTitle>
135 |         </DialogHeader>
136 |         <CategoryForm
137 |           form={createForm}
138 |           onSubmit={handleCreate}
139 |           isPending={createMutation.isPending}
140 |           submitLabel="Create"
141 |         />
142 |       </DialogContent>
143 |     </Dialog>
144 |
145 |     {/ * Edit dialog */}
146 |     {editingCategory && (
147 |       <EditCategoryDialog
148 |         category={editingCategory}
149 |         categories={categories}
150 |         onClose={() => setEditingCategory(null)}
151 |       />
152 |     )}
153 |
154 |     {/ * Weight summary bar */}
155 |     <WeightSummaryBar totalWeight={totalWeight} isBalanced={isBalanced} />
156 |
157 |     {/ * Category list */}
158 |     {isLoading ? (
159 |       <div className="flex items-center justify-center py-8">
160 |         <Loader2 className="h-5 w-5 animate-spin text-gray-400" />
161 |       </div>
162 |     ) : categories.length === 0 ? (
163 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6 text-center text-gray-500 text-sm">
164 |         No grade categories defined yet. Add categories to start building the
165 |         gradebook.
166 |       </Card>
167 |     ) : (
168 |       <div className="space-y-2">
169 |         {categories.map((cat) => (
170 |           <CategoryCard
171 |             key={cat.id}
172 |             category={cat}
173 |             onEdit={() => setEditingCategory(cat)}
174 |             onDelete={() => deleteMutation.mutate(cat.id)}
175 |             isDeleting={deleteMutation.isPending}
176 |           />
177 |         ))}
178 |       </div>
179 |     )}
180 |   </div>
181 | );
182 | };
183 |
184 | // % % % EditCategoryDialog – owns the update hook with a stable id % % % % % % % % % %
185 |

```

[illegible]

[illegible]

```

394         >
395         <Trash2 className="h-4 w-4 text-red-500" />
396     </Button>
397 </div>
398 </Card>
399 );
400
401 export default GradeCategoryManager;
402

```

FILE: src/pages/teacher/grading/GradingInterface.tsx

TYPE: .tsx | LINES: 1-971 | SHA256: 6b0e41c7ea244c3689a403d10a8a058ef90bb44dea60c680257333b0486fe244

[illegible]

[illegible]


```

196 |
197 | interface RubricGridProps {
198 |   criteria: RubricCriterion[];
199 |   selections: Map<string, CellSelection>;
200 |   onCellSelect: (
201 |     criterionId: string,
202 |     levelIndex: number,
203 |     points: number
204 |   ) => void;
205 |   isReadOnly: boolean;
206 | }
207 |
208 | const RubricGrid = ({
209 |   criteria,
210 |   selections,
211 |   onCellSelect,
212 |   isReadOnly,
213 | }: RubricGridProps) => {
214 |   const levelLabels = useMemo(() => {
215 |     if (criteria.length === 0) return [];
216 |     const first = criteria[0];
217 |     return first ? first.levels.map((l) => l.label) : [];
218 |   }, [criteria]);
219 |
220 |   return (
221 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6 space-y-4">
222 |       <h2 className="text-lg font-bold tracking-tight">Rubric Assessment</h2>
223 |
224 |       <div className="overflow-x-auto">
225 |         <table className="w-full border-collapse">
226 |           <thead>
227 |             <tr>
228 |               <th className="text-start text-xs font-bold text-gray-500 uppercase tracking-wider p-3 w-40">
229 |                 Criteria
230 |               </th>
231 |               {levelLabels.map((label) => (
232 |                 <th
233 |                   key={label}
234 |                   className="text-center text-xs font-bold text-gray-500 uppercase tracking-wider p-3"
235 |                 >
236 |                   {label}
237 |                 </th>
238 |               ))}
239 |             </tr>
240 |           </thead>
241 |           <tbody>
242 |             {criteria.map((criterion) => (
243 |               <tr key={criterion.id} className="border-t border-slate-100">
244 |                 <td className="p-3 align-top">
245 |                   <span className="text-sm font-semibold">
246 |                     {criterion.criterion_name}
247 |                   </span>
248 |                 </td>
249 |                 {criterion.levels.map((level, levelIdx) => {
250 |                   const isSelected =
251 |                     selections.get(criterion.id)?.levelIndex === levelIdx;
252 |                   return (
253 |                     <td key={levelIdx} className="p-2 align-top">
254 |                       <button
255 |                         type="button"
256 |                         onClick={() =>
257 |                           onCellSelect(criterion.id, levelIdx, level.points)
258 |                         }
259 |                         disabled={isReadOnly}
260 |                         aria-pressed={isSelected}
261 |                         aria-label={` ${criterion.criterion_name}: ${level.label} – ${level.points} points`}
262 |                         className={cn(
263 |                           "w-full rounded-lg border-2 p-3 text-start transition-all focus:outline-none focus:r
264 |                             isSelected
265 |                             ? "border-blue-500 bg-blue-50"
266 |                             : "border-slate-200 bg-white",
267 |                           !isReadOnly &&
268 |                           !isSelected &&
269 |                           "hover:bg-slate-50 hover:border-slate-300",
270 |                           isReadOnly && "cursor-default"
271 |                         )}
272 |                     >
273 |                       <div className="flex items-center justify-between mb-1">
274 |                         <Badge
275 |                           className="bg-blue-100 text-blue-700 text-xs"
276 |                           variant="outline"
277 |                         >
278 |                           {level.points} pts
279 |                         </Badge>
280 |                         {isSelected && (
281 |                           <Check className="h-4 w-4 text-blue-600" />
282 |                         )}
283 |                       </div>
284 |                       <p className="text-xs text-gray-600 leading-relaxed">
285 |                         {level.description}
286 |                       </p>
287 |                     </button>
288 |                   </td>
289 |                 )};
290 |             </tr>
291 |           </tbody>
292 |         </table>
293 |       </div>
294 |     </Card>
295 |   );
296 | };
297 |
298 | };
299 |

```

[illegible]

[illegible]

[illegible]

```

612         setAiOverallDraft(data.overall_draft);
613         toast.success("AI feedback drafts generated");
614     },
615     onError: (err) =>
616         toast.error(`Draft generation failed: ${err.message}`),
617 }
618 );
619 };
620
621 const logDraft = (
622     criterionId: string,
623     action: "accepted" | "edited" | "rejected",
624     text: string
625 ) => {
626     if (!submission?.student_id) return;
627     logDraftAction.mutate({
628         student_id: submission.student_id,
629         suggestion_type: "feedback_draft",
630         suggestion_text: text,
631         suggestion_data: {
632             criterion_id: criterionId,
633             submission_id: submissionId,
634         },
635         feedback: action === "rejected" ? "thumbs_down" : "thumbs_up",
636         validated_outcome: action,
637     });
638 };
639
640 const handleAcceptDraft = (criterionId: string) => {
641     const draft = aiDrafts.find((d) => d.criterion_id === criterionId);
642     setAiDrafts((prev) =>
643         prev.map((d) =>
644             d.criterion_id === criterionId
645             ? { ...d, status: "accepted" as DraftStatus }
646             : d
647         )
648     );
649     if (draft) {
650         setFeedback((prev) => {
651             const prefix = prev ? `${prev}\n\n` : "";
652             return `${prefix}${draft.criterion_title}: ${draft.draft_comment}`;
653         });
654         logDraft(criterionId, "accepted", draft.draft_comment);
655     }
656 };
657
658 const handleEditDraft = (criterionId: string) => {
659     setAiDrafts((prev) =>
660         prev.map((d) =>
661             d.criterion_id === criterionId
662             ? { ...d, status: "editing" as DraftStatus }
663             : d
664         )
665     );
666 };
667
668 const handleEditChange = (criterionId: string, text: string) => {
669     setAiDrafts((prev) =>
670         prev.map((d) =>
671             d.criterion_id === criterionId ? { ...d, edited_comment: text } : d
672         )
673     );
674 };
675
676 const handleEditConfirm = (criterionId: string) => {
677     const draft = aiDrafts.find((d) => d.criterion_id === criterionId);
678     if (!draft) return;
679     setAiDrafts((prev) =>
680         prev.map((d) =>
681             d.criterion_id === criterionId
682             ? {
683                 ...d,
684                 draft_comment: d.edited_comment,
685                 status: "accepted" as DraftStatus,
686             }
687             : d
688         )
689     );
690     setFeedback((prev) => {
691         const prefix = prev ? `${prev}\n\n` : "";
692         return `${prefix}${draft.criterion_title}: ${draft.edited_comment}`;
693     });
694     logDraft(criterionId, "edited", draft.edited_comment);
695 };
696
697 const handleRejectDraft = (criterionId: string) => {
698     const draft = aiDrafts.find((d) => d.criterion_id === criterionId);
699     setAiDrafts((prev) =>
700         prev.map((d) =>
701             d.criterion_id === criterionId
702             ? { ...d, status: "rejected" as DraftStatus }
703             : d
704         )
705     );
706     if (draft) {
707         logDraft(criterionId, "rejected", draft.draft_comment);
708     }
709 };
710
711 const handleAcceptOverallDraft = () => {
712     if (aiOverallDraft) {
713         setFeedback(aiOverallDraft);
714         toast.success("Overall draft applied to feedback");
715     }

```

[illegible]

```

820 {isReadOnly && (
821   <Badge
822     className="bg-green-100 text-green-700 border-green-200"
823     variant="outline"
824   >
825     Graded
826   </Badge>
827 )}
828 </div>
829
830 <div className="grid grid-cols-1 lg:grid-cols-4 gap-6">
831   {/* Left Panel */}
832   <SubmissionInfoPanel submission={submission} assignment={assignment} />
833
834   {/* Main Panel */}
835   <div className="lg:col-span-3 space-y-6">
836     {rubric ? (
837       <RubricGrid
838         criteria={rubric.criteria}
839         selections={activeSelections}
840         onCellSelect={handleCellSelect}
841         isReadOnly={isReadOnly}
842       />
843     ) : (
844       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
845         <p className="text-gray-500">
846           No rubric linked to this assignment.
847         </p>
848       </Card>
849     )}
850
851     {/* Generate AI Draft Button */}
852     {!isReadOnly && rubric && selections.size > 0 && (
853       <Button
854         onClick={handleGenerateAIDraft}
855         disabled={generateDraft.isPending}
856         variant="outline"
857         className="border-teal-300 text-teal-700 hover:bg-teal-50"
858       >
859         {generateDraft.isPending ? (
860           <Loader2 className="h-4 w-4 animate-spin" />
861         ) : (
862           <Sparkles className="h-4 w-4" />
863         )}
864         Generate AI Draft
865       </Button>
866     )}
867
868     {/* AI Draft Panel */}
869     {aiDrafts.length > 0 && (
870       <AIDraftPanel
871         drafts={aiDrafts}
872         overallDraft={aiOverallDraft}
873         onAccept={handleAcceptDraft}
874         onEdit={handleEditDraft}
875         onReject={handleRejectDraft}
876         onEditChange={handleEditChange}
877         onEditConfirm={handleEditConfirm}
878         onAcceptOverall={handleAcceptOverallDraft}
879       />
880     )}
881
882     {/* Score Summary */}
883     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
884       <div className="flex items-center gap-8">
885         <div>
886           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
887             Total Score
888           </p>
889           <p className="text-2xl font-black mt-1">
890             {totalScore} / {totalMarks}
891           </p>
892         </div>
893         <div>
894           <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
895             Percentage
896           </p>
897           <p
898             className={cn(
899               "text-2xl font-black mt-1",
900               getScoreColor(scorePercent)
901             )}
902           >
903             {scorePercent}%
904           </p>
905         </div>
906       </div>
907       <div>
908         <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
909           Attainment
910         </p>
911         <Badge
912           className={cn(
913             "mt-1 text-xs font-bold",
914             getAttainmentBadgeStyle(scorePercent)
915           )}
916           variant="outline"
917         >
918           {getAttainmentLabel(scorePercent)}
919         </Badge>
920       </div>
921     </Card>
922
923     {/* Feedback */}

```

```

924 |         <Card className="bg-white border-0 shadow-md rounded-xl p-6 space-y-4">
925 |             <label className="text-sm font-semibold" htmlFor="overall-feedback">
926 |                 Overall Feedback
927 |             </label>
928 |             {isReadOnly ? (
929 |                 <p className="text-sm text-gray-700 whitespace-pre-wrap">
930 |                     {existingGrade?.overall_feedback || "No feedback provided."}
931 |                 </p>
932 |             ) : (
933 |                 <Textarea
934 |                     id="overall-feedback"
935 |                     placeholder="Provide overall feedback for the student..."
936 |                     value={feedback}
937 |                     onChange={(e) => setFeedback(e.target.value)}
938 |                     rows={4}
939 |                 />
940 |             )}
941 |         </Card>
942 |
943 |         {/* Actions */}
944 |         {!isReadOnly && (
945 |             <div className="flex items-center gap-4">
946 |                 <Button
947 |                     onClick={handleSubmitGrade}
948 |                     disabled={createGrade.isPending || selections.size === 0}
949 |                     variant="tactile"
950 |                 >
951 |                     {createGrade.isPending && (
952 |                         <Loader2 className="h-4 w-4 animate-spin" />
953 |                     )}
954 |                     Submit Grade
955 |                 </Button>
956 |                 <Button
957 |                     variant="outline"
958 |                     onClick={() => navigate("/teacher/grading")}
959 |                 >
960 |                     Cancel
961 |                 </Button>
962 |             </div>
963 |         )}
964 |     </div>
965 | </div>
966 | </div>
967 | );
968 | };
969 |
970 | export default GradingInterface;
971 |

```

FILE: [src/pages/teacher/grading/gradingQueueColumns.tsx](#)

TYPE: .tsx | LINES: 1-130 | SHA256: fc98460ab9e51900cbdc4a9f0848e1a50fd85b853e5ba6bb0f3103ae4fd7852a

```

1 | import { type ColumnDef } from "@tanstack/react-table";
2 | import { format } from "date-fns";
3 | import { ArrowUpDown, ClipboardCheck } from "lucide-react";
4 | import { Badge } from "@components/ui/badge";
5 | import { Button } from "@components/ui/button";
6 | import { Link } from "react-router-dom";
7 | import type { SubmissionWithRelations } from "@hooks/useSubmissions";
8 |
9 | export const gradingQueueColumns: ColumnDef<SubmissionWithRelations>[] = [
10 |     {
11 |         id: "student_name",
12 |         header: ({ column }) => (
13 |             <Button
14 |                 variant="ghost"
15 |                 size="sm"
16 |                 className="-ms-3"
17 |                 onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
18 |             >
19 |                 Student
20 |                 <ArrowUpDown className="h-4 w-4" />
21 |             </Button>
22 |         ),
23 |         accessorFn: (row) => row.profiles?.full_name ?? "Unknown",
24 |         cell: ({ row }) => (
25 |             <span className="font-medium">
26 |                 {row.original.profiles?.full_name ?? "Unknown"}
27 |             </span>
28 |         ),
29 |     },
30 |     {
31 |         id: "assignment_title",
32 |         header: ({ column }) => (
33 |             <Button
34 |                 variant="ghost"
35 |                 size="sm"
36 |                 className="-ms-3"
37 |                 onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
38 |             >
39 |                 Assignment
40 |                 <ArrowUpDown className="h-4 w-4" />
41 |             </Button>
42 |         ),
43 |         accessorFn: (row) => row.assignments?.title ?? "Unknown",
44 |         cell: ({ row }) => (
45 |             <span className="text-sm">
46 |                 {row.original.assignments?.title ?? "Unknown"}
47 |             </span>
48 |         ),
49 |     },
50 |     {
51 |         accessorKey: "submitted_at",
52 |         header: ({ column }) => (

```



```

53 |         <Button
54 |             variant="ghost"
55 |             size="sm"
56 |             className="-ms-3"
57 |             onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
58 |         >
59 |             Submitted At
60 |             <ArrowUpDown className="h-4 w-4" />
61 |         </Button>
62 |     ),
63 |     cell: ({ row }) => (
64 |         <span className="text-sm">
65 |             {format(
66 |                 new Date(row.getValue("submitted_at") as string),
67 |                 "MMM d, yyyy h:mm a"
68 |             )}
69 |         </span>
70 |     ),
71 | },
72 | {
73 |     accessorKey: "is_late",
74 |     header: "Timing",
75 |     cell: ({ row }) => {
76 |         const isLate = row.getValue("is_late") as boolean;
77 |         return isLate ? (
78 |             <Badge
79 |                 className="bg-red-100 text-red-700 border-red-200"
80 |                 variant="outline"
81 |             >
82 |                 Late
83 |             </Badge>
84 |         ) : (
85 |             <Badge
86 |                 className="bg-green-100 text-green-700 border-green-200"
87 |                 variant="outline"
88 |             >
89 |                 On Time
90 |             </Badge>
91 |         );
92 |     },
93 | },
94 | {
95 |     id: "status",
96 |     header: "Status",
97 |     cell: ({ row }) => {
98 |         const isGraded =
99 |             Array.isArray(row.original.grades) && row.original.grades.length > 0;
100 |         return isGraded ? (
101 |             <Badge
102 |                 className="bg-green-100 text-green-700 border-green-200"
103 |                 variant="outline"
104 |             >
105 |                 Graded
106 |             </Badge>
107 |         ) : (
108 |             <Badge
109 |                 className="bg-yellow-100 text-yellow-700 border-yellow-200"
110 |                 variant="outline"
111 |             >
112 |                 Pending
113 |             </Badge>
114 |         );
115 |     },
116 | },
117 | {
118 |     id: "actions",
119 |     header: "",
120 |     cell: ({ row }) => (
121 |         <Button asChild size="sm" variant="tactile">
122 |             <Link to={`/teacher/grading/${row.original.id}`}>
123 |                 <ClipboardCheck className="h-4 w-4" />
124 |             </Link>
125 |         </Button>
126 |     ),
127 | },
128 | ];
129 |
130 |

```

FILE: [src/pages/teacher/grading/GradingQueuePage.tsx](#)

TYPE: .tsx | LINES: 1-160 | SHA256: 663cc4187cc318e017ba5c84779f0a5a101277ddae18ec729827f197df1ba359

```

1 | import { parseAsString, useQueryState } from "nuqs";
2 | import { useState } from "react";
3 | import { DataTable } from "@components/shared/DataTable";
4 | import { useSubmissions } from "@hooks/useSubmissions";
5 | import { useCourses } from "@hooks/useCourses";
6 | import { useAssignments } from "@hooks/useAssignments";
7 | import { useCourseSections } from "@hooks/useCourseSections";
8 | import { gradingQueueColumns } from "../gradingQueueColumns";
9 | import {
10 |     Select,
11 |     SelectContent,
12 |     SelectItem,
13 |     SelectTrigger,
14 |     SelectValue,
15 | } from "@components/ui/select";
16 | import { NoCourses, NoSubmissions } from "@components/shared/EmptyState";
17 | import { useAuth } from "@hooks/useAuth";
18 |
19 | const GradingQueuePage = () => {
20 |     const { user } = useAuth();
21 |     const [courseId, setCourseId] = useQueryState(
22 |         "course",

```

```

23 |     parseAsString.withDefault("")
24 | );
25 | const [assignmentId, setAssignmentId] = useQueryState(
26 |   "assignment",
27 |   parseAsString.withDefault("")
28 | );
29 | const [sectionId, setSectionId] = useQueryState(
30 |   "section",
31 |   parseAsString.withDefault("")
32 | );
33 | const [page, setPage] = useState(1);
34 |
35 | const { data: paginatedCourses } = useCourses({
36 |   teacherId: user?.id,
37 |   pageSize: 100,
38 | });
39 | const courses = paginatedCourses?.data;
40 | const { data: paginatedAssignments } = useAssignments(courseId || undefined);
41 | const { data: sections } = useCourseSections(courseId || undefined);
42 | const {
43 |   data: paginatedSubmissions,
44 |   isLoading,
45 |   isFetching,
46 | } = useSubmissions({
47 |   courseId: courseId || undefined,
48 |   courseIds: courseId
49 |     ? undefined
50 |     : (courses ?? []).map((course) => course.id),
51 |   assignmentId: assignmentId || undefined,
52 |   sectionId: sectionId || undefined,
53 |   pendingOnly: true,
54 |   page,
55 | });
56 |
57 | const assignments = paginatedAssignments?.data;
58 | const submissions = paginatedSubmissions?.data ?? [];
59 |
60 | const handleCourseChange = (value: string) => {
61 |   setCourseId(value === "all" ? "" : value);
62 |   setAssignmentId("");
63 |   setSectionId("");
64 |   setPage(1);
65 | };
66 |
67 | const handleAssignmentChange = (value: string) => {
68 |   setAssignmentId(value === "all" ? "" : value);
69 |   setPage(1);
70 | };
71 |
72 | const handleSectionChange = (value: string) => {
73 |   setSectionId(value === "all" ? "" : value);
74 |   setPage(1);
75 | };
76 |
77 | return (
78 |   <div className="space-y-6">
79 |     <div>
80 |       <h1 className="text-2xl font-bold tracking-tight">Grading Queue</h1>
81 |     </div>
82 |     <div>
83 |       <div className="flex items-center gap-4">
84 |         <Select value={courseId || "all"} onValueChange={handleCourseChange}>
85 |           <SelectTrigger className="w-[220px] bg-white">
86 |             <SelectValue placeholder="All Courses" />
87 |           </SelectTrigger>
88 |           <SelectContent>
89 |             <SelectItem value="all">All Courses</SelectItem>
90 |             {courses?.map((c) => (
91 |               <SelectItem key={c.id} value={c.id}>
92 |                 {c.code} - {c.name}
93 |               </SelectItem>
94 |             ))}
95 |           </SelectContent>
96 |         </Select>
97 |
98 |         <Select
99 |           value={assignmentId || "all"}
100 |           onValueChange={handleAssignmentChange}
101 |           disabled={!courseId}
102 |         >
103 |           <SelectTrigger className="w-[220px] bg-white">
104 |             <SelectValue placeholder="All Assignments" />
105 |           </SelectTrigger>
106 |           <SelectContent>
107 |             <SelectItem value="all">All Assignments</SelectItem>
108 |             {assignments?.map((a) => (
109 |               <SelectItem key={a.id} value={a.id}>
110 |                 {a.title}
111 |               </SelectItem>
112 |             ))}
113 |           </SelectContent>
114 |         </Select>
115 |
116 |         <Select
117 |           value={sectionId || "all"}
118 |           onValueChange={handleSectionChange}
119 |           disabled={!courseId}
120 |         >
121 |           <SelectTrigger className="w-[220px] bg-white">
122 |             <SelectValue placeholder="All Sections" />
123 |           </SelectTrigger>
124 |           <SelectContent>
125 |             <SelectItem value="all">All Sections</SelectItem>
126 |             {sections?.map((s) => (

```

```

127 |         <SelectItem key={s.id} value={s.id}>
128 |             Section {s.section_code}
129 |         </SelectItem>
130 |     ))}
131 | </SelectContent>
132 | </Select>
133 | </div>
134 |
135 | { /* Data Table */ }
136 | <DataTable
137 |     columns={gradingQueueColumns}
138 |     data={submissions}
139 |     isLoading={isLoading}
140 |     isFetching={isFetching}
141 |     page={page}
142 |     pageSize={paginatedSubmissions?.pageSize}
143 |     totalCount={paginatedSubmissions?.count}
144 |     onPageChange={setPage}
145 |     emptyState={
146 |         submissions.length === 0 && !isLoading ? (
147 |             courses?.length ? (
148 |                 <NoSubmissions />
149 |             ) : (
150 |                 <NoCourses />
151 |             )
152 |         ) : undefined
153 |     }
154 | > />
155 | </div>
156 | );
157 | };
158 |
159 | export default GradingQueuePage;
160 |

```

FILE: [src/pages/teacher/outcomes/SubCLOManager.tsx](#)

TYPE: .tsx | LINES: 1-224 | SHA256: 127e7e1a95552fc70234578fc22f8f4787432b8a474767633069f322b794d052

```

1 | import { useParams } from "react-router-dom";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { Plus, Loader2, AlertTriangle } from "lucide-react";
5 | import { toast } from "sonner";
6 | import { Card } from "@components/ui/card";
7 | import { Button } from "@components/ui/button";
8 | import { Input } from "@components/ui/input";
9 | import {
10 |   Form,
11 |   FormField,
12 |   FormItem,
13 |   FormLabel,
14 |   FormControl,
15 |   FormMessage,
16 | } from "@components/ui/form";
17 | import SubCLORow from "@components/shared/SubCLORow";
18 | import { useCLO } from "@hooks/useCLOs";
19 | import {
20 |   useSubCLOs,
21 |   useCreateSubCLO,
22 |   useDeleteSubCLO,
23 | } from "@hooks/useSubCLOs";
24 | import {
25 |   subCLOSchema,
26 |   isWeightSumValid,
27 |   type SubCLOFormData,
28 | } from "@lib/schemas/subCLO";
29 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
30 | import { useState } from "react";
31 |
32 | const SubCLOManager = () => {
33 |   const { cloId } = useParams<{ cloId: string }>();
34 |   const { data: parentCLO } = useCLO(cloId);
35 |   const { data: subCLOs = [], isLoading } = useSubCLOs(cloId);
36 |   const createMutation = useCreateSubCLO();
37 |   const deleteMutation = useDeleteSubCLO();
38 |   const [deleteTarget, setDeleteTarget] = useState<string | null>(null);
39 |
40 |   const form = useForm<SubCLOFormData>({
41 |     resolver: zodResolver(subCLOSchema),
42 |     defaultValues: {
43 |       title: "",
44 |       code: "",
45 |       weight: 0,
46 |       parent_outcome_id: cloId ?? "",
47 |     },
48 |   });
49 |
50 |   const currentWeights = subCLOs.map(
51 |     (sc) => (sc as { weight?: number }).weight ?? 0
52 |   );
53 |   const weightSum = currentWeights.reduce((a, b) => a + b, 0);
54 |   const weightsValid = isWeightSumValid(currentWeights);
55 |
56 |   const onSubmit = (data: SubCLOFormData) => {
57 |     createMutation.mutate(
58 |       { ...data, parent_outcome_id: cloId! },
59 |       {
60 |         onSuccess: () => {
61 |           toast.success("Sub-CLO created");
62 |           form.reset({
63 |             title: "",
64 |             code: "",
65 |             weight: 0,
66 |             parent_outcome_id: cloId ?? "",

```

```

67 |     });
68 |   },
69 |   onError: (err) => toast.error(err.message),
70 | }
71 | );
72 | };
73 |
74 | const handleDelete = () => {
75 |   if (!deleteTarget || !cloId) return;
76 |   deleteMutation.mutate(
77 |     { id: deleteTarget, parentCloId: cloId },
78 |     {
79 |       onSuccess: () => {
80 |         toast.success("Sub-CLO deleted");
81 |         setDeleteTarget(null);
82 |       },
83 |       onError: (err) => {
84 |         toast.error(err.message);
85 |         setDeleteTarget(null);
86 |       },
87 |     }
88 |   );
89 | };
90 |
91 | return (
92 |   <div className="space-y-6 max-w-3xl">
93 |     <div>
94 |       <h1 className="text-2xl font-bold tracking-tight">Sub-CLOs</h1>
95 |       {parentCLO && (
96 |         <p className="text-sm text-slate-500 mt-1">
97 |           Parent CLO: {parentCLO.title}
98 |         </p>
99 |       )}
100 |     </div>
101 |
102 |     { /* Weight sum indicator */ }
103 |     <div className="flex items-center gap-2 text-sm">
104 |       <span className="text-slate-500">Weight total:</span>
105 |       <span
106 |         className={
107 |           weightsValid || subCLOs.length === 0
108 |             ? "text-green-600 font-semibold"
109 |             : "text-amber-600 font-semibold"
110 |         }
111 |       >
112 |         {(weightSum * 100).toFixed(1)}% / 100%
113 |       </span>
114 |       { !weightsValid && subCLOs.length > 0 && (
115 |         <AlertTriangle className="h-4 w-4 text-amber-500" />
116 |       ) }
117 |     </div>
118 |
119 |     { /* Existing Sub-CLOs */ }
120 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4">
121 |       {isLoading ? (
122 |         <div className="h-20 rounded-lg animate-shimmer" />
123 |       ) : subCLOs.length === 0 ? (
124 |         <p className="text-sm text-slate-400 text-center py-6">
125 |           No Sub-CLOs yet. Add one below.
126 |         </p>
127 |       ) : (
128 |         <div className="space-y-1">
129 |           {subCLOs.map((sc) => (
130 |             <SubCLORow
131 |               key={sc.id}
132 |               subCLO={sc as never}
133 |               onDelete={(id) => setDeleteTarget(id)}
134 |             />
135 |           ))}
136 |         </div>
137 |       )}
138 |     </Card>
139 |
140 |     { /* Add Sub-CLO form */ }
141 |     <Card className="bg-white border-0 shadow-md rounded-xl p-6">
142 |       <h2 className="text-lg font-bold tracking-tight mb-4">Add Sub-CLO</h2>
143 |       <Form {...form}>
144 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
145 |           <div className="grid grid-cols-2 gap-4">
146 |             <FormField
147 |               control={form.control}
148 |               name="code"
149 |               render={({ field }) => (
150 |                 <FormItem>
151 |                   <FormLabel>Code</FormLabel>
152 |                   <FormControl>
153 |                     <Input placeholder="SC1.1" {...field} />
154 |                   </FormControl>
155 |                   <FormMessage />
156 |                 </FormItem>
157 |               )}
158 |             />
159 |             <FormField
160 |               control={form.control}
161 |               name="weight"
162 |               render={({ field }) => (
163 |                 <FormItem>
164 |                   <FormLabel>Weight (0-1)</FormLabel>
165 |                   <FormControl>
166 |                     <Input
167 |                       type="number"
168 |                       step="0.01"
169 |                       min="0"
170 |                       max="1"

```

```

171 |         {...field}
172 |         onChange={(e) =>
173 |             field.onChange(parseFloat(e.target.value) || 0)
174 |         }
175 |     />
176 | </FormControl>
177 | <FormMessage />
178 | </FormItem>
179 | }}
180 | />
181 | </div>
182 | <FormField
183 |     control={form.control}
184 |     name="title"
185 |     render={({ field }) => (
186 |         <FormItem>
187 |             <FormLabel>Title</FormLabel>
188 |             <FormControl>
189 |                 <Input placeholder="Sub-CLO title" {...field} />
190 |             </FormControl>
191 |             <FormMessage />
192 |         </FormItem>
193 |     )}
194 | />
195 | <Button
196 |     type="submit"
197 |     disabled={createMutation.isPending}
198 |     variant="tactile"
199 | >
200 |     {createMutation.isPending ? (
201 |         <Loader2 className="h-4 w-4 animate-spin" />
202 |     ) : (
203 |         <Plus className="h-4 w-4" />
204 |     )}
205 |     Add Sub-CLO
206 | </Button>
207 | </form>
208 | </Form>
209 | </Card>
210 |
211 | <ConfirmDialog
212 |     open={!!deleteTarget}
213 |     onOpenChange={({open: boolean}) => !open && setDeleteTarget(null)}
214 |     title="Delete Sub-CLO?"
215 |     description="This will permanently remove this Sub-CLO. Evidence linked to it must be removed first."
216 |     onConfirm={handleDelete}
217 |     isPending={deleteMutation.isPending}
218 | />
219 | </div>
220 | );
221 | };
222 |
223 | export default SubCLOManager;
224 |

```

FILE: src/pages/teacher/quiz-analytics/columns.tsx

TYPE: .tsx | LINES: 1-220 | SHA256: 1f37498b7e84ef75233afae0b0b8e4d80cbc0f5ba32211b267d5742c485f06a75

[illegible]

```

47 |         size="sm"
48 |         className="-ms-3"
49 |         onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
50 |     >
51 |         Question
52 |         <ArrowUpDown className="h-4 w-4" />
53 |     </Button>
54 | ),
55 | accessorFn: (row) => row.question_bank.question_text,
56 | cell: ({ row }) => {
57 |     const text = row.original.question_bank.question_text;
58 |     const isFlagged =
59 |         row.original.quality_flag !== null &&
60 |         row.original.quality_flag !== "good";
61 |     return (
62 |         <button
63 |             type="button"
64 |             className={cn(
65 |                 "text-start font-medium text-sm hover:underline",
66 |                 isFlagged && "cursor-pointer text-blue-600"
67 |             )}
68 |             onClick={() => isFlagged && onRowClick(row.original)}
69 |         >
70 |             {text.length > 60 ? `${text.slice(0, 60)}...` : text}
71 |         </button>
72 |     );
73 | },
74 | },
75 | {
76 |     id: "clo",
77 |     header: "CLO",
78 |     accessorFn: (row) => row.question_bank.clo_id,
79 |     cell: ({ row }) => (
80 |         <span className="text-sm text-gray-600 max-w-[120px] truncate inline-block">
81 |             {row.original.question_bank.clo_id.slice(0, 8)}
82 |         </span>
83 |     ),
84 | },
85 | {
86 |     id: "bloom_level",
87 |     header: "Bloom's",
88 |     accessorFn: (row) => row.question_bank.bloom_level,
89 |     cell: ({ row }) => {
90 |         const level = row.original.question_bank.bloom_level;
91 |         return (
92 |             <Badge
93 |                 className={cn(
94 |                     "text-xs font-bold tracking-wide uppercase border-transparent",
95 |                     BLOOM_COLORS[level] ?? "bg-gray-200 text-gray-700"
96 |                 )}
97 |             >
98 |                 {BLOOM_LABELS[level] ?? `L${level}`}
99 |             </Badge>
100 |         );
101 |     },
102 | },
103 | {
104 |     id: "question_type",
105 |     header: "Type",
106 |     accessorFn: (row) => row.question_bank.question_type,
107 |     cell: ({ row }) => {
108 |         const type = row.original.question_bank.question_type;
109 |         return (
110 |             <span className="text-sm text-gray-600">
111 |                 {TYPE_LABELS[type] ?? type}
112 |             </span>
113 |         );
114 |     },
115 | },
116 | {
117 |     accessorKey: "success_rate",
118 |     header: ({ column }) => (
119 |         <Button
120 |             variant="ghost"
121 |             size="sm"
122 |             className="-ms-3"
123 |             onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
124 |         >
125 |             Success %
126 |             <ArrowUpDown className="h-4 w-4" />
127 |         </Button>
128 |     ),
129 |     cell: ({ row }) => {
130 |         const rate = row.getValue("success_rate") as number;
131 |         return (
132 |             <span className="text-sm font-medium">{(rate * 100).toFixed(1)}%</span>
133 |         );
134 |     },
135 | },
136 | {
137 |     accessorKey: "avg_response_time_seconds",
138 |     header: ({ column }) => (
139 |         <Button
140 |             variant="ghost"
141 |             size="sm"
142 |             className="-ms-3"
143 |             onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
144 |         >
145 |             Avg. Time (s)
146 |             <ArrowUpDown className="h-4 w-4" />
147 |         </Button>
148 |     ),
149 |     cell: ({ row }) => {
150 |         const time = row.getValue("avg_response_time_seconds") as number;

```

```

151 |         return <span className="text-sm">{time.toFixed(1)}s</span>;
152 |     },
153 | },
154 | {
155 |   accessorKey: "discrimination_index",
156 |   header: ({ column }) => (
157 |     <Button
158 |       variant="ghost"
159 |       size="sm"
160 |       className="-ms-3"
161 |       onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
162 |     >
163 |       Discrim.
164 |       <ArrowUpDown className="h-4 w-4" />
165 |     </Button>
166 |   ),
167 |   cell: ({ row }) => {
168 |     const di = row.getValue("discrimination_index") as number;
169 |     return <span className="text-sm">{di.toFixed(2)}</span>;
170 |   },
171 | },
172 | {
173 |   accessorKey: "total_attempts",
174 |   header: ({ column }) => (
175 |     <Button
176 |       variant="ghost"
177 |       size="sm"
178 |       className="-ms-3"
179 |       onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
180 |     >
181 |       Attempts
182 |       <ArrowUpDown className="h-4 w-4" />
183 |     </Button>
184 |   ),
185 |   cell: ({ row }) => (
186 |     <span className="text-sm">
187 |       {row.getValue("total_attempts") as number}
188 |     </span>
189 |   ),
190 | },
191 | {
192 |   id: "difficulty",
193 |   header: "Difficulty",
194 |   cell: ({ row }) => {
195 |     const calibrated = row.original.calibrated_difficulty;
196 |     const original = row.original.question_bank.difficulty_rating;
197 |     return <DifficultyBadge difficulty={calibrated ?? original} />;
198 |   },
199 | },
200 | {
201 |   accessorKey: "quality_flag",
202 |   header: "Quality",
203 |   cell: ({ row }) => {
204 |     const flag = row.getValue("quality_flag") as string | null;
205 |     return (
206 |       <QuestionQualityIndicator
207 |         qualityFlag={
208 |           flag as
209 |           | "good"
210 |           | "low_discrimination"
211 |           | "too_easy"
212 |           | "too_hard"
213 |           | null
214 |         }
215 |       </>
216 |     );
217 |   },
218 | },
219 | ];
220 |

```

FILE: [src/pages/teacher/quiz-analytics/QuestionAnalyticsDashboard.tsx](#)

TYPE: .tsx | LINES: 1-353 | SHA256: cbe8ec1871f9c6a762cfff88c8ce5cdf01d3ff7fa19acc240cd633070573b2d3a

```

1 | import { useState } from "react";
2 | import { useParams } from "react-router-dom";
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { BarChart3 } from "lucide-react";
5 |
6 | import { cn } from "@lib/utils";
7 | import { DataTable } from "@components/shared/DataTable";
8 | import AnswerDistributionChart from "@components/shared/AnswerDistributionChart";
9 | import QuestionQualityIndicator from "@components/shared/QuestionQualityIndicator";
10 | import DifficultyBadge from "@components/shared/DifficultyBadge";
11 | import { Badge } from "@components/ui/badge";
12 | import { Card } from "@components/ui/card";
13 | import {
14 |   Select,
15 |   SelectContent,
16 |   SelectItem,
17 |   SelectTrigger,
18 |   SelectValue,
19 | } from "@components/ui/select";
20 | import {
21 |   Sheet,
22 |   SheetContent,
23 |   SheetHeader,
24 |   SheetTitle,
25 |   SheetDescription,
26 | } from "@components/ui/sheet";
27 |
28 | import {
29 |   useQuestionAnalytics,
30 |   type QuestionAnalyticsRow,

```

[illegible]


```

135 |     courseId ?? "",
136 |     {
137 |       clo_id: cloFilter || undefined,
138 |       bloom_level: bloomFilter ? Number(bloomFilter) : undefined,
139 |       quality_flag: qualityFilter || undefined,
140 |     }
141 |   );
142 |
143 |   const closQuery = useCLOs(courseId);
144 |   const clos = closQuery.data?.data ?? [];
145 |
146 |   const columns = createAnalyticsColumns(setSelectedQuestion);
147 |
148 |   const selected = selectedQuestion;
149 |   const suggestedAction = selected
150 |     ? getSuggestedAction(selected.quality_flag)
151 |     : null;
152 |
153 |   return (
154 |     <div className="space-y-6">
155 |       {/* Page Header */}
156 |       <div className="flex items-center gap-3">
157 |         <BarChart3 className="h-6 w-6 text-blue-600" />
158 |         <h1 className="text-2xl font-bold tracking-tight">
159 |           Question Analytics
160 |         </h1>
161 |       </div>
162 |
163 |       {/* Filters */}
164 |       <div className="flex items-center gap-3 flex-wrap">
165 |         <Select
166 |           value={cloFilter}
167 |           onChange={(val) => setCloFilter(val === "all" ? "" : val)}
168 |         >
169 |           <SelectTrigger className="w-[200px] bg-white">
170 |             <SelectValue placeholder="All CLOs" />
171 |           </SelectTrigger>
172 |           <SelectContent>
173 |             <SelectItem value="all">All CLOs</SelectItem>
174 |             {clos.map((clo) => (
175 |               <SelectItem key={clo.id} value={clo.id}>
176 |                 {clo.title}
177 |               </SelectItem>
178 |             ))}
179 |           </SelectContent>
180 |         </Select>
181 |
182 |         <Select
183 |           value={bloomFilter}
184 |           onChange={(val) => setBloomFilter(val === "all" ? "" : val)}
185 |         >
186 |           <SelectTrigger className="w-[160px] bg-white">
187 |             <SelectValue placeholder="Bloom's Level" />
188 |           </SelectTrigger>
189 |           <SelectContent>
190 |             <SelectItem value="all">All Levels</SelectItem>
191 |             {BLOOM_OPTIONS.map((opt) => (
192 |               <SelectItem key={opt.value} value={opt.value}>
193 |                 {opt.label}
194 |               </SelectItem>
195 |             ))}
196 |           </SelectContent>
197 |         </Select>
198 |
199 |         <Select
200 |           value={qualityFilter}
201 |           onChange={(val) => setQualityFilter(val === "all" ? "" : val)}
202 |         >
203 |           <SelectTrigger className="w-[180px] bg-white">
204 |             <SelectValue placeholder="Quality Flag" />
205 |           </SelectTrigger>
206 |           <SelectContent>
207 |             <SelectItem value="all">All Quality</SelectItem>
208 |             {QUALITY_OPTIONS.map((opt) => (
209 |               <SelectItem key={opt.value} value={opt.value}>
210 |                 {opt.label}
211 |               </SelectItem>
212 |             ))}
213 |           </SelectContent>
214 |         </Select>
215 |       </div>
216 |
217 |       {/* Data Table */}
218 |       <DataTable
219 |         columns={columns}
220 |         data={analyticsRows ?? []}
221 |         isLoading={isLoading}
222 |         emptyState={
223 |           {analyticsRows ?? []}.length === 0 && !isLoading ? (
224 |             <NoData />
225 |           ) : undefined
226 |         }
227 |       />
228 |
229 |       {/* Flagged Question Detail Panel */}
230 |       <Sheet
231 |         open={!selected}
232 |         onOpenChange={(open) => !open && setSelectedQuestion(null)}
233 |       >
234 |         <SheetContent
235 |           side="right"
236 |           className="w-full sm:max-w-lg overflow-y-auto"
237 |         >
238 |           {selected && (

```

```

239 | <>
240 | <SheetHeader>
241 |   <SheetTitle>Question Detail</SheetTitle>
242 |   <SheetDescription>
243 |     Analytics and suggested actions for this flagged question.
244 |   </SheetDescription>
245 | </SheetHeader>
246 |
247 | <div className="space-y-6 px-4 pb-6">
248 |   {/* Full question text */}
249 |   <Card className="bg-white border-0 shadow-md rounded-xl p-4">
250 |     <p className="text-sm font-medium leading-relaxed">
251 |       {selected.question_bank.question_text}
252 |     </p>
253 |   </Card>
254 |
255 |   {/* Metrics grid */}
256 |   <div className="grid grid-cols-2 gap-3">
257 |     <div className="space-y-1">
258 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
259 |         Success Rate
260 |       </p>
261 |       <p className="text-lg font-bold">
262 |         {(selected.success_rate * 100).toFixed(1)}%
263 |       </p>
264 |     </div>
265 |     <div className="space-y-1">
266 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
267 |         Avg Response Time
268 |       </p>
269 |       <p className="text-lg font-bold">
270 |         {selected.avg_response_time_seconds.toFixed(1)}s
271 |       </p>
272 |     </div>
273 |     <div className="space-y-1">
274 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
275 |         Discrimination Index
276 |       </p>
277 |       <p className="text-lg font-bold">
278 |         {selected.discrimination_index.toFixed(3)}
279 |       </p>
280 |     </div>
281 |     <div className="space-y-1">
282 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
283 |         Total Attempts
284 |       </p>
285 |       <p className="text-lg font-bold">
286 |         {selected.total_attempts}
287 |       </p>
288 |     </div>
289 |   </div>
290 |
291 |   {/* Badges row */}
292 |   <div className="flex items-center gap-2 flex-wrap">
293 |     <Badge
294 |       className={cn(
295 |         "text-xs font-bold tracking-wide uppercase border-transparent",
296 |         BLOOM_COLORS[selected.question_bank.bloom_level] ??
297 |         "bg-gray-200 text-gray-700"
298 |       )}
299 |     >
300 |       {BLOOM_LABELS[selected.question_bank.bloom_level] ??
301 |         `L${selected.question_bank.bloom_level}`}
302 |     </Badge>
303 |     <DifficultyBadge
304 |       difficulty={
305 |         selected.calibrated_difficulty ??
306 |         selected.question_bank.difficulty_rating
307 |       }
308 |     />
309 |     <QuestionQualityIndicator
310 |       qualityFlag={
311 |         selected.quality_flag as
312 |         | "good"
313 |         | "low_discrimination"
314 |         | "too_easy"
315 |         | "too_hard"
316 |         | null
317 |       }
318 |     />
319 |   </div>
320 |
321 |   {/* Answer Distribution Chart */}
322 |   <div className="space-y-2">
323 |     <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
324 |       Answer Distribution
325 |     </p>
326 |     <AnswerDistributionChart data={MOCK_ANSWER_DISTRIBUTION} />
327 |   </div>
328 |
329 |   {/* Suggested Action */}
330 |   {suggestedAction && (
331 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4 space-y-2">
332 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
333 |         Suggested Action
334 |       </p>
335 |       <p className="text-sm font-bold text-blue-600">
336 |         {suggestedAction.label}
337 |       </p>
338 |       <p className="text-sm text-gray-600 leading-relaxed">
339 |         {suggestedAction.description}
340 |       </p>
341 |     </Card>
342 |   )}

```

FILE: src/pages/teacher/quiz-analytics/QuizCL0CorrelationPage.tsx

```

1 | import { useMemo } from "react";
2 | import { useParams } from "react-router-dom";
3 | import {
4 |   BarChart,
5 |   Bar,
6 |   XAxis,
7 |   YAxis,
8 |   CartesianGrid,
9 |   Tooltip,
10 |   Legend,
11 |   ResponsiveContainer,
12 |   Cell,
13 | } from "recharts";
14 | import {
15 |   AlertTriangle,
16 |   GitCompareArrows,
17 |   Users,
18 |   Target,
19 |   BarChart3,
20 | } from "lucide-react";
21 |
22 | import { Card } from "@components/ui/card";
23 | import { Badge } from "@components/ui/badge";
24 | import { useQuizCLOCorrelation } from "@hooks/useQuizCLOCorrelation";
25 | import { useCLOs } from "@hooks/useCLOs";
26 | import { detectCLODiscrepancy } from "@lib/questionAnalytics";
27 | import {
28 |   InlineNoCorrelationData,
29 |   InlineNoBloomsData,
30 | } from "@components/shared/EmptyState";

```

```
34 const BLOOM_LABELS: Record<number, string> = {
35     1: "Remember",
36     2: "Understand",
37     3: "Apply",
38     4: "Analyze",
39     5: "Evaluate",
40     6: "Create",
41 };

```

```
43 const BLOOM_CHART_COLORS: Record<number, string> = {
44   1: "#a855f7", // purple-500
45   2: "#3b82f6", // blue-500
46   3: "#22c55e", // green-500
47   4: "#eab398", // yellow-500
48   5: "#f97316", // orange-500
49   6: "#ef4444", // red-500
50 };
```

```
54 | interface CLOComparisonRow {
55 |     cloId: string;
56 |     cloName: string;
57 |     quizScore: number;
58 |     attainment: number;
59 |     hasDiscrepancy: boolean;
60 | }
```

```
61 |  
62 | interface BloomsDistributionRow {  
63 |     level: number;  
64 |     label: string;  
65 |     count: number;  
66 |     color: string;  
67 | }
```

```

71 const QuizCLOCorrelationPage = () => {
72   const { quizId } = useParams<{ quizId: string }>();
73   const { data, isLoading } = useQuizCLOCorrelation(quizId ?? "");
74   const closQuery = useCLOs();
75   const closData = closQuery.data?.data;
76
77   // Build a CLO id !' title lookup
78   const cloTitleMap = useMemo(() => {
79     const map: Record<string, string> = {};
80     for (const clo of closData ?? []) {
81       map[clo.id] = clo.title;
82     }
83     return map;
84   }, [closData]);
85
86   // Compute per-CLO comparison data
87   const {
88     comparisonData,
89     bloomsData,

```

```

90 |     totalStudents,
91 |     avgQuizScore,
92 |     discrepancyCount,
93 | } = useMemo(() => {
94 |   if (!data) {
95 |     return {
96 |       comparisonData: [] as CLOComparisonRow[],
97 |       bloomsData: [] as BloomsDistributionRow[],
98 |       totalStudents: 0,
99 |       avgQuizScore: 0,
100 |       discrepancyCount: 0,
101 |     };
102 |   }
103 |
104 |   const { attempts, attainments } = data;
105 |
106 |   // Unique students
107 |   const studentIds = [...new Set(attempts.map((a) => a.student_id))];
108 |   const totalStudents = studentIds.length;
109 |
110 |   // Average quiz score across all attempts
111 |   const scores = attempts
112 |     .map((a) => a.score)
113 |     .filter((s): s is number => s !== null);
114 |   const avgQuizScore =
115 |     scores.length > 0
116 |       ? scores.reduce((sum, s) => sum + s, 0) / scores.length
117 |       : 0;
118 |
119 |   // Per-CLO attainment averages from outcome_attainment
120 |   const attainmentByCLO: Record<string, number[]> = {};
121 |   for (const att of attainments) {
122 |     const key = att.outcome_id;
123 |     if (!attainmentByCLO[key]) {
124 |       attainmentByCLO[key] = [];
125 |     }
126 |     attainmentByCLO[key]!.push(att.attainment_percent);
127 |   }
128 |
129 |   // Per-CLO quiz score: derive from question_sequence CLO mapping
130 |   // Since question_sequence is raw JSON, we use a simplified approach:
131 |   // group attempts by CLO from the attainment data and use the overall quiz score
132 |   // as a proxy per CLO (the hook returns raw data, full CLO-level scoring
133 |   // would require question-level answer data which isn't in the hook response)
134 |   const cloIds = Object.keys(attainmentByCLO);
135 |
136 |   const comparisonData: CLOComparisonRow[] = cloIds.map((cloId) => {
137 |     const attainmentValues = attainmentByCLO[cloId] ?? [];
138 |     const avgAttainment =
139 |       attainmentValues.length > 0
140 |         ? attainmentValues.reduce((sum, v) => sum + v, 0) /
141 |           attainmentValues.length
142 |         : 0;
143 |
144 |     // Use overall quiz score as proxy for per-CLO quiz score
145 |     const quizScore = avgQuizScore;
146 |     const hasDiscrepancy = detectCLODiscrepancy(quizScore, avgAttainment);
147 |
148 |     return {
149 |       cloId,
150 |       cloName: cloTitleMap[cloId] ?? cloId.slice(0, 8),
151 |       quizScore: Math.round(quizScore * 10) / 10,
152 |       attainment: Math.round(avgAttainment * 10) / 10,
153 |       hasDiscrepancy,
154 |     };
155 |   });
156 |
157 |   const discrepancyCount = comparisonData.filter(
158 |     (r) => r.hasDiscrepancy
159 |   ).length;
160 |
161 |   // Bloom's distribution: count questions per Bloom's level from question_sequence
162 |   const bloomCounts: Record<number, number> = {};
163 |   for (const attempt of attempts) {
164 |     const seq = attempt.question_sequence;
165 |     if (Array.isArray(seq)) {
166 |       for (const item of seq) {
167 |         const bl =
168 |           typeof item === "object" && item !== null && "bloom_level" in item
169 |             ? (item as { bloom_level: number }).bloom_level
170 |             : null;
171 |         if (bl && bl >= 1 && bl <= 6) {
172 |           bloomCounts[bl] = (bloomCounts[bl] ?? 0) + 1;
173 |         }
174 |       }
175 |     }
176 |   }
177 |
178 |   const bloomsData: BloomsDistributionRow[] = [1, 2, 3, 4, 5, 6].map(
179 |     (level) => ({
180 |       level,
181 |       label: BLOOM_LABELS[level] ?? `Level ${level}`,
182 |       count: bloomCounts[level] ?? 0,
183 |       color: BLOOM_CHART_COLORS[level] ?? "#6b7280",
184 |     })
185 |   );
186 |
187 |   return {
188 |     comparisonData,
189 |     bloomsData,
190 |     totalStudents,
191 |     avgQuizScore,
192 |     discrepancyCount,
193 |   };

```



```

298     />
299     <YAxis domain={[0, 100]} tick={{ fontSize: 12 }} unit="%" />
300     <Tooltip
301       formatter={(value) => {
302         const n = Array.isArray(value)
303           ? Number(value[0] ?? 0)
304           : Number(value ?? 0);
305         return `${n.toFixed(1)}%`;
306       }}
307       contentStyle={{
308         borderRadius: 8,
309         border: "none",
310         boxShadow: "0 4px 12px rgba(0,0,0,0.1)",
311       }}
312     />
313     <Legend />
314     <Bar
315       dataKey="quizScore"
316       name="Quiz Score"
317       fill="#3b82f6"
318       radius={[4, 4, 0, 0]}
319     />
320     <Bar
321       dataKey="attainment"
322       name="CLO Attainment"
323       fill="#14b8a6"
324       radius={[4, 4, 0, 0]}
325     />
326   </BarChart>
327 </ResponsiveContainer>
328
329   { /* Discrepancy badges */ }
330   {comparisonData.some((r) => r.hasDiscrepancy) && (
331     <div className="mt-4 flex flex-wrap gap-2">
332       {comparisonData
333         .filter((r) => r.hasDiscrepancy)
334         .map((r) => (
335         <Badge
336           key={r.cloId}
337           variant="outline"
338           className="border-amber-300 bg-amber-50 text-amber-700 text-xs font-bold"
339         >
340           <AlertTriangle className="h-3 w-3 me-1" />
341           {r.cloName}:{" "}
342           {Math.abs(r.quizScore - r.attainment).toFixed(1)}pp gap
343         </Badge>
344       )}}
345     </div>
346   )}
347 </div>
348 )}
349 </div>
350 </Card>
351
352 { /* Bloom's Distribution Chart */ }
353 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
354   <div
355     className="px-6 py-4 flex items-center gap-2"
356     style={{
357       background: "var(--brand-gradient)",
358     }}
359   >
360     <BarChart3 className="h-5 w-5 text-white" />
361     <h2 className="text-lg font-bold tracking-tight text-white">
362       Bloom's Level Distribution
363     </h2>
364   </div>
365   <div className="p-6">
366     {bloomsData.every((b) => b.count === 0) ? (
367       <InlineNoBloomsData />
368     ) : (
369       <ResponsiveContainer width="100%" height={280}>
370         <BarChart
371           data={bloomsData}
372           margin={{ top: 8, right: 16, left: 0, bottom: 0 }}
373         >
374           <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
375           <XAxis dataKey="label" tick={{ fontSize: 12 }} />
376           <YAxis allowDecimals={false} tick={{ fontSize: 12 }} />
377           <Tooltip
378             contentStyle={{
379               borderRadius: 8,
380               border: "none",
381               boxShadow: "0 4px 12px rgba(0,0,0,0.1)",
382             }}
383           />
384           <Bar dataKey="count" name="Questions" radius={[4, 4, 0, 0]}>
385             {bloomsData.map((entry) => (
386               <Cell key={entry.level} fill={entry.color} />
387             ))}
388           </Bar>
389         </BarChart>
390       </ResponsiveContainer>
391     )}
392   </div>
393 </Card>
394 </div>
395 );
396 };
397
398 export default QuizCLOCorrelationPage;
399

```

TYPE: .tsx | LINES: 1-202 | SHA256: be3d0f643d08036e4c886eca3d47d990ecb918e53d8dc01943c1baa89d36c14b

[illegible]

```

102 | {
103 |   id: "clo",
104 |   header: "CLO",
105 |   cell: ({ row }) => (
106 |     <span
107 |       className="text-sm text-gray-600 max-w-[140px] truncate inline-block"
108 |       title={row.original.clo_title}
109 |     >
110 |       {row.original.clo_title ?? row.original.clo_id.slice(0, 8)}
111 |     </span>
112 |   ),
113 | },
114 | {
115 |   accessorKey: "bloom_level",
116 |   header: "Bloom's",
117 |   cell: ({ row }) => {
118 |     const level = row.getValue("bloom_level") as number;
119 |     return (
120 |       <Badge
121 |         className={cn(
122 |           "text-xs font-bold tracking-wide uppercase border-transparent",
123 |           BLOOM_COLORS[level] ?? "bg-gray-200 text-gray-700"
124 |         )}
125 |       >
126 |         {BLOOM_LABELS[level] ?? `L${level}`}
127 |       </Badge>
128 |     );
129 |   },
130 | },
131 | {
132 |   accessorKey: "question_type",
133 |   header: "Type",
134 |   cell: ({ row }) => {
135 |     const type = row.getValue("question_type") as string;
136 |     return (
137 |       <span className="text-sm text-gray-600">
138 |         {TYPE_LABELS[type] ?? type}
139 |       </span>
140 |     );
141 |   },
142 | },
143 | {
144 |   accessorKey: "status",
145 |   header: "Status",
146 |   cell: ({ row }) => {
147 |     const status = row.getValue("status") as string;
148 |     return (
149 |       <Badge
150 |         variant="outline"
151 |         className={cn(
152 |           "text-xs font-bold tracking-wide",
153 |           STATUS_STYLES[status] ?? ""
154 |         )}
155 |       >
156 |         {STATUS_LABELS[status] ?? status}
157 |       </Badge>
158 |     );
159 |   },
160 | },
161 | {
162 |   accessorKey: "difficulty_rating",
163 |   header: "Difficulty",
164 |   cell: ({ row }) => (
165 |     <DifficultyBadge
166 |       difficulty={row.getValue("difficulty_rating") as number}
167 |     />
168 |   ),
169 | },
170 | {
171 |   id: "quality",
172 |   header: "Quality",
173 |   cell: ({ row }) => {
174 |     const analytics = row.original.analytics;
175 |     if (!analytics) return <span className="text-xs text-gray-400"></span>;
176 |     return <QuestionQualityIndicator qualityFlag={analytics.quality_flag} />;
177 |   },
178 | },
179 | {
180 |   id: "explanation",
181 |   header: "Explanation",
182 |   cell: ({ row }) => (
183 |     <ExplanationConfidenceBadge
184 |       confidence={row.original.explanation_confidence ?? null}
185 |       isVerified={false}
186 |     />
187 |   ),
188 | },
189 | {
190 |   accessorKey: "generation_source",
191 |   header: "Source",
192 |   cell: ({ row }) => {
193 |     const source = row.getValue("generation_source") as string;
194 |     return (
195 |       <span className="text-xs text-gray-500">
196 |         {SOURCE_LABELS[source] ?? source}
197 |       </span>
198 |     );
199 |   },
200 | },
201 | ];
202 |

```


TYPE: .tsx | LINES: 1-305 | SHA256: 289c054d5d7d3c3cb137f028e408402401d2a9b3eaad854011d53de84681e2a0

[illegible]

[illegible]

[illegible]

```
TYPE: .tsx | LINES: 1-425 | SHA256: 2ee2684fe127ceb530895b143715062169b52adaae331a76a1a09a7933f1ee25
```

[illegible]

[illegible]

```

206 |         }}
207 |     </>
208 |     </FormControl>
209 |     <Label className="text-sm font-normal cursor-pointer">
210 |       {level.value}. {level.label}
211 |     </Label>
212 |   </FormItem>
213 | }
214 | </>
215 | )}}
216 | </div>
217 | <FormMessage />
218 | </FormItem>
219 | )}
220 | />
221 |
222 | {/* Question Type Checkboxes */}
223 | <FormField
224 |   control={form.control}
225 |   name="question_types"
226 |   render={() => (
227 |     <FormItem>
228 |       <FormLabel>Question Types</FormLabel>
229 |       <div className="grid grid-cols-2 gap-2">
230 |         {QUESTION_TYPES.map((type) => (
231 |           <FormField
232 |             key={type.value}
233 |             control={form.control}
234 |             name="question_types"
235 |             render={({ field }) => (
236 |               <FormItem className="flex items-center gap-2">
237 |                 <FormControl>
238 |                   <Checkbox
239 |                     checked={field.value.includes(type.value)}
240 |                     onCheckedChange={(checked) => {
241 |                       field.onChange(
242 |                         checked
243 |                           ? [...field.value, type.value]
244 |                           : field.value.filter(
245 |                             (v: string) => v !== type.value
246 |                           )
247 |                       );
248 |                     }}
249 |                   </>
250 |                 </FormControl>
251 |                 <Label className="text-sm font-normal cursor-pointer">
252 |                   {type.label}
253 |                 </Label>
254 |               </FormItem>
255 |             )}
256 |           </>
257 |         )}}
258 |       </div>
259 |       <FormMessage />
260 |     </FormItem>
261 |   )}
262 | />
263 |
264 | {/* Question Count */}
265 | <FormField
266 |   control={form.control}
267 |   name="question_count"
268 |   render={({ field }) => (
269 |     <FormItem>
270 |       <FormLabel>Number of Questions (1-50)</FormLabel>
271 |       <FormControl>
272 |         <Input
273 |           type="number"
274 |           min={1}
275 |           max={50}
276 |           {...field}
277 |           onChange={(e) => field.onChange(Number(e.target.value))}
278 |         />
279 |       </FormControl>
280 |       <FormMessage />
281 |     </FormItem>
282 |   )}
283 | />
284 |
285 | {/* Generate Button */}
286 | <Button
287 |   type="submit"
288 |   disabled={generateMutation.isPending}
289 |   variant="tactile"
290 |   className="w-full"
291 | >
292 |   {generateMutation.isPending ? (
293 |     <Loader2 className="h-4 w-4 animate-spin" />
294 |   ) : (
295 |     <Sparkles className="h-4 w-4" />
296 |   )}
297 |   {generateMutation.isPending
298 |     ? "Generating..."
299 |     : "Generate Questions"}
300 | </Button>
301 | </form>
302 | </Form>
303 | </Card>
304 |
305 | {/* Results Panel */}
306 | <div className="space-y-4">
307 |   {result && result.warnings.length > 0 && (
308 |     <Card className="bg-yellow-50 border border-yellow-200 shadow-md rounded-xl p-4">
309 |       <div className="flex items-start gap-2">

```

[illegible]

```

414 |             <X className="h-4 w-4" />
415 |             Reject
416 |         </Button>
417 |     </div>
418 |   }}
419 | </div>
420 | </Card>
421 | );
422 | };
423 |
424 | export default GenerateQuestionsPage;
425 |

```

FILE: [src/pages/teacher/quiz-generation/QuestionBankPage.tsx](#)

TYPE: .tsx | LINES: 1-260 | SHA256: 48bf61dd589654ea71d065e184deb43a52298411521976c8360b856b638e4dbe

[illegible]


```

89 | });
90 |
91 | const { data: analyticsRows } = useQuestionAnalytics(courseId ?? "");
92 | const closQuery = useCLOs(courseId);
93 | const clos = closQuery.data?.data ?? [];
94 |
95 | // Build CLO title lookup
96 | const cloMap: Record<string, string> = {};
97 | for (const clo of clos) {
98 |   cloMap[clo.id] = clo.title;
99 | }
100 |
101 | // Build analytics lookup by question_id
102 | const analyticsMap: Record<
103 |   string,
104 |   {
105 |     quality_flag:
106 |       | "good"
107 |       | "low_discrimination"
108 |       | "too_easy"
109 |       | "too_hard"
110 |       | null;
111 |   }
112 | > = {};
113 | for (const row of analyticsRows ?? []) {
114 |   analyticsMap[row.question_id] = {
115 |     quality_flag: row.quality_flag as
116 |       | "good"
117 |       | "low_discrimination"
118 |       | "too_easy"
119 |       | "too_hard"
120 |       | null,
121 |   };
122 | }
123 |
124 | // Merge questions with analytics and CLO titles
125 | const enrichedData: QuestionWithAnalytics[] = (questions ?? []).map((q) => ({
126 |   ...q,
127 |   clo_title: cloMap[q.clo_id],
128 |   analytics: analyticsMap[q.id] ?? null,
129 | }));
130 |
131 | const columns = createColumns();
132 |
133 | return (
134 |   <div className="space-y-6">
135 |     {/* Page Header */}
136 |     <div className="flex items-center justify-between">
137 |       <h1 className="text-2xl font-bold tracking-tight">Question Bank</h1>
138 |       <Button
139 |         variant="tactile"
140 |         onClick={() =>
141 |           navigate(`/teacher/courses/${courseId}/generate-questions`)
142 |         }
143 |       >
144 |         <Plus className="h-4 w-4" /> Add Questions
145 |       </Button>
146 |     </div>
147 |
148 |     {/* Filters */}
149 |     <div className="flex items-center gap-3 flex-wrap">
150 |       <div className="relative flex-1 min-w-[200px] max-w-sm">
151 |         <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
152 |         <Input
153 |           placeholder="Search questions..."
154 |           value={search}
155 |           onChange={(e) => setSearch(e.target.value)}
156 |           className="ps-9"
157 |         />
158 |       </div>
159 |
160 |       <Select
161 |         value={cloFilter}
162 |         onValueChange={(val) => setCloFilter(val === "all" ? "" : val)}
163 |       >
164 |         <SelectTrigger className="w-[200px] bg-white">
165 |           <SelectValue placeholder="All CLOs" />
166 |         </SelectTrigger>
167 |         <SelectContent>
168 |           <SelectItem value="all">All CLOs</SelectItem>
169 |           {clos.map((clo) => (
170 |             <SelectItem key={clo.id} value={clo.id}>
171 |               {clo.title}
172 |             </SelectItem>
173 |           ))}
174 |         </SelectContent>
175 |       </Select>
176 |
177 |       <Select
178 |         value={bloomFilter}
179 |         onValueChange={(val) => setBloomFilter(val === "all" ? "" : val)}
180 |       >
181 |         <SelectTrigger className="w-[160px] bg-white">
182 |           <SelectValue placeholder="Bloom's Level" />
183 |         </SelectTrigger>
184 |         <SelectContent>
185 |           <SelectItem value="all">All Levels</SelectItem>
186 |           {BLOOM_OPTIONS.map((opt) => (
187 |             <SelectItem key={opt.value} value={opt.value}>
188 |               {opt.label}
189 |             </SelectItem>
190 |           ))}
191 |         </SelectContent>
192 |       </Select>

```

```

193     <Select
194       value={typeFilter}
195       onChange={(val) => setTypeFilter(val === "all" ? "" : val)}
196     >
197       <SelectTrigger className="w-[160px] bg-white">
198         <SelectValue placeholder="Question Type" />
199       </SelectTrigger>
200       <SelectContent>
201         <SelectItem value="all">All Types</SelectItem>
202         {TYPE_OPTIONS.map((opt) => (
203           <SelectItem key={opt.value} value={opt.value}>
204             {opt.label}
205           </SelectItem>
206         ))}
207       </SelectContent>
208     </Select>
209
210     <Select
211       value={statusFilter}
212       onChange={(val) => setStatusFilter(val === "all" ? "" : val)}
213     >
214       <SelectTrigger className="w-[160px] bg-white">
215         <SelectValue placeholder="Status" />
216       </SelectTrigger>
217       <SelectContent>
218         <SelectItem value="all">All Statuses</SelectItem>
219         {STATUS_OPTIONS.map((opt) => (
220           <SelectItem key={opt.value} value={opt.value}>
221             {opt.label}
222           </SelectItem>
223         ))}
224       </SelectContent>
225     </Select>
226
227     <Select
228       value={sourceFilter}
229       onChange={(val) => setSourceFilter(val === "all" ? "" : val)}
230     >
231       <SelectTrigger className="w-[160px] bg-white">
232         <SelectValue placeholder="Source" />
233       </SelectTrigger>
234       <SelectContent>
235         <SelectItem value="all">All Sources</SelectItem>
236         {SOURCE_OPTIONS.map((opt) => (
237           <SelectItem key={opt.value} value={opt.value}>
238             {opt.label}
239           </SelectItem>
240         ))}
241       </SelectContent>
242     </Select>
243   </div>
244
245   { /* Data Table */ }
246   <DataTable
247     columns={columns}
248     data={enrichedData}
249     isLoading={isLoading}
250     emptyState={
251       enrichedData.length === 0 && !isLoading ? <NoQuestions /> : undefined
252     }
253   </>
254 </div>
255 );
256 };
257
258 export default QuestionBankPage;
259
260

```

FILE: src/pages/teacher/quiz-generation/ReviewQueuePage.tsx

TYPE: .tsx | LINES: 1-337 | SHA256: 3a061851c87294ae8b92db6909c56006e1de42ea584e025ceb5098fd76ed591a


```

241 |   isApproving: boolean;
242 |   isRejecting: boolean;
243 | }
244 |
245 | const QuestionReviewCard = ({
246 |   question,
247 |   onApprove,
248 |   onReject,
249 |   isApproving,
250 |   isRejecting,
251 | }: QuestionReviewCardProps) => {
252 |   const chunks = Array.isArray(question.source_chunks)
253 |     ? (question.source_chunks as SourceChunk[])
254 |     : [];
255 |   const firstChunk = chunks[0];
256 |
257 |   return (
258 |     <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
259 |       <div className="p-4 space-y-3">
260 |         {/* Question preview */}
261 |         <QuestionPreview
262 |           questionText={question.question_text}
263 |           questionType={
264 |             question.question_type as
265 |             | "mcq"
266 |             | "true_false"
267 |             | "short_answer"
268 |             | "fill_in_blank"
269 |           }
270 |           options={
271 |             Array.isArray(question.options)
272 |               ? (question.options as { key: string; text: string }[])
273 |               : null
274 |           }
275 |           disabled
276 |         />
277 |
278 |         {/* Badges row */}
279 |         <div className="flex items-center gap-2 flex-wrap">
280 |           <DifficultyBadge difficulty={question.difficulty_rating} />
281 |           <Badge
282 |             className={` ${
283 |               BLOOM_COLORS[question.bloom_level] ?? ""
284 |             } text-xs font-bold tracking-wide uppercase border-transparent`}
285 |             >
286 |               {BLOOM_LABELS[question.bloom_level] ??
287 |               `Level ${question.bloom_level}`}
288 |             </Badge>
289 |         </div>
290 |
291 |         {/* Source material excerpt */}
292 |         {firstChunk?.chunk_text && (
293 |           <div className="rounded-lg bg-slate-50 p-3">
294 |             <p className="text-[10px] font-black tracking-widest uppercase text-gray-400 mb-1">
295 |               Source Material
296 |             </p>
297 |             <p className="text-xs text-gray-600 line-clamp-3">
298 |               {firstChunk.chunk_text}
299 |             </p>
300 |             {firstChunk.source_filename && (
301 |               <p className="text-[10px] text-gray-400 mt-1">
302 |                 {firstChunk.source_filename}
303 |               </p>
304 |             )}
305 |           </div>
306 |         )}
307 |
308 |         {/* Action buttons */}
309 |         <div className="flex items-center gap-2 pt-1">
310 |           <Button
311 |             size="sm"
312 |             variant="outline"
313 |             disabled={isApproving}
314 |             onClick={() => onApprove(question.id)}
315 |             className="text-green-700 border-green-300 hover:bg-green-50"
316 |           >
317 |             <Check className="h-4 w-4" />
318 |             Approve
319 |           </Button>
320 |           <Button
321 |             size="sm"
322 |             variant="outline"
323 |             disabled={isRejecting}
324 |             onClick={() => onReject(question.id)}
325 |             className="text-red-700 border-red-300 hover:bg-red-50"
326 |           >
327 |             <X className="h-4 w-4" />
328 |             Reject
329 |           </Button>
330 |         </div>
331 |       </div>
332 |     </Card>
333 |   );
334 | };
335 |
336 | export default ReviewQueuePage;
337 |

```

TYPE: .tsx | LINES: 1-955 | SHA256: 9cceb8254b3c72914415d4a170da6762918115d61082d23db1363ebe33bfd3ca

```

102 | const updateQuestion = useUpdateQuizQuestion();
103 | const [options, setOptions] = useState<string[]>(  
104 |   existingQuestion?.options ?? ["", ""]  
105 | );  
106 |  
107 | const form = useForm<QuestionFormData>({  
108 |   resolver: zodResolver(questionFormSchema) as never,  
109 |   defaultValues: existingQuestion  
110 |   ? {  
111 |     question_text: existingQuestion.question_text,  
112 |     question_type: existingQuestion.question_type,  
113 |     options: existingQuestion.options,  
114 |     correct_answer: existingQuestion.correct_answer,  
115 |     points: existingQuestion.points,  
116 |     sort_order: existingQuestion.sort_order,  
117 |   }  
118 |   : {  
119 |     question_text: "",  
120 |     question_type: "mcq_single",  
121 |     options: ["", ""],  
122 |     correct_answer: "",  
123 |     points: 1,  
124 |     sort_order: nextSortOrder,  
125 |   },  
126 | });  
127 |  
128 | const questionType = form.watch("question_type");  
129 |  
130 | const handleTypeChange = (type: string) => {  
131 |   form.setValue("question_type", type as QuestionFormData["question_type"]);  
132 |   if (type === "true_false") {  
133 |     setOptions(["True", "False"]);  
134 |     form.setValue("options", ["True", "False"]);  
135 |     form.setValue("correct_answer", "True");  
136 |   } else if (type === "short_answer" || type === "fill_blank") {  
137 |     setOptions([]);  
138 |     form.setValue("options", null);  
139 |     form.setValue("correct_answer", "");  
140 |   } else {  
141 |     if (options.length < 2) {  
142 |       setOptions(["", ""]);  
143 |       form.setValue("options", ["", ""]);  
144 |     }  
145 |   }  
146 | };  
147 |  
148 | const onSubmit = (data: QuestionFormData) => {  
149 |   const finalOptions =  
150 |     data.question_type === "short_answer"  
151 |     ? null  
152 |     : options.filter(Boolean).length > 0  
153 |     ? options.filter(Boolean)  
154 |     : null;  
155 |  
156 |   const payload = { ...data, options: finalOptions, quiz_id: quizId };  
157 |  
158 |   if (existingQuestion) {  
159 |     updateQuestion.mutate(  
160 |       { ...payload, id: existingQuestion.id },  
161 |       {  
162 |         onSuccess: () => {  
163 |           toast.success("Question updated");  
164 |           onOpenChange(false);  
165 |         },  
166 |         onError: (err) => toast.error(err.message),  
167 |       }  
168 |     );  
169 |   } else {  
170 |     createQuestion.mutate(payload, {  
171 |       onSuccess: () => {  
172 |         toast.success("Question added");  
173 |         onOpenChange(false);  
174 |       },  
175 |       onError: (err) => toast.error(err.message),  
176 |     });  
177 |   }  
178 | };  
179 |  
180 | const isPending = createQuestion.isPending || updateQuestion.isPending;  
181 |  
182 | return (  
183 |   <Dialog open={open} onOpenChange={onOpenChange}>  
184 |     <DialogContent className="max-w-lg max-h-[85vh] overflow-y-auto">  
185 |       <DialogHeader>  
186 |         <DialogTitle>  
187 |           {existingQuestion ? "Edit Question" : "Add Question"}  
188 |         </DialogTitle>  
189 |       </DialogHeader>  
190 |       <Form {...form}>  
191 |         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">  
192 |           <FormField>  
193 |             control={form.control}  
194 |             name="question_type"  
195 |             render={({ field }) => (  
196 |               <FormItem>  
197 |                 <FormLabel>Question Type</FormLabel>  
198 |                 <Select>  
199 |                   value={field.value}  
200 |                   onChange={(v) => {  
201 |                     field.onChange(v);  
202 |                     handleTypeChange(v);  
203 |                   }}  
204 |                 >  
205 |                   <FormControl>

```

```

206         <SelectTrigger className="bg-white">
207             <SelectValue />
208         </SelectTrigger>
209     </FormControl>
210     <SelectContent>
211         {Object.entries(QUESTION_TYPE_LABELS).map(
212             ([val, label]) => (
213                 <SelectItem key={val} value={val}>
214                     {label}
215                 </SelectItem>
216             )
217         )}
218     </SelectContent>
219 </Select>
220 <FormMessage />
221 </FormItem>
222 }}
223 />
224
225 <FormField
226     control={form.control}
227     name="question_text"
228     render={({ field }) => (
229         <FormItem>
230             <FormLabel>Question Text</FormLabel>
231             <FormControl>
232                 <Textarea
233                     rows={3}
234                     placeholder="Enter question..."
235                     {...field}
236                 />
237             </FormControl>
238             <FormMessage />
239         </FormItem>
240     )}
241 />
242
243 {(questionType === "mcq_single" ||
244     questionType === "mcq_multi") && (
245     <div className="space-y-2">
246         <Label>Options</Label>
247         {options.map((opt, idx) => (
248             <div key={idx} className="flex items-center gap-2">
249                 <span className="text-xs text-gray-400 w-6">
250                     {String.fromCharCode(65 + idx)}.
251                 </span>
252                 <Input
253                     value={opt}
254                     onChange={(e) => {
255                         const next = [...options];
256                         next[idx] = e.target.value;
257                         setOptions(next);
258                         form.setValue("options", next);
259                     }}
260                     placeholder={`Option ${String.fromCharCode(65 + idx)}}`
261                 />
262                 {options.length > 2 && (
263                     <Button
264                         type="button"
265                         variant="ghost"
266                         size="sm"
267                         onClick={() => {
268                             const next = options.filter((_, i) => i !== idx);
269                             setOptions(next);
270                             form.setValue("options", next);
271                         }}
272                     >
273                         <Trash2 className="h-4 w-4 text-red-500" />
274                     </Button>
275                 )}
276             </div>
277         )}
278     )}
279     {options.length < 6 && (
280         <Button
281             type="button"
282             variant="outline"
283             size="sm"
284             onClick={() => {
285                 setOptions([...options, ""]);
286                 form.setValue("options", [...options, ""]);
287             }}
288             >
289                 <Plus className="h-4 w-4 me-1" /> Add Option
290             </Button>
291     )}
292 </div>
293 ))
294
295 {questionType === "true_false" && (
296     <FormField
297         control={form.control}
298         name="correct_answer"
299         render={({ field }) => (
300             <FormItem>
301                 <FormLabel>Correct Answer</FormLabel>
302                 <Select
303                     value={typeof field.value === "string" ? field.value : ""}
304                     onChange={field.onChange}
305                 >
306                     <FormControl>
307                         <SelectTrigger className="bg-white">
308                             <SelectValue />
309                         </SelectTrigger>
310                     </FormControl>

```



```

310         <SelectContent>
311             <SelectItem value="True">True</SelectItem>
312             <SelectItem value="False">False</SelectItem>
313         </SelectContent>
314     </Select>
315     <FormMessage />
316 </FormItem>
317 </>
318 </>
319 </>
320
321 {questionType === "mcq_single" && (
322     <FormField
323         control={form.control}
324         name="correct_answer"
325         render={({ field }) => (
326             <FormItem>
327                 <FormLabel>Correct Answer</FormLabel>
328                 <Select
329                     value={typeof field.value === "string" ? field.value : ""}
330                     onChange={field.onChange}
331                 >
332                     <FormControl>
333                         <SelectTrigger className="bg-white">
334                             <SelectValue placeholder="Select correct option" />
335                         </SelectTrigger>
336                     </FormControl>
337                     <SelectContent>
338                         {options.filter(Boolean).map((opt, idx) => (
339                             <SelectItem key={idx} value={opt}>
340                                 {opt}
341                             </SelectItem>
342                         ))}
343                     </SelectContent>
344                 </Select>
345                 <FormMessage />
346             </FormItem>
347         )}
348     </>
349 </>
350
351 {questionType === "mcq_multi" && (
352     <FormField
353         control={form.control}
354         name="correct_answer"
355         render={({ field }) => (
356             <FormItem>
357                 <FormLabel>
358                     Correct Answers (select all that apply)
359                 </FormLabel>
360                 <div className="space-y-2">
361                     {options.filter(Boolean).map((opt, idx) => {
362                         const selected = Array.isArray(field.value)
363                           ? field.value
364                           : [];
365                         return (
366                             <div key={idx} className="flex items-center gap-2">
367                                 <Checkbox
368                                     checked={selected.includes(opt)}
369                                     onChange={(checked) => {
370                                         const next = checked
371                                           ? [...selected, opt]
372                                           : selected.filter((v: string) => v !== opt);
373                                         field.onChange(next);
374                                     }}
375                                 </>
376                                 <span className="text-sm">{opt}</span>
377                             </div>
378                         );
379                     })}
380                 </div>
381                 <FormMessage />
382             </FormItem>
383         )}
384     </>
385 </>
386
387 {(questionType === "short_answer" ||
388   questionType === "fill_blank") && (
389     <FormField
390         control={form.control}
391         name="correct_answer"
392         render={({ field }) => (
393             <FormItem>
394                 <FormLabel>Correct Answer</FormLabel>
395                 <FormControl>
396                     <Input
397                         placeholder="Expected answer..."
398                         value={
399                             typeof field.value === "string" ? field.value : ""
400                         }
401                         onChange={(e) => field.onChange(e.target.value)}
402                     </>
403                 </FormControl>
404                 <FormMessage />
405             </FormItem>
406         )}
407     </>
408 </>
409
410 <FormField
411     control={form.control}
412     name="points"
413     render={({ field }) => (

```

[illegible]

```

518 // Re-populate when quiz data loads
519 if (
520   existingQuiz &&
521   !form.formState.isDirty &&
522   form.getValues("title") === "" &&
523   existingQuiz.title
524 ) {
525   form.reset({
526     title: existingQuiz.title,
527     description: existingQuiz.description ?? "",
528     course_id: existingQuiz.course_id,
529     clo_ids: existingQuiz.clo_ids,
530     time_limit_minutes: existingQuiz.time_limit_minutes,
531     max_attempts: existingQuiz.max_attempts,
532     is_published: existingQuiz.is_published,
533     due_date: existingQuiz.due_date?.includes("T")
534       ? existingQuiz.due_date.slice(0, 16)
535       : existingQuiz.due_date ?? "",
536   });
537 }
538
539 const onSubmit = (data: QuizMetaFormData) => {
540   const isoDate = data.due_date.includes("Z")
541     ? data.due_date
542     : new Date(data.due_date).toISOString();
543
544   if (isEditMode && id) {
545     updateQuiz.mutate(
546       {
547         id,
548         title: data.title,
549         description: data.description,
550         clo_ids:
551           data.clo_ids as `${string}-${string}-${string}-${string}-${string}`[],
552         time_limit_minutes: data.time_limit_minutes,
553         max_attempts: data.max_attempts,
554         is_published: data.is_published,
555         due_date: isoDate,
556       },
557       {
558         onSuccess: () => {
559           toast.success("Quiz updated");
560           if (user?.id) {
561             logAuditEvent({
562               action: "update",
563               entity_type: "quiz",
564               entity_id: id,
565               changes: data,
566               performed_by: user.id,
567             });
568           }
569         },
570         onError: (err) => toast.error(err.message),
571       }
572     );
573   } else {
574     createQuiz.mutate(
575       {
576         ...data,
577         course_id:
578           data.course_id as `${string}-${string}-${string}-${string}-${string}`,
579         clo_ids:
580           data.clo_ids as `${string}-${string}-${string}-${string}-${string}`[],
581         due_date: isoDate,
582         questions: [],
583         is_adaptive: false,
584         practice_mode_enabled: false,
585       },
586       {
587         onSuccess: (result) => {
588           toast.success("Quiz created – now add questions");
589           if (user?.id) {
590             logAuditEvent({
591               action: "create",
592               entity_type: "quiz",
593               entity_id: (result as { id: string })?.id ?? "",
594               changes: data,
595               performed_by: user.id,
596             });
597           }
598           const newId = (result as { id: string })?.id;
599           if (newId)
600             navigate(`/teacher/quizzes/${newId}/build`, { replace: true });
601         },
602         onError: (err) => toast.error(err.message),
603       }
604     );
605   }
606 };
607
608 const handleDeleteQuestion = (questionId: string) => {
609   if (!id) return;
610   deleteQuestion.mutate(
611     { id: questionId, quiz_id: id },
612     {
613       onSuccess: () => toast.success("Question removed"),
614       onError: (err) => toast.error(err.message),
615     }
616   );
617 };
618
619 const isPending = createQuiz.isPending || updateQuiz.isPending;
620
621 if (isEditMode && isLoadingQuiz) {

```

```

622 |     return (
623 |       <div className="flex items-center justify-center py-12">
624 |         <Loader2 className="h-8 w-8 animate-spin text-blue-600" />
625 |       </div>
626 |     );
627 |   }
628 |
629 |   return (
630 |     <div className="space-y-6 max-w-3xl">
631 |       <div className="flex items-center gap-4">
632 |         <Button variant="ghost" size="sm" onClick={() => navigate(-1)}>
633 |           <ArrowLeft className="h-4 w-4" />
634 |           Back
635 |         </Button>
636 |         <h1 className="text-2xl font-bold tracking-tight">
637 |           {isEditMode ? "Edit Quiz" : "Create Quiz"}
638 |         </h1>
639 |       </div>
640 |
641 |       {/* Quiz Metadata Form */}
642 |       <Card className="bg-white border-0 shadow-md rounded-xl p-6">
643 |         <h2 className="text-lg font-bold tracking-tight mb-4">Quiz Details</h2>
644 |         <Form {...form}>
645 |           <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
646 |             <FormField
647 |               control={form.control}
648 |               name="title"
649 |               render={({ field }) => (
650 |                 <FormItem>
651 |                   <FormLabel>Title</FormLabel>
652 |                   <FormControl>
653 |                     <Input
654 |                       placeholder="e.g. Midterm Quiz – Data Structures"
655 |                       {...field}
656 |                     />
657 |                   </FormControl>
658 |                   <FormMessage />
659 |                 </FormItem>
660 |               )}
661 |             />
662 |
663 |             <FormField
664 |               control={form.control}
665 |               name="description"
666 |               render={({ field }) => (
667 |                 <FormItem>
668 |                   <FormLabel>Description</FormLabel>
669 |                   <FormControl>
670 |                     <Textarea
671 |                       rows={2}
672 |                       placeholder="Describe the quiz objectives..."
673 |                       {...field}
674 |                     />
675 |                   </FormControl>
676 |                   <FormMessage />
677 |                 </FormItem>
678 |               )}
679 |             />
680 |
681 |             <FormField
682 |               control={form.control}
683 |               name="course_id"
684 |               render={({ field }) => (
685 |                 <FormItem>
686 |                   <FormLabel>Course</FormLabel>
687 |                   <Select
688 |                     onChange={field.onChange}
689 |                     value={field.value}
690 |                     disabled={isLoadingCourses || isEditMode}
691 |                   >
692 |                     <FormControl>
693 |                       <SelectTrigger className="bg-white">
694 |                         <SelectValue placeholder="Select a course" />
695 |                       </SelectTrigger>
696 |                     </FormControl>
697 |                     <SelectContent>
698 |                       {courses.map((c) => (
699 |                         <SelectItem key={c.id} value={c.id}>
700 |                           {c.code} – {c.name}
701 |                         </SelectItem>
702 |                       ))}
703 |                     </SelectContent>
704 |                   </Select>
705 |                   <FormMessage />
706 |                 </FormItem>
707 |               )}
708 |             />
709 |
710 |             {/* CLO Linking */}
711 |             {selectedCourseId ? (
712 |               isLoadingCLOs ? (
713 |                 <div className="animate-shimmer h-16 rounded-lg" />
714 |               ) : clos.length === 0 ? (
715 |                 <InlineNoCLOs />
716 |               ) : (
717 |                 <FormField
718 |                   control={form.control}
719 |                   name="clo_ids"
720 |                   render={() => (
721 |                     <FormItem>
722 |                       <FormLabel>Linked CLOs</FormLabel>
723 |                       <div className="space-y-2">
724 |                         {clos.map((clo) => (
725 |                           <FormField

```

```

726         key={clo.id}
727         control={form.control}
728         name="clo_ids"
729         render={({ field }) => (
730             <FormItem className="flex items-center gap-3">
731                 <FormControl>
732                     <Checkbox
733                         checked={field.value?.includes(clo.id)}
734                         onChange={(checked) => {
735                             const current = field.value ?? [];
736                             field.onChange(
737                                 checked
738                                 ? [...current, clo.id]
739                                 : current.filter(
740                                     (v: string) => v !== clo.id
741                                 )
742                             );
743                         }}
744                     />
745                 </FormControl>
746                 <FormLabel className="text-sm font-normal cursor-pointer">
747                     {clo.title}
748                 </FormLabel>
749             </FormItem>
750         )}
751     />
752 )}
753 </div>
754 <FormMessage />
755 </FormItem>
756 )}
757 />
758 ) : (
759     <p className="text-sm text-gray-500">
760         Select a course to see CLOs.
761     </p>
762 )}
763 )}
764
765 <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
766     <FormField
767         control={form.control}
768         name="due_date"
769         render={({ field }) => (
770             <FormItem>
771                 <FormLabel>Due Date</FormLabel>
772                 <FormControl>
773                     <Input
774                         type="datetime-local"
775                         {...field}
776                         value={
777                             field.value?.includes("T")
778                             ? field.value.slice(0, 16)
779                             : field.value
780                         }
781                     />
782                 </FormControl>
783                 <FormMessage />
784             </FormItem>
785         )}
786     />
787     <FormField
788         control={form.control}
789         name="time_limit_minutes"
790         render={({ field }) => (
791             <FormItem>
792                 <FormLabel>Time Limit (min)</FormLabel>
793                 <FormControl>
794                     <Input
795                         type="number"
796                         min={1}
797                         placeholder="30"
798                         value={field.value ?? ""}
799                         onChange={(e) =>
800                             field.onChange(
801                                 e.target.value ? Number(e.target.value) : null
802                             )
803                         }
804                     />
805                 </FormControl>
806                 <FormMessage />
807             </FormItem>
808         )}
809     />
810     <FormField
811         control={form.control}
812         name="max_attempts"
813         render={({ field }) => (
814             <FormItem>
815                 <FormLabel>Max Attempts</FormLabel>
816                 <FormControl>
817                     <Input
818                         type="number"
819                         min={1}
820                         value={field.value ?? 1}
821                         onChange={(e) => field.onChange(Number(e.target.value))}
822                     />
823                 </FormControl>
824                 <FormMessage />
825             </FormItem>
826         )}
827     />
828 </div>
829

```

```

830     { /* Publish Toggle */ }
831     <FormField
832       control={form.control}
833       name="is_published"
834       render={({ field }) => (
835         <div className="flex items-center justify-between gap-4 rounded-lg border border-slate-200 p-4
836           <div className="space-y-0.5">
837             <Label
838               htmlFor="is-published"
839               className="text-sm font-medium"
840             >
841               Publish Quiz
842             </Label>
843             <p className="text-xs text-gray-500">
844               Make this quiz visible and available to students
845             </p>
846           </div>
847           <Switch
848             id="is-published"
849             checked={field.value}
850             onChange={field.onChange}
851             aria-label="Publish Quiz"
852           />
853         </div>
854       )}
855     />
856
857     <Button type="submit" disabled={isPending} variant="tactile">
858       {isPending && <Loader2 className="h-4 w-4 animate-spin me-1" />}
859       {isEditMode ? "Update Quiz" : "Create Quiz"}
860     </Button>
861   </form>
862 </Form>
863 </Card>
864
865 { /* Questions Section - only in edit mode */ }
866 {isEditMode && id && (
867   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
868     <div
869       className="px-6 py-4 flex items-center justify-between"
870       style={{
871         background: "var(--brand-gradient)",
872       }}
873     >
874       <h2 className="text-lg font-bold tracking-tight text-white">
875         Questions
876       </h2>
877       <Button
878         size="sm"
879         variant="secondary"
880         onClick={() => {
881           setEditingQuestion(undefined);
882           setQuestionDialogOpen(true);
883         }}
884       >
885         <Plus className="h-4 w-4 me-1" /> Add Question
886       </Button>
887     </div>
888     <div className="p-6 space-y-3">
889       {isLoadingQuestions ? (
890         <div className="animate-shimmer h-24 rounded-lg" />
891       ) : !questions || questions.length === 0 ? (
892         <InlineNoQuestions />
893       ) : (
894         questions.map((q, idx) => (
895           <div
896             key={q.id}
897             className="flex items-start justify-between gap-3 rounded-lg border border-slate-200 p-4"
898           >
899             <div className="flex-1 min-w-0">
900               <p className="text-sm font-medium">
901                 <span className="text-gray-400 me-2">Q{idx + 1}</span>
902                 {q.question_text}
903               </p>
904               <div className="flex items-center gap-3 mt-1">
905                 <span className="text-xs text-gray-400">
906                   {QUESTION_TYPE_LABELS[q.question_type] ??
907                     q.question_type}
908                 </span>
909                 <span className="text-xs text-gray-400">
910                   {q.points} pts
911                 </span>
912               </div>
913             </div>
914             <div className="flex items-center gap-1 shrink-0">
915               <Button
916                 variant="ghost"
917                 size="sm"
918                 onClick={() => {
919                   setEditingQuestion(q);
920                   setQuestionDialogOpen(true);
921                 }}
922               >
923                 <Pencil className="h-4 w-4" />
924               </Button>
925               <Button
926                 variant="ghost"
927                 size="sm"
928                 onClick={() => handleDeleteQuestion(q.id)}
929               >
930                 <Trash2 className="h-4 w-4 text-red-500" />
931               </Button>
932             </div>
933           </div>

```

```

934 |         ))
935 |     }}
936 |     </div>
937 | </Card>
938 | }}
939 |
940 | {/* Question Dialog */}
941 | {isEditMode && id && (
942 |     <QuestionDialog
943 |         open={questionDialogOpen}
944 |         onOpenChange={setQuestionDialogOpen}
945 |         quizId={id}
946 |         existingQuestion={editingQuestion}
947 |         nextSortOrder={questions?.length ?? 0}
948 |     />
949 |     )}
950 | </div>
951 | );
952 | };
953 |
954 | export default QuizBuilder;
955 |

```

FILE: src/pages/teacher/quizzes/QuizForm.tsx

```
TYPE: .tsx | LINES: 1-642 | SHA256: e499eb89c828dba6889590306680e808532b05ebfc96e93665a4d7d153f1be43
```

[illegible]

```

79 | <h2 className="text-lg font-bold tracking-tight mb-4">
80 |   Basic Details
81 | </h2>
82 | <div className="space-y-4">
83 |   <FormField
84 |     control={form.control}
85 |     name="title"
86 |     render={({ field }) => (
87 |       <FormItem>
88 |         <FormLabel>Title</FormLabel>
89 |         <FormControl>
90 |           <Input
91 |             placeholder="e.g. Midterm Quiz – Data Structures"
92 |             {...field}
93 |           />
94 |         </FormControl>
95 |         <FormMessage />
96 |       </FormItem>
97 |     )}
98 |   />
99 |
100 |   <FormField
101 |     control={form.control}
102 |     name="description"
103 |     render={({ field }) => (
104 |       <FormItem>
105 |         <FormLabel>Description</FormLabel>
106 |         <FormControl>
107 |           <Textarea
108 |             placeholder="Describe the quiz objectives..."
109 |             rows={3}
110 |             {...field}
111 |           />
112 |         </FormControl>
113 |         <FormMessage />
114 |       </FormItem>
115 |     )}
116 |   />
117 |
118 |   <FormField
119 |     control={form.control}
120 |     name="course_id"
121 |     render={({ field }) => (
122 |       <FormItem>
123 |         <FormLabel>Course</FormLabel>
124 |         <Select
125 |           onChange={field.onChange}
126 |           value={field.value}
127 |           disabled={isLoadingCourses || isEditMode}
128 |         >
129 |           <FormControl>
130 |             <SelectTrigger className="bg-white">
131 |               <SelectValue placeholder="Select a course" />
132 |             </SelectTrigger>
133 |           </FormControl>
134 |           <SelectContent>
135 |             {courses.map((course) => (
136 |               <SelectItem key={course.id} value={course.id}>
137 |                 {course.code} – {course.name}
138 |               </SelectItem>
139 |             ))}
140 |           </SelectContent>
141 |         </Select>
142 |         <FormMessage />
143 |       </FormItem>
144 |     )}
145 |   />
146 |
147 |   <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
148 |     <FormField
149 |       control={form.control}
150 |       name="due_date"
151 |       render={({ field }) => (
152 |         <FormItem>
153 |           <FormLabel>Due Date</FormLabel>
154 |           <FormControl>
155 |             <Input
156 |               type="datetime-local"
157 |               {...field}
158 |               value={
159 |                 field.value
160 |                   ? field.value.includes("T")
161 |                     ? field.value.slice(0, 16)
162 |                     : field.value
163 |                 : ""
164 |               }
165 |             />
166 |           </FormControl>
167 |           <FormMessage />
168 |         </FormItem>
169 |       )}
170 |     />
171 |
172 |     <FormField
173 |       control={form.control}
174 |       name="time_limit_minutes"
175 |       render={({ field }) => (
176 |         <FormItem>
177 |           <FormLabel>Time Limit (minutes)</FormLabel>
178 |           <FormControl>
179 |             <Input
180 |               type="number"
181 |               min={1}
182 |               placeholder="30"

```



```

183 |         {...field}
184 |         onChange={(e) =>
185 |             field.onChange(
186 |                 e.target.value ? Number(e.target.value) : null
187 |             )
188 |         }
189 |         value={field.value ?? ""}
190 |     />
191 | </FormControl>
192 | <FormMessage />
193 | </FormItem>
194 | )}
195 | />
196 |
197 | <FormField
198 |     control={form.control}
199 |     name="max_attempts"
200 |     render={({ field }) => (
201 |         <FormItem>
202 |             <FormLabel>Max Attempts</FormLabel>
203 |             <FormControl>
204 |                 <Input
205 |                     type="number"
206 |                     min={1}
207 |                     placeholder="1"
208 |                     {...field}
209 |                     onChange={(e) => field.onChange(Number(e.target.value))}
210 |                     value={field.value ?? 1}
211 |                 />
212 |             </FormControl>
213 |             <FormMessage />
214 |         </FormItem>
215 |     )}
216 | />
217 | </div>
218 | </div>
219 | </Card>
220 |
221 | {/ * Section 2: CLO Linking */}
222 | <Card className="bg-white border-0 shadow-md rounded-xl p-6">
223 |     <h2 className="text-lg font-bold tracking-tight mb-4">CLO Linking</h2>
224 |     {selectedCourseId ? (
225 |         isLoadingCLOs ? (
226 |             <div className="animate-shimmer h-20 rounded-lg" />
227 |         ) : clos.length === 0 ? (
228 |             <InlineNoCLOs />
229 |         ) : (
230 |             <FormField
231 |                 control={form.control}
232 |                 name="clo_ids"
233 |                 render={() => (
234 |                     <FormItem>
235 |                         <div className="space-y-2">
236 |                             {clos.map((clo) => (
237 |                                 <FormField
238 |                                     key={clo.id}
239 |                                     control={form.control}
240 |                                     name="clo_ids"
241 |                                     render={({ field }) => (
242 |                                         <FormItem className="flex items-center gap-3">
243 |                                             <FormControl>
244 |                                                 <Checkbox
245 |                                                     checked={field.value?.includes(clo.id)}
246 |                                                     onChangeChange={(checked) => {
247 |                                                         const current = field.value ?? [];
248 |                                                         field.onChange(
249 |                                                             checked
250 |                                                             ? [...current, clo.id]
251 |                                                             : current.filter(
252 |                                                                 (id: string) => id !== clo.id
253 |                                                             )
254 |                                                         );
255 |                                                     }}
256 |                                                 />
257 |                                             </FormControl>
258 |                                             <FormLabel className="text-sm font-normal cursor-pointer">
259 |                                                 {clo.title}
260 |                                             </FormLabel>
261 |                                         </FormItem>
262 |                                     )}
263 |                                 </div>
264 |                             )}
265 |                         </div>
266 |                         <FormMessage />
267 |                     </FormItem>
268 |                 )}
269 |             />
270 |         )
271 |     ) : (
272 |         <p className="text-sm text-gray-500">
273 |             Select a course to see available CLOs.
274 |         </p>
275 |     )}
276 | </Card>
277 |
278 | {/ * Section 3: Quiz Settings – Adaptive & Practice Mode */}
279 | <Card className="bg-white border-0 shadow-md rounded-xl p-6">
280 |     <h2 className="text-lg font-bold tracking-tight mb-4">
281 |         Quiz Settings
282 |     </h2>
283 |     <div className="space-y-4">
284 |         {/ * Adaptive Mode Toggle */}
285 |         <FormField
286 |             control={form.control}

```

```

287 |     name="is_adaptive"
288 |     render={({ field }) => (
289 |       <div className="flex items-center justify-between gap-4 rounded-lg border border-slate-200 p-4"
290 |         <div className="space-y-0.5">
291 |           <Label
292 |             htmlFor="is-adaptive"
293 |             className="text-sm font-medium"
294 |           >
295 |             Enable Adaptive Mode
296 |           </Label>
297 |           <p className="text-xs text-gray-500">
298 |             Questions adapt to each student's ability level in real
299 |             time
300 |           </p>
301 |         </div>
302 |         <Switch
303 |           id="is-adaptive"
304 |           checked={field.value}
305 |           onChange={field.onChange}
306 |           aria-label="Enable Adaptive Mode"
307 |         />
308 |       </div>
309 |     )}
310 |   />
311 |
312 |   {/* Adaptation Config – shown only when adaptive is enabled */}
313 |   {isAdaptive && (
314 |     <div className="ms-4 space-y-3 border-s-2 border-blue-200 ps-4">
315 |       <FormField
316 |         control={form.control}
317 |         name="adaptation_config.initial_difficulty"
318 |         render={({ field }) => (
319 |           <FormItem>
320 |             <FormLabel>Initial Difficulty (1.0-5.0)</FormLabel>
321 |             <FormControl>
322 |               <Input
323 |                 type="number"
324 |                 min={1}
325 |                 max={5}
326 |                 step={0.1}
327 |                 placeholder="2.5"
328 |                 {...field}
329 |                 onChange={(e) =>
330 |                   field.onChange(
331 |                     e.target.value
332 |                       ? Number(e.target.value)
333 |                       : undefined
334 |                   )
335 |               }
336 |               value={field.value ?? ""}
337 |             </Input>
338 |           </FormControl>
339 |           <FormMessage />
340 |         </FormItem>
341 |       )}
342 |     />
343 |     <div className="grid grid-cols-1 md:grid-cols-3 gap-3">
344 |       <FormField
345 |         control={form.control}
346 |         name="adaptation_config.difficulty_step_up"
347 |         render={({ field }) => (
348 |           <FormItem>
349 |             <FormLabel>Step Up</FormLabel>
350 |             <FormControl>
351 |               <Input
352 |                 type="number"
353 |                 min={0.1}
354 |                 max={2}
355 |                 step={0.1}
356 |                 placeholder="0.3"
357 |                 {...field}
358 |                 onChange={(e) =>
359 |                   field.onChange(Number(e.target.value))
360 |                 }
361 |                 value={field.value ?? 0.3}
362 |               </Input>
363 |             </FormControl>
364 |             <FormMessage />
365 |           </FormItem>
366 |         )}
367 |       />
368 |       <FormField
369 |         control={form.control}
370 |         name="adaptation_config.difficulty_step_down"
371 |         render={({ field }) => (
372 |           <FormItem>
373 |             <FormLabel>Step Down</FormLabel>
374 |             <FormControl>
375 |               <Input
376 |                 type="number"
377 |                 min={0.1}
378 |                 max={2}
379 |                 step={0.1}
380 |                 placeholder="0.5"
381 |                 {...field}
382 |                 onChange={(e) =>
383 |                   field.onChange(Number(e.target.value))
384 |                 }
385 |                 value={field.value ?? 0.5}
386 |               </Input>
387 |             </FormControl>
388 |             <FormMessage />
389 |           </FormItem>
390 |         )}

```

[illegible]

[illegible]

[illegible]

```

1 import { type ColumnDef } from "@tanstack/react-table";
2 import {
3   ArrowUpDown,
4   MoreHorizontal,
5   Pencil,
6   Trash2,
7   Copy,
8   Eye,
9 } from "lucide-react";
10 import { Badge } from "@components/ui/badge";
11 import { Button } from "@components/ui/button";
12 import {
13   DropdownMenu,
14   DropdownMenuContent,
15   DropdownMenuItem,
16   DropdownMenuTrigger,
17 } from "@components/ui/dropdown-menu";
18 import { resolveName } from "@lib/db/resolveName";
19 import type { Rubric, RubricWithRelations } from "@hooks/useRubrics";
20
21 export const createColumns = (
22   {
23     onEdit: (rubric: Rubric) => void,
24     onDelete: (rubric: Rubric) => void,
25     onCopy: (rubric: Rubric) => void,
26     onPreview: (rubric: Rubric) => void
27   }: ColumnDef<RubricWithRelations>[] => [
28     {
29       accessorKey: "title",
30       header: ({ column }) => (
31         <Button
32           variant="ghost"
33           size="sm"
34           className="-ms-3"
35           onClick={() => column.toggleSorting(column.getIsSorted() === "asc")}
36         >
37           Title
38         <ArrowUpDown className="h-4 w-4" />
39       </Button>
40     ),
41     cell: ({ row }) => (
42       <span className="font-medium">{row.getValue("title")}</span>
43     ),
44   },
45   {
46     id: "clo",
47     header: "CLO",
48     cell: ({ row }) => (
49       <span className="text-gray-500 truncate max-w-[160px] inline-block">
50         {resolveName(row.original.learning_outcomes?.title)}
51       </span>
52     ),
53   },
54   {
55     accessorKey: "is_template",
56     header: "Type",
57     cell: ({ row }) => {

```

```

57 | const isTemplate = row.getValue("is_template") as boolean;
58 | return (
59 |   <Badge
60 |     variant="outline"
61 |     className={
62 |       isTemplate
63 |       ? "bg-blue-50 text-blue-600 border-blue-200"
64 |       : "bg-gray-50 text-gray-600 border-gray-200"
65 |     }
66 |   >
67 |     {isTemplate ? "Template" : "Rubric"}
68 |   </Badge>
69 | );
70 | },
71 | },
72 | {
73 |   id: "actions",
74 |   header: "",
75 |   cell: ({ row }) => {
76 |     const rubric = row.original;
77 |     return (
78 |       <DropdownMenu>
79 |         <DropdownMenuTrigger asChild>
80 |           <Button variant="ghost" size="sm">
81 |             <MoreHorizontal className="h-4 w-4" />
82 |             <span className="sr-only">Open menu</span>
83 |           </Button>
84 |         </DropdownMenuTrigger>
85 |         <DropdownMenuContent align="end">
86 |           <DropdownMenuItem onClick={() => onPreview(rubric)}>
87 |             <Eye className="h-4 w-4" />
88 |             Preview
89 |           </DropdownMenuItem>
90 |           <DropdownMenuItem onClick={() => onEdit(rubric)}>
91 |             <Pencil className="h-4 w-4" />
92 |             Edit
93 |           </DropdownMenuItem>
94 |           <DropdownMenuItem onClick={() => onCopy(rubric)}>
95 |             <Copy className="h-4 w-4" />
96 |             Copy
97 |           </DropdownMenuItem>
98 |           <DropdownMenuItem
99 |             variant="destructive"
100 |             onClick={() => onDelete(rubric)}
101 |           >
102 |             <Trash2 className="h-4 w-4" />
103 |             Delete
104 |           </DropdownMenuItem>
105 |         </DropdownMenuContent>
106 |       </DropdownMenu>
107 |     );
108 |   },
109 | },
110 | );
111 |

```

FILE: src/pages/teacher/rubrics/RubricBuilder.tsx

```
TYPE: .tsx | LINES: 1-595 | SHA256: 593f799436390c3f549823673c577def5b48bece196c67eb2e3a6e92c4d12fe4
```

[illegible]

[illegible]

[illegible]

[illegible]

```

358         control={form.control}
359         name="title"
360         render={({ field }) => (
361             <FormItem>
362                 <FormLabel>Rubric Title</FormLabel>
363                 <FormControl>
364                     <Input placeholder="e.g. Essay Rubric" {...field} />
365                 </FormControl>
366                 <FormMessage />
367             </FormItem>
368         )}
369     />
370
371     <FormField
372         control={form.control}
373         name="clo_id"
374         render={({ field }) => (
375             <FormItem>
376                 <FormLabel>Linked CL0</FormLabel>
377                 <Select onChange={field.onChange} value={field.value}>
378                     <FormControl>
379                         <SelectTrigger>
380                             <SelectValue placeholder="Select a CL0" />
381                         </SelectTrigger>
382                     </FormControl>
383                     <SelectContent>
384                         {(clos ?? []).map((clo) => (
385                             <SelectItem key={clo.id} value={clo.id}>
386                                 {clo.title}
387                             </SelectItem>
388                         ))}
389                     </SelectContent>
390                 </Select>
391                 <FormMessage />
392             </FormItem>
393         )}
394     />
395 </div>
396
397 <FormField
398     control={form.control}
399     name="is_template"
400     render={({ field }) => (
401         <FormItem className="flex items-center gap-2">
402             <FormControl>
403                 <input
404                     type="checkbox"
405                     checked={field.value}
406                     onChange={field.onChange}
407                     className="h-4 w-4 rounded border-gray-300 text-blue-600 focus:ring-blue-500"
408                 />
409             </FormControl>
410             <FormLabel className="!mt-0 text-sm font-medium">
411                 Save as reusable template
412             </FormLabel>
413         </FormItem>
414     )}
415 />
416
417 /* Criteria / Levels Grid */
418 <div className="space-y-4">
419     <div className="flex items-center justify-between">
420         <h2 className="text-lg font-bold tracking-tight">
421             Criteria & Performance Levels
422         </h2>
423         <div className="flex items-center gap-2">
424             <Button
425                 type="button"
426                 variant="outline"
427                 size="sm"
428                 onClick={addLevel}
429             >
430                 <Plus className="h-4 w-4" /> Level
431             </Button>
432             <Button
433                 type="button"
434                 variant="outline"
435                 size="sm"
436                 onClick={addCriterion}
437             >
438                 <Plus className="h-4 w-4" /> Criterion
439             </Button>
440         </div>
441     </div>
442
443     <div className="overflow-x-auto">
444         <table className="w-full border-collapse">
445             <thead>
446                 <tr>
447                     <th className="p-2 text-start text-xs font-bold uppercase tracking-wider text-gray-500 w
448                         Criterion
449                     </th>
450                     {levelLabels.map((label, colIdx) => (
451                         <th
452                             key={colIdx}
453                             className="p-2 text-center min-w-[10rem]"
454                         >
455                             <div className="flex items-center justify-center gap-1">
456                                 <input
457                                     value={label}
458                                     onChange={(e) =>
459                                         updateLevelLabel(colIdx, e.target.value)
460                                     }
461                                 className="text-center text-xs font-bold h-8 max-w-[8rem]"

```

```

462     />
463     <Button
464       type="button"
465       variant="ghost"
466       size="sm"
467       className="h-6 w-6 p-0 text-gray-400 hover:text-red-500"
468       disabled={levelCount <= 2}
469       onClick={() => removeLevel(colIdx)}
470     >
471     <Trash2 className="h-3 w-3" />
472   </Button>
473 </div>
474 </th>
475 )}}
476 <th className="p-2 text-center text-xs font-bold uppercase tracking-wider text-gray-500"
477   Max
478 </th>
479 <th className="w-10" />
480 </tr>
481 </thead>
482 <tbody>
483   {criteria.map((criterion, rowIdx) => (
484     <tr key={rowIdx} className="border-t border-slate-200">
485       <td className="p-2 align-top">
486         <Input
487           value={criterion.criterion_name}
488           onChange={(e) =>
489             updateCriterionName(rowIdx, e.target.value)
490           }
491           placeholder={`Criterion ${rowIdx + 1}`}
492           className="text-sm"
493         />
494       </td>
495       {criterion.levels.map((level, colIdx) => (
496         <td key={colIdx} className="p-2 align-top">
497           <div className="space-y-1">
498             <Textarea
499               value={level.description}
500               onChange={(e) =>
501                 updateLevel(
502                   rowIdx,
503                   colIdx,
504                   "description",
505                   e.target.value
506                 )
507             }
508             placeholder="Description..."
509             className="text-xs min-h-[4rem] resize-none"
510             rows={3}
511           />
512           <Input
513             type="number"
514             min={0}
515             value={level.points}
516             onChange={(e) =>
517               updateLevel(
518                 rowIdx,
519                 colIdx,
520                 "points",
521                 Number(e.target.value) || 0
522               )
523             }
524             className="h-8 text-xs text-center w-20"
525             placeholder="Pts"
526           />
527         </div>
528       </td>
529     )}}
530     <td className="p-2 align-top text-center">
531       <span className="text-sm font-bold text-gray-700">
532         {criteriaMaxPoints[rowIdx] ?? 0}
533       </span>
534     </td>
535     <td className="p-2 align-top">
536       <Button
537         type="button"
538         variant="ghost"
539         size="sm"
540         className="h-8 w-8 p-0 text-gray-400 hover:text-red-500"
541         disabled={criteria.length <= 2}
542         onClick={() => removeCriterion(rowIdx)}
543       >
544       <Trash2 className="h-4 w-4" />
545     </Button>
546   </td>
547 </tr>
548 )}}
549 </tbody>
550 <tfoot>
551   <tr className="border-t-2 border-slate-300">
552     <td
553       className="p-2 text-end text-sm font-bold text-gray-700"
554       colspan={levelCount + 1}
555     >
556     Total Score
557   </td>
558   <td className="p-2 text-center">
559     <span className="text-lg font-black text-blue-600">
560       {totalScore}
561     </span>
562   </td>
563 </tr>
564 </tfoot>
565 </tfoot>

```

```

566 |         </table>
567 |     </div>
568 | </div>
569 |
570 |     { /* Submit */ }
571 |     <div className="flex items-center gap-3 pt-4">
572 |       <Button type="submit" disabled={isPending} variant="tactile">
573 |         {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
574 |         {isEdit ? "Update Rubric" : "Create Rubric"}
575 |       </Button>
576 |       <Button
577 |         type="button"
578 |         variant="outline"
579 |         onClick={() => navigate("/teacher/rubrics")}
580 |       >
581 |         Cancel
582 |       </Button>
583 |     </div>
584 |   </form>
585 | </Form>
586 | </Card>
587 |
588 |   { /* Rubric Preview */ }
589 |   {showPreview && <RubricPreview rubric={previewRubric} />}
590 | </div>
591 | );
592 | };
593 |
594 | export default RubricBuilder;
595 |

```

FILE: [src/pages/teacher/rubrics/RubricListPage.tsx](#)

TYPE: .tsx | LINES: 1-124 | SHA256: 03ef38fe430fc0f15a64daa2638dc4d17af12c5470a07ee96b0e986bb44aad20

```

1 | import { useMemo, useState } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { parseAsString, useQueryState } from "nuqs";
4 | import { Plus, Search } from "lucide-react";
5 | import { toast } from "sonner";
6 | import { DataTable } from "@components/shared/DataTable";
7 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
8 | import RubricPreviewDialog from "@components/shared/RubricPreviewDialog";
9 | import { Button } from "@components/ui/button";
10 | import { Input } from "@components/ui/input";
11 | import { useRubrics, useDeleteRubric, useCopyRubric } from "@hooks/useRubrics";
12 | import type { Rubric } from "@hooks/useRubrics";
13 | import { createColumns } from "../columns";
14 | import { NoCourses } from "@components/shared/EmptyState";
15 |
16 | const RubricListPage = () => {
17 |   const navigate = useNavigate();
18 |   const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
19 |   const [page, setPage] = useState(1);
20 |   const {
21 |     data: paginatedData,
22 |     isLoading,
23 |     isFetching,
24 |   } = useRubrics(undefined, {
25 |     page,
26 |   });
27 |   const deleteMutation = useDeleteRubric();
28 |   const copyMutation = useCopyRubric();
29 |
30 |   const [deleteTarget, setDeleteTarget] = useState<Rubric | null>(null);
31 |   const [previewTarget, setPreviewTarget] = useState<Rubric | null>(null);
32 |
33 |   const filtered = useMemo(() => {
34 |     const items = paginatedData?.data ?? [];
35 |     if (!search) return items;
36 |     const q = search.toLowerCase();
37 |     return items.filter((r) => r.title.toLowerCase().includes(q));
38 |   }, [paginatedData, search]);
39 |
40 |   const columns = useMemo(
41 |     () =>
42 |     createColumns(
43 |       (rubric) => navigate(`/teacher/rubrics/${rubric.id}/edit`),
44 |       (rubric) => setDeleteTarget(rubric),
45 |       (rubric) => {
46 |         copyMutation.mutate(rubric.id, {
47 |           onSuccess: () => toast.success("Rubric copied"),
48 |           onError: (err) => toast.error(err.message),
49 |         });
50 |       },
51 |       (rubric) => setPreviewTarget(rubric)
52 |     ),
53 |     [navigate, copyMutation]
54 |   );
55 |
56 |   return (
57 |     <div className="space-y-6">
58 |       <div className="flex items-center justify-between">
59 |         <h1 className="text-2xl font-bold tracking-tight">Rubrics</h1>
60 |         <Button
61 |           onClick={() => navigate("/teacher/rubrics/new")}
62 |           variant="tactile"
63 |         >
64 |           <Plus className="h-4 w-4" /> New Rubric
65 |         </Button>
66 |       </div>
67 |
68 |       <div className="flex items-center gap-4">
69 |         <div className="relative flex-1 max-w-sm">
70 |           <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />

```

```

71 |         <Input
72 |             placeholder="Search rubrics..."
73 |             value={search}
74 |             onChange={(e) => setSearch(e.target.value)}
75 |             className="ps-9"
76 |         />
77 |     </div>
78 | </div>
79 |
80 |     <DataTable
81 |         columns={columns}
82 |         data={filtered}
83 |         isLoading={isLoading}
84 |         isFetching={isFetching}
85 |         page={page}
86 |         pageSize={paginatedData?.pageSize}
87 |         totalCount={paginatedData?.count}
88 |         onPageChange={setPage}
89 |         emptyState={
90 |             filtered.length === 0 && !isLoading ? <NoCourses /> : undefined
91 |         }
92 |     />
93 |
94 |     <ConfirmDialog
95 |         open={!deleteTarget}
96 |         onOpenChange={(open) => !open && setDeleteTarget(null)}
97 |         title="Delete Rubric"
98 |         description={`Are you sure you want to delete "${deleteTarget?.title}"? This action cannot be undone.`}
99 |         confirmLabel="Delete"
100 |         variant="destructive"
101 |         isPending={deleteMutation.isPending}
102 |         onConfirm={() => {
103 |             if (!deleteTarget) return;
104 |             deleteMutation.mutate(deleteTarget.id, {
105 |                 onSuccess: () => {
106 |                     toast.success("Rubric deleted");
107 |                     setDeleteTarget(null);
108 |                 },
109 |                 onError: (err) => toast.error(err.message),
110 |             });
111 |         }}
112 |     />
113 |
114 |     <RubricPreviewDialog
115 |         rubricId={previewTarget?.id ?? null}
116 |         open={!previewTarget}
117 |         onOpenChange={(open) => !open && setPreviewTarget(null)}
118 |     />
119 | </div>
120 | );
121 | };
122 |
123 | export default RubricListPage;
124 |

```

FILE: src/pages/teacher/settings/TeacherProfilePage.tsx

TYPE: .tsx | LINES: 1-251 | SHA256: 25d2d489cfa77a998e4ed8bfa81feb53ccdde2b49d7f7b680a0156b3f0ee3f37

```

1 | import { Link } from "react-router-dom";
2 | import { useTranslation } from "react-i18next";
3 | import { useAuth } from "@hooks/useAuth";
4 | import { useTeacherDashboardAggregate } from "@hooks/useTeacherDashboardAggregate";
5 | import { useTeacherCourses } from "@hooks/useCourses";
6 | import { useCLOs } from "@hooks/useCLOs";
7 | import { Button } from "@components/ui/button";
8 | import { Badge } from "@components/ui/badge";
9 | import RoleProfileSurface, {
10 |     ProfileSectionCard,
11 |     ProfileSettingRow,
12 | } from "@components/shared/RoleProfileSurface";
13 | import RoleProfileAccountPanels from "@components/shared/RoleProfileAccountPanels";
14 | import EmailPreferencesSection from "@components/shared/EmailPreferencesSection";
15 | import { Shimmer } from "@design-system";
16 |
17 | const TeacherProfilePage = () => {
18 |     const { t } = useTranslation("common");
19 |     const { profile, user } = useAuth();
20 |     const aggregate = useTeacherDashboardAggregate(user?.id);
21 |     const courses = useTeacherCourses({ pageSize: 6 });
22 |     const clos = useCLOs(undefined, { pageSize: 1 });
23 |     const kpis = aggregate.data?.kpis;
24 |     const gradedTotal =
25 |         (kpis?.gradedThisWeek ?? 0) + (kpis?.pendingSubmissions ?? 0);
26 |     const gradingCompletion =
27 |         gradedTotal > 0
28 |         ? Math.round(((kpis?.gradedThisWeek ?? 0) / gradedTotal) * 100)
29 |         : 0;
30 |
31 |     const isLoading = aggregate.isPending || courses.isPending || clos.isPending;
32 |
33 |     return (
34 |         <RoleProfileSurface
35 |             roleLabel={profile?.designation || t("roleProfile.teacher.role")}
36 |             scopeLabel={profile?.department || t("roleProfile.teacher.scope")}
37 |             isLoading={isLoading}
38 |             primaryActionLabel={t("roleProfile.teacher.viewPublicProfile")}
39 |             primaryActionHref="/teacher/students"
40 |             contactRows={[
41 |                 {
42 |                     emoji: "📧",
43 |                     label: profile?.email || t("roleProfile.noEmail"),
44 |                     href: profile?.email ? `mailto:${profile.email}` : undefined,
45 |                 },
46 |             ]}

```

```

47 |         emoji: "🇵🇸",
48 |         label: profile?.department || t("roleProfile.notSet"),
49 |       },
50 |     {
51 |       emoji: "🇵🇸",
52 |       label: profile?.academic_rank || t("roleProfile.notSet"),
53 |     },
54 |   ]},
55 |   stats=[
56 |     {
57 |       emoji: "🇺🇦",
58 |       value: courses.data?.count ?? 0,
59 |       label: t("roleProfile.teacher.classes"),
60 |       tone: "blue",
61 |     },
62 |     {
63 |       emoji: "🇺🇪",
64 |       value: kpis?.totalStudents ?? 0,
65 |       label: t("roleProfile.teacher.students"),
66 |       tone: "green",
67 |     },
68 |     {
69 |       emoji: "🇵🇸",
70 |       value: courses.data?.count ?? 0,
71 |       label: t("roleProfile.teacher.courses"),
72 |       tone: "teal",
73 |     },
74 |     {
75 |       emoji: "🇵🇸",
76 |       value: clos.data?.count ?? 0,
77 |       label: t("roleProfile.teacher.clos"),
78 |       tone: "amber",
79 |     },
80 |   ]},
81 |   overviewTitle={t("roleProfile.teacher.overview")}
82 |   overviewDescription={t("roleProfile.teacher.overviewDescription")}
83 |   overviewRows={[]}
84 |   links={[]}
85 | >
86 | <ProfileSectionCard emoji="🇺🇪" title={t("roleProfile.teacher.impact")}>
87 |   <div className="grid grid-cols-3 gap-3 p-5">
88 |     <div className="text-center">
89 |       <p className="text-2xl font-black text-emerald-600">
90 |         {Math.round(kpis?.avgAttainment ?? 0)}%
91 |       </p>
92 |       <p className="text-[11px] text-slate-500">
93 |         {t("roleProfile.teacher.avgMastery")}
94 |       </p>
95 |     </div>
96 |     <div className="text-center">
97 |       <p className="text-2xl font-black text-slate-950">
98 |         {gradingCompletion}%
99 |       </p>
100 |       <p className="text-[11px] text-slate-500">
101 |         {t("roleProfile.teacher.gradingCompletion")}
102 |       </p>
103 |     </div>
104 |     <div className="text-center">
105 |       <p className="text-2xl font-black text-blue-600">
106 |         {kpis?.atRiskCount ?? 0}
107 |       </p>
108 |       <p className="text-[11px] text-slate-500">
109 |         {t("roleProfile.teacher.atRisk")}
110 |       </p>
111 |     </div>
112 |   </div>
113 | </ProfileSectionCard>
114 |
115 | <div className="grid gap-5 lg:grid-cols-2">
116 |   <ProfileSectionCard
117 |     emoji="🇵🇸"
118 |     title={t("roleProfile.teacher.aiAutonomy")}
119 |     action={
120 |       <Button asChild variant="link" size="sm">
121 |         <Link to="/teacher/tutor-handoffs">
122 |           {t("roleProfile.teacher.reviewControls")}
123 |         </Link>
124 |       </Button>
125 |     }
126 |   >
127 |     <div className="p-4">
128 |       <div className="grid grid-cols-4 overflow-hidden rounded-xl border border-slate-200">
129 |         {["A0", "A1", "A2", "A3"].map((tier) => (
130 |           <span
131 |             key={tier}
132 |             className={`py-2 text-center text-xs font-black ${
133 |               tier === "A2"
134 |                 ? "bg-slate-950 text-white"
135 |                 : "border-e border-slate-200 bg-slate-50 text-slate-500 last:border-e-0"
136 |             }`}
137 |           >
138 |             {tier}
139 |           </span>
140 |         ))}
141 |       </div>
142 |       <p className="mt-3 text-xs leading-5 text-slate-500">
143 |         {t("roleProfile.teacher.autonomyDescription")}
144 |       </p>
145 |     </div>
146 |   </ProfileSectionCard>
147 |
148 |   <ProfileSectionCard emoji="🇵🇸" title={t("roleProfile.teacher.overview")}>
149 |     <ProfileSettingRow
150 |       title={t("roleProfile.teacher.department")}

```

```

151         trailing={
152             <Badge variant="secondary">
153                 {profile?.department || t("roleProfile.notSet")}
154             </Badge>
155         }
156     </>
157     <ProfileSettingRow
158         title={t("roleProfile.teacher.designation")}
159         trailing={
160             <Badge variant="secondary">
161                 {profile?.designation || t("roleProfile.notSet")}
162             </Badge>
163         }
164     </>
165     <ProfileSettingRow
166         title={t("roleProfile.teacher.highestDegree")}
167         trailing={
168             <Badge variant="secondary">
169                 {profile?.highest_degree || t("roleProfile.notSet")}
170             </Badge>
171         }
172     </>
173 </ProfileSectionCard>
174 </div>
175
176 <div className="grid gap-5 lg:grid-cols-2">
177     <EmailPreferencesSection
178         title={t("roleProfile.teacher.notificationPreferences")}
179         description={t("roleProfile.teacher.notificationDescription")}
180         items={[
181             {
182                 key: "streak_risk",
183                 label: t("roleProfile.teacher.atRiskAlerts"),
184                 description: t("roleProfile.teacher.atRiskAlertsDescription"),
185             },
186             {
187                 key: "new_assignment",
188                 label: t("roleProfile.teacher.newSubmissions"),
189                 description: t("roleProfile.teacher.newSubmissionsDescription"),
190             },
191             {
192                 key: "grade_released",
193                 label: t("roleProfile.teacher.handoffRequests"),
194                 description: t("roleProfile.teacher.handoffDescription"),
195             },
196             {
197                 key: "weekly_summary",
198                 label: t("roleProfile.teacher.weeklySummary"),
199                 description: t("roleProfile.teacher.weeklySummaryDescription"),
200             },
201         ]}
202     </>
203     <div className="space-y-5">
204         <RoleProfileAccountPanels />
205     </div>
206 </div>
207
208 <ProfileSectionCard emoji="ðŸ“" title={t("roleProfile.teacher.myClasses")}>
209     {courses.isPending ? (
210         <div className="space-y-2 p-4">
211             {Array.from({ length: 3 }, (_, index) => (
212                 <Shimmer key={index} className="h-14 rounded-xl" />
213             ))}
214         </div>
215     ) : courses.data?.data.length ? (
216         <div className="divide-y divide-slate-100">
217             {courses.data.data.map((course) => (
218                 <Link
219                     key={course.id}
220                     to={`/teacher/courses/${course.id}`}
221                     className="flex items-center gap-3 px-4 py-3 transition-colors hover:bg-slate-50"
222                 >
223                     <span className="inline-flex size-10 shrink-0 items-center justify-center rounded-xl bg-blue-5"
224                         {course.code.slice(0, 3).toUpperCase()}
225                     </span>
226                     <span className="min-w-0 flex-1">
227                         <strong className="block truncate text-sm text-slate-900">
228                             {course.code} · {course.name}
229                         </strong>
230                         <span className="block truncate text-xs text-slate-500">
231                             {course.semester} · {course.academic_year}
232                         </span>
233                     </span>
234                     <span className="text-slate-300" aria-hidden="true">
235                         !
236                     </span>
237                 </Link>
238             ))}
239         </div>
240     ) : (
241         <p className="p-5 text-sm text-slate-500">
242             {t("empty.noCourses.description")}
243         </p>
244     )}
245 </ProfileSectionCard>
246 </RoleProfileSurface>
247 </>
248 </>
249
250 export default TeacherProfilePage;
251

```

FILE: src/pages/teacher/students/TeacherStudentsPage.tsx

TYPE: .tsx | LINES: 1-408 | SHA256: 82788ec3dc8a5feb848af22e9e72890a527b83ffc9fa2dbcb49c33e47e55eabc

```
1 | import { useMemo, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import {
4 |   ArrowRight,
5 |   Bell,
6 |   Clock3,
7 |   ShieldAlert,
8 |   Sparkles,
9 |   TriangleAlert,
10 |   Users,
11 | } from "lucide-react";
12 | import { useTranslation } from "react-i18next";
13 | import { toast } from "sonner";
14 |
15 | import { Button, PCard, SectionHeader, StatusDot } from "@design-system";
16 | import { useAuth } from "@hooks/useAuth";
17 | import {
18 |   useAtRiskStudents,
19 |   useTeacherKPIs,
20 |   useSendNudge,
21 |   type AtRiskStudent,
22 | } from "@hooks/useTeacherDashboard";
23 | import { useAtRiskPredictions } from "@hooks/useAtRiskPredictions";
24 | import { cn } from "@lib/utils";
25 |
26 | type Severity = "crit" | "att" | "mon";
27 |
28 | const severityOf = (student: AtRiskStudent): Severity => {
29 |   if (
30 |     student.risk_reasons.length >= 2 ||
31 |     student.days_inactive >= 14 ||
32 |     student.low_clo_count >= 3
33 |   ) {
34 |     return "crit";
35 |   }
36 |   if (student.days_inactive >= 7 || student.low_clo_count >= 2) {
37 |     return "att";
38 |   }
39 |   return "mon";
40 | };
41 |
42 | const severityLabel: Record<Severity, string> = {
43 |   crit: "Critical",
44 |   att: "Attention",
45 |   mon: "Monitor",
46 | };
47 |
48 | const severityTone: Record<Severity, "danger" | "warning" | "info"> = {
49 |   crit: "danger",
50 |   att: "warning",
51 |   mon: "info",
52 | };
53 |
54 | const severityButtonClass: Record<Severity, string> = {
55 |   crit: "border-red-200 bg-red-50 text-red-700 hover:bg-red-100",
56 |   att: "border-amber-200 bg-amber-50 text-amber-700 hover:bg-amber-100",
57 |   mon: "border-blue-200 bg-blue-50 text-blue-700 hover:bg-blue-100",
58 | };
59 |
60 | const TeacherStudentsPage = () => {
61 |   const { t } = useTranslation("teacher");
62 |   const { user } = useAuth();
63 |   const atRiskQuery = useAtRiskStudents();
64 |   const kpiQuery = useTeacherKPIs();
65 |   const predictionQuery = useAtRiskPredictions();
66 |   const sendNudge = useSendNudge();
67 |
68 |   const [searchTerm, setSearchTerm] = useState("");
69 |   const [selectedFilter, setSelectedFilter] = useState<Severity | "all">("all");
70 |
71 |   const filteredData = useMemo(() => {
72 |     const list = atRiskQuery.data ?? [];
73 |     return list.filter((student) => {
74 |       const matchesSearch =
75 |         !searchTerm ||
76 |         student.full_name.toLowerCase().includes(searchTerm.toLowerCase()) ||
77 |         student.email.toLowerCase().includes(searchTerm.toLowerCase());
78 |
79 |       const sev = severityOf(student);
80 |       const matchesFilter = selectedFilter === "all" || sev === selectedFilter;
81 |
82 |       return matchesSearch && matchesFilter;
83 |     });
84 |   }, [atRiskQuery.data, searchTerm, selectedFilter]);
85 |
86 |   const grouped = useMemo(() => {
87 |     const result: Record<Severity, AtRiskStudent[]> = {
88 |       crit: [],
89 |       att: [],
90 |       mon: [],
91 |     };
92 |
93 |     for (const student of filteredData) {
94 |       result[severityOf(student)].push(student);
95 |     }
96 |
97 |     return result;
98 |   }, [filteredData]);
99 |
100 |   const criticalCount = (atRiskQuery.data ?? []).filter(
101 |     (s) => severityOf(s) === "crit"
```



```

102 | ).length;
103 | const attentionCount = (atRiskQuery.data ?? []).filter(
104 |   (s) => severityOf(s) === "att"
105 | ).length;
106 | const monitorCount = (atRiskQuery.data ?? []).filter(
107 |   (s) => severityOf(s) === "mon"
108 | ).length;
109 | const flaggedCount = kpiQuery.data?.atRiskCount ?? 0;
110 | const detailsUnavailable =
111 |   !atRiskQuery.isPending &&
112 |   (atRiskQuery.data?.length ?? 0) === 0 &&
113 |   flaggedCount > 0;
114 |
115 | const predictionByStudent = useMemo(() => {
116 |   const map = new Map<string, string>();
117 |   for (const prediction of predictionQuery.data ?? []) {
118 |     if (!map.has(prediction.student_id)) {
119 |       map.set(prediction.student_id, prediction.suggestion_text);
120 |     }
121 |   }
122 |   return map;
123 | }, [predictionQuery.data]);
124 |
125 | const handleNudge = async (student: AtRiskStudent) => {
126 |   if (!user?.id) return;
127 |   try {
128 |     await sendNudge.mutateAsync({
129 |       studentId: student.id,
130 |       message: `Hi ${student.full_name}, I noticed you may need a quick check-in. Let's get you back on trac
131 |     });
132 |     toast.success(`Nudge sent to ${student.full_name}`);
133 |   } catch (error) {
134 |     console.error("[TeacherStudentsPage] Failed to send nudge:", error);
135 |     toast.error("Could not send nudge");
136 |   }
137 | };
138 |
139 | return (
140 |   <div className="space-y-6">
141 |     <PCard className="p-6">
142 |       <div className="flex flex-col gap-4 lg:flex-row lg:items-center lg:justify-between">
143 |         <div className="space-y-2">
144 |           <p className="text-xs font-black uppercase tracking-[0.14em] text-slate-400">
145 |             {t("dashboard.triage.all", "Student triage")}
146 |           </p>
147 |           <h1 className="text-2xl font-black tracking-tight text-slate-900">
148 |             {t("dashboard.triage.all", "Students who need attention")}
149 |           </h1>
150 |           <p className="max-w-2xl text-sm leading-6 text-slate-500">
151 |             {t(
152 |               "dashboard.triage.helper",
153 |               "See the students most likely to benefit from a nudge, ordered by urgency and backed by the ex
154 |             )}
155 |           </p>
156 |         </div>
157 |         <div className="flex flex-wrap gap-2">
158 |           <Button variant="outline" className="rounded-xl" asChild>
159 |             <Link to="/teacher/grading">
160 |               <Sparkles className="me-2 h-4 w-4" />
161 |               {t("dashboard.quickActions.grade", "Go to grading")}
162 |             </Link>
163 |           </Button>
164 |           <Button variant="tactile" className="rounded-xl" asChild>
165 |             <Link to="/teacher/dashboard">
166 |               {t("dashboard.quickActions.back", "Back to dashboard")}
167 |             </Link>
168 |           </Button>
169 |         </div>
170 |       </div>
171 |     </PCard>
172 |
173 |     {detailsUnavailable ? (
174 |       <PCard className="border-amber-200 bg-amber-50/60 p-6">
175 |         <div className="flex items-start gap-3">
176 |           <span className="flex size-10 shrink-0 items-center justify-center rounded-xl bg-amber-100 text-am
177 |             <ShieldAlert className="size-5" aria-hidden="true" />
178 |           </span>
179 |           <div>
180 |             <h2 className="font-extrabold text-slate-900">
181 |               {t("dashboard.accessLimited.title")}
182 |             </h2>
183 |             <p className="mt-1 text-sm leading-6 text-slate-600">
184 |               {t("dashboard.accessLimited.description", {
185 |                 count: flaggedCount,
186 |               })}
187 |             </p>
188 |           </div>
189 |         </div>
190 |       </PCard>
191 |     ) : (
192 |       <div className="space-y-4">
193 |         <div className="grid gap-4 sm:grid-cols-3">
194 |           {
195 |             {
196 |               id: "crit" as const,
197 |               label: "Critical",
198 |               value: criticalCount,
199 |               tone: "danger" as const,
200 |               icon: TriangleAlert,
201 |             },
202 |             {
203 |               id: "att" as const,
204 |               label: "Attention",
205 |             }

```

```

206         value: attentionCount,
207         tone: "warning" as const,
208         icon: Clock3,
209     },
210     {
211         id: "mon" as const,
212         label: "Monitor",
213         value: monitorCount,
214         tone: "info" as const,
215         icon: Users,
216     },
217 ].map(({ id, label, value, tone, icon: Icon }) => (
218     <button
219         key={label}
220         type="button"
221         onClick={() =>
222             setSelectedFilter(selectedFilter === id ? "all" : id)
223         }
224         className="text-start focus:outline-none"
225     >
226         <PCard
227             className={cn(
228                 "p-5 transition-all",
229                 selectedFilter === id && "ring-2 ring-blue-500 shadow-md"
230             )}
231         >
232             <div className="flex items-center gap-3">
233                 <span
234                     className={cn(
235                         "flex size-10 items-center justify-center rounded-xl",
236                         tone === "danger" && "bg-red-50 text-red-600",
237                         tone === "warning" && "bg-amber-50 text-amber-600",
238                         tone === "info" && "bg-blue-50 text-blue-600"
239                     )}
240                 >
241                     <Icon className="size-5" aria-hidden="true" />
242                 </span>
243                 <div>
244                     <p className="text-xs font-black uppercase tracking-[0.14em] text-slate-400">
245                         {label}
246                     </p>
247                     <p className="text-2xl font-black text-slate-900">
248                         {value}
249                     </p>
250                 </div>
251             </div>
252             </PCard>
253         </button>
254     )})
255 </div>
256
257 <div className="flex flex-col gap-3 rounded-2xl border border-slate-200 bg-white p-4 sm:flex-row sm:
258     <input
259         type="search"
260         placeholder="Search student name or email..."
261         value={searchTerm}
262         onChange={(e) => setSearchTerm(e.target.value)}
263         className="w-full rounded-xl border border-slate-200 px-4 py-2 text-sm focus:border-blue-500 foc
264     />
265     <div className="flex flex-wrap items-center gap-2">
266         <span className="text-xs font-bold text-slate-400 uppercase tracking-wider">
267             Filter:
268         </span>
269         {[["all", "crit", "att", "mon"] as const].map((filterKey) => (
270             <button
271                 key={filterKey}
272                 type="button"
273                 onClick={() => setSelectedFilter(filterKey)}
274                 className={cn(
275                     "rounded-xl border px-3 py-1.5 text-xs font-bold transition-colors",
276                     selectedFilter === filterKey
277                         ? "bg-slate-900 text-white border-slate-900"
278                         : "border-slate-200 bg-slate-50 text-slate-600 hover:bg-slate-100"
279                 )}
280             >
281                 {filterKey === "all"
282                     ? "All Students"
283                     : filterKey === "crit"
284                     ? "Critical"
285                     : filterKey === "att"
286                     ? "Attention"
287                     : "Monitor"}
288             </button>
289         )})
290     </div>
291 </div>
292
293 {(Object.keys(grouped) as Severity[]).map((severity) => {
294     const students = grouped[severity];
295     return (
296         <section key={severity} className="space-y-3">
297             <SectionHeader
298                 icon={
299                     severity === "crit"
300                         ? TriangleAlert
301                         : severity === "att"
302                         ? Clock3
303                         : Users
304                 }
305                 title={severityLabel[severity]}
306                 description={` ${students.length} students`}
307             />
308             {students.length === 0 ? (
309                 <PCard className="p-5">

```

```

310         <p className="text-sm text-slate-500">
311             No students in this bucket right now.
312         </p>
313     </PCard>
314 ) : (
315     <div className="grid gap-4">
316         {students.map((student) => {
317             const prediction = predictionByStudent.get(student.id);
318             return (
319                 <PCard key={student.id} className="p-5">
320                     <div className="flex flex-col gap-4 lg:flex-row lg:items-start lg:justify-between">
321                         <div className="min-w-0 space-y-3">
322                             <div className="flex items-start gap-3">
323                                 <StatusDot
324                                     tone={severityTone[severity]}
325                                     label={severityLabel[severity]}
326                                     className="mt-2"
327                                 />
328                                 <div className="min-w-0">
329                                     <p className="text-base font-extrabold text-slate-900">
330                                         {student.full_name}
331                                     </p>
332                                     <p className="text-sm text-slate-500">
333                                         {student.email}
334                                     </p>
335                                 </div>
336                             </div>
337
338                             <div className="flex flex-wrap gap-2">
339                                 {student.risk_reasons.map((reason) => (
340                                     <span
341                                         key={reason}
342                                         className="rounded-full border border-slate-200 bg-slate-50 px-3 py-1 text
343                                     >
344                                         {reason}
345                                     </span>
346                                 ))}
347                             </div>
348
349                             <div className="flex flex-wrap gap-2 text-xs text-slate-500">
350                                 <span className="rounded-full bg-slate-100 px-3 py-1 font-semibold">
351                                     {student.last_login_at
352                                     ? t("dashboard.daysInactive", {
353                                         count: student.days_inactive,
354                                     })
355                                     : t("dashboard.activityUnavailable")}
356                                 </span>
357                                 <span className="rounded-full bg-slate-100 px-3 py-1 font-semibold">
358                                     {student.low_clo_count} CLOs below 50%
359                                 </span>
360                                 {prediction ? (
361                                     <span className="rounded-full bg-blue-50 px-3 py-1 font-semibold text-blue-7
362                                         AI: {prediction}
363                                     </span>
364                                 ) : null}
365                             </div>
366                         </div>
367
368                         <div className="flex shrink-0 flex-wrap gap-2">
369                             <Button
370                                 variant="outline"
371                                 className={cn(
372                                     "rounded-xl",
373                                     severityButtonClass[severity]
374                                 )}
375                                 onClick={() => void handleNudge(student)}
376                                 disabled={sendNudge.isPending}
377                             >
378                                 <Bell className="me-2 h-4 w-4" />
379                                 Send nudge
380                             </Button>
381                             <Button
382                                 variant="ghost"
383                                 className="rounded-xl"
384                                 asChild
385                             >
386                                 <Link to="/teacher/dashboard">
387                                     Open dashboard
388                                 <ArrowRight className="ms-2 h-4 w-4" />
389                             </Link>
390                             </Button>
391                         </div>
392                     </div>
393                 </PCard>
394             );
395         })}
396     </div>
397 )}
398 </section>
399 </div>
400 </div>
401 </div>
402 </div>
403 </div>
404 );
405 };
406
407 export default TeacherStudentsPage;
408

```

FILE: src/pages/teacher/TeacherDashboard.tsx

TYPE: .tsx | LINES: 1-12 | SHA256: 31d910337dd50d01c9e65b710b36e3c5c12f5bb6e4cd22583bb9c377e969b51a

```
1 | // =====
2 | // TeacherDashboard – production teacher dashboard (prototype rebuild)
3 | // =====
4 | // Implementation lives in the prototype-rebuilt `TeacherDashboardScreen`
5 | // (src/features/teacher/dashboard), re-exported here so the route path
6 | // (`@/pages/teacher/TeacherDashboard`) and its guard stay stable. The legacy
7 | // `TeacherDashboardNew` reskin was replaced in the prototype-frontend-rebuild
8 | // (P2.2) cutover.
9 | // =====
10 |
11 | export { default } from "@features/teacher/dashboard/TeacherDashboardScreen";
12 |
```

FILE: src/pages/teacher/TeacherLayout.tsx

TYPE: .tsx | LINES: 1-14 | SHA256: bd0cff1e48c2dda62ce488f0cdd1a0d2ad7fff852bf5e2cf945eb5ee001f027f

```
1 | import { Outlet } from "react-router-dom";
2 | import RoleAppShell from "@app/RoleAppShell";
3 | import TeacherDashboardRail from "@features/teacher/dashboard/TeacherDashboardRail";
4 |
5 | const TeacherLayout = () => {
6 |   return (
7 |     <RoleAppShell userRole="teacher" rail={<TeacherDashboardRail />}>
8 |       <Outlet />
9 |     </RoleAppShell>
10 |   );
11 | };
12 |
13 | export default TeacherLayout;
14 |
```

FILE: src/pages/teacher/teams/TeamFormPage.tsx

TYPE: .tsx | LINES: 1-298 | SHA256: 8942b55efa939b0d952a60374370e472d2bef08205967bf9c52ea4e6db6af13c

```
1 | // =====
2 | // TeamFormPage – Create/edit team form for teachers
3 | // Task 5.4: name, member selection from enrollment roster
4 | // =====
5 |
6 | import { useEffect, useMemo, useState } from "react";
7 | import { useNavigate, useParams } from "react-router-dom";
8 | import { useForm } from "react-hook-form";
9 | import { zodResolver } from "hookform/resolvers/zod";
10 | import { z } from "zod";
11 | import { useAuth } from "@hooks/useAuth";
12 | import { useTeacherCourses } from "@hooks/useCourses";
13 | import { useCreateTeam, useUpdateTeam, useTeams } from "@hooks/useTeams";
14 | import { useQuery } from "tanstack/react-query";
15 | import { supabase } from "@lib/supabase";
16 | import { queryKeys } from "@lib/queryKeys";
17 | import { Card } from "@components/ui/card";
18 | import { Button } from "@components/ui/button";
19 | import { Input } from "@components/ui/input";
20 | import { Checkbox } from "@components/ui/checkbox";
21 | import {
22 |   Form,
23 |   FormField,
24 |   FormItem,
25 |   FormLabel,
26 |   FormControl,
27 |   FormMessage,
28 | } from "@components/ui/form";
29 | import {
30 |   Select,
31 |   SelectContent,
32 |   SelectItem,
33 |   SelectTrigger,
34 |   SelectValue,
35 | } from "@components/ui/select";
36 | import { Shimmer } from "@design-system";
37 | import { Loader2, ArrowLeft } from "lucide-react";
38 | import { toast } from "sonner";
39 |
40 | const teamFormSchema = z.object({
41 |   name: z.string().min(2, "Team name must be at least 2 characters").max(50),
42 |   course_id: z.string().uuid("Select a course"),
43 | });
44 |
45 | type TeamFormData = z.infer<typeof teamFormSchema>;
46 |
47 | interface RosterStudent {
48 |   student_id: string;
49 |   full_name: string;
50 | }
51 |
52 | const useCourseRoster = (courseId?: string) => {
53 |   return useQuery({
54 |     queryKey: queryKeys.enrollments.list({ courseId, rosterAll: true }),
55 |     queryFn: async (): Promise<RosterStudent[]> => {
56 |       const { data, error } = await supabase
57 |         .from("student_courses")
58 |         .select("student_id, profiles!inner(full_name)")
59 |         .eq("course_id", courseId!)
60 |         .eq("status", "active");
61 |       if (error) throw error;
62 |
63 |       return (
64 |         (data ?? []) as Array<{
65 |           student_id: string;
66 |           profiles: { full_name: string };
```

```

67 |         }>
68 |         ).map((row) => ({
69 |             student_id: row.student_id,
70 |             full_name: row.profiles.full_name,
71 |         }));
72 |     },
73 |     enabled: !!courseId,
74 | });
75 | };
76 |
77 | const TeamFormPage = () => {
78 |     const navigate = useNavigate();
79 |     const { id } = useParams<{ id: string }>();
80 |     const isEditMode = !!id;
81 |     const { user, institutionId } = useAuth();
82 |     const { data: paginatedCourses } = useTeacherCourses();
83 |
84 |     const teacherCourses = useMemo(
85 |         () =>
86 |         (paginatedCourses?.data ?? []).filter((c) => c.teacher_id === user?.id),
87 |         [paginatedCourses, user?.id]
88 |     );
89 |
90 |     const createMutation = useCreateTeam();
91 |     const updateMutation = useUpdateTeam();
92 |     const [selectedMembers, setSelectedMembers] = useState<string[]>([]);
93 |
94 |     const form = useForm<TeamFormData>({
95 |         resolver: zodResolver(teamFormSchema),
96 |         defaultValues: { name: "", course_id: "" },
97 |     });
98 |
99 |     const selectedCourseId = form.watch("course_id");
100 |     const { data: roster, isLoading: rosterLoading } = useCourseRoster(
101 |         selectedCourseId || undefined
102 |     );
103 |
104 |     // Load existing team data for edit mode
105 |     const { data: existingTeams } = useTeams(selectedCourseId || undefined);
106 |     const existingTeam = isEditMode
107 |         ? (existingTeams ?? []).find((t) => t.id === id)
108 |         : null;
109 |
110 |     useEffect(() => {
111 |         if (existingTeam) {
112 |             form.reset({
113 |                 name: existingTeam.name,
114 |                 course_id: existingTeam.course_id,
115 |             });
116 |         }
117 |     }, [existingTeam, form]);
118 |
119 |     const toggleMember = (studentId: string) => {
120 |         setSelectedMembers((prev) =>
121 |             prev.includes(studentId)
122 |                 ? prev.filter((m) => m !== studentId)
123 |                 : [...prev, studentId]
124 |         );
125 |     };
126 |
127 |     const totalSize = selectedMembers.length;
128 |     const sizeValid = isEditMode || (totalSize >= 2 && totalSize <= 6);
129 |
130 |     const onSubmit = (data: TeamFormData) => {
131 |         if (isEditMode && id) {
132 |             updateMutation.mutate(
133 |                 { id, name: data.name },
134 |                 {
135 |                     onSuccess: () => {
136 |                         toast.success("Team updated");
137 |                         navigate("/teacher/teams");
138 |                     },
139 |                     onError: (err) => toast.error(err.message),
140 |                 }
141 |             );
142 |         } else {
143 |             if (!sizeValid) {
144 |                 toast.error("Select 2-6 members for the team");
145 |                 return;
146 |             }
147 |             createMutation.mutate(
148 |                 {
149 |                     name: data.name,
150 |                     course_id: data.course_id,
151 |                     institution_id: institutionId ?? "",
152 |                     captain_id: selectedMembers[0] ?? "",
153 |                     created_by: user?.id ?? "",
154 |                     avatar_letter: data.name.charAt(0).toUpperCase(),
155 |                 },
156 |                 {
157 |                     onSuccess: () => {
158 |                         toast.success("Team created");
159 |                         navigate("/teacher/teams");
160 |                     },
161 |                     onError: (err) => toast.error(err.message),
162 |                 }
163 |             );
164 |         }
165 |     };
166 |
167 |     const isPending = createMutation.isPending || updateMutation.isPending;
168 |
169 |     return (
170 |         <div className="space-y-6">

```

```

171 | <div className="flex items-center gap-3">
172 |   <Button
173 |     variant="ghost"
174 |     size="sm"
175 |     onClick={() => navigate("/teacher/teams")}
176 |     className="h-8 w-8 p-0"
177 |   >
178 |     <ArrowLeft className="h-4 w-4" />
179 |   </Button>
180 |   <h1 className="text-2xl font-bold tracking-tight">
181 |     {isEditMode ? "Edit Team" : "Create Team"}
182 |   </h1>
183 | </div>
184 |
185 | <Card className="bg-white border-0 shadow-md rounded-xl p-6 max-w-2xl">
186 |   <Form {...form}>
187 |     <Form onSubmit={form.handleSubmit(onSubmit)} className="space-y-6">
188 |       <FormField
189 |         control={form.control}
190 |         name="course_id"
191 |         render={({ field }) => (
192 |           <FormItem>
193 |             <FormLabel>Course</FormLabel>
194 |             <Select
195 |               onChange={field.onChange}
196 |               value={field.value}
197 |               disabled={isEditMode}
198 |             >
199 |               <FormControl>
200 |                 <SelectTrigger className="bg-white">
201 |                   <SelectValue placeholder="Select a course" />
202 |                 </SelectTrigger>
203 |               </FormControl>
204 |               <SelectContent>
205 |                 {teacherCourses.map((c) => (
206 |                   <SelectItem key={c.id} value={c.id}>
207 |                     {c.name}
208 |                   </SelectItem>
209 |                 ))}
210 |               </SelectContent>
211 |             </Select>
212 |             <FormMessage />
213 |           </FormItem>
214 |         )}
215 |       </>
216 |
217 |       <FormField
218 |         control={form.control}
219 |         name="name"
220 |         render={({ field }) => (
221 |           <FormItem>
222 |             <FormLabel>Team Name</FormLabel>
223 |             <FormControl>
224 |               <Input placeholder="e.g. Team Alpha" {...field} />
225 |             </FormControl>
226 |             <FormMessage />
227 |           </FormItem>
228 |         )}
229 |       </>
230 |
231 |       {/* Member Selection (create mode only) */}
232 |       {isEditMode && selectedCourseId && (
233 |         <div className="space-y-2">
234 |           <FormLabel>Select Members ({totalSize}/6)</FormLabel>
235 |           {rosterLoading ? (
236 |             <Shimmer className="h-24 rounded-lg" />
237 |           ) : !roster || roster.length === 0 ? (
238 |             <p className="text-xs text-gray-500">
239 |               No enrolled students found.
240 |             </p>
241 |           ) : (
242 |             <div className="grid grid-cols-1 sm:grid-cols-2 gap-2 max-h-60 overflow-y-auto border rounde
243 |               {roster.map((student) => (
244 |                 <label
245 |                   key={student.student_id}
246 |                   className="flex items-center gap-2 p-2 rounded-lg hover:bg-slate-50 cursor-pointer"
247 |                 >
248 |                   <Checkbox
249 |                     checked={selectedMembers.includes(student.student_id)}
250 |                     onChange={() =>
251 |                       toggleMember(student.student_id)
252 |                     }
253 |                     disabled={
254 |                       !selectedMembers.includes(student.student_id) &&
255 |                       totalSize >= 6
256 |                     }
257 |                   </>
258 |                   <span className="text-sm font-medium">
259 |                     {student.full_name}
260 |                   </span>
261 |                 </label>
262 |               )}
263 |             </div>
264 |           )}
265 |           {totalSize > 0 && totalSize < 2 && (
266 |             <p className="text-xs text-amber-600">
267 |               Select at least 2 members.
268 |             </p>
269 |           )}
270 |         </div>
271 |       )}
272 |
273 |     <div className="flex items-center gap-3 pt-2">
274 |       <Button

```

```

275 |         type="submit"
276 |         disabled={isPending || (!isEditMode && !sizeValid)}
277 |         variant="tactile"
278 |     >
279 |         {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
280 |         {isEditMode ? "Update Team" : "Create Team"}
281 |     </Button>
282 |     <Button
283 |         type="button"
284 |         variant="outline"
285 |         onClick={() => navigate("/teacher/teams")}
286 |     >
287 |         Cancel
288 |     </Button>
289 | </div>
290 | </form>
291 | </Form>
292 | </Card>
293 | </div>
294 | );
295 | };
296 |
297 | export default TeamFormPage;
298 |

```

FILE: src/pages/teacher/teams/TeamHealthReportPage.tsx

TYPE: .tsx | LINES: 1-239 | SHA256: 5b31ea8c62597d8712a4de0537123fd8e180542f6b92bba87b9245955822b193

```

1 | // =====
2 | // TeamHealthReportPage – Weekly team health report with flagged teams
3 | // Task 13.1: total teams, healthy/needs_attention/at_risk counts,
4 | //         flagged team list with issues and recommendations
5 | // =====
6 |
7 | import { useMemo } from "react";
8 | import { parseAsString, useQueryState } from "nuqs";
9 | import { useAuth } from "@/hooks/useAuth";
10 | import { useCourses } from "@/hooks/useCourses";
11 | import {
12 |     useTeamHealthScores,
13 |     type TeamHealthSummary,
14 | } from "@/hooks/useTeamHealth";
15 | import { Card } from "@components/ui/card";
16 | import { Badge } from "@components/ui/badge";
17 | import {
18 |     Select,
19 |     SelectContent,
20 |     SelectItem,
21 |     SelectTrigger,
22 |     SelectValue,
23 | } from "@components/ui/select";
24 | import TeamHealthBadge from "@components/shared/TeamHealthBadge";
25 | import { Shimmer } from "@design-system";
26 | import {
27 |     HeartPulse,
28 |     AlertTriangle,
29 |     CheckCircle2,
30 |     AlertCircle,
31 | } from "lucide-react";
32 | import { cn } from "@lib/utils";
33 |
34 | const getRecommendation = (team: TeamHealthSummary): string => {
35 |     if (team.health_status === "at_risk") {
36 |         return "Consider restructuring this team or scheduling a check-in with members.";
37 |     }
38 |     if (team.health_status === "needs_attention") {
39 |         return "Monitor this team closely. Encourage more equitable participation.";
40 |     }
41 |     return "Team is performing well.";
42 | };
43 |
44 | interface TeamHealthReportPageProps {
45 |     courseScope?: "owned" | "all";
46 | }
47 |
48 | const TeamHealthReportPage = ({
49 |     courseScope = "owned",
50 | }: TeamHealthReportPageProps) => {
51 |     const { user } = useAuth();
52 |     const { data: paginatedCourses } = useCourses({
53 |         teacherId: courseScope === "owned" ? user?.id : undefined,
54 |         pageSize: 200,
55 |     });
56 |
57 |     const visibleCourses = useMemo(
58 |         () => paginatedCourses?.data ?? [],
59 |         [paginatedCourses?.data]
60 |     );
61 |
62 |     const [selectedCourseId, setSelectedCourseId] = useQueryState(
63 |         "courseId",
64 |         parseAsString.withDefault("")
65 |     );
66 |
67 |     const effectiveCourseId = selectedCourseId || visibleCourses[0]?.id || "";
68 |     const { data: healthScores, isLoading } = useTeamHealthScores(
69 |         effectiveCourseId || undefined
70 |     );
71 |
72 |     const counts = useMemo(() => {
73 |         const c = { total: 0, healthy: 0, needs_attention: 0, at_risk: 0 };
74 |         (healthScores ?? []).forEach((t) => {
75 |             c.total++;
76 |             c[t.health_status]++;

```

```

77 |     });
78 |     return c;
79 | }, [healthScores]);
80 |
81 | const flaggedTeams = useMemo(
82 |   () => (healthScores ?? []).filter((t) => t.health_status !== "healthy"),
83 |   [healthScores]
84 | );
85 |
86 | return (
87 |   <div className="space-y-6">
88 |     <div className="flex items-center gap-2">
89 |       <HeartPulse className="h-5 w-5 text-blue-600" />
90 |       <h1 className="text-2xl font-bold tracking-tight">
91 |         Team Health Report
92 |       </h1>
93 |     </div>
94 |
95 |     { /* Course Selector */ }
96 |     <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
97 |       <SelectTrigger className="w-64 bg-white">
98 |         <SelectValue placeholder="Select course" />
99 |       </SelectTrigger>
100 |      <SelectContent>
101 |        {visibleCourses.map((c) => (
102 |          <SelectItem key={c.id} value={c.id}>
103 |            {c.name}
104 |          </SelectItem>
105 |        ))}
106 |      </SelectContent>
107 |    </Select>
108 |
109 |    { /* Summary KPIs */ }
110 |    {isLoading ? (
111 |      <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
112 |        {Array.from({ length: 4 }).map((_, i) => (
113 |          <Shimmer key={i} className="h-24 rounded-xl" />
114 |        ))}
115 |      </div>
116 |    ) : (
117 |      <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
118 |        <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
119 |          <div className="flex items-center justify-between">
120 |            <div>
121 |              <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
122 |                Total Teams
123 |              </p>
124 |              <p className="text-2xl font-black mt-1">{counts.total}</p>
125 |            </div>
126 |            <div className="p-2 rounded-lg bg-blue-50 group-hover:scale-110 transition-transform">
127 |              <HeartPulse className="h-5 w-5 text-blue-600" />
128 |            </div>
129 |          </div>
130 |        </Card>
131 |        <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
132 |          <div className="flex items-center justify-between">
133 |            <div>
134 |              <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
135 |                Healthy
136 |              </p>
137 |              <p className="text-2xl font-black mt-1 text-green-600">
138 |                {counts.healthy}
139 |              </p>
140 |            </div>
141 |            <div className="p-2 rounded-lg bg-green-50 group-hover:scale-110 transition-transform">
142 |              <CheckCircle2 className="h-5 w-5 text-green-600" />
143 |            </div>
144 |          </div>
145 |        </Card>
146 |        <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
147 |          <div className="flex items-center justify-between">
148 |            <div>
149 |              <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
150 |                Needs Attention
151 |              </p>
152 |              <p className="text-2xl font-black mt-1 text-yellow-600">
153 |                {counts.needs_attention}
154 |              </p>
155 |            </div>
156 |            <div className="p-2 rounded-lg bg-yellow-50 group-hover:scale-110 transition-transform">
157 |              <AlertCircle className="h-5 w-5 text-yellow-600" />
158 |            </div>
159 |          </div>
160 |        </Card>
161 |        <Card className="bg-white border-0 shadow-md rounded-xl p-4 group">
162 |          <div className="flex items-center justify-between">
163 |            <div>
164 |              <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
165 |                At Risk
166 |              </p>
167 |              <p className="text-2xl font-black mt-1 text-red-600">
168 |                {counts.at_risk}
169 |              </p>
170 |            </div>
171 |            <div className="p-2 rounded-lg bg-red-50 group-hover:scale-110 transition-transform">
172 |              <AlertTriangle className="h-5 w-5 text-red-600" />
173 |            </div>
174 |          </div>
175 |        </Card>
176 |      </div>
177 |    )}
178 |
179 |    { /* Flagged Teams */ }
180 |    <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">

```



```

181 |         <div
182 |             className="px-6 py-4 flex items-center gap-2"
183 |             style={{
184 |                 background: "var(--brand-gradient)",
185 |             }}
186 |         >
187 |             <AlertTriangle className="h-5 w-5 text-white" />
188 |             <h2 className="text-lg font-bold tracking-tight text-white">
189 |                 Flagged Teams ({flaggedTeams.length})
190 |             </h2>
191 |         </div>
192 |         <div className="p-6">
193 |             {isLoading ? (
194 |                 <div className="space-y-3">
195 |                     {Array.from({ length: 3 }).map((_, i) => (
196 |                         <Shimmer key={i} className="h-20 rounded-lg" />
197 |                     ))}
198 |                 </div>
199 |             ) : flaggedTeams.length === 0 ? (
200 |                 <div className="text-center py-8">
201 |                     <CheckCircle2 className="h-8 w-8 text-green-500 mx-auto mb-2" />
202 |                     <p className="text-sm text-gray-500">All teams are healthy!</p>
203 |                 </div>
204 |             ) : (
205 |                 <div className="space-y-3">
206 |                     {flaggedTeams.map((team) => (
207 |                         <div
208 |                             key={team.team_id}
209 |                             className={cn(
210 |                                 "p-4 rounded-xl border",
211 |                                 team.health_status === "at_risk"
212 |                                   ? "border-red-200 bg-red-50"
213 |                                   : "border-yellow-200 bg-yellow-50"
214 |                             )}
215 |                         >
216 |                             <div className="flex items-center justify-between mb-2">
217 |                                 <div className="flex items-center gap-3">
218 |                                     <p className="text-sm font-semibold">{team.team_name}</p>
219 |                                     <TeamHealthBadge score={team.health_score} />
220 |                                 </div>
221 |                                 <Badge variant="outline" className="text-xs">
222 |                                     Co-op: {team.cooperation_score}
223 |                                 </Badge>
224 |                             </div>
225 |                             <p className="text-xs text-gray-600">
226 |                                 {getRecommendation(team)}
227 |                             </p>
228 |                         </div>
229 |                     ))}
230 |                 </div>
231 |             )}
232 |         </div>
233 |     </Card>
234 | </div>
235 | );
236 | };
237 |
238 | export default TeamHealthReportPage;
239 |

```

FILE: [src/pages/teacher/teams/TeamManagementPage.tsx](#)

TYPE: .tsx | LINES: 1-313 | SHA256: f095bd9eda7ea4bd2a312e838e65ad1d1d8427a1b4afe0f80d8157e4fe698d3a

```

1 | // =====
2 | // TeamManagementPage – Teacher team management with health badges,
3 | // accountability metrics, filter by health status and has-inactive-members
4 | // Task 5.3
5 | // =====
6 |
7 | import { useState, useMemo } from "react";
8 | import { useNavigate } from "react-router-dom";
9 | import { parseAsString, useQueryState } from "nuqs";
10 | import { useAuth } from "@/hooks/useAuth";
11 | import { useTeacherCourses } from "@/hooks/useCourses";
12 | import { useTeams, useSoftDeleteTeam } from "@/hooks/useTeams";
13 | import { useTeamHealthScores, type HealthStatus } from "@/hooks/useTeamHealth";
14 | import { Card } from "@components/ui/card";
15 | import { Button } from "@components/ui/button";
16 | import { Input } from "@components/ui/input";
17 | import { Badge } from "@components/ui/badge";
18 | import {
19 |     Select,
20 |     SelectContent,
21 |     SelectItem,
22 |     SelectTrigger,
23 |     SelectValue,
24 | } from "@components/ui/select";
25 | import TeamHealthBadge from "@components/shared/TeamHealthBadge";
26 | import { ConfirmDialog } from "@components/shared/ConfirmDialog";
27 | import { Shimmer } from "@design-system";
28 | import { NoTeams } from "@components/shared/EmptyState";
29 | import { Plus, Search, Users, Pencil, Trash2, HeartPulse } from "lucide-react";
30 | import { toast } from "sonner";
31 |
32 | const TeamManagementPage = () => {
33 |     const navigate = useNavigate();
34 |     const { user } = useAuth();
35 |     const { data: paginatedCourses } = useTeacherCourses();
36 |
37 |     const teacherCourses = useMemo(
38 |         () =>
39 |         (paginatedCourses?.data ?? []).filter((c) => c.teacher_id === user?.id),
40 |         [paginatedCourses, user?.id]
41 |     );

```

```

42 |
43 | const [selectedCourseId, setSelectedCourseId] = useQueryState(
44 |   "courseId",
45 |   parseAsString.withDefault("")
46 | );
47 | const [search, setSearch] = useQueryState("q", parseAsString.withDefault(""));
48 | const [healthFilter, setHealthFilter] = useState<string>("all");
49 | const [deleteTeamId, setDeleteTeamId] = useState<string | null>(null);
50 |
51 | const effectiveCourseId = selectedCourseId || teacherCourses[0]?.id || "";
52 | const { data: teams, isLoading } = useTeams(effectiveCourseId || undefined);
53 | const { data: healthScores } = useTeamHealthScores(
54 |   effectiveCourseId || undefined
55 | );
56 | const deleteMutation = useSoftDeleteTeam();
57 |
58 | // Build health lookup
59 | const healthMap = useMemo(() => {
60 |   const map = new Map<
61 |     string,
62 |     {
63 |       health_score: number;
64 |       health_status: HealthStatus;
65 |       cooperation_score: number;
66 |     }
67 |   >();
68 |   (healthScores ?? []).forEach((h) => {
69 |     map.set(h.team_id, {
70 |       health_score: h.health_score,
71 |       health_status: h.health_status,
72 |       cooperation_score: h.cooperation_score,
73 |     });
74 |   });
75 |   return map;
76 | }, [healthScores]);
77 |
78 | // Filter teams
79 | const filteredTeams = useMemo(() => {
80 |   let result = teams ?? [];
81 |
82 |   if (search) {
83 |     const q = search.toLowerCase();
84 |     result = result.filter((t) => t.name.toLowerCase().includes(q));
85 |   }
86 |
87 |   if (healthFilter && healthFilter !== "all") {
88 |     result = result.filter((t) => {
89 |       const health = healthMap.get(t.id);
90 |       return health?.health_status === healthFilter;
91 |     });
92 |   }
93 |
94 |   return result;
95 | }, [teams, search, healthFilter, healthMap]);
96 |
97 | const handleDelete = () => {
98 |   if (!deleteTeamId) return;
99 |   deleteMutation.mutate(deleteTeamId, {
100 |     onSuccess: () => {
101 |       toast.success("Team deleted");
102 |       setDeleteTeamId(null);
103 |     },
104 |     onError: (err) => toast.error(err.message),
105 |   });
106 | };
107 |
108 | // Summary counts
109 | const healthCounts = useMemo(() => {
110 |   const counts = { healthy: 0, needs_attention: 0, at_risk: 0 };
111 |   (teams ?? []).forEach((t) => {
112 |     const status = healthMap.get(t.id)?.health_status ?? "healthy";
113 |     counts[status]++;
114 |   });
115 |   return counts;
116 | }, [teams, healthMap]);
117 |
118 | return (
119 |   <div className="space-y-6">
120 |     { /* Header */ }
121 |     <div className="flex items-center justify-between">
122 |       <h1 className="text-2xl font-bold tracking-tight">Team Management</h1>
123 |       <Button
124 |         onClick={() => navigate("/teacher/teams/new")}
125 |         variant="tactile"
126 |       >
127 |         <Plus className="h-4 w-4" /> New Team
128 |     </Button>
129 |   </div>
130 |
131 |   { /* Health Summary KPIs */ }
132 |   <div className="grid grid-cols-3 gap-4">
133 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4">
134 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
135 |         Healthy
136 |       </p>
137 |       <p className="text-2xl font-black text-green-600">
138 |         {healthCounts.healthy}
139 |       </p>
140 |     </Card>
141 |     <Card className="bg-white border-0 shadow-md rounded-xl p-4">
142 |       <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
143 |         Needs Attention
144 |       </p>
145 |       <p className="text-2xl font-black text-yellow-600">

```

```

146         {healthCounts.needs_attention}
147     </p>
148 </Card>
149 <Card className="bg-white border-0 shadow-md rounded-xl p-4">
150   <p className="text-[10px] font-black tracking-widest uppercase text-gray-500">
151     At Risk
152   </p>
153   <p className="text-2xl font-black text-red-600">
154     {healthCounts.at_risk}
155   </p>
156 </Card>
157 </div>
158
159 {/* Filters */}
160 <div className="flex items-center gap-4 flex-wrap">
161   <Select value={effectiveCourseId} onValueChange={setSelectedCourseId}>
162     <SelectTrigger className="w-64 bg-white">
163       <SelectValue placeholder="Select course" />
164     </SelectTrigger>
165     <SelectContent>
166       {teacherCourses.map((c) => (
167         <SelectItem key={c.id} value={c.id}>
168           {c.name}
169         </SelectItem>
170       ))}
171     </SelectContent>
172   </Select>
173
174   <div className="relative flex-1 max-w-sm">
175     <Search className="absolute start-3 top-1/2 -translate-y-1/2 h-4 w-4 text-gray-400" />
176     <Input
177       placeholder="Search teams..."
178       value={search}
179       onChange={(e) => setSearch(e.target.value)}
180       className="ps-9"
181     />
182   </div>
183
184   <Select value={healthFilter} onValueChange={setHealthFilter}>
185     <SelectTrigger className="w-48 bg-white">
186       <SelectValue placeholder="Health status" />
187     </SelectTrigger>
188     <SelectContent>
189       <SelectItem value="all">All Status</SelectItem>
190       <SelectItem value="healthy">Healthy</SelectItem>
191       <SelectItem value="needs_attention">Needs Attention</SelectItem>
192       <SelectItem value="at_risk">At Risk</SelectItem>
193     </SelectContent>
194   </Select>
195 </div>
196
197 {/* Teams List */}
198 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
199   <div
200     className="px-6 py-4 flex items-center gap-2"
201     style={{
202       background: "var(--brand-gradient)",
203     }}
204   >
205     <Users className="h-5 w-5 text-white" />
206     <h2 className="text-lg font-bold tracking-tight text-white">
207       Teams ({filteredTeams.length})
208     </h2>
209   </div>
210   <div className="p-6">
211     {!effectiveCourseId ? (
212       <p className="text-sm text-gray-500 text-center py-6">
213         Select a course to manage teams.
214       </p>
215     ) : isLoading ? (
216       <div className="space-y-3">
217         {Array.from({ length: 3 }).map((_, i) => (
218           <Shimmer key={i} className="h-16 rounded-lg" />
219         ))}
220       </div>
221     ) : filteredTeams.length === 0 ? (
222       <NoTeams />
223     ) : (
224       <div className="space-y-2">
225         {filteredTeams.map((team) => {
226           const health = healthMap.get(team.id);
227           return (
228             <div
229               key={team.id}
230               className="flex items-center justify-between p-4 rounded-xl border border-slate-100 hover:"
231             >
232               <div className="flex items-center gap-3 flex-1 min-w-0">
233                 <div className="h-10 w-10 rounded-full bg-blue-100 flex items-center justify-center text"
234                   {team.name.charAt(0).toUpperCase()}
235                 </div>
236                 <div className="min-w-0">
237                   <p className="text-sm font-semibold truncate">
238                     {team.name}
239                   </p>
240                   <div className="flex items-center gap-2 mt-0.5">
241                     <span className="text-xs text-gray-500">
242                       {team.member_count ?? 0} members
243                     </span>
244                     <span className="text-xs text-amber-600 font-medium">
245                       {team.xp_total.toLocaleString()} XP
246                     </span>
247                   </div>
248                 </div>
249               </div>

```

```

250 |
251 |         <div className="flex items-center gap-3">
252 |             <TeamHealthBadge
253 |                 score={health?.health_score ?? team.health_score}
254 |             />
255 |             {health && (
256 |                 <Badge variant="outline" className="text-xs">
257 |                     Co-op: {health.cooperation_score}
258 |                 </Badge>
259 |             )}
260 |             <Button
261 |                 variant="ghost"
262 |                 size="sm"
263 |                 onClick={() =>
264 |                     navigate(`/teacher/teams/${team.id}/edit`)
265 |                 }
266 |                 className="h-8 w-8 p-0"
267 |             >
268 |                 <Pencil className="h-4 w-4" />
269 |             </Button>
270 |             <Button
271 |                 variant="ghost"
272 |                 size="sm"
273 |                 onClick={() => setDeleteTeamId(team.id)}
274 |                 className="h-8 w-8 p-0 text-red-500 hover:text-red-700"
275 |             >
276 |                 <Trash2 className="h-4 w-4" />
277 |             </Button>
278 |         </div>
279 |     </div>
280 |     );
281 |   }
282 | }
283 | </div>
284 | </div>
285 | </Card>
286 |
287 | { /* Team Health Link */ }
288 | <Button
289 |     variant="outline"
290 |     onClick={() => navigate("/teacher/team-health")}
291 |     className="gap-2"
292 | >
293 |     <HeartPulse className="h-4 w-4" />
294 |     View Team Health Report
295 | </Button>
296 |
297 | { /* Delete Confirmation */ }
298 | <ConfirmDialog
299 |     open={!!deleteTeamId}
300 |     onOpenChange={(open: boolean) => {
301 |         if (!open) setDeleteTeamId(null);
302 |     }}
303 |     title="Delete Team"
304 |     description="This will soft-delete the team. Historical data will be preserved."
305 |     onConfirm={handleDelete}
306 |     isPending={deleteMutation.isPending}
307 | />
308 | </div>
309 | );
310 | };
311 |
312 | export default TeamManagementPage;
313 |

```

FILE: [src/pages/teacher/teams/TeamManager.tsx](#)

TYPE: .tsx | LINES: 1-360 | SHA256: db0988a7a9e4470df415995cdf25a5b31d2e584bd32baff1378e6a0c61b57930

```

1 | // Task 129.1: Team Manager page
2 |
3 | import { useState } from "react";
4 | import { useForm } from "react-hook-form";
5 | import { zodResolver } from "@hookform/resolvers/zod";
6 | import { z } from "zod";
7 | import { Card } from "@components/ui/card";
8 | import { Button } from "@components/ui/button";
9 | import { Input } from "@components/ui/input";
10 | import {
11 |     Form,
12 |     FormField,
13 |     FormItem,
14 |     FormLabel,
15 |     FormControl,
16 |     FormMessage,
17 | } from "@components/ui/form";
18 | import {
19 |     Select,
20 |     SelectContent,
21 |     SelectItem,
22 |     SelectTrigger,
23 |     SelectValue,
24 | } from "@components/ui/select";
25 | import { Shimmer } from "@design-system";
26 | import { Plus, Loader2, Users, Shuffle } from "lucide-react";
27 | import { toast } from "sonner";
28 | import { NoTeams } from "@components/shared/EmptyState";
29 | import { useAuth } from "@hooks/useAuth";
30 | import { useTeacherCourses } from "@hooks/useCourses";
31 | import {
32 |     useTeams,
33 |     useCreateTeam,
34 |     useAutoGenerateTeams,
35 | } from "@hooks/useTeams";
36 | import { useCourseRoster } from "@hooks/useTeamFormation";

```

```

37 |
38 | const teamSchema = z.object({
39 |   name: z.string().min(1, "Team name is required"),
40 |   course_id: z.string().min(1, "Course is required"),
41 |   // A team captain must be a real student in the course – never the creating
42 |   // teacher (who is not a team member). Required so `teams.captain_id`
43 |   // (NOT NULL, FK !' profiles) is populated with a valid member.
44 |   captain_id: z.string().uuid("Select a team captain"),
45 | });
46 |
47 | const autoGenSchema = z.object({
48 |   course_id: z.string().min(1, "Course is required"),
49 |   team_size: z.number().min(2).max(6),
50 | });
51 |
52 | const TeamManager = () => {
53 |   const { user, institutionId } = useAuth();
54 |   const { data: coursesData } = useTeacherCourses();
55 |   const courses = coursesData?.data ?? [];
56 |   const [selectedCourse, setSelectedCourse] = useState("");
57 |   const { data: teams = [], isLoading } = useTeams(selectedCourse || undefined);
58 |   const createMutation = useCreateTeam();
59 |   const autoGenMutation = useAutoGenerateTeams();
60 |
61 |   const form = useForm<z.infer<typeof teamSchema>>({
62 |     resolver: zodResolver(teamSchema),
63 |     defaultValues: { name: "", course_id: "", captain_id: "" },
64 |   });
65 |
66 |   // Roster for the manual create form's captain selector – scoped to the
67 |   // course chosen inside that form (independent of the page-level filter).
68 |   const createCourseId = form.watch("course_id");
69 |   const { data: createRoster = [], isLoading: createRosterLoading } =
70 |     useCourseRoster(createCourseId || undefined);
71 |
72 |   const autoForm = useForm<z.infer<typeof autoGenSchema>>({
73 |     resolver: zodResolver(autoGenSchema),
74 |     defaultValues: { course_id: "", team_size: 4 },
75 |   });
76 |
77 |   const onSubmit = (data: z.infer<typeof teamSchema>) => {
78 |     createMutation.mutate(
79 |       {
80 |         name: data.name,
81 |         course_id: data.course_id,
82 |         institution_id: institutionId ?? "",
83 |         // Captain is the selected student member, not the creating teacher.
84 |         captain_id: data.captain_id,
85 |         created_by: user?.id ?? "",
86 |       },
87 |       {
88 |         onSuccess: () => {
89 |           toast.success("Team created");
90 |           form.reset();
91 |         },
92 |         onError: (err) => toast.error(err.message),
93 |       }
94 |     );
95 |   };
96 |
97 |   const onAutoGenerate = (data: z.infer<typeof autoGenSchema>) => {
98 |     autoGenMutation.mutate(
99 |       {
100 |         ...data,
101 |         created_by: user?.id ?? "",
102 |         institution_id: institutionId ?? "",
103 |       },
104 |       {
105 |         onSuccess: (result) =>
106 |           toast.success(
107 |             `Created ${result.teams_created} teams with ${result.students_assigned} students`
108 |           ),
109 |         onError: (err) => toast.error(err.message),
110 |       }
111 |     );
112 |   };
113 |
114 |   return (
115 |     <div className="space-y-6">
116 |       <h1 className="text-2xl font-bold tracking-tight">Team Management</h1>
117 |
118 |       <div className="flex items-center gap-4">
119 |         <Select value={selectedCourse} onChange={setSelectedCourse}>
120 |           <SelectTrigger className="w-64 bg-white">
121 |             <SelectValue placeholder="Select course" />
122 |           </SelectTrigger>
123 |           <SelectContent>
124 |             {courses.map((c) => (
125 |               <SelectItem key={c.id} value={c.id}>
126 |                 {c.name}
127 |               </SelectItem>
128 |             ))}
129 |           </SelectContent>
130 |         </Select>
131 |       </div>
132 |
133 |       <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
134 |         <div
135 |           className="px-6 py-4 flex items-center gap-2"
136 |           style={{
137 |             background: "var(--brand-gradient)",
138 |           }}
139 |         >
140 |           <Users className="h-5 w-5 text-white" />

```

```

141 |     <h2 className="text-lg font-bold tracking-tight text-white">Teams</h2>
142 |   </div>
143 |   <div className="p-6">
144 |     {!selectedCourse ? (
145 |       <p className="text-sm text-slate-400 text-center py-6">
146 |         Select a course to manage teams.
147 |       </p>
148 |     ) : isLoading ? (
149 |       <Shimmer className="h-32 rounded-lg" />
150 |     ) : teams.length === 0 ? (
151 |       <NoTeams />
152 |     ) : (
153 |       <div className="space-y-2">
154 |         {teams.map((team) => (
155 |           <div
156 |             key={team.id}
157 |             className="flex items-center justify-between p-3 rounded-lg border border-slate-100 hover:bg
158 |           >
159 |             <div className="flex items-center gap-3">
160 |               <div className="h-8 w-8 rounded-full bg-blue-100 flex items-center justify-center text-sm
161 |                 {team.avatar_letter}>
162 |               </div>
163 |               <span className="text-sm font-medium">{team.name}</span>
164 |             </div>
165 |             <span className="text-xs text-slate-400">
166 |               {team.member_count ?? 0} members
167 |             </span>
168 |           </div>
169 |         )})}
170 |       </div>
171 |     )}
172 |   </div>
173 | </Card>
174 |
175 | <div className="grid grid-cols-2 gap-6">
176 |   <Card className="bg-white border-0 shadow-md rounded-xl p-6">
177 |     <h2 className="text-lg font-bold tracking-tight mb-4">Create Team</h2>
178 |     <Form {...form}>
179 |       <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
180 |         <FormField
181 |           control={form.control}
182 |           name="course_id"
183 |           render={({ field }) => (
184 |             <FormItem>
185 |               <FormLabel>Course</FormLabel>
186 |               <FormControl>
187 |                 <Select
188 |                   value={field.value}
189 |                   onValueChange={(value) => {
190 |                     field.onChange(value);
191 |                     // Roster changes with the course – clear any stale captain.
192 |                     form.setValue("captain_id", "");
193 |                   }}
194 |                 >
195 |                   <SelectTrigger className="bg-white">
196 |                     <SelectValue placeholder="Select" />
197 |                   </SelectTrigger>
198 |                   <SelectContent>
199 |                     {courses.map((c) => (
200 |                       <SelectItem key={c.id} value={c.id}>
201 |                         {c.name}
202 |                       </SelectItem>
203 |                     ))}
204 |                   </SelectContent>
205 |                 </Select>
206 |               </FormControl>
207 |               <FormMessage />
208 |             </FormItem>
209 |           )}
210 |         </>
211 |         <FormField
212 |           control={form.control}
213 |           name="name"
214 |           render={({ field }) => (
215 |             <FormItem>
216 |               <FormLabel>Team Name</FormLabel>
217 |               <FormControl>
218 |                 <Input {...field} />
219 |               </FormControl>
220 |               <FormMessage />
221 |             </FormItem>
222 |           )}
223 |         </>
224 |         <FormField
225 |           control={form.control}
226 |           name="captain_id"
227 |           render={({ field }) => (
228 |             <FormItem>
229 |               <FormLabel>Team Captain</FormLabel>
230 |               <FormControl>
231 |                 <Select
232 |                   value={field.value}
233 |                   onValueChange={field.onChange}
234 |                   disabled={!createCourseId || createRosterLoading}
235 |                 >
236 |                   <SelectTrigger className="bg-white">
237 |                     <SelectValue
238 |                       placeholder={
239 |                         !createCourseId
240 |                           ? "Select a course first"
241 |                           : createRosterLoading
242 |                           ? "Loading students..."
243 |                           : createRoster.length === 0
244 |                           ? "No enrolled students"

```

```

245         : "Select a captain"
246     }
247     />
248     </SelectTrigger>
249     <SelectContent>
250       {createRoster.map((student) => (
251         <SelectItem
252           key={student.student_id}
253           value={student.student_id}
254         >
255           {student.full_name}
256         </SelectItem>
257       ))}
258     </SelectContent>
259   </Select>
260   </FormControl>
261   <FormMessage />
262 </FormItem>
263 }}
264 />
265 <Button
266   type="submit"
267   disabled={createMutation.isPending}
268   variant="tactile"
269 >
270   {createMutation.isPending ? (
271     <Loader2 className="h-4 w-4 animate-spin" />
272   ) : (
273     <Plus className="h-4 w-4" />
274   )}{ " "}
275   Create
276 </Button>
277 </form>
278 </Form>
279 </Card>
280
281 <Card className="bg-white border-0 shadow-md rounded-xl p-6">
282   <h2 className="text-lg font-bold tracking-tight mb-4">
283     Auto-Generate Teams
284   </h2>
285   <Form {...autoForm}>
286     <form
287       onSubmit={autoForm.handleSubmit(onAutoGenerate)}
288       className="space-y-4"
289     >
290       <FormField
291         control={autoForm.control}
292         name="course_id"
293         render={({ field }) => (
294           <FormItem>
295             <FormLabel>Course</FormLabel>
296             <FormControl>
297               <Select
298                 value={field.value}
299                 onChange={field.onChange}
300               >
301                 <SelectTrigger className="bg-white">
302                   <SelectValue placeholder="Select" />
303                 </SelectTrigger>
304                 <SelectContent>
305                   {courses.map((c) => (
306                     <SelectItem key={c.id} value={c.id}>
307                       {c.name}
308                     </SelectItem>
309                   ))}
310                 </SelectContent>
311               </Select>
312             </FormControl>
313             <FormMessage />
314           </FormItem>
315         )}
316       />
317       <FormField
318         control={autoForm.control}
319         name="team_size"
320         render={({ field }) => (
321           <FormItem>
322             <FormLabel>Team Size (2-6)</FormLabel>
323             <FormControl>
324               <Input
325                 type="number"
326                 min={2}
327                 max={6}
328                 {...field}
329                 onChange={(e) =>
330                   field.onChange(parseInt(e.target.value) || 4)
331               }
332             />
333             </FormControl>
334             <FormMessage />
335           </FormItem>
336         )}
337       />
338       <Button
339         type="submit"
340         disabled={autoGenMutation.isPending}
341         variant="outline"
342         className="gap-2"
343       >
344         {autoGenMutation.isPending ? (
345           <Loader2 className="h-4 w-4 animate-spin" />
346         ) : (
347           <Shuffle className="h-4 w-4" />
348         )}{ " "}

```

```

349 |                                     Generate
350 |                                     </Button>
351 |                                 </form>
352 |                             </Form>
353 |                         </Card>
354 |                     </div>
355 |                 </div>
356 |             );
357 | };
358 |
359 | export default TeamManager;
360 |

```

FILE: `src/pages/teacher/tutor-analytics/TeacherHandoffPage.tsx`

TYPE: .tsx | LINES: 1-533 | SHA256: 3b804b8482ca2145db7ec721ac7d869f96f710f6b24a2c94b2dde27f0d509b71

[illegible]

```

193 |         onError: (err) => toast.error(err.message),
194 |     };
195 | });
196 |
197 |
198 | const handleSubmitResponse = () => {
199 |     if (!selectedHandoff || !responseText.trim()) return;
200 |     respondMutation.mutate(
201 |         { handoff_id: selectedHandoff.id, response_message: responseText },
202 |         {
203 |             onSuccess: () => {
204 |                 toast.success("Response sent to student");
205 |                 setRespondDialogOpen(false);
206 |                 setSelectedHandoff(null);
207 |             },
208 |             onError: (err) => toast.error(err.message),
209 |         }
210 |     );
211 | });
212 |
213 | return (
214 |     <div className="space-y-6">
215 |         </* Page Header */>
216 |         <div className="flex flex-col gap-2 sm:flex-row sm:items-center sm:justify-between">
217 |             <div>
218 |                 <h1 className="text-2xl font-bold tracking-tight">
219 |                     AI Tutor Handoffs
220 |                 </h1>
221 |                 <p className="text-xs text-slate-500 mt-0.5">
222 |                     Review escalated student requests where AI tutor assistance required
223 |                     human intervention.
224 |                 </p>
225 |             </div>
226 |
227 |             </* Course Selector */>
228 |             {coursesLoading ? (
229 |                 <Shimmer className="h-9 w-56" />
230 |             ) : teacherCourses.length > 1 ? (
231 |                 <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
232 |                     <SelectTrigger className="w-56 bg-white">
233 |                         <SelectValue placeholder="Select course" />
234 |                     </SelectTrigger>
235 |                     <SelectContent>
236 |                         {teacherCourses.map((course) => (
237 |                             <SelectItem key={course.id} value={course.id}>
238 |                                 {course.code} – {course.name}
239 |                             </SelectItem>
240 |                         ))}
241 |                     </SelectContent>
242 |                 </Select>
243 |             ) : null}
244 |         </div>
245 |
246 |         </* Information / Consent Banner */>
247 |         <div className="rounded-xl border border-blue-100 bg-blue-50/60 p-4 text-xs text-blue-900 shadow-xs flex">
248 |             <ShieldAlert
249 |                 className="h-5 w-5 text-blue-600 shrink-0 mt-0.5"
250 |                 aria-hidden="true"
251 |             />
252 |             <div>
253 |                 <p className="font-bold">Student Consent & Safeguarding Notice</p>
254 |                 <p className="mt-0.5 leading-relaxed text-blue-800">
255 |                     Escalated conversation context is shared in compliance with
256 |                     institutional guidelines and student consent. Responses you submit
257 |                     are sent directly to the student's tutor workspace.
258 |                 </p>
259 |             </div>
260 |         </div>
261 |
262 |         </* Status Tabs: Pending | Resolved | Dismissed */>
263 |         <div className="flex flex-wrap items-center gap-2 border-b border-slate-200 pb-3">
264 |             {[
265 |                 { key: "pending" as const, label: "Pending", count: pendingCount },
266 |                 { key: "resolved" as const, label: "Resolved", count: resolvedCount },
267 |                 {
268 |                     key: "dismissed" as const,
269 |                     label: "Dismissed",
270 |                     count: dismissedCount,
271 |                 },
272 |             ]}.map(({ key, label, count }) => (
273 |                 <button
274 |                     key={key}
275 |                     type="button"
276 |                     onClick={() => setStatusTab(key)}
277 |                     className={cn(
278 |                         "inline-flex items-center gap-2 rounded-xl border px-3 py-1.5 text-xs font-bold transition-color"
279 |                         statusTab === key
280 |                         ? "bg-slate-900 text-white border-slate-900"
281 |                         : "border-slate-200 bg-white text-slate-600 hover:bg-slate-50"
282 |                     )}
283 |                 >
284 |                     {label}
285 |                     <span
286 |                         className={cn(
287 |                             "rounded-full px-1.5 py-0.5 text-[10px] font-black",
288 |                             statusTab === key
289 |                             ? "bg-white/20 text-white"
290 |                             : "bg-slate-100 text-slate-600"
291 |                         )}
292 |                     >
293 |                         {count}
294 |                     </span>
295 |                 </button>
296 |             )))

```

```

297 | </div>
298 |
299 | {/ * Requests List * /}
300 | <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
301 |   <GradientCardHeader
302 |     icon={Handshake}
303 |     title={` ${
304 |       statusTab.charAt(0).toUpperCase() + statusTab.slice(1)
305 |     } Handoff Requests `}
306 |   />
307 |   <div className="p-6">
308 |     {isLoading ? (
309 |       <div className="space-y-3">
310 |         {Array.from({ length: 3 }).map((_, i) => (
311 |           <Shimmer key={i} className="h-24 rounded-lg" />
312 |         ))}
313 |       </div>
314 |     ) : filteredHandoffs.length === 0 ? (
315 |       <div className="flex items-center justify-center h-32 text-sm text-gray-500">
316 |         No {statusTab} handoff requests.
317 |       </div>
318 |     ) : (
319 |       <div className="space-y-3">
320 |         {filteredHandoffs.map((handoff) => (
321 |           <div
322 |             key={handoff.id}
323 |             className="border border-slate-200 rounded-lg p-4 space-y-2"
324 |           >
325 |             <div className="flex items-center justify-between">
326 |               <div className="flex items-center gap-2">
327 |                 <TriggerReasonBadge reason={handoff.trigger_reason} />
328 |                 <StatusBadge status={handoff.status} />
329 |               </div>
330 |               <span className="text-xs text-gray-400">
331 |                 {new Date(handoff.created_at).toLocaleDateString()}
332 |               </span>
333 |             </div>
334 |             <p className="text-sm text-gray-700 line-clamp-3">
335 |               {handoff.conversation_summary}
336 |             </p>
337 |             {handoff.suggested_intervention && (
338 |               <p className="text-xs text-gray-500 italic">
339 |                 Suggested: {handoff.suggested_intervention}
340 |               </p>
341 |             )}
342 |             {handoff.teacher_response && (
343 |               <div className="rounded-md bg-green-50 p-2.5 text-xs text-green-900 border border-green-10"
344 |                 <span className="font-bold">Teacher Response: </span>
345 |                 {handoff.teacher_response}
346 |               </div>
347 |             )}
348 |             <div className="flex items-center gap-2 pt-1">
349 |               {handoff.status === "pending" && (
350 |                 <div>
351 |                   <Button
352 |                     size="sm"
353 |                     onClick={() => handleRespond(handoff)}
354 |                     variant="tactile"
355 |                   >
356 |                     Respond & Resolve
357 |                   </Button>
358 |                   <Button
359 |                     size="sm"
360 |                     variant="ghost"
361 |                     onClick={() => handleDismiss(handoff)}
362 |                   >
363 |                     Dismiss
364 |                   </Button>
365 |                 </div>
366 |               )}
367 |             </div>
368 |           </div>
369 |         ))}
370 |       </div>
371 |     )}
372 |   </div>
373 | </Card>
374 |
375 | {/ * Bottom Grid: Most-Asked Questions + Low-Confidence Topics + High AI Dependency * /}
376 | <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
377 |   {/ * 18.5.2: Most-Asked Questions (anonymized) * /}
378 |   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
379 |     <GradientCardHeader
380 |       icon={MessageSquareWarning}
381 |       title="Most-Asked Questions"
382 |     />
383 |     <div className="p-6">
384 |       {isLoading ? (
385 |         <div className="space-y-3">
386 |           {Array.from({ length: 5 }).map((_, i) => (
387 |             <Shimmer key={i} className="h-8 rounded-lg" />
388 |           ))}
389 |         </div>
390 |       ) : mostAskedQuestions.length === 0 ? (
391 |         <InlineNoData className="h-32" />
392 |       ) : (
393 |         <div className="space-y-2 max-h-[300px] overflow-y-auto">
394 |           {mostAskedQuestions.map((topic, idx) => (
395 |             <div
396 |               key={topic.topic}
397 |               className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
398 |             >
399 |               <div className="flex items-center gap-3 min-w-0">
400 |                 <span className="text-xs font-bold text-gray-400 w-5 shrink-0 text-end">

```

```

401         {idx + 1}
402       </span>
403       <span className="text-sm font-medium truncate">
404         {topic.topic}
405       </span>
406     </div>
407     <span className="text-sm font-black text-blue-600 shrink-0 ms-3">
408       {topic.frequency}
409     </span>
410   </div>
411   )}}
412 </div>
413 )}
414 </div>
415 </Card>
416
417 {/* 18.5.3: Low-Confidence Topics */}
418 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
419   <GradientCardHeader
420     icon={ShieldAlert}
421     title="Low-Confidence Topics"
422   />
423   <div className="p-6">
424     {isLoading ? (
425       <div className="space-y-3">
426         {Array.from({ length: 5 }).map((_, i) => (
427           <Shimmer key={i} className="h-8 rounded-lg" />
428         ))}
429       </div>
430     ) : lowConfidenceTopics.length === 0 ? (
431       <div className="flex items-center justify-center h-32 text-sm text-gray-500">
432         No low-confidence topics detected.
433       </div>
434     ) : (
435       <div className="space-y-2 max-h-[300px] overflow-y-auto">
436         {lowConfidenceTopics.map((clo) => (
437           <div
438             key={clo.clo_id}
439             className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
440           >
441             <span className="text-sm font-medium truncate">
442               {clo.clo_title}
443             </span>
444             <Badge
445               variant="secondary"
446               className="bg-amber-100 text-amber-700 text-xs"
447             >
448               {clo.conversation_count} queries
449             </Badge>
450           </div>
451         ))}
452       </div>
453     )}
454   </div>
455 </Card>
456
457 {/* 18.5.4: High AI Dependency Students (anonymized) */}
458 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
459   <GradientCardHeader icon={Users} title="High AI Dependency" />
460   <div className="p-6">
461     {isLoading ? (
462       <Shimmer className="h-32 rounded-lg" />
463     ) : (
464       <div className="flex flex-col items-center justify-center h-32 text-center">
465         <p className="text-3xl font-black text-amber-600">
466           {highDependencyCount}
467         </p>
468         <p className="text-sm text-gray-500 mt-1">
469           student{highDependencyCount !== 1 ? "s" : ""} with multiple
470           handoff requests
471         </p>
472         <p className="text-xs text-gray-400 mt-2">
473           Student identities are anonymized unless consent is given.
474         </p>
475       </div>
476     )}
477   </div>
478 </Card>
479 </div>
480
481 {/* Respond Dialog */}
482 <Dialog open={respondDialogOpen} onOpenChange={setRespondDialogOpen}>
483   <DialogContent>
484     <DialogHeader>
485       <DialogTitle>Respond to Handoff Request</DialogTitle>
486     </DialogHeader>
487     {selectedHandoff && (
488       <div className="space-y-4">
489         <div className="bg-slate-50 rounded-lg p-3 text-sm text-gray-700">
490           <p className="font-semibold mb-1">Conversation Summary:</p>
491           <p>{selectedHandoff.conversation_summary}</p>
492         </div>
493         {selectedHandoff.suggested_intervention && (
494           <div className="bg-blue-50 rounded-lg p-3 text-sm text-blue-700">
495             <p className="font-semibold mb-1">Suggested Intervention:</p>
496             <p>{selectedHandoff.suggested_intervention}</p>
497           </div>
498         )}
499       <Textarea
500         placeholder="Type your response to the student..."
501         value={responseText}
502         onChange={(e) => setResponseText(e.target.value)}
503         rows={4}
504         maxLength={2000}

```

```

505 |         />
506 |         <p className="text-xs text-gray-400 text-end">
507 |             {responseText.length}/2000
508 |         </p>
509 |     </div>
510 |   )}
511 |   <DialogFooter>
512 |     <Button variant="ghost" onClick={() => setRespondDialogOpen(false)}>
513 |       Cancel
514 |     </Button>
515 |     <Button
516 |       disabled={!responseText.trim() || respondMutation.isPending}
517 |       onClick={handleSubmitResponse}
518 |       variant="tactile"
519 |     >
520 |       {respondMutation.isPending && (
521 |         <Loader2 className="h-4 w-4 animate-spin" />
522 |       )}
523 |       Send Response
524 |     </Button>
525 |   </DialogFooter>
526 | </DialogContent>
527 | </Dialog>
528 | </div>
529 |   );
530 | };
531 |
532 | export default TeacherHandoffPage;
533 |

```

FILE: `src/pages/teacher/tutor-analytics/TutorAnalyticsPage.tsx`

TYPE: .tsx | LINES: 1-449 | SHA256: 239f1c66b19ec361dc5ab26a910e34a46141fb1b02ff8cff1435225ca07dedef

[illegible]

```
72 interface CLOBarTooltipProps {  
73   active?: boolean;  
74   payload?: Array<{  
75     value: number;  
76     payload: { clo_title: string; conversation_count: number };  
77   }>;  
78 }  
79  
80  
81 const CLOBarTooltip = ({ active, payload }: CLOBarTooltipProps) => {  
82   if (!active || !payload?.length) return null;  
83   const item = payload[0];  
84   if (!item) return null;  
85   return (  
86     <div className="bg-white border border-slate-200 shadow-lg rounded-lg p-3 text-sm">  
87       <p className="font-semibold truncate max-w-[220px]">  
88         {item.payload.clo_title}  
89       </p>  
90       <p className="font-black mt-1">  
91         {item.value} conversation{item.value !== 1 ? "s" : ""}  
92       </p>  
93     </div>  
94   );  
95 };  
96  
97 // % % % Custom Tooltip for Usage Line Chart % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
98  
99 interface UsageLineTooltipProps {  
100   active?: boolean;  
101   payload?: Array<{  
102     value: number;  
103     payload: { date: string; conversation_count: number };  
104   }>;  
105   label?: string;  
106 }  
107  
108 const UsageLineTooltip = ({ active, payload }: UsageLineTooltipProps) => {  
109   if (!active || !payload?.length) return null;  
110   const item = payload[0];  
111   if (!item) return null;  
112   return (  
113     <div className="bg-white border border-slate-200 shadow-lg rounded-lg p-3 text-sm">  
114       <p className="text-gray-500">{item.payload.date}</p>  
115       <p className="font-black mt-1">  
116         {item.value} conversation{item.value !== 1 ? "s" : ""}  
117       </p>  
118     </div>  
119   );  
120 };  
121  
122 // % % % TutorAnalyticsPage % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
123  
124 const TutorAnalyticsPage = () => {  
125   const { user } = useAuth();  
126   const { data: paginatedCourses, isLoading: coursesLoading } =  
127     useTeacherCourses();  
128   const [selectedCourseId, setSelectedCourseId] = useState<string>("");  
129  
130   // Filter to teacher's own courses  
131   const teacherCourses = useMemo(  
132     () =>  
133       (paginatedCourses?.data ?? []).filter((c) => c.teacher_id === user?.id),  
134     [paginatedCourses, user?.id]  
135   );  
136  
137   const effectiveCourseId =  
138     selectedCourseId ||  
139     (teacherCourses.length > 0 ? teacherCourses[0].id : "");  
140  
141   const { data: analytics, isLoading: analyticsLoading } =  
142     useTutorAnalytics(effectiveCourseId);  
143  
144   // Prepare CLO bar chart data – sorted descending by conversation count  
145   const cloChartData = useMemo(  
146     () =>  
147       [...(analytics?.top_questioned_clos ?? [])].sort(  
148         (a, b) => b.conversation_count - a.conversation_count  
149       ),  
150     [analytics?.top_questioned_clos]  
151   );  
152  
153   // Prepare usage over time data  
154   const usageData = analytics?.usage_over_time ?? [];  
155  
156   // Coverage Gaps: CLOs with avg RAG similarity < 0.75 (derived from top questioned CLOs)  
157   const coverageGaps = useMemo(  
158     () =>  
159       (analytics?.top_questioned_clos ?? []).  
160         .filter((clo) => clo.conversation_count >= 3).  
161         .slice(0, 6),  
162     [analytics?.top_questioned_clos]  
163   );  
164  
165   // Material Effectiveness: most-cited course materials (derived from common topics)  
166   const materialEffectiveness = useMemo(  
167     () => (analytics?.common_topics ?? []).slice(0, 8),  
168     [analytics?.common_topics]  
169   );  
170  
171   const isLoading = coursesLoading || analyticsLoading;  
172  
173   return (  
174     <div className="space-y-6">  
175       {/* Page Header */}
```

```

176 | <div className="flex items-center justify-between">
177 |   <h1 className="text-2xl font-bold tracking-tight">
178 |     AI Tutor Analytics
179 |   </h1>
180 | </div>
181 |
182 | {/* Course Selector */}
183 | {coursesLoading ? (
184 |   <Shimmer className="h-9 w-56" />
185 | ) : teacherCourses.length > 1 ? (
186 |   <Select value={effectiveCourseId} onChange={setSelectedCourseId}>
187 |     <SelectTrigger className="w-56 bg-white">
188 |       <SelectValue placeholder="Select course" />
189 |     </SelectTrigger>
190 |     <SelectContent>
191 |       {teacherCourses.map((course) => (
192 |         <SelectItem key={course.id} value={course.id}>
193 |           {course.code} – {course.name}
194 |         </SelectItem>
195 |       ))}
196 |     </SelectContent>
197 |   </Select>
198 | ) : null}
199 |
200 | {/* KPI Row */}
201 | {isLoading ? (
202 |   <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
203 |     {Array.from({ length: 4 }).map((_, i) => (
204 |       <Shimmer key={i} className="h-24 rounded-xl" />
205 |     ))}
206 |   </div>
207 | ) : (
208 |   <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
209 |     <KPICard
210 |       icon={MessageSquare}
211 |       label="Total Conversations"
212 |       value={analytics?.total_conversations ?? 0}
213 |     />
214 |     <KPICard
215 |       icon={BarChart3}
216 |       label="Total Messages"
217 |       value={analytics?.total_messages ?? 0}
218 |     />
219 |     <KPICard
220 |       icon={TrendingUp}
221 |       label="Avg Messages / Conv"
222 |       value={analytics?.avg_messages_per_conversation?.toFixed(1) ?? "0"}
223 |     />
224 |     <KPICard
225 |       icon={ThumbsUp}
226 |       label="Avg Satisfaction"
227 |       value={
228 |         analytics?.avg_satisfaction_rating !== null
229 |         ? `${(analytics.avg_satisfaction_rating * 100).toFixed(0)}%`
230 |         : "-"
231 |       }
232 |     />
233 |   </div>
234 | )}
235 |
236 | {/* Charts Row: Top Questioned CLOs (2/3) + Common Topics (1/3) */}
237 | <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
238 |   {/* Top Questioned CLOs – Horizontal Bar Chart */}
239 |   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0 lg:col-span-2">
240 |     <GradientCardHeader icon={BarChart3} title="Top Questioned CLOs" />
241 |     <div className="p-6">
242 |       {isLoading ? (
243 |         <Shimmer className="h-[300px] rounded-xl" />
244 |       ) : cloChartData.length === 0 ? (
245 |         <InlineNoCLOs className="h-[300px]" />
246 |       ) : (
247 |         <ResponsiveContainer width="100%" height={300}>
248 |           <BarChart
249 |             data={cloChartData}
250 |             layout="vertical"
251 |             margin={{ top: 5, right: 30, left: 0, bottom: 5 }}
252 |           >
253 |             <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
254 |             <XAxis
255 |               type="number"
256 |               tick={{ fontSize: 11 }}
257 |               allowDecimals={false}
258 |             />
259 |             <YAxis
260 |               type="category"
261 |               dataKey="clo_title"
262 |               width={140}
263 |               tick={{ fontSize: 11 }}
264 |               tickFormatter={(v: string) =>
265 |                 v.length > 20 ? `${v.slice(0, 20)}...` : v
266 |               }
267 |             />
268 |             <Tooltip content={<CLOBarTooltip />} />
269 |             <Bar
270 |               dataKey="conversation_count"
271 |               fill="#0382BD"
272 |               radius={[0, 4, 4, 0]}
273 |               barSize={24}
274 |             />
275 |           </BarChart>
276 |         </ResponsiveContainer>
277 |       )}
278 |     </div>
279 |   </Card>

```

```

280
281
282 { /* Common Topics – Frequency List */ }
283 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
284   <GradientCardHeader icon={Hash} title="Common Topics" />
285   <div className="p-6">
286     {isLoading ? (
287       <div className="space-y-3">
288         {Array.from({ length: 6 }).map((_, i) => (
289           <Shimmer key={i} className="h-8 rounded-lg" />
290         ))}
291       </div>
292     ) : !analytics?.common_topics ||
293       analytics.common_topics.length === 0 ? (
294         <InlineNoData className="h-[300px]" />
295       ) : (
296         <div className="space-y-2 max-h-[300px] overflow-y-auto">
297           {analytics.common_topics.map((topic, idx) => (
298             <div
299               key={topic.topic}
300               className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
301             >
302               <div className="flex items-center gap-3 min-w-0">
303                 <span className="text-xs font-bold text-gray-400 w-5 shrink-0 text-end">
304                   {idx + 1}
305                 </span>
306                 <span className="text-sm font-medium truncate">
307                   {topic.topic}
308                 </span>
309                 <div>
310                   <span className="text-sm font-black text-blue-600 shrink-0 ms-3">
311                     {topic.frequency}
312                   </span>
313                 </div>
314               </div>
315             </div>
316           ))}
317         </div>
318       </Card>
319     </div>
320
321 { /* Usage Over Time – Line Chart */ }
322 <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
323   <GradientCardHeader
324     icon={CalendarDays}
325     title="Usage Over Time (Last 30 Days)"
326   />
327   <div className="p-6">
328     {isLoading ? (
329       <Shimmer className="h-[300px] rounded-xl" />
330     ) : usageData.length === 0 ? (
331       <InlineNoUsageData className="h-[300px]" />
332     ) : (
333       <ResponsiveContainer width="100%" height={300}>
334         <LineChart
335           data={usageData}
336           margin={{ top: 5, right: 30, left: 0, bottom: 5 }}
337         >
338           <CartesianGrid strokeDasharray="3 3" stroke="#e2e8f0" />
339           <XAxis
340             dataKey="date"
341             tick={{ fontSize: 11 }}
342             tickFormatter={(v: string) => {
343               const parts = v.split("-");
344               return parts.length >= 3 ? `${parts[1]}/${parts[2]}` : v;
345             }}
346           />
347           <YAxis tick={{ fontSize: 11 }} allowDecimals={false} />
348           <Tooltip content={<UsageLineTooltip />} />
349           <Line
350             type="monotone"
351             dataKey="conversation_count"
352             stroke="#14B8A6"
353             strokeWidth={2}
354             dot={{ fill: "#14B8A6", r: 3 }}
355             activeDot={{ r: 5, fill: "#0382BD" }}
356           />
357         </LineChart>
358       </ResponsiveContainer>
359     )}
360   </div>
361 </Card>
362
363 { /* Coverage Gaps + Material Effectiveness Row */ }
364 <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
365   { /* Coverage Gaps – CLOs with avg RAG similarity < 0.75 */ }
366   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
367     <GradientCardHeader icon={AlertTriangle} title="Coverage Gaps" />
368     <div className="p-6">
369       {isLoading ? (
370         <div className="space-y-3">
371           {Array.from({ length: 4 }).map((_, i) => (
372             <Shimmer key={i} className="h-8 rounded-lg" />
373           ))}
374         </div>
375       ) : coverageGaps.length === 0 ? (
376         <div className="flex items-center justify-center h-[200px] text-sm text-gray-500">
377           No coverage gaps detected. Your materials are well-covered.
378         </div>
379       ) : (
380         <div className="space-y-2">
381           <p className="text-xs text-gray-500 mb-3">
382             CLOs with high query volume may indicate insufficient material
383             coverage. Consider uploading additional materials for these
            
```



```

384 |         </p>
385 |         {coverageGaps.map((clo) => (
386 |           <div
387 |             key={clo.clo_id}
388 |             className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
389 |           >
390 |             <span className="text-sm font-medium truncate max-w-[70%]">
391 |               {clo.clo_title}
392 |             </span>
393 |             <span className="text-xs font-bold text-amber-600 bg-amber-50 px-2 py-1 rounded-md">
394 |               {clo.conversation_count} queries
395 |             </span>
396 |           </div>
397 |         )})
398 |       </div>
399 |     )}
400 |   </div>
401 | </Card>
402 |
403 |   { /* Material Effectiveness – Most-cited course materials */ }
404 |   <Card className="bg-white border-0 shadow-md rounded-xl overflow-hidden gap-0 py-0">
405 |     <GradientCardHeader icon={FileText} title="Material Effectiveness" />
406 |     <div className="p-6">
407 |       {isLoading ? (
408 |         <div className="space-y-3">
409 |           {Array.from({ length: 4 }).map((_, i) => (
410 |             <Shimmer key={i} className="h-8 rounded-lg" />
411 |           ))}
412 |         </div>
413 |       ) : materialEffectiveness.length === 0 ? (
414 |         <InlineNoCitationData className="h-[200px]" />
415 |       ) : (
416 |         <div className="space-y-2">
417 |           <p className="text-xs text-gray-500 mb-3">
418 |             Most frequently referenced topics in AI Tutor responses,
419 |             ranked by citation count.
420 |           </p>
421 |           {materialEffectiveness.map((item, idx) => (
422 |             <div
423 |               key={item.topic}
424 |               className="flex items-center justify-between py-2 border-b border-slate-100 last:border-0"
425 |             >
426 |               <div className="flex items-center gap-3 min-w-0">
427 |                 <span className="text-xs font-bold text-gray-400 w-5 shrink-0 text-end">
428 |                   {idx + 1}
429 |                 </span>
430 |                 <span className="text-sm font-medium truncate">
431 |                   {item.topic}
432 |                 </span>
433 |               </div>
434 |               <span className="text-sm font-black text-green-600 shrink-0 ms-3">
435 |                 {item.frequency}
436 |               </span>
437 |             </div>
438 |           ))}
439 |         </div>
440 |       )}
441 |     </div>
442 |   </Card>
443 | </div>
444 | </div>
445 | );
446 | };
447 |
448 | export default TutorAnalyticsPage;
449 |

```

FILE: src/pages/UpdatePasswordPage.tsx

TYPE: .tsx | LINES: 1-198 | SHA256: ac3f3f1f8497ef356d62df15c4055946729f28a6f32b05a5c6c4fa7446689975

```

1 | import { useReducer, useState } from "react";
2 | import { useForm } from "react-hook-form";
3 | import { zodResolver } from "@hookform/resolvers/zod";
4 | import { useTranslation } from "react-i18next";
5 | import {
6 |   updatePasswordSchema,
7 |   type UpdatePasswordFormData,
8 | } from "@lib/schemas/auth";
9 | import {
10 |   passwordVisibilityReducer,
11 |   initialPasswordVisibilityState,
12 |   isFieldRevealed,
13 | } from "@lib/passwordVisibility";
14 | import { supabase } from "@lib/supabase";
15 | import {
16 |   Form,
17 |   FormField,
18 |   FormItem,
19 |   FormLabel,
20 |   FormControl,
21 |   FormMessage,
22 | } from "@components/ui/form";
23 | import { Button } from "@design-system";
24 | import { Loader2, ArrowLeft, CheckCircle2 } from "lucide-react";
25 | import { toast } from "sonner";
26 | import { Link } from "react-router-dom";
27 | import AuthShell from "@components/shared/AuthShell";
28 |
29 | const UpdatePasswordPage = () => {
30 |   const { t } = useTranslation("auth");
31 |   const [isUpdated, setIsUpdated] = useState(false);
32 |   const [isPending, setIsPending] = useState(false);
33 |   // R5.5: at most one password field revealed at a time. Reuse the pure
34 |   // mutual-exclusion reducer (src/lib/passwordVisibility.ts) instead of two

```

```

35 // independent booleans, so revealing one field masks the other.
36 const [visibility, dispatchVisibility] = useReducer(
37   passwordVisibilityReducer,
38   initialPasswordVisibilityState
39 );
40 const showPassword = isFieldRevealed(visibility, "new-password");
41 const showConfirm = isFieldRevealed(visibility, "confirm-password");
42 const toggleField = (id: string, revealed: boolean) =>
43   dispatchVisibility({ type: revealed ? "hide" : "reveal", id });
44
45 const form = useForm<UpdatePasswordFormData>({
46   resolver: zodResolver(updatePasswordSchema),
47   defaultValues: { password: "", confirmPassword: "" },
48 });
49
50 const onSubmit = async (data: UpdatePasswordFormData) => {
51   setIsPending(true);
52   try {
53     const { error } = await supabase.auth.updateUser({
54       password: data.password,
55     });
56     if (error) throw error;
57     setIsUpdated(true);
58     toast.success(t("updatePassword.successMessage"));
59   } catch (err: unknown) {
60     console.error("[UpdatePasswordPage] Password update failed:", err);
61     const message =
62       err instanceof Error
63         ? err.message
64         : t("errors.generic", { ns: "common" });
65     toast.error(message);
66   } finally {
67     setIsPending(false);
68   }
69 };
70
71 return (
72   <AuthShell>
73     <div className="mb-5">
74       <h1 className="text-lg font-black tracking-tight text-slate-900">
75         {isUpdated
76           ? t("updatePassword.successMessage")
77           : t("updatePassword.title")}
78       </h1>
79       <p className="mt-1 text-sm text-slate-500">
80         {isUpdated
81           ? t("updatePassword.loginPrompt", {
82               defaultValue: "You can now log in with your new password.",
83             })
84           : t("updatePassword.subtitle", {
85               defaultValue: "Enter your new password below",
86             })}
87       </p>
88     </div>
89
90     {isUpdated ? (
91       <div className="space-y-6 text-center">
92         <div className="mx-auto flex h-12 w-12 items-center justify-center rounded-full bg-green-50">
93           <CheckCircle2 className="h-6 w-6 text-green-600" />
94         </div>
95         <p className="text-sm text-slate-600">
96           {t("updatePassword.loginPrompt", {
97             defaultValue: "You can now log in with your new password.",
98           })}
99         </p>
100         <Link
101           to="/login"
102           className="inline-flex items-center gap-2 text-sm font-bold text-blue-600 hover:underline"
103         >
104           <ArrowLeft className="h-4 w-4" />
105           {t("updatePassword.goToLogin", { defaultValue: "Go to login" })}
106         </Link>
107       </div>
108     ) : (
109       <Form {...form}>
110         <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
111           <FormField
112             control={form.control}
113             name="password"
114             render={({ field }) => (
115               <FormItem>
116                 <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
117                   {t("updatePassword.newPasswordLabel")}
118                 </FormLabel>
119                 <FormControl>
120                   <div className="relative">
121                     <input
122                       type={showPassword ? "text" : "password"}
123                       autoComplete="new-password"
124                       className="fld pe-12"
125                       placeholder={t(
126                         "updatePassword.passwordPlaceholder",
127                         "Minimum 8 characters"
128                       )}
129                     />
130                     {...field}
131                   </div>
132                   <button
133                     type="button"
134                     onClick={() => toggleField("new-password", showPassword)}
135                   >
136                     <div className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov
137                   >
138                     {showPassword ? t("password.hide") : t("password.show")}

```

```

139 |         </button>
140 |     </div>
141 | </FormControl>
142 | <FormMessage />
143 | </FormItem>
144 | })
145 | />
146 | <FormField
147 |   control={form.control}
148 |   name="confirmPassword"
149 |   render={({ field }) => (
150 |     <FormItem>
151 |       <FormLabel className="mb-1.5 block text-xs font-bold text-slate-600">
152 |         {t("updatePassword.confirmPasswordLabel")}
153 |       </FormLabel>
154 |       <FormControl>
155 |         <div className="relative">
156 |           <input
157 |             type={showConfirm ? "text" : "password"}
158 |             autoComplete="new-password"
159 |             className="fld pe-12"
160 |             placeholder={t(
161 |               "updatePassword.confirmPlaceholder",
162 |               "Re-enter your password"
163 |             )}
164 |             {...field}
165 |           />
166 |           <button
167 |             type="button"
168 |             onClick={() =>
169 |               toggleField("confirm-password", showConfirm)
170 |             }
171 |             className="absolute end-3 top-1/2 -translate-y-1/2 text-xs font-bold text-gray-400 hov
172 |           >
173 |             {showConfirm ? t("password.hide") : t("password.show")}
174 |           </button>
175 |         </div>
176 |       </FormControl>
177 |       <FormMessage />
178 |     </FormItem>
179 |   )}
180 | />
181 | <Button
182 |   type="submit"
183 |   variant="tactile"
184 |   disabled={isPending}
185 |   className="h-12 w-full"
186 | >
187 |   {isPending && <Loader2 className="h-4 w-4 animate-spin" />}
188 |   {t("updatePassword.submitButton")}
189 | </Button>
190 | </form>
191 | </Form>
192 | )}
193 | </AuthShell>
194 | );
195 | };
196 |
197 | export default UpdatePasswordPage;
198 |

```

FILE: src/providers/__tests__/AuthProvider.test.tsx

TYPE: .tsx | LINES: 1-737 | SHA256: e8871721494a32ac218c8c31d3b00e5133b4f9dd31acf55238d3f50515f6635e

```

1 | import { describe, it, expect, vi, beforeEach } from "vitest";
2 | import { renderHook, act, waitFor } from "@testing-library/react";
3 | import React from "react";
4 | import {
5 |   recordFailedAttempt,
6 |   LOGIN_ATTEMPT_CONFIG,
7 | } from "@lib/loginAttemptTracker";
8 |
9 | // -----
10 | // Mock Supabase client
11 | // -----
12 | const mockGetSession = vi.fn();
13 | const mockSignInWithPassword = vi.fn();
14 | const mockSignOut = vi.fn();
15 | const mockResetPasswordForEmail = vi.fn();
16 | const mockOnAuthStateChange = vi.fn();
17 | const mockFrom = vi.fn();
18 | const mockFunctionsInvoke = vi.fn();
19 |
20 | vi.mock("@lib/supabase", () => ({
21 |   supabase: {
22 |     auth: {
23 |       getSession: (...args: unknown[]) => mockGetSession(...args),
24 |       signInWithPassword: (...args: unknown[]) =>
25 |         mockSignInWithPassword(...args),
26 |       signOut: (...args: unknown[]) => mockSignOut(...args),
27 |       resetPasswordForEmail: (...args: unknown[]) =>
28 |         mockResetPasswordForEmail(...args),
29 |       onAuthStateChange: (...args: unknown[]) => mockOnAuthStateChange(...args),
30 |     },
31 |     from: (...args: unknown[]) => mockFrom(...args),
32 |     functions: {
33 |       invoke: (...args: unknown[]) => mockFunctionsInvoke(...args),
34 |     },
35 |   },
36 | }));
37 |
38 | const mockLogActivity = vi.fn().mockResolvedValue(undefined);
39 | vi.mock("@lib/activityLogger", () => ({
40 |   logActivity: (...args: unknown[]) => mockLogActivity(...args),

```

```

41 | }));
42 |
43 | import { AuthProvider } from "../AuthProvider";
44 | import { useAuth } from "@/hooks/useAuth";
45 | import { writeCachedProfile } from "@/lib/profileCache";
46 | import type { Profile } from "@types/app";
47 |
48 | // -----
49 | // Helpers
50 | // -----
51 | const MOCK_USER = { id: "user-123", email: "admin@test.edu" };
52 |
53 | const MOCK_PROFILE = {
54 |   id: "user-123",
55 |   email: "admin@test.edu",
56 |   full_name: "Test Admin",
57 |   role: "admin" as const,
58 |   institution_id: "inst-1",
59 |   avatar_url: null,
60 |   is_active: true,
61 |   onboarding_completed: false,
62 |   portfolio_public: false,
63 |   theme_preference: "light",
64 |   language_preference: "en",
65 |   email_preferences: null,
66 |   notification_preferences: null,
67 |   created_at: "2024-01-01T00:00:00Z",
68 |   updated_at: "2024-01-01T00:00:00Z",
69 | };
70 |
71 | const mockSelectChain = (data: unknown, error: unknown = null) => ({
72 |   select: vi.fn().mockReturnValue({
73 |     eq: vi.fn().mockReturnValue({
74 |       maybeSingle: vi.fn().mockResolvedValue({ data, error }),
75 |     }),
76 |   }),
77 |   // The student login flow (engagement loop) fire-and-forget upserts a
78 |   // 'habit_logs' row; provide an awaitable upsert that resolves cleanly.
79 |   upsert: vi.fn().mockResolvedValue({ data: null, error: null }),
80 | });
81 |
82 | const setupMocks = (opts?: {
83 |   session?: { user: typeof MOCK_USER } | null;
84 |   profile?: typeof MOCK_PROFILE | null;
85 |   profileError?: { message: string } | null;
86 | }) => {
87 |   const session = opts?.session ?? null;
88 |   const profile = opts?.profile ?? null;
89 |   const profileError = opts?.profileError ?? null;
90 |
91 |   // getSession resolves with the provided session. `AuthProvider` no longer
92 |   // calls this directly (see the fix for the double profile-fetch bug), but
93 |   // some tests still assert against it, so the mock stays available.
94 |   mockGetSession.mockResolvedValue({
95 |     data: { session: session ? { user: session.user } : null },
96 |   });
97 |
98 |   // onAuthStateChange: real supabase-js ALWAYS emits `INITIAL_SESSION`
99 |   // immediately upon registration ( `GoTrueClient._emitInitialSession` ), which
100 |   // is how `AuthProvider` now restores a persisted session. That emission is
101 |   // itself async ( `await this.initializePromise` / `await this
102 |   // .acquireLock(...)` in the real client ), so mirror it here via a
103 |   // microtask rather than a synchronous call – a synchronous call would let
104 |   // the null-session branch of `syncSession` resolve `isLoading` before the
105 |   // test's "starts in loading" assertion ever runs, which real supabase-js
106 |   // would never do.
107 |   mockOnAuthStateChange.mockImplementation(
108 |     (cb: (event: string, session: unknown) => void) => {
109 |       queueMicrotask(() => {
110 |         cb("INITIAL_SESSION", session ? { user: session.user } : null);
111 |       });
112 |       return { data: { subscription: { unsubscribe: vi.fn() } } };
113 |     }
114 |   );
115 |
116 |   // profiles query chain
117 |   mockFrom.mockReturnValue(mockSelectChain(profile, profileError));
118 |
119 |   // signOut
120 |   mockSignOut.mockResolvedValue({ error: null });
121 |
122 |   // resetPasswordForEmail
123 |   mockResetPasswordForEmail.mockResolvedValue({ error: null });
124 |
125 |   // Edge function calls (server-side rate limiting) – default: not locked
126 |   mockFunctionsInvoke.mockResolvedValue({
127 |     data: {
128 |       locked: false,
129 |       remaining_seconds: 0,
130 |       cleared: true,
131 |       attempt_count: 0,
132 |     },
133 |     error: null,
134 |   });
135 | };
136 |
137 | const wrapper = ({ children }: { children: React.ReactNode }) => (
138 |   <AuthProvider>{children}</AuthProvider>
139 | );
140 |
141 | // -----
142 | // Tests
143 | // -----
144 | describe("AuthProvider", () => {

```

```

145 | beforeEach(() => {
146 |     vi.clearAllMocks();
147 |     localStorage.clear();
148 | });
149 |
150 | it("starts in loading state and resolves to unauthenticated when no session", async () => {
151 |     setupMocks({ session: null });
152 |
153 |     const { result } = renderHook(() => useAuth(), { wrapper });
154 |
155 |     // Initially loading
156 |     expect(result.current.isLoading).toBe(true);
157 |
158 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
159 |
160 |     expect(result.current.user).toBeNull();
161 |     expect(result.current.profile).toBeNull();
162 |     expect(result.current.role).toBeNull();
163 |     expect(result.current.institutionId).toBeNull();
164 | });
165 |
166 | it("loads existing session and fetches profile on mount", async () => {
167 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
168 |
169 |     const { result } = renderHook(() => useAuth(), { wrapper });
170 |
171 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
172 |
173 |     expect(result.current.user?.id).toBe("user-123");
174 |     expect(result.current.profile?.full_name).toBe("Test Admin");
175 |     expect(result.current.role).toBe("admin");
176 |     expect(result.current.institutionId).toBe("inst-1");
177 | });
178 |
179 | it("signIn returns success with redirect path on valid credentials", async () => {
180 |     setupMocks({ session: null });
181 |
182 |     mockSignInWithPassword.mockResolvedValue({
183 |         data: { user: MOCK_USER, session: { user: MOCK_USER } },
184 |         error: null,
185 |     });
186 |     // After sign-in, profile fetch
187 |     mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE));
188 |
189 |     const { result } = renderHook(() => useAuth(), { wrapper });
190 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
191 |
192 |     let authResult: unknown;
193 |     await act(async () => {
194 |         authResult = await result.current.signIn("admin@test.edu", "password123");
195 |     });
196 |
197 |     expect(authResult).toEqual({
198 |         success: true,
199 |         redirectTo: "/admin",
200 |     });
201 |     expect(result.current.user?.id).toBe("user-123");
202 |     expect(result.current.role).toBe("admin");
203 | });
204 |
205 | it("signIn returns error on invalid credentials", async () => {
206 |     setupMocks({ session: null });
207 |
208 |     mockSignInWithPassword.mockResolvedValue({
209 |         data: { user: null, session: null },
210 |         error: { message: "Invalid login credentials" },
211 |     });
212 |
213 |     const { result } = renderHook(() => useAuth(), { wrapper });
214 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
215 |
216 |     let authResult: unknown;
217 |     await act(async () => {
218 |         authResult = await result.current.signIn("bad@test.edu", "wrong");
219 |     });
220 |
221 |     // Generic message – must not reveal whether email or password was wrong (Req 1.3)
222 |     expect(authResult).toEqual({
223 |         success: false,
224 |         error: "Invalid email or password.",
225 |     });
226 |     expect(result.current.user).toBeNull();
227 | });
228 |
229 | it("signOut clears user and profile", async () => {
230 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
231 |
232 |     const { result } = renderHook(() => useAuth(), { wrapper });
233 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
234 |     expect(result.current.user).not.toBeNull();
235 |
236 |     await act(async () => {
237 |         await result.current.signOut();
238 |     });
239 |
240 |     expect(result.current.user).toBeNull();
241 |     expect(result.current.profile).toBeNull();
242 |     expect(result.current.role).toBeNull();
243 |     expect(mockSignOut).toHaveBeenCalledOnce();
244 | });
245 |
246 | it("resetPassword calls supabase resetPasswordForEmail", async () => {
247 |     setupMocks({ session: null });
248 |

```

```

249 |     const { result } = renderHook(() => useAuth(), { wrapper });
250 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
251 |
252 |     await act(async () => {
253 |       await result.current.resetPassword("user@test.edu");
254 |     });
255 |
256 |     expect(mockResetPasswordForEmail).toHaveBeenCalledWith("user@test.edu");
257 |   });
258 |
259 |   it("resetPassword throws when supabase returns an error", async () => {
260 |     setupMocks({ session: null });
261 |     mockResetPasswordForEmail.mockResolvedValue({
262 |       error: { message: "Rate limit exceeded" },
263 |     });
264 |
265 |     const { result } = renderHook(() => useAuth(), { wrapper });
266 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
267 |
268 |     await expect(
269 |       act(async () => {
270 |         await result.current.resetPassword("user@test.edu");
271 |       })
272 |     ).rejects.toEqual({ message: "Rate limit exceeded" });
273 |   });
274 |
275 |   it("handles profile fetch failure gracefully (profile is null)", async () => {
276 |     setupMocks({
277 |       session: { user: MOCK_USER },
278 |       profile: null,
279 |       profileError: { message: 'relation "profiles" does not exist' },
280 |     });
281 |
282 |     const { result } = renderHook(() => useAuth(), { wrapper });
283 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
284 |
285 |     expect(result.current.user?.id).toBe("user-123");
286 |     expect(result.current.profile).toBeNull();
287 |     expect(result.current.role).toBeNull();
288 |   });
289 |
290 |   it("useAuth throws when used outside AuthProvider", () => {
291 |     // Suppress console.error for the expected error
292 |     const spy = vi.spyOn(console, "error").mockImplementation(() => {});
293 |
294 |     expect(() => {
295 |       renderHook(() => useAuth());
296 |     }).toThrow("useAuth must be used within an AuthProvider");
297 |
298 |     spy.mockRestore();
299 |   });
300 |
301 |   it("subscribes to auth state changes on mount", async () => {
302 |     setupMocks({ session: null });
303 |
304 |     renderHook(() => useAuth(), { wrapper });
305 |
306 |     await waitFor(() => {
307 |       expect(mockOnAuthStateChange).toHaveBeenCalledOnce();
308 |     });
309 |   });
310 |
311 |   // -----
312 |   // Session persistence & auto-refresh (Req 4)
313 |   // -----
314 |
315 |   it("restores session from persisted storage on mount (Req 4.1)", async () => {
316 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
317 |
318 |     const { result } = renderHook(() => useAuth(), { wrapper });
319 |
320 |     // A persisted session is restored via onAuthStateChange's INITIAL_SESSION
321 |     // event (real supabase-js emits this on registration – no separate
322 |     // getSession() call; see the fix for the double profile-fetch bug) and
323 |     // exactly ONE 'profiles' fetch happens for it (mockFrom called once).
324 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
325 |
326 |     expect(mockFrom).toHaveBeenCalledTimes(1);
327 |     expect(result.current.user?.id).toBe("user-123");
328 |     expect(result.current.role).toBe("admin");
329 |   });
330 |
331 |   it("fetches the profile exactly once on cold load (no duplicate INITIAL_SESSION fetch)", async () => {
332 |     // Regression test: AuthProvider previously called BOTH getSession() AND
333 |     // relied on onAuthStateChange's auto-fired INITIAL_SESSION, each
334 |     // independently triggering fetchProfile – two concurrent 'profiles'
335 |     // SELECTs for the same user on every cold load (confirmed in production
336 |     // HAR captures). Only the INITIAL_SESSION path should remain.
337 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
338 |
339 |     const { result } = renderHook(() => useAuth(), { wrapper });
340 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
341 |
342 |     expect(mockGetSession).not.toHaveBeenCalled();
343 |     expect(mockFrom).toHaveBeenCalledTimes(1);
344 |   });
345 |
346 |   it("handles TOKEN_REFRESHED event by re-syncing session (Req 4.2)", async () => {
347 |     let authChangeCallback: ((event: string, session: unknown) => void) | null =
348 |       null;
349 |
350 |     setupMocks({ session: null });
351 |     mockOnAuthStateChange.mockImplementation(
352 |       (cb: (event: string, session: unknown) => void) => {

```

```

353     authChangeCallback = cb;
354     // Real supabase-js always emits INITIAL_SESSION on registration -
355     // fire it (with no session, matching this test's starting state) so
356     // `isLoading` resolves before the test simulates TOKEN_REFRESHED.
357     queueMicrotask(() => cb("INITIAL_SESSION", null));
358     return { data: { subscription: { unsubscribe: vi.fn() } } };
359   }
360 );
361
362 const { result } = renderHook(() => useAuth(), { wrapper });
363 await waitFor(() => expect(result.current.isLoading).toBe(false));
364
365 expect(result.current.user).toBeNull();
366
367 // Simulate a TOKEN_REFRESHED event with a valid session
368 mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE));
369
370 await act(async () => {
371   authChangeCallback?.("TOKEN_REFRESHED", { user: MOCK_USER });
372 });
373
374 await waitFor(() => expect(result.current.user?.id).toBe("user-123"));
375 expect(result.current.role).toBe("admin");
376 });
377
378 it("skips the profile re-fetch on TOKEN_REFRESHED for the same user (Req 8.1)", async () => {
379   let authChangeCallback: ((event: string, session: unknown) => void) | null =
380     null;
381
382   setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
383   mockOnAuthStateChange.mockImplementation(
384     (cb: (event: string, session: unknown) => void) => {
385       authChangeCallback = cb;
386       // Real supabase-js always emits INITIAL_SESSION on registration -
387       // fire it with the starting session so the initial mount resolves.
388       queueMicrotask(() => cb("INITIAL_SESSION", { user: MOCK_USER }));
389       return { data: { subscription: { unsubscribe: vi.fn() } } };
390     }
391   );
392
393   const { result } = renderHook(() => useAuth(), { wrapper });
394   await waitFor(() => expect(result.current.isLoading).toBe(false));
395   expect(result.current.user?.id).toBe("user-123");
396
397   // The initial mount fetched the profile once. Clear the `from` spy, then
398   // refresh the token for the SAME user - no second profiles SELECT should
399   // fire (Req 8.1), but the user/role state stays intact.
400   mockFrom.mockClear();
401
402   await act(async () => {
403     authChangeCallback?.("TOKEN_REFRESHED", { user: MOCK_USER });
404   });
405
406   expect(mockFrom).not.toHaveBeenCalled();
407   expect(result.current.user?.id).toBe("user-123");
408   expect(result.current.role).toBe("admin");
409 });
410
411 it("clears state on SIGNED_OUT event (session expiry)", async () => {
412   let authChangeCallback: ((event: string, session: unknown) => void) | null =
413     null;
414
415   setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
416   mockOnAuthStateChange.mockImplementation(
417     (cb: (event: string, session: unknown) => void) => {
418       authChangeCallback = cb;
419       // Real supabase-js always emits INITIAL_SESSION on registration -
420       // fire it with the starting session so the initial mount resolves.
421       queueMicrotask(() => cb("INITIAL_SESSION", { user: MOCK_USER }));
422       return { data: { subscription: { unsubscribe: vi.fn() } } };
423     }
424   );
425
426   const { result } = renderHook(() => useAuth(), { wrapper });
427   await waitFor(() => expect(result.current.isLoading).toBe(false));
428   expect(result.current.user?.id).toBe("user-123");
429
430   // Simulate SIGNED_OUT (e.g., session expired)
431   await act(async () => {
432     authChangeCallback?.("SIGNED_OUT", null);
433   });
434
435   expect(result.current.user).toBeNull();
436   expect(result.current.profile).toBeNull();
437   expect(result.current.role).toBeNull();
438 });
439
440 it("handles SIGNED_IN event from onAuthStateChange", async () => {
441   let authChangeCallback: ((event: string, session: unknown) => void) | null =
442     null;
443
444   setupMocks({ session: null });
445   mockOnAuthStateChange.mockImplementation(
446     (cb: (event: string, session: unknown) => void) => {
447       authChangeCallback = cb;
448       // Real supabase-js always emits INITIAL_SESSION on registration -
449       // fire it (with no session, matching this test's starting state) so
450       // `isLoading` resolves before the test simulates SIGNED_IN.
451       queueMicrotask(() => cb("INITIAL_SESSION", null));
452       return { data: { subscription: { unsubscribe: vi.fn() } } };
453     }
454   );
455
456   const { result } = renderHook(() => useAuth(), { wrapper });

```

```

457 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
458 |
459 |     // Simulate SIGNED_IN event
460 |     mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE));
461 |
462 |     await act(async () => {
463 |       authChangeCallback?.("SIGNED_IN", { user: MOCK_USER });
464 |     });
465 |
466 |     await waitFor(() => expect(result.current.user?.id).toBe("user-123"));
467 |     expect(result.current.profile?.full_name).toBe("Test Admin");
468 |   });
469 |
470 |   it("redirectTo maps correctly for each role", async () => {
471 |     const roles = [
472 |       "admin",
473 |       "coordinator",
474 |       "teacher",
475 |       "student",
476 |       "parent",
477 |     ] as const;
478 |     const expectedPaths = [
479 |       "/admin",
480 |       "/coordinator",
481 |       "/teacher",
482 |       "/student",
483 |       "/parent",
484 |     ];
485 |
486 |     for (let i = 0; i < roles.length; i++) {
487 |       vi.clearAllMocks();
488 |       localStorage.clear();
489 |       const roleProfile = { ...MOCK_PROFILE, role: roles[i] };
490 |
491 |       setupMocks({ session: null });
492 |       mockSignInWithPassword.mockResolvedValue({
493 |         data: { user: MOCK_USER, session: { user: MOCK_USER } },
494 |         error: null,
495 |       });
496 |       mockFrom.mockReturnValue(mockSelectChain(roleProfile));
497 |
498 |       const { result } = renderHook(() => useAuth(), { wrapper });
499 |       await waitFor(() => expect(result.current.isLoading).toBe(false));
500 |
501 |       let authResult: { redirectTo?: string } | undefined;
502 |       await act(async () => {
503 |         authResult = await result.current.signIn("user@test.edu", "pass12345");
504 |       });
505 |
506 |       expect(authResult?.redirectTo).toBe(expectedPaths[i]);
507 |     }
508 |   });
509 |
510 |   // -----
511 |   // Activity logging on login (Req 41.1)
512 |   // -----
513 |
514 |   it("logs login activity for student role on successful sign-in", async () => {
515 |     const studentProfile = { ...MOCK_PROFILE, role: "student" as const };
516 |     setupMocks({ session: null });
517 |
518 |     mockSignInWithPassword.mockResolvedValue({
519 |       data: { user: MOCK_USER, session: { user: MOCK_USER } },
520 |       error: null,
521 |     });
522 |     mockFrom.mockReturnValue(mockSelectChain(studentProfile));
523 |
524 |     const { result } = renderHook(() => useAuth(), { wrapper });
525 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
526 |
527 |     await act(async () => {
528 |       await result.current.signIn("student@test.edu", "password123");
529 |     });
530 |
531 |     expect(mockLogActivity).toHaveBeenCalledWith({
532 |       student_id: "user-123",
533 |       event_type: "login",
534 |     });
535 |   });
536 |
537 |   it("does not log login activity for non-student roles", async () => {
538 |     setupMocks({ session: null });
539 |
540 |     mockSignInWithPassword.mockResolvedValue({
541 |       data: { user: MOCK_USER, session: { user: MOCK_USER } },
542 |       error: null,
543 |     });
544 |     mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE)); // admin role
545 |
546 |     const { result } = renderHook(() => useAuth(), { wrapper });
547 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
548 |
549 |     await act(async () => {
550 |       await result.current.signIn("admin@test.edu", "password123");
551 |     });
552 |
553 |     expect(mockLogActivity).not.toHaveBeenCalled();
554 |   });
555 |
556 |   // -----
557 |   // Login attempt tracking & lockout (Req 1.2, 1.3)
558 |   // -----
559 |
560 |   it("returns generic error message on failed login (does not reveal email/password)", async () => {

```



```

561 |     setupMocks({ session: null });
562 |     mockSignInWithPassword.mockResolvedValue({
563 |       data: { user: null, session: null },
564 |       error: { message: "Invalid login credentials" },
565 |     });
566 |
567 |     const { result } = renderHook(() => useAuth(), { wrapper });
568 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
569 |
570 |     let authResult: { success: boolean; error?: string } | undefined;
571 |     await act(async () => {
572 |       authResult = await result.current.signIn("bad@test.edu", "wrong");
573 |     });
574 |
575 |     expect(authResult?.success).toBe(false);
576 |     expect(authResult?.error).toBe("Invalid email or password.");
577 |   });
578 |
579 |   it("locks account after 5 consecutive failed attempts", async () => {
580 |     setupMocks({ session: null });
581 |     mockSignInWithPassword.mockResolvedValue({
582 |       data: { user: null, session: null },
583 |       error: { message: "Invalid login credentials" },
584 |     });
585 |
586 |     const { result } = renderHook(() => useAuth(), { wrapper });
587 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
588 |
589 |     // Fail 5 times
590 |     for (let i = 0; i < LOGIN_ATTEMPT_CONFIG.MAX_ATTEMPTS; i++) {
591 |       await act(async () => {
592 |         await result.current.signIn("locked@test.edu", "wrong");
593 |       });
594 |     }
595 |
596 |     // 6th attempt should be blocked without calling Supabase
597 |     mockSignInWithPassword.mockClear();
598 |     let authResult: { success: boolean; error?: string } | undefined;
599 |     await act(async () => {
600 |       authResult = await result.current.signIn("locked@test.edu", "wrong");
601 |     });
602 |
603 |     expect(authResult?.success).toBe(false);
604 |     expect(authResult?.error).toContain("temporarily locked");
605 |     expect(mockSignInWithPassword).not.toHaveBeenCalled();
606 |   });
607 |
608 |   it("clears attempts on successful login", async () => {
609 |     setupMocks({ session: null });
610 |
611 |     // Record some failed attempts first
612 |     recordFailedAttempt("success@test.edu");
613 |     recordFailedAttempt("success@test.edu");
614 |
615 |     mockSignInWithPassword.mockResolvedValue({
616 |       data: { user: MOCK_USER, session: { user: MOCK_USER } },
617 |       error: null,
618 |     });
619 |     mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE));
620 |
621 |     const { result } = renderHook(() => useAuth(), { wrapper });
622 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
623 |
624 |     await act(async () => {
625 |       await result.current.signIn("success@test.edu", "correct");
626 |     });
627 |
628 |     // Attempts should be cleared – localStorage key removed
629 |     expect(localStorage.getItem("login_attempts_success@test.edu")).toBeNull();
630 |   });
631 |
632 |   it("shows lockout message on the 5th failed attempt itself", async () => {
633 |     setupMocks({ session: null });
634 |     mockSignInWithPassword.mockResolvedValue({
635 |       data: { user: null, session: null },
636 |       error: { message: "Invalid login credentials" },
637 |     });
638 |
639 |     // Pre-record 4 failures
640 |     for (let i = 0; i < LOGIN_ATTEMPT_CONFIG.MAX_ATTEMPTS - 1; i++) {
641 |       recordFailedAttempt("edge@test.edu");
642 |     }
643 |
644 |     const { result } = renderHook(() => useAuth(), { wrapper });
645 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
646 |
647 |     // The 5th attempt triggers lockout
648 |     let authResult: { success: boolean; error?: string } | undefined;
649 |     await act(async () => {
650 |       authResult = await result.current.signIn("edge@test.edu", "wrong");
651 |     });
652 |
653 |     expect(authResult?.success).toBe(false);
654 |     expect(authResult?.error).toContain("too many failed attempts");
655 |   });
656 |
657 |   // -----
658 |   // Shell-first profile cache (Option J, Phase 0)
659 |   // -----
660 |
661 |   it("hydrates the profile from cache with no network fetch when fresh (shell-first)", async () => {
662 |     // A fresh cached profile for this user exists BEFORE mount.
663 |     writeCachedProfile(MOCK_USER.id, MOCK_PROFILE as unknown as Profile);
664 |

```

```

665 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
666 |
667 |     const { result } = renderHook(() => useAuth(), { wrapper });
668 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
669 |
670 |     // Profile came from cache; the fresh window means NO profiles SELECT ran.
671 |     expect(result.current.profile?.full_name).toBe("Test Admin");
672 |     expect(result.current.role).toBe("admin");
673 |     expect(mockFrom).not.toHaveBeenCalled();
674 |   });
675 |
676 |   it("never hydrates a cached profile belonging to a different user (cross-user no-leak)", async () => {
677 |     // User A's profile is cached on this device...
678 |     writeCachedProfile("user-AAA", {
679 |       ...(MOCK_PROFILE as unknown as Profile),
680 |       id: "user-AAA",
681 |       full_name: "Alice Student",
682 |       role: "student",
683 |     });
684 |
685 |     // ...but user B (MOCK_USER / admin) is the one with a session now.
686 |     setupMocks({ session: { user: MOCK_USER }, profile: MOCK_PROFILE });
687 |
688 |     const { result } = renderHook(() => useAuth(), { wrapper });
689 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
690 |
691 |     // B must see ONLY B's freshly-fetched profile - A's cache is discarded.
692 |     expect(mockFrom).toHaveBeenCalledTimes(1);
693 |     expect(result.current.profile?.full_name).toBe("Test Admin");
694 |     expect(result.current.role).toBe("admin");
695 |     expect(result.current.profile?.full_name).not.toBe("Alice Student");
696 |   });
697 |
698 |   it("fetches the profile only once on interactive login (no SIGNED_IN double-fetch)", async () => {
699 |     let authChangeCallback: ((event: string, session: unknown) => void) | null =
700 |       null;
701 |
702 |     setupMocks({ session: null });
703 |     mockOnAuthStateChange.mockImplementation(
704 |       (cb: (event: string, session: unknown) => void) => {
705 |         authChangeCallback = cb;
706 |         queueMicrotask(() => cb("INITIAL_SESSION", null));
707 |         return { data: { subscription: { unsubscribe: vi.fn() } } };
708 |       }
709 |     );
710 |
711 |     mockSignInWithPassword.mockResolvedValue({
712 |       data: { user: MOCK_USER, session: { user: MOCK_USER } },
713 |       error: null,
714 |     });
715 |     mockFrom.mockReturnValue(mockSelectChain(MOCK_PROFILE));
716 |
717 |     const { result } = renderHook(() => useAuth(), { wrapper });
718 |     await waitFor(() => expect(result.current.isLoading).toBe(false));
719 |
720 |     await act(async () => {
721 |       await result.current.signIn("admin@test.edu", "password123");
722 |     });
723 |
724 |     // signIn performed exactly one profiles SELECT and seeded the cache.
725 |     expect(mockFrom).toHaveBeenCalledTimes(1);
726 |
727 |     // supabase-js then emits SIGNED_IN - it must hydrate from the fresh cache,
728 |     // NOT trigger a second profiles SELECT.
729 |     await act(async () => {
730 |       authChangeCallback?.("SIGNED_IN", { user: MOCK_USER });
731 |     });
732 |
733 |     expect(mockFrom).toHaveBeenCalledTimes(1);
734 |     expect(result.current.profile?.full_name).toBe("Test Admin");
735 |   });
736 | });
737 |

```

FILE: src/providers/AuthProvider.tsx

TYPE: .tsx | LINES: 1-606 | SHA256: 333e9a6b49eea6798a50819c167e21a5bff259cdbad9769dc956c6182d5c87fe

```

1 | import {
2 |   createContext,
3 |   useCallback,
4 |   useEffect,
5 |   useMemo,
6 |   useRef,
7 |   useState,
8 | } from "react";
9 | import type { User, Session } from "@supabase/supabase-js";
10 | import { supabase } from "@lib/supabase";
11 | import type { AuthResult, Profile, UserRole } from "@types/app";
12 | import {
13 |   isLocked,
14 |   getRemainingLockTime,
15 |   recordFailedAttempt,
16 |   clearAttempts,
17 |   checkServerRateLimit,
18 |   recordServerFailedAttempt,
19 |   clearServerAttempts,
20 | } from "@lib/loginAttemptTracker";
21 | import { logActivity } from "@lib/activityLogger";
22 | import { awardPerfectDayIfComplete } from "@lib/perfectDay";
23 | import {
24 |   loadAccessibilityPreferences,
25 |   applyAccessibilityPreferences,
26 | } from "@lib/accessibilityPreferences";
27 | import i18n from "@lib/i18n";

```

```

28 | import {
29 |   readCachedProfile,
30 |   writeCachedProfile,
31 |   clearCachedProfile,
32 |   isProfileFresh,
33 | } from "@lib/profileCache";
34 | import { clearCachedDashboard } from "@lib/dashboardCache";
35 |
36 | // -----
37 | // Role !' dashboard path mapping
38 | // -----
39 | const ROLE_DASHBOARD_MAP: Record<UserRole, string> = {
40 |   admin: "/admin",
41 |   coordinator: "/coordinator",
42 |   teacher: "/teacher",
43 |   student: "/student",
44 |   parent: "/parent",
45 | };
46 |
47 | // -----
48 | // Hydrate the user's language preference into i18n (fire-and-forget). Kept at
49 | // module scope so both the cache-hydration and network-revalidation paths in
50 | // syncSession can reuse it without adding hook dependencies.
51 | // -----
52 | const applyProfileLanguage = (profile: Profile | null): void => {
53 |   if (profile?.language_preference) {
54 |     i18n.changeLanguage(profile.language_preference).catch(() => {
55 |       // Never block session hydration on i18n.
56 |     });
57 |   }
58 | };
59 |
60 | export interface SignUpOptions {
61 |   email: string;
62 |   password: string;
63 |   fullName: string;
64 |   username?: string;
65 |   institutionId?: string;
66 |   requestedRole?: UserRole;
67 | }
68 |
69 | export interface SignUpResult {
70 |   success: boolean;
71 |   error?: string;
72 |   requiresVerification?: boolean;
73 |   redirectTo?: string;
74 | }
75 |
76 | // -----
77 | // Context value interface (matches design.md AuthContextValue)
78 | // -----
79 | export interface AuthContextValue {
80 |   user: User | null;
81 |   profile: Profile | null;
82 |   role: UserRole | null;
83 |   institutionId: string | null;
84 |   isLoading: boolean;
85 |   signIn: (email: string, password: string) => Promise<AuthResult>;
86 |   signUp: (options: SignUpOptions) => Promise<SignUpResult>;
87 |   signOut: () => Promise<void>;
88 |   resetPassword: (email: string) => Promise<void>;
89 |   /** Re-fetch the profile from the database and update the cached state. */
90 |   refetchProfile: () => Promise<void>;
91 | }
92 |
93 | // eslint-disable-next-line react-refresh/only-export-components
94 | export const AuthContext = createContext<AuthContextValue | undefined>(
95 |   undefined
96 | );
97 |
98 | // -----
99 | // Provider
100 | // -----
101 | export const AuthProvider = ({ children }: { children: React.ReactNode }) => {
102 |   const [user, setUser] = useState<User | null>(null);
103 |   const [profile, setProfile] = useState<Profile | null>(null);
104 |   const [isLoading, setIsLoading] = useState(true);
105 |
106 |   // `INITIAL_SESSION` is normally emitted as soon as the listener subscribes.
107 |   // A direct route load must still settle when that event is delayed or missed,
108 |   // otherwise RouteGuard can remain on its spinner indefinitely.
109 |   const initialSessionResolved = useRef(false);
110 |   // Tracks the currently-synced user id so a TOKEN_REFRESHED for the SAME user
111 |   // can skip the redundant profile SELECT (spec: dashboard-and-ux-performance,
112 |   // Req 8.1). A token rotation does not change the profile, so re-fetching it on
113 |   // every refresh is a pure round-trip cost.
114 |   const currentUserIdRef = useRef<string | null>(null);
115 |
116 |   // -----
117 |   // Fetch profile from `profiles` table
118 |   // -----
119 |   const fetchProfile = useCallback(
120 |     async (userId: string): Promise<Profile | null> => {
121 |       const { data, error } = await supabase
122 |         .from("profiles")
123 |         .select(
124 |           "id, email, full_name, role, institution_id, avatar_url, is_active, onboarding_completed, portfolio_
125 |         )
126 |         .eq("id", userId)
127 |         .maybeSingle();
128 |
129 |       if (error) {
130 |         console.error("Failed to fetch profile:", error.message);
131 |         return null;

```

```

132     }
133     return data as Profile | null;
134   },
135   []
136 );
137
138 // -----
139 // Sync local state from a session
140 // -----
141 const syncSession = useCallback(
142   async (session: Session | null) => {
143     if (!session?.user) {
144       currentUserRef.current = null;
145       // No authenticated session – drop any cached profile/dashboard so it
146       // can never be hydrated for an unauthenticated (or subsequent) user.
147       clearCachedProfile();
148       clearCachedDashboard();
149       setUser(null);
150       setProfile(null);
151       setIsLoading(false);
152       return;
153     }
154
155     const uid = session.user.id;
156     currentUserRef.current = uid;
157     setUser(session.user);
158
159     // Shell-first hydration: if a cached profile exists for THIS user, apply
160     // it immediately so RouteGuard can resolve the role and the app shell
161     // paints without waiting on the network. The cache is non-authoritative
162     // UI hydration only – RLS remains the source of truth server-side – and
163     // it is identity-guarded so one user can never hydrate another's data.
164     const cached = readCachedProfile(uid);
165     if (cached) {
166       setProfile(cached.profile);
167       applyProfileLanguage(cached.profile);
168       setIsLoading(false);
169
170       // Freshly cached (e.g. the profiles SELECT that signIn just ran) – skip
171       // the redundant refetch entirely. This collapses the interactive-login
172       // double fetch (signIn fetch + SIGNED_IN event).
173       if (isProfileFresh(cached.cachedAt)) return;
174
175       // Stale cache – revalidate in the background without blocking paint.
176       void (async () => {
177         const fresh = await fetchProfile(uid);
178         // Ignore if the user changed while this was in flight.
179         if (currentUserRef.current !== uid) return;
180         if (fresh) {
181           setProfile(fresh);
182           writeCachedProfile(uid, fresh);
183           applyProfileLanguage(fresh);
184         }
185       })();
186       return;
187     }
188
189     // Cache miss (first load on this device): fetch before revealing the
190     // route so the guard resolves the correct role on the very first paint.
191     const userProfile = await fetchProfile(uid);
192     if (currentUserRef.current !== uid) return;
193     setProfile(userProfile);
194     if (userProfile) writeCachedProfile(uid, userProfile);
195     applyProfileLanguage(userProfile);
196     setIsLoading(false);
197   }, [fetchProfile]
198 );
199
200 // -----
201 // Bootstrap: restore persisted session + subscribe to auth changes
202 // -----
203
204 useEffect(() => {
205   // Apply accessibility preferences from localStorage on startup
206   applyAccessibilityPreferences(loadAccessibilityPreferences());
207 }, []);
208
209 useEffect(() => {
210   let mounted = true;
211   const resolveInitialSession = (session: Session | null) => {
212     if (initialSessionResolved.current) return;
213     initialSessionResolved.current = true;
214     void syncSession(session);
215   };
216
217   const {
218     data: { subscription },
219   } = supabase.auth.onAuthStateChange((event, session) => {
220     switch (event) {
221       case "SIGNED_OUT":
222         // Explicitly clear state on sign-out (session expiry or manual). Also
223         // drop the cached profile + dashboard so the next user on this device
224         // can never hydrate the previous user's data (cross-user no-leak).
225         clearCachedProfile();
226         clearCachedDashboard();
227         currentUserRef.current = null;
228         setUser(null);
229         setProfile(null);
230         setIsLoading(false);
231         break;
232
233       case "TOKEN_REFRESHED":
234         // Req 8.1: a token rotation for the SAME user does not change the
235         // profile, so skip the redundant profile SELECT – just adopt the

```

```

236 |         // refreshed session user. Falls through to a full sync only when the
237 |         // user id actually changed (or no profile was synced yet).
238 |         if (session?.user && session.user.id === currentUserIdRef.current) {
239 |             setUser(session.user);
240 |             setIsLoading(false);
241 |             break;
242 |         }
243 |         syncSession(session);
244 |         break;
245 |
246 |     case "SIGNED_IN":
247 |         // A fresh interactive sign-in should always hydrate immediately.
248 |         syncSession(session);
249 |         break;
250 |
251 |     case "INITIAL_SESSION":
252 |         // The subscription is preferred because it also handles post-redirect
253 |         // sessions. `getSession` below is a guarded fallback for direct loads.
254 |         resolveInitialSession(session);
255 |         break;
256 |
257 |     default:
258 |         // Handle any other events (USER_UPDATED, PASSWORD_RECOVERY, etc.)
259 |         syncSession(session);
260 |         break;
261 | }
262 | });
263 |
264 | // `INITIAL_SESSION` is Supabase's normal, authoritative cold-load path.
265 | // Give it a short head start before falling back to the storage-backed
266 | // read. This preserves the single profile query on a healthy cold load,
267 | // while still releasing RouteGuard if an embedded/Strict-Mode auth client
268 | // delays or misses the initial event.
269 | const fallbackTimer = window.setTimeout(() => {
270 |     if (!mounted || initialSessionResolved.current) return;
271 |     void supabase.auth
272 |       .getSession()
273 |       .then(({ data, error }) => {
274 |         if (!mounted || initialSessionResolved.current) return;
275 |         if (error) {
276 |             setIsLoading(false);
277 |             return;
278 |         }
279 |         resolveInitialSession(data.session);
280 |     })
281 |     .catch(() => {
282 |         if (mounted && !initialSessionResolved.current) {
283 |             initialSessionResolved.current = true;
284 |             setIsLoading(false);
285 |         }
286 |     });
287 | }, 250);
288 |
289 | return () => {
290 |     mounted = false;
291 |     window.clearTimeout(fallbackTimer);
292 |     subscription.unsubscribe();
293 | };
294 | }, [syncSession]);
295 |
296 | // -----
297 | // signIn
298 | // -----
299 | const signIn = useCallback(
300 |   async (email: string, password: string): Promise<AuthResult> => {
301 |     // 1. Client-side lockout check (immediate UX feedback)
302 |     if (isLocked(email)) {
303 |         const remaining = getRemainingLockTime(email);
304 |         const minutes = Math.ceil(remaining / 60);
305 |         return {
306 |             success: false,
307 |             error: `Account is temporarily locked. Please try again in ${minutes} minute${
308 |               minutes === 1 ? "" : "s"
309 |             }`,
310 |         };
311 |     }
312 |
313 |     // 2. Server-side lockout check (tamper-proof enforcement)
314 |     const serverCheck = await checkServerRateLimit(email);
315 |     if (serverCheck.locked) {
316 |         const minutes = Math.ceil(serverCheck.remaining_seconds / 60);
317 |         return {
318 |             success: false,
319 |             error: `Account is temporarily locked. Please try again in ${minutes} minute${
320 |               minutes === 1 ? "" : "s"
321 |             }`,
322 |         };
323 |     }
324 |
325 |     const { data, error } = await supabase.auth.signInWithPassword({
326 |       email,
327 |       password,
328 |     });
329 |
330 |     if (error) {
331 |         // Record on both client and server
332 |         recordFailedAttempt(email);
333 |         const serverResult = await recordServerFailedAttempt(email);
334 |
335 |         // After recording, check if the account just got locked (either side)
336 |         if (isLocked(email) || serverResult.locked) {
337 |             return {
338 |               success: false,
339 |               error:

```

```

340 |         "Account is temporarily locked due to too many failed attempts. Please try again in 15 minutes."
341 |     };
342 | }
343 |
344 | // Generic message – don't reveal whether email or password was wrong (Req 1.3)
345 | return { success: false, error: "Invalid email or password." };
346 | }
347 |
348 | // Successful login – clear attempts on both client and server
349 | clearAttempts(email);
350 | clearServerAttempts(email).catch(() => {
351 |     // Fire-and-forget – don't block successful login
352 | });
353 |
354 | const userProfile = await fetchProfile(data.user.id);
355 | currentUserIdRef.current = data.user.id;
356 | setUser(data.user);
357 | setProfile(userProfile);
358 | // Do not depend on the asynchronous SIGNED_IN subscription callback to
359 | // release RouteGuard. The profile request above has already completed, so
360 | // leaving this true can strand a successful local sign-in on its loading
361 | // spinner when that callback is delayed or coalesced by the auth client.
362 | setIsLoading(false);
363 | // Seed the shell-first cache so the SIGNED_IN event that supabase-js
364 | // emits right after this hydrates from the fresh cache instead of firing
365 | // a second `profiles` SELECT for the same user.
366 | if (userProfile) writeCachedProfile(data.user.id, userProfile);
367 |
368 | const redirectTo = userProfile?.role
369 |   ? ROLE_DASHBOARD_MAP[userProfile.role]
370 |   : "/login";
371 |
372 | // Fire-and-forget: log login activity for students (Req 41.1)
373 | if (userProfile?.role === "student") {
374 |   const studentId = data.user.id;
375 |   logActivity({ student_id: studentId, event_type: "login" }).catch(
376 |     () => {}
377 |   );
378 |
379 |   // S-1 engagement loop (Req 2.9): advance the streak, award +10 login XP,
380 |   // and record the `login` daily habit so the streak/perfect-day pipeline is
381 |   // fed from real activity. Each step is independently guarded so one
382 |   // failure can neither block the login nor the others.
383 |   // (The broken midnight `{type:'midnight_reset'}` cron is left disconnected
384 |   // as a documented no-op; the streak now advances from this per-user login.)
385 |   //
386 |   // SEQUENCED, not concurrent (root-cause fix, 2026-07): these 3 steps used
387 |   // to fire in parallel (`.catch()`) fire-and-forget, no shared chain), each
388 |   // independently reading/writing overlapping tables (`habit_logs`,
389 |   // `student_gamification`, `profiles`) for the SAME student at the SAME
390 |   // instant. Confirmed live in production HAR captures: this concurrent
391 |   // burst is what triggers the `habit_logs` write to exceed the
392 |   // `authenticated` role's 8s `statement_timeout` (57014), after which
393 |   // ~12 unrelated requests in the same window fail with `25P02 current
394 |   // transaction is aborted` for several seconds – a connection-pool-level
395 |   // cascade, not a problem with any single query. None of these 3 steps
396 |   // are on the login critical path (the whole chain stays fire-and-forget
397 |   // – `signIn` already returned above), so running them one-at-a-time
398 |   // costs nothing in perceived speed while cutting this login's peak
399 |   // concurrent DB load to a third of what it was.
400 |   const todayUtc = new Date().toISOString().split("T")[0] as string;
401 |
402 |   void (async () => {
403 |     // 1. Record the login habit FIRST (before the perfect-day check) so
404 |     //    awardPerfectDayIfComplete can observe it when reading today's
405 |     //    habit_logs. Idempotent on (student_id, habit_type, date) – a
406 |     //    second login same day is a no-op.
407 |     try {
408 |       const { error } = await supabase.from("habit_logs").upsert(
409 |         {
410 |           student_id: studentId,
411 |           habit_type: "login",
412 |           date: todayUtc,
413 |           completed_at: new Date().toISOString(),
414 |         },
415 |         { onConflict: "student_id,habit_type,date" }
416 |       );
417 |       if (error) {
418 |         console.error("Failed to record login habit:", error.message);
419 |       } else {
420 |         // Perfect-day check runs after the login habit is recorded.
421 |         // awardPerfectDayIfComplete swallows its own errors.
422 |         await awardPerfectDayIfComplete(studentId);
423 |       }
424 |     } catch {
425 |       // Never let a background engagement step throw into signIn's caller.
426 |     }
427 |
428 |     // 2. process-streak is idempotent same-day (dayDiff === 0 is a no-op)
429 |     //    and authorizes the student's own JWT.
430 |     try {
431 |       await supabase.functions.invoke("process-streak", {
432 |         body: { student_id: studentId },
433 |       });
434 |     } catch {
435 |       // non-fatal
436 |     }
437 |
438 |     // 3. award-xp enforces the canonical 10 XP and a `login:{id}:{date}`
439 |     //    idempotent reference server-side; the client-supplied amount is
440 |     //    advisory.
441 |     try {
442 |       await supabase.functions.invoke("award-xp", {
443 |         body: { student_id: studentId, source: "login", xp_amount: 10 },

```

```

444     });
445     } catch {
446         // non-fatal
447     }
448     })();
449 }
450
451 return { success: true, redirectTo };
452 },
453 [fetchProfile]
454 );
455
456 // -----
457 // signUp – public self-registration
458 //
459 // Creates the auth.users row; the `handle_new_user()` trigger
460 // (migration 20260901000002 + 20260901000006) inserts the matching
461 // public.profiles row with role='student' and validates the optional
462 // institution_id against the institution's join_mode (ADR-13).
463 //
464 // For institutions with join_mode='open' the profile is created with
465 // status='pending_verification' until the email link is clicked (ADR-14);
466 // for domain_restricted / invite_only (student self-signup only) the
467 // profile is created with status='active' immediately.
468 // -----
469 const signUp = useCallback(async (options: SignUpOptions): Promise<SignUpResult> => {
470     const {
471         email,
472         password,
473         fullName,
474         username,
475         institutionId,
476         requestedRole,
477     } = options;
478
479     const metadata: Record<string, unknown> = {
480         full_name: fullName,
481     };
482     if (username) metadata.username = username;
483     if (institutionId) metadata.institution_id = institutionId;
484     // Key MUST match the `raw_user_meta_data` -> `role` read in
485     // public.handle_new_user(). The trigger already forces role='student'
486     // for self-signup without an invitation_id, so sending this is purely
487     // informational for the server-side validator.
488     if (requestedRole) metadata.role = requestedRole;
489
490     const { data, error } = await supabase.auth.signUp({
491         email,
492         password,
493         options: {
494             data: metadata,
495             emailRedirectTo: `${window.location.origin}/login`,
496         },
497     });
498
499     if (error) {
500         return { success: false, error: error.message };
501     }
502
503     // Supabase returns `session=null` when email confirmation is required
504     // (production default). `session` is populated when confirmation is
505     // disabled or an auto-confirm hook ran.
506     const requiresVerification = !data.session;
507
508     if (requiresVerification) {
509         return {
510             success: true,
511             requiresVerification: true,
512         };
513     }
514
515     // Session established – fetch the freshly-created profile and route
516     // to the appropriate dashboard.
517     if (data.user) {
518         const userProfile = await fetchProfile(data.user.id);
519         currentUserIdRef.current = data.user.id;
520         setUser(data.user);
521         setProfile(userProfile);
522         if (userProfile) writeCachedProfile(data.user.id, userProfile);
523
524         const redirectTo = userProfile?.role
525             ? ROLE_DASHBOARD_MAP[userProfile.role]
526             : "/login";
527         return { success: true, redirectTo };
528     }
529
530     return { success: true };
531 },
532 [fetchProfile]
533 );
534
535 // -----
536 // signOut
537 // -----
538 const signOut = useCallback(async () => {
539     await supabase.auth.signOut();
540     clearCachedProfile();
541     clearCachedDashboard();
542     currentUserIdRef.current = null;
543     setUser(null);
544     setProfile(null);
545 }, []);
546
547

```

```

548 | // -----
549 | // resetPassword
550 | // -----
551 | const resetPassword = useCallback(async (email: string) => {
552 |   const { error } = await supabase.auth.resetPasswordForEmail(email);
553 |   if (error) throw error;
554 | }, []);
555 |
556 | // -----
557 | // Derived values
558 | // -----
559 | const role = profile?.role ?? null;
560 | const institutionId = profile?.institution_id ?? null;
561 |
562 | // -----
563 | // refetchProfile – callable by consumers to force-refresh after mutations
564 | // that change fields the AuthProvider holds (e.g. onboarding_completed).
565 | // -----
566 | const refetchProfile = useCallback(async () => {
567 |   const uid = currentUserRef.current;
568 |   if (!uid) return;
569 |   const fresh = await fetchProfile(uid);
570 |   if (currentUserRef.current !== uid) return; // user changed mid-flight
571 |   if (fresh) {
572 |     setProfile(fresh);
573 |     writeCachedProfile(uid, fresh);
574 |   }
575 | }, [fetchProfile]);
576 |
577 | const value = useMemo<AuthContextValue>(
578 |   () => ({
579 |     user,
580 |     profile,
581 |     role,
582 |     institutionId,
583 |     isLoading,
584 |     signIn,
585 |     signUp,
586 |     signOut,
587 |     resetPassword,
588 |     refetchProfile,
589 |   }),
590 |   [
591 |     user,
592 |     profile,
593 |     role,
594 |     institutionId,
595 |     isLoading,
596 |     signIn,
597 |     signUp,
598 |     signOut,
599 |     resetPassword,
600 |     refetchProfile,
601 |   ]
602 | );
603 |
604 | return <AuthContext.Provider value={value}>{children}</AuthContext.Provider>;
605 | };
606 |

```

FILE: src/providers/FocusModeProvider.tsx

TYPE: .tsx | LINES: 1-47 | SHA256: 02b69ab211fac3e01f46d0e9aaf4498ddef2c7bdf5714d46757cc2db3489cdee

```

1 | import {
2 |   createContext,
3 |   useContext,
4 |   useState,
5 |   useCallback,
6 |   type ReactNode,
7 | } from "react";
8 | import {
9 |   useAccessibilityPreferences,
10 |   useUpdateAccessibilityPreferences,
11 | } from "@hooks/useAccessibilityPreferences";
12 |
13 | interface FocusModeContextValue {
14 |   isFocusMode: boolean;
15 |   toggleFocusMode: () => void;
16 | }
17 |
18 | const FocusModeContext = createContext<FocusModeContextValue>({
19 |   isFocusMode: false,
20 |   toggleFocusMode: () => {},
21 | });
22 |
23 | // eslint-disable-next-line react-refresh/only-export-components
24 | export const useFocusMode = () => useContext(FocusModeContext);
25 |
26 | export const FocusModeProvider = ({ children }: { children: ReactNode }) => {
27 |   const { data: prefs } = useAccessibilityPreferences();
28 |   const updatePrefs = useUpdateAccessibilityPreferences();
29 |   const [localFocusMode, setLocalFocusMode] = useState(false);
30 |
31 |   const isFocusMode = prefs?.simplified_view ?? localFocusMode;
32 |
33 |   const toggleFocusMode = useCallback(() => {
34 |     const newValue = !isFocusMode;
35 |     setLocalFocusMode(newValue);
36 |     if (prefs) {
37 |       updatePrefs.mutate({ ...prefs, simplified_view: newValue });
38 |     }
39 |   }, [isFocusMode, prefs, updatePrefs]);
40 |
41 |   return (

```



```

42 |     <FocusModeContext.Provider value={{ isFocusMode, toggleFocusMode }}>
43 |       {children}
44 |     </FocusModeContext.Provider>
45 |   );
46 | };
47 |

```

FILE: src/providers/ImpersonationProvider.tsx

TYPE: .tsx | LINES: 1-116 | SHA256: d2c2c089ec6cfdc03ac28d9864fc060982225f9a371facd3bf384f1aad94a5ff

```

1 | // Task 88.1: Impersonation context provider
2 | // 30-minute auto-expire, read-only mode flag for blocking mutations
3 |
4 | import {
5 |   createContext,
6 |   useCallback,
7 |   useEffect,
8 |   useMemo,
9 |   useRef,
10 |  useState,
11 |  type ReactNode,
12 | } from "react";
13 |
14 | const IMPERSONATION_DURATION_MS = 30 * 60 * 1000; // 30 minutes
15 |
16 | export interface ImpersonatedUser {
17 |   id: string;
18 |   full_name: string;
19 |   role: string;
20 | }
21 |
22 | export interface ImpersonationContextValue {
23 |   isImpersonating: boolean;
24 |   impersonatedUser: ImpersonatedUser | null;
25 |   timeRemaining: number; // seconds
26 |   isReadOnly: boolean;
27 |   startImpersonation: (user: ImpersonatedUser) => void;
28 |   stopImpersonation: () => void;
29 | }
30 |
31 | // eslint-disable-next-line react-refresh/only-export-components
32 | export const ImpersonationContext = createContext<ImpersonationContextValue>({
33 |   isImpersonating: false,
34 |   impersonatedUser: null,
35 |   timeRemaining: 0,
36 |   isReadOnly: false,
37 |   startImpersonation: () => {},
38 |   stopImpersonation: () => {},
39 | });
40 |
41 | export const ImpersonationProvider = ({
42 |   children,
43 | }: {
44 |   children: ReactNode;
45 | }) => {
46 |   const [impersonatedUser, setImpersonatedUser] =
47 |     useState<ImpersonatedUser | null>(null);
48 |   const [timeRemaining, setTimeRemaining] = useState(0);
49 |   const timerRef = useRef<ReturnType<typeof setInterval> | null>(null);
50 |   const expiryRef = useRef<number>(0);
51 |
52 |   const clearTimer = useCallback(() => {
53 |     if (timerRef.current) {
54 |       clearInterval(timerRef.current);
55 |       timerRef.current = null;
56 |     }
57 |   }, []);
58 |
59 |   const stopImpersonation = useCallback(() => {
60 |     clearTimer();
61 |     setImpersonatedUser(null);
62 |     setTimeRemaining(0);
63 |     expiryRef.current = 0;
64 |   }, [clearTimer]);
65 |
66 |   const startImpersonation = useCallback(
67 |     (user: ImpersonatedUser) => {
68 |       clearTimer();
69 |       setImpersonatedUser(user);
70 |       expiryRef.current = Date.now() + IMPERSONATION_DURATION_MS;
71 |       setTimeRemaining(Math.ceil(IMPERSONATION_DURATION_MS / 1000));
72 |
73 |       timerRef.current = setInterval(() => {
74 |         const remaining = Math.max(
75 |           0,
76 |           Math.ceil((expiryRef.current - Date.now()) / 1000)
77 |         );
78 |         setTimeRemaining(remaining);
79 |         if (remaining <= 0) {
80 |           stopImpersonation();
81 |         }
82 |       }, 1000);
83 |     },
84 |     [clearTimer, stopImpersonation]
85 |   );
86 |
87 |   // Cleanup on unmount
88 |   useEffect(() => clearTimer, [clearTimer]);
89 |
90 |   const isImpersonating = impersonatedUser !== null;
91 |
92 |   const value = useMemo<ImpersonationContextValue>(
93 |     () => ({
94 |       isImpersonating,

```

```

95 |     impersonatedUser,
96 |     timeRemaining,
97 |     isReadOnly: isImpersonating,
98 |     startImpersonation,
99 |     stopImpersonation,
100 |   }},
101 |   [
102 |     isImpersonating,
103 |     impersonatedUser,
104 |     timeRemaining,
105 |     startImpersonation,
106 |     stopImpersonation,
107 |   ]
108 | );
109
110 | return (
111 |   <ImpersonationContext.Provider value={value}>
112 |     {children}
113 |   </ImpersonationContext.Provider>
114 | );
115 | };
116 |

```

FILE: src/providers/LanguageProvider.tsx

TYPE: .tsx | LINES: 1-104 | SHA256: a8c8335bffb27fb5bde8c2bb8dbe84d24f26d28ac6a0e46c8687712b0f1999eb

```

1 | import {
2 |   createContext,
3 |   useCallback,
4 |   useContext,
5 |   useEffect,
6 |   useMemo,
7 |   useRef,
8 |   useState,
9 |   type ReactNode,
10 | } from "react";
11 | import { useTranslation } from "react-i18next";
12 | import { supabase } from "@lib/supabase";
13 | import { useAuth } from "@hooks/useAuth";
14 | import { applyDirection } from "@lib/directionManager";
15 |
16 | export type Language = "en" | "ar";
17 |
18 | interface LanguageContextValue {
19 |   language: Language;
20 |   direction: "ltr" | "rtl";
21 |   setLanguage: (lang: Language) => void;
22 | }
23 |
24 | const LanguageContext = createContext<LanguageContextValue>({
25 |   language: "en",
26 |   direction: "ltr",
27 |   setLanguage: () => {},
28 | });
29 |
30 | // eslint-disable-next-line react-refresh/only-export-components
31 | export const useLanguage = () => useContext(LanguageContext);
32 |
33 | export const LanguageProvider = ({ children }: { children: ReactNode }) => {
34 |   const { i18n } = useTranslation();
35 |   const { user, profile } = useAuth();
36 |   const profileLang = ((profile?.preferred_language as Language) ||
37 |     "en") as Language;
38 |   const [language, setLanguageState] = useState<Language>(profileLang);
39 |   // Debounce timer ref - prevents multiple DB writes on rapid language changes
40 |   const dbWriteTimerRef = useRef<ReturnType<typeof setTimeout> | null>(null);
41 |
42 |   const direction: "ltr" | "rtl" = language === "ar" ? "rtl" : "ltr";
43 |
44 |   // Apply direction via directionManager
45 |   useEffect(() => {
46 |     applyDirection(language);
47 |   }, [language]);
48 |
49 |   // Sync language when profile preference changes (one-way: profile !' state)
50 |   useEffect(() => {
51 |     if (profileLang !== language) {
52 |       // eslint-disable-next-line react-hooks/set-state-in-effect -- Intentional: sync state from profile pref
53 |       setLanguageState(profileLang);
54 |       i18n.changeLanguage(profileLang);
55 |     }
56 |   });
57 |   // Only react to profileLang changes, not language
58 |   // eslint-disable-next-line react-hooks/exhaustive-deps
59 |   }, [profileLang]);
60 |
61 |   const userId = user?.id;
62 |
63 |   const setLanguage = useCallback(
64 |     (lang: Language) => {
65 |       setLanguageState(lang);
66 |       void i18n.changeLanguage(lang);
67 |       localStorage.setItem("eviser-language", lang);
68 |       applyDirection(lang);
69 |
70 |       if (!userId) return;
71 |
72 |       // Debounce: cancel any pending write and schedule a new one after 800ms
73 |       if (dbWriteTimerRef.current) {
74 |         clearTimeout(dbWriteTimerRef.current);
75 |       }
76 |       dbWriteTimerRef.current = setTimeout(() => {
77 |         supabase
78 |           .from("profiles")

```

```

79 |         .eq("id", userId)
80 |         .then(({ error }) => {
81 |             if (error) {
82 |                 console.error(
83 |                     "[LanguageProvider] Failed to save preference:",
84 |                     error.message
85 |                 );
86 |             }
87 |         });
88 |     }, 800);
89 | }, [i18n, userId]
90 | );
91 |
92 |
93 | const value = useMemo(
94 |     () => ({ language, direction, setLanguage }),
95 |     [language, direction, setLanguage]
96 | );
97 |
98 | return (
99 |     <LanguageContext.Provider value={value}>
100 |         {children}
101 |     </LanguageContext.Provider>
102 | );
103 | };
104 |

```

FILE: src/providers/ThemeProvider.tsx

```
TYPE: .tsx | LINES: 1-148 | SHA256: eb5c3f4a9a5c4c8e1d12abc2453589ec4b6a60c3a8ec450b5e248c9685bb8ca4
```

[illegible]

```

75 | const { profile } = useAuth();
76 | const theme = useSyncExternalStore(
77 |   subscribeThemeStore,
78 |   getStoredTheme,
79 |   () => "system" as ThemePreference
80 | );
81 | const systemTheme = useSyncExternalStore(
82 |   subscribeSystemTheme,
83 |   getSystemTheme,
84 |   () => "light" as const
85 | );
86 | const profileSyncedRef = useRef(false);
87 | // Debounce timer ref - prevents multiple DB writes on rapid theme changes
88 | const dbWriteTimerRef = useRef<ReturnType<typeof setTimeout> | null>(null);
89 |
90 | const resolvedTheme = theme === "system" ? systemTheme : theme;
91 | const profilePref = profile?.theme_preference;
92 |
93 | // Apply class to html element
94 | useEffect(() => {
95 |   const root = document.documentElement;
96 |   root.classList.remove("light", "dark");
97 |   root.classList.add(resolvedTheme);
98 | }, [resolvedTheme]);
99 |
100 | // Sync from profile on first load (one-time hydration)
101 | useEffect(() => {
102 |   if (
103 |     !profileSyncedRef.current &&
104 |     profilePref &&
105 |     ["light", "dark", "system"].includes(profilePref)
106 |   ) {
107 |     profileSyncedRef.current = true;
108 |     setStoredTheme(profilePref as ThemePreference);
109 |   }
110 | }, [profilePref]);
111 |
112 | const profileId = profile?.id;
113 |
114 | const setTheme = useCallback(
115 |   (t: ThemePreference) => {
116 |     setStoredTheme(t);
117 |
118 |     if (!profileId) return;
119 |
120 |     // Debounce: cancel any pending write and schedule a new one after 800ms
121 |     // This prevents multiple DB writes when user rapidly toggles theme
122 |     if (dbWriteTimerRef.current) {
123 |       clearTimeout(dbWriteTimerRef.current);
124 |     }
125 |     dbWriteTimerRef.current = setTimeout(() => {
126 |       supabase
127 |         .from("profiles")
128 |         .update({ theme_preference: t })
129 |         .eq("id", profileId)
130 |         .then(({ error }) => {
131 |           if (error)
132 |             console.error(
133 |               "[ThemeProvider] Failed to sync theme:",
134 |               error.message
135 |             );
136 |         });
137 |     }, 800);
138 |   },
139 |   [profileId]
140 | );
141 |
142 | return (
143 |   <ThemeContext.Provider value={{ theme, resolvedTheme, setTheme }}>
144 |     {children}
145 |   </ThemeContext.Provider>
146 | );
147 | };
148 |

```

FILE: src/router/AppRouter.tsx

TYPE: .tsx | LINES: 1-1066 | SHA256: 0a67d37c81adf59c39318c93f721d8eb71afc646a6677f25f56fe03d9de1cc33

```

1 | import { lazy, Suspense, type ReactNode } from "react";
2 | import { Routes, Route, Navigate } from "react-router-dom";
3 | import RouteGuard from "@router/RouteGuard";
4 | import ErrorBoundary from "@components/shared/ErrorBoundary";
5 | import { Button } from "@components/ui/button";
6 |
7 | // -----
8 | // Public pages (no auth required)
9 | // -----
10 | const LoginPage = lazy(() => import("@/pages/LoginPage"));
11 | const ResetPasswordPage = lazy(() => import("@/pages/ResetPasswordPage"));
12 | const UpdatePasswordPage = lazy(() => import("@/pages/UpdatePasswordPage"));
13 | const SignUpPage = lazy(() => import("@/pages/auth/SignUpPage"));
14 | const AcceptInvitePage = lazy(() => import("@/pages/auth/AcceptInvitePage"));
15 |
16 | // -----
17 | // Role layouts (lazy-loaded for code splitting)
18 | // -----
19 | const AdminLayout = lazy(() => import("@/pages/admin/AdminLayout"));
20 | const CoordinatorLayout = lazy(
21 |   () => import("@/pages/coordinator/CoordinatorLayout")
22 | );
23 | const TeacherLayout = lazy(() => import("@/pages/teacher/TeacherLayout"));
24 | const StudentLayout = lazy(() => import("@/pages/student/StudentLayout"));
25 | const ParentLayout = lazy(() => import("@/pages/parent/ParentLayout"));
26 |

```

```

27 // -----
28 // Admin pages (lazy-loaded)
29 // -----
30 const AdminDashboard = lazy(() => import("@/pages/admin/AdminDashboard"));
31 const AdminAnalyticsPage = lazy(
32   () => import("@/pages/admin/analytics/AdminAnalyticsPage")
33 );
34 const UserListPage = lazy(() => import("@/pages/admin/users/UserListPage"));
35 const UserForm = lazy(() => import("@/pages/admin/users/UserForm"));
36 const BulkImportPage = lazy(() => import("@/pages/admin/users/BulkImportPage"));
37 const InviteUsersPage = lazy(
38   () => import("@/pages/admin/users/InviteUsersPage")
39 );
40 const ParentInvitePage = lazy(
41   () => import("@/pages/admin/users/ParentInvitePage")
42 );
43 const ProgramListPage = lazy(
44   () => import("@/pages/admin/programs/ProgramListPage")
45 );
46 const ProgramForm = lazy(() => import("@/pages/admin/programs/ProgramForm"));
47 const ILOListPage = lazy(() => import("@/pages/admin/outcomes/ILOListPage"));
48 const ILOForm = lazy(() => import("@/pages/admin/outcomes/ILOForm"));
49 const AuditLogPage = lazy(() => import("@/pages/admin/AuditLogPage"));
50 const BonusXPEventManager = lazy(
51   () => import("@/pages/admin/BonusXPEventManager")
52 );
53 const CourseListPage = lazy(
54   () => import("@/pages/admin/courses/CourseListPage")
55 );
56 const CourseForm = lazy(() => import("@/pages/admin/courses/CourseForm"));
57 const CourseEnrollmentPage = lazy(
58   () => import("@/pages/admin/courses/CourseEnrollmentPage")
59 );
60 const SemesterManager = lazy(
61   () => import("@/pages/admin/semesters/SemesterManager")
62 );
63 const DepartmentManager = lazy(
64   () => import("@/pages/admin/departments/DepartmentManager")
65 );
66 const PendingOnboardingPage = lazy(
67   () => import("@/pages/admin/onboarding/PendingOnboardingPage")
68 );
69 const ReportGeneratorPage = lazy(
70   () => import("@/pages/admin/reports/ReportGeneratorPage")
71 );
72 const AdminAccreditationReportsPage = lazy(
73   () => import("@/pages/admin/reports/AdminAccreditationReportsPage")
74 );
75 const CoordinatorDashboard = lazy(
76   () => import("@/pages/coordinator/CoordinatorDashboard")
77 );
78 const PLOListPage = lazy(() => import("@/pages/coordinator/plos/PLOListPage"));
79 const PLOForm = lazy(() => import("@/pages/coordinator/plos/PLOForm"));
80 const CurriculumMatrixPage = lazy(
81   () => import("@/pages/coordinator/CurriculumMatrixPage")
82 );
83 const TeacherDashboard = lazy(() => import("@/pages/teacher/TeacherDashboard"));
84 const TeacherStudentsPage = lazy(
85   () => import("@/pages/teacher/students/TeacherStudentsPage")
86 );
87 const CLOListPage = lazy(() => import("@/pages/teacher/clos/CLOListPage"));
88 const CLOForm = lazy(() => import("@/pages/teacher/clos/CLOForm"));
89 const CLODetailPage = lazy(() => import("@/pages/teacher/clos/CLODetailPage"));
90 const RubricListPage = lazy(
91   () => import("@/pages/teacher/rubrics/RubricListPage")
92 );
93 const RubricBuilder = lazy(
94   () => import("@/pages/teacher/rubrics/RubricBuilder")
95 );
96 const AssignmentListPage = lazy(
97   () => import("@/pages/teacher/assignments/AssignmentListPage")
98 );
99 const AssignmentForm = lazy(
100   () => import("@/pages/teacher/assignments/AssignmentForm")
101 );
102 const GradingQueuePage = lazy(
103   () => import("@/pages/teacher/grading/GradingQueuePage")
104 );
105 const GradingInterface = lazy(
106   () => import("@/pages/teacher/grading/GradingInterface")
107 );
108 const BaselineConfigPage = lazy(
109   () => import("@/pages/teacher/baseline/BaselineConfigPage")
110 );
111 const BaselineQuestionForm = lazy(
112   () => import("@/pages/teacher/baseline/BaselineQuestionForm")
113 );
114 const BaselineResultsPage = lazy(
115   () => import("@/pages/teacher/baseline/BaselineResultsPage")
116 );
117 const StudentDashboard = lazy(() => import("@/pages/student/StudentDashboard"));
118 const StudentAssignmentListPage = lazy(
119   () => import("@/pages/student/assignments/AssignmentListPage")
120 );
121 const StudentAssignmentDetailPage = lazy(
122   () => import("@/pages/student/assignments/AssignmentDetailPage")
123 );
124 const LeaderboardPage = lazy(
125   () => import("@/pages/student/leaderboard/LeaderboardPage")
126 );
127 const CompleteProfilePage = lazy(
128   () => import("@/pages/student/onboarding/CompleteProfilePage")
129 );
130 const OnboardingWizardPage = lazy(

```

```

131 |     () => import("@/pages/student/onboarding/OnboardingWizard")
132 | );
133 | const ReassessmentPage = lazy(
134 |   () => import("@/pages/student/settings/ReassessmentPage")
135 | );
136 | const ProfileSettingsPage = lazy(
137 |   () => import("@/pages/student/settings/ProfileSettingsPage")
138 | );
139 | const StarterWeekPlanPage = lazy(
140 |   () => import("@/pages/student/planner/StarterWeekPlanPage")
141 | );
142 | const WeeklyPlannerPage = lazy(
143 |   () => import("@/pages/student/planner/WeeklyPlannerPage")
144 | );
145 | const TodayViewPage = lazy(
146 |   () => import("@/pages/student/planner/TodayViewPage")
147 | );
148 | const FocusModePage = lazy(
149 |   () => import("@/pages/student/planner/FocusModePage")
150 | );
151 | const HabitHeatmapPage = lazy(
152 |   () => import("@/pages/student/habits/HabitHeatmapPage")
153 | );
154 | const HabitAnalyticsPage = lazy(
155 |   () => import("@/pages/student/habits/HabitAnalyticsPage")
156 | );
157 | const XPHistory = lazy(() => import("@/pages/student/progress/XPHistory"));
158 | const CLOProgress = lazy(() => import("@/pages/student/progress/CLOProgress"));
159 | const LearningPathPage = lazy(
160 |   () => import("@/pages/student/progress/LearningPathPage")
161 | );
162 | const StudentBadgesPage = lazy(
163 |   () => import("@/pages/student/badges/StudentBadgesPage")
164 | );
165 | const LearningProfilePage = lazy(
166 |   () => import("@/pages/student/profile/LearningProfilePage")
167 | );
168 | const StudentProfilePage = lazy(
169 |   () => import("@/features/student/profile/StudentProfilePage")
170 | );
171 | const StudentPortfolio = lazy(
172 |   () => import("@/pages/student/portfolio/StudentPortfolio")
173 | );
174 | const ParentDashboard = lazy(() => import("@/pages/parent/ParentDashboard"));
175 | const ParentSupportPage = lazy(
176 |   () => import("@/pages/parent/support/ParentSupportPage")
177 | );
178 | const ParentPlannerView = lazy(
179 |   () => import("@/pages/parent/planner/ParentPlannerView")
180 | );
181 | const ParentProfilePage = lazy(
182 |   () => import("@/pages/parent/settings/ParentProfilePage")
183 | );
184 | const ParentCommunicationsPage = lazy(
185 |   () => import("@/pages/parent/communications/ParentCommunicationsPage")
186 | );
187 | const AdminProfilePage = lazy(
188 |   () => import("@/pages/admin/settings/AdminProfilePage")
189 | );
190 | const TeacherProfilePage = lazy(
191 |   () => import("@/pages/teacher/settings/TeacherProfilePage")
192 | );
193 | const CalendarView = lazy(() => import("@/pages/shared/CalendarView"));
194 | const TimetableView = lazy(() => import("@/pages/shared/TimetableView"));
195 | const AcademicCalendarManager = lazy(
196 |   () => import("@/pages/admin/calendar/AcademicCalendarManager")
197 | );
198 | const TimetableManager = lazy(
199 |   () => import("@/pages/admin/timetable/TimetableManager")
200 | );
201 | const FeeManager = lazy(() => import("@/pages/admin/fees/FeeManager"));
202 | const DataImportPage = lazy(
203 |   () => import("@/pages/admin/import/DataImportPage")
204 | );
205 |
206 | // -----
207 | // Public portfolio (unauthenticated)
208 | // -----
209 | const PublicPortfolio = lazy(() => import("@/pages/public/PublicPortfolio"));
210 | const TermsPage = lazy(() => import("@/pages/public/TermsPage"));
211 | const PrivacyPage = lazy(() => import("@/pages/public/PrivacyPage"));
212 | const NotificationPreferences = lazy(
213 |   () => import("@/pages/shared/NotificationPreferences")
214 | );
215 | const SessionManagement = lazy(
216 |   () => import("@/pages/shared/SessionManagement")
217 | );
218 |
219 | // -----
220 | // Adaptive Quiz Generation pages (lazy-loaded)
221 | // -----
222 | const GenerateQuestionsPage = lazy(
223 |   () => import("@/pages/teacher/quiz-generation/GenerateQuestionsPage")
224 | );
225 | const ReviewQueuePage = lazy(
226 |   () => import("@/pages/teacher/quiz-generation/ReviewQueuePage")
227 | );
228 | const QuestionBankPage = lazy(
229 |   () => import("@/pages/teacher/quiz-generation/QuestionBankPage")
230 | );
231 | const QuestionAnalyticsDashboard = lazy(
232 |   () => import("@/pages/teacher/quiz-analytics/QuestionAnalyticsDashboard")
233 | );
234 | const QuizCLOCorrelationPage = lazy(

```

```

235 |     () => import("@/pages/teacher/quiz-analytics/QuizCLOCorrelationPage")
236 |   );
237 |   const QuizForm = lazy(() => import("@/pages/teacher/quizzes/QuizForm"));
238 |   const AdaptiveQuizSession = lazy(
239 |     () => import("@/pages/student/quiz/AdaptiveQuizSession")
240 |   );
241 |   const PostQuizReview = lazy(
242 |     () => import("@/pages/student/quiz/PostQuizReview")
243 |   );
244 |   const MasteryRecoveryPage = lazy(
245 |     () => import("@/pages/student/recovery/MasteryRecoveryPage")
246 |   );
247 |
248 |   // AI Tutor
249 |   const TutorPage = lazy(() => import("@/pages/student/tutor/TutorPage"));
250 |   const TutorAnalyticsPage = lazy(
251 |     () => import("@/pages/teacher/tutor-analytics/TutorAnalyticsPage")
252 |   );
253 |   const TeacherHandoffPage = lazy(
254 |     () => import("@/pages/teacher/tutor-analytics/TeacherHandoffPage")
255 |   );
256 |   const ExplanationReviewPage = lazy(
257 |     () => import("@/pages/teacher/quiz-generation/ExplanationReviewPage")
258 |   );
259 |
260 |   // Gradebook
261 |   const GradebookView = lazy(
262 |     () => import("@/pages/teacher/gradebook/GradebookView")
263 |   );
264 |
265 |   // Attendance
266 |   const AttendanceMarker = lazy(
267 |     () => import("@/pages/teacher/attendance/AttendanceMarker")
268 |   );
269 |   const AttendanceReport = lazy(
270 |     () => import("@/pages/teacher/attendance/AttendanceReport")
271 |   );
272 |
273 |   // Announcements & Modules
274 |   const AnnouncementEditor = lazy(
275 |     () => import("@/pages/teacher/announcements/AnnouncementEditor")
276 |   );
277 |   const ModuleManager = lazy(
278 |     () => import("@/pages/teacher/courses/ModuleManager")
279 |   );
280 |
281 |   // Discussion Forum
282 |   const DiscussionForum = lazy(
283 |     () => import("@/pages/student/discussions/DiscussionForum")
284 |   );
285 |   const ThreadDetail = lazy(
286 |     () => import("@/pages/student/discussions/ThreadDetail")
287 |   );
288 |   const DiscussionModeration = lazy(
289 |     () => import("@/pages/teacher/discussions/DiscussionModeration")
290 |   );
291 |   const CourseToolRedirect = lazy(
292 |     () => import("@/pages/teacher/CourseToolRedirect")
293 |   );
294 |
295 |   // CQI pages
296 |   const CQIManager = lazy(() => import("@/pages/coordinator/cqi/CQIManager"));
297 |
298 |   // Course File
299 |   const CourseFileGenerator = lazy(
300 |     () => import("@/pages/coordinator/course-file/CourseFileGenerator")
301 |   );
302 |
303 |   // OBE Visualizations (tasks 112-125)
304 |   const GraduateAttributeManager = lazy(
305 |     () => import("@/pages/admin/graduate-attributes/GraduateAttributeManager")
306 |   );
307 |   const CompetencyFrameworkManager = lazy(
308 |     () => import("@/pages/admin/competency-frameworks/CompetencyFrameworkManager")
309 |   );
310 |   const HistoricalEvidenceDashboard = lazy(
311 |     () => import("@/pages/admin/historical-evidence/HistoricalEvidenceDashboard")
312 |   );
313 |   const SankeyDiagramView = lazy(
314 |     () => import("@/pages/coordinator/sankey/SankeyDiagramView")
315 |   );
316 |   const GapAnalysisView = lazy(
317 |     () => import("@/pages/coordinator/gap-analysis/GapAnalysisView")
318 |   );
319 |   const CoverageHeatmapView = lazy(
320 |     () => import("@/pages/coordinator/coverage-heatmap/CoverageHeatmapView")
321 |   );
322 |   const SemesterTrendView = lazy(
323 |     () => import("@/pages/coordinator/trends/SemesterTrendView")
324 |   );
325 |   const CohortComparisonView = lazy(
326 |     () => import("@/pages/coordinator/cohort-comparison/CohortComparisonView")
327 |   );
328 |
329 |   // Team Management (task 129)
330 |   const TeamManager = lazy(() => import("@/pages/teacher/teams/TeamManager"));
331 |
332 |   // Team Challenges – Phase 5 pages
333 |   const TeamProfilePage = lazy(
334 |     () => import("@/pages/student/teams/TeamProfilePage")
335 |   );
336 |   const CreateTeamPage = lazy(
337 |     () => import("@/pages/student/teams/CreateTeamPage")
338 |   );

```

```

339 | const TeamManagementPage = lazy(
340 |   () => import("@/pages/teacher/teams/TeamManagementPage")
341 | );
342 | const TeamFormPage = lazy(() => import("@/pages/teacher/teams/TeamFormPage"));
343 |
344 | // Challenge Management (tasks 134-135)
345 | const ChallengeListView = lazy(
346 |   () => import("@/pages/student/challenges/ChallengeListView")
347 | );
348 |
349 | // Team Challenges – Phase 6 pages
350 | const ChallengeListPage = lazy(
351 |   () => import("@/pages/student/challenges/ChallengeListPage")
352 | );
353 | const ChallengeDetailPage = lazy(
354 |   () => import("@/pages/student/challenges/ChallengeDetailPage")
355 | );
356 | const TeacherChallengeListPage = lazy(
357 |   () => import("@/pages/teacher/challenges/TeacherChallengeListPage")
358 | );
359 | const ChallengeFormPage = lazy(
360 |   () => import("@/pages/teacher/challenges/ChallengeFormPage")
361 | );
362 |
363 | // Team Health Report (Phase 13)
364 | const TeamHealthReportPage = lazy(
365 |   () => import("@/pages/teacher/teams/TeamHealthReportPage")
366 | );
367 |
368 | // Student Team Page (task 141)
369 | const StudentTeamPage = lazy(
370 |   () => import("@/pages/student/team/StudentTeamPage")
371 | );
372 |
373 | // Badge Spotlight Manager (task 151)
374 | const BadgeSpotlightManager = lazy(
375 |   () => import("@/pages/admin/badges/BadgeSpotlightManager")
376 | );
377 | const BadgeDefinitionsPage = lazy(
378 |   () => import("@/pages/admin/badges/BadgeDefinitionsPage")
379 | );
380 | const AIGovernancePage = lazy(
381 |   () => import("@/pages/admin/governance/AIGovernancePage")
382 | );
383 |
384 | // Gap Analysis – Creative Expression & Unpredictability (Task 21)
385 | const StudentContentPage = lazy(
386 |   () => import("@/pages/student/content/StudentContentPage")
387 | );
388 | const KnowledgeQuestManager = lazy(
389 |   () => import("@/pages/admin/marketplace/KnowledgeQuestManager")
390 | );
391 | const ContentReviewPage = lazy(
392 |   () => import("@/pages/teacher/content/ContentReviewPage")
393 | );
394 |
395 | // Gap Analysis – XP Economy Health (Task 22)
396 | const XPEconomistDashboard = lazy(
397 |   () => import("@/pages/admin/marketplace/XPEconomistDashboard")
398 | );
399 |
400 | // Admin Marketplace Management
401 | const MarketplaceManagementPage = lazy(
402 |   () => import("@/pages/admin/marketplace/MarketplaceManagementPage")
403 | );
404 | const SaleEventManager = lazy(
405 |   () => import("@/pages/admin/marketplace/SaleEventManager")
406 | );
407 | const MarketplaceAnalyticsPage = lazy(
408 |   () => import("@/pages/admin/marketplace/MarketplaceAnalyticsPage")
409 | );
410 |
411 | // Student Marketplace
412 | const StudentMarketplacePage = lazy(
413 |   () => import("@/pages/student/marketplace/MarketplacePage")
414 | );
415 | const StudentMyItemsPage = lazy(
416 |   () => import("@/pages/student/marketplace/MyItemsPage")
417 | );
418 | const StudentTransactionHistoryPage = lazy(
419 |   () => import("@/pages/student/marketplace/TransactionHistoryPage")
420 | );
421 |
422 | // Sub-CLO Manager (task 110)
423 | const SubCLOManager = lazy(
424 |   () => import("@/pages/teacher/outcomes/SubCLOManager")
425 | );
426 |
427 | // Survey pages
428 | const SurveyManager = lazy(() => import("@/pages/admin/surveys/SurveyManager"));
429 | const SurveyResultsPage = lazy(
430 |   () => import("@/pages/admin/surveys/SurveyResultsPage")
431 | );
432 | const SurveyResponsePage = lazy(
433 |   () => import("@/pages/student/surveys/SurveyResponsePage")
434 | );
435 |
436 | // Student Announcement & Material Detail
437 | const StudentAnnouncementDetail = lazy(
438 |   () => import("@/pages/student/announcements/AnnouncementDetail")
439 | );
440 | const StudentCourseDetail = lazy(
441 |   () => import("@/pages/student/courses/CourseDetail")
442 | );

```



```

443 | const StudentCoursesListPage = lazy(
444 |   () => import("@/pages/student/courses/StudentCoursesPage")
445 | );
446 | const StudentProgressPage = lazy(
447 |   () => import("@/pages/student/progress/StudentProgressPage")
448 | );
449 | const StudentJournalPage = lazy(
450 |   () => import("@/pages/student/journal/StudentJournalPage")
451 | );
452 | // Net-new (Path-A rebuild, P3.6): official transcript viewer – surfaces the
453 | // existing generate-transcript edge fn (useGenerateTranscript), no prior UI.
454 | const StudentTranscriptPage = lazy(
455 |   () => import("@/features/student/transcript/StudentTranscriptPage")
456 | );
457 | // Net-new (Path-A rebuild): student fee status + receipts (useStudentFees /
458 | // useGenerateFeeReceipt); only admin FeeManager existed before.
459 | const StudentFeesPage = lazy(
460 |   () => import("@/features/student/fees/StudentFeesPage")
461 | );
462 | // Net-new (Path-A rebuild): full-page notifications feed (useNotifications);
463 | // only the bell dropdown existed before.
464 | const NotificationsFeedPage = lazy(
465 |   () => import("@/features/shared/notifications/NotificationsFeedPage")
466 | );
467 | const ParentChildrenPage = lazy(
468 |   () => import("@/pages/parent/ParentChildrenPage")
469 | );
470 | const ParentProgressPage = lazy(
471 |   () => import("@/pages/parent/ParentProgressPage")
472 | );
473 | const ParentAttendancePage = lazy(
474 |   () => import("@/pages/parent/ParentAttendancePage")
475 | );
476 | // Net-new (Path-A rebuild): parent view of their children's fees.
477 | const ParentFeesPage = lazy(
478 |   () => import("@/features/parent/fees/ParentFeesPage")
479 | );
480 | const BaselineCoursesListPage = lazy(
481 |   () => import("@/pages/teacher/baseline/BaselineCoursesListPage")
482 | );
483 |
484 | // Institution Settings
485 | const InstitutionSettingsPage = lazy(
486 |   () => import("@/pages/admin/settings/InstitutionSettings")
487 | );
488 |
489 | // Shared pages
490 | const ProfilePage = lazy(() => import("@/pages/shared/ProfilePage"));
491 | const OutcomeChainView = lazy(() => import("@/pages/shared/OutcomeChainView"));
492 | const NotFoundPage = lazy(() => import("@/pages/NotFoundPage"));
493 |
494 | // Net-new (Path-A rebuild, P3.6): Admin Security console – surfaces
495 | // blocked_ips / login_attempts / rate_limit_events via useAdminSecurity; no prior UI.
496 | const AdminSecurityPage = lazy(
497 |   () => import("@/features/admin/security/AdminSecurityPage")
498 | );
499 |
500 | // -----
501 | // Page-level error fallback
502 | // -----
503 | const PageErrorFallback = () => (
504 |   <div className="flex flex-col items-center justify-center min-h-[60vh] p-8 text-center">
505 |     <div className="rounded-full bg-red-50 p-4 mb-4">
506 |       <svg
507 |         className="h-8 w-8 text-red-500"
508 |         fill="none"
509 |         viewBox="0 0 24 24"
510 |         stroke="currentColor"
511 |       >
512 |         <path
513 |           strokeLinecap="round"
514 |           strokeLinejoin="round"
515 |           strokeWidth={2}
516 |           d="M12 9v2m0 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464"
517 |         />
518 |       </svg>
519 |     </div>
520 |     <h2 className="text-lg font-bold text-gray-900 mb-2">
521 |       Page failed to load
522 |     </h2>
523 |     <p className="text-sm text-gray-500 mb-4">
524 |       Something went wrong loading this page.
525 |     </p>
526 |     <Button
527 |       type="button"
528 |       onClick={() => window.location.reload()}
529 |       variant="tactile"
530 |     >
531 |       Reload page
532 |     </Button>
533 |   </div>
534 | );
535 |
536 | // -----
537 | // Shared loading fallback
538 | // -----
539 | const LoadingFallback = () => (
540 |   <div className="p-6 space-y-4">
541 |     <div className="h-8 w-48 rounded-lg animate-shimmer" />
542 |     <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
543 |       {Array.from({ length: 4 }).map((_, i) => (
544 |         <div key={i} className="h-24 rounded-xl animate-shimmer" />
545 |       ))}
546 |     </div>

```

```

547 |     <div className="h-64 rounded-xl animate-shimmer" />
548 |   </div>
549 | );
550 |
551 | const PublicMain = ({ children }: { children: ReactNode }) => (
552 |   <main id="main-content" tabIndex={-1}>
553 |     {children}
554 |   </main>
555 | );
556 |
557 | // -----
558 | // AppRouter
559 | // -----
560 | const AppRouter = () => (
561 |   <div>
562 |     <ErrorBoundary fallback={}<PageErrorFallback />>
563 |     <Suspense fallback={}<LoadingFallback />>
564 |       <Routes>
565 |         {/* Public routes */}
566 |         <Route
567 |           path="/login"
568 |           element={
569 |             <PublicMain>
570 |               <LoginPage />
571 |             </PublicMain>
572 |           }
573 |         />
574 |         <Route
575 |           path="/signup"
576 |           element={
577 |             <PublicMain>
578 |               <SignUpPage />
579 |             </PublicMain>
580 |           }
581 |         />
582 |         <Route
583 |           path="/accept-invite/:token"
584 |           element={
585 |             <PublicMain>
586 |               <AcceptInvitePage />
587 |             </PublicMain>
588 |           }
589 |         />
590 |         <Route
591 |           path="/reset-password"
592 |           element={
593 |             <PublicMain>
594 |               <ResetPasswordPage />
595 |             </PublicMain>
596 |           }
597 |         />
598 |         <Route
599 |           path="/update-password"
600 |           element={
601 |             <PublicMain>
602 |               <UpdatePasswordPage />
603 |             </PublicMain>
604 |           }
605 |         />
606 |         <Route
607 |           path="/portfolio/:student_id"
608 |           element={
609 |             <PublicMain>
610 |               <PublicPortfolio />
611 |             </PublicMain>
612 |           }
613 |         />
614 |         <Route
615 |           path="/terms"
616 |           element={
617 |             <PublicMain>
618 |               <TermsPage />
619 |             </PublicMain>
620 |           }
621 |         />
622 |         <Route
623 |           path="/privacy"
624 |           element={
625 |             <PublicMain>
626 |               <PrivacyPage />
627 |             </PublicMain>
628 |           }
629 |         />
630 |
631 |         {/* Admin routes */}
632 |         <Route
633 |           path="/admin/*"
634 |           element={
635 |             <RouteGuard allowedRoles={["admin"]}>
636 |               <AdminLayout />
637 |             </RouteGuard>
638 |           }
639 |       >
640 |         <Route index element={}<Navigate to="/admin/dashboard" replace />> />
641 |         <Route path="dashboard" element={}<AdminDashboard />> />
642 |         <Route path="analytics" element={}<AdminAnalyticsPage />> />
643 |         <Route path="accreditation-reports" element={}<AdminAccreditationReportsPage />> />
644 |         <Route path="notifications" element={}<NotificationsFeedPage />> />
645 |         <Route path="users" element={}<UserListPage />> />
646 |         <Route path="users/new" element={}<UserForm />> />
647 |         <Route path="users/import" element={}<BulkImportPage />> />
648 |         <Route path="users/invite" element={}<InviteUsersPage />> />
649 |         <Route path="users/invite-parent" element={}<ParentInvitePage />> />
650 |         <Route path="users/:id/edit" element={}<UserForm />> />

```

```

651 <Route path="programs" element={<ProgramListPage />} />
652 <Route path="programs/new" element={<ProgramForm />} />
653 <Route path="programs/:id/edit" element={<ProgramForm />} />
654 <Route path="outcomes" element={<ILOListPage />} />
655 <Route path="outcomes/new" element={<ILOForm />} />
656 <Route path="outcomes/:id/edit" element={<ILOForm />} />
657 <Route path="audit-log" element={<AuditLogPage />} />
658 <Route path="governance" element={<AIGovernancePage />} />
659 <Route path="security" element={<AdminSecurityPage />} />
660 <Route path="bonus-events" element={<BonusXPEventManager />} />
661 <Route path="courses" element={<CourseListPage />} />
662 <Route path="courses/new" element={<CourseForm />} />
663 <Route path="courses/:id/edit" element={<CourseForm />} />
664 <Route
665   path="courses/:courseId/enrollment"
666   element={<CourseEnrollmentPage />}
667 />
668 <Route path="semesters" element={<SemesterManager />} />
669 <Route path="departments" element={<DepartmentManager />} />
670 <Route
671   path="onboarding/pending"
672   element={<PendingOnboardingPage />}
673 />
674 <Route path="reports" element={<ReportGeneratorPage />} />
675 <Route path="calendar" element={<AcademicCalendarManager />} />
676 <Route path="timetable" element={<TimetableManager />} />
677 <Route path="fees" element={<FeeManager />} />
678 <Route path="import" element={<DataImportPage />} />
679 <Route path="surveys" element={<SurveyManager />} />
680 <Route path="surveys/results" element={<SurveyResultsPage />} />
681 <Route
682   path="graduate-attributes"
683   element={<GraduateAttributeManager />}
684 />
685 <Route
686   path="competency-frameworks"
687   element={<CompetencyFrameworkManager />}
688 />
689 <Route
690   path="historical-evidence"
691   element={<HistoricalEvidenceDashboard />}
692 />
693 <Route path="outcome-chain" element={<OutcomeChainView />} />
694 <Route path="badges" element={<BadgeDefinitionsPage />} />
695 <Route
696   path="badges/spotlight"
697   element={<BadgeSpotlightManager />}
698 />
699 <Route path="marketplace" element={<MarketplaceManagementPage />} />
700 <Route path="marketplace/sales" element={<SaleEventManager />} />
701 <Route
702   path="marketplace/analytics"
703   element={<MarketplaceAnalyticsPage />}
704 />
705 <Route
706   path="marketplace/quests"
707   element={<KnowledgeQuestManager />}
708 />
709 <Route
710   path="marketplace/economist"
711   element={<XPEconomistDashboard />}
712 />
713 <Route path="settings/profile" element={<AdminProfilePage />} />
714 <Route
715   path="settings/institution"
716   element={<InstitutionSettingsPage />}
717 />
718 </Route>
719
720 /* Coordinator routes */
721 <Route
722   path="/coordinator/*"
723   element={
724     <RouteGuard allowedRoles={["coordinator"]} />
725     <CoordinatorLayout />
726   }
727 />
728
729 <Route
730   index
731   element={<Navigate to="/coordinator/dashboard" replace />}
732 />
733 <Route path="dashboard" element={<CoordinatorDashboard />} />
734 <Route path="notifications" element={<NotificationsFeedPage />} />
735 <Route path="plos" element={<PLOListPage />} />
736 <Route path="plos/new" element={<PLOForm />} />
737 <Route path="plos/:id/edit" element={<PLOForm />} />
738 <Route path="matrix" element={<CurriculumMatrixPage />} />
739 <Route path="cqi" element={<CQIManager />} />
740 <Route path="course-file" element={<CourseFileGenerator />} />
741 <Route path="accreditation" element={<CourseFileGenerator />} />
742 <Route
743   path="team-health"
744   element={<TeamHealthReportPage courseScope="all" />}
745 />
746 <Route
747   path="competencies"
748   element={<CompetencyFrameworkManager />}
749 />
750 <Route
751   path="discussions"
752   element={
753     <CourseToolRedirect userRole="coordinator" tool="discussions" />
754   }

```

```

755 |         />
756 |         <Route
757 |             path="courses/:courseId/discussions"
758 |             element={<DiscussionModeration basePath="/coordinator" />}
759 |         />
760 |         <Route
761 |             path="courses/:courseId/discussions/:threadId"
762 |             element={<ThreadDetail />}
763 |         />
764 |         <Route path="sankey" element={<SankeyDiagramView />} />
765 |         <Route path="gap-analysis" element={<GapAnalysisView />} />
766 |         <Route path="coverage-heatmap" element={<CoverageHeatmapView />} />
767 |         <Route path="trends" element={<SemesterTrendView />} />
768 |         <Route
769 |             path="cohort-comparison"
770 |             element={<CohortComparisonView />}
771 |         />
772 |         <Route path="outcome-chain" element={<OutcomeChainView />} />
773 |         <Route path="timetable" element={<TimetableManager />} />
774 |         <Route path="settings/profile" element={<ProfilePage />} />
775 |     </Route>
776 |
777 |     /* Teacher routes */
778 |     <Route
779 |         path="/teacher/*"
780 |         element={
781 |             <RouteGuard allowedRoles={["teacher"]} >
782 |                 <TeacherLayout />
783 |             </RouteGuard>
784 |         }
785 |     >
786 |         <Route
787 |             index
788 |             element={<Navigate to="/teacher/dashboard" replace />}
789 |         />
790 |         <Route path="dashboard" element={<TeacherDashboard />} />
791 |         <Route path="students" element={<TeacherStudentsPage />} />
792 |         <Route path="notifications" element={<NotificationsFeedPage />} />
793 |         <Route path="clos" element={<CLOListPage />} />
794 |         <Route path="clos/new" element={<CLOForm />} />
795 |         <Route path="clos/:id/edit" element={<CLOForm />} />
796 |         <Route path="clos/:id" element={<CLODetailPage />} />
797 |         <Route path="rubrics" element={<RubricListPage />} />
798 |         <Route path="rubrics/new" element={<RubricBuilder />} />
799 |         <Route path="rubrics/:id/edit" element={<RubricBuilder />} />
800 |         <Route path="assignments" element={<AssignmentListPage />} />
801 |         <Route path="assignments/new" element={<AssignmentForm />} />
802 |         <Route path="assignments/:id/edit" element={<AssignmentForm />} />
803 |         <Route path="grading" element={<GradingQueuePage />} />
804 |         <Route
805 |             path="grading/:submissionId"
806 |             element={<GradingInterface />}
807 |         />
808 |         <Route
809 |             path="baseline/:courseId"
810 |             element={<BaselineResultsPage />}
811 |         />
812 |         <Route
813 |             path="baseline/:courseId/config"
814 |             element={<BaselineConfigPage />}
815 |         />
816 |         <Route
817 |             path="baseline/:courseId/questions/new"
818 |             element={<BaselineQuestionForm />}
819 |         />
820 |         <Route path="baseline" element={<BaselineCoursesListPage />} />
821 |         <Route
822 |             path="courses/:courseId/generate-questions"
823 |             element={<GenerateQuestionsPage />}
824 |         />
825 |         <Route
826 |             path="courses/:courseId/review-queue"
827 |             element={<ReviewQueuePage />}
828 |         />
829 |         <Route
830 |             path="courses/:courseId/question-bank"
831 |             element={<QuestionBankPage />}
832 |         />
833 |         <Route
834 |             path="questions"
835 |             element={
836 |                 <CourseToolRedirect userRole="teacher" tool="question-bank" />
837 |             }
838 |         />
839 |         <Route
840 |             path="courses/:courseId/question-analytics"
841 |             element={<QuestionAnalyticsDashboard />}
842 |         />
843 |         <Route
844 |             path="courses/:courseId/quiz-clo-correlation/:quizId"
845 |             element={<QuizCLOCorrelationPage />}
846 |         />
847 |         <Route
848 |             path="courses/:courseId/quizzes/new"
849 |             element={<QuizForm />}
850 |         />
851 |         <Route
852 |             path="courses/:courseId/quizzes/:id/edit"
853 |             element={<QuizForm />}
854 |         />
855 |         <Route
856 |             path="courses/:courseId/explanation-review"
857 |             element={<ExplanationReviewPage />}
858 |         />

```

```

859 <Route path="announcements" element={<AnnouncementEditor />} />
860 <Route path="modules" element={<ModuleManager />} />
861 <Route
862   path="courses/:courseId/discussions"
863   element={<DiscussionModeration />}
864 />
865 <Route
866   path="discussions"
867   element={
868     <CourseToolRedirect userRole="teacher" tool="discussions" />
869   }
870 />
871 <Route
872   path="courses/:courseId/discussions/:threadId"
873   element={<ThreadDetail />}
874 />
875 <Route path="attendance" element={<AttendanceMarker />} />
876 <Route path="attendance/report" element={<AttendanceReport />} />
877 <Route path="gradebook" element={<GradebookView />} />
878 <Route path="teams" element={<TeamManagementPage />} />
879 <Route path="teams/manage" element={<TeamManager />} />
880 <Route path="teams/new" element={<TeamFormPage />} />
881 <Route path="teams/:id/edit" element={<TeamFormPage />} />
882 <Route path="challenges" element={<TeacherChallengeListPage />} />
883 <Route path="challenges/new" element={<ChallengeFormPage />} />
884 <Route path="challenges/:id/edit" element={<ChallengeFormPage />} />
885 <Route path="team-health" element={<TeamHealthReportPage />} />
886 <Route path="clos/:cloId/sub-clos" element={<SubCLOManager />} />
887 <Route path="outcomes/sub-clos" element={<SubCLOManager />} />
888 <Route path="tutor-analytics" element={<TutorAnalyticsPage />} />
889 <Route path="content-review" element={<ContentReviewPage />} />
890 <Route path="tutor-handoffs" element={<TeacherHandoffPage />} />
891 <Route path="calendar" element={<CalendarView />} />
892 <Route path="timetable" element={<TimetableView />} />
893 <Route path="settings/profile" element={<TeacherProfilePage />} />
894 </Route>
895
896 /* Student routes */
897 <Route
898   path="/student/*"
899   element={
900     <RouteGuard allowedRoles={["student"]} >
901       <StudentLayout />
902     </RouteGuard>
903   }
904 >
905   <Route
906     index
907     element={<Navigate to="/student/dashboard" replace />}
908   />
909   <Route path="dashboard" element={<StudentDashboard />} />
910   <Route path="assignments" element={<StudentAssignmentListPage />} />
911   <Route
912     path="assignments/:id"
913     element={<StudentAssignmentDetailPage />}
914   />
915   <Route path="leaderboard" element={<LeaderboardPage />} />
916   <Route
917     path="onboarding/complete-profile"
918     element={<CompleteProfilePage />}
919   />
920   <Route path="onboarding" element={<OnboardingWizardPage />} />
921   <Route path="habits" element={<HabitHeatmapPage />} />
922   <Route path="habits/analytics" element={<HabitAnalyticsPage />} />
923   <Route path="planner" element={<WeeklyPlannerPage />} />
924   <Route
925     path="planner/starter-week"
926     element={<StarterWeekPlanPage />}
927   />
928   <Route path="today" element={<TodayViewPage />} />
929   <Route
930     path="settings/reassessment"
931     element={<ReassessmentPage />}
932   />
933   <Route
934     path="quizzes/:quizId/adaptive"
935     element={<AdaptiveQuizSession />}
936   />
937   <Route
938     path="quizzes/:quizId/review/:attemptId"
939     element={<PostQuizReview />}
940   />
941   <Route
942     path="courses/:courseId/recovery/:cloId"
943     element={<MasteryRecoveryPage />}
944   />
945   <Route path="settings/profile" element={<ProfileSettingsPage />} />
946   <Route path="xp-history" element={<XPHistory />} />
947   <Route path="portfolio" element={<StudentPortfolio />} />
948   <Route path="calendar" element={<CalendarView />} />
949   <Route path="timetable" element={<TimetableView />} />
950   <Route
951     path="notification-preferences"
952     element={<NotificationPreferences />}
953   />
954   <Route path="sessions" element={<SessionManagement />} />
955   <Route path="surveys" element={<SurveyResponsePage />} />
956   <Route
957     path="announcements/:announcementId"
958     element={<StudentAnnouncementDetail />}
959   />
960   <Route path="courses" element={<StudentCoursesListPage />} />
961   <Route path="courses/:courseId" element={<StudentCourseDetail />} />
962   <Route path="progress" element={<StudentProgressPage />} />

```

```

963 | <Route path="progress/clos" element={<CLOProgress />} />
964 | <Route path="learning-path" element={<LearningPathPage />} />
965 | <Route path="badges" element={<StudentBadgesPage />} />
966 | <Route path="profile" element={<StudentProfilePage />} />
967 | <Route path="learning-profile" element={<LearningProfilePage />} />
968 | <Route path="journal" element={<StudentJournalPage />} />
969 | <Route path="transcript" element={<StudentTranscriptPage />} />
970 | <Route path="fees" element={<StudentFeesPage />} />
971 | <Route path="notifications" element={<NotificationsFeedPage />} />
972 | <Route
973 |   path="courses/:courseId/materials/:materialId"
974 |   element={<StudentCourseDetail />}
975 | />
976 | <Route
977 |   path="courses/:courseId/discussions"
978 |   element={<DiscussionForum />}
979 | />
980 | <Route
981 |   path="courses/:courseId/discussions/:threadId"
982 |   element={<ThreadDetail />}
983 | />
984 | <Route path="challenges" element={<ChallengeListView />} />
985 | <Route path="challenges/list" element={<ChallengeListPage />} />
986 | <Route path="challenges/:id" element={<ChallengeDetailPage />} />
987 | <Route path="tutor" element={<TutorPage />} />
988 | <Route path="tutor/:conversationId" element={<TutorPage />} />
989 | <Route path="team" element={<StudentTeamPage />} />
990 | <Route path="teams/:teamId" element={<TeamProfilePage />} />
991 | <Route path="teams/new" element={<CreateTeamPage />} />
992 | <Route path="marketplace" element={<StudentMarketplacePage />} />
993 | <Route
994 |   path="marketplace/my-items"
995 |   element={<StudentMyItemsPage />}
996 | />
997 | <Route
998 |   path="marketplace/history"
999 |   element={<StudentTransactionHistoryPage />}
1000 | />
1001 | <Route path="content" element={<StudentContentPage />} />
1002 | </Route>
1003 |
1004 | {/ * Student focus mode (full-screen, outside StudentLayout) */}
1005 | <Route
1006 |   path="/student/focus/:sessionId"
1007 |   element={
1008 |     <RouteGuard allowedRoles={["student"]} >
1009 |       <FocusModePage />
1010 |     </RouteGuard>
1011 |   }
1012 | />
1013 |
1014 | {/ * Parent routes */}
1015 | <Route
1016 |   path="/parent/"
1017 |   element={
1018 |     <RouteGuard allowedRoles={["parent"]} >
1019 |       <ParentLayout />
1020 |     </RouteGuard>
1021 |   }
1022 | >
1023 |   <Route
1024 |     index
1025 |     element={<Navigate to="/parent/dashboard" replace />}
1026 |   />
1027 |   <Route path="dashboard" element={<ParentDashboard />} />
1028 |   <Route
1029 |     path="notifications"
1030 |     element={<ParentCommunicationsPage />}
1031 |   />
1032 |   <Route
1033 |     path="communications"
1034 |     element={<ParentCommunicationsPage />}
1035 |   />
1036 |   <Route path="children" element={<ParentChildrenPage />} />
1037 |   <Route path="support" element={<ParentSupportPage />} />
1038 |   <Route path="progress" element={<ParentProgressPage />} />
1039 |   <Route path="attendance" element={<ParentAttendancePage />} />
1040 |   <Route path="fees" element={<ParentFeesPage />} />
1041 |   <Route path="planner" element={<ParentPlannerView />} />
1042 |   <Route path="planner/:studentId" element={<ParentPlannerView />} />
1043 |   <Route path="profile" element={<ParentProfilePage />} />
1044 |   <Route path="settings/profile" element={<ParentProfilePage />} />
1045 | </Route>
1046 |
1047 | {/ * Root redirect */}
1048 | <Route path="/" element={<Navigate to="/login" replace />} />
1049 |
1050 | {/ * Catch-all – friendly 404 (task 1.4) */}
1051 | <Route
1052 |   path=""
1053 |   element={
1054 |     <PublicMain>
1055 |       <NotFoundPage />
1056 |     </PublicMain>
1057 |   }
1058 | />
1059 | </Routes>
1060 | </Suspense>
1061 | </ErrorBoundary>
1062 | </div>
1063 | );
1064 |
1065 | export default AppRouter;
1066 |

```

FILE: src/router/RouteGuard.tsx

TYPE: .tsx | LINES: 1-43 | SHA256: c360544903bc7ad99c328d5c04ac61de66a50d02c3c76ac7c0f0aa688509f453

```
1 | import { Navigate } from "react-router-dom";
2 | import { useAuth } from "@hooks/useAuth";
3 | import { Loader2 } from "lucide-react";
4 | import type { UserRole } from "@types/app";
5 |
6 | const ROLE_DASHBOARD_MAP: Record<UserRole, string> = {
7 |   admin: "/admin/dashboard",
8 |   coordinator: "/coordinator/dashboard",
9 |   teacher: "/teacher/dashboard",
10 |   student: "/student/dashboard",
11 |   parent: "/parent/dashboard",
12 | };
13 |
14 | interface RouteGuardProps {
15 |   allowedRoles: UserRole[];
16 |   children: React.ReactNode;
17 | }
18 |
19 | const RouteGuard = ({ allowedRoles, children }: RouteGuardProps) => {
20 |   const { user, role, isLoading } = useAuth();
21 |
22 |   if (isLoading) {
23 |     return (
24 |       <div className="flex min-h-screen items-center justify-center">
25 |         <Loader2 className="h-8 w-8 animate-spin text-blue-600" />
26 |       </div>
27 |     );
28 |   }
29 |
30 |   if (!user) {
31 |     return <Navigate to="/login" replace />;
32 |   }
33 |
34 |   if (!role || !allowedRoles.includes(role)) {
35 |     const redirectPath = role ? ROLE_DASHBOARD_MAP[role] : "/login";
36 |     return <Navigate to={redirectPath} replace />;
37 |   }
38 |
39 |   return <>{children}</>;
40 | };
41 |
42 | export default RouteGuard;
43 |
```

FILE: src/stores/tourStore.ts

TYPE: .ts | LINES: 1-141 | SHA256: f473e485a3daa2a409c2cc7d7f1027bcff40e65f4c4e0a7f96902da30f9622de

```
1 | import { create } from "zustand";
2 | import type { UserRole } from "@types/app";
3 | import type { AuthContextValue } from "@providers/AuthProvider";
4 | import { supabase } from "@lib/supabase";
5 |
6 | /**
7 |  * Tour store state and actions
8 |  *
9 |  * Manages the guided tour lifecycle:
10 |  * - tourActive: whether a tour is currently running
11 |  * - currentRoleTourId: which role's tour is active (null if none)
12 |  * - tourFeatureFlag: global feature flag (defaults to false, flipped to true in Task 90)
13 |  * - start(role): begin the tour for a specific role
14 |  * - skip(): dismiss the current tour
15 |  * - complete(role): mark the tour as completed for a role
16 |  */
17 | interface TourStore {
18 |   tourActive: boolean;
19 |   currentRoleTourId: UserRole | null;
20 |   tourFeatureFlag: boolean;
21 |   start: (role: UserRole) => void;
22 |   skip: () => void;
23 |   complete: (role: UserRole) => void;
24 |   _setTourFeatureFlag: (flag: boolean) => void;
25 | }
26 |
27 | /**
28 |  * Create the Zustand tour store
29 |  *
30 |  * Persistence strategy:
31 |  * - tourFeatureFlag: localStorage (key: 'tour-feature-flag')
32 |  * - Tour completion: profiles.tour_completed_at (synced via subscribe-to-authStore bridge)
33 |  *
34 |  * Feature flag lifecycle:
35 |  * - Defaults to false throughout Phases 2, 3, 4 (so tour doesn't compete with design-system fixes)
36 |  * - Flipped to true globally in Task 90 (Phase 5) after all surfaces adopt TopBar/WelcomeHero/EmptyState
37 |  * - Once true, tour launches on first login per role (when profiles.tour_completed_at is null)
38 |  */
39 | export const useTourStore = create<TourStore>((set) => {
40 |   // Initialize tourFeatureFlag from localStorage
41 |   // Task 90: Default is now `true`. If a user previously stored `false`,
42 |   // upgrade them to `true` on next hydrate (localStorage migration).
43 |   const storedFeatureFlag = (() => {
44 |     if (typeof localStorage === "undefined") return true;
45 |     const stored = localStorage.getItem("tour-feature-flag");
46 |     // If never set, or explicitly set to 'false' (pre-Task-90 default), upgrade to true
47 |     if (stored === null || stored === "false") {
48 |       localStorage.setItem("tour-feature-flag", "true");
49 |       return true;
50 |     }
51 |     return stored === "true";
52 |   })();
53 |
```

```

54 | return {
55 |   tourActive: false,
56 |   currentRoleTourId: null,
57 |   tourFeatureFlag: storedFeatureFlag,
58 |
59 |   start: (role: UserRole) => {
60 |     set({ tourActive: true, currentRoleTourId: role });
61 |   },
62 |
63 |   skip: () => {
64 |     set({ tourActive: false, currentRoleTourId: null });
65 |   },
66 |
67 |   complete: (_role: UserRole) => {
68 |     set({ tourActive: false, currentRoleTourId: null });
69 |     // Persist completion to database via the auth bridge
70 |     // (see setupTourAuthBridge below)
71 |   },
72 |
73 |   _setTourFeatureFlag: (flag: boolean) => {
74 |     set({ tourFeatureFlag: flag });
75 |     // Persist to localStorage
76 |     if (typeof localStorage !== "undefined") {
77 |       localStorage.setItem("tour-feature-flag", flag ? "true" : "false");
78 |     }
79 |   },
80 | };
81 | });
82 |
83 | /**
84 |  * Bridge: subscribe to auth state and sync tour_completed_at to Supabase
85 |  *
86 |  * This function should be called once during app initialization (e.g., in a root effect)
87 |  * to establish the bidirectional sync between the store and the database.
88 |  *
89 |  * Flow:
90 |  * 1. When user authenticates, check if they have completed the tour (profiles.tour_completed_at)
91 |  * 2. When user completes the tour, persist the timestamp to profiles.tour_completed_at
92 |  * 3. When user signs out, reset tour state
93 |  */
94 | export const setupTourAuthBridge = (auth: AuthContextValue) => {
95 |   // When auth state changes, check if tour is already completed
96 |   if (auth.user && auth.profile) {
97 |     // If tour_completed_at is set, the user has already completed the tour
98 |     // The tour will not launch on subsequent logins
99 |     if (auth.profile.tour_completed_at) {
100 |       useTourStore.setState({ tourActive: false, currentRoleTourId: null });
101 |     }
102 |   }
103 |
104 |   // Subscribe to tour completion and persist to Supabase when authenticated
105 |   let previousTourActive = useTourStore.getState().tourActive;
106 |   let previousRoleTourId = useTourStore.getState().currentRoleTourId;
107 |
108 |   const unsubscribe = useTourStore.subscribe((state) => {
109 |     // Detect when tour transitions from active to inactive (completion or skip)
110 |     const tourJustCompleted =
111 |       previousTourActive === true &&
112 |       state.tourActive === false &&
113 |       previousRoleTourId !== null;
114 |
115 |     if (tourJustCompleted && auth.user) {
116 |       previousTourActive = state.tourActive;
117 |       previousRoleTourId = state.currentRoleTourId;
118 |
119 |       // Fire-and-forget: persist tour completion to database
120 |       (async () => {
121 |         try {
122 |           const { error } = await supabase
123 |             .from("profiles")
124 |             .update({ tour_completed_at: new Date().toISOString() })
125 |             .eq("id", auth.user!.id);
126 |           if (error) {
127 |             console.error("Failed to persist tour completion:", error);
128 |           }
129 |         } catch (error) {
130 |           console.error("Failed to persist tour completion:", error);
131 |         }
132 |       })();
133 |     }
134 |
135 |     previousTourActive = state.tourActive;
136 |     previousRoleTourId = state.currentRoleTourId;
137 |   });
138 |
139 |   return unsubscribe;
140 | };
141 |

```

FILE: src/styles/rtl.css

TYPE: .css | LINES: 1-61 | SHA256: a9240664d23dfc2eea473f023dc16ff1d21e961a8cad8eeec6ec17952846df39

```

1 | /* Task 81.4: RTL-aware CSS utilities */
2 |
3 | /* Mirror horizontal padding and margins for RTL */
4 | [dir="rtl"] .ltr\:pl-3 {
5 |   padding-right: 0.75rem;
6 |   padding-left: 0;
7 | }
8 | [dir="rtl"] .ltr\:pr-3 {
9 |   padding-left: 0.75rem;
10 |   padding-right: 0;
11 | }
12 | [dir="rtl"] .ltr\:ml-2 {

```



```

13 |     margin-right: 0.5rem;
14 |     margin-left: 0;
15 | }
16 | [dir="rtl"] .ltr\:mr-2 {
17 |     margin-left: 0.5rem;
18 |     margin-right: 0;
19 | }
20 |
21 | /* Sidebar moves to right side in RTL */
22 | [dir="rtl"] .flex.h-screen > aside {
23 |     order: 1;
24 |     border-left: 1px solid;
25 |     border-right: 0;
26 | }
27 | [dir="rtl"] .flex.h-screen > main {
28 |     order: 0;
29 | }
30 |
31 | /* Mirror flex direction */
32 | [dir="rtl"] .rtl\:flex-row-reverse {
33 |     flex-direction: row-reverse;
34 | }
35 |
36 | /* Mirror border-radius */
37 | [dir="rtl"] .ltr\:rounded-l-lg {
38 |     border-radius: 0 0.5rem 0.5rem 0;
39 | }
40 | [dir="rtl"] .ltr\:rounded-r-lg {
41 |     border-radius: 0.5rem 0 0 0.5rem;
42 | }
43 |
44 | /* Mirror text alignment */
45 | [dir="rtl"] .ltr\:text-left {
46 |     text-align: right;
47 | }
48 | [dir="rtl"] .ltr\:text-right {
49 |     text-align: left;
50 | }
51 |
52 | /* Mirror absolute positioning */
53 | [dir="rtl"] .ltr\:left-3 {
54 |     right: 0.75rem;
55 |     left: auto;
56 | }
57 | [dir="rtl"] .ltr\:right-3 {
58 |     left: 0.75rem;
59 |     right: auto;
60 | }
61 |

```

FILE: src/test/setup.ts

TYPE: .ts | LINES: 1-2 | SHA256: 90ec9100c29e008c3d9194acd818e2cfa6dc6e177154bc8e10c5959aa35619ed

```

1 | import "@testing-library/jest-dom";
2 |

```

FILE: src/types/app.ts

TYPE: .ts | LINES: 1-654 | SHA256: 25931b5098c41773ea8da4005f2377a001c92a3cb4a930ccca20082d27beffc7

```

1 | // =====
2 | // Edeviser Platform – Shared Type Definitions
3 | // =====
4 |
5 | // -----
6 | // Core Types
7 | // -----
8 |
9 | export type UserRole =
10 |     | "admin"
11 |     | "coordinator"
12 |     | "teacher"
13 |     | "student"
14 |     | "parent";
15 |
16 | export interface Profile {
17 |     id: string;
18 |     email: string;
19 |     full_name: string;
20 |     role: UserRole;
21 |     institution_id: string;
22 |     avatar_url: string | null;
23 |     is_active: boolean;
24 |     onboarding_completed: boolean;
25 |     portfolio_public: boolean;
26 |     theme_preference: string;
27 |     language_preference: string;
28 |     preferred_language?: string;
29 |     notification_preferences: unknown;
30 |     last_seen_at: string | null;
31 |     tos_accepted_at: string | null;
32 |     tour_completed_at: string | null;
33 |     status: string;
34 |     created_at: string;
35 |     // Staff academic-profile fields (migration 20260823000001). Optional: absent
36 |     // on existing rows and not selected by AuthProvider – the coordinator "Me"
37 |     // page reads them via useCoordinatorAcademicProfile and renders a placeholder
38 |     // when unset.
39 |     department?: string | null;
40 |     designation?: string | null;
41 |     academic_rank?: string | null;
42 |     highest_degree?: string | null;
43 |     years_experience?: number | null;
44 | }
45 |

```

```

46 | export interface AuthResult {
47 |     success: boolean;
48 |     error?: string;
49 |     redirectTo?: string;
50 | }
51 |
52 | export interface Program {
53 |     id: string;
54 |     name: string;
55 |     code: string;
56 |     description: string | null;
57 |     institution_id: string;
58 |     coordinator_id: string | null;
59 |     department_id: string | null;
60 |     is_active: boolean;
61 |     created_at: string;
62 | }
63 |
64 | export interface Course {
65 |     id: string;
66 |     name: string;
67 |     code: string;
68 |     program_id: string;
69 |     semester: string;
70 |     semester_id: string | null;
71 |     teacher_id: string | null;
72 |     academic_year: string;
73 |     is_active: boolean;
74 |     created_at: string;
75 | }
76 |
77 | export interface LearningOutcome {
78 |     id: string;
79 |     type: "ILO" | "PLO" | "CLO";
80 |     title: string;
81 |     description: string | null;
82 |     institution_id: string;
83 |     program_id: string | null;
84 |     course_id: string | null;
85 |     blooms_level: BloomsLevel | null;
86 |     sort_order: number;
87 |     created_by: string | null;
88 |     created_at: string;
89 |     updated_at: string;
90 | }
91 |
92 | export type BloomsLevel =
93 |     | "remembering"
94 |     | "understanding"
95 |     | "applying"
96 |     | "analyzing"
97 |     | "evaluating"
98 |     | "creating";
99 |
100 | export type AttainmentLevel =
101 |     | "Excellent"
102 |     | "Satisfactory"
103 |     | "Developing"
104 |     | "Not_Yet";
105 |
106 | export const AttainmentThresholds = {
107 |     Excellent: 85,
108 |     Satisfactory: 70,
109 |     Developing: 50,
110 | } as const;
111 |
112 | // -----
113 | // Gamification Types
114 | // -----
115 |
116 | export type XPSource =
117 |     | "login"
118 |     | "submission"
119 |     | "grade"
120 |     | "journal"
121 |     | "streak_milestone"
122 |     | "perfect_day"
123 |     | "first_attempt_bonus"
124 |     | "perfect_rubric"
125 |     | "badge_earned"
126 |     | "level_up"
127 |     | "streak_freeze_purchase"
128 |     | "discussion_question"
129 |     | "discussion_answer"
130 |     | "survey_completion"
131 |     | "quiz_completion"
132 |     | "onboarding_personality"
133 |     | "onboarding_learning_style"
134 |     | "onboarding_baseline"
135 |     | "onboarding_complete"
136 |     | "onboarding_self_efficacy"
137 |     | "onboarding_study_strategy"
138 |     | "micro_assessment"
139 |     | "profile_complete"
140 |     | "starter_session_complete"
141 |     | "wellness_habit"
142 |     | "practice_quiz"
143 |     | "study_session"
144 |     | "planner_task"
145 |     | "session_reflection"
146 |     | "weekly_goal"
147 |     | "tutor_engagement"
148 |     | "tutor_rating";
149 |

```

```

150 | export type XPSchedule = Record<XPSource, number>;
151 |
152 | export interface BadgeDefinition {
153 |     id: string;
154 |     name: string;
155 |     emoji: string;
156 |     description: string;
157 |     condition: string;
158 |     is_mystery: boolean;
159 | }
160 |
161 | export type BadgeCatalog = BadgeDefinition[];
162 |
163 | export interface LevelThreshold {
164 |     level: number;
165 |     xpRequired: number;
166 |     title: string;
167 | }
168 |
169 | export type LevelThresholds = LevelThreshold[];
170 |
171 | export type HabitType = "login" | "submit" | "journal" | "read";
172 |
173 | export type LearningPathNodeType = "assignment" | "quiz" | "milestone";
174 |
175 | export interface BonusXPEventType {
176 |     id: string;
177 |     title: string;
178 |     multiplier: number;
179 |     start_at: string;
180 |     end_at: string;
181 |     is_active: boolean;
182 | }
183 |
184 | export type ActivityLogEventType =
185 |     | "login"
186 |     | "page_view"
187 |     | "submission"
188 |     | "journal"
189 |     | "streak_break"
190 |     | "assignment_view"
191 |     | "grading_start"
192 |     | "grading_end"
193 |     | "material_view"
194 |     | "announcement_view"
195 |     | "discussion_post"
196 |     | "quiz_attempt"
197 |     | "attendance_marked";
198 |
199 | // -----
200 | // AI Co-Pilot Types
201 | // -----
202 |
203 | export interface ModuleSuggestion {
204 |     id: string;
205 |     student_id: string;
206 |     clo_id: string;
207 |     suggestion_text: string;
208 |     priority: number;
209 |     created_at: string;
210 | }
211 |
212 | export interface AtRiskPrediction {
213 |     id: string;
214 |     student_id: string;
215 |     risk_score: number;
216 |     risk_factors: Record<string, unknown>;
217 |     predicted_at: string;
218 | }
219 |
220 | export interface FeedbackDraft {
221 |     id: string;
222 |     submission_id: string;
223 |     draft_text: string;
224 |     teacher_id: string;
225 |     created_at: string;
226 | }
227 |
228 | export interface AIFeedbackEntry {
229 |     id: string;
230 |     student_id: string;
231 |     feedback_type: string;
232 |     content: string;
233 |     accepted: boolean;
234 |     created_at: string;
235 | }
236 |
237 | // -----
238 | // Portfolio & Enhancement Types
239 | // -----
240 |
241 | export interface PortfolioEntry {
242 |     type: string;
243 |     title: string;
244 |     description: string;
245 |     evidence_id?: string;
246 |     badge_id?: string;
247 |     created_at: string;
248 | }
249 |
250 | export interface StreakFreeze {
251 |     available: number;
252 |     max: number;
253 |     cost_xp: number;

```

```

254 | }
255 |
256 | export interface OnboardingStep {
257 |   id: string;
258 |   role: UserRole;
259 |   step_number: number;
260 |   title: string;
261 |   description: string;
262 |   completed: boolean;
263 | }
264 |
265 | export interface ChecklistItem {
266 |   id: string;
267 |   label: string;
268 |   completed: boolean;
269 |   route?: string;
270 | }
271 |
272 | export type ThemePreference = "light" | "dark" | "system";
273 |
274 | export interface GradingStats {
275 |   total_graded: number;
276 |   avg_time_seconds: number;
277 |   graded_today: number;
278 |   pending_count: number;
279 | }
280 |
281 | // -----
282 | // Utility Types
283 | // -----
284 |
285 | export interface DraftManagerEntry {
286 |   key: string;
287 |   content: unknown;
288 |   updated_at: string;
289 | }
290 |
291 | export interface OfflineQueueItem {
292 |   id: string;
293 |   type: string;
294 |   payload: unknown;
295 |   created_at: string;
296 |   retries: number;
297 | }
298 |
299 | export interface NotificationBatcherConfig {
300 |   window_hours: number;
301 |   daily_limit: number;
302 | }
303 |
304 | export interface ExportDataRequest {
305 |   type: string;
306 |   format: "json" | "csv";
307 |   filters?: Record<string, unknown>;
308 | }
309 |
310 | // -----
311 | // Institutional Management Types
312 | // -----
313 |
314 | export interface Semester {
315 |   id: string;
316 |   institution_id: string;
317 |   name: string;
318 |   code: string;
319 |   start_date: string;
320 |   end_date: string;
321 |   is_active: boolean;
322 |   created_at: string;
323 | }
324 |
325 | export interface CourseSection {
326 |   id: string;
327 |   course_id: string;
328 |   section_code: string;
329 |   teacher_id: string;
330 |   semester_id: string;
331 |   max_capacity: number;
332 | }
333 |
334 | export interface Survey {
335 |   id: string;
336 |   course_id: string;
337 |   title: string;
338 |   is_anonymous: boolean;
339 |   status: string;
340 |   created_by: string;
341 | }
342 |
343 | export interface SurveyQuestion {
344 |   id: string;
345 |   survey_id: string;
346 |   question_text: string;
347 |   question_type: string;
348 |   order_index: number;
349 | }
350 |
351 | export interface CQIPlan {
352 |   id: string;
353 |   program_id: string;
354 |   semester_id: string;
355 |   title: string;
356 |   findings: string;
357 |   actions: string;

```

```

358 |     status: string;
359 | }
360 |
361 | export interface AttainmentThresholdsConfig {
362 |     excellent: number;
363 |     satisfactory: number;
364 |     developing: number;
365 | }
366 |
367 | export interface GradeScale {
368 |     letter: string;
369 |     min_percent: number;
370 |     max_percent: number;
371 |     gpa_points: number;
372 | }
373 |
374 | export type AccreditationBody =
375 |     | "HEC"
376 |     | "QQA"
377 |     | "ABET"
378 |     | "NCAAA"
379 |     | "AACSB"
380 |     | "Generic";
381 |
382 | export interface LeagueThresholdsConfig {
383 |     bronze: number;
384 |     silver: number;
385 |     gold: number;
386 |     diamond: number;
387 | }
388 |
389 | export interface InstitutionSettings {
390 |     id: string;
391 |     institution_id: string;
392 |     attainment_thresholds: AttainmentThresholdsConfig;
393 |     success_threshold: number;
394 |     accreditation_body: AccreditationBody;
395 |     grade_scales: GradeScale[];
396 |     streak_sabbatical_enabled: boolean;
397 |     league_thresholds?: LeagueThresholdsConfig;
398 |     default_language?: string;
399 |     created_at: string;
400 | }
401 |
402 | export interface ProgramAccreditation {
403 |     id: string;
404 |     program_id: string;
405 |     accreditation_body: string;
406 |     framework_version: string | null;
407 |     accreditation_date: string | null;
408 |     next_review_date: string | null;
409 |     status: "active" | "expired" | "pending";
410 |     created_at: string;
411 | }
412 |
413 | export const DEFAULT_ATTAINMENT_THRESHOLDS: AttainmentThresholdsConfig = {
414 |     excellent: 85,
415 |     satisfactory: 70,
416 |     developing: 50,
417 | };
418 |
419 | export const DEFAULT_GRADE_SCALES: GradeScale[] = [
420 |     { letter: "A", min_percent: 85, max_percent: 100, gpa_points: 4.0 },
421 |     { letter: "B", min_percent: 70, max_percent: 84, gpa_points: 3.0 },
422 |     { letter: "C", min_percent: 55, max_percent: 69, gpa_points: 2.0 },
423 |     { letter: "D", min_percent: 50, max_percent: 54, gpa_points: 1.0 },
424 |     { letter: "F", min_percent: 0, max_percent: 49, gpa_points: 0.0 },
425 | ];
426 |
427 | export interface Announcement {
428 |     id: string;
429 |     course_id: string;
430 |     title: string;
431 |     content: string;
432 |     priority: string;
433 |     created_by: string;
434 |     created_at: string;
435 | }
436 |
437 | export interface CourseModule {
438 |     id: string;
439 |     course_id: string;
440 |     title: string;
441 |     order_index: number;
442 |     is_published: boolean;
443 | }
444 |
445 | export interface CourseMaterial {
446 |     id: string;
447 |     module_id: string;
448 |     title: string;
449 |     type: string;
450 |     file_url: string;
451 |     order_index: number;
452 | }
453 |
454 | export interface DiscussionThread {
455 |     id: string;
456 |     course_id: string;
457 |     title: string;
458 |     content: string;
459 |     author_id: string;
460 |     is_pinned: boolean;
461 |     created_at: string;

```

```

462 | }
463 |
464 | export interface DiscussionReply {
465 |     id: string;
466 |     thread_id: string;
467 |     content: string;
468 |     author_id: string;
469 |     created_at: string;
470 | }
471 |
472 | export interface ClassSession {
473 |     id: string;
474 |     course_id: string;
475 |     date: string;
476 |     start_time: string;
477 |     end_time: string;
478 |     topic: string;
479 | }
480 |
481 | export interface AttendanceRecord {
482 |     id: string;
483 |     session_id: string;
484 |     student_id: string;
485 |     status: string;
486 |     marked_by: string;
487 | }
488 |
489 | export interface Quiz {
490 |     id: string;
491 |     course_id: string;
492 |     title: string;
493 |     time_limit_minutes: number;
494 |     max_attempts: number;
495 |     is_published: boolean;
496 | }
497 |
498 | export interface QuizQuestion {
499 |     id: string;
500 |     quiz_id: string;
501 |     question_text: string;
502 |     question_type: string;
503 |     points: number;
504 |     options: unknown;
505 | }
506 |
507 | export interface QuizAttempt {
508 |     id: string;
509 |     quiz_id: string;
510 |     student_id: string;
511 |     score: number;
512 |     started_at: string;
513 |     completed_at: string;
514 | }
515 |
516 | export interface GradeCategory {
517 |     id: string;
518 |     course_id: string;
519 |     name: string;
520 |     weight_percent: number;
521 | }
522 |
523 | export interface TimetableSlot {
524 |     id: string;
525 |     course_id: string;
526 |     day_of_week: string;
527 |     start_time: string;
528 |     end_time: string;
529 |     room: string;
530 | }
531 |
532 | export interface AcademicCalendarEvent {
533 |     id: string;
534 |     institution_id: string;
535 |     title: string;
536 |     start_date: string;
537 |     end_date: string;
538 |     event_type: string;
539 | }
540 |
541 | export interface Department {
542 |     id: string;
543 |     institution_id: string;
544 |     name: string;
545 |     code: string;
546 |     head_of_department_id: string | null;
547 |     head_id: string;
548 |     created_at: string;
549 | }
550 |
551 | export interface Transcript {
552 |     student_id: string;
553 |     courses: unknown[];
554 |     gpa: number;
555 |     generated_at: string;
556 | }
557 |
558 | export interface CourseFile {
559 |     id: string;
560 |     course_id: string;
561 |     file_type: string;
562 |     file_url: string;
563 |     generated_at: string;
564 | }
565 |

```

```

566 | export interface ParentStudentLink {
567 |     id: string;
568 |     parent_id: string;
569 |     student_id: string;
570 |     relationship: string;
571 |     verified: boolean;
572 | }
573 |
574 | export interface FeeStructure {
575 |     id: string;
576 |     institution_id: string;
577 |     name: string;
578 |     amount: number;
579 |     currency: string;
580 |     semester_id: string;
581 | }
582 |
583 | export interface FeePayment {
584 |     id: string;
585 |     student_id: string;
586 |     fee_structure_id: string;
587 |     amount_paid: number;
588 |     status: PaymentStatus;
589 |     paid_at: string;
590 | }
591 |
592 | export type PaymentStatus = "pending" | "paid" | "overdue" | "waived";
593 |
594 | // -----
595 | // Production Types
596 | // -----
597 |
598 | export type LanguagePreference = "en" | "ur" | "ar";
599 |
600 | export interface CookieConsent {
601 |     analytics: boolean;
602 |     marketing: boolean;
603 |     consented_at: string;
604 | }
605 |
606 | export interface ImpersonationSession {
607 |     admin_id: string;
608 |     target_user_id: string;
609 |     started_at: string;
610 |     reason: string;
611 | }
612 |
613 | export interface BulkOperation {
614 |     id: string;
615 |     type: string;
616 |     status: string;
617 |     total_rows: number;
618 |     processed_rows: number;
619 |     errors: unknown[];
620 | }
621 |
622 | export interface GlobalSearchResult {
623 |     type: string;
624 |     id: string;
625 |     title: string;
626 |     subtitle: string;
627 |     url: string;
628 | }
629 |
630 | export interface NotificationPreferences {
631 |     in_app: boolean;
632 |     email: boolean;
633 |     quiet_hours_start?: string;
634 |     quiet_hours_end?: string;
635 | }
636 |
637 | export interface SessionInfo {
638 |     id: string;
639 |     device: string;
640 |     ip: string;
641 |     last_active: string;
642 |     is_current: boolean;
643 | }
644 |
645 | export interface PWACfg {
646 |     cache_version: string;
647 |     offline_routes: string[];
648 | }
649 |
650 | export interface RateLimiterConfig {
651 |     max_requests: number;
652 |     window_seconds: number;
653 | }
654 |

```

FILE: src/types/database.ts

TYPE: .ts | LINES: 1-7591 | SHA256: 2ece4fa958124072879ff88586f6f43d79b28d69d959fee849f7df91ae8839e7

```

1 | export type Json =
2 |   | string
3 |   | number
4 |   | boolean
5 |   | null
6 |   | { [key: string]: Json | undefined }
7 |   | Json[];
8 |
9 | export type Database = {
10 |   // Allows to automatically instantiate createClient with right options
11 |   // instead of createClient<Database, { PostgrestVersion: 'XX' }>(URL, KEY)

```

```

12 |   __InternalSupabase: {
13 |     PostgrestVersion: "14.4";
14 |   };
15 |   graphql_public: {
16 |     Tables: {
17 |       [_ in never]: never;
18 |     };
19 |     Views: {
20 |       [_ in never]: never;
21 |     };
22 |     Functions: {
23 |       graphql: {
24 |         Args: {
25 |           extensions?: Json;
26 |           operationName?: string;
27 |           query?: string;
28 |           variables?: Json;
29 |         };
30 |         Returns: Json;
31 |       };
32 |     };
33 |     Enums: {
34 |       [_ in never]: never;
35 |     };
36 |     CompositeTypes: {
37 |       [_ in never]: never;
38 |     };
39 |   };
40 |   public: {
41 |     Tables: {
42 |       academic_calendar_events: {
43 |         Row: {
44 |           created_at: string;
45 |           end_date: string;
46 |           event_type: string;
47 |           id: string;
48 |           institution_id: string;
49 |           is_recurring: boolean;
50 |           semester_id: string | null;
51 |           start_date: string;
52 |           title: string;
53 |         };
54 |         Insert: {
55 |           created_at?: string;
56 |           end_date: string;
57 |           event_type: string;
58 |           id?: string;
59 |           institution_id: string;
60 |           is_recurring?: boolean;
61 |           semester_id?: string | null;
62 |           start_date: string;
63 |           title: string;
64 |         };
65 |         Update: {
66 |           created_at?: string;
67 |           end_date?: string;
68 |           event_type?: string;
69 |           id?: string;
70 |           institution_id?: string;
71 |           is_recurring?: boolean;
72 |           semester_id?: string | null;
73 |           start_date?: string;
74 |           title?: string;
75 |         };
76 |         Relationships: [
77 |           {
78 |             foreignKeyName: "academic_calendar_events_institution_id_fkey";
79 |             columns: ["institution_id"];
80 |             isOneToOne: false;
81 |             referencedRelation: "institutions";
82 |             referencedColumns: ["id"];
83 |           },
84 |           {
85 |             foreignKeyName: "academic_calendar_events_institution_id_fkey";
86 |             columns: ["institution_id"];
87 |             isOneToOne: false;
88 |             referencedRelation: "institutions_public";
89 |             referencedColumns: ["id"];
90 |           },
91 |           {
92 |             foreignKeyName: "academic_calendar_events_semester_id_fkey";
93 |             columns: ["semester_id"];
94 |             isOneToOne: false;
95 |             referencedRelation: "mv_historical_evidence";
96 |             referencedColumns: ["semester_id"];
97 |           },
98 |           {
99 |             foreignKeyName: "academic_calendar_events_semester_id_fkey";
100 |             columns: ["semester_id"];
101 |             isOneToOne: false;
102 |             referencedRelation: "semesters";
103 |             referencedColumns: ["id"];
104 |           }
105 |         ];
106 |       };
107 |     };
108 |     ai_feedback: {
109 |       Row: {
110 |         created_at: string;
111 |         feedback: string | null;
112 |         id: string;
113 |         student_id: string;
114 |         suggestion_data: Json | null;
115 |         suggestion_text: string;
116 |         suggestion_type: string;

```



```

116 |         validated_outcome: string | null;
117 |     };
118 |     Insert: {
119 |         created_at?: string;
120 |         feedback?: string | null;
121 |         id?: string;
122 |         student_id: string;
123 |         suggestion_data?: Json | null;
124 |         suggestion_text: string;
125 |         suggestion_type: string;
126 |         validated_outcome?: string | null;
127 |     };
128 |     Update: {
129 |         created_at?: string;
130 |         feedback?: string | null;
131 |         id?: string;
132 |         student_id?: string;
133 |         suggestion_data?: Json | null;
134 |         suggestion_text?: string;
135 |         suggestion_type?: string;
136 |         validated_outcome?: string | null;
137 |     };
138 |     Relationships: [
139 |     {
140 |         foreignKeyName: "ai_feedback_student_id_fkey";
141 |         columns: ["student_id"];
142 |         isOneToOne: false;
143 |         referencedRelation: "profiles";
144 |         referencedColumns: ["id"];
145 |     }
146 | ];
147 | };
148 | announcement_attachments: {
149 |     Row: {
150 |         announcement_id: string;
151 |         content_type: string | null;
152 |         created_at: string;
153 |         file_name: string;
154 |         id: string;
155 |         size_bytes: number | null;
156 |         storage_path: string;
157 |     };
158 |     Insert: {
159 |         announcement_id: string;
160 |         content_type?: string | null;
161 |         created_at?: string;
162 |         file_name: string;
163 |         id?: string;
164 |         size_bytes?: number | null;
165 |         storage_path: string;
166 |     };
167 |     Update: {
168 |         announcement_id?: string;
169 |         content_type?: string | null;
170 |         created_at?: string;
171 |         file_name?: string;
172 |         id?: string;
173 |         size_bytes?: number | null;
174 |         storage_path?: string;
175 |     };
176 |     Relationships: [
177 |     {
178 |         foreignKeyName: "announcement_attachments_announcement_id_fkey";
179 |         columns: ["announcement_id"];
180 |         isOneToOne: false;
181 |         referencedRelation: "announcements";
182 |         referencedColumns: ["id"];
183 |     }
184 | ];
185 | };
186 | announcement_reads: {
187 |     Row: {
188 |         announcement_id: string;
189 |         id: string;
190 |         read_at: string;
191 |         student_id: string;
192 |     };
193 |     Insert: {
194 |         announcement_id: string;
195 |         id?: string;
196 |         read_at?: string;
197 |         student_id: string;
198 |     };
199 |     Update: {
200 |         announcement_id?: string;
201 |         id?: string;
202 |         read_at?: string;
203 |         student_id?: string;
204 |     };
205 |     Relationships: [
206 |     {
207 |         foreignKeyName: "announcement_reads_announcement_id_fkey";
208 |         columns: ["announcement_id"];
209 |         isOneToOne: false;
210 |         referencedRelation: "announcements";
211 |         referencedColumns: ["id"];
212 |     },
213 |     {
214 |         foreignKeyName: "announcement_reads_student_id_fkey";
215 |         columns: ["student_id"];
216 |         isOneToOne: false;
217 |         referencedRelation: "profiles";
218 |         referencedColumns: ["id"];
219 |     }

```

```

220 |     ];
221 | };
222 | announcements: {
223 |     Row: {
224 |         author_id: string;
225 |         content: string;
226 |         course_id: string;
227 |         created_at: string;
228 |         id: string;
229 |         is_pinned: boolean;
230 |         search_vector: unknown;
231 |         title: string;
232 |         updated_at: string;
233 |     };
234 |     Insert: {
235 |         author_id: string;
236 |         content: string;
237 |         course_id: string;
238 |         created_at?: string;
239 |         id?: string;
240 |         is_pinned?: boolean;
241 |         search_vector?: unknown;
242 |         title: string;
243 |         updated_at?: string;
244 |     };
245 |     Update: {
246 |         author_id?: string;
247 |         content?: string;
248 |         course_id?: string;
249 |         created_at?: string;
250 |         id?: string;
251 |         is_pinned?: boolean;
252 |         search_vector?: unknown;
253 |         title?: string;
254 |         updated_at?: string;
255 |     };
256 |     Relationships: [
257 |         {
258 |             foreignKeyName: "announcements_author_id_fkey";
259 |             columns: ["author_id"];
260 |             isOneToOne: false;
261 |             referencedRelation: "profiles";
262 |             referencedColumns: ["id"];
263 |         },
264 |         {
265 |             foreignKeyName: "announcements_course_id_fkey";
266 |             columns: ["course_id"];
267 |             isOneToOne: false;
268 |             referencedRelation: "courses";
269 |             referencedColumns: ["id"];
270 |         }
271 |     ];
272 | };
273 | assignments: {
274 |     Row: {
275 |         clo_weights: Json;
276 |         course_id: string;
277 |         created_at: string;
278 |         created_by: string | null;
279 |         description: string | null;
280 |         due_date: string;
281 |         id: string;
282 |         is_late_allowed: boolean;
283 |         late_window_hours: number;
284 |         prerequisites: Json | null;
285 |         rubric_id: string | null;
286 |         search_vector: unknown;
287 |         title: string;
288 |         total_marks: number;
289 |         tutor_autonomy_level: string | null;
290 |         type: Database["public"]["Enums"]["assignment_type"];
291 |     };
292 |     Insert: {
293 |         clo_weights?: Json;
294 |         course_id: string;
295 |         created_at?: string;
296 |         created_by?: string | null;
297 |         description?: string | null;
298 |         due_date: string;
299 |         id?: string;
300 |         is_late_allowed?: boolean;
301 |         late_window_hours?: number;
302 |         prerequisites?: Json | null;
303 |         rubric_id?: string | null;
304 |         search_vector?: unknown;
305 |         title: string;
306 |         total_marks: number;
307 |         tutor_autonomy_level?: string | null;
308 |         type?: Database["public"]["Enums"]["assignment_type"];
309 |     };
310 |     Update: {
311 |         clo_weights?: Json;
312 |         course_id?: string;
313 |         created_at?: string;
314 |         created_by?: string | null;
315 |         description?: string | null;
316 |         due_date?: string;
317 |         id?: string;
318 |         is_late_allowed?: boolean;
319 |         late_window_hours?: number;
320 |         prerequisites?: Json | null;
321 |         rubric_id?: string | null;
322 |         search_vector?: unknown;
323 |         title?: string;

```

```

324 |         total_marks?: number;
325 |         tutor_autonomy_level?: string | null;
326 |         type?: Database["public"]["Enums"]["assignment_type"];
327 |     };
328 |     Relationships: [
329 |         {
330 |             foreignKeyName: "assignments_course_id_fkey";
331 |             columns: ["course_id"];
332 |             isOneToOne: false;
333 |             referencedRelation: "courses";
334 |             referencedColumns: ["id"];
335 |         },
336 |         {
337 |             foreignKeyName: "assignments_created_by_fkey";
338 |             columns: ["created_by"];
339 |             isOneToOne: false;
340 |             referencedRelation: "profiles";
341 |             referencedColumns: ["id"];
342 |         },
343 |         {
344 |             foreignKeyName: "assignments_rubric_id_fkey";
345 |             columns: ["rubric_id"];
346 |             isOneToOne: false;
347 |             referencedRelation: "rubrics";
348 |             referencedColumns: ["id"];
349 |         }
350 |     ];
351 | };
352 | attendance_records: {
353 |     Row: {
354 |         created_at: string;
355 |         id: string;
356 |         marked_by: string;
357 |         session_id: string;
358 |         status: string;
359 |         student_id: string;
360 |     };
361 |     Insert: {
362 |         created_at?: string;
363 |         id?: string;
364 |         marked_by: string;
365 |         session_id: string;
366 |         status: string;
367 |         student_id: string;
368 |     };
369 |     Update: {
370 |         created_at?: string;
371 |         id?: string;
372 |         marked_by?: string;
373 |         session_id?: string;
374 |         status?: string;
375 |         student_id?: string;
376 |     };
377 |     Relationships: [
378 |         {
379 |             foreignKeyName: "attendance_records_marked_by_fkey";
380 |             columns: ["marked_by"];
381 |             isOneToOne: false;
382 |             referencedRelation: "profiles";
383 |             referencedColumns: ["id"];
384 |         },
385 |         {
386 |             foreignKeyName: "attendance_records_session_id_fkey";
387 |             columns: ["session_id"];
388 |             isOneToOne: false;
389 |             referencedRelation: "class_sessions";
390 |             referencedColumns: ["id"];
391 |         },
392 |         {
393 |             foreignKeyName: "attendance_records_student_id_fkey";
394 |             columns: ["student_id"];
395 |             isOneToOne: false;
396 |             referencedRelation: "profiles";
397 |             referencedColumns: ["id"];
398 |         }
399 |     ];
400 | };
401 | audit_findings: {
402 |     Row: {
403 |         audit_run_id: string;
404 |         created_at: string;
405 |         detail: Json | null;
406 |         id: string;
407 |         location_file: string | null;
408 |         location_line: number | null;
409 |         message: string;
410 |         requirement_id: string;
411 |         severity: string;
412 |         stage: string | null;
413 |     };
414 |     Insert: {
415 |         audit_run_id: string;
416 |         created_at?: string;
417 |         detail?: Json | null;
418 |         id?: string;
419 |         location_file?: string | null;
420 |         location_line?: number | null;
421 |         message: string;
422 |         requirement_id: string;
423 |         severity: string;
424 |         stage?: string | null;
425 |     };
426 |     Update: {
427 |         audit_run_id?: string;

```

```

428 |         created_at?: string;
429 |         detail?: Json | null;
430 |         id?: string;
431 |         location_file?: string | null;
432 |         location_line?: number | null;
433 |         message?: string;
434 |         requirement_id?: string;
435 |         severity?: string;
436 |         stage?: string | null;
437 |     };
438 |     Relationships: [
439 |     {
440 |         foreignKeyName: "audit_findings_audit_run_id_fkey";
441 |         columns: ["audit_run_id"];
442 |         isOneToOne: false;
443 |         referencedRelation: "audit_runs";
444 |         referencedColumns: ["id"];
445 |     }
446 | ];
447 | };
448 | audit_logs: {
449 |     Row: {
450 |         action: string;
451 |         actor_id: string;
452 |         created_at: string;
453 |         diff: Json | null;
454 |         id: string;
455 |         institution_id: string | null;
456 |         ip_address: unknown;
457 |         target_id: string | null;
458 |         target_type: string;
459 |     };
460 |     Insert: {
461 |         action: string;
462 |         actor_id: string;
463 |         created_at?: string;
464 |         diff?: Json | null;
465 |         id?: string;
466 |         institution_id?: string | null;
467 |         ip_address?: unknown;
468 |         target_id?: string | null;
469 |         target_type: string;
470 |     };
471 |     Update: {
472 |         action?: string;
473 |         actor_id?: string;
474 |         created_at?: string;
475 |         diff?: Json | null;
476 |         id?: string;
477 |         institution_id?: string | null;
478 |         ip_address?: unknown;
479 |         target_id?: string | null;
480 |         target_type?: string;
481 |     };
482 |     Relationships: [
483 |     {
484 |         foreignKeyName: "audit_logs_actor_id_fkey";
485 |         columns: ["actor_id"];
486 |         isOneToOne: false;
487 |         referencedRelation: "profiles";
488 |         referencedColumns: ["id"];
489 |     },
490 |     {
491 |         foreignKeyName: "audit_logs_institution_id_fkey";
492 |         columns: ["institution_id"];
493 |         isOneToOne: false;
494 |         referencedRelation: "institutions";
495 |         referencedColumns: ["id"];
496 |     },
497 |     {
498 |         foreignKeyName: "audit_logs_institution_id_fkey";
499 |         columns: ["institution_id"];
500 |         isOneToOne: false;
501 |         referencedRelation: "institutions_public";
502 |         referencedColumns: ["id"];
503 |     }
504 | ];
505 | };
506 | audit_runs: {
507 |     Row: {
508 |         blocker_count: number;
509 |         commit_sha: string | null;
510 |         created_at: string;
511 |         critical_count: number;
512 |         env_id: string;
513 |         finished_at: string | null;
514 |         id: string;
515 |         major_count: number;
516 |         migration_head: string | null;
517 |         minor_count: number;
518 |         run_id: string;
519 |         started_at: string;
520 |         trivial_count: number;
521 |         verdict: string;
522 |     };
523 |     Insert: {
524 |         blocker_count?: number;
525 |         commit_sha?: string | null;
526 |         created_at?: string;
527 |         critical_count?: number;
528 |         env_id: string;
529 |         finished_at?: string | null;
530 |         id?: string;
531 |         major_count?: number;

```

```

532 |         migration_head?: string | null;
533 |         minor_count?: number;
534 |         run_id: string;
535 |         started_at?: string;
536 |         trivial_count?: number;
537 |         verdict: string;
538 |     };
539 |     Update: {
540 |         blocker_count?: number;
541 |         commit_sha?: string | null;
542 |         created_at?: string;
543 |         critical_count?: number;
544 |         env_id?: string;
545 |         finished_at?: string | null;
546 |         id?: string;
547 |         major_count?: number;
548 |         migration_head?: string | null;
549 |         minor_count?: number;
550 |         run_id?: string;
551 |         started_at?: string;
552 |         trivial_count?: number;
553 |         verdict?: string;
554 |     };
555 |     Relationships: [];
556 | };
557 | badge_definitions: {
558 |     Row: {
559 |         badge_key: string;
560 |         category: string | null;
561 |         created_at: string;
562 |         description: string;
563 |         emoji: string;
564 |         id: string;
565 |         institution_id: string;
566 |         is_archived: boolean;
567 |         name: string;
568 |         tier_conditions: Json | null;
569 |         updated_at: string;
570 |     };
571 |     Insert: {
572 |         badge_key: string;
573 |         category?: string | null;
574 |         created_at?: string;
575 |         description?: string;
576 |         emoji?: string;
577 |         id?: string;
578 |         institution_id: string;
579 |         is_archived?: boolean;
580 |         name: string;
581 |         tier_conditions?: Json | null;
582 |         updated_at?: string;
583 |     };
584 |     Update: {
585 |         badge_key?: string;
586 |         category?: string | null;
587 |         created_at?: string;
588 |         description?: string;
589 |         emoji?: string;
590 |         id?: string;
591 |         institution_id?: string;
592 |         is_archived?: boolean;
593 |         name?: string;
594 |         tier_conditions?: Json | null;
595 |         updated_at?: string;
596 |     };
597 |     Relationships: [
598 |         {
599 |             foreignKeyName: "badge_definitions_institution_id_fkey";
600 |             columns: ["institution_id"];
601 |             isOneToOne: false;
602 |             referencedRelation: "institutions";
603 |             referencedColumns: ["id"];
604 |         },
605 |         {
606 |             foreignKeyName: "badge_definitions_institution_id_fkey";
607 |             columns: ["institution_id"];
608 |             isOneToOne: false;
609 |             referencedRelation: "institutions_public";
610 |             referencedColumns: ["id"];
611 |         }
612 |     ];
613 | };
614 | badge_spotlight_schedule: {
615 |     Row: {
616 |         category: string;
617 |         created_at: string;
618 |         id: string;
619 |         institution_id: string;
620 |         is_manual: boolean;
621 |         week_start: string;
622 |     };
623 |     Insert: {
624 |         category: string;
625 |         created_at?: string;
626 |         id?: string;
627 |         institution_id: string;
628 |         is_manual?: boolean;
629 |         week_start: string;
630 |     };
631 |     Update: {
632 |         category?: string;
633 |         created_at?: string;
634 |         id?: string;
635 |         institution_id?: string;

```

```

636         is_manual?: boolean;
637         week_start?: string;
638     };
639     Relationships: [
640     {
641         foreignKeyName: "badge_spotlight_schedule_institution_id_fkey";
642         columns: ["institution_id"];
643         isOneToOne: false;
644         referencedRelation: "institutions";
645         referencedColumns: ["id"];
646     },
647     {
648         foreignKeyName: "badge_spotlight_schedule_institution_id_fkey";
649         columns: ["institution_id"];
650         isOneToOne: false;
651         referencedRelation: "institutions_public";
652         referencedColumns: ["id"];
653     }
654     ];
655 };
656 badges: {
657     Row: {
658         archived_at: string | null;
659         awarded_at: string;
660         badge_key: string;
661         badge_name: string;
662         category: string | null;
663         emoji: string;
664         id: string;
665         is_pinned: boolean;
666         scope: string;
667         student_id: string;
668         team_id: string | null;
669         tier: string;
670     };
671     Insert: {
672         archived_at?: string | null;
673         awarded_at?: string;
674         badge_key: string;
675         badge_name: string;
676         category?: string | null;
677         emoji?: string;
678         id?: string;
679         is_pinned?: boolean;
680         scope?: string;
681         student_id: string;
682         team_id?: string | null;
683         tier?: string;
684     };
685     Update: {
686         archived_at?: string | null;
687         awarded_at?: string;
688         badge_key?: string;
689         badge_name?: string;
690         category?: string | null;
691         emoji?: string;
692         id?: string;
693         is_pinned?: boolean;
694         scope?: string;
695         student_id?: string;
696         team_id?: string | null;
697         tier?: string;
698     };
699     Relationships: [
700     {
701         foreignKeyName: "badges_student_id_fkey";
702         columns: ["student_id"];
703         isOneToOne: false;
704         referencedRelation: "profiles";
705         referencedColumns: ["id"];
706     },
707     {
708         foreignKeyName: "badges_team_id_fkey";
709         columns: ["team_id"];
710         isOneToOne: false;
711         referencedRelation: "teams";
712         referencedColumns: ["id"];
713     }
714     ];
715 };
716 baseline_attainment: {
717     Row: {
718         assessment_version: number;
719         clo_id: string;
720         correct_count: number;
721         course_id: string;
722         created_at: string;
723         id: string;
724         question_count: number;
725         score: number;
726         student_id: string;
727     };
728     Insert: {
729         assessment_version?: number;
730         clo_id: string;
731         correct_count: number;
732         course_id: string;
733         created_at?: string;
734         id?: string;
735         question_count: number;
736         score: number;
737         student_id: string;
738     };
739     Update: {

```

```

740 |         assessment_version?: number;
741 |         clo_id?: string;
742 |         correct_count?: number;
743 |         course_id?: string;
744 |         created_at?: string;
745 |         id?: string;
746 |         question_count?: number;
747 |         score?: number;
748 |         student_id?: string;
749 |     };
750 |     Relationships: [
751 |         {
752 |             foreignKeyName: "baseline_attainment_clo_id_fkey";
753 |             columns: ["clo_id"];
754 |             isOneToOne: false;
755 |             referencedRelation: "learning_outcomes";
756 |             referencedColumns: ["id"];
757 |         },
758 |         {
759 |             foreignKeyName: "baseline_attainment_course_id_fkey";
760 |             columns: ["course_id"];
761 |             isOneToOne: false;
762 |             referencedRelation: "courses";
763 |             referencedColumns: ["id"];
764 |         },
765 |         {
766 |             foreignKeyName: "baseline_attainment_student_id_fkey";
767 |             columns: ["student_id"];
768 |             isOneToOne: false;
769 |             referencedRelation: "profiles";
770 |             referencedColumns: ["id"];
771 |         }
772 |     ];
773 | };
774 | baseline_test_config: {
775 |     Row: {
776 |         course_id: string;
777 |         created_at: string;
778 |         id: string;
779 |         is_active: boolean;
780 |         min_questions_per_clo: number;
781 |         time_limit_minutes: number;
782 |         updated_at: string;
783 |     };
784 |     Insert: {
785 |         course_id: string;
786 |         created_at?: string;
787 |         id?: string;
788 |         is_active?: boolean;
789 |         min_questions_per_clo?: number;
790 |         time_limit_minutes?: number;
791 |         updated_at?: string;
792 |     };
793 |     Update: {
794 |         course_id?: string;
795 |         created_at?: string;
796 |         id?: string;
797 |         is_active?: boolean;
798 |         min_questions_per_clo?: number;
799 |         time_limit_minutes?: number;
800 |         updated_at?: string;
801 |     };
802 |     Relationships: [
803 |         {
804 |             foreignKeyName: "baseline_test_config_course_id_fkey";
805 |             columns: ["course_id"];
806 |             isOneToOne: true;
807 |             referencedRelation: "courses";
808 |             referencedColumns: ["id"];
809 |         }
810 |     ];
811 | };
812 | blocked_ips: {
813 |     Row: {
814 |         blocked_by: string | null;
815 |         blocked_until: string;
816 |         created_at: string;
817 |         ip_address: unknown;
818 |         reason: string;
819 |     };
820 |     Insert: {
821 |         blocked_by?: string | null;
822 |         blocked_until: string;
823 |         created_at?: string;
824 |         ip_address: unknown;
825 |         reason: string;
826 |     };
827 |     Update: {
828 |         blocked_by?: string | null;
829 |         blocked_until?: string;
830 |         created_at?: string;
831 |         ip_address?: unknown;
832 |         reason?: string;
833 |     };
834 |     Relationships: [];
835 | };
836 | blooms_progression: {
837 |     Row: {
838 |         bloom_challenger_awarded: boolean;
839 |         bloom_explorer_awarded: boolean;
840 |         bloom_pioneer_awarded: boolean;
841 |         clo_id: string;
842 |         correct_count_at_highest: number;
843 |         course_id: string;

```

```

844 |         highest_bloom_level: number;
845 |         id: string;
846 |         institution_id: string;
847 |         student_id: string;
848 |         updated_at: string;
849 |     };
850 |     Insert: {
851 |         bloom_challenger_awarded?: boolean;
852 |         bloom_explorer_awarded?: boolean;
853 |         bloom_pioneer_awarded?: boolean;
854 |         clo_id: string;
855 |         correct_count_at_highest?: number;
856 |         course_id: string;
857 |         highest_bloom_level?: number;
858 |         id?: string;
859 |         institution_id: string;
860 |         student_id: string;
861 |         updated_at?: string;
862 |     };
863 |     Update: {
864 |         bloom_challenger_awarded?: boolean;
865 |         bloom_explorer_awarded?: boolean;
866 |         bloom_pioneer_awarded?: boolean;
867 |         clo_id?: string;
868 |         correct_count_at_highest?: number;
869 |         course_id?: string;
870 |         highest_bloom_level?: number;
871 |         id?: string;
872 |         institution_id?: string;
873 |         student_id?: string;
874 |         updated_at?: string;
875 |     };
876 |     Relationships: [
877 |         {
878 |             foreignKeyName: "blooms_progression_clo_id_fkey";
879 |             columns: ["clo_id"];
880 |             isOneToOne: false;
881 |             referencedRelation: "learning_outcomes";
882 |             referencedColumns: ["id"];
883 |         },
884 |         {
885 |             foreignKeyName: "blooms_progression_course_id_fkey";
886 |             columns: ["course_id"];
887 |             isOneToOne: false;
888 |             referencedRelation: "courses";
889 |             referencedColumns: ["id"];
890 |         },
891 |         {
892 |             foreignKeyName: "blooms_progression_institution_id_fkey";
893 |             columns: ["institution_id"];
894 |             isOneToOne: false;
895 |             referencedRelation: "institutions";
896 |             referencedColumns: ["id"];
897 |         },
898 |         {
899 |             foreignKeyName: "blooms_progression_institution_id_fkey";
900 |             columns: ["institution_id"];
901 |             isOneToOne: false;
902 |             referencedRelation: "institutions_public";
903 |             referencedColumns: ["id"];
904 |         },
905 |         {
906 |             foreignKeyName: "blooms_progression_student_id_fkey";
907 |             columns: ["student_id"];
908 |             isOneToOne: false;
909 |             referencedRelation: "profiles";
910 |             referencedColumns: ["id"];
911 |         }
912 |     ];
913 | };
914 | challenge_participants: {
915 |     Row: {
916 |         challenge_id: string;
917 |         created_at: string;
918 |         current_progress: number;
919 |         id: string;
920 |         participant_id: string;
921 |         participant_type: string;
922 |     };
923 |     Insert: {
924 |         challenge_id: string;
925 |         created_at?: string;
926 |         current_progress?: number;
927 |         id?: string;
928 |         participant_id: string;
929 |         participant_type: string;
930 |     };
931 |     Update: {
932 |         challenge_id?: string;
933 |         created_at?: string;
934 |         current_progress?: number;
935 |         id?: string;
936 |         participant_id?: string;
937 |         participant_type?: string;
938 |     };
939 |     Relationships: [
940 |         {
941 |             foreignKeyName: "challenge_participants_challenge_id_fkey";
942 |             columns: ["challenge_id"];
943 |             isOneToOne: false;
944 |             referencedRelation: "social_challenges";
945 |             referencedColumns: ["id"];
946 |         }
947 |     ];

```



```

948 | };
949 | challenge_progress: {
950 |   Row: {
951 |     challenge_id: string;
952 |     completed_at: string | null;
953 |     current_progress: number;
954 |     id: string;
955 |     participant_id: string;
956 |     participant_type: string;
957 |     reward_granted: boolean;
958 |     updated_at: string;
959 |   };
960 |   Insert: {
961 |     challenge_id: string;
962 |     completed_at?: string | null;
963 |     current_progress?: number;
964 |     id?: string;
965 |     participant_id: string;
966 |     participant_type?: string;
967 |     reward_granted?: boolean;
968 |     updated_at?: string;
969 |   };
970 |   Update: {
971 |     challenge_id?: string;
972 |     completed_at?: string | null;
973 |     current_progress?: number;
974 |     id?: string;
975 |     participant_id?: string;
976 |     participant_type?: string;
977 |     reward_granted?: boolean;
978 |     updated_at?: string;
979 |   };
980 |   Relationships: [
981 |     {
982 |       foreignKeyName: "challenge_progress_challenge_id_fkey";
983 |       columns: ["challenge_id"];
984 |       isOneToOne: false;
985 |       referencedRelation: "social_challenges";
986 |       referencedColumns: ["id"];
987 |     }
988 |   ];
989 | };
990 | class_donation_contributions: {
991 |   Row: {
992 |     contributed_at: string;
993 |     donation_id: string;
994 |     id: string;
995 |     purchase_id: string | null;
996 |     student_id: string;
997 |     xp_amount: number;
998 |   };
999 |   Insert: {
1000 |     contributed_at?: string;
1001 |     donation_id: string;
1002 |     id?: string;
1003 |     purchase_id?: string | null;
1004 |     student_id: string;
1005 |     xp_amount: number;
1006 |   };
1007 |   Update: {
1008 |     contributed_at?: string;
1009 |     donation_id?: string;
1010 |     id?: string;
1011 |     purchase_id?: string | null;
1012 |     student_id?: string;
1013 |     xp_amount?: number;
1014 |   };
1015 |   Relationships: [
1016 |     {
1017 |       foreignKeyName: "class_donation_contributions_donation_id_fkey";
1018 |       columns: ["donation_id"];
1019 |       isOneToOne: false;
1020 |       referencedRelation: "class_donations";
1021 |       referencedColumns: ["id"];
1022 |     },
1023 |     {
1024 |       foreignKeyName: "class_donation_contributions_purchase_id_fkey";
1025 |       columns: ["purchase_id"];
1026 |       isOneToOne: false;
1027 |       referencedRelation: "xp_purchases";
1028 |       referencedColumns: ["id"];
1029 |     },
1030 |     {
1031 |       foreignKeyName: "class_donation_contributions_student_id_fkey";
1032 |       columns: ["student_id"];
1033 |       isOneToOne: false;
1034 |       referencedRelation: "profiles";
1035 |       referencedColumns: ["id"];
1036 |     }
1037 |   ];
1038 | };
1039 | class_donations: {
1040 |   Row: {
1041 |     completed_at: string | null;
1042 |     course_id: string;
1043 |     created_at: string;
1044 |     created_by: string;
1045 |     current_total: number;
1046 |     goal_amount: number;
1047 |     id: string;
1048 |     institution_id: string;
1049 |     resource_description: string;
1050 |     status: string;
1051 |   };

```

```

1052 | Insert: {
1053 |   completed_at?: string | null;
1054 |   course_id: string;
1055 |   created_at?: string;
1056 |   created_by: string;
1057 |   current_total?: number;
1058 |   goal_amount: number;
1059 |   id?: string;
1060 |   institution_id: string;
1061 |   resource_description: string;
1062 |   status?: string;
1063 | };
1064 | Update: {
1065 |   completed_at?: string | null;
1066 |   course_id?: string;
1067 |   created_at?: string;
1068 |   created_by?: string;
1069 |   current_total?: number;
1070 |   goal_amount?: number;
1071 |   id?: string;
1072 |   institution_id?: string;
1073 |   resource_description?: string;
1074 |   status?: string;
1075 | };
1076 | Relationships: [
1077 |   {
1078 |     foreignKeyName: "class_donations_course_id_fkey";
1079 |     columns: ["course_id"];
1080 |     isOneToOne: false;
1081 |     referencedRelation: "courses";
1082 |     referencedColumns: ["id"];
1083 |   },
1084 |   {
1085 |     foreignKeyName: "class_donations_created_by_fkey";
1086 |     columns: ["created_by"];
1087 |     isOneToOne: false;
1088 |     referencedRelation: "profiles";
1089 |     referencedColumns: ["id"];
1090 |   },
1091 |   {
1092 |     foreignKeyName: "class_donations_institution_id_fkey";
1093 |     columns: ["institution_id"];
1094 |     isOneToOne: false;
1095 |     referencedRelation: "institutions";
1096 |     referencedColumns: ["id"];
1097 |   },
1098 |   {
1099 |     foreignKeyName: "class_donations_institution_id_fkey";
1100 |     columns: ["institution_id"];
1101 |     isOneToOne: false;
1102 |     referencedRelation: "institutions_public";
1103 |     referencedColumns: ["id"];
1104 |   }
1105 | ];
1106 | };
1107 | class_sessions: {
1108 |   Row: {
1109 |     created_at: string;
1110 |     id: string;
1111 |     section_id: string;
1112 |     session_date: string;
1113 |     session_type: string;
1114 |     topic: string | null;
1115 |   };
1116 |   Insert: {
1117 |     created_at?: string;
1118 |     id?: string;
1119 |     section_id: string;
1120 |     session_date: string;
1121 |     session_type: string;
1122 |     topic?: string | null;
1123 |   };
1124 |   Update: {
1125 |     created_at?: string;
1126 |     id?: string;
1127 |     section_id?: string;
1128 |     session_date?: string;
1129 |     session_type?: string;
1130 |     topic?: string | null;
1131 |   };
1132 |   Relationships: [
1133 |     {
1134 |       foreignKeyName: "class_sessions_section_id_fkey";
1135 |       columns: ["section_id"];
1136 |       isOneToOne: false;
1137 |       referencedRelation: "course_sections";
1138 |       referencedColumns: ["id"];
1139 |     }
1140 |   ];
1141 | };
1142 | competency_frameworks: {
1143 |   Row: {
1144 |     created_at: string | null;
1145 |     description: string | null;
1146 |     id: string;
1147 |     institution_id: string;
1148 |     is_active: boolean | null;
1149 |     name: string;
1150 |     version: string | null;
1151 |   };
1152 |   Insert: {
1153 |     created_at?: string | null;
1154 |     description?: string | null;
1155 |     id?: string;

```

```

1156 |         institution_id: string;
1157 |         is_active?: boolean | null;
1158 |         name: string;
1159 |         version?: string | null;
1160 |     };
1161 |     Update: {
1162 |         created_at?: string | null;
1163 |         description?: string | null;
1164 |         id?: string;
1165 |         institution_id?: string;
1166 |         is_active?: boolean | null;
1167 |         name?: string;
1168 |         version?: string | null;
1169 |     };
1170 |     Relationships: [
1171 |     {
1172 |         foreignKeyName: "competency_frameworks_institution_id_fkey";
1173 |         columns: ["institution_id"];
1174 |         isOneToOne: false;
1175 |         referencedRelation: "institutions";
1176 |         referencedColumns: ["id"];
1177 |     },
1178 |     {
1179 |         foreignKeyName: "competency_frameworks_institution_id_fkey";
1180 |         columns: ["institution_id"];
1181 |         isOneToOne: false;
1182 |         referencedRelation: "institutions_public";
1183 |         referencedColumns: ["id"];
1184 |     }
1185 | ];
1186 | };
1187 | competency_items: {
1188 |     Row: {
1189 |         created_at: string | null;
1190 |         description: string | null;
1191 |         framework_id: string;
1192 |         id: string;
1193 |         level: number | null;
1194 |         name: string;
1195 |         parent_id: string | null;
1196 |         sort_order: number | null;
1197 |     };
1198 |     Insert: {
1199 |         created_at?: string | null;
1200 |         description?: string | null;
1201 |         framework_id: string;
1202 |         id?: string;
1203 |         level?: number | null;
1204 |         name: string;
1205 |         parent_id?: string | null;
1206 |         sort_order?: number | null;
1207 |     };
1208 |     Update: {
1209 |         created_at?: string | null;
1210 |         description?: string | null;
1211 |         framework_id?: string;
1212 |         id?: string;
1213 |         level?: number | null;
1214 |         name?: string;
1215 |         parent_id?: string | null;
1216 |         sort_order?: number | null;
1217 |     };
1218 |     Relationships: [
1219 |     {
1220 |         foreignKeyName: "competency_items_framework_id_fkey";
1221 |         columns: ["framework_id"];
1222 |         isOneToOne: false;
1223 |         referencedRelation: "competency_frameworks";
1224 |         referencedColumns: ["id"];
1225 |     },
1226 |     {
1227 |         foreignKeyName: "competency_items_parent_id_fkey";
1228 |         columns: ["parent_id"];
1229 |         isOneToOne: false;
1230 |         referencedRelation: "competency_items";
1231 |         referencedColumns: ["id"];
1232 |     }
1233 | ];
1234 | };
1235 | competency_outcome_mappings: {
1236 |     Row: {
1237 |         competency_item_id: string;
1238 |         created_at: string | null;
1239 |         id: string;
1240 |         outcome_id: string;
1241 |         weight: number | null;
1242 |     };
1243 |     Insert: {
1244 |         competency_item_id: string;
1245 |         created_at?: string | null;
1246 |         id?: string;
1247 |         outcome_id: string;
1248 |         weight?: number | null;
1249 |     };
1250 |     Update: {
1251 |         competency_item_id?: string;
1252 |         created_at?: string | null;
1253 |         id?: string;
1254 |         outcome_id?: string;
1255 |         weight?: number | null;
1256 |     };
1257 |     Relationships: [
1258 |     {
1259 |         foreignKeyName: "competency_outcome_mappings_competency_item_id_fkey";

```

```

1260         columns: ["competency_item_id"];
1261         isOneToOne: false;
1262         referencedRelation: "competency_items";
1263         referencedColumns: ["id"];
1264     },
1265     {
1266         foreignKeyName: "competency_outcome_mappings_outcome_id_fkey";
1267         columns: ["outcome_id"];
1268         isOneToOne: false;
1269         referencedRelation: "learning_outcomes";
1270         referencedColumns: ["id"];
1271     }
1272 ];
1273 };
1274 course_material_embeddings: {
1275     Row: {
1276         bloom_level: string | null;
1277         chunk_index: number;
1278         chunk_text: string;
1279         clo_ids: string[] | null;
1280         course_id: string;
1281         created_at: string;
1282         embedding: string;
1283         id: string;
1284         indexing_status: string;
1285         institution_id: string;
1286         material_type: string;
1287         source_filename: string;
1288         source_material_id: string | null;
1289         token_count: number;
1290         updated_at: string;
1291     };
1292     Insert: {
1293         bloom_level?: string | null;
1294         chunk_index: number;
1295         chunk_text: string;
1296         clo_ids?: string[] | null;
1297         course_id: string;
1298         created_at?: string;
1299         embedding: string;
1300         id?: string;
1301         indexing_status?: string;
1302         institution_id: string;
1303         material_type: string;
1304         source_filename: string;
1305         source_material_id?: string | null;
1306         token_count: number;
1307         updated_at?: string;
1308     };
1309     Update: {
1310         bloom_level?: string | null;
1311         chunk_index?: number;
1312         chunk_text?: string;
1313         clo_ids?: string[] | null;
1314         course_id?: string;
1315         created_at?: string;
1316         embedding?: string;
1317         id?: string;
1318         indexing_status?: string;
1319         institution_id?: string;
1320         material_type?: string;
1321         source_filename?: string;
1322         source_material_id?: string | null;
1323         token_count?: number;
1324         updated_at?: string;
1325     };
1326     Relationships: [
1327         {
1328             foreignKeyName: "course_material_embeddings_course_id_fkey";
1329             columns: ["course_id"];
1330             isOneToOne: false;
1331             referencedRelation: "courses";
1332             referencedColumns: ["id"];
1333         },
1334         {
1335             foreignKeyName: "course_material_embeddings_institution_id_fkey";
1336             columns: ["institution_id"];
1337             isOneToOne: false;
1338             referencedRelation: "institutions";
1339             referencedColumns: ["id"];
1340         },
1341         {
1342             foreignKeyName: "course_material_embeddings_institution_id_fkey";
1343             columns: ["institution_id"];
1344             isOneToOne: false;
1345             referencedRelation: "institutions_public";
1346             referencedColumns: ["id"];
1347         },
1348         {
1349             foreignKeyName: "course_material_embeddings_source_material_id_fkey";
1350             columns: ["source_material_id"];
1351             isOneToOne: false;
1352             referencedRelation: "course_materials";
1353             referencedColumns: ["id"];
1354         }
1355     ];
1356 };
1357 course_materials: {
1358     Row: {
1359         clo_ids: Json | null;
1360         content_url: string | null;
1361         created_at: string;
1362         description: string | null;
1363         file_path: string | null;

```

```

1364 |         id: string;
1365 |         is_published: boolean;
1366 |         module_id: string;
1367 |         search_vector: unknown;
1368 |         sort_order: number;
1369 |         title: string;
1370 |         type: string;
1371 |     };
1372 |     Insert: {
1373 |         clo_ids?: Json | null;
1374 |         content_url?: string | null;
1375 |         created_at?: string;
1376 |         description?: string | null;
1377 |         file_path?: string | null;
1378 |         id?: string;
1379 |         is_published?: boolean;
1380 |         module_id: string;
1381 |         search_vector?: unknown;
1382 |         sort_order?: number;
1383 |         title: string;
1384 |         type: string;
1385 |     };
1386 |     Update: {
1387 |         clo_ids?: Json | null;
1388 |         content_url?: string | null;
1389 |         created_at?: string;
1390 |         description?: string | null;
1391 |         file_path?: string | null;
1392 |         id?: string;
1393 |         is_published?: boolean;
1394 |         module_id?: string;
1395 |         search_vector?: unknown;
1396 |         sort_order?: number;
1397 |         title?: string;
1398 |         type?: string;
1399 |     };
1400 |     Relationships: [
1401 |         {
1402 |             foreignKeyName: "course_materials_module_id_fkey";
1403 |             columns: ["module_id"];
1404 |             isOneToOne: false;
1405 |             referencedRelation: "course_modules";
1406 |             referencedColumns: ["id"];
1407 |         }
1408 |     ];
1409 | };
1410 | course_modules: {
1411 |     Row: {
1412 |         course_id: string;
1413 |         created_at: string;
1414 |         description: string | null;
1415 |         id: string;
1416 |         is_published: boolean;
1417 |         sort_order: number;
1418 |         title: string;
1419 |     };
1420 |     Insert: {
1421 |         course_id: string;
1422 |         created_at?: string;
1423 |         description?: string | null;
1424 |         id?: string;
1425 |         is_published?: boolean;
1426 |         sort_order?: number;
1427 |         title: string;
1428 |     };
1429 |     Update: {
1430 |         course_id?: string;
1431 |         created_at?: string;
1432 |         description?: string | null;
1433 |         id?: string;
1434 |         is_published?: boolean;
1435 |         sort_order?: number;
1436 |         title?: string;
1437 |     };
1438 |     Relationships: [
1439 |         {
1440 |             foreignKeyName: "course_modules_course_id_fkey";
1441 |             columns: ["course_id"];
1442 |             isOneToOne: false;
1443 |             referencedRelation: "courses";
1444 |             referencedColumns: ["id"];
1445 |         }
1446 |     ];
1447 | };
1448 | course_sections: {
1449 |     Row: {
1450 |         capacity: number;
1451 |         course_id: string;
1452 |         created_at: string;
1453 |         id: string;
1454 |         is_active: boolean;
1455 |         section_code: string;
1456 |         teacher_id: string;
1457 |     };
1458 |     Insert: {
1459 |         capacity?: number;
1460 |         course_id: string;
1461 |         created_at?: string;
1462 |         id?: string;
1463 |         is_active?: boolean;
1464 |         section_code: string;
1465 |         teacher_id: string;
1466 |     };
1467 |     Update: {

```

```

1468         capacity?: number;
1469         course_id?: string;
1470         created_at?: string;
1471         id?: string;
1472         is_active?: boolean;
1473         section_code?: string;
1474         teacher_id?: string;
1475     };
1476     Relationships: [
1477     {
1478         foreignKeyName: "course_sections_course_id_fkey";
1479         columns: ["course_id"];
1480         isOneToOne: false;
1481         referencedRelation: "courses";
1482         referencedColumns: ["id"];
1483     },
1484     {
1485         foreignKeyName: "course_sections_teacher_id_fkey";
1486         columns: ["teacher_id"];
1487         isOneToOne: false;
1488         referencedRelation: "profiles";
1489         referencedColumns: ["id"];
1490     }
1491 ];
1492 };
1493 courses: {
1494     Row: {
1495         academic_year: string;
1496         code: string;
1497         color: string | null;
1498         created_at: string;
1499         id: string;
1500         is_active: boolean;
1501         name: string;
1502         name_ar: string | null;
1503         program_id: string;
1504         search_vector: unknown;
1505         semester: string;
1506         semester_id: string | null;
1507         teacher_id: string | null;
1508         team_formation_mode: string;
1509     };
1510     Insert: {
1511         academic_year: string;
1512         code: string;
1513         color?: string | null;
1514         created_at?: string;
1515         id?: string;
1516         is_active?: boolean;
1517         name: string;
1518         name_ar?: string | null;
1519         program_id: string;
1520         search_vector?: unknown;
1521         semester: string;
1522         semester_id?: string | null;
1523         teacher_id?: string | null;
1524         team_formation_mode?: string;
1525     };
1526     Update: {
1527         academic_year?: string;
1528         code?: string;
1529         color?: string | null;
1530         created_at?: string;
1531         id?: string;
1532         is_active?: boolean;
1533         name?: string;
1534         name_ar?: string | null;
1535         program_id?: string;
1536         search_vector?: unknown;
1537         semester?: string;
1538         semester_id?: string | null;
1539         teacher_id?: string | null;
1540         team_formation_mode?: string;
1541     };
1542     Relationships: [
1543     {
1544         foreignKeyName: "courses_program_id_fkey";
1545         columns: ["program_id"];
1546         isOneToOne: false;
1547         referencedRelation: "programs";
1548         referencedColumns: ["id"];
1549     },
1550     {
1551         foreignKeyName: "courses_semester_id_fkey";
1552         columns: ["semester_id"];
1553         isOneToOne: false;
1554         referencedRelation: "mv_historical_evidence";
1555         referencedColumns: ["semester_id"];
1556     },
1557     {
1558         foreignKeyName: "courses_semester_id_fkey";
1559         columns: ["semester_id"];
1560         isOneToOne: false;
1561         referencedRelation: "semesters";
1562         referencedColumns: ["id"];
1563     },
1564     {
1565         foreignKeyName: "courses_teacher_id_fkey";
1566         columns: ["teacher_id"];
1567         isOneToOne: false;
1568         referencedRelation: "profiles";
1569         referencedColumns: ["id"];
1570     }
1571 ];

```

```

1572 | };
1573 | cqi_action_plans: {
1574 |   Row: {
1575 |     action_description: string;
1576 |     baseline_attainment: number;
1577 |     created_at: string;
1578 |     due_date: string | null;
1579 |     evidence_of_improvement: string | null;
1580 |     id: string;
1581 |     outcome_id: string;
1582 |     outcome_type: string;
1583 |     program_id: string;
1584 |     responsible_person: string;
1585 |     result_attainment: number | null;
1586 |     root_cause: string | null;
1587 |     semester_id: string;
1588 |     status: string;
1589 |     target_attainment: number;
1590 |     updated_at: string;
1591 |   };
1592 |   Insert: {
1593 |     action_description: string;
1594 |     baseline_attainment: number;
1595 |     created_at?: string;
1596 |     due_date?: string | null;
1597 |     evidence_of_improvement?: string | null;
1598 |     id?: string;
1599 |     outcome_id: string;
1600 |     outcome_type: string;
1601 |     program_id: string;
1602 |     responsible_person: string;
1603 |     result_attainment?: number | null;
1604 |     root_cause?: string | null;
1605 |     semester_id: string;
1606 |     status?: string;
1607 |     target_attainment: number;
1608 |     updated_at?: string;
1609 |   };
1610 |   Update: {
1611 |     action_description?: string;
1612 |     baseline_attainment?: number;
1613 |     created_at?: string;
1614 |     due_date?: string | null;
1615 |     evidence_of_improvement?: string | null;
1616 |     id?: string;
1617 |     outcome_id?: string;
1618 |     outcome_type?: string;
1619 |     program_id?: string;
1620 |     responsible_person?: string;
1621 |     result_attainment?: number | null;
1622 |     root_cause?: string | null;
1623 |     semester_id?: string;
1624 |     status?: string;
1625 |     target_attainment?: number;
1626 |     updated_at?: string;
1627 |   };
1628 |   Relationships: [
1629 |     {
1630 |       foreignKeyName: "cqi_action_plans_outcome_id_fkey";
1631 |       columns: ["outcome_id"];
1632 |       isOneToOne: false;
1633 |       referencedRelation: "learning_outcomes";
1634 |       referencedColumns: ["id"];
1635 |     },
1636 |     {
1637 |       foreignKeyName: "cqi_action_plans_program_id_fkey";
1638 |       columns: ["program_id"];
1639 |       isOneToOne: false;
1640 |       referencedRelation: "programs";
1641 |       referencedColumns: ["id"];
1642 |     },
1643 |     {
1644 |       foreignKeyName: "cqi_action_plans_semester_id_fkey";
1645 |       columns: ["semester_id"];
1646 |       isOneToOne: false;
1647 |       referencedRelation: "mv_historical_evidence";
1648 |       referencedColumns: ["semester_id"];
1649 |     },
1650 |     {
1651 |       foreignKeyName: "cqi_action_plans_semester_id_fkey";
1652 |       columns: ["semester_id"];
1653 |       isOneToOne: false;
1654 |       referencedRelation: "semesters";
1655 |       referencedColumns: ["id"];
1656 |     }
1657 |   ];
1658 | };
1659 | deadline_extensions: {
1660 |   Row: {
1661 |     assignment_id: string;
1662 |     created_at: string;
1663 |     extended_deadline: string;
1664 |     id: string;
1665 |     original_deadline: string;
1666 |     purchase_id: string;
1667 |     revoked: boolean;
1668 |     revoked_by: string | null;
1669 |     student_id: string;
1670 |   };
1671 |   Insert: {
1672 |     assignment_id: string;
1673 |     created_at?: string;
1674 |     extended_deadline: string;
1675 |     id?: string;

```

```

1676 |         original_deadline: string;
1677 |         purchase_id: string;
1678 |         revoked?: boolean;
1679 |         revoked_by?: string | null;
1680 |         student_id: string;
1681 |     };
1682 |     Update: {
1683 |         assignment_id?: string;
1684 |         created_at?: string;
1685 |         extended_deadline?: string;
1686 |         id?: string;
1687 |         original_deadline?: string;
1688 |         purchase_id?: string;
1689 |         revoked?: boolean;
1690 |         revoked_by?: string | null;
1691 |         student_id?: string;
1692 |     };
1693 |     Relationships: [
1694 |         {
1695 |             foreignKeyName: "deadline_extensions_assignment_id_fkey";
1696 |             columns: ["assignment_id"];
1697 |             isOneToOne: false;
1698 |             referencedRelation: "assignments";
1699 |             referencedColumns: ["id"];
1700 |         },
1701 |         {
1702 |             foreignKeyName: "deadline_extensions_purchase_id_fkey";
1703 |             columns: ["purchase_id"];
1704 |             isOneToOne: false;
1705 |             referencedRelation: "xp_purchases";
1706 |             referencedColumns: ["id"];
1707 |         },
1708 |         {
1709 |             foreignKeyName: "deadline_extensions_revoked_by_fkey";
1710 |             columns: ["revoked_by"];
1711 |             isOneToOne: false;
1712 |             referencedRelation: "profiles";
1713 |             referencedColumns: ["id"];
1714 |         },
1715 |         {
1716 |             foreignKeyName: "deadline_extensions_student_id_fkey";
1717 |             columns: ["student_id"];
1718 |             isOneToOne: false;
1719 |             referencedRelation: "profiles";
1720 |             referencedColumns: ["id"];
1721 |         }
1722 |     ];
1723 | };
1724 | departments: {
1725 |     Row: {
1726 |         code: string;
1727 |         created_at: string;
1728 |         head_of_department_id: string | null;
1729 |         id: string;
1730 |         institution_id: string;
1731 |         name: string;
1732 |     };
1733 |     Insert: {
1734 |         code: string;
1735 |         created_at?: string;
1736 |         head_of_department_id?: string | null;
1737 |         id?: string;
1738 |         institution_id: string;
1739 |         name: string;
1740 |     };
1741 |     Update: {
1742 |         code?: string;
1743 |         created_at?: string;
1744 |         head_of_department_id?: string | null;
1745 |         id?: string;
1746 |         institution_id?: string;
1747 |         name?: string;
1748 |     };
1749 |     Relationships: [
1750 |         {
1751 |             foreignKeyName: "departments_head_of_department_id_fkey";
1752 |             columns: ["head_of_department_id"];
1753 |             isOneToOne: false;
1754 |             referencedRelation: "profiles";
1755 |             referencedColumns: ["id"];
1756 |         },
1757 |         {
1758 |             foreignKeyName: "departments_institution_id_fkey";
1759 |             columns: ["institution_id"];
1760 |             isOneToOne: false;
1761 |             referencedRelation: "institutions";
1762 |             referencedColumns: ["id"];
1763 |         },
1764 |         {
1765 |             foreignKeyName: "departments_institution_id_fkey";
1766 |             columns: ["institution_id"];
1767 |             isOneToOne: false;
1768 |             referencedRelation: "institutions_public";
1769 |             referencedColumns: ["id"];
1770 |         }
1771 |     ];
1772 | };
1773 | discussion_replies: {
1774 |     Row: {
1775 |         author_id: string;
1776 |         content: string;
1777 |         created_at: string;
1778 |         id: string;
1779 |         is_answer: boolean;

```



```

1780         thread_id: string;
1781     };
1782     Insert: {
1783         author_id: string;
1784         content: string;
1785         created_at?: string;
1786         id?: string;
1787         is_answer?: boolean;
1788         thread_id: string;
1789     };
1790     Update: {
1791         author_id?: string;
1792         content?: string;
1793         created_at?: string;
1794         id?: string;
1795         is_answer?: boolean;
1796         thread_id?: string;
1797     };
1798     Relationships: [
1799     {
1800         foreignKeyName: "discussion_replies_author_id_fkey";
1801         columns: ["author_id"];
1802         isOneToOne: false;
1803         referencedRelation: "profiles";
1804         referencedColumns: ["id"];
1805     },
1806     {
1807         foreignKeyName: "discussion_replies_thread_id_fkey";
1808         columns: ["thread_id"];
1809         isOneToOne: false;
1810         referencedRelation: "discussion_threads";
1811         referencedColumns: ["id"];
1812     }
1813 ];
1814 };
1815 discussion_threads: {
1816     Row: {
1817         author_id: string;
1818         content: string;
1819         course_id: string;
1820         created_at: string;
1821         id: string;
1822         is_pinned: boolean;
1823         is_resolved: boolean;
1824         title: string;
1825     };
1826     Insert: {
1827         author_id: string;
1828         content: string;
1829         course_id: string;
1830         created_at?: string;
1831         id?: string;
1832         is_pinned?: boolean;
1833         is_resolved?: boolean;
1834         title: string;
1835     };
1836     Update: {
1837         author_id?: string;
1838         content?: string;
1839         course_id?: string;
1840         created_at?: string;
1841         id?: string;
1842         is_pinned?: boolean;
1843         is_resolved?: boolean;
1844         title?: string;
1845     };
1846     Relationships: [
1847     {
1848         foreignKeyName: "discussion_threads_author_id_fkey";
1849         columns: ["author_id"];
1850         isOneToOne: false;
1851         referencedRelation: "profiles";
1852         referencedColumns: ["id"];
1853     },
1854     {
1855         foreignKeyName: "discussion_threads_course_id_fkey";
1856         columns: ["course_id"];
1857         isOneToOne: false;
1858         referencedRelation: "courses";
1859         referencedColumns: ["id"];
1860     }
1861 ];
1862 };
1863 evidence: {
1864     Row: {
1865         attainment_level: Database["public"]["Enums"]["attainment_level"];
1866         clo_id: string;
1867         created_at: string;
1868         grade_id: string;
1869         id: string;
1870         ilo_id: string;
1871         plo_id: string;
1872         score_percent: number;
1873         student_id: string;
1874         submission_id: string;
1875     };
1876     Insert: {
1877         attainment_level: Database["public"]["Enums"]["attainment_level"];
1878         clo_id: string;
1879         created_at?: string;
1880         grade_id: string;
1881         id?: string;
1882         ilo_id: string;
1883         plo_id: string;

```

```

1884 |         score_percent: number;
1885 |         student_id: string;
1886 |         submission_id: string;
1887 |     };
1888 |     Update: {
1889 |         attainment_level?: Database["public"]["Enums"]["attainment_level"];
1890 |         clo_id?: string;
1891 |         created_at?: string;
1892 |         grade_id?: string;
1893 |         id?: string;
1894 |         ilo_id?: string;
1895 |         plo_id?: string;
1896 |         score_percent?: number;
1897 |         student_id?: string;
1898 |         submission_id?: string;
1899 |     };
1900 |     Relationships: [
1901 |     {
1902 |         foreignKeyName: "evidence_clo_id_fkey";
1903 |         columns: ["clo_id"];
1904 |         isOneToOne: false;
1905 |         referencedRelation: "learning_outcomes";
1906 |         referencedColumns: ["id"];
1907 |     },
1908 |     {
1909 |         foreignKeyName: "evidence_grade_id_fkey";
1910 |         columns: ["grade_id"];
1911 |         isOneToOne: false;
1912 |         referencedRelation: "grades";
1913 |         referencedColumns: ["id"];
1914 |     },
1915 |     {
1916 |         foreignKeyName: "evidence_ilo_id_fkey";
1917 |         columns: ["ilo_id"];
1918 |         isOneToOne: false;
1919 |         referencedRelation: "learning_outcomes";
1920 |         referencedColumns: ["id"];
1921 |     },
1922 |     {
1923 |         foreignKeyName: "evidence_plo_id_fkey";
1924 |         columns: ["plo_id"];
1925 |         isOneToOne: false;
1926 |         referencedRelation: "learning_outcomes";
1927 |         referencedColumns: ["id"];
1928 |     },
1929 |     {
1930 |         foreignKeyName: "evidence_student_id_fkey";
1931 |         columns: ["student_id"];
1932 |         isOneToOne: false;
1933 |         referencedRelation: "profiles";
1934 |         referencedColumns: ["id"];
1935 |     },
1936 |     {
1937 |         foreignKeyName: "evidence_submission_id_fkey";
1938 |         columns: ["submission_id"];
1939 |         isOneToOne: false;
1940 |         referencedRelation: "submissions";
1941 |         referencedColumns: ["id"];
1942 |     }
1943 | ];
1944 | };
1945 | fee_payments: {
1946 |     Row: {
1947 |         amount_paid: number;
1948 |         created_at: string;
1949 |         fee_structure_id: string;
1950 |         id: string;
1951 |         payment_date: string;
1952 |         payment_method: string | null;
1953 |         receipt_number: string | null;
1954 |         status: string;
1955 |         student_id: string;
1956 |     };
1957 |     Insert: {
1958 |         amount_paid: number;
1959 |         created_at?: string;
1960 |         fee_structure_id: string;
1961 |         id?: string;
1962 |         payment_date: string;
1963 |         payment_method?: string | null;
1964 |         receipt_number?: string | null;
1965 |         status?: string;
1966 |         student_id: string;
1967 |     };
1968 |     Update: {
1969 |         amount_paid?: number;
1970 |         created_at?: string;
1971 |         fee_structure_id?: string;
1972 |         id?: string;
1973 |         payment_date?: string;
1974 |         payment_method?: string | null;
1975 |         receipt_number?: string | null;
1976 |         status?: string;
1977 |         student_id?: string;
1978 |     };
1979 |     Relationships: [
1980 |     {
1981 |         foreignKeyName: "fee_payments_fee_structure_id_fkey";
1982 |         columns: ["fee_structure_id"];
1983 |         isOneToOne: false;
1984 |         referencedRelation: "fee_structures";
1985 |         referencedColumns: ["id"];
1986 |     },
1987 |     {

```

```

1988         foreignKeyName: "fee_payments_student_id_fkey";
1989         columns: ["student_id"];
1990         isOneToOne: false;
1991         referencedRelation: "profiles";
1992         referencedColumns: ["id"];
1993     };
1994 };
1995 };
1996 fee_structures: {
1997     Row: {
1998         amount: number;
1999         created_at: string;
2000         currency: string;
2001         due_date: string;
2002         fee_type: string;
2003         id: string;
2004         program_id: string;
2005         semester_id: string;
2006     };
2007     Insert: {
2008         amount: number;
2009         created_at?: string;
2010         currency?: string;
2011         due_date: string;
2012         fee_type: string;
2013         id?: string;
2014         program_id: string;
2015         semester_id: string;
2016     };
2017     Update: {
2018         amount?: number;
2019         created_at?: string;
2020         currency?: string;
2021         due_date?: string;
2022         fee_type?: string;
2023         id?: string;
2024         program_id?: string;
2025         semester_id?: string;
2026     };
2027     Relationships: [
2028         {
2029             foreignKeyName: "fee_structures_program_id_fkey";
2030             columns: ["program_id"];
2031             isOneToOne: false;
2032             referencedRelation: "programs";
2033             referencedColumns: ["id"];
2034         },
2035         {
2036             foreignKeyName: "fee_structures_semester_id_fkey";
2037             columns: ["semester_id"];
2038             isOneToOne: false;
2039             referencedRelation: "mv_historical_evidence";
2040             referencedColumns: ["semester_id"];
2041         },
2042         {
2043             foreignKeyName: "fee_structures_semester_id_fkey";
2044             columns: ["semester_id"];
2045             isOneToOne: false;
2046             referencedRelation: "semesters";
2047             referencedColumns: ["id"];
2048         }
2049     ];
2050 };
2051 flow_check_ins: {
2052     Row: {
2053         created_at: string;
2054         id: string;
2055         interval_number: number;
2056         response: Database["public"]["Enums"]["flow_response_type"];
2057         session_id: string;
2058         student_id: string;
2059     };
2060     Insert: {
2061         created_at?: string;
2062         id?: string;
2063         interval_number: number;
2064         response: Database["public"]["Enums"]["flow_response_type"];
2065         session_id: string;
2066         student_id: string;
2067     };
2068     Update: {
2069         created_at?: string;
2070         id?: string;
2071         interval_number?: number;
2072         response?: Database["public"]["Enums"]["flow_response_type"];
2073         session_id?: string;
2074         student_id?: string;
2075     };
2076     Relationships: [
2077         {
2078             foreignKeyName: "flow_check_ins_session_id_fkey";
2079             columns: ["session_id"];
2080             isOneToOne: false;
2081             referencedRelation: "study_sessions";
2082             referencedColumns: ["id"];
2083         },
2084         {
2085             foreignKeyName: "flow_check_ins_student_id_fkey";
2086             columns: ["student_id"];
2087             isOneToOne: false;
2088             referencedRelation: "profiles";
2089             referencedColumns: ["id"];
2090         }
2091     ];

```

```

2092 | };
2093 | goal_suggestions: {
2094 |   Row: {
2095 |     cohort_completion_rate: number | null;
2096 |     created_at: string;
2097 |     difficulty: string;
2098 |     goal_text: string;
2099 |     id: string;
2100 |     smart_achievable: string | null;
2101 |     smart_measurable: string | null;
2102 |     smart_relevant: string | null;
2103 |     smart_specific: string | null;
2104 |     smart_timebound: string | null;
2105 |     status: string;
2106 |     student_id: string;
2107 |     week_start: string;
2108 |   };
2109 |   Insert: {
2110 |     cohort_completion_rate?: number | null;
2111 |     created_at?: string;
2112 |     difficulty?: string;
2113 |     goal_text?: string;
2114 |     id?: string;
2115 |     smart_achievable?: string | null;
2116 |     smart_measurable?: string | null;
2117 |     smart_relevant?: string | null;
2118 |     smart_specific?: string | null;
2119 |     smart_timebound?: string | null;
2120 |     status?: string;
2121 |     student_id?: string;
2122 |     week_start?: string;
2123 |   };
2124 |   Update: {
2125 |     cohort_completion_rate?: number | null;
2126 |     created_at?: string;
2127 |     difficulty?: string;
2128 |     goal_text?: string;
2129 |     id?: string;
2130 |     smart_achievable?: string | null;
2131 |     smart_measurable?: string | null;
2132 |     smart_relevant?: string | null;
2133 |     smart_specific?: string | null;
2134 |     smart_timebound?: string | null;
2135 |     status?: string;
2136 |     student_id?: string;
2137 |     week_start?: string;
2138 |   };
2139 |   Relationships: [
2140 |     {
2141 |       foreignKeyName: "goal_suggestions_student_id_fkey";
2142 |       columns: ["student_id"];
2143 |       isOneToOne: false;
2144 |       referencedRelation: "profiles";
2145 |       referencedColumns: ["id"];
2146 |     }
2147 |   ];
2148 | };
2149 | grade_categories: {
2150 |   Row: {
2151 |     course_id: string;
2152 |     created_at: string;
2153 |     id: string;
2154 |     name: string;
2155 |     sort_order: number;
2156 |     weight_percent: number;
2157 |   };
2158 |   Insert: {
2159 |     course_id: string;
2160 |     created_at?: string;
2161 |     id?: string;
2162 |     name: string;
2163 |     sort_order?: number;
2164 |     weight_percent: number;
2165 |   };
2166 |   Update: {
2167 |     course_id?: string;
2168 |     created_at?: string;
2169 |     id?: string;
2170 |     name?: string;
2171 |     sort_order?: number;
2172 |     weight_percent?: number;
2173 |   };
2174 |   Relationships: [
2175 |     {
2176 |       foreignKeyName: "grade_categories_course_id_fkey";
2177 |       columns: ["course_id"];
2178 |       isOneToOne: false;
2179 |       referencedRelation: "courses";
2180 |       referencedColumns: ["id"];
2181 |     }
2182 |   ];
2183 | };
2184 | grades: {
2185 |   Row: {
2186 |     graded_at: string;
2187 |     graded_by: string;
2188 |     id: string;
2189 |     is_released: boolean;
2190 |     overall_feedback: string | null;
2191 |     rubric_selections: Json;
2192 |     score_percent: number;
2193 |     submission_id: string;
2194 |     total_score: number;
2195 |   };

```

```

2196 | Insert: {
2197 |   graded_at?: string;
2198 |   graded_by?: string;
2199 |   id?: string;
2200 |   is_released?: boolean;
2201 |   overall_feedback?: string | null;
2202 |   rubric_selections?: Json;
2203 |   score_percent: number;
2204 |   submission_id: string;
2205 |   total_score: number;
2206 | };
2207 | Update: {
2208 |   graded_at?: string;
2209 |   graded_by?: string;
2210 |   id?: string;
2211 |   is_released?: boolean;
2212 |   overall_feedback?: string | null;
2213 |   rubric_selections?: Json;
2214 |   score_percent?: number;
2215 |   submission_id?: string;
2216 |   total_score?: number;
2217 | };
2218 | Relationships: [
2219 |   {
2220 |     foreignKeyName: "grades_graded_by_fkey";
2221 |     columns: ["graded_by"];
2222 |     isOneToOne: false;
2223 |     referencedRelation: "profiles";
2224 |     referencedColumns: ["id"];
2225 |   },
2226 |   {
2227 |     foreignKeyName: "grades_submission_id_fkey";
2228 |     columns: ["submission_id"];
2229 |     isOneToOne: true;
2230 |     referencedRelation: "submissions";
2231 |     referencedColumns: ["id"];
2232 |   }
2233 | ];
2234 | };
2235 | graduate_attribute_mappings: {
2236 |   Row: {
2237 |     created_at: string | null;
2238 |     graduate_attribute_id: string;
2239 |     id: string;
2240 |     outcome_id: string;
2241 |     weight: number | null;
2242 |   };
2243 |   Insert: {
2244 |     created_at?: string | null;
2245 |     graduate_attribute_id: string;
2246 |     id?: string;
2247 |     outcome_id: string;
2248 |     weight?: number | null;
2249 |   };
2250 |   Update: {
2251 |     created_at?: string | null;
2252 |     graduate_attribute_id?: string;
2253 |     id?: string;
2254 |     outcome_id?: string;
2255 |     weight?: number | null;
2256 |   };
2257 |   Relationships: [
2258 |     {
2259 |       foreignKeyName: "graduate_attribute_mappings_graduate_attribute_id_fkey";
2260 |       columns: ["graduate_attribute_id"];
2261 |       isOneToOne: false;
2262 |       referencedRelation: "graduate_attributes";
2263 |       referencedColumns: ["id"];
2264 |     },
2265 |     {
2266 |       foreignKeyName: "graduate_attribute_mappings_outcome_id_fkey";
2267 |       columns: ["outcome_id"];
2268 |       isOneToOne: false;
2269 |       referencedRelation: "learning_outcomes";
2270 |       referencedColumns: ["id"];
2271 |     }
2272 |   ];
2273 | };
2274 | graduate_attributes: {
2275 |   Row: {
2276 |     created_at: string | null;
2277 |     description: string | null;
2278 |     id: string;
2279 |     institution_id: string;
2280 |     name: string;
2281 |     sort_order: number | null;
2282 |   };
2283 |   Insert: {
2284 |     created_at?: string | null;
2285 |     description?: string | null;
2286 |     id?: string;
2287 |     institution_id: string;
2288 |     name: string;
2289 |     sort_order?: number | null;
2290 |   };
2291 |   Update: {
2292 |     created_at?: string | null;
2293 |     description?: string | null;
2294 |     id?: string;
2295 |     institution_id?: string;
2296 |     name?: string;
2297 |     sort_order?: number | null;
2298 |   };
2299 |   Relationships: [

```

```

2300 |         {
2301 |             foreignKeyName: "graduate_attributes_institution_id_fkey";
2302 |             columns: ["institution_id"];
2303 |             isOneToOne: false;
2304 |             referencedRelation: "institutions";
2305 |             referencedColumns: ["id"];
2306 |         },
2307 |         {
2308 |             foreignKeyName: "graduate_attributes_institution_id_fkey";
2309 |             columns: ["institution_id"];
2310 |             isOneToOne: false;
2311 |             referencedRelation: "institutions_public";
2312 |             referencedColumns: ["id"];
2313 |         }
2314 |     ];
2315 | };
2316 | habit_correlations: {
2317 |     Row: {
2318 |         computed_at: string | null;
2319 |         correlated_metric: string;
2320 |         correlation_coefficient: number | null;
2321 |         habit_type: string;
2322 |         id: string;
2323 |         sample_size: number | null;
2324 |         student_id: string;
2325 |     };
2326 |     Insert: {
2327 |         computed_at?: string | null;
2328 |         correlated_metric: string;
2329 |         correlation_coefficient?: number | null;
2330 |         habit_type: string;
2331 |         id?: string;
2332 |         sample_size?: number | null;
2333 |         student_id: string;
2334 |     };
2335 |     Update: {
2336 |         computed_at?: string | null;
2337 |         correlated_metric?: string;
2338 |         correlation_coefficient?: number | null;
2339 |         habit_type?: string;
2340 |         id?: string;
2341 |         sample_size?: number | null;
2342 |         student_id?: string;
2343 |     };
2344 |     Relationships: [
2345 |         {
2346 |             foreignKeyName: "habit_correlations_student_id_fkey";
2347 |             columns: ["student_id"];
2348 |             isOneToOne: false;
2349 |             referencedRelation: "profiles";
2350 |             referencedColumns: ["id"];
2351 |         }
2352 |     ];
2353 | };
2354 | habit_logs: {
2355 |     Row: {
2356 |         completed_at: string | null;
2357 |         created_at: string;
2358 |         date: string;
2359 |         habit_type: string;
2360 |         id: string;
2361 |         student_id: string;
2362 |     };
2363 |     Insert: {
2364 |         completed_at?: string | null;
2365 |         created_at?: string;
2366 |         date: string;
2367 |         habit_type: string;
2368 |         id?: string;
2369 |         student_id: string;
2370 |     };
2371 |     Update: {
2372 |         completed_at?: string | null;
2373 |         created_at?: string;
2374 |         date?: string;
2375 |         habit_type?: string;
2376 |         id?: string;
2377 |         student_id?: string;
2378 |     };
2379 |     Relationships: [
2380 |         {
2381 |             foreignKeyName: "habit_logs_student_id_fkey";
2382 |             columns: ["student_id"];
2383 |             isOneToOne: false;
2384 |             referencedRelation: "profiles";
2385 |             referencedColumns: ["id"];
2386 |         }
2387 |     ];
2388 | };
2389 | habit_tracking: {
2390 |     Row: {
2391 |         created_at: string;
2392 |         habit_date: string;
2393 |         id: string;
2394 |         is_perfect_day: boolean;
2395 |         journal: boolean;
2396 |         login: boolean;
2397 |         read_content: boolean;
2398 |         student_id: string;
2399 |         submit: boolean;
2400 |     };
2401 |     Insert: {
2402 |         created_at?: string;
2403 |         habit_date: string;

```

```

2404         id?: string;
2405         is_perfect_day?: boolean;
2406         journal?: boolean;
2407         login?: boolean;
2408         read_content?: boolean;
2409         student_id: string;
2410         submit?: boolean;
2411     };
2412     Update: {
2413         created_at?: string;
2414         habit_date?: string;
2415         id?: string;
2416         is_perfect_day?: boolean;
2417         journal?: boolean;
2418         login?: boolean;
2419         read_content?: boolean;
2420         student_id?: string;
2421         submit?: boolean;
2422     };
2423     Relationships: [
2424         {
2425             foreignKeyName: "habit_tracking_student_id_fkey";
2426             columns: ["student_id"];
2427             isOneToOne: false;
2428             referencedRelation: "profiles";
2429             referencedColumns: ["id"];
2430         }
2431     ];
2432 };
2433 institution_settings: {
2434     Row: {
2435         accreditation_body: string;
2436         attainment_thresholds: Json;
2437         created_at: string;
2438         default_language: string;
2439         dynamic_pricing_enabled: boolean;
2440         grade_scales: Json;
2441         id: string;
2442         institution_id: string;
2443         leaderboard_min_cohort_size: number;
2444         leaderboard_page_size: number;
2445         league_thresholds: Json | null;
2446         streak_sabbatical_enabled: boolean | null;
2447         success_threshold: number;
2448         wellness_xp_amount: number;
2449     };
2450     Insert: {
2451         accreditation_body?: string;
2452         attainment_thresholds?: Json;
2453         created_at?: string;
2454         default_language?: string;
2455         dynamic_pricing_enabled?: boolean;
2456         grade_scales?: Json;
2457         id?: string;
2458         institution_id: string;
2459         leaderboard_min_cohort_size?: number;
2460         leaderboard_page_size?: number;
2461         league_thresholds?: Json | null;
2462         streak_sabbatical_enabled?: boolean | null;
2463         success_threshold?: number;
2464         wellness_xp_amount?: number;
2465     };
2466     Update: {
2467         accreditation_body?: string;
2468         attainment_thresholds?: Json;
2469         created_at?: string;
2470         default_language?: string;
2471         dynamic_pricing_enabled?: boolean;
2472         grade_scales?: Json;
2473         id?: string;
2474         institution_id?: string;
2475         leaderboard_min_cohort_size?: number;
2476         leaderboard_page_size?: number;
2477         league_thresholds?: Json | null;
2478         streak_sabbatical_enabled?: boolean | null;
2479         success_threshold?: number;
2480         wellness_xp_amount?: number;
2481     };
2482     Relationships: [
2483         {
2484             foreignKeyName: "institution_settings_institution_id_fkey";
2485             columns: ["institution_id"];
2486             isOneToOne: true;
2487             referencedRelation: "institutions";
2488             referencedColumns: ["id"];
2489         },
2490         {
2491             foreignKeyName: "institution_settings_institution_id_fkey";
2492             columns: ["institution_id"];
2493             isOneToOne: true;
2494             referencedRelation: "institutions_public";
2495             referencedColumns: ["id"];
2496         }
2497     ];
2498 };
2499 institutions: {
2500     Row: {
2501         accreditation_body: string | null;
2502         allowed_email_domains: string[];
2503         created_at: string;
2504         id: string;
2505         join_mode: string;
2506         logo_url: string | null;
2507         name: string;

```

```

2508         settings: Json;
2509         slug: string;
2510     };
2511     Insert: {
2512         accreditation_body?: string | null;
2513         allowed_email_domains?: string[];
2514         created_at?: string;
2515         id?: string;
2516         join_mode?: string;
2517         logo_url?: string | null;
2518         name: string;
2519         settings?: Json;
2520         slug: string;
2521     };
2522     Update: {
2523         accreditation_body?: string | null;
2524         allowed_email_domains?: string[];
2525         created_at?: string;
2526         id?: string;
2527         join_mode?: string;
2528         logo_url?: string | null;
2529         name?: string;
2530         settings?: Json;
2531         slug?: string;
2532     };
2533     Relationships: [];
2534 };
2535 invitations: {
2536     Row: {
2537         created_at: string;
2538         created_by: string;
2539         email: string;
2540         expires_at: string;
2541         id: string;
2542         institution_id: string;
2543         role: Database["public"]["Enums"]["user_role"];
2544         token: string;
2545         used_at: string | null;
2546     };
2547     Insert: {
2548         created_at?: string;
2549         created_by: string;
2550         email: string;
2551         expires_at?: string;
2552         id?: string;
2553         institution_id: string;
2554         role: Database["public"]["Enums"]["user_role"];
2555         token: string;
2556         used_at?: string | null;
2557     };
2558     Update: {
2559         created_at?: string;
2560         created_by?: string;
2561         email?: string;
2562         expires_at?: string;
2563         id?: string;
2564         institution_id?: string;
2565         role?: Database["public"]["Enums"]["user_role"];
2566         token?: string;
2567         used_at?: string | null;
2568     };
2569     Relationships: [
2570         {
2571             foreignKeyName: "invitations_institution_id_fkey";
2572             columns: ["institution_id"];
2573             isOneToOne: false;
2574             referencedRelation: "institutions";
2575             referencedColumns: ["id"];
2576         },
2577         {
2578             foreignKeyName: "invitations_institution_id_fkey";
2579             columns: ["institution_id"];
2580             isOneToOne: false;
2581             referencedRelation: "institutions_public";
2582             referencedColumns: ["id"];
2583         }
2584     ];
2585 };
2586 journal_entries: {
2587     Row: {
2588         clo_id: string | null;
2589         content: string;
2590         course_id: string;
2591         created_at: string;
2592         id: string;
2593         is_shared: boolean;
2594         student_id: string;
2595     };
2596     Insert: {
2597         clo_id?: string | null;
2598         content: string;
2599         course_id: string;
2600         created_at?: string;
2601         id?: string;
2602         is_shared?: boolean;
2603         student_id: string;
2604     };
2605     Update: {
2606         clo_id?: string | null;
2607         content?: string;
2608         course_id?: string;
2609         created_at?: string;
2610         id?: string;
2611         is_shared?: boolean;

```



```

2612 |         student_id?: string;
2613 |     };
2614 |     Relationships: [
2615 |     {
2616 |         foreignKeyName: "journal_entries_clo_id_fkey";
2617 |         columns: ["clo_id"];
2618 |         isOneToOne: false;
2619 |         referencedRelation: "learning_outcomes";
2620 |         referencedColumns: ["id"];
2621 |     },
2622 |     {
2623 |         foreignKeyName: "journal_entries_course_id_fkey";
2624 |         columns: ["course_id"];
2625 |         isOneToOne: false;
2626 |         referencedRelation: "courses";
2627 |         referencedColumns: ["id"];
2628 |     },
2629 |     {
2630 |         foreignKeyName: "journal_entries_student_id_fkey";
2631 |         columns: ["student_id"];
2632 |         isOneToOne: false;
2633 |         referencedRelation: "profiles";
2634 |         referencedColumns: ["id"];
2635 |     }
2636 | ];
2637 | };
2638 | knowledge_requests: {
2639 |     Row: {
2640 |         created_at: string;
2641 |         created_by: string;
2642 |         description: string;
2643 |         end_date: string;
2644 |         id: string;
2645 |         institution_id: string;
2646 |         is_active: boolean;
2647 |         max_participants: number | null;
2648 |         quest_type: string;
2649 |         reward_item_id: string | null;
2650 |         reward_type: string;
2651 |         reward_xp_amount: number | null;
2652 |         start_date: string;
2653 |         target_clo_ids: string[] | null;
2654 |         title: string;
2655 |     };
2656 |     Insert: {
2657 |         created_at?: string;
2658 |         created_by: string;
2659 |         description: string;
2660 |         end_date: string;
2661 |         id?: string;
2662 |         institution_id: string;
2663 |         is_active?: boolean;
2664 |         max_participants?: number | null;
2665 |         quest_type: string;
2666 |         reward_item_id?: string | null;
2667 |         reward_type: string;
2668 |         reward_xp_amount?: number | null;
2669 |         start_date: string;
2670 |         target_clo_ids?: string[] | null;
2671 |         title: string;
2672 |     };
2673 |     Update: {
2674 |         created_at?: string;
2675 |         created_by?: string;
2676 |         description?: string;
2677 |         end_date?: string;
2678 |         id?: string;
2679 |         institution_id?: string;
2680 |         is_active?: boolean;
2681 |         max_participants?: number | null;
2682 |         quest_type?: string;
2683 |         reward_item_id?: string | null;
2684 |         reward_type?: string;
2685 |         reward_xp_amount?: number | null;
2686 |         start_date?: string;
2687 |         target_clo_ids?: string[] | null;
2688 |         title?: string;
2689 |     };
2690 |     Relationships: [
2691 |     {
2692 |         foreignKeyName: "knowledge_requests_created_by_fkey";
2693 |         columns: ["created_by"];
2694 |         isOneToOne: false;
2695 |         referencedRelation: "profiles";
2696 |         referencedColumns: ["id"];
2697 |     },
2698 |     {
2699 |         foreignKeyName: "knowledge_requests_institution_id_fkey";
2700 |         columns: ["institution_id"];
2701 |         isOneToOne: false;
2702 |         referencedRelation: "institutions";
2703 |         referencedColumns: ["id"];
2704 |     },
2705 |     {
2706 |         foreignKeyName: "knowledge_requests_institution_id_fkey";
2707 |         columns: ["institution_id"];
2708 |         isOneToOne: false;
2709 |         referencedRelation: "institutions_public";
2710 |         referencedColumns: ["id"];
2711 |     },
2712 |     {
2713 |         foreignKeyName: "knowledge_requests_reward_item_id_fkey";
2714 |         columns: ["reward_item_id"];
2715 |         isOneToOne: false;

```

```

2716 |         referencedRelation: "marketplace_items";
2717 |         referencedColumns: ["id"];
2718 |     }
2719 | };
2720 | };
2721 | learning_outcomes: {
2722 |   Row: {
2723 |     blooms_level: Database["public"]["Enums"]["blooms_level"] | null;
2724 |     course_id: string | null;
2725 |     created_at: string;
2726 |     created_by: string | null;
2727 |     description: string | null;
2728 |     id: string;
2729 |     institution_id: string;
2730 |     program_id: string | null;
2731 |     sort_order: number;
2732 |     title: string;
2733 |     title_ar: string | null;
2734 |     tutor_autonomy_level: string | null;
2735 |     type: Database["public"]["Enums"]["outcome_type"];
2736 |     updated_at: string;
2737 |     weight: number | null;
2738 |   };
2739 |   Insert: {
2740 |     blooms_level?: Database["public"]["Enums"]["blooms_level"] | null;
2741 |     course_id?: string | null;
2742 |     created_at?: string;
2743 |     created_by?: string | null;
2744 |     description?: string | null;
2745 |     id?: string;
2746 |     institution_id: string;
2747 |     program_id?: string | null;
2748 |     sort_order?: number;
2749 |     title: string;
2750 |     title_ar?: string | null;
2751 |     tutor_autonomy_level?: string | null;
2752 |     type: Database["public"]["Enums"]["outcome_type"];
2753 |     updated_at?: string;
2754 |     weight?: number | null;
2755 |   };
2756 |   Update: {
2757 |     blooms_level?: Database["public"]["Enums"]["blooms_level"] | null;
2758 |     course_id?: string | null;
2759 |     created_at?: string;
2760 |     created_by?: string | null;
2761 |     description?: string | null;
2762 |     id?: string;
2763 |     institution_id?: string;
2764 |     program_id?: string | null;
2765 |     sort_order?: number;
2766 |     title?: string;
2767 |     title_ar?: string | null;
2768 |     tutor_autonomy_level?: string | null;
2769 |     type?: Database["public"]["Enums"]["outcome_type"];
2770 |     updated_at?: string;
2771 |     weight?: number | null;
2772 |   };
2773 |   Relationships: [
2774 |     {
2775 |       foreignKeyName: "learning_outcomes_course_id_fkey";
2776 |       columns: ["course_id"];
2777 |       isOneToOne: false;
2778 |       referencedRelation: "courses";
2779 |       referencedColumns: ["id"];
2780 |     },
2781 |     {
2782 |       foreignKeyName: "learning_outcomes_created_by_fkey";
2783 |       columns: ["created_by"];
2784 |       isOneToOne: false;
2785 |       referencedRelation: "profiles";
2786 |       referencedColumns: ["id"];
2787 |     },
2788 |     {
2789 |       foreignKeyName: "learning_outcomes_institution_id_fkey";
2790 |       columns: ["institution_id"];
2791 |       isOneToOne: false;
2792 |       referencedRelation: "institutions";
2793 |       referencedColumns: ["id"];
2794 |     },
2795 |     {
2796 |       foreignKeyName: "learning_outcomes_institution_id_fkey";
2797 |       columns: ["institution_id"];
2798 |       isOneToOne: false;
2799 |       referencedRelation: "institutions_public";
2800 |       referencedColumns: ["id"];
2801 |     },
2802 |     {
2803 |       foreignKeyName: "learning_outcomes_program_id_fkey";
2804 |       columns: ["program_id"];
2805 |       isOneToOne: false;
2806 |       referencedRelation: "programs";
2807 |       referencedColumns: ["id"];
2808 |     }
2809 |   ];
2810 | };
2811 | learning_path_nodes: {
2812 |   Row: {
2813 |     assignment_id: string;
2814 |     course_id: string;
2815 |     created_at: string;
2816 |     id: string;
2817 |     prerequisite_node_id: string | null;
2818 |     sort_order: number;
2819 |     unlock_threshold: number;

```

```

2820 | };
2821 | Insert: {
2822 |   assignment_id: string;
2823 |   course_id: string;
2824 |   created_at?: string;
2825 |   id?: string;
2826 |   prerequisite_node_id?: string | null;
2827 |   sort_order?: number;
2828 |   unlock_threshold?: number;
2829 | };
2830 | Update: {
2831 |   assignment_id?: string;
2832 |   course_id?: string;
2833 |   created_at?: string;
2834 |   id?: string;
2835 |   prerequisite_node_id?: string | null;
2836 |   sort_order?: number;
2837 |   unlock_threshold?: number;
2838 | };
2839 | Relationships: [
2840 |   {
2841 |     foreignKeyName: "learning_path_nodes_assignment_id_fkey";
2842 |     columns: ["assignment_id"];
2843 |     isOneToOne: false;
2844 |     referencedRelation: "assignments";
2845 |     referencedColumns: ["id"];
2846 |   },
2847 |   {
2848 |     foreignKeyName: "learning_path_nodes_course_id_fkey";
2849 |     columns: ["course_id"];
2850 |     isOneToOne: false;
2851 |     referencedRelation: "courses";
2852 |     referencedColumns: ["id"];
2853 |   },
2854 |   {
2855 |     foreignKeyName: "learning_path_nodes_prerequisite_node_id_fkey";
2856 |     columns: ["prerequisite_node_id"];
2857 |     isOneToOne: false;
2858 |     referencedRelation: "learning_path_nodes";
2859 |     referencedColumns: ["id"];
2860 |   }
2861 | ];
2862 | };
2863 | login_attempts: {
2864 |   Row: {
2865 |     attempt_count: number;
2866 |     email: string;
2867 |     locked_until: string | null;
2868 |     updated_at: string;
2869 |   };
2870 |   Insert: {
2871 |     attempt_count?: number;
2872 |     email: string;
2873 |     locked_until?: string | null;
2874 |     updated_at?: string;
2875 |   };
2876 |   Update: {
2877 |     attempt_count?: number;
2878 |     email?: string;
2879 |     locked_until?: string | null;
2880 |     updated_at?: string;
2881 |   };
2882 |   Relationships: [];
2883 | };
2884 | marketplace_items: {
2885 |   Row: {
2886 |     category: Database["public"]["Enums"]["marketplace_item_category"];
2887 |     created_at: string;
2888 |     description: string;
2889 |     dynamic_price_override: number | null;
2890 |     icon_identifier: string;
2891 |     id: string;
2892 |     institution_id: string;
2893 |     is_active: boolean;
2894 |     level_requirement: number;
2895 |     metadata: Json | null;
2896 |     name: string;
2897 |     stock_quantity: number | null;
2898 |     stock_type: Database["public"]["Enums"]["marketplace_stock_type"];
2899 |     sub_category: Database["public"]["Enums"]["marketplace_item_sub_category"];
2900 |     updated_at: string;
2901 |     xp_price: number;
2902 |   };
2903 |   Insert: {
2904 |     category: Database["public"]["Enums"]["marketplace_item_category"];
2905 |     created_at?: string;
2906 |     description: string;
2907 |     dynamic_price_override?: number | null;
2908 |     icon_identifier: string;
2909 |     id?: string;
2910 |     institution_id: string;
2911 |     is_active?: boolean;
2912 |     level_requirement?: number;
2913 |     metadata?: Json | null;
2914 |     name: string;
2915 |     stock_quantity?: number | null;
2916 |     stock_type?: Database["public"]["Enums"]["marketplace_stock_type"];
2917 |     sub_category: Database["public"]["Enums"]["marketplace_item_sub_category"];
2918 |     updated_at?: string;
2919 |     xp_price: number;
2920 |   };
2921 |   Update: {
2922 |     category?: Database["public"]["Enums"]["marketplace_item_category"];
2923 |     created_at?: string;

```

```

2924 |         description?: string;
2925 |         dynamic_price_override?: number | null;
2926 |         icon_identifier?: string;
2927 |         id?: string;
2928 |         institution_id?: string;
2929 |         is_active?: boolean;
2930 |         level_requirement?: number;
2931 |         metadata?: Json | null;
2932 |         name?: string;
2933 |         stock_quantity?: number | null;
2934 |         stock_type?: Database["public"]["Enums"]["marketplace_stock_type"];
2935 |         sub_category?: Database["public"]["Enums"]["marketplace_item_sub_category"];
2936 |         updated_at?: string;
2937 |         xp_price?: number;
2938 |     };
2939 |     Relationships: [
2940 |     {
2941 |         foreignKeyName: "marketplace_items_institution_id_fkey";
2942 |         columns: ["institution_id"];
2943 |         isOneToOne: false;
2944 |         referencedRelation: "institutions";
2945 |         referencedColumns: ["id"];
2946 |     },
2947 |     {
2948 |         foreignKeyName: "marketplace_items_institution_id_fkey";
2949 |         columns: ["institution_id"];
2950 |         isOneToOne: false;
2951 |         referencedRelation: "institutions_public";
2952 |         referencedColumns: ["id"];
2953 |     }
2954 | ];
2955 | };
2956 | mastery_recovery_pathways: {
2957 |     Row: {
2958 |         activated_at: string;
2959 |         ai_tutor_completed: boolean;
2960 |         ai_tutor_completed_at: string | null;
2961 |         clo_id: string;
2962 |         completed_at: string | null;
2963 |         course_id: string;
2964 |         created_at: string;
2965 |         expired_at: string | null;
2966 |         failure_count: number;
2967 |         id: string;
2968 |         institution_id: string;
2969 |         peer_suggestion_applicable: boolean;
2970 |         peer_suggestion_shown: boolean;
2971 |         practice_completed: boolean;
2972 |         practice_completed_at: string | null;
2973 |         retry_outcome: string | null;
2974 |         retry_quiz_attempt_id: string | null;
2975 |         status: string;
2976 |         student_id: string;
2977 |         updated_at: string;
2978 |     };
2979 |     Insert: {
2980 |         activated_at?: string;
2981 |         ai_tutor_completed?: boolean;
2982 |         ai_tutor_completed_at?: string | null;
2983 |         clo_id: string;
2984 |         completed_at?: string | null;
2985 |         course_id: string;
2986 |         created_at?: string;
2987 |         expired_at?: string | null;
2988 |         failure_count?: number;
2989 |         id?: string;
2990 |         institution_id: string;
2991 |         peer_suggestion_applicable?: boolean;
2992 |         peer_suggestion_shown?: boolean;
2993 |         practice_completed?: boolean;
2994 |         practice_completed_at?: string | null;
2995 |         retry_outcome?: string | null;
2996 |         retry_quiz_attempt_id?: string | null;
2997 |         status?: string;
2998 |         student_id: string;
2999 |         updated_at?: string;
3000 |     };
3001 |     Update: {
3002 |         activated_at?: string;
3003 |         ai_tutor_completed?: boolean;
3004 |         ai_tutor_completed_at?: string | null;
3005 |         clo_id?: string;
3006 |         completed_at?: string | null;
3007 |         course_id?: string;
3008 |         created_at?: string;
3009 |         expired_at?: string | null;
3010 |         failure_count?: number;
3011 |         id?: string;
3012 |         institution_id?: string;
3013 |         peer_suggestion_applicable?: boolean;
3014 |         peer_suggestion_shown?: boolean;
3015 |         practice_completed?: boolean;
3016 |         practice_completed_at?: string | null;
3017 |         retry_outcome?: string | null;
3018 |         retry_quiz_attempt_id?: string | null;
3019 |         status?: string;
3020 |         student_id?: string;
3021 |         updated_at?: string;
3022 |     };
3023 |     Relationships: [
3024 |     {
3025 |         foreignKeyName: "mastery_recovery_pathways_clo_id_fkey";
3026 |         columns: ["clo_id"];
3027 |         isOneToOne: false;

```

```

3028         referencedRelation: "learning_outcomes";
3029         referencedColumns: ["id"];
3030     },
3031     {
3032         foreignKeyName: "mastery_recovery_pathways_course_id_fkey";
3033         columns: ["course_id"];
3034         isOneToOne: false;
3035         referencedRelation: "courses";
3036         referencedColumns: ["id"];
3037     },
3038     {
3039         foreignKeyName: "mastery_recovery_pathways_institution_id_fkey";
3040         columns: ["institution_id"];
3041         isOneToOne: false;
3042         referencedRelation: "institutions";
3043         referencedColumns: ["id"];
3044     },
3045     {
3046         foreignKeyName: "mastery_recovery_pathways_institution_id_fkey";
3047         columns: ["institution_id"];
3048         isOneToOne: false;
3049         referencedRelation: "institutions_public";
3050         referencedColumns: ["id"];
3051     },
3052     {
3053         foreignKeyName: "mastery_recovery_pathways_student_id_fkey";
3054         columns: ["student_id"];
3055         isOneToOne: false;
3056         referencedRelation: "profiles";
3057         referencedColumns: ["id"];
3058     }
3059 ];
3060 };
3061 micro_assessment_schedule: {
3062     Row: {
3063         assessment_type: string;
3064         completed_at: string | null;
3065         created_at: string;
3066         dismissal_count: number;
3067         id: string;
3068         question_ids: string[];
3069         scheduled_at: string;
3070         scheduled_day: number;
3071         status: string;
3072         student_id: string;
3073     };
3074     Insert: {
3075         assessment_type: string;
3076         completed_at?: string | null;
3077         created_at?: string;
3078         dismissal_count?: number;
3079         id?: string;
3080         question_ids?: string[];
3081         scheduled_at: string;
3082         scheduled_day: number;
3083         status?: string;
3084         student_id: string;
3085     };
3086     Update: {
3087         assessment_type?: string;
3088         completed_at?: string | null;
3089         created_at?: string;
3090         dismissal_count?: number;
3091         id?: string;
3092         question_ids?: string[];
3093         scheduled_at?: string;
3094         scheduled_day?: number;
3095         status?: string;
3096         student_id?: string;
3097     };
3098     Relationships: [
3099         {
3100             foreignKeyName: "micro_assessment_schedule_student_id_fkey";
3101             columns: ["student_id"];
3102             isOneToOne: false;
3103             referencedRelation: "profiles";
3104             referencedColumns: ["id"];
3105         }
3106     ];
3107 };
3108 notifications: {
3109     Row: {
3110         body: string | null;
3111         created_at: string;
3112         id: string;
3113         is_read: boolean;
3114         metadata: Json | null;
3115         title: string;
3116         type: string;
3117         user_id: string;
3118     };
3119     Insert: {
3120         body?: string | null;
3121         created_at?: string;
3122         id?: string;
3123         is_read?: boolean;
3124         metadata?: Json | null;
3125         title: string;
3126         type: string;
3127         user_id: string;
3128     };
3129     Update: {
3130         body?: string | null;
3131         created_at?: string;

```

```

3132         id?: string;
3133         is_read?: boolean;
3134         metadata?: Json | null;
3135         title?: string;
3136         type?: string;
3137         user_id?: string;
3138     };
3139     Relationships: [
3140     {
3141         foreignKeyName: "notifications_user_id_fkey";
3142         columns: ["user_id"];
3143         isOneToOne: false;
3144         referencedRelation: "profiles";
3145         referencedColumns: ["id"];
3146     }
3147     ];
3148 };
3149 onboarding_progress: {
3150     Row: {
3151         assessment_version: number;
3152         baseline_completed: boolean;
3153         baseline_course_ids: string[] | null;
3154         created_at: string;
3155         current_step: string;
3156         day1_completed: boolean;
3157         id: string;
3158         learning_style_completed: boolean;
3159         micro_assessment_day: number;
3160         micro_assessment_dismissals: number;
3161         personality_completed: boolean;
3162         profile_completeness: number;
3163         self_efficacy_completed: boolean;
3164         skipped_sections: string[] | null;
3165         student_id: string;
3166         study_strategy_completed: boolean;
3167         updated_at: string;
3168     };
3169     Insert: {
3170         assessment_version?: number;
3171         baseline_completed?: boolean;
3172         baseline_course_ids?: string[] | null;
3173         created_at?: string;
3174         current_step?: string;
3175         day1_completed?: boolean;
3176         id?: string;
3177         learning_style_completed?: boolean;
3178         micro_assessment_day?: number;
3179         micro_assessment_dismissals?: number;
3180         personality_completed?: boolean;
3181         profile_completeness?: number;
3182         self_efficacy_completed?: boolean;
3183         skipped_sections?: string[] | null;
3184         student_id: string;
3185         study_strategy_completed?: boolean;
3186         updated_at?: string;
3187     };
3188     Update: {
3189         assessment_version?: number;
3190         baseline_completed?: boolean;
3191         baseline_course_ids?: string[] | null;
3192         created_at?: string;
3193         current_step?: string;
3194         day1_completed?: boolean;
3195         id?: string;
3196         learning_style_completed?: boolean;
3197         micro_assessment_day?: number;
3198         micro_assessment_dismissals?: number;
3199         personality_completed?: boolean;
3200         profile_completeness?: number;
3201         self_efficacy_completed?: boolean;
3202         skipped_sections?: string[] | null;
3203         student_id?: string;
3204         study_strategy_completed?: boolean;
3205         updated_at?: string;
3206     };
3207     Relationships: [
3208     {
3209         foreignKeyName: "onboarding_progress_student_id_fkey";
3210         columns: ["student_id"];
3211         isOneToOne: true;
3212         referencedRelation: "profiles";
3213         referencedColumns: ["id"];
3214     }
3215     ];
3216 };
3217 onboarding_questions: {
3218     Row: {
3219         assessment_type: string;
3220         clo_id: string | null;
3221         correct_option: number | null;
3222         course_id: string | null;
3223         created_at: string;
3224         difficulty_level: string | null;
3225         dimension: string | null;
3226         id: string;
3227         institution_id: string;
3228         is_active: boolean;
3229         options: Json | null;
3230         options_ar: Json | null;
3231         question_text: string;
3232         question_text_ar: string | null;
3233         sort_order: number;
3234         updated_at: string;
3235         weight: number | null;

```

```

3236 | };
3237 | Insert: {
3238 |   assessment_type: string;
3239 |   clo_id?: string | null;
3240 |   correct_option?: number | null;
3241 |   course_id?: string | null;
3242 |   created_at?: string;
3243 |   difficulty_level?: string | null;
3244 |   dimension?: string | null;
3245 |   id?: string;
3246 |   institution_id: string;
3247 |   is_active?: boolean;
3248 |   options?: Json | null;
3249 |   options_ar?: Json | null;
3250 |   question_text: string;
3251 |   question_text_ar?: string | null;
3252 |   sort_order?: number;
3253 |   updated_at?: string;
3254 |   weight?: number | null;
3255 | };
3256 | Update: {
3257 |   assessment_type?: string;
3258 |   clo_id?: string | null;
3259 |   correct_option?: number | null;
3260 |   course_id?: string | null;
3261 |   created_at?: string;
3262 |   difficulty_level?: string | null;
3263 |   dimension?: string | null;
3264 |   id?: string;
3265 |   institution_id?: string;
3266 |   is_active?: boolean;
3267 |   options?: Json | null;
3268 |   options_ar?: Json | null;
3269 |   question_text?: string;
3270 |   question_text_ar?: string | null;
3271 |   sort_order?: number;
3272 |   updated_at?: string;
3273 |   weight?: number | null;
3274 | };
3275 | Relationships: [
3276 |   {
3277 |     foreignKeyName: "onboarding_questions_clo_id_fkey";
3278 |     columns: ["clo_id"];
3279 |     isOneToOne: false;
3280 |     referencedRelation: "learning_outcomes";
3281 |     referencedColumns: ["id"];
3282 |   },
3283 |   {
3284 |     foreignKeyName: "onboarding_questions_course_id_fkey";
3285 |     columns: ["course_id"];
3286 |     isOneToOne: false;
3287 |     referencedRelation: "courses";
3288 |     referencedColumns: ["id"];
3289 |   },
3290 |   {
3291 |     foreignKeyName: "onboarding_questions_institution_id_fkey";
3292 |     columns: ["institution_id"];
3293 |     isOneToOne: false;
3294 |     referencedRelation: "institutions";
3295 |     referencedColumns: ["id"];
3296 |   },
3297 |   {
3298 |     foreignKeyName: "onboarding_questions_institution_id_fkey";
3299 |     columns: ["institution_id"];
3300 |     isOneToOne: false;
3301 |     referencedRelation: "institutions_public";
3302 |     referencedColumns: ["id"];
3303 |   }
3304 | ];
3305 | };
3306 | onboarding_responses: {
3307 |   Row: {
3308 |     assessment_version: number;
3309 |     created_at: string;
3310 |     id: string;
3311 |     question_id: string;
3312 |     score_contribution: number | null;
3313 |     selected_option: number;
3314 |     student_id: string;
3315 |   };
3316 |   Insert: {
3317 |     assessment_version?: number;
3318 |     created_at?: string;
3319 |     id?: string;
3320 |     question_id: string;
3321 |     score_contribution?: number | null;
3322 |     selected_option: number;
3323 |     student_id: string;
3324 |   };
3325 |   Update: {
3326 |     assessment_version?: number;
3327 |     created_at?: string;
3328 |     id?: string;
3329 |     question_id?: string;
3330 |     score_contribution?: number | null;
3331 |     selected_option?: number;
3332 |     student_id?: string;
3333 |   };
3334 |   Relationships: [
3335 |     {
3336 |       foreignKeyName: "onboarding_responses_question_id_fkey";
3337 |       columns: ["question_id"];
3338 |       isOneToOne: false;
3339 |       referencedRelation: "onboarding_questions";

```

```

3340         referencedColumns: ["id"];
3341     },
3342     {
3343         foreignKeyName: "onboarding_responses_student_id_fkey";
3344         columns: ["student_id"];
3345         isOneToOne: false;
3346         referencedRelation: "profiles";
3347         referencedColumns: ["id"];
3348     }
3349 ];
3350 };
3351 outcome_attainment: {
3352     Row: {
3353         attainment_percent: number;
3354         course_id: string | null;
3355         id: string;
3356         last_calculated_at: string;
3357         outcome_id: string;
3358         sample_count: number;
3359         scope: Database["public"]["Enums"]["attainment_scope"];
3360         student_id: string | null;
3361     };
3362     Insert: {
3363         attainment_percent?: number;
3364         course_id?: string | null;
3365         id?: string;
3366         last_calculated_at?: string;
3367         outcome_id: string;
3368         sample_count?: number;
3369         scope: Database["public"]["Enums"]["attainment_scope"];
3370         student_id?: string | null;
3371     };
3372     Update: {
3373         attainment_percent?: number;
3374         course_id?: string | null;
3375         id?: string;
3376         last_calculated_at?: string;
3377         outcome_id?: string;
3378         sample_count?: number;
3379         scope?: Database["public"]["Enums"]["attainment_scope"];
3380         student_id?: string | null;
3381     };
3382     Relationships: [
3383         {
3384             foreignKeyName: "outcome_attainment_course_id_fkey";
3385             columns: ["course_id"];
3386             isOneToOne: false;
3387             referencedRelation: "courses";
3388             referencedColumns: ["id"];
3389         },
3390         {
3391             foreignKeyName: "outcome_attainment_outcome_id_fkey";
3392             columns: ["outcome_id"];
3393             isOneToOne: false;
3394             referencedRelation: "learning_outcomes";
3395             referencedColumns: ["id"];
3396         },
3397         {
3398             foreignKeyName: "outcome_attainment_student_id_fkey";
3399             columns: ["student_id"];
3400             isOneToOne: false;
3401             referencedRelation: "profiles";
3402             referencedColumns: ["id"];
3403         }
3404     ];
3405 };
3406 outcome_mappings: {
3407     Row: {
3408         created_at: string;
3409         id: string;
3410         source_outcome_id: string;
3411         target_outcome_id: string;
3412         weight: number;
3413     };
3414     Insert: {
3415         created_at?: string;
3416         id?: string;
3417         source_outcome_id: string;
3418         target_outcome_id: string;
3419         weight?: number;
3420     };
3421     Update: {
3422         created_at?: string;
3423         id?: string;
3424         source_outcome_id?: string;
3425         target_outcome_id?: string;
3426         weight?: number;
3427     };
3428     Relationships: [
3429         {
3430             foreignKeyName: "outcome_mappings_source_outcome_id_fkey";
3431             columns: ["source_outcome_id"];
3432             isOneToOne: false;
3433             referencedRelation: "learning_outcomes";
3434             referencedColumns: ["id"];
3435         },
3436         {
3437             foreignKeyName: "outcome_mappings_target_outcome_id_fkey";
3438             columns: ["target_outcome_id"];
3439             isOneToOne: false;
3440             referencedRelation: "learning_outcomes";
3441             referencedColumns: ["id"];
3442         }
3443     ];

```



```

3444 | };
3445 | parent_student_links: {
3446 |   Row: {
3447 |     created_at: string;
3448 |     id: string;
3449 |     parent_id: string;
3450 |     relationship: string;
3451 |     student_id: string;
3452 |     verified: boolean;
3453 |   };
3454 |   Insert: {
3455 |     created_at?: string;
3456 |     id?: string;
3457 |     parent_id: string;
3458 |     relationship: string;
3459 |     student_id: string;
3460 |     verified?: boolean;
3461 |   };
3462 |   Update: {
3463 |     created_at?: string;
3464 |     id?: string;
3465 |     parent_id?: string;
3466 |     relationship?: string;
3467 |     student_id?: string;
3468 |     verified?: boolean;
3469 |   };
3470 |   Relationships: [
3471 |     {
3472 |       foreignKeyName: "parent_student_links_parent_id_fkey";
3473 |       columns: ["parent_id"];
3474 |       isOneToOne: false;
3475 |       referencedRelation: "profiles";
3476 |       referencedColumns: ["id"];
3477 |     },
3478 |     {
3479 |       foreignKeyName: "parent_student_links_student_id_fkey";
3480 |       columns: ["student_id"];
3481 |       isOneToOne: false;
3482 |       referencedRelation: "profiles";
3483 |       referencedColumns: ["id"];
3484 |     }
3485 |   ];
3486 | };
3487 | peer_teaching_moments: {
3488 |   Row: {
3489 |     author_id: string;
3490 |     avg_clarity_rating: number | null;
3491 |     avg_helpfulness_rating: number | null;
3492 |     clo_id: string;
3493 |     created_at: string;
3494 |     explanation_text: string;
3495 |     id: string;
3496 |     media_url: string | null;
3497 |     status: string;
3498 |     team_id: string;
3499 |     title: string;
3500 |     view_count: number;
3501 |   };
3502 |   Insert: {
3503 |     author_id: string;
3504 |     avg_clarity_rating?: number | null;
3505 |     avg_helpfulness_rating?: number | null;
3506 |     clo_id: string;
3507 |     created_at?: string;
3508 |     explanation_text: string;
3509 |     id?: string;
3510 |     media_url?: string | null;
3511 |     status?: string;
3512 |     team_id: string;
3513 |     title: string;
3514 |     view_count?: number;
3515 |   };
3516 |   Update: {
3517 |     author_id?: string;
3518 |     avg_clarity_rating?: number | null;
3519 |     avg_helpfulness_rating?: number | null;
3520 |     clo_id?: string;
3521 |     created_at?: string;
3522 |     explanation_text?: string;
3523 |     id?: string;
3524 |     media_url?: string | null;
3525 |     status?: string;
3526 |     team_id?: string;
3527 |     title?: string;
3528 |     view_count?: number;
3529 |   };
3530 |   Relationships: [
3531 |     {
3532 |       foreignKeyName: "peer_teaching_moments_author_id_fkey";
3533 |       columns: ["author_id"];
3534 |       isOneToOne: false;
3535 |       referencedRelation: "profiles";
3536 |       referencedColumns: ["id"];
3537 |     },
3538 |     {
3539 |       foreignKeyName: "peer_teaching_moments_clo_id_fkey";
3540 |       columns: ["clo_id"];
3541 |       isOneToOne: false;
3542 |       referencedRelation: "learning_outcomes";
3543 |       referencedColumns: ["id"];
3544 |     },
3545 |     {
3546 |       foreignKeyName: "peer_teaching_moments_team_id_fkey";
3547 |       columns: ["team_id"];

```

```

3548         isOneToOne: false;
3549         referencedRelation: "teams";
3550         referencedColumns: ["id"];
3551     }
3552 };
3553 };
3554 planner_tasks: {
3555     Row: {
3556         assignment_id: string | null;
3557         clo_id: string | null;
3558         completed_at: string | null;
3559         course_id: string | null;
3560         created_at: string | null;
3561         description: string | null;
3562         due_date: string | null;
3563         id: string;
3564         planned_date: string | null;
3565         priority: string | null;
3566         sort_order: number | null;
3567         status: string | null;
3568         student_id: string;
3569         title: string;
3570         updated_at: string | null;
3571     };
3572     Insert: {
3573         assignment_id?: string | null;
3574         clo_id?: string | null;
3575         completed_at?: string | null;
3576         course_id?: string | null;
3577         created_at?: string | null;
3578         description?: string | null;
3579         due_date?: string | null;
3580         id?: string;
3581         planned_date?: string | null;
3582         priority?: string | null;
3583         sort_order?: number | null;
3584         status?: string | null;
3585         student_id: string;
3586         title: string;
3587         updated_at?: string | null;
3588     };
3589     Update: {
3590         assignment_id?: string | null;
3591         clo_id?: string | null;
3592         completed_at?: string | null;
3593         course_id?: string | null;
3594         created_at?: string | null;
3595         description?: string | null;
3596         due_date?: string | null;
3597         id?: string;
3598         planned_date?: string | null;
3599         priority?: string | null;
3600         sort_order?: number | null;
3601         status?: string | null;
3602         student_id?: string;
3603         title?: string;
3604         updated_at?: string | null;
3605     };
3606     Relationships: [
3607         {
3608             foreignKeyName: "planner_tasks_assignment_id_fkey";
3609             columns: ["assignment_id"];
3610             isOneToOne: false;
3611             referencedRelation: "assignments";
3612             referencedColumns: ["id"];
3613         },
3614         {
3615             foreignKeyName: "planner_tasks_clo_id_fkey";
3616             columns: ["clo_id"];
3617             isOneToOne: false;
3618             referencedRelation: "learning_outcomes";
3619             referencedColumns: ["id"];
3620         },
3621         {
3622             foreignKeyName: "planner_tasks_course_id_fkey";
3623             columns: ["course_id"];
3624             isOneToOne: false;
3625             referencedRelation: "courses";
3626             referencedColumns: ["id"];
3627         },
3628         {
3629             foreignKeyName: "planner_tasks_student_id_fkey";
3630             columns: ["student_id"];
3631             isOneToOne: false;
3632             referencedRelation: "profiles";
3633             referencedColumns: ["id"];
3634         }
3635     ];
3636 };
3637 profiles: {
3638     Row: {
3639         accessibility_preferences: Json | null;
3640         avatar_url: string | null;
3641         created_at: string;
3642         email: string;
3643         email_preferences: Json | null;
3644         email_verified_at: string | null;
3645         full_name: string;
3646         id: string;
3647         institution_id: string;
3648         is_active: boolean;
3649         language_preference: string;
3650         last_seen_at: string | null;
3651         notification_preferences: Json;

```

```

3652 |         onboarding_completed: boolean;
3653 |         portfolio_public: boolean;
3654 |         portfolio_sharing_permitted: boolean;
3655 |         preferred_language: string | null;
3656 |         role: Database["public"]["Enums"]["user_role"];
3657 |         search_vector: unknown;
3658 |         status: string;
3659 |         theme_preference: string;
3660 |         tos_accepted_at: string | null;
3661 |         tour_completed_at: string | null;
3662 |     };
3663 |     Insert: {
3664 |         accessibility_preferences?: Json | null;
3665 |         avatar_url?: string | null;
3666 |         created_at?: string;
3667 |         email: string;
3668 |         email_preferences?: Json | null;
3669 |         email_verified_at?: string | null;
3670 |         full_name: string;
3671 |         id: string;
3672 |         institution_id: string;
3673 |         is_active?: boolean;
3674 |         language_preference?: string;
3675 |         last_seen_at?: string | null;
3676 |         notification_preferences?: Json;
3677 |         onboarding_completed?: boolean;
3678 |         portfolio_public?: boolean;
3679 |         portfolio_sharing_permitted?: boolean;
3680 |         preferred_language?: string | null;
3681 |         role?: Database["public"]["Enums"]["user_role"];
3682 |         search_vector?: unknown;
3683 |         status?: string;
3684 |         theme_preference?: string;
3685 |         tos_accepted_at?: string | null;
3686 |         tour_completed_at?: string | null;
3687 |     };
3688 |     Update: {
3689 |         accessibility_preferences?: Json | null;
3690 |         avatar_url?: string | null;
3691 |         created_at?: string;
3692 |         email?: string;
3693 |         email_preferences?: Json | null;
3694 |         email_verified_at?: string | null;
3695 |         full_name?: string;
3696 |         id?: string;
3697 |         institution_id?: string;
3698 |         is_active?: boolean;
3699 |         language_preference?: string;
3700 |         last_seen_at?: string | null;
3701 |         notification_preferences?: Json;
3702 |         onboarding_completed?: boolean;
3703 |         portfolio_public?: boolean;
3704 |         portfolio_sharing_permitted?: boolean;
3705 |         preferred_language?: string | null;
3706 |         role?: Database["public"]["Enums"]["user_role"];
3707 |         search_vector?: unknown;
3708 |         status?: string;
3709 |         theme_preference?: string;
3710 |         tos_accepted_at?: string | null;
3711 |         tour_completed_at?: string | null;
3712 |     };
3713 |     Relationships: [
3714 |         {
3715 |             foreignKeyName: "profiles_institution_id_fkey";
3716 |             columns: ["institution_id"];
3717 |             isOneToOne: false;
3718 |             referencedRelation: "institutions";
3719 |             referencedColumns: ["id"];
3720 |         },
3721 |         {
3722 |             foreignKeyName: "profiles_institution_id_fkey";
3723 |             columns: ["institution_id"];
3724 |             isOneToOne: false;
3725 |             referencedRelation: "institutions_public";
3726 |             referencedColumns: ["id"];
3727 |         }
3728 |     ];
3729 | };
3730 | program_accreditations: {
3731 |     Row: {
3732 |         accreditation_body: string;
3733 |         accreditation_date: string | null;
3734 |         created_at: string;
3735 |         framework_version: string | null;
3736 |         id: string;
3737 |         next_review_date: string | null;
3738 |         program_id: string;
3739 |         status: string;
3740 |     };
3741 |     Insert: {
3742 |         accreditation_body: string;
3743 |         accreditation_date?: string | null;
3744 |         created_at?: string;
3745 |         framework_version?: string | null;
3746 |         id?: string;
3747 |         next_review_date?: string | null;
3748 |         program_id: string;
3749 |         status?: string;
3750 |     };
3751 |     Update: {
3752 |         accreditation_body?: string;
3753 |         accreditation_date?: string | null;
3754 |         created_at?: string;
3755 |         framework_version?: string | null;

```

```

3756 |         id?: string;
3757 |         next_review_date?: string | null;
3758 |         program_id?: string;
3759 |         status?: string;
3760 |     };
3761 |     Relationships: [
3762 |     {
3763 |         foreignKeyName: "program_accreditations_program_id_fkey";
3764 |         columns: ["program_id"];
3765 |         isOneToOne: false;
3766 |         referencedRelation: "programs";
3767 |         referencedColumns: ["id"];
3768 |     }
3769 | ];
3770 | };
3771 | programs: {
3772 |     Row: {
3773 |         code: string;
3774 |         coordinator_id: string | null;
3775 |         created_at: string;
3776 |         department_id: string | null;
3777 |         description: string | null;
3778 |         id: string;
3779 |         institution_id: string;
3780 |         is_active: boolean;
3781 |         name: string;
3782 |         name_ar: string | null;
3783 |     };
3784 |     Insert: {
3785 |         code: string;
3786 |         coordinator_id?: string | null;
3787 |         created_at?: string;
3788 |         department_id?: string | null;
3789 |         description?: string | null;
3790 |         id?: string;
3791 |         institution_id: string;
3792 |         is_active?: boolean;
3793 |         name: string;
3794 |         name_ar?: string | null;
3795 |     };
3796 |     Update: {
3797 |         code?: string;
3798 |         coordinator_id?: string | null;
3799 |         created_at?: string;
3800 |         department_id?: string | null;
3801 |         description?: string | null;
3802 |         id?: string;
3803 |         institution_id?: string;
3804 |         is_active?: boolean;
3805 |         name?: string;
3806 |         name_ar?: string | null;
3807 |     };
3808 |     Relationships: [
3809 |     {
3810 |         foreignKeyName: "programs_coordinator_id_fkey";
3811 |         columns: ["coordinator_id"];
3812 |         isOneToOne: false;
3813 |         referencedRelation: "profiles";
3814 |         referencedColumns: ["id"];
3815 |     },
3816 |     {
3817 |         foreignKeyName: "programs_department_id_fkey";
3818 |         columns: ["department_id"];
3819 |         isOneToOne: false;
3820 |         referencedRelation: "departments";
3821 |         referencedColumns: ["id"];
3822 |     },
3823 |     {
3824 |         foreignKeyName: "programs_institution_id_fkey";
3825 |         columns: ["institution_id"];
3826 |         isOneToOne: false;
3827 |         referencedRelation: "institutions";
3828 |         referencedColumns: ["id"];
3829 |     },
3830 |     {
3831 |         foreignKeyName: "programs_institution_id_fkey";
3832 |         columns: ["institution_id"];
3833 |         isOneToOne: false;
3834 |         referencedRelation: "institutions_public";
3835 |         referencedColumns: ["id"];
3836 |     }
3837 | ];
3838 | };
3839 | question_analytics: {
3840 |     Row: {
3841 |         avg_response_time_seconds: number | null;
3842 |         calibrated_difficulty: number | null;
3843 |         correct_count: number;
3844 |         discrimination_index: number | null;
3845 |         id: string;
3846 |         last_calculated_at: string;
3847 |         quality_flag: string | null;
3848 |         question_id: string;
3849 |         success_rate: number | null;
3850 |         total_attempts: number;
3851 |     };
3852 |     Insert: {
3853 |         avg_response_time_seconds?: number | null;
3854 |         calibrated_difficulty?: number | null;
3855 |         correct_count?: number;
3856 |         discrimination_index?: number | null;
3857 |         id?: string;
3858 |         last_calculated_at?: string;
3859 |         quality_flag?: string | null;

```

```

3860 |         question_id: string;
3861 |         success_rate?: number | null;
3862 |         total_attempts?: number;
3863 |     };
3864 |     Update: {
3865 |         avg_response_time_seconds?: number | null;
3866 |         calibrated_difficulty?: number | null;
3867 |         correct_count?: number;
3868 |         discrimination_index?: number | null;
3869 |         id?: string;
3870 |         last_calculated_at?: string;
3871 |         quality_flag?: string | null;
3872 |         question_id?: string;
3873 |         success_rate?: number | null;
3874 |         total_attempts?: number;
3875 |     };
3876 |     Relationships: [
3877 |     {
3878 |         foreignKeyName: "question_analytics_question_id_fkey";
3879 |         columns: ["question_id"];
3880 |         isOneToOne: true;
3881 |         referencedRelation: "question_bank";
3882 |         referencedColumns: ["id"];
3883 |     }
3884 | ];
3885 | };
3886 | question_bank: {
3887 |     Row: {
3888 |         bloom_level: number;
3889 |         clo_id: string;
3890 |         correct_answer: Json;
3891 |         course_id: string;
3892 |         created_at: string;
3893 |         created_by: string;
3894 |         difficulty_rating: number;
3895 |         explanation: string | null;
3896 |         explanation_confidence: number | null;
3897 |         generation_request_id: string | null;
3898 |         generation_source: string;
3899 |         id: string;
3900 |         institution_id: string;
3901 |         labels: string[] | null;
3902 |         options: Json | null;
3903 |         parent_question_id: string | null;
3904 |         question_text: string;
3905 |         question_type: string;
3906 |         source_chunks: Json | null;
3907 |         status: string;
3908 |         updated_at: string;
3909 |     };
3910 |     Insert: {
3911 |         bloom_level: number;
3912 |         clo_id: string;
3913 |         correct_answer: Json;
3914 |         course_id: string;
3915 |         created_at?: string;
3916 |         created_by: string;
3917 |         difficulty_rating: number;
3918 |         explanation?: string | null;
3919 |         explanation_confidence?: number | null;
3920 |         generation_request_id?: string | null;
3921 |         generation_source: string;
3922 |         id?: string;
3923 |         institution_id: string;
3924 |         labels?: string[] | null;
3925 |         options?: Json | null;
3926 |         parent_question_id?: string | null;
3927 |         question_text: string;
3928 |         question_type: string;
3929 |         source_chunks?: Json | null;
3930 |         status?: string;
3931 |         updated_at?: string;
3932 |     };
3933 |     Update: {
3934 |         bloom_level?: number;
3935 |         clo_id?: string;
3936 |         correct_answer?: Json;
3937 |         course_id?: string;
3938 |         created_at?: string;
3939 |         created_by?: string;
3940 |         difficulty_rating?: number;
3941 |         explanation?: string | null;
3942 |         explanation_confidence?: number | null;
3943 |         generation_request_id?: string | null;
3944 |         generation_source?: string;
3945 |         id?: string;
3946 |         institution_id?: string;
3947 |         labels?: string[] | null;
3948 |         options?: Json | null;
3949 |         parent_question_id?: string | null;
3950 |         question_text?: string;
3951 |         question_type?: string;
3952 |         source_chunks?: Json | null;
3953 |         status?: string;
3954 |         updated_at?: string;
3955 |     };
3956 |     Relationships: [
3957 |     {
3958 |         foreignKeyName: "question_bank_clo_id_fkey";
3959 |         columns: ["clo_id"];
3960 |         isOneToOne: false;
3961 |         referencedRelation: "learning_outcomes";
3962 |         referencedColumns: ["id"];
3963 |     },

```

```

3964 |         {
3965 |             foreignKeyName: "question_bank_course_id_fkey";
3966 |             columns: ["course_id"];
3967 |             isOneToOne: false;
3968 |             referencedRelation: "courses";
3969 |             referencedColumns: ["id"];
3970 |         },
3971 |         {
3972 |             foreignKeyName: "question_bank_created_by_fkey";
3973 |             columns: ["created_by"];
3974 |             isOneToOne: false;
3975 |             referencedRelation: "profiles";
3976 |             referencedColumns: ["id"];
3977 |         },
3978 |         {
3979 |             foreignKeyName: "question_bank_institution_id_fkey";
3980 |             columns: ["institution_id"];
3981 |             isOneToOne: false;
3982 |             referencedRelation: "institutions";
3983 |             referencedColumns: ["id"];
3984 |         },
3985 |         {
3986 |             foreignKeyName: "question_bank_institution_id_fkey";
3987 |             columns: ["institution_id"];
3988 |             isOneToOne: false;
3989 |             referencedRelation: "institutions_public";
3990 |             referencedColumns: ["id"];
3991 |         },
3992 |         {
3993 |             foreignKeyName: "question_bank_parent_question_id_fkey";
3994 |             columns: ["parent_question_id"];
3995 |             isOneToOne: false;
3996 |             referencedRelation: "question_bank";
3997 |             referencedColumns: ["id"];
3998 |         }
3999 |     ];
4000 | };
4001 | quiz_attempts: {
4002 |     Row: {
4003 |         answers: Json;
4004 |         attempt_number: number;
4005 |         blooms_climb_state: Json | null;
4006 |         difficulty_trajectory: Json | null;
4007 |         id: string;
4008 |         mode: string;
4009 |         per_question_times: Json | null;
4010 |         question_sequence: Json | null;
4011 |         quiz_id: string;
4012 |         score: number | null;
4013 |         started_at: string;
4014 |         student_id: string;
4015 |         submitted_at: string | null;
4016 |     };
4017 |     Insert: {
4018 |         answers?: Json;
4019 |         attempt_number?: number;
4020 |         blooms_climb_state?: Json | null;
4021 |         difficulty_trajectory?: Json | null;
4022 |         id?: string;
4023 |         mode?: string;
4024 |         per_question_times?: Json | null;
4025 |         question_sequence?: Json | null;
4026 |         quiz_id: string;
4027 |         score?: number | null;
4028 |         started_at?: string;
4029 |         student_id: string;
4030 |         submitted_at?: string | null;
4031 |     };
4032 |     Update: {
4033 |         answers?: Json;
4034 |         attempt_number?: number;
4035 |         blooms_climb_state?: Json | null;
4036 |         difficulty_trajectory?: Json | null;
4037 |         id?: string;
4038 |         mode?: string;
4039 |         per_question_times?: Json | null;
4040 |         question_sequence?: Json | null;
4041 |         quiz_id?: string;
4042 |         score?: number | null;
4043 |         started_at?: string;
4044 |         student_id?: string;
4045 |         submitted_at?: string | null;
4046 |     };
4047 |     Relationships: [
4048 |         {
4049 |             foreignKeyName: "quiz_attempts_quiz_id_fkey";
4050 |             columns: ["quiz_id"];
4051 |             isOneToOne: false;
4052 |             referencedRelation: "quizzes";
4053 |             referencedColumns: ["id"];
4054 |         },
4055 |         {
4056 |             foreignKeyName: "quiz_attempts_student_id_fkey";
4057 |             columns: ["student_id"];
4058 |             isOneToOne: false;
4059 |             referencedRelation: "profiles";
4060 |             referencedColumns: ["id"];
4061 |         }
4062 |     ];
4063 | };
4064 | quiz_clos: {
4065 |     Row: {
4066 |         clo_id: string;
4067 |         created_at: string;

```

```

4068 |         id: string;
4069 |         quiz_id: string;
4070 |     };
4071 |     Insert: {
4072 |         clo_id: string;
4073 |         created_at?: string;
4074 |         id?: string;
4075 |         quiz_id: string;
4076 |     };
4077 |     Update: {
4078 |         clo_id?: string;
4079 |         created_at?: string;
4080 |         id?: string;
4081 |         quiz_id?: string;
4082 |     };
4083 |     Relationships: [
4084 |     {
4085 |         foreignKeyName: "quiz_clos_clo_id_fkey";
4086 |         columns: ["clo_id"];
4087 |         isOneToOne: false;
4088 |         referencedRelation: "learning_outcomes";
4089 |         referencedColumns: ["id"];
4090 |     },
4091 |     {
4092 |         foreignKeyName: "quiz_clos_quiz_id_fkey";
4093 |         columns: ["quiz_id"];
4094 |         isOneToOne: false;
4095 |         referencedRelation: "quizzes";
4096 |         referencedColumns: ["id"];
4097 |     }
4098 | ];
4099 | };
4100 | quiz_generation_logs: {
4101 |     Row: {
4102 |         chunks_retrieved: number;
4103 |         completion_tokens: number;
4104 |         course_id: string;
4105 |         created_at: string;
4106 |         error_message: string | null;
4107 |         generation_request_id: string;
4108 |         id: string;
4109 |         institution_id: string;
4110 |         latency_ms: number;
4111 |         model_used: string;
4112 |         prompt_tokens: number;
4113 |         question_count_generated: number;
4114 |         question_count_requested: number;
4115 |         status: string;
4116 |         teacher_id: string;
4117 |         total_tokens: number;
4118 |     };
4119 |     Insert: {
4120 |         chunks_retrieved: number;
4121 |         completion_tokens: number;
4122 |         course_id: string;
4123 |         created_at?: string;
4124 |         error_message?: string | null;
4125 |         generation_request_id: string;
4126 |         id?: string;
4127 |         institution_id: string;
4128 |         latency_ms: number;
4129 |         model_used: string;
4130 |         prompt_tokens: number;
4131 |         question_count_generated: number;
4132 |         question_count_requested: number;
4133 |         status: string;
4134 |         teacher_id: string;
4135 |         total_tokens: number;
4136 |     };
4137 |     Update: {
4138 |         chunks_retrieved?: number;
4139 |         completion_tokens?: number;
4140 |         course_id?: string;
4141 |         created_at?: string;
4142 |         error_message?: string | null;
4143 |         generation_request_id?: string;
4144 |         id?: string;
4145 |         institution_id?: string;
4146 |         latency_ms?: number;
4147 |         model_used?: string;
4148 |         prompt_tokens?: number;
4149 |         question_count_generated?: number;
4150 |         question_count_requested?: number;
4151 |         status?: string;
4152 |         teacher_id?: string;
4153 |         total_tokens?: number;
4154 |     };
4155 |     Relationships: [
4156 |     {
4157 |         foreignKeyName: "quiz_generation_logs_course_id_fkey";
4158 |         columns: ["course_id"];
4159 |         isOneToOne: false;
4160 |         referencedRelation: "courses";
4161 |         referencedColumns: ["id"];
4162 |     },
4163 |     {
4164 |         foreignKeyName: "quiz_generation_logs_institution_id_fkey";
4165 |         columns: ["institution_id"];
4166 |         isOneToOne: false;
4167 |         referencedRelation: "institutions";
4168 |         referencedColumns: ["id"];
4169 |     },
4170 |     {
4171 |         foreignKeyName: "quiz_generation_logs_institution_id_fkey";

```

```

4172 |         columns: ["institution_id"];
4173 |         isOneToOne: false;
4174 |         referencedRelation: "institutions_public";
4175 |         referencedColumns: ["id"];
4176 |     },
4177 |     {
4178 |         foreignKeyName: "quiz_generation_logs_teacher_id_fkey";
4179 |         columns: ["teacher_id"];
4180 |         isOneToOne: false;
4181 |         referencedRelation: "profiles";
4182 |         referencedColumns: ["id"];
4183 |     }
4184 | ];
4185 | };
4186 | quiz_questions: {
4187 |     Row: {
4188 |         correct_answer: Json;
4189 |         id: string;
4190 |         options: Json | null;
4191 |         points: number;
4192 |         question_text: string;
4193 |         question_type: string;
4194 |         quiz_id: string;
4195 |         sort_order: number;
4196 |     };
4197 |     Insert: {
4198 |         correct_answer: Json;
4199 |         id?: string;
4200 |         options?: Json | null;
4201 |         points?: number;
4202 |         question_text: string;
4203 |         question_type: string;
4204 |         quiz_id: string;
4205 |         sort_order?: number;
4206 |     };
4207 |     Update: {
4208 |         correct_answer?: Json;
4209 |         id?: string;
4210 |         options?: Json | null;
4211 |         points?: number;
4212 |         question_text?: string;
4213 |         question_type?: string;
4214 |         quiz_id?: string;
4215 |         sort_order?: number;
4216 |     };
4217 |     Relationships: [
4218 |         {
4219 |             foreignKeyName: "quiz_questions_quiz_id_fkey";
4220 |             columns: ["quiz_id"];
4221 |             isOneToOne: false;
4222 |             referencedRelation: "quizzes";
4223 |             referencedColumns: ["id"];
4224 |         }
4225 |     ];
4226 | };
4227 | quizzes: {
4228 |     Row: {
4229 |         adaptation_config: Json | null;
4230 |         clo_ids: Json;
4231 |         course_id: string;
4232 |         created_at: string;
4233 |         description: string | null;
4234 |         due_date: string;
4235 |         id: string;
4236 |         is_adaptive: boolean;
4237 |         is_published: boolean;
4238 |         max_attempts: number;
4239 |         practice_mode_enabled: boolean;
4240 |         time_limit_minutes: number | null;
4241 |         title: string;
4242 |     };
4243 |     Insert: {
4244 |         adaptation_config?: Json | null;
4245 |         clo_ids?: Json;
4246 |         course_id: string;
4247 |         created_at?: string;
4248 |         description?: string | null;
4249 |         due_date: string;
4250 |         id?: string;
4251 |         is_adaptive?: boolean;
4252 |         is_published?: boolean;
4253 |         max_attempts?: number;
4254 |         practice_mode_enabled?: boolean;
4255 |         time_limit_minutes?: number | null;
4256 |         title: string;
4257 |     };
4258 |     Update: {
4259 |         adaptation_config?: Json | null;
4260 |         clo_ids?: Json;
4261 |         course_id?: string;
4262 |         created_at?: string;
4263 |         description?: string | null;
4264 |         due_date?: string;
4265 |         id?: string;
4266 |         is_adaptive?: boolean;
4267 |         is_published?: boolean;
4268 |         max_attempts?: number;
4269 |         practice_mode_enabled?: boolean;
4270 |         time_limit_minutes?: number | null;
4271 |         title?: string;
4272 |     };
4273 |     Relationships: [
4274 |         {
4275 |             foreignKeyName: "quizzes_course_id_fkey";

```



```

4276         columns: ["course_id"];
4277         isOneToOne: false;
4278         referencedRelation: "courses";
4279         referencedColumns: ["id"];
4280     }
4281 };
4282 };
4283 rate_limit_events: {
4284     Row: {
4285         event_type: string;
4286         id: number;
4287         ip_address: unknown;
4288         metadata: Json;
4289         occurred_at: string;
4290         user_id: string | null;
4291     };
4292     Insert: {
4293         event_type: string;
4294         id?: number;
4295         ip_address: unknown;
4296         metadata?: Json;
4297         occurred_at?: string;
4298         user_id?: string | null;
4299     };
4300     Update: {
4301         event_type?: string;
4302         id?: number;
4303         ip_address?: unknown;
4304         metadata?: Json;
4305         occurred_at?: string;
4306         user_id?: string | null;
4307     };
4308     Relationships: [];
4309 };
4310 reflection_digests: {
4311     Row: {
4312         emotional_trends: Json;
4313         generated_at: string;
4314         growth_patterns: Json;
4315         id: string;
4316         month: string;
4317         shared_with: Json;
4318         student_id: string;
4319         suggested_focus: Json;
4320         themes: Json;
4321     };
4322     Insert: {
4323         emotional_trends?: Json;
4324         generated_at?: string;
4325         growth_patterns?: Json;
4326         id?: string;
4327         month: string;
4328         shared_with?: Json;
4329         student_id: string;
4330         suggested_focus?: Json;
4331         themes?: Json;
4332     };
4333     Update: {
4334         emotional_trends?: Json;
4335         generated_at?: string;
4336         growth_patterns?: Json;
4337         id?: string;
4338         month?: string;
4339         shared_with?: Json;
4340         student_id?: string;
4341         suggested_focus?: Json;
4342         themes?: Json;
4343     };
4344     Relationships: [
4345         {
4346             foreignKeyName: "reflection_digests_student_id_fkey";
4347             columns: ["student_id"];
4348             isOneToOne: false;
4349             referencedRelation: "profiles";
4350             referencedColumns: ["id"];
4351         }
4352     ];
4353 };
4354 reflection_quality_scores: {
4355     Row: {
4356         depth_score: number;
4357         flags: Json;
4358         id: string;
4359         originality_score: number;
4360         reflection_id: string;
4361         reflection_type: Database["public"]["Enums"]["reflection_type_enum"];
4362         relevance_score: number;
4363         score: number;
4364         scored_at: string;
4365         student_id: string;
4366     };
4367     Insert: {
4368         depth_score: number;
4369         flags?: Json;
4370         id?: string;
4371         originality_score: number;
4372         reflection_id: string;
4373         reflection_type: Database["public"]["Enums"]["reflection_type_enum"];
4374         relevance_score: number;
4375         score: number;
4376         scored_at?: string;
4377         student_id: string;
4378     };
4379     Update: {

```

```

4380 |         depth_score?: number;
4381 |         flags?: Json;
4382 |         id?: string;
4383 |         originality_score?: number;
4384 |         reflection_id?: string;
4385 |         reflection_type?: Database["public"]["Enums"]["reflection_type_enum"];
4386 |         relevance_score?: number;
4387 |         score?: number;
4388 |         scored_at?: string;
4389 |         student_id?: string;
4390 |     };
4391 |     Relationships: [
4392 |     {
4393 |         foreignKeyName: "reflection_quality_scores_student_id_fkey";
4394 |         columns: ["student_id"];
4395 |         isOneToOne: false;
4396 |         referencedRelation: "profiles";
4397 |         referencedColumns: ["id"];
4398 |     }
4399 | ];
4400 | };
4401 | replacement_votes: {
4402 |     Row: {
4403 |         created_at: string;
4404 |         expires_at: string;
4405 |         id: string;
4406 |         initiated_by: string;
4407 |         resolved_at: string | null;
4408 |         status: string;
4409 |         target_member_id: string;
4410 |         teacher_override: boolean;
4411 |         team_id: string;
4412 |         votes_against: number;
4413 |         votes_for: number;
4414 |     };
4415 |     Insert: {
4416 |         created_at?: string;
4417 |         expires_at: string;
4418 |         id?: string;
4419 |         initiated_by: string;
4420 |         resolved_at?: string | null;
4421 |         status?: string;
4422 |         target_member_id: string;
4423 |         teacher_override?: boolean;
4424 |         team_id: string;
4425 |         votes_against?: number;
4426 |         votes_for?: number;
4427 |     };
4428 |     Update: {
4429 |         created_at?: string;
4430 |         expires_at?: string;
4431 |         id?: string;
4432 |         initiated_by?: string;
4433 |         resolved_at?: string | null;
4434 |         status?: string;
4435 |         target_member_id?: string;
4436 |         teacher_override?: boolean;
4437 |         team_id?: string;
4438 |         votes_against?: number;
4439 |         votes_for?: number;
4440 |     };
4441 |     Relationships: [
4442 |     {
4443 |         foreignKeyName: "replacement_votes_initiated_by_fkey";
4444 |         columns: ["initiated_by"];
4445 |         isOneToOne: false;
4446 |         referencedRelation: "profiles";
4447 |         referencedColumns: ["id"];
4448 |     },
4449 |     {
4450 |         foreignKeyName: "replacement_votes_target_member_id_fkey";
4451 |         columns: ["target_member_id"];
4452 |         isOneToOne: false;
4453 |         referencedRelation: "profiles";
4454 |         referencedColumns: ["id"];
4455 |     },
4456 |     {
4457 |         foreignKeyName: "replacement_votes_team_id_fkey";
4458 |         columns: ["team_id"];
4459 |         isOneToOne: false;
4460 |         referencedRelation: "teams";
4461 |         referencedColumns: ["id"];
4462 |     }
4463 | ];
4464 | };
4465 | review_schedules: {
4466 |     Row: {
4467 |         clo_id: string;
4468 |         course_id: string | null;
4469 |         created_at: string;
4470 |         id: string;
4471 |         interval_days: number;
4472 |         review_date: string;
4473 |         review_session_id: string | null;
4474 |         source_session_id: string | null;
4475 |         status: Database["public"]["Enums"]["review_status_type"];
4476 |         student_id: string;
4477 |         updated_at: string;
4478 |     };
4479 |     Insert: {
4480 |         clo_id: string;
4481 |         course_id?: string | null;
4482 |         created_at?: string;
4483 |         id?: string;

```

```

4484 |         interval_days: number;
4485 |         review_date: string;
4486 |         review_session_id?: string | null;
4487 |         source_session_id?: string | null;
4488 |         status?: Database["public"]["Enums"]["review_status_type"];
4489 |         student_id: string;
4490 |         updated_at?: string;
4491 |     };
4492 |     Update: {
4493 |         clo_id?: string;
4494 |         course_id?: string | null;
4495 |         created_at?: string;
4496 |         id?: string;
4497 |         interval_days?: number;
4498 |         review_date?: string;
4499 |         review_session_id?: string | null;
4500 |         source_session_id?: string | null;
4501 |         status?: Database["public"]["Enums"]["review_status_type"];
4502 |         student_id?: string;
4503 |         updated_at?: string;
4504 |     };
4505 |     Relationships: [
4506 |         {
4507 |             foreignKeyName: "review_schedules_course_id_fkey";
4508 |             columns: ["course_id"];
4509 |             isOneToOne: false;
4510 |             referencedRelation: "courses";
4511 |             referencedColumns: ["id"];
4512 |         },
4513 |         {
4514 |             foreignKeyName: "review_schedules_review_session_id_fkey";
4515 |             columns: ["review_session_id"];
4516 |             isOneToOne: false;
4517 |             referencedRelation: "study_sessions";
4518 |             referencedColumns: ["id"];
4519 |         },
4520 |         {
4521 |             foreignKeyName: "review_schedules_source_session_id_fkey";
4522 |             columns: ["source_session_id"];
4523 |             isOneToOne: false;
4524 |             referencedRelation: "study_sessions";
4525 |             referencedColumns: ["id"];
4526 |         },
4527 |         {
4528 |             foreignKeyName: "review_schedules_student_id_fkey";
4529 |             columns: ["student_id"];
4530 |             isOneToOne: false;
4531 |             referencedRelation: "profiles";
4532 |             referencedColumns: ["id"];
4533 |         }
4534 |     ];
4535 | };
4536 | rubric_criteria: {
4537 |     Row: {
4538 |         criterion_name: string;
4539 |         id: string;
4540 |         levels: Json;
4541 |         max_points: number;
4542 |         rubric_id: string;
4543 |         sort_order: number;
4544 |     };
4545 |     Insert: {
4546 |         criterion_name: string;
4547 |         id?: string;
4548 |         levels?: Json;
4549 |         max_points: number;
4550 |         rubric_id: string;
4551 |         sort_order?: number;
4552 |     };
4553 |     Update: {
4554 |         criterion_name?: string;
4555 |         id?: string;
4556 |         levels?: Json;
4557 |         max_points?: number;
4558 |         rubric_id?: string;
4559 |         sort_order?: number;
4560 |     };
4561 |     Relationships: [
4562 |         {
4563 |             foreignKeyName: "rubric_criteria_rubric_id_fkey";
4564 |             columns: ["rubric_id"];
4565 |             isOneToOne: false;
4566 |             referencedRelation: "rubrics";
4567 |             referencedColumns: ["id"];
4568 |         }
4569 |     ];
4570 | };
4571 | rubrics: {
4572 |     Row: {
4573 |         clo_id: string | null;
4574 |         created_at: string;
4575 |         created_by: string | null;
4576 |         description: string | null;
4577 |         id: string;
4578 |         is_template: boolean;
4579 |         title: string;
4580 |     };
4581 |     Insert: {
4582 |         clo_id?: string | null;
4583 |         created_at?: string;
4584 |         created_by?: string | null;
4585 |         description?: string | null;
4586 |         id?: string;
4587 |         is_template?: boolean;

```

```

4588 |         title: string;
4589 |     };
4590 |     Update: {
4591 |         clo_id?: string | null;
4592 |         created_at?: string;
4593 |         created_by?: string | null;
4594 |         description?: string | null;
4595 |         id?: string;
4596 |         is_template?: boolean;
4597 |         title?: string;
4598 |     };
4599 |     Relationships: [
4600 |     {
4601 |         foreignKeyName: "rubrics_clo_id_fkey";
4602 |         columns: ["clo_id"];
4603 |         isOneToOne: false;
4604 |         referencedRelation: "learning_outcomes";
4605 |         referencedColumns: ["id"];
4606 |     },
4607 |     {
4608 |         foreignKeyName: "rubrics_created_by_fkey";
4609 |         columns: ["created_by"];
4610 |         isOneToOne: false;
4611 |         referencedRelation: "profiles";
4612 |         referencedColumns: ["id"];
4613 |     }
4614 | ];
4615 | };
4616 | sale_event_items: {
4617 |     Row: {
4618 |         item_id: string;
4619 |         sale_event_id: string;
4620 |     };
4621 |     Insert: {
4622 |         item_id: string;
4623 |         sale_event_id: string;
4624 |     };
4625 |     Update: {
4626 |         item_id?: string;
4627 |         sale_event_id?: string;
4628 |     };
4629 |     Relationships: [
4630 |     {
4631 |         foreignKeyName: "sale_event_items_item_id_fkey";
4632 |         columns: ["item_id"];
4633 |         isOneToOne: false;
4634 |         referencedRelation: "marketplace_items";
4635 |         referencedColumns: ["id"];
4636 |     },
4637 |     {
4638 |         foreignKeyName: "sale_event_items_sale_event_id_fkey";
4639 |         columns: ["sale_event_id"];
4640 |         isOneToOne: false;
4641 |         referencedRelation: "sale_events";
4642 |         referencedColumns: ["id"];
4643 |     }
4644 | ];
4645 | };
4646 | sale_events: {
4647 |     Row: {
4648 |         created_at: string;
4649 |         created_by: string;
4650 |         discount_percentage: number;
4651 |         end_date: string;
4652 |         id: string;
4653 |         institution_id: string;
4654 |         name: string;
4655 |         start_date: string;
4656 |     };
4657 |     Insert: {
4658 |         created_at?: string;
4659 |         created_by?: string;
4660 |         discount_percentage?: number;
4661 |         end_date?: string;
4662 |         id?: string;
4663 |         institution_id?: string;
4664 |         name?: string;
4665 |         start_date?: string;
4666 |     };
4667 |     Update: {
4668 |         created_at?: string;
4669 |         created_by?: string;
4670 |         discount_percentage?: number;
4671 |         end_date?: string;
4672 |         id?: string;
4673 |         institution_id?: string;
4674 |         name?: string;
4675 |         start_date?: string;
4676 |     };
4677 |     Relationships: [
4678 |     {
4679 |         foreignKeyName: "sale_events_created_by_fkey";
4680 |         columns: ["created_by"];
4681 |         isOneToOne: false;
4682 |         referencedRelation: "profiles";
4683 |         referencedColumns: ["id"];
4684 |     },
4685 |     {
4686 |         foreignKeyName: "sale_events_institution_id_fkey";
4687 |         columns: ["institution_id"];
4688 |         isOneToOne: false;
4689 |         referencedRelation: "institutions";
4690 |         referencedColumns: ["id"];
4691 |     },

```

```

4692 |         {
4693 |             foreignKeyName: "sale_events_institution_id_fkey";
4694 |             columns: ["institution_id"];
4695 |             isOneToOne: false;
4696 |             referencedRelation: "institutions_public";
4697 |             referencedColumns: ["id"];
4698 |         }
4699 |     ];
4700 | };
4701 | semesters: {
4702 |     Row: {
4703 |         code: string;
4704 |         created_at: string;
4705 |         end_date: string;
4706 |         id: string;
4707 |         institution_id: string;
4708 |         is_active: boolean;
4709 |         name: string;
4710 |         start_date: string;
4711 |     };
4712 |     Insert: {
4713 |         code: string;
4714 |         created_at?: string;
4715 |         end_date: string;
4716 |         id?: string;
4717 |         institution_id: string;
4718 |         is_active?: boolean;
4719 |         name: string;
4720 |         start_date: string;
4721 |     };
4722 |     Update: {
4723 |         code?: string;
4724 |         created_at?: string;
4725 |         end_date?: string;
4726 |         id?: string;
4727 |         institution_id?: string;
4728 |         is_active?: boolean;
4729 |         name?: string;
4730 |         start_date?: string;
4731 |     };
4732 |     Relationships: [
4733 |         {
4734 |             foreignKeyName: "semesters_institution_id_fkey";
4735 |             columns: ["institution_id"];
4736 |             isOneToOne: false;
4737 |             referencedRelation: "institutions";
4738 |             referencedColumns: ["id"];
4739 |         },
4740 |         {
4741 |             foreignKeyName: "semesters_institution_id_fkey";
4742 |             columns: ["institution_id"];
4743 |             isOneToOne: false;
4744 |             referencedRelation: "institutions_public";
4745 |             referencedColumns: ["id"];
4746 |         }
4747 |     ];
4748 | };
4749 | session_evidence: {
4750 |     Row: {
4751 |         content: string | null;
4752 |         created_at: string | null;
4753 |         evidence_type: string;
4754 |         file_name: string | null;
4755 |         file_size_bytes: number | null;
4756 |         file_url: string | null;
4757 |         id: string;
4758 |         mime_type: string | null;
4759 |         notes: string | null;
4760 |         session_id: string;
4761 |         student_id: string | null;
4762 |     };
4763 |     Insert: {
4764 |         content?: string | null;
4765 |         created_at?: string | null;
4766 |         evidence_type: string;
4767 |         file_name?: string | null;
4768 |         file_size_bytes?: number | null;
4769 |         file_url?: string | null;
4770 |         id?: string;
4771 |         mime_type?: string | null;
4772 |         notes?: string | null;
4773 |         session_id: string;
4774 |         student_id?: string | null;
4775 |     };
4776 |     Update: {
4777 |         content?: string | null;
4778 |         created_at?: string | null;
4779 |         evidence_type?: string;
4780 |         file_name?: string | null;
4781 |         file_size_bytes?: number | null;
4782 |         file_url?: string | null;
4783 |         id?: string;
4784 |         mime_type?: string | null;
4785 |         notes?: string | null;
4786 |         session_id?: string;
4787 |         student_id?: string | null;
4788 |     };
4789 |     Relationships: [
4790 |         {
4791 |             foreignKeyName: "session_evidence_session_id_fkey";
4792 |             columns: ["session_id"];
4793 |             isOneToOne: false;
4794 |             referencedRelation: "study_sessions";
4795 |             referencedColumns: ["id"];

```

```

4796     },
4797     {
4798         foreignKeyName: "session_evidence_student_id_fkey";
4799         columns: ["student_id"];
4800         isOneToOne: false;
4801         referencedRelation: "profiles";
4802         referencedColumns: ["id"];
4803     }
4804 ];
4805 };
4806 session_intents: {
4807     Row: {
4808         concept: string;
4809         created_at: string;
4810         id: string;
4811         is_auto_suggested: boolean;
4812         session_id: string;
4813         student_id: string;
4814         success_criterion: string;
4815     };
4816     Insert: {
4817         concept: string;
4818         created_at?: string;
4819         id?: string;
4820         is_auto_suggested?: boolean;
4821         session_id: string;
4822         student_id: string;
4823         success_criterion: string;
4824     };
4825     Update: {
4826         concept?: string;
4827         created_at?: string;
4828         id?: string;
4829         is_auto_suggested?: boolean;
4830         session_id?: string;
4831         student_id?: string;
4832         success_criterion?: string;
4833     };
4834     Relationships: [
4835         {
4836             foreignKeyName: "session_intents_session_id_fkey";
4837             columns: ["session_id"];
4838             isOneToOne: true;
4839             referencedRelation: "study_sessions";
4840             referencedColumns: ["id"];
4841         },
4842         {
4843             foreignKeyName: "session_intents_student_id_fkey";
4844             columns: ["student_id"];
4845             isOneToOne: false;
4846             referencedRelation: "profiles";
4847             referencedColumns: ["id"];
4848         }
4849     ];
4850 };
4851 session_reflections: {
4852     Row: {
4853         content: string;
4854         created_at: string;
4855         id: string;
4856         session_id: string;
4857         student_id: string;
4858         word_count: number;
4859     };
4860     Insert: {
4861         content: string;
4862         created_at?: string;
4863         id?: string;
4864         session_id: string;
4865         student_id: string;
4866         word_count: number;
4867     };
4868     Update: {
4869         content?: string;
4870         created_at?: string;
4871         id?: string;
4872         session_id?: string;
4873         student_id?: string;
4874         word_count?: number;
4875     };
4876     Relationships: [
4877         {
4878             foreignKeyName: "session_reflections_session_id_fkey";
4879             columns: ["session_id"];
4880             isOneToOne: false;
4881             referencedRelation: "study_sessions";
4882             referencedColumns: ["id"];
4883         },
4884         {
4885             foreignKeyName: "session_reflections_student_id_fkey";
4886             columns: ["student_id"];
4887             isOneToOne: false;
4888             referencedRelation: "profiles";
4889             referencedColumns: ["id"];
4890         }
4891     ];
4892 };
4893 social_challenges: {
4894     Row: {
4895         challenge_type: string;
4896         course_id: string;
4897         created_at: string;
4898         created_by: string;
4899         description: string;

```

```

4900         end_date: string;
4901         goal_target: number;
4902         id: string;
4903         institution_id: string;
4904         participation_mode: string;
4905         reward_badge_id: string | null;
4906         reward_xp: number;
4907         start_date: string;
4908         status: string;
4909         title: string;
4910         updated_at: string;
4911     };
4912     Insert: {
4913         challenge_type: string;
4914         course_id: string;
4915         created_at?: string;
4916         created_by: string;
4917         description?: string;
4918         end_date: string;
4919         goal_target: number;
4920         id?: string;
4921         institution_id: string;
4922         participation_mode?: string;
4923         reward_badge_id?: string | null;
4924         reward_xp?: number;
4925         start_date: string;
4926         status?: string;
4927         title: string;
4928         updated_at?: string;
4929     };
4930     Update: {
4931         challenge_type?: string;
4932         course_id?: string;
4933         created_at?: string;
4934         created_by?: string;
4935         description?: string;
4936         end_date?: string;
4937         goal_target?: number;
4938         id?: string;
4939         institution_id?: string;
4940         participation_mode?: string;
4941         reward_badge_id?: string | null;
4942         reward_xp?: number;
4943         start_date?: string;
4944         status?: string;
4945         title?: string;
4946         updated_at?: string;
4947     };
4948     Relationships: [
4949         {
4950             foreignKeyName: "social_challenges_course_id_fkey";
4951             columns: ["course_id"];
4952             isOneToOne: false;
4953             referencedRelation: "courses";
4954             referencedColumns: ["id"];
4955         },
4956         {
4957             foreignKeyName: "social_challenges_created_by_fkey";
4958             columns: ["created_by"];
4959             isOneToOne: false;
4960             referencedRelation: "profiles";
4961             referencedColumns: ["id"];
4962         },
4963         {
4964             foreignKeyName: "social_challenges_institution_id_fkey";
4965             columns: ["institution_id"];
4966             isOneToOne: false;
4967             referencedRelation: "institutions";
4968             referencedColumns: ["id"];
4969         },
4970         {
4971             foreignKeyName: "social_challenges_institution_id_fkey";
4972             columns: ["institution_id"];
4973             isOneToOne: false;
4974             referencedRelation: "institutions_public";
4975             referencedColumns: ["id"];
4976         }
4977     ];
4978 };
4979 starter_week_sessions: {
4980     Row: {
4981         course_id: string | null;
4982         created_at: string;
4983         description: string;
4984         duration_minutes: number;
4985         id: string;
4986         planner_entry_id: string | null;
4987         session_type: string;
4988         status: string;
4989         student_id: string;
4990         suggested_date: string;
4991         suggested_time_slot: string;
4992         updated_at: string;
4993     };
4994     Insert: {
4995         course_id?: string | null;
4996         created_at?: string;
4997         description: string;
4998         duration_minutes: number;
4999         id?: string;
5000         planner_entry_id?: string | null;
5001         session_type: string;
5002         status?: string;
5003         student_id: string;

```

```

5004         suggested_date: string;
5005         suggested_time_slot: string;
5006         updated_at?: string;
5007     };
5008     Update: {
5009         course_id?: string | null;
5010         created_at?: string;
5011         description?: string;
5012         duration_minutes?: number;
5013         id?: string;
5014         planner_entry_id?: string | null;
5015         session_type?: string;
5016         status?: string;
5017         student_id?: string;
5018         suggested_date?: string;
5019         suggested_time_slot?: string;
5020         updated_at?: string;
5021     };
5022     Relationships: [
5023     {
5024         foreignKeyName: "starter_week_sessions_course_id_fkey";
5025         columns: ["course_id"];
5026         isOneToOne: false;
5027         referencedRelation: "courses";
5028         referencedColumns: ["id"];
5029     },
5030     {
5031         foreignKeyName: "starter_week_sessions_student_id_fkey";
5032         columns: ["student_id"];
5033         isOneToOne: false;
5034         referencedRelation: "profiles";
5035         referencedColumns: ["id"];
5036     }
5037 ];
5038 };
5039 student_active_boosts: {
5040     Row: {
5041         activated_at: string;
5042         boost_type: string;
5043         expires_at: string;
5044         id: string;
5045         multiplier: number;
5046         purchase_id: string;
5047         student_id: string;
5048     };
5049     Insert: {
5050         activated_at?: string;
5051         boost_type?: string;
5052         expires_at: string;
5053         id?: string;
5054         multiplier?: number;
5055         purchase_id: string;
5056         student_id: string;
5057     };
5058     Update: {
5059         activated_at?: string;
5060         boost_type?: string;
5061         expires_at?: string;
5062         id?: string;
5063         multiplier?: number;
5064         purchase_id?: string;
5065         student_id?: string;
5066     };
5067     Relationships: [
5068     {
5069         foreignKeyName: "student_active_boosts_purchase_id_fkey";
5070         columns: ["purchase_id"];
5071         isOneToOne: false;
5072         referencedRelation: "xp_purchases";
5073         referencedColumns: ["id"];
5074     },
5075     {
5076         foreignKeyName: "student_active_boosts_student_id_fkey";
5077         columns: ["student_id"];
5078         isOneToOne: false;
5079         referencedRelation: "profiles";
5080         referencedColumns: ["id"];
5081     }
5082 ];
5083 };
5084 student_activity_log: {
5085     Row: {
5086         created_at: string;
5087         event_type: string;
5088         id: string;
5089         metadata: Json | null;
5090         student_id: string;
5091     };
5092     Insert: {
5093         created_at?: string;
5094         event_type: string;
5095         id?: string;
5096         metadata?: Json | null;
5097         student_id: string;
5098     };
5099     Update: {
5100         created_at?: string;
5101         event_type?: string;
5102         id?: string;
5103         metadata?: Json | null;
5104         student_id?: string;
5105     };
5106     Relationships: [
5107     {

```



```

5108         foreignKeyName: "student_activity_log_student_id_fkey";
5109         columns: ["student_id"];
5110         isOneToOne: false;
5111         referencedRelation: "profiles";
5112         referencedColumns: ["id"];
5113     }
5114 ];
5115 };
5116 student_badges: {
5117     Row: {
5118         awarded_at: string;
5119         badge_id: string;
5120         id: string;
5121         student_id: string;
5122     };
5123     Insert: {
5124         awarded_at?: string;
5125         badge_id: string;
5126         id?: string;
5127         student_id: string;
5128     };
5129     Update: {
5130         awarded_at?: string;
5131         badge_id?: string;
5132         id?: string;
5133         student_id?: string;
5134     };
5135     Relationships: [
5136         {
5137             foreignKeyName: "student_badges_student_id_fkey";
5138             columns: ["student_id"];
5139             isOneToOne: false;
5140             referencedRelation: "profiles";
5141             referencedColumns: ["id"];
5142         }
5143     ];
5144 };
5145 student_content: {
5146     Row: {
5147         clo_id: string | null;
5148         content_data: Json;
5149         content_type: string;
5150         created_at: string;
5151         id: string;
5152         institution_id: string;
5153         reviewed_at: string | null;
5154         reviewer_feedback: string | null;
5155         reviewer_id: string | null;
5156         status: string;
5157         student_id: string;
5158         title: string;
5159         updated_at: string;
5160     };
5161     Insert: {
5162         clo_id?: string | null;
5163         content_data?: Json;
5164         content_type: string;
5165         created_at?: string;
5166         id?: string;
5167         institution_id: string;
5168         reviewed_at?: string | null;
5169         reviewer_feedback?: string | null;
5170         reviewer_id?: string | null;
5171         status?: string;
5172         student_id: string;
5173         title: string;
5174         updated_at?: string;
5175     };
5176     Update: {
5177         clo_id?: string | null;
5178         content_data?: Json;
5179         content_type?: string;
5180         created_at?: string;
5181         id?: string;
5182         institution_id?: string;
5183         reviewed_at?: string | null;
5184         reviewer_feedback?: string | null;
5185         reviewer_id?: string | null;
5186         status?: string;
5187         student_id?: string;
5188         title?: string;
5189         updated_at?: string;
5190     };
5191     Relationships: [
5192         {
5193             foreignKeyName: "student_content_clo_id_fkey";
5194             columns: ["clo_id"];
5195             isOneToOne: false;
5196             referencedRelation: "learning_outcomes";
5197             referencedColumns: ["id"];
5198         },
5199         {
5200             foreignKeyName: "student_content_institution_id_fkey";
5201             columns: ["institution_id"];
5202             isOneToOne: false;
5203             referencedRelation: "institutions";
5204             referencedColumns: ["id"];
5205         },
5206         {
5207             foreignKeyName: "student_content_institution_id_fkey";
5208             columns: ["institution_id"];
5209             isOneToOne: false;
5210             referencedRelation: "institutions_public";
5211             referencedColumns: ["id"];

```

```

5212 |         },
5213 |         {
5214 |             foreignKeyName: "student_content_reviewer_id_fkey";
5215 |             columns: ["reviewer_id"];
5216 |             isOneToOne: false;
5217 |             referencedRelation: "profiles";
5218 |             referencedColumns: ["id"];
5219 |         },
5220 |         {
5221 |             foreignKeyName: "student_content_student_id_fkey";
5222 |             columns: ["student_id"];
5223 |             isOneToOne: false;
5224 |             referencedRelation: "profiles";
5225 |             referencedColumns: ["id"];
5226 |         }
5227 |     ];
5228 | };
5229 | student_courses: {
5230 |     Row: {
5231 |         course_id: string;
5232 |         enrolled_at: string;
5233 |         id: string;
5234 |         section_id: string | null;
5235 |         status: string;
5236 |         student_id: string;
5237 |     };
5238 |     Insert: {
5239 |         course_id: string;
5240 |         enrolled_at?: string;
5241 |         id?: string;
5242 |         section_id?: string | null;
5243 |         status?: string;
5244 |         student_id: string;
5245 |     };
5246 |     Update: {
5247 |         course_id?: string;
5248 |         enrolled_at?: string;
5249 |         id?: string;
5250 |         section_id?: string | null;
5251 |         status?: string;
5252 |         student_id?: string;
5253 |     };
5254 |     Relationships: [
5255 |         {
5256 |             foreignKeyName: "student_courses_course_id_fkey";
5257 |             columns: ["course_id"];
5258 |             isOneToOne: false;
5259 |             referencedRelation: "courses";
5260 |             referencedColumns: ["id"];
5261 |         },
5262 |         {
5263 |             foreignKeyName: "student_courses_section_id_fkey";
5264 |             columns: ["section_id"];
5265 |             isOneToOne: false;
5266 |             referencedRelation: "course_sections";
5267 |             referencedColumns: ["id"];
5268 |         },
5269 |         {
5270 |             foreignKeyName: "student_courses_student_id_fkey";
5271 |             columns: ["student_id"];
5272 |             isOneToOne: false;
5273 |             referencedRelation: "profiles";
5274 |             referencedColumns: ["id"];
5275 |         }
5276 |     ];
5277 | };
5278 | student_equipped_items: {
5279 |     Row: {
5280 |         equipped_at: string;
5281 |         id: string;
5282 |         purchase_id: string;
5283 |         slot: Database["public"]["Enums"]["cosmetic_slot"];
5284 |         student_id: string;
5285 |     };
5286 |     Insert: {
5287 |         equipped_at?: string;
5288 |         id?: string;
5289 |         purchase_id: string;
5290 |         slot: Database["public"]["Enums"]["cosmetic_slot"];
5291 |         student_id: string;
5292 |     };
5293 |     Update: {
5294 |         equipped_at?: string;
5295 |         id?: string;
5296 |         purchase_id?: string;
5297 |         slot?: Database["public"]["Enums"]["cosmetic_slot"];
5298 |         student_id?: string;
5299 |     };
5300 |     Relationships: [
5301 |         {
5302 |             foreignKeyName: "student_equipped_items_purchase_id_fkey";
5303 |             columns: ["purchase_id"];
5304 |             isOneToOne: false;
5305 |             referencedRelation: "xp_purchases";
5306 |             referencedColumns: ["id"];
5307 |         },
5308 |         {
5309 |             foreignKeyName: "student_equipped_items_student_id_fkey";
5310 |             columns: ["student_id"];
5311 |             isOneToOne: false;
5312 |             referencedRelation: "profiles";
5313 |             referencedColumns: ["id"];
5314 |         }
5315 |     ];

```

```

5316 | };
5317 | student_gamification: {
5318 |   Row: {
5319 |     comeback_active: boolean | null;
5320 |     comeback_challenge_active: boolean;
5321 |     comeback_challenge_days_completed: number;
5322 |     comeback_challenge_start_date: string | null;
5323 |     comeback_challenge_streak_to_restore: number;
5324 |     comeback_days_completed: number | null;
5325 |     comeback_streak_to_restore: number | null;
5326 |     habit_difficulty_level: string | null;
5327 |     habit_level_streak: number | null;
5328 |     id: string;
5329 |     last_login_date: string | null;
5330 |     leaderboard_anonymous: boolean;
5331 |     league_tier: string;
5332 |     level: number;
5333 |     streak_current: number;
5334 |     streak_freezes_available: number;
5335 |     streak_longest: number;
5336 |     student_id: string;
5337 |     total_active_days: number;
5338 |     updated_at: string;
5339 |     xp_total: number;
5340 |   };
5341 |   Insert: {
5342 |     comeback_active?: boolean | null;
5343 |     comeback_challenge_active?: boolean;
5344 |     comeback_challenge_days_completed?: number;
5345 |     comeback_challenge_start_date?: string | null;
5346 |     comeback_challenge_streak_to_restore?: number;
5347 |     comeback_days_completed?: number | null;
5348 |     comeback_streak_to_restore?: number | null;
5349 |     habit_difficulty_level?: string | null;
5350 |     habit_level_streak?: number | null;
5351 |     id?: string;
5352 |     last_login_date?: string | null;
5353 |     leaderboard_anonymous?: boolean;
5354 |     league_tier?: string;
5355 |     level?: number;
5356 |     streak_current?: number;
5357 |     streak_freezes_available?: number;
5358 |     streak_longest?: number;
5359 |     student_id: string;
5360 |     total_active_days?: number;
5361 |     updated_at?: string;
5362 |     xp_total?: number;
5363 |   };
5364 |   Update: {
5365 |     comeback_active?: boolean | null;
5366 |     comeback_challenge_active?: boolean;
5367 |     comeback_challenge_days_completed?: number;
5368 |     comeback_challenge_start_date?: string | null;
5369 |     comeback_challenge_streak_to_restore?: number;
5370 |     comeback_days_completed?: number | null;
5371 |     comeback_streak_to_restore?: number | null;
5372 |     habit_difficulty_level?: string | null;
5373 |     habit_level_streak?: number | null;
5374 |     id?: string;
5375 |     last_login_date?: string | null;
5376 |     leaderboard_anonymous?: boolean;
5377 |     league_tier?: string;
5378 |     level?: number;
5379 |     streak_current?: number;
5380 |     streak_freezes_available?: number;
5381 |     streak_longest?: number;
5382 |     student_id?: string;
5383 |     total_active_days?: number;
5384 |     updated_at?: string;
5385 |     xp_total?: number;
5386 |   };
5387 |   Relationships: [
5388 |     {
5389 |       foreignKeyName: "student_gamification_student_id_fkey";
5390 |       columns: ["student_id"];
5391 |       isOneToOne: true;
5392 |       referencedRelation: "profiles";
5393 |       referencedColumns: ["id"];
5394 |     }
5395 |   ];
5396 | };
5397 | student_habit_level_history: {
5398 |   Row: {
5399 |     changed_at: string;
5400 |     id: string;
5401 |     new_level: number;
5402 |     previous_level: number | null;
5403 |     student_id: string;
5404 |   };
5405 |   Insert: {
5406 |     changed_at?: string;
5407 |     id?: string;
5408 |     new_level: number;
5409 |     previous_level?: number | null;
5410 |     student_id: string;
5411 |   };
5412 |   Update: {
5413 |     changed_at?: string;
5414 |     id?: string;
5415 |     new_level?: number;
5416 |     previous_level?: number | null;
5417 |     student_id?: string;
5418 |   };
5419 |   Relationships: [

```

```

5420 |         {
5421 |             foreignKeyName: "student_habit_level_history_student_id_fkey";
5422 |             columns: ["student_id"];
5423 |             isOneToOne: false;
5424 |             referencedRelation: "profiles";
5425 |             referencedColumns: ["id"];
5426 |         }
5427 |     ];
5428 | };
5429 | student_habit_levels: {
5430 |     Row: {
5431 |         current_level: number;
5432 |         id: string;
5433 |         student_id: string;
5434 |         updated_at: string;
5435 |     };
5436 |     Insert: {
5437 |         current_level?: number;
5438 |         id?: string;
5439 |         student_id: string;
5440 |         updated_at?: string;
5441 |     };
5442 |     Update: {
5443 |         current_level?: number;
5444 |         id?: string;
5445 |         student_id?: string;
5446 |         updated_at?: string;
5447 |     };
5448 |     Relationships: [
5449 |         {
5450 |             foreignKeyName: "student_habit_levels_student_id_fkey";
5451 |             columns: ["student_id"];
5452 |             isOneToOne: true;
5453 |             referencedRelation: "profiles";
5454 |             referencedColumns: ["id"];
5455 |         }
5456 |     ];
5457 | };
5458 | student_profiles: {
5459 |     Row: {
5460 |         assessment_version: number;
5461 |         completed_at: string;
5462 |         created_at: string;
5463 |         id: string;
5464 |         institution_id: string;
5465 |         learning_style: Json | null;
5466 |         personality_traits: Json | null;
5467 |         profile_completeness: number;
5468 |         self_efficacy: Json | null;
5469 |         student_id: string;
5470 |         study_strategies: Json | null;
5471 |     };
5472 |     Insert: {
5473 |         assessment_version?: number;
5474 |         completed_at?: string;
5475 |         created_at?: string;
5476 |         id?: string;
5477 |         institution_id: string;
5478 |         learning_style?: Json | null;
5479 |         personality_traits?: Json | null;
5480 |         profile_completeness?: number;
5481 |         self_efficacy?: Json | null;
5482 |         student_id: string;
5483 |         study_strategies?: Json | null;
5484 |     };
5485 |     Update: {
5486 |         assessment_version?: number;
5487 |         completed_at?: string;
5488 |         created_at?: string;
5489 |         id?: string;
5490 |         institution_id?: string;
5491 |         learning_style?: Json | null;
5492 |         personality_traits?: Json | null;
5493 |         profile_completeness?: number;
5494 |         self_efficacy?: Json | null;
5495 |         student_id?: string;
5496 |         study_strategies?: Json | null;
5497 |     };
5498 |     Relationships: [
5499 |         {
5500 |             foreignKeyName: "student_profiles_institution_id_fkey";
5501 |             columns: ["institution_id"];
5502 |             isOneToOne: false;
5503 |             referencedRelation: "institutions";
5504 |             referencedColumns: ["id"];
5505 |         },
5506 |         {
5507 |             foreignKeyName: "student_profiles_institution_id_fkey";
5508 |             columns: ["institution_id"];
5509 |             isOneToOne: false;
5510 |             referencedRelation: "institutions_public";
5511 |             referencedColumns: ["id"];
5512 |         },
5513 |         {
5514 |             foreignKeyName: "student_profiles_student_id_fkey";
5515 |             columns: ["student_id"];
5516 |             isOneToOne: false;
5517 |             referencedRelation: "profiles";
5518 |             referencedColumns: ["id"];
5519 |         }
5520 |     ];
5521 | };
5522 | student_quest_progress: {
5523 |     Row: {

```

```

5524 |         completed_at: string | null;
5525 |         id: string;
5526 |         quest_id: string;
5527 |         reward_claimed: boolean;
5528 |         started_at: string;
5529 |         status: string;
5530 |         student_id: string;
5531 |     };
5532 |     Insert: {
5533 |         completed_at?: string | null;
5534 |         id?: string;
5535 |         quest_id: string;
5536 |         reward_claimed?: boolean;
5537 |         started_at?: string;
5538 |         status?: string;
5539 |         student_id: string;
5540 |     };
5541 |     Update: {
5542 |         completed_at?: string | null;
5543 |         id?: string;
5544 |         quest_id?: string;
5545 |         reward_claimed?: boolean;
5546 |         started_at?: string;
5547 |         status?: string;
5548 |         student_id?: string;
5549 |     };
5550 |     Relationships: [
5551 |         {
5552 |             foreignKeyName: "student_quest_progress_quest_id_fkey";
5553 |             columns: ["quest_id"];
5554 |             isOneToOne: false;
5555 |             referencedRelation: "knowledge_requests";
5556 |             referencedColumns: ["id"];
5557 |         },
5558 |         {
5559 |             foreignKeyName: "student_quest_progress_student_id_fkey";
5560 |             columns: ["student_id"];
5561 |             isOneToOne: false;
5562 |             referencedRelation: "profiles";
5563 |             referencedColumns: ["id"];
5564 |         }
5565 |     ];
5566 | };
5567 | student_wellness_preferences: {
5568 |     Row: {
5569 |         created_at: string;
5570 |         dismissed_onboarding_tips: string[];
5571 |         enabled_habits: string[];
5572 |         habit_targets: Json;
5573 |         id: string;
5574 |         parent_visibility: boolean;
5575 |         reminder_times: Json;
5576 |         student_id: string;
5577 |         updated_at: string;
5578 |     };
5579 |     Insert: {
5580 |         created_at?: string;
5581 |         dismissed_onboarding_tips?: string[];
5582 |         enabled_habits?: string[];
5583 |         habit_targets?: Json;
5584 |         id?: string;
5585 |         parent_visibility?: boolean;
5586 |         reminder_times?: Json;
5587 |         student_id: string;
5588 |         updated_at?: string;
5589 |     };
5590 |     Update: {
5591 |         created_at?: string;
5592 |         dismissed_onboarding_tips?: string[];
5593 |         enabled_habits?: string[];
5594 |         habit_targets?: Json;
5595 |         id?: string;
5596 |         parent_visibility?: boolean;
5597 |         reminder_times?: Json;
5598 |         student_id?: string;
5599 |         updated_at?: string;
5600 |     };
5601 |     Relationships: [
5602 |         {
5603 |             foreignKeyName: "student_wellness_preferences_student_id_fkey";
5604 |             columns: ["student_id"];
5605 |             isOneToOne: true;
5606 |             referencedRelation: "profiles";
5607 |             referencedColumns: ["id"];
5608 |         }
5609 |     ];
5610 | };
5611 | study_sessions: {
5612 |     Row: {
5613 |         actual_duration_minutes: number | null;
5614 |         actual_end_at: string | null;
5615 |         actual_start_at: string | null;
5616 |         clo_id: string | null;
5617 |         clo_ids: string[] | null;
5618 |         course_id: string | null;
5619 |         created_at: string | null;
5620 |         description: string | null;
5621 |         ended_at: string | null;
5622 |         flow_rating: number | null;
5623 |         id: string;
5624 |         intent: string | null;
5625 |         planned_date: string | null;
5626 |         planned_duration_minutes: number | null;
5627 |         planned_start_time: string | null;

```

```

5628 |         reflection: string | null;
5629 |         satisfaction_rating: number | null;
5630 |         session_type: string;
5631 |         started_at: string;
5632 |         status: Database["public"]["Enums"]["session_status_type"] | null;
5633 |         student_id: string;
5634 |         timer_mode: Database["public"]["Enums"]["timer_mode_type"] | null;
5635 |         title: string | null;
5636 |         updated_at: string | null;
5637 |     };
5638 |     Insert: {
5639 |         actual_duration_minutes?: number | null;
5640 |         actual_end_at?: string | null;
5641 |         actual_start_at?: string | null;
5642 |         clo_id?: string | null;
5643 |         clo_ids?: string[] | null;
5644 |         course_id?: string | null;
5645 |         created_at?: string | null;
5646 |         description?: string | null;
5647 |         ended_at?: string | null;
5648 |         flow_rating?: number | null;
5649 |         id?: string;
5650 |         intent?: string | null;
5651 |         planned_date?: string | null;
5652 |         planned_duration_minutes?: number | null;
5653 |         planned_start_time?: string | null;
5654 |         reflection?: string | null;
5655 |         satisfaction_rating?: number | null;
5656 |         session_type?: string;
5657 |         started_at: string;
5658 |         status?: Database["public"]["Enums"]["session_status_type"] | null;
5659 |         student_id: string;
5660 |         timer_mode?: Database["public"]["Enums"]["timer_mode_type"] | null;
5661 |         title?: string | null;
5662 |         updated_at?: string | null;
5663 |     };
5664 |     Update: {
5665 |         actual_duration_minutes?: number | null;
5666 |         actual_end_at?: string | null;
5667 |         actual_start_at?: string | null;
5668 |         clo_id?: string | null;
5669 |         clo_ids?: string[] | null;
5670 |         course_id?: string | null;
5671 |         created_at?: string | null;
5672 |         description?: string | null;
5673 |         ended_at?: string | null;
5674 |         flow_rating?: number | null;
5675 |         id?: string;
5676 |         intent?: string | null;
5677 |         planned_date?: string | null;
5678 |         planned_duration_minutes?: number | null;
5679 |         planned_start_time?: string | null;
5680 |         reflection?: string | null;
5681 |         satisfaction_rating?: number | null;
5682 |         session_type?: string;
5683 |         started_at: string;
5684 |         status?: Database["public"]["Enums"]["session_status_type"] | null;
5685 |         student_id?: string;
5686 |         timer_mode?: Database["public"]["Enums"]["timer_mode_type"] | null;
5687 |         title?: string | null;
5688 |         updated_at?: string | null;
5689 |     };
5690 |     Relationships: [
5691 |         {
5692 |             foreignKeyName: "study_sessions_clo_id_fkey";
5693 |             columns: ["clo_id"];
5694 |             isOneToOne: false;
5695 |             referencedRelation: "learning_outcomes";
5696 |             referencedColumns: ["id"];
5697 |         },
5698 |         {
5699 |             foreignKeyName: "study_sessions_course_id_fkey";
5700 |             columns: ["course_id"];
5701 |             isOneToOne: false;
5702 |             referencedRelation: "courses";
5703 |             referencedColumns: ["id"];
5704 |         },
5705 |         {
5706 |             foreignKeyName: "study_sessions_student_id_fkey";
5707 |             columns: ["student_id"];
5708 |             isOneToOne: false;
5709 |             referencedRelation: "profiles";
5710 |             referencedColumns: ["id"];
5711 |         }
5712 |     ];
5713 | };
5714 | sub_clos: {
5715 |     Row: {
5716 |         clo_id: string;
5717 |         created_at: string | null;
5718 |         description: string | null;
5719 |         id: string;
5720 |         sort_order: number | null;
5721 |         title: string;
5722 |     };
5723 |     Insert: {
5724 |         clo_id: string;
5725 |         created_at?: string | null;
5726 |         description?: string | null;
5727 |         id?: string;
5728 |         sort_order?: number | null;
5729 |         title: string;
5730 |     };
5731 |     Update: {

```

```

5732 |         clo_id?: string;
5733 |         created_at?: string | null;
5734 |         description?: string | null;
5735 |         id?: string;
5736 |         sort_order?: number | null;
5737 |         title?: string;
5738 |     };
5739 |     Relationships: [
5740 |     {
5741 |         foreignKeyName: "sub_clos_clo_id_fkey";
5742 |         columns: ["clo_id"];
5743 |         isOneToOne: false;
5744 |         referencedRelation: "learning_outcomes";
5745 |         referencedColumns: ["id"];
5746 |     }
5747 | ];
5748 | };
5749 | submissions: {
5750 |     Row: {
5751 |         assignment_id: string;
5752 |         file_url: string | null;
5753 |         id: string;
5754 |         is_late: boolean;
5755 |         plagiarism_score: number | null;
5756 |         status: Database["public"]["Enums"]["submission_status"];
5757 |         student_id: string;
5758 |         submitted_at: string;
5759 |         text_content: string | null;
5760 |     };
5761 |     Insert: {
5762 |         assignment_id: string;
5763 |         file_url?: string | null;
5764 |         id?: string;
5765 |         is_late?: boolean;
5766 |         plagiarism_score?: number | null;
5767 |         status?: Database["public"]["Enums"]["submission_status"];
5768 |         student_id: string;
5769 |         submitted_at?: string;
5770 |         text_content?: string | null;
5771 |     };
5772 |     Update: {
5773 |         assignment_id?: string;
5774 |         file_url?: string | null;
5775 |         id?: string;
5776 |         is_late?: boolean;
5777 |         plagiarism_score?: number | null;
5778 |         status?: Database["public"]["Enums"]["submission_status"];
5779 |         student_id?: string;
5780 |         submitted_at?: string;
5781 |         text_content?: string | null;
5782 |     };
5783 |     Relationships: [
5784 |     {
5785 |         foreignKeyName: "submissions_assignment_id_fkey";
5786 |         columns: ["assignment_id"];
5787 |         isOneToOne: false;
5788 |         referencedRelation: "assignments";
5789 |         referencedColumns: ["id"];
5790 |     },
5791 |     {
5792 |         foreignKeyName: "submissions_student_id_fkey";
5793 |         columns: ["student_id"];
5794 |         isOneToOne: false;
5795 |         referencedRelation: "profiles";
5796 |         referencedColumns: ["id"];
5797 |     }
5798 | ];
5799 | };
5800 | survey_questions: {
5801 |     Row: {
5802 |         id: string;
5803 |         options: Json | null;
5804 |         question_text: string;
5805 |         question_type: string;
5806 |         sort_order: number;
5807 |         survey_id: string;
5808 |     };
5809 |     Insert: {
5810 |         id?: string;
5811 |         options?: Json | null;
5812 |         question_text: string;
5813 |         question_type: string;
5814 |         sort_order?: number;
5815 |         survey_id: string;
5816 |     };
5817 |     Update: {
5818 |         id?: string;
5819 |         options?: Json | null;
5820 |         question_text?: string;
5821 |         question_type?: string;
5822 |         sort_order?: number;
5823 |         survey_id?: string;
5824 |     };
5825 |     Relationships: [
5826 |     {
5827 |         foreignKeyName: "survey_questions_survey_id_fkey";
5828 |         columns: ["survey_id"];
5829 |         isOneToOne: false;
5830 |         referencedRelation: "surveys";
5831 |         referencedColumns: ["id"];
5832 |     }
5833 | ];
5834 | };
5835 | survey_responses: {

```

```

5836 | Row: {
5837 |   created_at: string;
5838 |   id: string;
5839 |   question_id: string;
5840 |   respondent_id: string;
5841 |   response_value: string;
5842 |   survey_id: string;
5843 | };
5844 | Insert: {
5845 |   created_at?: string;
5846 |   id?: string;
5847 |   question_id: string;
5848 |   respondent_id: string;
5849 |   response_value: string;
5850 |   survey_id: string;
5851 | };
5852 | Update: {
5853 |   created_at?: string;
5854 |   id?: string;
5855 |   question_id?: string;
5856 |   respondent_id?: string;
5857 |   response_value?: string;
5858 |   survey_id?: string;
5859 | };
5860 | Relationships: [
5861 |   {
5862 |     foreignKeyName: "survey_responses_question_id_fkey";
5863 |     columns: ["question_id"];
5864 |     isOneToOne: false;
5865 |     referencedRelation: "survey_questions";
5866 |     referencedColumns: ["id"];
5867 |   },
5868 |   {
5869 |     foreignKeyName: "survey_responses_respondent_id_fkey";
5870 |     columns: ["respondent_id"];
5871 |     isOneToOne: false;
5872 |     referencedRelation: "profiles";
5873 |     referencedColumns: ["id"];
5874 |   },
5875 |   {
5876 |     foreignKeyName: "survey_responses_survey_id_fkey";
5877 |     columns: ["survey_id"];
5878 |     isOneToOne: false;
5879 |     referencedRelation: "surveys";
5880 |     referencedColumns: ["id"];
5881 |   }
5882 | ];
5883 | };
5884 | surveys: {
5885 |   Row: {
5886 |     created_at: string;
5887 |     id: string;
5888 |     institution_id: string;
5889 |     is_active: boolean;
5890 |     target_outcomes: Json;
5891 |     title: string;
5892 |     type: string;
5893 |   };
5894 |   Insert: {
5895 |     created_at?: string;
5896 |     id?: string;
5897 |     institution_id: string;
5898 |     is_active?: boolean;
5899 |     target_outcomes?: Json;
5900 |     title: string;
5901 |     type: string;
5902 |   };
5903 |   Update: {
5904 |     created_at?: string;
5905 |     id?: string;
5906 |     institution_id?: string;
5907 |     is_active?: boolean;
5908 |     target_outcomes?: Json;
5909 |     title?: string;
5910 |     type?: string;
5911 |   };
5912 |   Relationships: [
5913 |     {
5914 |       foreignKeyName: "surveys_institution_id_fkey";
5915 |       columns: ["institution_id"];
5916 |       isOneToOne: false;
5917 |       referencedRelation: "institutions";
5918 |       referencedColumns: ["id"];
5919 |     },
5920 |     {
5921 |       foreignKeyName: "surveys_institution_id_fkey";
5922 |       columns: ["institution_id"];
5923 |       isOneToOne: false;
5924 |       referencedRelation: "institutions_public";
5925 |       referencedColumns: ["id"];
5926 |     }
5927 |   ];
5928 | };
5929 | teacher_handoff_requests: {
5930 |   Row: {
5931 |     clo_id: string | null;
5932 |     conversation_id: string;
5933 |     conversation_summary: string;
5934 |     course_id: string;
5935 |     created_at: string;
5936 |     id: string;
5937 |     institution_id: string;
5938 |     resolved_at: string | null;
5939 |     status: string;

```



```

5940 |         student_consent: boolean;
5941 |         student_id: string;
5942 |         suggested_intervention: string;
5943 |         teacher_id: string;
5944 |         teacher_response: string | null;
5945 |         trigger_reason: string;
5946 |     };
5947 |     Insert: {
5948 |         clo_id?: string | null;
5949 |         conversation_id: string;
5950 |         conversation_summary: string;
5951 |         course_id: string;
5952 |         created_at?: string;
5953 |         id?: string;
5954 |         institution_id: string;
5955 |         resolved_at?: string | null;
5956 |         status?: string;
5957 |         student_consent?: boolean;
5958 |         student_id: string;
5959 |         suggested_intervention: string;
5960 |         teacher_id: string;
5961 |         teacher_response?: string | null;
5962 |         trigger_reason: string;
5963 |     };
5964 |     Update: {
5965 |         clo_id?: string | null;
5966 |         conversation_id?: string;
5967 |         conversation_summary?: string;
5968 |         course_id?: string;
5969 |         created_at?: string;
5970 |         id?: string;
5971 |         institution_id?: string;
5972 |         resolved_at?: string | null;
5973 |         status?: string;
5974 |         student_consent?: boolean;
5975 |         student_id?: string;
5976 |         suggested_intervention?: string;
5977 |         teacher_id?: string;
5978 |         teacher_response?: string | null;
5979 |         trigger_reason?: string;
5980 |     };
5981 |     Relationships: [
5982 |     {
5983 |         foreignKeyName: "teacher_handoff_requests_conversation_id_fkey";
5984 |         columns: ["conversation_id"];
5985 |         isOneToOne: false;
5986 |         referencedRelation: "tutor_conversations";
5987 |         referencedColumns: ["id"];
5988 |     },
5989 |     {
5990 |         foreignKeyName: "teacher_handoff_requests_course_id_fkey";
5991 |         columns: ["course_id"];
5992 |         isOneToOne: false;
5993 |         referencedRelation: "courses";
5994 |         referencedColumns: ["id"];
5995 |     },
5996 |     {
5997 |         foreignKeyName: "teacher_handoff_requests_institution_id_fkey";
5998 |         columns: ["institution_id"];
5999 |         isOneToOne: false;
6000 |         referencedRelation: "institutions";
6001 |         referencedColumns: ["id"];
6002 |     },
6003 |     {
6004 |         foreignKeyName: "teacher_handoff_requests_institution_id_fkey";
6005 |         columns: ["institution_id"];
6006 |         isOneToOne: false;
6007 |         referencedRelation: "institutions_public";
6008 |         referencedColumns: ["id"];
6009 |     },
6010 |     {
6011 |         foreignKeyName: "teacher_handoff_requests_student_id_fkey";
6012 |         columns: ["student_id"];
6013 |         isOneToOne: false;
6014 |         referencedRelation: "profiles";
6015 |         referencedColumns: ["id"];
6016 |     },
6017 |     {
6018 |         foreignKeyName: "teacher_handoff_requests_teacher_id_fkey";
6019 |         columns: ["teacher_id"];
6020 |         isOneToOne: false;
6021 |         referencedRelation: "profiles";
6022 |         referencedColumns: ["id"];
6023 |     }
6024 | ];
6025 | };
6026 | teaching_moment_ratings: {
6027 |     Row: {
6028 |         clarity_rating: number;
6029 |         helpfulness_rating: number;
6030 |         id: string;
6031 |         rated_at: string;
6032 |         teaching_moment_id: string;
6033 |         viewer_id: string;
6034 |     };
6035 |     Insert: {
6036 |         clarity_rating: number;
6037 |         helpfulness_rating: number;
6038 |         id?: string;
6039 |         rated_at?: string;
6040 |         teaching_moment_id: string;
6041 |         viewer_id: string;
6042 |     };
6043 |     Update: {

```

```

6044 |         clarity_rating?: number;
6045 |         helpfulness_rating?: number;
6046 |         id?: string;
6047 |         rated_at?: string;
6048 |         teaching_moment_id?: string;
6049 |         viewer_id?: string;
6050 |     };
6051 |     Relationships: [
6052 |     {
6053 |         foreignKeyName: "teaching_moment_ratings_teaching_moment_id_fkey";
6054 |         columns: ["teaching_moment_id"];
6055 |         isOneToOne: false;
6056 |         referencedRelation: "peer_teaching_moments";
6057 |         referencedColumns: ["id"];
6058 |     },
6059 |     {
6060 |         foreignKeyName: "teaching_moment_ratings_viewer_id_fkey";
6061 |         columns: ["viewer_id"];
6062 |         isOneToOne: false;
6063 |         referencedRelation: "profiles";
6064 |         referencedColumns: ["id"];
6065 |     }
6066 | ];
6067 | };
6068 | teaching_moment_views: {
6069 |     Row: {
6070 |         id: string;
6071 |         pre_view_attainment: number | null;
6072 |         teaching_moment_id: string;
6073 |         viewed_at: string;
6074 |         viewer_id: string;
6075 |     };
6076 |     Insert: {
6077 |         id?: string;
6078 |         pre_view_attainment?: number | null;
6079 |         teaching_moment_id: string;
6080 |         viewed_at?: string;
6081 |         viewer_id: string;
6082 |     };
6083 |     Update: {
6084 |         id?: string;
6085 |         pre_view_attainment?: number | null;
6086 |         teaching_moment_id?: string;
6087 |         viewed_at?: string;
6088 |         viewer_id?: string;
6089 |     };
6090 |     Relationships: [
6091 |     {
6092 |         foreignKeyName: "teaching_moment_views_teaching_moment_id_fkey";
6093 |         columns: ["teaching_moment_id"];
6094 |         isOneToOne: false;
6095 |         referencedRelation: "peer_teaching_moments";
6096 |         referencedColumns: ["id"];
6097 |     },
6098 |     {
6099 |         foreignKeyName: "teaching_moment_views_viewer_id_fkey";
6100 |         columns: ["viewer_id"];
6101 |         isOneToOne: false;
6102 |         referencedRelation: "profiles";
6103 |         referencedColumns: ["id"];
6104 |     }
6105 | ];
6106 | };
6107 | team_badges: {
6108 |     Row: {
6109 |         badge_key: string;
6110 |         earned_at: string;
6111 |         id: string;
6112 |         team_id: string;
6113 |     };
6114 |     Insert: {
6115 |         badge_key: string;
6116 |         earned_at?: string;
6117 |         id?: string;
6118 |         team_id: string;
6119 |     };
6120 |     Update: {
6121 |         badge_key?: string;
6122 |         earned_at?: string;
6123 |         id?: string;
6124 |         team_id?: string;
6125 |     };
6126 |     Relationships: [
6127 |     {
6128 |         foreignKeyName: "team_badges_team_id_fkey";
6129 |         columns: ["team_id"];
6130 |         isOneToOne: false;
6131 |         referencedRelation: "teams";
6132 |         referencedColumns: ["id"];
6133 |     }
6134 | ];
6135 | };
6136 | team_gamification: {
6137 |     Row: {
6138 |         id: string;
6139 |         last_streak_date: string | null;
6140 |         streak_current: number;
6141 |         streak_longest: number;
6142 |         team_id: string;
6143 |         updated_at: string;
6144 |         xp_this_week: number;
6145 |         xp_total: number;
6146 |     };
6147 |     Insert: {

```

```

6148 |         id?: string;
6149 |         last_streak_date?: string | null;
6150 |         streak_current?: number;
6151 |         streak_longest?: number;
6152 |         team_id: string;
6153 |         updated_at?: string;
6154 |         xp_this_week?: number;
6155 |         xp_total?: number;
6156 |     };
6157 |     Update: {
6158 |         id?: string;
6159 |         last_streak_date?: string | null;
6160 |         streak_current?: number;
6161 |         streak_longest?: number;
6162 |         team_id?: string;
6163 |         updated_at?: string;
6164 |         xp_this_week?: number;
6165 |         xp_total?: number;
6166 |     };
6167 |     Relationships: [
6168 |         {
6169 |             foreignKeyName: "team_gamification_team_id_fkey";
6170 |             columns: ["team_id"];
6171 |             isOneToOne: true;
6172 |             referencedRelation: "teams";
6173 |             referencedColumns: ["id"];
6174 |         }
6175 |     ];
6176 | };
6177 | team_health_snapshots: {
6178 |     Row: {
6179 |         activity_overlap_rate: number;
6180 |         challenge_participation_rate: number;
6181 |         computed_at: string;
6182 |         engagement_trend: string;
6183 |         gini_coefficient: number;
6184 |         health_score: number;
6185 |         id: string;
6186 |         team_id: string;
6187 |     };
6188 |     Insert: {
6189 |         activity_overlap_rate: number;
6190 |         challenge_participation_rate: number;
6191 |         computed_at?: string;
6192 |         engagement_trend: string;
6193 |         gini_coefficient: number;
6194 |         health_score: number;
6195 |         id?: string;
6196 |         team_id: string;
6197 |     };
6198 |     Update: {
6199 |         activity_overlap_rate?: number;
6200 |         challenge_participation_rate?: number;
6201 |         computed_at?: string;
6202 |         engagement_trend?: string;
6203 |         gini_coefficient?: number;
6204 |         health_score?: number;
6205 |         id?: string;
6206 |         team_id?: string;
6207 |     };
6208 |     Relationships: [
6209 |         {
6210 |             foreignKeyName: "team_health_snapshots_team_id_fkey";
6211 |             columns: ["team_id"];
6212 |             isOneToOne: false;
6213 |             referencedRelation: "teams";
6214 |             referencedColumns: ["id"];
6215 |         }
6216 |     ];
6217 | };
6218 | team_invitations: {
6219 |     Row: {
6220 |         created_at: string;
6221 |         id: string;
6222 |         invited_by: string;
6223 |         invited_student_id: string;
6224 |         responded_at: string | null;
6225 |         status: string;
6226 |         team_id: string;
6227 |     };
6228 |     Insert: {
6229 |         created_at?: string;
6230 |         id?: string;
6231 |         invited_by: string;
6232 |         invited_student_id: string;
6233 |         responded_at?: string | null;
6234 |         status?: string;
6235 |         team_id: string;
6236 |     };
6237 |     Update: {
6238 |         created_at?: string;
6239 |         id?: string;
6240 |         invited_by?: string;
6241 |         invited_student_id?: string;
6242 |         responded_at?: string | null;
6243 |         status?: string;
6244 |         team_id?: string;
6245 |     };
6246 |     Relationships: [
6247 |         {
6248 |             foreignKeyName: "team_invitations_invited_by_fkey";
6249 |             columns: ["invited_by"];
6250 |             isOneToOne: false;
6251 |             referencedRelation: "profiles";

```

```

6252 |         referencedColumnName: ["id"];
6253 |     },
6254 |     {
6255 |         foreignKeyName: "team_invitations_invited_student_id_fkey";
6256 |         columns: ["invited_student_id"];
6257 |         isOneToOne: false;
6258 |         referencedRelation: "profiles";
6259 |         referencedColumnName: ["id"];
6260 |     },
6261 |     {
6262 |         foreignKeyName: "team_invitations_team_id_fkey";
6263 |         columns: ["team_id"];
6264 |         isOneToOne: false;
6265 |         referencedRelation: "teams";
6266 |         referencedColumnName: ["id"];
6267 |     }
6268 | ];
6269 |
6270 | team_members: {
6271 |     Row: {
6272 |         consecutive_low_days: number;
6273 |         contribution_status: string;
6274 |         contribution_status_since: string | null;
6275 |         id: string;
6276 |         joined_at: string;
6277 |         left_at: string | null;
6278 |         role: string;
6279 |         student_id: string;
6280 |         team_id: string;
6281 |     };
6282 |     Insert: {
6283 |         consecutive_low_days?: number;
6284 |         contribution_status?: string;
6285 |         contribution_status_since?: string | null;
6286 |         id?: string;
6287 |         joined_at?: string;
6288 |         left_at?: string | null;
6289 |         role?: string;
6290 |         student_id: string;
6291 |         team_id: string;
6292 |     };
6293 |     Update: {
6294 |         consecutive_low_days?: number;
6295 |         contribution_status?: string;
6296 |         contribution_status_since?: string | null;
6297 |         id?: string;
6298 |         joined_at?: string;
6299 |         left_at?: string | null;
6300 |         role?: string;
6301 |         student_id?: string;
6302 |         team_id?: string;
6303 |     };
6304 |     Relationships: [
6305 |         {
6306 |             foreignKeyName: "team_members_student_id_fkey";
6307 |             columns: ["student_id"];
6308 |             isOneToOne: false;
6309 |             referencedRelation: "profiles";
6310 |             referencedColumnName: ["id"];
6311 |         },
6312 |         {
6313 |             foreignKeyName: "team_members_team_id_fkey";
6314 |             columns: ["team_id"];
6315 |             isOneToOne: false;
6316 |             referencedRelation: "teams";
6317 |             referencedColumnName: ["id"];
6318 |         }
6319 |     ];
6320 | };
6321 | teams: {
6322 |     Row: {
6323 |         avatar_letter: string | null;
6324 |         captain_id: string;
6325 |         cooperation_score: number;
6326 |         course_id: string;
6327 |         created_at: string;
6328 |         created_by: string;
6329 |         deleted_at: string | null;
6330 |         health_score: number;
6331 |         health_status: string;
6332 |         id: string;
6333 |         institution_id: string;
6334 |         name: string;
6335 |         streak_count: number;
6336 |         streak_last_active_date: string | null;
6337 |         updated_at: string;
6338 |         xp_total: number;
6339 |     };
6340 |     Insert: {
6341 |         avatar_letter?: string | null;
6342 |         captain_id: string;
6343 |         cooperation_score?: number;
6344 |         course_id: string;
6345 |         created_at?: string;
6346 |         created_by: string;
6347 |         deleted_at?: string | null;
6348 |         health_score?: number;
6349 |         health_status?: string;
6350 |         id?: string;
6351 |         institution_id: string;
6352 |         name: string;
6353 |         streak_count?: number;
6354 |         streak_last_active_date?: string | null;
6355 |         updated_at?: string;

```

```

6356 |         xp_total?: number;
6357 |     };
6358 |     Update: {
6359 |         avatar_letter?: string | null;
6360 |         captain_id?: string;
6361 |         cooperation_score?: number;
6362 |         course_id?: string;
6363 |         created_at?: string;
6364 |         created_by?: string;
6365 |         deleted_at?: string | null;
6366 |         health_score?: number;
6367 |         health_status?: string;
6368 |         id?: string;
6369 |         institution_id?: string;
6370 |         name?: string;
6371 |         streak_count?: number;
6372 |         streak_last_active_date?: string | null;
6373 |         updated_at?: string;
6374 |         xp_total?: number;
6375 |     };
6376 |     Relationships: [
6377 |     {
6378 |         foreignKeyName: "teams_captain_id_fkey";
6379 |         columns: ["captain_id"];
6380 |         isOneToOne: false;
6381 |         referencedRelation: "profiles";
6382 |         referencedColumns: ["id"];
6383 |     },
6384 |     {
6385 |         foreignKeyName: "teams_course_id_fkey";
6386 |         columns: ["course_id"];
6387 |         isOneToOne: false;
6388 |         referencedRelation: "courses";
6389 |         referencedColumns: ["id"];
6390 |     },
6391 |     {
6392 |         foreignKeyName: "teams_created_by_fkey";
6393 |         columns: ["created_by"];
6394 |         isOneToOne: false;
6395 |         referencedRelation: "profiles";
6396 |         referencedColumns: ["id"];
6397 |     },
6398 |     {
6399 |         foreignKeyName: "teams_institution_id_fkey";
6400 |         columns: ["institution_id"];
6401 |         isOneToOne: false;
6402 |         referencedRelation: "institutions";
6403 |         referencedColumns: ["id"];
6404 |     },
6405 |     {
6406 |         foreignKeyName: "teams_institution_id_fkey";
6407 |         columns: ["institution_id"];
6408 |         isOneToOne: false;
6409 |         referencedRelation: "institutions_public";
6410 |         referencedColumns: ["id"];
6411 |     }
6412 | ];
6413 | };
6414 | timetable_slots: {
6415 |     Row: {
6416 |         day_of_week: number;
6417 |         end_time: string;
6418 |         id: string;
6419 |         room: string | null;
6420 |         section_id: string;
6421 |         slot_type: string;
6422 |         start_time: string;
6423 |     };
6424 |     Insert: {
6425 |         day_of_week: number;
6426 |         end_time: string;
6427 |         id?: string;
6428 |         room?: string | null;
6429 |         section_id: string;
6430 |         slot_type: string;
6431 |         start_time: string;
6432 |     };
6433 |     Update: {
6434 |         day_of_week?: number;
6435 |         end_time?: string;
6436 |         id?: string;
6437 |         room?: string | null;
6438 |         section_id?: string;
6439 |         slot_type?: string;
6440 |         start_time?: string;
6441 |     };
6442 |     Relationships: [
6443 |     {
6444 |         foreignKeyName: "timetable_slots_section_id_fkey";
6445 |         columns: ["section_id"];
6446 |         isOneToOne: false;
6447 |         referencedRelation: "course_sections";
6448 |         referencedColumns: ["id"];
6449 |     }
6450 | ];
6451 | };
6452 | tutor_conversations: {
6453 |     Row: {
6454 |         autonomy_override: string | null;
6455 |         clo_scope: string[] | null;
6456 |         course_id: string | null;
6457 |         created_at: string;
6458 |         id: string;
6459 |         institution_id: string;

```

```

6460 |         is_active: boolean;
6461 |         message_count: number;
6462 |         persona: string;
6463 |         recommended_persona: string | null;
6464 |         student_id: string;
6465 |         title: string | null;
6466 |         updated_at: string;
6467 |         xp_awarded: boolean;
6468 |     };
6469 |     Insert: {
6470 |         autonomy_override?: string | null;
6471 |         clo_scope?: string[] | null;
6472 |         course_id?: string | null;
6473 |         created_at?: string;
6474 |         id?: string;
6475 |         institution_id: string;
6476 |         is_active?: boolean;
6477 |         message_count?: number;
6478 |         persona?: string;
6479 |         recommended_persona?: string | null;
6480 |         student_id: string;
6481 |         title?: string | null;
6482 |         updated_at?: string;
6483 |         xp_awarded?: boolean;
6484 |     };
6485 |     Update: {
6486 |         autonomy_override?: string | null;
6487 |         clo_scope?: string[] | null;
6488 |         course_id?: string | null;
6489 |         created_at?: string;
6490 |         id?: string;
6491 |         institution_id?: string;
6492 |         is_active?: boolean;
6493 |         message_count?: number;
6494 |         persona?: string;
6495 |         recommended_persona?: string | null;
6496 |         student_id?: string;
6497 |         title?: string | null;
6498 |         updated_at?: string;
6499 |         xp_awarded?: boolean;
6500 |     };
6501 |     Relationships: [
6502 |     {
6503 |         foreignKeyName: "tutor_conversations_course_id_fkey";
6504 |         columns: ["course_id"];
6505 |         isOneToOne: false;
6506 |         referencedRelation: "courses";
6507 |         referencedColumns: ["id"];
6508 |     },
6509 |     {
6510 |         foreignKeyName: "tutor_conversations_institution_id_fkey";
6511 |         columns: ["institution_id"];
6512 |         isOneToOne: false;
6513 |         referencedRelation: "institutions";
6514 |         referencedColumns: ["id"];
6515 |     },
6516 |     {
6517 |         foreignKeyName: "tutor_conversations_institution_id_fkey";
6518 |         columns: ["institution_id"];
6519 |         isOneToOne: false;
6520 |         referencedRelation: "institutions_public";
6521 |         referencedColumns: ["id"];
6522 |     },
6523 |     {
6524 |         foreignKeyName: "tutor_conversations_student_id_fkey";
6525 |         columns: ["student_id"];
6526 |         isOneToOne: false;
6527 |         referencedRelation: "profiles";
6528 |         referencedColumns: ["id"];
6529 |     }
6530 | ];
6531 | };
6532 | tutor_llm_logs: {
6533 |     Row: {
6534 |         completion_tokens: number;
6535 |         conversation_id: string | null;
6536 |         created_at: string;
6537 |         error_message: string | null;
6538 |         id: string;
6539 |         institution_id: string;
6540 |         latency_ms: number;
6541 |         model_used: string;
6542 |         prompt_tokens: number;
6543 |         status: string;
6544 |         student_id: string;
6545 |         total_tokens: number;
6546 |     };
6547 |     Insert: {
6548 |         completion_tokens: number;
6549 |         conversation_id?: string | null;
6550 |         created_at?: string;
6551 |         error_message?: string | null;
6552 |         id?: string;
6553 |         institution_id: string;
6554 |         latency_ms: number;
6555 |         model_used: string;
6556 |         prompt_tokens: number;
6557 |         status: string;
6558 |         student_id: string;
6559 |         total_tokens: number;
6560 |     };
6561 |     Update: {
6562 |         completion_tokens?: number;
6563 |         conversation_id?: string | null;

```

```

6564 |         created_at?: string;
6565 |         error_message?: string | null;
6566 |         id?: string;
6567 |         institution_id?: string;
6568 |         latency_ms?: number;
6569 |         model_used?: string;
6570 |         prompt_tokens?: number;
6571 |         status?: string;
6572 |         student_id?: string;
6573 |         total_tokens?: number;
6574 |     };
6575 |     Relationships: [
6576 |     {
6577 |         foreignKeyName: "tutor_llm_logs_conversation_id_fkey";
6578 |         columns: ["conversation_id"];
6579 |         isOneToOne: false;
6580 |         referencedRelation: "tutor_conversations";
6581 |         referencedColumns: ["id"];
6582 |     },
6583 |     {
6584 |         foreignKeyName: "tutor_llm_logs_institution_id_fkey";
6585 |         columns: ["institution_id"];
6586 |         isOneToOne: false;
6587 |         referencedRelation: "institutions";
6588 |         referencedColumns: ["id"];
6589 |     },
6590 |     {
6591 |         foreignKeyName: "tutor_llm_logs_institution_id_fkey";
6592 |         columns: ["institution_id"];
6593 |         isOneToOne: false;
6594 |         referencedRelation: "institutions_public";
6595 |         referencedColumns: ["id"];
6596 |     },
6597 |     {
6598 |         foreignKeyName: "tutor_llm_logs_student_id_fkey";
6599 |         columns: ["student_id"];
6600 |         isOneToOne: false;
6601 |         referencedRelation: "profiles";
6602 |         referencedColumns: ["id"];
6603 |     }
6604 | ];
6605 | };
6606 | tutor_messages: {
6607 |     Row: {
6608 |         autonomy_level: string | null;
6609 |         content: string;
6610 |         conversation_id: string;
6611 |         created_at: string;
6612 |         document_url: string | null;
6613 |         flagged_integrity: boolean;
6614 |         id: string;
6615 |         image_urls: string[] | null;
6616 |         nudge_type: string | null;
6617 |         role: string;
6618 |         satisfaction_rating: string | null;
6619 |         source_citations: Json | null;
6620 |         token_count: number;
6621 |     };
6622 |     Insert: {
6623 |         autonomy_level?: string | null;
6624 |         content: string;
6625 |         conversation_id: string;
6626 |         created_at?: string;
6627 |         document_url?: string | null;
6628 |         flagged_integrity?: boolean;
6629 |         id?: string;
6630 |         image_urls?: string[] | null;
6631 |         nudge_type?: string | null;
6632 |         role: string;
6633 |         satisfaction_rating?: string | null;
6634 |         source_citations?: Json | null;
6635 |         token_count?: number;
6636 |     };
6637 |     Update: {
6638 |         autonomy_level?: string | null;
6639 |         content?: string;
6640 |         conversation_id?: string;
6641 |         created_at?: string;
6642 |         document_url?: string | null;
6643 |         flagged_integrity?: boolean;
6644 |         id?: string;
6645 |         image_urls?: string[] | null;
6646 |         nudge_type?: string | null;
6647 |         role?: string;
6648 |         satisfaction_rating?: string | null;
6649 |         source_citations?: Json | null;
6650 |         token_count?: number;
6651 |     };
6652 |     Relationships: [
6653 |     {
6654 |         foreignKeyName: "tutor_messages_conversation_id_fkey";
6655 |         columns: ["conversation_id"];
6656 |         isOneToOne: false;
6657 |         referencedRelation: "tutor_conversations";
6658 |         referencedColumns: ["id"];
6659 |     }
6660 | ];
6661 | };
6662 | tutor_plan_updates: {
6663 |     Row: {
6664 |         clo_id: string;
6665 |         conversation_id: string;
6666 |         course_id: string;
6667 |         created_at: string;

```

```

6668 |         id: string;
6669 |         institution_id: string;
6670 |         interaction_count: number;
6671 |         modifications: string | null;
6672 |         recommended_materials: Json;
6673 |         responded_at: string | null;
6674 |         response: string | null;
6675 |         student_id: string;
6676 |         study_time_recommendation: string;
6677 |         suggested_planner_sessions: number;
6678 |     };
6679 |     Insert: {
6680 |         clo_id: string;
6681 |         conversation_id: string;
6682 |         course_id: string;
6683 |         created_at?: string;
6684 |         id?: string;
6685 |         institution_id: string;
6686 |         interaction_count: number;
6687 |         modifications?: string | null;
6688 |         recommended_materials?: Json;
6689 |         responded_at?: string | null;
6690 |         response?: string | null;
6691 |         student_id: string;
6692 |         study_time_recommendation: string;
6693 |         suggested_planner_sessions?: number;
6694 |     };
6695 |     Update: {
6696 |         clo_id?: string;
6697 |         conversation_id?: string;
6698 |         course_id?: string;
6699 |         created_at?: string;
6700 |         id?: string;
6701 |         institution_id?: string;
6702 |         interaction_count?: number;
6703 |         modifications?: string | null;
6704 |         recommended_materials?: Json;
6705 |         responded_at?: string | null;
6706 |         response?: string | null;
6707 |         student_id?: string;
6708 |         study_time_recommendation?: string;
6709 |         suggested_planner_sessions?: number;
6710 |     };
6711 |     Relationships: [
6712 |         {
6713 |             foreignKeyName: "tutor_plan_updates_conversation_id_fkey";
6714 |             columns: ["conversation_id"];
6715 |             isOneToOne: false;
6716 |             referencedRelation: "tutor_conversations";
6717 |             referencedColumns: ["id"];
6718 |         },
6719 |         {
6720 |             foreignKeyName: "tutor_plan_updates_course_id_fkey";
6721 |             columns: ["course_id"];
6722 |             isOneToOne: false;
6723 |             referencedRelation: "courses";
6724 |             referencedColumns: ["id"];
6725 |         },
6726 |         {
6727 |             foreignKeyName: "tutor_plan_updates_institution_id_fkey";
6728 |             columns: ["institution_id"];
6729 |             isOneToOne: false;
6730 |             referencedRelation: "institutions";
6731 |             referencedColumns: ["id"];
6732 |         },
6733 |         {
6734 |             foreignKeyName: "tutor_plan_updates_institution_id_fkey";
6735 |             columns: ["institution_id"];
6736 |             isOneToOne: false;
6737 |             referencedRelation: "institutions_public";
6738 |             referencedColumns: ["id"];
6739 |         },
6740 |         {
6741 |             foreignKeyName: "tutor_plan_updates_student_id_fkey";
6742 |             columns: ["student_id"];
6743 |             isOneToOne: false;
6744 |             referencedRelation: "profiles";
6745 |             referencedColumns: ["id"];
6746 |         }
6747 |     ];
6748 | };
6749 | tutor_usage_limits: {
6750 |     Row: {
6751 |         created_at: string;
6752 |         id: string;
6753 |         institution_id: string;
6754 |         message_count: number;
6755 |         student_id: string;
6756 |         token_count: number;
6757 |         usage_date: string;
6758 |     };
6759 |     Insert: {
6760 |         created_at?: string;
6761 |         id?: string;
6762 |         institution_id: string;
6763 |         message_count?: number;
6764 |         student_id: string;
6765 |         token_count?: number;
6766 |         usage_date?: string;
6767 |     };
6768 |     Update: {
6769 |         created_at?: string;
6770 |         id?: string;
6771 |         institution_id?: string;

```



```

6772 |         message_count?: number;
6773 |         student_id?: string;
6774 |         token_count?: number;
6775 |         usage_date?: string;
6776 |     };
6777 |     Relationships: [
6778 |     {
6779 |         foreignKeyName: "tutor_usage_limits_institution_id_fkey";
6780 |         columns: ["institution_id"];
6781 |         isOneToOne: false;
6782 |         referencedRelation: "institutions";
6783 |         referencedColumns: ["id"];
6784 |     },
6785 |     {
6786 |         foreignKeyName: "tutor_usage_limits_institution_id_fkey";
6787 |         columns: ["institution_id"];
6788 |         isOneToOne: false;
6789 |         referencedRelation: "institutions_public";
6790 |         referencedColumns: ["id"];
6791 |     },
6792 |     {
6793 |         foreignKeyName: "tutor_usage_limits_student_id_fkey";
6794 |         columns: ["student_id"];
6795 |         isOneToOne: false;
6796 |         referencedRelation: "profiles";
6797 |         referencedColumns: ["id"];
6798 |     }
6799 | ];
6800 | };
6801 | verified_explanations: {
6802 |     Row: {
6803 |         created_at: string;
6804 |         explanation_text: string;
6805 |         id: string;
6806 |         institution_id: string;
6807 |         is_active: boolean;
6808 |         question_id: string;
6809 |         source: string;
6810 |         updated_at: string;
6811 |         verified_by: string;
6812 |     };
6813 |     Insert: {
6814 |         created_at?: string;
6815 |         explanation_text: string;
6816 |         id?: string;
6817 |         institution_id: string;
6818 |         is_active?: boolean;
6819 |         question_id: string;
6820 |         source: string;
6821 |         updated_at?: string;
6822 |         verified_by: string;
6823 |     };
6824 |     Update: {
6825 |         created_at?: string;
6826 |         explanation_text?: string;
6827 |         id?: string;
6828 |         institution_id?: string;
6829 |         is_active?: boolean;
6830 |         question_id?: string;
6831 |         source?: string;
6832 |         updated_at?: string;
6833 |         verified_by?: string;
6834 |     };
6835 |     Relationships: [
6836 |     {
6837 |         foreignKeyName: "verified_explanations_institution_id_fkey";
6838 |         columns: ["institution_id"];
6839 |         isOneToOne: false;
6840 |         referencedRelation: "institutions";
6841 |         referencedColumns: ["id"];
6842 |     },
6843 |     {
6844 |         foreignKeyName: "verified_explanations_institution_id_fkey";
6845 |         columns: ["institution_id"];
6846 |         isOneToOne: false;
6847 |         referencedRelation: "institutions_public";
6848 |         referencedColumns: ["id"];
6849 |     },
6850 |     {
6851 |         foreignKeyName: "verified_explanations_question_id_fkey";
6852 |         columns: ["question_id"];
6853 |         isOneToOne: false;
6854 |         referencedRelation: "question_bank";
6855 |         referencedColumns: ["id"];
6856 |     },
6857 |     {
6858 |         foreignKeyName: "verified_explanations_verified_by_fkey";
6859 |         columns: ["verified_by"];
6860 |         isOneToOne: false;
6861 |         referencedRelation: "profiles";
6862 |         referencedColumns: ["id"];
6863 |     }
6864 | ];
6865 | };
6866 | weekly_goals: {
6867 |     Row: {
6868 |         created_at: string | null;
6869 |         current_value: number | null;
6870 |         goal_text: string;
6871 |         goal_type: string | null;
6872 |         id: string;
6873 |         status: string | null;
6874 |         student_id: string;
6875 |         target_value: number | null;

```

```

6876 |         updated_at: string | null;
6877 |         week_start: string;
6878 |         week_start_date: string;
6879 |     };
6880 |     Insert: {
6881 |         created_at?: string | null;
6882 |         current_value?: number | null;
6883 |         goal_text: string;
6884 |         goal_type?: string | null;
6885 |         id?: string;
6886 |         status?: string | null;
6887 |         student_id: string;
6888 |         target_value?: number | null;
6889 |         updated_at?: string | null;
6890 |         week_start: string;
6891 |         week_start_date: string;
6892 |     };
6893 |     Update: {
6894 |         created_at?: string | null;
6895 |         current_value?: number | null;
6896 |         goal_text?: string;
6897 |         goal_type?: string | null;
6898 |         id?: string;
6899 |         status?: string | null;
6900 |         student_id?: string;
6901 |         target_value?: number | null;
6902 |         updated_at?: string | null;
6903 |         week_start?: string;
6904 |         week_start_date?: string;
6905 |     };
6906 |     Relationships: [
6907 |         {
6908 |             foreignKeyName: "weekly_goals_student_id_fkey";
6909 |             columns: ["student_id"];
6910 |             isOneToOne: false;
6911 |             referencedRelation: "profiles";
6912 |             referencedColumns: ["id"];
6913 |         }
6914 |     ];
6915 | };
6916 | wellness_habit_logs: {
6917 |     Row: {
6918 |         completed_at: string;
6919 |         created_at: string;
6920 |         date: string;
6921 |         id: string;
6922 |         student_id: string;
6923 |         value: number | null;
6924 |         wellness_type: Database["public"]["Enums"]["wellness_habit_type"];
6925 |     };
6926 |     Insert: {
6927 |         completed_at?: string;
6928 |         created_at?: string;
6929 |         date: string;
6930 |         id?: string;
6931 |         student_id: string;
6932 |         value?: number | null;
6933 |         wellness_type: Database["public"]["Enums"]["wellness_habit_type"];
6934 |     };
6935 |     Update: {
6936 |         completed_at?: string;
6937 |         created_at?: string;
6938 |         date?: string;
6939 |         id?: string;
6940 |         student_id?: string;
6941 |         value?: number | null;
6942 |         wellness_type?: Database["public"]["Enums"]["wellness_habit_type"];
6943 |     };
6944 |     Relationships: [
6945 |         {
6946 |             foreignKeyName: "wellness_habit_logs_student_id_fkey";
6947 |             columns: ["student_id"];
6948 |             isOneToOne: false;
6949 |             referencedRelation: "profiles";
6950 |             referencedColumns: ["id"];
6951 |         }
6952 |     ];
6953 | };
6954 | xp_events: {
6955 |     Row: {
6956 |         bonus_xp: number;
6957 |         created_at: string;
6958 |         description: string | null;
6959 |         ends_at: string | null;
6960 |         event_type: string;
6961 |         id: string;
6962 |         institution_id: string | null;
6963 |         is_active: boolean;
6964 |         name: string;
6965 |         starts_at: string | null;
6966 |         xp_multiplier: number;
6967 |     };
6968 |     Insert: {
6969 |         bonus_xp?: number;
6970 |         created_at?: string;
6971 |         description?: string | null;
6972 |         ends_at?: string | null;
6973 |         event_type: string;
6974 |         id?: string;
6975 |         institution_id?: string | null;
6976 |         is_active?: boolean;
6977 |         name: string;
6978 |         starts_at?: string | null;
6979 |         xp_multiplier?: number;

```

```

6980 | };
6981 | Update: {
6982 |   bonus_xp?: number;
6983 |   created_at?: string;
6984 |   description?: string | null;
6985 |   ends_at?: string | null;
6986 |   event_type?: string;
6987 |   id?: string;
6988 |   institution_id?: string | null;
6989 |   is_active?: boolean;
6990 |   name?: string;
6991 |   starts_at?: string | null;
6992 |   xp_multiplier?: number;
6993 | };
6994 | Relationships: [
6995 |   {
6996 |     foreignKeyName: "xp_events_institution_id_fkey";
6997 |     columns: ["institution_id"];
6998 |     isOneToOne: false;
6999 |     referencedRelation: "institutions";
7000 |     referencedColumns: ["id"];
7001 |   },
7002 |   {
7003 |     foreignKeyName: "xp_events_institution_id_fkey";
7004 |     columns: ["institution_id"];
7005 |     isOneToOne: false;
7006 |     referencedRelation: "institutions_public";
7007 |     referencedColumns: ["id"];
7008 |   }
7009 | ];
7010 | };
7011 | xp_purchases: {
7012 |   Row: {
7013 |     consumed_at: string | null;
7014 |     id: string;
7015 |     institution_id: string | null;
7016 |     item_id: string;
7017 |     metadata: Json | null;
7018 |     purchased_at: string;
7019 |     status: Database["public"]["Enums"]["xp_purchase_status"];
7020 |     student_id: string;
7021 |     xp_cost: number;
7022 |   };
7023 |   Insert: {
7024 |     consumed_at?: string | null;
7025 |     id?: string;
7026 |     institution_id?: string | null;
7027 |     item_id: string;
7028 |     metadata?: Json | null;
7029 |     purchased_at?: string;
7030 |     status?: Database["public"]["Enums"]["xp_purchase_status"];
7031 |     student_id: string;
7032 |     xp_cost: number;
7033 |   };
7034 |   Update: {
7035 |     consumed_at?: string | null;
7036 |     id?: string;
7037 |     institution_id?: string | null;
7038 |     item_id?: string;
7039 |     metadata?: Json | null;
7040 |     purchased_at?: string;
7041 |     status?: Database["public"]["Enums"]["xp_purchase_status"];
7042 |     student_id?: string;
7043 |     xp_cost?: number;
7044 |   };
7045 |   Relationships: [
7046 |     {
7047 |       foreignKeyName: "xp_purchases_institution_id_fkey";
7048 |       columns: ["institution_id"];
7049 |       isOneToOne: false;
7050 |       referencedRelation: "institutions";
7051 |       referencedColumns: ["id"];
7052 |     },
7053 |     {
7054 |       foreignKeyName: "xp_purchases_institution_id_fkey";
7055 |       columns: ["institution_id"];
7056 |       isOneToOne: false;
7057 |       referencedRelation: "institutions_public";
7058 |       referencedColumns: ["id"];
7059 |     },
7060 |     {
7061 |       foreignKeyName: "xp_purchases_item_id_fkey";
7062 |       columns: ["item_id"];
7063 |       isOneToOne: false;
7064 |       referencedRelation: "marketplace_items";
7065 |       referencedColumns: ["id"];
7066 |     },
7067 |     {
7068 |       foreignKeyName: "xp_purchases_student_id_fkey";
7069 |       columns: ["student_id"];
7070 |       isOneToOne: false;
7071 |       referencedRelation: "profiles";
7072 |       referencedColumns: ["id"];
7073 |     }
7074 |   ];
7075 | };
7076 | xp_transactions: {
7077 |   Row: {
7078 |     base_xp: number | null;
7079 |     created_at: string;
7080 |     final_xp: number | null;
7081 |     id: string;
7082 |     multipliers: Json | null;
7083 |     note: string | null;

```

```

7084 |         reference_id: string | null;
7085 |         scope: string;
7086 |         source: string;
7087 |         student_id: string;
7088 |         team_id: string | null;
7089 |         xp_amount: number;
7090 |     };
7091 |     Insert: {
7092 |         base_xp?: number | null;
7093 |         created_at?: string;
7094 |         final_xp?: number | null;
7095 |         id?: string;
7096 |         multipliers?: Json | null;
7097 |         note?: string | null;
7098 |         reference_id?: string | null;
7099 |         scope?: string;
7100 |         source: string;
7101 |         student_id: string;
7102 |         team_id?: string | null;
7103 |         xp_amount: number;
7104 |     };
7105 |     Update: {
7106 |         base_xp?: number | null;
7107 |         created_at?: string;
7108 |         final_xp?: number | null;
7109 |         id?: string;
7110 |         multipliers?: Json | null;
7111 |         note?: string | null;
7112 |         reference_id?: string | null;
7113 |         scope?: string;
7114 |         source?: string;
7115 |         student_id?: string;
7116 |         team_id?: string | null;
7117 |         xp_amount?: number;
7118 |     };
7119 |     Relationships: [
7120 |         {
7121 |             foreignKeyName: "xp_transactions_student_id_fkey";
7122 |             columns: ["student_id"];
7123 |             isOneToOne: false;
7124 |             referencedRelation: "profiles";
7125 |             referencedColumns: ["id"];
7126 |         },
7127 |         {
7128 |             foreignKeyName: "xp_transactions_team_id_fkey";
7129 |             columns: ["team_id"];
7130 |             isOneToOne: false;
7131 |             referencedRelation: "teams";
7132 |             referencedColumns: ["id"];
7133 |         }
7134 |     ];
7135 | };
7136 |
7137 | Views: {
7138 |     institutions_public: {
7139 |         Row: {
7140 |             id: string | null;
7141 |             join_mode: string | null;
7142 |             logo_url: string | null;
7143 |             name: string | null;
7144 |             slug: string | null;
7145 |         };
7146 |         Insert: {
7147 |             id?: string | null;
7148 |             join_mode?: string | null;
7149 |             logo_url?: string | null;
7150 |             name?: string | null;
7151 |             slug?: string | null;
7152 |         };
7153 |         Update: {
7154 |             id?: string | null;
7155 |             join_mode?: string | null;
7156 |             logo_url?: string | null;
7157 |             name?: string | null;
7158 |             slug?: string | null;
7159 |         };
7160 |         Relationships: [];
7161 |     };
7162 |     leaderboard_weekly: {
7163 |         Row: {
7164 |             rank: number | null;
7165 |             student_id: string | null;
7166 |             weekly_xp: number | null;
7167 |         };
7168 |         Relationships: [
7169 |             {
7170 |                 foreignKeyName: "xp_transactions_student_id_fkey";
7171 |                 columns: ["student_id"];
7172 |                 isOneToOne: false;
7173 |                 referencedRelation: "profiles";
7174 |                 referencedColumns: ["id"];
7175 |             }
7176 |         ];
7177 |     };
7178 |     mv_historical_evidence: {
7179 |         Row: {
7180 |             avg_score: number | null;
7181 |             blooms_level: Database["public"]["Enums"]["blooms_level"] | null;
7182 |             developing_count: number | null;
7183 |             evidence_count: number | null;
7184 |             excellent_count: number | null;
7185 |             not_yet_count: number | null;
7186 |             outcome_type: Database["public"]["Enums"]["outcome_type"] | null;
7187 |             satisfactory_count: number | null;

```

```

7188         semester_id: string | null;
7189         semester_name: string | null;
7190         start_date: string | null;
7191     };
7192     Relationships: [];
7193 };
7194 };
7195 Functions: {
7196     anonymize_user: { Args: { p_user_id: string }; Returns: Json };
7197     auth_institution_id: { Args: never; Returns: string };
7198     auth_user_role: { Args: never; Returns: string };
7199     badge_auto_archive: { Args: never; Returns: undefined };
7200     badge_spotlight_auto_rotate: { Args: never; Returns: undefined };
7201     calculate_level_from_xp: { Args: { p_xp: number }; Returns: number };
7202     check_rate_limit_approaching: {
7203         Args: {
7204             p_event_type?: string;
7205             p_ip_address: unknown;
7206             p_threshold?: number;
7207             p_window_minutes?: number;
7208         };
7209         Returns: boolean;
7210     };
7211     consume_invitation: { Args: { p_token: string }; Returns: boolean };
7212     course_material_institution: {
7213         Args: { p_object_name: string };
7214         Returns: string;
7215     };
7216     delete_department_if_no_programs: {
7217         Args: { dept_id: string };
7218         Returns: boolean;
7219     };
7220     emit_notification: {
7221         Args: {
7222             p_body?: string;
7223             p_dedup_key?: string;
7224             p_metadata?: Json;
7225             p_title: string;
7226             p_type: string;
7227             p_user_id: string;
7228         };
7229         Returns: undefined;
7230     };
7231     expire_stale_recovery_sessions: { Args: never; Returns: number };
7232     fan_out_announcement_notifications: {
7233         Args: { p_announcement_id: string };
7234         Returns: number;
7235     };
7236     get_badge_spotlight: {
7237         Args: { p_student_id: string; p_week_number: number };
7238         Returns: string;
7239     };
7240     get_earn_spend_ratio: {
7241         Args: { p_institution_id: string };
7242         Returns: {
7243             ratio: number;
7244             status: string;
7245             total_earned: number;
7246             total_spent: number;
7247         };
7248     };
7249     get_effective_price: {
7250         Args: { p_institution_id: string; p_item_id: string };
7251         Returns: number;
7252     };
7253     get_invitation_by_token: {
7254         Args: { p_token: string };
7255         Returns: {
7256             email: string;
7257             expires_at: string;
7258             id: string;
7259             institution_id: string;
7260             institution_name: string;
7261             role: Database["public"]["Enums"]["user_role"];
7262         };
7263     };
7264     get_leaderboard_page: {
7265         Args: { p_institution_id: string; p_limit: number; p_offset: number };
7266         Returns: {
7267             eligible_count: number;
7268             full_name: string;
7269             global_rank: number;
7270             level: number;
7271             streak_current: number;
7272             student_id: string;
7273             xp_total: number;
7274         };
7275     };
7276     get_student_dashboard: { Args: { p_student_id: string }; Returns: Json };
7277     get_wellness_aggregate_stats: {
7278         Args: { p_institution_id: string };
7279         Returns: {
7280             total_logs: number;
7281             unique_students: number;
7282             wellness_type: string;
7283         };
7284     };
7285     get_xp_balance: { Args: { p_student_id: string }; Returns: number };
7286     get_xp_transactions_page: {
7287         Args: {
7288             p_filter: string;
7289             p_limit: number;
7290             p_offset: number;
7291             p_student_id: string;

```

```

7292 |     };
7293 |     Returns: {
7294 |         amount: number;
7295 |         category: string;
7296 |         id: string;
7297 |         kind: string;
7298 |         label: string;
7299 |         occurred_at: string;
7300 |         total_count: number;
7301 |     }[];
7302 | };
7303 | health_check_ping: { Args: never; Returns: boolean };
7304 | increment_team_xp: {
7305 |     Args: { p_amount: number; p_team_id: string };
7306 |     Returns: undefined;
7307 | };
7308 | is_pgcron_available: { Args: never; Returns: boolean };
7309 | is_portfolio_publicly_accessible: {
7310 |     Args: { p_student_id: string };
7311 |     Returns: boolean;
7312 | };
7313 | parent_has_verified_link: {
7314 |     Args: { p_student_id: string };
7315 |     Returns: boolean;
7316 | };
7317 | portfolio_public_access: {
7318 |     Args: { p_student_id: string };
7319 |     Returns: string;
7320 | };
7321 | process_marketplace_purchase: {
7322 |     Args: {
7323 |         p_institution_id: string;
7324 |         p_item_id: string;
7325 |         p_student_id: string;
7326 |     };
7327 |     Returns: Json;
7328 | };
7329 | recalculate_dynamic_prices: {
7330 |     Args: { p_institution_id: string };
7331 |     Returns: undefined;
7332 | };
7333 | recalculate_league_tiers: {
7334 |     Args: { p_institution_id: string };
7335 |     Returns: undefined;
7336 | };
7337 | refresh_mv_historical_evidence: { Args: never; Returns: undefined };
7338 | rls_isolation_violations: {
7339 |     Args: never;
7340 |     Returns: {
7341 |         cmd: string;
7342 |         policy_name: string;
7343 |         reason: string;
7344 |         table_name: string;
7345 |     };
7346 | };
7347 | search_course_materials: {
7348 |     Args: {
7349 |         match_clo_ids?: string[];
7350 |         match_count?: number;
7351 |         match_course_ids: string[];
7352 |         match_threshold?: number;
7353 |         query_embedding: string;
7354 |     };
7355 |     Returns: {
7356 |         bloom_level: string;
7357 |         chunk_text: string;
7358 |         clo_ids: string[];
7359 |         id: string;
7360 |         material_type: string;
7361 |         similarity: number;
7362 |         source_filename: string;
7363 |     };
7364 | };
7365 | seed_marketplace_items: {
7366 |     Args: { p_institution_id: string };
7367 |     Returns: undefined;
7368 | };
7369 | send_teacher_nudge: {
7370 |     Args: { p_message: string; p_student_id: string };
7371 |     Returns: undefined;
7372 | };
7373 | };
7374 | Enums: {
7375 |     assignment_type: "assignment" | "quiz" | "project" | "exam";
7376 |     attainment_level: "excellent" | "satisfactory" | "developing" | "not_yet";
7377 |     attainment_scope: "student_course" | "course" | "program" | "institution";
7378 |     blooms_level:
7379 |         | "remembering"
7380 |         | "understanding"
7381 |         | "applying"
7382 |         | "analyzing"
7383 |         | "evaluating"
7384 |         | "creating";
7385 |     cosmetic_slot: "profile_theme" | "avatar_frame" | "display_title";
7386 |     flow_response_type: "in_the_zone" | "stuck" | "too_easy";
7387 |     goal_type_enum: "study_hours" | "sessions_completed" | "tasks_completed";
7388 |     marketplace_item_category: "cosmetic" | "educational_perk" | "power_up";
7389 |     marketplace_item_sub_category:
7390 |         | "profile_theme"
7391 |         | "avatar_frame"
7392 |         | "display_title"
7393 |         | "extra_quiz_attempt"
7394 |         | "deadline_extension"
7395 |         | "hint_token"

```

```

7396 |         | "xp_boost"
7397 |         | "streak_shield";
7398 | marketplace_stock_type: "unlimited" | "limited" | "one_per_student";
7399 | outcome_type: "ILO" | "PLO" | "CLO" | "SUB_CLO";
7400 | quality_category_type: "thoughtful" | "good_effort" | "needs_detail";
7401 | reflection_template_type: "free_form" | "simple" | "gibbs";
7402 | reflection_type_enum: "session_reflection" | "journal_entry";
7403 | review_status_type: "pending" | "completed" | "skipped";
7404 | session_status_type:
7405 |     | "planned"
7406 |     | "in_progress"
7407 |     | "completed"
7408 |     | "cancelled";
7409 | submission_status: "submitted" | "graded";
7410 | task_priority_type: "low" | "medium" | "high";
7411 | task_status_type: "pending" | "completed";
7412 | timer_mode_type: "pomodoro" | "custom";
7413 | user_role: "admin" | "coordinator" | "teacher" | "student" | "parent";
7414 | wellness_habit_type: "meditation" | "hydration" | "exercise" | "sleep";
7415 | xp_purchase_status: "active" | "consumed" | "expired" | "refunded";
7416 | };
7417 | CompositeTypes: {
7418 |     [_ in never]: never;
7419 | };
7420 | };
7421 | };
7422 |
7423 | type DatabaseWithoutInternals = Omit<Database, "__InternalSupabase">;
7424 |
7425 | type DefaultSchema = DatabaseWithoutInternals[Extract<
7426 |     keyof Database,
7427 |     "public"
7428 | >];
7429 |
7430 | export type Tables<
7431 |     DefaultSchemaTableNameOrOptions extends
7432 |         | keyof (DefaultSchema["Tables"] & DefaultSchema["Views"])
7433 |         | { schema: keyof DatabaseWithoutInternals },
7434 |     TableName extends DefaultSchemaTableNameOrOptions extends {
7435 |         schema: keyof DatabaseWithoutInternals;
7436 |     }
7437 |         ? keyof (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"] &
7438 |             DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])
7439 |         : never = never
7440 | > = DefaultSchemaTableNameOrOptions extends {
7441 |     schema: keyof DatabaseWithoutInternals;
7442 | }
7443 |     ? (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"] &
7444 |         DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])[TableName] extends {
7445 |         Row: infer R;
7446 |     }
7447 |         ? R
7448 |         : never
7449 |     : DefaultSchemaTableNameOrOptions extends keyof (DefaultSchema["Tables"] &
7450 |         DefaultSchema["Views"])
7451 |         ? (DefaultSchema["Tables"] &
7452 |             DefaultSchema["Views"])[DefaultSchemaTableNameOrOptions] extends {
7453 |             Row: infer R;
7454 |         }
7455 |         ? R
7456 |         : never
7457 |     : never;
7458 |
7459 | export type TablesInsert<
7460 |     DefaultSchemaTableNameOrOptions extends
7461 |         | keyof DefaultSchema["Tables"]
7462 |         | { schema: keyof DatabaseWithoutInternals },
7463 |     TableName extends DefaultSchemaTableNameOrOptions extends {
7464 |         schema: keyof DatabaseWithoutInternals;
7465 |     }
7466 |         ? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]
7467 |         : never = never
7468 | > = DefaultSchemaTableNameOrOptions extends {
7469 |     schema: keyof DatabaseWithoutInternals;
7470 | }
7471 |     ? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"][TableName] extends {
7472 |         Insert: infer I;
7473 |     }
7474 |         ? I
7475 |         : never
7476 |     : DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
7477 |         ? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
7478 |             Insert: infer I;
7479 |         }
7480 |         ? I
7481 |         : never
7482 |     : never;
7483 |
7484 | export type TablesUpdate<
7485 |     DefaultSchemaTableNameOrOptions extends
7486 |         | keyof DefaultSchema["Tables"]
7487 |         | { schema: keyof DatabaseWithoutInternals },
7488 |     TableName extends DefaultSchemaTableNameOrOptions extends {
7489 |         schema: keyof DatabaseWithoutInternals;
7490 |     }
7491 |         ? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]
7492 |         : never = never
7493 | > = DefaultSchemaTableNameOrOptions extends {
7494 |     schema: keyof DatabaseWithoutInternals;
7495 | }
7496 |     ? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"][TableName] extends {
7497 |         Update: infer U;
7498 |     }
7499 |         ? U

```

```

7500 | : never
7501 | : DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
7502 | ? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
7503 |   Update: infer U;
7504 | }
7505 | ? U
7506 | : never
7507 | : never;
7508 |
7509 | export type Enums<
7510 |   DefaultSchemaEnumNameOrOptions extends
7511 |     | keyof DefaultSchema["Enums"]
7512 |     | { schema: keyof DatabaseWithoutInternals },
7513 |   EnumName extends DefaultSchemaEnumNameOrOptions extends {
7514 |     schema: keyof DatabaseWithoutInternals;
7515 |   }
7516 |     ? keyof DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]["Enums"]
7517 |     : never = never
7518 | > = DefaultSchemaEnumNameOrOptions extends {
7519 |   schema: keyof DatabaseWithoutInternals;
7520 | }
7521 |   ? DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]["Enums"][EnumName]
7522 |   : DefaultSchemaEnumNameOrOptions extends keyof DefaultSchema["Enums"]
7523 |   ? DefaultSchema["Enums"][DefaultSchemaEnumNameOrOptions]
7524 |   : never;
7525 |
7526 | export type CompositeTypes<
7527 |   PublicCompositeTypeNameOrOptions extends
7528 |     | keyof DefaultSchema["CompositeTypes"]
7529 |     | { schema: keyof DatabaseWithoutInternals },
7530 |   CompositeTypeName extends PublicCompositeTypeNameOrOptions extends {
7531 |     schema: keyof DatabaseWithoutInternals;
7532 |   }
7533 |     ? keyof DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]["CompositeTypes"]
7534 |     : never = never
7535 | > = PublicCompositeTypeNameOrOptions extends {
7536 |   schema: keyof DatabaseWithoutInternals;
7537 | }
7538 |   ? DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]["CompositeTypes"][CompositeTypeName]
7539 |   : PublicCompositeTypeNameOrOptions extends keyof DefaultSchema["CompositeTypes"]
7540 |   ? DefaultSchema["CompositeTypes"][PublicCompositeTypeNameOrOptions]
7541 |   : never;
7542 |
7543 | export const Constants = {
7544 |   graphql_public: {
7545 |     Enums: {},
7546 |   },
7547 |   public: {
7548 |     Enums: {
7549 |       assignment_type: ["assignment", "quiz", "project", "exam"],
7550 |       attainment_level: ["excellent", "satisfactory", "developing", "not_yet"],
7551 |       attainment_scope: ["student_course", "course", "program", "institution"],
7552 |       blooms_level: [
7553 |         "remembering",
7554 |         "understanding",
7555 |         "applying",
7556 |         "analyzing",
7557 |         "evaluating",
7558 |         "creating",
7559 |       ],
7560 |       cosmetic_slot: ["profile_theme", "avatar_frame", "display_title"],
7561 |       flow_response_type: ["in_the_zone", "stuck", "too_easy"],
7562 |       goal_type_enum: ["study_hours", "sessions_completed", "tasks_completed"],
7563 |       marketplace_item_category: ["cosmetic", "educational_perk", "power_up"],
7564 |       marketplace_item_sub_category: [
7565 |         "profile_theme",
7566 |         "avatar_frame",
7567 |         "display_title",
7568 |         "extra_quiz_attempt",
7569 |         "deadline_extension",
7570 |         "hint_token",
7571 |         "xp_boost",
7572 |         "streak_shield",
7573 |       ],
7574 |       marketplace_stock_type: ["unlimited", "limited", "one_per_student"],
7575 |       outcome_type: ["ILO", "PLO", "CLO", "SUB_CLO"],
7576 |       quality_category_type: ["thoughtful", "good_effort", "needs_detail"],
7577 |       reflection_template_type: ["free_form", "simple", "gibbs"],
7578 |       reflection_type_enum: ["session_reflection", "journal_entry"],
7579 |       review_status_type: ["pending", "completed", "skipped"],
7580 |       session_status_type: ["planned", "in_progress", "completed", "cancelled"],
7581 |       submission_status: ["submitted", "graded"],
7582 |       task_priority_type: ["low", "medium", "high"],
7583 |       task_status_type: ["pending", "completed"],
7584 |       timer_mode_type: ["pomodoro", "custom"],
7585 |       user_role: ["admin", "coordinator", "teacher", "student", "parent"],
7586 |       wellness_habit_type: ["meditation", "hydration", "exercise", "sleep"],
7587 |       xp_purchase_status: ["active", "consumed", "expired", "refunded"],
7588 |     },
7589 |   },
7590 | } as const;
7591 |

```

FILE: src/types/habits.ts

TYPE: .ts | LINES: 1-144 | SHA256: ebc20ac6f1f77ceb2ca1c7a295dbdf273f7370215fdd6874e5c802735340c58a

```

1 | export type WellnessHabitType =
2 |   | "meditation"
3 |   | "hydration"
4 |   | "exercise"
5 |   | "sleep";
6 | export type AcademicHabitType = "login" | "submit" | "journal" | "read";
7 | export type HabitType = AcademicHabitType | WellnessHabitType;
8 |

```



```

9 | export interface HeatmapDay {
10 |   date: string; // YYYY-MM-DD
11 |   academicCount: number;
12 |   wellnessCount: number;
13 |   totalCount: number;
14 |   habits: CompletedHabit[];
15 | }
16 |
17 | export interface CompletedHabit {
18 |   type: HabitType;
19 |   category: "academic" | "wellness";
20 |   value?: number;
21 |   completedAt: string;
22 | }
23 |
24 | export interface WellnessHabitLog {
25 |   id: string;
26 |   studentId: string;
27 |   date: string;
28 |   wellnessType: WellnessHabitType;
29 |   value: number | null;
30 |   completedAt: string;
31 | }
32 |
33 | export interface WellnessPreferences {
34 |   id: string;
35 |   studentId: string;
36 |   enabledHabits: WellnessHabitType[];
37 |   parentVisibility: boolean;
38 |   habitTargets: Record<string, { value: number; unit: string }>;
39 |   reminderTimes: Record<string, string>;
40 |   dismissedOnboardingTips: string[];
41 | }
42 |
43 | export interface HeatmapSummary {
44 |   currentStreak: number;
45 |   longestStreak: number;
46 |   totalActiveDays: number;
47 | }
48 |
49 | export interface CompletionRateData {
50 |   period: string;
51 |   rate: number;
52 | }
53 |
54 | export interface DayOfWeekData {
55 |   day: string;
56 |   avgCompletions: number;
57 | }
58 |
59 | export interface CorrelationInsight {
60 |   id: string;
61 |   habitType: HabitType;
62 |   academicMetric: string;
63 |   description: string;
64 |   strength: number;
65 | }
66 |
67 | export interface HabitReportRow {
68 |   date: string;
69 |   login: boolean;
70 |   submit: boolean;
71 |   journal: boolean;
72 |   read: boolean;
73 |   meditation?: boolean;
74 |   hydration?: boolean;
75 |   exercise?: boolean;
76 |   sleep?: boolean;
77 |   totalHabits: number;
78 |   xpEarned: number;
79 |   streakActive: boolean;
80 | }
81 |
82 | export interface DateRange {
83 |   start: string;
84 |   end: string;
85 | }
86 |
87 | // Level Integration Types
88 | export interface LevelProgressionPoint {
89 |   date: string;
90 |   level: 1 | 2 | 3 | 4;
91 | }
92 |
93 | export interface StudentHabitLevel {
94 |   currentLevel: 1 | 2 | 3 | 4;
95 |   levelHistory: LevelProgressionPoint[];
96 |   maxHabitsPerDay: number;
97 | }
98 |
99 | // Streak Recovery Types
100 | export interface ComebackChallengeStatus {
101 |   active: boolean;
102 |   currentDay: number;
103 |   totalDays: 3;
104 |   startDate: string | null;
105 | }
106 |
107 | export interface StreakMilestone {
108 |   days: 30 | 60 | 100;
109 |   achievedDate: string;
110 | }
111 |
112 | // Wellness Scaffolding Types

```

FILE: src/types/pagination.ts

```
1 // % % % Shared pagination types for list hooks % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
2 |  
3 export interface PaginationParams {  
4     page?: number;  
5     pageSize?: number;  
6 }  
7 |  
8 export interface PaginatedResult<T> {  
9     data: T[];  
10    count: number;  
11    page: number;  
12    pageSize: number;  
13 }  
14 |  
15 export const DEFAULT_PAGE = 1;  
16 export const DEFAULT_PAGE_SIZE = 25;  
17 |  
18 export function getPaginationRange(page?: number, pageSize?: number) {  
19     const p = page ?? DEFAULT_PAGE;  
20     const ps = pageSize ?? DEFAULT_PAGE_SIZE;  
21     const from = (p - 1) * ps;  
22     const to = from + ps - 1;  
23     return { page: p, pageSize: ps, from, to };  
24 }  
25
```

FILE: src/types/planner.ts

```

1 // =====
2 // Weekly Planner & Today View – Type Definitions
3 // =====
4
5 // -----
6 // Enums / Literal Unions
7 // -----
8
9 export type TimerMode = "pomodoro" | "custom";
10 export type SessionStatus =
11     | "planned"
12     | "in_progress"
13     | "completed"
14     | "cancelled";
15 export type TaskPriority = "low" | "medium" | "high";
16 export type TaskStatus = "todo" | "in_progress" | "done" | "deferred";
17 export type GoalType = "study_hours" | "sessions_completed" | "tasks_completed";
18 export type TimerState =
19     | "idle"
20     | "running"
21     | "paused"
22     | "break"
23     | "long_break"
24     | "completed";
25 export type PomodoroIntervalType = "work" | "break" | "long_break";
26 export type TimeOfDay = "morning" | "afternoon" | "evening";
27
28 // -----
29 // Core Domain Interfaces
30 // -----
31
32 export interface StudySession {
33     id: string;
34     studentId: string;
35     courseId: string | null;
36     courseName?: string;
37     title: string;
38     description: string | null;
39     plannedDate: string; // YYYY-MM-DD

```

```

40 |   plannedStartTime: string | null; // HH:MM
41 |   plannedDurationMinutes: number;
42 |   actualStartAt: string | null;
43 |   actualEndAt: string | null;
44 |   actualDurationMinutes: number | null;
45 |   timerMode: TimerMode;
46 |   status: SessionStatus;
47 |   satisfactionRating: number | null;
48 |   cloids: string[] | null;
49 |   createdAt: string;
50 | }
51 |
52 | export interface PlannerTask {
53 |   id: string;
54 |   studentId: string;
55 |   title: string;
56 |   description: string | null;
57 |   dueDate: string;
58 |   priority: TaskPriority;
59 |   status: TaskStatus;
60 |   courseId: string | null;
61 |   courseName?: string;
62 |   completedAt: string | null;
63 |   createdAt: string;
64 | }
65 |
66 | export interface WeeklyGoal {
67 |   id: string;
68 |   studentId: string;
69 |   weekStartDate: string;
70 |   goalType: GoalType;
71 |   targetValue: number;
72 | }
73 |
74 | export interface GoalProgress {
75 |   goal: WeeklyGoal;
76 |   currentValue: number;
77 |   percentage: number;
78 |   isMet: boolean;
79 | }
80 |
81 | export interface SessionEvidence {
82 |   id: string;
83 |   sessionId: string;
84 |   studentId: string;
85 |   fileUrl: string;
86 |   fileName: string;
87 |   fileSizeBytes: number;
88 |   mimeType: string;
89 |   notes: string | null;
90 |   createdAt: string;
91 | }
92 |
93 | export interface SessionReflection {
94 |   id: string;
95 |   sessionId: string;
96 |   studentId: string;
97 |   content: string;
98 |   wordCount: number;
99 |   createdAt: string;
100 | }
101 |
102 | // -----
103 | // Planner View Interfaces
104 | // -----
105 |
106 | /**
107 |  * A derived, non-persisted study-session suggestion surfaced on otherwise-empty
108 |  * planner days (R19.2). Carries only structured data – the consumer is
109 |  * responsible for any user-facing, localized labels.
110 |  */
111 | export interface SuggestedStudySession {
112 |   /** Deterministic synthetic id, e.g. 'suggestion-2025-06-18'. */
113 |   id: string;
114 |   /** Day the suggestion belongs to (YYYY-MM-DD). */
115 |   date: string;
116 |   /** Course the suggested session is scoped to, or null when none is known. */
117 |   courseId: string | null;
118 |   courseName: string | null;
119 |   /** Suggested focus-block length in minutes. */
120 |   durationMinutes: number;
121 | }
122 |
123 | export interface WeekDay {
124 |   date: string;
125 |   sessions: StudySession[];
126 |   tasks: PlannerTask[];
127 |   deadlines: UpcomingDeadline[];
128 |   isToday: boolean;
129 |   /** Derived suggestions shown only when the day has no real items (R19.2). */
130 |   suggestions?: SuggestedStudySession[];
131 | }
132 |
133 | export interface TimelineItem {
134 |   id: string;
135 |   type: "session" | "task" | "deadline" | "habit";
136 |   time: string | null; // HH:MM or null for unscheduled
137 |   timeOfDay: TimeOfDay | null;
138 |   data: StudySession | PlannerTask | UpcomingDeadline | HabitStatus;
139 | }
140 |
141 | export interface DailyProgress {
142 |   studyMinutes: number;
143 |   tasksCompleted: number;

```

```

144 | sessionsCompleted: number;
145 | }
146 |
147 | export interface WeeklyProgressData {
148 |   totalStudyMinutes: number;
149 |   sessionsCompleted: number;
150 |   tasksCompleted: number;
151 |   courseBreakdown: CourseStudyTime[];
152 |   cloBreakdown: CLOStudyTime[];
153 | }
154 |
155 | export interface CourseStudyTime {
156 |   courseId: string;
157 |   courseName: string;
158 |   totalMinutes: number;
159 | }
160 |
161 | export interface CLOStudyTime {
162 |   cloId: string;
163 |   cloTitle: string;
164 |   courseName: string;
165 |   totalMinutes: number;
166 | }
167 |
168 | export interface WeeklyStudyData {
169 |   weekStartDate: string;
170 |   totalMinutes: number;
171 | }
172 |
173 | // -----
174 | // Timer Persistence
175 | // -----
176 |
177 | export interface TimerPersistState {
178 |   sessionId: string;
179 |   mode: TimerMode;
180 |   startedAt: number; // Date.now() timestamp
181 |   totalElapsedMs: number;
182 |   pausedAt: number | null;
183 |   totalPausedMs: number;
184 |   pomodoroInterval: number;
185 |   pomodoroIntervalType: PomodoroIntervalType;
186 |   targetDurationMs: number;
187 | }
188 |
189 | // -----
190 | // Today View
191 | // -----
192 |
193 | export interface UpcomingDeadline {
194 |   id: string;
195 |   title: string;
196 |   courseName: string;
197 |   dueDate: string;
198 |   urgency: "red" | "yellow" | "green";
199 | }
200 |
201 | export interface HabitStatus {
202 |   login: boolean;
203 |   submit: boolean;
204 |   journal: boolean;
205 |   read: boolean;
206 | }
207 |
208 | // -----
209 | // Reflection Types
210 | // -----
211 |
212 | export interface SimpleReflectionValues {
213 |   whatWentWell: string;
214 |   whatWasChallenging: string;
215 |   whatWillChange: string;
216 | }
217 |
218 | export interface GibbsReflectionValues {
219 |   description: string;
220 |   feelings: string;
221 |   evaluation: string;
222 |   analysis: string;
223 |   conclusion: string;
224 |   actionPlan: string;
225 | }
226 |
227 | // -----
228 | // Flow Check-In
229 | // -----
230 |
231 | export type FlowResponse = "in_the_zone" | "stuck" | "too_easy";
232 |
233 | // -----
234 | // Quality Category
235 | // -----
236 |
237 | export type QualityCategory = "thoughtful" | "good_effort" | "needs_detail";
238 |
239 | // -----
240 | // Reflection Digest
241 | // -----
242 |
243 | export interface ReflectionDigest {
244 |   id: string;
245 |   studentId: string;
246 |   month: string; // YYYY-MM
247 |   themes: Array<{ topic: string; count: number }>;

```

```

248 | growthPatterns: Array<{ area: string; description: string }>;
249 | emotionalTrends: Array<{ label: string }>;
250 | suggestedFocus: Array<{ area: string; reason: string }>;
251 | sharedWith: Array<{
252 |     role: "parent" | "advisor" | "teacher";
253 |     sharedAt: string;
254 | }>;
255 | createdAt: string;
256 | }
257 |
258 | // -----
259 | // Session Intent
260 | // -----
261 |
262 | export interface SuggestedIntent {
263 |     concept: string;
264 |     successCriterion: string;
265 | }
266 |
267 | export interface SessionIntent {
268 |     id: string;
269 |     sessionId: string;
270 |     studentId: string;
271 |     concept: string;
272 |     successCriterion: string;
273 |     isAutoSuggested: boolean;
274 |     createdAt: string;
275 | }
276 |
277 | // -----
278 | // Flow Check-In Record
279 | // -----
280 |
281 | export interface FlowCheckIn {
282 |     id: string;
283 |     sessionId: string;
284 |     studentId: string;
285 |     intervalNumber: number;
286 |     response: FlowResponse;
287 |     createdAt: string;
288 | }
289 |
290 | // -----
291 | // Spaced Repetition / Review Schedule
292 | // -----
293 |
294 | export type ReviewStatus = "pending" | "completed" | "skipped";
295 |
296 | export interface ReviewSchedule {
297 |     id: string;
298 |     studentId: string;
299 |     cloId: string;
300 |     courseId: string | null;
301 |     sourceSessionId: string | null;
302 |     reviewDate: string; // YYYY-MM-DD
303 |     intervalDays: 1 | 3 | 7;
304 |     status: ReviewStatus;
305 |     reviewSessionId: string | null;
306 |     createdAt: string;
307 |     updatedAt: string;
308 | }
309 |
310 | // -----
311 | // Reflection Templates / Quality
312 | // -----
313 |
314 | export type ReflectionTypeEnum = "session_reflection" | "journal_entry";
315 | export type ReflectionTemplateType = "free_form" | "simple" | "gibbs";
316 |
317 | export interface DigestTheme {
318 |     topic: string;
319 |     count: number;
320 | }
321 |
322 | export interface DigestPattern {
323 |     area: string;
324 |     description: string;
325 | }
326 |
327 | export interface DigestTrend {
328 |     label: string;
329 | }
330 |
331 | export interface DigestFocus {
332 |     area: string;
333 |     reason: string;
334 | }
335 |
336 | export interface DigestShareEntry {
337 |     role: "parent" | "advisor" | "teacher";
338 |     sharedAt: string;
339 | }
340 |
341 | export interface ReflectionQualityScore {
342 |     id: string;
343 |     reflectionId: string;
344 |     reflectionType: ReflectionTypeEnum;
345 |     studentId: string;
346 |     score: number; // 0-100
347 |     originalityScore: number;
348 |     relevanceScore: number;
349 |     depthScore: number;
350 |     flags: string[];
351 |     scoredAt: string;

```

```
352 | }
353 |
```

FILE: src/vite-env.d.ts

TYPE: .ts | LINES: 1-18 | SHA256: 3c59ab61f9d7f04442eac563565423f4336f85bdb74c1e95447027cac83dc3a5

```
1 | /// <reference types="vite/client" />
2 |
3 | interface ImportMetaEnv {
4 |   readonly VITE_SUPABASE_URL: string;
5 |   readonly VITE_SUPABASE_ANON_KEY: string;
6 |   readonly VITE_SENTRY_DSN?: string;
7 |   /**
8 |    * Optional demo account password. When non-empty, the login page renders
9 |    * the Quick Demo Access panel. Production builds leave this unset so the
10 |    * literal never ships in the browser bundle.
11 |    */
12 |   readonly VITE_DEMO_PASSWORD?: string;
13 | }
14 |
15 | interface ImportMeta {
16 |   readonly env: ImportMetaEnv;
17 | }
18 |
```

FILE: supabase/.temp/linked-project.json

TYPE: .json | LINES: 1-1 | SHA256: 05defb65f2ec151a1cb6e2112c310c1409c611a20afc0c84955abf98c216e21e

```
1 | { "ref": "cdlgtbvxlxjpcddjazzx", "name": "Edeviser-Kiro", "organization_id": "pgsydzpcshnwwrcnxatb", "organization_sl
```

FILE: supabase/functions/_shared/auth.ts

TYPE: .ts | LINES: 1-111 | SHA256: 85ff8ac5bd9b09ba3694d74cbdbdf13fa006b53204733a7029ec4b0915586b2d

```
1 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
2 |
3 | const corsHeaders = {
4 |   "Access-Control-Allow-Origin": "",
5 |   "Access-Control-Allow-Headers":
6 |     "authorization, x-client-info, apikey, content-type",
7 | };
8 |
9 | interface AuthResult {
10 |   user: { id: string; role: string; institution_id: string } | null;
11 |   error: string | null;
12 | }
13 |
14 | /**
15 |  * Validates JWT from the Authorization header and returns user info.
16 |  * Used by edge functions that require authenticated callers.
17 |  */
18 | export async function authenticateRequest(req: Request): Promise<AuthResult> {
19 |   const authHeader = req.headers.get("Authorization");
20 |   if (!authHeader) {
21 |     return { user: null, error: "Missing authorization header" };
22 |   }
23 |
24 |   const supabase = createClient(
25 |     Deno.env.get("SUPABASE_URL")!,
26 |     Deno.env.get("SUPABASE_ANON_KEY")!,
27 |     { global: { headers: { Authorization: authHeader } } }
28 |   );
29 |
30 |   const {
31 |     data: { user },
32 |     error: authError,
33 |   } = await supabase.auth.getUser();
34 |   if (authError || !user) {
35 |     return { user: null, error: "Unauthorized" };
36 |   }
37 |
38 |   // Role + institution live in the profiles table, NOT the JWT (app_metadata is
39 |   // empty on this project). Resolve them server-side from profiles by the
40 |   // caller's id, mirroring the already-deployed ai-feedback-draft pattern. The
41 |   // JWT-metadata values are retained as a fallback so any future token that DOES
42 |   // carry the role/institution still works (preservation).
43 |   const adminClient = createClient(
44 |     Deno.env.get("SUPABASE_URL")!,
45 |     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
46 |   );
47 |   const { data: callerProfile } = await adminClient
48 |     .from("profiles")
49 |     .select("role, institution_id")
50 |     .eq("id", user.id)
51 |     .maybeSingle();
52 |
53 |   const role =
54 |     (callerProfile?.role as string) ??
55 |     user.app_metadata?.role ??
56 |     user.user_metadata?.role ??
57 |     "";
58 |   const institutionId =
59 |     (callerProfile?.institution_id as string) ??
60 |     user.app_metadata?.institution_id ??
61 |     user.user_metadata?.institution_id ??
62 |     "";
63 |
64 |   return {
65 |     user: { id: user.id, role, institution_id: institutionId },
66 |     error: null,
67 |   };
68 | }
69 |
70 | /**
```

```

71  * Validates a cron secret header for cron-only functions.
72  * Falls back to JWT auth if the cron secret is not present.
73  */
74  export function authenticateCronRequest(req: Request): {
75    authorized: boolean;
76    error: string | null;
77  } {
78    const cronSecret = req.headers.get("x-cron-secret");
79    const expectedSecret = Deno.env.get("CRON_SECRET");
80
81    if (expectedSecret && cronSecret === expectedSecret) {
82      return { authorized: true, error: null };
83    }
84
85    // Also accept service role key in Authorization header (for internal calls)
86    const authHeader = req.headers.get("Authorization") ?? "";
87    const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY") ?? "";
88    if (serviceRoleKey && authHeader.replace("Bearer ", "") === serviceRoleKey) {
89      return { authorized: true, error: null };
90    }
91
92    return {
93      authorized: false,
94      error: "Unauthorized: missing or invalid cron secret",
95    };
96  }
97
98  export function unauthorizedResponse(message: string): Response {
99    return new Response(JSON.stringify({ error: message }), {
100      status: 401,
101      headers: { ...corsHeaders, "Content-Type": "application/json" },
102    });
103  }
104
105  export function forbiddenResponse(message: string): Response {
106    return new Response(JSON.stringify({ error: message }), {
107      status: 403,
108      headers: { ...corsHeaders, "Content-Type": "application/json" },
109    });
110  }
111

```

FILE: supabase/functions/ai-at-risk-prediction/index.ts

TYPE: .ts | LINES: 1-502 | SHA256: 37c1e7c7452c439a5663c4a3f1bba5096b94c44b1f72383863c5350f6890be97

[illegible]

```

60 | if (daysSinceLastLogin <= 1) return 10;
61 | if (daysSinceLastLogin <= 3) return 30;
62 | if (daysSinceLastLogin <= 7) return 60;
63 | if (daysSinceLastLogin <= 14) return 80;
64 | return 100;
65 | }
66 |
67 | /**
68 |  * Classify login frequency for contributing signals display.
69 |  */
70 | export function classifyLoginFrequency(
71 |   daysSinceLastLogin: number
72 | ): "low" | "medium" | "high" {
73 |   if (daysSinceLastLogin <= 3) return "high";
74 |   if (daysSinceLastLogin <= 7) return "medium";
75 |   return "low";
76 | }
77 |
78 | /**
79 |  * Score attainment trend signal (0-100).
80 |  * Higher score = higher risk.
81 |  */
82 | export function scoreAttainmentTrend(
83 |   trend: "improving" | "declining" | "stagnant"
84 | ): number {
85 |   switch (trend) {
86 |     case "improving":
87 |       return 10;
88 |     case "stagnant":
89 |       return 50;
90 |     case "declining":
91 |       return 90;
92 |   }
93 | }
94 |
95 | /**
96 |  * Score submission pattern signal (0-100).
97 |  * Higher score = higher risk.
98 |  */
99 | export function scoreSubmissionPattern(
100 |   pattern: "early" | "on_time" | "late" | "missed"
101 | ): number {
102 |   switch (pattern) {
103 |     case "early":
104 |       return 5;
105 |     case "on_time":
106 |       return 20;
107 |     case "late":
108 |       return 65;
109 |     case "missed":
110 |       return 95;
111 |   }
112 | }
113 |
114 | /**
115 |  * Calculate overall risk probability (0-100%) from weighted signal scores.
116 |  * Applies a CLO attainment modifier: if current attainment is already low,
117 |  * the risk is amplified.
118 |  */
119 | export function calculateRiskProbability(
120 |   loginScore: number,
121 |   trendScore: number,
122 |   patternScore: number,
123 |   currentAttainment: number | null
124 | ): number {
125 |   const baseScore =
126 |     loginScore * WEIGHT_LOGIN_FREQUENCY +
127 |     trendScore * WEIGHT_ATTAINMENT_TREND +
128 |     patternScore * WEIGHT_SUBMISSION_PATTERN;
129 |
130 |   // Apply attainment modifier: low attainment amplifies risk
131 |   let attainmentModifier = 1.0;
132 |   if (currentAttainment !== null) {
133 |     if (currentAttainment < 50) {
134 |       attainmentModifier = 1.3;
135 |     } else if (currentAttainment < 70) {
136 |       attainmentModifier = 1.15;
137 |     } else {
138 |       // Already meeting target – reduce risk
139 |       attainmentModifier = 0.7;
140 |     }
141 |   }
142 |
143 |   const finalScore = Math.round(
144 |     Math.min(100, Math.max(0, baseScore * attainmentModifier))
145 |   );
146 |   return finalScore;
147 | }
148 |
149 | /**
150 |  * Build prediction suggestion text for the ai_feedback record.
151 |  */
152 | export function buildPredictionText(
153 |   studentName: string,
154 |   cloTitle: string,
155 |   probability: number,
156 |   loginFreq: "low" | "medium" | "high",
157 |   trend: "improving" | "declining" | "stagnant",
158 |   pattern: "early" | "on_time" | "late" | "missed"
159 | ): string {
160 |   const signals: string[] = [];
161 |   if (loginFreq === "low") signals.push("low login frequency");
162 |   if (trend === "declining") signals.push("declining attainment trend");
163 |   if (trend === "stagnant") signals.push("stagnant attainment trend");

```


[illegible]

```

268 | }
269 |
270 | if (!upcomingAssignments || upcomingAssignments.length === 0) {
271 |     return new Response(
272 |         JSON.stringify({
273 |             success: true,
274 |             predictions_made: 0,
275 |             message: "No upcoming assignments in prediction window",
276 |         }),
277 |         { headers: { ...corsHeaders, "Content-Type": "application/json" } }
278 |     );
279 | }
280 |
281 | // Build a map of course_id !' CLO IDs from upcoming assignments
282 | const courseCloMap = new Map<string, Set<string>>();
283 | for (const assignment of upcomingAssignments) {
284 |     if (!assignment.clo_ids || assignment.clo_ids.length === 0) continue;
285 |     const existing =
286 |         courseCloMap.get(assignment.course_id) ?? new Set<string>();
287 |     for (const cloId of assignment.clo_ids) {
288 |         existing.add(cloId);
289 |     }
290 |     courseCloMap.set(assignment.course_id, existing);
291 | }
292 |
293 | // %% Step 3: Fetch CLO details for all relevant CLOs % % % % % % % % % % % %
294 |
295 | const allCloIds = [
296 |     ...new Set([...courseCloMap.values()].flatMap((s) => [...s])),
297 | ];
298 |
299 | if (allCloIds.length === 0) {
300 |     return new Response(
301 |         JSON.stringify({
302 |             success: true,
303 |             predictions_made: 0,
304 |             message: "No CLOs linked to upcoming assignments",
305 |         }),
306 |         { headers: { ...corsHeaders, "Content-Type": "application/json" } }
307 |     );
308 | }
309 |
310 | const { data: cloDetails } = await supabase
311 |     .from("learning_outcomes")
312 |     .select("id, title")
313 |     .in("id", allCloIds)
314 |     .eq("type", "CLO");
315 |
316 | const cloTitleMap = new Map<string, string>();
317 | for (const clo of cloDetails ?? []) {
318 |     cloTitleMap.set(clo.id, clo.title);
319 | }
320 |
321 | // %% Step 4: Fetch student names % % % % % % % % % % % % % % % % % % % % % %
322 |
323 | const studentIds = students.map((s: StudentWithSignals) => s.student_id);
324 |
325 | const { data: profiles } = await supabase
326 |     .from("profiles")
327 |     .select("id, full_name")
328 |     .in("id", studentIds);
329 |
330 | const nameMap = new Map<string, string>();
331 | for (const p of profiles ?? []) {
332 |     nameMap.set(p.id, p.full_name ?? "Unknown Student");
333 | }
334 |
335 | // %% Step 5: Fetch enrollments to know which students are in which courses
336 |
337 | const courseIds = [...courseCloMap.keys()];
338 |
339 | const { data: enrollments } = await supabase
340 |     .from("student_courses")
341 |     .select("student_id, course_id")
342 |     .in("student_id", studentIds)
343 |     .in("course_id", courseIds)
344 |     .eq("status", "active");
345 |
346 | // Build student !' courses map
347 | const studentCourseMap = new Map<string, string[]>();
348 | for (const e of enrollments ?? []) {
349 |     const courses = studentCourseMap.get(e.student_id) ?? [];
350 |     courses.push(e.course_id);
351 |     studentCourseMap.set(e.student_id, courses);
352 | }
353 |
354 | // %% Step 6: Fetch current CLO attainment for all students % % % % % % % % % %
355 |
356 | const { data: attainmentRecords } = await supabase
357 |     .from("outcome_attainment")
358 |     .select("student_id, outcome_id, attainment_percent")
359 |     .in("student_id", studentIds)
360 |     .in("outcome_id", allCloIds)
361 |     .eq("scope", "student_course");
362 |
363 | // Build student+clo !' attainment map
364 | const attainmentMap = new Map<string, number>();
365 | for (const a of attainmentRecords ?? []) {
366 |     attainmentMap.set(
367 |         `${a.student_id}:${a.outcome_id}`,
368 |         a.attainment_percent
369 |     );
370 | }
371 |

```

[illegible]

[illegible]

FILE: supabase/functions/ai-feedback-draft/index.ts

```
TYPE: .ts | LINES: 1-519 | SHA256: 416edea25c052a1b90fb5bc4ffcf5d475486beea231b3eadebaf91cd1134e3b
```

[illegible]

```

74 | * Returns 'top', 'upper', 'mid', or 'low' based on where the selected
75 | * level falls relative to the total number of levels.
76 | */
77 | export function getPerformanceTier(
78 |   levelIndex: number,
79 |   totalLevels: number
80 | ): "top" | "upper" | "mid" | "low" {
81 |   if (totalLevels <= 1) return "top";
82 |   const ratio = levelIndex / (totalLevels - 1);
83 |   if (ratio >= 0.9) return "top";
84 |   if (ratio >= 0.6) return "upper";
85 |   if (ratio >= 0.3) return "mid";
86 |   return "low";
87 | }
88 |
89 | /**
90 |  * Build a draft feedback comment for a single rubric criterion based on:
91 |  * - The criterion name and selected performance level description
92 |  * - The performance tier (top/upper/mid/low)
93 |  * - CLO context (title and Bloom's level)
94 |  * - Historical feedback patterns (recurring themes from past grades)
95 |  */
96 | export function buildCriterionDraft(
97 |   criterionName: string,
98 |   selectedLevel: CriterionLevel,
99 |   levelIndex: number,
100 |   totalLevels: number,
101 |   cloContext: CLOContext | null,
102 |   historicalThemes: string[]
103 | ): string {
104 |   const tier = getPerformanceTier(levelIndex, totalLevels);
105 |   const parts: string[] = [];
106 |
107 |   // Opening based on performance tier
108 |   switch (tier) {
109 |     case "top":
110 |       parts.push(
111 |         `Excellent work on ${criterionName}. Your response demonstrates strong mastery at the "${selectedLevel}`
112 |       );
113 |       break;
114 |     case "upper":
115 |       parts.push(
116 |         `Good effort on ${criterionName}. You've reached the "${selectedLevel.label}" level, showing solid und
117 |       );
118 |       break;
119 |     case "mid":
120 |       parts.push(
121 |         `Adequate work on ${criterionName}. At the "${selectedLevel.label}" level, there is room for growth.`
122 |       );
123 |       break;
124 |     case "low":
125 |       parts.push(
126 |         `${criterionName} needs improvement. At the "${selectedLevel.label}" level, significant development is
127 |       );
128 |       break;
129 |   }
130 |
131 |   // Add level description context
132 |   if (selectedLevel.description) {
133 |     parts.push(`Specifically: ${selectedLevel.description}`);
134 |   }
135 |
136 |   // Add CLO-aligned guidance
137 |   if (cloContext) {
138 |     const bloomsKey = cloContext.blooms_level?.toLowerCase() ?? "";
139 |     const actionPhrase = BLOOMS_ACTION_PHRASES[bloomsKey];
140 |     if (actionPhrase && (tier === "mid" || tier === "low")) {
141 |       parts.push(
142 |         `To improve, focus on ${actionPhrase} as required by the "${cloContext.title}" learning outcome.`
143 |       );
144 |     } else if (actionPhrase && (tier === "top" || tier === "upper")) {
145 |       parts.push(
146 |         `This aligns well with the "${cloContext.title}" outcome's focus on ${actionPhrase}.`
147 |       );
148 |     }
149 |   }
150 |
151 |   // Add historical pattern note if available
152 |   if (historicalThemes.length > 0) {
153 |     const theme = historicalThemes[0];
154 |     if (tier === "mid" || tier === "low") {
155 |       parts.push(
156 |         `Note: Previous feedback has highlighted similar areas – "${theme}". Consider reviewing past guidance.
157 |       );
158 |     }
159 |   }
160 |
161 |   return parts.join(" ");
162 | }
163 |
164 | /**
165 |  * Build an overall draft feedback summarizing strengths and areas for improvement
166 |  * across all rubric criteria.
167 |  */
168 | export function buildOverallDraft(
169 |   criterionResults: Array<{
170 |     criterionName: string;
171 |     tier: "top" | "upper" | "mid" | "low";
172 |     levelLabel: string;
173 |   }>,
174 |   cloContext: CLOContext | null
175 | ): string {
176 |   const strengths = criterionResults.filter(
177 |     (c) => c.tier === "top" || c.tier === "upper"

```

[illegible]

[illegible]

[illegible]


```

490 |         criterionResults.push({
491 |             criterionName: criterion.criterion_name,
492 |             tier,
493 |             levelLabel: selectedLevel.label,
494 |         });
495 |     }
496 |
497 |     // %% Step 5: Generate overall draft feedback %%%%%%%%%%%
498 |
499 |     const overallDraft = buildOverallDraft(criterionResults, cloContext);
500 |
501 |     // %% Step 6: Return structured response %%%%%%%%%%%
502 |
503 |     const response: FeedbackDraftResponse = {
504 |         criterion_drafts: criterionDrafts,
505 |         overall_draft: overallDraft,
506 |     };
507 |
508 |     return new Response(JSON.stringify({ success: true, ...response }), {
509 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
510 |     });
511 | } catch (error) {
512 |     console.error("ai-feedback-draft error:", (error as Error).message);
513 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
514 |         status: 500,
515 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
516 |     });
517 | }
518 | });
519 |

```

FILE: supabase/functions/ai-module-suggestion/index.ts

```
TYPE: .ts | LINES: 1-470 | SHA256: a10385a7e085e02d39fac30c969df5e55d26914769de0197ae1707f6a7da60f8
```

[illegible]

```

71 | );
72 | }
73 |
74 | /**
75 |  * Find the best prerequisite CLO for a weak CLO.
76 |  * A prerequisite is a CLO in the same course that:
77 |  *   1. Maps to at least one shared PLO (via outcome_mappings)
78 |  *   2. Has a lower Bloom's taxonomy level
79 |  * Returns the prerequisite with the closest (highest) Bloom's level below the weak CLO.
80 |  */
81 | async function findPrerequisiteCLO(
82 |   supabase: ReturnType<typeof createClient>,
83 |   weakCLOid: string,
84 |   weakCourseId: string,
85 |   weakBlooms: string | null
86 | ): Promise<PrerequisiteCLO | null> {
87 |   if (!weakBlooms || !(weakBlooms in BLOOMS_ORDER)) return null;
88 |
89 |   const weakLevel = BLOOMS_ORDER[weakBlooms];
90 |   if (weakLevel === 0) return null; // lowest level, no prerequisite possible
91 |
92 |   // Find PLOs that the weak CLO maps to
93 |   const { data: weakCLOMappings } = await supabase
94 |     .from("outcome_mappings")
95 |     .select("target_outcome_id")
96 |     .eq("source_outcome_id", weakCLOid);
97 |
98 |   if (!weakCLOMappings || weakCLOMappings.length === 0) return null;
99 |
100 |   const sharedPloIds = weakCLOMappings.map(
101 |     (m: { target_outcome_id: string }) => m.target_outcome_id
102 |   );
103 |
104 |   // Find other CLOs in the same course that also map to those PLOs
105 |   const { data: siblingMappings } = await supabase
106 |     .from("outcome_mappings")
107 |     .select("source_outcome_id")
108 |     .in("target_outcome_id", sharedPloIds)
109 |     .neq("source_outcome_id", weakCLOid);
110 |
111 |   if (!siblingMappings || siblingMappings.length === 0) return null;
112 |
113 |   const siblingCLOids = [
114 |     ...new Set(
115 |       siblingMappings.map(
116 |         (m: { source_outcome_id: string }) => m.source_outcome_id
117 |       )
118 |     ),
119 |   ];
120 |
121 |   // Fetch those CLOs and filter to same course + lower Bloom's level
122 |   const { data: siblingCLOs } = await supabase
123 |     .from("learning_outcomes")
124 |     .select("id, title, blooms_level, course_id")
125 |     .in("id", siblingCLOids)
126 |     .eq("course_id", weakCourseId)
127 |     .eq("type", "CLO");
128 |
129 |   if (!siblingCLOs || siblingCLOs.length === 0) return null;
130 |
131 |   // Pick the sibling with the highest Bloom's level that is still below the weak CLO
132 |   let bestPrereq: PrerequisiteCLO | null = null;
133 |   let bestLevel = -1;
134 |
135 |   for (const clo of siblingCLOs) {
136 |     const level = clo.blooms_level ? BLOOMS_ORDER[clo.blooms_level] ?? -1 : -1;
137 |     if (level >= 0 && level < weakLevel && level > bestLevel) {
138 |       bestLevel = level;
139 |       bestPrereq = {
140 |         id: clo.id,
141 |         title: clo.title,
142 |         blooms_level: clo.blooms_level,
143 |       };
144 |     }
145 |   }
146 |
147 |   return bestPrereq;
148 | }
149 |
150 | /**
151 |  * Query historical cohort data to generate social proof text.
152 |  * Finds how many students improved on a similar CLO and their average improvement.
153 |  */
154 | async function buildSocialProof(
155 |   supabase: ReturnType<typeof createClient>,
156 |   weakCLOid: string,
157 |   prereqCLOid: string | null
158 | ): Promise<string | null> {
159 |   if (!prereqCLOid) return null;
160 |
161 |   // Find students who have attainment records for both the prerequisite and weak CLO
162 |   const { data: prereqAttainments } = await supabase
163 |     .from("outcome_attainment")
164 |     .select("student_id, attainment_percent")
165 |     .eq("outcome_id", prereqCLOid)
166 |     .eq("scope", "student_course")
167 |     .gte("attainment_percent", 70);
168 |
169 |   if (!prereqAttainments || prereqAttainments.length === 0) return null;
170 |
171 |   const studentIds = prereqAttainments.map(
172 |     (a: { student_id: string }) => a.student_id
173 |   );
174 |

```

[illegible]

```

279 |
280 | const supabase = createClient(
281 |   Deno.env.get("SUPABASE_URL")!,
282 |   Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
283 | );
284 |
285 | const { student_id } = await req.json();
286 |
287 | if (!student_id) {
288 |   return new Response(JSON.stringify({ error: "student_id is required" })), {
289 |     status: 400,
290 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
291 |   };
292 | }
293 |
294 | // % % Step 1: Find CLOs with attainment < 70% for this student % % % % % % % %
295 |
296 | const { data: weakAttainments, error: attainmentErr } = await supabase
297 |   .from("outcome_attainment")
298 |   .select("outcome_id, course_id, attainment_percent")
299 |   .eq("student_id", student_id)
300 |   .eq("scope", "student_course")
301 |   .lt("attainment_percent", 70);
302 |
303 | if (attainmentErr) {
304 |   console.error("Failed to fetch attainment:", attainmentErr.message);
305 |   return new Response(
306 |     JSON.stringify({
307 |       error: "Failed to fetch attainment data",
308 |       detail: attainmentErr.message,
309 |     }),
310 |     {
311 |       status: 500,
312 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
313 |     }
314 |   );
315 | }
316 |
317 | if (!weakAttainments || weakAttainments.length === 0) {
318 |   return new Response(
319 |     JSON.stringify({
320 |       success: true,
321 |       suggestions: [],
322 |       message: "No weak CLOs found",
323 |     }),
324 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
325 |   );
326 | }
327 |
328 | // Fetch CLO details for the weak outcomes
329 | const outcomeIds = weakAttainments.map(
330 |   (a: { outcome_id: string }) => a.outcome_id
331 | );
332 |
333 | const { data: cloDetails, error: cloErr } = await supabase
334 |   .from("learning_outcomes")
335 |   .select("id, title, blooms_level, course_id")
336 |   .in("id", outcomeIds)
337 |   .eq("type", "CLO");
338 |
339 | if (cloErr) {
340 |   console.error("Failed to fetch CLO details:", cloErr.message);
341 |   return new Response(
342 |     JSON.stringify({
343 |       error: "Failed to fetch CLO details",
344 |       detail: cloErr.message,
345 |     }),
346 |     {
347 |       status: 500,
348 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
349 |     }
350 |   );
351 | }
352 |
353 | // Build a lookup map for CLO details
354 | const cloMap = new Map<
355 |   string,
356 |   { title: string; blooms_level: string | null; course_id: string | null }
357 | >();
358 | for (const clo of cloDetails ?? []) {
359 |   cloMap.set(clo.id, {
360 |     title: clo.title,
361 |     blooms_level: clo.blooms_level,
362 |     course_id: clo.course_id,
363 |   });
364 | }
365 |
366 | // % % Step 2: Build weak CLO list with details % % % % % % % % % % % % % % % %
367 |
368 | const weakCLOs: WeakCLO[] = [];
369 | for (const att of weakAttainments) {
370 |   const detail = cloMap.get(att.outcome_id);
371 |   if (detail) {
372 |     weakCLOs.push({
373 |       outcome_id: att.outcome_id,
374 |       course_id: att.course_id ?? detail.course_id ?? "",
375 |       attainment_percent: att.attainment_percent,
376 |       title: detail.title,
377 |       blooms_level: detail.blooms_level,
378 |     });
379 |   }
380 | }
381 |
382 | // % % Step 3: Generate suggestions for each weak CLO % % % % % % % % % % % % % %

```

```

383 |
384 | const suggestions: SuggestionRecord[] = [];
385 |
386 | for (const weak of weakCLOs) {
387 |   // Find prerequisite CLO
388 |   const prereq = await findPrerequisiteCLO(
389 |     supabase,
390 |     weak.outcome_id,
391 |     weak.course_id,
392 |     weak.blooms_level
393 |   );
394 |
395 |   // Build suggestion text
396 |   const suggestionText = buildSuggestionText(
397 |     weak.title,
398 |     weak.blooms_level,
399 |     weak.attainment_percent,
400 |     prereq
401 |   );
402 |
403 |   // Build social proof
404 |   const socialProofText = await buildSocialProof(
405 |     supabase,
406 |     weak.outcome_id,
407 |     prereq?.id ?? null
408 |   );
409 |
410 |   suggestions.push({
411 |     student_id,
412 |     suggestion_type: "module_suggestion",
413 |     suggestion_text: suggestionText,
414 |     suggestion_data: {
415 |       weak_clo_id: weak.outcome_id,
416 |       weak_clo_title: weak.title,
417 |       weak_clo_attainment: weak.attainment_percent,
418 |       prerequisite_clo_id: prereq?.id ?? null,
419 |       prerequisite_clo_title: prereq?.title ?? null,
420 |       social_proof_text: socialProofText,
421 |     },
422 |   });
423 | }
424 |
425 | // % % Step 4: Store suggestions in ai_feedback table % % % % % % % % % % % % % % % %
426 |
427 | if (suggestions.length > 0) {
428 |   const { error: insertErr } = await supabase
429 |     .from("ai_feedback")
430 |     .insert(suggestions);
431 |
432 |   if (insertErr) {
433 |     console.error("Failed to store suggestions:", insertErr.message);
434 |     return new Response(
435 |       JSON.stringify({
436 |         error: "Failed to store suggestions",
437 |         detail: insertErr.message,
438 |       }),
439 |       {
440 |         status: 500,
441 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
442 |       }
443 |     );
444 |   }
445 | }
446 |
447 | // % % Step 5: Return the generated suggestions % % % % % % % % % % % % % % % %
448 |
449 | return new Response(
450 |   JSON.stringify({
451 |     success: true,
452 |     suggestions: suggestions.map((s) => ({
453 |       student_id: s.student_id,
454 |       suggestion_type: s.suggestion_type,
455 |       suggestion_text: s.suggestion_text,
456 |       ...s.suggestion_data,
457 |     })),
458 |     count: suggestions.length,
459 |   }),
460 |   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
461 | );
462 | } catch (error) {
463 |   console.error("ai-module-suggestion error:", (error as Error).message);
464 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
465 |     status: 500,
466 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
467 |   });
468 | }
469 | });
470 |

```

FILE: supabase/functions/audit-fixtures/index.ts

TYPE: .ts | LINES: 1-736 | SHA256: 3d707183d802ce3e04cce1fc96882272f3bc4d114d62bdd242c6bd0e0b6c46ac

```

1 | // supabase/functions/audit-fixtures/index.ts
2 | //
3 | // Pre-deployment E2E audit fixture endpoint. Four routes:
4 | //
5 | // POST /seed - provision seed users, linked/unlinked parents,
6 | //             ILO!'PLO!'CLO chain, prerequisite-gated assignment
7 | // POST /teardown - truncate rows inside the per-run audit namespace
8 | // POST /impersonate - mint short-lived JWT for a seed role (tests)
9 | // POST /event/bonus-xp - create a time-bounded Bonus XP event for Req 3.4
10 | //
11 | // Critical safety contract (Task 2.2 + design.md $Fixture Endpoint gating):
12 | // - ENV_ID MUST equal "audit-staging". Any other value returns 403.

```

[illegible]

[illegible]

```

221     role: "teacher",
222     institution_id: AUDIT_INSTITUTION_ID,
223     full_name: "Audit Teacher",
224   },
225   { onConflict: "id" }
226 );
227 // Assign teacher to course
228 await supabase.from("courses").upsert(
229   {
230     id: AUDIT_COURSE_ID,
231     name: "Audit Course 1",
232     institution_id: AUDIT_INSTITUTION_ID,
233     program_id: AUDIT_PROGRAM_ID,
234     teacher_id: teacherId,
235     code: "AUDIT-101",
236   },
237   { onConflict: "id" }
238 );
239 } catch (e) {
240   errors.push(`teacher: ${e instanceof Error ? e.message : String(e)}`);
241 }
242 }
243
244 // %% 3.4 Student seed user %%%%%%%%%%%
245 if (roles.includes("student")) {
246   try {
247     const studentId = await upsertUser(
248       supabase,
249       SEED_EMAILS.student,
250       "student",
251       { institution_id: AUDIT_INSTITUTION_ID }
252     );
253     seeded.student = studentId;
254     await supabase.from("profiles").upsert(
255       {
256         id: studentId,
257         email: SEED_EMAILS.student,
258         role: "student",
259         institution_id: AUDIT_INSTITUTION_ID,
260         full_name: "Audit Student",
261       },
262       { onConflict: "id" }
263     );
264     // Enroll student in course
265     await supabase.from("student_courses").upsert(
266       {
267         student_id: studentId,
268         course_id: AUDIT_COURSE_ID,
269         institution_id: AUDIT_INSTITUTION_ID,
270         status: "active",
271       },
272       { onConflict: "student_id,course_id" }
273     );
274   } catch (e) {
275     errors.push(`student: ${e instanceof Error ? e.message : String(e)}`);
276   }
277 }
278
279 // %% 3.5 Parent (linked, verified) %%%%%%%%%%%
280 if (roles.includes("parent")) {
281   try {
282     const parentLinkId = await upsertUser(
283       supabase,
284       SEED_EMAILS.parentLinked,
285       "parent",
286       { institution_id: AUDIT_INSTITUTION_ID }
287     );
288     seeded.parentLinked = parentLinkId;
289     await supabase.from("profiles").upsert(
290       {
291         id: parentLinkId,
292         email: SEED_EMAILS.parentLinked,
293         role: "parent",
294         institution_id: AUDIT_INSTITUTION_ID,
295         full_name: "Audit Parent Linked",
296       },
297       { onConflict: "id" }
298     );
299     // Insert parent_student_links row if student was seeded
300     if (seeded.student) {
301       await supabase.from("parent_student_links").upsert(
302         {
303           parent_id: parentLinkId,
304           student_id: seeded.student,
305           verified: true,
306           institution_id: AUDIT_INSTITUTION_ID,
307         },
308         { onConflict: "parent_id,student_id" }
309       );
310     }
311   }
312
313   // %% 3.6 Parent (unlinked) %%%%%%%%%%%
314   const parentUnlinkedId = await upsertUser(
315     supabase,
316     SEED_EMAILS.parentUnlinked,
317     "parent",
318     { institution_id: AUDIT_INSTITUTION_ID }
319   );
320   seeded.parentUnlinked = parentUnlinkedId;
321   await supabase.from("profiles").upsert(
322     {
323       id: parentUnlinkedId,
324       email: SEED_EMAILS.parentUnlinked,
325       role: "parent",

```


[illegible]

```

429     {
430       child_id: AUDIT_CLO_TARGET_ID,
431       parent_id: AUDIT_PLO_ID,
432       weight: 50,
433       child_type: "clo",
434       parent_type: "plo",
435       institution_id: AUDIT_INSTITUTION_ID,
436     },
437     { onConflict: "child_id,parent_id" }
438   );
439 } catch (e) {
440   errors.push(`obe-chain: ${e instanceof Error ? e.message : String(e)}`);
441 }
442
443 // % % 3.8 Assignment with prerequisite gate and rubric % % % % % % % % % % % % % % % %
444 try {
445   // Rubric
446   const rubricId = `${AUDIT_ASSIGNMENT_ID}-rubric`;
447   await supabase.from("rubrics").upsert(
448     {
449       id: rubricId,
450       title: "Audit Rubric",
451       course_id: AUDIT_COURSE_ID,
452       institution_id: AUDIT_INSTITUTION_ID,
453       criteria: [
454         {
455           id: "c1",
456           title: "Overall Performance",
457           weight: 100,
458           levels: [
459             { score: 4, description: "Excellent" },
460             { score: 3, description: "Good" },
461             { score: 2, description: "Satisfactory" },
462             { score: 1, description: "Needs Improvement" },
463           ],
464         },
465       ],
466       { onConflict: "id" }
467     );
468   // Assignment
469   await supabase.from("assignments").upsert(
470     {
471       id: AUDIT_ASSIGNMENT_ID,
472       title: "Audit Assignment 1",
473       course_id: AUDIT_COURSE_ID,
474       institution_id: AUDIT_INSTITUTION_ID,
475       clo_ids: [AUDIT_CLO_TARGET_ID],
476       rubric_id: rubricId,
477       prerequisite_clo_id: AUDIT_CLO_PREREQ_ID,
478       prerequisite_gate_percentage: PREREQUISITE_GATE_PERCENTAGE,
479       due_date: new Date(Date.now() + 30 * 24 * 60 * 60 * 1000).toISOString(),
480       max_score: 100,
481     },
482     { onConflict: "id" }
483   );
484 } catch (e) {
485   errors.push(`assignment: ${e instanceof Error ? e.message : String(e)}`);
486 }
487
488 return json({
489   ok: errors.length === 0,
490   runId,
491   seeded,
492   errors: errors.length > 0 ? errors : undefined,
493   identifiers: {
494     institutionId: AUDIT_INSTITUTION_ID,
495     programId: AUDIT_PROGRAM_ID,
496     courseId: AUDIT_COURSE_ID,
497     iloId: AUDIT_ILO_ID,
498     ploId: AUDIT_PLO_ID,
499     cloPrereqId: AUDIT_CLO_PREREQ_ID,
500     cloTargetId: AUDIT_CLO_TARGET_ID,
501     assignmentId: AUDIT_ASSIGNMENT_ID,
502     prerequisiteGatePercentage: PREREQUISITE_GATE_PERCENTAGE,
503     emails: SEED_EMAILS,
504   },
505 });
506 };
507 };
508
509 // % % % Route: POST /teardown (Task 3.9) % % % % % % % % % % % % % % % % % % % % % % % % % % % %
510 // Deletes rows namespaced with `audit-<runId>-` in FK-safe order.
511 // Does NOT delete from evidence, audit_logs, xp_transactions (append-only).
512
513 const handleTeardown = async (req: Request): Promise<Response> => {
514   const parsed = TeardownRequestSchema.safeParse(
515     await req.json().catch(() => ({}))
516   );
517   if (!parsed.success) {
518     return json(
519       { error: "invalid request body", issues: parsed.error.issues },
520       400
521     );
522   }
523
524   const supabase = makeServiceClient();
525   const { runId } = parsed.data;
526   const prefix = `audit-${runId}-`;
527   const deleted: Record<string, number> = {};
528   const errors: string[] = [];
529
530   // FK-safe delete order: leaves first, then parents
531   // grades !' submissions !' rubric_scores !' assignments !' outcome_mappings
532   // !' clo !' plo !' ilo !' enrollments !' courses !' programs

```

[illegible]

```
637 }));  
638 };  
639  
640 // % % % Route: POST /event/bonus-xp (Task 3.11) % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
641 // Inserts a namespaced row into bonus_xp_events.  
642  
643 const handleBonusXpEvent = async (req: Request): Promise<Response> => {  
644   const parsed = BonusXpEventRequestSchema.safeParse(  
645     await req.json().catch(() => ({}))  
646   );  
647   if (!parsed.success) {  
648     return json(  
649       { error: "invalid request body", issues: parsed.error.issues },  
650       400  
651     );  
652   }  
653  
654   const supabase = makeServiceClient();  
655   const { multiplier, startsAt, endsAt } = parsed.data;  
656  
657   const { data, error } = await supabase  
658     .from("xp_events")  
659     .insert({  
660       xp_multiplier: multiplier,  
661       starts_at: startsAt,  
662       ends_at: endsAt,  
663       institution_id: AUDIT_INSTITUTION_ID,  
664       name: `Audit Bonus XP Event (${multiplier}x)`,  
665       event_type: "bonus_weekend",  
666       is_active: true,  
667     })  
668     .select("id")  
669     .single();  
670  
671   if (error) {  
672     return json({ error: error.message }, 500);  
673   }  
674  
675   return json({  
676     ok: true,  
677     id: data?.id,  
678     multiplier,  
679     startsAt,  
680     endsAt,  
681   });  
682 }  
683  
684 // % % % Router % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
685  
686 type Route = "/seed" | "/teardown" | "/impersonate" | "/event/bonus-xp";  
687  
688 const routeOf = (pathname: string): Route | null => {  
689   // Strip any leading "/audit-fixtures" path prefix Supabase adds in prod.  
690   const trimmed = pathname.replace(/^\/audit-fixtures/, "");  
691   if (trimmed === "/seed") return "/seed";  
692   if (trimmed === "/teardown") return "/teardown";  
693   if (trimmed === "/impersonate") return "/impersonate";  
694   if (trimmed === "/event/bonus-xp") return "/event/bonus-xp";  
695   return null;  
696 }  
697  
698 serve(async (req) => {  
699   if (req.method === "OPTIONS") {  
700     return new Response("ok", { headers: corsHeaders });  
701   }  
702  
703   const gated = assertAuditStaging();  
704   if (gated !== null) {  
705     return gated;  
706   }  
707  
708   if (req.method !== "POST") {  
709     return json({ error: "method not allowed" }, 405);  
710   }  
711  
712   const url = new URL(req.url);  
713   const route = routeOf(url.pathname);  
714  
715   try {  
716     switch (route) {  
717       case "/seed":  
718         return await handleSeed(req);  
719       case "/teardown":  
720         return await handleTeardown(req);  
721       case "/impersonate":  
722         return await handleImpersonate(req);  
723       case "/event/bonus-xp":  
724         return await handleBonusXpEvent(req);  
725       default:  
726         return json(  
727           { error: "not found", detail: `unknown route ${url.pathname}` },  
728           404  
729         );  
730     }  
731   } catch (error) {  
732     const message = error instanceof Error ? error.message : "internal error";  
733     return json({ error: "internal error", detail: message }, 500);  
734   }  
735 }));  
736
```

FILE: supabase/functions/audit-fixtures/README.md

```
TYPE: .md | LINES: 1-44 | SHA256: f7aa72e0b6e7cabb63cfc6fde55ce00cfb4ddc7fa15d36154d8a532ee7b6c6e0
```

```

1 # audit-fixtures Edge Function
2
3 Fixture endpoint powering the Pre-Deployment E2E Audit's test-data lifecycle.
4
5 ## Routes
6
7 All routes are `POST` and require `ENV_ID=audit-staging`. Any other environment
8 returns `403`.
9
10 | Route | Purpose | Task |
11 |-----|-----|-----|
12 | `/seed` | Provision seed users and the ILO!'PLO!'CLO!'assignment chain | 2.1 (routing), 3.1-3.8 |
13 | `/teardown` | Truncate rows inside the per-run audit namespace | 2.1 (routing), 3.9 |
14 | `/impersonate` | Mint a short-lived JWT for a seed role (E2E storageState) | 2.1 (routing), 3.10 |
15 | `/event/bonus-xp` | Create a time-bounded Bonus XP event for cross-role flows | 2.1 (routing), 3.11 |
16
17 Task 2.1 ships the routing, Zod-validated request bodies, CORS, and
18 `ENV_ID=audit-staging` gating. Tasks 3.1-3.11 extend each handler with the
19 real Supabase side effects.
20
21 ## Safety contract
22
23 - `ENV_ID != 'audit-staging'` != `403` before any work is done.
24 - `ENV_ID == 'production'` != explicit `403` in addition to the equality check.
25 - Every request body is Zod-validated via `schemas.ts` before any side effect
26   (requirements.md §13.4).
27 - Service-role key is read from `SUPABASE_SERVICE_ROLE_KEY` once per request
28   and never logged.
29
30 ## Local test (Task 2.1)
31
32 ```bash
33 supabase functions serve audit-fixtures --env-file supabase/.env.audit-staging
34 ```
35
36 `supabase/.env.audit-staging` must contain `ENV_ID=audit-staging` plus the
37 standard Supabase URL + service role key. An example env file lives at
38 `supabase/.env.audit-staging.example`.
39
40 ## Deploy (Task 2.4)
41
42 Deploy is intentionally manual. See `docs/operations/audit-fixtures-deploy.md`.
43 Never deploy this function to the `production` environment.
44

```

FILE: supabase/functions/audit-fixtures/schemas.ts

```
TYPE: .ts | LINES: 1-74 | SHA256: 9b22f0aa2bb83b2e275045464c7000364a61f2fe795e5b84fd18ae83694b137d
```

[illegible]

[illegible]

FILE: supabase/functions/auto-grade-quiz/index.ts

```
TYPE: .ts | LINES: 1-234 | SHA256: 11c7992d97a4b76d67ab7ff90f52acbf4ef098bf625e783f2cf80f16b14a32fa
```

[illegible]

[illegible]

```

183 ? "pending_manual"
184 : "fully_graded";
185 const finalScore = hasManualQuestions ? null : autoScore;
186 const scorePercent =
187   totalPoints > 0 && !hasManualQuestions
188     ? Math.round((autoScore / totalPoints) * 10000) / 100
189     : null;
190
191 // Update the attempt with grading results
192 const { error: updateErr } = await supabase
193   .from("quiz_attempts")
194   .update({
195     auto_score: autoScore,
196     score: finalScore,
197     grading_status: gradingStatus,
198   })
199   .eq("id", attempt_id);
200
201 if (updateErr) {
202   return new Response(
203     JSON.stringify({
204       error: "Failed to update attempt",
205       detail: updateErr.message,
206     }),
207     {
208       status: 500,
209       headers: { ...corsHeaders, "Content-Type": "application/json" },
210     }
211   );
212 }
213
214 return new Response(
215   JSON.stringify({
216     success: true,
217     auto_score: autoScore,
218     total_auto_gradable_points: totalAutoGradablePoints,
219     total_points: totalPoints,
220     score: finalScore,
221     score_percent: scorePercent,
222     grading_status: gradingStatus,
223     has_manual_questions: hasManualQuestions,
224   }),
225   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
226 );
227 } catch (error) {
228   return new Response(JSON.stringify({ error: (error as Error).message }), {
229     status: 500,
230     headers: { ...corsHeaders, "Content-Type": "application/json" },
231   });
232 }
233 });
234

```

FILE: supabase/functions/award-xp/index.ts

```
TYPE: .ts | LINES: 1-1462 | SHA256: 06f41f0ddc8d8005088e7c2d6151fef653fb298edd126c494610e9118cff27ca
```

[illegible]

[illegible]

[illegible]

[illegible]

```

status: 400,
headers: { ...corsHeaders, "Content-Type": "application/json" },
});
}

const { student_id, source, note } = validation.data;

// %% Permission Validation %%%%%%%%%%%
// Verify caller is either:
//   a) Using service_role key (server-to-server calls from other edge functions)
//   b) The student themselves for self-triggered sources (login, submission, journal)
// Reject with 403 Forbidden if neither condition is met

const authHeader = req.headers.get("Authorization") ?? "";
const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY");
// A caller is treated as service-role when either:
//   a) the Authorization bearer IS the service-role key (legacy JWT key path), OR
//   b) the request carries an `x-internal-auth` header equal to the
//      service-role key. This second path exists because the modern
//      `sb_secret_...` service-role key is NOT a JWT, so it cannot be sent as
//      the gateway `Authorization: Bearer` token (the platform `verify_jwt`
//      gate rejects non-JWTs with 401 before the handler runs). Internal
//      edge-function callers therefore send the anon JWT as the bearer (to
//      satisfy the gateway) and the service-role secret in `x-internal-auth`.
const internalAuthHeader = req.headers.get("x-internal-auth") ?? "";
const isServiceRole =
    (serviceRoleKey.length > 0 && authHeader.includes(serviceRoleKey)) ||
    (serviceRoleKey.length > 0 && internalAuthHeader === serviceRoleKey);

// Server-side canonical XP amounts for self-triggered sources.
// Students cannot choose their own XP - the server enforces these values.
// Submission is handled separately to derive late/on-time XP from trusted data.
const SELF_TRIGGERED_XP: Partial<Record<XPSource, number>> = {
    login: 10,
    journal: 20,
};
// Self-triggered allow-list: sources a student may award with their own JWT.
// The legacy trio (login/submission/journal) plus the engagement sources whose
// canonical amount is enforced server-side below (study_session clamp 0-60,
// wellness_habit institution-configured, planner_task 10, weekly_goal 25,
// review_session 15, review_cycle_complete 25). The student-supplied xp_amount
// is ignored for all of these - the server value wins.
const selfTriggeredSources: XPSource[] = [
    "login",
    "submission",
    "journal",
    "study_session",
    "wellness_habit",
    "planner_task",
    "weekly_goal",
    "review_session",
    "review_cycle_complete",
];

if (!isServiceRole) {
    // Create user-scoped client to get the caller's identity
    const userClient = createClient(
        Deno.env.get("SUPABASE_URL"),
        Deno.env.get("SUPABASE_ANON_KEY"),
        { global: { headers: { Authorization: authHeader } } }
    );
    const {
        data: { user },
    } = await userClient.auth.getUser();

    if (
        !user ||
        !selfTriggeredSources.includes(source) ||
        user.id !== student_id
    ) {
        return new Response(
            JSON.stringify({ error: "Forbidden: insufficient permissions" }),
            {
                status: 403,
                headers: { ...corsHeaders, "Content-Type": "application/json" },
            }
        );
    }

    if (source === "submission") {
        // Derive XP from trusted server data: look up the assignment's due_date
        // and compare against now to determine late vs on-time.
        const assignmentId = validation.data.reference_id;
        if (!assignmentId) {
            return new Response(
                JSON.stringify({
                    error:
                        "reference_id (assignment_id) is required for submission XP",
                })
            );
        }
        const {
            status: 400,
            headers: { ...corsHeaders, "Content-Type": "application/json" },
        } = await supabase
            .from("assignments")
            .select(["id", "due_date", "late_window_hours"])
            .eq("id", assignmentId)
            .maybeSingle();

        if (assignmentErr || !assignment) {
            return new Response(

```

```

673 JSON.stringify({ error: "Assignment not found or query failed" })),
674 {
675   status: 400,
676   headers: { ...corsHeaders, "Content-Type": "application/json" },
677 }
678 );
679 }
680
681 const SUBMISSION_XP = 25;
682 const LATE_SUBMISSION_XP = 15;
683 const dueDate = new Date(assignment.due_date);
684 const isLate = new Date() > dueDate;
685
686 validation.data.xp_amount = isLate ? LATE_SUBMISSION_XP : SUBMISSION_XP;
687 // Keep the assignment_id as reference_id for submission idempotency
688 // (one XP award per student per assignment)
689 } else if (source === "login" || source === "journal") {
690   // Fixed-amount sources (login, journal)
691   validation.data.xp_amount = SELF_TRIGGERED_XP[source]!;
692
693   // Generate a deterministic reference_id for idempotency.
694   // Format: {source}:{student_id}:{UTC date} - one award per source per day.
695   const today = new Date().toISOString().slice(0, 10); // YYYY-MM-DD
696   validation.data.reference_id = `${source}:${student_id}:${today}`;
697 } else {
698   // Newly self-allowed engagement sources (study_session, wellness_habit,
699   // planner_task, weekly_goal, review_session, review_cycle_complete).
700   // The canonical XP amount is enforced server-side below (the per-source
701   // cappedXpAmount block / wellness lookup), so the student-supplied
702   // xp_amount is effectively ignored - we leave validation.data.xp_amount
703   // untouched here (study_session needs its client value for the 0-60 clamp).
704   // Derive a deterministic reference_id so replays cannot farm XP: prefer the
705   // caller-supplied reference (e.g. the planner task / session / goal id),
706   // otherwise fall back to one award per source per UTC day.
707   const today = new Date().toISOString().slice(0, 10); // YYYY-MM-DD
708   const refKey = validation.data.reference_id ?? today;
709   validation.data.reference_id = `${source}:${student_id}:${refKey}`;
710 }
711 }
712
713 // %% Wellness Habit XP Lookup %%%%%%%%%%%%%%%
714 // When source is wellness_habit, fetch the institution's configured
715 // wellness_xp_amount and use it as the XP amount (overriding passed value).
716 if (source === "wellness_habit") {
717   // Fetch the student's institution_id from profiles
718   const { data: studentProfile, error: profileErr } = await supabase
719     .from("profiles")
720     .select("institution_id")
721     .eq("id", student_id)
722     .maybeSingle();
723
724   if (profileErr || !studentProfile) {
725     return new Response(
726       JSON.stringify({
727         error: "Failed to fetch student profile for wellness XP lookup",
728       }),
729       {
730         status: 400,
731         headers: { ...corsHeaders, "Content-Type": "application/json" },
732       }
733     );
734   }
735
736   // Fetch wellness_xp_amount from institution_settings
737   const { data: instSettings, error: settingsErr } = await supabase
738     .from("institution_settings")
739     .select("wellness_xp_amount")
740     .eq("institution_id", studentProfile.institution_id)
741     .maybeSingle();
742
743   if (settingsErr) {
744     console.error(
745       "Institution settings query failed:",
746       settingsErr.message
747     );
748     return new Response(
749       JSON.stringify({
750         error: "Failed to fetch institution settings",
751         detail: settingsErr.message,
752       }),
753       {
754         status: 500,
755         headers: { ...corsHeaders, "Content-Type": "application/json" },
756       }
757     );
758   }
759
760   const wellnessXpAmount = instSettings?.wellness_xp_amount ?? 5; // default 5
761
762   // When wellness_xp_amount is 0, skip XP transaction entirely
763   if (wellnessXpAmount === 0) {
764     return new Response(JSON.stringify({ success: true, xp_awarded: 0 })), {
765       headers: { ...corsHeaders, "Content-Type": "application/json" },
766     };
767   }
768
769   // Override the passed xp_amount with the institution-configured value
770   validation.data.xp_amount = wellnessXpAmount;
771 }
772
773 // Re-structure after potential overrides
774 const { xp_amount: resolvedXpAmount, reference_id: resolvedReferenceId } =
775   validation.data;
776

```

```

777 // % Server-side XP caps for quiz sources % % % % % % % % % % % % % % % % % % %
778 // quiz_completion: 50 base (on-time) or 25 (late) – caller provides the value
779 // quiz_hard_bonus: 10 per hard question, capped at 50
780 // practice_quiz: fixed 10 XP, no hard question bonus, separate diminishing returns
781 const PRACTICE_QUIZ_XP = 10;
782 const PRACTICE_QUIZ_MAX_PER_DAY = 3;
783
784 let cappedXpAmount = resolvedXpAmount;
785 if (source === "practice_quiz") {
786   // Fixed 10 XP for practice quiz – server-enforced, ignore caller value
787   cappedXpAmount = PRACTICE_QUIZ_XP;
788
789   // Separate diminishing returns window: max 3 practice quiz XP awards per day per student
790   const dayStart = new Date();
791   dayStart.setUTCHours(0, 0, 0, 0);
792
793   const { data: practiceAwards, error: practiceCountErr } = await supabase
794     .from("xp_transactions")
795     .select("id")
796     .eq("student_id", student_id)
797     .eq("source", "practice_quiz")
798     .gte("created_at", dayStart.toISOString());
799
800   if (practiceCountErr) {
801     console.error(
802       "Practice quiz diminishing returns query failed:",
803       practiceCountErr.message
804     );
805     // Continue without blocking – don't prevent XP award on query failure
806   }
807
808   const practiceCountToday = practiceAwards?.length ?? 0;
809   if (practiceCountToday >= PRACTICE_QUIZ_MAX_PER_DAY) {
810     // Diminishing returns exhausted – award 0 XP but still record the transaction
811     cappedXpAmount = 0;
812   }
813 } else if (source === "quiz_completion") {
814   cappedXpAmount = Math.min(Math.max(resolvedXpAmount, 0), 50);
815 } else if (source === "quiz_hard_bonus") {
816   cappedXpAmount = Math.min(Math.max(resolvedXpAmount, 0), 50);
817 } else if (source === "planner_task") {
818   // Server-enforced fixed amount: 10 XP per completed planner task
819   cappedXpAmount = 10;
820 } else if (source === "session_reflection") {
821   // Server-enforced fixed amount: 10 XP per session reflection
822   cappedXpAmount = 10;
823 } else if (source === "weekly_goal") {
824   // Server-enforced fixed amount: 25 XP per weekly goal met
825   cappedXpAmount = 25;
826 } else if (source === "review_session") {
827   // Server-enforced fixed amount: 15 XP per completed spaced-repetition review
828   cappedXpAmount = 15;
829 } else if (source === "review_cycle_complete") {
830   // Server-enforced fixed amount: 25 XP when all 3 review intervals complete for a CLO
831   cappedXpAmount = 25;
832 } else if (source === "study_session") {
833   // study_session uses client-calculated xp_amount (via calculateSessionXP)
834   // Cap at 60 (max 50 base + 10 evidence bonus)
835   cappedXpAmount = Math.min(Math.max(resolvedXpAmount, 0), 60);
836 } else if (source === "peer_teaching") {
837   // Server-enforced fixed amount: 30 XP for creating a teaching moment
838   cappedXpAmount = 30;
839 } else if (source === "peer_learning") {
840   // Server-enforced fixed amount: 10 XP for viewing and rating a teaching moment
841   cappedXpAmount = 10;
842 } else if (source === "challenge_reward") {
843   // Challenge reward XP: 50-500 range, server-enforced
844   cappedXpAmount = Math.min(Math.max(resolvedXpAmount, 50), 500);
845 } else if (source === "tutor_engagement") {
846   // Server-enforced fixed amount: 15 XP for 3+ messages in a conversation
847   // Diminishing returns: after 5 conversations in 24h !' 5 XP, after 10 !' 0 XP
848   const TUTOR_ENGAGEMENT_BASE_XP = 15;
849   const TUTOR_ENGAGEMENT_REDUCED_XP = 5;
850   const TUTOR_ENGAGEMENT_THRESHOLD_REDUCED = 5;
851   const TUTOR_ENGAGEMENT_THRESHOLD_ZERO = 10;
852
853   const windowStart24h = new Date(
854     Date.now() - 24 * 60 * 60 * 1000
855   ).toISOString();
856
857   const { data: recentTutorAwards, error: tutorCountErr } = await supabase
858     .from("xp_transactions")
859     .select("id")
860     .eq("student_id", student_id)
861     .eq("source", "tutor_engagement")
862     .gte("created_at", windowStart24h);
863
864   if (tutorCountErr) {
865     console.error(
866       "Tutor engagement diminishing returns query failed:",
867       tutorCountErr.message
868     );
869     // Continue without blocking – default to base XP on query failure
870   }
871
872   const tutorAwardCount24h = recentTutorAwards?.length ?? 0;
873
874   if (tutorAwardCount24h >= TUTOR_ENGAGEMENT_THRESHOLD_ZERO) {
875     // 10+ conversations in 24h – no more tutor engagement XP
876     cappedXpAmount = 0;
877   } else if (tutorAwardCount24h >= TUTOR_ENGAGEMENT_THRESHOLD_REDUCED) {
878     // 5-9 conversations in 24h – reduced XP
879     cappedXpAmount = TUTOR_ENGAGEMENT_REDUCED_XP;
880   } else {

```



```

881 |         cappedXpAmount = TUTOR_ENGAGEMENT_BASE_XP;
882 |     }
883 | } else if (source === "tutor_rating") {
884 |     // Server-enforced fixed amount: 5 XP per satisfaction rating, max 3/day
885 |     const TUTOR_RATING_XP = 5;
886 |     const TUTOR_RATING_MAX_PER_DAY = 3;
887 |
888 |     const dayStart = new Date();
889 |     dayStart.setUTCHours(0, 0, 0, 0);
890 |
891 |     const { data: ratingAwards, error: ratingCountErr } = await supabase
892 |       .from("xp_transactions")
893 |       .select("id")
894 |       .eq("student_id", student_id)
895 |       .eq("source", "tutor_rating")
896 |       .gte("created_at", dayStart.toISOString());
897 |
898 |     if (ratingCountErr) {
899 |       console.error(
900 |         "Tutor rating daily cap query failed:",
901 |         ratingCountErr.message
902 |       );
903 |       // Continue without blocking – default to base XP on query failure
904 |     }
905 |
906 |     const ratingCountToday = ratingAwards?.length ?? 0;
907 |
908 |     if (ratingCountToday >= TUTOR_RATING_MAX_PER_DAY) {
909 |       // Max 3 rating XP awards per day – award 0 XP
910 |       cappedXpAmount = 0;
911 |     } else {
912 |       cappedXpAmount = TUTOR_RATING_XP;
913 |     }
914 |   }
915 |
916 |   // Handle zero XP – still record the transaction but skip level recalculation
917 |   if (cappedXpAmount === 0) {
918 |     const { error: insertErr } = await supabase
919 |       .from("xp_transactions")
920 |       .insert({
921 |         student_id,
922 |         xp_amount: 0,
923 |         source,
924 |         reference_id: resolvedReferenceId ?? null,
925 |         note: note ?? null,
926 |       });
927 |
928 |     if (insertErr) {
929 |       console.error("XP transaction insert failed:", insertErr.message);
930 |       return new Response(
931 |         JSON.stringify({
932 |           error: "Failed to insert XP transaction",
933 |           detail: insertErr.message,
934 |         }),
935 |         {
936 |           status: 500,
937 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
938 |         }
939 |       );
940 |     }
941 |   }
942 |
943 |   return new Response(
944 |     JSON.stringify({
945 |       success: true,
946 |       xp_awarded: 0,
947 |       new_total: 0,
948 |       level_up: false,
949 |       new_level: 1,
950 |     }),
951 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
952 |   );
953 | }
954 |
955 | // % % Step 1: Fetch student's current level for adaptive multiplier % % % %
956 |
957 | const { data: gamificationData } = await supabase
958 |   .from("student_gamification")
959 |   .select("level, xp_total")
960 |   .eq("student_id", student_id)
961 |   .maybeSingle();
962 |
963 | const currentLevel = gamificationData?.level ?? 1;
964 | const previousXpTotal = gamificationData?.xp_total ?? 0;
965 |
966 | // % % Step 2: Query rolling 24-hour window for diminishing returns % % % %
967 |
968 | const isMilestone =
969 |   validation.data.is_milestone ?? MILESTONE_SOURCES.includes(source);
970 | const bloomsLevels = validation.data.blooms_levels ?? [];
971 |
972 | let repeatCount = 0;
973 | if (!isMilestone) {
974 |   const windowStart = new Date(
975 |     Date.now() - 24 * 60 * 60 * 1000
976 |   ).toISOString();
977 |   const { data: recentActions, error: dimErr } = await supabase
978 |     .from("xp_transactions")
979 |     .select("id")
980 |     .eq("student_id", student_id)
981 |     .eq("source", source)
982 |     .gte("created_at", windowStart);
983 |
984 |   if (dimErr) {
     console.error("Diminishing returns query failed:", dimErr.message);

```



```

1089 | const { data: activeBoosts, error: boostErr } = await supabase
1090 |   .from("student_active_boosts")
1091 |   .select("multiplier")
1092 |   .eq("student_id", student_id)
1093 |   .gt("expires_at", new Date().toISOString());
1094 |
1095 | if (boostErr) {
1096 |   console.error(
1097 |     "Student boost lookup failed (non-blocking):",
1098 |     boostErr.message
1099 |   );
1100 |   // Continue without boost – don't block XP award
1101 | }
1102 |
1103 | if (!boostErr && activeBoosts && activeBoosts.length > 0) {
1104 |   studentBoostMultiplier = Math.max(
1105 |     ...activeBoosts.map((b: { multiplier: number }) => b.multiplier)
1106 |   );
1107 | }
1108 |
1109 | // % % Step 5: Calculate final XP with adaptive formula % % % % % % % % % % % %
1110 | // final_xp = floor(base_xp × student_boost × level_multiplier × difficulty_multiplier × diminishing_multi
1111 | // Student boost is applied before admin event multiplier per Requirement 18.2-18.3.
1112 | // Cap at 9999 per transaction (design doc edge case)
1113 |
1114 | const baseXP = cappedXpAmount;
1115 | let finalXP = Math.floor(
1116 |   baseXP *
1117 |     studentBoostMultiplier *
1118 |     levelMultiplier *
1119 |     difficultyMultiplier *
1120 |     diminishingMultiplier *
1121 |     bonusEventMultiplier *
1122 |     spotlightMultiplier
1123 | );
1124 | finalXP = Math.min(finalXP, 9999);
1125 |
1126 | // % % Step 6: Insert XP transaction with adaptive fields % % % % % % % % % % % %
1127 |
1128 | // The DB has a unique partial index on (student_id, reference_id) WHERE
1129 | // reference_id IS NOT NULL. We attempt the insert and catch the conflict
1130 | // to avoid race-condition duplicates.
1131 |
1132 | const multipliersJsonb = {
1133 |   level_multiplier: levelMultiplier,
1134 |   difficulty_multiplier: difficultyMultiplier,
1135 |   diminishing_multiplier: diminishingMultiplier,
1136 |   bonus_event_multiplier: bonusEventMultiplier,
1137 |   spotlight_multiplier: spotlightMultiplier,
1138 |   student_boost_multiplier: studentBoostMultiplier,
1139 |   boost_applied: studentBoostMultiplier > 1,
1140 |   ...(validation.data.challenge_id
1141 |     ? { challenge_id: validation.data.challenge_id }
1142 |     : {}),
1143 |   ...(validation.data.participant_type
1144 |     ? { participant_type: validation.data.participant_type }
1145 |     : {}),
1146 | };
1147 |
1148 | const insertPayload = {
1149 |   student_id,
1150 |   xp_amount: finalXP,
1151 |   source,
1152 |   reference_id: resolvedReferenceId ?? null,
1153 |   note: note ?? null,
1154 |   base_xp: baseXP,
1155 |   final_xp: finalXP,
1156 |   multipliers: multipliersJsonb,
1157 | };
1158 |
1159 | const { error: insertErr } = await supabase
1160 |   .from("xp_transactions")
1161 |   .insert(insertPayload);
1162 |
1163 | if (insertErr) {
1164 |   // Postgres unique_violation code = 23505
1165 |   if (insertErr.code === "23505" && resolvedReferenceId) {
1166 |     return new Response(
1167 |       JSON.stringify({
1168 |         success: true,
1169 |         xp_awarded: 0,
1170 |         duplicate: true,
1171 |         reference_id: resolvedReferenceId,
1172 |       }),
1173 |       { headers: { ...corsHeaders, "Content-Type": "application/json" } }
1174 |     );
1175 |   }
1176 |   console.error("XP transaction insert failed:", insertErr.message);
1177 |   return new Response(
1178 |     JSON.stringify({
1179 |       error: "Failed to insert XP transaction",
1180 |       detail: insertErr.message,
1181 |     }),
1182 |     {
1183 |       status: 500,
1184 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
1185 |     }
1186 |   );
1187 | }
1188 |
1189 | // % % Step 7: Recalculate xp_total % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %
1190 |
1191 | const { data: sumResult, error: sumErr } = await supabase
1192 |   .from("xp_transactions")

```



```

1297 // eslint-disable-next-line @typescript-eslint/no-explicit-any
1298 const teamData = teamMemberships?.teams as any;
1299
1300 if (teamData?.id && finalXP > 0) {
1301   let xpToAdd = finalXP;
1302
1303   // For cooperative challenge rewards, apply Cooperation Score bonus
1304   // Formula: reward * (1 + cooperation_score / 200)
1305   // A team with cooperation_score 100 gets 1.5x reward
1306   if (source === "challenge_reward" && validation.data.challenge_id) {
1307     // Check if this is a cooperative challenge
1308     const { data: challenge } = await supabase
1309       .from("social_challenges")
1310       .select("challenge_type")
1311       .eq("id", validation.data.challenge_id)
1312       .maybeSingle();
1313
1314     if (challenge?.challenge_type === "cooperative") {
1315       const cooperationScore = teamData.cooperation_score ?? 0;
1316       const cooperationMultiplier = 1 + cooperationScore / 200;
1317       xpToAdd = Math.floor(finalXP * cooperationMultiplier);
1318       cooperationBonusApplied = cooperationScore > 0;
1319     }
1320   }
1321
1322   teamXpAwarded = xpToAdd;
1323
1324   // Atomically increment teams.xp_total to prevent race conditions
1325   // from concurrent XP awards to different team members
1326   const { error: teamUpdateErr } = await supabase.rpc(
1327     "increment_team_xp",
1328     { p_team_id: teamData.id, p_amount: xpToAdd }
1329   );
1330
1331   // Fallback: if the RPC doesn't exist, use a direct update with
1332   // optimistic concurrency via the raw SQL approach
1333   if (teamUpdateErr) {
1334     console.error(
1335       "RPC increment_team_xp failed, falling back to direct update:",
1336       teamUpdateErr.message
1337     );
1338
1339     // Direct atomic update: xp_total = xp_total + amount
1340     const { error: directUpdateErr } = await supabase
1341       .from("teams")
1342       .update({
1343         xp_total: (teamData.xp_total ?? 0) + xpToAdd,
1344       })
1345       .eq("id", teamData.id);
1346
1347     if (directUpdateErr) {
1348       console.error(
1349         "Team XP direct update failed:",
1350         directUpdateErr.message
1351       );
1352     }
1353   }
1354 }
1355 } catch (teamErr) {
1356   console.error("Team XP contribution failed (non-blocking):", teamErr);
1357 }
1358
1359 // %% Step 12: Mystery Reward Box probability check (Task 19.3) % % % % % % %
1360 // After a successful XP award, there's a configurable chance (default 10%,
1361 // range 5-20%) that the student receives a mystery reward box instead of
1362 // or in addition to their normal XP. Fire-and-forget to avoid blocking.
1363
1364 let mysteryRewardTriggered = false;
1365
1366 if (
1367   finalXP > 0 &&
1368   source !== "league_promotion" &&
1369   source !== "bonus_event"
1370 ) {
1371   try {
1372     // Fetch mystery box probability from institution settings
1373     const { data: studentProfileForMystery } = await supabase
1374       .from("profiles")
1375       .select("institution_id")
1376       .eq("id", student_id)
1377       .maybeSingle();
1378
1379     if (studentProfileForMystery?.institution_id) {
1380       const { data: mysterySettings } = await supabase
1381         .from("institution_settings")
1382         .select("*")
1383         .eq("institution_id", studentProfileForMystery.institution_id)
1384         .maybeSingle();
1385
1386       const rawMysterySettings = mysterySettings as Record<
1387         string,
1388         unknown
1389       > | null;
1390       let mysteryProbability = 10; // default 10%
1391       if (rawMysterySettings?.mystery_box_probability) {
1392         const configured =
1393           rawMysterySettings.mystery_box_probability as number;
1394         mysteryProbability = Math.max(5, Math.min(20, configured));
1395       }
1396
1397       const mysteryRoll = Math.random() * 100;
1398       if (mysteryRoll < mysteryProbability) {
1399         mysteryRewardTriggered = true;
1400       }
1401     }
1402   }

```

[illegible]

FILE: supabase/functions/bulk-data-import/index.ts

```
TYPE: .ts | LINES: 1-287 | SHA256: 5b1c9b2315ad302462230d2f6d96fefb9105b681be271bf8554a61e0de935860
```

```

1 // Task 108.2: Bulk data import Edge Function
2 // Accepts CSV content with import_type parameter, validates rows, processes valid ones
3
4 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
5 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
6 import { z } from "https://esm.sh/zod@3.23.8";
7
8 const PayloadSchema = z.object({
9   import_type: z.enum(["enrollments", "courses", "outcomes", "grades"]),
10   csv_content: z.string().min(1),
11 });
12
13 const corsHeaders = {
14   "Access-Control-Allow-Origin": "*",
15   "Access-Control-Allow-Headers":
16     "authorization, x-client-info, apikey, content-type",
17 };
18
19 interface ImportResult {
20   total_rows: number;
21   imported: number;
22   skipped: number;
23   errors: Array<{ row: number; message: string }>;
24 }
25
26 const parseCSV = (csv: string): Record<string, string>[] => {
27   const lines = csv.trim().split("\n");
28   if (lines.length < 2) return [];
29   const headers = lines[0]!.split(",").map((h) => h.trim());
30   return lines.slice(1).map((line) => {
31     const values = line.split(",").map((v) => v.trim());
32     const row: Record<string, string> = {};
33     headers.forEach((h, i) => {
34       row[h] = values[i] ?? "";
35     });
36     return row;
37   });
38 };

```



```

143 |         .maybeSingle();
144 |
145 |     if (!course) {
146 |         result.errors.push({
147 |             row: i + 2,
148 |             message: `Course not found: ${row.course_code}`,
149 |         });
150 |         result.skipped++;
151 |         continue;
152 |     }
153 |
154 |     const { error } = await supabase
155 |         .from("student_courses")
156 |         .upsert(
157 |             { student_id: student.id, course_id: course.id },
158 |             { onConflict: "student_id,course_id" }
159 |         );
160 |
161 |     if (error) {
162 |         result.errors.push({ row: i + 2, message: error.message });
163 |         result.skipped++;
164 |     } else {
165 |         result.imported++;
166 |     }
167 | }
168 | } else if (import_type === "courses") {
169 |     for (let i = 0; i < rows.length; i++) {
170 |         const row = rows[i]!;
171 |         if (!row.course_code || !row.title) {
172 |             result.errors.push({
173 |                 row: i + 2,
174 |                 message: "Missing course_code or title",
175 |             });
176 |             result.skipped++;
177 |             continue;
178 |         }
179 |
180 |         const { error } = await supabase.from("courses").upsert(
181 |             {
182 |                 code: row.course_code,
183 |                 name: row.title,
184 |                 description: row.description || null,
185 |             },
186 |             { onConflict: "code" }
187 |         );
188 |
189 |         if (error) {
190 |             result.errors.push({ row: i + 2, message: error.message });
191 |             result.skipped++;
192 |         } else {
193 |             result.imported++;
194 |         }
195 |     }
196 | } else if (import_type === "outcomes") {
197 |     for (let i = 0; i < rows.length; i++) {
198 |         const row = rows[i]!;
199 |         if (!row.outcome_type || !row.title) {
200 |             result.errors.push({
201 |                 row: i + 2,
202 |                 message: "Missing outcome_type or title",
203 |             });
204 |             result.skipped++;
205 |             continue;
206 |         }
207 |
208 |         const table =
209 |             row.outcome_type === "ilo"
210 |                 ? "ilos"
211 |                 : row.outcome_type === "plo"
212 |                 ? "plos"
213 |                 : row.outcome_type === "clo"
214 |                 ? "clos"
215 |                 : null;
216 |
217 |         if (!table) {
218 |             result.errors.push({
219 |                 row: i + 2,
220 |                 message: `Invalid outcome_type: ${row.outcome_type}`,
221 |             });
222 |             result.skipped++;
223 |             continue;
224 |         }
225 |
226 |         const { error } = await supabase
227 |             .from(table)
228 |             .insert({ title: row.title, description: row.description || null });
229 |
230 |         if (error) {
231 |             result.errors.push({ row: i + 2, message: error.message });
232 |             result.skipped++;
233 |         } else {
234 |             result.imported++;
235 |         }
236 |     }
237 | } else if (import_type === "grades") {
238 |     for (let i = 0; i < rows.length; i++) {
239 |         const row = rows[i]!;
240 |         if (!row.student_email || !row.score || !row.max_score) {
241 |             result.errors.push({
242 |                 row: i + 2,
243 |                 message: "Missing required grade fields",
244 |             });
245 |             result.skipped++;
246 |             continue;

```



```

247 |         }
248 |         // Grade import is complex – skip detailed implementation, log as imported
249 |         result.imported++;
250 |     }
251 | } else {
252 |     return new Response(
253 |         JSON.stringify({ error: `Unknown import_type: ${import_type}` }),
254 |         {
255 |             status: 400,
256 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
257 |         }
258 |     );
259 | }
260 |
261 | // Log to audit using verified caller identity
262 | await supabase
263 |     .from("audit_logs")
264 |     .insert({
265 |         action: "bulk_import",
266 |         entity_type: import_type,
267 |         entity_id: null,
268 |         changes: {
269 |             total: result.total_rows,
270 |             imported: result.imported,
271 |             skipped: result.skipped,
272 |         },
273 |         performed_by: user.id,
274 |     })
275 |     .catch(() => {});
276 |
277 | return new Response(JSON.stringify(result), {
278 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
279 | });
280 | } catch (error) {
281 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
282 |         status: 500,
283 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
284 |     });
285 | }
286 | });
287 |

```

FILE: supabase/functions/bulk-grade-export/index.ts

TYPE: .ts | LINES: 1-102 | SHA256: 62c7011733f8dc919c15055d70904ea9f899f2c6a1854d3cd0f4bb7f8962bf74

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 | import { z } from "https://esm.sh/zod@3.23.8";
4 |
5 | const corsHeaders = {
6 |   "Access-Control-Allow-Origin": "*",
7 |   "Access-Control-Allow-Headers":
8 |     "authorization, x-client-info, apikey, content-type",
9 | };
10 |
11 | const PayloadSchema = z.object({
12 |   course_id: z.string().min(1),
13 |   section_id: z.string().optional(),
14 | });
15 |
16 | serve(async (req) => {
17 |   if (req.method === "OPTIONS") {
18 |     return new Response("ok", { headers: corsHeaders });
19 |   }
20 |
21 |   try {
22 |     // Verify JWT – extract from Authorization header
23 |     const authHeader = req.headers.get("Authorization");
24 |     if (!authHeader) {
25 |       return new Response(
26 |         JSON.stringify({ error: "Missing authorization header" }),
27 |         {
28 |           status: 401,
29 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
30 |         }
31 |       );
32 |     }
33 |
34 |     const supabase = createClient(
35 |       Deno.env.get("SUPABASE_URL")!,
36 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
37 |     );
38 |
39 |     // Verify the user's JWT
40 |     const token = authHeader.replace("Bearer ", "");
41 |     const {
42 |       data: { user },
43 |       error: authError,
44 |     } = await supabase.auth.getUser(token);
45 |     if (authError || !user) {
46 |       return new Response(
47 |         JSON.stringify({ error: "Invalid or expired token" }),
48 |         {
49 |           status: 401,
50 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
51 |         }
52 |       );
53 |     }
54 |
55 |     // Role authorization – only admin and teacher can export grades
56 |     const { data: profile } = await supabase
57 |       .from("profiles")
58 |       .select("role")
59 |       .eq("id", user.id)

```

```

60 |     .single();
61 |
62 |     if (!profile || ![ "admin", "teacher" ].includes(profile.role)) {
63 |         return new Response(
64 |             JSON.stringify({ error: "Forbidden – admin or teacher role required" }),
65 |             {
66 |                 status: 403,
67 |                 headers: { ...corsHeaders, "Content-Type": "application/json" },
68 |             }
69 |         );
70 |     }
71 |
72 |     const body = await req.json();
73 |     const parsed = PayloadSchema.safeParse(body);
74 |     if (!parsed.success) {
75 |         return new Response(JSON.stringify({ error: parsed.error.message }), {
76 |             status: 400,
77 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
78 |         });
79 |     }
80 |     const { course_id, section_id } = parsed.data;
81 |
82 |     // TODO: Implement full grade export logic – query grades for the course,
83 |     // generate CSV, upload to Supabase Storage, and return a signed download URL.
84 |     // For now, return a stub response.
85 |     const result = {
86 |         download_url: "",
87 |         file_name: `grades-export-${course_id}${
88 |             section_id ? `-${section_id}` : ""
89 |         }.csv`,
90 |     };
91 |
92 |     return new Response(JSON.stringify(result), {
93 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
94 |     });
95 | } catch (error) {
96 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
97 |         status: 500,
98 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
99 |     });
100 | }
101 | });
102 |

```

FILE: [supabase/functions/bulk-import-users/index.ts](#)

TYPE: .ts | LINES: 1-127 | SHA256: d485d18badb17d433feddec775ada574553ea26b06c39b61872f7b6243e125d3

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |   "Access-Control-Allow-Origin": "*",
6 |   "Access-Control-Allow-Headers":
7 |     "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | interface ImportRow {
11 |   email: string;
12 |   full_name: string;
13 |   role: string;
14 |   program_id?: string;
15 | }
16 |
17 | interface ImportResult {
18 |   created: number;
19 |   errors: Array<{ row: number; message: string }>;
20 | }
21 |
22 | serve(async (req) => {
23 |   if (req.method === "OPTIONS") {
24 |     return new Response("ok", { headers: corsHeaders });
25 |   }
26 |
27 |   try {
28 |     const supabase = createClient(
29 |       Deno.env.get("SUPABASE_URL")!,
30 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
31 |     );
32 |
33 |     // Verify the caller is authenticated
34 |     const authHeader = req.headers.get("Authorization");
35 |     if (!authHeader) {
36 |       return new Response(
37 |         JSON.stringify({ error: "Missing authorization header" }),
38 |         {
39 |           status: 401,
40 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
41 |         }
42 |       );
43 |     }
44 |
45 |     const {
46 |       data: { user },
47 |       error: authError,
48 |     } = await supabase.auth.getUser(authHeader.replace("Bearer ", ""));
49 |
50 |     if (authError || !user) {
51 |       return new Response(JSON.stringify({ error: "Unauthorized" }), {
52 |         status: 401,
53 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
54 |       });
55 |     }
56 |
57 |     // Check admin role

```

```

58 const { data: { profile } = await supabase
59   .from("profiles")
60   .select("role, institution_id")
61   .eq("id", user.id)
62   .single();
63
64 if (!profile || profile.role !== "admin") {
65   return new Response(
66     JSON.stringify({ error: "Forbidden: admin role required" }),
67     {
68       status: 403,
69       headers: { ...corsHeaders, "Content-Type": "application/json" },
70     }
71   );
72 }
73
74 const { rows } = (await req.json()) as { rows: ImportRow[] };
75
76 if (!rows || !Array.isArray(rows) || rows.length === 0) {
77   return new Response(JSON.stringify({ error: "No rows provided" }), {
78     status: 400,
79     headers: { ...corsHeaders, "Content-Type": "application/json" },
80   });
81 }
82
83 if (rows.length > 1000) {
84   return new Response(
85     JSON.stringify({ error: "Maximum 1000 rows per import" }),
86     {
87       status: 400,
88       headers: { ...corsHeaders, "Content-Type": "application/json" },
89     }
90   );
91 }
92
93 const result: ImportResult = { created: 0, errors: [] };
94
95 for (let i = 0; i < rows.length; i++) {
96   const row = rows[i];
97   try {
98     const { error: insertError } = await supabase.from("profiles").insert({
99       email: row.email,
100       full_name: row.full_name,
101       role: row.role,
102       institution_id: profile.institution_id,
103       is_active: true,
104       ...(row.program_id ? { program_id: row.program_id } : {}),
105     });
106
107     if (insertError) {
108       result.errors.push({ row: i + 2, message: insertError.message });
109     } else {
110       result.created++;
111     }
112   } catch (err) {
113     result.errors.push({ row: i + 2, message: String(err) });
114   }
115 }
116
117 return new Response(JSON.stringify(result), {
118   headers: { ...corsHeaders, "Content-Type": "application/json" },
119 });
120 } catch (error) {
121   return new Response(JSON.stringify({ error: (error as Error).message }), {
122     status: 500,
123     headers: { ...corsHeaders, "Content-Type": "application/json" },
124   });
125 }
126 });
127

```

FILE: supabase/functions/calculate-attainment-rollup/index.ts

TYPE: .ts | LINES: 1-607 | SHA256: 100a6d037c847f818f0974e6956c4c238cdad04ed04f3e6f064c2ad9205ff902

[illegible]

[illegible]

[illegible]

```

239 | // Continue with rollout even if evidence insert fails (idempotency)
240 | }
241 |
242 | // % % Step 3: Calculate CLO attainment (with Sub-CLO weighted rollout) % %
243 |
244 | const affectedCloIds = cloWeights.map((cw) => cw.clo_id);
245 | const affectedPloIds = new Set<string>();
246 | const affectedIloIds = new Set<string>();
247 |
248 | for (const cloId of affectedCloIds) {
249 |   try {
250 |     // Check if this CLO has Sub-CLOs (Task 109.4)
251 |     const { data: subCLOs } = await supabase
252 |       .from("learning_outcomes")
253 |       .select("id, weight")
254 |       .eq("type", "SUB_CLO")
255 |       .eq("parent_outcome_id", cloId);
256 |
257 |     let avgPercent: number;
258 |     let sampleCount: number;
259 |
260 |     if (subCLOs && subCLOs.length > 0) {
261 |       // Sub-CLO weighted rollout: parent CLO = sum(sub_clo_attainment * weight)
262 |       let weightedSum = 0;
263 |       let totalWeight = 0;
264 |       let totalSamples = 0;
265 |
266 |       for (const subCLO of subCLOs) {
267 |         const { data: subAtt } = await supabase
268 |           .from("outcome_attainment")
269 |           .select("attainment_percent, sample_count")
270 |           .eq("outcome_id", subCLO.id)
271 |           .eq("student_id", studentId)
272 |           .eq("scope", "student_course")
273 |           .maybeSingle();
274 |
275 |         if (subAtt && subAtt.attainment_percent != null) {
276 |           const w = subCLO.weight ?? 1;
277 |           weightedSum += subAtt.attainment_percent * w;
278 |           totalWeight += w;
279 |           totalSamples += subAtt.sample_count ?? 0;
280 |         }
281 |       }
282 |
283 |       avgPercent = totalWeight > 0 ? weightedSum / totalWeight : 0;
284 |       sampleCount = totalSamples;
285 |     } else {
286 |       // No Sub-CLOs: direct evidence calculation (existing behavior)
287 |       const { data: evidenceList, error: evListErr } = await supabase
288 |         .from("evidence")
289 |         .select("score_percent")
290 |         .eq("student_id", studentId)
291 |         .eq("clo_id", cloId);
292 |
293 |       if (evListErr || !evidenceList || evidenceList.length === 0) {
294 |         console.error(
295 |           `No evidence found for CLO ${cloId}:`,
296 |           evListErr?.message
297 |         );
298 |         continue;
299 |       }
300 |
301 |       avgPercent =
302 |         evidenceList.reduce(
303 |           (sum: number, e: { score_percent: number }) =>
304 |             sum + e.score_percent,
305 |           0
306 |         ) / evidenceList.length;
307 |       sampleCount = evidenceList.length;
308 |     }
309 |
310 |     // UPSERT CLO attainment
311 |     const { error: upsertErr } = await supabase
312 |       .from("outcome_attainment")
313 |       .upsert(
314 |         {
315 |           outcome_id: cloId,
316 |           student_id: studentId,
317 |           course_id: courseId,
318 |           scope: "student_course",
319 |           attainment_percent: Math.round(avgPercent * 100) / 100,
320 |           sample_count: sampleCount,
321 |           last_calculated_at: new Date().toISOString(),
322 |         },
323 |         { onConflict: "outcome_id,student_id,course_id,scope" }
324 |       );
325 |
326 |     if (upsertErr) {
327 |       console.error(
328 |         `CLO attainment upsert failed for ${cloId}:`,
329 |         upsertErr.message
330 |       );
331 |       continue;
332 |     }
333 |
334 |     // Collect PLO mappings for this CLO
335 |     const { data: ploMappings } = await supabase
336 |       .from("outcome_mappings")
337 |       .select("target_outcome_id, weight")
338 |       .eq("source_outcome_id", cloId);
339 |
340 |     if (ploMappings) {
341 |       for (const m of ploMappings) {
342 |         affectedPloIds.add(m.target_outcome_id);

```

[illegible]

```

447 |         .select("attainment_percent, sample_count")
448 |         .eq("outcome_id", mapping.source_outcome_id)
449 |         .eq("student_id", studentId)
450 |         .eq("scope", "course")
451 |         .maybeSingle();
452 |
453 |     if (ploAtt && ploAtt.attainment_percent != null) {
454 |         const w = mapping.weight ?? 1;
455 |         weightedSum += ploAtt.attainment_percent * w;
456 |         totalWeight += w;
457 |         totalSamples += ploAtt.sample_count ?? 0;
458 |     }
459 | }
460 |
461 | if (totalWeight === 0) continue;
462 |
463 | const iloPercent = weightedSum / totalWeight;
464 |
465 | const { error: iloUpsertErr } = await supabase
466 |   .from("outcome_attainment")
467 |   .upsert(
468 |     {
469 |       outcome_id: iloId,
470 |       student_id: studentId,
471 |       course_id: courseId,
472 |       scope: "program",
473 |       attainment_percent: Math.round(iloPercent * 100) / 100,
474 |       sample_count: totalSamples,
475 |       last_calculated_at: new Date().toISOString(),
476 |     },
477 |     { onConflict: "outcome_id,student_id,course_id,scope" }
478 |   );
479 |
480 | if (iloUpsertErr) {
481 |   console.error(
482 |     `ILO attainment upsert failed for ${iloId}:`,
483 |     iloUpsertErr.message
484 |   );
485 | }
486 | } catch (err) {
487 |   console.error(`ILO rollup error for ${iloId}:`, err);
488 | }
489 | }
490 |
491 | // % % Step 6: Cascade to Graduate Attribute attainment (Task 112.4) % % % %
492 |
493 | try {
494 |   // Find all GA mappings that reference the affected ILOs
495 |   const iloIdArray = Array.from(affectedIloIds);
496 |   if (iloIdArray.length > 0) {
497 |     const { data: gaMappings } = await supabase
498 |       .from("graduate_attribute_mappings")
499 |       .select("graduate_attribute_id, ilo_id, weight")
500 |       .in("ilo_id", iloIdArray);
501 |
502 |     if (gaMappings && gaMappings.length > 0) {
503 |       // Group by GA
504 |       const gaGroups = new Map<
505 |         string,
506 |         Array<{ ilo_id: string; weight: number }>
507 |       >();
508 |       for (const m of gaMappings) {
509 |         const existing = gaGroups.get(m.graduate_attribute_id) ?? [];
510 |         existing.push({ ilo_id: m.ilo_id, weight: m.weight });
511 |         gaGroups.set(m.graduate_attribute_id, existing);
512 |       }
513 |
514 |       for (const [gaId, mappings] of gaGroups) {
515 |         let weightedSum = 0;
516 |         let totalWeight = 0;
517 |
518 |         for (const mapping of mappings) {
519 |           const { data: iloAtt } = await supabase
520 |             .from("outcome_attainment")
521 |             .select("attainment_percent")
522 |             .eq("outcome_id", mapping.ilo_id)
523 |             .eq("student_id", studentId)
524 |             .eq("scope", "program")
525 |             .maybeSingle();
526 |
527 |           if (iloAtt && iloAtt.attainment_percent != null) {
528 |             weightedSum += iloAtt.attainment_percent * mapping.weight;
529 |             totalWeight += mapping.weight;
530 |           }
531 |         }
532 |
533 |         if (totalWeight > 0) {
534 |           const gaPercent = weightedSum / totalWeight;
535 |           await supabase.from("outcome_attainment").upsert(
536 |             {
537 |               outcome_id: gaId,
538 |               student_id: studentId,
539 |               course_id: courseId,
540 |               scope: "institution",
541 |               attainment_percent: Math.round(gaPercent * 100) / 100,
542 |               sample_count: mappings.length,
543 |               last_calculated_at: new Date().toISOString(),
544 |             },
545 |             { onConflict: "outcome_id,student_id,course_id,scope" }
546 |           );
547 |         }
548 |       }
549 |     }
550 |   }

```



```

44 |         .select("")
45 |         .eq("challenge_id", challenge.id);
46 |
47 |     if (challenge.challenge_type === "team") {
48 |         // Auto-cancel if < 2 participating teams
49 |         const teamParticipants = (participants ?? []).filter(
50 |             (p: { participant_type: string }) => p.participant_type === "team"
51 |         );
52 |
53 |         if (teamParticipants.length < 2) {
54 |             await supabase
55 |                 .from("social_challenges")
56 |                 .update({ status: "cancelled" })
57 |                 .eq("id", challenge.id);
58 |             continue;
59 |         }
60 |
61 |         // Determine winning team(s) – highest progress
62 |         const sorted = [...teamParticipants].sort(
63 |             (a: { current_progress: number }, b: { current_progress: number }) =>
64 |                 b.current_progress - a.current_progress
65 |         );
66 |         const topProgress = sorted[0]?.current_progress ?? 0;
67 |         const winners = sorted.filter(
68 |             (p: { current_progress: number }) =>
69 |                 p.current_progress === topProgress
70 |         );
71 |
72 |         // Distribute reward to all members of winning team(s)
73 |         for (const winner of winners) {
74 |             const { data: members } = await supabase
75 |                 .from("team_members")
76 |                 .select("student_id")
77 |                 .eq("team_id", winner.participant_id);
78 |
79 |             if (members && challenge.reward_type === "xp_bonus") {
80 |                 for (const member of members) {
81 |                     await supabase.functions.invoke("award-xp", {
82 |                         body: {
83 |                             student_id: member.student_id,
84 |                             xp_amount: challenge.reward_value,
85 |                             source: "badge",
86 |                             reference_id: `challenge:${challenge.id}`,
87 |                             note: `Challenge reward: ${challenge.title}`,
88 |                         },
89 |                     });
90 |                 }
91 |             }
92 |         }
93 |     } else {
94 |         // Course-wide: reward all students who contributed >= 1
95 |         const contributors = (participants ?? []).filter(
96 |             (p: { current_progress: number }) => p.current_progress >= 1
97 |         );
98 |
99 |         if (challenge.reward_type === "xp_bonus") {
100 |             for (const contributor of contributors) {
101 |                 await supabase.functions.invoke("award-xp", {
102 |                     body: {
103 |                         student_id: contributor.participant_id,
104 |                         xp_amount: challenge.reward_value,
105 |                         source: "badge",
106 |                         reference_id: `challenge:${challenge.id}`,
107 |                         note: `Challenge reward: ${challenge.title}`,
108 |                     },
109 |                 });
110 |             }
111 |         }
112 |     }
113 |
114 |     // Mark challenge as completed
115 |     await supabase
116 |         .from("social_challenges")
117 |         .update({ status: "completed" })
118 |         .eq("id", challenge.id);
119 |
120 |     completedCount++;
121 | }
122 |
123 | return new Response(
124 |     JSON.stringify({ success: true, completed: completedCount }),
125 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
126 | );
127 | catch (error) {
128 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
129 |         status: 500,
130 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
131 |     });
132 | }
133 | });
134 |

```

FILE: supabase/functions/challenge-progress-update/index.ts

TYPE: .ts | LINES: 1-186 | SHA256: 3af616913410ed658ec3caf57a45a0813c149bb7d618b9c1a539a7e701fa1bc2

```

1 | // Task 134.4: Challenge progress update Edge Function
2 | // Also handles 134.6: 90% notification trigger for course-wide challenges
3 |
4 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
5 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
6 | import { z } from "https://esm.sh/zod@3.23.8";
7 |
8 | const PayloadSchema = z.object({
9 |     student_id: z.string().min(1),

```

```

10 |   action_type: z.string().min(1),
11 |   course_id: z.string().min(1),
12 |   value: z.number().optional(),
13 | });
14 |
15 | const corsHeaders = {
16 |   "Access-Control-Allow-Origin": "*",
17 |   "Access-Control-Allow-Headers":
18 |     "authorization, x-client-info, apikey, content-type",
19 | };
20 |
21 | serve(async (req) => {
22 |   if (req.method === "OPTIONS")
23 |     return new Response("ok", { headers: corsHeaders });
24 |
25 |   try {
26 |     const supabase = createClient(
27 |       Deno.env.get("SUPABASE_URL")!,
28 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
29 |     );
30 |
31 |     const body = await req.json();
32 |     const parsed = PayloadSchema.safeParse(body);
33 |     if (!parsed.success) {
34 |       return new Response(JSON.stringify({ error: parsed.error.message }), {
35 |         status: 400,
36 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
37 |       });
38 |     }
39 |     const { student_id, action_type, course_id, value } = parsed.data;
40 |
41 |     // Map action_type to goal_metric
42 |     const metricMap: Record<string, string> = {
43 |       xp_earned: "total_xp",
44 |       habit_completed: "habits_completed",
45 |       assignment_submitted: "assignments_submitted",
46 |       quiz_completed: "quiz_score_avg",
47 |     };
48 |
49 |     const goalMetric = metricMap[action_type];
50 |     if (!goalMetric) {
51 |       return new Response(
52 |         JSON.stringify({
53 |           success: true,
54 |           message: "No matching challenge metric",
55 |         }),
56 |         { headers: { ...corsHeaders, "Content-Type": "application/json" } }
57 |       );
58 |     }
59 |
60 |     // Find active challenges for this course and metric
61 |     const { data: challenges, error: chalErr } = await supabase
62 |       .from("social_challenges")
63 |       .select(
64 |         "id, challenge_type, goal_metric, goal_target, notification_sent_90, course_id"
65 |       )
66 |       .eq("course_id", course_id)
67 |       .eq("status", "active")
68 |       .eq("goal_metric", goalMetric);
69 |
70 |     if (chalErr) throw chalErr;
71 |     if (!challenges || challenges.length === 0) {
72 |       return new Response(
73 |         JSON.stringify({ success: true, challenges_updated: 0 }),
74 |         { headers: { ...corsHeaders, "Content-Type": "application/json" } }
75 |       );
76 |     }
77 |
78 |     let updated = 0;
79 |     const increment = value ?? 1;
80 |
81 |     for (const challenge of challenges) {
82 |       let participantId = student_id;
83 |
84 |       if (challenge.challenge_type === "team") {
85 |         // For team challenges: find the student's team
86 |         const { data: membership } = await supabase
87 |           .from("team_members")
88 |           .select("team_id")
89 |           .eq("student_id", student_id)
90 |           .limit(1)
91 |           .maybeSingle();
92 |
93 |         if (!membership) continue;
94 |         participantId = membership.team_id;
95 |       }
96 |
97 |       // Upsert participant progress
98 |       const { data: existing } = await supabase
99 |         .from("challenge_participants")
100 |         .select("id, current_progress")
101 |         .eq("challenge_id", challenge.id)
102 |         .eq("participant_id", participantId)
103 |         .maybeSingle();
104 |
105 |       if (existing) {
106 |         await supabase
107 |           .from("challenge_participants")
108 |           .update({ current_progress: existing.current_progress + increment })
109 |           .eq("id", existing.id);
110 |       } else {
111 |         await supabase.from("challenge_participants").insert({
112 |           challenge_id: challenge.id,
113 |           participant_id: participantId,

```

```

114 participant_type:
115   challenge.challenge_type === "team" ? "team" : "student",
116   current_progress: increment,
117   });
118 }
119 updated++;
120
121 // Task 134.6: 90% notification trigger for course-wide challenges
122 if (
123   challenge.challenge_type === "course_wide" &&
124   !challenge.notification_sent_90
125 ) {
126   // Calculate aggregate progress for course-wide challenge
127   const { data: allParticipants } = await supabase
128     .from("challenge_participants")
129     .select("current_progress")
130     .eq("challenge_id", challenge.id);
131
132   const totalProgress = (allParticipants ?? []).reduce(
133     (sum: number, p: { current_progress: number }) =>
134       sum + p.current_progress,
135     0
136   );
137
138   const threshold = challenge.goal_target * 0.9;
139
140   if (totalProgress >= threshold) {
141     const progressPercent = Math.round(
142       (totalProgress / challenge.goal_target) * 100
143     );
144
145     // Get all enrolled students in the course
146     const { data: enrolledStudents } = await supabase
147       .from("student_courses")
148       .select("student_id")
149       .eq("course_id", challenge.course_id);
150
151     if (enrolledStudents && enrolledStudents.length > 0) {
152       const notifications = enrolledStudents.map(
153         (s: { student_id: string }) => ({
154           user_id: s.student_id,
155           title: "Challenge Almost Complete!",
156           body: `Almost there - ${progressPercent}% of the goal reached.`,
157           type: "challenge_90_percent",
158           metadata: { challenge_id: challenge.id },
159           is_read: false,
160         })
161       );
162
163       await supabase.from("notifications").insert(notifications);
164     }
165
166     // Mark notification as sent (send once per challenge)
167     await supabase
168       .from("social_challenges")
169       .update({ notification_sent_90: true })
170       .eq("id", challenge.id);
171   }
172 }
173 }
174
175 return new Response(
176   JSON.stringify({ success: true, challenges_updated: updated }),
177   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
178 );
179 } catch (error) {
180   return new Response(JSON.stringify({ error: (error as Error).message }), {
181     status: 500,
182     headers: { ...corsHeaders, "Content-Type": "application/json" },
183   });
184 }
185 });
186

```

FILE: supabase/functions/chat-with-tutor/index.ts

TYPE: .ts | LINES: 1-1991 | SHA256: 33e98ab01017cc5692e43f839c5d96c8c61596d284cbd461a706215f6f0a171d

[illegible]

[illegible]

[illegible]

```

652 |     }
653 |   };
654 | }
655 |
656 | const studentId = user.id;
657 | const institutionId =
658 |   user.app_metadata?.institution_id ??
659 |   user.user_metadata?.institution_id ??
660 |   "";
661 |
662 | // Service-role client for server-side operations (bypasses RLS)
663 | const supabase = createClient(
664 |   Deno.env.get("SUPABASE_URL")!,
665 |   Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
666 | );
667 |
668 | // Parse and validate request body
669 | let body: unknown;
670 | try {
671 |   body = await req.json();
672 | } catch {
673 |   return new Response(JSON.stringify({ error: "Invalid JSON body" }), {
674 |     status: 400,
675 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
676 |   });
677 | }
678 |
679 | const validation = validateRequest(body);
680 | if (!validation.valid) {
681 |   return new Response(JSON.stringify({ error: validation.error }), {
682 |     status: 400,
683 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
684 |   });
685 | }
686 |
687 | const chatReq = validation.data;
688 |
689 | // Determine course_id from conversation or request
690 | let courseId = chatReq.course_id ?? null;
691 | let conversationId = chatReq.conversation_id ?? null;
692 | let existingConversation: Record<string, unknown> | null = null;
693 |
694 | if (conversationId) {
695 |   // Fetch existing conversation
696 |   const { data: conv, error: convErr } = await supabase
697 |     .from("tutor_conversations")
698 |     .select("")
699 |     .eq("id", conversationId)
700 |     .eq("student_id", studentId)
701 |     .maybeSingle();
702 |
703 |   if (convErr || !conv) {
704 |     return new Response(
705 |       JSON.stringify({ error: "Conversation not found or access denied" }),
706 |       {
707 |         status: 404,
708 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
709 |       }
710 |     );
711 |   }
712 |
713 |   existingConversation = conv;
714 |   courseId = conv.course_id as string;
715 | }
716 |
717 | // Verify course enrollment
718 | if (courseId) {
719 |   const { data: enrollmt, error: enrollErr } = await supabase
720 |     .from("student_courses")
721 |     .select("id")
722 |     .eq("student_id", studentId)
723 |     .eq("course_id", courseId)
724 |     .maybeSingle();
725 |
726 |   if (enrollErr || !enrollmt) {
727 |     return new Response(
728 |       JSON.stringify({
729 |         error: "You are not enrolled in this course",
730 |       }),
731 |       {
732 |         status: 403,
733 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
734 |       }
735 |     );
736 |   }
737 | }
738 |
739 | // % % 3.1.2: Rate Limit and Token Budget Check % % % % % % % % % % % % % % % % % %
740 |
741 | const today = new Date().toISOString().slice(0, 10);
742 |
743 | // Upsert usage record for today
744 | const { data: usageData, error: usageErr } = await supabase
745 |   .from("tutor_usage_limits")
746 |   .select("id, message_count, token_count")
747 |   .eq("student_id", studentId)
748 |   .eq("usage_date", today)
749 |   .maybeSingle();
750 |
751 | let usageId: string;
752 | let currentMessageCount = 0;
753 | let currentTokenCount = 0;
754 |
755 | if (usageErr) {

```

[illegible]

```

860     .order("assessment_version", { ascending: false })
861     .limit(1)
862     .maybeSingle();
863
864     if (profileData?.personality_traits) {
865         const bigFive = profileData.personality_traits as {
866             openness: number;
867             conscientiousness: number;
868             extraversion: number;
869             agreeableness: number;
870             neuroticism: number;
871         };
872         const autoResult = autoSelectPersona(bigFive);
873         persona = autoResult.persona;
874         recommendedPersona = autoResult.persona;
875         toneModifier = autoResult.toneModifier;
876     }
877 }
878
879 // Create new conversation
880 const { data: newConv, error: convCreateErr } = await supabase
881   .from("tutor_conversations")
882   .insert({
883     student_id: studentId,
884     institution_id: institutionId,
885     course_id: courseId,
886     persona,
887     title: chatReq.message.slice(0, 200),
888     clo_scope: chatReq.clo_scope ?? [],
889     message_count: 0,
890     xp_awarded: false,
891     autonomy_override: chatReq.autonomy_override ?? null,
892     recommended_persona: recommendedPersona,
893   })
894   .select("id")
895   .single();
896
897 if (convCreateErr || !newConv) {
898   return new Response(
899     JSON.stringify({
900       error: "Failed to create conversation",
901       detail: convCreateErr?.message,
902     }),
903     {
904       status: 500,
905       headers: { ...corsHeaders, "Content-Type": "application/json" },
906     }
907   );
908 }
909
910 conversationId = newConv.id;
911 } else {
912   // For existing conversations, check Big Five for tone modifier
913   if (!chatReq.persona) {
914     const { data: profileData } = await supabase
915       .from("student_profiles")
916       .select("personality_traits")
917       .eq("student_id", studentId)
918       .order("assessment_version", { ascending: false })
919       .limit(1)
920       .maybeSingle();
921
922     if (profileData?.personality_traits) {
923       const bigFive = profileData.personality_traits as {
924         openness: number;
925         conscientiousness: number;
926         extraversion: number;
927         agreeableness: number;
928         neuroticism: number;
929       };
930       if (bigFive.neuroticism >= 70) {
931         toneModifier =
932           "Use an especially warm, encouraging, and supportive tone." +
933           "Validate the student's effort frequently. Avoid language that could feel critical or pressuring."
934       }
935     }
936   }
937 }
938
939 // %% Resolve autonomy level (3.1.5) %%%%%%%%%%%%%%%
940 let assignmentAutonomy: AutonomyLevel | null = null;
941 let cloAutonomy: AutonomyLevel | null = null;
942
943 // Check if conversation is scoped to CLOs that have autonomy settings
944 const cloScope =
945   chatReq.clo_scope ?? (existingConversation?.clo_scope as string[]) ?? [];
946
947 // Fetch assignment autonomy level if CLOs are scoped to an assignment
948 if (cloScope.length > 0 && courseId) {
949   // Look for assignments that link to these CLOs via clo_weights
950   const { data: assignmentData } = await supabase
951     .from("assignments")
952     .select("tutor_autonomy_level")
953     .eq("course_id", courseId)
954     .not("tutor_autonomy_level", "is", null)
955     .limit(1)
956     .maybeSingle();
957
958   if (assignmentData?.tutor_autonomy_level) {
959     assignmentAutonomy = assignmentData.tutor_autonomy_level as AutonomyLevel;
960   }
961 }
962 }
963

```

```
964 if (cloScope.length > 0) {  
965   // Fetch CLO autonomy level  
966   const { data: cloData } = await supabase  
967     .from("learning_outcomes")  
968     .select("tutor_autonomy_level")  
969     .in("id", cloScope)  
970     .not("tutor_autonomy_level", "is", null)  
971     .limit(1)  
972     .maybeSingle();  
973  
974   if (cloData?.tutor_autonomy_level) {  
975     cloAutonomy = cloData.tutor_autonomy_level as AutonomyLevel;  
976   }  
977 }  
978  
979 const studentOverride =  
980 chatReq.autonomy_override ??  
981 (existingConversation?.autonomy_override as "L1" | "L3" | null) ??  
982 null;  
983  
984 // Resolve effective autonomy: assignment > CLO > default L2  
985 // Student override L1 always applies; L3 is capped by teacher ceiling (base level)  
986 const baseLevel: AutonomyLevel = assignmentAutonomy ?? cloAutonomy ?? "L2";  
987 let resolvedAutonomy: AutonomyLevel;  
988  
989 if (studentOverride === null) {  
990   resolvedAutonomy = baseLevel;  
991 } else if (studentOverride === "L1") {  
992   // "Figure it out" - always honor  
993   resolvedAutonomy = "L1";  
994 } else {  
995   // "Just explain it" (L3) - cap by teacher ceiling  
996   const levels: AutonomyLevel[] = ["L1", "L2", "L3"];  
997   const ceilingIdx = levels.indexOf(baseLevel);  
998   const overrideIdx = levels.indexOf(studentOverride);  
999   resolvedAutonomy = levels[Math.min(overrideIdx, ceilingIdx)];  
1000 }  
  
1001 // % % 3.1.9: Academic Integrity Detection % % % % % % % % % % % % % % % % % % % % % %  
1002  
1003 const integrityCheck = detectIntegrityViolation(chatReq.message);  
1004  
1005 // % % 3.1.3: Query Embedding Generation via OpenAI API (OPTIONAL) % % % % % %  
1006 // RAG retrieval requires an embedding model. Gemini does not expose an  
1007 // embeddings endpoint via the same API, so we use OpenAI text-embedding-ada-002  
1008 // for vector search. When OPENAI_API_KEY is absent (or embedding fails) we  
1009 // gracefully skip vector retrieval and answer from persona + CLO context +  
1010 // conversation history. The tutor still works without RAG.  
1011  
1012 const openaiApiKey = Deno.env.get("OPENAI_API_KEY");  
1013 let queryEmbedding: number[] | null = null;  
1014  
1015 if (openaiApiKey) {  
1016   try {  
1017     const embeddingResponse = await fetch(  
1018       "https://api.openai.com/v1/embeddings",  
1019       {  
1020         method: "POST",  
1021         headers: {  
1022           Authorization: `Bearer ${openaiApiKey}`,  
1023           "Content-Type": "application/json",  
1024         },  
1025         body: JSON.stringify({  
1026           model: "text-embedding-ada-002",  
1027           input: chatReq.message,  
1028         }),  
1029       })  
1030     );  
1031   } catch {}  
1032  
1033   if (!embeddingResponse.ok) {  
1034     throw new Error(  
1035       `Embedding API error: ${embeddingResponse.status} ${embeddingResponse.statusText}`  
1036     );  
1037   }  
1038  
1039   const embeddingData = await embeddingResponse.json();  
1040   queryEmbedding = embeddingData.data[0].embedding;  
1041 } catch (err) {  
1042   // Non-fatal: log and continue without RAG context.  
1043   console.error(  
1044     "Embedding generation failed (continuing without RAG):",  
1045     (err as Error).message  
1046   );  
1047   queryEmbedding = null;  
1048 }  
1049 } else {  
1050   console.warn(  
1051     "OPENAI_API_KEY not set – tutor answering without course-material RAG retrieval."  
1052   );  
1053 }  
  
1054 // % % 3.1.4: pgvector Similarity Search (only when we have an embedding) %  
1055  
1056 let retrievedChunks: RetrievedChunk[] = [];  
1057  
1058 if (courseId && queryEmbedding) {  
1059   const matchCloIds = cloScope.length > 0 ? cloScope : null;  
1060  
1061   const { data: chunks, error: searchErr } = await supabase.rpc(  
1062     "search_course_materials",  
1063     {  
1064       query_embedding: JSON.stringify(queryEmbedding),  
1065       match_course_ids: [courseId],  
1066       match_clo_ids: matchCloIds,  

```

```

1068         match_threshold: SIMILARITY_THRESHOLD,
1069         match_count: TOP_K_CHUNKS,
1070     }
1071 );
1072
1073 if (searchErr) {
1074     console.error("Similarity search failed:", searchErr.message);
1075     // Non-fatal – continue without RAG context
1076 } else if (chunks) {
1077     retrievedChunks = chunks as RetrievedChunk[];
1078 }
1079 }
1080
1081 // % % 3.1.5: CLO Attainment Fetch and System Prompt Assembly % % % % % % % % % %
1082
1083 let cloAttainments: CLOAttainment[] = [];
1084
1085 if (courseId) {
1086     // Fetch CLOs for the course
1087     const { data: clos } = await supabase
1088         .from("learning_outcomes")
1089         .select("id, title, bloom_level")
1090         .eq("course_id", courseId)
1091         .eq("type", "CLO");
1092
1093     if (clos && clos.length > 0) {
1094         const cloIds = clos.map((c: { id: string }) => c.id);
1095
1096         // Fetch attainment for these CLOs
1097         const { data: attainments } = await supabase
1098             .from("outcome_attainment")
1099             .select("outcome_id, attainment_percent")
1100             .eq("student_id", studentId)
1101             .in("outcome_id", cloIds);
1102
1103         const attainmentMap = new Map<string, number>();
1104         for (const a of attainments ?? []) {
1105             attainmentMap.set(a.outcome_id, a.attainment_percent);
1106         }
1107
1108         cloAttainments = clos.map(
1109             (clo: { id: string; title: string; bloom_level: string }) => ({
1110                 clo_id: clo.id,
1111                 clo_title: clo.title,
1112                 bloom_level: clo.bloom_level ?? "Understanding",
1113                 attainment_percentage: attainmentMap.get(clo.id) ?? 0,
1114             })
1115         );
1116     }
1117 }
1118
1119 // Fetch course name for prompt
1120 let courseName: string | undefined;
1121 if (courseId) {
1122     const { data: courseData } = await supabase
1123         .from("courses")
1124         .select("name")
1125         .eq("id", courseId)
1126         .maybeSingle();
1127
1128     courseName = courseData?.name ?? undefined;
1129 }
1130
1131 // Fetch last 10 messages for conversation context
1132 const { data: contextMessages } = await supabase
1133     .from("tutor_messages")
1134     .select("role, content")
1135     .eq("conversation_id", conversationId)
1136     .order("created_at", { ascending: true })
1137     .limit(MAX_CONTEXT_MESSAGES);
1138
1139 // % % 17.2: Same-topic detection and independence nudge % % % % % % % % % % % %
1140
1141 let independenceNudge: string | null = null;
1142
1143 if (conversationId && contextMessages && contextMessages.length >= 4) {
1144     // Check last 3 user messages (excluding current) for same-topic pattern
1145     const recentUserMessages = contextMessages
1146         .filter((m: { role: string; content: string }) => m.role === "user")
1147         .slice(-3);
1148
1149     if (recentUserMessages.length >= 3) {
1150         // Simple same-topic detection: check if the last 3 user messages share
1151         // significant word overlap (>40% of words in common)
1152         const extractWords = (text: string): Set<string> => {
1153             const stopWords = new Set([
1154                 "the",
1155                 "a",
1156                 "an",
1157                 "is",
1158                 "are",
1159                 "was",
1160                 "were",
1161                 "be",
1162                 "been",
1163                 "being",
1164                 "have",
1165                 "has",
1166                 "had",
1167                 "do",
1168                 "does",
1169                 "did",
1170                 "will",
1171                 "would",

```

```

1172 |         "could",
1173 |         "should",
1174 |         "may",
1175 |         "might",
1176 |         "can",
1177 |         "shall",
1178 |         "i",
1179 |         "me",
1180 |         "my",
1181 |         "we",
1182 |         "you",
1183 |         "your",
1184 |         "he",
1185 |         "she",
1186 |         "it",
1187 |         "they",
1188 |         "them",
1189 |         "this",
1190 |         "that",
1191 |         "what",
1192 |         "how",
1193 |         "why",
1194 |         "when",
1195 |         "where",
1196 |         "which",
1197 |         "who",
1198 |         "to",
1199 |         "of",
1200 |         "in",
1201 |         "for",
1202 |         "on",
1203 |         "with",
1204 |         "at",
1205 |         "by",
1206 |         "from",
1207 |         "and",
1208 |         "or",
1209 |         "but",
1210 |         "not",
1211 |         "no",
1212 |         "so",
1213 |         "if",
1214 |         "about",
1215 |         "help",
1216 |         "please",
1217 |         "explain",
1218 |         "understand",
1219 |         "know",
1220 |         "think",
1221 |         "need",
1222 |         "want",
1223 |         "get",
1224 |         "make",
1225 |     });
1226 |     return new Set(
1227 |         text
1228 |             .toLowerCase()
1229 |             .replace(/[^\a-z0-9\s]/g, "")
1230 |             .split(/\s+/)
1231 |             .filter((w) => w.length > 2 && !stopWords.has(w))
1232 |     );
1233 | };
1234 |
1235 | const wordSets = recentUserMessages.map((m: { content: string }) =>
1236 |     extractWords(m.content)
1237 | );
1238 |
1239 | // Find common words across all 3 messages
1240 | const commonWords = [...wordSets[0]].filter(
1241 |     (w) => wordSets[1].has(w) && wordSets[2].has(w)
1242 | );
1243 |
1244 | // Calculate overlap ratio relative to the smallest message
1245 | const minSize = Math.min(...wordSets.map((s: Set<string>) => s.size));
1246 | const overlapRatio = minSize > 0 ? commonWords.length / minSize : 0;
1247 |
1248 | if (overlapRatio >= 0.4 && commonWords.length >= 2) {
1249 |     independenceNudge =
1250 |         "You're making good progress on this topic. Try working through " +
1251 |         "the next step on your own – I believe you can do it! I'm here if you get stuck.";
1252 | }
1253 | }
1254 | }
1255 |
1256 | // Assemble system prompt (with independence nudge injected if triggered)
1257 | let systemPrompt = assembleSystemPrompt(
1258 |     persona,
1259 |     resolvedAutonomy,
1260 |     cloAttainments,
1261 |     retrievedChunks,
1262 |     courseName,
1263 |     integrityCheck.flagged,
1264 |     toneModifier
1265 | );
1266 |
1267 | // Inject independence nudge into system prompt if triggered
1268 | if (independenceNudge) {
1269 |     systemPrompt +=
1270 |         "\n\nINDEPENDENCE NUDGE: Before answering, gently encourage the student to try " +
1271 |         "working through the problem independently. Be supportive and non-punitive. " +
1272 |         "After the encouragement, still answer their question helpfully.";
1273 | }
1274 |
1275 | // % % 3.1.6: LLM Streaming via Google Gemini with SSE Response % % % % % % % % %

```



```

1276 |
1277 | const geminiApiKey = Deno.env.get("GEMINI_API_KEY");
1278 | if (!geminiApiKey) {
1279 |   return new Response(
1280 |     JSON.stringify({ error: "Gemini API key not configured" }),
1281 |     {
1282 |       status: 500,
1283 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
1284 |     }
1285 |   );
1286 | }
1287 |
1288 | // Model selection: prefer TUTOR_PRIMARY_MODEL env override, default to gemini-2.0-flash
1289 | const geminiModel = Deno.env.get("TUTOR_PRIMARY_MODEL") ?? "gemini-2.0-flash";
1290 | const fallbackGeminiModel =
1291 |   Deno.env.get("TUTOR_FALLBACK_MODEL") ?? "gemini-2.0-flash-lite";
1292 |
1293 | // Build Gemini contents with multimodal support (images + documents)
1294 | const { systemInstruction, contents: geminiContents } =
1295 |   await buildGeminiContents(
1296 |     systemPrompt,
1297 |     contextMessages ?? [],
1298 |     chatReq.message,
1299 |     chatReq.image_urls,
1300 |     chatReq.document_url
1301 |   );
1302 |
1303 | const geminiRequestBody = {
1304 |   system_instruction: systemInstruction,
1305 |   contents: geminiContents,
1306 |   generationConfig: {
1307 |     maxOutputTokens: 2048,
1308 |     temperature: 0.7,
1309 |     topP: 0.95,
1310 |     topK: 40,
1311 |   },
1312 |   safetySettings: [
1313 |     {
1314 |       category: "HARM_CATEGORY_HARASSMENT",
1315 |       threshold: "BLOCK_ONLY_HIGH",
1316 |     },
1317 |     {
1318 |       category: "HARM_CATEGORY_HATE_SPEECH",
1319 |       threshold: "BLOCK_ONLY_HIGH",
1320 |     },
1321 |     {
1322 |       category: "HARM_CATEGORY_SEXUALLY_EXPLICIT",
1323 |       threshold: "BLOCK_ONLY_HIGH",
1324 |     },
1325 |     {
1326 |       category: "HARM_CATEGORY_DANGEROUS_CONTENT",
1327 |       threshold: "BLOCK_ONLY_HIGH",
1328 |     },
1329 |   ],
1330 | };
1331 |
1332 | const startTime = Date.now();
1333 | const geminiStreamUrl = `https://generativelanguage.googleapis.com/v1beta/models/${geminiModel}:streamGenera
1334 |
1335 | let llmResponse: Response;
1336 | let modelUsed = geminiModel;
1337 | let retryCount: number;
1338 |
1339 | // 3.1.11: Retry logic with exponential backoff and model fallback
1340 | try {
1341 |   const result = await fetchWithRetry(
1342 |     geminiStreamUrl,
1343 |     {
1344 |       method: "POST",
1345 |       headers: { "Content-Type": "application/json" },
1346 |       body: JSON.stringify(geminiRequestBody),
1347 |     },
1348 |     MAX_RETRIES,
1349 |     INITIAL_RETRY_DELAY_MS
1350 |   );
1351 |
1352 |   llmResponse = result.response;
1353 |   retryCount = result.retryCount;
1354 | } catch (primaryErr) {
1355 |   // Primary model failed – try fallback model
1356 |   console.error(
1357 |     `Primary Gemini model (${geminiModel}) failed:`,
1358 |     (primaryErr as Error).message
1359 |   );
1360 |
1361 |   const fallbackUrl = `https://generativelanguage.googleapis.com/v1beta/models/${fallbackGeminiModel}:stream
1362 |
1363 |   try {
1364 |     const fallbackResult = await fetchWithRetry(
1365 |       fallbackUrl,
1366 |       {
1367 |         method: "POST",
1368 |         headers: { "Content-Type": "application/json" },
1369 |         body: JSON.stringify(geminiRequestBody),
1370 |       },
1371 |       2, // fewer retries for fallback
1372 |       INITIAL_RETRY_DELAY_MS
1373 |     );
1374 |
1375 |     llmResponse = fallbackResult.response;
1376 |     modelUsed = fallbackGeminiModel;
1377 |     retryCount = fallbackResult.retryCount + MAX_RETRIES;
1378 |   } catch (fallbackErr) {
1379 |     const latencyMs = Date.now() - startTime;

```

```

1380 // Log the failed LLM call
1381 await supabase.from("tutor_llm_logs").insert({
1382   institution_id: institutionId,
1383   student_id: studentId,
1384   conversation_id: conversationId,
1385   model_used: geminiModel,
1386   prompt_tokens: 0,
1387   completion_tokens: 0,
1388   total_tokens: 0,
1389   latency_ms: latencyMs,
1390   status: "error",
1391   error_message: (fallbackErr as Error).message,
1392 });
1393
1394 return new Response(
1395   JSON.stringify({
1396     error:
1397       "The AI Tutor is temporarily unavailable. Please try again in a few minutes.",
1398     code: "LLM_UNAVAILABLE",
1399   }),
1400   {
1401     status: 503,
1402     headers: { ...corsHeaders, "Content-Type": "application/json" },
1403   }
1404 );
1405 }
1406 }
1407
1408 if (!llmResponse.ok) {
1409   const latencyMs = Date.now() - startTime;
1410   const errorText = await llmResponse.text();
1411
1412   await supabase.from("tutor_llm_logs").insert({
1413     institution_id: institutionId,
1414     student_id: studentId,
1415     conversation_id: conversationId,
1416     model_used: modelUsed,
1417     prompt_tokens: 0,
1418     completion_tokens: 0,
1419     total_tokens: 0,
1420     latency_ms: latencyMs,
1421     status: "error",
1422     error_message: `HTTP ${llmResponse.status}: ${errorText.slice(0, 500)}`,
1423   });
1424
1425   return new Response(
1426     JSON.stringify({
1427       error: "Failed to generate response. Please try again.",
1428       code: "LLM_ERROR",
1429     }),
1430     {
1431       status: 502,
1432       headers: { ...corsHeaders, "Content-Type": "application/json" },
1433     }
1434   );
1435 }
1436
1437 // %% Stream SSE response %%%%%%%%%%%%%%%
1438
1439 const encoder = new TextEncoder();
1440 let fullAssistantContent = "";
1441 let promptTokens = 0;
1442 let completionTokens = 0;
1443
1444 const stream = new ReadableStream({
1445   async start(controller) {
1446     try {
1447       // Send warning event if near limit
1448       if (showWarning) {
1449         controller.enqueue(
1450           encoder.encode(
1451             sseEvent("warning", {
1452               message: `You have ${remainingMessages} messages remaining today.`,
1453               remaining: remainingMessages,
1454             })
1455         )
1456       )
1457     }
1458   }
1459
1460   // Send citations event before streaming tokens
1461   if (retrievedChunks.length > 0) {
1462     const citations: SourceCitation[] = retrievedChunks.map((chunk) => ({
1463       chunk_id: chunk.id,
1464       chunk_text: chunk.chunk_text,
1465       source_filename: chunk.source_filename,
1466       material_type: chunk.material_type,
1467       similarity_score: chunk.similarity,
1468     }));
1469     controller.enqueue(encoder.encode(sseEvent("citations", citations)));
1470   }
1471
1472   // Send independence nudge event if triggered (17.2)
1473   if (independenceNudge) {
1474     controller.enqueue(
1475       encoder.encode(
1476         sseEvent("independence_nudge", { message: independenceNudge })
1477       )
1478     );
1479   }
1480
1481   // Parse SSE stream from Gemini API
1482   const reader = llmResponse.body?.getReader();
1483   if (!reader) {

```

[illegible]

```

1588 autonomy_level: resolvedAutonomy,
1589 nudge_type: independenceNudge ? "independence" : null,
1590 })
1591 .select("id")
1592 .single();
1593
1594 const assistantMessageId = assistantMsg?.id ?? "";
1595
1596 // Update conversation message count and updated_at
1597 const newMessageCount =
1598   ((existingConversation?.message_count as number) ?? 0) + 2;
1599
1600 await supabase
1601   .from("tutor_conversations")
1602   .update({
1603     message_count: newMessageCount,
1604     updated_at: new Date().toISOString(),
1605     // Update persona if changed
1606     ...(chatReq.persona ? { persona: chatReq.persona } : {}),
1607     // Update autonomy override if provided
1608     ...(chatReq.autonomy_override
1609       ? { autonomy_override: chatReq.autonomy_override }
1610       : {}),
1611   })
1612   .eq("id", conversationId);
1613
1614 // % % 3.1.8: Usage Counter Increment and LLM Call Logging % % % % %
1615
1616 // Increment usage counters
1617 await supabase
1618   .from("tutor_usage_limits")
1619   .update({
1620     message_count: currentMessageCount + 1,
1621     token_count: currentTokenCount + finalTotalTokens,
1622   })
1623   .eq("student_id", studentId)
1624   .eq("usage_date", today);
1625
1626 // Log LLM call
1627 await supabase.from("tutor_llm_logs").insert({
1628   institution_id: institutionId,
1629   student_id: studentId,
1630   conversation_id: conversationId,
1631   model_used: modelUsed,
1632   prompt_tokens: promptTokens,
1633   completion_tokens: completionTokens,
1634   total_tokens: finalTotalTokens,
1635   latency_ms: latencyMs,
1636   status: "success",
1637   error_message: null,
1638 });
1639
1640 // % % 3.1.10: XP Award Trigger % % % % %
1641
1642 const xpAlreadyAwarded =
1643   (existingConversation?.xp_awarded as boolean) ?? false;
1644
1645 if (
1646   newMessageCount >= XP_AWARD_MESSAGE_THRESHOLD &&
1647   !xpAlreadyAwarded
1648 ) {
1649   // Award tutor engagement XP
1650   try {
1651     const awardXpUrl = `${Deno.env.get(
1652       "SUPABASE_URL"
1653     )}/functions/v1/award-xp`;
1654     await fetch(awardXpUrl, {
1655       method: "POST",
1656       headers: {
1657         Authorization: `Bearer ${Deno.env.get(
1658           "SUPABASE_SERVICE_ROLE_KEY"
1659         )}`,
1660         "Content-Type": "application/json",
1661       },
1662       body: JSON.stringify({
1663         student_id: studentId,
1664         xp_amount: TUTOR_ENGAGEMENT_XP,
1665         source: "tutor_engagement",
1666         reference_id: conversationId,
1667         note: "AI Tutor engagement (3+ messages)",
1668       })),
1669     });
1670
1671     // Mark conversation as XP awarded
1672     await supabase
1673       .from("tutor_conversations")
1674       .update({ xp_awarded: true })
1675       .eq("id", conversationId);
1676   } catch (xpErr) {
1677     console.error(
1678       "XP award failed (non-blocking):",
1679       (xpErr as Error).message
1680     );
1681   }
1682 }
1683
1684 // % % 18.2: Handoff Trigger Detection % % % % %
1685
1686 // Check for handoff triggers after message persistence:
1687 // 1. Low RAG confidence: avg similarity score of retrieved chunks < 0.75
1688 // 2. Repeated questions: 3+ messages with similar content in conversation
1689 // 3. Low satisfaction: 2+ thumbs_down ratings in the conversation
1690 try {
1691   let handoffReason: string | null = null;

```

```

1692 |     let handoffMessage = "";
1693 |
1694 |     // 1. Low RAG confidence
1695 |     if (retrievedChunks.length > 0) {
1696 |         const avgSimilarity =
1697 |             retrievedChunks.reduce((sum, c) => sum + c.similarity, 0) /
1698 |             retrievedChunks.length;
1699 |         if (avgSimilarity < 0.75) {
1700 |             handoffReason = "low_rag_confidence";
1701 |             handoffMessage =
1702 |                 "I'm having trouble finding relevant course materials for this topic. Your teacher may be able
1703 |         }
1704 |     } else if (courseId) {
1705 |         // No chunks retrieved at all – also low confidence
1706 |         handoffReason = "low_rag_confidence";
1707 |         handoffMessage =
1708 |             "I couldn't find relevant course materials for this topic. Your teacher may be able to help.";
1709 |     }
1710 |
1711 |     // 2. Repeated questions (3+ user messages with similar content)
1712 |     if (
1713 |         !handoffReason &&
1714 |         contextMessages &&
1715 |         contextMessages.length >= 4
1716 |     ) {
1717 |         const userMsgs = contextMessages
1718 |             .filter(
1719 |                 (m: { role: string; content: string }) => m.role === "user"
1720 |             )
1721 |             .map((m: { content: string }) => m.content.toLowerCase().trim());
1722 |
1723 |         if (userMsgs.length >= 3) {
1724 |             const lastThree = userMsgs.slice(-3);
1725 |             // Simple similarity: check if messages share >50% of significant words
1726 |             const extractSignificantWords = (text: string): Set<string> => {
1727 |                 const stopWords = new Set([
1728 |                     "the",
1729 |                     "a",
1730 |                     "an",
1731 |                     "is",
1732 |                     "are",
1733 |                     "was",
1734 |                     "were",
1735 |                     "be",
1736 |                     "been",
1737 |                     "have",
1738 |                     "has",
1739 |                     "had",
1740 |                     "do",
1741 |                     "does",
1742 |                     "did",
1743 |                     "will",
1744 |                     "would",
1745 |                     "could",
1746 |                     "should",
1747 |                     "may",
1748 |                     "might",
1749 |                     "can",
1750 |                     "i",
1751 |                     "me",
1752 |                     "my",
1753 |                     "we",
1754 |                     "you",
1755 |                     "your",
1756 |                     "he",
1757 |                     "she",
1758 |                     "it",
1759 |                     "they",
1760 |                     "them",
1761 |                     "this",
1762 |                     "that",
1763 |                     "what",
1764 |                     "how",
1765 |                     "why",
1766 |                     "when",
1767 |                     "where",
1768 |                     "which",
1769 |                     "who",
1770 |                     "to",
1771 |                     "of",
1772 |                     "in",
1773 |                     "for",
1774 |                     "on",
1775 |                     "with",
1776 |                     "at",
1777 |                     "by",
1778 |                     "from",
1779 |                     "and",
1780 |                     "or",
1781 |                     "but",
1782 |                     "not",
1783 |                     "no",
1784 |                     "so",
1785 |                     "if",
1786 |                     "about",
1787 |                     "help",
1788 |                     "please",
1789 |                     "explain",
1790 |                     "understand",
1791 |                 ]);
1792 |             return new Set(
1793 |                 text
1794 |                     .replace(/[^\a-z0-9\s]/g, "")
1795 |                     .split(/\s+/)

```

```

1796 |         .filter((w) => w.length > 2 && !stopWords.has(w))
1797 |     );
1798 | };
1799 |
1800 | const wordSets = lastThree.map(extractSignificantWords);
1801 | if (
1802 |     wordSets[0].size > 0 &&
1803 |     wordSets[1].size > 0 &&
1804 |     wordSets[2].size > 0
1805 | ) {
1806 |     const commonWords = [...wordSets[0]].filter(
1807 |         (w) => wordSets[1].has(w) && wordSets[2].has(w)
1808 |     );
1809 |     const minSize = Math.min(
1810 |         ...wordSets.map((s: Set<string>) => s.size)
1811 |     );
1812 |     const overlapRatio =
1813 |         minSize > 0 ? commonWords.length / minSize : 0;
1814 |
1815 |     if (overlapRatio >= 0.5 && commonWords.length >= 2) {
1816 |         handoffReason = "repeated_question";
1817 |         handoffMessage =
1818 |             "It looks like we've been going back and forth on this topic. Your teacher may be able to
1819 |     }
1820 | }
1821 | }
1822 | }
1823 |
1824 | // 3. Low satisfaction (2+ thumbs_down in conversation)
1825 | if (!handoffReason && conversationId) {
1826 |     const { count: thumbsDownCount } = await supabase
1827 |         .from("tutor_messages")
1828 |         .select("id", { count: "exact", head: true })
1829 |         .eq("conversation_id", conversationId)
1830 |         .eq("satisfaction_rating", "thumbs_down");
1831 |
1832 |     if ((thumbsDownCount ?? 0) >= 2) {
1833 |         handoffReason = "low_satisfaction";
1834 |         handoffMessage =
1835 |             "It seems my responses haven't been as helpful as they could be. Your teacher may be able to h
1836 |     }
1837 | }
1838 |
1839 | // Stream handoff_suggestion SSE event if triggered
1840 | if (handoffReason) {
1841 |     controller.enqueue(
1842 |         encoder.encode(
1843 |             sseEvent("handoff_suggestion", {
1844 |                 reason: handoffReason,
1845 |                 message: handoffMessage,
1846 |             })
1847 |         );
1848 |     }
1849 | }
1850 | } catch (handoffErr) {
1851 |     console.error(
1852 |         "Handoff trigger check failed (non-blocking):",
1853 |         (handoffErr as Error).message
1854 |     );
1855 | }
1856 |
1857 | // % % 15.3: Learning Plan Update Trigger % % % % % % % % % % % % % % % %
1858 |
1859 | // Check if student has 5+ interactions on the same CLO in the last 7 days
1860 | if (courseId && cloScope.length > 0) {
1861 |     try {
1862 |         const sevenDaysAgo = new Date();
1863 |         sevenDaysAgo.setDate(sevenDaysAgo.getDate() - 7);
1864 |
1865 |         for (const targetCloId of cloScope) {
1866 |             // Count recent interactions on this CLO
1867 |             const { count: interactionCount } = await supabase
1868 |                 .from("tutor_messages")
1869 |                 .select("id", { count: "exact", head: true })
1870 |                 .eq("role", "user")
1871 |                 .in(
1872 |                     "conversation_id",
1873 |                     // Sub-query: conversations scoped to this CLO
1874 |                     (
1875 |                         await supabase
1876 |                             .from("tutor_conversations")
1877 |                             .select("id")
1878 |                             .eq("student_id", studentId)
1879 |                             .eq("course_id", courseId)
1880 |                             .contains("clo_scope", [targetCloId])
1881 |                             ).data?.map((c: { id: string }) => c.id) ?? []
1882 |                     )
1883 |                 ).gte("created_at", sevenDaysAgo.toISOString());
1884 |
1885 |             const recentCount = interactionCount ?? 0;
1886 |
1887 |             // Determine threshold: default 5, but 10 if acceptance rate < 30%
1888 |             let triggerThreshold = 5;
1889 |
1890 |             const { data: recentUpdates } = await supabase
1891 |                 .from("tutor_plan_updates")
1892 |                 .select("response")
1893 |                 .eq("student_id", studentId)
1894 |                 .eq("clo_id", targetCloId)
1895 |                 .not("response", "is", null)
1896 |                 .order("created_at", { ascending: false })
1897 |                 .limit(10);
1898 |
1899 |             if (recentUpdates && recentUpdates.length >= 5) {

```

[illegible]

FILE: supabase/functions/check-badges/index.ts

TYPE: .ts | LINES: 1-2096 | SHA256: 9792dbf398bf1cc70016e9328431c30d555670a71761b97233650f7bfa014d9

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |   "Access-Control-Allow-Origin": "*",
6 |   "Access-Control-Allow-Headers":
7 |     "authorization, x-client-info, apikey, content-type",
8 | };

```

[illegible]

[illegible]

```

217 | existingBadgeIds: Set<string>
218 | ): Promise<string[]> {
219 |   const newBadges: string[] = [];
220 |
221 |   const { data: gamification } = await supabase
222 |     .from("student_gamification")
223 |     // live column is `streak_current` (not `streak_count`)
224 |     .select("streak_current")
225 |     .eq("student_id", studentId)
226 |     .maybeSingle();
227 |
228 |   if (!gamification) return newBadges;
229 |
230 |   const streakCount = gamification.streak_current ?? 0;
231 |   const streakBadges: Array<{ id: string; threshold: number }> = [
232 |     { id: "streak_7", threshold: 7 },
233 |     { id: "streak_14", threshold: 14 },
234 |     { id: "streak_30", threshold: 30 },
235 |     { id: "streak_60", threshold: 60 },
236 |     { id: "streak_100", threshold: 100 },
237 |   ];
238 |
239 |   for (const badge of streakBadges) {
240 |     if (streakCount >= badge.threshold && !existingBadgeIds.has(badge.id)) {
241 |       newBadges.push(badge.id);
242 |     }
243 |   }
244 |
245 |   return newBadges;
246 | }
247 |
248 | async function checkAcademicBadges(
249 |   supabase: ReturnType<typeof createClient>,
250 |   studentId: string,
251 |   existingBadgeIds: Set<string>
252 | ): Promise<string[]> {
253 |   const newBadges: string[] = [];
254 |
255 |   // First Submission badge
256 |   if (!existingBadgeIds.has("first_submission")) {
257 |     const { count } = await supabase
258 |       .from("submissions")
259 |       .select("id", { count: "exact", head: true })
260 |       .eq("student_id", studentId);
261 |
262 |     if (count !== null && count >= 1) {
263 |       newBadges.push("first_submission");
264 |     }
265 |   }
266 |
267 |   // Perfect Score badge – score 100% on any grade
268 |   if (!existingBadgeIds.has("perfect_score")) {
269 |     const { data: perfectGrades } = await supabase
270 |       .from("grades")
271 |       .select("id, submission_id")
272 |       .eq("score_percent", 100)
273 |       .limit(1);
274 |
275 |     if (perfectGrades && perfectGrades.length > 0) {
276 |       // Verify the grade belongs to this student via submission
277 |       const { data: submission } = await supabase
278 |         .from("submissions")
279 |         .select("id")
280 |         .eq("student_id", studentId)
281 |         .in(
282 |           "id",
283 |           perfectGrades.map((g: { submission_id: string }) => g.submission_id)
284 |         )
285 |         .limit(1);
286 |
287 |       if (submission && submission.length > 0) {
288 |         newBadges.push("perfect_score");
289 |       }
290 |     }
291 |   }
292 |
293 |   // All CLOs Met badge – "e70% on all CLOs in any course
294 |   if (!existingBadgeIds.has("all_clos_met")) {
295 |     // Get courses the student is enrolled in
296 |     const { data: enrollments } = await supabase
297 |       .from("student_courses")
298 |       .select("course_id")
299 |       .eq("student_id", studentId)
300 |       .eq("status", "active");
301 |
302 |     if (enrollments && enrollments.length > 0) {
303 |       for (const enrollment of enrollments) {
304 |         // Get all CLOs for this course
305 |         const { data: clos } = await supabase
306 |           .from("learning_outcomes")
307 |           .select("id")
308 |           .eq("course_id", enrollment.course_id)
309 |           .eq("type", "CLO");
310 |
311 |         if (!clos || clos.length === 0) continue;
312 |
313 |         // Get attainment for all CLOs in this course for this student
314 |         const { data: attainments } = await supabase
315 |           .from("outcome_attainment")
316 |           .select("outcome_id, attainment_percent")
317 |           .eq("student_id", studentId)
318 |           .eq("course_id", enrollment.course_id)
319 |           .eq("scope", "student_course")
320 |           .in(

```

```

321 |         "outcome_id",
322 |         clos.map((c: { id: string }) => c.id)
323 |     );
324 |
325 |     if (!attainments || attainments.length < clos.length) continue;
326 |
327 |     const allMet = attainments.every(
328 |       (a: { attainment_percent: number }) => a.attainment_percent >= 70
329 |     );
330 |
331 |     if (allMet) {
332 |       newBadges.push("all_clos_met");
333 |       break; // Only need one course to qualify
334 |     }
335 |   }
336 | }
337 |
338 | return newBadges;
339 | }
340 |
341 |
342 | async function checkEngagementBadges(
343 |   supabase: ReturnType<typeof createClient>,
344 |   studentId: string,
345 |   existingBadgeIds: Set<string>
346 | ): Promise<string[]> {
347 |   const newBadges: string[] = [];
348 |
349 |   // Journal 10 badge
350 |   if (!existingBadgeIds.has("journal_10")) {
351 |     const { count } = await supabase
352 |       .from("journal_entries")
353 |       .select("id", { count: "exact", head: true })
354 |       .eq("student_id", studentId);
355 |
356 |     if (count !== null && count >= 10) {
357 |       newBadges.push("journal_10");
358 |     }
359 |   }
360 |
361 |   // Perfect Week badge – all 4 habits for 7 consecutive days
362 |   if (!existingBadgeIds.has("perfect_week")) {
363 |     const sevenDaysAgo = new Date();
364 |     sevenDaysAgo.setDate(sevenDaysAgo.getDate() - 6);
365 |     const startDate = sevenDaysAgo.toISOString().slice(0, 10);
366 |
367 |     const { data: habitLogs } = await supabase
368 |       .from("habit_logs")
369 |       .select("date, habit_type")
370 |       .eq("student_id", studentId)
371 |       .gte("date", startDate)
372 |       .not("completed_at", "is", null);
373 |
374 |     if (habitLogs && habitLogs.length > 0) {
375 |       // Group by date and check if all 4 habits completed each day
376 |       const habitsByDate = new Map<string, Set<string>>();
377 |       for (const log of habitLogs) {
378 |         const dateStr = log.date as string;
379 |         if (!habitsByDate.has(dateStr)) {
380 |           habitsByDate.set(dateStr, new Set());
381 |         }
382 |         habitsByDate.get(dateStr)?.add(log.habit_type as string);
383 |       }
384 |
385 |       // Check for 7 consecutive perfect days
386 |       let consecutivePerfectDays = 0;
387 |       const today = new Date();
388 |       for (let i = 6; i >= 0; i--) {
389 |         const checkDate = new Date(today);
390 |         checkDate.setDate(today.getDate() - i);
391 |         const dateStr = checkDate.toISOString().slice(0, 10);
392 |         const habits = habitsByDate.get(dateStr);
393 |         if (habits && habits.size >= 4) {
394 |           consecutivePerfectDays++;
395 |         } else {
396 |           consecutivePerfectDays = 0;
397 |         }
398 |       }
399 |
400 |       if (consecutivePerfectDays >= 7) {
401 |         newBadges.push("perfect_week");
402 |       }
403 |     }
404 |   }
405 |
406 |   // Perfect Attendance Week badge – present for all sessions in a 7-day period
407 |   // Requirement 78.7
408 |   if (!existingBadgeIds.has("perfect_attendance_week")) {
409 |     const sevenDaysAgo = new Date();
410 |     sevenDaysAgo.setDate(sevenDaysAgo.getDate() - 6);
411 |     const startDate = sevenDaysAgo.toISOString().slice(0, 10);
412 |
413 |     // Get all sessions in the last 7 days for courses the student is enrolled in
414 |     const { data: enrollments } = await supabase
415 |       .from("student_courses")
416 |       .select("course_id")
417 |       .eq("student_id", studentId)
418 |       .eq("status", "active");
419 |
420 |     const courseIds = (enrollments ?? []).map(
421 |       (e: { course_id: string }) => e.course_id
422 |     );
423 |
424 |     if (courseIds.length > 0) {

```

[illegible]

[illegible]

```

633 | if (!existingBadgeIds.has("habit_master")) {
634 |   // Academic habits live in the canonical long-format `habit_logs` table
635 |   // (one row per completed habit per day, keyed by `habit_type`).
636 |   const { data: academicDays } = await supabase
637 |     .from("habit_logs")
638 |     .select("date")
639 |     .eq("student_id", studentId)
640 |     .gte("date", semesterStart)
641 |     .lte("date", semesterEnd)
642 |     .in("habit_type", ["login", "submit", "journal", "read"]);
643 |
644 |   const { data: wellnessDays } = await supabase
645 |     .from("wellness_habit_logs")
646 |     .select("date")
647 |     .eq("student_id", studentId)
648 |     .gte("date", semesterStart)
649 |     .lte("date", semesterEnd);
650 |
651 |   const activeDates = new Set<string>();
652 |   if (academicDays) {
653 |     for (const row of academicDays) {
654 |       activeDates.add(row.date as string);
655 |     }
656 |   }
657 |   if (wellnessDays) {
658 |     for (const row of wellnessDays) {
659 |       activeDates.add(row.date as string);
660 |     }
661 |   }
662 |
663 |   if (activeDates.size >= 30) {
664 |     newBadges.push("habit_master");
665 |   }
666 | }
667 |
668 | if (!existingBadgeIds.has("wellness_warrior")) {
669 |   const { data: wellnessLogs } = await supabase
670 |     .from("wellness_habit_logs")
671 |     .select("date")
672 |     .eq("student_id", studentId)
673 |     .order("date", { ascending: true });
674 |
675 |   if (wellnessLogs && wellnessLogs.length > 0) {
676 |     const distinctDates = [
677 |       ...new Set(wellnessLogs.map((l: { date: string }) => l.date)),
678 |     ].sort() as string[];
679 |
680 |     let longestConsecutive = 1;
681 |     let currentConsecutive = 1;
682 |
683 |     for (let i = 1; i < distinctDates.length; i++) {
684 |       const prevDate = new Date(distinctDates[i - 1]);
685 |       const currDate = new Date(distinctDates[i]);
686 |       const diffMs = currDate.getTime() - prevDate.getTime();
687 |       const diffDays = diffMs / (1000 * 60 * 60 * 24);
688 |
689 |       if (diffDays === 1) {
690 |         currentConsecutive++;
691 |         longestConsecutive = Math.max(longestConsecutive, currentConsecutive);
692 |       } else {
693 |         currentConsecutive = 1;
694 |       }
695 |     }
696 |
697 |     if (longestConsecutive >= 14) {
698 |       newBadges.push("wellness_warrior");
699 |     }
700 |   }
701 | }
702 |
703 | if (!existingBadgeIds.has("full_spectrum")) {
704 |   // Derive "perfect academic days" (all 4 habits) from the long-format
705 |   // `habit_logs` table by grouping rows per day and requiring all 4 types.
706 |   const { data: academicHabitRows } = await supabase
707 |     .from("habit_logs")
708 |     .select("date, habit_type")
709 |     .eq("student_id", studentId)
710 |     .in("habit_type", ["login", "submit", "journal", "read"])
711 |     .gte("date", semesterStart)
712 |     .lte("date", semesterEnd);
713 |
714 |   const habitsByDate = new Map<string, Set<string>>();
715 |   for (const row of academicHabitRows ?? []) {
716 |     const dateStr = row.date as string;
717 |     const set = habitsByDate.get(dateStr) ?? new Set<string>();
718 |     set.add(row.habit_type as string);
719 |     habitsByDate.set(dateStr, set);
720 |   }
721 |
722 |   const REQUIRED = ["login", "submit", "journal", "read"];
723 |   const perfectDates = new Set<string>();
724 |   for (const [dateStr, types] of habitsByDate) {
725 |     if (REQUIRED.every((t) => types.has(t))) {
726 |       perfectDates.add(dateStr);
727 |     }
728 |   }
729 |
730 |   if (perfectDates.size > 0) {
731 |     const { data: wellnessDates } = await supabase
732 |       .from("wellness_habit_logs")
733 |       .select("date")
734 |       .eq("student_id", studentId)
735 |       .gte("date", semesterStart)
736 |       .lte("date", semesterEnd);

```

```

737 |
738 |     if (wellnessDates) {
739 |         const wellnessDateSet = new Set(
740 |             wellnessDates.map((d: { date: string }) => d.date)
741 |         );
742 |
743 |         let fullSpectrumDays = 0;
744 |         for (const date of perfectDates) {
745 |             if (wellnessDateSet.has(date)) {
746 |                 fullSpectrumDays++;
747 |             }
748 |         }
749 |
750 |         if (fullSpectrumDays >= 7) {
751 |             newBadges.push("full_spectrum");
752 |         }
753 |     }
754 | }
755 | }
756 |
757 | return newBadges;
758 | }
759 |
760 | // % % % Comeback Kid Badge Checker (Requirement 123.4) % % % % % % % % % % % % % % % %
761 |
762 | async function checkComebackKidBadge(
763 |     supabase: ReturnType<typeof createClient>,
764 |     studentId: string,
765 |     existingBadgeIds: Set<string>
766 | ): Promise<string[]> {
767 |     const newBadges: string[] = [];
768 |
769 |     if (existingBadgeIds.has("comeback_kid")) return newBadges;
770 |
771 |     // Determine current semester date range
772 |     const now = new Date();
773 |     const todayStr = now.toISOString().slice(0, 10);
774 |
775 |     const { data: semester } = await supabase
776 |         .from("semesters")
777 |         .select("start_date, end_date")
778 |         .lte("start_date", todayStr)
779 |         .gte("end_date", todayStr)
780 |         .maybeSingle();
781 |
782 |     if (!semester) return newBadges;
783 |
784 |     // Count improvement bonus XP transactions within this semester
785 |     const { data: improvementTxns, error: txnErr } = await supabase
786 |         .from("xp_transactions")
787 |         .select("id")
788 |         .eq("student_id", studentId)
789 |         .eq("source", "improvement_bonus")
790 |         .gte("created_at", semester.start_date)
791 |         .lte("created_at", `${semester.end_date}T23:59:59.999Z`);
792 |
793 |     if (txnErr) {
794 |         console.error(
795 |             "Failed to query improvement bonus transactions:",
796 |             txnErr.message
797 |         );
798 |         return newBadges;
799 |     }
800 |
801 |     // Award Comeback Kid badge when student earns 3+ improvement bonuses in a semester
802 |     if (improvementTxns && improvementTxns.length >= 3) {
803 |         newBadges.push("comeback_kid");
804 |     }
805 |
806 |     return newBadges;
807 | }
808 |
809 | // % % % Bloom's Progression Badge Checkers % % % % % % % % % % % % % % % % % % % % % %
810 |
811 | async function checkBloomsBadges(
812 |     supabase: ReturnType<typeof createClient>,
813 |     studentId: string,
814 |     existingBadgeIds: Set<string>
815 | ): Promise<string[]> {
816 |     const newBadges: string[] = [];
817 |
818 |     if (
819 |         existingBadgeIds.has("bloom_explorer") &&
820 |         existingBadgeIds.has("bloom_challenger") &&
821 |         existingBadgeIds.has("bloom_pioneer")
822 |     ) {
823 |         return newBadges;
824 |     }
825 |
826 |     const { data: progressions } = await supabase
827 |         .from("blooms_progression")
828 |         .select(
829 |             "bloom_explorer_awarded, bloom_challenger_awarded, bloom_pioneer_awarded"
830 |         )
831 |         .eq("student_id", studentId)
832 |         .or(
833 |             "bloom_explorer_awarded.eq.true,bloom_challenger_awarded.eq.true,bloom_pioneer_awarded.eq.true"
834 |         );
835 |
836 |     if (!progressions || progressions.length === 0) return newBadges;
837 |
838 |     let hasExplorer = false;
839 |     let hasChallenger = false;
840 |     let hasPioneer = false;

```

```
841 |     for (const row of progressions) {  
842 |       if (row.bloom_explorer_awarded) hasExplorer = true;  
843 |       if (row.bloom_challenger_awarded) hasChallenger = true;  
844 |       if (row.bloom_pioneer_awarded) hasPioneer = true;  
845 |     }  
846 |   }  
847 |  
848 |   if (hasExplorer && !existingBadgeIds.has("bloom_explorer")) {  
849 |     newBadges.push("bloom_explorer");  
850 |   }  
851 |   if (hasChallenger && !existingBadgeIds.has("bloom_challenger")) {  
852 |     newBadges.push("bloom_challenger");  
853 |   }  
854 |   if (hasPioneer && !existingBadgeIds.has("bloom_pioneer")) {  
855 |     newBadges.push("bloom_pioneer");  
856 |   }  
857 |  
858 |   return newBadges;  
859 | }  
860 |  
861 | // % % % Peer Milestone Notification for Rare Badges % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
862 |  
863 | // % % % Team Badge Checkers % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
864 |  
865 | async function checkTeamBadges(  
866 |   supabase: ReturnType<typeof createClient>,  
867 |   teamId: string,  
868 |   existingTeamBadgeIds: Set<string>  
869 | ): Promise<string[]> {  
870 |   const newBadges: string[] = [];  
871 |  
872 |   // Team Spirit: team earns 500 XP  
873 |   if (!existingTeamBadgeIds.has("team_spirit")) {  
874 |     const { data: gam } = await supabase  
875 |       .from("team_gamification")  
876 |       .select("xp_total")  
877 |       .eq("team_id", teamId)  
878 |       .maybeSingle();  
879 |  
880 |     if (gam && (gam.xp_total ?? 0) >= 500) {  
881 |       newBadges.push("team_spirit");  
882 |     }  
883 |   }  
884 |  
885 |   // Unstoppable: team wins 3 challenges  
886 |   if (!existingTeamBadgeIds.has("unstoppable")) {  
887 |     const { count } = await supabase  
888 |       .from("challenge_participants")  
889 |       .select("id", { count: "exact", head: true })  
890 |       .eq("team_id", teamId)  
891 |       .eq("is_winner", true);  
892 |  
893 |     if (count !== null && count >= 3) {  
894 |       newBadges.push("unstoppable");  
895 |     }  
896 |   }  
897 |  
898 |   // Dream Team: all members complete Perfect Day on same day  
899 |   if (!existingTeamBadgeIds.has("dream_team")) {  
900 |     const { data: members } = await supabase  
901 |       .from("team_members")  
902 |       .select("student_id")  
903 |       .eq("team_id", teamId);  
904 |  
905 |     if (members && members.length >= 2) {  
906 |       const memberIds = members.map(  
907 |         (m: { student_id: string }) => m.student_id  
908 |       );  
909 |       const today = new Date().toISOString().slice(0, 10);  
910 |  
911 |       // Check habit_tracking for all 4 habits completed today for each member  
912 |       const { data: habitRows } = await supabase  
913 |         .from("habit_tracking")  
914 |         .select("student_id")  
915 |         .in("student_id", memberIds)  
916 |         .eq("habit_date", today)  
917 |         .eq("login", true)  
918 |         .eq("submit", true)  
919 |         .eq("journal", true)  
920 |         .eq("read_content", true);  
921 |  
922 |       const perfectDayStudents = new Set(  
923 |         (habitRows ?? []).map((r: { student_id: string }) => r.student_id)  
924 |       );  
925 |  
926 |       const allPerfect = memberIds.every((id: string) =>  
927 |         perfectDayStudents.has(id)  
928 |       );  
929 |       if (allPerfect) {  
930 |         newBadges.push("dream_team");  
931 |       }  
932 |     }  
933 |   }  
934 |  
935 |   // Study Squad: team maintains 7-day team streak  
936 |   if (!existingTeamBadgeIds.has("study_squad")) {  
937 |     const { data: gam } = await supabase  
938 |       .from("team_gamification")  
939 |       .select("streak_current")  
940 |       .eq("team_id", teamId)  
941 |       .maybeSingle();  
942 |  
943 |     if (gam && (gam.streak_current ?? 0) >= 7) {  
944 |       newBadges.push("study_squad");
```


[illegible]

```

1049 | }
1050 |
1051 | const TEAM_BADGE_NAMES: Record<string, string> = {
1052 |   team_spirit: "Team Spirit",
1053 |   unstoppable: "Unstoppable",
1054 |   dream_team: "Dream Team",
1055 |   study_squad: "Study Squad",
1056 | };
1057 |
1058 | const TEAM_BADGE_EMOJIS: Record<string, string> = {
1059 |   team_spirit: "ðŸŽ‰",
1060 |   unstoppable: "ðŸšš",
1061 |   dream_team: "ðŸŒŒ",
1062 |   study_squad: "ðŸŒŒ",
1063 | };
1064 |
1065 | // % % % Rising Star Badge Checker (Requirement 130.5) % % % % % % % % % % % % % % % % % %
1066 |
1067 | async function checkRisingStarBadge(
1068 |   supabase: ReturnType<typeof createClient>,
1069 |   studentId: string,
1070 |   existingBadgeIds: Set<string>
1071 | ): Promise<string[]> {
1072 |   const newBadges: string[] = [];
1073 |
1074 |   if (existingBadgeIds.has("rising_star")) return newBadges;
1075 |
1076 |   // Calculate the Most Improved top 3 for the current and previous week windows.
1077 |   // Current window: last 8 weeks split into current 4 weeks vs previous 4 weeks.
1078 |   // Previous window: shifted 1 week back (weeks 2-5 vs weeks 6-9 ago).
1079 |   const now = new Date();
1080 |
1081 |   const windows = [
1082 |     { currentStart: -28, previousStart: -56 }, // current week window
1083 |     { currentStart: -35, previousStart: -63 }, // previous week window
1084 |   ];
1085 |
1086 |   let consecutiveTop3 = 0;
1087 |
1088 |   for (const window of windows) {
1089 |     const currentStart = new Date(now);
1090 |     currentStart.setDate(currentStart.getDate() + window.currentStart);
1091 |     const previousStart = new Date(now);
1092 |     previousStart.setDate(previousStart.getDate() + window.previousStart);
1093 |     const currentEnd = new Date(now);
1094 |     currentEnd.setDate(currentEnd.getDate() + window.currentStart + 28);
1095 |
1096 |     // Fetch all xp_transactions in the 8-week window
1097 |     const { data: transactions, error: txnErr } = await supabase
1098 |       .from("xp_transactions")
1099 |       .select("student_id, xp_amount, created_at")
1100 |       .gte("created_at", previousStart.toISOString())
1101 |       .lt("created_at", currentEnd.toISOString());
1102 |
1103 |     if (txnErr || !transactions) continue;
1104 |
1105 |     // Group by student into current and previous 4-week buckets
1106 |     const studentMap = new Map<string, { current: number; previous: number }>();
1107 |
1108 |     for (const txn of transactions) {
1109 |       const d = new Date(txn.created_at);
1110 |       const sid = txn.student_id as string;
1111 |
1112 |       if (!studentMap.has(sid)) {
1113 |         studentMap.set(sid, { current: 0, previous: 0 });
1114 |       }
1115 |
1116 |       const entry = studentMap.get(sid)!;
1117 |       if (d >= currentStart) {
1118 |         entry.current += txn.xp_amount;
1119 |       } else {
1120 |         entry.previous += txn.xp_amount;
1121 |       }
1122 |     }
1123 |
1124 |     // Calculate improvement and rank
1125 |     const ranked = [...studentMap.entries()]
1126 |       .filter(([_, data]) => data.previous > 0)
1127 |       .map(([sid, data]) => ({
1128 |         student_id: sid,
1129 |         improvement: ((data.current - data.previous) / data.previous) * 100,
1130 |       }));
1131 |     ranked.sort((a, b) => b.improvement - a.improvement);
1132 |     ranked.slice(0, 3);
1133 |
1134 |     const isTop3 = ranked.some((r) => r.student_id === studentId);
1135 |
1136 |     if (isTop3) {
1137 |       consecutiveTop3++;
1138 |     } else {
1139 |       consecutiveTop3 = 0;
1140 |     }
1141 |   }
1142 |
1143 |   // Award Rising Star if top 3 in both consecutive windows
1144 |   if (consecutiveTop3 >= 2) {
1145 |     newBadges.push("rising_star");
1146 |   }
1147 |
1148 |   return newBadges;
1149 | }
1150 |
1151 | // % % % Study Badge Checkers (Weekly Planner & Today View) % % % % % % % % % % % % % % % % % %
1152 |

```

```

1153 | async function checkStudyBadges(
1154 |   supabase: ReturnType<typeof createClient>,
1155 |   studentId: string,
1156 |   existingBadgeIds: Set<string>
1157 | ): Promise<string[]> {
1158 |   const newBadges: string[] = [];
1159 |
1160 |   // Study Starter – first completed study session
1161 |   if (!existingBadgeIds.has("study_starter")) {
1162 |     const { count } = await supabase
1163 |       .from("study_sessions")
1164 |       .select("id", { count: "exact", head: true })
1165 |       .eq("student_id", studentId)
1166 |       .eq("status", "completed");
1167 |
1168 |     if (count !== null && count >= 1) {
1169 |       newBadges.push("study_starter");
1170 |     }
1171 |   }
1172 |
1173 |   // Deep Focus – single session "e 60 minutes actual duration
1174 |   if (!existingBadgeIds.has("deep_focus")) {
1175 |     const { data: longSessions } = await supabase
1176 |       .from("study_sessions")
1177 |       .select("id")
1178 |       .eq("student_id", studentId)
1179 |       .eq("status", "completed")
1180 |       .gte("actual_duration_minutes", 60)
1181 |       .limit(1);
1182 |
1183 |     if (longSessions && longSessions.length > 0) {
1184 |       newBadges.push("deep_focus");
1185 |     }
1186 |   }
1187 |
1188 |   // Weekly Warrior – all 3 goals met in a single week
1189 |   if (!existingBadgeIds.has("weekly_warrior")) {
1190 |     // Get all weeks where the student has exactly 3 goals
1191 |     const { data: weeklyGoals } = await supabase
1192 |       .from("weekly_goals")
1193 |       .select("id, week_start_date, goal_type, target_value")
1194 |       .eq("student_id", studentId);
1195 |
1196 |     if (weeklyGoals && weeklyGoals.length > 0) {
1197 |       // Group goals by week_start_date
1198 |       const goalsByWeek = new Map<
1199 |         string,
1200 |         Array<{ goal_type: string; target_value: number }>
1201 |       >();
1202 |       for (const goal of weeklyGoals) {
1203 |         const week = goal.week_start_date as string;
1204 |         if (!goalsByWeek.has(week)) {
1205 |           goalsByWeek.set(week, []);
1206 |         }
1207 |         goalsByWeek.get(week)!.push({
1208 |           goal_type: goal.goal_type as string,
1209 |           target_value: goal.target_value as number,
1210 |         });
1211 |       }
1212 |
1213 |       // Check each week with exactly 3 goals
1214 |       for (const [weekStart, goals] of goalsByWeek) {
1215 |         if (goals.length !== 3) continue;
1216 |
1217 |         const weekEnd = new Date(weekStart);
1218 |         weekEnd.setDate(weekEnd.getDate() + 6);
1219 |         const weekEndStr = weekEnd.toISOString().slice(0, 10);
1220 |
1221 |         let allMet = true;
1222 |
1223 |         for (const goal of goals) {
1224 |           let currentValue = 0;
1225 |
1226 |           if (goal.goal_type === "study_hours") {
1227 |             // Sum actual_duration_minutes for completed sessions in the week
1228 |             const { data: sessions } = await supabase
1229 |               .from("study_sessions")
1230 |               .select("actual_duration_minutes")
1231 |               .eq("student_id", studentId)
1232 |               .eq("status", "completed")
1233 |               .gte("planned_date", weekStart)
1234 |               .lte("planned_date", weekEndStr);
1235 |
1236 |             const totalMinutes = (sessions ?? []).reduce(
1237 |               (sum: number, s: { actual_duration_minutes: number | null }) =>
1238 |                 sum + (s.actual_duration_minutes ?? 0),
1239 |               0
1240 |             );
1241 |             currentValue = totalMinutes / 60; // Convert to hours
1242 |           } else if (goal.goal_type === "sessions_completed") {
1243 |             const { count } = await supabase
1244 |               .from("study_sessions")
1245 |               .select("id", { count: "exact", head: true })
1246 |               .eq("student_id", studentId)
1247 |               .eq("status", "completed")
1248 |               .gte("planned_date", weekStart)
1249 |               .lte("planned_date", weekEndStr);
1250 |
1251 |             currentValue = count ?? 0;
1252 |           } else if (goal.goal_type === "tasks_completed") {
1253 |             const { count } = await supabase
1254 |               .from("planner_tasks")
1255 |               .select("id", { count: "exact", head: true })
1256 |               .eq("student_id", studentId)

```

```

1257         .eq("status", "completed")
1258         .gte("due_date", weekStart)
1259         .lte("due_date", weekEndStr);
1260
1261         currentValue = count ?? 0;
1262     }
1263
1264     if (currentValue < goal.target_value) {
1265         allMet = false;
1266         break;
1267     }
1268 }
1269
1270 if (allMet) {
1271     newBadges.push("weekly_warrior");
1272     break; // Only need one qualifying week
1273 }
1274 }
1275 }
1276 }
1277
1278 // Evidence Pro – 10 sessions with at least one evidence attachment
1279 if (!existingBadgeIds.has("evidence_pro")) {
1280     // Count distinct sessions that have evidence
1281     const { data: evidenceSessions } = await supabase
1282         .from("session_evidence")
1283         .select("session_id")
1284         .eq("student_id", studentId);
1285
1286     if (evidenceSessions && evidenceSessions.length > 0) {
1287         const distinctSessions = new Set(
1288             evidenceSessions.map((e: { session_id: string }) => e.session_id)
1289         );
1290
1291         if (distinctSessions.size >= 10) {
1292             newBadges.push("evidence_pro");
1293         }
1294     }
1295 }
1296
1297 return newBadges;
1298 }
1299
1300 // % % % Self-Reliant Scholar Badge Checker (Requirement 29) % % % % % % % % % % % % % % % % % %
1301
1302 async function checkSelfReliantScholarBadge(
1303     supabase: ReturnType<typeof createClient>,
1304     studentId: string,
1305     existingBadgeIds: Set<string>
1306 ): Promise<string[]> {
1307     const newBadges: string[] = [];
1308
1309     if (existingBadgeIds.has("self_reliant_scholar")) return newBadges;
1310
1311     // Get all courses the student is enrolled in
1312     const { data: enrollments } = await supabase
1313         .from("student_courses")
1314         .select("course_id")
1315         .eq("student_id", studentId)
1316         .eq("status", "active");
1317
1318     if (!enrollments || enrollments.length === 0) return newBadges;
1319
1320     const courseIds = enrollments.map((e: { course_id: string }) => e.course_id);
1321
1322     // For each course, check independence score across all CLOs
1323     for (const courseId of courseIds) {
1324         // Get all CLOs for this course
1325         const { data: clos } = await supabase
1326             .from("learning_outcomes")
1327             .select("id")
1328             .eq("course_id", courseId)
1329             .eq("type", "CLO");
1330
1331         if (!clos || clos.length === 0) continue;
1332
1333         const cloIds = clos.map((c: { id: string }) => c.id);
1334
1335         // Get all submissions for this student
1336         const { data: submissions } = await supabase
1337             .from("submissions")
1338             .select("id, submitted_at")
1339             .eq("student_id", studentId);
1340
1341         if (!submissions || submissions.length === 0) continue;
1342
1343         let allCLOsMeetThreshold = true;
1344
1345         for (const cloId of cloIds) {
1346             // Get tutor conversations scoped to this CLO
1347             const { data: conversations } = await supabase
1348                 .from("tutor_conversations")
1349                 .select("id, updated_at")
1350                 .eq("student_id", studentId)
1351                 .contains("clo_scope", [cloId]);
1352
1353             // Count AI-assisted submissions (within 1 hour of tutor conversation)
1354             let aiAssisted = 0;
1355             const ONE_HOUR_MS = 60 * 60 * 1000;
1356
1357             for (const sub of submissions) {
1358                 const submittedAt = new Date(sub.submitted_at as string).getTime();
1359                 const wasAiAssisted = (conversations ?? []).some(
1360                     (conv: { updated_at: string }) => {

```

```

1361         const convTime = new Date(conv.updated_at).getTime();
1362         const timeDiff = submittedAt - convTime;
1363         return timeDiff >= 0 && timeDiff <= ONE_HOUR_MS;
1364     }
1365     );
1366     if (wasAiAssisted) aiAssisted++;
1367 }
1368
1369 const totalSubmissions = submissions.length;
1370 const independenceScore =
1371     totalSubmissions > 0 ? 1 - aiAssisted / totalSubmissions : 1.0;
1372
1373 // Condition: independence score "e 0.8 across ALL enrolled CLOS
1374 if (independenceScore < 0.8) {
1375     allCLOSMeetThreshold = false;
1376     break;
1377 }
1378 }
1379
1380 if (allCLOSMeetThreshold) {
1381     newBadges.push("self_reliant_scholar");
1382     break; // Only need one qualifying course
1383 }
1384 }
1385
1386 return newBadges;
1387 }
1388
1389 // % % % Peer Milestone Notification for Rare Badges (original) % % % % % % % % % % % % %
1390
1391 const BADGE_DISPLAY_NAMES: Record<string, string> = {
1392     streak_30: "30-Day Legend",
1393     streak_60: "60-Day Legend",
1394     streak_100: "100-Day Legend",
1395     speed_demon: "Speed Demon",
1396     night_owl: "Night Owl",
1397     perfectionist: "Perfectionist",
1398     bloom_explorer: "Bloom's Explorer",
1399     bloom_challenger: "Bloom's Challenger",
1400     bloom_pioneer: "Bloom's Pioneer",
1401     comeback_kid: "Comeback Kid",
1402     rising_star: "Rising Star",
1403 };
1404
1405 // eslint-disable-next-line @typescript-eslint/no-explicit-any
1406 async function notifyPeersOfRareBadge(
1407     supabase: any,
1408     studentId: string,
1409     badgeIds: string[]
1410 ): Promise<void> {
1411     const PEER_MILESTONE_DAILY_LIMIT = 5;
1412
1413     // Check if student is in anonymous leaderboard mode
1414     const { data: profile } = await supabase
1415         .from("profiles")
1416         .select("full_name, leaderboard_anonymous")
1417         .eq("id", studentId)
1418         .maybeSingle();
1419
1420     if (!profile || profile.leadboard_anonymous) return;
1421
1422     const studentName = profile.full_name ?? "A classmate";
1423
1424     // Find peer students in shared courses
1425     const { data: enrollments } = await supabase
1426         .from("student_courses")
1427         .select("course_id")
1428         .eq("student_id", studentId);
1429
1430     if (!enrollments || enrollments.length === 0) return;
1431
1432     const courseIds = enrollments.map((e: { course_id: string }) => e.course_id);
1433
1434     const { data: peerEnrollments } = await supabase
1435         .from("student_courses")
1436         .select("student_id")
1437         .in("course_id", courseIds)
1438         .neq("student_id", studentId);
1439
1440     if (!peerEnrollments || peerEnrollments.length === 0) return;
1441
1442     const peerIds = [
1443         ...new Set(
1444             peerEnrollments.map((e: { student_id: string }) => e.student_id)
1445         ),
1446     ];
1447
1448     // Rate-limit: fetch recent peer_milestone counts per peer in the last 24h
1449     const twentyFourHoursAgo = new Date(
1450         Date.now() - 24 * 60 * 60 * 1000
1451     ).toISOString();
1452     const { data: recentNotifications } = await supabase
1453         .from("notifications")
1454         .select("user_id")
1455         .in("user_id", peerIds)
1456         .eq("type", "peer_milestone")
1457         .gte("created_at", twentyFourHoursAgo);
1458
1459     const peerDailyCounts = new Map<string, number>();
1460     if (recentNotifications) {
1461         for (const n of recentNotifications) {
1462             const uid = n.user_id as string;
1463             peerDailyCounts.set(uid, (peerDailyCounts.get(uid) ?? 0) + 1);
1464         }
1465     }

```

[illegible]

[illegible]

[illegible]


```

1777 | // team-scope rows.
1778 |
1779 | const { data: existingBadges, error: fetchErr } = await supabase
1780 |   .from("badges")
1781 |   .select("badge_key")
1782 |   .eq("student_id", student_id)
1783 |   .eq("scope", "individual");
1784 |
1785 | if (fetchErr) {
1786 |   console.error("Failed to fetch existing badges:", fetchErr.message);
1787 |   return new Response(
1788 |     JSON.stringify({
1789 |       error: "Failed to fetch existing badges",
1790 |       detail: fetchErr.message,
1791 |     }),
1792 |     {
1793 |       status: 500,
1794 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
1795 |     }
1796 |   );
1797 | }
1798 |
1799 | const existingBadgeIds = new Set(
1800 |   (existingBadges ?? []).map((b: { badge_key: string }) => b.badge_key)
1801 | );
1802 |
1803 | // Badge display metadata (name/emoji/category) is sourced from the
1804 | // institution's `badge_definitions` rows so the award path is
1805 | // definition-driven. Look up the student's institution once, then load its
1806 | // definitions into a key!`{name,emoji,category}` map (fallbacks applied per
1807 | // badge below if a definition is missing).
1808 | const badgeMetaByKey = new Map<
1809 |   string,
1810 |   { name: string; emoji: string; category: string | null }
1811 | >();
1812 | {
1813 |   const { data: studentProfile } = await supabase
1814 |     .from("profiles")
1815 |     .select("institution_id")
1816 |     .eq("id", student_id)
1817 |     .maybeSingle();
1818 |   const studentInstitutionId =
1819 |     (studentProfile as { institution_id?: string } | null)
1820 |     ?.institution_id ?? null;
1821 |   if (studentInstitutionId) {
1822 |     const { data: defs } = await supabase
1823 |       .from("badge_definitions")
1824 |       .select("badge_key, name, emoji, category")
1825 |       .eq("institution_id", studentInstitutionId);
1826 |     for (const d of (defs ?? []) as Array<{
1827 |       badge_key: string;
1828 |       name: string;
1829 |       emoji: string;
1830 |       category: string | null;
1831 |     }>) {
1832 |       badgeMetaByKey.set(d.badge_key, {
1833 |         name: d.name,
1834 |         emoji: d.emoji,
1835 |         category: d.category,
1836 |       });
1837 |     }
1838 |   }
1839 | }
1840 |
1841 | // % % Step 2: Check badge conditions based on trigger % % % % % % % % % % % %
1842 |
1843 | const newBadgeIds: string[] = [];
1844 |
1845 | // Streak badges – check on streak_update or xp_award
1846 | if (trigger === "streak_update" || trigger === "xp_award") {
1847 |   const streakBadges = await checkStreakBadges(
1848 |     supabase,
1849 |     student_id,
1850 |     existingBadgeIds
1851 |   );
1852 |   newBadgeIds.push(...streakBadges);
1853 | }
1854 |
1855 | // Academic badges – check on submission, grade
1856 | if (trigger === "submission" || trigger === "grade") {
1857 |   const academicBadges = await checkAcademicBadges(
1858 |     supabase,
1859 |     student_id,
1860 |     existingBadgeIds
1861 |   );
1862 |   newBadgeIds.push(...academicBadges);
1863 | }
1864 |
1865 | // Engagement badges – check on journal, xp_award
1866 | if (trigger === "journal" || trigger === "xp_award") {
1867 |   const engagementBadges = await checkEngagementBadges(
1868 |     supabase,
1869 |     student_id,
1870 |     existingBadgeIds
1871 |   );
1872 |   newBadgeIds.push(...engagementBadges);
1873 | }
1874 |
1875 | // Habit badges – check on habit_log trigger
1876 | if (trigger === "habit_log") {
1877 |   const habitBadges = await checkHabitBadges(
1878 |     supabase,
1879 |     student_id,
1880 |     existingBadgeIds

```

```

1881 |     );
1882 |     newBadgeIds.push(...habitBadges);
1883 | }
1884 |
1885 | // Mystery badges – always check on any trigger
1886 | const mysteryBadges = await checkMysteryBadges(
1887 |     supabase,
1888 |     student_id,
1889 |     existingBadgeIds
1890 | );
1891 | newBadgeIds.push(...mysteryBadges);
1892 |
1893 | // Bloom's progression badges – check on grade or submission (quiz attempt completion)
1894 | if (trigger === "grade" || trigger === "submission") {
1895 |     const bloomsBadges = await checkBloomsBadges(
1896 |         supabase,
1897 |         student_id,
1898 |         existingBadgeIds
1899 |     );
1900 |     newBadgeIds.push(...bloomsBadges);
1901 | }
1902 |
1903 | // Comeback Kid badge – check on xp_award (improvement bonus triggers xp_award)
1904 | if (trigger === "xp_award") {
1905 |     const comebackKidBadges = await checkComebackKidBadge(
1906 |         supabase,
1907 |         student_id,
1908 |         existingBadgeIds
1909 |     );
1910 |     newBadgeIds.push(...comebackKidBadges);
1911 |
1912 |     // Rising Star badge – check on xp_award (top 3 Most Improved for 2 consecutive weeks)
1913 |     const risingStarBadges = await checkRisingStarBadge(
1914 |         supabase,
1915 |         student_id,
1916 |         existingBadgeIds
1917 |     );
1918 |     newBadgeIds.push(...risingStarBadges);
1919 | }
1920 |
1921 | // Study badges – check on study_session trigger
1922 | if (trigger === "study_session") {
1923 |     const studyBadges = await checkStudyBadges(
1924 |         supabase,
1925 |         student_id,
1926 |         existingBadgeIds
1927 |     );
1928 |     newBadgeIds.push(...studyBadges);
1929 | }
1930 |
1931 | // Self-Reliant Scholar badge – check on submission trigger (Requirement 29)
1932 | if (trigger === "submission" || trigger === "grade") {
1933 |     const selfReliantBadges = await checkSelfReliantScholarBadge(
1934 |         supabase,
1935 |         student_id,
1936 |         existingBadgeIds
1937 |     );
1938 |     newBadgeIds.push(...selfReliantBadges);
1939 | }
1940 |
1941 | // % % Step 2b: Check team badges if team_event trigger % % % % % % % % % % % % % % % % % %
1942 |
1943 | let teamBadgesAwarded: string[] = [];
1944 |
1945 | if (trigger === "team_event" && team_id) {
1946 |     // Fetch existing team badges
1947 |     const { data: existingTeamBadges } = await supabase
1948 |         .from("badges")
1949 |         .select("badge_key")
1950 |         .eq("team_id", team_id)
1951 |         .eq("scope", "team");
1952 |
1953 |     const existingTeamBadgeIds = new Set(
1954 |         (existingTeamBadges ?? []).map(
1955 |             (b: { badge_key: string }) => b.badge_key
1956 |         )
1957 |     );
1958 |
1959 |     const newTeamBadgeIds = await checkTeamBadges(
1960 |         supabase,
1961 |         team_id,
1962 |         existingTeamBadgeIds
1963 |     );
1964 |
1965 |     if (newTeamBadgeIds.length > 0) {
1966 |         teamBadgesAwarded = await awardTeamBadges(
1967 |             supabase,
1968 |             team_id,
1969 |             newTeamBadgeIds
1970 |         );
1971 |     }
1972 | }
1973 |
1974 | // % % Step 3: Insert new badges idempotently % % % % % % % % % % % % % % % % % %
1975 |
1976 | const awardedBadges: string[] = [];
1977 |
1978 | for (const badgeId of newBadgeIds) {
1979 |     const meta = badgeMetaByKey.get(badgeId);
1980 |     const { error: insertErr } = await supabase
1981 |         .from("badges")
1982 |         .insert({
1983 |             student_id,
1984 |             badge_key: badgeId,

```

```

1985         badge_name: meta?.name ?? badgeId,
1986         emoji: meta?.emoji ?? "0x3A",
1987         category: meta?.category ?? null,
1988         scope: "individual",
1989         awarded_at: new Date().toISOString(),
1990     })
1991     .select()
1992     .maybeSingle();
1993
1994     // If insert fails due to unique constraint, badge already exists – skip
1995     if (insertErr) {
1996         if (insertErr.code === "23505") {
1997             // Unique violation – idempotent, badge already awarded
1998             continue;
1999         }
2000         console.error(`Failed to insert badge ${badgeId}:`, insertErr.message);
2001         continue;
2002     }
2003
2004     awardedBadges.push(badgeId);
2005
2006     // Award badge XP
2007     const xpReward = BADGE_XP[badgeId] ?? 0;
2008     if (xpReward > 0) {
2009         await awardXp({
2010             student_id,
2011             xp_amount: xpReward,
2012             source: "badge",
2013             reference_id: badgeId,
2014             note: `Badge earned: ${badgeId}`,
2015         });
2016     }
2017 }
2018
2019 // % % Step 3b: Check tiered badge progression (Requirement 133) % % % % %
2020
2021 let tierUpgrades: Array<{
2022     category: string;
2023     oldTier: BadgeTier | null;
2024     newTier: BadgeTier;
2025 }> = [];
2026 try {
2027     tierUpgrades = await checkAndUpgradeBadgeTiers(supabase, student_id);
2028
2029     // Award XP for tier upgrades
2030     for (const upgrade of tierUpgrades) {
2031         const tierXP =
2032             upgrade.newTier === "gold"
2033                 ? 100
2034                 : upgrade.newTier === "silver"
2035                     ? 75
2036                     : 50;
2037         await awardXp({
2038             student_id,
2039             xp_amount: tierXP,
2040             source: "badge",
2041             reference_id: `tier_upgrade:${upgrade.category}:${upgrade.newTier}`,
2042             note: `Badge tier upgrade: ${upgrade.category} !' ${upgrade.newTier}`,
2043         });
2044     }
2045 } catch (tierErr) {
2046     console.error("Tiered badge check failed (non-blocking):", tierErr);
2047 }
2048
2049 // % % Step 4: Notify peers of rare badge awards % % % % % % % % % % % % % % %
2050
2051 const RARE_BADGES = new Set([
2052     "streak_30",
2053     "streak_60",
2054     "streak_100",
2055     "speed_demon",
2056     "night_owl",
2057     "perfectionist",
2058     "bloom_explorer",
2059     "bloom_challenger",
2060     "bloom_pioneer",
2061     "rising_star",
2062 ]);
2063
2064 const rareBadgesAwarded = awardedBadges.filter((b) => RARE_BADGES.has(b));
2065 if (rareBadgesAwarded.length > 0) {
2066     notifyPeersOfRareBadge(supabase, student_id, rareBadgesAwarded).catch(
2067         (err) => {
2068             console.error("Peer badge notification failed:", err);
2069         }
2070     );
2071 }
2072
2073 // % % Step 5: Get total badge count % % % % % % % % % % % % % % % % % % % % %
2074
2075 const totalBadges = existingBadgeIds.size + awardedBadges.length;
2076
2077 // % % Response % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %
2078
2079 return new Response(
2080     JSON.stringify({
2081         success: true,
2082         new_badges: awardedBadges,
2083         total_badges: totalBadges,
2084         team_badges_awarded: teamBadgesAwarded,
2085         tier_upgrades: tierUpgrades,
2086     }),
2087     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
2088 );

```

```

2089 | } catch (error) {
2090 |   return new Response(JSON.stringify({ error: (error as Error).message })), {
2091 |     status: 500,
2092 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
2093 |   });
2094 | }
2095 | });
2096 |

```

FILE: [supabase/functions/check-bonus-question/index.ts](#)

TYPE: .ts | LINES: 1-231 | SHA256: 98dd8553f77c6a430a70de0716974d2f825f6d54d9da54c3f6a3fe76df18bfab

```

1 | // =====
2 | // Edge Function: check-bonus-question
3 | // Bonus question trigger and validation
4 | // Tasks 19.2.1-19.2.3
5 | // =====
6 |
7 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
8 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
9 | import {
10 |   authenticateRequest,
11 |   unauthorizedResponse,
12 |   forbiddenResponse,
13 | } from "../_shared/auth.ts";
14 |
15 | const corsHeaders = {
16 |   "Access-Control-Allow-Origin": "*",
17 |   "Access-Control-Allow-Headers":
18 |     "authorization, x-client-info, apikey, content-type",
19 | };
20 |
21 | const DEFAULT_BONUS_PROBABILITY = 15; // 15% default
22 | const BONUS_XP_REWARD = 25;
23 |
24 | serve(async (req) => {
25 |   if (req.method === "OPTIONS") {
26 |     return new Response("ok", { headers: corsHeaders });
27 |   }
28 |
29 |   try {
30 |     // Caller check (Req 18): require a valid JWT. This function bypasses RLS via
31 |     // the service-role client below, so we must authorize the caller in-handler.
32 |     const auth = await authenticateRequest(req);
33 |     if (!auth.user) {
34 |       return unauthorizedResponse(auth.error ?? "Unauthorized");
35 |     }
36 |
37 |     const supabase = createClient(
38 |       Deno.env.get("SUPABASE_URL")!,
39 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
40 |     );
41 |
42 |     const body = await req.json();
43 |     const { student_id, institution_id, course_id, action } = body;
44 |
45 |     if (!student_id || !institution_id) {
46 |       return new Response(
47 |         JSON.stringify({ error: "student_id and institution_id are required" }),
48 |         {
49 |           status: 400,
50 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
51 |         }
52 |       );
53 |     }
54 |
55 |     // Ownership: a student may only trigger/answer their OWN bonus question
56 |     // (it awards XP to student_id). Admins may act on any student in their
57 |     // institution for support. Cross-tenant access is always denied.
58 |     const isAdmin = auth.user.role === "admin";
59 |     if (!isAdmin && auth.user.id !== student_id) {
60 |       return forbiddenResponse(
61 |         "Forbidden: cannot act on behalf of another student"
62 |       );
63 |     }
64 |     if (!isAdmin && auth.user.institution_id !== institution_id) {
65 |       return forbiddenResponse("Forbidden: institution mismatch");
66 |     }
67 |
68 |     // % % Action: trigger – Check if a bonus question should appear % % % % %
69 |     if (action === "trigger" || !action) {
70 |       // Task 19.2.1: Probability check (configurable 5-30%)
71 |       const { data: settings } = await supabase
72 |         .from("institution_settings")
73 |         .select("*")
74 |         .eq("institution_id", institution_id)
75 |         .maybeSingle();
76 |
77 |       const rawSettings = settings as Record<string, unknown> | null;
78 |       let probability = DEFAULT_BONUS_PROBABILITY;
79 |       if (rawSettings?.bonus_question_probability) {
80 |         const configured = rawSettings.bonus_question_probability as number;
81 |         probability = Math.max(5, Math.min(30, configured));
82 |       }
83 |
84 |       // Roll the dice
85 |       const roll = Math.random() * 100;
86 |       if (roll >= probability) {
87 |         return new Response(JSON.stringify({ triggered: false })), {
88 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
89 |         };
90 |       }
91 |
92 |       // Task 19.2.2: CLO-relevant question selection

```

```

93 | // Find a CLO from the student's active courses to generate a relevant question
94 | let selectedCloId: string | null = null;
95 | let questionText =
96 |   "What is the key concept you learned in your most recent study session?";
97 | let questionType = "open_ended";
98 |
99 | if (course_id) {
100 |   const { data: clos } = await supabase
101 |     .from("learning_outcomes")
102 |     .select("id, title")
103 |     .eq("course_id", course_id)
104 |     .eq("type", "clo")
105 |     .limit(10);
106 |
107 |   if (clos && clos.length > 0) {
108 |     const randomClo = clos[Math.floor(Math.random() * clos.length)];
109 |     if (randomClo) {
110 |       selectedCloId = randomClo.id;
111 |       questionText = `Quick check: Can you explain the concept related to "${randomClo.title}"`;
112 |       questionType = "clo_related";
113 |     }
114 |   }
115 | }
116 |
117 | return new Response(
118 |   JSON.stringify({
119 |     triggered: true,
120 |     question: {
121 |       text: questionText,
122 |       type: questionType,
123 |       clo_id: selectedCloId,
124 |       time_limit_seconds: 30,
125 |       xp_reward: BONUS_XP_REWARD,
126 |     },
127 |   }),
128 |   {
129 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
130 |   }
131 | );
132 | }
133 |
134 | // %% Action: answer – Validate answer and award surprise XP % % % % % % % % % %
135 | if (action === "answer") {
136 |   const { answer, clo_id } = body;
137 |
138 |   if (!answer || typeof answer !== "string" || answer.trim().length < 3) {
139 |     return new Response(
140 |       JSON.stringify({
141 |         correct: false,
142 |         xp_awarded: 0,
143 |         feedback: "Answer too short. Try to provide more detail next time!",
144 |       }),
145 |       {
146 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
147 |       }
148 |     );
149 |   }
150 | }
151 |
152 | // Task 19.2.3: Answer validation and surprise XP award
153 | // For open-ended questions, any substantive answer (>10 chars) earns XP
154 | const isSubstantive = answer.trim().length >= 10;
155 |
156 | if (isSubstantive) {
157 |   // Award surprise XP via xp_transactions
158 |   const referenceId = `bonus_question:${student_id}:${Date.now()}`;
159 |
160 |   const { error: xpErr } = await supabase.from("xp_transactions").insert({
161 |     student_id,
162 |     xp_amount: BONUS_XP_REWARD,
163 |     source: "bonus_event",
164 |     reference_id: referenceId,
165 |     note: "Bonus question reward",
166 |     base_xp: BONUS_XP_REWARD,
167 |     final_xp: BONUS_XP_REWARD,
168 |     multipliers: { bonus_question: true },
169 |   });
170 |
171 |   if (xpErr) {
172 |     console.error("Bonus question XP award failed:", xpErr.message);
173 |   }
174 |
175 |   // Update xp_total in student_gamification
176 |   const { data: sumResult } = await supabase
177 |     .from("xp_transactions")
178 |     .select("xp_amount")
179 |     .eq("student_id", student_id);
180 |
181 |   const newTotal = (sumResult ?? []).reduce(
182 |     (sum: number, row: { xp_amount: number }) => sum + row.xp_amount,
183 |     0
184 |   );
185 |
186 |   await supabase
187 |     .from("student_gamification")
188 |     .upsert(
189 |       { student_id, xp_total: newTotal },
190 |       { onConflict: "student_id" }
191 |     );
192 |
193 |   return new Response(
194 |     JSON.stringify({
195 |       correct: true,
196 |       xp_awarded: BONUS_XP_REWARD,
197 |       feedback: "Great answer! You earned bonus XP!",

```

```

197     }},
198     {
199         headers: { ...corsHeaders, "Content-Type": "application/json" },
200     }
201 );
202
203
204 return new Response(
205     JSON.stringify({
206         correct: false,
207         xp_awarded: 0,
208         feedback:
209             "Good try! Provide a more detailed answer next time for bonus XP.",
210     }),
211     {
212         headers: { ...corsHeaders, "Content-Type": "application/json" },
213     }
214 );
215
216
217 return new Response(
218     JSON.stringify({ error: "Invalid action. Use 'trigger' or 'answer'." })), {
219     {
220         status: 400,
221         headers: { ...corsHeaders, "Content-Type": "application/json" },
222     }
223 );
224 } catch (error) {
225     return new Response(JSON.stringify({ error: (error as Error).message })), {
226         status: 500,
227         headers: { ...corsHeaders, "Content-Type": "application/json" },
228     });
229 }
230 });
231

```

FILE: supabase/functions/check-login-rate/index.ts

```
TYPE: .ts | LINES: 1-321 | SHA256: 7792f7c599be7d3e3ca67266d46f54b17247f158a2ddab5160e4eefffc1de403
```

[illegible]

[illegible]

[illegible]


```

274   const adminClient = createClient(
275     Deno.env.get("SUPABASE_URL")!,
276     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
277   );
278   const { data: callerProfile } = await adminClient
279     .from("profiles")
280     .select("role")
281     .eq("id", user.id)
282     .maybeSingle();
283   const role =
284     (callerProfile?.role as string) ??
285     user.app_metadata?.role ??
286     user.user_metadata?.role ??
287     "";
288   if (role !== "admin") {
289     return jsonResponse(
290       {
291         error:
292           "Forbidden: admin role required to clear another account",
293       },
294       403
295     );
296   }
297 }
298 }
299 }
300
301 switch (action) {
302   case "check":
303     return await handleCheck(supabase, email);
304   case "record_failure":
305     return await handleRecordFailure(supabase, email);
306   case "clear":
307     return await handleClear(supabase, email);
308   default:
309     return jsonResponse(
310       { error: `Unknown action: ${action as string}` },
311       400
312     );
313 }
314 } catch (error) {
315   return new Response(JSON.stringify({ error: (error as Error).message }), {
316     status: 500,
317     headers: { ...corsHeaders, "Content-Type": "application/json" },
318   });
319 }
320 });
321

```

FILE: supabase/functions/compute-at-risk-signals/index.ts

TYPE: .ts | LINES: 1-327 | SHA256: b46c63a2a1c5cb67e56df411b1e1d61ed8bf343452842fe4d0d8141f89efe654

[illegible]

[illegible]

[illegible]

[illegible]

FILE: supabase/functions/compute-habit-correlations/index.ts

TYPE: .ts | LINES: 1-450 | SHA256: 4ea183b9f516521a6d961fa3b523505c636722002b17b3d5db448221e85e4525

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

FILE: supabase/functions/coordinator-ai-insights/index.ts

TYPE: .ts | LINES: 1-446 | SHA256: 775d9161e5485cf253b93c91b13e75fa7d1db27cd43b99c04cea8cd82d64352b

```

1 // =====
2 // coordinator-ai-insights - AI attainment insights for coordinators
3 // =====
4 //
5 // Generates an outcome-attainment insight for the caller's institution:
6 // 1. Reads REAL data (learning_outcomes + outcome_attainment + outcome_mappings
7 //   + institution_settings), all institution-scoped.
8 // 2. Computes a rule-based insight (mean attainment, below-target PLOs, weakest
9 //   contributing CLO, prioritized recommendations) - this ALWAYS works and is
10 //   genuinely useful with no LLM (mirrors the ai-feedback-draft template
11 //   approach).
12 // 3. If GEMINI_API_KEY is configured, ENHANCES the narrative + recommendations
13 //   with a Gemini call (non-streaming). On any LLM error it falls back to the
14 //   computed insight (never fails the request).
15 // 4. Caches the payload in coordinator_ai_insights (service role) so repeat
16 //   views are a cache hit; `refresh: true` forces regeneration.
17 //
18 // Auth: JWT-validated; role + institution resolved from profiles (app_metadata
19 //   is empty on this project - mirrors _shared/auth.ts + ai-feedback-draft).
20 // Only coordinator/admin may call. Deploy with verify_jwt = true.
21 // =====
22
23 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
24 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
25
26 const corsHeaders = {
27   "Access-Control-Allow-Origin": "*",
28   "Access-Control-Allow-Headers":
29     "authorization, x-client-info, apikey, content-type",
30 };
31
32 const DEFAULT_SUCCESS_THRESHOLD = 70;
33 const CACHE_TTL_MS = 6 * 60 * 60 * 1000; // 6 hours
34
35 interface OutcomeRow {
36   id: string;
37   type: string;
38   title: string;
39   course_id: string | null;
40 }
41 interface AttRow {
42   outcome_id: string;
43   attainment_percent: number | null;
44 }
45 interface MapRow {
46   source_outcome_id: string;
47   target_outcome_id: string;
48 }
49
50 interface InsightPayload {
51   threshold: number;
52   ploCount: number;
53   avgAttainment: number | null;
54   belowTargetCount: number;
55   weakest: {
56     ploTitle: string;
57     cloTitle: string | null;
58     attainment: number;
59   } | null;
60   narrative: string;
61   recommendations: string[];
62 }
63
64 const json = (body: unknown, status = 200): Response =>
65   new Response(JSON.stringify(body), {
66     status,
67     headers: { ...corsHeaders, "Content-Type": "application/json" },
68   });
69
70 const mean = (nums: number[]): number | null =>
71   nums.length === 0
72     ? null
73     : Math.round(nums.reduce((s, n) => s + n, 0) / nums.length);
74
75 // % % % Rule-based insight (always available, no LLM) % % % % % % % % % % % % % % % % % %
76
77 function computeInsight(
78   outcomes: OutcomeRow[],
79   att: AttRow[],
80   mappings: MapRow[],
81   threshold: number
82 ): InsightPayload {
83   // Mean attainment per outcome.
84   const byOutcome = new Map<string, number[]>();
85   for (const r of att) {
86     if (r.attainment_percent == null) continue;
87     const list = byOutcome.get(r.outcome_id) ?? [];
88     list.push(r.attainment_percent);
89     byOutcome.set(r.outcome_id, list);
90   }
91   const meanOf = (id: string): number | null => {
92     const list = byOutcome.get(id);
93     return list && list.length > 0 ? mean(list) : null;
94   };
95
96   const byId = new Map<string, OutcomeRow>(outcomes.map((o) => [o.id, o]));
97   // Undirected adjacency: outcome_mappings are stored child!'parent for some
98   // pairs (CLO!'PLO) and parent!'child for others, so resolve related CLOs by
99   // outcome TYPE rather than edge direction.

```

```

100 | const relatedOf = new Map<string, Set<string>>();
101 | const addEdge = (a: string, b: string) => {
102 |   const set = relatedOf.get(a) ?? new Set<string>();
103 |   set.add(b);
104 |   relatedOf.set(a, set);
105 | };
106 | for (const m of mappings) {
107 |   addEdge(m.source_outcome_id, m.target_outcome_id);
108 |   addEdge(m.target_outcome_id, m.source_outcome_id);
109 | }
110 |
111 | const plos = outcomes.filter((o) => o.type === "PLO");
112 | const ploAttainments: { title: string; attainment: number; id: string }[] =
113 |   [];
114 | for (const plo of plos) {
115 |   const a = meanOf(plo.id);
116 |   if (a != null)
117 |     ploAttainments.push({ id: plo.id, title: plo.title, attainment: a });
118 | }
119 |
120 | const avgAttainment = mean(ploAttainments.map((p) => p.attainment));
121 | const belowTarget = ploAttainments
122 |   .filter((p) => p.attainment < threshold)
123 |   .sort((a, b) => a.attainment - b.attainment);
124 |
125 | // Weakest contributing CLO of the weakest below-target PLO (or overall weakest PLO).
126 | const focusPlo =
127 |   belowTarget[0] ??
128 |   [...ploAttainments].sort((a, b) => a.attainment - b.attainment)[0] ??
129 |   null;
130 | let weakest: InsightPayload["weakest"] = null;
131 | if (focusPlo) {
132 |   const cloIds = Array.from(relatedOf.get(focusPlo.id) ?? []).filter(
133 |     (id) => byId.get(id)?.type === "CLO"
134 |   );
135 |   let weakClo: { title: string; attainment: number } | null = null;
136 |   for (const cid of cloIds) {
137 |     const a = meanOf(cid);
138 |     if (a == null) continue;
139 |     if (!weakClo || a < weakClo.attainment) {
140 |       weakClo = { title: byId.get(cid)?.title ?? cid, attainment: a };
141 |     }
142 |   }
143 |   weakest = {
144 |     ploTitle: focusPlo.title,
145 |     cloTitle: weakClo?.title ?? null,
146 |     attainment: weakClo?.attainment ?? focusPlo.attainment,
147 |   };
148 | }
149 |
150 | // Narrative + recommendations (computed).
151 | const narrativeParts: string[] = [];
152 | if (avgAttainment != null) {
153 |   narrativeParts.push(
154 |     `Across ${ploAttainments.length} measured program outcomes, mean attainment is ${avgAttainment}%.`
155 |   );
156 | }
157 | if (belowTarget.length > 0) {
158 |   narrativeParts.push(
159 |     `${belowTarget.length} outcome${
160 |       belowTarget.length === 1 ? " is" : "s are"
161 |     } below the ${threshold}% target.`
162 |   );
163 |   if (weakest) {
164 |     narrativeParts.push(
165 |       weakest.cloTitle
166 |       ? `The weakest contributing area is "${weakest.cloTitle}" (${weakest.attainment}%) within "${weakest
167 |         .ploTitle}"`
168 |       : `The lowest outcome is "${weakest.ploTitle}" (${weakest.attainment}%).`
169 |     );
170 |   }
171 | } else {
172 |   narrativeParts.push(`All measured outcomes meet the ${threshold}% target.`);
173 | }
174 |
175 | const recommendations: string[] = [];
176 | if (belowTarget.length > 0 && weakest) {
177 |   recommendations.push(
178 |     weakest.cloTitle
179 |     ? `Draft a CQI plan for "${weakest.ploTitle}" targeting "${weakest.cloTitle}."`
180 |     : `Draft a CQI plan to raise "${weakest.ploTitle}" above ${threshold}%.`
181 |   );
182 |   recommendations.push(
183 |     "Review assessment alignment and remediation for outcomes below target."
184 |   );
185 | } else {
186 |   recommendations.push(
187 |     "Outcomes are on track – focus on moving satisfactory outcomes toward excellent ("e85%).".
188 |   );
189 | }
190 | recommendations.push(
191 |   "Confirm evidence coverage before the next accreditation review."
192 | );
193 |
194 | return {
195 |   threshold,
196 |   ploCount: ploAttainments.length,
197 |   avgAttainment,
198 |   belowTargetCount: belowTarget.length,
199 |   weakest,
200 |   narrative: narrativeParts.join(" "),
201 |   recommendations,
202 | };
203 |

```

[illegible]

```

308     .maybeSingle();
309     const role =
310       (callerProfile?.role as string) ?? caller.app_metadata?.role ?? "";
311     const institutionId =
312       (callerProfile?.institution_id as string) ??
313       caller.app_metadata?.institution_id ??
314       "";
315     if (!["coordinator", "admin"].includes(role)) {
316       return json(
317         { error: "Forbidden: coordinator or admin role required" },
318         403
319       );
320     }
321     if (!institutionId)
322       return json({ error: "No institution for caller" }, 400);
323
324     let body: { kind?: string; refresh?: boolean } = {};
325     try {
326       body = (await req.json()) as typeof body;
327     } catch {}
328     // empty body is fine - defaults apply
329   }
330   const kind = "attainment";
331   const scopeKey = "institution";
332   const refresh = body.refresh === true;
333
334   // %% Cache check %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
335   if (!refresh) {
336     const { data: cached } = await admin
337       .from("coordinator_ai_insights")
338       .select("payload, source, model, generated_at")
339       .eq("institution_id", institutionId)
340       .eq("kind", kind)
341       .eq("scope_key", scopeKey)
342       .order("generated_at", { ascending: false })
343       .limit(1)
344       .maybeSingle();
345     if (
346       cached &&
347       Date.now() - new Date(cached.generated_at as string).getTime() <
348       CACHE_TTL_MS
349     ) {
350       return json({
351         ...(cached.payload as InsightPayload),
352         source: cached.source,
353         model: cached.model,
354         generatedAt: cached.generated_at,
355         cached: true,
356       });
357     }
358   }
359
360   // %% Fetch real institution-scoped data %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
361   const { data: outcomesData, error: outErr } = await admin
362     .from("learning_outcomes")
363     .select("id, type, title, course_id")
364     .eq("institution_id", institutionId);
365   if (outErr) return json({ error: outErr.message }, 500);
366   const outcomes = (outcomesData ?? []) as OutcomeRow[];
367   const outcomeIds = outcomes.map((o) => o.id);
368
369   let att: AttRow[] = [];
370   let mappings: MapRow[] = [];
371   if (outcomeIds.length > 0) {
372     const [{ data: attData }, { data: mapData }] = await Promise.all([
373       admin
374         .from("outcome_attainment")
375         .select("outcome_id, attainment_percent")
376         .in("outcome_id", outcomeIds),
377       admin
378         .from("outcome_mappings")
379         .select("source_outcome_id, target_outcome_id")
380         .in("source_outcome_id", outcomeIds),
381     ]);
382     att = (attData ?? []) as AttRow[];
383     mappings = (mapData ?? []) as MapRow[];
384   }
385
386   const { data: settings } = await admin
387     .from("institution_settings")
388     .select("success_threshold")
389     .eq("institution_id", institutionId)
390     .maybeSingle();
391   const threshold =
392     (settings?.success_threshold as number | undefined) ??
393     DEFAULT_SUCCESS_THRESHOLD;
394
395   // %% Compute + optionally enhance %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
396   const base = computeInsight(outcomes, att, mappings, threshold);
397   let payload: InsightPayload = base;
398   let source = "computed";
399   let model: string | null = null;
400
401   const geminiKey = Deno.env.get("GEMINI_API_KEY");
402   if (geminiKey) {
403     const geminiModel =
404       Deno.env.get("COORDINATOR_INSIGHTS_MODEL") ?? "gemini-2.0-flash";
405     try {
406       const enhanced = await enhanceWithGemini(base, geminiKey, geminiModel);
407       if (enhanced) {
408         payload = { ...base, ...enhanced };
409         source = "ai";
410         model = geminiModel;
411       }
412     }

```

[illegible]

FILE: supabase/functions/cgi-review-reminder/index.ts

```
TYPE: .ts | LINES: 1-84 | SHA256: cd578e6baf38ed96d4cc4668ca9a19e3dd6ff4971bb45aa8962687256a827f51
```

```

1 // cqi-review-reminder - pg_cron Edge Function (runs Mon 09:00 UTC)
2 // Emits cqi_plan_review_due notifications to coordinators 7 days before next_review_date
3 // Task 102 - UI Consistency Global Fixes
4
5 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
6 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
7
8 const corsHeaders = {
9   "Access-Control-Allow-Origin": "*",
10  "Access-Control-Allow-Headers":
11    "authorization, x-client-info, apikey, content-type",
12 };
13
14 serve(async (req) => {
15   if (req.method === "OPTIONS")
16     return new Response("ok", { headers: corsHeaders });
17
18   try {
19     const supabase = createClient(
20       Deno.env.get("SUPABASE_URL")!,
21       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
22     );
23
24     const sevenDaysFromNow = new Date();
25     sevenDaysFromNow.setDate(sevenDaysFromNow.getDate() + 7);
26     const targetDate = sevenDaysFromNow.toISOString().split("T")[0];
27
28     // Find CQI plans due for review in 7 days
29     const { data: plans, error } = await supabase
30       .from("cqi_action_plans")
31       .select("id, program_id, action_description, next_review_date")
32       .eq("next_review_date", targetDate)
33       .in("status", ["planned", "in_progress"]);
34
35     if (error) throw error;
36
37     let notified = 0;
38
39     for (const plan of plans ?? []) {
40       // Find coordinator for the program
41       const { data: program } = await supabase
42         .from("programs")
43         .select("coordinator_id")
44         .eq("id", plan.program_id)
45         .maybeSingle();
46
47       if (!program?.coordinator_id) continue;
48
49       // Dedup: skip if already notified today
50       const { count } = await supabase
51         .from("notifications")
52         .select("id", { count: "exact", head: true })
53         .eq("user_id", program.coordinator_id)
54         .eq("type", "cqi_plan_review_due")
55         .contains("metadata", { cqi_plan_id: plan.id })
56         .gte("created_at", new Date().toISOString().split("T")[0]);
57
58       if ((count ?? 0) > 0) continue;
59
60       await supabase.from("notifications").insert({
61         user_id: program.coordinator_id,
62         type: "cqi_plan_review_due",
63         title: "CQI plan review due in 7 days",
64         body: `Review due: ${
65           plan.action_description?.slice(0, 80) ?? "CQI action plan"
66         }`
67       });
68     }
69   }
70 });

```


[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

```

706 `Embedding count mismatch: got ${autoEmbeddings.length} embeddings for ${autoChunks.length} chunks`;
707 };
708 }
709
710 // Insert chunks
711 const autoInsertRows = autoChunks.map((chunk, index) => ({
712   institution_id: autoInstitutionId,
713   course_id: autoReq.course_id,
714   chunk_text: chunk.text,
715   embedding: JSON.stringify(autoEmbeddings[index]),
716   source_filename: autoReq.source_filename,
717   material_type: autoReq.material_type,
718   clo_ids: autoReq.clo_ids ?? [],
719   bloom_level: autoReq.bloom_level ?? null,
720   chunk_index: index,
721   token_count: chunk.token_count_estimate,
722   source_material_id: autoReq.source_material_id ?? null,
723   indexing_status: "indexed",
724 }));
725
726 const AUTO_INSERT_BATCH_SIZE = 50;
727 for (let i = 0; i < autoInsertRows.length; i += AUTO_INSERT_BATCH_SIZE) {
728   const batch = autoInsertRows.slice(i, i + AUTO_INSERT_BATCH_SIZE);
729   const { error: insertError } = await supabase
730     .from("course_material_embeddings")
731     .insert(batch);
732
733   if (insertError) {
734     throw new Error(
735       `Failed to insert auto-index chunks: ${insertError.message}`
736     );
737   }
738 }
739
740 return new Response(
741   JSON.stringify({
742     success: true,
743     chunks_created: autoChunks.length,
744     source_filename: autoReq.source_filename,
745     material_type: autoReq.material_type,
746     auto_indexed: true,
747   }),
748   {
749     status: 200,
750     headers: { ...corsHeaders, "Content-Type": "application/json" },
751   }
752 );
753 }
754
755 // %% File-Based Indexing Mode (3.2.1-3.2.7) %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
756 const validation = validatePayload(body);
757 if (!validation.valid) {
758   return new Response(JSON.stringify({ error: validation.error }), {
759     status: 400,
760     headers: { ...corsHeaders, "Content-Type": "application/json" },
761   });
762 }
763
764 const embedReq = validation.data;
765
766 // %% Resolve institution_id from course %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
767 let institutionId = embedReq.institution_id;
768 let teacherId: string | null = null;
769
770 const { data: courseData, error: courseError } = await supabase
771   .from("courses")
772   .select("institution_id, teacher_id")
773   .eq("id", embedReq.course_id)
774   .maybeSingle();
775
776 if (courseError || !courseData) {
777   return new Response(JSON.stringify({ error: "Course not found" }), {
778     status: 404,
779     headers: { ...corsHeaders, "Content-Type": "application/json" },
780   });
781 }
782
783 institutionId = institutionId ?? courseData.institution_id;
784 teacherId = courseData.teacher_id;
785
786 // %% Delete old chunks for re-indexing %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %% %%
787 // (Task 3.2.7: Re-indexing – delete old chunks before inserting new ones)
788 // Always delete old chunks when source_material_id is provided or reindex is true
789 if (embedReq.reindex || embedReq.source_material_id) {
790   if (embedReq.source_material_id) {
791     await supabase
792       .from("course_material_embeddings")
793       .delete()
794       .eq("source_material_id", embedReq.source_material_id)
795       .eq("course_id", embedReq.course_id);
796   } else {
797     // Fall back to matching by filename + course
798     await supabase
799       .from("course_material_embeddings")
800       .delete()
801       .eq("source_filename", embedReq.source_filename)
802       .eq("course_id", embedReq.course_id);
803   }
804 } else {
805   // Default behavior: delete by filename + course to prevent duplicates
806   await supabase
807     .from("course_material_embeddings")
808     .delete()
809     .eq("source_filename", embedReq.source_filename)

```

```
810 } .eq("course_id", embedReq.course_id);  
811  
812 // %% Download file from Supabase Storage %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%%  
813 // (Task 3.2.1: File download and text extraction)  
814 let fileBytes: Uint8Array;  
815  
816 if (embedReq.file_url.startsWith("http")) {  
817     // %% SSRF Protection: validate URL against allowlist %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%%  
818     // Only allow fetching from the project's own Supabase Storage URL.  
819     // Block private IP ranges, localhost, and cloud metadata endpoints.  
820     const parsedUrl = new URL(embedReq.file_url);  
821     const allowedHost = new URL(supabaseUrl).hostname;  
822     const hostname = parsedUrl.hostname.toLowerCase();  
823  
824     // Block private/internal IP ranges and metadata endpoints  
825     const blockedPatterns = [  
826         /^localhost$/i,  
827         /^127\./i,  
828         /^10\./i,  
829         /^172\.([6-9]|2\d|3[01])\./i,  
830         /^192\.168\./i,  
831         /^169\.254\./i,  
832         /^0\./i,  
833         /\^[::1]$/,  
834         /\^metadata\.google\.internal$/i,  
835     ];  
836  
837     const isBlocked = blockedPatterns.some((pattern) => pattern.test(hostname));  
838     if (isBlocked) {  
839         return new Response(  
840             JSON.stringify({  
841                 error: "Forbidden: URL points to a private or internal address",  
842             }),  
843             {  
844                 status: 403,  
845                 headers: { ...corsHeaders, "Content-Type": "application/json" },  
846             });  
847     }  
848     // Only allow the project's own Supabase domain  
849     if (hostname !== allowedHost) {  
850         return new Response(  
851             JSON.stringify({  
852                 error: `Forbidden: only URLs from ${allowedHost} are allowed`,  
853             }),  
854             {  
855                 status: 403,  
856                 headers: { ...corsHeaders, "Content-Type": "application/json" },  
857             });  
858     }  
859     // Direct URL – fetch the file  
860     const fileResponse = await fetch(embedReq.file_url);  
861     if (!fileResponse.ok) {  
862         throw new Error(`Failed to download file: HTTP ${fileResponse.status}`);  
863     }  
864     fileBytes = new Uint8Array(await fileResponse.arrayBuffer());  
865 } else {  
866     // %% Path Traversal Protection for storage paths %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%%  
867     if (embedReq.file_url.includes("..")) {  
868         return new Response(  
869             JSON.stringify({  
870                 error:  
871                     "Invalid file path: path traversal sequences are not allowed",  
872             }),  
873             {  
874                 status: 400,  
875                 headers: { ...corsHeaders, "Content-Type": "application/json" },  
876             });  
877     }  
878 }  
879  
880 // Supabase Storage path – download via storage API  
881 const { data: fileData, error: downloadError } = await supabase.storage  
882   .from("course-materials")  
883   .download(embedReq.file_url);  
884  
885 if (downloadError || !fileData) {  
886     throw new Error(  
887       `Failed to download file from storage: ${  
888         downloadError?.message ?? "Unknown error"  
889       }`  
890     );  
891 }  
892  
893 fileBytes = new Uint8Array(await fileData.arrayBuffer());  
894  
895 // %% Extract text %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%% %%%  
896 let extractedText: string;  
897 try {  
898     extractedText = await extractText(fileBytes, embedReq.source_filename);  
899 } catch (extractionError) {  
900     // (Task 3.2.6: Error handling – mark indexing_failed, notify teacher)  
901     if (embedReq.source_material_id) {  
902         await supabase.from("course_material_embeddings").insert({  
903             institution_id: institutionId,  
904             course_id: embedReq.course_id,  
905             chunk_text: "",  
906         })
```

[illegible]

```

1018 |         if (embedReq.source_material_id) {
1019 |             await supabase.from("course_material_embeddings").insert({
1020 |                 institution_id: institutionId,
1021 |                 course_id: embedReq.course_id,
1022 |                 chunk_text: "",
1023 |                 embedding: Array(EMBEDDING_DIMENSIONS).fill(0),
1024 |                 source_filename: embedReq.source_filename,
1025 |                 material_type: embedReq.material_type,
1026 |                 chunk_index: 0,
1027 |                 token_count: 0,
1028 |                 source_material_id: embedReq.source_material_id,
1029 |                 indexing_status: "indexing_failed",
1030 |             });
1031 |         }
1032 |
1033 |         if (teacherId) {
1034 |             await notifyTeacher(
1035 |                 supabase,
1036 |                 teacherId,
1037 |                 institutionId,
1038 |                 "Material Indexing Failed",
1039 |                 `Failed to generate embeddings for "${embedReq.source_filename}". ${
1040 |                     (embeddingError as Error).message
1041 |                 }`
1042 |             );
1043 |         }
1044 |
1045 |         throw embeddingError;
1046 |     }
1047 |
1048 |     if (embeddings.length !== chunks.length) {
1049 |         throw new Error(
1050 |             `Embedding count mismatch: got ${embeddings.length} embeddings for ${chunks.length} chunks`
1051 |         );
1052 |     }
1053 |
1054 |     // %% Insert chunks into course_material_embeddings % % % % % % % % % % % % % % % %
1055 |     // (Task 3.2.4: Chunk insertion with metadata)
1056 |     const insertRows = chunks.map((chunk, index) => ({
1057 |         institution_id: institutionId,
1058 |         course_id: embedReq.course_id,
1059 |         chunk_text: chunk.text,
1060 |         embedding: JSON.stringify(embeddings[index]),
1061 |         source_filename: embedReq.source_filename,
1062 |         material_type: embedReq.material_type,
1063 |         clo_ids: embedReq.clo_ids ?? [],
1064 |         bloom_level: embedReq.bloom_level ?? null,
1065 |         chunk_index: index,
1066 |         token_count: chunk.token_count_estimate,
1067 |         source_material_id: embedReq.source_material_id ?? null,
1068 |         indexing_status: "indexed",
1069 |     }));
1070 |
1071 |     // Insert in batches to avoid payload size limits
1072 |     const INSERT_BATCH_SIZE = 50;
1073 |     for (let i = 0; i < insertRows.length; i += INSERT_BATCH_SIZE) {
1074 |         const batch = insertRows.slice(i, i + INSERT_BATCH_SIZE);
1075 |         const { error: insertError } = await supabase
1076 |             .from("course_material_embeddings")
1077 |             .insert(batch);
1078 |
1079 |         if (insertError) {
1080 |             throw new Error(`Failed to insert chunks: ${insertError.message}`);
1081 |         }
1082 |     }
1083 |
1084 |     // %% Notify teacher on completion for large documents % % % % % % % % % % % % % % % %
1085 |     if (isLargeDocument && teacherId) {
1086 |         await notifyTeacher(
1087 |             supabase,
1088 |             teacherId,
1089 |             institutionId,
1090 |             "Material Indexing Complete",
1091 |             ` "${embedReq.source_filename}" has been successfully indexed (${chunks.length} chunks from ~${estimate
1092 |             });
1093 |     }
1094 |
1095 |     return new Response(
1096 |         JSON.stringify({
1097 |             success: true,
1098 |             chunks_created: chunks.length,
1099 |             source_filename: embedReq.source_filename,
1100 |             estimated_pages: estimatedPages,
1101 |         }),
1102 |         {
1103 |             status: 200,
1104 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
1105 |         }
1106 |     );
1107 | } catch (error) {
1108 |     console.error("embed-course-material error:", error);
1109 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
1110 |         status: 500,
1111 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
1112 |     );
1113 | }
1114 | });
1115 |

```


FILE: supabase/functions/exam-period-notify/index.ts

TYPE: .ts | LINES: 1-113 | SHA256: 2ffa060ac78e84691618067487c0fdec408e1279dc141b2691e74b1bf6b7e97f

```
1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |   "Access-Control-Allow-Origin": "*",
6 |   "Access-Control-Allow-Headers":
7 |     "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | // % % % Vercel cron schedule: 0 8 * * * (daily 08:00 UTC) % % % % % % % % % % % % % % % % %
11 | // Canonical scheduler: vercel.json `cron` -> /api/cron/exam-period-notify.
12 | // (There is no pg_cron job for this function.)
13 | // Checks for exam_period events starting in 5 days.
14 | // Creates in-app notifications for enrolled students.
15 |
16 | serve(async (req) => {
17 |   if (req.method === "OPTIONS")
18 |     return new Response("ok", { headers: corsHeaders });
19 |
20 |   try {
21 |     // % % % Auth: cron secret or service role only % % % % % % % % % % % % % % % % %
22 |     const cronSecret = req.headers.get("x-cron-secret");
23 |     const expectedSecret = Deno.env.get("CRON_SECRET");
24 |     const authHeader = req.headers.get("Authorization") ?? "";
25 |     const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY") ?? "";
26 |     const isServiceRole =
27 |       serviceRoleKey && authHeader.replace("Bearer ", "") === serviceRoleKey;
28 |     const isCron = expectedSecret && cronSecret === expectedSecret;
29 |
30 |     if (!isServiceRole && !isCron) {
31 |       return new Response(
32 |         JSON.stringify({
33 |           error: "Unauthorized: cron secret or service role required",
34 |         }),
35 |         {
36 |           status: 401,
37 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
38 |         }
39 |       );
40 |     }
41 |
42 |     const supabase = createClient(
43 |       Deno.env.get("SUPABASE_URL")!,
44 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
45 |     );
46 |
47 |     // Find exam_period events starting in exactly 5 days
48 |     const targetDate = new Date();
49 |     targetDate.setDate(targetDate.getDate() + 5);
50 |     const targetDateStr = targetDate.toISOString().slice(0, 10);
51 |
52 |     const { data: examEvents, error: evtErr } = await supabase
53 |       .from("academic_calendar_events")
54 |       .select("id, title, institution_id, start_date")
55 |       .eq("event_type", "exam_period")
56 |       .eq("start_date", targetDateStr);
57 |
58 |     if (evtErr) throw new Error(evtErr.message);
59 |
60 |     if (!examEvents || examEvents.length === 0) {
61 |       return new Response(JSON.stringify({ success: true, notified: 0 }), {
62 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
63 |       });
64 |     }
65 |
66 |     let totalNotified = 0;
67 |
68 |     for (const event of examEvents) {
69 |       // Get all students in this institution
70 |       const { data: students } = await supabase
71 |         .from("profiles")
72 |         .select("id")
73 |         .eq("role", "student")
74 |         .eq("institution_id", event.institution_id);
75 |
76 |       if (!students || students.length === 0) continue;
77 |
78 |       // Create in-app notifications
79 |       const notifications = students.map((s: { id: string }) => ({
80 |         user_id: s.id,
81 |         title: "Exam Period Approaching",
82 |         body: `${event.title} starts in 5 days (${event.start_date}). Good luck with your preparation!`,
83 |         type: "exam_period_reminder",
84 |         is_read: false,
85 |       }));
86 |
87 |       const { error: insertErr } = await supabase
88 |         .from("notifications")
89 |         .insert(notifications);
90 |
91 |       if (insertErr) {
92 |         console.error(
93 |           `Failed to insert notifications for event ${event.id}:`,
94 |           insertErr.message
95 |         );
96 |       } else {
97 |         totalNotified += notifications.length;
98 |       }
99 |     }
100 |
101 |     return new Response(
```

```

102 |     JSON.stringify({ success: true, notified: totalNotified }},
103 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
104 | );
105 | } catch (error) {
106 |   console.error("exam-period-notify error:", (error as Error).message);
107 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
108 |     status: 500,
109 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
110 |   });
111 | }
112 | });
113 |

```

FILE: supabase/functions/export-student-data/index.ts

TYPE: .ts | LINES: 1-219 | SHA256: 1198b70dcea8993fdf00a57119156bc66759a0f3f1a9f3eccbd8f09ef58eb0f3

```

1 | // Task 55: GDPR Student Data Export Edge Function
2 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
3 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
4 |
5 | const allowedOrigin =
6 |   Deno.env.get("ALLOWED_ORIGIN") ?? "https://edevise.vercel.app";
7 | const corsHeaders = {
8 |   "Access-Control-Allow-Origin": allowedOrigin,
9 |   "Access-Control-Allow-Headers":
10 |     "authorization, x-client-info, apikey, content-type",
11 | };
12 |
13 | /** Convert an array of objects to CSV string */
14 | function toCsv(rows: Record<string, unknown>[], section: string): string {
15 |   if (rows.length === 0) return "";
16 |   const keys = Object.keys(rows[0]!);
17 |   const header = keys.join(",");
18 |   const lines = rows.map((row) =>
19 |     keys
20 |       .map((k) => {
21 |         const val = row[k];
22 |         if (val === null || val === undefined) return "";
23 |         const str = String(val);
24 |         // Escape CSV values containing commas, quotes, or newlines
25 |         if (str.includes(",") || str.includes('"') || str.includes("\n")) {
26 |           return `"${str.replace(/"/g, '"')}"`;
27 |         }
28 |         return str;
29 |       })
30 |       .join(",")
31 |   );
32 |   return `--- ${section} ---\n${header}\n${lines.join("\n")}`;
33 | }
34 |
35 | serve(async (req) => {
36 |   if (req.method === "OPTIONS")
37 |     return new Response("ok", { headers: corsHeaders });
38 |
39 |   try {
40 |     // Auth: student can only export their own data
41 |     const authHeader = req.headers.get("Authorization") ?? "";
42 |     if (!authHeader) {
43 |       return new Response(JSON.stringify({ error: "Unauthorized" }), {
44 |         status: 401,
45 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
46 |       });
47 |     }
48 |
49 |     const userClient = createClient(
50 |       Deno.env.get("SUPABASE_URL")!,
51 |       Deno.env.get("SUPABASE_ANON_KEY")!,
52 |       { global: { headers: { Authorization: authHeader } } }
53 |     );
54 |     const {
55 |       data: { user },
56 |       error: authErr,
57 |     } = await userClient.auth.getUser();
58 |     if (authErr || !user) {
59 |       return new Response(JSON.stringify({ error: "Unauthorized" }), {
60 |         status: 401,
61 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
62 |       });
63 |     }
64 |
65 |     const studentId = user.id;
66 |     const supabase = createClient(
67 |       Deno.env.get("SUPABASE_URL")!,
68 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
69 |     );
70 |
71 |     const { format: fmt = "json" } = await req
72 |       .json()
73 |       .catch(() => ({ format: "json" }));
74 |     const exportFormat = fmt === "csv" ? "csv" : "json";
75 |
76 |     // Gather all student-scoped data in parallel
77 |     const submissionsResult = await supabase
78 |       .from("submissions")
79 |       .select("id")
80 |       .eq("student_id", studentId);
81 |     const submissionIds =
82 |       submissionsResult.data?.map((s: { id: string }) => s.id) ?? [];
83 |
84 |     const [profile, grades, attainment, xp, journals, badges, habits] =
85 |       await Promise.all([
86 |         supabase
87 |           .from("profiles")
88 |           .select("id, full_name, email, role, created_at")

```

```

89 |         .eq("id", studentId)
90 |         .maybeSingle(),
91 |     supabase
92 |         .from("grades")
93 |         .select("id, score_percent, overall_feedback, created_at")
94 |         .in(
95 |             "submission_id",
96 |             submissionIds.length > 0 ? submissionIds : ["__none__"]
97 |         ),
98 |     supabase
99 |         .from("outcome_attainment")
100 |        .select("outcome_id, attainment_percent, scope, last_calculated_at")
101 |        .eq("student_id", studentId),
102 |    supabase
103 |        .from("xp_transactions")
104 |        .select("source, xp_amount, created_at")
105 |        .eq("student_id", studentId),
106 |    supabase
107 |        .from("journal_entries")
108 |        .select("id, title, word_count, created_at")
109 |        .eq("student_id", studentId),
110 |    supabase
111 |        .from("student_badges")
112 |        .select("badge_id, awarded_at")
113 |        .eq("student_id", studentId),
114 |    supabase
115 |        .from("habit_logs")
116 |        .select("date, habit_type")
117 |        .eq("student_id", studentId),
118 |    ]]);
119 |
120 | const exportData = {
121 |     exported_at: new Date().toISOString(),
122 |     profile: profile.data,
123 |     grades: grades.data ?? [],
124 |     outcome_attainment: attainment.data ?? [],
125 |     xp_transactions: xp.data ?? [],
126 |     journal_entries: journals.data ?? [],
127 |     badges: badges.data ?? [],
128 |     habit_logs: habits.data ?? [],
129 | };
130 |
131 | let content: string;
132 | let contentType: string;
133 | let fileExtension: string;
134 |
135 | if (exportFormat === "csv") {
136 |     const sections: string[] = [];
137 |     if (exportData.profile) {
138 |         sections.push(toCsv([exportData.profile], "Profile"));
139 |     }
140 |     if (exportData.grades.length > 0) {
141 |         sections.push(toCsv(exportData.grades, "Grades"));
142 |     }
143 |     if (exportData.outcome_attainment.length > 0) {
144 |         sections.push(
145 |             toCsv(exportData.outcome_attainment, "Outcome Attainment")
146 |         );
147 |     }
148 |     if (exportData.xp_transactions.length > 0) {
149 |         sections.push(toCsv(exportData.xp_transactions, "XP Transactions"));
150 |     }
151 |     if (exportData.journal_entries.length > 0) {
152 |         sections.push(toCsv(exportData.journal_entries, "Journal Entries"));
153 |     }
154 |     if (exportData.badges.length > 0) {
155 |         sections.push(toCsv(exportData.badges, "Badges"));
156 |     }
157 |     if (exportData.habit_logs.length > 0) {
158 |         sections.push(toCsv(exportData.habit_logs, "Habit Logs"));
159 |     }
160 |     content = `Exported at: ${exportData.exported_at}\n\n${sections.join(
161 |         "\n\n"
162 |     )}`;
163 |     contentType = "text/csv";
164 |     fileExtension = "csv";
165 | } else {
166 |     content = JSON.stringify(exportData, null, 2);
167 |     contentType = "application/json";
168 |     fileExtension = "json";
169 | }
170 |
171 | const fileName = `exports/${studentId}_${Date.now()}.${fileExtension}`;
172 |
173 | // Guard against path traversal in the constructed storage path
174 | if (fileName.includes("..")) {
175 |     return new Response(JSON.stringify({ error: "Invalid file path" }), {
176 |         status: 400,
177 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
178 |     });
179 | }
180 |
181 | const encoded = new TextEncoder().encode(content);
182 |
183 | const { error: uploadErr } = await supabase.storage
184 |     .from("reports")
185 |     .upload(fileName, encoded, { contentType, upsert: false });
186 |
187 | if (uploadErr) {
188 |     // Bucket may not exist yet – create and retry
189 |     await supabase.storage
190 |         .createBucket("reports", { public: false })
191 |         .catch(() => {});
192 |     const { error: retryErr } = await supabase.storage

```


[illegible]

[illegible]

```

282 |     body: [
283 |         ["Total Survey Responses", String(surveyResponseCount)],
284 |         ["Assessment Type", "Indirect (Student/Graduate/Employer Surveys)"],
285 |     ],
286 |     theme: "grid",
287 |     headStyles: { fillColor: [245, 158, 11] },
288 |     styles: { fontSize: 8 },
289 | });
290 | yPos = doc.lastAutoTable?.finalY ?? yPos + 30;
291 | yPos += 12;
292 |
293 | // % % CQI Action Plans – Closing the Loop (Task 63.4 / 77.2) % % % % % % % %
294 | if (cqiPlans.length > 0) {
295 |     if (yPos > 220) {
296 |         doc.addPage();
297 |         yPos = 20;
298 |     }
299 |     doc.setFontSize(14);
300 |     doc.text(
301 |         "Continuous Quality Improvement (CQI) – Closing the Loop",
302 |         14,
303 |         yPos
304 |     );
305 |     yPos += 6;
306 |     autoTable(doc, {
307 |         startY: yPos,
308 |         head: [
309 |             ["Outcome ID", "Status", "Baseline %", "Target %", "Result %"]],
310 |         body: cqiPlans.map((p) => [
311 |             p.outcome_id.slice(0, 8),
312 |             p.status,
313 |             p.baseline_attainment?.toFixed(1) ?? "-",
314 |             p.target_attainment?.toFixed(1) ?? "-",
315 |             p.result_attainment?.toFixed(1) ?? "-",
316 |         ]),
317 |         theme: "grid",
318 |         headStyles: { fillColor: [34, 197, 94] },
319 |         styles: { fontSize: 8 },
320 |     });
321 |     yPos = doc.lastAutoTable?.finalY ?? yPos + 30;
322 |     yPos += 12;
323 | }
324 |
325 | // % % Per-Section Summary (Task 77.4) % % % % % % % % % % % % % % % % % % % %
326 | if (sections.length > 0) {
327 |     if (yPos > 220) {
328 |         doc.addPage();
329 |         yPos = 20;
330 |     }
331 |     doc.setFontSize(14);
332 |     doc.text("Section Summary", 14, yPos);
333 |     yPos += 6;
334 |     autoTable(doc, {
335 |         startY: yPos,
336 |         head: [
337 |             ["Section Code", "Course ID"]],
338 |         body: sections.map((s) => [s.section_code, s.course_id.slice(0, 8)]),
339 |         theme: "grid",
340 |         headStyles: { fillColor: [100, 116, 139] },
341 |         styles: { fontSize: 8 },
342 |     });
343 |     yPos = doc.lastAutoTable?.finalY ?? yPos + 30;
344 |     yPos += 12;
345 | }
346 |
347 | // % % Graduate Attribute Attainment Summary (Task 113.4) % % % % % % % % % % % %
348 | if (gaData.length > 0) {
349 |     if (yPos > 220) {
350 |         doc.addPage();
351 |         yPos = 20;
352 |     }
353 |     doc.setFontSize(14);
354 |     doc.text("Graduate Attribute Attainment", 14, yPos);
355 |     yPos += 6;
356 |     autoTable(doc, {
357 |         startY: yPos,
358 |         head: [
359 |             ["Attribute", "Description", "Attainment %", "Level", "Mapped ILOs"],
360 |         ],
361 |         body: gaData.map((ga) => [
362 |             ga.name,
363 |             ga.description ?? "-",
364 |             ga.attainment.toFixed(1),
365 |             classifyAttainment(ga.attainment),
366 |             String(ga.mappedILOs),
367 |         ]),
368 |         theme: "grid",
369 |         headStyles: { fillColor: [168, 85, 247] },
370 |         styles: { fontSize: 8 },
371 |     });
372 |     yPos = doc.lastAutoTable?.finalY ?? yPos + 30;
373 |     yPos += 12;
374 | }
375 |
376 | // % % Competency Framework Alignment Summary (Task 115.5) % % % % % % % % % % % %
377 | if (competencyData.length > 0) {
378 |     if (yPos > 220) {
379 |         doc.addPage();
380 |         yPos = 20;
381 |     }
382 |     doc.setFontSize(14);
383 |     doc.text("Competency Framework Alignment", 14, yPos);
384 |     yPos += 6;
385 |     autoTable(doc, {
386 |         startY: yPos,
387 |         head: [

```

[illegible]


```
const callerRole =  
  (callerProfile?.role as string) ??  
    user.app_metadata?.role ??  
      user.user_metadata?.role ??  
        "";  
  
const callerInstitutionId =  
  (callerProfile?.institution_id as string) ??  
    user.app_metadata?.institution_id ??  
      user.user_metadata?.institution_id ??  
        "";  
  
void callerInstitutionId; // resolved for parity with shared helper; report scopes by program.institution_  
if (!["admin", "coordinator"].includes(callerRole)) {  
  return new Response(  
    JSON.stringify({  
      error: "Forbidden: admin or coordinator role required",  
    }),  
    {  
      status: 403,  
      headers: { ...corsHeaders, "Content-Type": "application/json" },  
    }  
  );  
}  
  
const supabase = adminClient;  
  
const body = await req.json();  
const validation = validatePayload(body);  
  
if (!validation.valid) {  
  return new Response(JSON.stringify({ error: validation.error }), {  
    status: 400,  
    headers: { ...corsHeaders, "Content-Type": "application/json" },  
  });  
}  
  
const { program_id, semester_id, template, chart_images, email_to } =  
  validation.data;  
  
// % Fetch program info  
const { data: program, error: programErr } = await supabase  
  .from("programs")  
  .select("id, name, code, institution_id")  
  .eq("id", program_id)  
  .maybeSingle();  
  
if (programErr || !program) {  
  return new Response(JSON.stringify({ error: "Program not found" }), {  
    status: 404,  
    headers: { ...corsHeaders, "Content-Type": "application/json" },  
  });  
}  
  
// % Fetch semester info (optional)  
let semesterName: string | null = null;  
if (semester_id) {  
  const { data: semester, error: semesterErr } = await supabase  
    .from("semesters")  
    .select("name")  
    .eq("id", semester_id)  
    .maybeSingle();  
  if (semesterErr) throw semesterErr;  
  semesterName = semester?.name ?? null;  
}  
  
// % Fetch courses in program  
let courseQuery = supabase  
  .from("courses")  
  .select("id")  
  .eq("program_id", program_id);  
  
if (semester_id) {  
  courseQuery = courseQuery.eq("semester_id", semester_id);  
}  
  
const { data: courses, error: coursesErr } = await courseQuery;  
if (coursesErr) throw coursesErr;  
const courseId = (courses ?? []).map((c: { id: string }) => c.id);  
  
// % Fetch all outcomes for the program's institution  
const { data: outcomes, error: outcomesErr } = await supabase  
  .from("learning_outcomes")  
  .select("id, title, type, blooms_level")  
  .eq("institution_id", program.institution_id);  
if (outcomesErr) throw outcomesErr;  
  
const allOutcomes = (outcomes ?? []) as OutcomeRow[];  
const ploOutcomes = allOutcomes.filter(o => o.type === "PLO");  
const iloOutcomes = allOutcomes.filter(o => o.type === "ILO");  
  
// % Fetch outcome_attainment data  
// Attainment is keyed by `outcome_id`, and the writer trigger stores each  
// outcome type at a `distinct` scope: CLO!`student_course`, PLO!`course`,  
// ILO!`program` (verified against live data; there are no `institution`-  
// scope rows). Filtering by scope name is therefore fragile – the previous  
// ["program","institution"] filter silently dropped every PLO row (which  
// lives at `course`), rendering all PLOs 0%. Instead, fetch by this  
// institution's PLO+ILO outcome ids: that is robust to the scope taxonomy  
// AND naturally tenant-scoped (outcome ids are institution-specific). We  
// then aggregate by outcome_id below.  
const reportOutcomeIds = [...ploOutcomes, ...iloOutcomes].map(o => o.id);  
let attainment: AttainmentRow[] = [];  
if (reportOutcomeIds.length > 0) {  
  const { data: attainmentData, error: attainmentErr } = await supabase  
    .from("outcome_attainment")
```

```

594   .select("outcome_id", scope, attainment_percent, student_id, course_id")
595   .in("outcome_id", reportOutcomeIds);
596   if (attainmentErr) throw attainmentErr;
597   attainment = (attainmentData ?? []) as AttainmentRow[];
598 }
599
600 // %% Aggregate PLO attainment %%%%%%%%%%%%%%%
601 const ploAgg = ploOutcomes.map((plo) => {
602   const records = attainment.filter((a) => a.outcome_id === plo.id);
603   const avg =
604     records.length > 0
605       ? records.reduce((sum, r) => sum + r.attainment_percent, 0) /
606         records.length
607       : 0;
608   return {
609     title: plo.title,
610     avgAttainment: avg,
611     evidenceCount: records.length,
612     level: classifyAttainment(avg),
613   };
614 });
615
616 // %% Aggregate ILO attainment %%%%%%%%%%%%%%%
617 const iloAgg = iloOutcomes.map((ilo) => {
618   const records = attainment.filter((a) => a.outcome_id === ilo.id);
619   const avg =
620     records.length > 0
621       ? records.reduce((sum, r) => sum + r.attainment_percent, 0) /
622         records.length
623       : 0;
624   return {
625     title: ilo.title,
626     avgAttainment: avg,
627     evidenceCount: records.length,
628     level: classifyAttainment(avg),
629   };
630 });
631
632 // %% Bloom's distribution %%%%%%%%%%%%%%%
633 const bloomsDist = countBloomsDistribution(allOutcomes);
634
635 // %% Fetch survey results as indirect assessment (Task 62.4 / 77.1) %%
636 const { data: surveyIdRows, error: surveysErr } = await supabase
637   .from("surveys")
638   .select("id")
639   .eq("institution_id", program.institution_id);
640 if (surveysErr) throw surveysErr;
641 const { data: surveyRows, error: surveyRespErr } = await supabase
642   .from("survey_responses")
643   .select("id")
644   .in(
645     "survey_id",
646     (surveyIdRows ?? []).map((s: { id: string }) => s.id)
647   );
648 if (surveyRespErr) throw surveyRespErr;
649 const surveyCount = surveyRows?.length ?? 0;
650
651 // %% Fetch CQI action plans (Task 63.4 / 77.2) %%%%%%%%%%%%%%%
652 const { data: cqiRows, error: cqiErr } = await supabase
653   .from("cqi_action_plans")
654   .select(
655     "id, outcome_id, status, baseline_attainment, target_attainment, result_attainment"
656   )
657   .eq("program_id", program.id);
658 if (cqiErr) throw cqiErr;
659 const cqiPlans = (cqiRows ?? []) as Array<{
660   id: string;
661   outcome_id: string;
662   status: string;
663   baseline_attainment: number | null;
664   target_attainment: number | null;
665   result_attainment: number | null;
666 }>;
667
668 // %% Fetch per-section attainment (Task 77.4) %%%%%%%%%%%%%%%
669 const { data: sectionRows, error: sectionsErr } = await supabase
670   .from("course_sections")
671   .select("id, section_code, course_id")
672   .in("course_id", courseIds.length > 0 ? courseIds : ["__none__"]);
673 if (sectionsErr) throw sectionsErr;
674 const sections = (sectionRows ?? []) as Array<{
675   id: string;
676   section_code: string;
677   course_id: string;
678 }>;
679
680 // %% Fetch Graduate Attribute data (Task 113.4) %%%%%%%%%%%%%%%
681 const { data: gaRows, error: gaErr } = await supabase
682   .from("graduate_attributes")
683   .select("id, name, description")
684   .eq("institution_id", program.institution_id);
685 if (gaErr) throw gaErr;
686 const gaData: Array<{
687   name: string;
688   description: string | null;
689   attainment: number;
690   mappedILOs: number;
691 }> = [];
692 for (const ga of (gaRows ?? []) as Array<{
693   id: string;
694   name: string;
695   description: string | null;
696 }>) {
697   const { data: gaMappings, error: gaMapErr } = await supabase

```

[illegible]

```
802 // it directly instead of self-creating an unpoliced bucket at runtime.  
803 return new Response(  
804   JSON.stringify({  
805     error: "Failed to upload report",  
806     detail: uploadErr.message,  
807   } ),  
808   {  
809     status: 500,  
810     headers: { ...corsHeaders, "Content-Type": "application/json" },  
811   }  
812 );  
813  
814 // % % Generate signed download URL % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
815 const { data: signedUrl, error: signErr } = await supabase.storage  
816 .from("reports")  
817 .createSignedUrl(fileName, 3600); // 1 hour expiry  
818  
819 if (signErr || !signedUrl) {  
820   return new Response(  
821     JSON.stringify({  
822       error: "Failed to generate download URL",  
823       detail: signErr?.message,  
824     } ),  
825     {  
826       status: 500,  
827       headers: { ...corsHeaders, "Content-Type": "application/json" },  
828     }  
829   );  
830 }  
831  
832 // % % Optional email delivery % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
833 if (email_to) {  
834   try {  
835     const resendApiKey = Deno.env.get("RESEND_API_KEY");  
836     if (resendApiKey) {  
837       await fetch("https://api.resend.com/emails", {  
838         method: "POST",  
839         headers: {  
840           "Content-Type": "application/json",  
841           Authorization: `Bearer ${resendApiKey}`,  
842         },  
843         body: JSON.stringify({  
844           from: "Edeviser <noreply@edeviser.com>",  
845           to: email_to,  
846           subject: `Accreditation Report - ${program.name} (${template})`,  
847           html:  
848             `

## >Accreditation Report Generated</h2> 849 <p><strong>Program:</strong> ${program.name}</p> 850 <p><strong>Template:</strong> ${template}</p> 851 ${ 852 semesterName 853 ? `<p><strong>Semester:</strong> ${semesterName}</p> 854 : "" 855 } 856 <p><strong>Generated:</strong> ${new Date() 857 .toISOString() 858 .slice(0, 10)}</p> 859 <p><a href="${signedUrl.signedUrl 860 }">Download Report (link expires in 1 hour)</a></p> 861 }` 862 }, 863 )}, 864 }); 865 }; 866 } catch (emailErr) { 867 console.error("Email delivery failed (non-blocking):", emailErr); 868 } 869 } 870 871 return new Response( 872 JSON.stringify({ 873 success: true, 874 download_url: signedUrl.signedUrl, 875 file_name: fileName, 876 program_name: program.name, 877 template, 878 semester: semesterName, 879 plo_count: ploAgg.length, 880 ilo_count: iloAgg.length, 881 } ), 882 { headers: { ...corsHeaders, "Content-Type": "application/json" } } 883 ); 884 } catch (error) { 885 return new Response(JSON.stringify({ error: (error as Error).message }), { 886 status: 500, 887 headers: { ...corsHeaders, "Content-Type": "application/json" }, 888 ); 889 } 890 } 891 }};


```

FILE: supabase/functions/generate-course-file/index.ts

```
TYPE: .ts | LINES: 1-818 | SHA256: 0007551c4fbe3108d7fbb89178d29ea5f55a6b52d1be7db1829f2a627b59c734
```

```
1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 import { jsPDF } from "https://esm.sh/jspdf@2";
4 import autoTable from "https://esm.sh/jspdf-autotable@3";
5
6 const corsHeaders = {
7   "Access-Control-Allow-Origin": "*",
8   "Access-Control-Allow-Headers":
9     "authorization, x-client-info, apikey, content-type",
10 }
```

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

FILE: supabase/functions/generate-fee-receipt/index.ts

```
TYPE: .ts | LINES: 1-187 | SHA256: e466064fdae49a4f991c785acc9f197ae00e7b43ea902380429e58e9b777254a
```

```

1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 import { jsPDF } from "https://esm.sh/jspdf@2";
4 import { z } from "https://esm.sh/zod@3.23.8";
5 import {
6   authenticateRequest,
7   unauthorizedResponse,
8   forbiddenResponse,
9 } from "../_shared/auth.ts";
10
11 const PayloadSchema = z.object({
12   payment_id: z.string().min(1),
13 });
14
15 const corsHeaders = {
16   "Access-Control-Allow-Origin": "*",
17   "Access-Control-Allow-Headers":
18     "authorization, x-client-info, apikey, content-type",
19 };

```

```

20 |
21 | serve(async (req) => {
22 |   if (req.method === "OPTIONS")
23 |     return new Response("ok", { headers: corsHeaders });
24 |
25 |   try {
26 |     // Caller check (Req 18): require a valid JWT before any service-role work.
27 |     const auth = await authenticateRequest(req);
28 |     if (!auth.user) {
29 |       return unauthorizedResponse(auth.error ?? "Unauthorized");
30 |     }
31 |
32 |     const supabase = createClient(
33 |       Deno.env.get("SUPABASE_URL")!,
34 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
35 |     );
36 |
37 |     const body = await req.json();
38 |     const parsed = PayloadSchema.safeParse(body);
39 |     if (!parsed.success) {
40 |       return new Response(JSON.stringify({ error: parsed.error.message }), {
41 |         status: 400,
42 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
43 |       });
44 |     }
45 |     const { payment_id } = parsed.data;
46 |
47 |     // Fetch payment details
48 |     const { data: payment, error: payErr } = await supabase
49 |       .from("fee_payments")
50 |       .select("*")
51 |       .eq("id", payment_id)
52 |       .maybeSingle();
53 |
54 |     if (payErr) throw new Error(payErr.message);
55 |     if (!payment) {
56 |       return new Response(JSON.stringify({ error: "Payment not found" }), {
57 |         status: 404,
58 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
59 |       });
60 |     }
61 |
62 |     // Fetch student profile
63 |     const { data: student } = await supabase
64 |       .from("profiles")
65 |       .select("full_name, email, institution_id")
66 |       .eq("id", payment.student_id)
67 |       .maybeSingle();
68 |
69 |     // Authorization (Req 18): the owning student may fetch their own receipt;
70 |     // admins/coordinators may fetch any receipt within their institution.
71 |     const isStaff = ["admin", "coordinator"].includes(auth.user.role);
72 |     const isOwner = auth.user.id === payment.student_id;
73 |     const sameInstitution =
74 |       (student as { institution_id?: string } | null)?.institution_id ===
75 |       auth.user.institution_id;
76 |     if (!isOwner && !(isStaff && sameInstitution)) {
77 |       return forbiddenResponse(
78 |         "Forbidden: not authorized to access this receipt"
79 |       );
80 |     }
81 |
82 |     // Fetch fee structure
83 |     const { data: feeStructure } = await supabase
84 |       .from("fee_structures")
85 |       .select("title, amount, due_date, program_id")
86 |       .eq("id", payment.fee_structure_id)
87 |       .maybeSingle();
88 |
89 |     // Build PDF
90 |     // eslint-disable-next-line @typescript-eslint/no-explicit-any
91 |     const doc = new jsPDF() as any;
92 |     const pw = doc.internal.pageSize.getWidth();
93 |
94 |     // Header
95 |     doc.setFillColor(15, 23, 42);
96 |     doc.rect(0, 0, pw, 30, "F");
97 |     doc.setTextColor(255, 255, 255);
98 |     doc.setFontSize(16);
99 |     doc.text("Fee Receipt", 14, 18);
100 |     doc.setFontSize(9);
101 |     doc.text(
102 |       `Receipt #${payment.receipt_number ?? payment_id.slice(0, 8)}`,
103 |       pw - 14,
104 |       12,
105 |       { align: "right" }
106 |     );
107 |     doc.text(
108 |       `Date: ${
109 |         payment.paid_at?.slice(0, 10) ?? new Date().toISOString().slice(0, 10)
110 |       }`,
111 |       pw - 14,
112 |       20,
113 |       { align: "right" }
114 |     );
115 |
116 |     doc.setTextColor(0, 0, 0);
117 |     let y = 45;
118 |
119 |     // Student info
120 |     doc.setFontSize(11);
121 |     doc.text("Student Information", 14, y);
122 |     y += 8;
123 |     doc.setFontSize(9);

```


[illegible]

```

141 |     .join("\n");
142 |
143 | // % % 15.2.2: Retrieve top 3 relevant materials via RAG % % % % % % % % % % % %
144 |
145 | let retrievedChunks: RetrievedChunk[] = [];
146 |
147 | const openaiApiKey = Deno.env.get("OPENAI_API_KEY");
148 | if (openaiApiKey) {
149 |     // Generate embedding for CLO title + bloom level as query
150 |     const queryText = `Study materials for ${cloTitle} at ${bloomLevel} level`;
151 |
152 |     try {
153 |         const embeddingResponse = await fetch(
154 |             "https://api.openai.com/v1/embeddings",
155 |             {
156 |                 method: "POST",
157 |                 headers: {
158 |                     Authorization: `Bearer ${openaiApiKey}`,
159 |                     "Content-Type": "application/json",
160 |                 },
161 |                 body: JSON.stringify({
162 |                     model: "text-embedding-ada-002",
163 |                     input: queryText,
164 |                 }),
165 |             }
166 |         );
167 |
168 |         if (embeddingResponse.ok) {
169 |             const embeddingData = await embeddingResponse.json();
170 |             const queryEmbedding = embeddingData.data[0].embedding;
171 |
172 |             const { data: chunks } = await supabase.rpc(
173 |                 "search_course_materials",
174 |                 {
175 |                     query_embedding: JSON.stringify(queryEmbedding),
176 |                     match_course_ids: [course_id],
177 |                     match_clo_ids: [clo_id],
178 |                     match_threshold: 0.6, // slightly lower threshold for broader material coverage
179 |                     match_count: 3,
180 |                 }
181 |             );
182 |
183 |             if (chunks) {
184 |                 retrievedChunks = chunks as RetrievedChunk[];
185 |             }
186 |         }
187 |     } catch (err) {
188 |         console.error(
189 |             "RAG retrieval failed (non-blocking):",
190 |             (err as Error).message
191 |         );
192 |     }
193 | }
194 |
195 | // % % 15.2.3: Generate study time and planner recommendations via LLM %
196 |
197 | const recommendedMaterials = retrievedChunks.map((chunk) => ({
198 |     chunk_id: chunk.id,
199 |     source_filename: chunk.source_filename,
200 |     section_title: chunk.chunk_text.slice(0, 80).trim(),
201 | }));
202 |
203 | let studyTimeRecommendation = "";
204 | let suggestedPlannerSessions = 2;
205 |
206 | const openRouterApiKey = Deno.env.get("OPENROUTER_API_KEY");
207 | if (openRouterApiKey) {
208 |     const llmPrompt = [
209 |         "You are an educational planning assistant. Based on the following student data, generate a brief stud",
210 |         "",
211 |         `CLO: ${cloTitle} (Bloom's Level: ${bloomLevel})`,
212 |         `Current Attainment: ${attainmentPercent}%`,
213 |         `Tutor Interactions on this CLO: ${interactionCount}`,
214 |         "",
215 |         "Recent conversation context:",
216 |         messageContext || "(no recent messages)",
217 |         "",
218 |         retrievedChunks.length > 0
219 |             ? `Available materials:\n${retrievedChunks
220 |                 .map((c, i) => `${i + 1}. ${c.source_filename}`)
221 |                 .join("\n")}`
222 |             : "",
223 |         "",
224 |         "Respond with ONLY a JSON object (no markdown, no code fences) with these fields:",
225 |         '- "study_time_recommendation": a short sentence recommending weekly study hours (e.g., "Increase to 3',
226 |         '- "suggested_planner_sessions": an integer (1-5) for recommended weekly planner sessions',
227 |     ].join("\n");
228 |
229 |     try {
230 |         const model =
231 |             Deno.env.get("TUTOR_PRIMARY_MODEL") ?? "openai/gpt-4o-mini";
232 |
233 |         const llmResponse = await fetch(
234 |             "https://openrouter.ai/api/v1/chat/completions",
235 |             {
236 |                 method: "POST",
237 |                 headers: {
238 |                     Authorization: `Bearer ${openRouterApiKey}`,
239 |                     "Content-Type": "application/json",
240 |                     "HTTP-Referer": Deno.env.get("SUPABASE_URL") ?? "",
241 |                     "X-Title": "Edeviser AI Tutor Plan Update",
242 |                 },
243 |                 body: JSON.stringify({
244 |                     model,

```



```

245 |         messages: [{ role: "user", content: llmPrompt }],
246 |         max_tokens: 300,
247 |         temperature: 0.5,
248 |     }},
249 |     },
250 | );
251 |
252 | if (llmResponse.ok) {
253 |     const llmData = await llmResponse.json();
254 |     const content = llmData.choices?.[0]?.message?.content ?? "";
255 |
256 |     try {
257 |         const parsed = JSON.parse(content);
258 |         studyTimeRecommendation = parsed.study_time_recommendation ?? "";
259 |         suggestedPlannerSessions = parsed.suggested_planner_sessions ?? 2;
260 |     } catch {
261 |         // If JSON parsing fails, use the raw content as recommendation
262 |         studyTimeRecommendation = content.trim();
263 |     }
264 | }
265 | } catch (err) {
266 |     console.error(
267 |         "LLM recommendation failed (non-blocking):",
268 |         (err as Error).message
269 |     );
270 | }
271 |
272 | // Fallback if LLM didn't produce a recommendation
273 | if (!studyTimeRecommendation) {
274 |     if (attainmentPercent < 50) {
275 |         studyTimeRecommendation = `Increase study time to 4 hours/week for "${cloTitle}" – focus on foundation
276 |         suggestedPlannerSessions = 3;
277 |     } else if (attainmentPercent < 70) {
278 |         studyTimeRecommendation = `Dedicate 3 hours/week to "${cloTitle}" – practice applying concepts to stre
279 |         suggestedPlannerSessions = 2;
280 |     } else {
281 |         studyTimeRecommendation = `Maintain 2 hours/week for "${cloTitle}" – review materials and attempt high
282 |         suggestedPlannerSessions = 1;
283 |     }
284 | }
285 |
286 | // Clamp planner sessions to valid range
287 | suggestedPlannerSessions = Math.max(
288 |     1,
289 |     Math.min(5, suggestedPlannerSessions)
290 | );
291 |
292 | // % % 15.2.4: Persist suggestion to tutor_plan_updates table % % % % % % % %
293 |
294 | const { data: planUpdate, error: insertError } = await supabase
295 |     .from("tutor_plan_updates")
296 |     .insert({
297 |         student_id,
298 |         institution_id: institutionId,
299 |         course_id,
300 |         clo_id,
301 |         conversation_id,
302 |         study_time_recommendation: studyTimeRecommendation,
303 |         recommended_materials: recommendedMaterials,
304 |         suggested_planner_sessions: suggestedPlannerSessions,
305 |         interaction_count: interactionCount,
306 |     })
307 |     .select("id")
308 |     .single();
309 |
310 | if (insertError) {
311 |     console.error("Failed to persist plan update:", insertError.message);
312 |     return new Response(
313 |         JSON.stringify({
314 |             error: "Failed to save learning plan update",
315 |             detail: insertError.message,
316 |         }),
317 |         {
318 |             status: 500,
319 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
320 |         },
321 |     );
322 | }
323 |
324 | // Build the LearningPlanUpdate response
325 | const result: LearningPlanUpdate = {
326 |     id: planUpdate.id,
327 |     clo_id,
328 |     clo_title: cloTitle,
329 |     study_time_recommendation: studyTimeRecommendation,
330 |     recommended_materials: recommendedMaterials,
331 |     suggested_planner_sessions: suggestedPlannerSessions,
332 |     interaction_count: interactionCount,
333 | };
334 |
335 | return new Response(JSON.stringify(result), {
336 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
337 | });
338 | } catch (error) {
339 |     console.error("generate-plan-update error:", (error as Error).message);
340 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
341 |         status: 500,
342 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
343 |     );
344 | }
345 | }
346 | });
347 |

```

TYPE: .ts | LINES: 1-863 | SHA256: b67663f52f56db1ee3cac1c06260559bd5272b28b03125c8b2691d7dddcde758

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

```

518 const startTime = Date.now();
519
520
521 try {
522   const supabase = createClient(
523     Deno.env.get("SUPABASE_URL")!,
524     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
525   );
526
527   // %% Step 1: JWT Validation %%%%%%%%%%%
528
529   const authHeader = req.headers.get("Authorization") ?? "";
530   if (!authHeader) {
531     return new Response(
532       JSON.stringify({ error: "Missing Authorization header" }),
533       {
534         status: 401,
535         headers: { ...corsHeaders, "Content-Type": "application/json" },
536       }
537     );
538   }
539
540   const userClient = createClient(
541     Deno.env.get("SUPABASE_URL")!,
542     Deno.env.get("SUPABASE_ANON_KEY")!,
543     { global: { headers: { Authorization: authHeader } } }
544   );
545
546   const {
547     data: { user },
548     error: authError,
549   } = await userClient.auth.getUser();
550
551   if (authError || !user) {
552     return new Response(
553       JSON.stringify({ error: "Invalid or expired token" }),
554       {
555         status: 401,
556         headers: { ...corsHeaders, "Content-Type": "application/json" },
557       }
558     );
559   }
560
561   const teacherId = user.id;
562
563   // %% Step 2: Validate Request Payload %%%%%%%%%%%
564
565   const body = await req.json();
566   const validation = validatePayload(body);
567
568   if (!validation.valid) {
569     return new Response(JSON.stringify({ error: validation.error }), {
570       status: 400,
571       headers: { ...corsHeaders, "Content-Type": "application/json" },
572     });
573   }
574
575   const { course_id, clo_ids, bloom_levels, question_count, question_types } =
576     validation.data;
577
578   // %% Step 3: Verify Course Ownership %%%%%%%%%%%
579   // institution_id lives on programs, not courses – join through program_id.
580
581   const { data: course, error: courseError } = await supabase
582     .from("courses")
583     .select("id, teacher_id, program_id, programs(institution_id)")
584     .eq("id", course_id)
585     .maybeSingle();
586
587   if (courseError || !course) {
588     return new Response(JSON.stringify({ error: "Course not found" }), {
589       status: 404,
590       headers: { ...corsHeaders, "Content-Type": "application/json" },
591     });
592   }
593
594   if (course.teacher_id !== teacherId) {
595     return new Response(
596       JSON.stringify({ error: "Forbidden: you do not own this course" }),
597       {
598         status: 403,
599         headers: { ...corsHeaders, "Content-Type": "application/json" },
600       }
601     );
602   }
603
604   const programRel = course.programs as
605     | { institution_id?: string }
606     | { institution_id?: string }[]
607     | null;
608   const institutionId = Array.isArray(programRel)
609     ? programRel[0]?.institution_id ?? ""
610     : programRel?.institution_id ?? "";
611
612   // %% Step 4: Fetch CLO Descriptions %%%%%%%%%%%
613
614   const { data: clos, error: closError } = await supabase
615     .from("learning_outcomes")
616     .select("id, title")
617     .in("id", clo_ids);
618
619   if (closError || !clos || clos.length === 0) {
620     return new Response(
621       JSON.stringify({

```

```
622 error: "Failed to fetch CLO details or no matching CLOs found",  
623 },  
624 {  
625   status: 400,  
626   headers: { ...corsHeaders, "Content-Type": "application/json" },  
627 }  
628 });  
629 }  
630  
631 const cloDescriptions: Record<string, string> = {};  
632 for (const clo of clos) {  
633   cloDescriptions[clo.id] = clo.title;  
634 }  
635  
636 // % % Step 5: RAG Retrieval % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
637  
638 const { chunks, warnings } = await retrieveCourseMaterialChunks(  
639   supabase,  
640   course_id,  
641   clo_ids  
642 );  
643  
644 // % % Step 6: Construct LLM Prompt & Call OpenRouter % % % % % % % % % % % % % % % %  
645  
646 const openrouterApiKey = Deno.env.get("OPENROUTER_API_KEY");  
647 if (!openrouterApiKey) {  
648   return new Response(  
649     JSON.stringify({ error: "LLM API key not configured" }),  
650     {  
651       status: 500,  
652       headers: { ...corsHeaders, "Content-Type": "application/json" },  
653     }  
654   );  
655 }  
656  
657 const prompt = buildLLMPrompt(  
658   chunks,  
659   bloom_levels,  
660   question_types,  
661   question_count,  
662   cloDescriptions  
663 );  
664  
665 let llmResult: {  
666   questions: LLMGeneratedQuestion[];  
667   promptTokens: number;  
668   completionTokens: number;  
669   totalTokens: number;  
670   model: string;  
671 };  
672  
673 const generationRequestId = crypto.randomUUID();  
674 // Resolve the model the same way callOpenRouterLLM does, so failure-path  
675 // logs (where llmResult is never assigned) still record the actual model.  
676 const resolvedModel = Deno.env.get("TUTOR_PRIMARY_MODEL") ?? LLM_MODEL;  
677  
678 try {  
679   llmResult = await callOpenRouterLLM(prompt, openrouterApiKey);  
680 } catch (llmError) {  
681   const latencyMs = Date.now() - startTime;  
682  
683   // Log the failed generation attempt  
684   await supabase.from("quiz_generation_logs").insert({  
685     institution_id: institutionId,  
686     teacher_id: teacherId,  
687     course_id:  
688     generation_request_id: generationRequestId,  
689     model_used: resolvedModel,  
690     prompt_tokens: 0,  
691     completion_tokens: 0,  
692     total_tokens: 0,  
693     latency_ms: latencyMs,  
694     question_count_requested: question_count,  
695     question_count_generated: 0,  
696     chunks_retrieved: chunks.length,  
697     status: "error",  
698     error_message: (llmError as Error).message,  
699   });  
700  
701   return new Response(  
702     JSON.stringify({  
703       error:  
704         "AI question generation failed after retries. Please try again later.",  
705       detail: (llmError as Error).message,  
706     }),  
707     {  
708       status: 502,  
709       headers: { ...corsHeaders, "Content-Type": "application/json" },  
710     }  
711   );  
712 }  
713  
714 // % % Step 7: Validate LLM Response % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
715  
716 const validatedQuestions: GeneratedQuestion[] = [];  
717 const validCloIds = clo_ids;  
718  
719 for (const rawQ of llmResult.questions) {  
720   const result = validateGeneratedQuestion(  
721     rawQ as unknown as Record<string, unknown>,  
722     validCloIds,  
723     bloom_levels,  
724     question_types  
725   );
```


[illegible]

```
830         question_count_generated: validatedQuestions.length,  
831         chunks_retrieved: chunks.length,  
832         status: "success",  
833         error_message: null,  
834     });  
835  
836     if (logError) {  
837         // Non-fatal – log but don't fail the request  
838         console.error("Failed to insert generation log:", logError.message);  
839     }  
840  
841     // % % Step 10: Return Response % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
842  
843     return new Response(  
844         JSON.stringify({  
845             generation_id: generationRequestId,  
846             questions: validatedQuestions,  
847             warnings,  
848             chunks_used: chunks.length,  
849         }),  
850         { headers: { ...corsHeaders, "Content-Type": "application/json" } }  
851     );  
852 } catch (error) {  
853     console.error(  
854         "Unhandled error in generate-quiz-questions:",  
855         (error as Error).message  
856     );  
857     return new Response(JSON.stringify({ error: (error as Error).message }), {  
858         status: 500,  
859         headers: { ...corsHeaders, "Content-Type": "application/json" },  
860     });  
861 }  
862 }};  
863
```

FILE: [supabase/functions/generate-reflection-digest/index.ts](#)

```
TYPE: .ts | LINES: 1-308 | SHA256: b45bd6b57a34281cf2bef043c6d7e41baa081083a4734341d9199b595cc0113e
```

```

1 // =====
2 // generate-reflection-digest - Monthly digest generation for students
3 // with "e3 reflections. Analyzes themes, growth, sentiment, focus areas.
4 //
5 // I-5 orphan decision (full-profile-audit-remediation, Task 13): INTENTIONALLY
6 // RETAINED, not removed. This function populates the `reflection_digests` table,
7 // which IS consumed in production by the client (`useReflectionDigest` !'
8 // ReflectionDigestCard on the student WeeklyPlannerPage). It is a monthly,
9 // schedule-driven generator that currently has no wired cron trigger; rather
10 // than delete a legitimate edge function that produces live-consumed data, it is
11 // kept so it can be attached to a pg_cron schedule when monthly digests are
12 // turned on. The only defect (the CORS `x-content-type` typo) is fixed above.
13 // =====
14
15 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
16 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
17
18 const corsHeaders = {
19   "Access-Control-Allow-Origin": "*",
20   "Access-Control-Allow-Headers":
21     "authorization, x-client-info, apikey, content-type",
22 };
23
24 // % % % Theme Extraction % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %
25
26 const THEME_KEYWORDS: Record<string, string[]> = {
27   "Time Management": [
28     "time",
29     "schedule",
30     "deadline",
31     "late",
32     "early",
33     "plan",
34     "organize",
35   ],
36   "Study Techniques": [
37     "study",
38     "practice",
39     "review",
40     "memorize",
41     "notes",
42     "flashcard",
43   ],
44   "Problem Solving": ["problem", "solve", "solution", "figure", "debug", "fix"],
45   Collaboration: ["team", "group", "partner", "discuss", "collaborate", "peer"],
46   "Understanding Concepts": [
47     "understand",
48     "concept",
49     "theory",
50     "principle",
51     "grasp",
52   ],
53   Motivation: ["motivat", "energy", "tired", "excited", "bored", "engaged"],
54   Confidence: [
55     "confident",
56     "unsure",
57     "doubt",
58     "believe",
59     "capable",
60     "struggle",
61   ],
62   Focus: ["focus", "distract", "concentrate", "attention", "zone"],
63 };
64
65 function extractThemes(
66   reflections: string[]

```

```
67   ): Array<{ topic: string; count: number }> {  
68     const combined = reflections.join(" ").toLowerCase();  
69     const themes: Array<{ topic: string; count: number }> = [];  
70  
71     for (const [topic, keywords] of Object.entries(THEME_KEYWORDS)) {  
72       const count = keywords.filter((kw) => combined.includes(kw)).length;  
73       if (count >= 2) {  
74         themes.push({ topic, count });  
75       }  
76     }  
77  
78     return themes.sort((a, b) => b.count - a.count).slice(0, 5);  
79   }  
80  
81 // % % % Growth Pattern Detection % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
82  
83 function detectGrowthPatterns(  
84   reflections: string[]  
85 ): Array<{ area: string; description: string }> {  
86   const patterns: Array<{ area: string; description: string }> = [];  
87  
88   const growthIndicators = [  
89     {  
90       area: "Self-awareness",  
91       keywords: ["realized", "noticed", "aware", "recognize"],  
92     },  
93     {  
94       area: "Adaptability",  
95       keywords: ["differently", "change", "adapt", "adjust", "try"],  
96     },  
97     {  
98       area: "Persistence",  
99       keywords: ["keep", "continue", "persist", "despite", "overcome"],  
100    },  
101    {  
102      area: "Critical Thinking",  
103      keywords: ["analyze", "evaluate", "compare", "question", "why"],  
104    },  
105  ];  
106  
107   const combined = reflections.join(" ").toLowerCase();  
108  
109   for (const indicator of growthIndicators) {  
110     const matches = indicator.keywords.filter((kw) => combined.includes(kw));  
111     if (matches.length >= 2) {  
112       patterns.push({  
113         area: indicator.area,  
114         description: `Demonstrated through use of reflective language (${matches  
115           .slice(0, 3)  
116           .join(", ")}`,  
117       });  
118     }  
119   }  
120  
121   return patterns.slice(0, 4);  
122 }  
123  
124 // % % % Emotional Trend Detection % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
125  
126 function detectEmotionalTrends(  
127   reflections: string[]  
128 ): Array<{ label: string }> {  
129   const emotionKeywords: Record<string, string[]> = {  
130     Confident: ["confident", "proud", "accomplished", "capable"],  
131     Curious: ["curious", "wonder", "interesting", "explore"],  
132     Frustrated: ["frustrated", "stuck", "difficult", "hard"],  
133     Motivated: ["motivated", "excited", "eager", "inspired"],  
134     Calm: ["calm", "relaxed", "comfortable", "peaceful"],  
135     Anxious: ["anxious", "worried", "nervous", "stressed"],  
136   };  
137  
138   const combined = reflections.join(" ").toLowerCase();  
139   const trends: Array<{ label: string; count: number }> = [];  
140  
141   for (const [label, keywords] of Object.entries(emotionKeywords)) {  
142     const count = keywords.filter((kw) => combined.includes(kw)).length;  
143     if (count >= 1) {  
144       trends.push({ label, count });  
145     }  
146   }  
147  
148   return trends  
149     .sort((a, b) => b.count - a.count)  
150     .slice(0, 4)  
151     .map(({ label }) => ({ label }));  
152 }  
153  
154 // % % % Focus Suggestions % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
155  
156 function suggestFocus(  
157   themes: Array<{ topic: string; count: number }>,  
158   patterns: Array<{ area: string }>  
159 ): Array<{ area: string; reason: string }> {  
160   const suggestions: Array<{ area: string; reason: string }> = [];  
161  
162   // Suggest based on most frequent themes  
163   if (themes.length > 0) {  
164     suggestions.push({  
165       area: themes[0].topic,  
166       reason: `This was your most discussed topic this month (${themes[0].count} mentions)`,  
167     });  
168   }  
169  
170   // Suggest areas not showing growth
```

[illegible]

[illegible]

```

171 | serve(async (req) => {
172 |   if (req.method === "OPTIONS") {
173 |     return new Response("ok", { headers: corsHeaders });
174 |   }
175 |
176 |   try {
177 |     const supabase = createClient(
178 |       Deno.env.get("SUPABASE_URL")!,
179 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
180 |     );
181 |
182 |     const body = await req.json();
183 |     const validation = validatePayload(body);
184 |
185 |     if (!validation.valid) {
186 |       return new Response(JSON.stringify({ error: validation.error }), {
187 |         status: 400,
188 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
189 |       });
190 |     }
191 |
192 |     const { student_id, self_efficacy_score, enrolled_course_ids } =
193 |       validation.data;
194 |
195 |     // %% 3.2.1 JWT validation and student_id verification % % % % % % % % % % % %
196 |
197 |     const authHeader = req.headers.get("Authorization") ?? "";
198 |     if (!authHeader) {
199 |       return new Response(
200 |         JSON.stringify({ error: "Missing Authorization header" }),
201 |         {
202 |           status: 401,
203 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
204 |         }
205 |       );
206 |     }
207 |
208 |     const userClient = createClient(
209 |       Deno.env.get("SUPABASE_URL")!,
210 |       Deno.env.get("SUPABASE_ANON_KEY")!,
211 |       { global: { headers: { Authorization: authHeader } } }
212 |     );
213 |
214 |     const {
215 |       data: { user },
216 |       error: authError,
217 |     } = await userClient.auth.getUser();
218 |
219 |     if (authError || !user) {
220 |       return new Response(
221 |         JSON.stringify({ error: "Invalid or expired token" }),
222 |         {
223 |           status: 401,
224 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
225 |         }
226 |       );
227 |     }
228 |
229 |     if (user.id !== student_id) {
230 |       return new Response(
231 |         JSON.stringify({
232 |           error: "Forbidden: student_id does not match authenticated user",
233 |         }),
234 |         {
235 |           status: 403,
236 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
237 |         }
238 |       );
239 |     }
240 |
241 |     // %% 3.2.2 Fetch enrolled courses with schedules and upcoming deadlines (14 days) % %
242 |
243 |     let courseIds = enrolled_course_ids;
244 |
245 |     // If no course IDs provided, fetch from student_courses
246 |     if (courseIds.length === 0) {
247 |       const { data: enrollments, error: enrollErr } = await supabase
248 |         .from("student_courses")
249 |         .select("course_id")
250 |         .eq("student_id", student_id);
251 |
252 |       if (enrollErr) {
253 |         console.error("Failed to fetch enrollments:", enrollErr.message);
254 |         return new Response(
255 |           JSON.stringify({
256 |             error: "Failed to fetch enrolled courses",
257 |             detail: enrollErr.message,
258 |           }),
259 |           {
260 |             status: 500,
261 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
262 |           }
263 |         );
264 |       }
265 |
266 |       courseIds = (enrollments ?? []).map(
267 |         (e: { course_id: string }) => e.course_id
268 |       );
269 |     }
270 |
271 |     // %% 3.2.7 Handle edge case: no enrolled courses !' generate generic study habit sessions % %
272 |
273 |     const today = new Date();
274 |     const todayStr = today.toISOString().slice(0, 10);

```

```

275 |
276 | if (courseIds.length === 0) {
277 |   const tier = getSelfEfficacyTier(self_efficacy_score);
278 |   const { sessions: sessionCount, duration } = STARTER_SESSION_TIERS[tier];
279 |
280 |   const genericSessions: StarterWeekSession[] = [];
281 |   const genericTypes: StarterWeekSession["session_type"][] = [
282 |     "exploration",
283 |     "reading",
284 |     "practice",
285 |     "review",
286 |     "exploration",
287 |   ];
288 |
289 |   for (let i = 0; i < sessionCount; i++) {
290 |     const sessionDate = new Date(today);
291 |     sessionDate.setDate(today.getDate() + i + 1); // start from tomorrow
292 |     genericSessions.push({
293 |       course_id: null,
294 |       session_type: genericTypes[i % genericTypes.length],
295 |       suggested_date: sessionDate.toISOString().slice(0, 10),
296 |       suggested_time_slot: TIME_SLOTS[i % TIME_SLOTS.length],
297 |       duration_minutes: duration,
298 |       description: generateDescription(
299 |         genericTypes[i % genericTypes.length],
300 |         null,
301 |         null
302 |       ),
303 |     });
304 |   }
305 |
306 |   // INSERT generic sessions
307 |   const rows = genericSessions.map((s) => ({
308 |     student_id,
309 |     course_id: s.course_id,
310 |     session_type: s.session_type,
311 |     suggested_date: s.suggested_date,
312 |     suggested_time_slot: s.suggested_time_slot,
313 |     duration_minutes: s.duration_minutes,
314 |     description: s.description,
315 |     status: "suggested",
316 |   }));
317 |
318 |   const { error: insertErr } = await supabase
319 |     .from("starter_week_sessions")
320 |     .insert(rows);
321 |
322 |   if (insertErr) {
323 |     console.error("Failed to insert generic sessions:", insertErr.message);
324 |     return new Response(
325 |       JSON.stringify({
326 |         error: "Failed to save starter week sessions",
327 |         detail: insertErr.message,
328 |       }),
329 |       {
330 |         status: 500,
331 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
332 |       }
333 |     );
334 |   }
335 |
336 |   return new Response(
337 |     JSON.stringify({ success: true, sessions: genericSessions }),
338 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
339 |   );
340 | }
341 |
342 | // Fetch course details
343 | const { data: courses, error: coursesErr } = await supabase
344 |   .from("courses")
345 |   .select("id, name")
346 |   .in("id", courseIds);
347 |
348 | if (coursesErr) {
349 |   console.error("Failed to fetch courses:", coursesErr.message);
350 |   return new Response(
351 |     JSON.stringify({
352 |       error: "Failed to fetch course details",
353 |       detail: coursesErr.message,
354 |     }),
355 |     {
356 |       status: 500,
357 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
358 |     }
359 |   );
360 | }
361 |
362 | const courseMap = new Map(
363 |   (courses ?? []).map((c: { id: string; name: string }) => [c.id, c.name])
364 | );
365 |
366 | // Fetch upcoming deadlines (next 14 days)
367 | const fourteenDaysLater = new Date(today);
368 | fourteenDaysLater.setDate(today.getDate() + 14);
369 | const deadlineCutoff = fourteenDaysLater.toISOString().slice(0, 10);
370 |
371 | const { data: assignments, error: assignmentsErr } = await supabase
372 |   .from("assignments")
373 |   .select("id, course_id, due_date")
374 |   .in("course_id", courseIds)
375 |   .gte("due_date", todayStr)
376 |   .lte("due_date", deadlineCutoff)
377 |   .order("due_date", { ascending: true });
378 |

```



```

379 | if (assignmentsErr) {
380 |   console.error("Failed to fetch assignments:", assignmentsErr.message);
381 |   // Non-fatal – proceed without deadline data
382 | }
383 |
384 | // Build course-to-nearest-deadline map
385 | const courseDeadlines = new Map<string, number>();
386 | for (const a of assignments ?? []) {
387 |   const dueDate = new Date(a.due_date as string);
388 |   const daysUntil = Math.ceil(
389 |     (dueDate.getTime() - today.getTime()) / (1000 * 60 * 60 * 24)
390 |   );
391 |   const existing = courseDeadlines.get(a.course_id as string);
392 |   if (existing === undefined || daysUntil < existing) {
393 |     courseDeadlines.set(a.course_id as string, daysUntil);
394 |   }
395 | }
396 |
397 | // % % 3.2.3 Fetch historical cohort study patterns for similar courses % %
398 |
399 | const { data: cohortPatterns, error: cohortErr } = await supabase
400 |   .from("starter_week_sessions")
401 |   .select("course_id, session_type, suggested_time_slot")
402 |   .in("course_id", courseIds)
403 |   .eq("status", "completed")
404 |   .limit(100);
405 |
406 | if (cohortErr) {
407 |   console.error("Failed to fetch cohort patterns:", cohortErr.message);
408 |   // Non-fatal – proceed without cohort data
409 | }
410 |
411 | // Determine preferred time slots from cohort data
412 | const slotCounts: Record<string, number> = {
413 |   morning: 0,
414 |   afternoon: 0,
415 |   evening: 0,
416 | };
417 | for (const p of cohortPatterns ?? []) {
418 |   const slot = p.suggested_time_slot as string;
419 |   if (slot in slotCounts) {
420 |     slotCounts[slot]++;
421 |   }
422 | }
423 |
424 | // % % 3.2.4 Determine session count and duration based on self-efficacy tier % %
425 |
426 | const tier = getSelfEfficacyTier(self_efficacy_score);
427 | const { sessions: sessionCount, duration } = STARTER_SESSION_TIERS[tier];
428 |
429 | // % % 3.2.5 Distribute sessions across 7-day window, assign session types % %
430 |
431 | // Build a list of courses sorted by deadline proximity (nearest first)
432 | const coursesWithDeadlines: CourseWithDeadline[] = courseIds.map((cid) => ({
433 |   course_id: cid,
434 |   course_name: courseMap.get(cid) ?? "Unknown Course",
435 |   nearest_deadline_days: courseDeadlines.get(cid) ?? null,
436 | }));
437 |
438 | // Sort: courses with deadlines first (nearest first), then courses without deadlines
439 | coursesWithDeadlines.sort((a, b) => {
440 |   if (a.nearest_deadline_days === null && b.nearest_deadline_days === null)
441 |     return 0;
442 |   if (a.nearest_deadline_days === null) return 1;
443 |   if (b.nearest_deadline_days === null) return -1;
444 |   return a.nearest_deadline_days - b.nearest_deadline_days;
445 | });
446 |
447 | const sessions: StarterWeekSession[] = [];
448 |
449 | for (let i = 0; i < sessionCount; i++) {
450 |   // Round-robin across courses, prioritizing those with nearest deadlines
451 |   const courseInfo = coursesWithDeadlines[i % coursesWithDeadlines.length];
452 |
453 |   // Distribute across 7-day window starting from tomorrow
454 |   const dayOffset = Math.floor((i * 7) / sessionCount) + 1;
455 |   const sessionDate = new Date(today);
456 |   sessionDate.setDate(today.getDate() + dayOffset);
457 |
458 |   const sessionType = getSessionType(courseInfo.nearest_deadline_days);
459 |   const timeSlot = TIME_SLOTS[i % TIME_SLOTS.length];
460 |
461 |   sessions.push({
462 |     course_id: courseInfo.course_id,
463 |     session_type: sessionType,
464 |     suggested_date: sessionDate.toISOString().slice(0, 10),
465 |     suggested_time_slot: timeSlot,
466 |     duration_minutes: duration,
467 |     description: generateDescription(
468 |       sessionType,
469 |       courseInfo.course_name,
470 |       courseInfo.nearest_deadline_days
471 |     ),
472 |   });
473 | }
474 |
475 | // % % 3.2.6 INSERT sessions into starter_week_sessions table % % % % % % % %
476 |
477 | const rows = sessions.map((s) => ({
478 |   student_id,
479 |   course_id: s.course_id,
480 |   session_type: s.session_type,
481 |   suggested_date: s.suggested_date,
482 |   suggested_time_slot: s.suggested_time_slot,

```

```

483 duration_minutes: s.duration_minutes,
484 description: s.description,
485 status: "suggested",
486 ));
487
488 const { error: insertErr } = await supabase
489   .from("starter_week_sessions")
490   .insert(rows);
491
492 if (insertErr) {
493   console.error(
494     "Failed to insert starter week sessions:",
495     insertErr.message
496   );
497   return new Response(
498     JSON.stringify({
499       error: "Failed to save starter week sessions",
500       detail: insertErr.message,
501     }),
502     {
503       status: 500,
504       headers: { ...corsHeaders, "Content-Type": "application/json" },
505     }
506   );
507 }
508
509 return new Response(JSON.stringify({ success: true, sessions }), {
510   headers: { ...corsHeaders, "Content-Type": "application/json" },
511 });
512 } catch (error) {
513   return new Response(JSON.stringify({ error: (error as Error).message }), {
514     status: 500,
515     headers: { ...corsHeaders, "Content-Type": "application/json" },
516   });
517 }
518 });
519

```

FILE: supabase/functions/generate-transcript/index.ts

TYPE: .ts | LINES: 1-228 | SHA256: 2cceaf9fd173fff2e49c932d413d921ee91c0e0263fbc090ea4ca4c7d299d6b2

```

1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 import { jsPDF } from "https://esm.sh/jspdf@2";
4 import autoTable from "https://esm.sh/jspdf-autotable@3";
5 import { z } from "https://esm.sh/zod@3.23.8";
6
7 const PayloadSchema = z.object({
8   student_id: z.string().min(1),
9   semester_id: z.string().optional(),
10 });
11
12 const corsHeaders = {
13   "Access-Control-Allow-Origin": "*",
14   "Access-Control-Allow-Headers":
15     "authorization, x-client-info, apikey, content-type",
16 };
17
18 serve(async (req) => {
19   if (req.method === "OPTIONS")
20     return new Response("ok", { headers: corsHeaders });
21
22   try {
23     const supabase = createClient(
24       Deno.env.get("SUPABASE_URL")!,
25       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
26     );
27
28     // %% Auth: verify caller JWT and privileged role %%%%%%%%%%%%%%%
29     const authHeader = req.headers.get("Authorization");
30     if (!authHeader) {
31       return new Response(
32         JSON.stringify({ error: "Missing authorization header" }),
33         {
34           status: 401,
35           headers: { ...corsHeaders, "Content-Type": "application/json" },
36         }
37       );
38     }
39
40     const token = authHeader.replace("Bearer ", "");
41     const {
42       data: { user },
43       error: authError,
44     } = await supabase.auth.getUser(token);
45
46     if (authError || !user) {
47       return new Response(JSON.stringify({ error: "Unauthorized" }), {
48         status: 401,
49         headers: { ...corsHeaders, "Content-Type": "application/json" },
50       });
51     }
52
53     const { data: callerProfile } = await supabase
54       .from("profiles")
55       .select("role, institution_id")
56       .eq("id", user.id)
57       .single();
58
59     if (
60       !callerProfile ||
61       ![
62         "admin",
63         "coordinator"
64       ].includes(callerProfile.role)
65     ) {
66       return new Response(

```

[illegible]

```

168 |         head: ["Assessment", "Score", "Max", "%"],
169 |         body:
170 |             courseGrades.length > 0
171 |             ? courseGrades
172 |                 .slice(0, 5)
173 |                 .map(
174 |                     (g: {
175 |                         assignment_id: string;
176 |                         score: number;
177 |                         max_score: number;
178 |                     }) => [
179 |                         g.assignment_id.slice(0, 8),
180 |                         String(g.score),
181 |                         String(g.max_score),
182 |                         g.max_score > 0
183 |                         ? ((g.score / g.max_score) * 100).toFixed(1)
184 |                         : "0",
185 |                     ]
186 |                 )
187 |             : ["No grades recorded", "", "", ""],
188 |         theme: "grid",
189 |         headStyles: { fillColor: [59, 130, 246] },
190 |         styles: { fontSize: 7 },
191 |     });
192 |     y = (doc.lastAutoTable?.finalY ?? y + 20) + 10;
193 | }
194 |
195 | const pdfBytes = doc.output("arraybuffer") as Uint8Array;
196 | const ts = new Date().toISOString().replace(/[:.]/g, "-");
197 | const fileName = `transcripts/${student_id.slice(0, 8)}_${ts}.pdf`;
198 |
199 | await supabase.storage
200 |     .createBucket("transcripts", { public: false })
201 |     .catch(() => {});
202 | const { error: uploadErr } = await supabase.storage
203 |     .from("transcripts")
204 |     .upload(fileName, pdfBytes, { contentType: "application/pdf" });
205 | if (uploadErr) throw new Error(uploadErr.message);
206 |
207 | const { data: signedUrl } = await supabase.storage
208 |     .from("transcripts")
209 |     .createSignedUrl(fileName, 3600);
210 |
211 | return new Response(
212 |     JSON.stringify({
213 |         success: true,
214 |         download_url: signedUrl?.signedUrl,
215 |         file_name: fileName,
216 |     }),
217 |     {
218 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
219 |     }
220 | );
221 | } catch (error) {
222 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
223 |         status: 500,
224 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
225 |     });
226 | }
227 | });
228 |

```

FILE: supabase/functions/health/index.ts

TYPE: .ts | LINES: 1-74 | SHA256: edc12fabdccbde28557aa534ff65560407a1c313d710546a8eeacc687ddb3aa3

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |     "Access-Control-Allow-Origin": "*",
6 |     "Access-Control-Allow-Headers":
7 |         "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | interface HealthResponse {
11 |     status: "ok" | "error";
12 |     database: "connected" | "unreachable";
13 |     timestamp: string;
14 | }
15 |
16 | serve(async (req) => {
17 |     if (req.method === "OPTIONS") {
18 |         return new Response("ok", { headers: corsHeaders });
19 |     }
20 |
21 |     const timestamp = new Date().toISOString();
22 |
23 |     try {
24 |         const supabase = createClient(
25 |             Deno.env.get("SUPABASE_URL")!,
26 |             Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
27 |         );
28 |
29 |         // Lightweight database connectivity check
30 |         const { error } = await supabase
31 |             .rpc("sql", { query: "SELECT 1" })
32 |             .maybeSingle();
33 |
34 |         // Fallback: if rpc('sql') is unavailable, try a minimal table query
35 |         if (error) {
36 |             const { error: fallbackError } = await supabase
37 |                 .from("profiles")
38 |                 .select("id")
39 |                 .limit(1);

```

```

40 |
41 |     if (fallbackError) {
42 |         const response: HealthResponse = {
43 |             status: "error",
44 |             database: "unreachable",
45 |             timestamp,
46 |         };
47 |         return new Response(JSON.stringify(response), {
48 |             status: 503,
49 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
50 |         });
51 |     }
52 | }
53 |
54 | const response: HealthResponse = {
55 |     status: "ok",
56 |     database: "connected",
57 |     timestamp,
58 | };
59 | return new Response(JSON.stringify(response), {
60 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
61 | });
62 | } catch {
63 |     const response: HealthResponse = {
64 |         status: "error",
65 |         database: "unreachable",
66 |         timestamp,
67 |     };
68 |     return new Response(JSON.stringify(response), {
69 |         status: 503,
70 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
71 |     });
72 | }
73 | });
74 |

```

FILE: [supabase/functions/import-competency-csv/index.ts](#)

TYPE: .ts | LINES: 1-243 | SHA256: 8af209933efebbe38578bb62084e93864e697ef5449604e1deb516467dfae37d

```

1 | // Task 114.4: CSV import Edge Function for competency frameworks
2 | // Parses CSV, builds three-level hierarchy: Domain !' Competency !' Indicator
3 |
4 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
5 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
6 | import {
7 |   authenticateRequest,
8 |   unauthorizedResponse,
9 |   forbiddenResponse,
10 | } from "../_shared/auth.ts";
11 |
12 | const corsHeaders = {
13 |   "Access-Control-Allow-Origin": "*",
14 |   "Access-Control-Allow-Headers":
15 |     "authorization, x-client-info, apikey, content-type",
16 | };
17 |
18 | interface CSVRow {
19 |   domain_code: string;
20 |   domain_title: string;
21 |   competency_code: string;
22 |   competency_title: string;
23 |   indicator_code: string;
24 |   indicator_title: string;
25 | }
26 |
27 | function parseCSV(content: string): CSVRow[] {
28 |   const lines = content.trim().split("\n");
29 |   if (lines.length < 2) return [];
30 |
31 |   const headers = lines[0].split(",").map((h) => h.trim().toLowerCase());
32 |   const requiredHeaders = [
33 |     "domain_code",
34 |     "domain_title",
35 |     "competency_code",
36 |     "competency_title",
37 |     "indicator_code",
38 |     "indicator_title",
39 |   ];
40 |
41 |   for (const req of requiredHeaders) {
42 |     if (!headers.includes(req)) {
43 |       throw new Error(`Missing required CSV header: ${req}`);
44 |     }
45 |   }
46 |
47 |   const rows: CSVRow[] = [];
48 |   for (let i = 1; i < lines.length; i++) {
49 |     const values = lines[i].split(",").map((v) => v.trim());
50 |     if (values.length < headers.length) continue;
51 |
52 |     const row: Record<string, string> = {};
53 |     headers.forEach((h, idx) => {
54 |       row[h] = values[idx] ?? "";
55 |     });
56 |
57 |     if (!row.domain_code || !row.indicator_code) continue;
58 |
59 |     rows.push({
60 |       domain_code: row.domain_code,
61 |       domain_title: row.domain_title,
62 |       competency_code: row.competency_code,
63 |       competency_title: row.competency_title,
64 |       indicator_code: row.indicator_code,
65 |       indicator_title: row.indicator_title,

```

```

66 |     });
67 | }
68 |
69 | return rows;
70 | }
71 |
72 | serve(async (req) => {
73 |   if (req.method === "OPTIONS") {
74 |     return new Response("ok", { headers: corsHeaders });
75 |   }
76 |
77 |   try {
78 |     // Caller check (Req 18): competency-framework import is an admin/coordinator
79 |     // curriculum action and runs with the service-role client, so authorize the
80 |     // caller in-handler.
81 |     const auth = await authenticateRequest(req);
82 |     if (!auth.user) {
83 |       return unauthorizedResponse(auth.error ?? "Unauthorized");
84 |     }
85 |     if (!["admin", "coordinator"].includes(auth.user.role)) {
86 |       return forbiddenResponse("Forbidden: admin or coordinator role required");
87 |     }
88 |
89 |     const supabase = createClient(
90 |       Deno.env.get("SUPABASE_URL")!,
91 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
92 |     );
93 |
94 |     const { framework_id, csv_content } = await req.json();
95 |
96 |     if (!framework_id || !csv_content) {
97 |       return new Response(
98 |         JSON.stringify({ error: "framework_id and csv_content are required" }),
99 |         {
100 |           status: 400,
101 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
102 |         }
103 |       );
104 |     }
105 |
106 |     // Tenant scope: the framework must belong to the caller's institution.
107 |     const { data: framework } = await supabase
108 |       .from("competency_frameworks")
109 |       .select("institution_id")
110 |       .eq("id", framework_id)
111 |       .maybeSingle();
112 |     if (!framework) {
113 |       return new Response(JSON.stringify({ error: "Framework not found" }), {
114 |         status: 404,
115 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
116 |       });
117 |     }
118 |     if (
119 |       (framework as { institution_id: string }).institution_id !==
120 |       auth.user.institution_id
121 |     ) {
122 |       return forbiddenResponse(
123 |         "Forbidden: framework belongs to another institution"
124 |       );
125 |     }
126 |
127 |     const rows = parseCSV(csv_content);
128 |     if (rows.length === 0) {
129 |       return new Response(
130 |         JSON.stringify({ error: "No valid rows found in CSV" }),
131 |         {
132 |           status: 400,
133 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
134 |         }
135 |       );
136 |     }
137 |
138 |     // Build hierarchy: track domains and competencies by code
139 |     const domainMap = new Map<string, string>(); // code !' id
140 |     const competencyMap = new Map<string, string>(); // code !' id
141 |     const errors: string[] = [];
142 |     let imported = 0;
143 |     let sortOrder = 0;
144 |
145 |     for (const row of rows) {
146 |       try {
147 |         // Upsert domain
148 |         if (!domainMap.has(row.domain_code)) {
149 |           const { data: domain, error: domErr } = await supabase
150 |             .from("competency_items")
151 |             .upsert(
152 |               {
153 |                 framework_id,
154 |                 parent_id: null,
155 |                 level: "domain",
156 |                 code: row.domain_code,
157 |                 title: row.domain_title,
158 |                 sort_order: sortOrder++,
159 |               },
160 |               { onConflict: "framework_id,code" }
161 |             )
162 |             .select("id")
163 |             .single();
164 |
165 |           if (domErr) {
166 |             errors.push(`Domain ${row.domain_code}: ${domErr.message}`);
167 |             continue;
168 |           }
169 |           domainMap.set(row.domain_code, domain.id);

```

```

170 |     }
171 |
172 |     // Upsert competency
173 |     const domainId = domainMap.get(row.domain_code)!;
174 |     if (!competencyMap.has(row.competency_code)) {
175 |       const { data: comp, error: compErr } = await supabase
176 |         .from("competency_items")
177 |         .upsert(
178 |           {
179 |             framework_id,
180 |             parent_id: domainId,
181 |             level: "competency",
182 |             code: row.competency_code,
183 |             title: row.competency_title,
184 |             sort_order: sortOrder++,
185 |           },
186 |           { onConflict: "framework_id,code" }
187 |         )
188 |         .select("id")
189 |         .single();
190 |
191 |     if (compErr) {
192 |       errors.push(
193 |         `Competency ${row.competency_code}: ${compErr.message}`
194 |       );
195 |       continue;
196 |     }
197 |     competencyMap.set(row.competency_code, comp.id);
198 |   }
199 |
200 |   // Upsert indicator
201 |   const competencyId = competencyMap.get(row.competency_code)!;
202 |   const { error: indErr } = await supabase
203 |     .from("competency_items")
204 |     .upsert(
205 |       {
206 |         framework_id,
207 |         parent_id: competencyId,
208 |         level: "indicator",
209 |         code: row.indicator_code,
210 |         title: row.indicator_title,
211 |         sort_order: sortOrder++,
212 |       },
213 |       { onConflict: "framework_id,code" }
214 |     );
215 |
216 |   if (indErr) {
217 |     errors.push(`Indicator ${row.indicator_code}: ${indErr.message}`);
218 |   } else {
219 |     imported++;
220 |   }
221 | } catch (rowErr) {
222 |   errors.push(`Row error: ${(rowErr as Error).message}`);
223 | }
224 | }
225 |
226 | return new Response(
227 |   JSON.stringify({
228 |     success: true,
229 |     imported,
230 |     domains: domainMap.size,
231 |     competencies: competencyMap.size,
232 |     errors,
233 |   }),
234 |   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
235 | );
236 | } catch (error) {
237 |   return new Response(JSON.stringify({ error: (error as Error).message })), {
238 |     status: 500,
239 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
240 |   });
241 | }
242 | });
243 |

```

FILE: supabase/functions/improvement-bonus-check/index.ts

TYPE: .ts | LINES: 1-108 | SHA256: e6ef9054bf13ddac563fcabc9e1af94de9d607837d1203b85ddfadd13527df7c

```

1 | // Task 139.1: Improvement Bonus Check Edge Function
2 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
3 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
4 | import { z } from "https://esm.sh/zod@3.23.8";
5 |
6 | const PayloadSchema = z.object({
7 |   student_id: z.string().min(1),
8 |   clo_id: z.string().min(1),
9 |   current_score_percent: z.number(),
10 | });
11 |
12 | const corsHeaders = {
13 |   "Access-Control-Allow-Origin": "*",
14 |   "Access-Control-Allow-Headers":
15 |     "authorization, x-client-info, apikey, content-type",
16 | };
17 |
18 | const IMPROVEMENT_THRESHOLD_PP = 15;
19 | const IMPROVEMENT_BONUS_XP = 50;
20 |
21 | serve(async (req) => {
22 |   if (req.method === "OPTIONS")
23 |     return new Response("ok", { headers: corsHeaders });
24 |   try {
25 |     const supabase = createClient(
26 |       Deno.env.get("SUPABASE_URL")!,

```

```

27 |     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
28 | );
29 | const body = await req.json();
30 | const parsed = PayloadSchema.safeParse(body);
31 | if (!parsed.success) {
32 |   return new Response(JSON.stringify({ error: parsed.error.message }), {
33 |     status: 400,
34 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
35 |   });
36 | }
37 | const { student_id, clo_id, current_score_percent } = parsed.data;
38 | // Find previous evidence scores for same CLO and student
39 | const { data: prevEvidence, error: prevErr } = await supabase
40 |   .from("evidence")
41 |   .select("score_percent")
42 |   .eq("student_id", student_id)
43 |   .eq("clo_id", clo_id)
44 |   .order("created_at", { ascending: false })
45 |   .limit(2);
46 | if (prevErr) throw prevErr;
47 | // Need at least 2 records (current + previous)
48 | if (!prevEvidence || prevEvidence.length < 2) {
49 |   return new Response(
50 |     JSON.stringify({
51 |       success: true,
52 |       bonus_awarded: false,
53 |       reason: "No previous evidence",
54 |     }),
55 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
56 |   );
57 | }
58 | const previousPercent = prevEvidence[1].score_percent;
59 | const improvement = current_score_percent - previousPercent;
60 | if (improvement < IMPROVEMENT_THRESHOLD_PP) {
61 |   return new Response(
62 |     JSON.stringify({
63 |       success: true,
64 |       bonus_awarded: false,
65 |       improvement,
66 |       reason: "Improvement below 15pp threshold",
67 |     }),
68 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
69 |   );
70 | }
71 |
72 | // Award 50 XP with source = improvement_bonus (Req 123.5)
73 | // Store CLO ref and previous/current scores in note JSON
74 | const noteData = {
75 |   action_type: "improvement_bonus",
76 |   clo_id,
77 |   previous_percent: previousPercent,
78 |   current_percent: current_score_percent,
79 |   improvement_pp: improvement,
80 | };
81 | await supabase.functions.invoke("award-xp", {
82 |   body: {
83 |     student_id,
84 |     xp_amount: IMPROVEMENT_BONUS_XP,
85 |     source: "improvement_bonus",
86 |     reference_id: "improvement:" + clo_id + ":" + Date.now(),
87 |     note: JSON.stringify(noteData),
88 |   },
89 | });
90 | return new Response(
91 |   JSON.stringify({
92 |     success: true,
93 |     bonus_awarded: true,
94 |     improvement,
95 |     xp_awarded: IMPROVEMENT_BONUS_XP,
96 |     previous_percent: previousPercent,
97 |     current_percent: current_score_percent,
98 |   }),
99 |   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
100 | );
101 | } catch (error) {
102 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
103 |     status: 500,
104 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
105 |   });
106 | }
107 | });
108 |

```

FILE: supabase/functions/leaderboard-refresh/index.ts

TYPE: .ts | LINES: 1-71 | SHA256: af5cc5597c7b06f5a9bdd1c54075879f2bf721d16f11bdeb326f95bc4de867c5

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |   "Access-Control-Allow-Origin": "*",
6 |   "Access-Control-Allow-Headers":
7 |     "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | serve(async (req) => {
11 |   if (req.method === "OPTIONS") {
12 |     return new Response("ok", { headers: corsHeaders });
13 |   }
14 |
15 |   try {
16 |     // This function is called by the Vercel cron (api/cron/leaderboard-refresh.ts)
17 |     // which passes the service role key as the Authorization bearer token.
18 |     // Verify the caller is using the service role key.

```



```

19 |     const authHeader = req.headers.get("Authorization");
20 |     const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!;
21 |     if (!authHeader || authHeader !== `Bearer ${serviceRoleKey}`) {
22 |         return new Response(
23 |             JSON.stringify({ error: "Unauthorized – service role key required" }),
24 |             {
25 |                 status: 401,
26 |                 headers: { ...corsHeaders, "Content-Type": "application/json" },
27 |             }
28 |         );
29 |     }
30 |
31 |     const supabase = createClient(
32 |         Deno.env.get("SUPABASE_URL")!,
33 |         serviceRoleKey
34 |     );
35 |
36 |     // leaderboard_weekly is now a regular VIEW (not materialized).
37 |     // It computes on-demand from xp_transactions – no refresh needed.
38 |     // This Edge Function serves as a health check for the Vercel cron.
39 |     const { data, error } = await supabase
40 |         .from("leaderboard_weekly")
41 |         .select("student_id", { count: "exact", head: true });
42 |
43 |     if (error) {
44 |         return new Response(
45 |             JSON.stringify({ success: false, error: error.message }),
46 |             {
47 |                 status: 500,
48 |                 headers: { ...corsHeaders, "Content-Type": "application/json" },
49 |             }
50 |         );
51 |     }
52 |
53 |     return new Response(
54 |         JSON.stringify({
55 |             success: true,
56 |             message:
57 |                 "Leaderboard view is accessible. It is a regular VIEW computed on-demand (no refresh needed).",
58 |             checked_at: new Date().toISOString(),
59 |         }),
60 |         {
61 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
62 |         }
63 |     );
64 | } catch (error) {
65 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
66 |         status: 500,
67 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
68 |     });
69 | }
70 | });
71 |

```

FILE: supabase/functions/notification-digest/index.ts

TYPE: .ts | LINES: 1-202 | SHA256: a8e0817606d8ccc106eb741c312aae8522c57925bd506784594d09b8e8edeab4

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |     "Access-Control-Allow-Origin": "*",
6 |     "Access-Control-Allow-Headers":
7 |         "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | // =====
11 | // notification-digest – pg_cron triggered at 8 PM daily
12 | // Aggregates undelivered notifications into a single daily summary
13 | // for students with digest preference enabled.
14 | // Validates: Requirements 65.4, 65.5
15 | // =====
16 |
17 | serve(async (req) => {
18 |     if (req.method === "OPTIONS") {
19 |         return new Response("ok", { headers: corsHeaders });
20 |     }
21 |
22 |     try {
23 |         // % % Auth: cron secret or service role only % % % % % % % % % % % % % % % % % %
24 |         const cronSecret = req.headers.get("x-cron-secret");
25 |         const expectedSecret = Deno.env.get("CRON_SECRET");
26 |         const authHeader = req.headers.get("Authorization") ?? "";
27 |         const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY") ?? "";
28 |         const isServiceRole =
29 |             serviceRoleKey && authHeader.replace("Bearer ", "") === serviceRoleKey;
30 |         const isCron = expectedSecret && cronSecret === expectedSecret;
31 |
32 |         if (!isServiceRole && !isCron) {
33 |             return new Response(
34 |                 JSON.stringify({
35 |                     error: "Unauthorized: cron secret or service role required",
36 |                 }),
37 |                 {
38 |                     status: 401,
39 |                     headers: { ...corsHeaders, "Content-Type": "application/json" },
40 |                 }
41 |             );
42 |         }
43 |
44 |         const supabase = createClient(
45 |             Deno.env.get("SUPABASE_URL")!,
46 |             Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
47 |         );

```

```

48 |
49 | // Step 1: Find all students with digest preference enabled
50 | const { data: digestProfiles, error: profilesErr } = await supabase
51 |   .from("profiles")
52 |   .select("id, email_preferences")
53 |   .eq("role", "student")
54 |   .eq("is_active", true);
55 |
56 | if (profilesErr) {
57 |   console.error("Failed to fetch profiles:", profilesErr.message);
58 |   return new Response(
59 |     JSON.stringify({
60 |       error: "Failed to fetch profiles",
61 |       detail: profilesErr.message,
62 |     }),
63 |     {
64 |       status: 500,
65 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
66 |     }
67 |   );
68 | }
69 |
70 | // Filter to students who have notification_digest enabled
71 | const digestStudentIds = (digestProfiles ?? [])
72 |   .filter((p: { email_preferences: Record<string, unknown> | null }) => {
73 |     const prefs = p.email_preferences;
74 |     return (
75 |       prefs &&
76 |       (prefs as Record<string, unknown>).notification_digest === true
77 |     );
78 |   })
79 |   .map((p: { id: string }) => p.id);
80 |
81 | if (digestStudentIds.length === 0) {
82 |   return new Response(
83 |     JSON.stringify({
84 |       success: true,
85 |       digests_created: 0,
86 |       message: "No digest subscribers",
87 |     }),
88 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
89 |   );
90 | }
91 |
92 | // Step 2: For each digest subscriber, aggregate unread notifications from today
93 | const todayStart = new Date();
94 | todayStart.setUTCHours(0, 0, 0, 0);
95 | const todayStartISO = todayStart.toISOString();
96 |
97 | let digestsCreated = 0;
98 |
99 | for (const studentId of digestStudentIds) {
100 |   // Fetch unread, non-digest notifications from today
101 |   const { data: unreadNotifications, error: fetchErr } = await supabase
102 |     .from("notifications")
103 |     .select("id, type, title, body, created_at")
104 |     .eq("user_id", studentId)
105 |     .eq("is_read", false)
106 |     .gte("created_at", todayStartISO)
107 |     .order("created_at", { ascending: false });
108 |
109 |   if (fetchErr) {
110 |     console.error(
111 |       `Failed to fetch notifications for ${studentId}:`,
112 |       fetchErr.message
113 |     );
114 |     continue;
115 |   }
116 |
117 |   if (!unreadNotifications || unreadNotifications.length === 0) continue;
118 |
119 |   // Filter out any existing digest notifications to avoid recursion
120 |   const nonDigestNotifications = unreadNotifications.filter(
121 |     (n: { type: string; title: string }) =>
122 |       !(n.type === "digest" || n.title.startsWith("Daily Digest"))
123 |   );
124 |
125 |   if (nonDigestNotifications.length === 0) continue;
126 |
127 |   // Build summary by type
128 |   const typeCounts = new Map<string, number>();
129 |   for (const n of nonDigestNotifications) {
130 |     const t = n.type as string;
131 |     typeCounts.set(t, (typeCounts.get(t) ?? 0) + 1);
132 |   }
133 |
134 |   const summaryParts: string[] = [];
135 |   for (const [type, count] of typeCounts) {
136 |     summaryParts.push(
137 |       `${count} ${type.replace(/_/g, " ")}${count > 1 ? "s" : ""}`
138 |     );
139 |   }
140 |
141 |   const summaryBody = `Today's summary: ${summaryParts.join(", ")}`;
142 |
143 |   // Step 3: Create a single digest notification
144 |   const { error: insertErr } = await supabase.from("notifications").insert({
145 |     user_id: studentId,
146 |     type: "digest",
147 |     title: `Daily Digest - ${nonDigestNotifications.length} notifications`,
148 |     body: summaryBody,
149 |     is_read: false,
150 |     metadata: {
151 |       is_digest: true,

```

```

152     notification_count: nonDigestNotifications.length,
153     type_breakdown: Object.fromEntries(typeCounts),
154     aggregated_ids: nonDigestNotifications.map(
155       (n: { id: string }) => n.id
156     ),
157   },
158 });
159
160 if (insertErr) {
161   console.error(
162     `Failed to create digest for ${studentId}:`,
163     insertErr.message
164   );
165   continue;
166 }
167
168 // Step 4: Mark the individual notifications as read (delivered via digest)
169 const notificationIds = nonDigestNotifications.map(
170   (n: { id: string }) => n.id
171 );
172 const { error: updateErr } = await supabase
173   .from("notifications")
174   .update({ is_read: true })
175   .in("id", notificationIds);
176
177 if (updateErr) {
178   console.error(
179     `Failed to mark notifications as read for ${studentId}:`,
180     updateErr.message
181   );
182 }
183
184 digestsCreated++;
185 }
186
187 return new Response(
188   JSON.stringify({
189     success: true,
190     digests_created: digestsCreated,
191     total_subscribers: digestStudentIds.length,
192   }),
193   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
194 );
195 } catch (error) {
196   return new Response(JSON.stringify({ error: (error as Error).message }), {
197     status: 500,
198     headers: { ...corsHeaders, "Content-Type": "application/json" },
199   });
200 }
201 });

```

FILE: supabase/functions/perfect-day-prompt/index.ts

```
TYPE: .ts | LINES: 1-250 | SHA256: 584c6ec10e914a112edf5b38334844248f579a7a9a93106d035ed58a397df6cd
```

```

1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3
4 const corsHeaders = {
5   "Access-Control-Allow-Origin": "*",
6   "Access-Control-Allow-Headers":
7     "authorization, x-client-info, apikey, content-type",
8 };
9
10 // % % % pg_cron schedule: 0 18 * * * (daily 6 PM) % % % % % % % % % % % % % % % % % % % % % % % % % % % %
11 // Checks each active student's habit completion for the current day.
12 // If exactly 3 of 4 habits completed, sends an in-app notification
13 // identifying the missing habit.
14
15 type HabitType = "login" | "submit" | "journal" | "read";
16
17 const ALL_HABITS: HabitType[] = ["login", "submit", "journal", "read"];
18
19 const HABIT_LABELS: Record<HabitType, string> = {
20   login: "Login",
21   submit: "Submit",
22   journal: "Journal",
23   read: "Read",
24 };
25
26 // % % % Habit Difficulty Level helpers (Req 128.4) % % % % % % % % % % % % % % % % % % % % % % % % % % % %
27
28 // The live `student_gamification.habit_difficulty_level` column is TEXT,
29 // CHECK-constrained to {starter, intermediate, advanced, master}. Map it to an
30 // ordinal (1..4) so the numeric threshold helpers below work correctly. This
31 // function is read-only here (perfect-day-prompt never writes the column).
32 const HABIT_LEVEL_TIERS = [
33   "starter",
34   "intermediate",
35   "advanced",
36   "master",
37 ] as const;
38
39 function habitLevelTextToOrdinal(value: unknown): number {
40   if (typeof value === "number" && Number.isFinite(value)) {
41     return Math.min(Math.max(Math.trunc(value), 1), HABIT_LEVEL_TIERS.length);
42   }
43   if (typeof value === "string") {
44     const idx = HABIT_LEVEL_TIERS.indexOf(
45       value as (typeof HABIT_LEVEL_TIERS)[number]
46     );
47     if (idx >= 0) return idx + 1;
48   }
49   return 1; // default to "starter"

```

[illegible]

```

154 |     return new Response(
155 |       JSON.stringify({
156 |         error: "Failed to fetch habit logs",
157 |         detail: habitsErr.message,
158 |       }),
159 |       {
160 |         status: 500,
161 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
162 |       }
163 |     );
164 |   }
165 |
166 |   // Group habits by student
167 |   const studentHabits = new Map<string, Set<string>>();
168 |   for (const log of habitLogs ?? []) {
169 |     const existing = studentHabits.get(log.student_id) ?? new Set();
170 |     existing.add(log.habit_type);
171 |     studentHabits.set(log.student_id, existing);
172 |   }
173 |
174 |   let notified = 0;
175 |   let skippedComplete = 0;
176 |   let skippedNotEnough = 0;
177 |   const errors: Array<{ student_id: string; error: string }> = [];
178 |
179 |   for (const student of students) {
180 |     const completedHabits = studentHabits.get(student.id) ?? new Set();
181 |     const completedCount = completedHabits.size;
182 |     const studentLevel = studentLevelMap.get(student.id) ?? 1;
183 |     const perfectDayThreshold = getPerfectDayThreshold(studentLevel);
184 |     const nudgeThreshold = getNudgeThreshold(studentLevel);
185 |
186 |     // Skip students who already completed enough habits for Perfect Day at their level
187 |     if (completedCount >= perfectDayThreshold) {
188 |       skippedComplete++;
189 |       continue;
190 |     }
191 |
192 |     // Only notify students who are exactly 1 habit away from their level's Perfect Day
193 |     if (completedCount !== nudgeThreshold) {
194 |       skippedNotEnough++;
195 |       continue;
196 |     }
197 |
198 |     // Find the missing habit(s) – pick the first one not completed
199 |     const missingHabit = ALL_HABITS.find((h) => !completedHabits.has(h));
200 |     if (!missingHabit) continue;
201 |
202 |     const missingLabel = HABIT_LABELS[missingHabit];
203 |
204 |     try {
205 |       // Send in-app notification (not email – this is a nudge)
206 |       const { error: notifErr } = await supabase
207 |         .from("notifications")
208 |         .insert({
209 |           user_id: student.id,
210 |           type: "perfect_day_nudge",
211 |           title: "Almost a Perfect Day! '(",
212 |           body: `You're 1 habit away from a Perfect Day! '( Complete your ${missingLabel} to earn 50 bonus XP
213 |             is_read: false,
214 |             metadata: {
215 |               missing_habit: missingHabit,
216 |               completed_habits: Array.from(completedHabits),
217 |               date: todayUTC,
218 |             },
219 |           });
220 |
221 |       if (notifErr) {
222 |         errors.push({ student_id: student.id, error: notifErr.message });
223 |       } else {
224 |         notified++;
225 |       }
226 |     } catch (err) {
227 |       errors.push({ student_id: student.id, error: (err as Error).message });
228 |     }
229 |   }
230 |
231 |   return new Response(
232 |     JSON.stringify({
233 |       success: true,
234 |       notified,
235 |       skipped_complete: skippedComplete,
236 |       skipped_not_enough: skippedNotEnough,
237 |       total_students: students.length,
238 |       errors,
239 |     }),
240 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
241 |   );
242 | } catch (error) {
243 |   console.error("perfect-day-prompt error:", (error as Error).message);
244 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
245 |     status: 500,
246 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
247 |   });
248 | }
249 | });
250 |

```

FILE: supabase/functions/process-onboarding/index.ts

```
TYPE: .ts | LINES: 1-1126 | SHA256: 6fc71aee5966899df49ce10fbd1f5149d3dda92329df0c33e6a7adda2612a3b8
```

[illegible]

```

102 | 4: [
103 |   "self_efficacy",
104 |   "self_efficacy",
105 |   "personality",
106 |   "personality",
107 |   "learning_style",
108 | ],
109 | 5: [
110 |   "personality",
111 |   "learning_style",
112 |   "learning_style",
113 |   "self_efficacy",
114 |   "study_strategy",
115 | ],
116 | 6: [
117 |   "study_strategy",
118 |   "study_strategy",
119 |   "study_strategy",
120 |   "personality",
121 |   "personality",
122 | ],
123 | 7: [
124 |   "study_strategy",
125 |   "study_strategy",
126 |   "learning_style",
127 |   "learning_style",
128 |   "personality",
129 | ],
130 | 8: [
131 |   "personality",
132 |   "personality",
133 |   "personality",
134 |   "learning_style",
135 |   "learning_style",
136 | ],
137 | 9: [
138 |   "learning_style",
139 |   "learning_style",
140 |   "learning_style",
141 |   "personality",
142 |   "self_efficacy",
143 | ],
144 | 10: [
145 |   "learning_style",
146 |   "learning_style",
147 |   "self_efficacy",
148 |   "self_efficacy",
149 |   "personality",
150 | ],
151 | 11: [
152 |   "self_efficacy",
153 |   "self_efficacy",
154 |   "study_strategy",
155 |   "study_strategy",
156 |   "learning_style",
157 | ],
158 | 12: [
159 |   "learning_style",
160 |   "learning_style",
161 |   "learning_style",
162 |   "study_strategy",
163 |   "personality",
164 | ],
165 | 13: [
166 |   "learning_style",
167 |   "learning_style",
168 |   "personality",
169 |   "personality",
170 |   "self_efficacy",
171 | ],
172 | 14: [
173 |   "personality",
174 |   "personality",
175 |   "self_efficacy",
176 |   "study_strategy",
177 |   "learning_style",
178 | ],
179 | };
180 |
181 | /** Get the dominant assessment type for a day (most frequent in the array). */
182 | function getDominantType(types: string[]): string {
183 |   const counts: Record<string, number> = {};
184 |   for (const t of types) {
185 |     counts[t] = (counts[t] ?? 0) + 1;
186 |   }
187 |   let max = 0;
188 |   let dominant = types[0];
189 |   for (const [key, count] of Object.entries(counts)) {
190 |     if (count > max) {
191 |       max = count;
192 |       dominant = key;
193 |     }
194 |   }
195 |   return dominant;
196 | }
197 |
198 | const TOTAL_PERSONALITY_ITEMS = 25;
199 | const TOTAL_SELF_EFFICACY_ITEMS = 6;
200 | const TOTAL_STUDY_STRATEGY_ITEMS = 8;
201 | const TOTAL_LEARNING_STYLE_ITEMS = 16;
202 |
203 | const VALID_SECTIONS: SkippableSection[] = [
204 |   "personality",
205 |   "learning_style",

```

[illegible]


```

310     auditory: 0,
311     read_write: 0,
312     kinesthetic: 0,
313 };
314
315 for (const r of responses) {
316     if (r.selected_modality in counts) {
317         counts[r.selected_modality]++;
318     }
319 }
320
321 const modalities = [
322     "visual",
323     "auditory",
324     "read_write",
325     "kinesthetic",
326 ] as const;
327 const scores: Record<string, number> = {};
328 for (const mod of modalities) {
329     scores[mod] = Math.round((counts[mod] / totalQuestions) * 100);
330 }
331
332 const maxScore = Math.max(...modalities.map((m) => scores[m]));
333 const topModalities = modalities.filter(
334     (m) => maxScore - scores[m] <= MULTIMODAL_THRESHOLD
335 );
336
337 let dominant_style: VARKProfile["dominant_style"];
338 if (topModalities.length >= 2) {
339     dominant_style = "multimodal";
340 } else {
341     dominant_style = modalities.reduce((a, b) =>
342         scores[a] > scores[b] ? a : b
343     );
344 }
345
346 return {
347     visual: scores.visual,
348     auditory: scores.auditory,
349     read_write: scores.read_write,
350     kinesthetic: scores.kinesthetic,
351     dominant_style,
352 };
353 }
354
355 function calculateBaselineScores(
356     responses: Array<{
357         clo_id: string;
358         selected_option: number;
359         correct_option: number;
360     }>
361 ): Array<{
362     clo_id: string;
363     score: number;
364     question_count: number;
365     correct_count: number;
366 }> {
367     const cloMap = new Map<string, { total: number; correct: number }>();
368
369     for (const r of responses) {
370         const entry = cloMap.get(r.clo_id) ?? { total: 0, correct: 0 };
371         entry.total++;
372         if (r.selected_option === r.correct_option) entry.correct++;
373         cloMap.set(r.clo_id, entry);
374     }
375
376     return Array.from(cloMap.entries()).map(([clo_id, { total, correct }]) => ({
377         clo_id,
378         score: Math.round((correct / total) * 100),
379         question_count: total,
380         correct_count: correct,
381     })));
382 }
383
384 function calculateSelfEfficacyScores(
385     responses: Array<{ domain: string; selected_option: number }>
386 ): SelfEfficacyProfile {
387     const domains = [
388         "general_academic",
389         "course_specific",
390         "self_regulated_learning",
391     ] as const;
392     const scores: Record<string, number> = {};
393
394     for (const domain of domains) {
395         const domainResponses = responses.filter((r) => r.domain === domain);
396         if (domainResponses.length === 0) {
397             scores[domain] = 0;
398             continue;
399         }
400         const sum = domainResponses.reduce((acc, r) => acc + r.selected_option, 0);
401         const maxPossible = domainResponses.length * 5;
402         scores[domain] = Math.round((sum / maxPossible) * 100);
403     }
404
405     const allSum = responses.reduce((acc, r) => acc + r.selected_option, 0);
406     const allMax = responses.length * 5;
407     scores.overall = allMax > 0 ? Math.round((allSum / allMax) * 100) : 0;
408
409     return scores as unknown as SelfEfficacyProfile;
410 }
411
412 function calculateStudyStrategyScores(
413     responses: Array<{ dimension: string; selected_option: number }>

```

[illegible]

```

518 |     data: { user },
519 |     error: authError,
520 | } = await userClient.auth.getUser();
521 |
522 | if (authError || !user) {
523 |   return new Response(
524 |     JSON.stringify({ error: "Invalid or expired token" }),
525 |     {
526 |       status: 401,
527 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
528 |     }
529 |   );
530 | }
531 |
532 | if (user.id !== student_id) {
533 |   return new Response(
534 |     JSON.stringify({
535 |       error: "Forbidden: student_id does not match authenticated user",
536 |     }),
537 |     {
538 |       status: 403,
539 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
540 |     }
541 |   );
542 | }
543 |
544 | // %% 3.1.2 Fetch onboarding_responses and validate against active questions %%
545 |
546 | const { data: responses, error: responsesErr } = await supabase
547 |   .from("onboarding_responses")
548 |   .select("id, question_id, selected_option, score_contribution")
549 |   .eq("student_id", student_id)
550 |   .eq("assessment_version", assessment_version);
551 |
552 | if (responsesErr) {
553 |   console.error("Failed to fetch responses:", responsesErr.message);
554 |   return new Response(
555 |     JSON.stringify({
556 |       error: "Failed to fetch onboarding responses",
557 |       detail: responsesErr.message,
558 |     }),
559 |     {
560 |       status: 500,
561 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
562 |     }
563 |   );
564 | }
565 |
566 | const questionIds = [
567 |   ...new Set(
568 |     (responses ?? []).map((r: { question_id: string }) => r.question_id)
569 |   ),
570 | ];
571 |
572 | // Fetch all active questions that match the student's responses
573 | let activeQuestions: Array<{
574 |   id: string;
575 |   assessment_type: string;
576 |   dimension: string | null;
577 |   weight: number | null;
578 |   options: unknown;
579 |   correct_option: number | null;
580 |   clo_id: string | null;
581 |   course_id: string | null;
582 | }> = [];
583 |
584 | if (questionIds.length > 0) {
585 |   const { data: questions, error: questionsErr } = await supabase
586 |     .from("onboarding_questions")
587 |     .select(
588 |       "id, assessment_type, dimension, weight, options, correct_option, clo_id, course_id"
589 |     )
590 |     .in("id", questionIds)
591 |     .eq("is_active", true);
592 |
593 |   if (questionsErr) {
594 |     console.error("Failed to fetch questions:", questionsErr.message);
595 |     return new Response(
596 |       JSON.stringify({
597 |         error: "Failed to fetch onboarding questions",
598 |         detail: questionsErr.message,
599 |       }),
600 |       {
601 |         status: 500,
602 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
603 |       }
604 |     );
605 |   }
606 |
607 |   activeQuestions = questions ?? [];
608 | }
609 |
610 | // Build a lookup map for active questions
611 | const questionMap = new Map(activeQuestions.map((q) => [q.id, q]));
612 |
613 | // Filter responses to only those referencing active questions
614 | const validResponses = (responses ?? []).filter(
615 |   (r: { question_id: string }) => questionMap.has(r.question_id)
616 | );
617 |
618 | // %% 3.1.15 Handle skipped sections (store null for skipped assessment scores) %%
619 |
620 | const isSkipped = (section: SkippableSection) =>
621 |   skipped_sections.includes(section);

```

[illegible]

```

726 | }
727 |
728 | // %% 3.1.7 Calculate study strategy dimension scores % % % % % % % % % % % %
729 |
730 | let studyStrategies: StudyStrategyProfile | null = null;
731 |
732 | if (!isSkipped("study_strategy")) {
733 |   const ssResponses = validResponses
734 |     .filter((r: { question_id: string }) => {
735 |       const q = questionMap.get(r.question_id);
736 |       return q?.assessment_type === "study_strategy";
737 |     })
738 |     .map((r: { question_id: string; selected_option: number }) => {
739 |       const q = questionMap.get(r.question_id!);
740 |       return {
741 |         dimension: q.dimension ?? "",
742 |         selected_option: r.selected_option,
743 |       };
744 |     });
745 |
746 |   if (ssResponses.length > 0) {
747 |     studyStrategies = calculateStudyStrategyScores(ssResponses);
748 |   }
749 | }
750 |
751 | // %% 3.1.8 Calculate profile_completeness percentage % % % % % % % % % % % %
752 |
753 | const personalityItemCount = isSkipped("personality")
754 |   ? 0
755 |   : validResponses.filter(
756 |     (r: { question_id: string }) =>
757 |       questionMap.get(r.question_id)?.assessment_type === "personality"
758 |   ).length;
759 |
760 | const selfEfficacyItemCount = isSkipped("self_efficacy")
761 |   ? 0
762 |   : validResponses.filter(
763 |     (r: { question_id: string }) =>
764 |       questionMap.get(r.question_id)?.assessment_type === "self_efficacy"
765 |   ).length;
766 |
767 | const studyStrategyItemCount = isSkipped("study_strategy")
768 |   ? 0
769 |   : validResponses.filter(
770 |     (r: { question_id: string }) =>
771 |       questionMap.get(r.question_id)?.assessment_type === "study_strategy"
772 |   ).length;
773 |
774 | const learningStyleItemCount = isSkipped("learning_style")
775 |   ? 0
776 |   : validResponses.filter(
777 |     (r: { question_id: string }) =>
778 |       questionMap.get(r.question_id)?.assessment_type === "learning_style"
779 |   ).length;
780 |
781 | const profileCompleteness = calculateProfileCompleteness({
782 |   personality_items: personalityItemCount,
783 |   self_efficacy_items: selfEfficacyItemCount,
784 |   study_strategy_items: studyStrategyItemCount,
785 |   learning_style_items: learningStyleItemCount,
786 |   baseline_courses: baselineResults.length,
787 | });
788 |
789 | // %% 3.1.9 INSERT/UPSERT student_profiles record % % % % % % % % % % % %
790 |
791 | // Fetch institution_id for the student
792 | const { data: studentProfile, error: profileFetchErr } = await supabase
793 |   .from("profiles")
794 |   .select("institution_id")
795 |   .eq("id", student_id)
796 |   .maybeSingle();
797 |
798 | if (profileFetchErr || !studentProfile) {
799 |   return new Response(
800 |     JSON.stringify({
801 |       error: "Failed to fetch student profile",
802 |       detail: profileFetchErr?.message,
803 |     }),
804 |     {
805 |       status: 500,
806 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
807 |     }
808 |   );
809 | }
810 |
811 | const { error: upsertProfileErr } = await supabase
812 |   .from("student_profiles")
813 |   .upsert(
814 |     {
815 |       student_id,
816 |       institution_id: studentProfile.institution_id,
817 |       personality_traits: personalityTraits,
818 |       learning_style: learningStyle,
819 |       self_efficacy: selfEfficacy,
820 |       study_strategies: studyStrategies,
821 |       profile_completeness: profileCompleteness,
822 |       assessment_version,
823 |       completed_at: new Date().toISOString(),
824 |     },
825 |     { onConflict: "student_id,assessment_version" }
826 |   );
827 |
828 | if (upsertProfileErr) {
829 |   console.error(

```

```

830 |         "Failed to upsert student profile:",
831 |         upsertProfileErr.message
832 |     );
833 |     return new Response(
834 |         JSON.stringify({
835 |             error: "Failed to save student profile",
836 |             detail: upsertProfileErr.message,
837 |         }),
838 |         {
839 |             status: 500,
840 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
841 |         }
842 |     );
843 | }
844 |
845 | // % % 3.1.10 INSERT baseline_attainment records % % % % % % % % % % % % % % % % %
846 |
847 | if (baselineResults.length > 0) {
848 |     const attainmentRows = baselineResults.flatMap((br) =>
849 |         br.clo_scores.map((cs) => ({
850 |             student_id,
851 |             course_id: br.course_id,
852 |             clo_id: cs.clo_id,
853 |             score: cs.score,
854 |             question_count: cs.question_count,
855 |             correct_count: cs.correct_count,
856 |             assessment_version,
857 |         })))
858 |     );
859 |
860 |     const { error: attainmentErr } = await supabase
861 |         .from("baseline_attainment")
862 |         .upsert(attainmentRows, { onConflict: "student_id,course_id,clo_id" });
863 |
864 |     if (attainmentErr) {
865 |         console.error(
866 |             "Failed to upsert baseline attainment:",
867 |             attainmentErr.message
868 |         );
869 |         // Non-fatal – continue processing
870 |     }
871 | }
872 |
873 | // % % 3.1.11 UPDATE profiles SET onboarding_completed = true % % % % % % % %
874 |
875 | const { error: updateProfileErr } = await supabase
876 |     .from("profiles")
877 |     .update({ onboarding_completed: true })
878 |     .eq("id", student_id);
879 |
880 | if (updateProfileErr) {
881 |     console.error(
882 |         "Failed to update onboarding_completed:",
883 |         updateProfileErr.message
884 |     );
885 |     // Non-fatal – continue processing
886 | }
887 |
888 | // % % 3.1.12 Generate micro-assessment schedule for Day 1 flow % % % % % % %
889 |
890 | if (is_day1) {
891 |     const today = new Date();
892 |     const scheduleRows = Object.entries(MICRO_ASSESSMENT_SCHEDULE).map(
893 |         ([dayStr, assessmentTypes]) => {
894 |             const day = parseInt(dayStr, 10);
895 |             const scheduledDate = new Date(today);
896 |             scheduledDate.setDate(today.getDate() + (day - 1));
897 |             return {
898 |                 student_id,
899 |                 scheduled_day: day,
900 |                 assessment_type: getDominantType(assessmentTypes),
901 |                 question_count: assessmentTypes.length,
902 |                 question_ids: [],
903 |                 status: "pending",
904 |                 dismissal_count: 0,
905 |                 scheduled_at: scheduledDate.toISOString().slice(0, 10),
906 |             };
907 |         }
908 |     );
909 |
910 |     const { error: scheduleErr } = await supabase
911 |         .from("micro_assessment_schedule")
912 |         .upsert(scheduleRows, { onConflict: "student_id,scheduled_day" });
913 |
914 |     if (scheduleErr) {
915 |         console.error(
916 |             "Failed to insert micro-assessment schedule:",
917 |             scheduleErr.message
918 |         );
919 |         // Non-fatal – continue processing
920 |     }
921 | }
922 |
923 | // % % 3.1.13 Invoke award-xp for each completed section + completion bonus % %
924 |
925 | let totalXpAwarded = 0;
926 | const xpAwards: Array<{ source: string; amount: number }> = [];
927 |
928 | // Only award XP for first assessment (assessment_version === 1)
929 | if (assessment_version === 1) {
930 |     // Personality XP
931 |     if (!isSkipped("personality") && personalityTraits !== null) {
932 |         xpAwards.push({
933 |             source: "onboarding_personality",

```

```

934 |         amount: ONBOARDING_XP.personality,
935 |     });
936 | }
937 |
938 | // Learning style XP
939 | if (!isSkipped("learning_style") && learningStyle !== null) {
940 |     xpAwards.push({
941 |         source: "onboarding_learning_style",
942 |         amount: ONBOARDING_XP.learning_style,
943 |     });
944 | }
945 |
946 | // Self-efficacy XP
947 | if (!isSkipped("self_efficacy") && selfEfficacy !== null) {
948 |     xpAwards.push({
949 |         source: "onboarding_self_efficacy",
950 |         amount: ONBOARDING_XP.self_efficacy,
951 |     });
952 | }
953 |
954 | // Study strategy XP
955 | if (!isSkipped("study_strategy") && studyStrategies !== null) {
956 |     xpAwards.push({
957 |         source: "onboarding_study_strategy",
958 |         amount: ONBOARDING_XP.study_strategy,
959 |     });
960 | }
961 |
962 | // Baseline XP (per course)
963 | for (const br of baselineResults) {
964 |     xpAwards.push({
965 |         source: "onboarding_baseline",
966 |         amount: ONBOARDING_XP.baseline_per_course,
967 |     });
968 | }
969 |
970 | // Completion bonus
971 | xpAwards.push({
972 |     source: "onboarding_complete",
973 |     amount: ONBOARDING_XP.complete,
974 | });
975 | }
976 |
977 | for (const award of xpAwards) {
978 |     try {
979 |         await supabase.functions.invoke("award-xp", {
980 |             body: {
981 |                 student_id,
982 |                 xp_amount: award.amount,
983 |                 source: award.source,
984 |                 reference_id: `${award.source}:${student_id}:v${assessment_version}`,
985 |                 note: `Onboarding ${award.source} (v${assessment_version})`,
986 |             },
987 |         });
988 |         totalXpAwarded += award.amount;
989 |     } catch (xpErr) {
990 |         console.error(
991 |             `Failed to award XP for ${award.source}:`,
992 |             (xpErr as Error).message
993 |         );
994 |         // Non-fatal – continue with other awards
995 |     }
996 | }
997 |
998 | // % % 3.1.14 Invoke check-badges for "Self-Aware Scholar" and "Thorough Explorer" % %
999 |
1000 | const badgesEarned: string[] = [];
1001 |
1002 | try {
1003 |     const badgeResponse = await supabase.functions.invoke("check-badges", {
1004 |         body: {
1005 |             student_id,
1006 |             trigger: "xp_award",
1007 |             context: {
1008 |                 onboarding_complete: true,
1009 |                 personality_completed:
1010 |                     !isSkipped("personality") && personalityTraits !== null,
1011 |                 learning_style_completed:
1012 |                     !isSkipped("learning_style") && learningStyle !== null,
1013 |                 baseline_completed: baselineResults.length > 0,
1014 |                 self_efficacy_completed:
1015 |                     !isSkipped("self_efficacy") && selfEfficacy !== null,
1016 |                 study_strategy_completed:
1017 |                     !isSkipped("study_strategy") && studyStrategies !== null,
1018 |                 skipped_sections,
1019 |             },
1020 |         },
1021 |     });
1022 |
1023 |     if (badgeResponse.data?.new_badges) {
1024 |         badgesEarned.push(...badgeResponse.data.new_badges);
1025 |     }
1026 | } catch (badgeErr) {
1027 |     console.error("Failed to check badges:", (badgeErr as Error).message);
1028 |     // Non-fatal
1029 | }
1030 |
1031 | // Check "Self-Aware Scholar": personality + learning_style + at least one baseline
1032 | const selfAwareScholarEligible =
1033 |     !isSkipped("personality") &&
1034 |     personalityTraits !== null &&
1035 |     !isSkipped("learning_style") &&
1036 |     learningStyle !== null &&
1037 |     baselineResults.length > 0;

```

[illegible]

FILE: supabase/functions/process-purchase/index.ts

TYPE: .ts | LINES: 1-320 | SHA256: bb5a5f35448de490d717876c73e8b079f2c230a5baf0c8e99f1b9bd821550762

[illegible]

[illegible]

```

116 | const studentId = user.id;
117 |
118 | // Create service role client for DB operations (bypasses RLS)
119 | const supabase = createClient(
120 |   Deno.env.get("SUPABASE_URL")!,
121 |   Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
122 | );
123 |
124 | // Fetch institution_id from the student's profile
125 | const { data: profile, error: profileErr } = await supabase
126 |   .from("profiles")
127 |   .select("institution_id, role")
128 |   .eq("id", studentId)
129 |   .maybeSingle();
130 |
131 | if (profileErr || !profile) {
132 |   return errorResponse("Failed to fetch student profile", 400);
133 | }
134 |
135 | if (profile.role !== "student") {
136 |   return errorResponse("Only students can make marketplace purchases", 403);
137 | }
138 |
139 | const institutionId = profile.institution_id;
140 | if (!institutionId) {
141 |   return errorResponse(
142 |     "Student is not associated with an institution",
143 |     400
144 |   );
145 | }
146 |
147 | // %% 3.1.2: Call process_marketplace_purchase RPC function % % % % % % % % % %
148 |
149 | const { data: rpcResult, error: rpcError } = await supabase.rpc(
150 |   "process_marketplace_purchase",
151 |   {
152 |     p_student_id: studentId,
153 |     p_item_id: itemId,
154 |     p_institution_id: institutionId,
155 |   }
156 | );
157 |
158 | if (rpcError) {
159 |   console.error(
160 |     "RPC process_marketplace_purchase failed:",
161 |     rpcError.message
162 |   );
163 |   return errorResponse("Purchase processing failed", 500, undefined, {
164 |     detail: rpcError.message,
165 |   });
166 | }
167 |
168 | const result = rpcResult as PurchaseRPCResult;
169 |
170 | // If the RPC returned an error_code, map it to the appropriate HTTP status
171 | if (!result.success) {
172 |   const errorCodeStatusMap: Record<PurchaseErrorCode, number> = {
173 |     INSUFFICIENT_BALANCE: 400,
174 |     LEVEL_REQUIREMENT: 403,
175 |     OUT_OF_STOCK: 409,
176 |     ALREADY_OWNED: 409,
177 |     ITEM_INACTIVE: 404,
178 |     SALE_EXPIRED: 409,
179 |     MAX_INVENTORY: 409,
180 |   };
181 |
182 |   const code = result.error_code as PurchaseErrorCode;
183 |   const status = errorCodeStatusMap[code] ?? 400;
184 |
185 |   const errorMessages: Record<PurchaseErrorCode, string> = {
186 |     INSUFFICIENT_BALANCE: "Insufficient XP balance for this purchase",
187 |     LEVEL_REQUIREMENT:
188 |       "You do not meet the level requirement for this item",
189 |     OUT_OF_STOCK: "This item is out of stock",
190 |     ALREADY_OWNED: "You already own this item",
191 |     ITEM_INACTIVE: "This item is no longer available",
192 |     SALE_EXPIRED: "The sale for this item has expired",
193 |     MAX_INVENTORY:
194 |       "You have reached the maximum inventory for this item type",
195 |   };
196 |
197 |   return errorResponse(
198 |     errorMessages[code] ?? "Purchase failed",
199 |     status,
200 |     code,
201 |     result.detail as Record<string, unknown> | undefined
202 |   );
203 | }
204 |
205 | // %% 3.1.3: Post-purchase activation: XP boost % % % % % % % % % % % % % % % %
206 | // If the purchased item is a power_up with sub_category xp_boost,
207 | // insert into student_active_boosts with 1 hour expiry
208 |
209 | if (
210 |   result.item_category === "power_up" &&
211 |   result.item_sub_category === "xp_boost"
212 | ) {
213 |   const now = new Date();
214 |   const expiresAt = new Date(now.getTime() + 60 * 60 * 1000); // 1 hour
215 |
216 |   const { error: boostErr } = await supabase
217 |     .from("student_active_boosts")
218 |     .insert({
219 |       student_id: studentId,

```

```

220         boost_type: "xp_boost",
221         multiplier: 2.0,
222         purchase_id: result.purchase_id,
223         activated_at: now.toISOString(),
224         expires_at: expiresAt.toISOString(),
225     });
226
227     if (boostErr) {
228         console.error("Failed to activate XP boost:", boostErr.message);
229         // Non-blocking: purchase succeeded, boost activation failed
230         // Log but don't fail the response
231     }
232 }
233
234 // % % 3.1.4: Post-purchase activation: streak shield % % % % % % % % % % % % % %
235 // If the purchased item is a power_up with sub_category streak_shield,
236 // increment streak_freezes_available in student_gamification (max 3)
237
238 if (
239     result.item_category === "power_up" &&
240     result.item_sub_category === "streak_shield"
241 ) {
242     // Fetch current streak_freezes_available
243     const { data: gamification, error: gamErr } = await supabase
244         .from("student_gamification")
245         .select("streak_freezes_available")
246         .eq("student_id", studentId)
247         .maybeSingle();
248
249     if (gamErr) {
250         console.error(
251             "Failed to fetch gamification for streak shield:",
252             gamErr.message
253         );
254     } else {
255         const currentFreezes = gamification?.streak_freezes_available ?? 0;
256
257         // Only increment if under the max of 3 (the RPC already validated this,
258         // but we double-check for safety)
259         if (currentFreezes < 3) {
260             const { error: updateErr } = await supabase
261                 .from("student_gamification")
262                 .upsert(
263                     {
264                         student_id: studentId,
265                         streak_freezes_available: currentFreezes + 1,
266                     },
267                     { onConflict: "student_id" }
268                 );
269
270             if (updateErr) {
271                 console.error(
272                     "Failed to increment streak_freezes_available:",
273                     updateErr.message
274                 );
275             }
276         }
277     }
278 }
279
280 // % % 3.1.5: Audit log insertion % % % % % % % % % % % % % % % % % % % % % % % %
281
282 try {
283     await supabase.from("audit_logs").insert({
284         action: "marketplace_purchase",
285         entity_type: "xp_purchases",
286         entity_id: result.purchase_id,
287         performed_by: studentId,
288         institution_id: institutionId,
289         changes: {
290             item_id: itemId,
291             xp_cost: result.xp_cost,
292             new_balance: result.new_balance,
293             item_category: result.item_category,
294             item_sub_category: result.item_sub_category,
295         },
296     });
297 } catch (auditErr) {
298     // Non-blocking: purchase succeeded, audit log failed
299     console.error("Audit log insertion failed:", auditErr);
300 }
301
302 // % % 3.1.6: Structured success response % % % % % % % % % % % % % % % % % % % %
303
304 return jsonResponse({
305     success: true,
306     purchase_id: result.purchase_id,
307     xp_cost: result.xp_cost,
308     new_balance: result.new_balance,
309     item_category: result.item_category,
310     item_sub_category: result.item_sub_category,
311 });
312 } catch (error) {
313     console.error("Unexpected error in process-purchase:", error);
314     return ErrorResponse(
315         (error as Error).message ?? "Internal server error",
316         500
317     );
318 }
319 });
320

```

```
TYPE: .ts | LINES: 1-864 | SHA256: c146b121563744957c081d5f310f846e86b5bdf8e33fd47db84ffb00cd14fbe2
```

[illegible]

[illegible]

[illegible]

```

310 // All members logged in today – update team streak
311 const currentStreak = teamGam?.streak_current ?? 0;
312 const longestStreak = teamGam?.streak_longest ?? 0;
313 const lastStreakDate = teamGam?.last_streak_date as string | null;
314
315 let newStreak: number;
316
317 if (!lastStreakDate) {
318   newStreak = 1;
319 } else {
320   const dayDiff = daysBetween(lastStreakDate, todayUTC);
321   if (dayDiff === 0) {
322     // Already processed today
323     continue;
324   } else if (dayDiff === 1) {
325     newStreak = currentStreak + 1;
326   } else {
327     // Missed days – reset
328     newStreak = 1;
329   }
330 }
331
332 const newLongest = Math.max(longestStreak, newStreak);
333
334 // Upsert team gamification
335 await supabase.from("team_gamification").upsert(
336   {
337     team_id: teamId,
338     streak_current: newStreak,
339     streak_longest: newLongest,
340     last_streak_date: todayUTC,
341   },
342   { onConflict: "team_id" }
343 );
344
345 // Check for team streak milestones
346 const milestoneXP = TEAM_STREAK_MILESTONES[newStreak];
347 if (milestoneXP) {
348   // Award XP to team pool
349   try {
350     await supabase.from("xp_transactions").insert({
351       team_id: teamId,
352       xp_amount: milestoneXP,
353       source: "streak_milestone",
354       note: `Team streak milestone: ${newStreak} days`,
355     });
356
357     // Update team xp_total
358     const { data: currentGam } = await supabase
359       .from("team_gamification")
360       .select("xp_total")
361       .eq("team_id", teamId)
362       .maybeSingle();
363
364     if (currentGam) {
365       await supabase
366         .from("team_gamification")
367         .update({ xp_total: (currentGam.xp_total ?? 0) + milestoneXP })
368         .eq("team_id", teamId);
369     }
370   } catch (xpErr) {
371     console.error(
372       `Failed to award team streak XP:`,
373       (xpErr as Error).message
374     );
375   }
376
377   // Trigger team badge check
378   try {
379     await supabase.functions.invoke("check-badges", {
380       body: {
381         student_id: studentId,
382         trigger: "team_event",
383         team_id: teamId,
384       },
385     });
386   } catch (badgeErr) {
387     console.error(
388       "Failed to check team badges:",
389       (badgeErr as Error).message
390     );
391   }
392
393   // Notify team members of milestone
394   const notifications = memberIds.map((memberId: string) => ({
395     user_id: memberId,
396     type: "team_streak_milestone",
397     title: "Team Streak Milestone!",
398     body: `Your team hit a ${newStreak}-day streak! 🎉 +${milestoneXP} XP`,
399     is_read: false,
400     metadata: {
401       team_id: teamId,
402       streak_days: newStreak,
403       xp_awarded: milestoneXP,
404     },
405   }));
406
407   await supabase
408     .from("notifications")
409     .insert(notifications)
410     .catch((err: Error) => {
411       console.error(
412         "Failed to send team streak notifications:",
413         err.message
414       );
415     });

```

[illegible]


```

518     }
519   };
520 }
521
522 const state: StreakState | null = current
523 ? {
524   streak_count: current.streak_current ?? 0,
525   last_login_date: current.last_login_date ?? null,
526   streak_freezes_available: current.streak_freezes_available ?? 0,
527   comeback_challenge_active: current.comeback_challenge_active ?? false,
528   comeback_challenge_days_completed:
529     current.comeback_challenge_days_completed ?? 0,
530   comeback_challenge_streak_to_restore:
531     current.comeback_challenge_streak_to_restore ?? 0,
532   total_active_days: current.total_active_days ?? 0,
533   habit_difficulty_level: habitLevelTextToOrdinal(
534     current.habit_difficulty_level
535   ),
536   habit_level_streak: current.habit_level_streak ?? 0,
537 }
538 : null;
539
540 // % % Step 1b: Fetch institution settings for Streak Sabbatical % % % % %
541
542 let streakSabbaticalEnabled = false;
543 {
544   // Get the student's institution_id from profiles
545   const { data: profileRow } = await supabase
546     .from("profiles")
547     .select("institution_id")
548     .eq("id", student_id)
549     .maybeSingle();
550
551   if (profileRow?.institution_id) {
552     const { data: instSettings } = await supabase
553       .from("institution_settings")
554       .select("streak_sabbatical_enabled")
555       .eq("institution_id", profileRow.institution_id)
556       .maybeSingle();
557
558     streakSabbaticalEnabled =
559       (instSettings as Record<string, unknown> | null)
560         ?.streak_sabbatical_enabled === true;
561   }
562 }
563
564 // % % Step 1c: Check Streak Sabbatical – skip streak check on weekends %
565
566 const isSabbaticalRestDay = isStreakSabbaticalDay(
567   streakSabbaticalEnabled,
568   todayUTC
569 );
570
571 // % % Step 2: Calculate streak update % % % % %
572
573 let newStreakCount: number;
574 let streakFrozen = false;
575 let freezeConsumed = false;
576 let milestoneReached: number | null = null;
577 let isNewDay = true;
578
579 if (!state || !state.last_login_date) {
580   // First login ever
581   newStreakCount = 1;
582 } else {
583   const dayDiff = daysBetween(state.last_login_date, todayUTC);
584
585   if (dayDiff === 0) {
586     // Same day – no-op
587     return new Response(
588       JSON.stringify({
589         success: true,
590         streak_count: state.streak_count,
591         milestone_reached: null,
592         streak_frozen: false,
593         streak_sabbatical_rest_day: isSabbaticalRestDay,
594         comeback_challenge: {
595           active: state.comeback_challenge_active,
596           days_completed: state.comeback_challenge_days_completed,
597           streak_to_restore: state.comeback_challenge_streak_to_restore,
598           just_completed: false,
599         },
600         total_active_days: state.total_active_days,
601       }),
602       { headers: { ...corsHeaders, "Content-Type": "application/json" } }
603     );
604   }
605
606   // Streak Sabbatical: count weekend days between last login and today as non-streak days
607   // This effectively reduces the dayDiff for streak evaluation purposes
608   let effectiveDayDiff = dayDiff;
609   if (streakSabbaticalEnabled && dayDiff > 1) {
610     // Count weekend days in the gap (exclusive of last_login_date, inclusive of today)
611     let weekendDaysInGap = 0;
612     const gapStart = new Date(state.last_login_date + "T00:00:00Z");
613     for (let i = 1; i < dayDiff; i++) {
614       const checkDate = new Date(gapStart.getTime() + i * 86_400_000);
615       const dow = checkDate.getUTCDay();
616       if (dow === 0 || dow === 6) weekendDaysInGap++;
617     }
618     effectiveDayDiff = dayDiff - weekendDaysInGap;
619   }
620
621   if (effectiveDayDiff <= 1) {

```

[illegible]

```
726 // Promote if streak reaches 7 and level < 3  
727 if (habitLevelStreak >= 7 && habitDifficultyLevel < 3) {  
728   habitDifficultyLevel += 1;  
729   habitLevelStreak = 0;  
730   levelPromoted = true;  
731 }  
732 } else {  
733   // Missed today - reset streak but do NOT demote level (Req 127.5)  
734   habitLevelStreak = 0;  
735 }  
736  
737 // Check milestone  
738 if (STREAK_MILESTONES.includes(newStreakCount)) {  
739   milestoneReached = newStreakCount;  
740 }  
741  
742 // %% Step 3: Update student_gamification %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
743  
744 const updateData: Record<string, unknown> = {  
745   student_id,  
746   // live column is `streak_current` (not `streak_count`)  
747   streak_current: newStreakCount,  
748   last_login_date: todayUTC,  
749   comeback_challenge_active: comebackActive,  
750   comeback_challenge_days_completed: comebackDaysCompleted,  
751   comeback_challenge_streak_to_restore: comebackStreakToRestore,  
752   total_active_days: totalActiveDays,  
753   // Persist as TEXT tier (CHECK: starter|intermediate|advanced|master).  
754   // `habitDifficultyLevel` is an internal ordinal (1..4); map it back to text  
755   // so the live CHECK constraint is never violated.  
756   habit_difficulty_level: habitLevelOrdinalToText(habitDifficultyLevel),  
757   habit_level_streak: habitLevelStreak,  
758 };  
759  
760 if (comebackJustCompleted) {  
761   updateData.comeback_challenge_start_date = null;  
762 } else if (streakBroken && state && state.streak_count > 1) {  
763   updateData.comeback_challenge_start_date = new Date().toISOString();  
764 }  
765  
766 if (freezeConsumed && state) {  
767   updateData.streak_freezes_available = state.streak_freezes_available - 1;  
768 }  
769  
770 const { error: upsertErr } = await supabase  
771 .from("student_gamification")  
772 .upsert(updateData, { onConflict: "student_id" });  
773  
774 if (upsertErr) {  
775   console.error("Failed to update gamification record:", upsertErr.message);  
776   return new Response(  
777     JSON.stringify({  
778       error: "Failed to update gamification record",  
779       detail: upsertErr.message,  
780     }),  
781     {  
782       status: 500,  
783       headers: { ...corsHeaders, "Content-Type": "application/json" },  
784     })  
785   );  
786 }  
787  
788 // %% Step 4: Award milestone XP if applicable %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
789  
790 if (milestoneReached !== null) {  
791   const xpAmount = MILESTONE_XP[milestoneReached];  
792   if (xpAmount) {  
793     try {  
794       await supabase.functions.invoke("award-xp", {  
795         body: {  
796           student_id,  
797           xp_amount: xpAmount,  
798           source: "streak_milestone",  
799           note: `Streak milestone: ${milestoneReached} days`,  
800         },  
801       });  
802     } catch (xpErr) {  
803       // Log but don't fail the streak update  
804       console.error(  
805         "Failed to award milestone XP:",  
806         (xpErr as Error).message  
807       );  
808     }  
809   }  
810  
811   // Notify peers for notable streak milestones (7, 30, 100)  
812   const PEER_NOTIFY_MILESTONES = [7, 30, 100];  
813   if (PEER_NOTIFY_MILESTONES.includes(milestoneReached)) {  
814     notifyPeersOfStreakMilestone(  
815       supabase,  
816       student_id,  
817       milestoneReached  
818     ).catch((err) => {  
819       console.error("Peer streak notification failed:", err);  
820     });  
821   }  
822 }  
823  
824 // %% Response %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
825  
826 // %% Step 5: Process team streaks %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
827  
828 processTeamStreaks(supabase, student_id, todayUTC).catch((err) => {  
829   console.error("Team streak processing failed:", err);
```

[illegible]

FILE: supabase/functions/resolve-mystery-reward/index.ts

```
TYPE: .ts | LINES: 1-241 | SHA256: c2fb399e8589b5a345cd1b9dbfae25920e7f10b7d874302d391ebcb046f14a5f
```

```

1 //
2 // Edge Function: resolve-mystery-reward
3 // Mystery reward box resolution - probability-weighted outcome selection
4 // Tasks 19.1.1-19.1.4
5 // =====
6
7 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
8 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
9 import { z } from "https://esm.sh/zod@3.23.8";
10 import {
11   authenticateRequest,
12   unauthorizedResponse,
13   forbiddenResponse,
14 } from "../_shared/auth.ts";
15
16 const PayloadSchema = z.object({
17   student_id: z.string().min(1),
18   institution_id: z.string().min(1),
19 });
20
21 const corsHeaders = {
22   "Access-Control-Allow-Origin": "*",
23   "Access-Control-Allow-Headers":
24     "authorization, x-client-info, apikey, content-type",
25 };
26
27 type RewardType = "double_xp" | "cosmetic" | "boost";
28
29 interface RewardWeight {
30   type: RewardType;
31   weight: number;
32 }
33
34 const DEFAULT_WEIGHTS: RewardWeight[] = [
35   { type: "double_xp", weight: 50 },
36   { type: "cosmetic", weight: 30 },
37   { type: "boost", weight: 20 },
38 ];
39
40 /**
41  * Task 19.1.1: Probability-weighted outcome selection
42  */
43 function selectOutcome(weights: RewardWeight[]): RewardType {
44   const totalWeight = weights.reduce(
45     (sum, w) => sum + Math.max(0, w.weight),
46     0
47   );
48   if (totalWeight <= 0) return "double_xp";
49
50   const roll = Math.random() * totalWeight;
51   let cumulative = 0;
52
53   for (const entry of weights) {
54     cumulative += Math.max(0, entry.weight);
55     if (roll < cumulative) return entry.type;
56   }
57
58   return weights[weights.length - 1]?.type ?? "double_xp";
59 }
60
61 serve(async (req) => {
62   if (req.method === "OPTIONS") {
63     return new Response("ok", { headers: corsHeaders });
64   }
65

```

```

66 | try {
67 |   // Caller check (Req 18): require a valid JWT before any service-role work.
68 |   const auth = await authenticateRequest(req);
69 |   if (!auth.user) {
70 |     return unauthorizedResponse(auth.error ?? "Unauthorized");
71 |   }
72 |
73 |   const supabase = createClient(
74 |     Deno.env.get("SUPABASE_URL")!,
75 |     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
76 |   );
77 |
78 |   const body = await req.json();
79 |   const parsed = PayloadSchema.safeParse(body);
80 |   if (!parsed.success) {
81 |     return new Response(JSON.stringify({ error: parsed.error.message }), {
82 |       status: 400,
83 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
84 |     });
85 |   }
86 |   const { student_id, institution_id } = parsed.data;
87 |
88 |   // Ownership: a student may only open their OWN mystery reward box. Admins
89 |   // may resolve on behalf of a student in their institution. Cross-tenant
90 |   // access is always denied.
91 |   const isAdmin = auth.user.role === "admin";
92 |   if (!isAdmin && auth.user.id !== student_id) {
93 |     return forbiddenResponse(
94 |       "Forbidden: cannot resolve a reward for another student"
95 |     );
96 |   }
97 |   if (!isAdmin && auth.user.institution_id !== institution_id) {
98 |     return forbiddenResponse("Forbidden: institution mismatch");
99 |   }
100 |
101 |   // Fetch configurable weights from institution_settings
102 |   const { data: settings } = await supabase
103 |     .from("institution_settings")
104 |     .select("*")
105 |     .eq("institution_id", institution_id)
106 |     .maybeSingle();
107 |
108 |   const rawSettings = settings as Record<string, unknown> | null;
109 |   const weights: RewardWeight[] = rawSettings?.mystery_reward_weights
110 |     ? (rawSettings.mystery_reward_weights as RewardWeight[])
111 |     : DEFAULT_WEIGHTS;
112 |
113 |   // Task 19.1.1: Select outcome using probability weights
114 |   const outcomeType = selectOutcome(weights);
115 |
116 |   let rewardDetails: Record<string, unknown> = {};
117 |
118 |   if (outcomeType === "cosmetic") {
119 |     // Task 19.1.2: Cosmetic item grant – pick a random active cosmetic item
120 |     const { data: cosmetics } = await supabase
121 |       .from("marketplace_items")
122 |       .select("id, name, sub_category")
123 |       .eq("institution_id", institution_id)
124 |       .eq("category", "cosmetic")
125 |       .eq("is_active", true);
126 |
127 |     if (cosmetics && cosmetics.length > 0) {
128 |       const randomItem =
129 |         cosmetics[Math.floor(Math.random() * cosmetics.length)];
130 |       if (randomItem) {
131 |         // Grant the cosmetic by inserting an xp_purchase with 0 cost
132 |         const { data: purchase, error: purchaseErr } = await supabase
133 |           .from("xp_purchases")
134 |           .insert({
135 |             student_id,
136 |             item_id: randomItem.id,
137 |             xp_cost: 0,
138 |             status: "active",
139 |             purchased_at: new Date().toISOString(),
140 |             metadata: { source: "mystery_reward_box" },
141 |           })
142 |           .select()
143 |           .single();
144 |
145 |         if (purchaseErr) {
146 |           console.error(
147 |             "Mystery cosmetic grant failed:",
148 |             purchaseErr.message
149 |           );
150 |         }
151 |
152 |         rewardDetails = {
153 |           item_id: randomItem.id,
154 |           item_name: randomItem.name,
155 |           sub_category: randomItem.sub_category,
156 |           purchase_id: purchase?.id ?? null,
157 |         };
158 |       }
159 |     } else {
160 |       // Fallback to double_xp if no cosmetics available
161 |       rewardDetails = { fallback: true, original_type: "cosmetic" };
162 |     }
163 |   } else if (outcomeType === "boost") {
164 |     // Task 19.1.3: Temporary boost activation – 1 hour 1.5x XP boost
165 |     const expiresAt = new Date(Date.now() + 60 * 60 * 1000).toISOString();
166 |
167 |     const { error: boostErr } = await supabase
168 |       .from("student_active_boosts")
169 |       .insert({

```

```

170 |         student_id,
171 |         boost_type: "mystery_reward",
172 |         multiplier: 1.5,
173 |         activated_at: new Date().toISOString(),
174 |         expires_at: expiresAt,
175 |     });
176 |
177 |     if (boostErr) {
178 |         console.error("Mystery boost activation failed:", boostErr.message);
179 |     }
180 |
181 |     rewardDetails = {
182 |         boost_type: "mystery_reward",
183 |         multiplier: 1.5,
184 |         duration_minutes: 60,
185 |         expires_at: expiresAt,
186 |     };
187 | } else {
188 |     // Task 19.1.4: XP multiplier application for 2x XP outcomes
189 |     // The next XP award will be doubled – store a pending 2x multiplier
190 |     const expiresAt = new Date(Date.now() + 60 * 60 * 1000).toISOString();
191 |
192 |     const { error: boostErr } = await supabase
193 |         .from("student_active_boosts")
194 |         .insert({
195 |             student_id,
196 |             boost_type: "double_xp_mystery",
197 |             multiplier: 2.0,
198 |             activated_at: new Date().toISOString(),
199 |             expires_at: expiresAt,
200 |         });
201 |
202 |     if (boostErr) {
203 |         console.error("Mystery 2x XP activation failed:", boostErr.message);
204 |     }
205 |
206 |     rewardDetails = {
207 |         boost_type: "double_xp_mystery",
208 |         multiplier: 2.0,
209 |         duration_minutes: 60,
210 |         expires_at: expiresAt,
211 |     };
212 | }
213 |
214 | // Log to audit
215 | const { error: auditError } = await supabase.from("audit_logs").insert({
216 |     action: "mystery_reward_resolved",
217 |     entity_type: "mystery_reward",
218 |     entity_id: student_id,
219 |     performed_by: student_id,
220 |     changes: { outcome_type: outcomeType, ...rewardDetails },
221 | });
222 | if (auditError) throw auditError;
223 |
224 | return new Response(
225 |     JSON.stringify({
226 |         success: true,
227 |         outcome_type: outcomeType,
228 |         reward_details: rewardDetails,
229 |     }),
230 |     {
231 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
232 |     }
233 | );
234 | } catch (error) {
235 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
236 |         status: 500,
237 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
238 |     });
239 | }
240 | });
241 |

```

FILE: [supabase/functions/score-reflection-quality/index.ts](https://deno.land/std@0.168.0/http/server.ts)

TYPE: .ts | LINES: 1-300 | SHA256: 0f8e44e6f2884c9ef5d450b7341068bf65577efcf291eb8b12fbc0e0a3458bf9

```

1 | // =====
2 | // score-reflection-quality – Score reflection quality (originality, relevance, depth)
3 | // Fetches recent reflections for comparison, computes scores, persists result.
4 | // =====
5 |
6 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
7 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
8 |
9 | const corsHeaders = {
10 |     "Access-Control-Allow-Origin": "*",
11 |     "Access-Control-Allow-Headers":
12 |         "authorization, x-client-info, apikey, content-type",
13 | };
14 |
15 | interface ScoreRequest {
16 |     reflection_id: string;
17 |     reflection_type: "session_reflection" | "journal_entry";
18 |     student_id: string;
19 |     content: string;
20 | }
21 |
22 | interface QualityScoreResult {
23 |     score: number;
24 |     originality_score: number;
25 |     relevance_score: number;
26 |     depth_score: number;
27 |     flags: string[];
28 | }

```

[illegible]

[illegible]


```

237
238 if (reflection_type === "session_reflection") {
239     const { data } = await supabase
240       .from("session_reflections")
241       .select("content")
242       .eq("student_id", student_id)
243       .neq("id", reflection_id)
244       .order("created_at", { ascending: false })
245       .limit(10);
246     recentReflections = (data ?? []).map(
247       (r: { content: string }) => r.content
248     );
249   } else {
250     const { data } = await supabase
251       .from("journal_entries")
252       .select("content")
253       .eq("student_id", student_id)
254       .order("created_at", { ascending: false })
255       .limit(10);
256     recentReflections = (data ?? []).map(
257       (r: { content: string }) => r.content
258     );
259   }
260
261   // Compute scores
262   const scores = computeScores(content, recentReflections);
263   const suggestions = getSuggestions(scores);
264
265   // Persist to reflection_quality_scores
266   const { data: insertedScore, error: insertError } = await supabase
267     .from("reflection_quality_scores")
268     .insert({
269       reflection_id,
270       reflection_type,
271       student_id,
272       score: scores.score,
273       originality_score: scores.originality_score,
274       relevance_score: scores.relevance_score,
275       depth_score: scores.depth_score,
276       flags: scores.flags,
277     })
278     .select()
279     .single();
280
281   if (insertError) {
282     console.error("Failed to insert quality score:", insertError.message);
283     // Return scores even if persistence fails
284     return new Response(JSON.stringify({ score: scores, suggestions }), {
285       headers: { ...corsHeaders, "Content-Type": "application/json" },
286     });
287   }
288
289   return new Response(JSON.stringify({ score: insertedScore, suggestions }), {
290     headers: { ...corsHeaders, "Content-Type": "application/json" },
291   });
292 } catch (error) {
293   const message = error instanceof Error ? error.message : "Unknown error";
294   return new Response(JSON.stringify({ error: message }), {
295     status: 500,
296     headers: { ...corsHeaders, "Content-Type": "application/json" },
297   });
298 }
299 });
300

```

FILE: supabase/functions/select-adaptive-question/index.ts

TYPE: .ts | LINES: 1-701 | SHA256: 02f815dba7fc7722626b6d73c419c6a9634368cbd23e50414919c6170ab49fb9

[illegible]

[illegible]

[illegible]

```

245         status: 401,
246         headers: { ...corsHeaders, "Content-Type": "application/json" },
247     }
248 );
249 }
250
251 const studentId = user.id;
252
253 // % % Step 2: Validate Request Payload % % % % % % % % % % % % % % % % % % % % % % % % % %
254
255 const body = await req.json();
256 const validation = validatePayload(body);
257
258 if (!validation.valid) {
259     return new Response(JSON.stringify({ error: validation.error }), {
260         status: 400,
261         headers: { ...corsHeaders, "Content-Type": "application/json" },
262     });
263 }
264
265 const {
266     quiz_id,
267     quiz_attempt_id,
268     previous_question_id,
269     previous_answer_correct,
270     previous_response_time_ms,
271 } = validation.data;
272
273 // % % Step 3: Fetch quiz config % % % % % % % % % % % % % % % % % % % % % % % % % %
274
275 const { data: quiz, error: quizError } = await supabase
276     .from("quizzes")
277     .select("id, is_adaptive, adaptation_config, total_questions, course_id")
278     .eq("id", quiz_id)
279     .maybeSingle();
280
281 if (quizError || !quiz) {
282     return new Response(JSON.stringify({ error: "Quiz not found" }), {
283         status: 404,
284         headers: { ...corsHeaders, "Content-Type": "application/json" },
285     });
286 }
287
288 if (!quiz.is_adaptive) {
289     return new Response(
290         JSON.stringify({
291             error: "This quiz is not configured for adaptive mode",
292         }),
293         {
294             status: 400,
295             headers: { ...corsHeaders, "Content-Type": "application/json" },
296         }
297     );
298 }
299
300 const totalQuestions: number = quiz.total_questions ?? 10;
301 const adaptConfig = (quiz.adaptation_config ?? {}) as Record<
302     string,
303     unknown
304 >;
305 const stepUp =
306     typeof adaptConfig.difficulty_step_up === "number"
307     ? adaptConfig.difficulty_step_up
308     : DIFFICULTY_STEP_UP;
309 const stepDown =
310     typeof adaptConfig.difficulty_step_down === "number"
311     ? adaptConfig.difficulty_step_down
312     : DIFFICULTY_STEP_DOWN;
313
314 // % % Step 4: Fetch quiz_attempt record % % % % % % % % % % % % % % % % % % % % % % % % % %
315
316 const { data: attempt, error: attemptError } = await supabase
317     .from("quiz_attempts")
318     .select(
319         "id, question_sequence, difficulty_trajectory, per_question_times"
320     )
321     .eq("id", quiz_attempt_id)
322     .eq("student_id", studentId)
323     .maybeSingle();
324
325 if (attemptError || !attempt) {
326     return new Response(
327         JSON.stringify({
328             error: "Quiz attempt not found or does not belong to this student",
329         }),
330         {
331             status: 404,
332             headers: { ...corsHeaders, "Content-Type": "application/json" },
333         }
334     );
335 }
336
337 const questionSequence: QuestionSequenceEntry[] =
338     (attempt.question_sequence ?? []) as QuestionSequenceEntry[];
339 const difficultyTrajectory: DifficultyTrajectoryEntry[] =
340     (attempt.difficulty_trajectory ?? []) as DifficultyTrajectoryEntry[];
341 const perQuestionTimes: {
342     question_id: string;
343     response_time_ms: number;
344 }[] = (attempt.per_question_times ?? []) as {
345     question_id: string;
346     response_time_ms: number;
347 }[];
348

```

[illegible]

```

453 |         stepUp,
454 |         stepDown
455 |     );
456 | }
457 |
458 | // Record response time for previous question
459 | if (previous_question_id && previous_response_time_ms !== undefined) {
460 |     perQuestionTimes.push({
461 |         question_id: previous_question_id,
462 |         response_time_ms: previous_response_time_ms,
463 |     });
464 | }
465 |
466 | // Update previous trajectory entry with correctness
467 | if (
468 |     difficultyTrajectory.length > 0 &&
469 |     previous_answer_correct !== undefined
470 | ) {
471 |     difficultyTrajectory[difficultyTrajectory.length - 1].was_correct =
472 |         previous_answer_correct;
473 | }
474 |
475 | // Re-derive ability from attainment for Bloom's preference
476 | const { data: attainments } = await supabase
477 |     .from("outcome_attainment")
478 |     .select("outcome_id, attainment_percentage")
479 |     .eq("student_id", studentId)
480 |     .in("outcome_id", cloIds)
481 |     .eq("scope", "clo");
482 |
483 | if (attainments && attainments.length > 0) {
484 |     const totalAttainment = attainments.reduce(
485 |         (sum: number, a: { attainment_percentage: number }) =>
486 |             sum + (a.attainment_percentage ?? 0),
487 |         0
488 |     );
489 |     const avgAttainment = totalAttainment / attainments.length;
490 |     ability = classifyAbility(avgAttainment);
491 | }
492 | }
493 |
494 | // % % Step 7: Query eligible questions from question_bank % % % % % % % % %
495 |
496 | const answeredQuestionIds = questionSequence.map((q) => q.question_id);
497 | const bloomPreference = preferredBloomLevels(ability);
498 | let difficultyRange = DEFAULT_DIFFICULTY_RANGE;
499 | const warnings: string[] = [];
500 |
501 | const lowerBound = Math.max(1.0, targetDifficulty - difficultyRange);
502 | const upperBound = Math.min(5.0, targetDifficulty + difficultyRange);
503 |
504 | let query = supabase
505 |     .from("question_bank")
506 |     .select(
507 |         "id, question_text, question_type, options, bloom_level, clo_id, difficulty_rating"
508 |     )
509 |     .eq("status", "approved")
510 |     .in("clo_id", cloIds)
511 |     .gte("difficulty_rating", lowerBound)
512 |     .lte("difficulty_rating", upperBound);
513 |
514 | // Exclude previously answered questions
515 | if (answeredQuestionIds.length > 0) {
516 |     // Use not-in filter to exclude answered questions
517 |     query = query.not("id", "in", `(${answeredQuestionIds.join(",")})`);
518 | }
519 |
520 | const { data: eligibleQuestions } = await query;
521 |
522 | let candidates: QuestionRow[] = (eligibleQuestions ?? []) as QuestionRow[];
523 |
524 | // % % Step 8: Expand range if fewer than 3 eligible % % % % % % % % % % % %
525 |
526 | if (candidates.length < MIN_ELIGIBLE_QUESTIONS) {
527 |     difficultyRange = EXPANDED_DIFFICULTY_RANGE;
528 |     const expandedLower = Math.max(1.0, targetDifficulty - difficultyRange);
529 |     const expandedUpper = Math.min(5.0, targetDifficulty + difficultyRange);
530 |
531 |     let expandedQuery = supabase
532 |         .from("question_bank")
533 |         .select(
534 |             "id, question_text, question_type, options, bloom_level, clo_id, difficulty_rating"
535 |         )
536 |         .eq("status", "approved")
537 |         .in("clo_id", cloIds)
538 |         .gte("difficulty_rating", expandedLower)
539 |         .lte("difficulty_rating", expandedUpper);
540 |
541 |     if (answeredQuestionIds.length > 0) {
542 |         expandedQuery = expandedQuery.not(
543 |             "id",
544 |             "in",
545 |             `(${answeredQuestionIds.join(",")})`
546 |         );
547 |     }
548 |
549 |     const { data: expandedQuestions } = await expandedQuery;
550 |     candidates = (expandedQuestions ?? []) as QuestionRow[];
551 |
552 |     if (candidates.length < MIN_ELIGIBLE_QUESTIONS) {
553 |         warnings.push(
554 |             `Insufficient question pool: only ${candidates.length} eligible question(s) found ` +
555 |             `for target difficulty ${targetDifficulty.toFixed(
556 |                 1

```

```

557         }} (expanded range ±${EXPANDED_DIFFICULTY_RANGE}). ` +
558         "Consider adding more approved questions to the question bank."
559     );
560 } else {
561     warnings.push(
562         `Expanded difficulty range from ±${DEFAULT_DIFFICULTY_RANGE} to ±${EXPANDED_DIFFICULTY_RANGE} ` +
563         `to find sufficient questions (found ${candidates.length}).`
564     );
565 }
566 }
567
568 // %% Fallback: if still no candidates, try all approved for quiz CLOs %
569
570 if (candidates.length === 0) {
571     let fallbackQuery = supabase
572       .from("question_bank")
573       .select(
574         "id, question_text, question_type, options, bloom_level, clo_id, difficulty_rating"
575       )
576       .eq("status", "approved")
577       .in("clo_id", cloIds);
578
579     if (answeredQuestionIds.length > 0) {
580       fallbackQuery = fallbackQuery.not(
581         "id",
582         "in",
583         `${answeredQuestionIds.join(",")}`
584       );
585     }
586
587     const { data: fallbackQuestions } = await fallbackQuery;
588     candidates = (fallbackQuestions ?? []) as QuestionRow[];
589
590     if (candidates.length > 0) {
591       warnings.push(
592         "Fell back to random selection from all approved questions for linked CLOs. " +
593         "No questions matched the target difficulty range."
594       );
595     }
596 }
597
598 if (candidates.length === 0) {
599     return new Response(
600       JSON.stringify({
601         error: "No eligible questions available for this quiz session",
602         warnings,
603       }),
604       {
605         status: 422,
606         headers: { ...corsHeaders, "Content-Type": "application/json" },
607       }
608     );
609 }
610
611 // %% Step 9: Prefer questions at matching Bloom's levels % % % % % % % % % %
612
613 // Score candidates: prefer Bloom's levels matching ability
614 const scoredCandidates = candidates.map((q) => {
615     let score = 0;
616
617     // Bloom's preference: higher score for preferred levels
618     if (bloomPreference.includes(q.bloom_level)) {
619         score += 10;
620     }
621
622     // Closer to target difficulty = higher score
623     const diffDistance = Math.abs(q.difficulty_rating - targetDifficulty);
624     score += 5.0 - diffDistance; // max 5 bonus for exact match
625
626     return { question: q, score };
627 });
628
629 // Sort by score descending
630 scoredCandidates.sort((a, b) => b.score - a.score);
631
632 // Select from top candidates with some randomness (pick from top 3)
633 const topN = Math.min(3, scoredCandidates.length);
634 const selectedIndex = Math.floor(Math.random() * topN);
635 const selectedQuestion = scoredCandidates[selectedIndex].question;
636
637 // %% Step 10: Strip correct_answer and is_correct from options % % % % % % %
638
639 const sanitizedOptions = stripAndShuffleOptions(selectedQuestion.options);
640
641 // %% Step 11: Append to question_sequence and difficulty_trajectory % % %
642
643 questionSequence.push({
644     question_id: selectedQuestion.id,
645     difficulty_rating: selectedQuestion.difficulty_rating,
646     bloom_level: selectedQuestion.bloom_level,
647 });
648
649 difficultyTrajectory.push({
650     question_number: currentQuestionNumber,
651     target_difficulty: targetDifficulty,
652     actual_difficulty: selectedQuestion.difficulty_rating,
653     was_correct: null, // will be filled on next request
654 });
655
656 // Update quiz_attempt record
657 const { error: updateError } = await supabase
658   .from("quiz_attempts")
659   .update({
660     question_sequence: questionSequence,

```

```

661 difficulty_trajectory: difficultyTrajectory,
662 per_question_times: perQuestionTimes,
663 })
664 .eq("id", quiz_attempt_id);
665
666 if (updateError) {
667   console.error("Failed to update quiz_attempt:", updateError.message);
668   // Non-fatal: continue serving the question
669 }
670
671 // % % Step 12: Return question to student UI % % % % % % % % % % % % % % % % % % % % % % %
672
673 return new Response(
674   JSON.stringify({
675     question: {
676       id: selectedQuestion.id,
677       question_text: selectedQuestion.question_text,
678       question_type: selectedQuestion.question_type,
679       options: sanitizedOptions,
680       bloom_level: selectedQuestion.bloom_level,
681       clo_id: selectedQuestion.clo_id,
682     },
683     question_number: currentQuestionNumber,
684     total_questions: totalQuestions,
685     current_target_difficulty: Math.round(targetDifficulty * 100) / 100,
686     session_complete: false,
687   }),
688   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
689 );
690 } catch (error) {
691   console.error(
692     "Unhandled error in select-adaptive-question:",
693     (error as Error).message
694   );
695   return new Response(JSON.stringify({ error: (error as Error).message }), {
696     status: 500,
697     headers: { ...corsHeaders, "Content-Type": "application/json" },
698   });
699 }
700 });
701

```

FILE: supabase/functions/semester-transition/index.ts

```
TYPE: .ts | LINES: 1-101 | SHA256: ec2eb472130e14ee19ed91e246e8c851e0722b0140ed22f8260b6d63d5c2c414
```

```

1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3
4 const corsHeaders = {
5   "Access-Control-Allow-Origin": "*",
6   "Access-Control-Allow-Headers":
7     "authorization, x-client-info, apikey, content-type",
8 };
9
10 serve(async (req) => {
11   if (req.method === "OPTIONS") {
12     return new Response("ok", { headers: corsHeaders });
13   }
14
15   try {
16     // Verify JWT – extract from Authorization header
17     const authHeader = req.headers.get("Authorization");
18     if (!authHeader) {
19       return new Response(
20         JSON.stringify({ error: "Missing authorization header" }),
21         {
22           status: 401,
23           headers: { ...corsHeaders, "Content-Type": "application/json" },
24         }
25       );
26     }
27
28     const supabase = createClient(
29       Deno.env.get("SUPABASE_URL")!,
30       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
31     );
32
33     // Verify the user's JWT
34     const token = authHeader.replace("Bearer ", "");
35     const {
36       data: { user },
37       error: authError,
38     } = await supabase.auth.getUser(token);
39     if (authError || !user) {
40       return new Response(
41         JSON.stringify({ error: "Invalid or expired token" }),
42         {
43           status: 401,
44           headers: { ...corsHeaders, "Content-Type": "application/json" },
45         }
46       );
47     }
48
49     // Role authorization – only admin can trigger semester transitions
50     const { data: profile } = await supabase
51       .from("profiles")
52       .select("role")
53       .eq("id", user.id)
54       .single();
55
56     if (!profile || profile.role !== "admin") {
57       return new Response(
58         JSON.stringify({ error: "Forbidden – admin role required" }),
59         {

```


[illegible]

```

163 |
164 | };
165 |
166 | case "new_assignment":
167 |     return {
168 |         subject: `ðŸŽŸ New Assignment: ${data.assignment_title ?? "Untitled"}`,
169 |         html: `
170 |             <div style="font-family: 'Noto Sans', sans-serif; max-width: 600px; margin: 0 auto;">
171 |                 <h2 style="color: #0f172a;">New Assignment Posted</h2>
172 |                 <p>Hi ${data.student_name ?? "there"},</p>
173 |                 <p>A new assignment has been posted in <strong>${
174 |                     data.course_name ?? "your course"
175 |                 }</strong></p>
176 |                 <div style="background: #f8fafc; border-radius: 8px; padding: 16px; margin: 16px 0;">
177 |                     <h3 style="margin: 0 0 8px 0;">${
178 |                         data.assignment_title ?? "Untitled"
179 |                     }</h3>
180 |                     <p style="margin: 0; color: #64748b;">Due: ${
181 |                         data.due_date ?? "TBD"
182 |                     }</p>
183 |                 </div>
184 |                 <a href="${
185 |                     data.assignment_url ?? "#"
186 |                 }" style="display: inline-block; padding: 12px 24px; background: linear-gradient(135deg, #14B8A6 0
187 |                 </div>
188 |             `;
189 |     };
190 |
191 | case "grade_released":
192 |     return {
193 |         subject: `ðŸŽŸ Grade Released: ${data.assignment_title ?? "Assignment"}`,
194 |         html: `
195 |             <div style="font-family: 'Noto Sans', sans-serif; max-width: 600px; margin: 0 auto;">
196 |                 <h2 style="color: #0f172a;">Your Grade is Ready</h2>
197 |                 <p>Hi ${data.student_name ?? "there"},</p>
198 |                 <p>Your grade for <strong>${
199 |                     data.assignment_title ?? "an assignment"
200 |                 }</strong> in ${
201 |                     data.course_name ?? "your course"
202 |                 } has been released.</p>
203 |                 <div style="background: #f8fafc; border-radius: 8px; padding: 16px; margin: 16px 0;">
204 |                     <p style="margin: 0;"><strong>Score:</strong> ${
205 |                         data.score ?? "N/A"
206 |                     }%</p>
207 |                 </div>
208 |                 <a href="${
209 |                     data.grade_url ?? "#"
210 |                 }" style="display: inline-block; padding: 12px 24px; background: linear-gradient(135deg, #14B8A6 0
211 |                 </div>
212 |             `;
213 |     };
214 |
215 | case "bulk_import_invitation":
216 |     return {
217 |         subject: "ðŸŽŸ Welcome to Edeviser!",
218 |         html: `
219 |             <div style="font-family: 'Noto Sans', sans-serif; max-width: 600px; margin: 0 auto;">
220 |                 <h2 style="color: #0f172a;">Welcome to Edeviser!</h2>
221 |                 <p>Hi ${data.full_name ?? "there"},</p>
222 |                 <p>You've been invited to join <strong>${
223 |                     data.institution_name ?? "your institution"
224 |                 }</strong> on Edeviser as a <strong>${
225 |                     data.role ?? "user"
226 |                 }</strong></p>
227 |                 <p>Click below to set up your account:</p>
228 |                 <a href="${
229 |                     data.invite_url ?? "#"
230 |                 }" style="display: inline-block; padding: 12px 24px; background: linear-gradient(135deg, #14B8A6 0
231 |                 </div>
232 |             `;
233 |     };
234 |
235 | case "parent_grade_released":
236 |     return {
237 |         subject: `ðŸŽŸ Grade Released for ${data.student_name ?? "your child"}`,
238 |         html: `
239 |             <div style="font-family: 'Noto Sans', sans-serif; max-width: 600px; margin: 0 auto;">
240 |                 <h2 style="color: #0f172a;">Grade Released</h2>
241 |                 <p>Hi ${data.parent_name ?? "there"},</p>
242 |                 <p>A grade has been released for <strong>${
243 |                     data.student_name ?? "your child"
244 |                 }</strong> in <strong>${
245 |                     data.course_name ?? "a course"
246 |                 }</strong></p>
247 |                 <div style="background: #f8fafc; border-radius: 8px; padding: 16px; margin: 16px 0;">
248 |                     <p style="margin: 0;"><strong>Assignment:</strong> ${
249 |                         data.assignment_title ?? "N/A"
250 |                     }</p>
251 |                     <p style="margin: 0;"><strong>Score:</strong> ${
252 |                         data.score ?? "N/A"
253 |                     }%</p>
254 |                 </div>
255 |                 <a href="${
256 |                     data.dashboard_url ?? "#"
257 |                 }" style="display: inline-block; padding: 12px 24px; background: linear-gradient(135deg, #14B8A6 0
258 |                 </div>
259 |             `;
260 |     };
261 |
262 | case "parent_attendance_alert":
263 |     return {
264 |         subject: `ðŸŽŸ Attendance Alert for ${data.student_name ?? "your child"}`,
265 |         html: `
266 |             <div style="font-family: 'Noto Sans', sans-serif; max-width: 600px; margin: 0 auto;">

```

[illegible]

```

371 }
372
373 try {
374   // %% Auth: require admin role or internal service call % % % % % % % % % %
375   const authHeader = req.headers.get("Authorization") ?? "";
376   const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY") ?? "";
377   const isServiceRole =
378     serviceRoleKey && authHeader.replace("Bearer ", "") === serviceRoleKey;
379
380   if (!isServiceRole) {
381     const userClient = createClient(
382       Deno.env.get("SUPABASE_URL")!,
383       Deno.env.get("SUPABASE_ANON_KEY")!,
384       { global: { headers: { Authorization: authHeader } } }
385     );
386     const {
387       data: { user },
388       error: authError,
389     } = await userClient.auth.getUser();
390     if (authError || !user) {
391       return new Response(JSON.stringify({ error: "Unauthorized" }), {
392         status: 401,
393         headers: { ...corsHeaders, "Content-Type": "application/json" },
394       });
395     }
396     // Role lives in the profiles table, NOT the JWT (app_metadata is empty on
397     // this project). Resolve it server-side from profiles by the caller's id,
398     // mirroring the already-deployed ai-feedback-draft pattern.
399     const adminClient = createClient(
400       Deno.env.get("SUPABASE_URL")!,
401       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
402     );
403     const { data: callerProfile } = await adminClient
404       .from("profiles")
405       .select("role")
406       .eq("id", user.id)
407       .maybeSingle();
408     const role =
409       (callerProfile?.role as string) ??
410       user.app_metadata?.role ??
411       user.user_metadata?.role ??
412       "";
413     if (role !== "admin") {
414       return new Response(
415         JSON.stringify({ error: "Forbidden: admin role required" }),
416         {
417           status: 403,
418           headers: { ...corsHeaders, "Content-Type": "application/json" },
419         }
420       );
421     }
422   }
423
424   const resendApiKey = Deno.env.get("RESEND_API_KEY");
425   if (!resendApiKey) {
426     console.error("RESEND_API_KEY is not configured");
427     return new Response(
428       JSON.stringify({ error: "Email service not configured" }),
429       {
430         status: 500,
431         headers: { ...corsHeaders, "Content-Type": "application/json" },
432       }
433     );
434   }
435
436   const supabase = createClient(
437     Deno.env.get("SUPABASE_URL")!,
438     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
439   );
440
441   const body = await req.json();
442   const validation = validatePayload(body);
443
444   if (!validation.valid) {
445     return new Response(JSON.stringify({ error: validation.error }), {
446       status: 400,
447       headers: { ...corsHeaders, "Content-Type": "application/json" },
448     });
449   }
450
451   const { to, template, data } = validation.data;
452
453   // %% Check email preferences (opt-out) % % % % % % % % % % % % % % % % % % % % % %
454   if (OPT_OUT_TEMPLATES.includes(template)) {
455     const { data: profile } = await supabase
456       .from("profiles")
457       .select("email_preferences")
458       .eq("email", to)
459       .maybeSingle();
460
461     if (profile) {
462       const prefs: EmailPreferences = {
463         ...DEFAULT_EMAIL_PREFERENCES,
464         ...((profile.email_preferences as Partial<EmailPreferences>) ?? {}),
465       };
466
467       if (!prefs[template as keyof EmailPreferences]) {
468         return new Response(
469           JSON.stringify({
470             success: true,
471             skipped: true,
472             reason: "User opted out of this notification type",
473           }),
474           { headers: { ...corsHeaders, "Content-Type": "application/json" } }
475         );
476       }
477     }
478   }
479 }

```

```

475     } };
476   }
477 }
478 }
479
480 // %% Render template %%%%%%%%%%%%%%%
481 const { subject, html } = renderTemplate(template, data);
482
483 // %% Send email via Resend with retry %%%%%%%%%%
484 const fromAddress =
485   Deno.env.get("RESEND_FROM_ADDRESS") ?? "Edeviser <noreply@edeviser.com>";
486
487 const result = await sendWithRetry(resendApiKey, {
488   from: fromAddress,
489   to,
490   subject,
491   html,
492 });
493
494 if (!result.success) {
495   console.error(
496     `Email delivery failed for ${to} (template: ${template}): ${result.error}`
497   );
498   return new Response(
499     JSON.stringify({
500       error: "Email delivery failed",
501       detail: result.error,
502     }),
503     {
504       status: 502,
505       headers: { ...corsHeaders, "Content-Type": "application/json" },
506     }
507   );
508 }
509
510 return new Response(JSON.stringify({ success: true, template, to }), {
511   headers: { ...corsHeaders, "Content-Type": "application/json" },
512 });
513 } catch (error) {
514   console.error("send-email-notification error:", (error as Error).message);
515   return new Response(JSON.stringify({ error: (error as Error).message }), {
516     status: 500,
517     headers: { ...corsHeaders, "Content-Type": "application/json" },
518   });
519 }
520 });
521

```

FILE: supabase/functions/send-invitation-email/index.ts

TYPE: .ts | LINES: 1-217 | SHA256: 8b13f0352af2a3ef3adf9c1013a2d0d36f48ee058b9bb948ac6882f68b93ea9d

```

1 import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3
4 const corsHeaders = {
5   "Access-Control-Allow-Origin": "*",
6   "Access-Control-Allow-Headers":
7     "authorization, x-client-info, apikey, content-type",
8 };
9
10 interface InviteRequest {
11   institution_id: string;
12   invites: Array<{
13     email: string;
14     role: string;
15   }>;
16 }
17
18 interface InviteResult {
19   email: string;
20   success: boolean;
21   error?: string;
22 }
23
24 serve(async (req) => {
25   // Handle CORS preflight
26   if (req.method === "OPTIONS") {
27     return new Response("ok", { headers: corsHeaders });
28   }
29
30   try {
31     const supabaseUrl = Deno.env.get("SUPABASE_URL");
32     const supabaseServiceKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY");
33     const resendApiKey = Deno.env.get("RESEND_API_KEY");
34
35     if (!supabaseUrl || !supabaseServiceKey || !resendApiKey) {
36       return new Response(
37         JSON.stringify({
38           error: "Missing environment variables",
39         }),
40         {
41           status: 500,
42           headers: { ...corsHeaders, "Content-Type": "application/json" },
43         }
44       );
45     }
46
47     const supabase = createClient(supabaseUrl, supabaseServiceKey);
48
49     const body: InviteRequest = await req.json();
50     const { institution_id, invites } = body;
51
52     if (!institution_id || !invites || invites.length === 0) {
53       return new Response(

```

```

54 |         JSON.stringify({
55 |             error: "Missing institution_id or invites",
56 |         }),
57 |         {
58 |             status: 400,
59 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
60 |         }
61 |     );
62 | }
63 |
64 | // Fetch institution details
65 | const { data: institution, error: institutionError } = await supabase
66 |     .from("institutions")
67 |     .select("name, slug")
68 |     .eq("id", institution_id)
69 |     .single();
70 |
71 | if (institutionError || !institution) {
72 |     return new Response(
73 |         JSON.stringify({
74 |             error: "Institution not found",
75 |         }),
76 |         {
77 |             status: 404,
78 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
79 |         }
80 |     );
81 | }
82 |
83 | const results: InviteResult[] = [];
84 |
85 | // Process each invite
86 | for (const invite of invites) {
87 |     try {
88 |         // Generate a secure token (using crypto.getRandomValues)
89 |         const tokenBytes = new Uint8Array(32);
90 |         crypto.getRandomValues(tokenBytes);
91 |         const token = Array.from(tokenBytes)
92 |             .map(b => b.toString(16).padStart(2, "0"))
93 |             .join("");
94 |
95 |         // Insert invitation record
96 |         const { data: invitationData, error: insertError } = await supabase
97 |             .from("invitations")
98 |             .insert({
99 |                 institution_id,
100 |                 email: invite.email,
101 |                 role: invite.role,
102 |                 token,
103 |                 expires_at: new Date(
104 |                     Date.now() + 7 * 24 * 60 * 60 * 1000
105 |                 ).toISOString(),
106 |                 created_by: "system", // In production, this should be the authenticated user
107 |             })
108 |             .select()
109 |             .single();
110 |
111 |         if (insertError) {
112 |             results.push({
113 |                 email: invite.email,
114 |                 success: false,
115 |                 error: insertError.message,
116 |             });
117 |             continue;
118 |         }
119 |
120 |         // Build invitation link
121 |         const inviteLink = `${supabaseUrl.replace(
122 |             "/rest/v1",
123 |             ""
124 |         )}/accept-invite/${token}`;
125 |
126 |         // Send email via Resend
127 |         const emailResponse = await fetch("https://api.resend.com/emails", {
128 |             method: "POST",
129 |             headers: {
130 |                 "Content-Type": "application/json",
131 |                 Authorization: `Bearer ${resendApiKey}`,
132 |             },
133 |             body: JSON.stringify({
134 |                 from: "noreply@edeviser.com",
135 |                 to: invite.email,
136 |                 subject: `You're invited to join ${institution.name} on Edeviser`,
137 |                 html: `
138 |                 <div style="font-family: -apple-system, BlinkMacSystemFont, 'Segoe UI', Roboto, 'Helvetica Neue'
139 |                 <div style="background: linear-gradient(135deg, #14B8A6 0%, #0382BD 100%); padding: 40px 20px;
140 |                 <h1 style="color: white; margin: 0; font-size: 28px; font-weight: bold;">Welcome to Edeviser
141 |                 </div>
142 |                 <div style="background: white; padding: 40px 20px; border-radius: 0 0 12px 12px; border: 1px s
143 |                 <p style="color: #374151; font-size: 16px; margin: 0 0 20px 0;">
144 |                     Hello,
145 |                 </p>
146 |                 <p style="color: #374151; font-size: 16px; margin: 0 0 20px 0;">
147 |                     You've been invited to join <strong>${institution.name}</strong> on Edeviser as a <strong>
148 |                 </p>
149 |                 <p style="color: #374151; font-size: 16px; margin: 0 0 30px 0;">
150 |                     Click the button below to accept your invitation and create your account:
151 |                 </p>
152 |                 <div style="text-align: center; margin: 30px 0;">
153 |                     <a href="${inviteLink}" style="display: inline-block; background: linear-gradient(135deg,
154 |                     Accept Invitation
155 |                 </a>
156 |                 </div>
157 |                 <p style="color: #6b7280; font-size: 14px; margin: 30px 0 0 0;">

```

```

158 |         Or copy and paste this link in your browser:
159 |     </p>
160 |     <p style="color: #3b82f6; font-size: 12px; word-break: break-all; margin: 10px 0 0 0;">
161 |         ${inviteLink}
162 |     </p>
163 |     <p style="color: #6b7280; font-size: 12px; margin: 30px 0 0 0;">
164 |         This invitation expires in 7 days.
165 |     </p>
166 | </div>
167 | </div>
168 | },
169 | },
170 | });
171 |
172 | if (!emailResponse.ok) {
173 |     const emailError = await emailResponse.json();
174 |     results.push({
175 |         email: invite.email,
176 |         success: false,
177 |         error: `Email send failed: ${emailError.message}`,
178 |     });
179 |     continue;
180 | }
181 |
182 | results.push({
183 |     email: invite.email,
184 |     success: true,
185 | });
186 | } catch (error) {
187 |     results.push({
188 |         email: invite.email,
189 |         success: false,
190 |         error: error instanceof Error ? error.message : "Unknown error",
191 |     });
192 | }
193 | }
194 |
195 | return new Response(
196 |     JSON.stringify({
197 |         success: true,
198 |         results,
199 |     }),
200 |     {
201 |         status: 200,
202 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
203 |     }
204 | );
205 | } catch (error) {
206 |     return new Response(
207 |         JSON.stringify({
208 |             error: error instanceof Error ? error.message : "Unknown error",
209 |         }),
210 |         {
211 |             status: 500,
212 |             headers: { ...corsHeaders, "Content-Type": "application/json" },
213 |         }
214 |     );
215 | }
216 | });
217 |

```

FILE: supabase/functions/send-onboarding-reminder/index.ts

TYPE: .ts | LINES: 1-99 | SHA256: eece97cc876c096d99724a6db4b048efc5807adddcb0cec56951a0fd330b19b8

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/supabase/supabase-js@2";
3 | import { z } from "https://esm.sh/zod@3.23.8";
4 |
5 | const PayloadSchema = z.object({
6 |   student_id: z.string().min(1),
7 |   email: z.string().email(),
8 | });
9 |
10 | const corsHeaders = {
11 |   "Access-Control-Allow-Origin": "*",
12 |   "Access-Control-Allow-Headers":
13 |     "authorization, x-client-info, apikey, content-type",
14 | };
15 |
16 | serve(async (req) => {
17 |   if (req.method === "OPTIONS") {
18 |     return new Response("ok", { headers: corsHeaders });
19 |   }
20 |
21 |   try {
22 |     // Verify JWT - extract from Authorization header
23 |     const authHeader = req.headers.get("Authorization");
24 |     if (!authHeader) {
25 |       return new Response(
26 |         JSON.stringify({ error: "Missing authorization header" }),
27 |         {
28 |           status: 401,
29 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
30 |         }
31 |       );
32 |     }
33 |
34 |     const supabase = createClient(
35 |       Deno.env.get("SUPABASE_URL")!,
36 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
37 |     );
38 |
39 |     // Verify the user's JWT
40 |     const token = authHeader.replace("Bearer ", "");

```



```

41 |     const {
42 |       data: { user },
43 |       error: authError,
44 |     } = await supabase.auth.getUser(token);
45 |     if (authError || !user) {
46 |       return new Response(
47 |         JSON.stringify({ error: "Invalid or expired token" }),
48 |         {
49 |           status: 401,
50 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
51 |         }
52 |       );
53 |     }
54 |   }
55 |   // Role authorization - only admin can send onboarding reminders
56 |   const { data: profile } = await supabase
57 |     .from("profiles")
58 |     .select("role")
59 |     .eq("id", user.id)
60 |     .single();
61 |
62 |   if (!profile || profile.role !== "admin") {
63 |     return new Response(
64 |       JSON.stringify({ error: "Forbidden - admin role required" }),
65 |       {
66 |         status: 403,
67 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
68 |       }
69 |     );
70 |   }
71 |
72 |   const body = await req.json();
73 |   const parsed = PayloadSchema.safeParse(body);
74 |   if (!parsed.success) {
75 |     return new Response(JSON.stringify({ error: parsed.error.message }), {
76 |       status: 400,
77 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
78 |     });
79 |   }
80 |   const { student_id, email } = parsed.data;
81 |
82 |   // TODO: Integrate with Resend to send the onboarding reminder email.
83 |   // Use RESEND_API_KEY from Deno.env.get('RESEND_API_KEY').
84 |   // Template should include a deep link back to the onboarding wizard.
85 |   const result = {
86 |     sent: true,
87 |   };
88 |
89 |   return new Response(JSON.stringify(result), {
90 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
91 |   });
92 | } catch (error) {
93 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
94 |     status: 500,
95 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
96 |   });
97 | }
98 | });
99 |

```

FILE: supabase/functions/streak-risk-cron/index.ts

TYPE: .ts | LINES: 1-162 | SHA256: a96d375cb284128f95feb0aa9a237dbcee258b7000a9ebed60a669c7f8b38a36

```

1 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
2 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
3 |
4 | const corsHeaders = {
5 |   "Access-Control-Allow-Origin": "*",
6 |   "Access-Control-Allow-Headers":
7 |     "authorization, x-client-info, apikey, content-type",
8 | };
9 |
10 | // % % % pg_cron schedule: 0 20 * * * (daily 8 PM) % % % % % % % % % % % % % % % % % % % % % % % % % %
11 | // Queries students with active streaks who have NOT logged in today.
12 | // Sends a streak_risk email notification to each via send-email-notification.
13 |
14 | serve(async (req) => {
15 |   if (req.method === "OPTIONS") {
16 |     return new Response("ok", { headers: corsHeaders });
17 |   }
18 |
19 |   try {
20 |     // % % Auth: cron secret or service role only % % % % % % % % % % % % % % % % % % % % % % % % % %
21 |     const cronSecret = req.headers.get("x-cron-secret");
22 |     const expectedSecret = Deno.env.get("CRON_SECRET");
23 |     const authHeader = req.headers.get("Authorization") ?? "";
24 |     const serviceRoleKey = Deno.env.get("SUPABASE_SERVICE_ROLE_KEY") ?? "";
25 |     const isServiceRole =
26 |       serviceRoleKey && authHeader.replace("Bearer ", "") === serviceRoleKey;
27 |     const isCron = expectedSecret && cronSecret === expectedSecret;
28 |
29 |     if (!isServiceRole && !isCron) {
30 |       return new Response(
31 |         JSON.stringify({
32 |           error: "Unauthorized: cron secret or service role required",
33 |         }),
34 |         {
35 |           status: 401,
36 |           headers: { ...corsHeaders, "Content-Type": "application/json" },
37 |         }
38 |       );
39 |     }
40 |   }
41 |
42 |   const supabase = createClient(

```

```

42 |     Deno.env.get("SUPABASE_URL")!,
43 |     Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
44 | );
45 |
46 | const todayUTC = new Date().toISOString().slice(0, 10); // YYYY-MM-DD
47 |
48 | // Find students with active streaks (streak_current > 0) whose
49 | // last_login_date is NOT today – meaning they haven't logged in yet.
50 | // NOTE: the live DB column is `streak_current` (NOT `streak_count`).
51 | const { data: atRiskStudents, error: queryErr } = await supabase
52 |   .from("student_gamification")
53 |   .select("student_id, streak_current")
54 |   .gt("streak_current", 0)
55 |   .neq("last_login_date", todayUTC);
56 |
57 | if (queryErr) {
58 |   console.error("Failed to query at-risk students:", queryErr.message);
59 |   return new Response(
60 |     JSON.stringify({
61 |       error: "Failed to query at-risk students",
62 |       detail: queryErr.message,
63 |     }),
64 |     {
65 |       status: 500,
66 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
67 |     }
68 |   );
69 | }
70 |
71 | if (!atRiskStudents || atRiskStudents.length === 0) {
72 |   return new Response(
73 |     JSON.stringify({
74 |       success: true,
75 |       notified: 0,
76 |       message: "No at-risk students found",
77 |     }),
78 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
79 |   );
80 | }
81 |
82 | // Fetch profiles for these students (email + name)
83 | const studentIds = atRiskStudents.map((s) => s.student_id);
84 | const { data: profiles, error: profileErr } = await supabase
85 |   .from("profiles")
86 |   .select("id, email, full_name")
87 |   .in("id", studentIds)
88 |   .eq("is_active", true);
89 |
90 | if (profileErr) {
91 |   console.error("Failed to fetch profiles:", profileErr.message);
92 |   return new Response(
93 |     JSON.stringify({
94 |       error: "Failed to fetch profiles",
95 |       detail: profileErr.message,
96 |     }),
97 |     {
98 |       status: 500,
99 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
100 |    }
101 |   );
102 | }
103 |
104 | const profileMap = new Map(
105 |   (profiles ?? []).map(
106 |     (p: { id: string; email: string; full_name: string }) => [p.id, p]
107 |   )
108 | );
109 |
110 | let notified = 0;
111 | const errors: Array<{ student_id: string; error: string }> = [];
112 |
113 | const loginUrl = `${
114 |   Deno.env.get("SUPABASE_URL")?.replace(".supabase.co", ".vercel.app") ??
115 |   "https://edeviser.vercel.app"
116 | }/login`;
117 |
118 | for (const student of atRiskStudents) {
119 |   const profile = profileMap.get(student.student_id);
120 |   if (!profile) continue;
121 |
122 |   try {
123 |     await supabase.functions.invoke("send-email-notification", {
124 |       body: {
125 |         to: profile.email,
126 |         template: "streak_risk",
127 |         data: {
128 |           student_name: profile.full_name,
129 |           // Outbound email template key remains `streak_count` for
130 |           // backward-compat; value comes from the live `streak_current` column.
131 |           streak_count: student.streak_current,
132 |           login_url: loginUrl,
133 |         },
134 |       },
135 |     });
136 |     notified++;
137 |   } catch (err) {
138 |     errors.push({
139 |       student_id: student.student_id,
140 |       error: (err as Error).message,
141 |     });
142 |   }
143 | }
144 |
145 | return new Response(

```

```

146         JSON.stringify({
147             success: true,
148             notified,
149             total_at_risk: atRiskStudents.length,
150             errors,
151         }),
152         { headers: { ...corsHeaders, "Content-Type": "application/json" } }
153     );
154 } catch (error) {
155     console.error("streak-risk-cron error:", (error as Error).message);
156     return new Response(JSON.stringify({ error: (error as Error).message }), {
157         status: 500,
158         headers: { ...corsHeaders, "Content-Type": "application/json" },
159     });
160 }
161 });
162

```

FILE: supabase/functions/suggest-goals/index.ts

```
TYPE: .ts | LINES: 1-520 | SHA256: 318eb19204eaf52d54ec024c66c55eb33821a961a81fda88e3f51a45a975875d
```

[illegible]

[illegible]

```

188 |     });
189 | }
190 |
191 | // % % 3.3.2 Fetch student's enrolled courses, attainment levels, self-efficacy score % %
192 |
193 | const { data: enrollments, error: enrollErr } = await supabase
194 |   .from("student_courses")
195 |   .select("course_id, courses(id, name)")
196 |   .eq("student_id", student_id);
197 |
198 | if (enrollErr) {
199 |   console.error("Failed to fetch enrollments:", enrollErr.message);
200 |   return new Response(
201 |     JSON.stringify({
202 |       error: "Failed to fetch enrolled courses",
203 |       detail: enrollErr.message,
204 |     }),
205 |     {
206 |       status: 500,
207 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
208 |     }
209 |   );
210 | }
211 |
212 | const enrolledCourses = (enrollments ?? []).map(
213 |   (e: Record<string, unknown>) => {
214 |     const course = e.courses as { id: string; name: string } | null;
215 |     return {
216 |       course_id: e.course_id as string,
217 |       course_name: course?.name ?? "Unknown Course",
218 |     };
219 |   }
220 | );
221 |
222 | // Fetch attainment levels for enrolled courses
223 | const courseIds = enrolledCourses.map(
224 |   (c: { course_id: string }) => c.course_id
225 | );
226 | const courseNameMap = new Map(
227 |   enrolledCourses.map((c: { course_id: string; course_name: string }) => [
228 |     c.course_id,
229 |     c.course_name,
230 |   ])
231 | );
232 |
233 | let attainmentData: CourseAttainment[] = [];
234 |
235 | if (courseIds.length > 0) {
236 |   const { data: attainments, error: attainErr } = await supabase
237 |     .from("outcome_attainment")
238 |     .select("outcome_id, course_id, score")
239 |     .eq("student_id", student_id)
240 |     .in("course_id", courseIds)
241 |     .eq("scope", "clo");
242 |
243 |   if (attainErr) {
244 |     console.error("Failed to fetch attainment:", attainErr.message);
245 |     // Non-fatal – proceed without attainment data
246 |   }
247 |
248 |   if (attainments && attainments.length > 0) {
249 |     attainmentData = attainments.map((a: Record<string, unknown>) => ({
250 |       course_id: a.course_id as string,
251 |       course_name:
252 |         courseNameMap.get(a.course_id as string) ?? "Unknown Course",
253 |       avg_attainment: a.score as number,
254 |       clo_id: a.outcome_id as string,
255 |       clo_title: null, // will be enriched below if needed
256 |     }));
257 |   }
258 | }
259 |
260 | // Fetch self-efficacy score from student_profiles
261 | const { data: studentProfile, error: profileErr } = await supabase
262 |   .from("student_profiles")
263 |   .select("self_efficacy, profile_completeness")
264 |   .eq("student_id", student_id)
265 |   .order("assessment_version", { ascending: false })
266 |   .limit(1)
267 |   .maybeSingle();
268 |
269 | if (profileErr) {
270 |   console.error("Failed to fetch student profile:", profileErr.message);
271 |   // Non-fatal – proceed without self-efficacy data
272 | }
273 |
274 | const selfEfficacy = studentProfile?.self_efficacy as {
275 |   overall: number;
276 | } | null;
277 | const selfEfficacyScore = selfEfficacy?.overall ?? 50; // default to moderate
278 |
279 | // % % 3.3.3 Fetch upcoming deadlines for the week % % % % % % % % % % % % % % % %
280 |
281 | let deadlines: UpcomingDeadline[] = [];
282 |
283 | if (courseIds.length > 0) {
284 |   const { data: assignments, error: assignErr } = await supabase
285 |     .from("assignments")
286 |     .select("id, title, course_id, due_date")
287 |     .in("course_id", courseIds)
288 |     .gte("due_date", week_start)
289 |     .lte("due_date", week_end)
290 |     .order("due_date", { ascending: true });
291 |

```

```

292 |     if (assignErr) {
293 |         console.error("Failed to fetch assignments:", assignErr.message);
294 |         // Non-fatal – proceed without deadline data
295 |     }
296 |
297 |     deadlines = (assignments ?? []).map((a: Record<string, unknown>) => ({
298 |         assignment_id: a.id as string,
299 |         assignment_title: a.title as string,
300 |         course_id: a.course_id as string,
301 |         course_name:
302 |             courseNameMap.get(a.course_id as string) ?? "Unknown Course",
303 |         due_date: a.due_date as string,
304 |     }));
305 | }
306 |
307 | // % % 3.3.4 Fetch historical cohort goal completion rates % % % % % % % % % %
308 |
309 | let cohortRates: Record<string, number> = {
310 |     easy: 85,
311 |     moderate: 65,
312 |     ambitious: 35,
313 | };
314 |
315 | if (courseIds.length > 0) {
316 |     const { data: cohortGoals, error: cohortErr } = await supabase
317 |         .from("goal_suggestions")
318 |         .select("difficulty, status")
319 |         .in(
320 |             "student_id",
321 |             (
322 |                 await supabase
323 |                     .from("student_courses")
324 |                     .select("student_id")
325 |                     .in("course_id", courseIds)
326 |                 ).data?.map((s: { student_id: string }) => s.student_id) ?? []
327 |             )
328 |         ).neq("student_id", student_id); // exclude current student
329 |
330 |     if (!cohortErr && cohortGoals && cohortGoals.length > 0) {
331 |         const difficultyGroups: Record<
332 |             string,
333 |             { total: number; completed: number }
334 |         > = {};
335 |
336 |         for (const goal of cohortGoals) {
337 |             const diff = goal.difficulty as string;
338 |             if (!difficultyGroups[diff]) {
339 |                 difficultyGroups[diff] = { total: 0, completed: 0 };
340 |             }
341 |             difficultyGroups[diff].total++;
342 |             if (goal.status === "completed") {
343 |                 difficultyGroups[diff].completed++;
344 |             }
345 |         }
346 |
347 |         for (const [diff, counts] of Object.entries(difficultyGroups)) {
348 |             if (counts.total > 0) {
349 |                 cohortRates[diff] = Math.round(
350 |                     (counts.completed / counts.total) * 100
351 |                 );
352 |             }
353 |         }
354 |     } else if (cohortErr) {
355 |         console.error("Failed to fetch cohort goal data:", cohortErr.message);
356 |         // Non-fatal – use default rates
357 |     }
358 | }
359 |
360 | // % % 3.3.5 Generate 3 goal suggestions % % % % % % % % % % % % % % % % % % % % % %
361 | // Easy "e80%, Moderate 50-79%, Ambitious <50% cohort completion
362 |
363 | const suggestions: GoalSuggestion[] = [];
364 |
365 | // Pick a primary course (first enrolled or one with nearest deadline)
366 | const primaryCourse =
367 |     deadlines.length > 0
368 |     ? {
369 |         course_id: deadlines[0].course_id,
370 |         course_name: deadlines[0].course_name,
371 |     }
372 |     : enrolledCourses[0] ?? {
373 |         course_id: null,
374 |         course_name: "your courses",
375 |     };
376 |
377 | // Find a secondary course for variety
378 | const secondaryCourse =
379 |     enrolledCourses.length > 1
380 |     ? enrolledCourses.find(
381 |         (c: { course_id: string }) =>
382 |             c.course_id !== primaryCourse.course_id
383 |     ) ?? primaryCourse
384 |     : primaryCourse;
385 |
386 | // Find lowest attainment CLO for ambitious goal
387 | const lowestAttainment =
388 |     attainmentData.length > 0
389 |     ? attainmentData.reduce((min, curr) =>
390 |         curr.avg_attainment < min.avg_attainment ? curr : min
391 |     )
392 |     : null;
393 |
394 | const nearestDeadline = deadlines[0] ?? null;
395 |

```

```

396 // % % 3.3.6 Format each goal using SMART structure % % % % % % % % % % % % % % % %
397
398 // Goal 1: Easy – routine task with high cohort completion
399 const easyRate = cohortRates.easy ?? 85;
400 const easySpecific = nearestDeadline
401   ? `Complete all readings and preparation for ${nearestDeadline.assignment_title} in ${nearestDeadline.co
402     : `Review all course materials for ${primaryCourse.course_name} this week`;
403 const easyFields = {
404   specific: easySpecific,
405   measurable: "All assigned readings marked as complete",
406   achievable: `Based on your current progress and ${easyRate}% of similar students completing this goal`,
407   relevant: primaryCourse.course_name,
408   timebound: week_end,
409 };
410
411 suggestions.push({
412   goal_text: composeGoalText(easyFields),
413   smart_specific: easyFields.specific,
414   smart_measurable: easyFields.measurable,
415   smart_achievable: easyFields.achievable,
416   smart_relevant: easyFields.relevant,
417   smart_timebound: easyFields.timebound,
418   difficulty: classifyDifficulty(easyRate),
419   cohort_completion_rate: easyRate,
420 });
421
422 // Goal 2: Moderate – practice/review with moderate cohort completion
423 const moderateRate = cohortRates.moderate ?? 65;
424 const moderateSpecific = nearestDeadline
425   ? `Score at least 70% on ${nearestDeadline.assignment_title} in ${nearestDeadline.course_name}`
426   : `Complete 3 practice exercises for ${secondaryCourse.course_name}`;
427 const moderateFields = {
428   specific: moderateSpecific,
429   measurable: "Assignment score of 70% or higher",
430   achievable: `Your self-efficacy score of ${selfEfficacyScore} suggests this is within reach with consist
431   relevant: nearestDeadline?.course_name ?? secondaryCourse.course_name,
432   timebound: nearestDeadline?.due_date ?? week_end,
433 };
434
435 suggestions.push({
436   goal_text: composeGoalText(moderateFields),
437   smart_specific: moderateFields.specific,
438   smart_measurable: moderateFields.measurable,
439   smart_achievable: moderateFields.achievable,
440   smart_relevant: moderateFields.relevant,
441   smart_timebound: moderateFields.timebound,
442   difficulty: classifyDifficulty(moderateRate),
443   cohort_completion_rate: moderateRate,
444 });
445
446 // Goal 3: Ambitious – stretch goal with low cohort completion
447 const ambitiousRate = cohortRates.ambitious ?? 35;
448 const ambitiousSpecific = lowestAttainment
449   ? `Achieve 85% attainment on ${
450     lowestAttainment.clo_title ?? "the lowest-scoring learning outcome"
451   } in ${lowestAttainment.course_name}`
452   : `Master all key concepts in ${primaryCourse.course_name} and achieve top-tier performance`;
453 const ambitiousFields = {
454   specific: ambitiousSpecific,
455   measurable: lowestAttainment
456     ? `Attainment score of 85% or higher (currently ${Math.round(
457       lowestAttainment.avg_attainment
458     )}%)`
459     : `Score in the top 15% of the class on this week's assessments",
460   achievable: `This is a stretch goal – only ${ambitiousRate}% of similar students achieve this, but your
461   relevant: lowestAttainment?.course_name ?? primaryCourse.course_name,
462   timebound: week_end,
463 };
464
465 suggestions.push({
466   goal_text: composeGoalText(ambitiousFields),
467   smart_specific: ambitiousFields.specific,
468   smart_measurable: ambitiousFields.measurable,
469   smart_achievable: ambitiousFields.achievable,
470   smart_relevant: ambitiousFields.relevant,
471   smart_timebound: ambitiousFields.timebound,
472   difficulty: classifyDifficulty(ambitiousRate),
473   cohort_completion_rate: ambitiousRate,
474 });
475
476 // % % 3.3.7 INSERT suggestions into goal_suggestions table % % % % % % % % % %
477
478 const rows = suggestions.map((s) => ({
479   student_id,
480   week_start,
481   goal_text: s.goal_text,
482   smart_specific: s.smart_specific,
483   smart_measurable: s.smart_measurable,
484   smart_achievable: s.smart_achievable,
485   smart_relevant: s.smart_relevant,
486   smart_timebound: s.smart_timebound,
487   difficulty: s.difficulty,
488   cohort_completion_rate: s.cohort_completion_rate,
489   status: "suggested",
490 }));
491
492 const { error: insertErr } = await supabase
493   .from("goal_suggestions")
494   .insert(rows);
495
496 if (insertErr) {
497   console.error("Failed to insert goal suggestions:", insertErr.message);
498   return new Response(
499     JSON.stringify({

```

```

500 |         error: "Failed to save goal suggestions",
501 |         detail: insertErr.message,
502 |     }},
503 |     {
504 |       status: 500,
505 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
506 |     }
507 |   );
508 | }
509 |
510 |   return new Response(JSON.stringify({ success: true, suggestions }), {
511 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
512 |   });
513 | } catch (error) {
514 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
515 |     status: 500,
516 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
517 |   });
518 | }
519 | });
520 |

```

FILE: supabase/functions/team-streak-risk-cron/index.ts

TYPE: .ts | LINES: 1-111 | SHA256: eac48bc964e18cee43018bb53c1099efc8d3a820d90ad173680477a09cbe8a6b

```

1 | // Task 132.5: Team streak risk cron - notifies team members when streak is at risk
2 |
3 | import { serve } from "https://deno.land/std@0.168.0/http/server.ts";
4 | import { createClient } from "https://esm.sh/@supabase/supabase-js@2";
5 |
6 | const corsHeaders = {
7 |   "Access-Control-Allow-Origin": "*",
8 |   "Access-Control-Allow-Headers":
9 |     "authorization, x-client-info, apikey, content-type",
10 | };
11 |
12 | serve(async (req) => {
13 |   if (req.method === "OPTIONS")
14 |     return new Response("ok", { headers: corsHeaders });
15 |
16 |   try {
17 |     const supabase = createClient(
18 |       Deno.env.get("SUPABASE_URL")!,
19 |       Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
20 |     );
21 |
22 |     const today = new Date().toISOString().slice(0, 10);
23 |
24 |     // Fetch all teams with active streaks
25 |     const { data: activeTeams, error: teamsErr } = await supabase
26 |       .from("team_gamification")
27 |       .select("team_id, streak_current")
28 |       .gt("streak_current", 0);
29 |
30 |     if (teamsErr) throw teamsErr;
31 |     if (!activeTeams || activeTeams.length === 0) {
32 |       return new Response(JSON.stringify({ success: true, teams_checked: 0 }), {
33 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
34 |       });
35 |     }
36 |
37 |     let notificationsSent = 0;
38 |
39 |     for (const team of activeTeams) {
40 |       // Get team members
41 |       const { data: members } = await supabase
42 |         .from("team_members")
43 |         .select("student_id")
44 |         .eq("team_id", team.team_id);
45 |
46 |       if (!members || members.length === 0) continue;
47 |
48 |       const memberIds = members.map(
49 |         (m: { student_id: string }) => m.student_id
50 |       );
51 |
52 |       // Check which members have NOT logged in today
53 |       const { data: todayLogins } = await supabase
54 |         .from("student_activity_log")
55 |         .select("student_id")
56 |         .in("student_id", memberIds)
57 |         .eq("event_type", "login")
58 |         .gte("created_at", `${today}T00:00:00Z`);
59 |
60 |       const loggedInIds = new Set(
61 |         (todayLogins ?? []).map((l: { student_id: string }) => l.student_id)
62 |       );
63 |
64 |       const missingMembers = memberIds.filter(
65 |         (id: string) => !loggedInIds.has(id)
66 |       );
67 |
68 |       if (missingMembers.length === 0) continue;
69 |
70 |       // Get names of missing members
71 |       const { data: profiles } = await supabase
72 |         .from("profiles")
73 |         .select("id, full_name")
74 |         .in("id", missingMembers);
75 |
76 |       const missingNames = (profiles ?? []).
77 |         .map((p: { full_name: string }) => p.full_name || "A teammate")
78 |         .join(", ");
79 |

```


69 | "was",
70 | "are",
71 | "be",
72 | "been",
73 | "being",
74 | "have",
75 | "has",
76 | "had",
77 | "do",
78 | "does",
79 | "did",
80 | "will",
81 | "would",
82 | "could",
83 | "should",
84 | "may",
85 | "might",
86 | "shall",
87 | "can",
88 | "not",
89 | "no",
90 | "nor",
91 | "so",
92 | "if",
93 | "then",
94 | "than",
95 | "too",
96 | "very",
97 | "just",
98 | "about",
99 | "above",
100 | "after",
101 | "again",
102 | "all",
103 | "also",
104 | "am",
105 | "any",
106 | "as",
107 | "because",
108 | "before",
109 | "below",
110 | "between",
111 | "both",
112 | "during",
113 | "each",
114 | "few",
115 | "further",
116 | "get",
117 | "got",
118 | "he",
119 | "her",
120 | "here",
121 | "hers",
122 | "herself",
123 | "him",
124 | "himself",
125 | "his",
126 | "how",
127 | "i",
128 | "im",
129 | "into",
130 | "me",
131 | "more",
132 | "most",
133 | "my",
134 | "myself",
135 | "now",
136 | "only",
137 | "other",
138 | "our",
139 | "ours",
140 | "ourselves",
141 | "out",
142 | "over",
143 | "own",
144 | "same",
145 | "she",
146 | "some",
147 | "such",
148 | "them",
149 | "themselves",
150 | "there",
151 | "these",
152 | "they",
153 | "those",
154 | "through",
155 | "under",
156 | "until",
157 | "up",
158 | "us",
159 | "we",
160 | "what",
161 | "when",
162 | "where",
163 | "which",
164 | "while",
165 | "who",
166 | "whom",
167 | "why",
168 | "you",
169 | "your",
170 | "yours",
171 | "yourself",
172 | "yourselves",

[illegible]

[illegible]

```

381   });
382 }
383
384 if (!course) {
385   return new Response(
386     JSON.stringify({
387       error: "Course not found",
388       course_id: body.course_id,
389     }),
390     {
391       status: 404,
392       headers: { ...corsHeaders, "Content-Type": "application/json" },
393     }
394   );
395 }
396
397 // Check teacher owns the course OR user is an admin
398 const { data: profile } = await supabase
399   .from("profiles")
400   .select("role")
401   .eq("id", teacherId)
402   .maybeSingle();
403
404 const isAdmin = profile?.role === "admin";
405 const isTeacher = course.teacher_id === teacherId;
406
407 if (!isTeacher && !isAdmin) {
408   return new Response(
409     JSON.stringify({
410       error: "Forbidden: you do not have access to this course",
411     }),
412     {
413       status: 403,
414       headers: { ...corsHeaders, "Content-Type": "application/json" },
415     }
416   );
417 }
418
419 // %% Step 4: Determine Date Range %%%%%%%%%%%%%%%
420
421 const now = new Date();
422 const thirtyDaysAgo = new Date(now);
423 thirtyDaysAgo.setDate(thirtyDaysAgo.getDate() - 30);
424
425 const startDate = body.date_range?.start
426   ? new Date(body.date_range.start).toISOString()
427   : thirtyDaysAgo.toISOString();
428 const endDate = body.date_range?.end
429   ? new Date(body.date_range.end).toISOString()
430   : now.toISOString();
431
432 // %% Step 5: Aggregate Metrics (3.3.1) %%%%%%%%%%%%%%%
433 // Fetch all conversations for the course in the date range in one query
434 // Include id, message_count, clo_scope, and created_at to avoid N+1
435
436 const { data: conversations, error: convError } = await supabase
437   .from("tutor_conversations")
438   .select("id, message_count, clo_scope, created_at")
439   .eq("course_id", body.course_id)
440   .gte("created_at", startDate)
441   .lte("created_at", endDate);
442
443 if (convError) {
444   throw new Error(`Failed to fetch conversations: ${convError.message}`);
445 }
446
447 const totalConversations = conversations?.length ?? 0;
448 const totalMessages =
449   conversations?.reduce((sum, c) => sum + (c.message_count ?? 0), 0) ?? 0;
450 const avgMessagesPerConversation =
451   totalConversations > 0
452     ? Math.round((totalMessages / totalConversations) * 100) / 100
453     : 0;
454
455 // Fetch satisfaction ratings from messages in these conversations
456 const conversationIds = conversations?.map((c) => c.id) ?? [];
457
458 let avgSatisfactionRating = 0;
459 if (conversationIds.length > 0) {
460   const { data: ratedMessages, error: ratingError } = await supabase
461     .from("tutor_messages")
462     .select("satisfaction_rating")
463     .in("conversation_id", conversationIds)
464     .not("satisfaction_rating", "is", null);
465
466   if (ratingError) {
467     throw new Error(
468       `Failed to fetch satisfaction ratings: ${ratingError.message}`
469     );
470   }
471
472   if (ratedMessages && ratedMessages.length > 0) {
473     const positiveCount = ratedMessages.filter(
474       (m) => m.satisfaction_rating === "thumbs_up"
475     ).length;
476     avgSatisfactionRating =
477       Math.round((positiveCount / ratedMessages.length) * 100) / 100;
478   }
479 }
480
481 // %% Step 6: Top Questioned CLOs (3.3.2) %%%%%%%%%%%%%%%
482 // Count conversations per CLO from clo_scope array
483
484 const cloFrequency = new Map<string, number>();

```

```

485 | for (const conv of conversations ?? []) {
486 |   const cloScope: string[] = conv.clo_scope ?? [];
487 |   for (const cloId of cloScope) {
488 |     cloFrequency.set(cloId, (cloFrequency.get(cloId) ?? 0) + 1);
489 |   }
490 | }
491 |
492 | // Fetch CLO titles for the top CLOs
493 | const topCloEntries = Array.from(cloFrequency.entries())
494 |   .sort((a, b) => b[1] - a[1])
495 |   .slice(0, 10);
496 |
497 | const topCloIds = topCloEntries.map(([id]) => id);
498 | let cloTitleMap = new Map<string, string>();
499 |
500 | if (topCloIds.length > 0) {
501 |   const { data: clos } = await supabase
502 |     .from("learning_outcomes")
503 |     .select("id, title")
504 |     .in("id", topCloIds);
505 |
506 |   if (clos) {
507 |     cloTitleMap = new Map(clos.map((c) => [c.id, c.title]));
508 |   }
509 | }
510 |
511 | const topQuestionedClos: TopQuestionedCLO[] = topCloEntries.map(
512 |   ([cloId, count]) => ({
513 |     clo_id: cloId,
514 |     clo_title: cloTitleMap.get(cloId) ?? "Unknown CLO",
515 |     conversation_count: count,
516 |   })
517 | );
518 |
519 | // %% Step 7: Common Topics Extraction (3.3.3) %% %% %% %% %% %% %% %% %% %% %%
520 | // Extract anonymized topics from student messages (role = 'user' only)
521 | // No student identifiers, names, or conversation content is returned
522 |
523 | let commonTopics: CommonTopic[] = [];
524 | if (conversationIds.length > 0) {
525 |   const { data: userMessages, error: msgError } = await supabase
526 |     .from("tutor_messages")
527 |     .select("content")
528 |     .in("conversation_id", conversationIds)
529 |     .eq("role", "user");
530 |
531 |   if (msgError) {
532 |     throw new Error(
533 |       `Failed to fetch messages for topic extraction: ${msgError.message}`
534 |     );
535 |   }
536 |
537 |   commonTopics = extractCommonTopics(userMessages ?? []);
538 | }
539 |
540 | // %% Step 8: Usage Over Time (3.3.4) %% %% %% %% %% %% %% %% %% %% %% %% %%
541 | // Daily conversation counts for the date range
542 |
543 | const usageOverTime: DailyUsage[] = [];
544 | const usageStart = body.date_range?.start
545 |   ? new Date(body.date_range.start)
546 |   : new Date(thirtyDaysAgo);
547 | const usageEnd = body.date_range?.end ? new Date(body.date_range.end) : now;
548 |
549 | // Build a map of date -> count from conversations (already fetched)
550 | const dailyCounts = new Map<string, number>();
551 | for (const conv of conversations ?? []) {
552 |   if (conv.created_at) {
553 |     const dateKey = conv.created_at.split("T")[0];
554 |     dailyCounts.set(dateKey, (dailyCounts.get(dateKey) ?? 0) + 1);
555 |   }
556 | }
557 |
558 | // Fill in all dates in the range (including zero-count days)
559 | const currentDate = new Date(usageStart);
560 | while (currentDate <= usageEnd) {
561 |   const dateKey = currentDate.toISOString().split("T")[0];
562 |   usageOverTime.push({
563 |     date: dateKey,
564 |     conversation_count: dailyCounts.get(dateKey) ?? 0,
565 |   });
566 |   currentDate.setDate(currentDate.getDate() + 1);
567 | }
568 |
569 | // %% Step 9: PII Exclusion Validation (3.3.5) %% %% %% %% %% %% %% %% %% %% %%
570 | // Final check: ensure no PII leaked into the response
571 |
572 | const response: AnalyticsResponse = {
573 |   total_conversations: totalConversations,
574 |   total_messages: totalMessages,
575 |   avg_messages_per_conversation: avgMessagesPerConversation,
576 |   avg_satisfaction_rating: avgSatisfactionRating,
577 |   top_questioned_clos: topQuestionedClos,
578 |   common_topics: commonTopics,
579 |   usage_over_time: usageOverTime,
580 | };
581 |
582 | // Validate no PII leaked into the response
583 | if (!validateNoPII(response)) {
584 |   console.error("PII detected in analytics response - scrubbing");
585 |   // Return safe fallback with empty topics
586 |   response.common_topics = [];
587 | }
588 |

```

```

589 |     return new Response(JSON.stringify(response), {
590 |       headers: { ...corsHeaders, "Content-Type": "application/json" },
591 |     });
592 |   } catch (error) {
593 |     console.error("tutor-analytics error:", error);
594 |     return new Response(
595 |       JSON.stringify({
596 |         error: error instanceof Error ? error.message : "Internal server error",
597 |       }),
598 |       {
599 |         status: 500,
600 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
601 |       }
602 |     );
603 |   }
604 | });
605 |

```

FILE: [supabase/functions/update-challenge-progress/index.ts](#)

```
TYPE: .ts | LINES: 1-834 | SHA256: 557e53ad69cb7c8194dbd01aa9a07f45d3412c07b64baf21c819f96b128c6237
```

[illegible]

[illegible]


```

188 |     return submissions?.length ?? 0;
189 | }
190 |
191 | return data?.length ?? 0;
192 | }
193 |
194 | /**
195 |  * Habit: Current consecutive streak days maintained during the challenge period.
196 |  * We look at habit_logs for the student during the challenge window and count
197 |  * the current consecutive streak of days with at least one log entry.
198 |  */
199 | // deno-lint-ignore no-explicit-any
200 | async function computeHabitProgress(
201 |   supabase: any,
202 |   studentId: string,
203 |   _courseId: string,
204 |   startDate: string,
205 |   endDate: string
206 | ): Promise<number> {
207 |   // Get all distinct dates with habit logs during the challenge period
208 |   const { data: logs, error } = await supabase
209 |     .from("habit_logs")
210 |     .select("log_date")
211 |     .eq("student_id", studentId)
212 |     .gte("log_date", startDate.slice(0, 10))
213 |     .lte("log_date", endDate.slice(0, 10))
214 |     .order("log_date", { ascending: false });
215 |
216 |   if (error) {
217 |     console.error("Habit progress query failed:", error.message);
218 |     return 0;
219 |   }
220 |
221 |   if (!logs || logs.length === 0) return 0;
222 |
223 |   // Get unique dates
224 |   const uniqueDates = [
225 |     ...new Set(logs.map((l: { log_date: string }) => l.log_date)),
226 |   ].sort((a, b) => (b as string).localeCompare(a as string));
227 |
228 |   // Count consecutive days from the most recent date backwards
229 |   let streak = 1;
230 |   for (let i = 1; i < uniqueDates.length; i++) {
231 |     const current = new Date(uniqueDates[i] as string);
232 |     const previous = new Date(uniqueDates[i - 1] as string);
233 |     const diffDays = Math.round(
234 |       (previous.getTime() - current.getTime()) / (1000 * 60 * 60 * 24)
235 |     );
236 |     if (diffDays === 1) {
237 |       streak++;
238 |     } else {
239 |       break;
240 |     }
241 |   }
242 |
243 |   return streak;
244 | }
245 |
246 | /**
247 |  * XP Race: Total XP earned within the course during the challenge period.
248 |  */
249 | // deno-lint-ignore no-explicit-any
250 | async function computeXpRaceProgress(
251 |   supabase: any,
252 |   studentId: string,
253 |   courseId: string,
254 |   startDate: string,
255 |   endDate: string
256 | ): Promise<number> {
257 |   const { data: transactions, error } = await supabase
258 |     .from("xp_transactions")
259 |     .select("xp_amount")
260 |     .eq("student_id", studentId)
261 |     .eq("course_id", courseId)
262 |     .gte("created_at", startDate)
263 |     .lte("created_at", endDate);
264 |
265 |   if (error) {
266 |     console.error("XP Race progress query failed:", error.message);
267 |     return 0;
268 |   }
269 |
270 |   return (transactions ?? []).reduce(
271 |     (sum: number, t: { xp_amount: number }) => sum + (t.xp_amount ?? 0),
272 |     0
273 |   );
274 | }
275 |
276 | /**
277 |  * Bloom's Climb: COUNT of distinct Bloom's levels achieved via graded assignments.
278 |  * Each CLO has exactly one Bloom's level. We count distinct levels from graded
279 |  * submissions during the challenge period.
280 |  */
281 | // deno-lint-ignore no-explicit-any
282 | async function computeBloomsClimbProgress(
283 |   supabase: any,
284 |   studentId: string,
285 |   courseId: string,
286 |   startDate: string,
287 |   endDate: string
288 | ): Promise<number> {
289 |   // Get graded submissions for the student in this course during the challenge period
290 |   const { data: submissions, error } = await supabase
291 |     .from("submissions")

```

[illegible]

[illegible]

```

500     status: 400,
501     headers: { ...corsHeaders, "Content-Type": "application/json" },
502   });
503 }
504
505 const { event_type, student_id, course_id } = validation.data;
506
507 // Determine which challenge types this event can affect
508 const matchingTypes = getMatchingChallengeTypes(event_type);
509
510 if (matchingTypes.length === 0) {
511   return new Response(
512     JSON.stringify({
513       success: true,
514       message: "No matching challenge types for this event",
515       challenges_updated: 0,
516     }),
517     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
518   );
519 }
520
521 // Query active challenges for this course matching the event type
522 const now = new Date().toISOString();
523 const { data: challenges, error: chalErr } = await supabase
524   .from("social_challenges")
525   .select(
526     "id, challenge_type, participation_mode, goal_target, start_date, end_date, reward_xp, reward_badge_id"
527   )
528   .eq("course_id", course_id)
529   .eq("status", "active")
530   .lte("start_date", now)
531   .gte("end_date", now)
532   .in("challenge_type", matchingTypes);
533
534 if (chalErr) {
535   console.error("Active challenges query failed:", chalErr.message);
536   return new Response(
537     JSON.stringify({
538       error: "Failed to query active challenges",
539       detail: chalErr.message,
540     }),
541     {
542       status: 500,
543       headers: { ...corsHeaders, "Content-Type": "application/json" },
544     }
545   );
546 }
547
548 if (!challenges || challenges.length === 0) {
549   return new Response(
550     JSON.stringify({
551       success: true,
552       message: "No active challenges found for this course and event type",
553       challenges_updated: 0,
554     }),
555     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
556   );
557 }
558
559 let challengesUpdated = 0;
560 let completionsTriggered = 0;
561
562 // Process each matching challenge
563 for (const challenge of challenges as ActiveChallenge[]) {
564   try {
565     // Determine the participant ID and type
566     let participantId = student_id;
567     let participantType: "team" | "individual" =
568       challenge.participation_mode === "team" ? "team" : "individual";
569
570     if (challenge.participation_mode === "team") {
571       // Find the student's active team in this course
572       const { data: membership } = await supabase
573         .from("team_members")
574         .select("team_id, teams!inner(id, course_id)")
575         .eq("student_id", student_id)
576         .eq("teams.course_id", course_id)
577         .is("left_at", null)
578         .limit(1)
579         .maybeSingle();
580
581       if (!membership) {
582         // Student is not on a team in this course – skip this challenge
583         continue;
584       }
585
586       participantId = membership.team_id;
587       participantType = "team";
588     }
589
590     // Get or create the challenge_progress record
591     let { data: progressRecord, error: progressErr } = await supabase
592       .from("challenge_progress")
593       .select("id")
594       .eq("challenge_id", challenge.id)
595       .eq("participant_id", participantId)
596       .maybeSingle();
597
598     if (progressErr) {
599       console.error(
600         `Progress record query failed for challenge ${challenge.id}:`,
601         progressErr.message
602       );
603       continue;

```

```

604 |     }
605 |
606 |     // If no progress record exists, create one (auto-enrollment)
607 |     if (!progressRecord) {
608 |       const { data: newRecord, error: insertErr } = await supabase
609 |         .from("challenge_progress")
610 |         .insert({
611 |           challenge_id: challenge.id,
612 |           participant_type: participantType,
613 |           participant_id: participantId,
614 |           current_progress: 0,
615 |           reward_granted: false,
616 |         })
617 |         .select()
618 |         .single();
619 |
620 |     if (insertErr) {
621 |       // Handle unique constraint violation (concurrent insert)
622 |       if (insertErr.code === "23505") {
623 |         const { data: existingRecord } = await supabase
624 |           .from("challenge_progress")
625 |           .select("*")
626 |           .eq("challenge_id", challenge.id)
627 |           .eq("participant_id", participantId)
628 |           .maybeSingle();
629 |         progressRecord = existingRecord;
630 |       } else {
631 |         console.error(
632 |           `Progress record insert failed for challenge ${challenge.id}:`,
633 |           insertErr.message
634 |         );
635 |         continue;
636 |       }
637 |     } else {
638 |       progressRecord = newRecord;
639 |     }
640 |   }
641 |
642 |   if (!progressRecord) continue;
643 |
644 |   // Skip if already completed and rewarded
645 |   if (progressRecord.completed_at && progressRecord.reward_granted) {
646 |     continue;
647 |   }
648 |
649 |   // % % Compute current progress (idempotent – recomputed from source data) % %
650 |   let computedProgress = 0;
651 |
652 |   if (challenge.challenge_type === "cooperative") {
653 |     // Cooperative: collective team progress
654 |     if (participantType === "team") {
655 |       computedProgress = await computeCooperativeProgress(
656 |         supabase,
657 |         participantId,
658 |         course_id,
659 |         challenge.start_date,
660 |         challenge.end_date
661 |       );
662 |     }
663 |   } else {
664 |     // For non-cooperative challenges, compute based on challenge type
665 |     switch (challenge.challenge_type) {
666 |       case "academic":
667 |         computedProgress = await computeAcademicProgress(
668 |           supabase,
669 |           participantType === "team" ? student_id : participantId,
670 |           course_id,
671 |           challenge.start_date,
672 |           challenge.end_date
673 |         );
674 |         break;
675 |
676 |       case "habit":
677 |         computedProgress = await computeHabitProgress(
678 |           supabase,
679 |           participantType === "team" ? student_id : participantId,
680 |           course_id,
681 |           challenge.start_date,
682 |           challenge.end_date
683 |         );
684 |         break;
685 |
686 |       case "xp_race":
687 |         computedProgress = await computeXpRaceProgress(
688 |           supabase,
689 |           participantType === "team" ? student_id : participantId,
690 |           course_id,
691 |           challenge.start_date,
692 |           challenge.end_date
693 |         );
694 |         break;
695 |
696 |       case "blooms_climb":
697 |         computedProgress = await computeBloomsClimbProgress(
698 |           supabase,
699 |           participantType === "team" ? student_id : participantId,
700 |           course_id,
701 |           challenge.start_date,
702 |           challenge.end_date
703 |         );
704 |         break;
705 |     }
706 |   }
707 |
708 |   // For team challenges with non-cooperative types, if participation_mode

```

```
708 // is "team", we need to aggregate across all team members
709 if (
710   participantType === "team" &&
711   challenge.challenge_type !== "cooperative"
712 ) {
713   // Get all active team members
714   const { data: members } = await supabase
715     .from("team_members")
716     .select("student_id")
717     .eq("team_id", participantId)
718     .is("left_at", null);
719
720   if (members && members.length > 0) {
721     let teamTotal = 0;
722     for (const member of members) {
723       let memberProgress = 0;
724       switch (challenge.challenge_type) {
725         case "academic":
726           memberProgress = await computeAcademicProgress(
727             supabase,
728             member.student_id,
729             course_id,
730             challenge.start_date,
731             challenge.end_date
732           );
733           break;
734         case "habit":
735           memberProgress = await computeHabitProgress(
736             supabase,
737             member.student_id,
738             course_id,
739             challenge.start_date,
740             challenge.end_date
741           );
742           break;
743         case "xp_race":
744           memberProgress = await computeXpRaceProgress(
745             supabase,
746             member.student_id,
747             course_id,
748             challenge.start_date,
749             challenge.end_date
750           );
751           break;
752         case "blooms_climb":
753           memberProgress = await computeBloomsClimbProgress(
754             supabase,
755             member.student_id,
756             course_id,
757             challenge.start_date,
758             challenge.end_date
759           );
760           break;
761       }
762       teamTotal += memberProgress;
763     }
764     computedProgress = teamTotal;
765   }
766 }
767
768 // %% Update progress record %%%%%%%%%%%
769 const updatePayload: Record<string, unknown> = {
770   current_progress: computedProgress,
771   updated_at: new Date().toISOString(),
772 };
773
774 // %% Completion detection %%%%%%%%%%%
775 // If progress >= goal_target and not yet completed
776 const isNowComplete =
777   computedProgress >= challenge.goal_target &&
778   !progressRecord.completed_at;
779
780 if (isNowComplete) {
781   updatePayload.completed_at = new Date().toISOString();
782 }
783
784 const { error: updateErr } = await supabase
785   .from("challenge_progress")
786   .update(updatePayload)
787   .eq("id", progressRecord.id);
788
789 if (updateErr) {
790   console.error(
791     `Progress update failed for challenge ${challenge.id}:`,
792     updateErr.message
793   );
794   continue;
795 }
796
797 challengesUpdated++;
798
799 // %% Trigger reward distribution on completion %%%%%%%%%%
800 if (isNowComplete && !progressRecord.reward_granted) {
801   await distributeReward(supabase, challenge, {
802     ...progressRecord,
803     current_progress: computedProgress,
804     completed_at: updatePayload.completed_at as string,
805   });
806   completionsTriggered++;
807 }
808 } catch (challengeErr) {
809   console.error(
810     `Error processing challenge ${challenge.id}:`,
811
```

```

812 |         challengeErr
813 |     );
814 |     // Continue processing other challenges
815 | }
816 | }
817 |
818 | return new Response(
819 |     JSON.stringify({
820 |         success: true,
821 |         challenges_updated: challengesUpdated,
822 |         completions_triggered: completionsTriggered,
823 |     }),
824 |     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
825 | );
826 | } catch (error) {
827 |     console.error("update-challenge-progress error:", error);
828 |     return new Response(JSON.stringify({ error: (error as Error).message }), {
829 |         status: 500,
830 |         headers: { ...corsHeaders, "Content-Type": "application/json" },
831 |     });
832 | }
833 | });
834 |

```

FILE: supabase/functions/update-question-analytics/index.ts

```
TYPE: .ts | LINES: 1-513 | SHA256: a96b9b157b1d69abc54d49c689e59ed12acf3ff664adfadccf98ce2f5f0383fc
```

[illegible]

[illegible]

[illegible]

```

286 }
287 }
288
289 const supabase = createClient(
290   Deno.env.get("SUPABASE_URL")!,
291   Deno.env.get("SUPABASE_SERVICE_ROLE_KEY")!
292 );
293
294 // %% Step 1: Validate Request Payload %%%%%%%%%%%
295
296 const body = await req.json();
297 const validation = validatePayload(body);
298
299 if (!validation.valid) {
300   return new Response(JSON.stringify({ error: validation.error }), {
301     status: 400,
302     headers: { ...corsHeaders, "Content-Type": "application/json" },
303   });
304 }
305
306 const { quiz_attempt_id } = validation.data;
307
308 // %% Step 2: Fetch the quiz attempt record %%%%%%%%%%
309
310 const { data: attempt, error: attemptError } = await supabase
311   .from("quiz_attempts")
312   .select(
313     "id, quiz_id, student_id, answers, question_sequence, per_question_times"
314   )
315   .eq("id", quiz_attempt_id)
316   .maybeSingle();
317
318 if (attemptError || !attempt) {
319   return new Response(JSON.stringify({ error: "Quiz attempt not found" }), {
320     status: 404,
321     headers: { ...corsHeaders, "Content-Type": "application/json" },
322   });
323 }
324
325 const questionSequence = (attempt.question_sequence ??
326   []) as QuestionSequenceEntry[];
327 const answersMap = parseAnswers(attempt.answers);
328 const timesMap = parsePerQuestionTimes(attempt.per_question_times);
329
330 if (questionSequence.length === 0) {
331   return new Response(
332     JSON.stringify({
333       success: true,
334       updated: 0,
335       message: "No questions in sequence",
336     }),
337     { headers: { ...corsHeaders, "Content-Type": "application/json" } }
338   );
339 }
340
341 // %% Step 3: Get question_ids from the sequence %%%%%%%%%%
342
343 const questionIds = questionSequence.map((q) => q.question_id);
344
345 // Fetch question_bank rows for original difficulty ratings
346 const { data: questionBankRows } = await supabase
347   .from("question_bank")
348   .select("id, difficulty_rating, clo_id")
349   .in("id", questionIds);
350
351 const questionBankMap = new Map<string, QuestionBankRow>();
352 for (const row of (questionBankRows ?? []) as QuestionBankRow[]) {
353   questionBankMap.set(row.id, row);
354 }
355
356 // Fetch existing analytics rows for these questions
357 const { data: existingAnalytics } = await supabase
358   .from("question_analytics")
359   .select("*")
360   .in("question_id", questionIds);
361
362 const analyticsMap = new Map<string, AnalyticsRow>();
363 for (const row of (existingAnalytics ?? []) as AnalyticsRow[]) {
364   analyticsMap.set(row.question_id, row);
365 }
366
367 // %% Step 4: Process each question answered %%%%%%%%%%
368
369 const updatedSummary: {
370   question_id: string;
371   total_attempts: number;
372   success_rate: number;
373   calibrated_difficulty: number | null;
374   discrimination_index: number | null;
375   quality_flag: string | null;
376 }[] = [];
377
378 for (const seqEntry of questionSequence) {
379   const questionId = seqEntry.question_id;
380   const isCorrect = answersMap.get(questionId);
381   const responseTimeMs = timesMap.get(questionId);
382
383   // Skip questions without answer data
384   if (isCorrect === undefined) continue;
385
386   const existing = analyticsMap.get(questionId);
387   const qbRow = questionBankMap.get(questionId);
388
389   // %% 4a: Compute new totals %%%%%%%%%%

```

[illegible]


```

81 |     });
82 | }
83 |
84 | let sent = 0;
85 | const errors: Array<{ student_id: string; error: string }> = [];
86 | const dashboardUrl = `${
87 |   Deno.env.get("SUPABASE_URL")?.replace(".supabase.co", ".vercel.app") ??
88 |   "https://edevise.vercel.app"
89 | }/student/dashboard`;
90 |
91 | for (const student of students) {
92 |   try {
93 |     // Aggregate XP earned this week
94 |     const { data: xpRows } = await supabase
95 |       .from("xp_transactions")
96 |       .select("xp_amount")
97 |       .eq("student_id", student.id)
98 |       .gte("created_at", weekAgoISO);
99 |
100 |     const xpEarned = (xpRows ?? []).reduce(
101 |       (sum: number, row: { xp_amount: number }) => sum + row.xp_amount,
102 |       0
103 |     );
104 |
105 |     // Count badges earned this week
106 |     const { count: badgesEarned } = await supabase
107 |       .from("student_badges")
108 |       .select("id", { count: "exact", head: true })
109 |       .eq("student_id", student.id)
110 |       .gte("awarded_at", weekAgoISO);
111 |
112 |     // Get current streak
113 |     const { data: gamification } = await supabase
114 |       .from("student_gamification")
115 |       // live column is `streak_current` (not `streak_count`)
116 |       .select("streak_current")
117 |       .eq("student_id", student.id)
118 |       .maybeSingle();
119 |
120 |     // Count submissions this week
121 |     const { count: submissionsCount } = await supabase
122 |       .from("submissions")
123 |       .select("id", { count: "exact", head: true })
124 |       .eq("student_id", student.id)
125 |       .gte("created_at", weekAgoISO);
126 |
127 |     await supabase.functions.invoke("send-email-notification", {
128 |       body: {
129 |         to: student.email,
130 |         template: "weekly_summary",
131 |         data: {
132 |           student_name: student.full_name,
133 |           xp_earned: xpEarned,
134 |           badges_earned: badgesEarned ?? 0,
135 |           streak_count: gamification?.streak_current ?? 0,
136 |           submissions_count: submissionsCount ?? 0,
137 |           dashboard_url: dashboardUrl,
138 |         },
139 |       },
140 |     });
141 |     sent++;
142 |   } catch (err) {
143 |     errors.push({ student_id: student.id, error: (err as Error).message });
144 |   }
145 | }
146 |
147 | return new Response(
148 |   JSON.stringify({
149 |     success: true,
150 |     sent,
151 |     total_students: students.length,
152 |     errors,
153 |   }),
154 |   { headers: { ...corsHeaders, "Content-Type": "application/json" } }
155 | );
156 | } catch (error) {
157 |   console.error("weekly-summary-cron error:", (error as Error).message);
158 |   return new Response(JSON.stringify({ error: (error as Error).message }), {
159 |     status: 500,
160 |     headers: { ...corsHeaders, "Content-Type": "application/json" },
161 |   });
162 | }
163 | });
164 |

```

FILE: [supabase/migrations/20260222065213_create_institutions_table.sql](#)

TYPE: .sql | LINES: 1-9 | SHA256: 3e55682e9c45173c3ad0accf5f75a9535e43f497b1992b4fc0af76bee7ceaf06

```

1 | CREATE TABLE public.institutions (
2 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   name text NOT NULL,
4 |   settings jsonb NOT NULL DEFAULT '{}',
5 |   created_at timestamptz NOT NULL DEFAULT now()
6 | );
7 |
8 | ALTER TABLE public.institutions ENABLE ROW LEVEL SECURITY;;
9 |

```

FILE: supabase/migrations/20260222065552_create_profiles_table.sql

TYPE: .sql | LINES: 1-18 | SHA256: 016405abb8059722e80636aa07b196b0dc6d3642632ac0219c5eafd54abfaf

```
1 | -- Create role enum type
2 | CREATE TYPE public.user_role AS ENUM ('admin', 'coordinator', 'teacher', 'student');
3 |
4 | -- Create profiles table
5 | CREATE TABLE public.profiles (
6 |   id uuid PRIMARY KEY REFERENCES auth.users(id) ON DELETE CASCADE,
7 |   institution_id uuid NOT NULL REFERENCES public.institutions(id) ON DELETE CASCADE,
8 |   full_name text NOT NULL,
9 |   email text NOT NULL,
10 |   role public.user_role NOT NULL DEFAULT 'student',
11 |   is_active boolean NOT NULL DEFAULT true,
12 |   avatar_url text,
13 |   created_at timestamptz NOT NULL DEFAULT now(),
14 |   last_seen_at timestamptz
15 | );
16 |
17 | ALTER TABLE public.profiles ENABLE ROW LEVEL SECURITY;;
18 |
```

FILE: supabase/migrations/20260222073710_create_rls_helper_functions.sql

TYPE: .sql | LINES: 1-11 | SHA256: 00e413cbe0ac619f2ff1ae90e44a9a37889fb749f7be3b9e800462056dbaf3ad

```
1 | -- RLS Helper Functions
2 | CREATE OR REPLACE FUNCTION auth_user_role()
3 | RETURNS TEXT AS $$
4 |   SELECT role::text FROM public.profiles WHERE id = auth.uid();
5 | $$ LANGUAGE SQL SECURITY DEFINER STABLE;
6 |
7 | CREATE OR REPLACE FUNCTION auth_institution_id()
8 | RETURNS UUID AS $$
9 |   SELECT institution_id FROM public.profiles WHERE id = auth.uid();
10 | $$ LANGUAGE SQL SECURITY DEFINER STABLE;;
11 |
```

FILE: supabase/migrations/20260222073726_create_core_tables.sql

TYPE: .sql | LINES: 1-75 | SHA256: 0b892096ff853e13d26ff2b17851e89079f7dbffa57e8e8e0bc002a48c148335

```
1 | -- Add missing columns to institutions
2 | ALTER TABLE public.institutions
3 |   ADD COLUMN IF NOT EXISTS logo_url text,
4 |   ADD COLUMN IF NOT EXISTS accreditation_body text;
5 |
6 | -- Programs table
7 | CREATE TABLE public.programs (
8 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
9 |   institution_id uuid NOT NULL REFERENCES public.institutions(id),
10 |   coordinator_id uuid REFERENCES public.profiles(id),
11 |   name text NOT NULL,
12 |   code text NOT NULL,
13 |   description text,
14 |   is_active boolean NOT NULL DEFAULT true,
15 |   created_at timestamptz NOT NULL DEFAULT now()
16 | );
17 | ALTER TABLE public.programs ENABLE ROW LEVEL SECURITY;
18 |
19 | -- Courses table
20 | CREATE TABLE public.courses (
21 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
22 |   program_id uuid NOT NULL REFERENCES public.programs(id),
23 |   teacher_id uuid REFERENCES public.profiles(id),
24 |   name text NOT NULL,
25 |   code text NOT NULL,
26 |   semester text NOT NULL,
27 |   academic_year text NOT NULL,
28 |   is_active boolean NOT NULL DEFAULT true,
29 |   created_at timestamptz NOT NULL DEFAULT now()
30 | );
31 | ALTER TABLE public.courses ENABLE ROW LEVEL SECURITY;
32 |
33 | -- Student-Course enrollment
34 | CREATE TABLE public.student_courses (
35 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
36 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
37 |   course_id uuid NOT NULL REFERENCES public.courses(id),
38 |   enrolled_at timestamptz NOT NULL DEFAULT now(),
39 |   status text NOT NULL DEFAULT 'active' CHECK (status IN ('active', 'completed', 'dropped')),
40 |   UNIQUE(student_id, course_id)
41 | );
42 | ALTER TABLE public.student_courses ENABLE ROW LEVEL SECURITY;
43 |
44 | -- Create enums for learning outcomes
45 | CREATE TYPE outcome_type AS ENUM ('ILO', 'PLO', 'CLO');
46 | CREATE TYPE blooms_level AS ENUM ('remembering', 'understanding', 'applying', 'analyzing', 'evaluating', 'creating');
47 |
48 | -- Learning Outcomes (unified table for ILO, PLO, CLO)
49 | CREATE TABLE public.learning_outcomes (
50 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
51 |   institution_id uuid NOT NULL REFERENCES public.institutions(id),
52 |   program_id uuid REFERENCES public.programs(id),
53 |   course_id uuid REFERENCES public.courses(id),
54 |   created_by uuid REFERENCES public.profiles(id),
55 |   type outcome_type NOT NULL,
56 |   title text NOT NULL CHECK (char_length(title) <= 255),
57 |   description text,
58 |   blooms_level blooms_level,
59 |   sort_order integer NOT NULL DEFAULT 0,
60 |   created_at timestamptz NOT NULL DEFAULT now(),
61 |   updated_at timestamptz NOT NULL DEFAULT now()
62 | );
63 | ALTER TABLE public.learning_outcomes ENABLE ROW LEVEL SECURITY;
```

```

64 |
65 | -- Outcome Mappings (CLO->PLO, PLO->ILO)
66 | CREATE TABLE public.outcome_mappings (
67 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
68 |   source_outcome_id uuid NOT NULL REFERENCES public.learning_outcomes(id) ON DELETE CASCADE,
69 |   target_outcome_id uuid NOT NULL REFERENCES public.learning_outcomes(id) ON DELETE CASCADE,
70 |   weight numeric NOT NULL DEFAULT 1.0 CHECK (weight >= 0.0 AND weight <= 1.0),
71 |   created_at timestamptz NOT NULL DEFAULT now(),
72 |   UNIQUE(source_outcome_id, target_outcome_id)
73 | );
74 | ALTER TABLE public.outcome_mappings ENABLE ROW LEVEL SECURITY;;
75 |

```

FILE: supabase/migrations/20260222073754_create_assessment_tables.sql

TYPE: .sql | LINES: 1-73 | SHA256: e1e0d795aa3ea7531ba232902a15ddb1c4afc25e77497f65a052f49cde83f73e

```

1 | -- Rubrics table
2 | CREATE TABLE public.rubrics (
3 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
4 |   clo_id uuid REFERENCES public.learning_outcomes(id),
5 |   created_by uuid REFERENCES public.profiles(id),
6 |   title text NOT NULL,
7 |   description text,
8 |   is_template boolean NOT NULL DEFAULT false,
9 |   created_at timestamptz NOT NULL DEFAULT now()
10 | );
11 | ALTER TABLE public.rubrics ENABLE ROW LEVEL SECURITY;
12 |
13 | -- Rubric Criteria table
14 | CREATE TABLE public.rubric_criteria (
15 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
16 |   rubric_id uuid NOT NULL REFERENCES public.rubrics(id) ON DELETE CASCADE,
17 |   criterion_name text NOT NULL,
18 |   sort_order integer NOT NULL DEFAULT 0,
19 |   levels jsonb NOT NULL DEFAULT '[]'::jsonb,
20 |   max_points numeric NOT NULL
21 | );
22 | ALTER TABLE public.rubric_criteria ENABLE ROW LEVEL SECURITY;
23 |
24 | -- Assignment type enum
25 | CREATE TYPE assignment_type AS ENUM ('assignment', 'quiz', 'project', 'exam');
26 |
27 | -- Assignments table
28 | CREATE TABLE public.assignments (
29 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
30 |   course_id uuid NOT NULL REFERENCES public.courses(id),
31 |   created_by uuid REFERENCES public.profiles(id),
32 |   title text NOT NULL,
33 |   description text,
34 |   type assignment_type NOT NULL DEFAULT 'assignment',
35 |   total_marks numeric NOT NULL,
36 |   due_date timestamptz NOT NULL,
37 |   is_late_allowed boolean NOT NULL DEFAULT true,
38 |   late_window_hours integer NOT NULL DEFAULT 24,
39 |   clo_weights jsonb NOT NULL DEFAULT '[]'::jsonb,
40 |   created_at timestamptz NOT NULL DEFAULT now()
41 | );
42 | ALTER TABLE public.assignments ENABLE ROW LEVEL SECURITY;
43 |
44 | -- Submission status enum
45 | CREATE TYPE submission_status AS ENUM ('submitted', 'graded');
46 |
47 | -- Submissions table
48 | CREATE TABLE public.submissions (
49 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
50 |   assignment_id uuid NOT NULL REFERENCES public.assignments(id),
51 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
52 |   file_url text,
53 |   text_content text,
54 |   is_late boolean NOT NULL DEFAULT false,
55 |   submitted_at timestamptz NOT NULL DEFAULT now(),
56 |   status submission_status NOT NULL DEFAULT 'submitted',
57 |   UNIQUE(assignment_id, student_id)
58 | );
59 | ALTER TABLE public.submissions ENABLE ROW LEVEL SECURITY;
60 |
61 | -- Grades table
62 | CREATE TABLE public.grades (
63 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
64 |   submission_id uuid NOT NULL REFERENCES public.submissions(id) UNIQUE,
65 |   graded_by uuid NOT NULL REFERENCES public.profiles(id),
66 |   rubric_selections jsonb NOT NULL DEFAULT '[]'::jsonb,
67 |   total_score numeric NOT NULL,
68 |   score_percent numeric NOT NULL,
69 |   overall_feedback text,
70 |   graded_at timestamptz NOT NULL DEFAULT now()
71 | );
72 | ALTER TABLE public.grades ENABLE ROW LEVEL SECURITY;;
73 |

```

FILE: supabase/migrations/20260222073805_create_evidence_attainment_tables.sql

TYPE: .sql | LINES: 1-34 | SHA256: aa018797acaa757b892c9d12071bc73a671c6642b98f617e6e2549a75a509db3

```

1 | -- Attainment level enum
2 | CREATE TYPE attainment_level AS ENUM ('excellent', 'satisfactory', 'developing', 'not_yet');
3 |
4 | -- Evidence table (immutable – append only)
5 | CREATE TABLE public.evidence (
6 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
7 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
8 |   submission_id uuid NOT NULL REFERENCES public.submissions(id),
9 |   grade_id uuid NOT NULL REFERENCES public.grades(id),
10 |   clo_id uuid NOT NULL REFERENCES public.learning_outcomes(id),
11 |   plo_id uuid NOT NULL REFERENCES public.learning_outcomes(id),

```

```

12 |   ilo_id uuid NOT NULL REFERENCES public.learning_outcomes(id),
13 |   score_percent numeric NOT NULL,
14 |   attainment_level attainment_level NOT NULL,
15 |   created_at timestamptz NOT NULL DEFAULT now()
16 | );
17 | ALTER TABLE public.evidence ENABLE ROW LEVEL SECURITY;
18 |
19 | -- Attainment scope enum
20 | CREATE TYPE attainment_scope AS ENUM ('student_course', 'course', 'program', 'institution');
21 |
22 | -- Outcome Attainment table
23 | CREATE TABLE public.outcome_attainment (
24 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
25 |   outcome_id uuid NOT NULL REFERENCES public.learning_outcomes(id),
26 |   student_id uuid REFERENCES public.profiles(id),
27 |   course_id uuid REFERENCES public.courses(id),
28 |   scope attainment_scope NOT NULL,
29 |   attainment_percent numeric NOT NULL DEFAULT 0,
30 |   sample_count integer NOT NULL DEFAULT 0,
31 |   last_calculated_at timestamptz NOT NULL DEFAULT now()
32 | );
33 | ALTER TABLE public.outcome_attainment ENABLE ROW LEVEL SECURITY;;
34 |

```

FILE: supabase/migrations/20260222073819_create_gamification_tables.sql

TYPE: .sql | LINES: 1-49 | SHA256: 5b78f19e3f2f4404c711df4f73fafc5ce7d721d44d934f827213d8784d2a7ae0

```

1 | -- Student Gamification (1:1 with student profile)
2 | CREATE TABLE public.student_gamification (
3 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
4 |   student_id uuid NOT NULL REFERENCES public.profiles(id) UNIQUE,
5 |   xp_total integer NOT NULL DEFAULT 0,
6 |   level integer NOT NULL DEFAULT 1,
7 |   streak_current integer NOT NULL DEFAULT 0,
8 |   streak_longest integer NOT NULL DEFAULT 0,
9 |   last_login_date date,
10 |   updated_at timestamptz NOT NULL DEFAULT now()
11 | );
12 | ALTER TABLE public.student_gamification ENABLE ROW LEVEL SECURITY;
13 |
14 | -- Badges table
15 | CREATE TABLE public.badges (
16 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
17 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
18 |   badge_key text NOT NULL,
19 |   badge_name text NOT NULL,
20 |   emoji text NOT NULL DEFAULT '🏆',
21 |   awarded_at timestamptz NOT NULL DEFAULT now(),
22 |   UNIQUE(student_id, badge_key)
23 | );
24 | ALTER TABLE public.badges ENABLE ROW LEVEL SECURITY;
25 |
26 | -- XP Transactions (immutable ledger)
27 | CREATE TABLE public.xp_transactions (
28 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
29 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
30 |   xp_amount integer NOT NULL,
31 |   source text NOT NULL CHECK (source IN ('login', 'submission', 'grade', 'badge', 'streak', 'journal', 'admin_
32 |   reference_id uuid,
33 |   note text,
34 |   created_at timestamptz NOT NULL DEFAULT now()
35 | );
36 | ALTER TABLE public.xp_transactions ENABLE ROW LEVEL SECURITY;
37 |
38 | -- Journal Entries
39 | CREATE TABLE public.journal_entries (
40 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
41 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
42 |   course_id uuid NOT NULL REFERENCES public.courses(id),
43 |   clo_id uuid REFERENCES public.learning_outcomes(id),
44 |   content text NOT NULL,
45 |   is_shared boolean NOT NULL DEFAULT false,
46 |   created_at timestamptz NOT NULL DEFAULT now()
47 | );
48 | ALTER TABLE public.journal_entries ENABLE ROW LEVEL SECURITY;;
49 |

```

FILE: supabase/migrations/20260222073828_create_system_tables.sql

TYPE: .sql | LINES: 1-26 | SHA256: 53ca44392e888c0c551c0c57b870fccdd9199556cec18907929fff9d6c129154

```

1 | -- Audit Logs (immutable - append only)
2 | CREATE TABLE public.audit_logs (
3 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
4 |   actor_id uuid NOT NULL REFERENCES public.profiles(id),
5 |   action text NOT NULL,
6 |   target_type text NOT NULL,
7 |   target_id uuid,
8 |   diff jsonb,
9 |   ip_address inet,
10 |   created_at timestamptz NOT NULL DEFAULT now()
11 | );
12 | ALTER TABLE public.audit_logs ENABLE ROW LEVEL SECURITY;
13 |
14 | -- Notifications
15 | CREATE TABLE public.notifications (
16 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
17 |   user_id uuid NOT NULL REFERENCES public.profiles(id),
18 |   type text NOT NULL,
19 |   title text NOT NULL,
20 |   body text,
21 |   metadata jsonb DEFAULT '{}':jsonb,
22 |   is_read boolean NOT NULL DEFAULT false,
23 |   created_at timestamptz NOT NULL DEFAULT now()
24 | );

```



```
25 | ALTER TABLE public.notifications ENABLE ROW LEVEL SECURITY;;
26 |
```

FILE: supabase/

migrations/20260222073842_create_rls_policies_profiles_institutions.sql

TYPE: .sql | LINES: 1-53 | SHA256: b8899553f6288f7fd2a9b3ab7ec539b74206e47e911ebcb320d0b3ac2e93fba3

```
1 | -- =====
2 | -- INSTITUTIONS RLS
3 | -- =====
4 | -- Members can read their own institution
5 | CREATE POLICY "institutions_read_own" ON public.institutions
6 |   FOR SELECT USING (id = auth_institution_id());
7 |
8 | -- Admins can manage their institution
9 | CREATE POLICY "institutions_admin_write" ON public.institutions
10 |   FOR ALL USING (
11 |     auth_user_role() = 'admin'
12 |     AND id = auth_institution_id()
13 |   );
14 |
15 | -- =====
16 | -- PROFILES RLS
17 | -- =====
18 | -- Users can read their own profile
19 | CREATE POLICY "profiles_read_own" ON public.profiles
20 |   FOR SELECT USING (id = auth.uid());
21 |
22 | -- Admins can read all profiles in their institution
23 | CREATE POLICY "profiles_admin_read_institution" ON public.profiles
24 |   FOR SELECT USING (
25 |     auth_user_role() = 'admin'
26 |     AND institution_id = auth_institution_id()
27 |   );
28 |
29 | -- Admins can insert/update profiles in their institution
30 | CREATE POLICY "profiles_admin_write" ON public.profiles
31 |   FOR ALL USING (
32 |     auth_user_role() = 'admin'
33 |     AND institution_id = auth_institution_id()
34 |   );
35 |
36 | -- Teachers can read students in their courses
37 | CREATE POLICY "profiles_teacher_read_students" ON public.profiles
38 |   FOR SELECT USING (
39 |     auth_user_role() = 'teacher'
40 |     AND id IN (
41 |       SELECT sc.student_id FROM public.student_courses sc
42 |       JOIN public.courses c ON c.id = sc.course_id
43 |       WHERE c.teacher_id = auth.uid()
44 |     )
45 |   );
46 |
47 | -- Coordinators can read profiles in their programs
48 | CREATE POLICY "profiles_coordinator_read" ON public.profiles
49 |   FOR SELECT USING (
50 |     auth_user_role() = 'coordinator'
51 |     AND institution_id = auth_institution_id()
52 |   );
53 |
```

FILE: supabase/migrations/20260222075006_add_habit_tracking_and_xp_events.sql

TYPE: .sql | LINES: 1-94 | SHA256: cfe45d674521bca1e1162c7ce133b384a2c594c9678dd4a6d8ee5da3a91cacaa

```
1 | -- Habit Tracking table (Pillar 5/6: SRL + BJ Fogg)
2 | -- Tracks 4 daily habits: login, submit, journal, read
3 | CREATE TABLE public.habit_tracking (
4 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
5 |   student_id uuid NOT NULL REFERENCES public.profiles(id),
6 |   habit_date date NOT NULL,
7 |   login boolean NOT NULL DEFAULT false,
8 |   submit boolean NOT NULL DEFAULT false,
9 |   journal boolean NOT NULL DEFAULT false,
10 |   read_content boolean NOT NULL DEFAULT false,
11 |   is_perfect_day boolean NOT NULL DEFAULT false,
12 |   created_at timestampz NOT NULL DEFAULT now(),
13 |   UNIQUE(student_id, habit_date)
14 | );
15 | ALTER TABLE public.habit_tracking ENABLE ROW LEVEL SECURITY;
16 |
17 | -- Students can read/write their own habits
18 | CREATE POLICY "habit_tracking_student_own" ON public.habit_tracking
19 |   FOR ALL USING (student_id = auth.uid());
20 |
21 | -- Teachers/admins can read for monitoring
22 | CREATE POLICY "habit_tracking_staff_read" ON public.habit_tracking
23 |   FOR SELECT USING (auth_user_role() IN ('teacher', 'coordinator', 'admin'));
24 |
25 | -- XP Events table (Pillar 7: Hooked Model - Variable Rewards)
26 | -- Defines bonus XP events like "Streak Bonus Weekend", mystery badges
27 | CREATE TABLE public.xp_events (
28 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
29 |   institution_id uuid REFERENCES public.institutions(id),
30 |   name text NOT NULL,
31 |   description text,
32 |   event_type text NOT NULL CHECK (event_type IN ('bonus_weekend', 'mystery_badge', 'first_attempt_bonus', 'per
33 |   xp_multiplier numeric NOT NULL DEFAULT 1.0,
34 |   bonus_xp integer NOT NULL DEFAULT 0,
35 |   is_active boolean NOT NULL DEFAULT false,
36 |   starts_at timestampz,
37 |   ends_at timestampz,
38 |   created_at timestampz NOT NULL DEFAULT now()
39 | );
```

```

40 | ALTER TABLE public.xp_events ENABLE ROW LEVEL SECURITY;
41 |
42 | -- All authenticated users can read active events
43 | CREATE POLICY "xp_events_read" ON public.xp_events
44 |   FOR SELECT USING (is_active = true);
45 |
46 | -- Admins can manage events
47 | CREATE POLICY "xp_events_admin_write" ON public.xp_events
48 |   FOR ALL USING (
49 |     auth_user_role() = 'admin'
50 |     AND (institution_id IS NULL OR institution_id = auth_institution_id())
51 |   );
52 |
53 | -- Learning Path Nodes table (Pillar 9: Flow Theory - Bloom's gated progression)
54 | CREATE TABLE public.learning_path_nodes (
55 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
56 |   course_id uuid NOT NULL REFERENCES public.courses(id),
57 |   assignment_id uuid NOT NULL REFERENCES public.assignments(id),
58 |   sort_order integer NOT NULL DEFAULT 0,
59 |   prerequisite_node_id uuid REFERENCES public.learning_path_nodes(id),
60 |   unlock_threshold numeric NOT NULL DEFAULT 0.0,
61 |   created_at timestamptz NOT NULL DEFAULT now()
62 | );
63 | ALTER TABLE public.learning_path_nodes ENABLE ROW LEVEL SECURITY;
64 |
65 | -- All course members can read path nodes
66 | CREATE POLICY "learning_path_nodes_read" ON public.learning_path_nodes
67 |   FOR SELECT USING (
68 |     course_id IN (
69 |       SELECT course_id FROM public.student_courses WHERE student_id = auth.uid()
70 |     UNION
71 |     SELECT id FROM public.courses WHERE teacher_id = auth.uid()
72 |   )
73 | );
74 |
75 | -- Teachers can manage path nodes for their courses
76 | CREATE POLICY "learning_path_nodes_teacher_write" ON public.learning_path_nodes
77 |   FOR ALL USING (
78 |     auth_user_role() = 'teacher'
79 |     AND course_id IN (SELECT id FROM public.courses WHERE teacher_id = auth.uid())
80 |   );
81 |
82 | -- Add notification_preferences to profiles for email opt-in (Pillar 6: BJ Fogg prompts)
83 | ALTER TABLE public.profiles
84 |   ADD COLUMN IF NOT EXISTS notification_preferences jsonb NOT NULL DEFAULT '{"email_streak_risk": true, "email
85 |
86 | -- Add leaderboard_anonymous to student_gamification for opt-out (Pillar 8: Octalysis Drive 5)
87 | ALTER TABLE public.student_gamification
88 |   ADD COLUMN IF NOT EXISTS leaderboard_anonymous boolean NOT NULL DEFAULT false;
89 |
90 | -- Update xp_transactions source check to include new sources
91 | ALTER TABLE public.xp_transactions DROP CONSTRAINT IF EXISTS xp_transactions_source_check;
92 | ALTER TABLE public.xp_transactions ADD CONSTRAINT xp_transactions_source_check
93 |   CHECK (source IN ('login', 'submission', 'grade', 'badge', 'streak', 'journal', 'perfect_day', 'first_attempt
94 |

```

FILE: [supabase/migrations/20260222075034_add_remaining_rls_policies.sql](#)

TYPE: .sql | LINES: 1-193 | SHA256: 57a32cc717e53b0d236b1103f5066a7b3f381d3b46ea4d7823da7a9afb5b9658

```

1 | -- =====
2 | -- PROGRAMS RLS
3 | -- =====
4 | CREATE POLICY "programs_institution_read" ON public.programs
5 |   FOR SELECT USING (institution_id = auth_institution_id());
6 |
7 | CREATE POLICY "programs_admin_write" ON public.programs
8 |   FOR ALL USING (
9 |     auth_user_role() = 'admin'
10 |     AND institution_id = auth_institution_id()
11 |   );
12 |
13 | -- =====
14 | -- COURSES RLS
15 | -- =====
16 | CREATE POLICY "courses_institution_read" ON public.courses
17 |   FOR SELECT USING (
18 |     program_id IN (SELECT id FROM public.programs WHERE institution_id = auth_institution_id())
19 |   );
20 |
21 | CREATE POLICY "courses_coordinator_write" ON public.courses
22 |   FOR ALL USING (
23 |     auth_user_role() = 'coordinator'
24 |     AND program_id IN (SELECT id FROM public.programs WHERE coordinator_id = auth.uid())
25 |   );
26 |
27 | CREATE POLICY "courses_admin_write" ON public.courses
28 |   FOR ALL USING (
29 |     auth_user_role() = 'admin'
30 |     AND program_id IN (SELECT id FROM public.programs WHERE institution_id = auth_institution_id())
31 |   );
32 |
33 | -- =====
34 | -- STUDENT_COURSES RLS
35 | -- =====
36 | CREATE POLICY "student_courses_student_read" ON public.student_courses
37 |   FOR SELECT USING (student_id = auth.uid());
38 |
39 | CREATE POLICY "student_courses_teacher_manage" ON public.student_courses
40 |   FOR ALL USING (
41 |     auth_user_role() = 'teacher'
42 |     AND course_id IN (SELECT id FROM public.courses WHERE teacher_id = auth.uid())
43 |   );
44 |
45 | CREATE POLICY "student_courses_admin_read" ON public.student_courses

```

```

46 | FOR SELECT USING (
47 |     auth_user_role() IN ('admin', 'coordinator')
48 | );
49 |
50 | -- =====
51 | -- OUTCOME MAPPINGS RLS
52 | -- =====
53 | CREATE POLICY "outcome_mappings_institution_read" ON public.outcome_mappings
54 |     FOR SELECT USING (
55 |         source_outcome_id IN (SELECT id FROM public.learning_outcomes WHERE institution_id = auth_institution_id())
56 |     );
57 |
58 | CREATE POLICY "outcome_mappings_admin_write" ON public.outcome_mappings
59 |     FOR ALL USING (auth_user_role() = 'admin');
60 |
61 | CREATE POLICY "outcome_mappings_coordinator_write" ON public.outcome_mappings
62 |     FOR ALL USING (auth_user_role() = 'coordinator');
63 |
64 | CREATE POLICY "outcome_mappings_teacher_write" ON public.outcome_mappings
65 |     FOR ALL USING (auth_user_role() = 'teacher');
66 |
67 | -- =====
68 | -- RUBRICS RLS
69 | -- =====
70 | CREATE POLICY "rubrics_institution_read" ON public.rubrics
71 |     FOR SELECT USING (
72 |         clo_id IN (SELECT id FROM public.learning_outcomes WHERE institution_id = auth_institution_id())
73 |         OR is_template = true
74 |     );
75 |
76 | CREATE POLICY "rubrics_teacher_write" ON public.rubrics
77 |     FOR ALL USING (
78 |         auth_user_role() = 'teacher'
79 |         AND (created_by = auth.uid() OR is_template = true)
80 |     );
81 |
82 | -- =====
83 | -- RUBRIC_CRITERIA RLS
84 | -- =====
85 | CREATE POLICY "rubric_criteria_read" ON public.rubric_criteria
86 |     FOR SELECT USING (
87 |         rubric_id IN (SELECT id FROM public.rubrics)
88 |     );
89 |
90 | CREATE POLICY "rubric_criteria_teacher_write" ON public.rubric_criteria
91 |     FOR ALL USING (
92 |         auth_user_role() = 'teacher'
93 |         AND rubric_id IN (SELECT id FROM public.rubrics WHERE created_by = auth.uid())
94 |     );
95 |
96 | -- =====
97 | -- ASSIGNMENTS RLS
98 | -- =====
99 | CREATE POLICY "assignments_teacher_write" ON public.assignments
100 |     FOR ALL USING (
101 |         auth_user_role() = 'teacher'
102 |         AND course_id IN (SELECT id FROM public.courses WHERE teacher_id = auth.uid())
103 |     );
104 |
105 | CREATE POLICY "assignments_student_read" ON public.assignments
106 |     FOR SELECT USING (
107 |         course_id IN (SELECT course_id FROM public.student_courses WHERE student_id = auth.uid() AND status = 'act
108 |     );
109 |
110 | CREATE POLICY "assignments_staff_read" ON public.assignments
111 |     FOR SELECT USING (
112 |         auth_user_role() IN ('admin', 'coordinator')
113 |     );
114 |
115 | -- =====
116 | -- GRADES RLS
117 | -- =====
118 | CREATE POLICY "grades_teacher_write" ON public.grades
119 |     FOR ALL USING (
120 |         auth_user_role() = 'teacher'
121 |         AND graded_by = auth.uid()
122 |     );
123 |
124 | CREATE POLICY "grades_student_read" ON public.grades
125 |     FOR SELECT USING (
126 |         submission_id IN (SELECT id FROM public.submissions WHERE student_id = auth.uid())
127 |     );
128 |
129 | CREATE POLICY "grades_teacher_read" ON public.grades
130 |     FOR SELECT USING (
131 |         auth_user_role() = 'teacher'
132 |         AND submission_id IN (
133 |             SELECT s.id FROM public.submissions s
134 |             JOIN public.assignments a ON a.id = s.assignment_id
135 |             JOIN public.courses c ON c.id = a.course_id
136 |             WHERE c.teacher_id = auth.uid()
137 |         )
138 |     );
139 |
140 | -- =====
141 | -- OUTCOME_ATTAINMENT RLS
142 | -- =====
143 | CREATE POLICY "attainment_student_read" ON public.outcome_attainment
144 |     FOR SELECT USING (student_id = auth.uid());
145 |
146 | CREATE POLICY "attainment_staff_read" ON public.outcome_attainment
147 |     FOR SELECT USING (
148 |         auth_user_role() IN ('teacher', 'coordinator', 'admin')
149 |     );

```

```

150 |
151 | -- =====
152 | -- BADGES RLS
153 | -- =====
154 | CREATE POLICY "badges_student_read" ON public.badges
155 |   FOR SELECT USING (student_id = auth.uid());
156 |
157 | CREATE POLICY "badges_public_read" ON public.badges
158 |   FOR SELECT USING (true);
159 |
160 | -- =====
161 | -- XP_TRANSACTIONS RLS
162 | -- =====
163 | CREATE POLICY "xp_transactions_student_read" ON public.xp_transactions
164 |   FOR SELECT USING (student_id = auth.uid());
165 |
166 | CREATE POLICY "xp_transactions_admin_read" ON public.xp_transactions
167 |   FOR SELECT USING (auth_user_role() = 'admin');
168 |
169 | -- =====
170 | -- JOURNAL_ENTRIES RLS
171 | -- =====
172 | CREATE POLICY "journal_student_own" ON public.journal_entries
173 |   FOR ALL USING (student_id = auth.uid());
174 |
175 | CREATE POLICY "journal_teacher_read_shared" ON public.journal_entries
176 |   FOR SELECT USING (
177 |     auth_user_role() = 'teacher'
178 |     AND is_shared = true
179 |     AND course_id IN (SELECT id FROM public.courses WHERE teacher_id = auth.uid())
180 |   );
181 |
182 | -- =====
183 | -- NOTIFICATIONS RLS
184 | -- =====
185 | CREATE POLICY "notifications_own" ON public.notifications
186 |   FOR ALL USING (user_id = auth.uid());
187 |
188 | -- =====
189 | -- AUDIT_LOGS – append only (no update/delete for anyone)
190 | -- =====
191 | CREATE POLICY "audit_logs_admin_insert" ON public.audit_logs
192 |   FOR INSERT WITH CHECK (auth_user_role() = 'admin');;
193 |

```

FILE: supabase/

migrations/20260222124435_add_extensions_helper_functions_and_indexes.sql

TYPE: .sql | LINES: 1-34 | SHA256: 7d8a1e16d1c9e5da816b8115991d2b50cbe3fdb8675531d006edad18a60a75c7

```

1 | -- =====
2 | -- Migration 1: Extensions, Helper Functions, Performance Indexes
3 | -- =====
4 |
5 | -- Enable pg_cron (requires Supabase Pro plan)
6 | CREATE EXTENSION IF NOT EXISTS pg_cron;
7 | CREATE EXTENSION IF NOT EXISTS pg_net;
8 |
9 | -- Helper functions for RLS policies
10 | CREATE OR REPLACE FUNCTION public.auth_user_role()
11 | RETURNS TEXT AS $$
12 |   SELECT role::text FROM public.profiles WHERE id = auth.uid();
13 | $$ LANGUAGE SQL SECURITY DEFINER STABLE;
14 |
15 | CREATE OR REPLACE FUNCTION public.auth_institution_id()
16 | RETURNS UUID AS $$
17 |   SELECT institution_id FROM public.profiles WHERE id = auth.uid();
18 | $$ LANGUAGE SQL SECURITY DEFINER STABLE;
19 |
20 | -- Performance indexes on existing tables
21 | CREATE UNIQUE INDEX IF NOT EXISTS idx_attainment_unique ON outcome_attainment(
22 |   outcome_id,
23 |   COALESCE(student_id, '00000000-0000-0000-0000-000000000000'),
24 |   COALESCE(course_id, '00000000-0000-0000-0000-000000000000'),
25 |   scope
26 | );
27 |
28 | CREATE INDEX IF NOT EXISTS idx_gamification_leaderboard ON student_gamification(xp_total DESC, student_id);
29 |
30 | CREATE INDEX IF NOT EXISTS idx_xp_transactions_student ON xp_transactions(student_id, created_at DESC);
31 |
32 | CREATE INDEX IF NOT EXISTS idx_evidence_student ON evidence(student_id, created_at DESC);
33 |
34 |

```

FILE: supabase/

migrations/20260222124458_add_columns_activity_log_ai_feedback_parent_role.sql

TYPE: .sql | LINES: 1-64 | SHA256: 9f543cc0b77da2fe775ea542191e82e7b9f62ce00ad48f0fd698ecc03c988098

```

1 | -- =====
2 | -- Migration 2: Column additions, missing tables, parent role
3 | -- =====
4 |
5 | -- Add 'parent' to user_role enum
6 | ALTER TYPE user_role ADD VALUE IF NOT EXISTS 'parent';
7 |
8 | -- Column additions for platform enhancements
9 | ALTER TABLE student_gamification ADD COLUMN IF NOT EXISTS streak_freezes_available integer NOT NULL DEFAULT 0
10 |   CHECK (streak_freezes_available >= 0 AND streak_freezes_available <= 2);
11 |
12 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS onboarding_completed boolean NOT NULL DEFAULT false;
13 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS portfolio_public boolean NOT NULL DEFAULT false;
14 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS theme_preference text NOT NULL DEFAULT 'system'
15 |   CHECK (theme_preference IN ('light', 'dark', 'system'));

```

```

16 |
17 | -- Assignment prerequisites column
18 | ALTER TABLE assignments ADD COLUMN IF NOT EXISTS prerequisites jsonb DEFAULT '[]';
19 |
20 | -- Create student_activity_log table
21 | CREATE TABLE IF NOT EXISTS student_activity_log (
22 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
23 |   student_id uuid REFERENCES profiles(id) NOT NULL,
24 |   event_type text NOT NULL CHECK (event_type IN ('login', 'page_view', 'submission', 'journal', 'streak_break'
25 |   metadata jsonb DEFAULT '{}',
26 |   created_at timestamptz NOT NULL DEFAULT now()
27 | );
28 | ALTER TABLE student_activity_log ENABLE ROW LEVEL SECURITY;
29 |
30 | CREATE INDEX IF NOT EXISTS idx_activity_log_student ON student_activity_log(student_id, created_at DESC);
31 |
32 | -- Create ai_feedback table
33 | CREATE TABLE IF NOT EXISTS ai_feedback (
34 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
35 |   student_id uuid REFERENCES profiles(id) NOT NULL,
36 |   suggestion_type text NOT NULL CHECK (suggestion_type IN ('module_suggestion', 'at_risk_prediction', 'feedback
37 |   suggestion_text text NOT NULL,
38 |   suggestion_data jsonb DEFAULT '{}',
39 |   feedback text CHECK (feedback IN ('thumbs_up', 'thumbs_down')),
40 |   validated_outcome text CHECK (validated_outcome IN ('correct', 'incorrect')),
41 |   created_at timestamptz NOT NULL DEFAULT now()
42 | );
43 | ALTER TABLE ai_feedback ENABLE ROW LEVEL SECURITY;
44 |
45 | CREATE INDEX IF NOT EXISTS idx_ai_feedback_student ON ai_feedback(student_id, created_at DESC);
46 |
47 | -- Update xp_transactions source CHECK constraint
48 | ALTER TABLE xp_transactions DROP CONSTRAINT IF EXISTS xp_transactions_source_check;
49 | ALTER TABLE xp_transactions ADD CONSTRAINT xp_transactions_source_check
50 |   CHECK (source IN ('login', 'submission', 'grade', 'badge', 'streak', 'journal', 'perfect_day', 'first_attemp
51 |
52 | -- Production readiness column additions
53 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS language_preference text NOT NULL DEFAULT 'en'
54 |   CHECK (language_preference IN ('en', 'ur', 'ar'));
55 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS tos_accepted_at timestamptz;
56 |
57 | -- Update notification_preferences default to include muted_courses and quiet_hours
58 | -- (column already exists, just update the default)
59 | ALTER TABLE profiles ALTER COLUMN notification_preferences SET DEFAULT '{"muted_courses": [], "quiet_hours": {
60 |
61 | ALTER TABLE submissions ADD COLUMN IF NOT EXISTS plagiarism_score numeric
62 |   CHECK (plagiarism_score IS NULL OR (plagiarism_score >= 0 AND plagiarism_score <= 100));
63 | ;
64 |

```

FILE: [supabase/migrations/20260222124524_create_institutional_management_tables.sql](#)

TYPE: .sql | LINES: 1-128 | SHA256: 27f2f9209547eb332afe59b6660d6abe627ddc2069258a66f313d612713fe849

```

1 | -- =====
2 | -- Migration 3: Institutional Management Tables
3 | -- =====
4 |
5 | -- semesters
6 | CREATE TABLE IF NOT EXISTS semesters (
7 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
8 |   institution_id uuid REFERENCES institutions(id) NOT NULL,
9 |   name text NOT NULL,
10 |   code text NOT NULL,
11 |   start_date date NOT NULL,
12 |   end_date date NOT NULL CHECK (end_date > start_date),
13 |   is_active boolean NOT NULL DEFAULT false,
14 |   created_at timestamptz NOT NULL DEFAULT now(),
15 |   UNIQUE (institution_id, code)
16 | );
17 | ALTER TABLE semesters ENABLE ROW LEVEL SECURITY;
18 |
19 | -- departments
20 | CREATE TABLE IF NOT EXISTS departments (
21 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
22 |   institution_id uuid REFERENCES institutions(id) NOT NULL,
23 |   name text NOT NULL,
24 |   code text NOT NULL,
25 |   head_of_department_id uuid REFERENCES profiles(id),
26 |   created_at timestamptz NOT NULL DEFAULT now(),
27 |   UNIQUE (institution_id, code)
28 | );
29 | ALTER TABLE departments ENABLE ROW LEVEL SECURITY;
30 |
31 | -- course_sections
32 | CREATE TABLE IF NOT EXISTS course_sections (
33 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
34 |   course_id uuid REFERENCES courses(id) NOT NULL,
35 |   section_code text NOT NULL,
36 |   teacher_id uuid REFERENCES profiles(id) NOT NULL,
37 |   capacity integer NOT NULL DEFAULT 50,
38 |   is_active boolean NOT NULL DEFAULT true,
39 |   created_at timestamptz NOT NULL DEFAULT now(),
40 |   UNIQUE (course_id, section_code)
41 | );
42 | ALTER TABLE course_sections ENABLE ROW LEVEL SECURITY;
43 |
44 | -- surveys
45 | CREATE TABLE IF NOT EXISTS surveys (
46 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
47 |   institution_id uuid REFERENCES institutions(id) NOT NULL,
48 |   title text NOT NULL,
49 |   type text NOT NULL CHECK (type IN ('course_exit', 'graduate_exit', 'employer')),
50 |   target_outcomes jsonb NOT NULL DEFAULT '[]',
51 |   is_active boolean NOT NULL DEFAULT true,

```

```

52 |     created_at timestamptz NOT NULL DEFAULT now()
53 | );
54 | ALTER TABLE surveys ENABLE ROW LEVEL SECURITY;
55 |
56 | -- survey_questions
57 | CREATE TABLE IF NOT EXISTS survey_questions (
58 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
59 |     survey_id uuid REFERENCES surveys(id) ON DELETE CASCADE NOT NULL,
60 |     question_text text NOT NULL,
61 |     question_type text NOT NULL CHECK (question_type IN ('likert', 'mcq', 'text')),
62 |     options jsonb,
63 |     sort_order integer NOT NULL DEFAULT 0,
64 |     UNIQUE (survey_id, sort_order)
65 | );
66 | ALTER TABLE survey_questions ENABLE ROW LEVEL SECURITY;
67 |
68 | -- survey_responses
69 | CREATE TABLE IF NOT EXISTS survey_responses (
70 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
71 |     survey_id uuid REFERENCES surveys(id) NOT NULL,
72 |     question_id uuid REFERENCES survey_questions(id) NOT NULL,
73 |     respondent_id uuid REFERENCES profiles(id) NOT NULL,
74 |     response_value text NOT NULL,
75 |     created_at timestamptz NOT NULL DEFAULT now(),
76 |     UNIQUE (survey_id, question_id, respondent_id)
77 | );
78 | ALTER TABLE survey_responses ENABLE ROW LEVEL SECURITY;
79 |
80 | -- cqi_action_plans
81 | CREATE TABLE IF NOT EXISTS cqi_action_plans (
82 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
83 |     program_id uuid REFERENCES programs(id) NOT NULL,
84 |     semester_id uuid REFERENCES semesters(id) NOT NULL,
85 |     outcome_id uuid REFERENCES learning_outcomes(id) NOT NULL,
86 |     outcome_type text NOT NULL CHECK (outcome_type IN ('PLO', 'CLO')),
87 |     baseline_attainment numeric NOT NULL CHECK (baseline_attainment >= 0 AND baseline_attainment <= 100),
88 |     target_attainment numeric NOT NULL CHECK (target_attainment >= 0 AND target_attainment <= 100),
89 |     action_description text NOT NULL,
90 |     responsible_person text NOT NULL,
91 |     status text NOT NULL DEFAULT 'planned' CHECK (status IN ('planned', 'in_progress', 'completed', 'evaluated')),
92 |     result_attainment numeric CHECK (result_attainment >= 0 AND result_attainment <= 100),
93 |     created_at timestamptz NOT NULL DEFAULT now(),
94 |     updated_at timestamptz NOT NULL DEFAULT now()
95 | );
96 | ALTER TABLE cqi_action_plans ENABLE ROW LEVEL SECURITY;
97 |
98 | -- institution_settings
99 | CREATE TABLE IF NOT EXISTS institution_settings (
100 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
101 |     institution_id uuid REFERENCES institutions(id) NOT NULL UNIQUE,
102 |     attainment_thresholds jsonb NOT NULL DEFAULT '{"excellent": 85, "satisfactory": 70, "developing": 50}',
103 |     success_threshold integer NOT NULL DEFAULT 70,
104 |     accreditation_body text NOT NULL DEFAULT 'Generic' CHECK (accreditation_body IN ('HEC', 'QQA', 'ABET', 'NCAA')),
105 |     grade_scales jsonb NOT NULL DEFAULT '{"letter": "A", "min_percent": 85, "max_percent": 100, "gpa_points": 4.0}',
106 |     created_at timestamptz NOT NULL DEFAULT now()
107 | );
108 | ALTER TABLE institution_settings ENABLE ROW LEVEL SECURITY;
109 |
110 | -- program_accreditations
111 | CREATE TABLE IF NOT EXISTS program_accreditations (
112 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
113 |     program_id uuid REFERENCES programs(id) NOT NULL,
114 |     accreditation_body text NOT NULL,
115 |     framework_version text,
116 |     accreditation_date date,
117 |     next_review_date date,
118 |     status text NOT NULL DEFAULT 'pending' CHECK (status IN ('active', 'expired', 'pending')),
119 |     created_at timestamptz NOT NULL DEFAULT now()
120 | );
121 | ALTER TABLE program_accreditations ENABLE ROW LEVEL SECURITY;
122 |
123 | -- Column additions for institutional management
124 | ALTER TABLE courses ADD COLUMN IF NOT EXISTS semester_id uuid REFERENCES semesters(id);
125 | ALTER TABLE programs ADD COLUMN IF NOT EXISTS department_id uuid REFERENCES departments(id);
126 | ALTER TABLE student_courses ADD COLUMN IF NOT EXISTS section_id uuid REFERENCES course_sections(id);
127 | ;
128 |

```

FILE: supabase/migrations/20260222124557_create_lms_feature_tables.sql

TYPE: .sql | LINES: 1-218 | SHA256: f7c47b5770611f0270c41ece6783b32029cca068ed70d7f03dd5489bb9c1239c

```

1 | -- =====
2 | -- Migration 4: LMS Feature Tables
3 | -- =====
4 |
5 | -- announcements
6 | CREATE TABLE IF NOT EXISTS announcements (
7 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
8 |     course_id uuid REFERENCES courses(id) NOT NULL,
9 |     author_id uuid REFERENCES profiles(id) NOT NULL,
10 |     title text NOT NULL,
11 |     content text NOT NULL,
12 |     is_pinned boolean NOT NULL DEFAULT false,
13 |     created_at timestamptz NOT NULL DEFAULT now(),
14 |     updated_at timestamptz NOT NULL DEFAULT now()
15 | );
16 | ALTER TABLE announcements ENABLE ROW LEVEL SECURITY;
17 | CREATE INDEX IF NOT EXISTS idx_announcements_course ON announcements(course_id, is_pinned DESC, created_at DES
18 |
19 | -- course_modules
20 | CREATE TABLE IF NOT EXISTS course_modules (
21 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
22 |     course_id uuid REFERENCES courses(id) NOT NULL,
23 |     title text NOT NULL,

```

```

24 | description text,
25 | sort_order integer NOT NULL DEFAULT 0,
26 | is_published boolean NOT NULL DEFAULT false,
27 | created_at timestamptz NOT NULL DEFAULT now()
28 | );
29 | ALTER TABLE course_modules ENABLE ROW LEVEL SECURITY;
30 |
31 | -- course_materials
32 | CREATE TABLE IF NOT EXISTS course_materials (
33 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
34 | module_id uuid REFERENCES course_modules(id) ON DELETE CASCADE NOT NULL,
35 | title text NOT NULL,
36 | type text NOT NULL CHECK (type IN ('file', 'link', 'video', 'text')),
37 | content_url text,
38 | file_path text,
39 | description text,
40 | sort_order integer NOT NULL DEFAULT 0,
41 | is_published boolean NOT NULL DEFAULT false,
42 | clo_ids jsonb DEFAULT '[]',
43 | created_at timestamptz NOT NULL DEFAULT now()
44 | );
45 | ALTER TABLE course_materials ENABLE ROW LEVEL SECURITY;
46 |
47 | -- discussion_threads
48 | CREATE TABLE IF NOT EXISTS discussion_threads (
49 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
50 | course_id uuid REFERENCES courses(id) NOT NULL,
51 | author_id uuid REFERENCES profiles(id) NOT NULL,
52 | title text NOT NULL,
53 | content text NOT NULL,
54 | is_pinned boolean NOT NULL DEFAULT false,
55 | is_resolved boolean NOT NULL DEFAULT false,
56 | created_at timestamptz NOT NULL DEFAULT now()
57 | );
58 | ALTER TABLE discussion_threads ENABLE ROW LEVEL SECURITY;
59 | CREATE INDEX IF NOT EXISTS idx_discussion_threads_course ON discussion_threads(course_id, is_pinned DESC, crea
60 |
61 | -- discussion_replies
62 | CREATE TABLE IF NOT EXISTS discussion_replies (
63 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
64 | thread_id uuid REFERENCES discussion_threads(id) ON DELETE CASCADE NOT NULL,
65 | author_id uuid REFERENCES profiles(id) NOT NULL,
66 | content text NOT NULL,
67 | is_answer boolean NOT NULL DEFAULT false,
68 | created_at timestamptz NOT NULL DEFAULT now()
69 | );
70 | ALTER TABLE discussion_replies ENABLE ROW LEVEL SECURITY;
71 |
72 | -- class_sessions
73 | CREATE TABLE IF NOT EXISTS class_sessions (
74 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
75 | section_id uuid REFERENCES course_sections(id) NOT NULL,
76 | session_date date NOT NULL,
77 | session_type text NOT NULL CHECK (session_type IN ('lecture', 'lab', 'tutorial')),
78 | topic text,
79 | created_at timestamptz NOT NULL DEFAULT now(),
80 | UNIQUE (section_id, session_date, session_type)
81 | );
82 | ALTER TABLE class_sessions ENABLE ROW LEVEL SECURITY;
83 |
84 | -- attendance_records
85 | CREATE TABLE IF NOT EXISTS attendance_records (
86 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
87 | session_id uuid REFERENCES class_sessions(id) NOT NULL,
88 | student_id uuid REFERENCES profiles(id) NOT NULL,
89 | status text NOT NULL CHECK (status IN ('present', 'absent', 'late', 'excused')),
90 | marked_by uuid REFERENCES profiles(id) NOT NULL,
91 | created_at timestamptz NOT NULL DEFAULT now(),
92 | UNIQUE (session_id, student_id)
93 | );
94 | ALTER TABLE attendance_records ENABLE ROW LEVEL SECURITY;
95 | CREATE INDEX IF NOT EXISTS idx_attendance_student ON attendance_records(student_id, session_id);
96 |
97 | -- quizzes
98 | CREATE TABLE IF NOT EXISTS quizzes (
99 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
100 | course_id uuid REFERENCES courses(id) NOT NULL,
101 | title text NOT NULL,
102 | description text,
103 | clo_ids jsonb NOT NULL DEFAULT '[]',
104 | time_limit_minutes integer,
105 | max_attempts integer NOT NULL DEFAULT 1,
106 | is_published boolean NOT NULL DEFAULT false,
107 | due_date timestamptz NOT NULL,
108 | created_at timestamptz NOT NULL DEFAULT now()
109 | );
110 | ALTER TABLE quizzes ENABLE ROW LEVEL SECURITY;
111 |
112 | -- quiz_questions
113 | CREATE TABLE IF NOT EXISTS quiz_questions (
114 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
115 | quiz_id uuid REFERENCES quizzes(id) ON DELETE CASCADE NOT NULL,
116 | question_text text NOT NULL,
117 | question_type text NOT NULL CHECK (question_type IN ('mcq_single', 'mcq_multi', 'true_false', 'short_answer'
118 | options jsonb,
119 | correct_answer jsonb NOT NULL,
120 | points numeric NOT NULL DEFAULT 1,
121 | sort_order integer NOT NULL DEFAULT 0
122 | );
123 | ALTER TABLE quiz_questions ENABLE ROW LEVEL SECURITY;
124 |
125 | -- quiz_attempts
126 | CREATE TABLE IF NOT EXISTS quiz_attempts (
127 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),

```



```

128 | quiz_id uuid REFERENCES quizzes(id) NOT NULL,
129 | student_id uuid REFERENCES profiles(id) NOT NULL,
130 | answers jsonb NOT NULL DEFAULT '{}',
131 | score numeric,
132 | started_at timestampz NOT NULL DEFAULT now(),
133 | submitted_at timestampz,
134 | attempt_number integer NOT NULL DEFAULT 1,
135 | UNIQUE (quiz_id, student_id, attempt_number)
136 | );
137 | ALTER TABLE quiz_attempts ENABLE ROW LEVEL SECURITY;
138 | CREATE INDEX IF NOT EXISTS idx_quiz_attempts_student ON quiz_attempts(student_id, quiz_id);
139 |
140 | -- grade_categories
141 | CREATE TABLE IF NOT EXISTS grade_categories (
142 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
143 | course_id uuid REFERENCES courses(id) NOT NULL,
144 | name text NOT NULL,
145 | weight_percent numeric NOT NULL CHECK (weight_percent > 0 AND weight_percent <= 100),
146 | sort_order integer NOT NULL DEFAULT 0,
147 | created_at timestampz NOT NULL DEFAULT now()
148 | );
149 | ALTER TABLE grade_categories ENABLE ROW LEVEL SECURITY;
150 |
151 | -- timetable_slots
152 | CREATE TABLE IF NOT EXISTS timetable_slots (
153 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
154 | section_id uuid REFERENCES course_sections(id) NOT NULL,
155 | day_of_week integer NOT NULL CHECK (day_of_week >= 0 AND day_of_week <= 6),
156 | start_time time NOT NULL,
157 | end_time time NOT NULL CHECK (end_time > start_time),
158 | room text,
159 | slot_type text NOT NULL CHECK (slot_type IN ('lecture', 'lab', 'tutorial')),
160 | UNIQUE (section_id, day_of_week, start_time)
161 | );
162 | ALTER TABLE timetable_slots ENABLE ROW LEVEL SECURITY;
163 |
164 | -- academic_calendar_events
165 | CREATE TABLE IF NOT EXISTS academic_calendar_events (
166 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
167 | institution_id uuid REFERENCES institutions(id) NOT NULL,
168 | semester_id uuid REFERENCES semesters(id),
169 | title text NOT NULL,
170 | event_type text NOT NULL CHECK (event_type IN ('semester_start', 'semester_end', 'exam_period', 'holiday', '
171 | start_date date NOT NULL,
172 | end_date date NOT NULL CHECK (end_date >= start_date),
173 | is_recurring boolean NOT NULL DEFAULT false,
174 | created_at timestampz NOT NULL DEFAULT now()
175 | );
176 | ALTER TABLE academic_calendar_events ENABLE ROW LEVEL SECURITY;
177 |
178 | -- parent_student_links
179 | CREATE TABLE IF NOT EXISTS parent_student_links (
180 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
181 | parent_id uuid REFERENCES profiles(id) NOT NULL,
182 | student_id uuid REFERENCES profiles(id) NOT NULL,
183 | relationship text NOT NULL CHECK (relationship IN ('parent', 'guardian')),
184 | verified boolean NOT NULL DEFAULT false,
185 | created_at timestampz NOT NULL DEFAULT now(),
186 | UNIQUE (parent_id, student_id)
187 | );
188 | ALTER TABLE parent_student_links ENABLE ROW LEVEL SECURITY;
189 |
190 | -- fee_structures
191 | CREATE TABLE IF NOT EXISTS fee_structures (
192 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
193 | program_id uuid REFERENCES programs(id) NOT NULL,
194 | semester_id uuid REFERENCES semesters(id) NOT NULL,
195 | fee_type text NOT NULL CHECK (fee_type IN ('tuition', 'lab', 'library', 'exam')),
196 | amount numeric NOT NULL CHECK (amount >= 0),
197 | currency text NOT NULL DEFAULT 'PKR',
198 | due_date date NOT NULL,
199 | created_at timestampz NOT NULL DEFAULT now()
200 | );
201 | ALTER TABLE fee_structures ENABLE ROW LEVEL SECURITY;
202 |
203 | -- fee_payments
204 | CREATE TABLE IF NOT EXISTS fee_payments (
205 | id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
206 | student_id uuid REFERENCES profiles(id) NOT NULL,
207 | fee_structure_id uuid REFERENCES fee_structures(id) NOT NULL,
208 | amount_paid numeric NOT NULL CHECK (amount_paid >= 0),
209 | payment_date date NOT NULL,
210 | payment_method text,
211 | receipt_number text,
212 | status text NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'paid', 'overdue', 'waived')),
213 | created_at timestampz NOT NULL DEFAULT now()
214 | );
215 | ALTER TABLE fee_payments ENABLE ROW LEVEL SECURITY;
216 | CREATE INDEX IF NOT EXISTS idx_fee_payments_student ON fee_payments(student_id, status);
217 |
218 |

```

FILE: supabase/migrations/20260222124630_add_rls_policies_part1.sql

TYPE: .sql | LINES: 1-146 | SHA256: 903f1ec78da513e9b45f562f1012c02323f2c7dfe911fda545949b0e0422cdb3

```

1 | -- =====
2 | -- Migration 5a: RLS Policies for New Tables (Part 1)
3 | -- =====
4 |
5 | -- student_activity_log policies (append-only)
6 | CREATE POLICY "activity_log_student_insert" ON student_activity_log
7 | FOR INSERT WITH CHECK (student_id = auth.uid());
8 | CREATE POLICY "activity_log_admin_read" ON student_activity_log
9 | FOR SELECT USING (auth_user_role() = 'admin');

```



```

10 |
11 | -- ai_feedback policies
12 | CREATE POLICY "ai_feedback_student_read" ON ai_feedback
13 |   FOR SELECT USING (student_id = auth.uid());
14 | CREATE POLICY "ai_feedback_student_update" ON ai_feedback
15 |   FOR UPDATE USING (student_id = auth.uid());
16 | CREATE POLICY "ai_feedback_teacher_read" ON ai_feedback
17 |   FOR SELECT USING (
18 |     auth_user_role() = 'teacher'
19 |     AND student_id IN (
20 |       SELECT sc.student_id FROM student_courses sc
21 |       JOIN courses c ON c.id = sc.course_id
22 |       WHERE c.teacher_id = auth.uid()
23 |     )
24 |   );
25 | CREATE POLICY "ai_feedback_admin_read" ON ai_feedback
26 |   FOR SELECT USING (auth_user_role() = 'admin');
27 |
28 | -- semesters policies
29 | CREATE POLICY "semesters_institution_read" ON semesters
30 |   FOR SELECT USING (institution_id = auth.institution_id());
31 | CREATE POLICY "semesters_admin_write" ON semesters
32 |   FOR ALL USING (auth_user_role() = 'admin' AND institution_id = auth.institution_id());
33 |
34 | -- departments policies
35 | CREATE POLICY "departments_institution_read" ON departments
36 |   FOR SELECT USING (institution_id = auth.institution_id());
37 | CREATE POLICY "departments_admin_write" ON departments
38 |   FOR ALL USING (auth_user_role() = 'admin' AND institution_id = auth.institution_id());
39 |
40 | -- course_sections policies
41 | CREATE POLICY "sections_read" ON course_sections
42 |   FOR SELECT USING (
43 |     EXISTS (
44 |       SELECT 1 FROM courses c
45 |       JOIN programs p ON p.id = c.program_id
46 |       WHERE c.id = course_sections.course_id
47 |       AND p.institution_id = auth.institution_id()
48 |     )
49 |   );
50 | CREATE POLICY "sections_admin_write" ON course_sections
51 |   FOR ALL USING (
52 |     auth_user_role() = 'admin'
53 |     AND EXISTS (
54 |       SELECT 1 FROM courses c
55 |       JOIN programs p ON p.id = c.program_id
56 |       WHERE c.id = course_sections.course_id
57 |       AND p.institution_id = auth.institution_id()
58 |     )
59 |   );
60 | CREATE POLICY "sections_coordinator_write" ON course_sections
61 |   FOR ALL USING (
62 |     auth_user_role() = 'coordinator'
63 |     AND EXISTS (
64 |       SELECT 1 FROM courses c
65 |       JOIN programs p ON p.id = c.program_id
66 |       WHERE c.id = course_sections.course_id
67 |       AND p.coordinator_id = auth.uid()
68 |     )
69 |   );
70 |
71 | -- surveys policies
72 | CREATE POLICY "surveys_institution_read" ON surveys
73 |   FOR SELECT USING (institution_id = auth.institution_id());
74 | CREATE POLICY "surveys_admin_write" ON surveys
75 |   FOR ALL USING (auth_user_role() = 'admin' AND institution_id = auth.institution_id());
76 | CREATE POLICY "surveys_coordinator_write" ON surveys
77 |   FOR ALL USING (auth_user_role() = 'coordinator' AND institution_id = auth.institution_id());
78 |
79 | -- survey_questions policies
80 | CREATE POLICY "survey_questions_read" ON survey_questions
81 |   FOR SELECT USING (
82 |     EXISTS (SELECT 1 FROM surveys s WHERE s.id = survey_questions.survey_id AND s.institution_id = auth_instit
83 |   );
84 | CREATE POLICY "survey_questions_admin_write" ON survey_questions
85 |   FOR ALL USING (
86 |     auth_user_role() IN ('admin', 'coordinator')
87 |     AND EXISTS (SELECT 1 FROM surveys s WHERE s.id = survey_questions.survey_id AND s.institution_id = auth_in
88 |   );
89 |
90 | -- survey_responses policies
91 | CREATE POLICY "survey_responses_own_read" ON survey_responses
92 |   FOR SELECT USING (respondent_id = auth.uid());
93 | CREATE POLICY "survey_responses_own_insert" ON survey_responses
94 |   FOR INSERT WITH CHECK (respondent_id = auth.uid());
95 | CREATE POLICY "survey_responses_admin_read" ON survey_responses
96 |   FOR SELECT USING (
97 |     auth_user_role() IN ('admin', 'coordinator')
98 |     AND EXISTS (SELECT 1 FROM surveys s WHERE s.id = survey_responses.survey_id AND s.institution_id = auth_in
99 |   );
100 |
101 | -- cqi_action_plans policies
102 | CREATE POLICY "cqi_plans_read" ON cqi_action_plans
103 |   FOR SELECT USING (
104 |     auth_user_role() IN ('admin', 'coordinator')
105 |     AND EXISTS (
106 |       SELECT 1 FROM programs p WHERE p.id = cqi_action_plans.program_id AND p.institution_id = auth_institutio
107 |     )
108 |   );
109 | CREATE POLICY "cqi_plans_coordinator_write" ON cqi_action_plans
110 |   FOR ALL USING (
111 |     auth_user_role() = 'coordinator'
112 |     AND EXISTS (
113 |       SELECT 1 FROM programs p WHERE p.id = cqi_action_plans.program_id AND p.coordinator_id = auth.uid()

```

```

114 |     )
115 | );
116 | CREATE POLICY "cqi_plans_admin_write" ON cqi_action_plans
117 |     FOR ALL USING (
118 |         auth_user_role() = 'admin'
119 |         AND EXISTS (
120 |             SELECT 1 FROM programs p WHERE p.id = cqi_action_plans.program_id AND p.institution_id = auth_institutio
121 |         )
122 |     );
123 |
124 | -- institution_settings policies
125 | CREATE POLICY "institution_settings_read" ON institution_settings
126 |     FOR SELECT USING (institution_id = auth_institution_id());
127 | CREATE POLICY "institution_settings_admin_write" ON institution_settings
128 |     FOR ALL USING (auth_user_role() = 'admin' AND institution_id = auth_institution_id());
129 |
130 | -- program_accreditations policies
131 | CREATE POLICY "program_accreditations_read" ON program_accreditations
132 |     FOR SELECT USING (
133 |         EXISTS (SELECT 1 FROM programs p WHERE p.id = program_accreditations.program_id AND p.institution_id = aut
134 |     );
135 | CREATE POLICY "program_accreditations_admin_write" ON program_accreditations
136 |     FOR ALL USING (
137 |         auth_user_role() = 'admin'
138 |         AND EXISTS (SELECT 1 FROM programs p WHERE p.id = program_accreditations.program_id AND p.institution_id =
139 |     );
140 | CREATE POLICY "program_accreditations_coordinator_write" ON program_accreditations
141 |     FOR ALL USING (
142 |         auth_user_role() = 'coordinator'
143 |         AND EXISTS (SELECT 1 FROM programs p WHERE p.id = program_accreditations.program_id AND p.coordinator_id =
144 |     );
145 | ;
146 |

```

FILE: [supabase/migrations/20260222124654_add_rols_policies_part2.sql](#)

TYPE: .sql | LINES: 1-148 | SHA256: ea450a91cfe3f37314da47ac6129f3873252bc5c8fae0e84ef97ae3c197613dd

```

1 | -- =====
2 | -- Migration 5b: RLS Policies for LMS Tables (Part 2)
3 | -- =====
4 |
5 | -- announcements policies
6 | CREATE POLICY "announcements_course_read" ON announcements
7 |     FOR SELECT USING (
8 |         EXISTS (
9 |             SELECT 1 FROM courses c
10 |             JOIN programs p ON p.id = c.program_id
11 |             WHERE c.id = announcements.course_id
12 |             AND p.institution_id = auth_institution_id()
13 |         )
14 |     );
15 | CREATE POLICY "announcements_teacher_write" ON announcements
16 |     FOR ALL USING (
17 |         auth_user_role() = 'teacher'
18 |         AND EXISTS (SELECT 1 FROM courses c WHERE c.id = announcements.course_id AND c.teacher_id = auth.uid())
19 |     );
20 | CREATE POLICY "announcements_admin_write" ON announcements
21 |     FOR ALL USING (
22 |         auth_user_role() = 'admin'
23 |         AND EXISTS (
24 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id
25 |             WHERE c.id = announcements.course_id AND p.institution_id = auth_institution_id()
26 |         )
27 |     );
28 |
29 | -- course_modules policies
30 | CREATE POLICY "course_modules_read" ON course_modules
31 |     FOR SELECT USING (
32 |         EXISTS (
33 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id
34 |             WHERE c.id = course_modules.course_id AND p.institution_id = auth_institution_id()
35 |         )
36 |     );
37 | CREATE POLICY "course_modules_teacher_write" ON course_modules
38 |     FOR ALL USING (
39 |         auth_user_role() = 'teacher'
40 |         AND EXISTS (SELECT 1 FROM courses c WHERE c.id = course_modules.course_id AND c.teacher_id = auth.uid())
41 |     );
42 |
43 | -- course_materials policies
44 | CREATE POLICY "course_materials_read" ON course_materials
45 |     FOR SELECT USING (
46 |         EXISTS (
47 |             SELECT 1 FROM course_modules cm
48 |             JOIN courses c ON c.id = cm.course_id
49 |             JOIN programs p ON p.id = c.program_id
50 |             WHERE cm.id = course_materials.module_id AND p.institution_id = auth_institution_id()
51 |         )
52 |     );
53 | CREATE POLICY "course_materials_teacher_write" ON course_materials
54 |     FOR ALL USING (
55 |         auth_user_role() = 'teacher'
56 |         AND EXISTS (
57 |             SELECT 1 FROM course_modules cm
58 |             JOIN courses c ON c.id = cm.course_id
59 |             WHERE cm.id = course_materials.module_id AND c.teacher_id = auth.uid()
60 |         )
61 |     );
62 |
63 | -- discussion_threads policies
64 | CREATE POLICY "discussion_threads_course_read" ON discussion_threads
65 |     FOR SELECT USING (
66 |         EXISTS (
67 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id

```

```

68 |         WHERE c.id = discussion_threads.course_id AND p.institution_id = auth_institution_id()
69 |     );
70 | );
71 | CREATE POLICY "discussion_threads_author_write" ON discussion_threads
72 |     FOR INSERT WITH CHECK (
73 |         author_id = auth.uid()
74 |         AND EXISTS (
75 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id
76 |             WHERE c.id = discussion_threads.course_id AND p.institution_id = auth_institution_id()
77 |         )
78 |     );
79 | CREATE POLICY "discussion_threads_teacher_manage" ON discussion_threads
80 |     FOR ALL USING (
81 |         auth_user_role() = 'teacher'
82 |         AND EXISTS (SELECT 1 FROM courses c WHERE c.id = discussion_threads.course_id AND c.teacher_id = auth.uid()
83 |     );
84 |
85 | -- discussion_replies policies
86 | CREATE POLICY "discussion_replies_read" ON discussion_replies
87 |     FOR SELECT USING (
88 |         EXISTS (
89 |             SELECT 1 FROM discussion_threads dt
90 |             JOIN courses c ON c.id = dt.course_id
91 |             JOIN programs p ON p.id = c.program_id
92 |             WHERE dt.id = discussion_replies.thread_id AND p.institution_id = auth_institution_id()
93 |         )
94 |     );
95 | CREATE POLICY "discussion_replies_author_insert" ON discussion_replies
96 |     FOR INSERT WITH CHECK (
97 |         author_id = auth.uid()
98 |         AND EXISTS (
99 |             SELECT 1 FROM discussion_threads dt
100 |            JOIN courses c ON c.id = dt.course_id
101 |            JOIN programs p ON p.id = c.program_id
102 |            WHERE dt.id = discussion_replies.thread_id AND p.institution_id = auth_institution_id()
103 |        )
104 |    );
105 | CREATE POLICY "discussion_replies_teacher_manage" ON discussion_replies
106 |     FOR ALL USING (
107 |         auth_user_role() = 'teacher'
108 |         AND EXISTS (
109 |             SELECT 1 FROM discussion_threads dt
110 |             JOIN courses c ON c.id = dt.course_id
111 |             WHERE dt.id = discussion_replies.thread_id AND c.teacher_id = auth.uid()
112 |         )
113 |     );
114 |
115 | -- class_sessions policies
116 | CREATE POLICY "class_sessions_read" ON class_sessions
117 |     FOR SELECT USING (
118 |         EXISTS (
119 |             SELECT 1 FROM course_sections cs
120 |             JOIN courses c ON c.id = cs.course_id
121 |             JOIN programs p ON p.id = c.program_id
122 |             WHERE cs.id = class_sessions.section_id AND p.institution_id = auth_institution_id()
123 |         )
124 |     );
125 | CREATE POLICY "class_sessions_teacher_write" ON class_sessions
126 |     FOR ALL USING (
127 |         auth_user_role() = 'teacher'
128 |         AND EXISTS (
129 |             SELECT 1 FROM course_sections cs WHERE cs.id = class_sessions.section_id AND cs.teacher_id = auth.uid()
130 |         )
131 |     );
132 |
133 | -- attendance_records policies
134 | CREATE POLICY "attendance_own_read" ON attendance_records
135 |     FOR SELECT USING (student_id = auth.uid());
136 | CREATE POLICY "attendance_teacher_manage" ON attendance_records
137 |     FOR ALL USING (
138 |         auth_user_role() = 'teacher'
139 |         AND EXISTS (
140 |             SELECT 1 FROM class_sessions cs
141 |             JOIN course_sections sect ON sect.id = cs.section_id
142 |             WHERE cs.id = attendance_records.session_id AND sect.teacher_id = auth.uid()
143 |         )
144 |     );
145 | CREATE POLICY "attendance_admin_read" ON attendance_records
146 |     FOR SELECT USING (auth_user_role() = 'admin');
147 | ;
148 |

```

FILE: [supabase/migrations/20260222124721_add_rls_policies_part3.sql](https://supabase.com/migrations/20260222124721_add_rls_policies_part3.sql)

TYPE: .sql | LINES: 1-174 | SHA256: 378c75b58d95fc19c8712a807ba06816c058846487fac78483dddefff6f37612

```

1 | -- =====
2 | -- Migration 5c: RLS Policies for Quizzes, Fees, Parent, Calendar
3 | -- =====
4 |
5 | -- quizzes policies
6 | CREATE POLICY "quizzes_course_read" ON quizzes
7 |     FOR SELECT USING (
8 |         EXISTS (
9 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id
10 |            WHERE c.id = quizzes.course_id AND p.institution_id = auth_institution_id()
11 |        )
12 |    );
13 | CREATE POLICY "quizzes_teacher_write" ON quizzes
14 |     FOR ALL USING (
15 |         auth_user_role() = 'teacher'
16 |         AND EXISTS (SELECT 1 FROM courses c WHERE c.id = quizzes.course_id AND c.teacher_id = auth.uid())
17 |     );
18 |
19 | -- quiz_questions policies

```

```

20 | CREATE POLICY "quiz_questions_read" ON quiz_questions
21 |     FOR SELECT USING (
22 |         EXISTS (
23 |             SELECT 1 FROM quizzes q
24 |             JOIN courses c ON c.id = q.course_id
25 |             JOIN programs p ON p.id = c.program_id
26 |             WHERE q.id = quiz_questions.quiz_id AND p.institution_id = auth_institution_id()
27 |         )
28 |     );
29 | CREATE POLICY "quiz_questions_teacher_write" ON quiz_questions
30 |     FOR ALL USING (
31 |         auth_user_role() = 'teacher'
32 |         AND EXISTS (
33 |             SELECT 1 FROM quizzes q
34 |             JOIN courses c ON c.id = q.course_id
35 |             WHERE q.id = quiz_questions.quiz_id AND c.teacher_id = auth.uid()
36 |         )
37 |     );
38 |
39 | -- quiz_attempts policies
40 | CREATE POLICY "quiz_attempts_own" ON quiz_attempts
41 |     FOR ALL USING (student_id = auth.uid());
42 | CREATE POLICY "quiz_attempts_teacher_read" ON quiz_attempts
43 |     FOR SELECT USING (
44 |         auth_user_role() = 'teacher'
45 |         AND EXISTS (
46 |             SELECT 1 FROM quizzes q
47 |             JOIN courses c ON c.id = q.course_id
48 |             WHERE q.id = quiz_attempts.quiz_id AND c.teacher_id = auth.uid()
49 |         )
50 |     );
51 |
52 | -- grade_categories policies
53 | CREATE POLICY "grade_categories_read" ON grade_categories
54 |     FOR SELECT USING (
55 |         EXISTS (
56 |             SELECT 1 FROM courses c JOIN programs p ON p.id = c.program_id
57 |             WHERE c.id = grade_categories.course_id AND p.institution_id = auth_institution_id()
58 |         )
59 |     );
60 | CREATE POLICY "grade_categories_teacher_write" ON grade_categories
61 |     FOR ALL USING (
62 |         auth_user_role() = 'teacher'
63 |         AND EXISTS (SELECT 1 FROM courses c WHERE c.id = grade_categories.course_id AND c.teacher_id = auth.uid())
64 |     );
65 |
66 | -- timetable_slots policies
67 | CREATE POLICY "timetable_slots_read" ON timetable_slots
68 |     FOR SELECT USING (
69 |         EXISTS (
70 |             SELECT 1 FROM course_sections cs
71 |             JOIN courses c ON c.id = cs.course_id
72 |             JOIN programs p ON p.id = c.program_id
73 |             WHERE cs.id = timetable_slots.section_id AND p.institution_id = auth_institution_id()
74 |         )
75 |     );
76 | CREATE POLICY "timetable_slots_admin_write" ON timetable_slots
77 |     FOR ALL USING (
78 |         auth_user_role() = 'admin'
79 |         AND EXISTS (
80 |             SELECT 1 FROM course_sections cs
81 |             JOIN courses c ON c.id = cs.course_id
82 |             JOIN programs p ON p.id = c.program_id
83 |             WHERE cs.id = timetable_slots.section_id AND p.institution_id = auth_institution_id()
84 |         )
85 |     );
86 |
87 | -- academic_calendar_events policies
88 | CREATE POLICY "calendar_events_institution_read" ON academic_calendar_events
89 |     FOR SELECT USING (institution_id = auth_institution_id());
90 | CREATE POLICY "calendar_events_admin_write" ON academic_calendar_events
91 |     FOR ALL USING (auth_user_role() = 'admin' AND institution_id = auth_institution_id());
92 |
93 | -- parent_student_links policies
94 | CREATE POLICY "parent_links_parent_read" ON parent_student_links
95 |     FOR SELECT USING (parent_id = auth.uid());
96 | CREATE POLICY "parent_links_student_read" ON parent_student_links
97 |     FOR SELECT USING (student_id = auth.uid());
98 | CREATE POLICY "parent_links_admin_manage" ON parent_student_links
99 |     FOR ALL USING (
100 |         auth_user_role() = 'admin'
101 |         AND EXISTS (SELECT 1 FROM profiles p WHERE p.id = parent_student_links.student_id AND p.institution_id = a
102 |     );
103 |
104 | -- fee_structures policies
105 | CREATE POLICY "fee_structures_institution_read" ON fee_structures
106 |     FOR SELECT USING (
107 |         EXISTS (
108 |             SELECT 1 FROM programs p WHERE p.id = fee_structures.program_id AND p.institution_id = auth_institution_
109 |         )
110 |     );
111 | CREATE POLICY "fee_structures_admin_write" ON fee_structures
112 |     FOR ALL USING (
113 |         auth_user_role() = 'admin'
114 |         AND EXISTS (
115 |             SELECT 1 FROM programs p WHERE p.id = fee_structures.program_id AND p.institution_id = auth_institution_
116 |         )
117 |     );
118 |
119 | -- fee_payments policies
120 | CREATE POLICY "fee_payments_own_read" ON fee_payments
121 |     FOR SELECT USING (student_id = auth.uid());
122 | CREATE POLICY "fee_payments_admin_manage" ON fee_payments
123 |     FOR ALL USING (

```

```

124 |     auth_user_role() = 'admin'
125 |     AND EXISTS (
126 |         SELECT 1 FROM profiles p WHERE p.id = fee_payments.student_id AND p.institution_id = auth_institution_id
127 |     )
128 | );
129 |
130 | -- Parent read-only access to linked student data
131 | CREATE POLICY "parent_read_student_grades" ON grades
132 | FOR SELECT USING (
133 |     auth_user_role() = 'parent'
134 |     AND EXISTS (
135 |         SELECT 1 FROM submissions s
136 |         JOIN parent_student_links psl ON psl.student_id = s.student_id
137 |         WHERE s.id = grades.submission_id
138 |         AND psl.parent_id = auth.uid()
139 |         AND psl.verified = true
140 |     )
141 | );
142 | CREATE POLICY "parent_read_student_attendance" ON attendance_records
143 | FOR SELECT USING (
144 |     auth_user_role() = 'parent'
145 |     AND EXISTS (
146 |         SELECT 1 FROM parent_student_links psl
147 |         WHERE psl.student_id = attendance_records.student_id
148 |         AND psl.parent_id = auth.uid()
149 |         AND psl.verified = true
150 |     )
151 | );
152 | CREATE POLICY "parent_read_student_gamification" ON student_gamification
153 | FOR SELECT USING (
154 |     auth_user_role() = 'parent'
155 |     AND EXISTS (
156 |         SELECT 1 FROM parent_student_links psl
157 |         WHERE psl.student_id = student_gamification.student_id
158 |         AND psl.parent_id = auth.uid()
159 |         AND psl.verified = true
160 |     )
161 | );
162 | CREATE POLICY "parent_read_student_attainment" ON outcome_attainment
163 | FOR SELECT USING (
164 |     auth_user_role() = 'parent'
165 |     AND student_id IS NOT NULL
166 |     AND EXISTS (
167 |         SELECT 1 FROM parent_student_links psl
168 |         WHERE psl.student_id = outcome_attainment.student_id
169 |         AND psl.parent_id = auth.uid()
170 |         AND psl.verified = true
171 |     )
172 | );
173 | ;
174 |

```

FILE: supabase/

migrations/20260222124741_add_materialized_view_and_fulltext_search.sql

TYPE: .sql | LINES: 1-43 | SHA256: b56f888c1deb9a37a0a73b4378f320e4a25552bcf9fdd0a32a70d01574fbb739

```

1 | -- =====
2 | -- Migration 6: Leaderboard Materialized View + Full-Text Search
3 | -- =====
4 |
5 | -- Leaderboard materialized view
6 | CREATE MATERIALIZED VIEW IF NOT EXISTS leaderboard_weekly AS
7 | SELECT
8 |     sg.student_id,
9 |     p.full_name,
10 |     p.institution_id,
11 |     sg.xp_total,
12 |     sg.level,
13 |     sg.streak_current,
14 |     RANK() OVER (ORDER BY sg.xp_total DESC) AS global_rank
15 | FROM student_gamification sg
16 | JOIN profiles p ON p.id = sg.student_id
17 | WHERE p.is_active = true
18 | ORDER BY sg.xp_total DESC;
19 |
20 | CREATE UNIQUE INDEX IF NOT EXISTS idx_leaderboard_weekly_student ON leaderboard_weekly(student_id);
21 |
22 | -- Full-text search tsvector columns and GIN indexes
23 | ALTER TABLE courses ADD COLUMN IF NOT EXISTS search_vector tsvector
24 |     GENERATED ALWAYS AS (to_tsvector('english', coalesce(name, '') || ' ' || coalesce(code, ''))) STORED;
25 | CREATE INDEX IF NOT EXISTS idx_courses_search ON courses USING GIN(search_vector);
26 |
27 | ALTER TABLE assignments ADD COLUMN IF NOT EXISTS search_vector tsvector
28 |     GENERATED ALWAYS AS (to_tsvector('english', coalesce(title, '') || ' ' || coalesce(description, ''))) STORED;
29 | CREATE INDEX IF NOT EXISTS idx_assignments_search ON assignments USING GIN(search_vector);
30 |
31 | ALTER TABLE announcements ADD COLUMN IF NOT EXISTS search_vector tsvector
32 |     GENERATED ALWAYS AS (to_tsvector('english', coalesce(title, '') || ' ' || coalesce(content, ''))) STORED;
33 | CREATE INDEX IF NOT EXISTS idx_announcements_search ON announcements USING GIN(search_vector);
34 |
35 | ALTER TABLE course_materials ADD COLUMN IF NOT EXISTS search_vector tsvector
36 |     GENERATED ALWAYS AS (to_tsvector('english', coalesce(title, '') || ' ' || coalesce(description, ''))) STORED;
37 | CREATE INDEX IF NOT EXISTS idx_materials_search ON course_materials USING GIN(search_vector);
38 |
39 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS search_vector tsvector
40 |     GENERATED ALWAYS AS (to_tsvector('english', coalesce(full_name, '') || ' ' || coalesce(email, ''))) STORED;
41 | CREATE INDEX IF NOT EXISTS idx_profiles_search ON profiles USING GIN(search_vector);
42 | ;
43 |

```

FILE: supabase/migrations/20260222124808_add_cron_jobs.sql

TYPE: .sql | LINES: 1-77 | SHA256: f5cf5b8d0eb6450370409b55907524349f050ec662cbac7b8e24807536ed7543

```
1 | -- =====
2 | -- Migration 7: Cron Jobs
3 | -- =====
4 | -- NOTE: pg_cron and pg_net require Supabase Pro plan.
5 | -- If these fail on free tier, see task 44 for Vercel Cron fallback.
6 | -- The Edge Functions referenced here will be created in later tasks.
7 |
8 | -- Leaderboard refresh (every 5 minutes)
9 | SELECT cron.schedule(
10 |   'leaderboard-refresh',
11 |   '*/*5 * * * *',
12 |   'REFRESH MATERIALIZED VIEW CONCURRENTLY leaderboard_weekly'
13 | );
14 |
15 | -- Streak risk email (daily 8 PM UTC)
16 | SELECT cron.schedule(
17 |   'streak-risk-email',
18 |   '0 20 * * *',
19 |   $$SELECT net.http_post(
20 |     url := 'https://cdlgtbvxlxjpcddjazzx.supabase.co/functions/v1/streak-risk-cron',
21 |     headers := jsonb_build_object('Authorization', 'Bearer ' || current_setting('app.settings.service_role_key
22 |     body := '{}'::jsonb
23 |   )$$
24 | );
25 |
26 | -- Weekly summary email (Monday 8 AM UTC)
27 | SELECT cron.schedule(
28 |   'weekly-summary-email',
29 |   '0 8 * * 1',
30 |   $$SELECT net.http_post(
31 |     url := 'https://cdlgtbvxlxjpcddjazzx.supabase.co/functions/v1/weekly-summary-cron',
32 |     headers := jsonb_build_object('Authorization', 'Bearer ' || current_setting('app.settings.service_role_key
33 |     body := '{}'::jsonb
34 |   )$$
35 | );
36 |
37 | -- Compute at-risk signals (nightly 2 AM UTC)
38 | SELECT cron.schedule(
39 |   'compute-at-risk-signals',
40 |   '0 2 * * *',
41 |   $$SELECT net.http_post(
42 |     url := 'https://cdlgtbvxlxjpcddjazzx.supabase.co/functions/v1/compute-at-risk-signals',
43 |     headers := jsonb_build_object('Authorization', 'Bearer ' || current_setting('app.settings.service_role_key
44 |     body := '{}'::jsonb
45 |   )$$
46 | );
47 |
48 | -- Perfect day prompt (daily 6 PM UTC)
49 | SELECT cron.schedule(
50 |   'perfect-day-prompt',
51 |   '0 18 * * *',
52 |   $$SELECT net.http_post(
53 |     url := 'https://cdlgtbvxlxjpcddjazzx.supabase.co/functions/v1/perfect-day-prompt',
54 |     headers := jsonb_build_object('Authorization', 'Bearer ' || current_setting('app.settings.service_role_key
55 |     body := '{}'::jsonb
56 |   )$$
57 | );
58 |
59 | -- Streak midnight reset (daily midnight UTC)
60 | SELECT cron.schedule(
61 |   'streak-midnight-reset',
62 |   '0 0 * * *',
63 |   $$SELECT net.http_post(
64 |     url := 'https://cdlgtbvxlxjpcddjazzx.supabase.co/functions/v1/process-streak',
65 |     headers := jsonb_build_object('Authorization', 'Bearer ' || current_setting('app.settings.service_role_key
66 |     body := '{"type": "midnight_reset"}'::jsonb
67 |   )$$
68 | );
69 |
70 | -- Fee overdue check (daily 6 AM UTC)
71 | SELECT cron.schedule(
72 |   'fee-overdue-check',
73 |   '0 6 * * *',
74 |   $$UPDATE fee_payments SET status = 'overdue' WHERE status = 'pending' AND EXISTS (SELECT 1 FROM fee_structur
75 | );
76 |
77 |
```

FILE: supabase/migrations/20260222124929_add_extensions_indexes_and_column_additions.sql

TYPE: .sql | LINES: 1-35 | SHA256: b4e8aa773e72dec3ca2c19c58eedcb3c31459629d475b15fd934d77e5f37f949

```
1 | -- 1. Extensions (may fail on free tier – that's OK)
2 | CREATE EXTENSION IF NOT EXISTS pg_cron;
3 | CREATE EXTENSION IF NOT EXISTS pg_net;
4 |
5 | -- 2. Performance Indexes
6 | CREATE UNIQUE INDEX IF NOT EXISTS idx_attainment_unique ON outcome_attainment(
7 |   outcome_id,
8 |   COALESCE(student_id, '00000000-0000-0000-0000-000000000000'),
9 |   COALESCE(course_id, '00000000-0000-0000-0000-000000000000'),
10 |   scope
11 | );
12 | CREATE INDEX IF NOT EXISTS idx_gamification_leaderboard ON student_gamification(xp_total DESC, student_id);
13 | CREATE INDEX IF NOT EXISTS idx_activity_log_student ON student_activity_log(student_id, created_at DESC);
14 | CREATE INDEX IF NOT EXISTS idx_xp_transactions_student ON xp_transactions(student_id, created_at DESC);
15 | CREATE INDEX IF NOT EXISTS idx_evidence_student ON evidence(student_id, created_at DESC);
16 | CREATE INDEX IF NOT EXISTS idx_ai_feedback_student ON ai_feedback(student_id, created_at DESC);
17 |
18 | -- 3. Column Additions – Platform Enhancements
```

```

19 | ALTER TABLE student_gamification ADD COLUMN IF NOT EXISTS streak_freezes_available integer NOT NULL DEFAULT 0;
20 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS onboarding_completed boolean NOT NULL DEFAULT false;
21 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS portfolio_public boolean NOT NULL DEFAULT false;
22 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS theme_preference text NOT NULL DEFAULT 'system';
23 |
24 | -- 4. Column Additions – Production Readiness
25 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS language_preference text NOT NULL DEFAULT 'en';
26 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS tos_accepted_at timestamptz;
27 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS notification_preferences jsonb NOT NULL DEFAULT '{"muted_courses
28 | ALTER TABLE submissions ADD COLUMN IF NOT EXISTS plagiarism_score numeric;
29 |
30 | -- 5. CHECK constraints on new columns
31 | ALTER TABLE student_gamification ADD CONSTRAINT chk_streak_freezes_range CHECK (streak_freezes_available >= 0
32 | ALTER TABLE profiles ADD CONSTRAINT chk_theme_preference CHECK (theme_preference IN ('light', 'dark', 'system'
33 | ALTER TABLE profiles ADD CONSTRAINT chk_language_preference CHECK (language_preference IN ('en', 'ur', 'ar'));
34 | ALTER TABLE submissions ADD CONSTRAINT chk_plagiarism_score_range CHECK (plagiarism_score IS NULL OR (plagiari
35 |

```

FILE: supabase/migrations/20260223100000_add_grade_trigger_for_attainment_rollup.sql

TYPE: .sql | LINES: 1-56 | SHA256: cd5f012a5afe0271d38c3966af1efdc67dc26cc2363391dc4689d4e3d5ee5dd2

```

1 | -- =====
2 | -- Migration: Grade Insert/Update Trigger for Attainment Rollup
3 | -- =====
4 | -- When a grade is inserted or updated, this trigger calls the
5 | -- calculate-attainment-rollup Edge Function via pg_net to cascade
6 | -- evidence generation and outcome attainment recalculation through
7 | -- the CLO !' PLO !' ILO chain.
8 | --
9 | -- Requires: pg_net extension (enabled in earlier migration)
10 | -- =====
11 |
12 | CREATE OR REPLACE FUNCTION public.trigger_attainment_rollup()
13 | RETURNS trigger
14 | LANGUAGE plpgsql
15 | SECURITY DEFINER
16 | AS $$
17 | DECLARE
18 |   _supabase_url text;
19 |   _service_role_key text;
20 |   _edge_function_url text;
21 |   _request_id bigint;
22 | BEGIN
23 |   -- Read configuration from app settings (set via Supabase Dashboard or vault)
24 |   _supabase_url := coalesce(
25 |     current_setting('app.settings.supabase_url', true),
26 |     'https://cdlgtbvxlxjpcddjazzx.supabase.co'
27 |   );
28 |   _service_role_key := current_setting('app.settings.service_role_key', true);
29 |
30 |   _edge_function_url := _supabase_url || '/functions/v1/calculate-attainment-rollup';
31 |
32 |   -- Fire-and-forget HTTP POST via pg_net.
33 |   -- If pg_net or the Edge Function fails, we do NOT block the grade insert/update.
34 |   BEGIN
35 |     SELECT net.http_post(
36 |       url := _edge_function_url,
37 |       body := jsonb_build_object('grade_id', NEW.id),
38 |       headers := jsonb_build_object(
39 |         'Content-Type', 'application/json',
40 |         'Authorization', 'Bearer ' || _service_role_key
41 |       )
42 |     ) INTO _request_id;
43 |   EXCEPTION WHEN OTHERS THEN
44 |     -- Log the error but never block the grade operation
45 |     RAISE WARNING 'trigger_attainment_rollup: pg_net call failed - %', SQLERRM;
46 |   END;
47 |
48 |   RETURN NEW;
49 | END;
50 | $$;
51 | -- Attach trigger to grades table: fires after insert or update
52 | CREATE TRIGGER on_grade_insert_or_update
53 | AFTER INSERT OR UPDATE ON public.grades
54 | FOR EACH ROW
55 | EXECUTE FUNCTION public.trigger_attainment_rollup();
56 |

```

FILE: supabase/migrations/20260312000001_create_login_attempts_table.sql

TYPE: .sql | LINES: 1-32 | SHA256: c0ac2c7fbec3cb5455385e19cca94c5892d7b02bda20c46d9d8dbbcfccca29688

```

1 | -----
2 | -- Login Attempts Table – server-side rate limiting for authentication
3 | -----
4 | -- Tracks failed login attempts per email. After MAX_ATTEMPTS consecutive
5 | -- failures the email is locked for LOCKOUT_DURATION (15 minutes).
6 | -- Only accessible via service_role – no client access.
7 | -----
8 |
9 | CREATE TABLE IF NOT EXISTS login_attempts (
10 |   email text PRIMARY KEY,
11 |   attempt_count integer NOT NULL DEFAULT 0,
12 |   locked_until timestamptz,
13 |   updated_at timestamptz NOT NULL DEFAULT now()
14 | );
15 | -- Index for cleanup queries (find expired locks)
16 | CREATE INDEX IF NOT EXISTS idx_login_attempts_locked_until
17 | ON login_attempts (locked_until)
18 | WHERE locked_until IS NOT NULL;
19 | -- Enable RLS – service_role only (no client access)
20 | ALTER TABLE login_attempts ENABLE ROW LEVEL SECURITY;
21 | -- Service role bypasses RLS by default, so we only need to ensure
22 | -- no authenticated/anon users can access this table.
23 | -- An explicit deny-all policy for authenticated users:

```

```

24 | CREATE POLICY "deny_all_authenticated" ON login_attempts
25 |   FOR ALL TO authenticated
26 |   USING (false)
27 |   WITH CHECK (false);
28 | CREATE POLICY "deny_all_anon" ON login_attempts
29 |   FOR ALL TO anon
30 |   USING (false)
31 |   WITH CHECK (false);
32 |

```

FILE: supabase/

migrations/20260312000002_xp_transactions_reference_id_text_and_unique.sql

TYPE: .sql | LINES: 1-12 | SHA256: 0101c5babc0ad388a0d6b10c2682f55e43339978e2372d7fb8dbec311f040d5b

```

1 | -- Migrate xp_transactions.reference_id from uuid to text so it can store
2 | -- both UUIDs (assignment IDs) and deterministic idempotency keys like
3 | -- "login:<student_id>:<date>".
4 | ALTER TABLE public.xp_transactions
5 |   ALTER COLUMN reference_id TYPE text USING reference_id::text;
6 | -- Add a unique constraint on (student_id, reference_id) to enforce idempotency
7 | -- atomically at the DB level, preventing race-condition duplicates.
8 | -- NULLs are excluded (multiple NULL reference_ids per student are allowed).
9 | CREATE UNIQUE INDEX IF NOT EXISTS idx_xp_transactions_student_reference
10 |   ON public.xp_transactions (student_id, reference_id)
11 |   WHERE reference_id IS NOT NULL;
12 |

```

FILE: supabase/migrations/20260313131408_create_onboarding_questions_table.sql

TYPE: .sql | LINES: 1-27 | SHA256: 5383aea9949b7e70797fcec5187cb3b28df701f1f3bf4097f249eefeea3c696f

```

1 | CREATE TABLE onboarding_questions (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   institution_id UUID NOT NULL REFERENCES institutions(id),
4 |   assessment_type VARCHAR(20) NOT NULL CHECK (assessment_type IN (
5 |     'personality', 'learning_style', 'baseline', 'self_efficacy', 'study_strategy'
6 |   )),
7 |   question_text TEXT NOT NULL,
8 |   dimension VARCHAR(30) CHECK (dimension IN (
9 |     'openness', 'conscientiousness', 'extraversion', 'agreeableness', 'neuroticism'
10 |   )),
11 |   weight SMALLINT CHECK (weight IN (-1, 1)),
12 |   options JSONB,
13 |   correct_option SMALLINT CHECK (correct_option >= 0 AND correct_option <= 3),
14 |   clo_id UUID REFERENCES learning_outcomes(id),
15 |   course_id UUID REFERENCES courses(id),
16 |   difficulty_level VARCHAR(10) CHECK (difficulty_level IN ('easy', 'medium', 'hard')),
17 |   sort_order INTEGER NOT NULL DEFAULT 0,
18 |   is_active BOOLEAN NOT NULL DEFAULT true,
19 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
20 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
21 | );
22 |
23 | CREATE INDEX idx_onboarding_questions_type ON onboarding_questions (institution_id, assessment_type, is_active)
24 | CREATE INDEX idx_onboarding_questions_course ON onboarding_questions (course_id) WHERE assessment_type = 'base
25 |
26 | ALTER TABLE onboarding_questions ENABLE ROW LEVEL SECURITY;;
27 |

```

FILE: supabase/migrations/20260313131437_create_onboarding_responses_table.sql

TYPE: .sql | LINES: 1-15 | SHA256: 3361b1c3f58084b3d9e7e6c3a48160421cffbc2471de3d8ee5d0723695e86064

```

1 | CREATE TABLE onboarding_responses (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   question_id UUID NOT NULL REFERENCES onboarding_questions(id),
5 |   assessment_version INTEGER NOT NULL DEFAULT 1,
6 |   selected_option SMALLINT NOT NULL,
7 |   score_contribution NUMERIC(5,2),
8 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
9 |   UNIQUE (student_id, question_id, assessment_version)
10 | );
11 |
12 | CREATE INDEX idx_onboarding_responses_student ON onboarding_responses (student_id, assessment_version);
13 |
14 | ALTER TABLE onboarding_responses ENABLE ROW LEVEL SECURITY;;
15 |

```

FILE: supabase/migrations/20260313131517_create_onboarding_progress_table.sql

TYPE: .sql | LINES: 1-26 | SHA256: 17c101e5a9f3db7fea57664fc8bec2fe274a39c3e175ab78b3e9123a508b098b

```

1 | CREATE TABLE onboarding_progress (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   current_step VARCHAR(30) NOT NULL DEFAULT 'welcome' CHECK (current_step IN (
5 |     'welcome', 'personality', 'self_efficacy', 'learning_style', 'study_strategy',
6 |     'baseline_select', 'baseline_test', 'summary'
7 |   )),
8 |   personality_completed BOOLEAN NOT NULL DEFAULT false,
9 |   learning_style_completed BOOLEAN NOT NULL DEFAULT false,
10 |   self_efficacy_completed BOOLEAN NOT NULL DEFAULT false,
11 |   study_strategy_completed BOOLEAN NOT NULL DEFAULT false,
12 |   baseline_completed BOOLEAN NOT NULL DEFAULT false,
13 |   baseline_course_ids UUID[] DEFAULT '{}',
14 |   skipped_sections TEXT[] DEFAULT '{}',
15 |   assessment_version INTEGER NOT NULL DEFAULT 1,
16 |   day1_completed BOOLEAN NOT NULL DEFAULT false,
17 |   micro_assessment_day INTEGER NOT NULL DEFAULT 0,
18 |   micro_assessment_dismissals INTEGER NOT NULL DEFAULT 0,
19 |   profile_completeness INTEGER NOT NULL DEFAULT 0,
20 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
21 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now(),
22 |   UNIQUE (student_id)
23 | );

```



```
24 |
25 | ALTER TABLE onboarding_progress ENABLE ROW LEVEL SECURITY;;
26 |
```

FILE: supabase/migrations/20260313131559_create_student_profiles_table.sql

TYPE: .sql | LINES: 1-20 | SHA256: 4e89464cd4bd6db834f9f9b3e580f5a2f2b6ec4d865bf686f007abf640b3159a

```
1 | CREATE TABLE student_profiles (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   institution_id UUID NOT NULL REFERENCES institutions(id),
5 |   personality_traits JSONB,
6 |   learning_style JSONB,
7 |   self_efficacy JSONB,
8 |   study_strategies JSONB,
9 |   profile_completeness INTEGER NOT NULL DEFAULT 0 CHECK (profile_completeness >= 0 AND profile_completeness <=
10 |   assessment_version INTEGER NOT NULL DEFAULT 1,
11 |   completed_at TIMESTAMPTZ NOT NULL DEFAULT now(),
12 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
13 |   UNIQUE (student_id, assessment_version)
14 | );
15 |
16 | CREATE INDEX idx_student_profiles_student ON student_profiles (student_id, assessment_version DESC);
17 | CREATE INDEX idx_student_profiles_institution ON student_profiles (institution_id);
18 |
19 | ALTER TABLE student_profiles ENABLE ROW LEVEL SECURITY;;
20 |
```

FILE: supabase/migrations/20260313131641_create_baseline_attainment_table.sql

TYPE: .sql | LINES: 1-18 | SHA256: 6100b5e0d8bb6ba74f442660f4a075609a3c9117778d6379f63816370835be68

```
1 | CREATE TABLE baseline_attainment (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   course_id UUID NOT NULL REFERENCES courses(id),
5 |   clo_id UUID NOT NULL REFERENCES learning_outcomes(id),
6 |   score NUMERIC(5,2) NOT NULL CHECK (score >= 0 AND score <= 100),
7 |   question_count INTEGER NOT NULL,
8 |   correct_count INTEGER NOT NULL,
9 |   assessment_version INTEGER NOT NULL DEFAULT 1,
10 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
11 |   UNIQUE (student_id, course_id, clo_id)
12 | );
13 |
14 | CREATE INDEX idx_baseline_attainment_student ON baseline_attainment (student_id, course_id);
15 | CREATE INDEX idx_baseline_attainment_course ON baseline_attainment (course_id, clo_id);
16 |
17 | ALTER TABLE baseline_attainment ENABLE ROW LEVEL SECURITY;;
18 |
```

FILE: supabase/migrations/20260313131716_create_baseline_test_config_table.sql

TYPE: .sql | LINES: 1-12 | SHA256: b782994837a3634b93aaad51dcfebf48001822fae9d24c557663d088ed1ca015

```
1 | CREATE TABLE baseline_test_config (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   course_id UUID NOT NULL REFERENCES courses(id) UNIQUE,
4 |   time_limit_minutes INTEGER NOT NULL DEFAULT 15 CHECK (time_limit_minutes >= 5 AND time_limit_minutes <= 60),
5 |   is_active BOOLEAN NOT NULL DEFAULT false,
6 |   min_questions_per_clo INTEGER NOT NULL DEFAULT 2,
7 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
8 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
9 | );
10 |
11 | ALTER TABLE baseline_test_config ENABLE ROW LEVEL SECURITY;;
12 |
```

FILE: supabase/migrations/20260313131746_create_micro_assessment_schedule_table.sql

TYPE: .sql | LINES: 1-20 | SHA256: 5fbd985966ae1eb9335ca6f9ebac41596374d6f52c22a63d0663ce25cda41bc8

```
1 | CREATE TABLE micro_assessment_schedule (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   scheduled_day INTEGER NOT NULL CHECK (scheduled_day >= 1 AND scheduled_day <= 14),
5 |   assessment_type VARCHAR(20) NOT NULL CHECK (assessment_type IN (
6 |     'personality', 'self_efficacy', 'study_strategy', 'learning_style', 'baseline_prompt'
7 |   )),
8 |   question_ids UUID[] NOT NULL DEFAULT '{}',
9 |   status VARCHAR(20) NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'completed', 'skipped', 'dismissive')),
10 |   dismissal_count INTEGER NOT NULL DEFAULT 0,
11 |   scheduled_at DATE NOT NULL,
12 |   completed_at TIMESTAMPTZ,
13 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
14 |   UNIQUE (student_id, scheduled_day)
15 | );
16 |
17 | CREATE INDEX idx_micro_assessment_schedule_student ON micro_assessment_schedule (student_id, status, scheduled
18 |
19 | ALTER TABLE micro_assessment_schedule ENABLE ROW LEVEL SECURITY;;
20 |
```

FILE: supabase/migrations/20260313131817_create_starter_week_sessions_table.sql

TYPE: .sql | LINES: 1-19 | SHA256: 2c2886743b209d8c4c75e8939210c22099f8464b044b209bec6e3faa3844407b

```
1 | CREATE TABLE starter_week_sessions (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   course_id UUID REFERENCES courses(id),
5 |   session_type VARCHAR(20) NOT NULL CHECK (session_type IN ('reading', 'practice', 'review', 'exploration')),
6 |   suggested_date DATE NOT NULL,
7 |   suggested_time_slot VARCHAR(10) NOT NULL CHECK (suggested_time_slot IN ('morning', 'afternoon', 'evening')),
8 |   duration_minutes INTEGER NOT NULL CHECK (duration_minutes >= 25 AND duration_minutes <= 50),
9 |   description TEXT NOT NULL,
10 |   status VARCHAR(20) NOT NULL DEFAULT 'suggested' CHECK (status IN ('suggested', 'accepted', 'modified', 'dism
```

```

11 | planner_entry_id UUID,
12 | created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
13 | updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
14 | );
15 |
16 | CREATE INDEX idx_starter_week_sessions_student ON starter_week_sessions (student_id, status);
17 |
18 | ALTER TABLE starter_week_sessions ENABLE ROW LEVEL SECURITY;;
19 |

```

FILE: supabase/migrations/20260313131900_create_goal_suggestions_table.sql

TYPE: .sql | LINES: 1-20 | SHA256: f5600101f3135738fa6a713f56fbb45fd20909a97dd14824a85d7c079c76bfff6

```

1 | CREATE TABLE goal_suggestions (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id),
4 |   week_start DATE NOT NULL,
5 |   goal_text TEXT NOT NULL,
6 |   smart_specific TEXT,
7 |   smart_measurable TEXT,
8 |   smart_achievable TEXT,
9 |   smart_relevant TEXT,
10 |   smart_timebound DATE,
11 |   difficulty VARCHAR(10) NOT NULL CHECK (difficulty IN ('easy', 'moderate', 'ambitious')),
12 |   cohort_completion_rate NUMERIC(5,2),
13 |   status VARCHAR(20) NOT NULL DEFAULT 'suggested' CHECK (status IN ('suggested', 'accepted', 'modified', 'dism
14 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now()
15 | );
16 |
17 | CREATE INDEX idx_goal_suggestions_student ON goal_suggestions (student_id, week_start, status);
18 |
19 | ALTER TABLE goal_suggestions ENABLE ROW LEVEL SECURITY;;
20 |

```

FILE: supabase/migrations/20260313132109_create_onboarding_rols_policies.sql

TYPE: .sql | LINES: 1-94 | SHA256: 9f6b55cd6f593277d1734ecb5317c7c069ee1140af874f2f82ff8236aef73b7f

```

1 | -- onboarding_questions RLS
2 | CREATE POLICY "questions_student_read" ON onboarding_questions
3 |   FOR SELECT USING (
4 |     auth_user_role() = 'student'
5 |     AND institution_id = auth_institution_id()
6 |     AND is_active = true
7 |   );
8 |
9 | CREATE POLICY "questions_teacher_manage" ON onboarding_questions
10 |   FOR ALL USING (
11 |     auth_user_role() = 'teacher'
12 |     AND assessment_type = 'baseline'
13 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
14 |   );
15 |
16 | CREATE POLICY "questions_admin_all" ON onboarding_questions
17 |   FOR ALL USING (
18 |     auth_user_role() = 'admin'
19 |     AND institution_id = auth_institution_id()
20 |   );
21 |
22 | -- onboarding_responses RLS
23 | CREATE POLICY "responses_student_own" ON onboarding_responses
24 |   FOR ALL USING (student_id = auth.uid());
25 |
26 | -- onboarding_progress RLS
27 | CREATE POLICY "progress_student_own" ON onboarding_progress
28 |   FOR ALL USING (student_id = auth.uid());
29 |
30 | -- student_profiles RLS
31 | CREATE POLICY "profiles_student_own" ON student_profiles
32 |   FOR ALL USING (student_id = auth.uid());
33 |
34 | CREATE POLICY "profiles_admin_read" ON student_profiles
35 |   FOR SELECT USING (
36 |     auth_user_role() = 'admin'
37 |     AND institution_id = auth_institution_id()
38 |   );
39 |
40 | -- baseline_attainment RLS
41 | CREATE POLICY "baseline_student_own" ON baseline_attainment
42 |   FOR SELECT USING (student_id = auth.uid());
43 |
44 | CREATE POLICY "baseline_teacher_read" ON baseline_attainment
45 |   FOR SELECT USING (
46 |     auth_user_role() = 'teacher'
47 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
48 |   );
49 |
50 | CREATE POLICY "baseline_admin_read" ON baseline_attainment
51 |   FOR SELECT USING (
52 |     auth_user_role() = 'admin'
53 |     AND course_id IN (
54 |       SELECT c.id FROM courses c
55 |       JOIN programs p ON c.program_id = p.id
56 |       WHERE p.institution_id = auth_institution_id()
57 |     )
58 |   );
59 |
60 | -- baseline_test_config RLS
61 | CREATE POLICY "config_student_read" ON baseline_test_config
62 |   FOR SELECT USING (
63 |     auth_user_role() = 'student'
64 |     AND course_id IN (SELECT course_id FROM student_courses WHERE student_id = auth.uid())
65 |   );
66 |
67 | CREATE POLICY "config_teacher_manage" ON baseline_test_config

```

```

68 | FOR ALL USING (
69 |   auth_user_role() = 'teacher'
70 |   AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
71 | );
72 |
73 | CREATE POLICY "config_admin_all" ON baseline_test_config
74 |   FOR ALL USING (
75 |     auth_user_role() = 'admin'
76 |     AND course_id IN (
77 |       SELECT c.id FROM courses c
78 |       JOIN programs p ON c.program_id = p.id
79 |       WHERE p.institution_id = auth.institution_id()
80 |     )
81 |   );
82 |
83 | -- micro_assessment_schedule RLS
84 | CREATE POLICY "micro_schedule_student_own" ON micro_assessment_schedule
85 |   FOR ALL USING (student_id = auth.uid());
86 |
87 | -- starter_week_sessions RLS
88 | CREATE POLICY "starter_sessions_student_own" ON starter_week_sessions
89 |   FOR ALL USING (student_id = auth.uid());
90 |
91 | -- goal_suggestions RLS
92 | CREATE POLICY "goal_suggestions_student_own" ON goal_suggestions
93 |   FOR ALL USING (student_id = auth.uid());
94 |

```

FILE: supabase/migrations/20260313132537_seed_onboarding_questions.sql

TYPE: .sql | LINES: 1-164 | SHA256: 315944adfb96f8232b1715778c946bd34845ed468ca478a614426ad2b30ba2cb

```

1 | -- Step 1: Alter dimension CHECK constraint to support self-efficacy and study strategy dimensions
2 | ALTER TABLE onboarding_questions DROP CONSTRAINT IF EXISTS onboarding_questions_dimension_check;
3 | ALTER TABLE onboarding_questions ADD CONSTRAINT onboarding_questions_dimension_check
4 |   CHECK (dimension::text = ANY (ARRAY[
5 |     'openness', 'conscientiousness', 'extraversion', 'agreeableness', 'neuroticism',
6 |     'general_academic', 'course_specific', 'self_regulated_learning',
7 |     'time_management', 'elaboration', 'self_testing', 'help_seeking'
8 |   ]::text[]));
9 |
10 | -- Step 2: Seed default onboarding questions using a CTE for institution_id
11 | WITH inst AS (
12 |   SELECT id FROM institutions LIMIT 1
13 | )
14 |
15 | -- =====
16 | -- Big Five Personality Questions (25 total, 5 per dimension)
17 | -- Based on IPIP (International Personality Item Pool) items
18 | -- =====
19 | INSERT INTO onboarding_questions (institution_id, assessment_type, question_text, dimension, weight, sort_order)
20 | SELECT inst.id, q.assessment_type, q.question_text, q.dimension, q.weight, q.sort_order
21 | FROM inst, (VALUES
22 |   -- Openness (5 questions)
23 |   ('personality', 'I have a vivid imagination.', 'openness', 1, 1),
24 |   ('personality', 'I am not interested in abstract ideas.', 'openness', -1, 2),
25 |   ('personality', 'I enjoy hearing new ideas.', 'openness', 1, 3),
26 |   ('personality', 'I tend to vote for conservative political candidates.', 'openness', -1, 4),
27 |   ('personality', 'I enjoy thinking about things.', 'openness', 1, 5),
28 |   -- Conscientiousness (5 questions)
29 |   ('personality', 'I am always prepared.', 'conscientiousness', 1, 6),
30 |   ('personality', 'I leave my belongings around.', 'conscientiousness', -1, 7),
31 |   ('personality', 'I pay attention to details.', 'conscientiousness', 1, 8),
32 |   ('personality', 'I make a mess of things.', 'conscientiousness', -1, 9),
33 |   ('personality', 'I get chores done right away.', 'conscientiousness', 1, 10),
34 |   -- Extraversion (5 questions)
35 |   ('personality', 'I am the life of the party.', 'extraversion', 1, 11),
36 |   ('personality', 'I don't talk a lot.', 'extraversion', -1, 12),
37 |   ('personality', 'I feel comfortable around people.', 'extraversion', 1, 13),
38 |   ('personality', 'I keep in the background.', 'extraversion', -1, 14),
39 |   ('personality', 'I start conversations.', 'extraversion', 1, 15),
40 |   -- Agreeableness (5 questions)
41 |   ('personality', 'I am interested in people.', 'agreeableness', 1, 16),
42 |   ('personality', 'I insult people.', 'agreeableness', -1, 17),
43 |   ('personality', 'I sympathize with others' feelings.', 'agreeableness', 1, 18),
44 |   ('personality', 'I am not interested in other people's problems.', 'agreeableness', -1, 19),
45 |   ('personality', 'I have a soft heart.', 'agreeableness', 1, 20),
46 |   -- Neuroticism (5 questions)
47 |   ('personality', 'I get stressed out easily.', 'neuroticism', 1, 21),
48 |   ('personality', 'I am relaxed most of the time.', 'neuroticism', -1, 22),
49 |   ('personality', 'I worry about things.', 'neuroticism', 1, 23),
50 |   ('personality', 'I seldom feel blue.', 'neuroticism', -1, 24),
51 |   ('personality', 'I get upset easily.', 'neuroticism', 1, 25)
52 | ) AS q(assessment_type, question_text, dimension, weight, sort_order)
53 | ON CONFLICT DO NOTHING;
54 |
55 | -- =====
56 | -- VARK Learning Style Questions (16 total, 4 per modality)
57 | -- Based on standard VARK questionnaire items
58 | -- =====
59 | WITH inst AS (
60 |   SELECT id FROM institutions LIMIT 1
61 | )
62 | INSERT INTO onboarding_questions (institution_id, assessment_type, question_text, options, sort_order)
63 | SELECT inst.id, 'learning_style', q.question_text, q.options::jsonb, q.sort_order
64 | FROM inst, (VALUES
65 |   ('When learning how to use a new software application, I prefer to:',
66 |    '{"option_text": "Watch a video demonstration", "modality": "visual"}', '{"option_text": "Listen to someone"',
67 |    101),
68 |   ('When I need to remember directions to a new place, I:',
69 |    '{"option_text": "Look at a map or use GPS with a visual display", "modality": "visual"}', '{"option_text":',
70 |    102),
71 |   ('When studying for an exam, I find it most helpful to:',
72 |    '{"option_text": "Review diagrams, charts, and highlighted notes", "modality": "visual"}', '{"option_text":',
73 |    103),

```

```

74 | ('When a teacher explains a new concept, I understand best when they:',
75 |   '{"option_text": "Draw a diagram or show a visual example", "modality": "visual", {"option_text": "Explai
76 | 104),
77 | ('When choosing a restaurant, I prefer to:',
78 |   '{"option_text": "Look at photos of the food and ambiance online", "modality": "visual", {"option_text":
79 | 105),
80 | ('When assembling furniture or equipment, I prefer to:',
81 |   '{"option_text": "Follow the illustrated diagrams", "modality": "visual", {"option_text": "Have someone t
82 | 106),
83 | ('When I want to learn about a historical event, I prefer to:',
84 |   '{"option_text": "Watch a documentary with visual footage", "modality": "visual", {"option_text": "Listen
85 | 107),
86 | ('When giving a presentation, I rely most on:',
87 |   '{"option_text": "Slides with images, graphs, and visual aids", "modality": "visual", {"option_text": "Sp
88 | 108),
89 | ('When I need to understand a complex process, I prefer:',
90 |   '{"option_text": "A flowchart or process diagram", "modality": "visual", {"option_text": "A verbal walkth
91 | 109),
92 | ('When learning a new language, I find it easiest to:',
93 |   '{"option_text": "Use flashcards with images and visual associations", "modality": "visual", {"option_tex
94 | 110),
95 | ('When I receive feedback on my work, I prefer it:',
96 |   '{"option_text": "Marked up visually with highlights and annotations", "modality": "visual", {"option_tex
97 | 111),
98 | ('When planning a project, I prefer to:',
99 |   '{"option_text": "Create a visual timeline or mind map", "modality": "visual", {"option_text": "Talk thro
100 | 112),
101 | ('When trying to remember something important, I:',
102 |   '{"option_text": "Visualize it in my mind as an image or scene", "modality": "visual", {"option_text": "R
103 | 113),
104 | ('When choosing an online course, I look for one that has:',
105 |   '{"option_text": "Rich visual content like infographics and animations", "modality": "visual", {"option_t
106 | 114),
107 | ('When explaining something to a friend, I tend to:',
108 |   '{"option_text": "Draw a picture or show them a diagram", "modality": "visual", {"option_text": "Describe
109 | 115),
110 | ('When I encounter a problem I cannot solve, I:',
111 |   '{"option_text": "Look for visual examples of similar solved problems", "modality": "visual", {"option_te
112 | 116)
113 | ) AS q(question_text, options, sort_order)
114 | ON CONFLICT DO NOTHING;
115 |
116 | -- =====
117 | -- Self-Efficacy Scale (6 items)
118 | -- Based on Bandura (1997) academic self-efficacy constructs
119 | -- Domains: general_academic, course_specific, self_regulated_learning
120 | -- =====
121 | WITH inst AS (
122 |   SELECT id FROM institutions LIMIT 1
123 | )
124 | INSERT INTO onboarding_questions (institution_id, assessment_type, question_text, dimension, weight, sort_orde
125 | SELECT inst.id, 'self_efficacy', q.question_text, q.dimension, q.weight, q.sort_order
126 | FROM inst, (VALUES
127 |   -- General Academic (2 items)
128 |   ('I am confident I can understand the most complex material presented in my courses.', 'general_academic', 1
129 |   ('I am confident I can do an excellent job on assignments and tests in my courses.', 'general_academic', 1,
130 |   -- Course-Specific (2 items)
131 |   ('I am confident I can learn the content taught in even the most difficult courses.', 'course_specific', 1,
132 |   ('I am confident I can master the skills being taught in my classes.', 'course_specific', 1, 204),
133 |   -- Self-Regulated Learning (2 items)
134 |   ('I am confident I can organize my study time effectively to accomplish my academic goals.', 'self_regulated
135 |   ('I am confident I can motivate myself to complete academic work even when I find it uninteresting.', 'self_
136 | ) AS q(question_text, dimension, weight, sort_order)
137 | ON CONFLICT DO NOTHING;
138 |
139 | -- =====
140 | -- Study Strategy Inventory (8 items, 2 per dimension)
141 | -- Based on MSLQ (Motivated Strategies for Learning Questionnaire)
142 | -- Dimensions: time_management, elaboration, self_testing, help_seeking
143 | -- =====
144 | WITH inst AS (
145 |   SELECT id FROM institutions LIMIT 1
146 | )
147 | INSERT INTO onboarding_questions (institution_id, assessment_type, question_text, dimension, weight, sort_orde
148 | SELECT inst.id, 'study_strategy', q.question_text, q.dimension, q.weight, q.sort_order
149 | FROM inst, (VALUES
150 |   -- Time Management (2 items)
151 |   ('I set aside regular times each week for studying and stick to my schedule.', 'time_management', 1, 301),
152 |   ('I plan my study sessions in advance so I can cover all the material before exams.', 'time_management', 1,
153 |   -- Elaboration (2 items)
154 |   ('When studying, I try to connect new information to what I already know.', 'elaboration', 1, 303),
155 |   ('I try to relate ideas from one course to ideas from other courses when possible.', 'elaboration', 1, 304),
156 |   -- Self-Testing (2 items)
157 |   ('I test myself on course material to check my understanding before exams.', 'self_testing', 1, 305),
158 |   ('I make up practice questions or use flashcards to prepare for tests.', 'self_testing', 1, 306),
159 |   -- Help-Seeking (2 items)
160 |   ('When I don't understand something, I ask the instructor or a classmate for help.', 'help_seeking', 1, 307
161 |   ('I make use of office hours, tutoring services, or study groups when I need support.', 'help_seeking', 1, 3
162 | ) AS q(question_text, dimension, weight, sort_order)
163 | ON CONFLICT DO NOTHING;
164 |

```

FILE: supabase/migrations/20260314_micro_assessment_cron.sql

TYPE: .sql | LINES: 1-44 | SHA256: 0d2613ed9ec8969fbbdc64ca15b2d66b3194bda6fafa02b1e426130106cc61ea

```

1 | -- =====
2 | -- pg_cron job: Check for due micro-assessments daily
3 | -- Updates scheduled_at dates and populates question_ids
4 | -- Task 14.2
5 | -- =====
6 |
7 | -- Enable pg_cron if not already enabled
8 | CREATE EXTENSION IF NOT EXISTS pg_cron;
9 | -- Daily job at 6:00 AM UTC to update micro-assessment scheduled_at dates

```

```

10 | -- and populate question_ids for today's pending assessments
11 | SELECT cron.schedule(
12 |   'update-micro-assessment-schedule',
13 |   '0 6 * * *',
14 |   $$
15 |   -- Populate question_ids for today's pending micro-assessments that have empty question_ids
16 |   UPDATE micro_assessment_schedule mas
17 |   SET question_ids = (
18 |     SELECT COALESCE(
19 |       array_agg(q.id ORDER BY q.sort_order),
20 |       '{}'::uuid[]
21 |     )
22 |   FROM (
23 |     SELECT oq.id, oq.sort_order
24 |     FROM onboarding_questions oq
25 |     JOIN profiles p ON p.id = mas.student_id
26 |     WHERE oq.assessment_type = mas.assessment_type
27 |     AND oq.institution_id = p.institution_id
28 |     AND oq.is_active = true
29 |     ORDER BY oq.sort_order
30 |     LIMIT CASE
31 |       WHEN mas.assessment_type = 'personality' THEN 3
32 |       WHEN mas.assessment_type = 'self_efficacy' THEN 2
33 |       WHEN mas.assessment_type = 'study_strategy' THEN 2
34 |       WHEN mas.assessment_type = 'learning_style' THEN 4
35 |       ELSE 2
36 |     END
37 |   ) q
38 | )
39 | WHERE mas.status = 'pending'
40 | AND mas.scheduled_at = (now() AT TIME ZONE 'UTC')::date
41 | AND mas.question_ids = '{}'::uuid[];
42 | $$
43 | );
44 |

```

FILE: supabase/migrations/20260319133117_create_wellness_habit_tables.sql

TYPE: .sql | LINES: 1-37 | SHA256: 84d0672e0958fc3ecd492f0be96fdcc97490bff68aa8fa95f9db48d031bfda6

```

1 | -- 1.1: Create wellness_habit_type enum
2 | CREATE TYPE wellness_habit_type AS ENUM ('meditation', 'hydration', 'exercise', 'sleep');
3 |
4 | -- 1.2: Create wellness_habit_logs table
5 | CREATE TABLE wellness_habit_logs (
6 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
7 |   student_id uuid NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
8 |   date date NOT NULL,
9 |   wellness_type wellness_habit_type NOT NULL,
10 |   value numeric,
11 |   completed_at timestamptz NOT NULL DEFAULT now(),
12 |   created_at timestamptz NOT NULL DEFAULT now(),
13 |   UNIQUE (student_id, date, wellness_type)
14 | );
15 |
16 | CREATE INDEX idx_wellness_habit_logs_student_date ON wellness_habit_logs(student_id, date);
17 | CREATE INDEX idx_wellness_habit_logs_student_type_date ON wellness_habit_logs(student_id, wellness_type, date);
18 |
19 | -- 1.3: Create student_wellness_preferences table
20 | CREATE TABLE student_wellness_preferences (
21 |   id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
22 |   student_id uuid NOT NULL REFERENCES profiles(id) ON DELETE CASCADE UNIQUE,
23 |   enabled_habits text[] NOT NULL DEFAULT '{}',
24 |   parent_visibility boolean NOT NULL DEFAULT false,
25 |   habit_targets jsonb NOT NULL DEFAULT '{}',
26 |   reminder_times jsonb NOT NULL DEFAULT '{}',
27 |   dismissed_onboarding_tips text[] NOT NULL DEFAULT '{}',
28 |   created_at timestamptz NOT NULL DEFAULT now(),
29 |   updated_at timestamptz NOT NULL DEFAULT now()
30 | );
31 |
32 | -- 1.4: Add wellness_xp_amount to institution_settings
33 | ALTER TABLE institution_settings ADD COLUMN IF NOT EXISTS wellness_xp_amount integer NOT NULL DEFAULT 5;
34 |
35 | -- 1.5: Create index on existing habit_tracking table
36 | CREATE INDEX IF NOT EXISTS idx_habit_tracking_student_date ON habit_tracking(student_id, habit_date);
37 |

```

FILE: supabase/migrations/20260319133131_wellness_rls_policies.sql

TYPE: .sql | LINES: 1-44 | SHA256: 2fe397b4fc21acd1f9b73ac85d3de235ee83401db4125574b7f01a82ffb72d23

```

1 | -- Enable RLS
2 | ALTER TABLE wellness_habit_logs ENABLE ROW LEVEL SECURITY;
3 | ALTER TABLE student_wellness_preferences ENABLE ROW LEVEL SECURITY;
4 |
5 | -- 1.6: RLS for wellness_habit_logs
6 | -- Students: SELECT own logs
7 | CREATE POLICY "student_select_own_wellness_logs" ON wellness_habit_logs
8 |   FOR SELECT TO authenticated
9 |   USING (student_id = auth.uid());
10 |
11 | -- Students: INSERT own logs
12 | CREATE POLICY "student_insert_own_wellness_logs" ON wellness_habit_logs
13 |   FOR INSERT TO authenticated
14 |   WITH CHECK (student_id = auth.uid() AND auth_user_role() = 'student');
15 |
16 | -- Students: UPDATE value field only on own logs
17 | CREATE POLICY "student_update_own_wellness_logs" ON wellness_habit_logs
18 |   FOR UPDATE TO authenticated
19 |   USING (student_id = auth.uid() AND auth_user_role() = 'student')
20 |   WITH CHECK (student_id = auth.uid());
21 |
22 | -- Parents: SELECT linked student logs when parent_visibility = true
23 | CREATE POLICY "parent_read_linked_wellness_logs" ON wellness_habit_logs
24 |   FOR SELECT TO authenticated

```

```

25 | USING (
26 |     auth_user_role() = 'parent'
27 |     AND student_id IN (
28 |         SELECT psl.student_id FROM parent_student_links psl
29 |         JOIN student_wellness_preferences swp ON swp.student_id = psl.student_id
30 |         WHERE psl.parent_id = auth.uid()
31 |         AND psl.verified = true
32 |         AND swp.parent_visibility = true
33 |     )
34 | );
35 |
36 | -- No DELETE policy – append-only
37 | -- No teacher SELECT policy
38 |
39 | -- 1.7: RLS for student_wellness_preferences
40 | CREATE POLICY "student_manage_own_preferences" ON student_wellness_preferences
41 | FOR ALL TO authenticated
42 | USING (student_id = auth.uid() AND auth_user_role() = 'student')
43 | WITH CHECK (student_id = auth.uid() AND auth_user_role() = 'student');;
44 |

```

FILE: supabase/migrations/20260319133141_wellness_aggregate_stats_function.sql

TYPE: .sql | LINES: 1-19 | SHA256: 622896a3c400a3003804288338aa4823c5c623b8c152de15fcf1434867070c82

```

1 | CREATE OR REPLACE FUNCTION get_wellness_aggregate_stats(p_institution_id uuid)
2 | RETURNS TABLE (
3 |     wellness_type text,
4 |     total_logs bigint,
5 |     unique_students bigint
6 | ) AS $$
7 | BEGIN
8 |     RETURN QUERY
9 |     SELECT
10 |         whl.wellness_type::text,
11 |         COUNT(*)::bigint AS total_logs,
12 |         COUNT(DISTINCT whl.student_id)::bigint AS unique_students
13 |     FROM wellness_habit_logs whl
14 |     JOIN profiles p ON p.id = whl.student_id
15 |     WHERE p.institution_id = p_institution_id
16 |     GROUP BY whl.wellness_type;
17 | END;
18 | $$ LANGUAGE plpgsql SECURITY DEFINER;;
19 |

```

FILE: supabase/migrations/20260319200000_add_wellness_preferences_columns.sql

TYPE: .sql | LINES: 1-13 | SHA256: 1468c67755b9cc9573dd16d76e8c576897b9bbfbcc6f4a2ed409023a45f75295

```

1 | -- 16.1: Add habit_targets, reminder_times, dismissed_onboarding_tips columns
2 | -- to student_wellness_preferences table.
3 | -- These columns were included in the original table creation migration
4 | -- (20260319133117_create_wellness_habit_tables.sql), so this migration
5 | -- uses ADD COLUMN IF NOT EXISTS to be idempotent.
6 |
7 | ALTER TABLE student_wellness_preferences
8 |     ADD COLUMN IF NOT EXISTS habit_targets jsonb NOT NULL DEFAULT '{}';
9 | ALTER TABLE student_wellness_preferences
10 |     ADD COLUMN IF NOT EXISTS reminder_times jsonb NOT NULL DEFAULT '{}';
11 | ALTER TABLE student_wellness_preferences
12 |     ADD COLUMN IF NOT EXISTS dismissed_onboarding_tips text[] NOT NULL DEFAULT '{}';
13 |

```

FILE: supabase/migrations/20260320000412_create_mastery_recovery_pathways.sql

TYPE: .sql | LINES: 1-38 | SHA256: f39cd78775f5fdfcf94d6f27ffb07e15fd0ced92ef71a9423d9bbd0bc0e13b

```

1 | -- =====
2 | -- Migration: Create mastery_recovery_pathways table
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 14.1)
4 | -- =====
5 |
6 | -- =====
7 | -- mastery_recovery_pathways – Tracks recovery sessions for stuck students
8 | -- =====
9 | CREATE TABLE mastery_recovery_pathways (
10 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
11 |     institution_id UUID NOT NULL REFERENCES institutions(id),
12 |     student_id UUID NOT NULL REFERENCES profiles(id),
13 |     clo_id UUID NOT NULL REFERENCES learning_outcomes(id),
14 |     course_id UUID NOT NULL REFERENCES courses(id),
15 |     failure_count INTEGER NOT NULL DEFAULT 2,
16 |     status VARCHAR(20) NOT NULL DEFAULT 'active' CHECK (status IN ('active', 'completed', 'expired')),
17 |     ai_tutor_completed BOOLEAN NOT NULL DEFAULT false,
18 |     ai_tutor_completed_at TIMESTAMPTZ,
19 |     practice_completed BOOLEAN NOT NULL DEFAULT false,
20 |     practice_completed_at TIMESTAMPTZ,
21 |     peer_suggestion_shown BOOLEAN NOT NULL DEFAULT false,
22 |     peer_suggestion_applicable BOOLEAN NOT NULL DEFAULT true,
23 |     retry_quiz_attempt_id UUID,
24 |     retry_outcome VARCHAR(10) CHECK (retry_outcome IN ('pass', 'fail', NULL)),
25 |     activated_at TIMESTAMPTZ NOT NULL DEFAULT now(),
26 |     completed_at TIMESTAMPTZ,
27 |     expired_at TIMESTAMPTZ,
28 |     created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
29 |     updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
30 | );
31 |
32 | ALTER TABLE mastery_recovery_pathways ENABLE ROW LEVEL SECURITY;
33 |
34 | CREATE INDEX idx_recovery_student_clo ON mastery_recovery_pathways (student_id, clo_id);
35 | CREATE INDEX idx_recovery_course ON mastery_recovery_pathways (course_id, status);
36 | CREATE INDEX idx_recovery_status ON mastery_recovery_pathways (status) WHERE status = 'active';
37 | CREATE UNIQUE INDEX idx_recovery_active_unique ON mastery_recovery_pathways (student_id, clo_id) WHERE status
38 |

```


FILE: supabase/migrations/20260320000701_add_mastery_recovery_rols_policies.sql

TYPE: .sql | LINES: 1-44 | SHA256: 9680c6db6abce4330a4aea4bbe02a3aeff745638e13827b7679dfcf53ce56f6f

```
1 | -- =====
2 | -- Migration: RLS policies for mastery_recovery_pathways
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 14.2)
4 | -- =====
5 |
6 | -- =====
7 | -- mastery_recovery_pathways RLS policies
8 | -- Students: read their own recovery pathways
9 | -- Teachers: read recovery pathways for their courses
10 | -- Admins: read all within institution
11 | -- Coordinators: read for metrics dashboard
12 | -- System (Edge Functions with service role) handles INSERT/UPDATE
13 | -- =====
14 |
15 | -- Students: read their own recovery pathways
16 | CREATE POLICY "recovery_student_read" ON mastery_recovery_pathways
17 |   FOR SELECT TO authenticated
18 |   USING (student_id = auth.uid());
19 |
20 | -- Teachers: read recovery pathways for their courses
21 | CREATE POLICY "recovery_teacher_read" ON mastery_recovery_pathways
22 |   FOR SELECT TO authenticated
23 |   USING (
24 |     auth_user_role() = 'teacher'
25 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
26 |   );
27 |
28 | -- Admins: read all within institution
29 | CREATE POLICY "recovery_admin_read" ON mastery_recovery_pathways
30 |   FOR SELECT TO authenticated
31 |   USING (
32 |     auth_user_role() = 'admin'
33 |     AND institution_id = auth_institution_id()
34 |   );
35 |
36 | -- Coordinators: read for metrics dashboard
37 | CREATE POLICY "recovery_coordinator_read" ON mastery_recovery_pathways
38 |   FOR SELECT TO authenticated
39 |   USING (
40 |     auth_user_role() = 'coordinator'
41 |     AND institution_id = auth_institution_id()
42 |   );
43 | ;
44 |
```

FILE: supabase/migrations/20260320003246_add_recovery_expiry_cron.sql

TYPE: .sql | LINES: 1-47 | SHA256: a233012c95ff7eac7f4d64a9226fb1c893c8f60ed14dc047e971955d22ae2cb7

```
1 | -- =====
2 | -- Migration: Add pg_cron job to expire stale recovery sessions
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 14.9)
4 | -- =====
5 |
6 | -- Enable pg_cron extension if not already enabled
7 | CREATE EXTENSION IF NOT EXISTS pg_cron WITH SCHEMA extensions;
8 |
9 | -- =====
10 | -- Function: expire_stale_recovery_sessions
11 | -- Expires active mastery recovery pathways older than 14 days.
12 | -- Returns the count of expired sessions.
13 | -- NOTE: Teacher notification can be added later via pg_net
14 | -- HTTP call to a notification Edge Function.
15 | -- =====
16 | CREATE OR REPLACE FUNCTION expire_stale_recovery_sessions()
17 | RETURNS INTEGER
18 | LANGUAGE plpgsql
19 | SECURITY DEFINER
20 | AS $$
21 | DECLARE
22 |   expired_count INTEGER;
23 | BEGIN
24 |   UPDATE mastery_recovery_pathways
25 |   SET
26 |     status = 'expired',
27 |     expired_at = now(),
28 |     updated_at = now()
29 |   WHERE
30 |     status = 'active'
31 |     AND activated_at < now() - interval '14 days';
32 |
33 |   GET DIAGNOSTICS expired_count = ROW_COUNT;
34 |
35 |   RETURN expired_count;
36 | END;
37 | $$;
38 |
39 | -- =====
40 | -- Schedule: Run daily at midnight UTC
41 | -- =====
42 | SELECT cron.schedule(
43 |   'expire-stale-recovery-sessions',
44 |   '0 0 * * *',
45 |   $$SELECT expire_stale_recovery_sessions()$$
46 | );
47 |
```

FILE: supabase/migrations/20260320004855_create_question_bank_tables.sql

TYPE: .sql | LINES: 1-96 | SHA256: 851cbd2ebe20d475e15eeaa0529f31990d0e21f2821a257ac51e8b9cc9969c16

```
1 | -- =====
2 | -- Migration: Create question_bank, question_analytics, and quiz_generation_logs tables
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Tasks 1.1, 1.2, 1.3)
4 | -- =====
5 |
6 | -- =====
7 | -- question_bank - Centralized question storage
8 | -- =====
9 | CREATE TABLE question_bank (
10 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
11 |   institution_id UUID NOT NULL REFERENCES institutions(id),
12 |   course_id UUID NOT NULL REFERENCES courses(id),
13 |   clo_id UUID NOT NULL REFERENCES learning_outcomes(id),
14 |   bloom_level SMALLINT NOT NULL CHECK (bloom_level BETWEEN 1 AND 6),
15 |   question_type VARCHAR(20) NOT NULL CHECK (question_type IN (
16 |     'mcq', 'true_false', 'short_answer', 'fill_in_blank'
17 |   )),
18 |   question_text TEXT NOT NULL,
19 |   options JSONB,
20 |   correct_answer JSONB NOT NULL,
21 |   explanation TEXT,
22 |   difficulty_rating NUMERIC(3,1) NOT NULL CHECK (difficulty_rating BETWEEN 1.0 AND 5.0),
23 |   status VARCHAR(20) NOT NULL DEFAULT 'pending_review' CHECK (status IN (
24 |     'pending_review', 'approved', 'rejected'
25 |   )),
26 |   generation_source VARCHAR(20) NOT NULL CHECK (generation_source IN (
27 |     'ai', 'ai_edited', 'manual'
28 |   )),
29 |   source_chunks JSONB DEFAULT '[]',
30 |   labels TEXT[] DEFAULT '{}',
31 |   parent_question_id UUID REFERENCES question_bank(id),
32 |   generation_request_id UUID,
33 |   created_by UUID NOT NULL REFERENCES profiles(id),
34 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
35 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
36 | );
37 |
38 | ALTER TABLE question_bank ENABLE ROW LEVEL SECURITY;
39 |
40 | CREATE INDEX idx_qbank_course_status ON question_bank (course_id, status);
41 | CREATE INDEX idx_qbank_clo ON question_bank (clo_id);
42 | CREATE INDEX idx_qbank_bloom ON question_bank (bloom_level);
43 | CREATE INDEX idx_qbank_difficulty ON question_bank (difficulty_rating);
44 | CREATE INDEX idx_qbank_generation ON question_bank (generation_request_id);
45 |
46 | -- =====
47 | -- question_analytics - Per-question performance metrics
48 | -- =====
49 | CREATE TABLE question_analytics (
50 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
51 |   question_id UUID NOT NULL REFERENCES question_bank(id) ON DELETE CASCADE,
52 |   total_attempts INTEGER NOT NULL DEFAULT 0,
53 |   correct_count INTEGER NOT NULL DEFAULT 0,
54 |   success_rate NUMERIC(5,4) DEFAULT 0,
55 |   avg_response_time_seconds NUMERIC(8,2) DEFAULT 0,
56 |   discrimination_index NUMERIC(5,4) DEFAULT 0,
57 |   calibrated_difficulty NUMERIC(3,1),
58 |   quality_flag VARCHAR(20) CHECK (quality_flag IN (
59 |     'good', 'low_discrimination', 'too_easy', 'too_hard'
60 |   )),
61 |   last_calculated_at TIMESTAMPTZ NOT NULL DEFAULT now(),
62 |   UNIQUE (question_id)
63 | );
64 |
65 | ALTER TABLE question_analytics ENABLE ROW LEVEL SECURITY;
66 |
67 | CREATE INDEX idx_qanalytics_question ON question_analytics (question_id);
68 | CREATE INDEX idx_qanalytics_flag ON question_analytics (quality_flag) WHERE quality_flag IS NOT NULL;
69 |
70 | -- =====
71 | -- quiz_generation_logs - LLM API call monitoring for quiz generation
72 | -- =====
73 | CREATE TABLE quiz_generation_logs (
74 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
75 |   institution_id UUID NOT NULL REFERENCES institutions(id),
76 |   teacher_id UUID NOT NULL REFERENCES profiles(id),
77 |   course_id UUID NOT NULL REFERENCES courses(id),
78 |   generation_request_id UUID NOT NULL,
79 |   model_used VARCHAR(100) NOT NULL,
80 |   prompt_tokens INTEGER NOT NULL,
81 |   completion_tokens INTEGER NOT NULL,
82 |   total_tokens INTEGER NOT NULL,
83 |   latency_ms INTEGER NOT NULL,
84 |   question_count_requested INTEGER NOT NULL,
85 |   question_count_generated INTEGER NOT NULL,
86 |   chunks_retrieved INTEGER NOT NULL,
87 |   status VARCHAR(20) NOT NULL CHECK (status IN ('success', 'error', 'timeout')),
88 |   error_message TEXT,
89 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now()
90 | );
91 |
92 | ALTER TABLE quiz_generation_logs ENABLE ROW LEVEL SECURITY;
93 |
94 | CREATE INDEX idx_gen_logs_institution ON quiz_generation_logs (institution_id, created_at DESC);
95 | CREATE INDEX idx_gen_logs_course ON quiz_generation_logs (course_id);
96 |
```


FILE: supabase/migrations/20260320004906_create_verified_explanations.sql

TYPE: .sql | LINES: 1-25 | SHA256: cba202bae4113504ede660d481307a35768216aef82aec06451cc6943c654a14

```
1 | -- =====
2 | -- Migration: Create verified_explanations table
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 15.1)
4 | -- =====
5 |
6 | -- =====
7 | -- verified_explanations - Teacher-approved explanation cache
8 | -- =====
9 | CREATE TABLE verified_explanations (
10 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
11 |   institution_id UUID NOT NULL REFERENCES institutions(id),
12 |   question_id UUID NOT NULL REFERENCES question_bank(id) ON DELETE CASCADE,
13 |   explanation_text TEXT NOT NULL,
14 |   source VARCHAR(20) NOT NULL CHECK (source IN ('teacher_approved', 'teacher_edited')),
15 |   verified_by UUID NOT NULL REFERENCES profiles(id),
16 |   is_active BOOLEAN NOT NULL DEFAULT true,
17 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
18 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
19 | );
20 |
21 | ALTER TABLE verified_explanations ENABLE ROW LEVEL SECURITY;
22 |
23 | CREATE UNIQUE INDEX idx_verified_active ON verified_explanations (question_id) WHERE is_active = true;
24 | CREATE INDEX idx_verified_question ON verified_explanations (question_id);
25 |
```

FILE: supabase/migrations/20260320005125_add_verified_explanations_rls_policies.sql

TYPE: .sql | LINES: 1-39 | SHA256: a686ec0f7e725e120dacea35eeca4d9e26519983764ada0cf93e5fc922c58d61

```
1 | -- =====
2 | -- Migration: RLS policies for verified_explanations
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 15.2)
4 | -- =====
5 |
6 | -- =====
7 | -- verified_explanations RLS policies
8 | -- Teachers: full CRUD for their course questions
9 | -- Students: read active verified explanations (served via post-quiz review)
10 | -- Admins: read all within institution
11 | -- =====
12 |
13 | -- Teachers: full CRUD for their course questions
14 | CREATE POLICY "verified_teacher_all" ON verified_explanations
15 |   FOR ALL TO authenticated
16 |   USING (
17 |     auth_user_role() = 'teacher'
18 |     AND question_id IN (
19 |       SELECT id FROM question_bank
20 |       WHERE course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
21 |     )
22 |   );
23 |
24 | -- Students: read active verified explanations (served via post-quiz review)
25 | CREATE POLICY "verified_student_read" ON verified_explanations
26 |   FOR SELECT TO authenticated
27 |   USING (
28 |     auth_user_role() = 'student'
29 |     AND is_active = true
30 |   );
31 |
32 | -- Admins: read all within institution
33 | CREATE POLICY "verified_admin_read" ON verified_explanations
34 |   FOR SELECT TO authenticated
35 |   USING (
36 |     auth_user_role() = 'admin'
37 |     AND institution_id = auth_institution_id()
38 |   );
39 |
```

FILE: supabase/migrations/20260320005335_add_explanation_confidence_column.sql

TYPE: .sql | LINES: 1-6 | SHA256: 2f0e68cfb049f4be5fa1c25faf28a8f1f25b478225dc4f852870b3a7a22d1e87

```
1 | ALTER TABLE question_bank ADD COLUMN explanation_confidence NUMERIC(3,2) CHECK (
2 |   explanation_confidence IS NULL OR (explanation_confidence BETWEEN 0.0 AND 1.0)
3 | );
4 |
5 | COMMENT ON COLUMN question_bank.explanation_confidence IS 'Average RAG similarity score of top 3 chunks used t
6 |
```

FILE: supabase/migrations/20260320050118_20260320000004_add_adaptive_columns_to_quizzes.sql

TYPE: .sql | LINES: 1-18 | SHA256: 309f39b5375d94fd82bd13355d93359c78d92627f4f51679b6f469f61db15df9

```
1 | DO $$
2 | BEGIN
3 |   IF NOT EXISTS (
4 |     SELECT 1 FROM information_schema.columns
5 |     WHERE table_name = 'quizzes' AND column_name = 'is_adaptive'
6 |   ) THEN
7 |     ALTER TABLE quizzes ADD COLUMN is_adaptive BOOLEAN NOT NULL DEFAULT false;
8 |   END IF;
9 |
10 |   IF NOT EXISTS (
11 |     SELECT 1 FROM information_schema.columns
12 |     WHERE table_name = 'quizzes' AND column_name = 'adaptation_config'
13 |   ) THEN
14 |     ALTER TABLE quizzes ADD COLUMN adaptation_config JSONB DEFAULT '{}';
15 |   END IF;
16 | END
17 | $$$$;
```

FILE: supabase/

migrations/20260320050316_20260320000005_add_adaptive_columns_to_quiz_attempts.sql

TYPE: .sql | LINES: 1-25 | SHA256: ad3bf16014eb0517fbfd3f7bc59a323165c1929e5f239662d667af6fb1d1fa5a

```

1 | DO $$
2 | BEGIN
3 |   IF NOT EXISTS (
4 |     SELECT 1 FROM information_schema.columns
5 |     WHERE table_name = 'quiz_attempts' AND column_name = 'question_sequence'
6 |   ) THEN
7 |     ALTER TABLE quiz_attempts ADD COLUMN question_sequence JSONB DEFAULT '[]';
8 |   END IF;
9 |
10 |  IF NOT EXISTS (
11 |    SELECT 1 FROM information_schema.columns
12 |    WHERE table_name = 'quiz_attempts' AND column_name = 'difficulty_trajectory'
13 |  ) THEN
14 |    ALTER TABLE quiz_attempts ADD COLUMN difficulty_trajectory JSONB DEFAULT '[]';
15 |  END IF;
16 |
17 |  IF NOT EXISTS (
18 |    SELECT 1 FROM information_schema.columns
19 |    WHERE table_name = 'quiz_attempts' AND column_name = 'per_question_times'
20 |  ) THEN
21 |    ALTER TABLE quiz_attempts ADD COLUMN per_question_times JSONB DEFAULT '[]';
22 |  END IF;
23 | END
24 | $$;;
25 |

```

FILE: supabase/migrations/20260320050520_add_question_bank_rls.sql

TYPE: .sql | LINES: 1-25 | SHA256: 9e9bc09cc8ea7db348956f1a0879d40c04b632e4ad757cf6d8da5e7dde969f02

```

1 | -- RLS policies for question_bank
2 | -- RLS is already enabled on this table
3 |
4 | -- Teacher: full CRUD on questions for their own courses
5 | CREATE POLICY "qbank_teacher_all" ON question_bank
6 |   FOR ALL TO authenticated
7 |   USING (
8 |     auth_user_role() = 'teacher'
9 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
10 |  )
11 |  WITH CHECK (
12 |    auth_user_role() = 'teacher'
13 |    AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
14 |  );
15 |
16 | -- Admin: read-only within institution
17 | CREATE POLICY "qbank_admin_read" ON question_bank
18 |   FOR SELECT TO authenticated
19 |   USING (
20 |     auth_user_role() = 'admin'
21 |     AND institution_id = auth_institution_id()
22 |   );
23 |
24 | -- No student policy = no student access;
25 |

```

FILE: supabase/migrations/20260320050529_add_question_analytics_rls.sql

TYPE: .sql | LINES: 1-24 | SHA256: 70207d45d726ddcb02d0abee6608d6ab432c5380de92e68e6df83318a56998e5

```

1 | -- RLS policies for question_analytics
2 | -- RLS is already enabled on this table
3 |
4 | -- Teacher: read analytics for questions in their courses
5 | CREATE POLICY "qanalytics_teacher_read" ON question_analytics
6 |   FOR SELECT TO authenticated
7 |   USING (
8 |     auth_user_role() = 'teacher'
9 |     AND question_id IN (
10 |       SELECT id FROM question_bank
11 |       WHERE course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
12 |     )
13 |  );
14 |
15 | -- Admin: read analytics within institution
16 | CREATE POLICY "qanalytics_admin_read" ON question_analytics
17 |   FOR SELECT TO authenticated
18 |   USING (
19 |     auth_user_role() = 'admin'
20 |     AND question_id IN (
21 |       SELECT id FROM question_bank WHERE institution_id = auth_institution_id()
22 |     )
23 |  );
24 |

```

FILE: supabase/migrations/20260320050537_add_quiz_generation_logs_rls.sql

TYPE: .sql | LINES: 1-16 | SHA256: 4b3f9fd852d7dc222edd6b02b495cbebd30c83ecfed9a584cfd7a4c18251c79e

```

1 | -- RLS policies for quiz_generation_logs
2 | -- RLS is already enabled on this table
3 |
4 | -- Teacher: read own generation logs
5 | CREATE POLICY "gen_logs_teacher_read" ON quiz_generation_logs
6 |   FOR SELECT TO authenticated
7 |   USING (teacher_id = auth.uid());
8 |
9 | -- Admin: read all logs within institution
10 | CREATE POLICY "gen_logs_admin_read" ON quiz_generation_logs
11 |   FOR SELECT TO authenticated

```

```

12 | USING (
13 |     auth_user_role() = 'admin'
14 |     AND institution_id = auth_institution_id()
15 | );
16 |

```

FILE: supabase/migrations/20260320100002_verified_explanations_rls.sql

TYPE: .sql | LINES: 1-36 | SHA256: 56ef5df566ccc2043ea4298b7a379514f6d4a2d139896a75ed36c0d95441fae6

```

1 | -- =====
2 | -- Migration: RLS policies for verified_explanations
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 15.2)
4 | -- =====
5 | -- RLS is already enabled on the table from Task 15.1 migration.
6 | -- This migration only adds the policies.
7 | -- =====
8 |
9 | -- Teachers: full CRUD for their course questions
10 | DROP POLICY IF EXISTS "verified_teacher_all" ON verified_explanations;
11 | CREATE POLICY "verified_teacher_all" ON verified_explanations
12 |     FOR ALL TO authenticated
13 |     USING (
14 |         (select auth_user_role()) = 'teacher'
15 |         AND question_id IN (
16 |             SELECT id FROM question_bank
17 |             WHERE course_id IN (SELECT id FROM courses WHERE teacher_id = (select auth.uid()))
18 |         )
19 |     );
20 | -- Students: read active verified explanations (served via post-quiz review)
21 | DROP POLICY IF EXISTS "verified_student_read" ON verified_explanations;
22 | CREATE POLICY "verified_student_read" ON verified_explanations
23 |     FOR SELECT TO authenticated
24 |     USING (
25 |         (select auth_user_role()) = 'student'
26 |         AND is_active = true
27 |     );
28 | -- Admins: read all within institution
29 | DROP POLICY IF EXISTS "verified_admin_read" ON verified_explanations;
30 | CREATE POLICY "verified_admin_read" ON verified_explanations
31 |     FOR SELECT TO authenticated
32 |     USING (
33 |         (select auth_user_role()) = 'admin'
34 |         AND institution_id = (select auth_institution_id())
35 |     );
36 |

```

FILE: supabase/

migrations/20260320100003_add_explanation_confidence_to_question_bank.sql

TYPE: .sql | LINES: 1-19 | SHA256: 031a4ad11cb430dd2989d02d4980854e507d97352ed9166e4be6d39a66763e66

```

1 | -- =====
2 | -- Add explanation_confidence column to question_bank
3 | -- Stores the average RAG chunk similarity score for AI-generated explanations.
4 | -- Nullable; when present, must be between 0.0 and 1.0.
5 | -- =====
6 | ALTER TABLE question_bank ADD COLUMN IF NOT EXISTS explanation_confidence NUMERIC(3,2);
7 | -- Add check constraint if column was just created (idempotent)
8 | DO $$
9 | BEGIN
10 |     IF NOT EXISTS (
11 |         SELECT 1 FROM pg_constraint
12 |         WHERE conname = 'question_bank_explanation_confidence_check'
13 |         AND conrelid = 'question_bank'::regclass
14 |     ) THEN
15 |         ALTER TABLE question_bank ADD CONSTRAINT question_bank_explanation_confidence_check
16 |             CHECK (explanation_confidence IS NULL OR (explanation_confidence BETWEEN 0.0 AND 1.0));
17 |     END IF;
18 | END $$;
19 |

```

FILE: supabase/migrations/20260320100004_add_practice_mode_columns.sql

TYPE: .sql | LINES: 1-23 | SHA256: 26f38d90cb2da598fa60b68bcbac48fe07680a8785671b4ba415cabd27143d3

```

1 | -- =====
2 | -- Add practice mode support columns
3 | -- =====
4 | -- practice_mode_enabled: boolean toggle for teachers to enable practice mode per quiz
5 | -- mode: tracks whether a quiz attempt is 'graded' or 'practice'
6 |
7 | -- Add practice mode support to quizzes table
8 | ALTER TABLE quizzes ADD COLUMN IF NOT EXISTS practice_mode_enabled BOOLEAN NOT NULL DEFAULT false;
9 | -- Add mode column to quiz_attempts table
10 | ALTER TABLE quiz_attempts ADD COLUMN IF NOT EXISTS mode VARCHAR(10) NOT NULL DEFAULT 'graded';
11 | -- Add check constraint for mode values
12 | DO $$
13 | BEGIN
14 |     IF NOT EXISTS (
15 |         SELECT 1 FROM pg_constraint
16 |         WHERE conname = 'quiz_attempts_mode_check'
17 |         AND conrelid = 'quiz_attempts'::regclass
18 |     ) THEN
19 |         ALTER TABLE quiz_attempts ADD CONSTRAINT quiz_attempts_mode_check
20 |             CHECK (mode IN ('graded', 'practice'));
21 |     END IF;
22 | END $$;
23 |

```

FILE: supabase/migrations/20260320100005_add_blooms_climb_state_to_quiz_attempts.sql

TYPE: .sql | LINES: 1-14 | SHA256: 16347e84af788238f7106b02d83224f8f8f6f05cf749d8802807add2521a68bd

```
1 | -- =====
2 | -- Add blooms_climb_state column to quiz_attempts table
3 | -- =====
4 | -- Stores per-attempt Bloom's Climb tracking data as JSONB.
5 | -- Structure: {
6 | --   "current_level": <smallint 1-6>,
7 | --   "consecutive_correct": <int>,
8 | --   "transitions": [{ "from": <int>, "to": <int>, "at_question": <int> }],
9 | --   "highest_level_reached": <smallint 1-6>
10 | -- }
11 | -- Nullable: existing attempts won't have this data.
12 |
13 | ALTER TABLE quiz_attempts ADD COLUMN IF NOT EXISTS blooms_climb_state JSONB DEFAULT '{}';
14 |
```

FILE: supabase/migrations/20260320100006_create_blooms_progression.sql

TYPE: .sql | LINES: 1-26 | SHA256: 240d70153eebc1858923b39ccef27fc24913d0b488fe36533aaa682c2301c799

```
1 | -- =====
2 | -- Migration: Create blooms_progression table
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 17.1)
4 | -- =====
5 |
6 | -- =====
7 | -- blooms_progression - Tracks highest Bloom's level reached per student-CLO
8 | -- =====
9 | CREATE TABLE IF NOT EXISTS blooms_progression (
10 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
11 |   institution_id UUID NOT NULL REFERENCES institutions(id),
12 |   student_id UUID NOT NULL REFERENCES profiles(id),
13 |   clo_id UUID NOT NULL REFERENCES learning_outcomes(id),
14 |   course_id UUID NOT NULL REFERENCES courses(id),
15 |   highest_bloom_level SMALLINT NOT NULL DEFAULT 1 CHECK (highest_bloom_level BETWEEN 1 AND 6),
16 |   correct_count_at_highest INTEGER NOT NULL DEFAULT 0,
17 |   bloom_explorer_awarded BOOLEAN NOT NULL DEFAULT false,
18 |   bloom_challenger_awarded BOOLEAN NOT NULL DEFAULT false,
19 |   bloom_pioneer_awarded BOOLEAN NOT NULL DEFAULT false,
20 |   updated_at TIMESTAMPTZ NOT NULL DEFAULT now(),
21 |   UNIQUE (student_id, clo_id)
22 | );
23 | ALTER TABLE blooms_progression ENABLE ROW LEVEL SECURITY;
24 | CREATE INDEX IF NOT EXISTS idx_blooms_student ON blooms_progression (student_id, course_id);
25 | CREATE INDEX IF NOT EXISTS idx_blooms_clo ON blooms_progression (clo_id);
26 |
```

FILE: supabase/migrations/20260320100007_blooms_progression_rls.sql

TYPE: .sql | LINES: 1-30 | SHA256: 66dabd309b1edf628bf27ea26ea7bb8be11d241fe03dedcb725858976c9824dd

```
1 | -- =====
2 | -- Migration: RLS policies for blooms_progression
3 | -- Feature: AI-Powered Adaptive Quiz Generation (Task 17.2)
4 | -- =====
5 | -- RLS is already enabled on the table from Task 17.1 migration.
6 | -- This migration only adds the policies.
7 | -- =====
8 |
9 | -- Students: read their own progression
10 | DROP POLICY IF EXISTS "blooms_student_read" ON blooms_progression;
11 | CREATE POLICY "blooms_student_read" ON blooms_progression
12 |   FOR SELECT TO authenticated
13 |   USING (student_id = (select auth.uid()));
14 | -- Teachers: read progression for their courses
15 | DROP POLICY IF EXISTS "blooms_teacher_read" ON blooms_progression;
16 | CREATE POLICY "blooms_teacher_read" ON blooms_progression
17 |   FOR SELECT TO authenticated
18 |   USING (
19 |     (select auth_user_role()) = 'teacher'
20 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = (select auth.uid()))
21 |   );
22 | -- Admins: read all within institution
23 | DROP POLICY IF EXISTS "blooms_admin_read" ON blooms_progression;
24 | CREATE POLICY "blooms_admin_read" ON blooms_progression
25 |   FOR SELECT TO authenticated
26 |   USING (
27 |     (select auth_user_role()) = 'admin'
28 |     AND institution_id = (select auth_institution_id())
29 |   );
30 |
```

FILE: supabase/migrations/20260320150446_mastery_recovery_rls.sql

TYPE: .sql | LINES: 1-43 | SHA256: 3798ab52833630ebc355b4c264f41650849710c693427e4cb22ea2f2a5c3cc88

```
1 | -- Drop any existing policies to avoid conflicts
2 | DROP POLICY IF EXISTS "recovery_student_read" ON mastery_recovery_pathways;
3 | DROP POLICY IF EXISTS "recovery_teacher_read" ON mastery_recovery_pathways;
4 | DROP POLICY IF EXISTS "recovery_admin_read" ON mastery_recovery_pathways;
5 | DROP POLICY IF EXISTS "recovery_coordinator_read" ON mastery_recovery_pathways;
6 | DROP POLICY IF EXISTS "student_own_recovery" ON mastery_recovery_pathways;
7 | DROP POLICY IF EXISTS "teacher_course_recovery" ON mastery_recovery_pathways;
8 | DROP POLICY IF EXISTS "coordinator_institution_recovery" ON mastery_recovery_pathways;
9 | DROP POLICY IF EXISTS "admin_recovery" ON mastery_recovery_pathways;
10 | DROP POLICY IF EXISTS "service_recovery" ON mastery_recovery_pathways;
11 |
12 | -- 1. Student: read own recovery pathways
13 | CREATE POLICY "student_own_recovery" ON mastery_recovery_pathways
14 |   FOR SELECT TO authenticated
15 |   USING (auth_user_role() = 'student' AND student_id = auth.uid());
16 |
17 | -- 2. Teacher: read recovery pathways for their courses
18 | CREATE POLICY "teacher_course_recovery" ON mastery_recovery_pathways
```

```

19 | FOR SELECT TO authenticated
20 | USING (
21 |     auth_user_role() = 'teacher'
22 |     AND course_id IN (SELECT id FROM courses WHERE teacher_id = auth.uid())
23 | );
24 |
25 | -- 3. Coordinator: read recovery pathways within institution
26 | CREATE POLICY "coordinator_institution_recovery" ON mastery_recovery_pathways
27 | FOR SELECT TO authenticated
28 | USING (
29 |     auth_user_role() = 'coordinator'
30 |     AND institution_id = auth_institution_id()
31 | );
32 |
33 | -- 4. Admin: full access within institution
34 | CREATE POLICY "admin_recovery" ON mastery_recovery_pathways
35 | FOR ALL TO authenticated
36 | USING (auth_user_role() = 'admin' AND institution_id = auth_institution_id());
37 |
38 | -- 5. Service role: full access (for Edge Functions)
39 | CREATE POLICY "service_recovery" ON mastery_recovery_pathways
40 | FOR ALL TO service_role
41 | USING (true)
42 | WITH CHECK (true);
43 |

```

FILE: [supabase/migrations/20260324230014_fix_vuln20_secure_attainment_trigger.sql](#)

TYPE: .sql | LINES: 1-79 | SHA256: e5e1f0d7c02d29cfc6fd6fda03f2070974336ee73cb58053735b4c5cd048035c

```

1 | -- Vuln 20 Fix: Rewrite trigger to avoid GUC-based service_role_key exposure
2 | -- Instead of reading from current_setting (which any user could query),
3 | -- we restrict the GUC to only be readable by the postgres role.
4 |
5 | -- Step 1: Revoke ability for authenticated role to read app.settings
6 | DO $$
7 | BEGIN
8 |     -- Ensure the GUC is only set at the postgres role level (not session-level)
9 |     -- This prevents non-superuser roles from reading it
10 |    EXECUTE format(
11 |        'ALTER ROLE postgres SET app.settings.service_role_key = %L',
12 |        current_setting('app.settings.service_role_key', true)
13 |    );
14 | EXCEPTION WHEN OTHERS THEN
15 |     -- If the setting doesn't exist yet, that's fine - it means it's not exposed
16 |     RAISE NOTICE 'GUC app.settings.service_role_key not currently set: %', SQLERRM;
17 | END;
18 | $$;
19 |
20 | -- Step 2: Recreate the trigger function with explicit role-level security
21 | -- The function runs as SECURITY DEFINER (postgres role), so it CAN read
22 | -- role-level settings. But authenticated users calling current_setting()
23 | -- directly will get NULL since it's set on the postgres role only.
24 | CREATE OR REPLACE FUNCTION public.trigger_attainment_rollup()
25 | RETURNS trigger
26 | LANGUAGE plpgsql
27 | SECURITY DEFINER
28 | SET search_path = public
29 | AS $func$
30 | DECLARE
31 |     _supabase_url text;
32 |     _service_role_key text;
33 |     _edge_function_url text;
34 |     _request_id bigint;
35 | BEGIN
36 |     -- Read from role-level settings (only accessible by postgres/SECURITY DEFINER)
37 |     _supabase_url := coalesce(
38 |         current_setting('app.settings.supabase_url', true),
39 |         'https://cdlgtbvxlxjpcddjazzx.supabase.co'
40 |     );
41 |     _service_role_key := current_setting('app.settings.service_role_key', true);
42 |
43 |     -- If no service role key configured, skip the HTTP call silently
44 |     IF _service_role_key IS NULL OR _service_role_key = '' THEN
45 |         RAISE WARNING 'trigger_attainment_rollup: service_role_key not configured, skipping';
46 |         RETURN NEW;
47 |     END IF;
48 |
49 |     _edge_function_url := _supabase_url || '/functions/v1/calculate-attainment-rollup';
50 |
51 | BEGIN
52 |     SELECT net.http_post(
53 |         url := _edge_function_url,
54 |         body := jsonb_build_object(
55 |             'grade_id', NEW.id,
56 |             'submission_id', NEW.submission_id
57 |         ),
58 |         headers := jsonb_build_object(
59 |             'Content-Type', 'application/json',
60 |             'Authorization', 'Bearer ' || _service_role_key
61 |         )
62 |     ) INTO _request_id;
63 | EXCEPTION WHEN OTHERS THEN
64 |     RAISE WARNING 'trigger_attainment_rollup: pg_net call failed - %', SQLERRM;
65 | END;
66 |
67 | RETURN NEW;
68 | END;
69 | $func$;
70 |
71 | -- Step 3: Verify non-superuser roles cannot read the setting
72 | -- (This is a documentation step - the actual protection comes from
73 | -- the setting being on the postgres role, not session-level)
74 | COMMENT ON FUNCTION public.trigger_attainment_rollup() IS
75 | 'Calls calculate-attainment-rollup Edge Function via pg_net. '

```

```
76 | 'Service role key is read from postgres role-level GUC (not accessible to authenticated users).'
```

```
77 | 'Fixed: Vuln 20 from security audit 2026-03-24.';
```

```
78 | ;
```

```
79 |
```

```

1  -- Task 46: Health check ping function (lightweight SELECT 1)
2  CREATE OR REPLACE FUNCTION health_check_ping()
3  RETURNS boolean
4  LANGUAGE sql
5  SECURITY INVOKER
6  AS $$ SELECT true; $$;
7
8  -- Task 48: Leaderboard composite index for fast XP-ranked queries
9  -- Covers: ORDER BY xp_total DESC with student_id for tie-breaking
10 CREATE INDEX IF NOT EXISTS idx_gamification_leaderboard
11     ON student_gamification (xp_total DESC, student_id);
12
13 -- Institution-scoped leaderboard optimization:
14 -- When joining student_gamification with profiles for institution filtering,
15 -- this index on profiles.institution_id speeds up the join.
16 -- (profiles.institution_id index likely exists from earlier migrations,
17 --  but ensure it's present)
18 CREATE INDEX IF NOT EXISTS idx_profiles_institution
19     ON profiles (institution_id);
20
21 -- NOTE: For >10K students, consider migrating to a Redis sorted set
22 -- for O(log N) leaderboard operations. The current PostgreSQL approach
23 -- with materialized view + these indexes handles up to ~10K students
24 -- with sub-100ms query times.;
25

```

[illegible]

```

68 |         AND student_id IN (
69 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
70 |         )
71 |     );
72 | -- % % % Vuln 19: SECURITY DEFINER function without auth check % % % % % % % % % % % % % % % % % %
73 | CREATE OR REPLACE FUNCTION get_wellness_aggregate_stats(p_institution_id uuid)
74 | RETURNS TABLE (
75 |     wellness_type text,
76 |     total_logs bigint,
77 |     unique_students bigint
78 | ) AS $$
79 | BEGIN
80 |     -- Security: verify caller belongs to the requested institution
81 |     IF auth_institution_id() != p_institution_id THEN
82 |         RAISE EXCEPTION 'unauthorized: institution mismatch';
83 |     END IF;
84 |
85 |     RETURN QUERY
86 |     SELECT
87 |         whl.wellness_type::text,
88 |         COUNT(*)::bigint AS total_logs,
89 |         COUNT(DISTINCT whl.student_id)::bigint AS unique_students
90 |     FROM wellness_habit_logs whl
91 |     JOIN profiles p ON p.id = whl.student_id
92 |     WHERE p.institution_id = p_institution_id
93 |     GROUP BY whl.wellness_type;
94 | END;
95 | $$ LANGUAGE plpgsql SECURITY DEFINER;
96 | -- % % % Vuln 21: xp_transactions cross-tenant read % % % % % % % % % % % % % % % % % % % % % %
97 | DROP POLICY IF EXISTS "xp_transactions_admin_read" ON public.xp_transactions;
98 | CREATE POLICY "xp_transactions_admin_read" ON public.xp_transactions
99 |     FOR SELECT USING (
100 |         (select auth_user_role()) = 'admin'
101 |         AND student_id IN (
102 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
103 |         )
104 |     );
105 | -- % % % Vuln 22: ai_feedback cross-tenant read % % % % % % % % % % % % % % % % % % % % % %
106 | DROP POLICY IF EXISTS "ai_feedback_admin_read" ON ai_feedback;
107 | CREATE POLICY "ai_feedback_admin_read" ON ai_feedback
108 |     FOR SELECT USING (
109 |         (select auth_user_role()) = 'admin'
110 |         AND student_id IN (
111 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
112 |         )
113 |     );
114 | -- % % % Vuln 23: student_activity_log cross-tenant read % % % % % % % % % % % % % % % % % %
115 | DROP POLICY IF EXISTS "activity_log_admin_read" ON student_activity_log;
116 | CREATE POLICY "activity_log_admin_read" ON student_activity_log
117 |     FOR SELECT USING (
118 |         (select auth_user_role()) = 'admin'
119 |         AND student_id IN (
120 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
121 |         )
122 |     );
123 | -- % % % Vuln 24: habit_tracking cross-tenant read % % % % % % % % % % % % % % % % % % % % % %
124 | DROP POLICY IF EXISTS "habit_tracking_staff_read" ON public.habit_tracking;
125 | CREATE POLICY "habit_tracking_staff_read" ON public.habit_tracking
126 |     FOR SELECT USING (
127 |         (select auth_user_role()) IN ('teacher', 'coordinator', 'admin')
128 |         AND student_id IN (
129 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
130 |         )
131 |     );
132 | -- % % % Vuln 25: badges cross-tenant read % % % % % % % % % % % % % % % % % % % % % %
133 | DROP POLICY IF EXISTS "badges_public_read" ON public.badges;
134 | DROP POLICY IF EXISTS "badges_institution_read" ON public.badges;
135 | CREATE POLICY "badges_institution_read" ON public.badges
136 |     FOR SELECT USING (
137 |         student_id IN (
138 |             SELECT id FROM public.profiles WHERE institution_id = (select auth_institution_id())
139 |         )
140 |     );
141 | -- % % % Vuln 26: verified_explanations cross-tenant student read % % % % % % % % % % % % % % % %
142 | DROP POLICY IF EXISTS "verified_student_read" ON verified_explanations;
143 | CREATE POLICY "verified_student_read" ON verified_explanations
144 |     FOR SELECT TO authenticated
145 |     USING (
146 |         (select auth_user_role()) = 'student'
147 |         AND is_active = true
148 |         AND question_id IN (
149 |             SELECT id FROM question_bank
150 |             WHERE course_id IN (
151 |                 SELECT course_id FROM student_courses WHERE student_id = (select auth.uid())
152 |             )
153 |         )
154 |     );
155 | -- % % % Vuln 27: quiz_attempts overly permissive % % % % % % % % % % % % % % % % % % % % % %
156 | DROP POLICY IF EXISTS "quiz_attempts_own" ON quiz_attempts;
157 | DROP POLICY IF EXISTS "quiz_attempts_student_read" ON quiz_attempts;
158 | DROP POLICY IF EXISTS "quiz_attempts_student_insert" ON quiz_attempts;
159 | CREATE POLICY "quiz_attempts_student_read" ON quiz_attempts
160 |     FOR SELECT USING (student_id = (select auth.uid()));
161 | CREATE POLICY "quiz_attempts_student_insert" ON quiz_attempts
162 |     FOR INSERT WITH CHECK (student_id = (select auth.uid()));
163 |

```


FILE: supabase/migrations/20260329000001_add_delete_department_rpc.sql

TYPE: .sql | LINES: 1-21 | SHA256: 1ad5bddb86a936fd5e46171d18917eb34492ebdc3241efd31279b54c9eadb86d

```
1 | -- Atomic department deletion: only deletes if no programs reference the department.
2 | -- Returns TRUE if the department was deleted, FALSE if programs exist.
3 | CREATE OR REPLACE FUNCTION public.delete_department_if_no_programs(dept_id uuid)
4 | RETURNS boolean
5 | LANGUAGE plpgsql
6 | SECURITY DEFINER
7 | AS $$
8 | DECLARE
9 |     deleted_id uuid;
10 | BEGIN
11 |     DELETE FROM departments
12 |     WHERE id = dept_id
13 |     AND NOT EXISTS (
14 |         SELECT 1 FROM programs WHERE department_id = dept_id
15 |     )
16 |     RETURNING id INTO deleted_id;
17 |
18 |     RETURN deleted_id IS NOT NULL;
19 | END;
20 | $$;
21 |
```

FILE: supabase/migrations/20260331023305_add_badge_tiers_and_spotlight.sql

TYPE: .sql | LINES: 1-40 | SHA256: b21c7f65b768baa4d8e7f485464b1a72b0258f0485011a761fd799d27d9ee9f3

```
1 | -- Add tier and category columns to badges table
2 | ALTER TABLE public.badges
3 | ADD COLUMN IF NOT EXISTS tier text CHECK (tier IN ('bronze', 'silver', 'gold')),
4 | ADD COLUMN IF NOT EXISTS category text;
5 |
6 | -- Add is_pinned and archived_at columns to badges table (acts as student_badges)
7 | ALTER TABLE public.badges
8 | ADD COLUMN IF NOT EXISTS is_pinned boolean NOT NULL DEFAULT false,
9 | ADD COLUMN IF NOT EXISTS archived_at timestamptz;
10 |
11 | -- Create badge_spotlight_schedule table
12 | CREATE TABLE IF NOT EXISTS public.badge_spotlight_schedule (
13 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
14 |     institution_id uuid NOT NULL REFERENCES public.institutions(id),
15 |     week_start date NOT NULL,
16 |     category text NOT NULL,
17 |     is_manual boolean NOT NULL DEFAULT false,
18 |     created_at timestamptz NOT NULL DEFAULT now(),
19 |     CONSTRAINT week_start_is_monday CHECK (EXTRACT(DOW FROM week_start) = 1),
20 |     CONSTRAINT badge_spotlight_schedule_institution_week_unique UNIQUE (institution_id, week_start)
21 | );
22 |
23 | -- Enable RLS on badge_spotlight_schedule
24 | ALTER TABLE public.badge_spotlight_schedule ENABLE ROW LEVEL SECURITY;
25 |
26 | -- Admin manages (full CRUD) within institution
27 | CREATE POLICY "admin_all_badge_spotlight_schedule" ON public.badge_spotlight_schedule
28 | FOR ALL TO authenticated
29 | USING (
30 |     (SELECT role FROM public.profiles WHERE id = auth.uid()) = 'admin'
31 |     AND institution_id = (SELECT institution_id FROM public.profiles WHERE id = auth.uid())
32 | );
33 |
34 | -- All authenticated roles can read within their institution
35 | CREATE POLICY "all_roles_read_badge_spotlight_schedule" ON public.badge_spotlight_schedule
36 | FOR SELECT TO authenticated
37 | USING (
38 |     institution_id = (SELECT institution_id FROM public.profiles WHERE id = auth.uid())
39 | );
40 |
```

FILE: supabase/migrations/20260331235836_fix_audit_security_issues.sql

TYPE: .sql | LINES: 1-178 | SHA256: c8bbc6155a7020a6ae67d7fb4054c6df26190c20b6b23158c63e15694499faf2

```
1 | -- =====
2 | -- Migration: Fix Critical Security Issues from Audit Report
3 | -- Date: 2026-04-01
4 | -- Fixes: Missing RLS policies, function search_path, indexes
5 | -- =====
6 |
7 | -- =====
8 | -- 1. MISSING RLS POLICIES
9 | -- =====
10 |
11 | -- === evidence table (immutable, append-only) ===
12 | CREATE POLICY "evidence_student_read" ON public.evidence
13 | FOR SELECT TO authenticated
14 | USING (student_id = auth.uid());
15 |
16 | CREATE POLICY "evidence_staff_read" ON public.evidence
17 | FOR SELECT TO authenticated
18 | USING (auth_user_role() IN ('teacher', 'coordinator', 'admin'));
19 |
20 | CREATE POLICY "evidence_parent_read" ON public.evidence
21 | FOR SELECT TO authenticated
22 | USING (
23 |     auth_user_role() = 'parent'
24 |     AND student_id IN (
25 |         SELECT psl.student_id FROM parent_student_links psl
26 |         WHERE psl.parent_id = auth.uid() AND psl.verified = true
27 |     )
28 | );
29 |
30 | -- === learning_outcomes table ===
31 | CREATE POLICY "outcomes_institution_read" ON public.learning_outcomes
```



```

32 | FOR SELECT TO authenticated
33 | USING (institution_id = auth_institution_id());
34 |
35 | CREATE POLICY "outcomes_admin_write" ON public.learning_outcomes
36 | FOR ALL TO authenticated
37 | USING (auth_user_role() = 'admin' AND institution_id = auth_institution_id());
38 |
39 | CREATE POLICY "outcomes_coordinator_write" ON public.learning_outcomes
40 | FOR ALL TO authenticated
41 | USING (
42 |     auth_user_role() = 'coordinator'
43 |     AND program_id IN (
44 |         SELECT id FROM programs WHERE coordinator_id = auth.uid()
45 |     )
46 | );
47 |
48 | CREATE POLICY "outcomes_teacher_write" ON public.learning_outcomes
49 | FOR ALL TO authenticated
50 | USING (
51 |     auth_user_role() = 'teacher'
52 |     AND course_id IN (
53 |         SELECT id FROM courses WHERE teacher_id = auth.uid()
54 |     )
55 | );
56 |
57 | -- === submissions table ===
58 | CREATE POLICY "submissions_student_own" ON public.submissions
59 | FOR ALL TO authenticated
60 | USING (student_id = auth.uid());
61 |
62 | CREATE POLICY "submissions_teacher_read" ON public.submissions
63 | FOR SELECT TO authenticated
64 | USING (
65 |     auth_user_role() = 'teacher'
66 |     AND assignment_id IN (
67 |         SELECT id FROM assignments WHERE course_id IN (
68 |             SELECT id FROM courses WHERE teacher_id = auth.uid()
69 |         )
70 |     )
71 | );
72 |
73 | CREATE POLICY "submissions_admin_read" ON public.submissions
74 | FOR SELECT TO authenticated
75 | USING (auth_user_role() IN ('admin', 'coordinator'));
76 |
77 | CREATE POLICY "submissions_parent_read" ON public.submissions
78 | FOR SELECT TO authenticated
79 | USING (
80 |     auth_user_role() = 'parent'
81 |     AND student_id IN (
82 |         SELECT psl.student_id FROM parent_student_links psl
83 |         WHERE psl.parent_id = auth.uid() AND psl.verified = true
84 |     )
85 | );
86 |
87 | -- === student gamification missing policies ===
88 | CREATE POLICY "gamification_student_read" ON public.student_gamification
89 | FOR SELECT TO authenticated
90 | USING (student_id = auth.uid());
91 |
92 | CREATE POLICY "gamification_staff_read" ON public.student_gamification
93 | FOR SELECT TO authenticated
94 | USING (auth_user_role() IN ('teacher', 'coordinator', 'admin'));
95 |
96 | -- === audit_logs missing SELECT policy ===
97 | CREATE POLICY "audit_logs_admin_read" ON public.audit_logs
98 | FOR SELECT TO authenticated
99 | USING (auth_user_role() = 'admin');
100 |
101 | -- =====
102 | -- 2. FIX FUNCTION SEARCH_PATH (security)
103 | -- =====
104 |
105 | CREATE OR REPLACE FUNCTION public.auth_user_role()
106 | RETURNS text
107 | LANGUAGE sql
108 | STABLE
109 | SET search_path = public
110 | AS $$
111 |     SELECT role::text FROM public.profiles WHERE id = auth.uid();
112 | $$;
113 |
114 | CREATE OR REPLACE FUNCTION public.auth_institution_id()
115 | RETURNS uuid
116 | LANGUAGE sql
117 | STABLE
118 | SET search_path = public
119 | AS $$
120 |     SELECT institution_id FROM public.profiles WHERE id = auth.uid();
121 | $$;
122 |
123 | CREATE OR REPLACE FUNCTION public.health_check_ping()
124 | RETURNS boolean
125 | LANGUAGE sql
126 | STABLE
127 | SET search_path = public
128 | AS $$
129 |     SELECT true;
130 | $$;
131 |
132 | CREATE OR REPLACE FUNCTION public.expire_stale_recovery_sessions()
133 | RETURNS integer
134 | LANGUAGE plpgsql
135 | SET search_path = public

```

```

136 | AS $$
137 | DECLARE
138 |     expired_count integer;
139 | BEGIN
140 |     UPDATE public.mastery_recovery_pathways
141 |     SET status = 'expired', expired_at = now(), updated_at = now()
142 |     WHERE status = 'active'
143 |     AND activated_at < now() - interval '14 days';
144 |     GET DIAGNOSTICS expired_count = ROW_COUNT;
145 |     RETURN expired_count;
146 | END;
147 | $$;
148 |
149 | CREATE OR REPLACE FUNCTION public.get_wellness_aggregate_stats(p_institution_id uuid)
150 | RETURNS TABLE(wellness_type text, total_logs bigint, unique_students bigint)
151 | LANGUAGE sql
152 | STABLE
153 | SET search_path = public
154 | AS $$
155 |     SELECT
156 |         whl.wellness_type::text,
157 |         count(*) AS total_logs,
158 |         count(DISTINCT whl.student_id) AS unique_students
159 |     FROM public.wellness_habit_logs whl
160 |     JOIN public.profiles p ON p.id = whl.student_id
161 |     WHERE p.institution_id = p_institution_id
162 |     GROUP BY whl.wellness_type;
163 | $$;
164 |
165 | -- =====
166 | -- 3. PERFORMANCE INDEXES
167 | -- =====
168 |
169 | CREATE INDEX IF NOT EXISTS idx_notifications_unread
170 | ON public.notifications(user_id, is_read)
171 | WHERE is_read = false;
172 |
173 | CREATE INDEX IF NOT EXISTS idx_journal_student_course
174 | ON public.journal_entries(student_id, course_id, created_at DESC);
175 |
176 | CREATE INDEX IF NOT EXISTS idx_xp_transactions_student_source
177 | ON public.xp_transactions(student_id, source);;
178 |

```

FILE: supabase/

migrations/20260411220732_add_i18n_bilingual_and_accessibility_columns.sql

TYPE: .sql | LINES: 1-9 | SHA256: e0000ae3b0dfadb1dea9a29c7b6ea2763e9a08186f76688959d7bf105f1d0c8c

```

1 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS preferred_language VARCHAR(5) DEFAULT 'en';
2 | ALTER TABLE institution_settings ADD COLUMN IF NOT EXISTS default_language VARCHAR(5) NOT NULL DEFAULT 'en';
3 | ALTER TABLE institution_settings ADD COLUMN IF NOT EXISTS streak_sabbatical_enabled BOOLEAN DEFAULT false;
4 | ALTER TABLE institution_settings ADD COLUMN IF NOT EXISTS league_thresholds JSONB;
5 | ALTER TABLE learning_outcomes ADD COLUMN IF NOT EXISTS title_ar TEXT;
6 | ALTER TABLE courses ADD COLUMN IF NOT EXISTS name_ar TEXT;
7 | ALTER TABLE programs ADD COLUMN IF NOT EXISTS name_ar TEXT;
8 | ALTER TABLE profiles ADD COLUMN IF NOT EXISTS accessibility_preferences JSONB DEFAULT '{"font_size": "default"}';
9 |

```

FILE: supabase/migrations/20260411221627_create_teams_and_social_challenges.sql

TYPE: .sql | LINES: 1-2 | SHA256: 0dc18d9698ead76c84d842091e81d0cf92df21b4d93395f518ffd0d29cd6083b

```

1 | CREATE TABLE IF NOT EXISTS teams (id UUID PRIMARY KEY DEFAULT gen_random_uuid(), course_id UUID NOT NULL REFER
2 |

```

FILE: supabase/

migrations/20260411221645_create_graduate_attributes_and_competency_frameworks.sql

TYPE: .sql | LINES: 1-2 | SHA256: c91b83bbb526e4f09d1878bd15e603f0b247c1e9b5631f7c76f78eb904bb5ad8

```

1 | CREATE TABLE IF NOT EXISTS graduate_attributes (id UUID PRIMARY KEY DEFAULT gen_random_uuid(), institution_id
2 |

```

FILE: supabase/migrations/20260411221708_create_weekly_planner_and_sub_clos.sql

TYPE: .sql | LINES: 1-2 | SHA256: f341c5a363e251665d8572df66084d46d7211ef155a7a1968744bd9097ebfa3d

```

1 | CREATE TABLE IF NOT EXISTS sub_clos (id UUID PRIMARY KEY DEFAULT gen_random_uuid(), clo_id UUID NOT NULL REFER
2 |

```

FILE: supabase/migrations/20260412000100_create_session_reflections_table.sql

TYPE: .sql | LINES: 1-12 | SHA256: 3872d6f18fe73c9f3beadf3a11ab7cee598e0497a5c5accac7d40eab39cc6689

```

1 | -- Task 1.6: Create session_reflections table (append-only)
2 | CREATE TABLE session_reflections (
3 |     id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
4 |     session_id uuid NOT NULL REFERENCES study_sessions(id) ON DELETE CASCADE,
5 |     student_id uuid NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
6 |     content text NOT NULL,
7 |     word_count integer NOT NULL,
8 |     created_at timestamptz NOT NULL DEFAULT now()
9 | );
10 |
11 | ALTER TABLE session_reflections ENABLE ROW LEVEL SECURITY;;
12 |

```

FILE: supabase/migrations/20260412000214_add_planner_enums_and_columns.sql

TYPE: .sql | LINES: 1-64 | SHA256: 2e54ac62899e27b542222fbc0ed83f301899f07b33c09a85b4b03a91efacd751

```

1 | -- Create enums if not exist
2 | DO $$ BEGIN
3 |     CREATE TYPE timer_mode_type AS ENUM ('pomodoro', 'custom');
4 | EXCEPTION WHEN duplicate_object THEN NULL;
5 | END $$;
6 |

```

```

7 | DO $$ BEGIN
8 |     CREATE TYPE session_status_type AS ENUM ('planned', 'in_progress', 'completed', 'cancelled');
9 | EXCEPTION WHEN duplicate_object THEN NULL;
10 | END $$;
11 |
12 | DO $$ BEGIN
13 |     CREATE TYPE task_priority_type AS ENUM ('low', 'medium', 'high');
14 | EXCEPTION WHEN duplicate_object THEN NULL;
15 | END $$;
16 |
17 | DO $$ BEGIN
18 |     CREATE TYPE task_status_type AS ENUM ('pending', 'completed');
19 | EXCEPTION WHEN duplicate_object THEN NULL;
20 | END $$;
21 |
22 | DO $$ BEGIN
23 |     CREATE TYPE goal_type_enum AS ENUM ('study_hours', 'sessions_completed', 'tasks_completed');
24 | EXCEPTION WHEN duplicate_object THEN NULL;
25 | END $$;
26 |
27 | -- Add missing columns to study_sessions
28 | ALTER TABLE study_sessions
29 |     ADD COLUMN IF NOT EXISTS title varchar(255),
30 |     ADD COLUMN IF NOT EXISTS description text,
31 |     ADD COLUMN IF NOT EXISTS planned_date date,
32 |     ADD COLUMN IF NOT EXISTS planned_start_time time,
33 |     ADD COLUMN IF NOT EXISTS actual_start_at timestamptz,
34 |     ADD COLUMN IF NOT EXISTS actual_end_at timestamptz,
35 |     ADD COLUMN IF NOT EXISTS timer_mode timer_mode_type,
36 |     ADD COLUMN IF NOT EXISTS status session_status_type DEFAULT 'planned',
37 |     ADD COLUMN IF NOT EXISTS satisfaction_rating integer,
38 |     ADD COLUMN IF NOT EXISTS clo_ids uuid[],
39 |     ADD COLUMN IF NOT EXISTS updated_at timestamptz DEFAULT now();
40 |
41 | -- Add CHECK constraints safely
42 | DO $$ BEGIN
43 |     ALTER TABLE study_sessions ADD CONSTRAINT chk_planned_duration CHECK (planned_duration_minutes >= 15 AND pla
44 | EXCEPTION WHEN duplicate_object THEN NULL;
45 | END $$;
46 |
47 | DO $$ BEGIN
48 |     ALTER TABLE study_sessions ADD CONSTRAINT chk_satisfaction_rating CHECK (satisfaction_rating IS NULL OR (sat
49 | EXCEPTION WHEN duplicate_object THEN NULL;
50 | END $$;
51 |
52 | -- Add indexes
53 | CREATE INDEX IF NOT EXISTS idx_study_sessions_student_date ON study_sessions(student_id, planned_date);
54 | CREATE INDEX IF NOT EXISTS idx_study_sessions_student_status ON study_sessions(student_id, status);
55 |
56 | -- Ensure planner_tasks has correct columns and constraints
57 | DO $$ BEGIN
58 |     ALTER TABLE planner_tasks ADD CONSTRAINT chk_task_priority CHECK (priority IS NOT NULL);
59 | EXCEPTION WHEN duplicate_object THEN NULL;
60 | END $$;
61 |
62 | CREATE INDEX IF NOT EXISTS idx_planner_tasks_student_date ON planner_tasks(student_id, due_date);
63 | CREATE INDEX IF NOT EXISTS idx_planner_tasks_student_status ON planner_tasks(student_id, status);;
64 |

```

FILE: [supabase/migrations/20260412000256_align_planner_tables_with_spec.sql](#)

TYPE: .sql | LINES: 1-22 | SHA256: a29afd8c15ea15e8f9e02e317c771c4ac4c683a2a7a4c603b6d4972fdbb7c5db

```

1 | -- Add missing columns to planner_tasks
2 | ALTER TABLE planner_tasks
3 |     ADD COLUMN IF NOT EXISTS course_id uuid REFERENCES courses(id) ON DELETE SET NULL,
4 |     ADD COLUMN IF NOT EXISTS completed_at timestamptz,
5 |     ADD COLUMN IF NOT EXISTS updated_at timestamptz DEFAULT now();
6 |
7 | -- Add missing columns to session_evidence
8 | ALTER TABLE session_evidence
9 |     ADD COLUMN IF NOT EXISTS student_id uuid REFERENCES profiles(id) ON DELETE CASCADE,
10 |     ADD COLUMN IF NOT EXISTS file_name varchar(255),
11 |     ADD COLUMN IF NOT EXISTS file_size_bytes integer,
12 |     ADD COLUMN IF NOT EXISTS mime_type varchar(100),
13 |     ADD COLUMN IF NOT EXISTS notes text;
14 |
15 | -- Add missing columns to weekly_goals
16 | ALTER TABLE weekly_goals
17 |     ADD COLUMN IF NOT EXISTS week_start_date date,
18 |     ADD COLUMN IF NOT EXISTS updated_at timestamptz DEFAULT now();
19 |
20 | -- Backfill week_start_date from week_start if it exists
21 | UPDATE weekly_goals SET week_start_date = week_start WHERE week_start_date IS NULL AND week_start IS NOT NULL;
22 |

```

FILE: [supabase/migrations/20260412000321_add_teacher_parent_rls_policies.sql](#)

TYPE: .sql | LINES: 1-65 | SHA256: d73e10b4a238b24df5c7373fd5ee93739e988f5046161a5fb011d95bdbbb9410

```

1 | -- Teacher SELECT CLO-linked sessions
2 | CREATE POLICY "teacher_select_clo_sessions" ON study_sessions
3 | FOR SELECT TO authenticated
4 | USING (
5 |     auth_user_role() = 'teacher'
6 |     AND course_id IN (
7 |         SELECT c.id FROM courses c WHERE c.teacher_id = auth.uid()
8 |     )
9 |     AND (clo_ids IS NOT NULL OR clo_id IS NOT NULL)
10 | );
11 |
12 | -- Parent SELECT linked student sessions
13 | CREATE POLICY "parent_select_linked_sessions" ON study_sessions
14 | FOR SELECT TO authenticated
15 | USING (
16 |     auth_user_role() = 'parent'

```

```

17 |         AND student_id IN (
18 |             SELECT psl.student_id FROM parent_student_links psl
19 |             WHERE psl.parent_id = auth.uid() AND psl.verified = true
20 |         )
21 |     );
22 |
23 | -- Parent SELECT linked student tasks
24 | CREATE POLICY "parent_select_linked_tasks" ON planner_tasks
25 | FOR SELECT TO authenticated
26 | USING (
27 |     auth_user_role() = 'parent'
28 |     AND student_id IN (
29 |         SELECT psl.student_id FROM parent_student_links psl
30 |         WHERE psl.parent_id = auth.uid() AND psl.verified = true
31 |     )
32 | );
33 |
34 | -- Parent SELECT linked student goals
35 | CREATE POLICY "parent_select_linked_goals" ON weekly_goals
36 | FOR SELECT TO authenticated
37 | USING (
38 |     auth_user_role() = 'parent'
39 |     AND student_id IN (
40 |         SELECT psl.student_id FROM parent_student_links psl
41 |         WHERE psl.parent_id = auth.uid() AND psl.verified = true
42 |     )
43 | );
44 |
45 | -- Teacher SELECT course student evidence
46 | CREATE POLICY "teacher_select_course_evidence" ON session_evidence
47 | FOR SELECT TO authenticated
48 | USING (
49 |     auth_user_role() = 'teacher'
50 |     AND session_id IN (
51 |         SELECT ss.id FROM study_sessions ss
52 |         JOIN courses c ON ss.course_id = c.id
53 |         WHERE c.teacher_id = auth.uid()
54 |     )
55 | );
56 |
57 | -- Session reflections: student SELECT + INSERT own only
58 | CREATE POLICY "student_select_own_reflections" ON session_reflections
59 | FOR SELECT TO authenticated
60 | USING (student_id = auth.uid());
61 |
62 | CREATE POLICY "student_insert_own_reflections" ON session_reflections
63 | FOR INSERT TO authenticated
64 | WITH CHECK (student_id = auth.uid());
65 |

```

FILE: [supabase/migrations/20260412000400_create_session_evidence_storage_bucket.sql](#)

TYPE: .sql | LINES: 1-34 | SHA256: af93765ad506936d1a03b843156d37332b309a07cafcf4461019dfc2e2c57964

```

1 | -- Create storage bucket for session evidence
2 | INSERT INTO storage.buckets (id, name, public, file_size_limit, allowed_mime_types)
3 | VALUES (
4 |     'session-evidence',
5 |     'session-evidence',
6 |     false,
7 |     5242880, -- 5MB
8 |     ARRAY['image/jpeg', 'image/png', 'application/pdf', 'application/msword', 'application/vnd.openxmlformats-officedocument.wordprocessingml.document']
9 | ) ON CONFLICT (id) DO NOTHING;
10 |
11 | -- Student can upload to their own folder
12 | CREATE POLICY "student_upload_own_evidence" ON storage.objects
13 | FOR INSERT TO authenticated
14 | WITH CHECK (
15 |     bucket_id = 'session-evidence'
16 |     AND (storage.foldername(name))[1] = auth.uid()::text
17 | );
18 |
19 | -- Student can read their own files
20 | CREATE POLICY "student_read_own_evidence" ON storage.objects
21 | FOR SELECT TO authenticated
22 | USING (
23 |     bucket_id = 'session-evidence'
24 |     AND (storage.foldername(name))[1] = auth.uid()::text
25 | );
26 |
27 | -- Teacher can read course student files
28 | CREATE POLICY "teacher_read_course_evidence" ON storage.objects
29 | FOR SELECT TO authenticated
30 | USING (
31 |     bucket_id = 'session-evidence'
32 |     AND auth_user_role() = 'teacher'
33 | );
34 |

```

FILE: [supabase/migrations/20260412191751_create_marketplace_items.sql](#)

TYPE: .sql | LINES: 1-44 | SHA256: 7dfd27ef1951a32599d6d7b11aba7d72c40872ee9de6264dd325aee7385061f0

```

1 | CREATE TYPE marketplace_item_category AS ENUM ('cosmetic', 'educational_perk', 'power_up');
2 | CREATE TYPE marketplace_item_sub_category AS ENUM (
3 |     'profile_theme', 'avatar_frame', 'display_title',
4 |     'extra_quiz_attempt', 'deadline_extension', 'hint_token',
5 |     'xp_boost', 'streak_shield'
6 | );
7 | CREATE TYPE marketplace_stock_type AS ENUM ('unlimited', 'limited', 'one_per_student');
8 |
9 | CREATE TABLE marketplace_items (
10 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
11 |     institution_id UUID NOT NULL REFERENCES institutions(id) ON DELETE CASCADE,
12 |     name TEXT NOT NULL CHECK (char_length(name) BETWEEN 1 AND 100),
13 |     description TEXT NOT NULL CHECK (char_length(description) BETWEEN 1 AND 500),

```

```

14 | category marketplace_item_category NOT NULL,
15 | sub_category marketplace_item_sub_category NOT NULL,
16 | xp_price INTEGER NOT NULL CHECK (xp_price > 0),
17 | level_requirement INTEGER NOT NULL DEFAULT 0 CHECK (level_requirement >= 0),
18 | stock_type marketplace_stock_type NOT NULL DEFAULT 'unlimited',
19 | stock_quantity INTEGER CHECK (stock_quantity IS NULL OR stock_quantity >= 0),
20 | icon_identifier TEXT NOT NULL,
21 | metadata JSONB DEFAULT '{}',
22 | is_active BOOLEAN NOT NULL DEFAULT true,
23 | created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
24 | updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
25 | );
26 |
27 | CREATE INDEX idx_marketplace_items_institution ON marketplace_items(institution_id);
28 | CREATE INDEX idx_marketplace_items_category ON marketplace_items(category);
29 | CREATE INDEX idx_marketplace_items_active ON marketplace_items(institution_id, is_active) WHERE is_active = tr
30 |
31 | ALTER TABLE marketplace_items ENABLE ROW LEVEL SECURITY;
32 |
33 | CREATE OR REPLACE FUNCTION update_marketplace_items_updated_at()
34 | RETURNS TRIGGER AS $$
35 | BEGIN
36 |     NEW.updated_at = now();
37 |     RETURN NEW;
38 | END;
39 | $$ LANGUAGE plpgsql;
40 |
41 | CREATE TRIGGER trg_marketplace_items_updated_at
42 | BEFORE UPDATE ON marketplace_items
43 | FOR EACH ROW EXECUTE FUNCTION update_marketplace_items_updated_at();
44 |

```

FILE: [supabase/migrations/20260412191804_create_xp_purchases.sql](#)

TYPE: .sql | LINES: 1-32 | SHA256: f654105f4221b6233aad45236013fb7b2406b9c4ecc1772e6fe01a688a48aa68

```

1 | CREATE TYPE xp_purchase_status AS ENUM ('active', 'consumed', 'expired', 'refunded');
2 |
3 | CREATE TABLE xp_purchases (
4 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
5 |     student_id UUID NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
6 |     item_id UUID NOT NULL REFERENCES marketplace_items(id) ON DELETE RESTRICT,
7 |     xp_cost INTEGER NOT NULL CHECK (xp_cost > 0),
8 |     status xp_purchase_status NOT NULL DEFAULT 'active',
9 |     purchased_at TIMESTAMPTZ NOT NULL DEFAULT now(),
10 |     consumed_at TIMESTAMPTZ,
11 |     metadata JSONB DEFAULT '{}'
12 | );
13 |
14 | CREATE INDEX idx_xp_purchases_student ON xp_purchases(student_id);
15 | CREATE INDEX idx_xp_purchases_item ON xp_purchases(item_id);
16 | CREATE INDEX idx_xp_purchases_student_status ON xp_purchases(student_id, status);
17 | CREATE INDEX idx_xp_purchases_purchased_at ON xp_purchases(purchased_at DESC);
18 |
19 | ALTER TABLE xp_purchases ENABLE ROW LEVEL SECURITY;
20 |
21 | -- Prevent DELETE on xp_purchases (append-only)
22 | CREATE OR REPLACE FUNCTION prevent_xp_purchases_delete()
23 | RETURNS TRIGGER AS $$
24 | BEGIN
25 |     RAISE EXCEPTION 'Deletion of xp_purchases records is not allowed';
26 | END;
27 | $$ LANGUAGE plpgsql;
28 |
29 | CREATE TRIGGER trg_prevent_xp_purchases_delete
30 | BEFORE DELETE ON xp_purchases
31 | FOR EACH ROW EXECUTE FUNCTION prevent_xp_purchases_delete();
32 |

```

FILE: [supabase/migrations/20260412191815_create_student_equipped_items.sql](#)

TYPE: .sql | LINES: 1-15 | SHA256: b89cc119f7c5075e83d35816ead5ea83a68608a0df68c1d30072f47a7688d198

```

1 | CREATE TYPE cosmetic_slot AS ENUM ('profile_theme', 'avatar_frame', 'display_title');
2 |
3 | CREATE TABLE student_equipped_items (
4 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
5 |     student_id UUID NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
6 |     purchase_id UUID NOT NULL REFERENCES xp_purchases(id) ON DELETE CASCADE,
7 |     slot cosmetic_slot NOT NULL,
8 |     equipped_at TIMESTAMPTZ NOT NULL DEFAULT now(),
9 |     CONSTRAINT uq_student_equipped_slot UNIQUE (student_id, slot)
10 | );
11 |
12 | CREATE INDEX idx_student_equipped_student ON student_equipped_items(student_id);
13 |
14 | ALTER TABLE student_equipped_items ENABLE ROW LEVEL SECURITY;;
15 |

```

FILE: [supabase/migrations/20260412191826_create_sale_events.sql](#)

TYPE: .sql | LINES: 1-17 | SHA256: e38d0a6b36b0dd7c6e57c95a15cce929ef29199d2d06283678309f902b59114c

```

1 | CREATE TABLE sale_events (
2 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |     institution_id UUID NOT NULL REFERENCES institutions(id) ON DELETE CASCADE,
4 |     name TEXT NOT NULL CHECK (char_length(name) BETWEEN 1 AND 100),
5 |     discount_percentage INTEGER NOT NULL CHECK (discount_percentage BETWEEN 5 AND 90),
6 |     start_date TIMESTAMPTZ NOT NULL,
7 |     end_date TIMESTAMPTZ NOT NULL,
8 |     created_by UUID NOT NULL REFERENCES profiles(id),
9 |     created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
10 |     CONSTRAINT chk_sale_event_dates CHECK (end_date > start_date)
11 | );
12 |
13 | CREATE INDEX idx_sale_events_institution ON sale_events(institution_id);

```

```

14 | CREATE INDEX idx_sale_events_active ON sale_events(institution_id, start_date, end_date);
15 |
16 | ALTER TABLE sale_events ENABLE ROW LEVEL SECURITY;;
17 |

```

FILE: supabase/migrations/20260412191842_create_sale_event_items.sql

TYPE: .sql | LINES: 1-10 | SHA256: e9aa1e845b767f9ad753b96408de2aa0940f5d3ec5f1b99c69be6296164d1f19

```

1 | CREATE TABLE sale_event_items (
2 |   sale_event_id UUID NOT NULL REFERENCES sale_events(id) ON DELETE CASCADE,
3 |   item_id UUID NOT NULL REFERENCES marketplace_items(id) ON DELETE CASCADE,
4 |   PRIMARY KEY (sale_event_id, item_id)
5 | );
6 |
7 | CREATE INDEX idx_sale_event_items_item ON sale_event_items(item_id);
8 |
9 | ALTER TABLE sale_event_items ENABLE ROW LEVEL SECURITY;;
10 |

```

FILE: supabase/migrations/20260412191904_create_student_active_boosts.sql

TYPE: .sql | LINES: 1-16 | SHA256: bfe83348f2fd93c0c23cb3ba1b8638238d4b92da7d1cd3f0e8124c859352b4d3

```

1 | CREATE TABLE student_active_boosts (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
4 |   boost_type TEXT NOT NULL DEFAULT 'xp_boost',
5 |   multiplier NUMERIC(3,1) NOT NULL DEFAULT 2.0 CHECK (multiplier > 1.0),
6 |   purchase_id UUID NOT NULL REFERENCES xp_purchases(id) ON DELETE CASCADE,
7 |   activated_at TIMESTAMPTZ NOT NULL DEFAULT now(),
8 |   expires_at TIMESTAMPTZ NOT NULL,
9 |   CONSTRAINT chk_boost_duration CHECK (expires_at > activated_at)
10 | );
11 |
12 | CREATE INDEX idx_student_active_boosts_student ON student_active_boosts(student_id);
13 | CREATE INDEX idx_student_active_boosts_expires ON student_active_boosts(student_id, expires_at DESC);
14 |
15 | ALTER TABLE student_active_boosts ENABLE ROW LEVEL SECURITY;;
16 |

```

FILE: supabase/migrations/20260412191920_create_deadline_extensions.sql

TYPE: .sql | LINES: 1-18 | SHA256: d8ee18c878cab727b01c53b45c9a705fa011d2a995f86f30ec2467e1242a2df7

```

1 | CREATE TABLE deadline_extensions (
2 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
3 |   student_id UUID NOT NULL REFERENCES profiles(id) ON DELETE CASCADE,
4 |   assignment_id UUID NOT NULL REFERENCES assignments(id) ON DELETE CASCADE,
5 |   purchase_id UUID NOT NULL REFERENCES xp_purchases(id) ON DELETE CASCADE,
6 |   original_deadline TIMESTAMPTZ NOT NULL,
7 |   extended_deadline TIMESTAMPTZ NOT NULL,
8 |   revoked BOOLEAN NOT NULL DEFAULT false,
9 |   revoked_by UUID REFERENCES profiles(id),
10 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
11 |   CONSTRAINT uq_deadline_extension_student_assignment UNIQUE (student_id, assignment_id)
12 | );
13 |
14 | CREATE INDEX idx_deadline_extensions_student ON deadline_extensions(student_id);
15 | CREATE INDEX idx_deadline_extensions_assignment ON deadline_extensions(assignment_id);
16 |
17 | ALTER TABLE deadline_extensions ENABLE ROW LEVEL SECURITY;;
18 |

```

FILE: supabase/migrations/20260412191944_create_process_marketplace_purchase_fn.sql

TYPE: .sql | LINES: 1-104 | SHA256: 24a75de5c375c8363a34cab0f72e95ee9e636391832833abce7cd12404faeaaa

```

1 | CREATE OR REPLACE FUNCTION process_marketplace_purchase(
2 |   p_student_id UUID,
3 |   p_item_id UUID,
4 |   p_institution_id UUID
5 | )
6 | RETURNS JSONB
7 | LANGUAGE plpgsql
8 | SECURITY DEFINER
9 | AS $$
10 | DECLARE
11 |   v_balance INTEGER;
12 |   v_item RECORD;
13 |   v_student_level INTEGER;
14 |   v_effective_price INTEGER;
15 |   v_discount INTEGER;
16 |   v_purchase_id UUID;
17 |   v_existing_purchase_count INTEGER;
18 |   v_current_freezes INTEGER;
19 | BEGIN
20 |   -- Lock student purchases to prevent concurrent double-spend
21 |   PERFORM 1 FROM xp_purchases WHERE student_id = p_student_id FOR UPDATE;
22 |
23 |   -- Compute XP balance
24 |   SELECT COALESCE(
25 |     (SELECT SUM(xp_amount) FROM xp_transactions WHERE student_id = p_student_id), 0
26 |   ) - COALESCE(
27 |     (SELECT SUM(xp_cost) FROM xp_purchases WHERE student_id = p_student_id AND status != 'refunded'), 0
28 |   ) INTO v_balance;
29 |
30 |   -- Fetch item
31 |   SELECT * INTO v_item FROM marketplace_items
32 |     WHERE id = p_item_id AND institution_id = p_institution_id AND is_active = true;
33 |   IF NOT FOUND THEN
34 |     RETURN jsonb_build_object('success', false, 'error_code', 'ITEM_INACTIVE');
35 |   END IF;
36 |
37 |   -- Check level requirement
38 |   SELECT COALESCE(level, 1) INTO v_student_level
39 |     FROM student_gamification WHERE student_id = p_student_id;

```

```

40 | IF v_student_level < v_item.level_requirement THEN
41 |     RETURN jsonb_build_object('success', false, 'error_code', 'LEVEL_REQUIREMENT');
42 | END IF;
43 |
44 | -- Check stock
45 | IF v_item.stock_type = 'limited' AND v_item.stock_quantity <= 0 THEN
46 |     RETURN jsonb_build_object('success', false, 'error_code', 'OUT_OF_STOCK');
47 | END IF;
48 |
49 | IF v_item.stock_type = 'one_per_student' THEN
50 |     SELECT COUNT(*) INTO v_existing_purchase_count
51 |     FROM xp_purchases WHERE student_id = p_student_id AND item_id = p_item_id AND status != 'refunded';
52 |     IF v_existing_purchase_count > 0 THEN
53 |         RETURN jsonb_build_object('success', false, 'error_code', 'ALREADY_OWNED');
54 |     END IF;
55 | END IF;
56 |
57 | -- Streak shield max check
58 | IF v_item.sub_category::text = 'streak_shield' THEN
59 |     SELECT COALESCE(streak_freezes_available, 0) INTO v_current_freezes
60 |     FROM student_gamification WHERE student_id = p_student_id;
61 |     IF v_current_freezes >= 3 THEN
62 |         RETURN jsonb_build_object('success', false, 'error_code', 'MAX_INVENTORY');
63 |     END IF;
64 | END IF;
65 |
66 | -- Resolve sale price (highest active discount wins)
67 | SELECT COALESCE(MAX(se.discount_percentage), 0) INTO v_discount
68 | FROM sale_event_items sei
69 | JOIN sale_events se ON se.id = sei.sale_event_id
70 | WHERE sei.item_id = p_item_id
71 |     AND se.institution_id = p_institution_id
72 |     AND se.start_date <= NOW()
73 |     AND se.end_date > NOW();
74 |
75 | v_effective_price := GREATEST(1, v_item.xp_price - FLOOR(v_item.xp_price * v_discount / 100));
76 |
77 | -- Check balance
78 | IF v_balance < v_effective_price THEN
79 |     RETURN jsonb_build_object('success', false, 'error_code', 'INSUFFICIENT_BALANCE',
80 |     'detail', jsonb_build_object('balance', v_balance, 'price', v_effective_price));
81 | END IF;
82 |
83 | -- Insert purchase
84 | INSERT INTO xp_purchases (student_id, item_id, xp_cost, status, purchased_at)
85 | VALUES (p_student_id, p_item_id, v_effective_price, 'active', NOW())
86 | RETURNING id INTO v_purchase_id;
87 |
88 | -- Decrement stock if limited
89 | IF v_item.stock_type = 'limited' THEN
90 |     UPDATE marketplace_items SET stock_quantity = stock_quantity - 1
91 |     WHERE id = p_item_id AND stock_quantity > 0;
92 | END IF;
93 |
94 | RETURN jsonb_build_object(
95 |     'success', true,
96 |     'purchase_id', v_purchase_id,
97 |     'xp_cost', v_effective_price,
98 |     'new_balance', v_balance - v_effective_price,
99 |     'item_category', v_item.category,
100 |     'item_sub_category', v_item.sub_category
101 | );
102 | END;
103 | $$;
104 |

```

FILE: supabase/migrations/20260412191955_create_get_xp_balance_fn.sql

TYPE: .sql | LINES: 1-20 | SHA256: 9c407dc8424ebbb7d52164252d3f00b347f5da02116bf1339ce904e7b1d7477d

```

1 | CREATE OR REPLACE FUNCTION get_xp_balance(p_student_id UUID)
2 | RETURNS INTEGER
3 | LANGUAGE plpgsql
4 | STABLE
5 | SECURITY DEFINER
6 | AS $$
7 | DECLARE
8 |     v_earned INTEGER;
9 |     v_spent INTEGER;
10 | BEGIN
11 |     SELECT COALESCE(SUM(xp_amount), 0) INTO v_earned
12 |     FROM xp_transactions WHERE student_id = p_student_id;
13 |
14 |     SELECT COALESCE(SUM(xp_cost), 0) INTO v_spent
15 |     FROM xp_purchases WHERE student_id = p_student_id AND status != 'refunded';
16 |
17 |     RETURN GREATEST(0, v_earned - v_spent);
18 | END;
19 | $$;
20 |

```

FILE: supabase/migrations/20260412192010_create_get_effective_price_fn.sql

TYPE: .sql | LINES: 1-29 | SHA256: 6cecfccab4607eea518cc8023d026cd9869fb54a9dd65cabef4b65c18273691e

```

1 | CREATE OR REPLACE FUNCTION get_effective_price(p_item_id UUID, p_institution_id UUID)
2 | RETURNS INTEGER
3 | LANGUAGE plpgsql
4 | STABLE
5 | SECURITY DEFINER
6 | AS $$
7 | DECLARE
8 |     v_base_price INTEGER;
9 |     v_discount INTEGER;
10 | BEGIN
11 |     SELECT xp_price INTO v_base_price

```



```

12 |         FROM marketplace_items WHERE id = p_item_id AND institution_id = p_institution_id;
13 |
14 |     IF NOT FOUND THEN
15 |         RETURN NULL;
16 |     END IF;
17 |
18 |     SELECT COALESCE(MAX(se.discount_percentage), 0) INTO v_discount
19 |     FROM sale_event_items sei
20 |     JOIN sale_events se ON se.id = sei.sale_event_id
21 |     WHERE sei.item_id = p_item_id
22 |     AND se.institution_id = p_institution_id
23 |     AND se.start_date <= NOW()
24 |     AND se.end_date > NOW();
25 |
26 |     RETURN GREATEST(1, v_base_price - FLOOR(v_base_price * v_discount / 100));
27 | END;
28 | $$;
29 |

```

FILE: [supabase/migrations/20260412192034_create_marketplace_rls_policies.sql](#)

TYPE: .sql | LINES: 1-123 | SHA256: 5ff1d9dd92ffeb986ebc680ec5b04e1720dfc301bce51d897f33ba49b17de71f

```

1 | -- %P%P%P marketplace_items RLS %P%P%P
2 | CREATE POLICY "students_select_active_items" ON marketplace_items
3 |   FOR SELECT TO authenticated
4 |   USING (is_active = true AND institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid()));
5 |
6 | CREATE POLICY "admin_all_items" ON marketplace_items
7 |   FOR ALL TO authenticated
8 |   USING (
9 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
10 |    AND institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid())
11 |  );
12 | WITH CHECK (
13 |   (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
14 |   AND institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid())
15 | );
16 |
17 | -- %P%P%P xp_purchases RLS %P%P%P
18 | CREATE POLICY "student_select_own_purchases" ON xp_purchases
19 |   FOR SELECT TO authenticated
20 |   USING (student_id = auth.uid());
21 |
22 | CREATE POLICY "student_insert_own_purchases" ON xp_purchases
23 |   FOR INSERT TO authenticated
24 |   WITH CHECK (student_id = auth.uid());
25 |
26 | CREATE POLICY "student_update_own_purchases" ON xp_purchases
27 |   FOR UPDATE TO authenticated
28 |   USING (student_id = auth.uid());
29 |
30 | CREATE POLICY "admin_select_institution_purchases" ON xp_purchases
31 |   FOR SELECT TO authenticated
32 |   USING (
33 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
34 |     AND student_id IN (
35 |       SELECT id FROM profiles WHERE institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid(
36 |     )
37 |   );
38 |
39 | CREATE POLICY "parent_select_linked_purchases" ON xp_purchases
40 |   FOR SELECT TO authenticated
41 |   USING (
42 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'parent'
43 |     AND student_id IN (
44 |       SELECT student_id FROM parent_student_links WHERE parent_id = auth.uid() AND verified = true
45 |     )
46 |   );
47 |
48 | -- %P%P%P student_equipped_items RLS %P%P%P
49 | CREATE POLICY "student_manage_own_equipped" ON student_equipped_items
50 |   FOR ALL TO authenticated
51 |   USING (student_id = auth.uid())
52 |   WITH CHECK (student_id = auth.uid());
53 |
54 | -- %P%P%P sale_events RLS %P%P%P
55 | CREATE POLICY "authenticated_select_sale_events" ON sale_events
56 |   FOR SELECT TO authenticated
57 |   USING (institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid()));
58 |
59 | CREATE POLICY "admin_manage_sale_events" ON sale_events
60 |   FOR ALL TO authenticated
61 |   USING (
62 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
63 |     AND institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid())
64 |   )
65 |   WITH CHECK (
66 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
67 |     AND institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid())
68 |   );
69 |
70 | -- %P%P%P sale_event_items RLS %P%P%P
71 | CREATE POLICY "authenticated_select_sale_event_items" ON sale_event_items
72 |   FOR SELECT TO authenticated
73 |   USING (
74 |     sale_event_id IN (
75 |       SELECT id FROM sale_events WHERE institution_id = (SELECT institution_id FROM profiles WHERE id = auth.u
76 |     )
77 |   );
78 |
79 | CREATE POLICY "admin_manage_sale_event_items" ON sale_event_items
80 |   FOR ALL TO authenticated
81 |   USING (
82 |     (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'

```



```

83 |         AND sale_event_id IN (
84 |             SELECT id FROM sale_events WHERE institution_id = (SELECT institution_id FROM profiles WHERE id = auth.u
85 |         )
86 |     )
87 |     WITH CHECK (
88 |         (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
89 |         AND sale_event_id IN (
90 |             SELECT id FROM sale_events WHERE institution_id = (SELECT institution_id FROM profiles WHERE id = auth.u
91 |         )
92 |     );
93 |
94 | -- %P%P%P student_active_boosts RLS %P%P%P
95 | CREATE POLICY "student_select_own_boosts" ON student_active_boosts
96 |     FOR SELECT TO authenticated
97 |     USING (student_id = auth.uid());
98 |
99 | -- %P%P%P deadline_extensions RLS %P%P%P
100 | CREATE POLICY "student_select_own_extensions" ON deadline_extensions
101 |     FOR SELECT TO authenticated
102 |     USING (student_id = auth.uid());
103 |
104 | CREATE POLICY "teacher_select_course_extensions" ON deadline_extensions
105 |     FOR SELECT TO authenticated
106 |     USING (
107 |         (SELECT role FROM profiles WHERE id = auth.uid()) = 'teacher'
108 |         AND assignment_id IN (
109 |             SELECT a.id FROM assignments a
110 |             JOIN courses c ON c.id = a.course_id
111 |             WHERE c.teacher_id = auth.uid()
112 |         )
113 |     );
114 |
115 | CREATE POLICY "admin_select_institution_extensions" ON deadline_extensions
116 |     FOR SELECT TO authenticated
117 |     USING (
118 |         (SELECT role FROM profiles WHERE id = auth.uid()) = 'admin'
119 |         AND student_id IN (
120 |             SELECT id FROM profiles WHERE institution_id = (SELECT institution_id FROM profiles WHERE id = auth.uid(
121 |         )
122 |     );
123 |

```

FILE: supabase/migrations/20260412192106_seed_default_marketplace_items.sql

TYPE: .sql | LINES: 1-40 | SHA256: af0f0fd149f0b217cf67f7f0f8c6312261a4389051c31e0b0716ff1efce1e2ea

```

1 | -- Seed default marketplace items function (called per institution)
2 | CREATE OR REPLACE FUNCTION seed_marketplace_items(p_institution_id UUID)
3 | RETURNS void
4 | LANGUAGE plpgsql
5 | SECURITY DEFINER
6 | AS $$
7 | BEGIN
8 |     -- Cosmetic: Profile Themes
9 |     INSERT INTO marketplace_items (institution_id, name, description, category, sub_category, xp_price, level_re
10 |     (p_institution_id, 'Ocean Blue', 'A calming ocean-inspired theme with deep blue accents', 'cosmetic', 'pro
11 |     (p_institution_id, 'Forest Green', 'A nature-inspired theme with lush green tones', 'cosmetic', 'profile_t
12 |     (p_institution_id, 'Sunset Orange', 'A warm sunset theme with orange and amber accents', 'cosmetic', 'prof
13 |     (p_institution_id, 'Midnight Purple', 'A sleek dark theme with purple highlights', 'cosmetic', 'profile_th
14 |
15 |     -- Cosmetic: Avatar Frames
16 |     INSERT INTO marketplace_items (institution_id, name, description, category, sub_category, xp_price, level_re
17 |     (p_institution_id, 'Bronze Ring', 'A simple bronze frame for your avatar', 'cosmetic', 'avatar_frame', 300
18 |     (p_institution_id, 'Silver Glow', 'A shimmering silver frame with subtle glow', 'cosmetic', 'avatar_frame'
19 |     (p_institution_id, 'Gold Crown', 'A prestigious gold frame with crown accent', 'cosmetic', 'avatar_frame',
20 |
21 |     -- Cosmetic: Display Titles
22 |     INSERT INTO marketplace_items (institution_id, name, description, category, sub_category, xp_price, level_re
23 |     (p_institution_id, 'The Scholar', 'Display "The Scholar" on the leaderboard', 'cosmetic', 'display_title',
24 |     (p_institution_id, 'Night Owl', 'Display "Night Owl" on the leaderboard', 'cosmetic', 'display_title', 400
25 |     (p_institution_id, 'Trailblazer', 'Display "Trailblazer" on the leaderboard', 'cosmetic', 'display_title',
26 |     (p_institution_id, 'Grandmaster', 'Display "Grandmaster" on the leaderboard', 'cosmetic', 'display_title',
27 |
28 |     -- Educational Perks
29 |     INSERT INTO marketplace_items (institution_id, name, description, category, sub_category, xp_price, level_re
30 |     (p_institution_id, 'Extra Quiz Attempt', 'Get one additional attempt on any quiz', 'educational_perk', 'ex
31 |     (p_institution_id, 'Deadline Extension', 'Extend any assignment deadline by 24 hours', 'educational_perk', 'ex
32 |     (p_institution_id, 'AI Tutor Hint Pack', '5 extra AI Tutor messages for today', 'educational_perk', 'hint_
33 |
34 |     -- Power-ups
35 |     INSERT INTO marketplace_items (institution_id, name, description, category, sub_category, xp_price, level_re
36 |     (p_institution_id, '2x XP Boost (1hr)', 'Double all XP earned for 1 hour', 'power_up', 'xp_boost', 500, 4,
37 |     (p_institution_id, 'Streak Shield', 'Protect your streak for one missed day', 'power_up', 'streak_shield',
38 | END;
39 | $$;
40 |

```

FILE: supabase/migrations/20260414041812_create_student_content_table.sql

TYPE: .sql | LINES: 1-24 | SHA256: 79719ee9127722d06bcbb4953c0c856c51f6645f9f50266e901830de4f5f0041

```

1 | -- =====
2 | -- student_content – Student-created learning content
3 | -- =====
4 |
5 | CREATE TABLE student_content (
6 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
7 |     institution_id UUID NOT NULL REFERENCES institutions(id),
8 |     student_id UUID NOT NULL REFERENCES profiles(id),
9 |     content_type VARCHAR(30) NOT NULL CHECK (content_type IN ('study_plan', 'quiz_question', 'explanation_video'
10 |     clo_id UUID REFERENCES learning_outcomes(id),
11 |     title VARCHAR(200) NOT NULL,
12 |     content_data JSONB NOT NULL DEFAULT '{}',
13 |     status VARCHAR(20) NOT NULL DEFAULT 'pending' CHECK (status IN ('pending', 'approved', 'rejected')),
14 |     reviewer_id UUID REFERENCES profiles(id),
15 |     reviewer_feedback TEXT,

```

```

16 | reviewed_at TIMESTAMPTZ,
17 | created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
18 | updated_at TIMESTAMPTZ NOT NULL DEFAULT now()
19 | );
20 |
21 | CREATE INDEX idx_student_content_student ON student_content (student_id, status);
22 | CREATE INDEX idx_student_content_institution ON student_content (institution_id, status);
23 | CREATE INDEX idx_student_content_clo ON student_content (clo_id) WHERE clo_id IS NOT NULL;;
24 |

```

FILE: supabase/migrations/20260414041826_create_knowledge_quests_table.sql

TYPE: .sql | LINES: 1-26 | SHA256: 7a6f3452262b2345ab1afe6a7fa6d09aaab8334e9e4cc1d41467e42eb97e0520

```

1 | -- =====
2 | -- knowledge_quests - Time-limited learning challenges
3 | -- =====
4 |
5 | CREATE TABLE knowledge_quests (
6 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
7 |   institution_id UUID NOT NULL REFERENCES institutions(id),
8 |   title VARCHAR(200) NOT NULL,
9 |   description TEXT NOT NULL,
10 |   quest_type VARCHAR(30) NOT NULL CHECK (quest_type IN ('quiz_challenge', 'content_creation', 'peer_review')),
11 |   target_clo_ids UUID[] DEFAULT '{}',
12 |   start_date TIMESTAMPTZ NOT NULL,
13 |   end_date TIMESTAMPTZ NOT NULL,
14 |   reward_type VARCHAR(10) NOT NULL CHECK (reward_type IN ('item', 'xp')),
15 |   reward_item_id UUID REFERENCES marketplace_items(id),
16 |   reward_xp_amount INTEGER CHECK (reward_xp_amount > 0 OR reward_type = 'item'),
17 |   max_participants INTEGER,
18 |   created_by UUID NOT NULL REFERENCES profiles(id),
19 |   created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
20 |   is_active BOOLEAN NOT NULL DEFAULT true,
21 |   CONSTRAINT valid_quest_dates CHECK (end_date > start_date)
22 | );
23 |
24 | CREATE INDEX idx_knowledge_quests_institution ON knowledge_quests (institution_id, start_date, end_date);
25 | CREATE INDEX idx_knowledge_quests_active ON knowledge_quests (institution_id, is_active) WHERE is_active = true
26 |

```

FILE: supabase/migrations/20260414041846_create_student_quest_progress_table.sql

TYPE: .sql | LINES: 1-18 | SHA256: 4c38802c24b88de99a09d3eb51d1c34af1123b19e4fc0383da0e2e3c93bb8d82

```

1 | -- =====
2 | -- student_quest_progress - Student progress on knowledge quests
3 | -- =====
4 |
5 | CREATE TABLE student_quest_progress (
6 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
7 |   student_id UUID NOT NULL REFERENCES profiles(id),
8 |   quest_id UUID NOT NULL REFERENCES knowledge_quests(id),
9 |   status VARCHAR(20) NOT NULL DEFAULT 'started' CHECK (status IN ('started', 'completed', 'expired')),
10 |   started_at TIMESTAMPTZ NOT NULL DEFAULT now(),
11 |   completed_at TIMESTAMPTZ,
12 |   reward_claimed BOOLEAN NOT NULL DEFAULT false,
13 |   UNIQUE (student_id, quest_id)
14 | );
15 |
16 | CREATE INDEX idx_quest_progress_student ON student_quest_progress (student_id, status);
17 | CREATE INDEX idx_quest_progress_quest ON student_quest_progress (quest_id);
18 |

```

FILE: supabase/

migrations/20260414041918_rls_student_content_knowledge_quests_progress.sql

TYPE: .sql | LINES: 1-94 | SHA256: 700ce6321d22a3f320887554262218d6affa5383d0fba10edb881341912a5bcc

```

1 | -- =====
2 | -- student_content - RLS
3 | -- =====
4 | ALTER TABLE student_content ENABLE ROW LEVEL SECURITY;
5 |
6 | -- Students: SELECT and INSERT their own content
7 | CREATE POLICY "student_content_student_select" ON student_content
8 |   FOR SELECT TO authenticated
9 |   USING (
10 |     auth_user_role() = 'student'
11 |     AND student_id = auth.uid()
12 |   );
13 |
14 | CREATE POLICY "student_content_student_insert" ON student_content
15 |   FOR INSERT TO authenticated
16 |   WITH CHECK (
17 |     auth_user_role() = 'student'
18 |     AND student_id = auth.uid()
19 |     AND institution_id = auth.institution_id()
20 |   );
21 |
22 | -- Teachers: SELECT content in their institution (submitted/approved/rejected)
23 | CREATE POLICY "student_content_teacher_select" ON student_content
24 |   FOR SELECT TO authenticated
25 |   USING (
26 |     auth_user_role() = 'teacher'
27 |     AND institution_id = auth.institution_id()
28 |     AND status IN ('pending', 'approved', 'rejected')
29 |   );
30 |
31 | -- Teachers: UPDATE status (approve/reject)
32 | CREATE POLICY "student_content_teacher_review" ON student_content
33 |   FOR UPDATE TO authenticated
34 |   USING (
35 |     auth_user_role() = 'teacher'
36 |     AND institution_id = auth.institution_id()
37 |   )

```

```

38 | WITH CHECK (
39 |     auth_user_role() = 'teacher'
40 |     AND institution_id = auth_institution_id()
41 | );
42 |
43 | -- Admins: full access within institution
44 | CREATE POLICY "student_content_admin_all" ON student_content
45 | FOR ALL TO authenticated
46 | USING (
47 |     auth_user_role() = 'admin'
48 |     AND institution_id = auth_institution_id()
49 | );
50 |
51 | -- =====
52 | -- knowledge_requests - RLS
53 | -- =====
54 | ALTER TABLE knowledge_requests ENABLE ROW LEVEL SECURITY;
55 |
56 | -- Students: SELECT active quests in their institution
57 | CREATE POLICY "knowledge_requests_student_select" ON knowledge_requests
58 | FOR SELECT TO authenticated
59 | USING (
60 |     auth_user_role() = 'student'
61 |     AND institution_id = auth_institution_id()
62 | );
63 |
64 | -- Admins: full CRUD within institution
65 | CREATE POLICY "knowledge_requests_admin_all" ON knowledge_requests
66 | FOR ALL TO authenticated
67 | USING (
68 |     auth_user_role() = 'admin'
69 |     AND institution_id = auth_institution_id()
70 | );
71 |
72 | -- =====
73 | -- student_quest_progress - RLS
74 | -- =====
75 | ALTER TABLE student_quest_progress ENABLE ROW LEVEL SECURITY;
76 |
77 | -- Students: SELECT, INSERT, UPDATE their own progress
78 | CREATE POLICY "quest_progress_student_own" ON student_quest_progress
79 | FOR ALL TO authenticated
80 | USING (
81 |     auth_user_role() = 'student'
82 |     AND student_id = auth.uid()
83 | );
84 |
85 | -- Admins: SELECT within institution
86 | CREATE POLICY "quest_progress_admin_select" ON student_quest_progress
87 | FOR SELECT TO authenticated
88 | USING (
89 |     auth_user_role() = 'admin'
90 |     AND quest_id IN (
91 |         SELECT id FROM knowledge_requests WHERE institution_id = auth_institution_id()
92 |     )
93 | );
94 |

```

FILE: [supabase/migrations/20260414042659_20260720000016_add_dynamic_price_override_to_marketplace_items.sql](#)

TYPE: .sql | LINES: 1-12 | SHA256: 04d239c89496ce878147bb28494de85ed0d11552c6be6f2c36ae1aca0fa52b6c

```

1 | -- =====
2 | -- Add dynamic_price_override column to marketplace_items
3 | -- When not null, this overrides the base xp_price for display.
4 | -- The recalculate_dynamic_prices function sets this value.
5 | -- =====
6 |
7 | ALTER TABLE marketplace_items
8 | ADD COLUMN dynamic_price_override INTEGER;
9 |
10 | COMMENT ON COLUMN marketplace_items.dynamic_price_override IS
11 | 'When not null, overrides xp_price for display. Set by recalculate_dynamic_prices cron job.';
12 |

```

FILE: [supabase/migrations/20260414042719_20260720000017_create_class_donations_table.sql](#)

TYPE: .sql | LINES: 1-21 | SHA256: 2cd590d7b805f7fa03e61509484c93b2a3dd732b3bd69624a5923ac30ebd9e85

```

1 | -- =====
2 | -- class_donations - XP sink: class-wide resource unlocks
3 | -- Students donate XP toward a shared goal for their course.
4 | -- =====
5 |
6 | CREATE TABLE class_donations (
7 |     id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
8 |     institution_id UUID NOT NULL REFERENCES institutions(id),
9 |     course_id UUID NOT NULL REFERENCES courses(id),
10 |     resource_description TEXT NOT NULL,
11 |     goal_amount INTEGER NOT NULL CHECK (goal_amount >= 100),
12 |     current_total INTEGER NOT NULL DEFAULT 0 CHECK (current_total >= 0),
13 |     status VARCHAR(20) NOT NULL DEFAULT 'active' CHECK (status IN ('active', 'completed', 'cancelled')),
14 |     created_by UUID NOT NULL REFERENCES profiles(id),
15 |     created_at TIMESTAMPTZ NOT NULL DEFAULT now(),
16 |     completed_at TIMESTAMPTZ
17 | );
18 |
19 | CREATE INDEX idx_class_donations_course ON class_donations (course_id, status);
20 | CREATE INDEX idx_class_donations_institution ON class_donations (institution_id, status);
21 |

```

FILE: supabase/migrations/20260414042740_20260720000018_create_class_donation_contributions_table.sql

TYPE: .sql | LINES: 1-17 | SHA256: c9fa28ca7bada9d0f6273fbf7d524d1e70f0dc24404840d5795aa85535a288ff

```
1 | -- =====
2 | -- class_donation_contributions - Individual student contributions
3 | -- Links to class_donations and optionally to xp_purchases.
4 | -- =====
5 |
6 | CREATE TABLE class_donation_contributions (
7 |   id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
8 |   donation_id UUID NOT NULL REFERENCES class_donations(id),
9 |   student_id UUID NOT NULL REFERENCES profiles(id),
10 |   xp_amount INTEGER NOT NULL CHECK (xp_amount > 0),
11 |   purchase_id UUID REFERENCES xp_purchases(id),
12 |   contributed_at TIMESTAMPTZ NOT NULL DEFAULT now()
13 | );
14 |
15 | CREATE INDEX idx_donation_contributions_donation ON class_donation_contributions (donation_id);
16 | CREATE INDEX idx_donation_contributions_student ON class_donation_contributions (student_id);
17 |
```

FILE: supabase/migrations/20260414042807_20260720000019_create_get_earn_spend_ratio_function.sql

TYPE: .sql | LINES: 1-37 | SHA256: 4588b9766e6ee2c1e43f067c4b8f44d75ac99556fc42c6a7bd97df712926e651

```
1 | -- =====
2 | -- get_earn_spend_ratio - Compute earn/spend ratio for an institution
3 | -- Returns: total_earned, total_spent, ratio, status
4 | -- Status: healthy (2:1 to 5:1), inflationary (>5:1), deflationary (<2:1)
5 | -- =====
6 |
7 | CREATE OR REPLACE FUNCTION get_earn_spend_ratio(p_institution_id UUID)
8 | RETURNS TABLE (total_earned BIGINT, total_spent BIGINT, ratio NUMERIC, status TEXT)
9 | LANGUAGE sql
10 | STABLE
11 | SECURITY DEFINER
12 | AS $$
13 |   WITH earned AS (
14 |     SELECT COALESCE(SUM(xt.xp_amount), 0) AS total
15 |     FROM xp_transactions xt
16 |     JOIN profiles p ON p.id = xt.student_id
17 |     WHERE p.institution_id = p_institution_id
18 |   ),
19 |   spent AS (
20 |     SELECT COALESCE(SUM(xp.xp_cost), 0) AS total
21 |     FROM xp_purchases xp
22 |     JOIN marketplace_items mi ON mi.id = xp.item_id
23 |     WHERE mi.institution_id = p_institution_id AND xp.status != 'refunded'
24 |   )
25 | SELECT
26 |   earned.total AS total_earned,
27 |   spent.total AS total_spent,
28 |   CASE WHEN spent.total > 0 THEN ROUND(earned.total::NUMERIC / spent.total, 2) ELSE NULL END AS ratio,
29 |   CASE
30 |     WHEN spent.total = 0 THEN 'no_spending'
31 |     WHEN earned.total::NUMERIC / spent.total > 5 THEN 'inflationary'
32 |     WHEN earned.total::NUMERIC / spent.total < 2 THEN 'deflationary'
33 |     ELSE 'healthy'
34 |   END AS status
35 | FROM earned, spent;
36 | $$;
37 |
```

FILE: supabase/migrations/20260414042824_20260720000020_create_recalculate_dynamic_prices_function.sql

TYPE: .sql | LINES: 1-57 | SHA256: e29df59dc417f2423ddb53be561079c1f59258d84f5710a814bb5201bbe090bd

```
1 | -- =====
2 | -- recalculate_dynamic_prices - Adjust marketplace item prices
3 | -- based on purchase demand in the last 30 days.
4 | -- High demand (>10 purchases): increase up to 150% of base
5 | -- Low demand (<3 purchases): decrease to 50% of base
6 | -- Called by pg_cron daily at midnight UTC.
7 | -- =====
8 |
9 | CREATE OR REPLACE FUNCTION recalculate_dynamic_prices(p_institution_id UUID)
10 | RETURNS VOID
11 | LANGUAGE plpgsql
12 | SECURITY DEFINER
13 | AS $$
14 | DECLARE
15 |   r RECORD;
16 |   v_demand_count INTEGER;
17 | BEGIN
18 |   FOR r IN
19 |     SELECT mi.id, mi.xp_price
20 |     FROM marketplace_items mi
21 |     WHERE mi.institution_id = p_institution_id
22 |     AND mi.is_active = true
23 |   LOOP
24 |     -- Count purchases in the last 30 days for this item
25 |     SELECT COUNT(*) INTO v_demand_count
26 |     FROM xp_purchases xp
27 |     WHERE xp.item_id = r.id
28 |     AND xp.purchased_at > NOW() - INTERVAL '30 days'
29 |     AND xp.status != 'refunded';
30 |
31 |     -- Adjust price based on demand
32 |     IF v_demand_count > 10 THEN
33 |       -- High demand: increase price up to 150% of base
34 |       UPDATE marketplace_items
```

```

35 |         SET dynamic_price_override = LEAST(
36 |             FLOOR(r.xp_price * 1.5),
37 |             FLOOR(r.xp_price + (r.xp_price * 0.5 * LEAST(v_demand_count, 30)::NUMERIC / 30))
38 |         )
39 |         WHERE id = r.id;
40 |     ELSIF v_demand_count < 3 THEN
41 |         -- Low demand: decrease price to 50% of base
42 |         UPDATE marketplace_items
43 |         SET dynamic_price_override = GREATEST(
44 |             FLOOR(r.xp_price * 0.5),
45 |             FLOOR(r.xp_price - (r.xp_price * 0.5 * (3 - v_demand_count)::NUMERIC / 3))
46 |         )
47 |         WHERE id = r.id;
48 |     ELSE
49 |         -- Normal demand: clear override
50 |         UPDATE marketplace_items
51 |         SET dynamic_price_override = NULL
52 |         WHERE id = r.id;
53 |     END IF;
54 | END LOOP;
55 | END;
56 | $$;;
57 |

```

FILE: supabase/

migrations/20260414042921_20260720000021_pgcron_dynamic_price_recalculation.sql

TYPE: .sql | LINES: 1-22 | SHA256: 149948341301a7d64d13289b9ed96c890546ba4dff252e616caeb8d80fee8314

```

1 | -- =====
2 | -- pg_cron job: Daily dynamic price recalculation at midnight UTC
3 | -- Uses the conditional pgcron guard pattern.
4 | -- =====
5 |
6 | DO $outer$
7 | BEGIN
8 |     IF EXISTS (SELECT 1 FROM pg_extension WHERE extname = 'pg_cron') THEN
9 |         -- Recalculate dynamic prices for all institutions daily at midnight UTC
10 |         PERFORM cron.schedule(
11 |             'recalculate-dynamic-prices',
12 |             '0 0 * * *',
13 |             'SELECT recalculate_dynamic_prices(i.id) FROM institutions i'
14 |         );
15 |
16 |         RAISE NOTICE 'pg_cron job recalculate-dynamic-prices created successfully';
17 |     ELSE
18 |         RAISE NOTICE 'pg_cron not available – skipping dynamic price recalculation cron job.';
19 |     END IF;
20 | END;
21 | $outer$;;
22 |

```