

semesterplannerLua — Semesterplanner package in lua with tikz only

Lukas Heindl

<+email+>

📧: <https://github.com/atticus-sullivan/semesterplannerLua>

? from ?

Abstract

This package provides a mean to easily print a timetable e.g. for a semesterplan. The reason for this package to exist is that I wanted to reimplement <https://github.com/nlschn/semesterplanner/> with printing the timetable with `tikz` only (which is more easily to be modified) and with the ability of making entries spanning only a fraction of the column (for showing simultaneous events).

Documents using this package need to be compiled with LuaLaTeX. The package requires `xcolor`, `fontawesome`, `tikz` (and `pgfkeys`).

Contents

1 Usage	1
1.1 timetable	1
1.1.1 Special Notes	3
1.1.2 Example	4
1.2 Calendar related things	4
1.2.1 Appointments	6
1.2.2 Exams	6
1.2.3 Deadlines	7
1.3 Icons	7
2 Implementation	8
2.1 semesterplannerLua.sty	8
2.1.1 Global Stuff	8
2.2 Tikz Calendar add weekday labels	11
2.2.1 Local Stuff (timetable-env local)	11
3 Change History	14
4 Index	14

1 Usage

1.1 timetable

`timetable (env.) \begin{timetable}[opts]... \end{timetable}`

This is the core environment of this package. Within it you can use `\lecture`, `\seminar`, `\tutorial`, `\officehour` and `\meeting`. All these commands are only defined inside the `timetable` environment, and have the same structure. It typesets a timetable with the specified entries. If you have a look at the `.sty` file you'll see that these macros just take a general macro and set some default values before. Thus it is easy to define new ones (keep in mind that you'll need `\makeatletter`) to access the general macro.

Writes out a file containing the data from the timetable (your events) to be able to have just the .tex file containing the timetable, but do some scriping on the data (e.g. show the last, current and next events). For simplicity the data is stored in lua-syntax (**returns** a table of the events). This way we don't need to worry about any string escaping (like with csv) and no complicated parsers are needed. Be aware though that a simple **events = dofile**"path" has risks since "path" might contain lua code which is simply executed that way.

opts are optional arguments (enclosed with {}) separated with ,:

days List of the names of the days that should be set as column names. Note that if you specify only 4 names only these 4 columns will be printed (with the first day being identified as Monday) *Default: Mon, Tue, Wed, Thur, Fri*

dayse List of strings used in the code to identify the day. This list is kind of a mapping string → integer.

start time Explicit start-time of the timetable given in minutes (HH*60 + MM). Can be set as **start time/.evaluated={HH*60 + MM}**. If this is empty, the start time is derived from the given events. *Default: ""*

end time Equivalent to **start-time** *Default: ""*

width Give the width of the timetable. (can be given e.g. as \textwidth as this is directly given to tikz). *Default: \textwidth*

length Give the length of the timetable (measured in cm) (has to be a straight number since this is needed in calculation) *Default: 10*

```
\lecture    \lecture    [opts]
\tutorial    \tutorial    [opts]
\seminar     \seminar     [opts]
\officehour  \officehour [opts]
\meeting     \meeting     [opts]
```

opts are optional arguments (enclosed with {}) separated with ,:

title Give the name of the lecture

speaker Give the name of the lecturer

location Give the place of the event (most probably the room or an online platform, see 1.3). If you want to use \href{url}{string repr}, keep in mind that you need to \unescaped{} it, since all input to lua has to be text

day The weekday on which the event takes place. Has to be one of those you specified in **dayse** (or by default: M,T,W,Th,F)

time The timespan of the event formatted as HH:MM-HH:MM (24H clock)

prio The priority of the event (see 1.3)

scale width Specify the width of the entry in fractions of column (use 0.5 to span half the column).

offset Shift the entry to the right. Specified in fractions of column.

password Original purpose: Only included in the file written out with the timetable data, to be able to make a script which quickly copies url (from **location**) and **password** to the clipboard.

type Only included in the file written out with the timetable data as well (Original purpose: To be able to exclude some types)

tikz Free customizable event code. See the documentation at the end for keys that can be used here (all keys in `/event`). To simply pass arguments to the tikz-node that is being created for the event use `tikz/.append={your arguments}` (be careful with `text width`, `text height`, `text depth` as these keys are being used for the dimensions of the node as well as with `anchor`)

content Is usually set automatically based on the other keys (`title` for instance). This key can override this.

textcolor Usually set by the type of macro used

formatter internal stub for providing different formatting options. Formatting functions need to be specified in the `-timetable.lua` file

The entries **Day** and **Time** are mandatory since they are needed for the positioning of the node. All others are merely necessary for the content of the node and are therefore not mandatory.

1.1.1 Special Notes

Note that the **length** argument does specify the length of the timetable without taking account of the column headers.

Same goes for the **width** parameter regarding the labels containing the time on the right. Since in this case any tex-length is allowed, you can simply try to subtract the length of the clock label using something like `\settowidth{\length}{12:30}` to set a length to the length of a clock label and then subtract this from the length you want to specify.

Hint: The content of the environment isn't processed by this package. Only the event commands (so to speak `\lecture`, `\tutorial`, `\seminar`, `\officehour`, `\meeting`) are relevant. All other contents are set immediately before the timetable. Therefore, if you want to add e.g. a `\hspace*{10cm}` to shift the timetable to the left, the last line of the env would be the place to do so (there mustn't be an empty line below since otherwise a new paragraph is started).

1.1.2 Example

```
\begin{timetable}[
  days={Mon,Thue,Wend,Thur,Fri},
  start time/.evaluated={11*60}, end time/.evaluated={15*60}
]
\lecture[title={TestingLectureLongOne},speaker={Doe},
  location={RN1},day={W},time={12:30-13:30}]
\lecture[title={TestingLectureLongOne},speaker={John},
  location={RN1},day={Th},time={12:30-13:30},offset=0.5,scale width=0.5]
\lecture[title={TestingLectureLongOne},speaker={Dr. Doe},
  location={\zoom},day={T},time={12:30-13:30},prio={\phigh}]
\end{timetable}
```

⌚ Timetable

	Mon	Thue	Wend	Thur	Fri
11:00					
12:00					
13:00		<div>TestingLectureLongOne</div> <div>Heindl</div> <div>🚩</div> <div>📍</div> <div>12:30-13:30</div>	<div>TestingLectureLongOne</div> <div>Heindl</div> <div>RN1</div> <div>12:30-13:30</div>	<div>TestingLectureLongOne</div> <div>Heindl</div> <div>RN1</div> <div>12:30-13:30</div>	
14:00					
15:00					

1.2 Calendar related things

Now some environments and commands come which in generally are being used to typeset a table with the detailed information, but which also store the gathered data internally. This saved data can be used to output a calendar where the events (from the saved data) are highlighted with a mark (already passed days are crossed and the current day is highlighted as well).

The different environments described below are similar in general, but differ in detail (mostly the list of argument that are passed and printed in the table).

Example

```
\begin{appointments}{true}
  \appointment[print=true,shift=false,tikz={fill=black,rectangle},
    date={2022-04-15}, course={Appointment with my dog},
    end={2022-04-18}, period={1}]
  \appointment[date={2022-04-14}, course={Appointment with my dog},
    room={at home}, time={12:00}, prio={\pmandatory}]
\end{appointments}
\begin{exams}{false}
  \exam[tikz={fill=yellow}, date={2022-06-20}, time={arround midday},
    course={Driving}, desc={Mid-Term}, prio={\phigh},
    room={University}, type={\oral}]
\end{exams}
\begin{deadlines}{false}
  \deadline[tikz={fill=blue}, date={2022-06-22},
    course={Submitting Driver-license form}, prio={\phigh}]
\end{deadlines}

\printSpCalendar[2]{2022-04-01}{2022-07-31}
```

📅 Appointments

Date	Time	Course	Description	Room	Prio.
2022-04-15		■ Appointment with my dog			
2022-04-14	12:00	● Appointment with my dog		at home	▲

📅 Exams

Date	Time	Course	Type	Note
2022-06-20	arround midday	● Driving	🗨	Mid-Term

📅 Deadlines

Date	Course	Description	Prio
2022-06-22	● Submitting Driver-license form		🚩

April 2022							May 2022						
M	T	W	T	F	S	S	M	T	W	T	F	S	S
				1	2	3							1
4	5	6	7	8	9	10	2	3	4	5	6	7	8
11	12	13	14	15	16	17	9	10	11	12	13	14	15
18	19	20	21	22	23	24	16	17	18	19	20	21	22
25	26	27	28	29	30		23	24	25	26	27	28	29
							30	31					

June 2022							July 2022						
M	T	W	T	F	S	S	M	T	W	T	F	S	S
			1	2	3	4					1	2	3
6	7	8	9	10	11	12	4	5	6	7	8	9	10
13	14	15	16	17	18	19	11	12	13	14	15	16	17
20	21	22	23	24	25	26	18	19	20	21	22	23	24
27	28	29	30				25	26	27	28	29	30	31

\printSpCalendar \printSpCalendar[cols]{start_date}{end_date}

This is the macro to output such a calendar populated with the gathered events.
 Use the `cols` argument to specify the amount of columns being used (months set side by side).

`start_date` and `end_date` both have to be specified in the YYYY-MM-DD format.

1.2.1 Appointments

`appointments (env.)` `\begin{appointments}[Room]{true/false}...\end{appointments}`

Environment to typeset a table of appointments. Stores the data internally to be able to typeset a calendar (with `\printSpCalendar`) with a mark for each event.

The optional argument is used as header for the Room column (maybe for some appointments another title is more suitable).

The mandatory argument which is `true/false` decides if the internally stored data used to typeset the calendar is being erased before this environment.

`\appointment` `\appointment[opts]`

`opts` are optional arguments (enclosed with `{}`) separated with `,:`

`date` Date of the appointment formatted as YYYY-MM-DD

`course` Name of the course

`room` Room (only shown in the table)

`time` Time of the event (free text independant of any formatting, only shown in the table)

`prio` priority of the event (shown in the table) (see 1.3)

`desc` Description of the event (shown in the table)

`end` upper boundary when the event should stop to repeat (with `period`). Has to be set to make event periodic/repeating.

`period` Set the period of the repeating event.

`draw true/false` wether to draw a mark in the calendar

`print true/false` wether to display the entry in the appointments table.

`shift true/false` wether to shift the mark in the calendar if there is already another event on that date (to be able to see both marks)

`tikz` Free customizable tikz code used for drawing the mark in the calendar. See the documentation at the end for keys that can be used here (all keys in `/cal`). To simply pass arguments to the tikz-node that is being created for the event use `tikz/.append={your arguments}`

Use e.g. to set the color of the mark via `tikz/.append={green}`

1.2.2 Exams

`exams (env.)` `\begin{exams}{true/false}...\end{exams}`

Environment to typeset a table of exams. Stores the data internally to be able to typeset a calendar (with `\printSpCalendar`) with a mark for each event.

The mandatory argument which is `true/false` decides if the internally stored data used to typeset the calendar is being erased before this environment.

`\exam` `\exam[opts]`

`opts` are optional arguments (enclosed with `{}`) separated with `,:`

`date` Date of the exam formatted as YYYY-MM-DD

`course` Name of the course

`room` Room (only shown in the table)

`type` Type of the exam (see 1.3) (intended: written/oral)

time Time of the event (free text independant of any formatting, only shown in the table)

desc Description of the event (shown in the table)

draw true/false wether to draw a mark in the calendar

print true/false wether to display te entry in the exams table.

shift true/false wether to shift the mark in the calendar if there is already another event on that date (to be able to see both marks)

tikz Free customizable tikz code used for drawing the mark in the calendar. See the documentation at the end for keys that can be used here (all keys in `/cal`). To simply pass arguments to the tikz-node that is being created for the event use `tikz/.append={your arguments}`
 Use e.g. to set the color of the mark via `tikz/.append={green}`

1.2.3 Deadlines

deadlines (*env.*) `\begin{deadlines}{true/false}...\end{deadlines}`
 Environment to typeset a table of deadlines. Stores the data internally to be able to typeset a calendar (with `\printSpCalendar`) with a mark for each event.
 The mandatory argument which is **true/false** decides if the internally stored data used to typeset the calendar is being erased before this environment.

\deadline `\deadline[opts]`
 opts are optional arguments (enclosed with `{}`) separated with `,:`

date Date of the deadline formatted as YYYY-MM-DD

course Name of the course

prio priority of the event (shown in the table) (see 1.3)

desc Description of the event (shown in the table)

draw true/false wether to draw a mark in the calendar












print true/false wether to display te entry in the deadlines table.

shift true/false wether to shift the mark in the calendar if there is already another event on that date (to be able to see both marks)

tikz Free customizable tikz code used for drawing the mark in the calendar. See the documentation at the end for keys that can be used here (all keys in `/cal`). To simply pass arguments to the tikz-node that is being created for the event use `tikz/.append={your arguments}`
 Use e.g. to set the color of the mark via `tikz/.append={green}`

1.3 Icons

This package defines some modified fontawesome icons (they are being encircled with a white circle for better readability).

<code>\zoom</code>		<code>\teams</code>	
<code>\BBB</code>		<code>\youtube</code>	
<code>\pmandatory</code>		<code>\phigh</code>	
<code>\pmid</code>		<code>\plow</code>	
<code>\pnone</code>			
<code>\tbd</code>		<code>\tba</code>	

2 Implementation

This package uses `semesterplannerLua` as prefix/directory where possible. Since this is not possible for latex macro names, in this occasions `semesterplannerLua@` is used as prefix.

2.1 semesterplannerLua.sty

2.1.1 Global Stuff

```
1 \package
2 \RequirePackage{tikz}
3 \usetikzlibrary{calendar, positioning, shapes.misc, backgrounds}
4 \RequirePackage{pgfkeys}
5 \RequirePackage{xcolor}
6 \RequirePackage{fontawesome}
7 \usepackage{luapackageloader} % use the default lua path as well
```

Define some colors for the course types (can be globally overwritten)

```
8 \definecolor{seminar}{rgb}{1.0, 0.8, 0.0}
9 \definecolor{lecture}{rgb}{0.2, 0.7, 1.0}
10 \definecolor{tutorial}{rgb}{0.0, 0.8, 0.0}
11 \definecolor{meeting}{rgb}{0.8, 0.0, 0.0}
12 \definecolor{officehour}{rgb}{0.0, 0.4, 0.6}
13 \definecolor{DodgerBlue}{HTML}{1E90FF}
```

`\semesterplannerLua@encircle` This macro puts a circle around its argument for better readability. In this package this is used for the fontawesome symbols.

```
14 \newcommand*\semesterplannerLua@encircle[1]{
15     \begin{minipage}[b][1em][c]{1.5em}
16         \begin{tikzpicture}
17             \node[fill,circle,inner sep=1pt, color = white] {#1};
18         \end{tikzpicture}
19     \end{minipage}
20 }
```

Commands for exams

`\oral`

```
21 \protected\def\oral{\faComment}
```

`\written`

```
22 \protected\def\written{\faPencil}
```

Commands for symbols of priority

`\pmandatory`

```
23 \protected\def\pmandatory{\semesterplannerLua@encircle{\textcolor{red}{\faWarning}}}
```

`\phigh`

```
24 \protected\def\phigh{\semesterplannerLua@encircle{\textcolor{red}{\faFlag}}}
```

`\pmid`

```
25 \protected\def\pmid{\semesterplannerLua@encircle{\textcolor{yellow}{\faFlag}}}
```

`\plow`

```
26 \protected\def\plow{\semesterplannerLua@encircle{\textcolor{green}{\faFlag}}}
```

`\pnone`

```
27 \protected\def\pnone{\semesterplannerLua@encircle{\textcolor{gray}{\faTimesCircle}}}
```

Commands for online platforms.

`\teams`

```
28 \protected\def\teams{\semesterplannerLua@encircle{\textcolor{DodgerBlue}{\faWindows}}}
```



```

\zoom
29   \protected\def\zoom{\semesterplannerLua@encircle{\textcolor{DodgerBlue}{\faCamera}}}

\youtube
30   \protected\def\youtube{\semesterplannerLua@encircle{\textcolor{red}{\faYoutubePlay}}}

\BBB
31   \protected\def\BBB{\semesterplannerLua@encircle{\textcolor{DodgerBlue}{\faBold}}}

Command for "To be determined" and "To be Announced"

\tbd
32   \protected\def\tbd{\faQuestion}

\tba
33   \protected\def\tba{\faBullhorn}

Load the lua modules
34 \directlua{sp = require("semesterplannerLua_timetable.lua")}
35 \directlua{cal = require("semesterplannerLua_calendar.lua")}

Set all the pgfkeys required for the arguments. To achieve that the defaults are restored
every time the environment is used, this is inside the environment definition. This of
course disables all possibilities of setting a global default but enables setting local defaults
for the events
36   \pgfkeys{
/semesterplannerLua will be the pgf-path used for this package. Here all used keys are
set (and initialized with defaults. timetable/env/:

days is a list of strings representing the header names for the day columns in the
timetable (adding Sat and Sun (additional entries) will result in two more columns.

start time can be used to set a fixed time where the timetable starts (otherwise this
is calculated from the entries) to enable this behaviour this key has to be set to
HH*60 + MM (easy way is by using start time/.evaluated={HH*60+MM})

end time equivalent to start time

width is the horizontal width of the timetable (not including the column headers on the
top) this can be a latex length string or \textwidth as well.

length is the vertical length of the timetable (not including the clock labels on the side)
measured in cm (in future versions this may become measured in pts for better
interaction with the LaTeX lengths.

37   /semesterplannerLua/timetable/env/.cd,
38   days/.initial={Mon,Thue,Wend,Thur,Fri}, days/.default={Mon,Thue,Wend,Thur,Fri},
39   dayse/.initial={M,T,W,Th,F}, dayse/.default={M,T,W,Th,F},
40   %
41   start time/.initial=, start time/.default=,
42   end time/.initial=, end time/.default=,
43   %
44   width/.initial=\textwidth, width/.default=\textwidth,
45   length/.initial=10, length/.default=10,
46   %

timetable/event/:

content is the content of the event (is passed on without any formatting). Since this
is passed to lua without modification its value must be an unexpanded string (lua
will simply print it so the eventually the string will be evaluated)

time is a HH:MM-HH:MM string representing start- and end-time of the event. Used in
constructing the content as well

```

day is either M,T,W,Th or F specifying the day on which the event takes place

tikz this key allows the user to manually pass options to the node created for this event

scale width allows to scale the width of the event to be able to draw overlapping events besides each other. Will usually be a value between 0 and 1.

offset same goal like **scale width** but shifts the event node by the given value to the right. (Given as value between 0 and 1 indicating how many columns the event should be shifted)

textcolor foreground color of the content text

title title (set in bold by default)

speaker

location

prio

formatter this is special

```
47      /semesterplannerLua/timetable/event/.cd,  
48      % event arguments  
49      content/.initial=, content/.default=,  
50      %  
51      time/.initial=, time/.default=,  
52      day/.initial=, day/.default=,  
53      %  
54      tikz/.initial=, tikz/.default=,  
55      scale width/.initial=1, scale width/.default=1,  
56      offset/.initial=0, offset/.default=0,  
57      %  
58      textcolor/.initial=, textcolor/.default=,  
59      title/.initial=, title/.default=,  
60      speaker/.initial=, speaker/.default=,  
61      location/.initial=, location/.default=,  
62      password/.initial=, password/.default=,  
63      prio/.initial=, prio/.default=,  
64      type/.initial=, type/.default=,  
65      formatter/.initial=timetableformatter, formatter/.default=timetableformatter,  
66      %
```

calendar/:

draw

room

prio

course

desc

start

end

tikz

period

shift

print Only makes sense if the command is suffixed by a % otherwise somehow a space gets inserted (eventhough the % is inserted from lua as well)

```

67     /semesterplannerLua/calendar/.cd,
68     draw/.initial={true}, draw/.default={true},
69     room/.initial={}, room/.default={},
70     time/.initial={}, time/.default={},
71     prio/.initial={}, prio/.default={},
72     course/.initial={}, course/.default={},
73     desc/.initial={}, desc/.default={},
74     type/.initial={}, type/.default={},
75     date/.initial={}, date/.default={},
76     end/.initial={}, end/.default={},
77     tikz/.initial={}, tikz/.default={},
78     period/.initial={nil}, period/.default={nil},
79     shift/.initial={true}, shift/.default={true},
80     print/.initial={true}, print/.default={true},
81 }

```

2.2 Tikz Calendar add weekday labels

```

82 \tikzoption{day headings}{\tikzstyle{day heading}=[#1]}
83 \tikzstyle{day heading}=[]
84 \tikzstyle{day letter headings}=[
85     execute before day scope={ \ifdate{day of month=1}{%
86         \pgfmathsetlength{\pgf@ya}{\tikz@lib@cal@yshift}%
87         \pgfmathsetlength{\pgf@xa}{\tikz@lib@cal@xshift}%
88         \pgftransformyshift{-\pgf@ya}
89         \foreach \d/\l in {0/M,1/T,2/W,3/T,4/F,5/S,6/S} {
90             \pgf@xa=\d\pgf@xa%
91             \pgftransformxshift{\pgf@xa}%
92             \pgftransformyshift{\pgf@ya}%
93             \node[every day,day heading]{\l};%
94         }
95     }{}%
96 }%
97 ]

```

2.2.1 Local Stuff (timetable-env local)

timetable (*env.*) This is the environment doing all the stuff. To gate the positions where the corresponding macros can be used (and in terms of pgfkeys for reasons of default values) all the macros used are put into the environment.

```

98 \newenvironment{timetable}[1][]{
99     \section*{\faClockO~Timetable}

```

Read the arguments given by the user after restoring the defaults (Restoring currently makes no sense, since they are created a few lines above anyways, but creation might be moved outside the environment some day.

Afterwards the lua module is being initialized (erase data from possible previous runs.

```

100 \pgfkeys{/semesterplannerLua/timetable/env/.cd, days,dayse, start time,end time, width,le
101 \directlua{sp.init{
102     days=[[ \pgfkeysvalueof{/semesterplannerLua/timetable/env/days}]],
103     min=[[ \pgfkeysvalueof{/semesterplannerLua/timetable/env/start time}]],
104     max=[[ \pgfkeysvalueof{/semesterplannerLua/timetable/env/end time}]],
105     dayse=[[ \pgfkeysvalueof{/semesterplannerLua/timetable/env/dayse}]]}}

```

\semesterplannerLua@event Is used to pass the event to the lua engine which in turn will collect the event to draw it in the end. For that the arguments given are parsed after restoring the pgf keys to their default values. The optional argument hereby is a sequence of pgf keys, the second argument is a string representing the content (this MUST be unexpanded since this is passed to lua which in turn will pass it unmodified back)

```

106 \newcommand{\semesterplannerLua@event}[1][]{
107     \pgfkeys{/semesterplannerLua/timetable/event/.cd,content,time,day,tikz,scale
108     width,offset,textcolor,title,speaker,type,location,password,prio,formatter, ##1}
109     \directlua{
110         sp.addEvent{

```

```

111         time="\pgfkeysvalueof{/semesterplannerLua/timetable/event/time}",
112         day="\pgfkeysvalueof{/semesterplannerLua/timetable/event/day}",
113         tikz=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/tikz}],
114         offset=\pgfkeysvalueof{/semesterplannerLua/timetable/event/offset},
115         scale_width=\pgfkeysvalueof{/semesterplannerLua/timetable/event/scale width},
116         formatter=\pgfkeysvalueof{/semesterplannerLua/timetable/event/formatter},
117         textcolor=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/textcolor}],
118         title=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/title}],
119         speaker=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/speaker}],
120         location=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/location}],
121         password=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/password}],
122         prio=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/prio}],
123         type=[\pgfkeysvalueof{/semesterplannerLua/timetable/event/type}],
124     }
125 }
126 }

```

Short-hand macros for different events using the corresponding background color

```

\lecture
127 \newcommand{\lecture}[1][]{
128     \semesterplannerLua@event[tikz={fill=lecture,}, textcolor=white, type=lect, ##1]
129     \ignorespaces
130 }

\seminar
131 \newcommand{\seminar}[1][]{
132     \semesterplannerLua@event[tikz={fill=seminar,}, textcolor=white, type=sem, ##1]
133     \ignorespaces
134 }

\tutorial
135 \newcommand{\tutorial}[1][]{
136     \semesterplannerLua@event[tikz={fill=tutorial,}, textcolor=white, type=tut, ##1]
137     \ignorespaces
138 }

\meeting
139 \newcommand{\meeting}[1][]{
140     \semesterplannerLua@event[tikz={fill=meeting,}, textcolor=white, type=meet, ##1]
141     \ignorespaces
142 }

\officehour
143 \newcommand{\officehour}[1][]{
144     \semesterplannerLua@event[tikz={fill=officehour,}, textcolor=white, type=office, ##1]
145     \ignorespaces
146 }

147 }{

```

At the end of the environment after all events have been collected, generate and output the tikz code needed to draw the timetable.

```

148 \directlua{sp.draw(
149     [[\pgfkeysvalueof{/semesterplannerLua/timetable/env/length}]],
150     [[\pgfkeysvalueof{/semesterplannerLua/timetable/env/width}]])}
151 }
152

```

printSpCalendar Print a calendar from startDate to endDate (encoded as YYYY-MM-DD) as one calendar per month in a matrix with the given amount of columns

```

153 \newcommand{\printSpCalendar}[3][3]{\directlua{cal.drawCalendar("#2", "#3", #1)}}

```

```

154
155 \newenvironment{appointments}[2][Room]{
156     \directlua{cal.init(#2)}
157     \newcommand{\appointment}[1][{}]{%
158         \pgfkeys{/semesterplannerLua/calendar/.cd,draw,room,time,prio,course,desc,date,end,tikz}
159         \directlua{
160             cal.addAppointment{draw=\pgfkeysvalueof{/semesterplannerLua/calendar/draw},
161                 room=[\pgfkeysvalueof{/semesterplannerLua/calendar/room}],
162                 time=[\pgfkeysvalueof{/semesterplannerLua/calendar/time}],
163                 prio=[\pgfkeysvalueof{/semesterplannerLua/calendar/prio}],
164                 course=[\pgfkeysvalueof{/semesterplannerLua/calendar/course}],
165                 desc=[\pgfkeysvalueof{/semesterplannerLua/calendar/desc}],
166                 date=[\pgfkeysvalueof{/semesterplannerLua/calendar/date}],
167                 endDate=[\pgfkeysvalueof{/semesterplannerLua/calendar/end}],
168                 tikz=[\pgfkeysvalueof{/semesterplannerLua/calendar/tikz}],
169                 period=\pgfkeysvalueof{/semesterplannerLua/calendar/period},
170                 shift=\pgfkeysvalueof{/semesterplannerLua/calendar/shift},
171                 print=\pgfkeysvalueof{/semesterplannerLua/calendar/print}}}%
172         \ignorespaces
173     }
174     \section*{\faCalendar~Appointments}
175     \begin{tabular}{rlllll}
176         \textbf{Date}&\textbf{Time}&\textbf{Course}&\textbf{Description}&\textbf{\#1}&\textbf{Time}
177     \end{tabular}
178 }
179 }
180
181 \newenvironment{exams}[1]{
182     \directlua{cal.init(#1)}
183     \newcommand{\exam}[1][{}]{%
184         \pgfkeys{/semesterplannerLua/calendar/.cd,draw,room,time,prio,course,desc,date,end,tikz}
185         \directlua{
186             cal.addExam{
187                 draw=\pgfkeysvalueof{/semesterplannerLua/calendar/draw},
188                 room=[\pgfkeysvalueof{/semesterplannerLua/calendar/room}],
189                 time=[\pgfkeysvalueof{/semesterplannerLua/calendar/time}],
190                 course=[\pgfkeysvalueof{/semesterplannerLua/calendar/course}],
191                 desc=[\pgfkeysvalueof{/semesterplannerLua/calendar/desc}],
192                 date=[\pgfkeysvalueof{/semesterplannerLua/calendar/date}],
193                 tikz=[\pgfkeysvalueof{/semesterplannerLua/calendar/tikz}],
194                 type=[\pgfkeysvalueof{/semesterplannerLua/calendar/type}],
195                 shift=\pgfkeysvalueof{/semesterplannerLua/calendar/shift},
196                 print=\pgfkeysvalueof{/semesterplannerLua/calendar/print}}}%
197         \ignorespaces
198     }
199     \section*{\faStickyNoteO~Exams}
200     \begin{tabular}{rlllll}
201         \textbf{Date}&\textbf{Time}&\textbf{Course}&\textbf{Type}&\textbf{Note}
202     \end{tabular}
203 }
204 }
205
206 \newenvironment{deadlines}[1]{
207     \directlua{cal.init(#1)}
208     \newcommand{\deadline}[1][{}]{%
209         \pgfkeys{/semesterplannerLua/calendar/.cd,draw,room,time,prio,course,desc,date,end,tikz}
210         \directlua{
211             cal.addDeadline{
212                 draw=\pgfkeysvalueof{/semesterplannerLua/calendar/draw},
213                 course=[\pgfkeysvalueof{/semesterplannerLua/calendar/course}],
214                 desc=[\pgfkeysvalueof{/semesterplannerLua/calendar/desc}],
215                 date=[\pgfkeysvalueof{/semesterplannerLua/calendar/date}],
216                 tikz=[\pgfkeysvalueof{/semesterplannerLua/calendar/tikz}],

```

```

217         prio=[\pgfkeysvalueof{/semesterplannerLua/calendar/prio}]],
218         shift=\pgfkeysvalueof{/semesterplannerLua/calendar/shift},
219         print=\pgfkeysvalueof{/semesterplannerLua/calendar/print}}}%
220     \ignorespaces
221 }
222 \section*{\faStickyNote0~Deadlines}
223 \begin{tabular}{rlll}
224     \textbf{Date}&\&\textbf{Course}&\&\textbf{Description}&\&\textbf{Prio}\\
225 \end{tabular}
226 \end{tabular}
227 }

```

3 Change History

v0.0.0		be able to build e.g. something
General: First draft	1	with dmenu over it and provide an
v0.0.1		example dmenu lua script 1
General: Added new options		
(providing day representation in		v0.0.3
source code)	1	General: Rename to
v0.0.2		semesterplannerLua and rewrite
General: Write out timetable data to		for l3build 1

4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

A	O	\seminar 2, <u>131</u>
\appointment 6, <u>157</u>	\officehour 2, <u>143</u>	
appointments (env.) 6	\oral <u>21</u>	T
B	P	\tba <u>33</u>
\BBB <u>31</u>	\pgftransformxshift .. 91	\tbd <u>32</u>
D	\phigh <u>24</u>	\teams <u>28</u>
\deadline 7, <u>208</u>	\plow <u>26</u>	\tikzoption 82
deadlines (env.) 7	\pmandatory <u>23</u>	\tikzstyle 82, 83, 84
E	\pmid <u>25</u>	timetable (env.) <u>1</u> , <u>98</u>
environments:	\pnone <u>27</u>	\tutorial 2, <u>135</u>
appointments 6	\printSpCalendar	U
deadlines 7 5, <u>153</u> , <u>153</u>	\usepackage 7
exams 6	R	\usetikzlibrary 3
timetable <u>1</u> , <u>98</u>	\RequirePackage . 2, 4, 5, 6	W
\exam 6, <u>183</u>	S	\written <u>22</u>
exams (env.) 6	\semesterplannerLua@encircle	Y
L	... <u>14</u> , <u>23</u> , <u>24</u> , <u>25</u> ,	\youtube <u>30</u>
\lecture 2, <u>127</u>	<u>26</u> , <u>27</u> , <u>28</u> , <u>29</u> , <u>30</u> , <u>31</u>	Z
M	\semesterplannerLua@event	\zoom <u>29</u>
\meeting 2, <u>139</u> <u>106</u> ,	
	<u>128</u> , <u>132</u> , <u>136</u> , <u>140</u> , <u>144</u>	