备注: 1.HDMI 走线需要考虑到匹配阻抗,等长等宽走线。 2.尽量少打过空穿层走线。 3.各组差分线间需要地隔离 Place close to HDMI Connector BV ULC0524P J1 HDMI19-CTYPE TVS1 WCM-2012HDMI-900T TX2P >> TMDS D2 SHIELD TMDS D2+ TX2N>> TMDS D2-TMDS D1 SHIELD TX1P > TMDS D1+ TMDS D1-TX1N TX0P TMDS D0 SHIELD TMDS D0+ TMDS D0-10 TX0N) TMDS CK SHIELD WCM-2012HDMI-900T 11 TXCP TMDS CK+ 12 TMDS CK-13 TXCN > DDC/CEC GND 14 CEC 15 **DDCSCL** SCL 16 **DDCSDA** SDA 17 RESERVED FBMA-11-160808-601A20V HDMI 5V 18 +5V POWER HOTPLUG >> **HOT PLUG DET** C2 TVS4 유유 10uF 1000PF D9 D8 BV05C BV05C BV-SR05 HDMI接口EMC设计标准电路> 一站式电磁兼容(EMC)方案供应商!需器件请联系 Document Number Rev <1.0> 电话: 钟凯 13632524150; 0755-26532285 Compon20110322-2 邮箱: kai.zhong@compon-tech.com Wednesday, October 26, 2011 Sheet