Requirements Engineering

Lecture 2

Prof. Dr. Alexander Pretschner

Chair of Software & Systems Engineering
TUM Department of Informatics
Technical University of Munich

Orientation

Recap:

- Core activities in RE
- Context dependency of RE and SE
- RE results as input for whole SE process and thus reason for project failures

Coming up:

- Quality of requirements
- What makes a requirement a useful requirement?

Natural language must be interpreted!

Example: *„I saw a man on the hill with a telescope.“*

=> Who has the telescope?

Countless more examples:

„The father slapped his son because he was drunk“.
Who was drunk?

Image source: https://www.ashishdalela.com/2017/01/15/problem-meaning-artificial-intelligence/

Same holds for Requirements!



Consequences of subpar requirements



		Usability (NFR)	A system component shall save a users edits when ever possible.
J010PE01		Performance (NFR)	The perceived response time shall not be too high.

→How can the requirement be clearly implemented?
→How can the requirement be checked and tested?
→How can a reasonable cost estimate be made based on this requirement?
→...

Requirements Quality Model versus Quality Requirements

Requirements Quality Model:

describes the quality of requirements

≠

Quality Requirements:

describe the quality of a system



Example: ISO/IEC/IEEE Std. 29148



Language criteria will be covered in depth later in this course

Example: ISO/IEC/IEEE Std. 29148

Quality criteria for a set of requirements

- *Able to be validated*
- *Affordable/Feasible*
- *Complete*
- *Consistent*
- *Comprehensible*

Quality criteria for individual requirements

- *Feasible*
- *Conforming: compliance to template etc*
- *Correct*
- *Verifiable*
- *Unambigous*
- *Necessary*
- *Appropriate level*
- *Complete*
- *Singular*

Language criteria (covered later in this course)

- *best practices to achieve these quality criteria*



Second Example: IEEE Std 830-1998 / Part I

- **Consistency**: *Consistency and thus feasibility*
- **Completeness**: *All relevant requirements are recorded*
- **Correctness**: *All recorded requirements represent valid, applicable wishes and specifications of the stakeholders*
- **Clarity**: *Requirements are unambiguous*
- **Verifiability**: *(Fulfillment of the) requirements can be verified beyond any doubt, requirements are measurable if necessary*



IEEE Std 830-1998
(Revision of
IEEE Std 830-1993)

IEEE Recommended Practice for Software Requirements Specifications

Sponsor

Software Engineering Standards Committee of the IEEE Computer Society

Approved 25 June 1998

IEEE-SA Standards Board

Abstract: The content and qualities of a good software requirements specification (SRS) are described and several sample SRS outlines are presented. This recommended practice is aimed at specifying requirements of software to be developed but also can be applied to assist in the selection of in-house and commercial software products. Guidelines for compliance with IEEE/EIA 12207.1-1997 are also provided.
Keywords: contract, customer, prototyping, software requirements specification, supplier, system requirements specifications

Second Example: IEEE Std 830-1998 / Part II

- **Modifiability**: *Changes to the requirements can be made in a controlled manner*
- **Traceability**: *The implementation of the requirement can be traced*
- **Prioritization**: *Requirements are ranked according to their importance*
- **Comprehensibility**: *Requirements are easy to understand*



IEEE Std 830-1998
(Revision of
IEEE Std 830-1993)

IEEE Recommended Practice for Software Requirements Specifications

Sponsor

Software Engineering Standards Committee of the IEEE Computer Society

Approved 25 June 1998

IEEE-SA Standards Board

Abstract: The content and qualities of a good software requirements specification (SRS) are described and several sample SRS outlines are presented. This recommended practice is aimed at specifying requirements of software to be developed but also can be applied to assist in the selection of in-house and commercial software products. Guidelines for compliance with IEEE/EIA 12207.1-1997 are also provided.
Keywords: contract, customer, prototyping, software requirements specification, supplier, system requirements specifications

Terminology in the context of quality assurance (in RE)

Important terms (simplified)

Incorrect (invalid) requirement: Requirement that does **not** reflect the intention of the stakeholders.

Quality deficiency: Requirements that may be valid in terms of content, but have qualitative defects, i.e. violate quality criteria

Validation and Verification (simplified)

Validation: Checking the requirements for validity (right system built)

Verification: Testing the system for compliance with the requirements (correctness: system built right)

Quality assurance (simplified)

→Systematic measures to identify quality defects

→Attention: Validation and Verification are part of quality assurance

Quality assurance in RE

Constructive quality assurance: Assurance of the quality of the artifacts to be created during the creation process, e.g. by means of model building

Analytical quality assurance: independent and autonomous testing and evaluation of the artifacts created, e.g. within the framework of quality gates



Linguistics in RE

Classification of linguistic quality deficiencies

- ontological/lexical (*„The button shall be green“.)*
- syntactic (*"I saw the man on the hill with a telescope."*)
- semantic ("*All persons have a unique national insurance number.*")
- pragmatic ("*The trucks shall treat the roads before they freeze.*")
- weak phrases: („… *as soon as possible.*")
- Eradication/Generalization/Distortion (*„The response is never higher than 100ms.“*)

How to avoid this by constructive QA?

More about this later in the course!

Requirements Quality Model versus Quality Requirements

Requirements Quality Model:

describes the quality of requirements

≠

Quality Requirements:

describe the quality of a system



Software Product Quality: (ISO/IEC/IEEE Std. 25010)

Quality does not only consist of non-functional requirements!

but also: **functional** correctness

internal Quality (properties of code)

vs

external Quality (user-observable)



Quality-in-use

Quality-in-use measures to which extent the software meets the **needs** of the user in the working environment (such as productivity, satisfaction and effectiveness)

Differentiation from **Usability**:
- Ease of interaction with the system.
- Part of external quality!



Figure and Definition: Bevan 1999 – Quality in use: Meeting user needs for quality

Stop!

When talking about the "quality of requirements", this wording alone implicitly assumes that these requirements already exist! This may well be the case, in the form of user needs, but knowing the "right" requirements, and writing them down the "right" way, precedes the notion of quality (unless "validity" is considered a quality).

This problem of validity is a fundamental problem, giving rise, among other things, to design thinking.

What are the requirements for rent-a-scooter?

Measuring System Quality

Functional Quality:

Is the system doing as intended? **=> Testing!**

Without verifiable requirements, testing is impossible!

Non-functional Quality:

Is the system "well" programmed? Quality is subjective!

- How to verify non-functional requirements?
- How to formulate non-functional requirements?



More details in Lecture 6

Outline and Outlook

Terms and Definitions *(Lecture 1)*
Core activities *(Lecture 1)*

Quality models for Requirements
Natural language as one source of possible quality defects

Engineering models in RE
Stakeholder and Requirements Elicitation
Goals and Goal-oriented RE
Non-functional requirements
Functional requirements
Formalization
Agile Processes
Requirements Management and Quality Assurance
Trends in Research