

# XHTML Cheat Sheet v. 1.03

<b>%attrs</b> %coreattrs %i18n %events  <b>%coreattrs</b> id class style title  <b>%i18n</b> xml:lang lang dir  <b>%events</b> onclick ondblclick onmousedown onmouseup onmouseover onmousemove onmouseout onkeypress onkeydown onkeyup  <b>%focus</b> accesskey tabindex onfocus onblur  <b>input types</b> text password checkbox radio submit image reset button hidden file  <b>link types (rel, rev)</b> alternate stylesheet start next prev contents index glossary copyright chapter section subsection appendix help bookmark  <b>media descriptors</b> screen tty tv projection handheld print braille aural all	BLOCK ELEMENTS			<b>deprecated elements</b> applet center dir menu basefont font isindex s strike u  <b>entities</b> " &quot; & &amp; < &lt; > &gt; ' &apos;  (space) &nbsp; i &iexcl; ¢ &cent; £ &pound; ₣ &curren; ¥ &yen; ¦ &brvbar; § &sect; ¨ &uml; © &copy; ª &ordf; « &laquo; ¬ &not; - (cond.) &shy; ® &reg; ¯ &macr; ° &deg; ± &plusmn; ¹ &sup1; ² &sup2; ³ &sup3; ´ &acute; µ &micro; ¶ &para; · &middot; ¸ &cedil; º &ordm; » &raquo; ¼ &frac14; ½ &frac12; ¾ &frac34; ¿ &iquest; À &Agrave; Á &Aacute; Â &Acirc; Ã &Atilde; Ä &Auml; Å &Aring; Æ &AElig; Ç &Ccedil; È &Egrave; É &Eacute; Ê &Ecirc; Ë &Euml; Ì &Igrave; Í &Iacute; Î &Icirc; Ï &Iuml; Ð &ETH; Ñ &Ntilde; Ò &Ograve; Ó &Oacute; Ô &Ocirc; Õ &Otilde; Ö &Ouml;
	address	information on author	%attrs	
	blockquote	long quotation	%attrs, cite	
	div	generic container (block)	%attrs, align*	
	dl	definition list	%attrs, compact*	
	fieldset	form control group	%attrs	
	form	interactive form	%attrs, <b>action</b> , method, enctype, accept, name*, onsubmit, onreset, accept-charset, target*	
	h1-h6	six levels of headings	%attrs, align*	
	hr	horizontal rule	%attrs, align*, size*, width*, noshade*	
	noframes*	alternate content for non frame-based rendering	%attrs	
	noscript	content when scripts disabled	%attrs	
	ol	ordered list	%attrs, type*, start*, compact*	
	p	paragraph	%attrs, align*	
	pre	preformatted text	%attrs, width*	
	ul	unordered list	%attrs, type*, compact*	
	INLINE ELEMENTS			
	a	anchor (or link)	%attrs, charset, type, name, rel, rev, href, hreflang, target*, shape, coords, %focus	
	abbr	abbreviation	%attrs	
	acronym	acronym (UNO, NATO,...)	%attrs	
	b	bold text	%attrs	
	bdo	I18N BiDi over-ride	%coreattrs, %events, xml:lang, lang, <b>dir</b>	
	big	large font	%attrs	
	br	forced line break	%coreattrs, clear*	
	button	push button	%attrs, name, value, type, disabled, %focus	
	cite	citation or reference	%attrs	
	code	computer code	%attrs	
	dfn	definition	%attrs	
	em	emphasis	%attrs	
	i	italic text	%attrs	
	iframe*	inline subwindow	%coreattrs, londes, name, src, frameborder, marginwidth, marginheight, scrolling, align*, height, width	
	img	embedded image	%attrs, <b>src</b> , <b>alt</b> , longdesc, name, height, width, usemap, ismap, align*, border*, hspace*, vspace*	
	input	form control	%attrs, type, name, value, checked, disabled, readonly, size, maxlength, src, alt, ismap, usemap, onselect, onchange, accept, %focus, align*	
	kbd	text to be entered by the user	%attrs	
	label	form field label text	%attrs, for, accesskey, onfocus, onblur	
	map	client-side image map	%i18n, %events, <b>id</b> , class, style, title, name	
	object	generic embedded object	%attrs, declare, classid, codebase, data, type, codetype, archive, standby, height, width, usemap, name, tabindex, align*, border*, hspace*, vspace*	
	q	short inline quotation	%attrs, cite	
	samp	sample output from scripts	%attrs	
	select	option selector	%attrs, name, size, multiple, disabled, tabindex, onfocus, onblur, onchange	

&times;	×	small	small font	%attrs	⊆ &sube;
&Oslash;	Ø	span	generic container (inline)	%attrs	⊇ &supe;
&Ugrave;	Ù	strong	indicates stronger emphasis	%attrs	⊕ &oplus;
&Uacute;	Ú				⊗ &otimes;
&Ucirc;	Û	sub	subscript	%attrs	⊥ &perp;
&Uuml;	Ü	sup	superscript	%attrs	· &sdot;
&Yacute;	Ý				◇ &lloz;
&THORN;	þ	textarea	multi-line text field	%attrs, name, <b>rows</b> , <b>cols</b> , <i>disabled</i> , <i>readonly</i> , <i>onselect</i> , <i>onchange</i> , %focus	[ &lceil;
&szlig;	ß				] &rceil;
&agrave;	à	tt	teletype or monospaced text	%attrs	] &lfloor;
&aacute;	á				] &rfloor;
&acirc;	â	var	instance of a variable or program argument	%attrs	< &lang;
&atilde;	ã				> &rang;
&auml;	ä				
&aring;	å				
&aelig;	æ	TABLE ELEMENTS			← &larr;
&ccedil;	ç	caption	table caption	%attrs, align*	↑ &uarr;
&egrave;	è	col	table column	%attrs, span, width, valign, align, char, charoff	→ &rarr;
&eacute;	é	colgroup	table column group	%attrs, span, width, valign, align, char, charoff	↓ &darr;
&ecirc;	ê	table	table element (block)	%attrs, summary, width, border, frame, rules, cellpadding, cellspacing, align*, bgcolor*	↔ &harr;
&euml;	ë	tbody	table body	%attrs, align, char, charoff, valign	↵ &crarr;
&igrave;	ì	td	table data cell	%attrs, abbr, axis, headers, scope, rowspan, colspan, align, char, charoff, valign, bgcolor*, nowrap*, width*, height*	⇐ &lArr;
&iacute;	í				⇒ &uArr;
&icirc;	î	tfoot	table footer	%attrs, align, char, charoff, valign	⇒ &rArr;
&iuml;	ï	th	table header cell	%attrs, abbr, axis, headers, scope, rowspan, colspan, align, char, charoff, valign, bgcolor*, nowrap*, width*, height*	⇓ &dArr;
&eth;	ð				⇔ &hArr;
&ntilde;	ñ	thead	table header	%attrs, align, char, charoff, valign	
&ograve;	ò	tr	table row	%attrs, align, char, charoff, valign, bgcolor*	• &bull;
&oacute;	ó				' &prime;
&ocirc;	ô				— &oline;
&otilde;	õ				/ &frasl;
&ouml;	ö				⌘ &weierp;
&divide;	÷				⌚ &image;
&oslash;	ø				ℜ &real;
&ugrave;	ù				™ &trade;
&uacute;	ú				€ &euro;
&ucirc;	û				ℵ &alefsym;
&uuml;	ü				♠ &spades;
&yacute;	ý	area	image map area	%attrs, shape, coords, href, nohref, <b>alt</b> , target*, %focus	♣ &clubs;
&thorn;	þ				♥ &hearts;
&yuml;	ÿ	base	document base URI	<b>href</b> , id, target*	♦ &diams;
		body	document body	%attrs, onload, onunload, background*, bgcolor*, text*, link*, vlink*, alink*	
&forall;	∀	dd	definition description	%attrs	&ensp;
&part;	∂	del	deleted text	%attrs, cite, datetime	&emsp;
&exist;	∃	dt	definition term	%attrs	&thinsp;
&empty;	∅	frame	subwindow	%coreattrs, longdesc, name, src, frameborder, marginwidth, marginheight, <i>noresize</i> , scrolling	&zwj;
&nabla;	∇	frameset	window subdivision	%coreattrs, rows, cols, onload, onunload	&zwj;
&isin;	∈	head	document head	%i18n, id, profile	&lrm;
&notin;	∉	html	root element	<b>xmlns</b> ="http://www.w3.org/1999/xhtml", id, %i18n, version*	&rlm;
&ni;	∋	ins	inserted text	%attrs, cite, datetime	- &ndash;
&prod;	∏	legend	fieldset legend	%attrs, accesskey, align*	— &mdash;
&sum;	∑	li	list item	%attrs, type*, value*	` &lsquo;
&minus;	−	link	media-independent link	%attrs, charset, href, hreflang, type, rel, rev, media, target*	' &rsquo;
&lowast;	*	meta	generic metainformation	%i18n, id, http-equiv, name, <b>content</b> , scheme	' &sbquo;
&radic;	√	optgroup	option group	%attrs, <i>disabled</i> , <b>label</b>	` &ldquo;
&prop;	∝	option	selectable choice	%attrs, <i>selected</i> , <i>disabled</i> , label, value	" &rdquo;
&infin;	∞	param	named property value	id, <b>name</b> , value, valuetype, type	" &bldquo;
&ang;	∠	script	script statements	id, charset, <b>type</b> , src, <i>defer</i> , language*	† &dagger;
&and;	∧	style	style info	%i18n, id, <b>type</b> , media, title	‡ &Dagger;
&or;	∨	title	document title	%i18n, id	… &hellip;
&cap;	∩				%o &permil;
&cup;	∪				< &lsaquo;
&int;	∫				> &rsaquo;
&there4;	∴				
&sim;	∼				
&cong;	≈				
&asymp;	≈				
&neq;	≠				
&equiv;	≡				
&leq;	≤				
&geq;	≥				
&sub;	⊂				
&sup;	⊃				
&sub;	⊂				