Exp. No. E15	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO.: 01	ISSUE DATE: 05/12/2018
REV. NO.: 0	REV. DATE: 05/12/18	

Experiment Title: Write a program to send Mail using PHP

Objective:

To learn and implement a program to send Mail using PHP

Theory & Procedure:

PHP must be configured correctly in the php.ini file with the details of how your system sends email. Open php.ini file available in /etc/ directory and find the section headed [mail function].

Windows users should ensure that two directives are supplied. The first is called SMTP that defines your email server address. The second is called sendmail_from which defines your own email address. The configuration for Windows should look something like this –

```
[mail function]
; For Win32 only.
SMTP = smtp.secureserver.net
; For win32 only
sendmail_from = webmaster@tutorialspoint.com
```

Linux users simply need to let PHP know the location of their sendmail application. The path and any desired switches should be specified to the sendmail path directive.

The configuration for Linux should look something like this -

```
[mail function]
; For Win32 only.
SMTP =
; For win32 only
sendmail_from =
; For Unix only
sendmail_path = /usr/sbin/sendmail -t -i
Now you are ready to go -
```

Sending plain text email

PHP makes use of mail() function to send an email. This function requires three mandatory arguments that specify the recipient's email address, the subject of the message and the actual message additionally there are other two optional parameters.

```
mail( to, subject, message, headers, parameters );
Here is the description for each parameters.
```

Exp. No. E15	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO.: 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE: 05/12/18	

Sr.No	Parameter & Description
1	to
	Required. Specifies the receiver / receivers of the email
2	subject
	Required. Specifies the subject of the email. This parameter cannot contain any newline characters
3	message
	Required. Defines the message to be sent. Each line should be separated with a LF (\n). Lines should not exceed 70 characters
4	headers
	Optional. Specifies additional headers, like From, Cc, and Bcc. The additional headers should be separated with a CRLF (\r\n)
5	parameters
	Optional. Specifies an additional parameter to the send mail program

As soon as the mail function is called PHP will attempt to send the email then it will return true if successful or false if it is failed.

Multiple recipients can be specified as the first argument to the mail() function in a comma separated list.

Sending HTML email

When you send a text message using PHP then all the content will be treated as simple text. Even if you will include HTML tags in a text message, it will be displayed as simple text and HTML tags will not be formatted according to HTML syntax. But PHP provides option to send an HTML message as actual HTML message.

Exp. No. E15	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO.: 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE: 05/12/18	

While sending an email message you can specify a Mime version, content type and character set to send an HTML email.

Example

Following example will send an HTML email message to xyz@somedomain.com copying it to afgh@somedomain.com. You can code this program in such a way that it should receive all content from the user and then it should send an email.

```
<html>
 <head>
   <title>Sending HTML email using PHP</title>
 </head>
 <body>
   <?php
    $to = "xyz@somedomain.com";
    $subject = "This is subject";
    $message = "<b>This is HTML message.</b>";
    $message .= "<h1>This is headline.</h1>";
    $header = "From:abc@somedomain.com \r\n";
    $header .= "Cc:afgh@somedomain.com \r\n";
    $header .= "MIME-Version: 1.0\r\n";
    $header .= "Content-type: text/html\r\n";
    $retval = mail ($to,$subject,$message,$header);
    if( $retval == true ) {
      echo "Message sent successfully...";
    }else {
      echo "Message could not be sent...";
    }
   ?>
 </body>
</html>
```

Conclusion: