

Exp. No. E05	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

Experiment Title: Write a sample application to demonstrate AJAX

Objective: To learn and implement ASP AJAX

Theory:

ASP AJAX


AJAX is about updating parts of a web page, without reloading the whole page.

What is AJAX?

AJAX = Asynchronous JavaScript and XML. AJAX is a technique for creating fast and dynamic web pages.

AJAX allows web pages to be updated asynchronously by exchanging small amounts of data with the server behind the scenes. This means that it is possible to update parts of a web page, without reloading the whole page. Classic web pages, (which do not use AJAX) must reload the entire page if the content should change. Examples of applications using AJAX: Google Maps, Gmail, Youtube, and Facebook tabs.

How AJAX Works



AJAX is Based on Internet Standards. AJAX is based on internet standards, and uses a combination of:

- XMLHttpRequest object (to exchange data asynchronously with a server)
- JavaScript/DOM (to display/interact with the information)
- CSS (to style the data)
- XML (often used as the format for transferring data)

Exp. No. E05	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

AJAX applications are browser- and platform-independent!

The ASP File - "gethint.asp"

The ASP file checks an array of names, and returns the corresponding name(s) to the browser:

```

<%
response.expires=-1
dim a(30)
'Fill up array with names
a(1)="Anna"
a(2)="Brittany"
a(3)="Cinderella"
a(4)="Diana"
a(5)="Eva"
a(6)="Fiona"
a(7)="Gunda"
a(8)="Hege"
a(9)="Inga"
a(10)="Johanna"
a(11)="Kitty"
a(12)="Linda"
a(13)="Nina"
a(14)="Ophelia"
a(15)="Petunia"
a(16)="Amanda"
a(17)="Raquel"
a(18)="Cindy"
a(19)="Doris"
a(20)="Eve"
a(21)="Evita"
a(22)="Sunniva"
a(23)="Tove"
a(24)="Unni"
a(25)="Violet"
a(26)="Liza"
a(27)="Elizabeth"
a(28)="Ellen"

a(29)="Wenche"
a(30)="Vicky"

'get the q parameter from URL
q=ucase(request.querystring("q"))

'lookup all hints from array if length of
q>0
if len(q)>0 then
    hint=""
    for i=1 to 30
        if q=ucase(mid(a(i),1,len(q))) then
            if hint="" then
                hint=a(i)
            else
                hint=hint & " , " & a(i)
            end if
        end if
    next
end if

'Output "no suggestion" if no hint were
found
'or output the correct values
if hint="" then
    response.write("no suggestion")
else
    response.write(hint)
end if
%>

```

Procedure :

Write web application implementing above codes.

Conclusion: