

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

Experiment Title: Experiment Based on OOP and Advance OOP PHP

Objective:

To learn and implement programs based on OOP and Advance OOP PHP

Theory:

Object Oriented Concepts

Lets define important terms related to Object Oriented Programming.

Class – This is a programmer-defined data type, which includes local functions as well as local data. You can think of a class as a template for making many instances of the same kind (or class) of object.

Object – An individual instance of the data structure defined by a class. You define a class once and then make many objects that belong to it. Objects are also known as instance.

Member Variable – These are the variables defined inside a class. This data will be invisible to the outside of the class and can be accessed via member functions. These variables are called attribute of the object once an object is created.

Member function – These are the function defined inside a class and are used to access object data.

Inheritance – When a class is defined by inheriting existing function of a parent class then it is called inheritance. Here child class will inherit all or few member functions and variables of a parent class.

Parent class – A class that is inherited from by another class. This is also called a base class or super class.

Child Class – A class that inherits from another class. This is also called a subclass or derived class.

Polymorphism – This is an object oriented concept where same function can be used for different purposes. For example function name will remain same but it take different number of arguments and can do different task.

Overloading – a type of polymorphism in which some or all of operators have different implementations depending on the types of their arguments. Similarly functions can also be overloaded with different implementation.

Data Abstraction – Any representation of data in which the implementation details are hidden (abstracted).

Encapsulation – refers to a concept where we encapsulate all the data and member functions together to form an object.

Constructor – refers to a special type of function which will be called automatically whenever there is an object formation from a class.

Destructor – refers to a special type of function which will be called automatically whenever an object is deleted or goes out of scope.

Defining PHP Classes

The general form for defining a new class in PHP is as follows –

```
<?php
class phpClass {
    var $var1;
    var $var2 = "constant string";

    function myfunc ($arg1, $arg2) {
```

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

```

        [..]
    }
    [..]
}
?>

```

Here is the description of each line –

The special form class, followed by the name of the class that you want to define.

A set of braces enclosing any number of variable declarations and function definitions.

Variable declarations start with the special form var, which is followed by a conventional \$ variable name; they may also have an initial assignment to a constant value.

Function definitions look much like standalone PHP functions but are local to the class and will be used to set and access object data.

Example

Here is an example which defines a class of Books type –

```

<?php
class Books {
    /* Member variables */
    var $price;
    var $title;

    /* Member functions */
    function setPrice($par){
        $this->price = $par;
    }

    function getPrice(){
        echo $this->price . "<br/>";
    }

    function setTitle($par){
        $this->title = $par;
    }

    function getTitle(){
        echo $this->title . "<br/>";
    }
}
?>

```

The variable \$this is a special variable and it refers to the same object ie. itself.

Creating Objects in PHP

Once you defined your class, then you can create as many objects as you like of that class type. Following is an

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

example of how to create object using new operator.

```
$physics = new Books;
```

```
$maths = new Books;
```

```
$chemistry = new Books;
```

Here we have created three objects and these objects are independent of each other and they will have their existence separately. Next we will see how to access member function and process member variables.

Calling Member Functions

After creating your objects, you will be able to call member functions related to that object. One member function will be able to process member variable of related object only.

Following example shows how to set title and prices for the three books by calling member functions.

```
$physics->setTitle( "Physics for High School" );
```

```
$chemistry->setTitle( "Advanced Chemistry" );
```

```
$maths->setTitle( "Algebra" );
```

```
$physics->setPrice( 10 );
```

```
$chemistry->setPrice( 15 );
```

```
$maths->setPrice( 7 );
```

Now you call another member functions to get the values set by in above example –

```
$physics->getTitle();
```

```
$chemistry->getTitle();
```

```
$maths->getTitle();
```

```
$physics->getPrice();
```

```
$chemistry->getPrice();
```

```
$maths->getPrice();
```

This will produce the following result –

```
Physics for High School
```

```
Advanced Chemistry
```

```
Algebra
```

```
10
```

```
15
```

```
7
```

Constructor Functions

Constructor Functions are special type of functions which are called automatically whenever an object is created. So we take full advantage of this behaviour, by initializing many things through constructor functions.

PHP provides a special function called `__construct()` to define a constructor. You can pass as many as arguments you like into the constructor function.

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

Following example will create one constructor for Books class and it will initialize price and title for the book at the time of object creation.

```
function __construct( $par1, $par2 ) {
    $this->title = $par1;
    $this->price = $par2;
}
```

Now we don't need to call set function separately to set price and title. We can initialize these two member variables at the time of object creation only. Check following example below –

```
$physics = new Books( "Physics for High School", 10 );
$maths = new Books ( "Advanced Chemistry", 15 );
$chemistry = new Books ( "Algebra", 7 );
```

```
/* Get those set values */
$physics->getTitle();
$chemistry->getTitle();
$maths->getTitle();
```

```
$physics->getPrice();
$chemistry->getPrice();
$maths->getPrice();
```

This will produce the following result –

```
Physics for High School
Advanced Chemistry
Algebra
10
15
7
```

Destructor

Like a constructor function you can define a destructor function using function `__destruct()`. You can release all the resources with-in a destructor.

Inheritance

PHP class definitions can optionally inherit from a parent class definition by using the `extends` clause. The syntax is as follows –

```
class Child extends Parent {
    <definition body>
}
```

The effect of inheritance is that the child class (or subclass or derived class) has the following characteristics –

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

Automatically has all the member variable declarations of the parent class.

Automatically has all the same member functions as the parent, which (by default) will work the same way as those functions do in the parent.

Following example inherit Books class and adds more functionality based on the requirement.

```
class Novel extends Books {
    var $publisher;

    function setPublisher($par){
        $this->publisher = $par;
    }

    function getPublisher(){
        echo $this->publisher. "<br />";
    }
}
```

Now apart from inherited functions, class Novel keeps two additional member functions.

Function Overriding

Function definitions in child classes override definitions with the same name in parent classes. In a child class, we can modify the definition of a function inherited from parent class.

In the following example getPrice and getTitle functions are overridden to return some values.

```
function getPrice() {
    echo $this->price . "<br/>";
    return $this->price;
}
```

```
function getTitle(){
    echo $this->title . "<br/>";
    return $this->title;
}
```

Public Members

Unless you specify otherwise, properties and methods of a class are public. That is to say, they may be accessed in three possible situations –

From outside the class in which it is declared

From within the class in which it is declared

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

From within another class that implements the class in which it is declared

Till now we have seen all members as public members. If you wish to limit the accessibility of the members of a class then you define class members as private or protected.

Private members

By designating a member private, you limit its accessibility to the class in which it is declared. The private member cannot be referred to from classes that inherit the class in which it is declared and cannot be accessed from outside the class.

A class member can be made private by using private keyword in front of the member.

```
class MyClass {
  private $car = "skoda";
  $driver = "SRK";

  function __construct($par) {
    // Statements here run every time
    // an instance of the class
    // is created.
  }

  function myPublicFunction() {
    return("I'm visible!");
  }

  private function myPrivateFunction() {
    return("I'm not visible outside!");
  }
}
```

When MyClass class is inherited by another class using extends, myPublicFunction() will be visible, as will \$driver. The extending class will not have any awareness of or access to myPrivateFunction and \$car, because they are declared private.

Protected members

A protected property or method is accessible in the class in which it is declared, as well as in classes that extend that class. Protected members are not available outside of those two kinds of classes. A class member can be made protected by using protected keyword in front of the member.

Here is different version of MyClass –

```
class MyClass {
  protected $car = "skoda";
  $driver = "SRK";
}
```

Exp. No. E12	MANUAL NO. : DYPPCOE-CSE-T2-WT-II	SUBJECT: WEB TECHNOLOGIES- II
DEPARTMENT: CSE	ISSUE NO. : 01	ISSUE DATE: 05/12/2018
REV. NO. : 0	REV. DATE : 05/12/18	

```

function __construct($par) {
    // Statements here run every time
    // an instance of the class
    // is created.
}

function myPublicFunction() {
    return("I'm visible!");
}

protected function myPrivateFunction() {
    return("I'm visible in child class!");
}
}

```

Interfaces

Interfaces are defined to provide a common function names to the implementers. Different implementors can implement those interfaces according to their requirements. You can say, interfaces are skeletons which are implemented by developers.

As of PHP5, it is possible to define an interface, like this –

```

interface Mail {
    public function sendMail();
}

```

Then, if another class implemented that interface, like this –

```

class Report implements Mail {
    // sendMail() Definition goes here
}

```

} **Procedure :**

Write web programs using above code snippets for OOP in PHP.

Conclusion: