

Chilled Water Coil Output Report

Customer Name	Date	2026-08-08 19:53
Contact	Reference	
Project	Prepared By	admin
Tag / Description	Quantity	1

Coil Data

Coil Data	Value
Finned height	560.0 mm
Finned length	1100.0 mm
Rows deep	4
Number of feeds / circuits	22
Number of passes	4
Fins per inch	12.0
Tube material	Copper - wall 0.300 mm
Tube diameter	OD 9.530 mm / ID 8.930 mm
Fin material	Aluminum - 0.110 mm
Fin surface	Wavy + louvers
Face area	0.616 m2
External surface area	47.38 m2

Air Data

Air Data	Value
Total air flow	0.970 m3/s (3492 m3/h / 2055 CFM)
Face velocity	1.57 m/s
Entering dry bulb	27.00 degC
Entering wet bulb	19.53 degC
Entering relative humidity	50.0%
Leaving dry bulb	11.79 degC
Leaving wet bulb	11.17 degC
Leaving relative humidity	93.1%
Condensate rate	12.73 kg/h
Air pressure drop	24.38 Pa
Total capacity	26.43 kW
Sensible capacity	17.48 kW
Latent capacity	8.95 kW

Fluid Data

Fluid Data	Value
Fluid type	Water
Glycol concentration	0.0%
Entering fluid temperature	6.00 degC
Leaving fluid temperature	11.12 degC
Fluid flow rate	4.430 m3/h (1.231 L/s)
Fluid velocity in tubes	0.893 m/s
Fluid pressure drop	10.01 kPa
Supply header velocity	1.009 m/s
Return header velocity	1.009 m/s

Design target: Required capacity 25.26 kW; required leaving air 11.97 degC DB / 11.60 degC WB

This output report summarizes the selected coil operating point. Final production release should follow the organization's normal engineering review and validation procedure.