

Ore's Theorem

CS 111 Presentation

Youssef Adam Thomas Kang
Youssef Koreatam Michael Wong Gabriel Serrano

Department of Computer Science, University of California, Riverside

March 19, 2024

Questions

Introduction: Background Knowledge

To understand **Ore's theorem**, we must briefly recapitulate what it means for a graph to be **Hamiltonian**.

Introduction: Background Knowledge

To understand **Ore's theorem**, we must briefly recapitulate what it means for a graph to be **Hamiltonian**.

Let $G(V, E)$ be an undirected graph with $|V| \geq 3$ vertices.

Introduction: Background Knowledge

To understand **Ore's theorem**, we must briefly recapitulate what it means for a graph to be **Hamiltonian**.


Let $G(V, E)$ be an undirected graph with $|V| \geq 3$ vertices. If we are able to create a cycle T that meets each and every vertex strictly once, then G is considered **Hamiltonian**.

Introduction: Background Knowledge

To understand **Ore's theorem**, we must briefly recapitulate what it means for a graph to be **Hamiltonian**.

Let $G(V, E)$ be an undirected graph with $|V| \geq 3$ vertices. If we are able to create a cycle T that meets each and every vertex strictly once, then G is considered **Hamiltonian**.

Example:





Introduction: Background Knowledge

To understand **Ore's theorem**, we must briefly recapitulate what it means for a graph to be **Hamiltonian**.

Let $G(V, E)$ be an undirected graph with $|V| \geq 3$ vertices. If we are able to create a cycle T that meets each and every vertex strictly once, then G is considered **Hamiltonian**.

Example:



$$T = \{a, b, c, e, d, a\}$$

Introduction: Ore's Theorem Statement

Examples

Examples

Examples

Applications

Conclusion: Summary

Conclusion: Questions