

CHAPTER 1

Introduction

The proportion of elderly and mobility-impaired people in the overall population is predicted to grow dramatically over the next century, leaving a large proportion of the population unable to care for themselves, and also reducing the proportion of the able-bodied population available to care for those individuals [3]. With this issue looming, serious investments need to be made into technologies that can provide the support these groups need to live independent of human assistance.

Additionally, the emergence of carbon pricing in many countries to combat anthropogenic climate change, as well as underinvestment in Australian energy infrastructure, are causing rising energy prices. These prices have a particularly large effect on the elderly and disabled, as they generally have quite low incomes.

Coinciding with these issues is the booming embedded systems and sensor industries, which are creating increasingly smaller computer and sensing systems. Each iteration, these systems become more powerful, more affordable, and more networked. This phenomena, termed the Internet of Things (IoT), has produced sub-\$50 devices such as the Arduino and Raspberry Pi which unlock enormous potential to create embedded systems to help combat these and other issues. One can envision a future ‘smart home for the disabled’ which leverages the IoT to offer a variety of services to help reduce financial and physical burdens alike.

Sensing techniques to determine occupancy, the detection of the presence and number of people in an area, are of particular use to the elderly and disabled. Detection can be used to inform various devices that change state depending on the user’s location, providing a variety of useful automations. In particular, such a system could better regulate energy hungry devices to help reduce financial burden. Household climate control, which in some regions of Australia accounts for up to 40% of energy usage [1] is one area in which occupancy detection can reduce costs. Several papers have found efficiency can be significantly increased, with some approaches providing annual energy savings of up to 25% [2].

There exist a great many cheap sensors in this field that offer the capacity to predict occupancy. However, in many cases they suffer from problems of installa-

tion logistics, difficult assembly, assumptions on user's technology ownership and component cost. In a smart home for the disabled, accuracy is important, but accessibility is paramount.

In this research project, we construct an IoT-style occupancy detection sensor system that forms part of a theoretical 'smart home for the disabled.' This system must meet the following qualitative accessibility criteria;

- *Low Cost*: The set of components required should aim to minimise cost, as these devices are intended to be deployed in situations where the serviced user may be financially restricted.
- *Non-Invasive*: The sensors used in the system should gather as little information as necessary to achieve the detection goal; there are privacy concerns with the use of high-definition sensors.
- *Reliable*: The system should be able to operate without user intervention or frequent maintenance, and should be able to perform its occupancy detection goal with a high degree of accuracy.
- *Energy Efficient*: The system may be placed in a location where there is no access to mains power, or where the retrofitting of appropriate power interfaces can be expensive (such as a residential roof); the ability to survive for long periods on only battery power is advantageous.

Constructing a sensor system that meets these criteria involves a four step process outlined below. Each of these steps is dedicated a chapter in this dissertation.

1. *Literature Review*: An extensive literature review will be performed of the field of occupancy detection to determine which sensors types are most apparently appropriate for occupancy detection given the above criteria.
2. *Design*: Once the most appropriate sensor type is determined, a hardware and software prototype will be developed to provide a platform for experimentation and evaluation of the sensor, as well as to capture, store, visualize and replay sensor data for those purposes.
3. *Evaluation*: Once a prototype exists, a methodology will be developed to evaluate the properties of the sensor, and experiments will be designed and conducted to test different algorithms effectiveness in using the prototype for occupancy detection.
4. *Conclusion*: The prototype's experimental results will be analyzed to conclude as to its effectiveness with relation to the above criteria.

Bibliography

- [1] AUSTRALIAN BUREAU OF STATISTICS. Household water and energy use, Victoria: Heating and cooling. Tech. Rep. 4602.2, October 2011. Retrieved October 6, 2014 from <http://www.abs.gov.au/ausstats/abs@.nsf/0/85424ADCCF6E5AE9CA257A670013AF89>.
- [2] BELTRAN, A., ERICKSON, V. L., AND CERPA, A. E. ThermoSense: Occupancy thermal based sensing for HVAC control. In *Proceedings of the 5th ACM Workshop on Embedded Systems For Energy-Efficient Buildings* (2013), ACM, pp. 1–8.
- [3] CHAN, M., CAMPO, E., ESTÈVE, D., AND FOURNIOLS, J.-Y. Smart homes - current features and future perspectives. *Maturitas* 64, 2 (2009), 90–97.