
Improving Cantonese translation in existing multilingual translation models

Andreas H. H. Hansen

Department of Computer Science
Aarhus University
Aarhus, Denmark
ahhh@cs.au.dk

Lasse W. Edslev

Department of Computer Science
Aarhus University
Aarhus, Denmark
lasse.edslev@cs.au.dk

Victor B. Poulsen

Department of Computer Science
Aarhus University
Aarhus, Denmark
au705783@uni.au.dk

Abstract

This is the abstract...

1 Related works

1.1 MADLAD

MADLAD As a base for our experiments, and later as a model to finetune, we use the MADLAD model. This is a general translation model, with 10.7B parameters, trained on web-scraped unlabeled data in 419 languages. The dataset contains both Mandarin and Cantonese data, but the amount of Cantonese data is very limited compared to the amount of Mandarin data (approximately 61 times less). The model architecture is a standard transformer-based sequence-to-sequence model, similar to the architecture used in models such as T5[?].

2 Introduction

This project explores improving machine translation tasks working with Cantonese text. Although Cantonese has more than 85 million speakers, it is very underrepresented in machine learning and translation, as large training corpusses are rare as the language is most used in its spoken form. This results in many Cantonese NLP tasks simply being handled by models trained mostly or exclusively on Mandarin language data.

In this project, we explore how both unsupervised and supervised learning can be applied to improve the quality of translation tasks. For this, we use the professionally translated data in the SMOL[1] and GATITOS[3] datasets and the unlabeled data in the dataset collected by Dare et al.[2].

The first experiment performed was a simple token replacement. As there is overlap between Cantonese and Mandarin characters, we replace the tokens that are different in the Cantonese input with their Mandarin equivalents before feeding the text to a pre-trained MADLAD[5]. This simple approach showed some promise, but was limited by not being able to handle differences in grammar and differences in meaning of characters that are the same in both languages.

We use the unlabeled data to train Cantonese token embeddings and then transform these embeddings into the embedding space of a pre-trained English-Mandarin model, MADLAD, using the token-level translations in GATITOS. This **TODO: Results of this.**

We then finetune MADLAD on the SMOL dataset and evaluate the performance of the finetuned model on a held-out test set from SMOL. **TODO: Results of this.**

3 Datasets

3.1 SMOL

SMOL[1] (Set of Maximal Leverage) is a high-quality translation corpus from English to more than a hundred low-resource languages. SMOL includes SMOLSent and SMOLDoc, which represent sentence-level and document-level translations is nicely accompanied by Gatitos[3] which provides token-level translations across many of the same languages. In this project specifically, we use the English-Cantonese portion of SMOL and GATITOS, where there are translations on all three levels of data.

3.2 Monolingual Cantonese corpus by M. Dare, et. al

In their work on unsupervised Mandarin-Cantonese machine translation, Dare et. al.[2] collected a large corpus of monolingual Cantonese sentences from various online sources. In total 912258 lines were collected by scraping and cleaning data from Wikipedia, Instagram, and a few other sites including a few corpusses compiled for previous academic work. Common for most sources that form the corpus is that the content is mostly user-generated text, which often includes non-standard spellings and colloquial language, which is typical for Cantonese as a written language. We use this corpus to train Cantonese token embeddings for the embedding transform experiment described in Section 3.

4 Experiments

4.1 Embedding transform

If we were to simply train a model on Gatitos token-level data it might get slightly better at some characters in the small Gatitos dataset, but we would not be able to generalize the model to become better at all Cantonese vocabulary.

Instead we propose the following experiment: We train embeddings on a large corpus of unlabeled Cantonese data, hoping to get embeddings that better represent semantic similarity between Cantonese tokens than the embeddings of MADLAD do. We then perform an embedding transform from our Cantonese embeddings to MADLAD’s Chinese embedding space using token-level translations from Gatitos. Specifically, we train a transformation matrix W such that for a specific Cantonese-Chinese token embedding pair $E_{canto}, E_{mandarin}$ the embedding transformation $E_{canto}W$ approximates $E_{mandarin}$. This training was simply done optimizing the loss function $\|E_{canto}W - E_{mandarin}\|$ with the ADAM-algorithm[4].

For training the Cantonese embeddings we use the Monolingual Cantonese corpus by M. Dare, et. al. to train a Word2Vec[6] model.

4.2 Smol finetuning

We finetune the MADLAD model on the SMOL dataset, specifically the English-Cantonese portion of the dataset, using a ??? split for training/validation. We finetune for ?? epochs with a learning rate of ??? and batch size ???.

5 Results

5.1 Embedding transform

5.2 Smol finetuning

6 Discussion

References

- [1] Isaac Caswell, Elizabeth Nielsen, Jiaming Luo, Colin Cherry, Geza Kovacs, Hadar Shemtov, Partha Talukdar, Dinesh Tewari, Baba Mamadi Diane, Djibrila Diane, Solo Farabado Cissé, Koulako Moussa Doumbouya, Edoardo Ferrante, Alessandro Guasoni, Christopher Homan, Mamadou K. Keita, Sudhamoy DebBarma, Ali Kuzhuget, David Anugraha, Muhammad Ravi Shulthan Habibi, Genta Indra Winata, Anthony Munthali, Sina Ahmadi, Andrei Chermyshev, Mingfei Lau, and Jonathan Eng. Smol: Professionally translated parallel data for 115 under-represented languages, 2025.
- [2] Megan Dare, Valentina Fajardo Diaz, Averie Ho Zoen So, Yifan Wang, and Shibingfeng Zhang. Unsupervised mandarin-cantonese machine translation, 2023.
- [3] Alexander Jones, Isaac Caswell, Orhan Firat, and Ishank Saxena. GATITOS: Using a new multilingual lexicon for low-resource machine translation. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 371–405, Singapore, December 2023. Association for Computational Linguistics.
- [4] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017.
- [5] Sneha Kudugunta, Isaac Caswell, Biao Zhang, Xavier Garcia, Christopher A. Choquette-Choo, Katherine Lee, Derrick Xin, Aditya Kusupati, Romi Stella, Ankur Bapna, and Orhan Firat. Madlad-400: A multilingual and document-level large audited dataset, 2023.
- [6] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space, 2013.