

# DataFrames in R

## Loading and looking at your dataframe

The easiest data source to load is a csv. To read a csv into the global environment use the `read_csv` function. To see all the arguments of `read_csv` type `?read.csv` in the console and run the command.

You can assign variables with either `<-` or the `=` sign. We name our data frame `qbs` below.

```
# NOTE: Make sure your .rmd file is in the same directory as your .csv file.
qbs <- read.csv('nfl_qbs.csv', stringsAsFactors = FALSE)
```

You can look at a preview of your data frame by double clicking on the data frame in the data UI to the left. If you want to look at it without the interface use the `head()` function.

```
head(qbs)
```

##	Player	Year	Age	Draft	Tm	Lg	G	GS	Cmp	Att	Cmp_per	Yds	TD	Int	Pick6
## 1	Alex Tanney	2019	32		NYG	NFL	1	0	1	1	100.00	1	0	0	NA
## 2	Tim Boyle	2019	25		GNB	NFL	3	0	3	4	75.00	15	0	0	NA
## 3	Matt Schaub	2019	38	Mar-90	ATL	NFL	6	1	50	67	74.63	580	3	1	NA
## 4	Drew Brees	2019	40	Feb-32	NOR	NFL	11	11	281	378	74.34	2979	27	4	NA
## 5	Derek Carr	2019	28	Feb-36	OAK	NFL	16	16	361	513	70.37	4054	21	8	2
## 6	Chase Daniel	2019	33		CHI	NFL	3	1	45	64	70.31	435	3	2	NA
##	TD_per	Int_per	Rate	Sk	Yds.1	Y.A	AY.A	ANY.A	Y.G	W	L	T	X4QC	GWD	
## 1	0.0	0.00	79.2	0	0	1.00	1.00	1.00	1.0	NA	NA	NA	NA	NA	
## 2	0.0	0.00	80.2	0	0	3.75	3.75	3.75	5.0	NA	NA	NA	NA	NA	
## 3	4.5	1.49	109.0	2	19	8.66	8.88	8.35	96.7	0	1	0	NA	NA	
## 4	7.1	1.06	116.3	12	89	7.88	8.83	8.33	270.8	8	3	0	1	2	
## 5	4.1	1.56	100.8	29	184	7.90	8.02	7.25	253.4	7	9	0	2	3	
## 6	4.7	3.13	91.6	7	48	6.80	6.33	5.03	145.0	0	1	0	NA	NA	

You can view the first however many by adding an argument to `head`.

```
head(qbs, 3)
```

##	Player	Year	Age	Draft	Tm	Lg	G	GS	Cmp	Att	Cmp_per	Yds	TD	Int	Pick6
## 1	Alex Tanney	2019	32		NYG	NFL	1	0	1	1	100.00	1	0	0	NA
## 2	Tim Boyle	2019	25		GNB	NFL	3	0	3	4	75.00	15	0	0	NA
## 3	Matt Schaub	2019	38	Mar-90	ATL	NFL	6	1	50	67	74.63	580	3	1	NA
##	TD_per	Int_per	Rate	Sk	Yds.1	Y.A	AY.A	ANY.A	Y.G	W	L	T	X4QC	GWD	
## 1	0.0	0.00	79.2	0	0	1.00	1.00	1.00	1.0	NA	NA	NA	NA	NA	
## 2	0.0	0.00	80.2	0	0	3.75	3.75	3.75	5.0	NA	NA	NA	NA	NA	
## 3	4.5	1.49	109.0	2	19	8.66	8.88	8.35	96.7	0	1	0	NA	NA	

Our data in this example has column titles and players in each row which help us identify the data. If you don't have this then you can name the columns and rows with `colnames()` and `row.names()`. The `c()` stands for concatenate, it creates a vector.

Notice I have `eval=FALSE` in the chunk options. This means we will not run the code even when we run the entire file. I also put a `#` in front, this makes the code a comment and no longer runnable.

```
#colnames(qbs) <- c("column1", "column2", "column3", "column4")  
  
#row.names(qbs) <- c("player1", "player2", "player3", "player4")
```

To see the size of your data frame you can either look at the data UI or you can run `dim()`. The `[]` notation allows us to return the subset of the `dim()` vector. Vectors in R start with an index at 1 unlike python which starts at 0. Essentially, `dim(qbs)[1]` will return the first number in the `dim(qbs)` returned vector. You can also use `nrow()` and `ncol()` to get the dataframe size.

```
# Returns the number of rows and columns  
dim(qbs)
```

```
## [1] 73 29
```

```
# number of rows  
dim(qbs)[1]
```

```
## [1] 73
```

```
# number of columns  
dim(qbs)[2]
```

```
## [1] 29
```

```
# number of rows  
nrow(qbs)
```

```
## [1] 73
```

```
# number of columns  
ncol(qbs)
```

```
## [1] 29
```

## Subsetting

You can subset data frames very easily with the `[]` notation. The subset is `dataframe[rows,columns]`.

```
# returns the 1st row
```

```
qbs[1,]
```

```
##           Player Year Age Draft  Tm  Lg G GS Cmp Att Cmp_per Yds TD Int Pick6
## 1 Alex Tanney 2019  32      NYG NFL 1  0  1  1    100  1  0  0    NA
##   TD_per Int_per Rate Sk Yds.1 Y.A AY.A ANY.A Y.G  W  L  T X4QC GWD
## 1      0      0 79.2  0      0  1  1      1  1 NA NA NA  NA  NA
```

```
# returns the 1st column
```

```
qbs[,1]
```

```
## [1] "Alex Tanney"      "Tim Boyle"      "Matt Schaub"
## [4] "Drew Brees"       "Derek Carr"     "Chase Daniel"
## [7] "Ryan Tannehill"   "Kirk Cousins"   "Jimmy Garoppolo"
## [10] "Teddy Bridgewater" "Deshaun Watson" "Colt McCoy"
## [13] "Tyrod Taylor"     "Matt Ryan"      "Russell Wilson"
## [16] "Lamar Jackson"    "Philip Rivers"  "Patrick Mahomes"
## [19] "Nick Foles"       "Joe Flacco"     "Dak Prescott"
## [22] "Matt Moore"       "Case Keenum"    "Kyler Murray"
## [25] "Luke Falk"        "Matthew Stafford" "Drew Lock"
## [28] "Carson Wentz"     "Mitchell Trubisky" "Jared Goff"
## [31] "Devlin Hodges"    "Mason Rudolph"  "Aaron Rodgers"
## [34] "Kyle Allen"       "Ryan Fitzpatrick" "Sam Darnold"
## [37] "Eli Manning"      "Daniel Jones"   "Tom Brady"
## [40] "Jacoby Brissett" "Jameis Winston" "Gardner Minshew"
## [43] "Robert Griffin"  "Mike Glennon"   "Josh McCown"
## [46] "Andy Dalton"      "Marcus Mariota" "Baker Mayfield"
## [49] "Jeff Driskel"     "Josh Allen"     "Dwayne Haskins"
## [52] "Sean Mannion"     "A.J. McCarron"  "Ben Roethlisberger"
## [55] "Cam Newton"       "David Blough"   "Will Grier"
## [58] "Brian Hoyer"      "Josh Rosen"     "Matt Barkley"
## [61] "Blake Bortles"    "Ryan Griffin"   "Taysom Hill"
## [64] "Trevor Siemian"   "Jarrett Stidham" "Ryan Finley"
## [67] "Brandon Allen"    "Brett Hundley"  "Garrett Gilbert"
## [70] "David Fales"      "Trace McSorley" "Nick Mullens"
## [73] "Cooper Rush"
```

```
# returns the value at the 15th row and first column
```

```
qbs[15, 1]
```

```
## [1] "Russell Wilson"
```

You can use combinations of `c()` and `:` to get more than single values!

```
# returns the 10th and 15th items in the first row
```

```
qbs[c(10, 15), 1]
```

```
## [1] "Teddy Bridgewater" "Russell Wilson"
```

```
# returns rows 10 through 15 and columns 1 through 3
```

```
qbs[10:15, 1:3]
```

```
##           Player Year Age
## 10 Teddy Bridgewater 2019 27
```

```
## 11    Deshaun Watson 2019 24
## 12      Colt McCoy 2019 33
## 13      Tyrod Taylor 2019 30
## 14      Matt Ryan 2019 34
## 15    Russell Wilson 2019 31
```

Another way to get a single vector column is with the \$ sign.

```
qbs$Player
```

```
## [1] "Alex Tanney"      "Tim Boyle"      "Matt Schaub"
## [4] "Drew Brees"      "Derek Carr"     "Chase Daniel"
## [7] "Ryan Tannehill"  "Kirk Cousins"   "Jimmy Garoppolo"
## [10] "Teddy Bridgewater" "Deshaun Watson" "Colt McCoy"
## [13] "Tyrod Taylor"    "Matt Ryan"      "Russell Wilson"
## [16] "Lamar Jackson"   "Philip Rivers"  "Patrick Mahomes"
## [19] "Nick Foles"      "Joe Flacco"     "Dak Prescott"
## [22] "Matt Moore"      "Case Keenum"    "Kyler Murray"
## [25] "Luke Falk"       "Matthew Stafford" "Drew Lock"
## [28] "Carson Wentz"    "Mitchell Trubisky" "Jared Goff"
## [31] "Devlin Hodges"   "Mason Rudolph"  "Aaron Rodgers"
## [34] "Kyle Allen"      "Ryan Fitzpatrick" "Sam Darnold"
## [37] "Eli Manning"     "Daniel Jones"   "Tom Brady"
## [40] "Jacoby Brissett" "Jameis Winston" "Gardner Minshew"
## [43] "Robert Griffin"  "Mike Glennon"   "Josh McCown"
## [46] "Andy Dalton"     "Marcus Mariota" "Baker Mayfield"
## [49] "Jeff Driskel"    "Josh Allen"     "Dwayne Haskins"
## [52] "Sean Mannion"    "A.J. McCarron"  "Ben Roethlisberger"
## [55] "Cam Newton"      "David Blough"   "Will Grier"
## [58] "Brian Hoyer"     "Josh Rosen"     "Matt Barkley"
## [61] "Blake Bortles"   "Ryan Griffin"   "Taysom Hill"
## [64] "Trevor Siemian"  "Jarrett Stidham" "Ryan Finley"
## [67] "Brandon Allen"   "Brett Hundley"  "Garrett Gilbert"
## [70] "David Fales"     "Trace McSorley" "Nick Mullens"
## [73] "Cooper Rush"
```

Notice that when you return a single column the output is a vector but when it is more than one you return a data frame.

```
qbs[, c('Player', 'Age')]
```

```
##      Player Age
## 1    Alex Tanney 32
## 2      Tim Boyle 25
## 3    Matt Schaub 38
## 4    Drew Brees 40
## 5    Derek Carr 28
## 6    Chase Daniel 33
## 7    Ryan Tannehill 31
## 8      Kirk Cousins 31
## 9    Jimmy Garoppolo 28
## 10  Teddy Bridgewater 27
## 11   Deshaun Watson 24
## 12     Colt McCoy 33
## 13   Tyrod Taylor 30
## 14     Matt Ryan 34
```

## 15	Russell Wilson	31
## 16	Lamar Jackson	22
## 17	Philip Rivers	38
## 18	Patrick Mahomes	24
## 19	Nick Foles	30
## 20	Joe Flacco	34
## 21	Dak Prescott	26
## 22	Matt Moore	35
## 23	Case Keenum	31
## 24	Kyler Murray	22
## 25	Luke Falk	25
## 26	Matthew Stafford	31
## 27	Drew Lock	23
## 28	Carson Wentz	27
## 29	Mitchell Trubisky	25
## 30	Jared Goff	25
## 31	Devlin Hodges	23
## 32	Mason Rudolph	24
## 33	Aaron Rodgers	36
## 34	Kyle Allen	23
## 35	Ryan Fitzpatrick	37
## 36	Sam Darnold	22
## 37	Eli Manning	38
## 38	Daniel Jones	22
## 39	Tom Brady	42
## 40	Jacoby Brissett	27
## 41	Jameis Winston	25
## 42	Gardner Minshew	23
## 43	Robert Griffin	29
## 44	Mike Glennon	30
## 45	Josh McCown	40
## 46	Andy Dalton	32
## 47	Marcus Mariota	26
## 48	Baker Mayfield	24
## 49	Jeff Driskel	26
## 50	Josh Allen	23
## 51	Dwayne Haskins	22
## 52	Sean Mannion	27
## 53	A.J. McCarron	29
## 54	Ben Roethlisberger	37
## 55	Cam Newton	30
## 56	David Blough	24
## 57	Will Grier	24
## 58	Brian Hoyer	34
## 59	Josh Rosen	22
## 60	Matt Barkley	29
## 61	Blake Bortles	27
## 62	Ryan Griffin	30
## 63	Taysom Hill	29
## 64	Trevor Siemian	28
## 65	Jarrett Stidham	23
## 66	Ryan Finley	25
## 67	Brandon Allen	27
## 68	Brett Hundley	26

```
## 69    Garrett Gilbert  28
## 70      David Fales  29
## 71    Trace McSorley  24
## 72      Nick Mullens  24
## 73      Cooper Rush  26
```

You can also subset the dataframe by looking for certain values.

```
qbs[qbs$Player == "Jimmy Garoppolo", ]
```

```
##           Player Year Age  Draft  Tm  Lg  G  GS  Cmp Att Cmp_per  Yds TD Int
## 9 Jimmy Garoppolo 2019  28 Feb-62 SFO NFL 16 16 329 476   69.12 3978 27 13
##   Pick6 TD_per Int_per Rate Sk Yds.1  Y.A AY.A ANY.A  Y.G  W L T X4QC GWD
## 9      1   5.7     2.73 102 36   237 8.36 8.26  7.22 248.6 13 3 0    4   4
```

## Computing in dataframes

It is pretty easy to compute values from the dataframe. Generally, you want to compute values from columns. Below we return the mean and median of TDs from the QBs.

```
mean(qbs$TD)
```

```
## [1] 10.83562
```

```
median(qbs$TD)
```

```
## [1] 6
```

You can get your basic distribution with the `summary()` function.

```
summary(qbs$TD)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      0.00   0.00   6.00   10.84   21.00   36.00
```

Now, with what we learned before, what if we wanted all the information of qbs who threw more than 30 TDs?

```
qbs[qbs$TD > 30, ]
```

```
##      Player Year Age Draft Tm Lg G GS Cmp Att Cmp_per Yds TD Int
## 15 Russell Wilson 2019 31 Mar-75 SEA NFL 16 16 341 516 66.09 4110 31 5
## 16 Lamar Jackson 2019 22 Jan-32 BAL NFL 15 15 265 401 66.08 3127 36 6
## 41 Jameis Winston 2019 25 1-Jan TAM NFL 16 16 380 626 60.70 5109 33 30
##      Pick6 TD_per Int_per Rate Sk Yds.1 Y.A AY.A ANY.A Y.G W L T X4QC GWD
## 15      2      6.0      0.97 106.3 48 319 7.97 8.73 7.42 256.9 11 5 0 4 5
## 16     NA      9.0      1.50 113.3 23 106 7.80 8.92 8.19 208.5 13 2 0 1 2
## 41      7      5.3      4.79 84.3 47 282 8.16 7.06 6.15 319.3 7 9 0 2 2
```

or we can use the `which` function

```
qbs[which(qbs$TD > 30), ]
```

```
##      Player Year Age Draft Tm Lg G GS Cmp Att Cmp_per Yds TD Int
## 15 Russell Wilson 2019 31 Mar-75 SEA NFL 16 16 341 516 66.09 4110 31 5
## 16 Lamar Jackson 2019 22 Jan-32 BAL NFL 15 15 265 401 66.08 3127 36 6
## 41 Jameis Winston 2019 25 1-Jan TAM NFL 16 16 380 626 60.70 5109 33 30
##      Pick6 TD_per Int_per Rate Sk Yds.1 Y.A AY.A ANY.A Y.G W L T X4QC GWD
## 15      2      6.0      0.97 106.3 48 319 7.97 8.73 7.42 256.9 11 5 0 4 5
## 16     NA      9.0      1.50 113.3 23 106 7.80 8.92 8.19 208.5 13 2 0 1 2
## 41      7      5.3      4.79 84.3 47 282 8.16 7.06 6.15 319.3 7 9 0 2 2
```

The `which` function returns an index value and the subset uses those index values to decide what to keep.

Which QB has the most TDs? Notice we use `==`. `=` assigns variables while `==` is what we think of when we say equals.

```
qbs$Player[which(qbs$TD == max(qbs$TD))]
```

```
## [1] "Lamar Jackson"
```

or to get the player and value

```
qbs[which(qbs$TD == max(qbs$TD)), c('Player', 'TD')]
```

```
##      Player TD
## 16 Lamar Jackson 36
```

## Missing Data

To check if our data is missing values we use the `is.na` function. Combined with the `any` you can see if your data frame has missing data.

```
any(is.na(qbs))
```

```
## [1] TRUE
```

let's remove the na's with `na.omit`

```
qbs_com <- na.omit(qbs)
```

```
dim(qbs_com)[1]
```

```
## [1] 14
```

Now we see only 14 QBs had all columns filled. That's not even the entire leagues starting QBs. Why is that? Be careful with data. In this example, one of the reasons is Pick6's. A Pick6 is recorded only when it happens so instead of a zero when a QB didn't throw any in the season it is missing. Instead let's make our new data frame starter QBs who threw at least 200 passes.

```
qbs_start <- qbs[(qbs$GS > 0 & qbs$Att >= 200), ]
```

Now we are down to 33 QBs.

Lastly, we can create new columns from others!

```
qbs_start$td_int_ratio <- qbs_start$TD_per/qbs_start$Int_per
```

## Practice - Class Activity

Create a new data frame called `mvp`. Start by further narrowing the `qbs_start` data frame by only keeping the top half of QBs by the number of TDs thrown. That means greater than or equal to the top 50 percent.

How many QBs are in the discussion?

Show the distribution of the TDs by these QBs

Using what you learned show the top three QBs in total number of TDs. (Hint: Look up the `order` function)

Now, I like a QB who is efficient. Let's narrow it down to 5 candidates by taking the top 5 QBs in `td_int_ratio`!

Finally, we will decide our MVP based on a weighted scale. Create a column called `rank` that is the sum of 20 percent times `cmp_per` (completion percentage), 30 percent times `TD`, 30 percent times `td_int_ratio`, and 20 percent times `GWD` (game winning drives). Show the QBs, their statistics used to create `rank`, and `rank` in the final output dataframe. The highest overall rank value is our MVP.

Turn your R-notebook into the appropriate Gradescope Assignment. Turn it in by the end of class