

Das ECI-Offsetprofil **PSO\_Uncoated\_ISO12647\_eci.icc** basiert auf der Charakterisierungsdatei „**FOGRA47L.txt**“ und gilt für die folgenden Druckbedingungen gemäß internationaler Standards ISO 12647-2:2004 und ISO 12647-2:2004/Amd 1:2007:

Akzidenzoffset, Papiertyp 4, ungestrichen weiß Offset, Positivkopie, Tonwertzunahmekurven C (CMY) und D (K), weiße Messunterlage.

Die Profilberechnung erfolgte im Heidelberg ColorTool 3.5.1 mit den folgenden Einstellungen:

GCR	50%
max. Flächendeckung	300%
max. Schwarz	98%

*The ECI offset profile **PSO\_Uncoated\_ISO12647\_eci.icc** is based on the characterization data set “**FOGRA47L.txt**” applicable to the following reference printing condition according to the international standards ISO 12647-2:2004 and ISO 12647-2:2004/Amd 1:2007:*

*Commercial and specialty offset, paper type 4, uncoated white paper, positive plates, tone value increase curves C (CMY) and D (K), white backing.*

*The profile was created using the Heidelberg ColorTool 3.5.1 with the following settings:*

<i>GCR</i>	<i>50%</i>
<i>total dot area</i>	<i>300%</i>
<i>maximum Black</i>	<i>98%</i>