



Implementing probabilistic photometric redshifts on DES SV data

Matías Carrasco Kind

Department of Astronomy
University of Illinois

DES SV data (fixed!)



VVDS Deep 02hr (3117)

CDFS (3721)

VVDS Wide 14hr (2970)

COSMOS (6148)

Secure redshifts $3 \leq Z_{\text{FLAG}} \leq 4$

$0.01 \leq Z \leq 1.5$

15956 galaxies

7978 for training and 7978 for testing


Use 5 bands from MAG_AUTO and MAG_DETMODEL

Use colors (8)

TPZ: Trees for Photo-Z







- Provides photo- z PDF and confidence values
- Deals with missing data
- Includes measurements errors
- Provides useful ancillary information
- *Out-of-Bag* data for unbiased errors
- No need for validation set




Carrasco Kind & Brunner 2013a

<http://lcdm.astro.illinois.edu/research/TPZ.html>


Preliminary results : True plots and PDF



Preliminary results : Metrics



Preliminary results: Error distribution




All these metrics were calculated using the mean of the probability density function


Preliminary results: Using PDFs for $N(z)$





$N(z)$ from PDFs reproduces better the underlying distribution.



Also seen in SDSS,
DEEP2 and z COSMOS
among others.



Ancillary examples: OOB error and importance



MAG_DETMODEL

MAG_AUTO



Multiple "independent" techniques can be combined into a powerful one (Carrasco Kind & Brunner, 2013b, c in prep.)

We use a modified and parallel version of BPZ (Benitez, 2000) with a prior from Random Naïve Bayes Classifier method

Extend it using a 3rd technique from Self-Organized-Maps

Our approach

Template fitting

+

Prior information

+

Empirical method

+

Weigthing scheme



photo- z PDF



Suppose a set of templates T and n magnitudes m_1, m_2, \dots, m_n , the probability is:

$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T P(z, T|\vec{m}) P(\vec{m}|z, T)$$

where $\vec{m} = (m_1, m_2, \dots, m_n)$

Template fitting photo- z



Suppose a set of templates T and n magnitudes m_1, m_2, \dots, m_n , the probability is:

$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T P(z, T|\vec{m}) P(\vec{m}|z, T)$$

where $\vec{m} = (m_1, m_2, \dots, m_n)$

Prior

Likelihood

Template fitting photo- z





Suppose a set of templates T and n magnitudes m_1, m_2, \dots, m_n , the probability is:

$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T P(z, T|\vec{m}) P(\vec{m}|z, T)$$

where $\vec{m} = (m_1, m_2, \dots, m_n)$

Prior

Likelihood



Random Naïve Bayes Classifier prior



$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T \underbrace{P(z, T|\vec{m})}_{\text{Prior}} \underbrace{P(\vec{m}|z, T)}_{\text{Likelihood}}$$

RNBC needs training set

Assume *naïvely* $m_i \perp m_j$

Bootstrap samples, random subset of magnitudes

Random Naïve Bayes Classifier prior



$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T \underbrace{P(z, T|\vec{m})}_{\text{Prior}} \underbrace{P(\vec{m}|z, T)}_{\text{Likelihood}}$$

RNBC needs training set

Assume *naïvely* $m_i \perp m_j$

Bootstrap samples, random subset of magnitudes

$$\text{RNBC prior} \Rightarrow P(z, T|\vec{m}) \propto P(z)P(T|z) \prod_{i=1}^n P(m_i|z, T)$$

Random Naïve Bayes Classifier prior



$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T P(z, T|\vec{m}) P(\vec{m}|z, T)$$

Prior Likelihood

RNBC needs training set

Assume *naïvely* $m_i \perp m_j$

Bootstrap samples, random subset of magnitudes

$$\text{RNBC prior} \Rightarrow P(z, T|\vec{m}) \propto P(z)P(T|z) \prod_{i=1}^n P(m_i|z, T)$$


PCA transformations

A model is assumed for this term

Random Naïve Bayes Classifier prior



$$P(z|\vec{m}) = \sum_T P(z, T|\vec{m}) \propto \sum_T P(z, T|\vec{m}) P(\vec{m}|z, T)$$




Likelihood

$P(m_i | z, T)$

Combining techniques


Mod BPZ



Combining techniques

Mod BPZ

Mod BPZ + RNBC prior




Combining techniques

Mod BPZ

Mod BPZ + RNBC prior

TPZ




Combining techniques

Mod BPZ

Mod BPZ + RNBC prior

TPZ

TPZ+Mod BPZ + prior



Combining techniques


Mod BPZ

Mod BPZ + RNBC prior

TPZ

TPZ+Mod BPZ + prior

TPZ+Mod BPZ+prior
 $z_{\text{Conf}} > 0.5$



Combining techniques

Mod BPZ


Mod BPZ + RNBC prior

TPZ




TPZ+Mod BPZ + prior

TPZ+Mod BPZ+prior
 $z_{\text{Conf}} > 0.5$

TPZ+Mod BPZ+prior
 $z_{\text{Conf}} > 0.9$



Combining techniques



Simulated DES




We use TPZ (Carrasco Kind & Brunner, 2013a) to generate photo- z for all galaxies.

100,00 for training
5 magnitudes only


~ 0.17 sec per PDF

Store 43 million PDFs
for analysis

No outlier removal



Simulated DES



Thanks!




Questions?

Matias Carrasco Kind
University of Illinois
mcarras2@illinois.edu

TPZ scheme



TPZ Trees for Photo-Z



Performance tests

