

Machine Learning course

Lab assignment 1: linear-threshold classifiers

Augustin VIOT

October 17, 2017

Contents

1	Introduction	1
2	Program a simple linear classifier	2
3	Simple linear classifier for 2D binary problems, manual design	3
3.1	Dataset1	3
3.2	Dataset 2	6
3.3	Adding a random perturbation	7
3.3.1	Analyse of the results	8
4	Simple linear classifier for Iris data, manual design	9

1 Introduction

This document is a repport of the lab assignement done in the course of Machine learning at the University of Genova (UNIGE). It describes the basic methods and implementations for the Simple linear classifier. We will describe the three tasks done in this lab assignement :

1. Program a simple linear classifier
2. Simple linear classifier for 2D binary problems, manual design
3. Simple linear classifier for Iris data, manual design

2 Program a simple linear classifier

For this task, the function was given, so we will simply give an analysis of the function.

```
1      function y = linclass(x,w)
2          % linear threshold classifier
3          % x: n x m data set to classify
4          % w: 1 x m coefficient vector of hyperplane
5          y = 2*(x*w' < 0) - 1;
6      end
```

The function takes two parameters:

- a set of n data, as a $n \times d$ matrix (or possibly $d+1$), observations in rows
- a row vector w of d (or $d + 1$) coefficients

It returns a vector y of n values in $\{-1, +1\}$, each representing the classification output for the corresponding input pattern (row of the input data matrix).

We can see that we changed the initial function a little : We added a $*2 -1$ to the results, because we want this function to return the class given by the classifier w (the target set taken is $\{-1, 1\}$).

3 Simple linear classifier for 2D binary problems, manual design

3.1 Dataset1

In this exercise, we had to create a linear classifier to separate the data provided (7 two dimensions points). To do so, we used graphical method to determine an hyperplan that separate linearly the data. Here is the basic code used to charge the data and define a target vector for each dataset:

```
1 %load a file :
2 dataset1 = load('dataset1.txt');
3 dataset2 = load('dataset2.txt');
4 %we create a vector that contains the target for each dataset
5 t1=dataset1(:,3);
6 t2=dataset1(:,3);
```

The target vector is created so it is easier to access directly the target information without having to call the all dataset.

We also created a function **resultLinClass** that calculates the percentage of correctly classified points. We will use this value to estimate the classifier efficiency instead of counting the number of correctly classified points (so we can reuse the function with other datasets since it is more general than counting the points). Here is the code of this function and a short description of it :

```
1 function resultLinClass = resultLinClass(dataset, w, t)
2     %This function calculates the percentage of points correctly
3     %classified
4     %it takes three parameters :
5     %    dataset : the dataset we want to check
6     %    w       : 1 x m coefficient vector of
7     %               hyperplane used to classify
8     %    t       : the vector containing the target of
9     %               each individual
10
11     numberOfCorrectlyClassifiedPoints = sum(linclass(dataset, w)==t);
12     numberOfPoints = size(dataset, 1);
13
14     %size(A,1) for number of rows. size(A,2) for number of columns
15     resultLinClass = numberOfCorrectlyClassifiedPoints /
16         numberOfPoints;
17 end
```


To find the correct classifier, our strategy was to correct the hyperplan parameters in a way that provides a satisfying graphic linear separation. We started with $w=[1;1;1]$.

```

1 w1 = 1;
2 w2 = 1;
3 w3 = 1;
4 w = [w1 w2 w3];
5 percentageOfClassifiedPoints = resultLinClass(dataset1, w, t1);
6 disp('the percentage of classified with w = [1;1;1] points is : ');
7 disp(percentageOfClassifiedPoints);
8 %result in console :
9 %     the percentage of classified with w = [1;1;1] points is :
10 %     0.4286
11
12 %let's plot with the line to know how we should change the coefs :
13
14 figure(3);
15 plot(dataset1(t1==1,1), dataset1(t1==1,2), 'xb');
16 hold on;
17 plot(dataset1(t1==-1, 1), dataset1(t1==-1,2), 'or');
18 title('Plot of dataset1, first try to draw an hyperplan') % add figure
    title
19 % linspaceForVector = linspace(0,1,1);
20 x = linspace(0,1,10);
21 hyperplan = -w3/w2 -(w1*x)/w2;
22 plot(x, hyperplan);
23 hold off;


```

This try gave us the following figure :




We can see here that the hyperplan does not separate correctly the data. We change manually the hyperplan parameters to obtain a correct hyperplan.

With the parameters $w = w=[1;1;-1]$, we obtain a correct classifier. Here is the graph produced with this hyperplan :



We computed the percentage of correctly classified points with our function **resultLinClass**. The results given by the function was 100%.

During the try and retry tests to get the correct paramters for the hyperplan, we found a confusing configuration. Actually, with $w=[-1;-1;1]$, we obtain a graph that shows a line in the same position as the previous hyperplan (so correct graphical separation), but when we compute the percentage of correctly classified points, we obtain 0%. Here is the grap obtained with $w=[-1;-1;1]$.




This can be explained by the equation used to classify the points "linclass.m". Actually, if we change the ">" to "<", the problem is solved. It is in fact because of our class names. If the class had opposite names, this classifier would perfectly work.

3.2 Dataset 2

We followed the same method to find a good classifier for the second dataset. Here are the parameters we found $w=[1;1;-1.06]$. Here is the code used for this dataset :

```
1 w1dataset2 = 1;
2 w2dataset2 = 1;
3 w3dataset2 = -1.06;
4 wdataset2 = [w1dataset2 w2dataset2 w3dataset2];
5 percentageOfClassifiedPointsdataset2 = resultLinClass(dataset2 ,
    wdataset2 , t2);
6 disp('the percentage of classfyed points is : ');
7 disp(percentageOfClassifiedPointsdataset2);
8 figure(9);
9 plot(dataset2(t2==1,1),dataset2(t2==1,2),'xb');
10 hold on;
11 plot(dataset2(t2==-1, 1), dataset2(t2==-1,2),'or');
12 stringTitle = compose("Plot of dataset2 , second try.\nPercentage of
    corretly classfyed points = %.5f",
    percentageOfClassifiedPointsdataset2);
13 title(stringTitle) % add figure title
14 x = linspace(0,1,10);
15 hyperplan = -w3dataset2/w2dataset2 -(w1dataset2*x)/w2dataset2;
16 plot(x, hyperplan);
17 hold off;
```

Here is the graph displaying the hyperplan for this dataset :



3.3 Adding a random perturbation

Now we add a random perturbation to our hyperplan. You can find a detailed example and explanation of a random perturbation for only one hyperplan in the code, but here we will only describe the final result. Here is the function used to generate a growing perturbation (with 100 iteration for each value of p).

```

1 %we are going to store the percentage of correctly classfyed
2 %poitns is the following variable :
3 matrixOfErrors = zeros(100,10);
4 %we have 10 colomns, each colomns is a p value (0.1, 0.2, ..., 0.10)
5 %we have 100 lines, each p value has 100 percentage of error to
   calculate
6
7 counter = 1;
8 %we also keep a counter because we can't use p directly as an index to
9 %access the values inside the matrixOfErrors
10 disp("this is the w value we will use :");
11 disp(w);
12 wNormalized = w / norm(w);
13
14 for p = 0.01:0.01:0.1
15     for i = 0:100
16         randomVector = 2*rand(1,3) -1;
17         randomVector = randomVector / norm(randomVector);
18         randomVector = p * randomVector;
19
20         wWithPerturbation = wNormalized + randomVector;
21         percentageOfClassifiedPoints = resultLinClass(dataset1 ,
22             wWithPerturbation, t1);
23         matrixOfErrors(i+1,counter) =
24             percentageOfClassifiedPoints;
25     end
26     counter = counter + 1;
27 end

```

Explanation of the loop : the p loop represents all the perturbation percentage we want to cover, we will go from 0.01 to 0.1 with a stepsize of 0.01. The i loop indicates how many iterations should be compute for each p value. To provide more accurate curve, we used 10000 iterations to generate the following graphs. To generate the random perturbation, we followed the explanation given by the teacher. You can also find precise exlanation and example directly in the code.

Now we can represent the consequence of the perturbation on the classification.


Comment : We decided to represent the percentage of correctly classified points instead of the average number of errors because it makes more sense.

```

1 percentageErrorsAverrage = mean(matrixOfErrors);
2 %we also create a vector of p value :
3 pValuesVector = 0.01:0.01:0.10;
4 %then we just have to plot the percentage average VS
   the p values :
5 figure(11);
6 plot(pValuesVector, percentageErrorsAverrage);
7 hold on;
8 title('Classification Error Average VS perturbation
9       size p, \ndataset 1'); % add figure title
10 hold off;


```

Here are the two graph for each datasets.As said before, the average percentage of classified points has been computed using 10000 iteration to get a more accurate graph.



3.3.1 Analyse of the results

We print the two curves on the same graph to make a comparison :



We can see in this graph that the perturbations have stronger effects on the second dataset classification than the first. This is due to the data contained in each data set. Actually, we can see that for the second dataset, the two class points are really closer to the hyperplan than they are in the first dataset. One consequence of this difference, is that the second hyperplan is more sensitive to parameters changes where the first can handle higher perturbations. This problem can also appear on real data since we can not control how close two classes are.


4 Simple linear classifier for Iris data, manual design

For this last task, we used the tools and methods learned before in this lab. We had to implement a linear classifier for a bigger dataset (iris dataset).

The first thing we did was to load the data and plot it so we can get an idea of what it look like.

```
1 datasetEx2 = load('datasetEx2.txt');
2 t=datasetEx2(:,3);
3 figure(1);
4 plot(datasetEx2(t==1,1),datasetEx2(t==1,2),'xb');
5 hold on;
6 plot(datasetEx2(t== -1, 1), datasetEx2(t== -1,2),'or');
7 title('Plot of dataset1') % add figure title
8 hold off;
```

Here is the figure obtained :




We used the same methods as the previous exercise to find a correct hyperplan. Here is the code generating the graph :

```

1 w1 = -0.1;
2 w2 = 1;
3 w3 = -1;
4 w = [w1 w2 w3];
5
6 percentageOfClassifiedPoints = resultLinClass(datasetEx2, w, t);
7 disp('the percentage of classified points (dataset1, correct
  classification) is : ');
8 disp(percentageOfClassifiedPoints);
9 %this is definitely better
10 figure(6);
11 plot(datasetEx2(t==1,1), datasetEx2(t==1,2), 'xb');
12 hold on;
13 plot(datasetEx2(t==-1, 1), datasetEx2(t==-1,2), 'or');
14 title(compose('Plot of dataset1, correct hyperplan & classification.\
  nPercentage of correctly classified poitns = %.5f',
  percentageOfClassifiedPoints)); % add figure title
15 % linspaceForVector = linspace(0,1,1);
16 x = linspace(0,35,3);
17 hyperplan = -w3/w2 -(w1*x)/w2;
18 plot(x, hyperplan);
19 hold off;

```

Here is the figure obtained :



We found a correct linear classifier for this problem. However, this graphical method only works when we have a two dimensions dataset. Other methods would be required when we get higher than three dimensions.