

Project 2: Price assurance?

DS 3010 Data Science III: Computational Data Intelligence

Aukkawut Ammartayakun

April 19, 2022

Worcester Polytechnic Institute

1. Introduction

2. Case study: Mobile Phone

3. Accuracy Problem


Structured vs Quasi-Continuous

n-Binary vs Dirichlet?

4. Conclusion

Introduction

Introduction



Case Study: Mobile Phone

Numerical information

- Battery power
- Talk time

Numerical information

- Battery power
- Talk time
- Clock speed?
- Front camera and primary camera pixel count?
- Internal storage and RAM?
- Mobile dimensions?

Numerical information


- Battery power
- Talk time
- Clock speed?
- Front camera and primary camera pixel count?
- Internal storage and RAM?
- Mobile dimensions?

Non-numerical information


- Connectivity (Bluetooth, 4G, etc.)
- Touchscreen

- Linear model
 - Linear Support Vector Classification (LinearSVC)
 - Logistic Regression (LR)
- Non-linear model
 - Multi-Layer Perceptrons (MLP)

LinearSVC




Accuracy=0.39




Accuracy=0.68

Logistic Regression






Accuracy = 0.84



Accuracy = 0.76

Multi-Layer Perceptrons



Accuracy Problem

Why ordinal classification instead of normal classification?

Let say we have observations

$$X_1, \dots, X_n \sim \text{Categorical}(|\mathcal{C}|, \rho)$$

with a class set $\mathcal{C} = \{c_1, c_2, \dots, c_k\}$ and probability measure ρ .

Why ordinal classification instead of normal classification?

Let say we have observations

$$X_1, \dots, X_n \sim \text{Categorical}(|\mathcal{C}|, \rho)$$

with a class set $\mathcal{C} = \{c_1, c_2, \dots, c_k\}$ and probability measure ρ .

Our classification task is to find $\hat{q} : \mathcal{X} \rightarrow \mathcal{C}$ such that their classes are **closed** to the real classes.

Why ordinal classification instead of normal classification?

Let say we have observations


$$X_1, \dots, X_n \sim \text{Categorical}(|\mathcal{C}|, \rho)$$

with a class set $\mathcal{C} = \{c_1, c_2, \dots, c_k\}$ and probability measure ρ .

Our classification task is to find $\hat{q} : \mathcal{X} \rightarrow \mathcal{C}$ such that their classes are **closed** to the real classes.


Generally, we would use categorical cross-entropy as our objective. However, what if the class set is quasi-continuous in such the way that distance measure can be used?

Why ordinal classification instead of normal classification?




In this scenario, the quasi-continuous space can be defined as discretized space. Notice that the continuity implies that the blue prediction should have less penalty to the objective function compared to orange one.

One-vs-Rest vs Multinomial?



One-VS-Rest



Multinomial

Conclusion

- How can we use the model in real world?

- How can we use the model in real world?
- Will our business works?