

# Computer Vision I

Tim Luchterhand, Paul Nykiel (Group 17)

21. Mai 2018

## 1 Filter Algebra

### 1.1

Without loss of generality choose an image  $I \in [0, 255]$  with size  $3 \times 3$ .

The maximum value for  $I_{22}$  is achieved by weighting all positive values in the filter with 255 and all negative values with 0. This results in image (1). With this image the maximum output value is  $2 \cdot 255 + 2 \cdot 255 + 1 \cdot 255 = 1275$ .

$$I_{max} = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 255 \\ 0 & 255 & 255 \end{pmatrix} \quad (1)$$

The minimum value for  $I_{22}$  is achieved by weighting all positive values in the filter with 0 and all negative values with 255. This results in image (2). With this image the maximum output value is  $-2 \cdot 255 + (-2) \cdot 255 + (-1) \cdot 255 = -1275$ .

$$I_{max} = \begin{pmatrix} 255 & 255 & 0 \\ 255 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \quad (2)$$

### 1.2

$$\begin{aligned} I &= \begin{pmatrix} 1 & 2 \end{pmatrix} \\ H &= \begin{pmatrix} 1 & -1 \end{pmatrix} \\ \alpha &= 255 \end{aligned}$$

With these values calculate the convolution (the values are continued with 0):

$$\begin{aligned}(\alpha \cdot I) * H &= (255 \ 255) * (1 \ -1) = (255 \ 0 \ 0) \\ \alpha \cdot (I * H) &= 255 \cdot (1 \ 1 \ 0) = (255 \ 255 \ 0) \\ &\Rightarrow (\alpha \cdot I) * H \neq \alpha \cdot (I * H)\end{aligned}$$

As shown by the contradiction above the linearity does not hold for clamped values.

### 1.3

Matlab Code:

```

1 I = imread("lena.tif");
2 sigma = 3;
3 G = fspecial("gaussian", 2*ceil(2*sigma)+1, sigma);
4 H = [-1 -2 0; -2 0 2; 0 2 1];
5
6 T1 = imfilter(I, G, 'replicate', 'conv');
7 R1 = imfilter(T1, H, 'replicate', 'conv');
8
9 figure();
10 subplot(1,3,1);
11 imshow(I);
12 title("Original image");
13 subplot(1,3,2);
14 imshow(T1);
15 title("Blurred Image");
16 subplot(1,3,3);
17 imshow(R1);
18 title("Diagonal edges of the blurred image");
19
20 print("lenaEdge1.eps", "-depsc");

```




Abbildung 1: Output of the Matlab script

The filter highlights strong corner in the diagonal axis (north-west to south-east) by calculating an approximation of the derivative in this direction.

```

22 T2 = imfilter(I, H, 'replicate', 'conv');
23 R2 = imfilter(T2, G, 'replicate', 'conv');
24
25 figure();
26 subplot(2,3,1);
27 imshow(I);
28 title("Original image");
29 subplot(2,3,2);
30 imshow(T1);
31 title("Blurred Image");
32 subplot(2,3,3);
33 imshow(R1);
34 title("Diagonal edges of the blurred image");
35 subplot(2,3,4);
36 imshow(abs(R2-R1));
37 title("Difference of both images");
38 subplot(2,3,5);
39 imshow(T2);
40 title("Diagonal edges of the original image");
41 subplot(2,3,6);
42 imshow(R2);
43 title("Blurred image of the diagonal edges");
44

```

```
45 print("lenaEdge2.eps", "-depsc");
```




Abbildung 2: Output of the second part of the Matlab script

## 2 Discrete Fourier Transform

## 3 Fourier Transform for Image Quality Assessment