

```
58. for(string& s: *stringValue)
59. {
60.     os << s << endl;
61. }
62. }
63.
64. int orderValue(char a)
65. {
66.     switch(a)
67.     {
68.         case '=':
69.             return 0;
70.             break;
71.         case '+':
72.         case '-':
73.             return 1;
74.             break;
75.         case '*':
76.         case '/':
77.             return 2;
78.             break;
79.         default:
80.             return -1;
81.     }
82. }
83.
84. bool precedence(char a, char b)
85. {
86.     if(a == '(')
87.     {
88.         return false;
89.     }
90.     if((b == '(') && (a != '('))
91.     {
92.         return false;
93.     }
94.     if((a != '(') && (b == '('))
95.     {
96.         return true;
97.     }
98.     if((a == '(') && (b == '('))
99.     {
100.         return false;
101.     }
102.     return orderValue(a) >= orderValue(b);
103. }
104.
105. bool isOperation(char a)
106. {
107.     return (orderValue(a) >= 0) || (a == '(') || (a == ')');
108. }
109.
110. string infixToPostfix(string s)
111. {
112.     string postfix = "";
113.     stack<char> opstk;
114.     for(char c: s)
115.     {
116.         if(c == ' ')
117.         {
118.             continue;
119.         }
```

Compiling lab2.cpp:
Source file timestamp: 2016-02-23 11:36:50
Compiled at: 2016-02-23 11:47:09

```
1. /**
2. ===== TOLSA =====
3. ===== LAB 2 =====
4. ===== Variant 16 =====
5. ===== Author: Oleg Pedorenko, IP-31 =====
6. ===== FICT, ASOIU =====
7. ===== Created on: 23.02.2016 =====
8. =====
9. */
10.
11. #include "iostream"
12. #include "fstream"
13. #include "string"
14. #include "vector"
15. #include "stack"
16.
17. using namespace std;
18.
19. void printHelp(string exeName)
20. {
21.     cout << "===== TOLSA =====\n" <<
22.     "===== LAB 2 =====\n" <<
23.     "===== Variant 16 =====\n" <<
24.     "===== Author: Oleg Pedorenko, IP-31 =====\n" <<
25.     "===== FICT, ASOIU =====\n" <<
26.     "===== Created on: 23.02.2016 =====\n" <<
27.     "===== \n";
28.     cout << endl;
29.     cout << "Pass the path to the file with a list of lines to\n" <<
30.     "analyze as a command line argument\n";
31.     cout << "Pass the name of the file where you want to direct the output as\n" <<
32.     "the second argument";
33.     cout << endl;
34.     cout << "Example:\n" << exeName << " sample.pas\n";
35.     cout << endl;
36.     cout << "Output: \nAAAABBBBCC\nThis word exists in given language\n";
37.     cout << endl;
38. }
39.
40. vector<string>* loadFile(string fileName)
41. {
42.     ifstream inputFile(fileName.c_str());
43.     if(!inputFile.good())
44.     {
45.         return NULL;
46.     }
47.     vector<string>* stringValue = new vector<string>();
48.     do
49.     {
50.         stringValue->push_back("");
51.         getline(inputFile, stringValue->back());
52.     } while (inputFile.good());
53.     return stringValue;
54. }
55.
56. void printStringVector(vector<string>* stringValue, ostream& os = cout)
57. {
```

```
182. ofstream os(argv[2]);
183. if(lines == NULL)
184. {
185.     cout << "i/o error\n";
186. }
187. else
188. {
189.     printStringVector(stringVectorInfixToPostfix(lines), os);
190. }
191. }
192. else if(argc > 3)
193. {
194.     cout << "Too many arguments";
195. }
196. }
```

196 lines: No errors

```
120. if(isOperation(c))
121. {
122.     char smbtop;
123.     while(!opstk.empty() && precedence(smbtop = opstk.top(), c))
124.     {
125.         postfix += smbtop;
126.         opstk.pop();
127.     }
128.     if((opstk.empty()) || (c != '('))
129.     {
130.         opstk.push(c);
131.     }
132.     else
133.     {
134.         smbtop = opstk.top();
135.         opstk.pop();
136.     }
137. }
138. else
139. {
140.     postfix += c;
141. }
142. }
143. while(!opstk.empty())
144. {
145.     postfix += opstk.top();
146.     opstk.pop();
147. }
148. return postfix;
149. }
150.
151. vector<string>* stringVectorInfixToPostfix(vector<string>* stringVector)
152. {
153.     vector<string>* result = new vector<string>();
154.     for(string& s: *stringVector)
155.     {
156.         result->push_back(infixToPostfix(s));
157.     }
158.     return result;
159. }
160.
161. int main(int argc, char** argv)
162. {
163.     if(argc == 1)
164.     {
165.         printHelp(argv[0]);
166.     }
167.     else if(argc == 2)
168.     {
169.         vector<string>* lines = loadFile(argv[1]);
170.         if(lines == NULL)
171.         {
172.             cout << "i/o error\n";
173.         }
174.         else
175.         {
176.             printStringVector(stringVectorInfixToPostfix(lines));
177.         }
178.     }
179.     else if (argc == 3)
180.     {
181.         vector<string>* lines = loadFile(argv[1]);
```