




deeplearning.ai

Regularizing your neural network

Dropout regularization

Dropout regularization



↑
0.5 ↑
0.5 ↑
0.5

Implementing dropout ("Inverted dropout")

Illustrate with layer $l=3$. keep-prob = 0.8 0.2

→ $d3 = \text{np.random.rand}(a3.\text{shape}[0], a3.\text{shape}[1]) < \text{keep-prob}$

$a3 = \text{np.multiply}(a3, d3)$ # $a3 \neq d3$.

→ $a3 /= \text{keep-prob}$ ←

50 units. \leadsto 10 units shut off

$$z^{[4]} = w^{[4]} \cdot a^{[3]} + b^{[4]}$$

\uparrow

\nwarrow reduced by 20%.

\nwarrow $= 0.8$

Test

Making predictions at test time

$$a^{[0]} = X$$

No drop out.

$$z^{[1]} = W^{[1]} \frac{a^{[0]}}{\quad} + b^{[1]}$$

$$a^{[1]} = g^{[1]}(z^{[1]})$$

$$z^{[2]} = W^{[2]} \frac{a^{[1]}}{\quad} + b^{[2]}$$

$$a^{[2]} = \dots$$

↓
↑
y

/= keep-prob



deeplearning.ai

Regularizing your neural network

Understanding dropout

Why does drop-out work?

Intuition: Can't rely on any one feature, so have to spread out weights. \leadsto Shrink weights. b_2

