

File Structures Lab Manual

Commands For Running In Ubuntu

- **\$sudo apt-get install libncurses5-dev libncursesw5-dev**
- Since conio is not supported in ubuntu, we use the alternative library called as curses
- First create a directory with usn as the name using the command below
- **\$mkdir usn**
- Using any editor of your choice create a c++ file using the command below
- **\$editorname filename.cpp** ex: \$gedit prog1.cpp
- editors available for typing the program
 1. Gedit (recommended)
 2. Vi
 3. Vim
 4. Nano
- Replace editorname with any one of the above mentioned editors
- After u type save the file it varies for each editor as shown below
 1. Vi to start typing press i once file is created and after u finish typing click esc and type :wq to save the file
 2. Gedit there is a direct save option click on it to save and click on close symbol to close
 3. Vim same as vi only difference is it is more user friendly than vi
 4. Nano once file is created you can directly start typing once u finish type control+x then it will ask whether to save click y and then enter file will be saved
- It is recommended to use Gedit as it the most user friendly and easy to type n save
- For executing command is same irrespective of editors
- The command for executing is
- **\$g++ filename.cpp -lcurses**
- To view the output use the command
- **\$/a.out**
- Create all the text file mentioned in the program if any before executing it

PROGRAMS

Program 1

/* Write a program to read series of name, one per line, from standard input and write these names spelled in reverse order to the standard output using I/O redirection and pipes. Repeat the exercise using an input file specified by the user instead of the standard input and using an output file specified by the user instead of the standard output */

```
#include<iostream>
#include<stdio.h>
#include<cstdlib>
#include<fstream>
#include<unistd.h>
#include<iomanip>
#include<stdlib.h>
using namespace std;
// function to reverse the string
void reverse(char *s,char *r)
{
    int j,len=0;
    while(s[len]!='\0')
        len++;
    for(j=len-1;j>=0;j--)
        r[len-j-1]=s[j];
    r[len]='\0';
}
// to calculate the length of string
// main program
int main()
{
    char name[10][20],rev[10][20],input[20],output[20],str[20],rstr[20];
    int i,n,len;
    fstream ifile,ofile;
    curscr;
    cout<<"enter the number of names to read "<<endl;
    cin>>n;
    cout<<"enter the names"<<endl;
    for(i=0;i<n;i++)
    {
        scanf("%s",name[i]);
    }
    for(i=0;i<n;i++)
    {
        reverse(name[i],rev[i]);
    }
    cout<<"the names and its reverse order are"<<endl;
    for(i=0;i<n;i++)
        cout<<name[i]<<setw(25)<<rev[i]<<endl;
    cout<<"enter the filename which contain list of names"<<endl;
    cin>>input;
    ifile.open(input,ios::in);
    if(!ifile)
    {
        cout<<"file doesnot exist";
        getch();
        exit(1);
    }
}
```

```
}
cout<<"enter the filename to store names in reverse order"<<endl;
cin>>output;
ofile.open(output,ios::out);
if(!ofile)
{
cout<<"file doesnot exit";
getch();
exit(1);
}
while(!ifile.eof())
{
ifile.getline(str,20,'\n');
reverse(str,rstr);
ofile<<rstr<<endl;
}
getch();
return 0;
}
```

Output

Output 1:

enter the number of names to read

3

enter the names

michael j folk

bill zoellick

greg riccardi

the names and its reverse order are

michael j folk klofj leahcim

bill zoellick kcilleozllib

greg riccardi idracirgerg

enter the filename which contain list of names

abc.dat

enter the filename to store reverse the names

xyz.dat

c:\tc> type abc.dat

ma noj kumar

praveen kollegal

vikarmanarayana

sathish madappa

neminchand

yadhu nandan

c:\tc> type xyz.dat

ramukjona m

laxlok neevarp

narayan marakiv

appa damhshtas

dhanhimen

nandanhday

Output 2:

enter the number of names to read

2

enter the names

narayan poojari

s hiva ra j
the nam es and its re ver es e or de r ar e
na ga ra j pooja ri irajoop ja ra ga n
s hiva ra j ja ra vihs
e nte r the f ile name w hic h c ontain lis t of nam e s
pqr.txt
fil e does not exis t
Outp ut 3: us ing I/O r e dire c tion and pipe s (R un the progra m in C omma nd prompt)
I/O re dire c tion : R e dir ec t the oup ut f r om st d out to a f ile aaa.txt
Syntax : pr ogr am 1 >f ile name
N OT E : go to c om m and pr om pt
F ile - D OS She ll
C :\tc> progra m na me > any.t xt file
E x: c:\tc> prog1>a a.txt
c :\tc > pr og1 > aaa.txt
1
rns it college
zz z.txt
c :\tc > type aaa.txt
enter the number of na mes to rea d
enter the na mes
the na mes and its rever es e ord er a re
rns it college egelloc tis nr
enter the filena me w h ich c onta in lis t of na mes
P ipes : take any st d o ut outp ut f r om pr ogr am 1 and us e it in plac e of any st di n inp ut
to pr ogr am 2.
Syntax : pr ogr am 1 | pr ogr am 2
c :\tc > type xyz.dat | s or t
a ppa da m hs ihtas
dna hc imen
la gellok nee va rp
na dnan uhda y
na ya ra n ma ra kiv
ra muk jona m

Program 2

/* Write a program to read and write student objects with fixed length records and the fields delimited by "|". Implement pack () and unpack (), modify() and search() methods */

```
#include<iostream>
#include<fstream>
#include<urses.h>
#include<stdio.h>
#include<iomanip>
#include<stdlib.h>
#include<string.h>
using namespace std;
```

```
#define filename "std2.txt"
fstream ifile;
class student
{
char usn[15],name[20],age[5],branch[6],sem[5];
public:
void opener(fstream& ifile,char *fn,ios_base::openmode mode);
void read();
void pack();
void display();
void unpack();
int search();
void modify(int);
};
// function to open a file
void student::opener(fstream& sfile,char *fn,ios_base::openmode mode)
{
sfile.open(fn,mode);
if(!sfile)
{
cout<<"unable to open a file"<<endl;
getch();
exit(1);
}
}
//function to read the student record
void student::read()
{
cout<<"enter the usn number:";
scanf("%s",usn);
cout<<"enter the name:";
scanf("%s",name);
cout<<"enter the age:";
scanf("%s",age);
cout<<"enter the branch:";
scanf("%s",branch);
cout<<"enter the sem:";
scanf("%s",sem);
pack();
}
// function to pack the student record using delimiter
void student::pack()
{
char buffer[75];
strcpy(buffer,usn);
strcat(buffer,"|");
strcat(buffer,name);
strcat(buffer,"|");
strcat(buffer,age);
strcat(buffer,"|");
strcat(buffer,branch);
strcat(buffer,"|");
strcat(buffer,sem);
strcat(buffer,"|");
}
```

```
ifile.fill('*');
ifile<<setiosflags(ios::left)<<setw(sizeof(student))<<buffer<<endl;
}
//function to display student record
void student::display()
{
char buffer[75];
cout<<setiosflags(ios::left);
cout<<setw(15)<<"USN"<<setw(20)<<"NAME"<<setw(5)<<"AGE";
cout<<setw(10)<<"BRANCH"<<setw(5)<<"SEM"<<endl;
while(1)
{
unpack();
if(ifile.eof())
break;
if(usn[0]!='$')
{
cout<<setw(15)<<usn<<setw(20)<<name<<setw(5)<<age;
cout<<setw(10)<<branch<<setw(5)<<sem<<endl;
}
}
}
// function to unpack
void student::unpack()
{
char dummy[75];
ifile.getline(usn,15,'|');
ifile.getline(name,20,'|');
ifile.getline(age,5,'|');
ifile.getline(branch,6,'|');
ifile.getline(sem,5,'|');
ifile.getline(dummy,75,'\n');
}
//function to search student record based on USN.
int student::search()
{
int flag;
char susn[15];
cout<<"enter the usn to be searched:";
cin>>susn;
while(!ifile.eof())
{
flag=ifile.tellg();
unpack();
if(usn[0]!='$' &&strcmp(usn,susn)==0)
{
cout<<"USN:"<<usn<<"\n"<<"NAME:"<<name<<"\n"<<"AGE:"<<age;
cout<<"\n"<<"BRANCH:"<<branch<<"\n"<<"SEM:"<<sem<<"\n";
return flag;
}
}
return -1;
}
//function to modify record.
```

```
void student::modify(int recpos)
{
    ifile.seekp(recpos,ios::beg);
    ifile.put('$');
    ifile.seekp(0,ios::end);
    read();
}
//main program
int main()
{
    int ch,flag;
    student s;
    curscr;
    for(;;)
    {
        cout<<endl<<"1.- read\t2- display\t3 .-search\t4.- modify\t5.- exit"<<endl;
        cout<<"enter the choice:";
        cin>>ch;
        switch(ch)
        {
            case 1: s.opener(ifile,filename,ios::app);
                cout<<"enter the student details\n";
                s.read();
                break;
            case 2: s.opener(ifile,filename,ios::in);
                cout<<"The student details are:"<<endl;
                s.display();
                break;
            case 3:s.opener(ifile,filename,ios::in);
                cout<<"Searching based on USN number"<<endl;
                flag=s.search();
                if(flag== -1)
                    cout<<"Record not found"<<endl;
                break;
            case 4: s.opener(ifile,filename,ios::in | ios::out);
                cout<<"To modify the record based on USN"<<endl;
                flag=s.search();
                if(flag== -1)
                    cout<<"Record not found"<<endl;
                else
                    s.modify(flag);
                break;
            default:
                exit(0);
                return 0;
        }
        ifile.close();
    }
}
```

Output :

```
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:1
enter the student details
enter the usn number:100
```

```
enter the name:ajay
enter the age:30
enter the branch:ise
enter the sem:5
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:1
enter the student details
enter the usn number:200
enter the name:suresh
enter the age:21
enter the branch:cse
enter the sem:6
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:1
enter the student details
enter the usn number:300
enter the name:shashi
enter the age:20
enter the branch:me
enter the sem:2
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:2
The student details are:
USN NAME AGE BRANCH SEM
100 ajay 30 ise 5
200 suresh 21 cse 6
300 shashi 20 me 2
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:3
Searching based on USN number
enter the usn to be searched:200
USN:200
NAME:suresh
AGE:21
BRANCH:cse
SEM:6
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:3
Searching based on USN number
enter the usn to be searched:125
Record not found
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:4
To modify the record based on USN
enter the usn to be searched:300
USN:300
NAME:shashi
AGE:20
BRANCH:me
SEM:2
enter the usn number:450
enter the name:yadhu
enter the age:18
enter the branch:ece
```



```
enter the sem:2
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:2
The student details are:
USN NAME AGE BRANCH SEM
100 ajay 30 ise 5
200 suresh 21 cse 6
450 yadhu 18 ece 2
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:5
c :\tc \s td2.txt
100|ajay|30|ise|5|*****
200|suresh|21|cse|6|*****
450|yadhu|18|ece|2|*****
```

Program 3

/* Write a program to read and write student objects with variable -Length records using any suitable record structures. Implement pack (), unpack (), modify () and search () methods. */

```
#include<iostream>
#include<fstream>
#include<cstring>
#include<stdio.h>
#include<iomanip>
#include<stdlib.h>
#include<string.h>
using namespace std;
#define filename "std3.txt"
fstream ifile;
class student
{
char usn[15],name[20],age[5],branch[6],sem[5];
public:
void opener(fstream& ifile,char *fn,ios_base::openmode mode) ;
void read();
void pack();
void display();
void unpack();
int search();
void modify(int);
};
//function to open a file
void student::opener(fstream& sfile,char *fn,ios_base::openmode mode)
{
sfile.open(fn,mode);
if(!sfile)
{
cout<<"unable to open a file"<<endl;
getch();
}
```

```
exit(1);
}
}
//function to read the student record
void student::read()
{
cout<<"enter the usn number :";
scanf("%s",usn);
cout<<"enter the name:";
scanf("%s",name);
cout<<"enter the age:";
scanf("%s",age);
cout<<"enter the branch";
scanf("%s",branch);
cout<<"enter the sem";
scanf("%s",sem);
pack();
}
//function to pack the student record using delimiter
void student::pack()
{
char buffer [75];
strcpy(buffer,usn);
strcat(buffer,"|");
strcat(buffer,name);
strcat(buffer,"|");
strcat(buffer,age);
strcat(buffer,"|");
strcat(buffer,branch);
strcat(buffer,"|");
strcat(buffer,sem);
strcat(buffer,"|");
ifile<<buffer<<"#";
}
//function to display student record
void student::display()
{
char buffer[75];
cout<<setiosflags(ios::left);
cout<<setw(15)<<"USN"<<setw(20)<<"NAME"<<setw(5)<<"AGE";
cout<<setw(10)<<"BRANCH"<<setw(5)<<"SEM"<<endl;
while(1)
{
unpack();
if(ifile.eof())
break;
if(usn[0]!='$')
{
cout<<setw(15)<<usn<<setw(20)<<name<<setw(5)<<age;
cout<<setw(10)<<branch<<setw(5)<<sem<<endl;
}
}
}
//function to unpack
```

```
void student::unpack()
{
char dummy[75];
ifile.getline(usn,15,'|');
ifile.getline(name,20,'|');
ifile.getline(age,5,'|');
ifile.getline(branch,6,'|');
ifile.getline(sem,5,'|');
ifile.getline(dummy,10,'#');
}
//function to search student record based on USN.
int student::search()
{
int flag ;
char susn[15];
cout<<"enter the usn to be searched :";
cin>>susn;
while(!ifile.eof())
{
flag = ifile.tellg();
unpack();
if(usn[0]!='$'&&strcmp(usn,susn)==0)
{
cout<<"USN:"<<usn<<"\n"<<"NAME:"<<name<<"\n"<<"AGE:"<<age;
cout<<"\n"<<"BRANCH:"<<branch<<"\n"<<"SEM : "<<sem<<"\n";
return flag;
}
}
return-1;
}
//function to modify record .
void student::modify(int recpos)
{
ifile.seekp(recpos ,ios ::beg);
ifile.put("$");
ifile.seekp(0,ios::end);
read();
}
//main program
int main()
{
int ch,flag;
student s;
curscr;
for(;;)
{
cout<<endl<<"1 .-read \t2 .-display\t3 .-search\t4 .- modify\t5 .-exit"<<endl;
cout<<"enter the choice:";
cin>>ch;
switch(ch)
{
case 1 : s.opener(ifile,filename,ios::app);
cout<<"enter the student details \n";
s.read();
```

```
break;
case 2 :s.opener(ifile,filename,ios::in);
cout<<"The student details are : "<<endl;
s.display();
break;
case 3 :s.opener(ifile,filename,ios::in) ;
cout<<"Searching based on USN number"<<endl;
flag =s .search();
if(flag== -1)
cout<<"Record not found "<<endl;
break;
case 4 :s.opener(ifile,filename,ios ::in|ios::out);
cout<<"To modify the record based on USN " <<endl;
flag = s.search();
if(flag== -1)
cout<<"Record not found"<<endl;
else
s.modify(flag);
break;
default:
exit(0);
}
ifile.close();
}
return 0;
}
```

Output

1.- read 2- display 3 .-search 4.- modify 5.- exit

enter the choice:1

enter the student details

enter the usn number:100

enter the name: amar

enter the age:20

enter the branch: ise

enter the sem:6

1.- read 2- display 3 .-search 4.- modify 5.- exit

enter the choice:1

enter the student details

enter the usn number:200

enter the name:chethan

enter the age:21

enter the branch:cse

enter the sem:7

1.- read 2- display 3 .-search 4.- modify 5.- exit

enter the choice:1

enter the student details

enter the usn number:300

enter the name:guru

enter the age:22

enter the branch:8

enter the sem:ece

1.- read 2- display 3 .-search 4.- modify 5.- exit

enter the choice:8

1.- read 2- display 3 .-search 4.- modify 5.- exit

```
enter the choice:1
enter the student details
enter the usn number:400
enter the name:krishna
enter the age:23
enter the branch:eee
enter the sem:6
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:5
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:2
The student details are:
USN NAME AGE BRANCH SEM
100 amar 20 ise 6
200 chethan 21 cse 7
300 guru 22 ece 8
400 krishna 23 eee 6
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:3
Searching based on USN number
enter the usn to be searched:250
Record not found
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:3
Searching based on USN number
enter the usn to be searched:200
USN:200
NAME:chethan
AGE:21
BRANCH:cse
SEM:7
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:4
To modify the record based on USN
enter the usn to be searched:300
USN:300
NAME:guru
AGE:22
BRANCH:8
SEM:ece
enter the usnnumber:guruprasad
enter the name:20
enter the age:ece
enter the branch:7
enter the sem:2
1.- read 2- display 3 .-search 4.- modify 5.- exit
enter the choice:2
The student details are:
USN NAME AGE BRANCH SEM
100 amar 20 ise 6
200 chethan 21 cse 7
300 guruprasad 20 ece 7
400 krishna 23 eee 6
1.- read 2- display 3 .-search 4.- modify 5.- exit
```

enter the choice:5

c:\tc\std3.txt

100|amar|20|ise|6|#200|chethan|21|cse|7|#guruprasad|20|ece|7|2|#400|krishna|23|eee|6|#

Program 4

/* Write a program to write student objects with Variable – Length records using any suitable record structure and to read from this file a student record using RRN. */

```
#include<iostream>
#include<fstream>
#include<curses.h>
#include<stdio.h>
#include<iomanip>
#include<stdlib.h>
#include<string.h>
using namespace std;
#define filename "std4.txt"
fstream ifile;
class student
{
    char usn[15],name[20],age[5],branch[6],sem[5];
public:
    void opener(fstream &ifile, char *fn , ios_base::openmode mode);
    void read();
    void pack();
    void display();
    void unpack();
    int search();
};
void student::opener(fstream &sfile, char *fn , ios_base::openmode mode)
{
    sfile.open(fn,mode);
    if(!sfile)
    {
        cout<<"unable to open a file"<<endl;
        getch();
        exit(1);
    }
}
//function to read the student record
void student::read()
{
    cout<<"enter the usn number:";
    scanf("%s",usn);
    cout<<"enter the name:";
    scanf("%s",name);
    cout<<"enter the age:";
    scanf("%s",age);
    cout<<"enter the branch:";
    scanf("%s",branch);
}
```

```
cout<<"enter the sem:";
scanf("%s",sem);
pack();
}
// function to pack the student record using delimiter
void student::pack()
{
char buffer[75];
strcpy(buffer,usn);
strcat(buffer,"|");
strcat(buffer,name);
strcat(buffer,"|");
strcat(buffer,age);
strcat(buffer,"|");
strcat(buffer,branch);
strcat(buffer,"|");
strcat(buffer,sem);
strcat(buffer,"|");
ifile<<buffer<<"#";
}
//function to display student record
void student::display()
{
int count=0;
cout<<setiosflags(ios::left);
cout<<setw(5)<<"RRN"<<setw(15)<<"USN"<<setw(20)<<"NAME"<<setw(5);
cout<<"AGE"<<setw(10)<<"BRANCH"<<setw(5)<<"SEM"<<endl;
while(1)
{
ifile.getline(usn,15,"|");
if(ifile.eof())
break;
unpack();
count++;
cout<<setw(5)<<count<<setw(15)<<usn<<setw(20)<<name<<setw(5)<<age;
cout<<setw(10)<<branch<<setw(5)<<sem<<endl;
}
}
// function to unpack
void student::unpack()
{
char dummy[75];
ifile.getline(name,20,"|");
ifile.getline(age,5,"|");
ifile.getline(branch,6,"|");
ifile.getline(sem,5,"|");
ifile.getline(dummy,75,'#');
}
//function to search student record based on rrn.
int student::search()
{
int rrn,count=0;
char dummy[75];
cout<<"enter the rrn to be searched:";
```

```
cin>>rrn;
cout<<"RRN:"<<rrn;
while(1)
{
ifile.getline(usn,15,'|');
if(ifile.eof())
break;
count++;
if(rrn==count)
{
cout<<"\nRecord found\n";
unpack();
cout<<"USN:"<<usn<<"\n"<<"NAME:"<<name<<"\n"<<"AGE:"<<age;
cout<<"\n"<<"BRANCH:"<<branch<<"\n"<<"SEM:"<<sem<<"\n";
return 1;
}
else
ifile.getline(dummy,100,'#');
}
return -1;
}
// MAIN PROGRAM
int main()
{
int ch,pos;
student s;
curser;
for(;;)
{
cout<<endl<<"1.for read\t2.for display\t3.for search\t4.for exit\n";
cout<<"Enter the choice:";
cin>>ch;
switch(ch)
{
case 1: s.opener(ifile,filename,ios::app);
cout<<"enter the student details\n";
s.read();
break;
case 2: s.opener(ifile,filename,ios::in);
cout<<"The student details are:"<<endl;
s.display();
break;
case 3:s.opener(ifile,filename,ios::in);
cout<<"To search record based on Relative record number(RRN) \n";
pos=s.search();
if(pos== -1)
cout<<"\nRRN number is out of range-Record not found\n";
break;
default:exit(0);
}
ifile.close();
}
return 0;
}
```


Output:

```
1.for read 2.for display 3.for search 4.for exit
Enter the choice:1
enter the student details
enter the usn number:100
enter the name:adi
enter the age:21
enter the branch:ise
enter the sem:5
1.for read 2.for display 3.for search 4.for exit
Enter the choice:1
enter the student details
enter the usn number:200
enter the name:arya
enter the age:20
enter the branch:cse
enter the sem:6
1.for read 2.for display 3.for search 4.for exit
Enter the choice:1
enter the student details
enter the usn number:300
enter the name:harsha
enter the age:19
enter the branch:me
enter the sem:6
1.for read 2.for display 3.for search 4.for exit
Enter the choice:2
The student details are:
RRN USN NAME AGE BRANCH SEM
1 100 adi 21 ise 5
2 200 arya 20 cse 6
3 300 harsha 19 me 6
1.for read 2.for display 3.for search 4.for exit
Enter the choice:3
To search record based on Relative record number(RRN)
enter the rrn to be searched:RRN:2
Record found
USN:200
NAME:arya
AGE:20
BRANCH:cse
SEM:6
1.for read 2.for display 3.for search 4.for exit
Enter the choice:3
To search record based on Relative record number(RRN)
enter the rrn to be searched:RRN:50
RRN number is out of range-Record not found
1.for read 2.for display 3.for search 4.for exit
Enter the choice:4
C:\tc\std4.txt
100|adi|21|ise|5|#200|arya|20|cse|6|#300|harsha|19|me|6|
```

Program 5

/* Write a program to implement simple index on primary key for a file of student objects. Implement add (), search (), delete () using the index. */

```
#include<iostream>
#include<fstream>
#include<unistd.h>
#include<stdio.h>
#include<iomanip>
#include<stdlib.h>
#include<string.h>
using namespace std;
#define max 10
#define datafile "student5.txt"
#define indexfile "index5.txt"
fstream stdfile, indfile;
int i, indsize;
char buffer[80];
class Student
{
char duns[15], name[20], age[5], branch[5], sem[5];
public:
void read();
void pack();
friend int search(char*);
void recDisp(int);
void remove(int);
void dataDisp();
void unpack();
};
class index
{
public:
char iuns[15], addr[5];
void initial();
void write();
}in, id[max];
void index::initial()
{
indfile.open(indexfile, ios::in);
if(!indfile)
{
indsize=0;
return;
}
for(indsize=0; indsize++)
{
indfile.getline(id[indsize].iuns, 15, '|');
indfile.getline(id[indsize].addr, 5, '\n');
```

```
if(indfile.eof())
break;
}
indfile.close();
}
// function to open file
void opener(fstream &sfile,char* fn,ios_base::openmode mode)
{
sfile.open(fn,mode);
if(!sfile)
{
cout<<"Unable to open the file\n";
exit(1);
}
}
// function to write
void index::write()
{
opener(indfile,indexfile,ios::out);
for(i=0;i<indsize;i++)
indfile<<id[i].iusn<<"|"<<id[i].addr<<"\n";
indfile.close();
}
int search(char* fusr)
{
int low=0,high=indsize-1;
int mid;
while(low<=high)
{
mid=(low+high)/2;
if(strcmp(fusr,id[mid].iusn)==0)
return mid;
else if(strcmp(fusr,id[mid].iusn)>0)
low=mid+1;
else
high=mid-1;
}
return -1;
}
// function to read
void Student::read()
{
cout<<"Enter the usn no.\n";
scanf("%s",dusr);
if(search(dusr)>=0)
{
cout<<"usn is already present,we can't add to index file\n";
return;
}
for(i=indsize;i>0;i--)
{
if(strcmp(dusr,id[i-1].iusn)<0)
id[i]=id[i-1];
else
```

```
break;
}
opener(stdfile,datafile,ios::app);
cout<<"Enter the Name\n";
scanf("%s",name);
cout<<"Enter the age\n";
scanf("%s",age);
cout<<"Enter the branch\n";
scanf("%s",branch);
cout<<"Enter the semester\n";
scanf("%s",sem);
pack();
stdfile.seekg(0,ios::end);
int k=stdfile.tellg();
stdfile<<buffer<<endl;
strcpy(id[i].iusn,dusn);
sprintf(id[i].addr,"%d",k);
indsize++;
}
// function to pack
void Student::pack()
{
strcpy(buffer,dusn); strcat(buffer,"|");
strcat(buffer,name); strcat(buffer,"|");
strcat(buffer,age); strcat(buffer,"|");
strcat(buffer,branch); strcat(buffer,"|");
strcat(buffer,sem); strcat(buffer,"|");
}
// function to record display
void Student::recDisp(int pos)
{
opener(stdfile,datafile,ios::in);
stdfile.seekg(atoi(id[pos].addr),ios::beg);
cout<<"The searched record details are:\n";
cout<<setw(16)<<"USN"<<setw(16)<<"Name"<<setw(16)<<"Age"<<setw(16)
<<"Branch"<<setw(16)<<"Sem"<<endl;
unpack();
}
// function to Remove
void Student::remove(int pos)
{
opener(stdfile,datafile,ios::in|ios::out);
stdfile.seekg(atoi(id[pos].addr),ios::beg);
stdfile.put('$');
for(i=pos;i<indsize;i++)
id[i]=id[i+1];
indsize--;
}
// function to data display
void Student::dataDisp()
{
cout<<setiosflags(ios::left);
cout<<setw(16)<<"USN"<<setw(16)<<"Name"<<setw(16)<<"Age" \
<<setw(16)<<"Branch"<<setw(16)<<"Sem"<<endl;
```

```
while(1)
{
unpack();
if(stdfile.eof())
break;
}
}
// function to unpack
void Student::unpack()
{
stdfile.getline(buffer,100,'\n');
i=0;
if(buffer[i]!='$')
{
cout<<"\n";
while(buffer[i]!='\0')
{
if(buffer[i]=='\t')
cout<<"\t\t";
else
cout<<buffer[i];
i++;
}
}
}
int main()
{
int ch,pos,flag;
char susn[15];
Student S;
in.initial();
curscr;
for(;;)
{
cout<<endl<<"1.Read\n2.Display\n3.Search\n4.Delete\n5.exit\n";
cin>>ch;
switch(ch)
{
case 1: cout<<"Enter student details\n";
S.read();
in.write();
break;
case 2: opener(stdfile,datafile,ios::in);
cout<<endl<<"Student Details\n";
S.dataDisp();
cout<<endl<<"Index file details are:\n";
cout<<setw(10)<<"USN"<<setw(10)<<"Address";
for(i=0;i<indsize;i++)
{
cout<<endl<<setw(10)<<id[i].iusn<<setw(10)<<id[i].addr<<endl;
}
break;
case 3: cout<<"Enter the USN to be searched\n";
cin>>susn;
```

```
flag=search(susn);
if(flag==-1)
cout<<"Record Not found\n";
else
S.recDisp(flag);
break;
case 4: cout<<"Enter the usn no to delete from the record\n";
cin>>susn;
pos=search(susn);
if(pos==-1)
cout<<"Usn No. not found\n";
else
{
S.remove(pos);
in.write();
}
break;
default: exit(0);
}
stdfile.close();
}
return 0;
}
```

Output :

1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit

1

enter student details :

enter the usn number= 101

enter the name= manoj kumar

enter the age= 25

enter the branch= ise

enter the semester= 6

1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit

2

the student details are

usn name age branch sem

101 manoj kumar 25 ise 6

the index file details are

usn address

101 0

1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit

1

enter student details :

enter the usn number= cs 201

enter the name= vikram narayan

enter the age= 35

enter the branch= cse

enter the semester= 8

1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit

2

the student details are

usn name age branch sem

101 manoj kumar 25 ise 6

cs 201 vikram narayan 35 cse 8

```
the index file details are
us n address
cs 201 29
is 101 0
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
1
enter student details :
enter the us n number= me301
enter the name= pra deep
enter the age= 24
enter the branch= mec
enter the semester= 7
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
1
enter student details :
enter the us n number= ee401
enter the name= shruthi
enter the age= 20
enter the branch= eee
enter the semester= 6
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
1
enter student details :
enter the us n number= it501
enter the name= sunitha
enter the age= 21
enter the branch= it
enter the semester= 6
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
2
the student details are
us n name age branch sem
is 101 manoj kumar 25 is ee 6
cs 201 vikram narayan 35 cs ee 8
me301 pra deep 24 mec 7
ee401 shruthi 20 eee 6
it501 sunitha 21 it 6
the index file details are
us n address
cs 201 29
ee401 86
is 101 0
it501 111
me301 61
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
3
enter us n number to search : me301
us n = me301
name = pra deep
age = 24
branch = mec
sem = 7
1 for read, 2 for display, 3 for search, 4 for delete, 5 for exit
3
```

```
enter us n number to s ea rch : ec250
us n number rec ord not found for s ea rch
1 for rea d, 2 for dis pla y, 3 for s ea rch, 4 for delet e, 5 for e xit
4
enter us n number to delete the r ec ord : me301
1 for rea d, 2 for dis pla y, 3 for s ea rch, 4 for delet e, 5 for e xit
2
the s tudent deta ils a re
us n na me a ge bra nch s em
is 101 ma noj kuma r 25 is e 6
cs 201 vikra m na ra ya n 35 cs e 8
ee401 s hruthi 20 eee 6
it501 sunitha 21 it 6
the index file deta ils a re
us n a ddress
cs 201 29
ee401 86
is 101 0
it501 111
1 for rea d, 2 for dis pla y, 3 for s ea rch , 4 for delet e, 5 for e xit
4
enter us n number to delete the r ec ord : c v105
us n number not found to delet e
1 for rea d, 2 for dis pla y, 3 for s ea rch, 4 for delet e, 5 for e xit
5
C :\tc\typ es td5.txt
is 101|ma noj kuma r|25|is e|6|
cs 201|vikra m na ra ya n|35|cs e|8|
$e301|pra deep|24|mec|7|
ee401|s hruthi|20|eee|6|
it501|s unitha |21|it|6|
c:\tc\t yoe index5.t xt
cs 201|29
ee401|86
is 101|0
it501|111
```

Program 6

/* Write a program to implement index on secondary key, the name, for a file of student objects. Implement add(), search(), delete () using the secondary index. */

```
#include<fstream>
#include<iostream>
#include<curses.h>
#include<stdio.h>
#include<iomanip>
#include<stdlib.h>
#include<string.h>
using namespace std;
```



```
#define datafile "stud6.txt"
#define indexfile "pri6.txt"
#define sindexfile "sec6.txt"
fstream dfile,ifile,sifile;
int i,indsize,sindsize;
char buffer[100],skey[20];
//function to open
void opener(fstream &file, char *fn,ios_base::openmode mode)
{
file.open(fn,mode);
if(!file)
{
cout<<"unable to open a file";
getch();
exit(1);
}
}
class student
{
char dusn[15],name[20],age[5],branch[6],sem[5];
public:
void read();
void pack();
friend int search(char *);
void remove();
void datadisp();
void unpack();
}s;
class index
{
public:
char iusn[15],addr[5];
void initial();
void write();
}id[50],in;
class sindex
{
public:
char sname[20],susn[15];
void sinitial();
void swrite();
}sid[50],sin;
// function to copy index file to array structure
void index::initial()
{
ifile.open(indexfile,ios::in);
if(!ifile)
{
indsize=0;
return;
}
for(indsize=0;;indsize++)
{
ifile.getline(id[indsize].iusn,15,"");
```

```
ifile.getline(id[indsize].addr,5,'\n');
if(ifile.eof())
break;
}
ifile.close();
}
//function to copy sindex file to array structure
void sindex::sinitail()
{
sifile.open(sindexfile,ios::in);
if(!sifile)
{
sindsize=0;
return;
}
for(sindsize=0;;sindsize++)
{
sifile.getline(sid[sindsize].sname,20,'|');
sifile.getline(sid[sindsize].susn,15,'\n');
if(sifile.eof())
break;
}
sifile.close();
}
// function to update the index file
void index::write()
{
opener(ifile,indexfile,ios::out);
for(i=0;i<indsize;i++)
ifile<<id[i].iusn<<"|"<<id[i].addr<<"\n";
}
//function to upadate the secondary file
void sindex::swrite()
{
opener(sifile,sindexfile,ios::out);
for(i=0;i<sindsize;i++)
sifile<<sid[i].sname<<"|"<<sid[i].susn<<"\n";
}
//function to search based on usn number
int search(char * fusn)
{
{
int low=0,high=indsize-1,mid;
while(low <=high)
{
mid = (low+high)/2;
if(strcmp(fusn,id[mid].iusn)==0)
return mid;
if(strcmp(fusn,id[mid].iusn)>0)
low=mid+1;
else
high=mid-1;
}
return -1;
}
```

```
// function to read the student record
void student::read()
{
    int k;
    cout<<"enter the usn number="; scanf("%s",dusn);
    if(search(dusn)>=0)
    {
        cout<<"usn is already present we can't add to index file\n";
        return;
    }
    for(i=indsize;i>0;i--)
    {
        if(strcmp(dusn,id[i-1].iusn)<0)
            id[i]=id[i-1];
        else
            break;
    }
    opener(dfile,datafile,ios::app);
    cout<<"enter the name=";
    scanf("%s",name);
    cout<<"enter the age=";
    scanf("%s",age);
    cout<<"enter the branch="; scanf("%s",branch);
    cout<<"enter the semester=";
    scanf("%s",sem);
    pack();
    dfile.seekg(0,ios::end);
    k=dfile.tellg();
    dfile<<buffer<<"\n";
    strcpy(id[i].iusn,dusn);
    sprintf(id[i].addr,"%d",k);
    indsize++;
    for(i=sindsize;i>0;i--)
    {
        if(strcmp(name,sid[i-1].sname)<0)
            sid[i]=sid[i-1];
        else if((strcmp(name,sid[i-1].sname)==0) && (strcmp(dusn,sid[i-1].susn)<0))
            sid[i]=sid[i-1];
        else
            break;
    }
    strcpy(sid[i].sname,name);
    strcpy(sid[i].susn,dusn);
    sindsize++;
}
//function to pack
void student::pack()
{
    strcpy(buffer,dusn);
    strcat(buffer,"|");
    strcat(buffer,name);
    strcat(buffer,"|");
    strcat(buffer,age);
    strcat(buffer,"|");
}
```

```
strcat(buffer,branch);
strcat(buffer,"|");
strcat(buffer,sem);
strcat(buffer,"|");
} //function to search based on usn number
//function to search based on secondary key
int sec_search()
{
int pos,j,flag=-1;
cout<<"\nenter the name to search(sec key):";
scanf("%s",skey);
cout<<"the searched record details are : "<<endl;
cout<<setiosflags(ios::left);
cout<<"usn"<<"\t\tname"<<endl;
opener(dfile,datafile,ios::in|ios::out);
for(j=0;j<sindsize;j++)
if(strcmp(skey,sid[j].sname)==0)
{
cout<<sid[j].susn<<"\t\t"<<sid[j].sname<<endl;
flag=j;
}
return flag;
}
// function to remove the record
void student::remove()
{
char rusn[10];
int pos,spos;
cout<<"enter the usn number above listed to delete:";
cin>>rusn;
for(i=0;i<sindsize;i++)
{
if(strcmp(sid[i].susn,rusn)==0)
{
spos=i;
break;
}
}
if(strcmp(sid[spos].sname,skey)==0)
{
pos=search(rusn);
dfile.seekp(atoi(id[pos].addr),ios::beg);
dfile.put("$");
for(i=pos;i<indsize;i++)
id[i]=id[i+1];
indsize--;
for(i=spos;i<sindsize;i++)
sid[i]=sid[i+1];
sindsize--;
}
else
cout<<"usn number and name doesnot match";
}
//function to display the datafile
```

```
void student::datadispatch()
{
    cout<<setiosflags(ios::left);
    cout<<setw(16)<<"usn"<<setw(16)<<"name"<<setw(16)<<"age"<<setw(16);
    cout<<"branch"<<setw(16)<<"sem";
    while(1)
    {
        unpack();
        if(dfile.eof())
            break;
    }
    cout<<endl<<"the index file details are "<<endl;
    cout<<setw(10)<<"usn"<<setw(10)<<"address";
    for(i=0;i<indsize;i++)
        cout<<endl<<setw(10)<<id[i].iusn<<setw(10)<<id[i].addr;
    cout<<endl<<"\n the secondary file details are " <<endl;
    cout<<setw(20)<<"name"<<setw(15)<<"primary reference";
    for(i=0;i<sindsize;i++)
        cout<<endl<<setw(20)<<sid[i].sname<<setw(15)<<sid[i].susn;
    }
    //function to unpack the data file
    void student::unpack()
    {
        dfile.getline(buffer,100,'\n');
        i=0;
        if(buffer[i]!='$')
            while(buffer[i]!='\0')
            {
                if(buffer[i]=='|')
                    cout<<"\t\t";
                else
                    cout<<buffer[i];
                i++;
            }
    }
    //main program
    int main()
    {
        int ch,flag;
        in.initial();
        sin.sinitial();
        curser;
        for(;;)
        {
            cout<<endl<<"1-read,2-display,3-search,4-delete,5-exit\n";
            cin>>ch;
            switch(ch)
            {
                case 1: cout<<endl<<"enter student details : " <<endl;
                    s.read();
                    in.write();
                    sin.swrite();
                    break;
                case 2: opener(dfile,datafile,ios::in);
                    cout<<"\nthe datafile,indexfile and secondary file" <<endl;
```

```
s.datadisp();
break;
case 3:cout<<"To search based on sec key ";
flag=sec_search();
if(flag==1)
cout<<"no data record ";
break;
case 4: flag=sec_search();
if(flag==1)
cout<<"no data record found";
else
{
s.remove();
in.write();
sin.swrite();
}
break;
default : exit(0);
}
dfile.close();
ifile.close();
sifile.close();
}
return 0;
}
```

Output

1. read, 2. display, 3. search, 4 .delete, 5 .exit
1

enter student details :

enter the usn number= 101

enter the name= manoj kumar

enter the age= 25

enter the branch= ise

enter the semester= 6

1. read, 2. display, 3. search, 4 .delete, 5 .exit
2

the student details are

usn name age branch sem

101 manoj kumar 25 ise 6

the index file details are

usn address

101 0

1. read, 2. display, 3. search, 4 .delete, 5 .exit
1

enter student details :

enter the usn number= 201

enter the name= vikram narayan

enter the age= 35

enter the branch= cse

enter the semester= 8

1. read, 2. display, 3. search, 4 .delete, 5 .exit
2

the datafile, indexfile and secondary file

the student details are

```
us n na me a ge bra nch s em
is 101 ma noj kuma r 25 is e 6
cs 201 vikra m na ra ya n 35 cs e 8
the index file deta ils a re
us n a ddress
cs 201 29
is 101 0
the secondary file details are
name usn
is101 manoj kumar
cs101 vikram narayan
1.rea d, 2. dis pla y, 3. s ea rch, 4 .delete, 5 .exit
3
To s ea rch ba s ed on s ec ke y
Enter the na me to s ea rch (s ec ke y): vikra m na ra ya n
us n name a ge bra nch s em
cs 201 vikra m na ra ya n 35 cs e 8
1. rea d, 2. dis pla y, 3. s ea rch, 4 .delete, 5 .exit
4
Enter the na me to s ea rch (s ec ke y): vikra m na ra ya n
us n name a ge bra nch s em
cs 201 vikra m na ra ya n 35 cs e 8
enter the us n number a bove lis ted to delet e
cs 201
```

Program 7

/* Write a program to read two lists of names and then match the names in the two lists using consequential Match based on a single loop. Output the names common to both the files */

```
#include<stdio.h>
#include<iostream>
#include<curses.h>
#include<stdlib.h>
#include<fstream>
#include<string.h>
using namespace std;
//function to open a file in different mode
void opener(fstream &file, char *fn,ios_base::openmode mode)
{
file.open(fn,mode);
if(!file)
{
cout<<"unable to open the file \n ";
getch();
exit(1);
}
}
//function to match the common names from two files
void match(fstream &file1 ,fstream &file2 ,fstream &ofile)
{
```

```
char s1[25],s2[25];
file1.getline(s1,25,'\n');
file2.getline(s2,25,'\n');
while(!file1.eof() && !file2.eof())
{
if(strcmp(s1,s2)== 0)
{
ofile<<s1<<"\n";
cout<<s1<<endl;
file1.getline(s1,25,'\n');
file2.getline(s2,25,'\n');
}
else if(strcmp(s1,s2)<0)
file1.getline(s1,25,'\n');
else
file2.getline(s2,25,'\n');
}
}
//main program
int main()
{
fstream list1,list2,outlist;
curscr;
opener(list1,"name1.txt",ios::in);
opener(list2,"name2.txt",ios::in);
opener(outlist,"names.txt",ios::out);
match(list1,list2,outlist);
cout<<"name1.txt & name2.txt matching names in names.txt\n";
list1.close();
list2.close();
outlist.close();
getch();
return 0;
}
```

NOTE: In file name1.txt and name2.txt

Names should be in ascending order

OUTPUT:

names1.txt

navnish

pavan

sharath

sagar

vallish

names2.txt

navnish

niranjan

pavan

puneeth

sharath

sagar

output.txt

name1.txt & name2.txt matching names in names.txt

na vnish

pa va n

s ha ra th
s a ga r

Program 8

/*Write a program to read k Lists of names and merge them using k-way merge algorithm with k = 8. */

```
#include<stdio.h>
#include<curses.h>
#include<iostream>
#include<fstream>
#include<stdlib.h>
#include<string.h>
#define k 8
using namespace std;
//function to open a file in different mode
void opener(fstream &file, char *fn, ios_base::openmode mode)
{
file.open(fn,mode);
if(!file)
{
cout<<"unable to open the file \n";
getch();
exit(1);
}
}
//main program
int main()
{
fstream list[8], outfile;
char name[8][20]={ "name0.txt", "name1.txt", "name2.txt", "name3.txt", "name4.txt", "name5.txt", "name6.txt", "name7.txt" };
char item[8][20], min[20]="";
int i, count=0;
for(i=0; i<k; i++)
opener(list[i], name[i], ios::in);
opener(outfile, "merge8.txt", ios::out);
for(i=0; i<k; i++)
{
list[i].getline(item[i], 20, '\n');
if(list[i].eof())
count++;
}
cout<< "the names after merging using k-way merge algorithm\n";
while(count<k)
{
strcpy(min, "");
for(i=0; i<k; i++)
if(!list[i].eof())
{
strcpy(min, item[i]);
break;
}
count=0;
for(i=0; i<k; i++)
```

```
{
if(list[i].eof())
count++;
else if(strcmp(item[i],min)<0)
strcpy(min,item[i]);
}
if(count==8)break;
outfile<<min<<"\n";
cout<<min<<"\n";
for(i=0;i<k;i++)
if(strcmp(item[i],min)==0)
list[i].getline(item[i],20,'\n');
}
for(i=0;i<8;i++)
list[i].close();
getch();
return 0;
}
```

OUTPUT

N ame 0.txt

A ka rsh

*

N ame 2.txt

N a vnish

Pa van

*

N ame 3.txt

N a vnish

Sha rath

*

N ame 4.txt

Sha rath

Srinidhi

*

Name 5 .txt

Srinidhi

V allish

*

Name 6 .txt

V allish

*

Name 7 .txt

*

Merge 8.txt

A ka rsh

A nura g

N a vnish

Pa van

Sha rath

Srinidhi

V allish

