

Storypoint Problem Exploration - clover

September 3, 2024

1 Storypoint Prediction: Problem Exploration

1.1 Problem Statement

In modern agile development settings, software is developed through repeated cycles (iterative) and in smaller parts at a time (incremental), allowing for adaptation to changing requirements at any point during a project's life. A project has a number of iterations (e.g. sprints in Scrum). Each iteration requires the completion of a number of user stories, which are a common way for agile teams to express user requirements.

There is thus a need to focus on estimating the effort of completing a single user story at a time rather than the entire project. In fact, it has now become a common practice for agile teams to go through each user story and estimate its "size". Story points are commonly used as a unit of measure for specifying the overall size of a user story.

1.2 Problem Formulation

Input: A string of length N that contains a story's name and description $C = \{c_1, c_2, c_3, \dots, c_n\}$. For each story, a set of text embeddings that contains features $E = \{e_1, e_2, e_3, \dots, e_m\}$ extracted from C has been provided.

Output: A natural number P associated with the story point of that user story

1.3 Dataset Information

Text Embeddings: Text embeddings are a way to convert words or phrases from text into a list of numbers, where each number captures a part of the text's meaning. The dataset has been preprocessed and converted into two kinds of text embeddings. You can choose to work with either of them or both: - **Doc2Vec:** Input strings are transformed into fixed-length vectors of size 128. These vectors capture the semantic meaning of words and their relationships within a document. - **Look-upTable:** Input strings are transformed into fixed-length vectors of size 2264. These vectors are obtained via transforming each word in the input strings into an identifier number, then padded to the length of the longest sample.

Dataset Structure & Format: Storypoint Estimation Dataset is stored in 3 folders labeled *raw data*, *look-up*, and *doc2vec*. Within each folder are 3 CSV files for training, testing, validation. Each csv file has the following columns: - **issuekey** : The unique identifier for a story. - **storypoint**: The correct number of storypoint. - An embedding column (**embedding** or **doc2vec**) contains text embedding vectors. The raw data csv will not have this and instead contain two columns with **story name** and **description**.

1.4 Exploration

1.4.1 Raw data exploration

```
[ ]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

from sklearn.feature_extraction.text import CountVectorizer
```

Output exploration

```
[ ]: # Import raw data from the CSV file

project_name = 'clover'

all_data = pd.concat([pd.read_csv('data/' + project_name + '/' + project_name +
    ↪ '_train.csv'),
                      pd.read_csv('data/' + project_name + '/' + project_name +
    ↪ '_valid.csv'),
                      pd.read_csv('data/' + project_name + '/' + project_name +
    ↪ '_test.csv')])

print('Check the shape of the dataset', all_data.shape)
```

Check the shape of the dataset (361, 4)

```
[ ]: all_data.drop(['issuekey'], axis=1, inplace=True)
all_data.head()
```

```
[ ]:
                                     title \
0                line coverage data inconsistent
1  surefire classpath incorrect depending jar tes...
2                message balloon clean snapshot bogus
3  instrumentation done always get two tests run
4  test columns empty projectjs generated via jso...

                                     description  storypoint
0  running idea get inconsistent line branch cove...         2
1  two different applications symptom test cases ...         2
2  clean shapshot first optimised test run balloo...         2
3  although instr done still see two tests run co...         1
4  json report generated test fields erroneoustes...         2
```

First, let take a look at the distribution of the story point:

Interpretation of Skewness Values:

- **Skewness > 0:** Right-skewed distribution.
- **Skewness < 0:** Left-skewed distribution.


- **Skewness = 0**: Symmetrical distribution (like a normal distribution).

Interpretation of kurtosis: - **Leptokurtic (Kurtosis > 3)**: The distribution has heavier tails and a sharper peak than the normal distribution. Data points are more likely to produce extreme values. The distribution has a higher peak and fatter tails. - **Platykurtic (Kurtosis < 3)**: The distribution has lighter tails and a flatter peak than the normal distribution. Data are fewer extreme values compared to a normal distribution. - **Mesokurtic (Kurtosis = 3)**: The distribution has a similar kurtosis to the normal distribution, indicating a moderate level of outliers.

```
[ ]: # Draw a histogram of the story points
plt.figure(figsize=(12, 4))
plt.xticks(np.arange(0, max(all_data['storypoint']) + 1, 5))
sns.histplot(all_data['storypoint'], bins=100, kde=True)

print('Skewness:', all_data['storypoint'].skew())
print('Kurtosis:', all_data['storypoint'].kurt())
```

Skewness: 3.6594420968073123
Kurtosis: 15.933910666176914



```
[ ]: tmp = pd.concat([all_data['storypoint'].value_counts(),
                    all_data['storypoint'].value_counts() / all_data.shape[0] * 100],
                    axis=1, keys=['Counts', 'Percentage (%)'])
tmp.head(20)
```

```
[ ]:
      storypoint  Counts  Percentage (%)
1              1      111      30.747922
2              2       79      21.883657
3              3       58      16.066482
5              5       44      12.188366
8              8       25       6.925208
13             13       24       6.648199
```

20	9	2.493075
40	7	1.939058
4	4	1.108033


At the first sight, this data is bad. Then take a look at the statistic values, this data is even worse. Its distribution of the label is **right-skewed** and **leptokurtis**. This means if we use this to train model, the right side of the data can be the outliers and make the models become unsuable.

I will try 2 solutions: - Use log-scale on the label - Remove all the examples with label greater than a threshold (20, 30 or 40)

The first solution: logarithm magic

```
[ ]: sns.histplot(np.log(all_data['storypoint']), bins=20, kde=True)
```

```
[ ]: <Axes: xlabel='storypoint', ylabel='Count'>
```




The second solution: Dismantle and Cleave

```
[ ]: threshold = 20 # This threshold means that we will take all the examples with
    ↪ story points less than or equal to 20
```

```
new_data = all_data[all_data['storypoint'] <= threshold]
```

```
plt.figure(figsize=(12, 4))
plt.xticks(np.arange(0, max(new_data['storypoint']) + 1, 1))
sns.histplot(new_data['storypoint'], bins=threshold, kde=True)
print('Fitered percentage: ', round(1 - new_data.shape[0] / all_data.shape[0], 2) * 100, '%')
```

Fitered percentage: 2.0 %



Input exploration The input of this problem is 2 texts: title and description. First we will find some statistics:

```
[ ]: title_lengths = all_data['title'].apply(lambda x: len(x.split(' ')))
print('Title analysis:')
print(' - Mean length:', round(title_lengths.mean()))
print(' - Min length:', title_lengths.min())
print(' - Max length:', title_lengths.max())

description_lengths = all_data['description'].apply(lambda x: len(x.split(' '))
↳if type(x) != float else 0)
print('Description analysis:')
print(' - Mean length:', round(description_lengths.mean()))
print(' - Min length:', description_lengths.min())
print(' - Max length:', description_lengths.max())
```

Title analysis:

- Mean length: 6
- Min length: 2
- Max length: 13

Description analysis:

- Mean length: 49
- Min length: 0
- Max length: 673


Plot the histogram of the title length and KDE of the description length (exclude 0):

```
[ ]: plt.figure(figsize=(12, 8))

plt.subplot(2, 1, 1)
plt.xticks(np.arange(0, max(title_lengths) + 1, 1))
plt.xlabel('Title Length')
sns.histplot(title_lengths, bins=max(title_lengths))

plt.subplot(2, 1, 2)
plt.xlabel('Description Length')
plt.xscale('log')
sns.kdeplot(description_lengths[description_lengths > 0])
```

```
[ ]: <Axes: xlabel='Description Length', ylabel='Density'>
```



I think we should check the correlation between title length and description length:

```
[ ]: plt.figure(figsize=(12, 4))

plt.subplot(1, 2, 1)
plt.xticks(np.arange(0, max(all_data['title'].apply(lambda x: len(x.split('␣↵')))) + 1, 5))
sns.regplot(x=all_data['title'].apply(lambda x : len(x.split(' '))),
            y=all_data['storypoint'],
```


```

        line_kws={'color': 'red'})

plt.subplot(1, 2, 2)
sns.regplot(x=all_data['description'].apply(lambda x : len(x.split(' ')) if
↳type(x) != float else 0),
            y=all_data['storypoint'],
            line_kws={'color': 'red'})

```

```
[ ]: <Axes: xlabel='description', ylabel='storypoint'>
```



Maybe a small correlation between storypoint and title

Let dive deeper in the input:

Title analysis:

```

[ ]: count_vectorizer = CountVectorizer()
count_vectorizer.fit(all_data['title'])

dictionary = pd.DataFrame(list(count_vectorizer.vocabulary_.items()),
↳columns=['word', 'frequency'])
dictionary.sort_values(by='frequency', ascending=False, inplace=True)
print(dictionary.shape)
dictionary.head(10)

```

```
(849, 2)
```

```

[ ]:
      word  frequency
827  zerowidth      848
458      xml        847
729    wrong        846
116    write        845
469    works        844
118  working        843

```

463	workaround	842
57	work	841
538	wizards	840
248	wins	839

Description analysis:

```
[ ]: count_vectorizer = CountVectorizer()
count_vectorizer.fit(all_data[all_data['description'].isnull() ==
↪False]['description'])

dictionary = pd.DataFrame(list(count_vectorizer.vocabulary_.items()),
↪columns=['word', 'frequency'])
dictionary.sort_values(by='frequency', ascending=False, inplace=True)
print(dictionary.shape)
dictionary.head(20)
```

(4203, 2)

```
[ ]:
      word  frequency
1066    zip        4202
1784    zim        4201
4122 zerowidth      4200
2725    zero        4199
1733   youre        4198
2335   youd        4197
982    yet        4196
1540   yes        4195
1712  yellow        4194
1008   years        4193
4130 xyzjavaunexpected 4192
2390    xyz        4191
3888  xxxxxxxxxxxx    4190
3220    xxxx        4189
1162    xxx        4188
728    xml        4187
3505  xception        4186
1052  xbootclasspath    4185
1422  wwwatlassiancom    4184
3526  wsdljava         4183
```

Yet I don't find any thing special about the words in input except so many things are bad.

1.4.2 Solving strategies

My first intuition in this problem is that the hard part is not on the algorithm we use, it is on the **embedding** part. Therefore, in case the given embedded datasets work not properly, I will use a better embedding method which is **Bidirectional Encoder Representations from Transformers (BERT)**. Also, I will try an old way to embedding the text too: **Bag of words**.

In conclusion, I will have 4 ways to embed the text: - doc2vec (already available) - Look up (already available) - Bag Of Words - BERT

About algorithm, I will try all the regression algorithm that may give a good result:

- Ridge Regressor
- Support Vector Regressor
- Random Forest Regressor
- Gradient Boosting
- XGBoost
- Lightgbm
- Blended

Maybe, we can change the problem to the classification problem with 100 labels (desparation confirmed). In the classification problem, I will use: - Support Vector Classifier - Softmax Regression (Multinomial Logistic Regression) - Random Forest - Adaboost - XGBoost

Thanks to the libraries, the implementation of all the algorithm shrinks to its minimum form.

At last, there is still a situation that all of mentioned model don't give a good result. This gamble is thrilling (hopeless).

“But would you lose?”

Nah, I'd win.