

Storypoint Prediction - moodle

September 8, 2024

1 Storypoint Prediction: Regression Approach

1.1 Preparation

```
[ ]: import os
import json
import random

import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import seaborn as sns
from scipy.sparse import csr_matrix, hstack, vstack

from sklearn.pipeline import Pipeline
from sklearn.preprocessing import RobustScaler
from sklearn.metrics import mean_squared_error, r2_score, mean_absolute_error, f1_score, precision_score, recall_score, accuracy_score
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.model_selection import learning_curve, validation_curve
from trainer import GridSearchCVTrainer

#['appceleratorstudio', 'aptanastudio', 'bamboo', 'clover',
# 'datamanagement', 'duracloud', 'jirasoftware', 'mesos',
# 'moodle', 'mule', 'mulestudio', 'springxd',
# 'talenddataquality', 'talendesb', 'titanium', 'usergrid']
project_name = 'moodle'
```

1.1.1 Plot learning curve

```
[ ]: def plot_learning_curve(estimator, title, X, y, ylim=None, cv=None,
                             n_jobs=-1, train_sizes=np.linspace(.1, 1.0, 10)):
    plt.figure()          # Create new figure
    plt.title(title)      # Set title of the figure

    # Set y-axis limits: ylim=(min, max)
    if ylim is not None:
        plt.ylim(*ylim)
```

```

plt.xlabel("Training examples") # Set x-axis label
plt.ylabel("Score")             # Set y-axis label

# Generate learning curve data
train_sizes, train_scores, test_scores = learning_curve(
    estimator, X, y, cv=cv, n_jobs=n_jobs, train_sizes=train_sizes,
    ↪scoring='neg_mean_squared_error')

train_scores_mean = np.mean(train_scores, axis=1) # Calculate mean of
↪training scores
train_scores_std = np.std(train_scores, axis=1)   # Calculate standard
↪deviation of training scores
test_scores_mean = np.mean(test_scores, axis=1)   # Calculate mean of test
↪scores
test_scores_std = np.std(test_scores, axis=1)      # Calculate standard
↪deviation of test scores

plt.grid() # Display grid

# Fill the area between the mean training score and the mean +/- std
↪training score
plt.fill_between(train_sizes, train_scores_mean - train_scores_std,
                 train_scores_mean + train_scores_std, alpha=0.1,
                 color="r")

# Fill the area between the mean test score and the mean +/- std test score
plt.fill_between(train_sizes, test_scores_mean - test_scores_std,
                 test_scores_mean + test_scores_std, alpha=0.1, color="g")

# Plot mean training score as points
plt.plot(train_sizes, train_scores_mean, 'o-', color="r",
         label="Training score")
# Plot mean test score as points
plt.plot(train_sizes, test_scores_mean, 'o-', color="g",
         label="Validation score")

plt.legend(loc="best") # Display legend
return plt

```

1.1.2 Plot validation curve

```

[ ]: def plot_validation_curve(estimator, title, X, y, param_name, param_range,
                             y_lim=None, cv=10, n_jobs=-1):
    train_scores, val_scores = validation_curve(estimator=estimator, X=X, y=y,
                                                param_name=param_name,
    ↪param_range=param_range,

```

```

cv=cv, n_jobs=n_jobs,
    ↪
    ↪scoring='neg_mean_squared_error')

    # Calculate mean and standard deviation of training and validation scores
    train_mean = np.mean(train_scores, axis=1)
    tran_std = np.std(train_scores, axis=1)
    val_mean = np.mean(val_scores, axis=1)
    val_std = np.std(val_scores, axis=1)
    print(val_mean)

    # Plot train scores
    plt.plot(param_range, train_mean, color='r', marker='o', markersize=5,
    ↪label='Training score')
    plt.fill_between(param_range, train_mean + tran_std, train_mean - tran_std,
    ↪alpha=0.15, color='r')

    # Plot validation scores
    plt.plot(param_range, val_mean, color='g', linestyle='--', marker='s',
    ↪markersize=5, label='Validation score')
    plt.fill_between(param_range, val_mean + val_std, val_mean - val_std,
    ↪alpha=0.15, color='g')

    plt.title(title)          # Set title of the plot
    plt.grid()                # Display grid
    plt.xscale('log')         # Set x-axis scale to log
    plt.legend(loc='best')    # Display legend
    plt.xlabel('Parameter')   # Set x-axis label
    plt.ylabel('Score')       # Set y-axis label

    # Set y-axis limits
    if y_lim != None:
        plt.ylim(y_lim)

    return plt

```

1.1.3 Evaluate model

```

[ ]: def evaluate_model(model, model_name, X_test, y_test, y_logscale=False,
    ↪save_directory=None):
    y_pred = model.predict(X_test)
    if(y_logscale):
        y_pred = np.exp(y_pred)

    lines = [model_name + '\s evaluation results:']

    mse = mean_squared_error(y_test, y_pred)

```

```

rmse = np.sqrt(mse)
mae = mean_absolute_error(y_test, y_pred)
r2 = r2_score(y_test, y_pred)

lines.append(f' - Mean squared error:      {mse:.4f}')
lines.append(f' - Root mean squared error: {rmse:.4f}')
lines.append(f' - Mean absolute error:     {mae:.4f}')
lines.append(f' - R2 error:                {r2:.4f}')

y_pred = np.round(y_pred).astype(int)
f1 = f1_score(y_test, y_pred, average='weighted')
precision = precision_score(y_test, y_pred, average='weighted',
↪zero_division=0)
recall = recall_score(y_test, y_pred, average='weighted', zero_division=0)
accuracy = accuracy_score(y_test, y_pred)

lines.append(f' - F1 score:                {f1:.4f}')
lines.append(f' - Precision:              {precision:.4f}')
lines.append(f' - Recall:                 {recall:.4f}')
lines.append(f' - Accuracy:               {accuracy:.4f}')
lines.append('-----')
lines.append('')

# Save to file

if(save_directory != None):
    filename = save_directory + project_name + '.txt'
    directory = os.path.dirname(filename)
    if not os.path.exists(directory):
        os.makedirs(directory)
    with open(filename, 'a') as f:
        for line in lines:
            print(line)
            f.write(line + '\n')
else:
    for line in lines:
        print(line)

```

1.1.4 Set random seed

```

[ ]: # Set random seed for numpy
np.random.seed(42)

# Set random seed for random
random.seed(42)

# Set random seed for os

```

```
os.environ['PYTHONHASHSEED'] = '42'
```

1.2 Dataset set-up

1.2.1 Bag of Words preprocessing

This is a Bag of Words preprocess approach. I will use 2 CountVectorizer from sklearn to change title and description to two 2 vectors and then concatenate them together. In the rest of this notebook, I will use cross-validation instead hold-out. Therefore, I will join the validation set with training set.

```
[ ]: # # Import and remove NaN value

# data_train = pd.concat([pd.read_csv('data/' + project_name + '/' +
    ↪project_name + '_train.csv'),
#                          pd.read_csv('data/' + project_name + '/' +
    ↪project_name + '_valid.csv')])
# data_test = pd.read_csv('data/' + project_name + '/' + project_name + '_test.
    ↪csv')

# data_train['description'].replace(np.nan, '', inplace=True)
# data_test['description'].replace(np.nan, '', inplace=True)

# # Vectorize title
# title_vectorizer = CountVectorizer(ngram_range=(1, 2), min_df=2)
# title_vectorizer.fit(pd.concat([data_train['title'], data_test['title']]))

# # Vectorize description
# description_vectorizer = CountVectorizer(ngram_range=(1, 2), min_df=2)
# description_vectorizer.fit(pd.concat([data_train['description'],
    ↪data_test['description']]))

# X_train = hstack([title_vectorizer.transform(data_train['title']).
    ↪astype(float),
#                  description_vectorizer.transform(data_train['description']).
    ↪astype(float),
#                  data_train['title'].apply(lambda x : len(x)).to_numpy().
    ↪reshape(-1, 1),
#                  data_train['description'].apply(lambda x : len(x)).
    ↪to_numpy().reshape(-1, 1)
#                  ])

# y_train = data_train['storypoint'].to_numpy().astype(float)

# X_test = hstack([title_vectorizer.transform(data_test['title']).astype(float),
```

```
#             description_vectorizer.transform(data_test['description']).
↳astype(float),
#             data_test['title'].apply(lambda x : len(x)).to_numpy().
↳reshape(-1, 1),
#             data_test['description'].apply(lambda x : len(x)).
↳to_numpy().reshape(-1, 1)
#             ])

# y_test = data_test['storypoint'].to_numpy().astype(float)
```

```
[ ]: # print('Check training dataset\'shape:', X_train.shape, y_train.shape)
# print('Check testing dataset\'shape:', X_test.shape, y_test.shape)
```

I will use log-scale the label to get a normal distribution of it.

```
[ ]: # y_train_log = np.log(y_train)
```

1.2.2 doc2vec preprocessing

This process is already prepared so I only need to import the thing

```
[ ]: data_train = pd.concat([pd.read_csv('doc2vec/' + project_name + '/' +
↳project_name + '_train.csv'),
                             pd.read_csv('doc2vec/' + project_name + '/' +
↳project_name + '_valid.csv')])
data_test = pd.read_csv('doc2vec/' + project_name + '/' + project_name + '_test.
↳csv')

X_train = np.vstack(data_train['doc2vec'].apply(lambda x: np.fromstring(x[1:
↳-1], sep=' ')).to_numpy())
y_train = data_train['storypoint'].to_numpy().astype(int)

X_test = np.vstack(data_test['doc2vec'].apply(lambda x: np.fromstring(x[1:-1],
↳sep=' ')).to_numpy())
y_test = data_test['storypoint'].to_numpy().astype(int)
```

Check shape of the datasets

```
[ ]: print('Check training dataset\'shape:', X_train.shape, y_train.shape)
print('Check testing dataset\'shape:', X_test.shape, y_test.shape)
```

Check training dataset'shape: (1050, 128) (1050,)

Check testing dataset'shape: (116, 128) (116,)

```
[ ]: y_train_log = np.log(y_train)
```

1.3 Model training

1.3.1 Linear Regressor

```
[ ]: from sklearn.linear_model import ElasticNet, Ridge
```

Ridge

```
[ ]: dict_param = {  
    'alpha': [.0001, .001, .01, .1, 1, 10, 100, 1000, 10000],  
    'random_state': [42]  
}
```

```
[ ]: grid_search = GridSearchCVTrainer(name='Ridge', model=Ridge(),  
    ↪param_grid=dict_param,  
                                     cv=5, n_jobs=5, directory='settings/doc2vec/'  
    ↪+ project_name + '/')  
grid_search.load_if_exists()  
grid_search.fit(X_train, y_train_log)  
  
ridge_model = grid_search.best_estimator_  
ridge_model.fit(X_train, y_train_log)
```

There is no checkpoint file for this model.

100%| | 9/9 [00:02<00:00, 4.49it/s]

```
[ ]: Ridge(alpha=1, random_state=42)
```

```
[ ]: evaluate_model(ridge_model, 'Ridge model', X_test, y_test, y_logscale=True,  
    ↪save_directory='results/doc2vec/')
```

Ridge model's evaluation results:

- Mean squared error:	74.2880
- Root mean squared error:	8.6190
- Mean absolute error:	8.0101
- R2 error:	-18.3575
- F1 score:	0.0000
- Precision:	0.0000
- Recall:	0.0000
- Accuracy:	0.0000

```
[ ]: ridge_model.get_params()
```

```
[ ]: {'alpha': 1,  
    'copy_X': True,  
    'fit_intercept': True,  
    'max_iter': None,
```

```
'positive': False,
'random_state': 42,
'solver': 'auto',
'tol': 0.0001}
```

Elastic net:

```
[ ]: dict_param['l1_ratio'] = [.2, .4, .6, .8, 1]
dict_param['max_iter'] = [100000]
```

```
[ ]: grid_search = GridSearchCVTrainer(name='Elastic Net', model=ElasticNet(),
    ↪ param_grid=dict_param,
                                cv=5, n_jobs=5, directory='settings/doc2vec/'
    ↪ + project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

elastic_model = grid_search.best_estimator_
elastic_model.fit(X_train, y_train_log)
```

There is no checkpoint file for this model.

100%| | 45/45 [00:14<00:00, 3.07it/s]

```
[ ]: ElasticNet(alpha=0.001, l1_ratio=1, max_iter=100000, random_state=42)
```

```
[ ]: evaluate_model(elastic_model, 'Elastic Net model', X_test, y_test,
    ↪ y_logscale=True, save_directory='results/doc2vec/')
```

Elastic Net model's evaluation results:

```
- Mean squared error:      71.8456
- Root mean squared error: 8.4762
- Mean absolute error:     7.9185
- R2 error:                -17.7210
- F1 score:                0.0000
- Precision:               0.0000
- Recall:                  0.0000
- Accuracy:                0.0000
```

```
[ ]: elastic_model.get_params()
```

```
[ ]: {'alpha': 0.001,
'copy_X': True,
'fit_intercept': True,
'l1_ratio': 1,
'max_iter': 100000,
'positive': False,
```



```
'precompute': False,
'random_state': 42,
'selection': 'cyclic',
'tol': 0.0001,
'warm_start': False}
```

Choose final linear regressor model:

```
[ ]: if mean_squared_error(y_test, np.exp(ridge_model.predict(X_test))) < \
      mean_squared_error(y_test, np.exp(elastic_model.predict(X_test))):
      linear_model = ridge_model
else:
      linear_model = elastic_model
```

1.3.2 Support Vector Regressor

```
[ ]: from sklearn.svm import SVR
```

```
[ ]: dict_param = {
      'C': [.0001, .001, .01, .1, 1, 10, 100, 1000, 10000],
      'gamma': np.logspace(-9, 3, 13),
      'kernel': ['rbf']
    }
```

```
[ ]: grid_search = GridSearchCVTrainer(name="Support Vector Regressor", model=SVR(),
    ↪ param_grid=dict_param,
    cv=5, n_jobs=5, directory='settings/doc2vec/'
    ↪ project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

svr_model = grid_search.best_estimator_
svr_model.fit(X_train, y_train_log)
```

There is no checkpoint file for this model.

```
100%|      | 117/117 [00:28<00:00, 4.09it/s]
```

```
[ ]: SVR(C=10000, gamma=1e-05)
```

```
[ ]: evaluate_model(svr_model, 'SVR model', X_test, y_test, y_logscale=True,
    ↪ save_directory='results/doc2vec/')
```

SVR model's evaluation results:

```
- Mean squared error:      65.9389
- Root mean squared error: 8.1203
- Mean absolute error:     7.4888
- R2 error:                -16.1819
- F1 score:                0.0000
```

```
- Precision:          0.0000
- Recall:            0.0000
- Accuracy:          0.0000
```

```
[ ]: svr_model.get_params()
```

```
[ ]: {'C': 10000,
      'cache_size': 200,
      'coef0': 0.0,
      'degree': 3,
      'epsilon': 0.1,
      'gamma': 1e-05,
      'kernel': 'rbf',
      'max_iter': -1,
      'shrinking': True,
      'tol': 0.001,
      'verbose': False}
```

1.3.3 Random Forest Regressor

```
[ ]: from sklearn.ensemble import RandomForestRegressor
```

```
[ ]: dict_param = {
      'max_depth' : [1000, 2000, 5000],
      'min_samples_split': [25, 200, 1000],
      'min_samples_leaf': [1, 2, 3, 4],
      'max_features': [50, 100, 200],
      'n_estimators': [1024],
      'random_state': [42]
    }
```

```
[ ]: grid_search = GridSearchCVTrainer(name="Random Forest Regressor",
                                       model=RandomForestRegressor(),
                                       param_grid=dict_param, cv = 5, n_jobs=-1,
                                       directory='settings/doc2vec/' + project_name_
                                       ↵+ '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

rfr_model = grid_search.best_estimator_
rfr_model.fit(X_train, y_train_log)
```

There is no checkpoint file for this model.

```
100%|      | 108/108 [38:44<00:00, 21.52s/it]
```

```
[ ]: RandomForestRegressor(max_depth=1000, max_features=200, min_samples_leaf=4,
                           min_samples_split=25, n_estimators=1024, random_state=42)
```

```
[ ]: evaluate_model(rfr_model, 'Random Forest model', X_test, y_test,
                    y_logscale=True, save_directory='results/doc2vec/')
```

Random Forest model's evaluation results:

```
- Mean squared error:      93.3487
- Root mean squared error: 9.6617
- Mean absolute error:     8.8428
- R2 error:                -23.3242
- F1 score:                0.0031
- Precision:               0.0019
- Recall:                  0.0086
- Accuracy:                0.0086
```

```
[ ]: rfr_model.get_params()
```

```
[ ]: {'bootstrap': True,
      'ccp_alpha': 0.0,
      'criterion': 'squared_error',
      'max_depth': 1000,
      'max_features': 200,
      'max_leaf_nodes': None,
      'max_samples': None,
      'min_impurity_decrease': 0.0,
      'min_samples_leaf': 4,
      'min_samples_split': 25,
      'min_weight_fraction_leaf': 0.0,
      'monotonic_cst': None,
      'n_estimators': 1024,
      'n_jobs': None,
      'oob_score': False,
      'random_state': 42,
      'verbose': 0,
      'warm_start': False}
```

1.3.4 XGBoost

```
[ ]: from xgboost import XGBRegressor
```

```
[ ]: dict_param = {
      'eta' : np.linspace(0.01, 0.2, 3),
      'gamma': np.logspace(-2, 2, 5),
      'max_depth': np.asarray([3, 5, 7, 9]).tolist(),
      'min_child_weight': np.logspace(-2, 2, 5),
```

```

    'subsample': np.asarray([0.5, .1]),
    'reg_alpha': np.asarray([0.0, 0.05]),
    'n_estimators': np.asarray([10, 20, 50, 100]).tolist(),
    'random_state': [42]
}

```

```

[ ]: grid_search = GridSearchCVTrainer(name='XGBoost_
    ↳Regressor', model=XGBRegressor(), param_grid=dict_param,
                                cv = 5, n_jobs=2, directory='settings/doc2vec/
    ↳' + project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

xgb_model = grid_search.best_estimator_
xgb_model.fit(X_train, y_train_log)

```

There is no checkpoint file for this model.

100%| | 4800/4800 [48:44<00:00, 1.64it/s]

```

[ ]: XGBRegressor(base_score=None, booster=None, callbacks=None,
    colsample_bylevel=None, colsample_bynode=None,
    colsample_bytree=None, device=None, early_stopping_rounds=None,
    enable_categorical=False, eta=0.105, eval_metric=None,
    feature_types=None, gamma=0.01, grow_policy=None,
    importance_type=None, interaction_constraints=None,
    learning_rate=None, max_bin=None, max_cat_threshold=None,
    max_cat_to_onehot=None, max_delta_step=None, max_depth=3,
    max_leaves=None, min_child_weight=100.0, missing=nan,
    monotone_constraints=None, multi_strategy=None, n_estimators=100,
    n_jobs=None, num_parallel_tree=None, ...)

```

```

[ ]: evaluate_model(xgb_model, 'XGBoost Regressor model', X_test, y_test,
    ↳y_logscale=True, save_directory='results/doc2vec/')

```

XGBoost Regressor model's evaluation results:

```

- Mean squared error:      114.1811
- Root mean squared error: 10.6856
- Mean absolute error:     9.6697
- R2 error:                -28.7525
- F1 score:                0.0000
- Precision:               0.0000
- Recall:                  0.0000
- Accuracy:                0.0000
-----

```

```

[ ]: xgb_model.get_params()

```

```
[ ]: {'objective': 'reg:squarederror',
      'base_score': None,
      'booster': None,
      'callbacks': None,
      'colsample_bylevel': None,
      'colsample_bynode': None,
      'colsample_bytree': None,
      'device': None,
      'early_stopping_rounds': None,
      'enable_categorical': False,
      'eval_metric': None,
      'feature_types': None,
      'gamma': 0.01,
      'grow_policy': None,
      'importance_type': None,
      'interaction_constraints': None,
      'learning_rate': None,
      'max_bin': None,
      'max_cat_threshold': None,
      'max_cat_to_onehot': None,
      'max_delta_step': None,
      'max_depth': 3,
      'max_leaves': None,
      'min_child_weight': 100.0,
      'missing': nan,
      'monotone_constraints': None,
      'multi_strategy': None,
      'n_estimators': 100,
      'n_jobs': None,
      'num_parallel_tree': None,
      'random_state': 42,
      'reg_alpha': 0.0,
      'reg_lambda': None,
      'sampling_method': None,
      'scale_pos_weight': None,
      'subsample': 0.5,
      'tree_method': None,
      'validate_parameters': None,
      'verbosity': None,
      'eta': 0.105}
```

1.3.5 LightGBM

```
[ ]: from lightgbm import LGBMRegressor
      from sklearn.model_selection import ParameterSampler
```

```
[ ]: dict_param = {
    'n_estimator': [10, 20, 50, 100, 200, 500],
    'max_depth': np.asarray([5, 7, 9, 11, 13]).tolist(),
    'num_leaves': ((np.power(2, np.asarray([5, 7, 9, 11, 13])) - 1) * (0.55 +
↪(0.65 - 0.55) * np.random.rand(5))).astype(int).tolist(),
    'min_data_in_leaf': np.linspace(100, 1000, 4).astype(int).tolist(),
    'feature_fraction': np.linspace(0.6, 1, 3),
    'bagging_fraction': np.linspace(0.6, 1, 3),
    'learning_rate': [0.01],
    'verbose': [-1],
    'random_state': [42]
}

def custom_sampler(param_grid):
    for params in ParameterSampler(param_grid, n_iter=1e9):
        range_num_leaves = ((0.5 * (2**params['max_depth'] - 1)), (0.7 *
↪(2**params['max_depth'] - 1))
        if (range_num_leaves[0] <= params['num_leaves'] <= range_num_leaves[1]):
            for key, value in params.items():
                params[key] = [value]
            yield params

[ ]: grid_search = GridSearchCVTrainer(name='LightGBM Regressor',
↪model=LGBMRegressor(),
                                param_grid=list(custom_sampler(dict_param)), cv
↪= 5, n_jobs=1,
                                directory='settings/doc2vec/' + project_name +
↪ '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

lgbmr_model = grid_search.best_estimator_
lgbmr_model.fit(X_train, y_train_log)
```

c:\Users\aupho\AppData\Local\Programs\Python\Python311\Lib\site-packages\sklearn\model_selection_search.py:320: UserWarning: The total space of parameters 5400 is smaller than n_iter=1000000000. Running 5400 iterations. For exhaustive searches, use GridSearchCV.

warnings.warn(

There is no checkpoint file for this model.

100%| | 1080/1080 [09:53<00:00, 1.82it/s]

```
[ ]: LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6, learning_rate=0.01,
                    max_depth=7, min_data_in_leaf=100, n_estimator=10, num_leaves=72,
                    random_state=42, verbose=-1)
```

```
[ ]: evaluate_model(lgbmr_model, 'LightGBM regressor model', X_test, y_test,
    ↪y_logscale=True, save_directory='results/doc2vec/')
```

LightGBM regressor model's evaluation results:

- Mean squared error:	72.5536
- Root mean squared error:	8.5178
- Mean absolute error:	8.2308
- R2 error:	-17.9055
- F1 score:	0.0000
- Precision:	0.0000
- Recall:	0.0000
- Accuracy:	0.0000

```
[ ]: lgbmr_model.get_params()
```

```
[ ]: {'boosting_type': 'gbdt',
      'class_weight': None,
      'colsample_bytree': 1.0,
      'importance_type': 'split',
      'learning_rate': 0.01,
      'max_depth': 7,
      'min_child_samples': 20,
      'min_child_weight': 0.001,
      'min_split_gain': 0.0,
      'n_estimators': 100,
      'n_jobs': None,
      'num_leaves': 72,
      'objective': None,
      'random_state': 42,
      'reg_alpha': 0.0,
      'reg_lambda': 0.0,
      'subsample': 1.0,
      'subsample_for_bin': 200000,
      'subsample_freq': 0,
      'verbose': -1,
      'n_estimator': 10,
      'min_data_in_leaf': 100,
      'feature_fraction': 0.6,
      'bagging_fraction': 0.6}
```

1.3.6 Stacked model:

```
[ ]: from mlxtend.regressor import StackingCVRegressor
```

Define component models:

```
[ ]: trained_models = [linear_model, svr_model, rfr_model, xgb_model, lgblmr_model]
```

Define blended model:

```
[ ]: stack_gen = StackingCVRegressor(regressors=tuple(trained_models),
                                     meta_regressor=trained_models[np.
                                     ↪argmin([mean_squared_error(np.exp(model.predict(X_test)), y_test) for model_
                                     ↪in trained_models]]),
                                     use_features_in_secondary=True, n_jobs=-1,
                                     ↪random_state=42)
print(stack_gen)
```

```
StackingCVRegressor(meta_regressor=SVR(C=10000, gamma=1e-05), n_jobs=-1,
                    random_state=42,
                    regressors=(ElasticNet(alpha=0.001, l1_ratio=1,
                                             max_iter=100000, random_state=42),
                                SVR(C=10000, gamma=1e-05),
                                RandomForestRegressor(max_depth=1000,
                                                       max_features=200,
                                                       min_samples_leaf=4,
                                                       min_samples_split=25,
                                                       n_estimators=1024,
                                                       random_state=42),
                                XGBRegressor(base_score=None, bo...
                                             max_leaves=None,
                                             min_child_weight=100.0,
                                             missing=nan,
                                             monotone_constraints=None,
                                             multi_strategy=None,
                                             n_estimators=100, n_jobs=None,
                                             num_parallel_tree=None, ...),
                                LGBMRegressor(bagging_fraction=0.6,
                                             feature_fraction=0.6,
                                             learning_rate=0.01, max_depth=7,
                                             min_data_in_leaf=100,
                                             n_estimator=10, num_leaves=72,
                                             random_state=42, verbose=-1)),
                    use_features_in_secondary=True)
```

```
[ ]: stack_gen.fit(X_train, y_train_log)
```

```
[ ]: StackingCVRegressor(meta_regressor=SVR(C=10000, gamma=1e-05), n_jobs=-1,
                        random_state=42,
                        regressors=(ElasticNet(alpha=0.001, l1_ratio=1,
                                                max_iter=100000, random_state=42),
                                    SVR(C=10000, gamma=1e-05),
                                    RandomForestRegressor(max_depth=1000,
                                                           max_features=200,
```



```

        min_samples_leaf=4,
        min_samples_split=25,
        n_estimators=1024,
        random_state=42),
XGBRegressor(base_score=None, bo...
        max_leaves=None,
        min_child_weight=100.0,
        missing=nan,
        monotone_constraints=None,
        multi_strategy=None,
        n_estimators=100, n_jobs=None,
        num_parallel_tree=None, ...),
LGBMRegressor(bagging_fraction=0.6,
        feature_fraction=0.6,
        learning_rate=0.01, max_depth=7,
        min_data_in_leaf=100,
        n_estimator=10, num_leaves=72,
        random_state=42, verbose=-1)),
use_features_in_secondary=True)

```

```
[ ]: evaluate_model(stack_gen, 'Stacking model', X_test, y_test, y_logscale=True,
    ↪save_directory='results/doc2vec/')
```

Stacking model's evaluation results:

```

- Mean squared error:      81.7969
- Root mean squared error: 9.0442
- Mean absolute error:     8.2498
- R2 error:                -20.3141
- F1 score:                0.0000
- Precision:               0.0000
- Recall:                  0.0000
- Accuracy:                0.0000

```

```
[ ]: stack_gen.get_params()
```

```
[ ]: {'cv': 5,
      'meta_regressor__C': 10000,
      'meta_regressor__cache_size': 200,
      'meta_regressor__coef0': 0.0,
      'meta_regressor__degree': 3,
      'meta_regressor__epsilon': 0.1,
      'meta_regressor__gamma': 1e-05,
      'meta_regressor__kernel': 'rbf',
      'meta_regressor__max_iter': -1,
      'meta_regressor__shrinking': True,
      'meta_regressor__tol': 0.001,

```

```

'meta_regressor__verbose': False,
'meta_regressor': SVR(C=10000, gamma=1e-05),
'multi_output': False,
'n_jobs': -1,
'pre_dispatch': '2*n_jobs',
'random_state': 42,
'refit': True,
'regressors': (ElasticNet(alpha=0.001, l1_ratio=1, max_iter=100000,
random_state=42),
    SVR(C=10000, gamma=1e-05),
    RandomForestRegressor(max_depth=1000, max_features=200, min_samples_leaf=4,
        min_samples_split=25, n_estimators=1024,
random_state=42),
    XGBRegressor(base_score=None, booster=None, callbacks=None,
        colsample_bylevel=None, colsample_bynode=None,
        colsample_bytree=None, device=None, early_stopping_rounds=None,
        enable_categorical=False, eta=0.105, eval_metric=None,
        feature_types=None, gamma=0.01, grow_policy=None,
        importance_type=None, interaction_constraints=None,
        learning_rate=None, max_bin=None, max_cat_threshold=None,
        max_cat_to_onehot=None, max_delta_step=None, max_depth=3,
        max_leaves=None, min_child_weight=100.0, missing=nan,
        monotone_constraints=None, multi_strategy=None, n_estimators=100,
        n_jobs=None, num_parallel_tree=None, ...),
    LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6, learning_rate=0.01,
        max_depth=7, min_data_in_leaf=100, n_estimator=10,
num_leaves=72,
        random_state=42, verbose=-1)),
'shuffle': True,
'store_train_meta_features': False,
'use_features_in_secondary': True,
'verbose': 0,
'elasticnet': ElasticNet(alpha=0.001, l1_ratio=1, max_iter=100000,
random_state=42),
'svr': SVR(C=10000, gamma=1e-05),
'randomforestregressor': RandomForestRegressor(max_depth=1000,
max_features=200, min_samples_leaf=4,
        min_samples_split=25, n_estimators=1024,
random_state=42),
'xgbregressor': XGBRegressor(base_score=None, booster=None, callbacks=None,
        colsample_bylevel=None, colsample_bynode=None,
        colsample_bytree=None, device=None, early_stopping_rounds=None,
        enable_categorical=False, eta=0.105, eval_metric=None,
        feature_types=None, gamma=0.01, grow_policy=None,
        importance_type=None, interaction_constraints=None,
        learning_rate=None, max_bin=None, max_cat_threshold=None,
        max_cat_to_onehot=None, max_delta_step=None, max_depth=3,

```

```

        max_leaves=None, min_child_weight=100.0, missing=nan,
        monotone_constraints=None, multi_strategy=None, n_estimators=100,
        n_jobs=None, num_parallel_tree=None, ...),
'lgbmregressor': LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6,
learning_rate=0.01,
        max_depth=7, min_data_in_leaf=100, n_estimator=10, num_leaves=72,
        random_state=42, verbose=-1),
'elasticnet__alpha': 0.001,
'elasticnet__copy_X': True,
'elasticnet__fit_intercept': True,
'elasticnet__l1_ratio': 1,
'elasticnet__max_iter': 100000,
'elasticnet__positive': False,
'elasticnet__precompute': False,
'elasticnet__random_state': 42,
'elasticnet__selection': 'cyclic',
'elasticnet__tol': 0.0001,
'elasticnet__warm_start': False,
'svr__C': 10000,
'svr__cache_size': 200,
'svr__coef0': 0.0,
'svr__degree': 3,
'svr__epsilon': 0.1,
'svr__gamma': 1e-05,
'svr__kernel': 'rbf',
'svr__max_iter': -1,
'svr__shrinking': True,
'svr__tol': 0.001,
'svr__verbose': False,
'randomforestregressor__bootstrap': True,
'randomforestregressor__ccp_alpha': 0.0,
'randomforestregressor__criterion': 'squared_error',
'randomforestregressor__max_depth': 1000,
'randomforestregressor__max_features': 200,
'randomforestregressor__max_leaf_nodes': None,
'randomforestregressor__max_samples': None,
'randomforestregressor__min_impurity_decrease': 0.0,
'randomforestregressor__min_samples_leaf': 4,
'randomforestregressor__min_samples_split': 25,
'randomforestregressor__min_weight_fraction_leaf': 0.0,
'randomforestregressor__monotonic_cst': None,
'randomforestregressor__n_estimators': 1024,
'randomforestregressor__n_jobs': None,
'randomforestregressor__oob_score': False,
'randomforestregressor__random_state': 42,
'randomforestregressor__verbose': 0,
'randomforestregressor__warm_start': False,

```

```
'xgbregressor__objective': 'reg:squarederror',
'xgbregressor__base_score': None,
'xgbregressor__booster': None,
'xgbregressor__callbacks': None,
'xgbregressor__colsample_bylevel': None,
'xgbregressor__colsample_bynode': None,
'xgbregressor__colsample_bytree': None,
'xgbregressor__device': None,
'xgbregressor__early_stopping_rounds': None,
'xgbregressor__enable_categorical': False,
'xgbregressor__eval_metric': None,
'xgbregressor__feature_types': None,
'xgbregressor__gamma': 0.01,
'xgbregressor__grow_policy': None,
'xgbregressor__importance_type': None,
'xgbregressor__interaction_constraints': None,
'xgbregressor__learning_rate': None,
'xgbregressor__max_bin': None,
'xgbregressor__max_cat_threshold': None,
'xgbregressor__max_cat_to_onehot': None,
'xgbregressor__max_delta_step': None,
'xgbregressor__max_depth': 3,
'xgbregressor__max_leaves': None,
'xgbregressor__min_child_weight': 100.0,
'xgbregressor__missing': nan,
'xgbregressor__monotone_constraints': None,
'xgbregressor__multi_strategy': None,
'xgbregressor__n_estimators': 100,
'xgbregressor__n_jobs': None,
'xgbregressor__num_parallel_tree': None,
'xgbregressor__random_state': 42,
'xgbregressor__reg_alpha': 0.0,
'xgbregressor__reg_lambda': None,
'xgbregressor__sampling_method': None,
'xgbregressor__scale_pos_weight': None,
'xgbregressor__subsample': 0.5,
'xgbregressor__tree_method': None,
'xgbregressor__validate_parameters': None,
'xgbregressor__verbosity': None,
'xgbregressor__eta': 0.105,
'lgbmregressor__boosting_type': 'gbdt',
'lgbmregressor__class_weight': None,
'lgbmregressor__colsample_bytree': 1.0,
'lgbmregressor__importance_type': 'split',
'lgbmregressor__learning_rate': 0.01,
'lgbmregressor__max_depth': 7,
'lgbmregressor__min_child_samples': 20,
```

```
'lgbmregressor__min_child_weight': 0.001,  
'lgbmregressor__min_split_gain': 0.0,  
'lgbmregressor__n_estimators': 100,  
'lgbmregressor__n_jobs': None,  
'lgbmregressor__num_leaves': 72,  
'lgbmregressor__objective': None,  
'lgbmregressor__random_state': 42,  
'lgbmregressor__reg_alpha': 0.0,  
'lgbmregressor__reg_lambda': 0.0,  
'lgbmregressor__subsample': 1.0,  
'lgbmregressor__subsample_for_bin': 200000,  
'lgbmregressor__subsample_freq': 0,  
'lgbmregressor__verbose': -1,  
'lgbmregressor__n_estimator': 10,  
'lgbmregressor__min_data_in_leaf': 100,  
'lgbmregressor__feature_fraction': 0.6,  
'lgbmregressor__bagging_fraction': 0.6}
```