

Storypoint Prediction - usergrid

September 14, 2024

1 Storypoint Prediction: Regression Approach

1.1 Preparation

```
[330]: import os
import json
import random

import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import seaborn as sns
from scipy.sparse import csr_matrix, hstack, vstack

from sklearn.pipeline import Pipeline
from sklearn.preprocessing import RobustScaler
from sklearn.metrics import mean_squared_error, r2_score, mean_absolute_error, f1_score, precision_score, recall_score, accuracy_score
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.model_selection import learning_curve, validation_curve
from trainer import GridSearchCVTrainer

# ['appceleratorstudio', 'aptanastudio', 'bamboo', 'clover',
#  'datamanagement', 'duracloud', 'jirasoftware', 'mesos',
#  'moodle', 'mule', 'mulestudio', 'springxd',
#  'talenddataquality', 'talendesb', 'titanium', 'usergrid']
project_name = 'usergrid'
```

1.1.1 Plot learning curve

```
[331]: def plot_learning_curve(estimator, title, X, y, ylim=None, cv=None,
                                n_jobs=-1, train_sizes=np.linspace(.1, 1.0, 10)):
    plt.figure()          # Create new figure
    plt.title(title)      # Set title of the figure

    # Set y-axis limits: ylim=(min, max)
    if ylim is not None:
        plt.ylim(*ylim)
```

```

plt.xlabel("Training examples") # Set x-axis label
plt.ylabel("Score")             # Set y-axis label

# Generate learning curve data
train_sizes, train_scores, test_scores = learning_curve(
    estimator, X, y, cv=cv, n_jobs=n_jobs, train_sizes=train_sizes,
    ↪scoring='neg_mean_squared_error')

train_scores_mean = np.mean(train_scores, axis=1) # Calculate mean of
↪training scores
train_scores_std = np.std(train_scores, axis=1)   # Calculate standard
↪deviation of training scores
test_scores_mean = np.mean(test_scores, axis=1)   # Calculate mean of test
↪scores
test_scores_std = np.std(test_scores, axis=1)      # Calculate standard
↪deviation of test scores

plt.grid() # Display grid

# Fill the area between the mean training score and the mean +/- std
↪training score
plt.fill_between(train_sizes, train_scores_mean - train_scores_std,
                 train_scores_mean + train_scores_std, alpha=0.1,
                 color="r")

# Fill the area between the mean test score and the mean +/- std test score
plt.fill_between(train_sizes, test_scores_mean - test_scores_std,
                 test_scores_mean + test_scores_std, alpha=0.1, color="g")

# Plot mean training score as points
plt.plot(train_sizes, train_scores_mean, 'o-', color="r",
         label="Training score")
# Plot mean test score as points
plt.plot(train_sizes, test_scores_mean, 'o-', color="g",
         label="Validation score")

plt.legend(loc="best") # Display legend
return plt

```

1.1.2 Plot validation curve

```

[332]: def plot_validation_curve(estimator, title, X, y, param_name, param_range,
                                y_lim=None, cv=10, n_jobs=-1):
    train_scores, val_scores = validation_curve(estimator=estimator, X=X, y=y,
                                                param_name=param_name,
    ↪param_range=param_range,

```

```

cv=cv, n_jobs=n_jobs,
    ↪
    ↪scoring='neg_mean_squared_error')

    # Calculate mean and standard deviation of training and validation scores
    train_mean = np.mean(train_scores, axis=1)
    tran_std = np.std(train_scores, axis=1)
    val_mean = np.mean(val_scores, axis=1)
    val_std = np.std(val_scores, axis=1)
    print(val_mean)

    # Plot train scores
    plt.plot(param_range, train_mean, color='r', marker='o', markersize=5,
    ↪label='Training score')
    plt.fill_between(param_range, train_mean + tran_std, train_mean - tran_std,
    ↪alpha=0.15, color='r')

    # Plot validation scores
    plt.plot(param_range, val_mean, color='g', linestyle='--', marker='s',
    ↪markersize=5, label='Validation score')
    plt.fill_between(param_range, val_mean + val_std, val_mean - val_std,
    ↪alpha=0.15, color='g')

    plt.title(title)          # Set title of the plot
    plt.grid()                # Display grid
    plt.xscale('log')          # Set x-axis scale to log
    plt.legend(loc='best')     # Display legend
    plt.xlabel('Parameter')    # Set x-axis label
    plt.ylabel('Score')        # Set y-axis label

    # Set y-axis limits
    if y_lim != None:
        plt.ylim(y_lim)

    return plt

```

1.1.3 Evaluate model

```

[333]: def evaluate_model(model, model_name, X_test, y_test, y_logscale=False,
    ↪save_directory=None):
    y_pred = model.predict(X_test)
    if(y_logscale):
        y_pred = np.exp(y_pred)

    lines = [model_name + '\s evaluation results:']

    mse = mean_squared_error(y_test, y_pred)

```

```

rmse = np.sqrt(mse)
mae = mean_absolute_error(y_test, y_pred)
r2 = r2_score(y_test, y_pred)

lines.append(f' - Mean squared error:      {mse:.4f}')
lines.append(f' - Root mean squared error: {rmse:.4f}')
lines.append(f' - Mean absolute error:     {mae:.4f}')
lines.append(f' - R2 error:                {r2:.4f}')

y_pred = np.round(y_pred).astype(int)
f1 = f1_score(y_test, y_pred, average='weighted')
precision = precision_score(y_test, y_pred, average='weighted',
↪zero_division=0)
recall = recall_score(y_test, y_pred, average='weighted', zero_division=0)
accuracy = accuracy_score(y_test, y_pred)

lines.append(f' - F1 score:                {f1:.4f}')
lines.append(f' - Precision:              {precision:.4f}')
lines.append(f' - Recall:                 {recall:.4f}')
lines.append(f' - Accuracy:               {accuracy:.4f}')
lines.append('-----')
lines.append('')

# Save to file

if(save_directory != None):
    filename = save_directory + project_name + '.txt'
    directory = os.path.dirname(filename)
    if not os.path.exists(directory):
        os.makedirs(directory)
    with open(filename, 'a') as f:
        for line in lines:
            print(line)
            f.write(line + '\n')
else:
    for line in lines:
        print(line)

```

1.1.4 Set random seed

```

[334]: # Set random seed for numpy
np.random.seed(42)

# Set random seed for random
random.seed(42)

# Set random seed for os

```

```
os.environ['PYTHONHASHSEED'] = '42'
```

1.2 Dataset set-up

1.2.1 Bag of Words preprocessing

This is a Bag of Words preprocess approach. I will use 2 CountVectorizer from sklearn to change title and description to two 2 vectors and then concatenate them together. In the rest of this notebook, I will use cross-validation instead hold-out. Therefore, I will join the validation set with training set.

```
[335]: # Import and remove NaN value

data_train = pd.concat([pd.read_csv('data/' + project_name + '/' + project_name_
    ↪ '_train.csv'),
                        pd.read_csv('data/' + project_name + '/' + project_name_
    ↪ '_valid.csv')])
data_test = pd.read_csv('data/' + project_name + '/' + project_name + '_test.
    ↪ csv')

data_train['description'].replace(np.nan, '', inplace=True)
data_test['description'].replace(np.nan, '', inplace=True)

# Vectorize title
title_vectorizer = CountVectorizer(ngram_range=(1, 2), min_df=2)
title_vectorizer.fit(pd.concat([data_train['title'], data_test['title']]))

# Vectorize description
description_vectorizer = CountVectorizer(ngram_range=(1, 2), min_df=2)
description_vectorizer.fit(pd.concat([data_train['description'],
    ↪ data_test['description']]))

X_train = hstack([title_vectorizer.transform(data_train['title']).astype(float),
                  description_vectorizer.transform(data_train['description']).
    ↪ astype(float),
                  data_train['title'].apply(lambda x : len(x)).to_numpy().
    ↪ reshape(-1, 1),
                  data_train['description'].apply(lambda x : len(x)).to_numpy().
    ↪ reshape(-1, 1)
                  ])

y_train = data_train['storypoint'].to_numpy().astype(float)

X_test = hstack([title_vectorizer.transform(data_test['title']).astype(float),
```

```

        description_vectorizer.transform(data_test['description']).
↪astype(float),
        data_test['title'].apply(lambda x : len(x)).to_numpy().
↪reshape(-1, 1),
        data_test['description'].apply(lambda x : len(x)).to_numpy().
↪reshape(-1, 1)
    ])

y_test = data_test['storypoint'].to_numpy().astype(float)

```

```

[336]: print('Check training dataset\'shape:', X_train.shape, y_train.shape)
       print('Check testing dataset\'shape:', X_test.shape, y_test.shape)

```

Check training dataset'shape: (300, 1986) (300,)

Check testing dataset'shape: (33, 1986) (33,)

I will use log-scale the label to get a normal distribution of it.

```

[337]: y_train_log = np.log(y_train)

```

1.2.2 doc2vec preprocessing

This process is already prepared so I only need to import the thing

```

[338]: # data_train = pd.concat([pd.read_csv('doc2vec/' + project_name + '/' +
↪project_name + '_train.csv'),
#                               pd.read_csv('doc2vec/' + project_name + '/' +
↪project_name + '_valid.csv')])
# data_test = pd.read_csv('doc2vec/' + project_name + '/' + project_name +
↪'_test.csv')

# X_train = np.vstack(data_train['doc2vec'].apply(lambda x: np.fromstring(x[1:
↪-1], sep=' ')).to_numpy())
# y_train = data_train['storypoint'].to_numpy().astype(int)

# X_test = np.vstack(data_test['doc2vec'].apply(lambda x: np.fromstring(x[1:
↪-1], sep=' ')).to_numpy())
# y_test = data_test['storypoint'].to_numpy().astype(int)

```

Check shape of the datasets

```

[339]: # print('Check training dataset\'shape:', X_train.shape, y_train.shape)
       # print('Check testing dataset\'shape:', X_test.shape, y_test.shape)

```

```

[340]: # y_train_log = np.log(y_train)

```

1.3 Model training

1.3.1 Linear Regressor

```
[341]: from sklearn.linear_model import ElasticNet, Ridge
```

Ridge

```
[342]: dict_param = {  
    'alpha': [.0001, .001, .01, .1, 1, 10, 100, 1000, 10000],  
    'random_state': [42]  
}
```

```
[343]: grid_search = GridSearchCVTrainer(name='Ridge', model=Ridge(),  
    ↪param_grid=dict_param,  
    cv=5, n_jobs=5, directory='settings/BoW/' +  
    ↪project_name + '/')  
grid_search.load_if_exists()  
grid_search.fit(X_train, y_train_log)  
  
ridge_model = grid_search.best_estimator_  
ridge_model.fit(X_train, y_train_log)
```

0it [00:00, ?it/s]

```
[343]: Ridge(alpha=1000, random_state=42)
```

```
[344]: evaluate_model(ridge_model, 'Ridge model', X_test, y_test, y_logscale=True,  
    ↪save_directory='results/BoW/')
```

Ridge model's evaluation results:

- Mean squared error:	3.5401
- Root mean squared error:	1.8815
- Mean absolute error:	1.3950
- R2 error:	-0.1899
- F1 score:	0.1558
- Precision:	0.1091
- Recall:	0.2727
- Accuracy:	0.2727

```
[345]: ridge_model.get_params()
```

```
[345]: {'alpha': 1000,  
    'copy_X': True,  
    'fit_intercept': True,  
    'max_iter': None,  
    'positive': False,  
    'random_state': 42,
```

```
'solver': 'auto',
'tol': 0.0001}
```

Elastic net:

```
[346]: dict_param['l1_ratio'] = [.2, .4, .6, .8, 1]
dict_param['max_iter'] = [5000]
```

```
[347]: grid_search = GridSearchCVTrainer(name='Elastic Net', model=ElasticNet(),
    ↪param_grid=dict_param,
                                cv=5, n_jobs=5, directory='settings/BoW/' +
    ↪project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

elastic_model = grid_search.best_estimator_
elastic_model.fit(X_train, y_train_log)
```

0it [00:00, ?it/s]

```
[347]: ElasticNet(alpha=0.1, l1_ratio=0.2, max_iter=5000, random_state=42)
```

```
[348]: evaluate_model(elastic_model, 'Elastic Net model', X_test, y_test,
    ↪y_logscale=True, save_directory='results/BoW/')
```

Elastic Net model's evaluation results:

```
- Mean squared error:      3.5212
- Root mean squared error: 1.8765
- Mean absolute error:     1.3929
- R2 error:                -0.1835
- F1 score:                0.1855
- Precision:               0.1429
- Recall:                  0.2727
- Accuracy:                0.2727
```

```
[349]: elastic_model.get_params()
```

```
[349]: {'alpha': 0.1,
'copy_X': True,
'fit_intercept': True,
'l1_ratio': 0.2,
'max_iter': 5000,
'positive': False,
'precompute': False,
'random_state': 42,
'selection': 'cyclic',
'tol': 0.0001,
```



```
'warm_start': False}
```

Choose final linear regressor model:

```
[350]: if mean_squared_error(y_test, np.exp(ridge_model.predict(X_test))) < \
        mean_squared_error(y_test, np.exp(elastic_model.predict(X_test))):
        linear_model = ridge_model
else:
    linear_model = elastic_model
```

1.3.2 Support Vector Regressor

```
[351]: from sklearn.svm import SVR
```

```
[352]: dict_param = {
        'C': [.0001, .001, .01, .1, 1, 10, 100, 1000, 10000],
        'epsilon': [.0001, .001, .01, .1, 1, 10, 100, 1000, 10000],
        'gamma': np.logspace(-9, 3, 13),
        'kernel': ['rbf']
    }
```

```
[353]: grid_search = GridSearchCVTrainer(name="Support Vector Regressor", model=SVR(),
    ↪param_grid=dict_param,
    cv=5, n_jobs=5, directory='settings/BoW/' +
    ↪project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

svr_model = grid_search.best_estimator_
svr_model.fit(X_train, y_train_log)
```

There is no checkpoint file for this model.

100%| | 1053/1053 [00:31<00:00, 33.62it/s]

```
[353]: SVR(C=10, epsilon=0.01, gamma=0.1)
```

```
[354]: evaluate_model(svr_model, 'SVR model', X_test, y_test, y_logscale=True,
    ↪save_directory='results/BoW/')
```

SVR model's evaluation results:

```
- Mean squared error:      3.5377
- Root mean squared error: 1.8809
- Mean absolute error:     1.3614
- R2 error:                -0.1891
- F1 score:                0.1939
- Precision:               0.1322
- Recall:                  0.3636
- Accuracy:                0.3636
```

```
[355]: svr_model.get_params()
```

```
[355]: {'C': 10,
        'cache_size': 200,
        'coef0': 0.0,
        'degree': 3,
        'epsilon': 0.01,
        'gamma': 0.1,
        'kernel': 'rbf',
        'max_iter': -1,
        'shrinking': True,
        'tol': 0.001,
        'verbose': False}
```

1.3.3 Random Forest Regressor

```
[356]: from sklearn.ensemble import RandomForestRegressor
```

```
[357]: dict_param = {
        'max_depth' : [1000, 2000, 5000],
        'min_samples_split': [25, 200, 1000],
        'min_samples_leaf': [1, 2, 3, 4],
        'max_features': [50, 100, 200],
        'n_estimators': [1024],
        'random_state': [42]
    }
```

```
[358]: grid_search = GridSearchCVTrainer(name="Random Forest Regressor",
                                         model=RandomForestRegressor(),
                                         param_grid=dict_param, cv = 5, n_jobs=-1,
                                         directory='settings/BoW/' + project_name + '/'
                                         ↪)
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

rfr_model = grid_search.best_estimator_
rfr_model.fit(X_train, y_train_log)
```

0it [00:00, ?it/s]

```
[358]: RandomForestRegressor(max_depth=1000, max_features=100, min_samples_leaf=4,
                             min_samples_split=25, n_estimators=1024, random_state=42)
```

```
[359]: evaluate_model(rfr_model, 'Random Forest model', X_test, y_test,
                     ↪y_logscale=True, save_directory='results/BoW/')
```

Random Forest model's evaluation results:

- Mean squared error: 3.4945
- Root mean squared error: 1.8693
- Mean absolute error: 1.3870
- R2 error: -0.1745
- F1 score: 0.1636
- Precision: 0.1169
- Recall: 0.2727
- Accuracy: 0.2727

```
[360]: rfr_model.get_params()
```

```
[360]: {'bootstrap': True,
       'ccp_alpha': 0.0,
       'criterion': 'squared_error',
       'max_depth': 1000,
       'max_features': 100,
       'max_leaf_nodes': None,
       'max_samples': None,
       'min_impurity_decrease': 0.0,
       'min_samples_leaf': 4,
       'min_samples_split': 25,
       'min_weight_fraction_leaf': 0.0,
       'monotonic_cst': None,
       'n_estimators': 1024,
       'n_jobs': None,
       'oob_score': False,
       'random_state': 42,
       'verbose': 0,
       'warm_start': False}
```

1.3.4 XGBoost

```
[361]: from xgboost import XGBRegressor
```

```
[362]: dict_param = {
       'eta' : np.linspace(0.01, 0.2, 3),
       'gamma': np.logspace(-2, 2, 5),
       'max_depth': np.asarray([3, 5, 7, 9]).tolist(),
       'min_child_weight': np.logspace(-2, 2, 5),
       'subsample': np.asarray([0.5, .1]),
       'reg_alpha': np.asarray([0.0, 0.05]),
       'n_estimators': np.asarray([10, 20, 50, 100]).tolist(),
       'random_state': [42]
}
```

```
[363]: grid_search = GridSearchCVTrainer(name='XGBoost_
↳Regressor',model=XGBRegressor(), param_grid=dict_param,
cv = 5, n_jobs=2, directory='settings/BoW/' +
↳project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

xgb_model = grid_search.best_estimator_
xgb_model.fit(X_train, y_train_log)
```

Oit [00:00, ?it/s]

```
[363]: XGBRegressor(base_score=None, booster=None, callbacks=None,
colsample_bylevel=None, colsample_bynode=None,
colsample_bytree=None, device=None, early_stopping_rounds=None,
enable_categorical=False, eta=0.01, eval_metric=None,
feature_types=None, gamma=0.1, grow_policy=None,
importance_type=None, interaction_constraints=None,
learning_rate=None, max_bin=None, max_cat_threshold=None,
max_cat_to_onehot=None, max_delta_step=None, max_depth=7,
max_leaves=None, min_child_weight=10.0, missing=nan,
monotone_constraints=None, multi_strategy=None, n_estimators=100,
n_jobs=None, num_parallel_tree=None, ...)
```

```
[364]: evaluate_model(xgb_model, 'XGBoost Regressor model', X_test, y_test,
↳y_logscale=True, save_directory='results/BoW/')
```

XGBoost Regressor model's evaluation results:

```
- Mean squared error:      3.4284
- Root mean squared error: 1.8516
- Mean absolute error:     1.3580
- R2 error:                -0.1523
- F1 score:                0.1636
- Precision:               0.1169
- Recall:                  0.2727
- Accuracy:                0.2727
```

```
[365]: xgb_model.get_params()
```

```
[365]: {'objective': 'reg:squarederror',
'base_score': None,
'booster': None,
'callbacks': None,
'colsample_bylevel': None,
'colsample_bynode': None,
'colsample_bytree': None,
```

```

'device': None,
'early_stopping_rounds': None,
'enable_categorical': False,
'eval_metric': None,
'feature_types': None,
'gamma': 0.1,
'grow_policy': None,
'importance_type': None,
'interaction_constraints': None,
'learning_rate': None,
'max_bin': None,
'max_cat_threshold': None,
'max_cat_to_onehot': None,
'max_delta_step': None,
'max_depth': 7,
'max_leaves': None,
'min_child_weight': 10.0,
'missing': nan,
'monotone_constraints': None,
'multi_strategy': None,
'n_estimators': 100,
'n_jobs': None,
'num_parallel_tree': None,
'random_state': 42,
'reg_alpha': 0.0,
'reg_lambda': None,
'sampling_method': None,
'scale_pos_weight': None,
'subsample': 0.5,
'tree_method': None,
'validate_parameters': None,
'verbosity': None,
'eta': 0.01}

```

1.3.5 LightGBM

```

[366]: from lightgbm import LGBMRegressor
       from sklearn.model_selection import ParameterSampler

```

```

[367]: dict_param = {
    'n_estimator': [10, 20, 50, 100, 200, 500],
    'max_depth': np.asarray([5, 7, 9, 11, 13]).tolist(),
    'num_leaves': ((np.power(2, np.asarray([5, 7, 9, 11, 13]))) - 1) * (0.55 +
↪(0.65 - 0.55) * np.random.rand(5))).astype(int).tolist(),
    'min_data_in_leaf': np.linspace(100, 1000, 4).astype(int).tolist(),
    'feature_fraction': np.linspace(0.6, 1, 3),
    'bagging_fraction': np.linspace(0.6, 1, 3),

```

```

    'learning_rate': [0.01],
    'verbose': [-1],
    'random_state': [42]
}

def custom_sampler(param_grid):
    for params in ParameterSampler(param_grid, n_iter=1e9):
        range_num_leaves = ((0.5 * (2**params['max_depth'] - 1)), (0.7 *
↪(2**params['max_depth']) - 1))
        if (range_num_leaves[0] <= params['num_leaves'] <= range_num_leaves[1]):
            for key, value in params.items():
                params[key] = [value]
            yield params

```

```

[368]: grid_search = GridSearchCVTrainer(name='LightGBM Regressor',
↪model=LGBMRegressor(),
                                param_grid=list(custom_sampler(dict_param)), cv
↪= 5, n_jobs=1,
                                directory='settings/BoW/' + project_name + '/')
grid_search.load_if_exists()
grid_search.fit(X_train, y_train_log)

lgbmr_model = grid_search.best_estimator_
lgbmr_model.fit(X_train, y_train_log)

```

c:\Users\aupho\AppData\Local\Programs\Python\Python311\Lib\site-packages\sklearn\model_selection_search.py:320: UserWarning: The total space of parameters 5400 is smaller than n_iter=1000000000. Running 5400 iterations. For exhaustive searches, use GridSearchCV.

```

warnings.warn(
Oit [00:00, ?it/s]

```

```

[368]: LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6, learning_rate=0.01,
                    max_depth=5, min_data_in_leaf=100, n_estimator=10, num_leaves=19,
                    random_state=42, verbose=-1)

```

```

[369]: evaluate_model(lgbmr_model, 'LightGBM regressor model', X_test, y_test,
↪y_logscale=True, save_directory='results/BoW/')

```

c:\Users\aupho\AppData\Local\Programs\Python\Python311\Lib\site-packages\lightgbm\basic.py:1218: UserWarning: Converting data to scipy sparse matrix.

```

_log_warning("Converting data to scipy sparse matrix.")

```

LightGBM regressor model's evaluation results:

```

- Mean squared error:      3.5161
- Root mean squared error: 1.8751
- Mean absolute error:     1.3708
- R2 error:                -0.1818

```

```

- F1 score:                0.1939
- Precision:               0.1322
- Recall:                  0.3636
- Accuracy:                0.3636
-----

```

```
[370]: lgbmr_model.get_params()
```

```
[370]: {'boosting_type': 'gbdt',
        'class_weight': None,
        'colsample_bytree': 1.0,
        'importance_type': 'split',
        'learning_rate': 0.01,
        'max_depth': 5,
        'min_child_samples': 20,
        'min_child_weight': 0.001,
        'min_split_gain': 0.0,
        'n_estimators': 100,
        'n_jobs': None,
        'num_leaves': 19,
        'objective': None,
        'random_state': 42,
        'reg_alpha': 0.0,
        'reg_lambda': 0.0,
        'subsample': 1.0,
        'subsample_for_bin': 200000,
        'subsample_freq': 0,
        'verbose': -1,
        'n_estimator': 10,
        'min_data_in_leaf': 100,
        'feature_fraction': 0.6,
        'bagging_fraction': 0.6}
```

1.3.6 Stacked model:

```
[371]: from mlxtend.regressor import StackingCVRegressor
```

Define component models:

```
[372]: trained_models = [linear_model, svr_model, rfr_model, xgb_model, lgbmr_model]
```

Define blended model:

```
[373]: stack_gen = StackingCVRegressor(regressors=tuple(trained_models),
                                       meta_regressor=trained_models[np.
                                       ↪argmin([mean_squared_error(np.exp(model.predict(X_test)), y_test) for model_
                                       ↪in trained_models]]),
```

```

                                use_features_in_secondary=True, n_jobs=-1,
↪random_state=42)
print(stack_gen)

```

```

StackingCVRegressor(meta_regressor=XGBRegressor(base_score=None, booster=None,
                                                callbacks=None,
                                                colsample_bylevel=None,
                                                colsample_bynode=None,
                                                colsample_bytree=None,
                                                device=None,
                                                early_stopping_rounds=None,
                                                enable_categorical=False,
                                                eta=0.01, eval_metric=None,
                                                feature_types=None, gamma=0.1,
                                                grow_policy=None,
                                                importance_type=None,
                                                interaction_constraints=None,
                                                learn...
                                                max_leaves=None,
                                                min_child_weight=10.0, missing=nan,
                                                monotone_constraints=None,
                                                multi_strategy=None,
                                                n_estimators=100, n_jobs=None,
                                                num_parallel_tree=None, ...),
                    LGBMRegressor(bagging_fraction=0.6,
                                    feature_fraction=0.6,
                                    learning_rate=0.01, max_depth=5,
                                    min_data_in_leaf=100,
                                    n_estimator=10, num_leaves=19,
                                    random_state=42, verbose=-1)),
                    use_features_in_secondary=True)

c:\Users\aupho\AppData\Local\Programs\Python\Python311\Lib\site-
packages\lightgbm\basic.py:1218: UserWarning: Converting data to scipy sparse
matrix.
    _log_warning("Converting data to scipy sparse matrix.")

```

```
[374]: stack_gen.fit(X_train, y_train_log)
```

```

[374]: StackingCVRegressor(meta_regressor=XGBRegressor(base_score=None, booster=None,
                                                callbacks=None,
                                                colsample_bylevel=None,
                                                colsample_bynode=None,
                                                colsample_bytree=None,
                                                device=None,
                                                early_stopping_rounds=None,
                                                enable_categorical=False,
                                                eta=0.01, eval_metric=None,

```



```

        feature_types=None, gamma=0.1,
        grow_policy=None,
        importance_type=None,
        interaction_constraints=None,
        learn...
max_leaves=None,
min_child_weight=10.0, missing=nan,
monotone_constraints=None,
multi_strategy=None,
n_estimators=100, n_jobs=None,
num_parallel_tree=None, ...),
LGBMRegressor(bagging_fraction=0.6,
               feature_fraction=0.6,
               learning_rate=0.01, max_depth=5,
               min_data_in_leaf=100,
               n_estimator=10, num_leaves=19,
               random_state=42, verbose=-1)),
use_features_in_secondary=True)

```

```

[375]: evaluate_model(stack_gen, 'Stacking model', X_test, y_test, y_logscale=True,
↳ save_directory='results/BoW/')

```

Stacking model's evaluation results:

```

- Mean squared error:      3.5149
- Root mean squared error: 1.8748
- Mean absolute error:     1.3796
- R2 error:                -0.1814
- F1 score:                0.1818
- Precision:               0.1299
- Recall:                  0.3030
- Accuracy:                0.3030

```

```

c:\Users\aupho\AppData\Local\Programs\Python\Python311\Lib\site-
packages\lightgbm\basic.py:1218: UserWarning: Converting data to scipy sparse
matrix.

```

```

    _log_warning("Converting data to scipy sparse matrix.")

```

```

[376]: stack_gen.get_params()

```

```

[376]: {'cv': 5,
'meta_regressor__objective': 'reg:squarederror',
'meta_regressor__base_score': None,
'meta_regressor__booster': None,
'meta_regressor__callbacks': None,
'meta_regressor__colsample_bylevel': None,
'meta_regressor__colsample_bynode': None,

```

```

'meta_regressor__colsample_bytree': None,
'meta_regressor__device': None,
'meta_regressor__early_stopping_rounds': None,
'meta_regressor__enable_categorical': False,
'meta_regressor__eval_metric': None,
'meta_regressor__feature_types': None,
'meta_regressor__gamma': 0.1,
'meta_regressor__grow_policy': None,
'meta_regressor__importance_type': None,
'meta_regressor__interaction_constraints': None,
'meta_regressor__learning_rate': None,
'meta_regressor__max_bin': None,
'meta_regressor__max_cat_threshold': None,
'meta_regressor__max_cat_to_onehot': None,
'meta_regressor__max_delta_step': None,
'meta_regressor__max_depth': 7,
'meta_regressor__max_leaves': None,
'meta_regressor__min_child_weight': 10.0,
'meta_regressor__missing': nan,
'meta_regressor__monotone_constraints': None,
'meta_regressor__multi_strategy': None,
'meta_regressor__n_estimators': 100,
'meta_regressor__n_jobs': None,
'meta_regressor__num_parallel_tree': None,
'meta_regressor__random_state': 42,
'meta_regressor__reg_alpha': 0.0,
'meta_regressor__reg_lambda': None,
'meta_regressor__sampling_method': None,
'meta_regressor__scale_pos_weight': None,
'meta_regressor__subsample': 0.5,
'meta_regressor__tree_method': None,
'meta_regressor__validate_parameters': None,
'meta_regressor__verbosity': None,
'meta_regressor__eta': 0.01,
'meta_regressor': XGBRegressor(base_score=None, booster=None, callbacks=None,
                                colsample_bylevel=None, colsample_bynode=None,
                                colsample_bytree=None, device=None, early_stopping_rounds=None,
                                enable_categorical=False, eta=0.01, eval_metric=None,
                                feature_types=None, gamma=0.1, grow_policy=None,
                                importance_type=None, interaction_constraints=None,
                                learning_rate=None, max_bin=None, max_cat_threshold=None,
                                max_cat_to_onehot=None, max_delta_step=None, max_depth=7,
                                max_leaves=None, min_child_weight=10.0, missing=nan,
                                monotone_constraints=None, multi_strategy=None, n_estimators=100,
                                n_jobs=None, num_parallel_tree=None, ...),
'multi_output': False,
'n_jobs': -1,

```

```

'pre_dispatch': '2*n_jobs',
'random_state': 42,
'refit': True,
'regressors': (ElasticNet(alpha=0.1, l1_ratio=0.2, max_iter=5000,
random_state=42),
SVR(C=10, epsilon=0.01, gamma=0.1),
RandomForestRegressor(max_depth=1000, max_features=100, min_samples_leaf=4,
min_samples_split=25, n_estimators=1024,
random_state=42),
XGBRegressor(base_score=None, booster=None, callbacks=None,
colsample_bylevel=None, colsample_bynode=None,
colsample_bytree=None, device=None, early_stopping_rounds=None,
enable_categorical=False, eta=0.01, eval_metric=None,
feature_types=None, gamma=0.1, grow_policy=None,
importance_type=None, interaction_constraints=None,
learning_rate=None, max_bin=None, max_cat_threshold=None,
max_cat_to_onehot=None, max_delta_step=None, max_depth=7,
max_leaves=None, min_child_weight=10.0, missing=nan,
monotone_constraints=None, multi_strategy=None, n_estimators=100,
n_jobs=None, num_parallel_tree=None, ...),
LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6, learning_rate=0.01,
max_depth=5, min_data_in_leaf=100, n_estimator=10,
num_leaves=19,
random_state=42, verbose=-1)),
'shuffle': True,
'store_train_meta_features': False,
'use_features_in_secondary': True,
'verbose': 0,
'elasticnet': ElasticNet(alpha=0.1, l1_ratio=0.2, max_iter=5000,
random_state=42),
'svr': SVR(C=10, epsilon=0.01, gamma=0.1),
'randomforestregressor': RandomForestRegressor(max_depth=1000,
max_features=100, min_samples_leaf=4,
min_samples_split=25, n_estimators=1024,
random_state=42),
'xgbregressor': XGBRegressor(base_score=None, booster=None, callbacks=None,
colsample_bylevel=None, colsample_bynode=None,
colsample_bytree=None, device=None, early_stopping_rounds=None,
enable_categorical=False, eta=0.01, eval_metric=None,
feature_types=None, gamma=0.1, grow_policy=None,
importance_type=None, interaction_constraints=None,
learning_rate=None, max_bin=None, max_cat_threshold=None,
max_cat_to_onehot=None, max_delta_step=None, max_depth=7,
max_leaves=None, min_child_weight=10.0, missing=nan,
monotone_constraints=None, multi_strategy=None, n_estimators=100,
n_jobs=None, num_parallel_tree=None, ...),
'lgbmregressor': LGBMRegressor(bagging_fraction=0.6, feature_fraction=0.6,

```

```

learning_rate=0.01,
        max_depth=5, min_data_in_leaf=100, n_estimator=10, num_leaves=19,
        random_state=42, verbose=-1),
'elasticnet__alpha': 0.1,
'elasticnet__copy_X': True,
'elasticnet__fit_intercept': True,
'elasticnet__l1_ratio': 0.2,
'elasticnet__max_iter': 5000,
'elasticnet__positive': False,
'elasticnet__precompute': False,
'elasticnet__random_state': 42,
'elasticnet__selection': 'cyclic',
'elasticnet__tol': 0.0001,
'elasticnet__warm_start': False,
'svr__C': 10,
'svr__cache_size': 200,
'svr__coef0': 0.0,
'svr__degree': 3,
'svr__epsilon': 0.01,
'svr__gamma': 0.1,
'svr__kernel': 'rbf',
'svr__max_iter': -1,
'svr__shrinking': True,
'svr__tol': 0.001,
'svr__verbose': False,
'randomforestregressor__bootstrap': True,
'randomforestregressor__ccp_alpha': 0.0,
'randomforestregressor__criterion': 'squared_error',
'randomforestregressor__max_depth': 1000,
'randomforestregressor__max_features': 100,
'randomforestregressor__max_leaf_nodes': None,
'randomforestregressor__max_samples': None,
'randomforestregressor__min_impurity_decrease': 0.0,
'randomforestregressor__min_samples_leaf': 4,
'randomforestregressor__min_samples_split': 25,
'randomforestregressor__min_weight_fraction_leaf': 0.0,
'randomforestregressor__monotonic_cst': None,
'randomforestregressor__n_estimators': 1024,
'randomforestregressor__n_jobs': None,
'randomforestregressor__oob_score': False,
'randomforestregressor__random_state': 42,
'randomforestregressor__verbose': 0,
'randomforestregressor__warm_start': False,
'xgbregressor__objective': 'reg:squarederror',
'xgbregressor__base_score': None,
'xgbregressor__booster': None,
'xgbregressor__callbacks': None,

```

```
'xgbregressor__colsample_bylevel': None,
'xgbregressor__colsample_bynode': None,
'xgbregressor__colsample_bytree': None,
'xgbregressor__device': None,
'xgbregressor__early_stopping_rounds': None,
'xgbregressor__enable_categorical': False,
'xgbregressor__eval_metric': None,
'xgbregressor__feature_types': None,
'xgbregressor__gamma': 0.1,
'xgbregressor__grow_policy': None,
'xgbregressor__importance_type': None,
'xgbregressor__interaction_constraints': None,
'xgbregressor__learning_rate': None,
'xgbregressor__max_bin': None,
'xgbregressor__max_cat_threshold': None,
'xgbregressor__max_cat_to_onehot': None,
'xgbregressor__max_delta_step': None,
'xgbregressor__max_depth': 7,
'xgbregressor__max_leaves': None,
'xgbregressor__min_child_weight': 10.0,
'xgbregressor__missing': nan,
'xgbregressor__monotone_constraints': None,
'xgbregressor__multi_strategy': None,
'xgbregressor__n_estimators': 100,
'xgbregressor__n_jobs': None,
'xgbregressor__num_parallel_tree': None,
'xgbregressor__random_state': 42,
'xgbregressor__reg_alpha': 0.0,
'xgbregressor__reg_lambda': None,
'xgbregressor__sampling_method': None,
'xgbregressor__scale_pos_weight': None,
'xgbregressor__subsample': 0.5,
'xgbregressor__tree_method': None,
'xgbregressor__validate_parameters': None,
'xgbregressor__verbosity': None,
'xgbregressor__eta': 0.01,
'lgbmregressor__boosting_type': 'gbdt',
'lgbmregressor__class_weight': None,
'lgbmregressor__colsample_bytree': 1.0,
'lgbmregressor__importance_type': 'split',
'lgbmregressor__learning_rate': 0.01,
'lgbmregressor__max_depth': 5,
'lgbmregressor__min_child_samples': 20,
'lgbmregressor__min_child_weight': 0.001,
'lgbmregressor__min_split_gain': 0.0,
'lgbmregressor__n_estimators': 100,
'lgbmregressor__n_jobs': None,
```

```
'lgbmregressor__num_leaves': 19,  
'lgbmregressor__objective': None,  
'lgbmregressor__random_state': 42,  
'lgbmregressor__reg_alpha': 0.0,  
'lgbmregressor__reg_lambda': 0.0,  
'lgbmregressor__subsample': 1.0,  
'lgbmregressor__subsample_for_bin': 200000,  
'lgbmregressor__subsample_freq': 0,  
'lgbmregressor__verbose': -1,  
'lgbmregressor__n_estimator': 10,  
'lgbmregressor__min_data_in_leaf': 100,  
'lgbmregressor__feature_fraction': 0.6,  
'lgbmregressor__bagging_fraction': 0.6}
```