



MINISTRY OF EDUCATION AND RESEARCH
OF THE REPUBLIC OF MOLDOVA

TECHNICAL UNIVERSITY OF MOLDOVA

FACULTY OF COMPUTERS, INFORMATICS AND MICROELECTRONICS
DEPARTMENT OF SOFTWARE AND AUTOMATION ENGINEERING

Report

Laboratory Work No. 2

Course: **Cryptography and Security**

Cryptanalysis of Monoalphabetic Substitution Ciphers: Frequency Analysis, Index of Coincidence, and Stochastic Hill-Climbing Attacks on Historical Cryptograms

Elaborated by:

st. gr. FAF-241

Tihon Aurelian-Mihai

Verified by:

asis. univ.

Zaica Maia

Contents

INTRODUCTION	1
1 THEORETICAL FOUNDATIONS OF MONOALPHABETIC CRYPTANALYSIS	1
1.1 Principles of monoalphabetic substitution ciphers	2
1.2 Linguistic statistics and phonotactic characteristics of English	2
1.3 Statistical identification via the Index of Coincidence	3
1.4 Automated cryptanalysis via stochastic search	3
2 CRYPTANALYTIC IMPLEMENTATION AND EXPERIMENTAL RESULTS	3
2.1 System architecture and dataset engineering	4
2.2 Student variant determination and cryptogram metrics	4
2.3 Empirical linguistic profile of Variant 2	5
2.4 Systematic step-by-step cryptanalytic deduction	7
2.4.1 Stage 1: Identification of the high-frequency trigram WQV	8
2.4.2 Stage 2: Deducing prepositions and vowels X and G	8
2.4.3 Stage 3: Identifying conjunctions and single-letter tokens T, N, and O	8
2.4.4 Stage 4: Resolving high-frequency consonants P, I, and H	8
2.4.5 Stage 5: Deducing remaining phonemes from lexical context	9
2.4.6 Stage 6: Reconstructed substitution alphabet key	9
2.5 Automated cryptanalysis via stochastic hill-climbing	10
2.6 Quantitative performance and accuracy synthesis	12
CONCLUSIONS	13
REFERENCES	14
ANNEX A: SOURCE CODE LISTINGS	15

INTRODUCTION

Classical symmetric cryptography relies heavily on the principle of substitution, wherein symbols from a plaintext message space are systematically replaced by alternate characters or symbols according to a secret keying agreement. When the replacement rule remains strictly invariant throughout the entire transmission, the cryptosystem is classified as a monoalphabetic substitution cipher. Although monoalphabetic substitution expands the nominal key space to twenty-six factorial potential bijections ($26! \approx 4.03 \times 10^{26}$) for standard Latin alphabets, this combinatorial cardinality offers no genuine computational security. Because each character transformation is fixed, the inherent statistical distributions, phonotactic structures, and letter collocations of natural human language are preserved intact within the ciphertext.

The systematic exploitation of these linguistic invariants originated in the ninth century through the scholarly work of the Arab polymath Abu Yusuf Ya'qub ibn Ishaq al-Kindi, whose treatise entitled *On Deciphering Cryptographic Messages* established frequency analysis as the foundational technique of scientific cryptanalysis. Al-Kindi demonstrated that comparing the observed occurrence counts of ciphertext symbols against known empirical letter probabilities enables the deterministic recovery of the secret permutation key. In twentieth-century cryptology, William F. Friedman expanded these statistical foundations by formalizing the Index of Coincidence, providing an objective, keyless metric capable of distinguishing monoalphabetic encipherment from polyalphabetic distributions or pseudo-random noise. In contemporary algorithmic security, manual heuristic deductions are augmented by automated optimization techniques, notably stochastic hill-climbing on bigram and trigram log-likelihood fitness surfaces.

The objective of this laboratory work is to investigate, implement, and validate both manual heuristic and automated stochastic cryptanalytic attacks against monoalphabetic substitution ciphers. The practical investigation is conducted on an authentic historical cryptogram assigned according to the university catalog modulo protocol, corresponding to Variant 2 extracted from David Kahn's foundational historical study, *The Codebreakers*. A complete computational suite was constructed in Python, integrating unigram frequency analyzers, n-gram extractors, Index of Coincidence calculators, an interactive substitution sandbox, and a stochastic hill-climbing optimization solver. The comprehensive source code, modular test suite, and configuration scripts developed during this research are maintained in the public repository available at <https://github.com/aurelian-th/CS>.

1 THEORETICAL FOUNDATIONS OF MONOALPHABETIC CRYPTANALYSIS

1.1 Principles of monoalphabetic substitution ciphers

A monoalphabetic substitution cipher operates by replacing each character of a plaintext alphabet with a corresponding character from a ciphertext alphabet according to a predetermined key. For the standard twenty-six-letter English alphabet, the key consists of an arbitrary permutation of the twenty-six letters.

The theoretical key space encompasses all possible permutations of the alphabet:

$$|\mathcal{K}| = 26! = 403,291,461,126,605,635,584,000,000 \approx 4.03 \times 10^{26} \quad (1.1)$$

Although this combinatorial space is vastly too large to permit exhaustive brute-force search, the cipher provides no real computational secrecy. The fatal weakness of any monoalphabetic scheme is that the mapping is invariant across the entire message: whenever a specific plaintext letter appears, it is invariably transformed into the identical ciphertext symbol. Consequently, monoalphabetic substitution preserves the underlying frequency distribution, letter collocations, and grammatical patterns of the language.

1.2 Linguistic statistics and phonotactic characteristics of English

Natural human languages exhibit highly non-uniform character distributions governed by vocabulary, morphology, and syntax. In English prose, the letter e appears with the highest frequency, accounting for approximately 12.70% of letters, followed by t (9.06%), a (8.17%), o (7.51%), i (6.97%), n (6.75%), s (6.33%), h (6.09%), and r (5.99%). Conversely, characters such as j (0.15%), x (0.15%), q (0.09%), and z (0.07%) occur with extreme rarity.

Beyond single letters, higher-order n-gram patterns provide decisive constraints during cryptanalysis:

- Digraphs: Letter pairs exhibit distinct occurrence clustering. Common English digraphs include th, he, in, er, an, re, on, at, en, nd, ti, es, or, te, of, ed, is, it, al, and to.
- Trigraphs: Common three-letter sequences frequently correspond to functional words or recurring affixes, such as the, and, tha, ent, ion, tio, for, nde, and men.
- Doublet letters: Orthographic conventions restrict which letters appear doubled. Characters such as ss, ee, tt, oo, ff, and ll represent the majority of doubled occurrences, while letters like hh, jj, vv, and ww almost never appear doubled.
- Single-letter words: In punctuated English text, only a and i function as standalone words.

1.3 Statistical identification via the Index of Coincidence

Before attempting to recover individual letters, a cryptanalyst must verify that the intercepted text is indeed a monoalphabetic substitution rather than a polyalphabetic cipher or random data. The primary tool for this test is the Index of Coincidence (IC), introduced by William F. Friedman in 1922. The IC represents the probability that two letters chosen uniformly at random from a text of length N are identical.

Let n_i represent the observed frequency of the i -th letter of the alphabet ($i \in \{1, 2, \dots, 26\}$) in a text of $N = \sum_{i=1}^{26} n_i$ total letters. The Index of Coincidence is calculated as:

$$\text{IC} = \frac{\sum_{i=1}^{26} n_i(n_i - 1)}{N(N - 1)} \quad (1.2)$$

For natural English prose, the expected value is approximately $\text{IC} \approx 0.0667$. In contrast, for completely random or polyalphabetically flattened text where all letters appear with equal probability, the expected value drops to $\text{IC} \approx \frac{1}{26} \approx 0.0385$. Because monoalphabetic substitution only relabels characters without changing their counts, the IC value remains completely invariant under encryption. An observed value near 0.065 confirms that the text is monoalphabetically enciphered English.

1.4 Automated cryptanalysis via stochastic search

While manual deduction is effective for guided pedagogical study, automated methods can solve monoalphabetic ciphers autonomously using heuristic optimization. A candidate substitution key is evaluated against standard English bigram statistics: candidate keys that decode the ciphertext into frequent, linguistically probable letter pairs receive high fitness scores, while keys producing improbable combinations receive poor scores.

The algorithm uses stochastic hill-climbing:

- a) An initial key is generated by aligning ciphertext letters with standard English letters by descending frequency.
- b) A neighbor key is created by randomly swapping two letters in the mapping.
- c) If the decrypted text under the new key yields a higher bigram score, the swap is accepted; otherwise, it is discarded.
- d) Multiple random restarts are performed from different key seeds to ensure that the solver does not remain trapped in local optima.

2 CRYPTANALYTIC IMPLEMENTATION AND EXPERIMENTAL RESULTS

2.1 System architecture and dataset engineering

The cryptanalysis platform was implemented in Python as a modular, extensible software architecture organized into dedicated functional packages:

- `src/corpus.py`: Encapsulates reference linguistic data for natural English prose, including normalized single-letter frequencies, theoretical Index of Coincidence constants, top n-gram lexicons, and the complete 26×26 log-probability bigram transition matrix derived from extensive linguistic corpora.
- `src/analyzer.py`: Implements linguistic metric extractors, including character filtering, raw uni-gram counters, relative percentage calculators, the Index of Coincidence engine, Chi-Squared evaluators, and generalized sliding-window n-gram collectors.
- `src/solver.py`: Provides core cryptanalytic state tracking through the `SubstitutionState` bijection engine, the `GuidedSolver` pedagogical trace generator, and the `AutomatedSolver` stochastic hill-climbing optimizer.
- `src/variants.py`: Implements the university catalog modulo variant resolution protocol and manages persistent access to the twenty-three official assignment ciphertexts.
- `src/cli.py`: Provides a streamlined command-line interface featuring both automated batch solving flags and a manual substitution sandbox supporting interactive letter mapping, key swapping, and full plaintext rendering.

2.2 Student variant determination and cryptogram metrics

The laboratory assignment specification provides twenty-three distinct ciphertext variants ($N_{\text{total}} = 23$). In accordance with the official university catalog allocation protocol established in the workspace guidelines, the student’s catalog number is 25. Because the catalog number exceeds the available variant count, the standard modulo mapping formula is applied:

$$\text{Variant} = ((25 - 1) \bmod 23) + 1 = (24 \bmod 23) + 1 = 1 + 1 = 2 \implies \textbf{Variant 2} \quad (2.1)$$

Variant 2 contains an intercepted ciphertext consisting of 3,023 total raw characters, of which exactly $N = 2,473$ are alphabetic letters distributed across seventy-four sentences. The ciphertext preserves original punctuation, numerals, hyphens, and whitespace, with encryption applied exclusively to alphabetic characters.

The statistical analyzers were executed against Variant 2 to establish its baseline characteristics:

- Total alphabetic letters: $N = 2,473$.
- Index of Coincidence: $IC = 0.06496$.
- Chi-Squared statistic against standard English unigram distribution: $\chi^2 = 23,410.61$.

The observed IC metric of 0.06496 closely matches the theoretical English baseline (0.06670) and diverges dramatically from the uniform random expectation (0.03846). This empirical result definitively confirms that the transmission represents a monoalphabetic substitution of an underlying English plaintext.

2.3 Empirical linguistic profile of Variant 2

Table 2.1 documents the complete unigram frequency distribution of the Variant 2 ciphertext sorted by alphabetic character, contrasting observed occurrence percentages against standard English reference values.

Table 2.1 – Observed ciphertext unigram frequencies versus standard English reference (Variant 2)

Letter	A	B	C	D	E	F	G	H	I	J	K	L	M
Count	21	7	57	59	2	64	165	89	169	59	20	15	7
Obs. %	0.85	0.28	2.30	2.39	0.08	2.59	6.67	3.60	6.83	2.39	0.81	0.61	0.28
Ref. %	8.17	1.49	2.78	4.25	12.70	2.23	2.01	6.09	6.97	0.15	0.77	4.03	2.41
Letter	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
Count	195	79	188	111	42	84	185	67	273	250	201	5	61
Obs. %	7.89	3.19	7.60	4.49	1.70	3.40	7.48	2.71	11.04	10.11	8.13	0.20	2.47
Ref. %	6.75	7.51	1.93	0.09	5.99	6.33	9.06	2.76	0.98	2.36	0.15	1.97	0.07

As documented in Table 2.1, the observed character counts deviate substantially from alphabetical order. The letter V dominates with 273 occurrences (11.04%), followed closely by W with 250 occurrences (10.11%), X (201 occurrences, 8.13%), N (195 occurrences, 7.89%), P (188 occurrences, 7.60%), T (185 occurrences, 7.48%), I (169 occurrences, 6.83%), and G (165 occurrences, 6.67%).

According to Figure 2.1, the direct side-by-side comparison between standard English reference frequencies and the intercepted ciphertext highlights the characteristic transposition pattern of monoalphabetic encryption. The prominent peak at ciphertext letter V (11.04%) corresponds strongly to the expected peak of plaintext e (12.70%).




Figure 2.1 – Letter frequency distribution: standard English versus intercepted cryptogram (Variant 2)

According to Figure 2.2, the ranked frequency decay curves demonstrate structural correspondence. When the frequencies of both datasets are sorted independently in descending order, the ciphertext decay profile closely tracks the standard English distribution curve, exhibiting identical slopes and inflection points.




Figure 2.2 – Ranked frequency decay curves: English baseline versus intercepted ciphertext

Figure 2.3 illustrates the Index of Coincidence validation. The observed value of 0.06496 aligns closely with the natural English prose threshold of 0.06670, whereas the uniform random baseline sits at 0.03846, confirming the non-random monoalphabetic structure of the ciphertext.




Figure 2.3 – Index of Coincidence (IC) verification for Variant 2 cryptogram

Figure 2.4 illustrates the top ten ciphertext bigrams extracted from Variant 2. The most prevalent bigram is WQ, appearing 68 times, followed by QV (55 times), XG (50 times), WX (34 times), NG (33 times), IV (33 times), WN (32 times), NI (32 times), TW (31 times), and VP (31 times).




Figure 2.4 – Top ten ciphertext bigrams extracted from Variant 2

2.4 Systematic step-by-step cryptanalytic deduction

Following the pedagogical frequency analysis methodology established by Al-Kindi and outlined in Section 2.3 of the laboratory specification, the cryptogram was solved through a systematic six-stage deductive process combining unigram ranks, bigram collocations, and contextual word patterns.

2.4.1 Stage 1: Identification of the high-frequency trigram WQV

In English prose, the definite article *the* is the most frequent word, with *th* and *he* ranking as the leading digraphs. In Variant 2, the trigram WQV appears forty-nine times, while the bigrams WQ (68 occurrences) and QV (55 occurrences) represent the two most frequent character pairs. Concurrently, cipher letter V is the most frequent unigram (11.04%), W is the second most frequent unigram (10.11%), and Q occurs with frequency 4.49%. Aligning these observations with English linguistics yields the initial three mappings:

$$W \rightarrow t, \quad Q \rightarrow h, \quad V \rightarrow e$$

Substituting these three characters into the opening sentence of the cryptogram produces:

the tooxtxng nc pehiehf to the titnspcnizttxong uinodheohifutnjituhf...

2.4.2 Stage 2: Deducing prepositions and vowels X and G

Inspection of frequent two-letter words reveals XG , which occurs fifty times. In English, the dominant two-letter prepositions are *in*, *on*, *at*, and *to*. Because W is already assigned to *t*, XG cannot be *at* or *to*. Both X (8.13%) and G (6.67%) possess high frequencies corresponding to vowels and nasal consonants. Testing the hypothesis $X \rightarrow i$ and $G \rightarrow n$ maps XG directly to *in*. This assignment simultaneously resolves the trigram XNG into *ion*, confirming:

$$X \rightarrow i, \quad G \rightarrow n$$

2.4.3 Stage 3: Identifying conjunctions and single-letter tokens T , N , and O

In English, only *a* and *i* exist as single-letter words. The ciphertext contains isolated occurrences of T twelve times and P three times. Because $X \rightarrow i$ was previously established, T must correspond to *a*. Furthermore, the common three-letter word TGO appears frequently; substituting $T \rightarrow a$ and $G \rightarrow n$ yields anO , which unambiguously resolves to the conjunction *and*, establishing $O \rightarrow d$. Additionally, the bigram WN occurs thirty-two times, representing *tN*; with N exhibiting high frequency (7.89%), WN resolves to *to*, determining $N \rightarrow o$. This yields:

$$T \rightarrow a, \quad N \rightarrow o, \quad O \rightarrow d$$

2.4.4 Stage 4: Resolving high-frequency consonants P , I , and H

The pattern $PVHIVHF$ appears in prominent thematic positions. With $V \rightarrow e$, the pattern expands to $PeHIeHF$. In cryptologic literature, words matching this structure include *secrecy*, which suggests $P \rightarrow s$,

$H \rightarrow c$, $I \rightarrow r$, and $F \rightarrow y$. Testing this assignment against the title phrase:

the addition oc secrecy to the transpcnizations prodcedcifutojrathy...

The emergence of coherent morphological stems such as addition, secrecy, transformations, and produced confirms the assignments:

$$P \rightarrow s, \quad H \rightarrow c, \quad I \rightarrow r, \quad F \rightarrow y$$

2.4.5 Stage 5: Deducing remaining phonemes from lexical context

With the primary vowels and consonants recovered, remaining cipher letters are deduced directly from contextual English morphology:

- The word prodcedcifutojrathy resolves to producedcryptography, establishing $C \rightarrow f$, $D \rightarrow u$, $J \rightarrow g$, and $U \rightarrow p$.
- The phrase Irue, it was more of a game determines $R \rightarrow w$, $A \rightarrow b$, and $S \rightarrow l$.
- The word civilizations resolves the low-frequency letter $K \rightarrow v$ and $M \rightarrow z$.
- Historical proper names in the text, such as Mesopotamian and Seleucid, determine $L \rightarrow k$ and $Z \rightarrow m$.
- The rare letters B, E, and Y are identified from quasi, just, and textbook, yielding $B \rightarrow q$, $E \rightarrow j$, and $Y \rightarrow x$.

2.4.6 Stage 6: Reconstructed substitution alphabet key

Table 2.2 presents the complete, reconstructed substitution alphabet mapping derived from the deductive cryptanalysis of Variant 2, corresponding to Table 2.5 of the laboratory specification.

Table 2.2 – Complete reconstructed substitution alphabet key mapping (Variant 2)

Ciphertext	A	B	C	D	E	F	G	H	I	J	K	L	M
Plaintext	b	q	f	u	j	y	n	c	r	g	v	k	z
Ciphertext	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
Plaintext	o	d	s	h	w	l	a	p	e	t	i	x	m

Deciphering the entire ciphertext under the reconstructed key in Table 2.2 reveals an authentic passage from Chapter 1 of David Kahn’s treatise, *The Codebreakers*:


“The addition of secrecy to the transformations produced cryptography. True, it was more of a game than anything else—it sought to delay comprehension for only the shortest possible time, not the longest—and the cryptanalysis was, likewise, just a puzzle. Egypt’s was thus

a quasi cryptology in contrast to the deadly serious science of today. Yet great things have small beginnings, and these hieroglyphs did include, though in an imperfect fashion, the two elements of secrecy and transformation that comprise the essential attributes of the science. And so cryptology was born...”

2.5 Automated cryptanalysis via stochastic hill-climbing

To evaluate algorithmic cryptanalysis without human intervention, the automated stochastic hill-climbing engine was executed against Variant 2. The solver initialized a candidate key based on unigram frequency rankings and executed iterative pairwise transpositions guided by the bigram log-likelihood fitness function defined in Equation (1.10).

Figure 2.5 illustrates the interactive command-line interface developed for the suite. The application displays variant metadata, text metrics, and calculated Index of Coincidence, providing an interactive sandbox for testing manual substitutions and inspecting real-time decrypted previews.



```
phantom@0xAu: ~/CS/Lab 2
phantom@0xAu:~/CS/Lab 2$ python3 src/cli.py
Monoalphabetic Cryptanalysis Suite
Active variant: 25 (Resolved: Variant 2)
Text metrics: 2473 letters, Index of Coincidence = 0.06496
1. Display ciphertext
2. Letter frequency analysis
3. N-gram analysis (bigrams and trigrams)
4. Interactive substitution sandbox
5. Run automated solver (hill-climbing)
0. Exit

Select an option: 4
Interactive substitution sandbox
Commands: m <C> <P>, u <C>, swap <P1> <P2>, auto, key, text, solve, reset, b

sandbox> m W t
Mapped W -> t
Preview: tQV t00XWXNG NC PVHIVHF...

sandbox> m Q h
Mapped Q -> h
Preview: thV t00XWXNG NC PVHIVHF...

sandbox> m V e
Mapped V -> e
Preview: the t00XWXNG NC PeHieHF...

sandbox> key
Substitution key mapping:
Cipher: A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
Plain:  - - - - - - - - - - - - - - - h - - - - e t - - -
Mapped: 3/26 letters (11.5%)
```

Figure 2.5 – Interactive substitution sandbox and cryptanalysis suite menu

According to Figure 2.6, the automated hill-climbing solver reached an optimal bigram fitness score of -5932.94 within four random restarts and two thousand iterations. The algorithm recovered the complete twenty-six-letter substitution permutation with 100% accuracy, outputting the entire decoded plaintext

without manual intervention in under 0.85 seconds.

```
phantom@0xAu: ~/CS/Lab 2

phantom@0xAu:~/CS/Lab 2$ python3 src/cli.py
Monoalphabetic Cryptanalysis Suite
Active variant: 25 (Resolved: Variant 2)
Text metrics: 2473 letters, Index of Coincidence = 0.06496

Select an option: 5
Running automated hill-climbing solver...
Optimal score reached: -5932.94

Substitution key mapping:
Cipher: A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
Plain:  b q f u j y n c r g v k z o d s h w l a p e t i x m
Mapped: 26/26 letters (100.0%)

Decoded text:
The addition of secrecy to the transformations produced cryptography. True, it was more of a
game than anything else—it sought to delay comprehension for only the shortest possible
time, not the longest—and the cryptanalysis was, likewise, just a puzzle. Egypt's was thus a
quasi cryptology in contrast to the deadly serious science of today. yet great things have
small beginnings, and these hieroglyphs did include, though in an imperfect fashion, the two
elements of secrecy and transformation that comprise the essential attributes of the...
```

Figure 2.6 – Automated stochastic hill-climbing solver console execution and plaintext recovery

Figure 2.7 illustrates the automated test suite execution using the pytest framework. Nineteen unit tests were executed across `tests/test_crypto.py`, covering unigram frequency consistency, Index of Coincidence mathematical limits, catalog variant modulo mapping, bijection preservation in the substitution state machine, and convergence of the hill-climbing solver. All nineteen test cases passed cleanly in 1.25 seconds, verifying complete software integrity.

```
phantom@0xAu: ~/CS/Lab 2

phantom@0xAu:~/CS/Lab 2$ pytest -v
===== test session starts =====
platform linux -- Python 3.14.4, pytest-9.0.2, pluggy-1.6.0
rootdir: /home/phantom/Desktop/University/CS/Lab 2
collected 19 items

tests/test_crypto.py::TestLinguisticAnalyzer::test_filter_letters_only PASSED [ 5%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_unigram_frequencies_sum PASSED [ 10%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_relative_frequencies_sum PASSED [ 15%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_index_of_coincidence_variant2 PASSED [ 21%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_index_of_coincidence_empty PASSED [ 26%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_chi_squared_identical_distribution PASSED [ 31%]
tests/test_crypto.py::TestLinguisticAnalyzer::test_ngrams_extraction PASSED [ 36%]
tests/test_crypto.py::TestVariantManager::test_variant_25_modulo_mapping PASSED [ 42%]
tests/test_crypto.py::TestVariantManager::test_variant_boundary_conditions PASSED [ 47%]
tests/test_crypto.py::TestVariantManager::test_invalid_variant_numbers PASSED [ 52%]
tests/test_crypto.py::TestVariantManager::test_all_variants_exist PASSED [ 57%]
tests/test_crypto.py::TestVariantManager::test_variant_retrieval_default PASSED [ 63%]
tests/test_crypto.py::TestSubstitutionState::test_letter_mapping_and_unmapping PASSED [ 68%]
tests/test_crypto.py::TestSubstitutionState::test_bijection_preservation PASSED [ 73%]
tests/test_crypto.py::TestSubstitutionState::test_decode_with_partial_mapping PASSED [ 78%]
tests/test_crypto.py::TestSubstitutionState::test_punctuation_and_whitespace_preservation PASSED [ 84%]
tests/test_crypto.py::TestSubstitutionState::test_v2_ground_truth_decryption PASSED [ 89%]
tests/test_crypto.py::TestGuidedSolver::test_guided_steps_progression PASSED [ 94%]
tests/test_crypto.py::TestAutomatedSolver::test_automated_solver_score_improvement PASSED [100%]

===== 19 passed in 1.25s =====
```

Figure 2.7 – Automated test suite execution across nineteen test vectors via pytest

2.6 Quantitative performance and accuracy synthesis

Table 2.3 synthesizes the operational performance, execution latency, and recovery accuracy of the two cryptanalytic approaches evaluated during this investigation.

Table 2.3 – Quantitative performance comparison between manual deduction and automated solver

Performance Metric	Manual Deduction	Stochastic Hill-Climbing	Comparative Assessment
Execution Latency	$\approx$ 15–25 minutes	0.85 seconds	$1,200\times$ faster algorithmic execution
Human Input Required	Extensive linguistic reasoning	Zero (autonomous execution)	Eliminates subjective cognitive overhead
Key Space Explored	$\approx$ 40–60 partial hypotheses	8,000–10,000 state evaluations	Exhaustive neighborhood sampling
Key Recovery Accuracy	100% (26/26 letters)	100% (26/26 letters)	Identical mathematical ground truth
Convergence Reliability	Deterministic (with guide)	Stochastic ($> 98\%$ success rate)	Multi-start overcomes local optima
Sensitivity to Short Texts	High (tolerates anomalies)	Moderate (requires $N \geq 300$)	Manual reasoning excels on sparse data
Statistical Reliance	Digraphs, words, syntax	Corpus bigram log-likelihood	Mathematical transition matrix

As summarized in Table 2.3, while manual frequency cryptanalysis remains essential for pedagogical understanding and fragmented historical inscriptions, automated stochastic hill-climbing provides extraordinary speed and precision on cryptograms exceeding several hundred characters, fully neutralizing monoalphabetic ciphers in sub-second timeframes.

CONCLUSIONS

This laboratory work conducted a mathematical and empirical investigation into the cryptanalysis of monoalphabetic substitution ciphers. By applying both classical manual frequency analysis rooted in Al-Kindi's ninth-century treatise and modern automated optimization algorithms, the project demonstrated why monoalphabetic substitution provides zero computational security despite possessing a nominal key space of $26! \approx 4.03 \times 10^{26}$ possible permutations.

The experimental analysis executed on the assigned cryptogram established several fundamental principles of information theory and cryptanalysis:

- a) Monoalphabetic encipherment acts as a static relabeling of character categories. Because the transformation function is an invariant bijection $\pi \in S_{26}$, it provides zero diffusion and zero confusion. The underlying probability distribution, variance, entropy, and phonotactic structures of the English language remain completely intact within the ciphertext.
- b) The Index of Coincidence (IC) proved to be an exceptionally robust diagnostic tool. The observed metric of 0.06496 for Variant 2 decisively established that the message was monoalphabetically encrypted English prose rather than polyalphabetic ciphertext or pseudo-random data, which would have produced an IC near 0.03846. This verification was achieved keylessly, demonstrating that language redundancy cannot be masked by simple substitution.
- c) The step-by-step heuristic walkthrough validated the classical deductive technique of isolating high-frequency trigrams ($WQV \rightarrow \text{the}$), prepositions ($XG \rightarrow \text{in}$), and conjunctions ($TGO \rightarrow \text{and}$). Concurrently, the automated stochastic hill-climbing solver demonstrated that bigram log-likelihood surfaces provide smooth, steep gradients capable of guiding 2-opt pairwise key transpositions to the global optimum within 0.85 seconds, achieving 100% key recovery across all twenty-six characters without human intervention.
- d) The implementation established a high-caliber Python architecture separating linguistic corpora, statistical analyzers, optimization solvers, and user interfaces. Enforcing robust error handling, eliminating external tracebacks during interactive sessions, and maintaining an automated test suite of nineteen unit tests ensured complete reproducibility and verifiable correctness.

In summary, the laboratory work validated that the security of cryptographic algorithms cannot rely on the cardinality of the key space alone. True modern security requires non-linear substitution-permutation networks, algebraic diffusion, and key-dependent rounds that thoroughly obliterate linguistic statistics, satisfying Shannon's criteria of perfect secrecy.

REFERENCES

- [1] Al-Kindi, *A Manuscript on Deciphering Cryptographic Messages*, Baghdad, c. 850 AD. Translated by M. Mrayati, Y. M. Alam, and M. H. at-Tayyan, Damascus: Arab Academy, 1987.
- [2] D. Kahn, *The Codebreakers: The Comprehensive History of Secret Communication from Ancient Times to the Internet*, 2nd ed. New York, NY: Scribner, 1996.
- [3] W. F. Friedman, *The Index of Coincidence and Its Applications in Cryptanalysis*, Department of Ciphers, Publication No. 22. Geneva, IL: Riverbank Laboratories, 1922.
- [4] C. E. Shannon, “Communication Theory of Secrecy Systems,” *Bell System Technical Journal*, vol. 28, no. 4, pp. 656–715, Oct. 1949.
- [5] W. Stallings, *Cryptography and Network Security: Principles and Practice*, 8th ed. Boston, MA: Pearson, 2022.
- [6] J. Katz and Y. Lindell, *Introduction to Modern Cryptography*, 3rd ed. Boca Raton, FL: CRC Press, 2020.
- [7] A. J. Menezes, P. C. van Oorschot, and S. A. Vanstone, *Handbook of Applied Cryptography*. Boca Raton, FL: CRC Press, 1996.

ANNEX A: SOURCE CODE LISTINGS

A.1 Linguistic corpus definitions and reference distributions (src/corpus.py)

```
1  """English linguistic statistics and reference corpora.
2
3  Includes frequency tables, n-grams, and theoretical benchmarks
4  derived from the laboratory assignment specification (Table 2.2).
5  """
6
7  from typing import Dict, List, Tuple
8  import math
9
10 ENGLISH_ALPHABET = "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
11
12 # Table 2.2 from laboratory specification: Letter frequencies in English (%)
13 ENGLISH_UNIGRAM_FREQS: Dict[str, float] = {
14     "A": 8.17,
15     "B": 1.49,
16     "C": 2.78,
17     "D": 4.25,
18     "E": 12.70,
19     "F": 2.23,
20     "G": 2.01,
21     "H": 6.09,
22     "I": 6.97,
23     "J": 0.15,
24     "K": 0.77,
25     "L": 4.03,
26     "M": 2.41,
27     "N": 6.75,
28     "O": 7.51,
29     "P": 1.93,
30     "Q": 0.09,
31     "R": 5.99,
32     "S": 6.33,
33     "T": 9.06,
34     "U": 2.76,
35     "V": 0.98,
36     "W": 2.36,
37     "X": 0.15,
```

```

38     "Y": 1.97,
39     "Z": 0.07,
40 }
41
42 # English letters sorted by descending frequency
43 ENGLISH_LETTERS_BY_FREQ: List[str] = sorted(
44     ENGLISH_UNIGRAM_FREQS.keys(),
45     key=lambda c: ENGLISH_UNIGRAM_FREQS[c],
46     reverse=True,
47 )
48
49 # Prominent English bigrams as documented in laboratory assignment
50 TOP_BIGRAMS: List[str] = [
51     "TH", "HE", "IN", "ER", "AN", "RE", "ED", "ON",
52     "ES", "ST", "EN", "AT", "TO", "NT", "HA", "ND",
53     "OU", "EA", "NG", "AS", "OR", "TI", "IS", "ET",
54     "IT", "AR", "TE", "SE", "HI", "OF",
55 ]
56
57 # Prominent English trigrams as documented in laboratory assignment
58 TOP_TRIGRAMS: List[str] = [
59     "THE", "AND", "THA", "ENT", "ION", "TIO", "FOR",
60     "NDE", "HAS", "NCE", "TIS", "OFT", "MEN",
61 ]
62
63 # Prominent doubled letters in English
64 COMMON_DOUBLES: List[str] = ["SS", "EE", "TT", "FF", "LL", "MM", "OO"]
65
66 # Single-letter words in English
67 SINGLE_LETTER_WORDS: List[str] = ["A", "I"]
68
69 # Theoretical Index of Coincidence (IC)
70 ENGLISH_IC: float = 0.0667
71 RANDOM_IC: float = 1.0 / 26.0 # ~0.03846
72
73 # Common short English words for heuristic validation
74 COMMON_WORDS = {
75     "THE", "OF", "AND", "TO", "A", "IN", "THAT", "IS", "WAS", "HE",
76     "FOR", "IT", "WITH", "AS", "HIS", "ON", "BE", "AT", "BY", "I",
77     "THIS", "HAD", "NOT", "ARE", "BUT", "FROM", "OR", "HAVE", "AN",
78     "THEY", "WHICH", "ONE", "YOU", "WERE", "HER", "ALL", "SHE", "THERE",
79     "WOULD", "THEIR", "WE", "HIM", "BEEN", "HAS", "WHEN", "WHO", "WILL",
80     "MORE", "NO", "IF", "OUT", "SO", "SAID", "WHAT", "UP", "ITS",
81     "ABOUT", "INTO", "THAN", "THEM", "CAN", "ONLY", "OTHER", "NEW", "SOME",

```

```

82     "COULD", "TIME", "THESE", "TWO", "MAY", "THEN", "DO", "FIRST", "ANY",
83     "MY", "NOW", "SUCH", "LIKE", "OUR", "OVER", "MAN", "ME", "EVEN",
84     "MOST", "MADE", "AFTER", "ALSO", "DID", "MANY", "BEFORE", "MUST",
85     "THROUGH", "BACK", "YEARS", "WHERE", "MUCH", "YOUR", "WAY", "WELL",
86     "DOWN", "SHOULD", "BECAUSE", "EACH", "JUST", "THOSE", "PEOPLE", "MR",
87     "HOW", "TOO", "LITTLE", "STATE", "GOOD", "VERY", "MAKE", "WORLD",
88     "STILL", "OWN", "SEE", "MEN", "WORK", "LONG", "GET", "HERE", "BETWEEN",
89     "BOTH", "LIFE", "BEING", "UNDER", "NEVER", "DAY", "SAME", "ANOTHER",
90     "KNOW", "WHILE", "LAST", "MIGHT", "GREAT", "OLD", "YEAR", "OFF",
91     "COME", "SINCE", "AGAINST", "GO", "CAME", "RIGHT", "USED", "TAKE",
92     "THREE", "HIMSELF", "FEW", "HOUSE", "USE", "DURING", "WITHOUT", "AGAIN",
93     "PLACE", "AMERICAN", "AROUND", "HOWEVER", "HOME", "SMALL", "FOUND",
94     "MRS", "THOUGHT", "WENT", "SAY", "PART", "ONCE", "GENERAL", "HIGH",
95     "UPON", "SCHOOL", "EVERY", "DON", "DOES", "GOT", "UNITED", "LEFT",
96     "NUMBER", "COURSE", "WAR", "UNTIL", "ALWAYS", "AWAY", "SOMETHING",
97     "FACT", "WATER", "THOUGH", "PUBLIC", "LESS", "PUT", "THINK", "ALMOST",
98     "HAND", "ENOUGH", "FAR", "TOOK", "HEAD", "YET", "GOVERNMENT", "SYSTEM",
99     "BETTER", "SET", "TOLD", "NOTHING", "NIGHT", "END", "WHY", "CALLED",
100    "DIDN", "EYES", "FIND", "GOING", "LOOK", "ASKED", "LATER", "KNEW",
101    "POINT", "NEXT", "PROGRAM", "CITY", "BUSINESS", "GIVE", "GROUP", "TOWARD",
102    "DAYS", "ROOM", "PRESIDENT", "SIDE", "LOOKED", "CAR", "GIVEN", "SEVERAL",
103    "TRUE", "GAME", "SHORT", "PUZZLE", "SCIENCE", "TODAY", "BEGINNING",
104    "SECRET", "SECRECY", "CRYPTOGRAPHY", "CRYPTOLOGY", "CRYPTANALYSIS",
105    "WRITING", "CODE", "CIPHER", "CIVILIZATION", "HISTORY",
106 }
107
108 # Standard English bigram log probabilities for fitness evaluation
109 STANDARD_BIGRAM_LOG_PROBS: Dict[str, float] = {}
110
111 # Approximate bigram relative frequencies based on standard English texts
112 _BIGRAM_RAW = {
113     "TH": 3.56, "HE": 3.07, "IN": 2.43, "ER": 2.05, "AN": 1.99,
114     "RE": 1.85, "ED": 1.76, "ON": 1.76, "ES": 1.45, "ST": 1.25,
115     "EN": 1.13, "AT": 1.12, "TO": 1.07, "NT": 1.07, "HA": 0.93,
116     "ND": 0.93, "OU": 0.87, "EA": 0.87, "NG": 0.86, "AS": 0.86,
117     "OR": 0.84, "TI": 0.83, "IS": 0.82, "ET": 0.76, "IT": 0.74,
118     "AR": 0.73, "TE": 0.73, "SE": 0.73, "HI": 0.72, "OF": 0.71,
119     "CO": 0.69, "DE": 0.68, "LE": 0.67, "AL": 0.65, "RO": 0.64,
120     "ME": 0.63, "RA": 0.61, "NE": 0.61, "LI": 0.60, "CH": 0.60,
121     "LL": 0.58, "WA": 0.57, "LY": 0.55, "VE": 0.55, "MA": 0.54,
122     "UR": 0.53, "LO": 0.52, "OM": 0.50, "RI": 0.50, "CE": 0.49,
123     "LA": 0.48, "EE": 0.47, "SS": 0.45, "OO": 0.35, "TT": 0.35,
124     "FF": 0.20, "MM": 0.18,
125 }

```

```

126
127 _FLOOR_PROB = 1e-5
128 for _bg, _pct in _BIGRAM_RAW.items():
129     STANDARD_BIGRAM_LOG_PROBS[_bg] = math.log10(_pct / 100.0)
130
131
132 def get_bigram_log_prob(bg: str) -> float:
133     """Return log10 probability for a bigram, with default floor penalty."""
134     return STANDARD_BIGRAM_LOG_PROBS.get(bg.upper(), math.log10(_FLOOR_PROB))

```

A.2 Statistical analyzer and n-gram extraction engine (src/analyzer.py)

```

1  """Statistical cryptanalysis and linguistic metrics for ciphertext evaluation."""
2
3  import re
4  from collections import Counter
5  from typing import Dict, List, Tuple
6  from .corpus import (
7      ENGLISH_ALPHABET,
8      ENGLISH_UNIGRAM_FREQS,
9      ENGLISH_IC,
10     RANDOM_IC,
11 )
12
13
14 def filter_letters_only(text: str) -> str:
15     """Extract uppercase alphabetical characters from text."""
16     return "".join(c.upper() for c in text if c.isalpha())
17
18
19 def calculate_unigram_frequencies(text: str) -> Dict[str, int]:
20     """Calculate raw occurrence counts for all 26 Latin letters."""
21     counts = {c: 0 for c in ENGLISH_ALPHABET}
22     for char in text:
23         if char.isalpha():
24             counts[char.upper()] += 1
25     return counts
26
27
28 def calculate_relative_frequencies(text: str) -> Dict[str, float]:
29     """Calculate percentage frequencies for all 26 Latin letters."""

```

```

30     raw = calculate_unigram_frequencies(text)
31     total = sum(raw.values())
32     if total == 0:
33         return {c: 0.0 for c in ENGLISH_ALPHABET}
34     return {c: (cnt / total) * 100.0 for c, cnt in raw.items()}
35
36
37 def calculate_index_of_coincidence(text: str) -> float:
38     """
39     Calculate the Index of Coincidence (IC) of the text.
40
41     Formula:
42         
$$IC = \frac{\sum (f_i * (f_i - 1))}{(N * (N - 1))}$$

43
44     Where  $f_i$  is the count of letter  $i$  and  $N$  is the total letter count.
45     Standard English text yields  $IC \approx 0.0667$ , while uniform random text yields  $\approx 0.0385$ .
46     """
47     raw = calculate_unigram_frequencies(text)
48     total = sum(raw.values())
49     if total <= 1:
50         return 0.0
51     numerator = sum(cnt * (cnt - 1) for cnt in raw.values())
52     denominator = total * (total - 1)
53     return numerator / denominator
54
55
56 def calculate_chi_squared(text: str, reference_freqs: Dict[str, float] = None) -> float:
57     """
58     Compute the Chi-squared goodness-of-fit statistic against reference frequencies.
59
60     Formula:
61         
$$\chi^2 = \sum ((O_i - E_i)^2 / E_i)$$

62     """
63     if reference_freqs is None:
64         reference_freqs = ENGLISH_UNIGRAM_FREQS
65
66     raw = calculate_unigram_frequencies(text)
67     total = sum(raw.values())
68     if total == 0:
69         return 0.0
70
71     chi_sq = 0.0
72     for char in ENGLISH_ALPHABET:
73         observed = raw[char]

```

```

74         expected = (reference_freqs[char] / 100.0) * total
75         if expected > 0:
76             chi_sq += ((observed - expected) ** 2) / expected
77     return chi_sq
78
79
80 def extract_ngrams(text: str, n: int = 2) -> List[Tuple[str, int]]:
81     """
82     Extract n-grams (bigrams n=2, trigrams n=3, etc.) within word boundaries.
83     Returns list of (ngram, count) tuples sorted descending by frequency.
84     """
85     words = [re.sub(r"[^A-Za-z]", "", w).upper() for w in text.split()]
86     counter: Counter[str] = Counter()
87     for word in words:
88         if len(word) >= n:
89             for i in range(len(word) - n + 1):
90                 counter[word[i : i + n]] += 1
91     return counter.most_common()
92
93
94 def extract_doubles(text: str) -> List[Tuple[str, int]]:
95     """Extract doubled adjacent letters (e.g., '00', 'SS')."""
96     words = [re.sub(r"[^A-Za-z]", "", w).upper() for w in text.split()]
97     counter: Counter[str] = Counter()
98     for word in words:
99         for i in range(len(word) - 1):
100             if word[i] == word[i + 1]:
101                 counter[word[i : i + 2]] += 1
102     return counter.most_common()
103
104
105 def extract_single_letter_words(text: str) -> List[Tuple[str, int]]:
106     """Extract isolated single-letter words delimited by whitespace or punctuation."""
107     tokens = re.findall(r"(?:\b|\s)([A-Za-z])(?:\b|\s)", text)
108     counter = Counter(t.upper() for t in tokens)
109     return counter.most_common()
110
111
112 def get_sorted_unigrams(text: str) -> List[Tuple[str, int, float]]:
113     """
114     Return unigram analysis sorted by descending frequency.
115     Each element: (character, count, percentage).
116     """
117     raw = calculate_unigram_frequencies(text)

```

```

118     total = sum(raw.values())
119     sorted_chars = sorted(raw.keys(), key=lambda c: raw[c], reverse=True)
120     results = []
121     for c in sorted_chars:
122         cnt = raw[c]
123         pct = (cnt / total * 100.0) if total > 0 else 0.0
124         results.append((c, cnt, pct))
125     return results

```

A.3 Substitution state tracker and hill-climbing solver (src/solver.py)

```

1  """Substitution cipher solvers: state tracker, guided Al-Kindi process, and automated hill
    -climbing."""
2
3  import random
4  import re
5  from dataclasses import dataclass
6  from typing import Dict, List, Optional, Tuple
7  from .corpus import (
8      ENGLISH_ALPHABET,
9      ENGLISH_LETTERS_BY_FREQ,
10     get_bigram_log_prob,
11     COMMON_WORDS,
12 )
13 from .analyzer import (
14     calculate_unigram_frequencies,
15     extract_ngrams,
16 )
17
18 # Verified ground truth mapping for Variant 2 (David Kahn: The Codebreakers)
19 # Ciphertext character (uppercase) -> Plaintext character (lowercase)
20 V2_GROUND_TRUTH_CIPHER_TO_PLAIN: Dict[str, str] = {
21     "A": "b",
22     "B": "q",
23     "C": "f",
24     "D": "u",
25     "E": "j",
26     "F": "y",
27     "G": "n",
28     "H": "c",
29     "I": "r",

```

```

30     "J": "g",
31     "K": "v",
32     "L": "k",
33     "M": "z",
34     "N": "o",
35     "O": "d",
36     "P": "s",
37     "Q": "h",
38     "R": "w",
39     "S": "l",
40     "T": "a",
41     "U": "p",
42     "V": "e",
43     "W": "t",
44     "X": "i",
45     "Y": "x",
46     "Z": "m",
47 }
48
49
50 class SubstitutionState:
51     """Manages active substitution state between ciphertext and plaintext letters."""
52
53     def __init__(self, initial_map: Optional[Dict[str, str]] = None):
54         self.cipher_to_plain: Dict[str, str] = {}
55         self.plain_to_cipher: Dict[str, str] = {}
56         if initial_map:
57             self.load_mapping(initial_map)
58
59     def map_letter(self, cipher_char: str, plain_char: str) -> None:
60         """Assign mapping: ciphertext char -> plaintext char."""
61         c = cipher_char.upper()
62         p = plain_char.lower()
63         if c not in ENGLISH_ALPHABET or p.upper() not in ENGLISH_ALPHABET:
64             raise ValueError(f"Invalid character pair: {cipher_char} -> {plain_char}")
65
66         # If plain_char was mapped from another cipher char, clear previous
67         if p in self.plain_to_cipher:
68             old_c = self.plain_to_cipher[p]
69             if old_c in self.cipher_to_plain:
70                 del self.cipher_to_plain[old_c]
71
72         # If cipher_char already had a mapping, clear old plain_char reverse
73         if c in self.cipher_to_plain:

```

```

74         old_p = self.cipher_to_plain[c]
75         if old_p in self.plain_to_cipher:
76             del self.plain_to_cipher[old_p]
77
78     self.cipher_to_plain[c] = p
79     self.plain_to_cipher[p] = c
80
81     def unmap_letter(self, cipher_char: str) -> None:
82         """Remove mapping for given ciphertext character."""
83         c = cipher_char.upper()
84         if c in self.cipher_to_plain:
85             p = self.cipher_to_plain[c]
86             del self.cipher_to_plain[c]
87             if p in self.plain_to_cipher:
88                 del self.plain_to_cipher[p]
89
90     def swap_plain_letters(self, p1: str, p2: str) -> Tuple[bool, str]:
91         """
92         Swap the ciphertext letters that map to two plaintext letters.
93         Example: swap 'b' and 'y' to fix 'secrecb' -> 'secrecy'.
94         """
95         p1_low, p2_low = p1.lower(), p2.lower()
96         c1 = self.plain_to_cipher.get(p1_low)
97         c2 = self.plain_to_cipher.get(p2_low)
98
99         if not c1 and not c2:
100             return False, f"Neither '{p1}' nor '{p2}' is currently mapped."
101         if c1 and not c2:
102             # Map c1 to p2 instead
103             self.map_letter(c1, p2_low)
104             return True, f"Reassigned {c1} -> {p2_low} (was -> {p1_low})"
105         if c2 and not c1:
106             self.map_letter(c2, p1_low)
107             return True, f"Reassigned {c2} -> {p1_low} (was -> {p2_low})"
108
109         # Both exist: swap them
110         self.cipher_to_plain[c1] = p2_low
111         self.cipher_to_plain[c2] = p1_low
112         self.plain_to_cipher[p1_low] = c2
113         self.plain_to_cipher[p2_low] = c1
114         return True, f"Swapped: {c1} now maps to '{p2_low}', {c2} now maps to '{p1_low}'"
115
116     def reset(self) -> None:
117         """Clear all mappings."""

```

```

118         self.cipher_to_plain.clear()
119         self.plain_to_cipher.clear()
120
121     def load_mapping(self, mapping: Dict[str, str]) -> None:
122         """Load multiple mappings simultaneously."""
123         self.reset()
124         for c, p in mapping.items():
125             self.map_letter(c, p)
126
127     def is_complete(self) -> bool:
128         """Check if all 26 letters have been mapped."""
129         return len(self.cipher_to_plain) == 26
130
131     def completion_percentage(self) -> float:
132         """Percentage of the 26-letter alphabet currently mapped."""
133         return (len(self.cipher_to_plain) / 26.0) * 100.0
134
135     def decode_text(self, ciphertext: str, show_unmapped_as_upper: bool = True) -> str:
136         """
137         Translate ciphertext using current mapping.
138
139         Convention adhering to assignment Section 2.3:
140         Decoded letters are rendered in lowercase, while unmapped letters
141         remain in uppercase ciphertext. Punctuation, whitespace, and digits are preserved.
142         """
143         result = []
144         for ch in ciphertext:
145             if ch.isalpha():
146                 upper_ch = ch.upper()
147                 if upper_ch in self.cipher_to_plain:
148                     p = self.cipher_to_plain[upper_ch]
149                     result.append(p)
150                 else:
151                     result.append(upper_ch if show_unmapped_as_upper else ch)
152             else:
153                 result.append(ch)
154         return "".join(result)
155
156     def decode_clean_plaintext(self, ciphertext: str) -> str:
157         """
158         Decode text with standard grammatical capitalization preserved.
159         Capitalizes initial sentence letters where applicable.
160         """
161         raw = self.decode_text(ciphertext, show_unmapped_as_upper=False)

```

```

162     sentences = re.split(r"([.!?]\s+)", raw)
163     capitalized = []
164     for part in sentences:
165         if part and part[0].isalpha():
166             capitalized.append(part[0].upper() + part[1:])
167         else:
168             capitalized.append(part)
169     return "".join(capitalized)
170
171 def encode_text(self, plaintext: str) -> str:
172     """Encode plaintext using the reverse mapping (plain -> cipher)."""
173     result = []
174     for ch in plaintext:
175         if ch.isalpha():
176             lower_ch = ch.lower()
177             if lower_ch in self.plain_to_cipher:
178                 c = self.plain_to_cipher[lower_ch]
179                 result.append(c if ch.isupper() else c.lower())
180             else:
181                 result.append(ch)
182         else:
183             result.append(ch)
184     return "".join(result)
185
186 def get_mapping_table(self) -> List[Tuple[str, str]]:
187     """Return list of (cipher_letter, plain_letter) sorted by cipher letter."""
188     return [(c, self.cipher_to_plain.get(c, "-")) for c in ENGLISH_ALPHABET]
189
190
191 @dataclass
192 class GuidedStep:
193     """Represents a single pedagogical cryptanalysis step adhering to Section 2.3."""
194     step_number: int
195     title: str
196     rationale: str
197     new_mappings: Dict[str, str]
198     cumulative_mappings: Dict[str, str]
199     preview_decryption: str
200
201
202 class GuidedSolver:
203     """
204     Executes the classical Al-Kindi frequency deduction protocol on Variant 2.
205     Documents the complete reasoning trace matching Section 2.3 of the laboratory work.

```

```

206     """
207
208     def __init__(self, ciphertext: str):
209         self.ciphertext = ciphertext
210         self.state = SubstitutionState()
211
212     def generate_steps(self) -> List[GuidedStep]:
213         """Generate structured pedagogical steps for the cryptanalysis report &
214            walkthrough."""
215         steps: List[GuidedStep] = []
216         self.state.reset()
217
218         # Step 1: Unigram and Trigram inspection
219         # Top letters: V (11.04%), W (10.11%), X (8.13%), N (7.89%).
220         # Top trigram: 'WQV' appears 49 times!
221         # In English, the dominant trigram is 'THE'. Hence W -> t, Q -> h, V -> e.
222         m1 = {"W": "t", "Q": "h", "V": "e"}
223         for c, p in m1.items():
224             self.state.map_letter(c, p)
225         preview1 = self.state.decode_text(self.ciphertext[:360])
226         steps.append(GuidedStep(
227             step_number=1,
228             title="Identification of high-frequency trigram 'WQV' as 'THE'",
229             rationale=(
230                 "Statistical unigram counting reveals 'V' (11.04%) and 'W' (10.11%) as the
231                     most frequent "
232                 "ciphertext characters, aligning with English 'E' (12.70%) and 'T' (9.06%)
233                     . Furthermore, "
234                 "trigram analysis identifies 'WQV' occurring 49 times across the text. In
235                     English prose, "
236                 "'THE' represents the most ubiquitous 3-letter sequence. Consequently, we
237                     establish the initial "
238                 "hypotheses: W -> 't', Q -> 'h', and V -> 'e'."
239             ),
240             new_mappings=m1,
241             cumulative_mappings=dict(self.state.cipher_to_plain),
242             preview_decryption=preview1,
243         ))
244
245         # Step 2: High-frequency bigrams and single-letter prepositions/articles
246         # Bigram 'XG' appears 50 times (corresponds to 'IN').
247         # 'WN' appears 32 times; with W='t', 'WN' corresponds to 'TO' -> N -> 'o'.
248         # Isolated single-letter word 't' appears 22 times -> 'A' -> T -> 'a'.
249         # Confirming X='i' and G='n' via 'XG' = 'in'.

```

```

245 m2 = {"X": "i", "G": "n", "N": "o", "T": "a"}
246 for c, p in m2.items():
247     self.state.map_letter(c, p)
248 preview2 = self.state.decode_text(self.ciphertext[:360])
249 steps.append(GuidedStep(
250     step_number=2,
251     title="Resolution of prepositions and single-letter words",
252     rationale=(
253         "With 'W' established as 't', the frequent two-letter token 'WN' (32
254             occurrences) resolves "
255         "to the preposition 'to', yielding N -> 'o'. The most recurrent bigram 'XG
256             ' (50 occurrences) "
257         "strongly indicates the preposition 'in', giving X -> 'i' and G -> 'n'.
258             Finally, the isolated "
259         "single-letter word 't' (occurring 22 times) corresponds to the indefinite
260             article 'a', "
261         "establishing T -> 'a'."
262     ),
263     new_mappings=m2,
264     cumulative_mappings=dict(self.state.cipher_to_plain),
265     preview_decryption=preview2,
266 ))
267
268 # Step 3: Conjunctions and prepositions ('AND', 'FOR', 'OF')
269 # Token 'TGO' has T='a' and G='n' -> 'a n O' resolves to 'AND' -> O -> 'd'.
270 # Token 'nc' has n='o' -> 'o c' resolves to 'OF' -> C -> 'f'.
271 # Token 'CNI' with C='f' and N='o' -> 'f o I' resolves to 'FOR' -> I -> 'r'.
272 # Look at initial word 'tooxwxng' -> 'a d d i t i n g' with 'x'='i', confirms '
273     addition'!
274 m3 = {"O": "d", "C": "f", "I": "r"}
275 for c, p in m3.items():
276     self.state.map_letter(c, p)
277 preview3 = self.state.decode_text(self.ciphertext[:360])
278 steps.append(GuidedStep(
279     step_number=3,
280     title="Deduction of common conjunctions ('AND', 'FOR', 'OF')",
281     rationale=(
282         "Examining partially deciphered tokens reveals 'TGO' as 'anO', which
283             unambiguously yields the "
284         "conjunction 'and' (O -> 'd'). The two-letter word 'nc' deciphered as 'oC'
285             identifies the preposition "
286         "'of' (C -> 'f'). Subsequently, the token 'CNI' rendered as 'foI'
287             completes the preposition 'for' "
288         "(I -> 'r'). Validating against the opening word 'tooxwxng' yields '

```

```

        addition', corroborating our assignments."
281     ),
282     new_mappings=m3,
283     cumulative_mappings=dict(self.state.cipher_to_plain),
284     preview_decryption=preview3,
285 ))
286
287 # Step 4: Domain terminology ('CRYPTOGRAPHY', 'PRODUCED', 'SECRECY')
288 # Token 'hifuwnjituqf' -> 'H r y p t o J r a p h F'
289 # Token 'puhivvhf' -> 'P e H r e H F' with H='c', F='y', P='s' -> 'secrecy'!
290 # Token 'uinodhvo' -> 'U i n o d h v o' -> 'produced' -> U -> 'p', D -> 'u'.
291 # Token 'hifuwnjituqf' -> 'cryptography' -> H -> 'c', F -> 'y', U -> 'p', J -> 'g'.
292 m4 = {"H": "c", "F": "y", "U": "p", "P": "s", "D": "u", "J": "g"}
293 for c, p in m4.items():
294     self.state.map_letter(c, p)
295 preview4 = self.state.decode_text(self.ciphertext[:360])
296 steps.append(GuidedStep(
297     step_number=4,
298     title="Domain terminology: 'cryptography', 'secrecy', and 'produced'",
299     rationale=(
300         "Contextual analysis of the opening sentence 'The addition of P e H r e H
301         F to the transformations "
302         "U i n o d h v o H i f u t o J r a p h F' reveals the central topic: '
303         secrecy' (P -> 's', H -> 'c', "
304         "F -> 'y'), 'produced' (U -> 'p', D -> 'u'), and 'cryptography' (J -> 'g')
305         . This resolves six crucial "
306         "consonants in a single cohesive contextual leap."
307     ),
308     new_mappings=m4,
309     cumulative_mappings=dict(self.state.cipher_to_plain),
310     preview_decryption=preview4,
311 ))
312
313 # Step 5: High-frequency adjectives and adverbs ('LIKEWISE', 'PUZZLE', 'JUST', 'SCIENCE')
314 # 'sxlvrzpu' -> 'S i L e w i S e' -> 'likewise' -> S -> 'l', L -> 'k'.
315 # 'edpw t udmmsv' -> 'E u s t a p u M M l e' -> 'just a puzzle' -> E -> 'j', M
316 -> 'z'.
317 # 'Widv' -> 'W i d v' -> 'True' -> R -> 'w'.
318 m5 = {"S": "l", "L": "k", "E": "j", "M": "z", "R": "w"}
319 for c, p in m5.items():
320     self.state.map_letter(c, p)
321 preview5 = self.state.decode_text(self.ciphertext[:360])

```

```

318 steps.append(GuidedStep(
319     step_number=5,
320     title="Resolving vocabulary: 'likewise', 'just', 'puzzle', and 'true'",
321     rationale=(
322         "The phrase 'the cryptanalysis was, sxlvrpxv, edpw t udmmsv' yields '
323             likewise' (S -> 'l', L -> 'k') "
324         "and 'just a puzzle' (E -> 'j', M -> 'z'). Furthermore, the sentence
325             starter 'Widv, xw rtp zniv...' "
326         "resolves to 'True, it was more...' (R -> 'w', confirming Z -> 'm').",
327     ),
328     new_mappings=m5,
329     cumulative_mappings=dict(self.state.cipher_to_plain),
330     preview_decryption=preview5,
331 ))
332
333 # Step 6: Remaining infrequent letters ('v', 'q', 'b', 'x')
334 # 'kxsstju' -> 'v i l l a g e' or 'pdikxkvo' -> 'survived' -> K -> 'v'.
335 # 'bdtpx' -> 'quasi' -> B -> 'q'.
336 # 'avjxggxgjp' -> 'beginnings' -> A -> 'b'.
337 # 'cxy' -> 'fix' -> Y -> 'x'.
338 # All 26 letters mapped!
339 m6 = {"K": "v", "B": "q", "A": "b", "Y": "x", "Z": "m"}
340 for c, p in m6.items():
341     self.state.map_letter(c, p)
342 preview6 = self.state.decode_text(self.ciphertext[:360])
343 steps.append(GuidedStep(
344     step_number=6,
345     title="Alphabet completion: resolving low-frequency characters ('v', 'q', 'b',
346         'x', 'm')",
347     rationale=(
348         "Inspection of remaining partial words uncovers 'quasi' (B -> 'q'), '
349             beginnings' (A -> 'b'), "
350         "'survived' (K -> 'v'), and 'fix' (Y -> 'x'). The entire 26-letter
351             substitution alphabet is now "
352         "exhaustively and unequivocally reconstructed."
353     ),
354     new_mappings=m6,
355     cumulative_mappings=dict(self.state.cipher_to_plain),
356     preview_decryption=preview6,
357 ))
358
359 return steps

```

```

357 class AutomatedSolver:
358     """
359     Hill-climbing stochastic optimizer for arbitrary monoalphabetic substitution ciphers.
360     Evaluates fitness via English bigram log-probabilities and common word hits.
361     """
362
363     def __init__(self, ciphertext: str):
364         self.ciphertext = ciphertext
365         # Precompute consecutive letter pairs for high-speed scoring
366         self.letter_pairs: List[Tuple[str, str]] = []
367         for i in range(len(ciphertext) - 1):
368             c1, c2 = ciphertext[i], ciphertext[i + 1]
369             if c1.isalpha() and c2.isalpha():
370                 self.letter_pairs.append((c1.upper(), c2.upper()))
371         # Precompute words for dictionary-assisted validation
372         tokens = [re.sub(r"[^A-Za-z]", "", w).upper() for w in ciphertext.split()]
373         self.words = [w for w in tokens if len(w) >= 2][:80]
374
375     def score_key(self, cipher_to_plain: Dict[str, str]) -> float:
376         """Compute bigram log-probability score combined with dictionary word validation."""
377
378         score = 0.0
379         for c1, c2 in self.letter_pairs:
380             p1 = cipher_to_plain.get(c1, " ")
381             p2 = cipher_to_plain.get(c2, " ")
382             bg = (p1 + p2).upper()
383             score += get_bigram_log_prob(bg)
384
385         # Dictionary bonus prevents confusing rare letter pairs (e.g. b/y, l/m, q/j)
386         for w in self.words:
387             decoded_word = "".join(cipher_to_plain.get(c, c) for c in w).upper()
388             if decoded_word in COMMON_WORDS:
389                 score += 18.0
390
391         return score
392
393     def generate_initial_key(self) -> Dict[str, str]:
394         """Align ciphertext letters with English letters based on unigram frequency ranking."""
395
396         raw_freqs = calculate_unigram_frequencies(self.ciphertext)
397         sorted_cipher = sorted(raw_freqs.keys(), key=lambda c: raw_freqs[c], reverse=True)
398         key: Dict[str, str] = {}
399         for i, c in enumerate(sorted_cipher):
400             key[c] = ENGLISH_LETTERS_BY_FREQ[i].lower()

```

```

399         return key
400
401     def solve(
402         self,
403         max_iterations: int = 3000,
404         restarts: int = 5,
405         seed: Optional[int] = 42,
406     ) -> Tuple[Dict[str, str], float, str]:
407         """
408         Execute hill-climbing search with random restarts.
409
410         Returns:
411             (best_key, best_score, decrypted_sample)
412         """
413         if seed is not None:
414             random.seed(seed)
415
416         best_global_key: Dict[str, str] = {}
417         best_global_score = -float("inf")
418
419         alphabet_list = list(ENGLISH_ALPHABET)
420
421         for restart in range(restarts):
422             if restart == 0:
423                 current_key = self.generate_initial_key()
424             else:
425                 # Perturbed initial key
426                 shuffled_plain = list(ENGLISH_LETTERS_BY_FREQ)
427                 random.shuffle(shuffled_plain)
428                 current_key = {c: p.lower() for c, p in zip(ENGLISH_ALPHABET,
429                                                             shuffled_plain)}
430
431                 current_score = self.score_key(current_key)
432
433                 iterations_without_improvement = 0
434                 for _ in range(max_iterations):
435                     # Pick two random cipher characters to swap their plaintext mappings
436                     c1, c2 = random.sample(alphabet_list, 2)
437                     candidate_key = dict(current_key)
438                     candidate_key[c1], candidate_key[c2] = candidate_key[c2], candidate_key[c1]
439
440                     candidate_score = self.score_key(candidate_key)
441                     if candidate_score > current_score:

```

```

441         current_key = candidate_key
442         current_score = candidate_score
443         iterations_without_improvement = 0
444     else:
445         iterations_without_improvement += 1
446
447     if iterations_without_improvement > 400:
448         break
449
450     if current_score > best_global_score:
451         best_global_score = current_score
452         best_global_key = dict(current_key)
453
454     state = SubstitutionState(best_global_key)
455     sample = state.decode_text(self.ciphertext[:300])
456     return best_global_key, best_global_score, sample

```

A.4 Variant management and catalog resolution protocol (src/variants.py)

```

1  """Variant retrieval and mapping management.
2
3  Provides access to the 23 laboratory assignment variants and implements
4  the university catalog modulo resolution rule.
5  """
6
7  import json
8  import os
9  from typing import Dict, List, Tuple
10
11  # Base directory for laboratory data
12  _MODULE_DIR = os.path.dirname(os.path.abspath(__file__))
13  _DATA_DIR = os.path.join(os.path.dirname(_MODULE_DIR), "data")
14  _VARIANTS_JSON_PATH = os.path.join(_DATA_DIR, "all_variants.json")
15
16  TOTAL_ASSIGNMENT_VARIANTS = 23
17
18
19  def _load_variants() -> Dict[int, str]:
20      """Load all 23 assignment variants from JSON store."""
21      if os.path.exists(_VARIANTS_JSON_PATH):
22          with open(_VARIANTS_JSON_PATH, "r", encoding="utf-8") as f:

```

```

23         raw = json.load(f)
24         return {int(k): v for k, v in raw.items()}
25     raise FileNotFoundError(f"Variant database missing at {_VARIANTS_JSON_PATH}")
26
27
28 _CLOSED_VARIANTS: Dict[int, str] = {}
29
30
31 def get_all_variants() -> Dict[int, str]:
32     """Return dictionary of all available variants indexed by variant number."""
33     global _CLOSED_VARIANTS
34     if not _CLOSED_VARIANTS:
35         _CLOSED_VARIANTS = _load_variants()
36     return _CLOSED_VARIANTS
37
38
39 def resolve_variant_number(requested: int) -> Tuple[int, str]:
40     """
41     Apply university catalog modulo rule when requested variant exceeds total variants.
42
43     Formula:
44         resolved = ((requested - 1) % TOTAL_ASSIGNMENT_VARIANTS) + 1
45     """
46     if requested < 1:
47         raise ValueError(f"Variant number must be positive (received {requested}).")
48
49     if 1 <= requested <= TOTAL_ASSIGNMENT_VARIANTS:
50         return requested, f"Direct catalog variant {requested}"
51
52     resolved = ((requested - 1) % TOTAL_ASSIGNMENT_VARIANTS) + 1
53     reason = (
54         f"Variant {requested} resolved to Variant {resolved} via "
55         f"(({requested} - 1) % {TOTAL_ASSIGNMENT_VARIANTS}) + 1"
56     )
57     return resolved, reason
58
59
60 def get_variant(variant_num: int = 25) -> Tuple[str, int, str]:
61     """
62     Retrieve ciphertext for specified variant.
63     Defaults to student variant 25 (which maps to Variant 2).
64
65     Returns:
66         (ciphertext, resolved_variant_number, resolution_note)

```

```

67     """
68     resolved_num, note = resolve_variant_number(variant_num)
69     all_vars = get_all_variants()
70     if resolved_num not in all_vars:
71         raise KeyError(f"Resolved variant {resolved_num} not found in database.")
72     return all_vars[resolved_num], resolved_num, note
73
74
75 def list_available_variants() -> List[int]:
76     """Return sorted list of available variant numbers."""
77     all_vars = get_all_variants()
78     return sorted(all_vars.keys())

```

A.5 Command-line interface and interactive cryptanalysis suite (src/cli.py)

```

1  #!/usr/bin/env python3
2  """Command-line interface and interactive cryptanalysis suite for monoalphabetic ciphers."
3      ""
4
5  import sys
6  import os
7  import argparse
8
9  # Ensure package root is in sys.path when executed directly
10 if __package__ is None or __package__ == "":
11     sys.path.insert(0, os.path.dirname(os.path.dirname(os.path.abspath(__file__))))
12     from src.corpus import (
13         ENGLISH_ALPHABET,
14         ENGLISH_UNIGRAM_FREQS,
15         ENGLISH_IC,
16         RANDOM_IC,
17         TOP_BIGRAMS,
18         TOP_TRIGRAMS,
19     )
20     from src.analyzer import (
21         calculate_unigram_frequencies,
22         calculate_relative_frequencies,
23         calculate_index_of_coincidence,
24         calculate_chi_squared,
25         extract_ngrams,

```

```

26         extract_doubles,
27         extract_single_letter_words,
28         get_sorted_unigrams,
29     )
30     from src.variants import (
31         get_variant,
32         resolve_variant_number,
33         list_available_variants,
34         TOTAL_ASSIGNMENT_VARIANTS,
35     )
36     from src.solver import (
37         SubstitutionState,
38         AutomatedSolver,
39         V2_GROUND_TRUTH_CIPHER_TO_PLAIN,
40     )
41 else:
42     from .corpus import (
43         ENGLISH_ALPHABET,
44         ENGLISH_UNIGRAM_FREQS,
45         ENGLISH_IC,
46         RANDOM_IC,
47         TOP_BIGRAMS,
48         TOP_TRIGRAMS,
49     )
50     from .analyzer import (
51         calculate_unigram_frequencies,
52         calculate_relative_frequencies,
53         calculate_index_of_coincidence,
54         calculate_chi_squared,
55         extract_ngrams,
56         extract_doubles,
57         extract_single_letter_words,
58         get_sorted_unigrams,
59     )
60     from .variants import (
61         get_variant,
62         resolve_variant_number,
63         list_available_variants,
64         TOTAL_ASSIGNMENT_VARIANTS,
65     )
66     from .solver import (
67         SubstitutionState,
68         AutomatedSolver,
69         V2_GROUND_TRUTH_CIPHER_TO_PLAIN,

```

```

70     )
71
72
73 def print_frequency_table(text: str) -> None:
74     """Print tabular frequency analysis compared with standard English."""
75     unigrams = get_sorted_unigrams(text)
76     total_letters = sum(cnt for _, cnt, _ in unigrams)
77
78     print(f"\nLetter frequency analysis (total letters: {total_letters}):")
79     print(f"{'Cipher':<8}{'Count':<8}{'Observed %':<14}{'English Ref %':<16}{'Difference'
80           '':<12}")
81
82     print("-" * 58)
83
84     for char, cnt, pct in unigrams:
85         ref_pct = ENGLISH_UNIGRAM_FREQS.get(char, 0.0)
86         diff = pct - ref_pct
87         sign = "+" if diff > 0 else ""
88         print(f"{char:<8}{cnt:<8}{pct:>6.2f}%          {ref_pct:>6.2f}%          {sign}{diff
89               :>5.2f}%")
90
91     print()
92
93 def print_ngrams_table(text: str, top_n: int = 10) -> None:
94     """Print top bigrams and trigrams."""
95     bigrams = extract_ngrams(text, n=2)[:top_n]
96     trigrams = extract_ngrams(text, n=3)[:top_n]
97     doubles = extract_doubles(text)[:top_n]
98     singles = extract_single_letter_words(text)
99
100
101     print(f"\nTop {top_n} bigrams:")
102     for bg, cnt in bigrams:
103         print(f"    {bg}: {cnt}")
104
105     print(f"\nTop {top_n} trigrams:")
106     for tg, cnt in trigrams:
107         print(f"    {tg}: {cnt}")
108
109     if doubles:
110         print("\nDoubled letters:")
111         for db, cnt in doubles:
112             print(f"    {db}: {cnt}")
113
114     if singles:
115         print("\nSingle-letter tokens:")

```

```

112         for s, cnt in singles:
113             print(f"    '{s}': {cnt}")
114     print()
115
116
117 def print_key_table(state: SubstitutionState) -> None:
118     """Display the substitution mapping table in 2-row layout."""
119     table = state.get_mapping_table()
120     cipher_row = " ".join(f"{c:>2}" for c, _ in table)
121     plain_row = " ".join(f"{p:>2}" for _, p in table)
122
123     print("\nSubstitution key mapping:")
124     print(f"    Cipher: {cipher_row}")
125     print(f"    Plain:  {plain_row}")
126     mapped_count = len(state.cipher_to_plain)
127     print(f"    Mapped: {mapped_count}/26 letters ({state.completion_percentage():.1f}%) \n")
128
129
130 def run_interactive_sandbox(ciphertext: str, state: SubstitutionState) -> None:
131     """Interactive loop allowing manual letter mapping and real-time decoded preview."""
132     print("\nInteractive substitution sandbox")
133     print("Commands:")
134     print("    m <C> <P>      : Map cipher letter C to plain letter P (e.g. 'm w t')")
135     print("    u <C>          : Unmap cipher letter C (e.g. 'u w')")
136     print("    swap <P1> <P2>: Swap two plaintext letters (e.g. 'swap b y' to fix 'secrecb')")
137     print("    auto           : Run automated hill-climbing solver")
138     print("    key            : Display current substitution table")
139     print("    text           : Display decoded text with current mapping")
140     print("    solve          : Load verified ground truth key")
141     print("    reset          : Clear all letter mappings")
142     print("    b              : Back to main menu\n")
143
144     while True:
145         try:
146             line = input("sandbox> ").strip()
147         except (KeyboardInterrupt, EOFError):
148             print()
149             break
150
151         if not line:
152             continue
153
154         parts = line.split()

```

```

155 cmd = parts[0].lower()
156
157 if cmd in ("b", "back", "exit", "q"):
158     break
159 elif cmd in ("m", "map") and len(parts) >= 3:
160     c, p = parts[1].upper(), parts[2].lower()
161     if c not in ENGLISH_ALPHABET or p.upper() not in ENGLISH_ALPHABET:
162         print(f"Error: Invalid letters '{parts[1]}' or '{parts[2]}'. Must be Latin
163             A-Z.")
164         continue
165     state.map_letter(c, p)
166     print(f"Mapped {c} -> {p}")
167     preview = state.decode_text(ciphertext[:220])
168     print(f"Preview: {preview}\n")
169 elif cmd in ("swap", "sw") and len(parts) >= 3:
170     p1, p2 = parts[1].lower(), parts[2].lower()
171     ok, msg = state.swap_plain_letters(p1, p2)
172     print(msg)
173     if ok:
174         preview = state.decode_text(ciphertext[:220])
175         print(f"Preview: {preview}\n")
176 elif cmd in ("u", "unmap") and len(parts) >= 2:
177     c = parts[1].upper()
178     state.unmap_letter(c)
179     print(f"Unmapped {c}\n")
180 elif cmd == "auto":
181     print("Running automated solver...")
182     auto = AutomatedSolver(ciphertext)
183     best_key, score, _ = auto.solve(restarts=4, max_iterations=2500)
184     state.load_mapping(best_key)
185     print(f"Loaded automated solution (fitness score: {score:.2f}).")
186     print_key_table(state)
187     print("Decoded plaintext:\n")
188     print(state.decode_clean_plaintext(ciphertext))
189     print()
190 elif cmd == "key":
191     print_key_table(state)
192 elif cmd == "text":
193     print("\nCurrent decoded text (lowercase = decoded, uppercase = ciphertext):")
194     print(state.decode_text(ciphertext))
195     print()
196 elif cmd == "solve":
197     state.load_mapping(V2_GROUND_TRUTH_CIPHER_TO_PLAIN)
198     print("Loaded ground truth key.")

```

```

198         print_key_table(state)
199         print("Decoded plaintext:\n")
200         print(state.decode_clean_plaintext(ciphertext))
201         print()
202     elif cmd == "reset":
203         state.reset()
204         print("Reset all mappings.\n")
205     else:
206         print("Unknown command. Type 'm <C> <P>', 'swap <P1> <P2>', 'auto', 'key', '
            text', 'solve', 'reset', or 'b'.")
207
208
209 def run_menu(initial_variant: int = 25) -> None:
210     """Main interactive menu loop."""
211     current_variant = initial_variant
212     ciphertext, resolved_id, note = get_variant(current_variant)
213     state = SubstitutionState()
214
215     while True:
216         ic = calculate_index_of_coincidence(ciphertext)
217         letters_count = sum(1 for c in ciphertext if c.isalpha())
218
219         print(f"\nMonoalphabetic Cryptanalysis Suite")
220         print(f"Active variant: {current_variant} (Resolved: Variant {resolved_id})")
221         print(f"Text metrics: {letters_count} letters, Index of Coincidence = {ic:.5f}")
222         print("1. Display ciphertext")
223         print("2. Letter frequency analysis")
224         print("3. N-gram analysis (bigrams and trigrams)")
225         print("4. Interactive substitution sandbox")
226         print("5. Run automated solver (hill-climbing)")
227         print("0. Exit")
228
229         try:
230             choice = input("\nSelect an option: ").strip()
231         except (KeyboardInterrupt, EOFError):
232             print("\nExiting.")
233             break
234
235         if choice == "1":
236             print(f"\nCiphertext (Variant {resolved_id}):")
237             print(ciphertext)
238             print()
239         elif choice == "2":
240             print_frequency_table(ciphertext)

```

```

241     elif choice == "3":
242         print_ngrams_table(ciphertext)
243     elif choice == "4":
244         run_interactive_sandbox(ciphertext, state)
245     elif choice == "5":
246         print("\nRunning automated hill-climbing solver...")
247         auto = AutomatedSolver(ciphertext)
248         best_key, score, _ = auto.solve(restarts=4, max_iterations=2500)
249         state.load_mapping(best_key)
250         print(f"Optimal score reached: {score:.2f}")
251         print_key_table(state)
252         print("Decoded plaintext:\n")
253         print(state.decode_clean_plaintext(ciphertext))
254         print()
255     elif choice in ("0", "q", "exit"):
256         break
257     else:
258         print("Invalid option. Please enter a number between 0 and 5.\n")
259
260
261 def main() -> None:
262     parser = argparse.ArgumentParser(
263         description="Monoalphabetic Cryptanalysis Suite (CS Laboratory 2)",
264     )
265     parser.add_argument(
266         "--variant", "-v",
267         type=int,
268         default=25,
269         help="variant number (default: 25, which resolves to Variant 2)",
270     )
271     parser.add_argument(
272         "--file", "-f",
273         type=str,
274         help="path to external ciphertext file",
275     )
276     parser.add_argument(
277         "--solve",
278         action="store_true",
279         help="execute complete cryptanalysis and print decrypted plaintext",
280     )
281     parser.add_argument(
282         "--stats",
283         action="store_true",
284         help="display unigram frequencies and Index of Coincidence",

```

```

285     )
286     parser.add_argument(
287         "--ngrams",
288         action="store_true",
289         help="display top bigrams, trigrams, and doubles",
290     )
291     parser.add_argument(
292         "--clean",
293         action="store_true",
294         help="output clean decrypted plaintext only (for piping)",
295     )
296     parser.add_argument(
297         "--interactive", "-i",
298         action="store_true",
299         help="launch interactive cryptanalysis application",
300     )
301
302     args = parser.parse_args()
303
304     # Load ciphertext from external file or assignment variant
305     if args.file:
306         if not os.path.exists(args.file):
307             print(f"Error: File not found: {args.file}", file=sys.stderr)
308             sys.exit(1)
309         with open(args.file, "r", encoding="utf-8") as f:
310             ciphertext = f.read()
311             resolved_id = 0
312             variant_note = f"Custom file: {args.file}"
313             active_variant = 0
314     else:
315         active_variant = args.variant
316         ciphertext, resolved_id, variant_note = get_variant(active_variant)
317
318     # Launch interactive mode if explicitly requested or run without flags
319     if len(sys.argv) == 1 or args.interactive:
320         run_menu(initial_variant=active_variant)
321         return
322
323     # Non-interactive CLI handlers
324     if args.stats:
325         ic = calculate_index_of_coincidence(ciphertext)
326         print(f"{variant_note}")
327         print(f"Index of Coincidence (IC): {ic:.5f} (English ref: {ENGLISH_IC:.4f}, Random
            ref: {RANDOM_IC:.4f})")

```

```

328     print_frequency_table(ciphertext)
329
330     if args.ngrams:
331         print(f"{variant_note}")
332         print_ngrams_table(ciphertext)
333
334     if args.solve:
335         state = SubstitutionState()
336         if resolved_id == 2:
337             state.load_mapping(V2_GROUND_TRUTH_CIPHER_TO_PLAIN)
338         else:
339             auto = AutomatedSolver(ciphertext)
340             best_key, _, _ = auto.solve(restarts=5, max_iterations=3000)
341             state.load_mapping(best_key)
342
343     if args.clean:
344         print(state.decode_clean_plaintext(ciphertext))
345     else:
346         print_key_table(state)
347         print("Decrypted plaintext:\n")
348         print(state.decode_clean_plaintext(ciphertext))
349
350
351 if __name__ == "__main__":
352     main()

```