

# On the Computational Power of Simple Dynamics

Emanuele Natale


Supervisors: Andrea Clementi, Riccardo Silvestri




SAPIENZA  
UNIVERSITÀ DI ROMA

Sapienza University of Rome  
February 13, 2017

# Communication in *Simple* Systems



# Communication in *Simple* Systems



# Communication in *Simple* Systems




Schools of fish  
[Sumpter et al. '08]

Insects colonies  
[Franks et al. '02]



Flocks of birds  
[Ben-Shahar et al. '10]



# Communication Model

Animal communication:

- Chaotic
- Anonymous
- Parsimonious
- Uni-directional (Passive)
- Noisy

# Communication Model


Animal communication:

- ✓ Chaotic
- ✓ Anonymous
- ✓ Parsimonious

- Uni-directional (Passive) ✓
- Noisy

$PULL(h, \ell)$  model

[Demers '88]: at each round each agent can *observe*  $h$  other agents chosen independently and uniformly at random, and *shows*  $\ell$  bits to her observers.



# Communication Model

Animal communication:

- ✓ Chaotic
- ✓ Anonymous
- ✓ Parsimonious

- Uni-directional (Passive) ✓
- Noisy

$PULL(h, \ell)$  model

[Demers '88]: at each round each agent can *observe*  $h$  other agents chosen independently and uniformly at random, and *shows*  $\ell$  bits to her observers.



# Dynamics

(informal) *Very simple distributed algorithms:* For every graph, agent and round, states are updated according to fixed rule of current state and symmetric function of states of neighbors.




# Dynamics

(informal) *Very simple distributed algorithms:* For every graph, agent and round, states are updated according to **fixed rule of current state and symmetric function of states of neighbors.**

Examples of Dynamics

- 3-Median dynamics




# Dynamics

(informal) *Very simple distributed algorithms:* For every graph, agent and round, states are updated according to **fixed rule of current state and symmetric function of states of neighbors.**

## Examples of Dynamics

- 3-Median dynamics
- 3-Majority dynamics




# Dynamics

(informal) *Very simple distributed algorithms:* For every graph, agent and round, states are updated according to **fixed rule of current state and symmetric function of states of neighbors.**

## Examples of Dynamics

- 3-Median dynamics
- 3-Majority dynamics
- Undecided-state dynamics




# Dynamics

(informal) *Very simple distributed algorithms:* For every graph, agent and round, states are updated according to **fixed rule of current state and symmetric function of states of neighbors.**

## Examples of Dynamics

- 3-Median dynamics
- 3-Majority dynamics
- Undecided-state dynamics
- Averaging dynamics



# The Power of Dynamics: Plurality Consensus

## Computing the Median

**3-Median dynamics** [Doerr et al. '11]. Converge to  $\mathcal{O}(\sqrt{n \log n})$  approximation of **median** of system in  $\mathcal{O}(\log n)$  rounds w.h.p., even if  $\mathcal{O}(\sqrt{n})$  states are arbitrarily changed at each round ( $\mathcal{O}(\sqrt{n})$ -bounded adversary).

# The Power of Dynamics: Plurality Consensus

## Computing the Median

**3-Median dynamics** [Doerr et al. '11]. Converge to  $\mathcal{O}(\sqrt{n \log n})$  approximation of **median** of system in  $\mathcal{O}(\log n)$  rounds w.h.p., even if  $\mathcal{O}(\sqrt{n})$  states are arbitrarily changed at each round ( $\mathcal{O}(\sqrt{n})$ -bounded adversary).

## Computing the Majority

**3-Majority dynamics** [SPAA '14, SODA '16]. If **plurality** has **bias**  $\mathcal{O}(\sqrt{kn \log n})$ , converges to it in  $\mathcal{O}(k \log n)$  rounds w.h.p., even against  $o(\sqrt{n/k})$ -bounded adversary. Without bias, converges in  $\text{poly}(k)$ .  $h$ -majority converges in  $\Omega(k/h^2)$ .

# The Power of Dynamics: Plurality Consensus

## Computing the Median

**3-Median dynamics** [Doerr et al. '11]. Converge to  $\mathcal{O}(\sqrt{n \log n})$  approximation of **median** of system in  $\mathcal{O}(\log n)$  rounds w.h.p., even if  $\mathcal{O}(\sqrt{n})$  states are arbitrarily changed at each round ( $\mathcal{O}(\sqrt{n})$ -bounded adversary).

## Computing the Majority

**3-Majority dynamics** [SPAA '14, SODA '16]. If **plurality** has **bias**  $\mathcal{O}(\sqrt{kn \log n})$ , converges to it in  $\mathcal{O}(k \log n)$  rounds w.h.p., even against  $o(\sqrt{n/k})$ -bounded adversary. Without bias, converges in  $\text{poly}(k)$ .  $h$ -majority converges in  $\Omega(k/h^2)$ .

**Undecided-State dynamics** [SODA '15]. If majority/second-majority ( $c_{maj}/c_{2^{nd}maj}$ ) is at least  $1 + \epsilon$ , system converges to **plurality** within  $\tilde{\Theta}(\text{md}(\mathbf{c}))$  rounds w.h.p.

# A Global Measure of Bias

$$\text{md}(\mathbf{c}^{(0)}) := \sum_{i=1}^k \left( \frac{c_i^{(0)}}{c_{maj}^{(0)}} \right)^2 = 1 + \mathcal{D} \left( \begin{array}{c} \text{[Bar Chart 1]} \end{array} \right)$$

$1 \leq \text{md} \left( \begin{array}{c} \text{[Bar Chart 2]} \end{array} \right) \ll \text{md} \left( \begin{array}{c} \text{[Bar Chart 3]} \end{array} \right) \leq k$

Undecided-State dynamics [SODA '15]. If majority/second-majority ( $c_{maj}/c_{2^{nd}maj}$ ) is at least  $1 + \epsilon$ , system converges to plurality within  $\tilde{\Theta}(\text{md}(\mathbf{c}))$  rounds w.h.p.



# The Median, the Mode and... the Mean

Dynamics can solve Consensus, Median, Majority, in robust and fault tolerant ways, but this is trivial in centralized setting.

# The Median, the Mode and... the Mean

Dynamics can solve Consensus, Median, Majority, in robust and fault tolerant ways, but this is trivial in centralized setting.


Can dynamics solve a problem **non-trivial in centralized setting**?

# Community Detection as Minimum Bisection

## Minimum Bisection Problem.

*Input:* a graph  $G$  with  $2n$  nodes.

*Output:*  $S = \arg \min_{\substack{S \subset V \\ |S|=n}} E(S, V - S).$




[Garey, Johnson, Stockmeyer '76]:

**Min-Bisection** is *NP-Complete*.


# The Stochastic Block Model

**Stochastic Block Model (SBM).** Two “communities” of equal size  $V_1$  and  $V_2$ , each edge inside a community included with probability  $p = \frac{a}{n}$ , each edge across communities included with probability  $q = \frac{b}{n} < p$ .




# The Stochastic Block Model

**Reconstruction problem.** Given graph generated by SBM, find original partition.



# The Stochastic Block Model






**Reconstruction problem.** Given graph generated by SBM, find original partition.



# The Averaging Dynamics

All nodes at the same time:

- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.



# The Averaging Dynamics

All nodes at the same time:

- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.







# The Averaging Dynamics

All nodes at the same time:


- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.



# The Averaging Dynamics

All nodes at the same time:


- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.



# The Averaging Dynamics

All nodes at the same time:



- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.



# The Averaging Dynamics

All nodes at the same time:


- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.




# The Averaging Dynamics

All nodes at the same time:

- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.



$$\frac{\text{envelope} + \text{envelope} + \text{envelope} + \text{envelope}}{4} = \text{envelope}$$




# The Averaging Dynamics

All nodes at the same time:

- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.

Well studied process [Shah '09]:

- Converges to (weighted) global average of initial values,
- Convergence time = mixing time of  $G$ ,
- Important applications in fault-tolerant self-stabilizing consensus.



# The Averaging Dynamics

All nodes at the same time:

- At  $t = 0$ , randomly pick value  $x^{(t)} \in \{+1, -1\}$ .
- Then, at each round
  1. Set value  $x^{(t)}$  to average of neighbors,
  2. Set label to **blue** if  $x^{(t)} < x^{(t-1)}$ , **red** otherwise.

Well studied process [Shah '09]:


- Converges to (weighted) global average of initial values,
- Convergence time = mixing time of  $G$ ,
- Important applications in fault-tolerant self-stabilizing consensus.

Averaging  
is a **linear** dynamics  $\mathbf{x}^{(t)} = \begin{pmatrix} \circ \\ \bullet \\ \circ \\ \bullet \\ \bullet \end{pmatrix}$

$$\mathbf{x}^{(t)} = P \cdot \mathbf{x}^{(t-1)} = P^t \cdot \mathbf{x}^{(0)}$$


$P$  transition matrix  
of random walk

# Community Detection via Averaging Dynamics







# Community Detection via Averaging Dynamics




# Community Detection via Averaging Dynamics



# Community Detection via Averaging Dynamics



# Community Detection via Averaging Dynamics



[SODA '17] (Informal).  $G = (V_1 \cup V_2, E)$  s.t.

i)  $\chi = \mathbf{1}_{V_1} - \mathbf{1}_{V_2}$  close to right-eigenvector of eigenvalue  $\lambda_2$  of transition matrix of  $G$ , and


ii) gap between  $\lambda_2$  and  $\lambda = \max\{\lambda_3, |\lambda_n|\}$

sufficiently large,

then Averaging (approximately) identifies  $(V_1, V_2)$ .

Thank you!

# Analysis on Regular SBM

$P$   symmetric  $\implies$  orthonormal  
eigenvectors  $\mathbf{v}_1, \dots, \mathbf{v}_n$  and real  
eigenvalues  $\lambda_1, \dots, \lambda_n$ .

# Analysis on Regular SBM

$P$   $\longrightarrow$  symmetric  $\implies$  orthonormal  
eigenvectors  $\mathbf{v}_1, \dots, \mathbf{v}_n$  and real  
eigenvalues  $\lambda_1, \dots, \lambda_n$ .

$$\mathbf{x}^{(t)} = P^t \cdot \mathbf{x}^{(0)} = \sum_i \lambda_i^t (\mathbf{v}_i^\top \mathbf{x}^{(0)}) \mathbf{v}_i$$

# Analysis on Regular SBM

$P$   $\longrightarrow$  symmetric  $\implies$  orthonormal  
eigenvectors  $\mathbf{v}_1, \dots, \mathbf{v}_n$  and real  
eigenvalues  $\lambda_1, \dots, \lambda_n$ .

$$\mathbf{x}^{(t)} = P^t \cdot \mathbf{x}^{(0)} = \sum_i \lambda_i^t (\mathbf{v}_i^\top \mathbf{x}^{(0)}) \mathbf{v}_i$$

$$\mathbf{v}_1 = \frac{1}{\sqrt{n}} \mathbf{1}$$

$$\text{Regular SBM} \implies P\chi = \left(\frac{a-b}{a+b}\right) \cdot \chi$$



# Analysis on Regular SBM

$P$   $\longrightarrow$  symmetric  $\implies$  orthonormal  
 eigenvectors  $\mathbf{v}_1, \dots, \mathbf{v}_n$  and real  
 eigenvalues  $\lambda_1, \dots, \lambda_n$ .

$$\mathbf{x}^{(t)} = P^t \cdot \mathbf{x}^{(0)} = \sum_i \lambda_i^t (\mathbf{v}_i^\top \mathbf{x}^{(0)}) \mathbf{v}_i$$

$$\mathbf{v}_1 = \frac{1}{\sqrt{n}} \mathbf{1}$$

$$\text{Regular SBM} \implies P\chi = \left(\frac{a-b}{a+b}\right) \cdot \chi$$

$$\frac{1}{a+b} \begin{pmatrix} \dots\dots\dots & \dots\dots\dots \\ \dots a \text{ "1"s" } \dots & \dots b \text{ "1"s" } \dots \\ \dots\dots\dots & \dots\dots\dots \\ \dots\dots\dots & \dots\dots\dots \\ \dots b \text{ "1"s" } \dots & \dots a \text{ "1"s" } \dots \\ \dots\dots\dots & \dots\dots\dots \end{pmatrix} \cdot \begin{pmatrix} 1 \\ \vdots \\ 1 \\ -1 \\ \vdots \\ -1 \end{pmatrix} = \frac{a-b}{a+b} \begin{pmatrix} 1 \\ \vdots \\ 1 \\ -1 \\ \vdots \\ -1 \end{pmatrix}$$

# Analysis on Regular SBM

$P$   $\longrightarrow$  symmetric  $\implies$  orthonormal  
eigenvectors  $\mathbf{v}_1, \dots, \mathbf{v}_n$  and real  
eigenvalues  $\lambda_1, \dots, \lambda_n$ .

$$\mathbf{x}^{(t)} = P^t \cdot \mathbf{x}^{(0)} = \sum_i \lambda_i^t (\mathbf{v}_i^\top \mathbf{x}^{(0)}) \mathbf{v}_i$$

$$\mathbf{v}_1 = \frac{1}{\sqrt{n}} \mathbf{1}$$

$$\text{Regular SBM} \implies P\chi = \left(\frac{a-b}{a+b}\right) \cdot \chi$$


W.h.p.  $\max\{\lambda_3, |\lambda_n|\}(1 + \delta) < \frac{a-b}{a+b} = \lambda_2$ , then

$$\mathbf{x}^{(t+1)} = \frac{1}{n} (\mathbf{1}^\top \mathbf{x}^{(0)}) \mathbf{1} + \lambda_2^t \frac{1}{n} (\chi^\top \mathbf{x}^{(0)}) \chi + \mathbf{e}^{(t)}$$

with  $\|\mathbf{e}^{(t)}\| \leq (\max\{\lambda_3, |\lambda_n|\})^t \sqrt{n}$

# Analysis on Regular SBM

$$\left( \frac{1}{n} \sum_{u \in V_1} \mathbf{x}^{(0)}(u) - \frac{1}{n} \sum_{u \in V_2} \mathbf{x}^{(0)}(u) \right)$$



W.h.p.  $\max\{\lambda_3, |\lambda_n|\}(1 + \delta) < \frac{a-b}{a+b} = \lambda_2$ , then

$$\mathbf{x}^{(t+1)} = \frac{1}{n} (\mathbf{1}^\top \mathbf{x}^{(0)}) \mathbf{1} + \lambda_2^t \frac{1}{n} (\chi^\top \mathbf{x}^{(0)}) \chi + \mathbf{e}^{(t)}$$

with  $\|\mathbf{e}^{(t)}\| \leq (\max\{\lambda_3, |\lambda_n|\})^t \sqrt{n}$

# Analysis on Regular SBM

$$\mathbf{x}^{(t)} = \frac{1}{n}(\mathbf{1}^\top \mathbf{x}^{(0)})\mathbf{1} + \lambda_2^t \frac{1}{n}(\chi^\top \mathbf{x}^{(0)})\chi + \mathbf{e}^{(t)}$$

# Analysis on Regular SBM


$$\mathbf{x}^{(t)} = \frac{1}{n}(\mathbf{1}^\top \mathbf{x}^{(0)})\mathbf{1} + \lambda_2^t \frac{1}{n}(\chi^\top \mathbf{x}^{(0)})\chi + \mathbf{e}^{(t)}$$

$$\mathbf{x}^{(t)} - \mathbf{x}^{(t-1)} = (\chi^\top \mathbf{x}^{(0)})\lambda_2^{t-1}(\lambda_2 - 1)\chi + \underbrace{\mathbf{e}^{(t)} - \mathbf{e}^{(t-1)}}_{\ll \lambda_2^{t-1} \text{ if } t = \Omega(\log n)}$$

# Analysis on Regular SBM

$$\mathbf{x}^{(t)} = \frac{1}{n}(\mathbf{1}^\top \mathbf{x}^{(0)})\mathbf{1} + \lambda_2^t \frac{1}{n}(\chi^\top \mathbf{x}^{(0)})\chi + \mathbf{e}^{(t)}$$

$$\mathbf{x}^{(t)} - \mathbf{x}^{(t-1)} = (\chi^\top \mathbf{x}^{(0)})\lambda_2^{t-1}(\lambda_2 - 1)\chi + \underbrace{\mathbf{e}^{(t)} - \mathbf{e}^{(t-1)}}_{\ll \lambda_2^{t-1} \text{ if } t = \Omega(\log n)}$$



$$\text{sign}(\mathbf{x}^{(t)}(u) - \mathbf{x}^{(t-1)}(u)) \propto \text{sign}(\chi(u))$$