ASICamera Software Development Kit

Revision:V1, 2
2016.9.8

1 Introduction

This SDK is used to operate ASI serial cameras, can be used by C, C++, C# and other develop tools, is suit for Windows, Linux, OSX operating system of x86 and x64.

Header file: ASICamera.h

Under Windows the import library and dynamic library: ASICamera.lib、ASICamera.dll

Under Linux the dynamic library and static library: ASICamera.so、ASICamera.a

Under OSX the dynamic library and static library: ASICamera.dylib、ASICamera.a

Installation method:

Under Windows, extract the downloaded zip file to any directory, and add DLL's path to system environment variables, sometimes logout and re-login is required

2 Definition of enum-type and struct

2.1 enum Control_TYPE

{

　　CONTROL_GAIN=0,//gain

　　CONTROL_EXPOSURE,/ exposure time(us)

　　CONTROL_GAMMA,// gamma

　　CONTROL_WB_R,// red component of white balance

　　CONTROL_WB_B,// blue component of white balance

　　CONTROL_BRIGHTNESS,// offset

　　CONTROL_BANDWIDTHOVERLOAD,// USB band width

　　CONTROL_OVERCLOCK,// over clock

　　CONTROL_TEMPERATURE,// sensor temperature，10 times the actual temperature

　　CONTROL_HARDWAREBIN,// hardware bin

　　CONTROL_HIGHSPEED,//high speed mode

　　CONTROL_COOLERPOWERPERC,// cooler power percent(only cool camera)

　　CONTROL_TARGETTEMP,// sensor's target temperature(only cool camera)，don't multiply by 10

　　CONTROL_COOLER_ON,// open cooler(only cool camera)

　　CONTROL _MONO_BIN,//lead to less grid at software bin mode for color camera

　　CONTROL _FAN_ON, //only cooled camera has fan

　　CONTROL_PATTERN_ADJUST//currently only supported by 1600 mono camera

};

　　Camera control type

2.2 enum IMG_TYPE

{

　　IMG_RAW8=0, //1 byte every pixel

IMG_RGB24,// Each pixel consists of RGB, 3 bytes totally (color cameras only)

IMG_RAW16,// 2 byte every pixel

IMG_Y8,// mono mode，1 byte every pixel (color cameras only)

};

Image type

2.3 enum GuideDirections

{

guideNorth=0,

guideSouth,

guideEast,

guideWest

};

Moving direction when guiding

2.4 enum BayerPattern

{

BayerRG=0,

BayerBG,

BayerGR,

BayerGB

};

Bayer filter type

2.5 enum EXPOSURE_STATUS

{

EXP_IDLE = 0,// /idle, ready to start exposure

EXP_WORKING,// exposuring

EXP_SUCCESS,// exposure successfully, image can be read out

EXP_FAILED,// exposure fail, require restart exposure

};

Used under snap mode to describe exposure status

2.6 typedef struct _ASIID

{

unsigned char id[8];

}ASIID;

ID to be write into camera flash, 8 bytes totally

3 Function declaration

3.1 getNumberOfConnectedCameras

Syntax: int getNumberOfConnectedCameras();
Usage: get the count of connected cameras

3.2 getCameraModel
Syntax: char* getCameraModel(int camIndex);
Usage: get camera name(0 is the first one)

3.3 openCamera
Syntax: bool openCamera(int camIndex);
Usage: open a camera

3.4 initCamera
Syntax: bool initCamera();
Usage: initialize the camera，called after openCamera()

3.5 closeCamera
Syntax: void closeCamera();
Usage: close camera

3.6 isColorCam
Syntax: bool isColorCam();
Usage: whether camera is color

3.7 getPixelSize
Syntax: double getPixelSize();
Usage: get pixel size(um)

3.8 getColorBayer
Syntax: BayerPattern getColorBayer();
Usage: get Bayer filter type

3.9 EnableDarkSubtract
Syntax: bool EnableDarkSubtract(char *BMPPath);
Usage: enable dark subtract function
Description:
    char *BMPPath：path of dark field image(.bmp)
    return : success or not
Notes: dark field image is get by camera's direct show driver，located in capture application's menu "video capture filter"->"ROI and others" table

3.10 DisableDarkSubtract
Syntax: void DisableDarkSubtract();
Usage: disable dark subtract function

3.11 isAvailable

Syntax: bool isAvailable(Control_TYPE control) ;

Usage: Whether the control type is supported

3.12 isAutoSupported

Syntax: bool isAutoSupported(Control_TYPE control) ;

Usage: Whether the control type supports auto adjust

3.13 getValue

Syntax: int getValue(Control_TYPE control, bool *pbAuto)　;

Usage: get value of control

Description:

    Control_TYPE control：control type

    bool *pbAuto：is auto adjust?

    Return: value

3.14 getMin

Syntax: int getMin(Control_TYPE control) ;

Usage: get the minimum value of the control type

3.15 getMax

Syntax: int getMax(Control_TYPE control) ;

Usage: get the maximum value of the control value

3.16 setValue

Syntax: void setValue(Control_TYPE control, int value, bool autoset);

Usage: set value of the control value

Description:

    Control_TYPE control：control type

    int value：value

    bool autoset：is auto adjust?

Notes: when set to auto adjust (autoset =true)，lValue should be current value

3.17 setAutoPara

Syntax: void setAutoPara(int iMaxGain, int iMaxExp, int iDestBrightness);

Usage: set parameters of auto adjusting

Description:

    int iMaxGain：maximum gain value

    int iMaxExp：maximum value of exposure time, unit is second

    int iDestBrightness：target brightness

3.18 getAutoPara

Syntax: void getAutoPara(int *pMaxGain, int *pMaxExp, int *pDestBrightness);

Usage: get parameters of auto adjusting

Description:

　　int *pMaxGain：maximum gain value

　　int *pMaxExp：maximum value of exposure time, unit is second

　　int *pDestBrightness：target brightness

3.19 getMaxWidth
Syntax: int getMaxWidth();
Usage: get maximum image width

3.20 getMaxHeight
Syntax: int getMaxHeight();
Usage: get maximum image height

3.21 getWidth
Syntax: int getWidth();
Usage: get current image width

3.22 getHeight
Syntax: int getHeight();
Usage: get current image height

3.23 getStartX
Syntax: int getStartX();
Usage: get start position of x-axis when ROI

3.24 getStartY
Syntax: int getStartY();
Usage: get start position of y-axis when ROI

3.25 getSensorTemp
Syntax: float getSensorTemp();
Usage: get sensor temperature，accurate to one decimal place

3.26 getDroppedFrames
Syntax: unsigned long getDroppedFrames();
Usage: get dropped frames' count during video capture

3.27 SetMisc
Syntax: void SetMisc(bool bFlipRow, bool bFlipColumn);
Usage: flip image
Description:

　　bool bFlipRow：horizontal flip

　　bool bFlipColumn：vertical flip

3.28 GetMisc

Syntax: void GetMisc(bool * pbFlipRow, bool * pbFlipColumn);

Usage: get image flip

Description:

  bool * pbFlipRow：horizontal flip

  bool * pbFlipColumn：vertical flip

3.29 isBinSupported

Syntax: bool isBinSupported(int binning);

Usage: whether given bin is supported

3.30 isImgTypeSupported

Syntax: bool isImgTypeSupported(IMG_TYPE img_type);

Usage: whether given image type is supported

3.31 getBin

Syntax: int getBin();

Usage: get current bin value

3.32 setStartPos

Syntax: void setStartPos(int startx, int starty);

Usage: set start position of ROI

Description:

  int startx：start position of x-axis

  int starty：start position of y-axis

  Notes: the position is relative to the image after binning. call this function to change ROI area to the origin after ASISetROIFormat, because ASISetROIFormat will change ROI to the center.

3.33 setImageFormat

Syntax: bool setImageFormat(int width, int height,　int binning, IMG_TYPE img_type);

Usage: set ROI size and image type

Description:

  int width：image width

  int height：image height

  int binning：bin value

  IMG_TYPE img_type：image type

  Return: success or not

  Notes: make sure iWidth%8=0，iHeight%2=0. For USB2.0 camera ASI120，make sure iWidth* iHeight%1024=0，otherwise setting will be failed.

3.34 getImgType

IMG_TYPE getImgType();

Usage: get image type

3.35 startCapture

Syntax: void startCapture();

Usage: start video capture

3.36 stopCapture

Syntax: void stopCapture();

Usage: stop video capture

3.37 getImageData

Syntax: bool getImageData(unsigned char* buffer, int bufSize, int waitms);

Usage: after startCapture()，call this function to get image continuously

Description:

    unsigned char* buffer：pointer to image buffer

    int bufSize：size of buffer

    int waitms：wait time, unit is ms, -1 means wait forever

Notes:

    If read out speed isn't fast enough, the frame will be discard

    bufSize Byte length：for RAW8 and Y8，bufSize >= image_width*image_height，for RAW16 , bufSize >= image_width*image_height *2 , for RGB8 , bufSiz >= image_width*image_height *3

    suggested waitms value: exposure_time*2

3.38 pulseGuide

Syntax: void pulseGuide(GuideDirections direction, int timems);

Usage: send ST4 guiding pulse，only the camera with ST4 port support

Description:

    GuideDirections direction：guiding direction

    int timems：duration in ms

3.39 startExposure

Syntax: void startExposure();

Usage: start snap

3.40 getExpStatus

Syntax: enum EXPOSURE_STATUS getExpStatus();

Usage: get snap status

Notes: after snap is started，the status should be checked continuously

3.41 getImageAfterExp

Syntax: bool getImageAfterExp(unsigned char* buffer, int bufSize);

Usage: get image after snap successfully

Description:

    unsigned char* buffer：pointer to image buffer

    int bufSize：buffer size

Notes: bufSize refer to ASIGetVideoData ()

3.42 stopExposure
Syntax: void stopExposure();
Usage: stop snap
Notes: if exposure status is success after stop exposure，image can still be read out

3.43 isUSB3Host
Syntax: bool isUSB3Host();
Usage: whether camera works under USB3 status

3.44 isCoolerCam
Syntax: bool isCoolerCam();
Usage: whether camera is equiped with cooler

3.45 GetID
Syntax: bool GetID(ASIID *pID);
Usage: get camera id stored in flash, only available for USB3.0 camera

3.46 SetID
Syntax: bool SetID(ASIID ID);
Usage: write camera id to flash, only available for USB3.0 camera

3.47 isUSB3Camera
Syntax: bool isUSB3Camera();
Usage: whether this is USB3.0 camera

3.48 getElectronsPerADU
float getElectronsPerADU();
Usage: get system gain of sensor in e/ADU

4 Suggested call sequence

4.1 Initialization
Get count of connected cameras-->--> getNumberOfConnectedCameras
Get cameras' name --> getCameraModel
Open camera --> openCamera
Initialize-->initCamera
Set image size and format--> setImageFormat
Set start position when ROI --> setStartPos

4.2 Get and set control value
    getValue
    setValue

allowed during capture

4.3 Capture image

There are two mode：video and snap mode. Images are captured continuously under video mode, and only single image is captured under snap mode.

● video mode

Start video capture --> startCapture

Stop video capture --> stopCapture

It is suggested that get and save data in single thread:

```
while(1)
{
    getImageData

    ...
}
```

● snap mode

```
startExposure
while(1)
{
    status = getExpStatus

    ...
}
```

Cancel exposure：stopExposure

if(status == EXP_SUCCESS) //get image if snap successfully

```
    getImageAfterExp
```

4.4 Close camera

closeCamera/release resource