

Beam Mismatch and Halo Formation

USPAS - Beam Physics with Intense Space Charge

Austin Hoover Steven Lund Daniel Winklehner John Barnard

2026-07-01

Table of contents I

2D envelope modes in continuous focusing channels

Derivation of equilibrium beam radius

The KV envelope equations describe the evolution of the elliptical beam radii $r_{x,y}$ in a linear focusing system:

$$\begin{aligned} r_x'' + \kappa_x(s)r_x - \frac{2Q}{r_x + r_y} - \frac{\varepsilon_x^2}{r_x^3} &= 0, \\ r_y'' + \kappa_y(s)r_y - \frac{2Q}{r_x + r_y} - \frac{\varepsilon_y^2}{r_y^3} &= 0, \end{aligned}$$

where $\varepsilon_{x,y}$ are the invariant emittances, Q is the beam perveance, and $\kappa_{x,y}(s)$ are the linear focusing strengths. We will study continuous, axisymmetric focusing systems with $\kappa_x(s) = \kappa_y(s) = k_0^2$. We will also assume equal emittances in each plane: $\varepsilon_x = \varepsilon_y = 0$. With these assumptions, the envelope equations become:

$$\begin{aligned} r_x'' + k_0^2 r_x - \frac{2Q}{r_x + r_y} - \frac{\varepsilon^2}{r_x^3} &= 0, \\ r_y'' + k_0^2 r_y - \frac{2Q}{r_x + r_y} - \frac{\varepsilon^2}{r_y^3} &= 0. \end{aligned} \tag{1}$$

An equilibrium occurs when $r_x'' = r_y'' = 0$, indicating exact balance between external and internal forces. This gives the following expression for the equilibrium radius $r_x = r_y = r_0$:

3D envelope modes in continuous focusing channels

It is natural to extend the above analysis to three-dimensional systems. We will simplify things by restricting our attention to upright beams with axial symmetry. We study the coupling between the transverse radius $r_{\perp}$ and the longitudinal radius r_z .

[...]

Particle-core models of halo formation

Introduction

Beam distributions in high-intensity accelerators tend to develop a low-density cloud of charge surrounding a dense, oscillating core, which we call a *halo*. For example, Figure 1 shows the measured two-dimensional phase space density after acceleration in the Spallation Neutron Source (SNS) linac. Although the halo density can be orders of magnitude less than the core, it still presents a problem in the SNS and other high-power facilities. The accelerator operating power is ultimately constrained by uncontrolled *beam loss*, which leads to radioactivation in the accelerator tunnel. High-power facilities must adhere to strict beam loss limits—typically set at 1 W/m. For a 1-MW beam, the loss limit corresponds to one out of every million particles, or a fractional loss of 10^{-6} . Once the loss limit is reached, increasing the beam power requires a proportional decrease in the beam loss. Understanding the mechanisms of halo formation is, therefore, highly relevant for modern and future high-power accelerators.

Horiz_LW-2023-08-03_15-28-10-Comb#1-Combined

