

Package ‘pros’

December 4, 2018

Title Penalized Regression on Steroids

Version 0.1

Author Austin David Brown <brow5079@umn.edu>

Maintainer Austin David Brown <brow5079@umn.edu>

Description This is a project for STAT8053 at the University of Minnesota.

Depends R (>= 3.5.1)

License Licensed under the Apache-2 (<https://www.apache.org/licenses/LICENSE-2.0>) license.

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

R topics documented:

cv.pros	1
predict.cv_pros	2
predict.pros	3
pros	3

Index	5
--------------	----------

cv.pros	<i>Cross-validation</i>
---------	-------------------------

Description

The K-fold cross-validation function.

Usage

```
cv.pros(X, y, K_fold = 5, alpha = c(1, 0, 0, 0, 0, 0, 0),  
        lambdas = seq(10^(-7), 1, 0.1), algorithm = "proximal_gradient_cd",  
        max_iter = 10000, tolerance = 10^(-3))
```

Arguments

<code>X</code>	the matrix of the data
<code>y</code>	the vector of response values
<code>alpha</code>	the convex combination of length 7 corresponding to the penalties: <ul style="list-style-type: none"> • l1 penalty • l2 penalty • l4 penalty • l6 penalty • l8 penalty • l10 penalty
<code>lambdas</code>	A vector of dual penalization values to be evaluated
<code>algorithm</code>	the optimization algorithm <ul style="list-style-type: none"> • proximal_gradient_cd • subgradient_cd
<code>max_iter</code>	maximum iterations. This also tunes the step size.
<code>tolerance</code>	tolerance

Value

A class `cv_pros`

Examples

```
cv = cv.pros(X_train, y_train)
pred = predict(cv, X_test)
```

predict.cv_pros	<i>Cross-validation Prediction</i>
-----------------	------------------------------------

Description

The cross-validation prediction function.

Usage

```
## S3 method for class 'cv_pros'
predict(cv_prosObj, X_new)
```

Arguments

<code>cv_prosObj</code>	an object of class <code>cv_pros</code>
<code>X_new</code>	the matrix of the data to predict

Value

A vector of prediction values.

Examples

```
cv = cv.pros(X_train, y_train)
pred = predict(cv, X_test)
```

predict.pros

Pros Prediction

Description

The prediction function.

Usage

```
## S3 method for class 'pros'
predict(prosObj, X)
```

Arguments

prosObj	an object of class pros
X	the matrix of the data to predict

Value

A vector of prediction values.

Examples

```
fit = pros(X_train, y_train, lambda = .1)
pred = predict(fit, X_test)
```

pros

Pros

Description

The fit function for a specific lambda value.

Usage

```
pros(X, y, alpha = c(1, 0, 0, 0, 0, 0, 0), lambda,
     algorithm = "proximal_gradient_cd", max_iter = 10000,
     tolerance = 10^(-3))
```

Arguments

<code>X</code>	the matrix of the data
<code>y</code>	the vector of response values
<code>alpha</code>	the convex combination of length 7 corresponding to the penalties: <ul style="list-style-type: none">• l1 penalty• l2 penalty• l4 penalty• l6 penalty• l8 penalty• l10 penalty
<code>lambda</code>	the dual penalization value
<code>algorithm</code>	the optimization algorithm <ul style="list-style-type: none">• proximal_gradient_cd• subgradient_cd
<code>max_iter</code>	maximum iterations. This also tunes the step size.
<code>tolerance</code>	tolerance

Value

A class `pros`

Examples

```
fit = pros(X_train, y_train, lambda = .1)
pred = predict(fit, X_test)
```

Index

`cv.pros`, [1](#)

`predict.cv_pros`, [2](#)

`predict.pros`, [3](#)

`pros`, [3](#)