

OpenAM 10.0.2 Release Notes

Mark Craig

Software release date: December 16, 2013

Publication date: December 07, 2013

Copyright © 2011-2013 ForgeRock AS

Abstract

Notes covering OpenAM prerequisites, fixes, known issues. OpenAM provides open source Authentication, Authorization, Entitlement and Federation software.



This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/> or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.

Trademarks are the property of their respective owners.

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DejaVu Fonts

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: [fonts at gnome dot org](mailto:fonts@gnome dot org).

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: [tavmjong @ free . fr](mailto:tavmjong@free . fr).

Table of Contents

- 1. What's New in OpenAM 10.0.2 1
- 2. Before You Install OpenAM Software 3
- 3. Updating & Installing OpenAM 7
- 4. OpenAM Changes & Deprecated Functionality 9
- 5. OpenAM Fixes, Limitations, & Known Issues 11
- 6. How to Report Problems & Provide Feedback 17
- 7. Support 19

Chapter 1. What's New in OpenAM 10.0.2

OpenAM 10.0.2 is a maintenance release that resolves a number of issues, including security issues in OpenAM. It is strongly recommended that you update to this release to make your deployment more secure, and to take advantage of important functional fixes. ForgeRock customers can contact support for help and further information.

Before you install OpenAM or update your existing OpenAM installation, read these release notes. Then update or install OpenAM.

- If you have already installed OpenAM, see *To Update From OpenAM 10.0.0*.
- If you are installing OpenAM for the first time, see *To Install OpenAM*.

1.1. Product Enhancements

In addition to fixes, this release includes the following limited product enhancements.

- OPENAM-3190: IdP Adapter should have an extension point that can manipulate the SAML response
- OPENAM-2767: The default IDP attribute mapper should provide a way to Base64 encode binary attributes
- OPENAM-2765: DirectoryManagerImpl, IdRepoJAXRPCObjectImpl and SMSJAXRPCObjectImpl should return cluster unique ID's when registering notification URL's
- OPENAM-2604: Password reset should have configurable mail attribute
- OPENAM-2425: OAuth2 Consumer needs the name of the parameter to hold the value of the token when accessing the profile service
- OPENAM-2184: Provide a mechanism to supply static attribute values in IDP and SP SAML2 attribute mappings
- OPENAM-1749: AttributeQueryUtil.getAttributeMapForFedlet eats non-Success StatusCode from IDP
- OPENAM-1623: Improve the IDPAdapter functionality

In order to have the default IDP attribute mapper Base64 encode binary attributes when adding them to the SAML attributes, use the ;binary postfix for the attribute name, as in the following example:

```
objectGUID=objectGUID;binary
```

This maps the local binary attribute objectGUID to a SAML attribute called objectGUID that is Base64 encoded.

The default IDP attribute mapper also supports NameFormatURI format as shown in the following example:

```
urn:oasis:names:tc:SAML:2.0:attrname-format:uri|objectGUID=objectGUID;binary
```

1.2. OpenAM Documentation

You can read the following additional product documentation for OpenAM 10.0 online at docs.forgerock.org

- [OpenAM 10.0.0 Release Notes](#)
- [OpenAM 10.0.0 Installation Guide](#)
- [OpenAM 10.0.0 Administration Guide](#)
- [OpenAM 10.0.0 Developer's Guide](#)
- [OpenAM 10.0.0 Reference](#)
- [OpenAM 10.0.0 Javadoc](#)

Chapter 2. Before You Install OpenAM Software

This chapter covers software and hardware prerequisites for installing and running OpenAM software. If you have a special request to support a component or combination not listed here, contact ForgeRock at info@forgerock.com.

Note

The content of this chapter has not changed since OpenAM 10.0.0.

2.1. Java Requirements

This release of OpenAM requires Java Development Kit 1.6, at least 1.6.0_10. ForgeRock recommends that you use at least version 1.6.0_27 due to security fixes.

ForgeRock has tested this release of OpenAM primarily with Oracle Java SE JDK.

OpenAM Java SDK requires Java Development Kit 1.5 or 1.6.

2.2. Web Application Container Requirements

This release of OpenAM runs in the following web application containers.

- Apache Tomcat 6.0.x, 7.0.x
- GlassFish v2
- JBoss Enterprise Application Platform 4.x, 5.x
JBoss Application Server 7.x
- Jetty 7
- Oracle WebLogic Server 11g
Oracle WebLogic Server 12c

If running as a non-root user, the web application container must be able to write to its own home directory, where OpenAM stores configuration files.

2.3. Data Store Requirements

This release of OpenAM works with the following configuration data stores.

- Embedded (using ForgeRock OpenDJ 2.4.5 for the data store)

When using the embedded configuration store, you must deploy OpenAM on a local file system and not on an NFS-mounted file system.

- External ForgeRock OpenDJ data store
- External Sun OpenDS data store
- External Oracle Directory Server Enterprise Edition data store

This release of OpenAM works with the following user profile data stores.

- ForgeRock OpenDJ
- Microsoft Active Directory
- IBM Tivoli Directory Server
- OpenDS
- Oracle Directory Server Enterprise Edition

OpenAM also works with OpenLDAP and other LDAPv3 compliant directory servers. Some features of OpenAM depend on features supported by your directory service, such as the following:

- Extensible LDAP schema, required to extend the schema for OpenAM. First, install OpenAM to use a fresh instance of OpenDJ, such as the embedded OpenDJ server. After installation, study the custom schema definitions from the OpenDJ file, `config/schema/99-user.ldif`, to see what schema definitions you must add to your directory. You might need to adapt the schema definition format before adding the definitions to your directory.
- The persistent search request control (OID: 2.16.840.1.113730.3.4.3).
- The Behera Internet-Draft Password Policy for LDAP Directories (for OpenAM password reset, for example)

If you plan to deploy with OpenLDAP or other LDAPv3 directory for user data, make sure you test your solution before you deploy to ensure all OpenAM features that you use work as expected.

2.4. Browsers Tested

ForgeRock has tested many browsers with OpenAM console and end user pages, including the following browsers.

- Chrome and Chromium 16 and later

- Firefox 3.6 and later
- Internet Explorer 7 and later
- Safari 5 and later

2.5. Platform Requirements

ForgeRock has tested this release of OpenAM on the following platforms.

- Linux 2.6, 3.0
- Microsoft Windows Server 2003, 2008
- Oracle Solaris 10

2.6. Hardware Requirements

You can deploy OpenAM on any hardware supported for the combination of software required. Deploying OpenAM requires a minimum of 1 GB free RAM over and above the RAM used by all other software on the system.

ForgeRock has tested this release of OpenAM primarily on x86 and x64 based systems.

Chapter 3. Updating & Installing OpenAM

ForgeRock recommends that you update OpenAM 10.0.0 installations to this release. If you are installing OpenAM for the first time, you can use the same installation instructions as for 10.0.0.

Procedure 3.1. To Update From OpenAM 10.0.0

If you have already installed OpenAM, follow these steps.

1. Download and unzip OpenAM 10.0.2.

The download page is <http://forgerock.org/openam.html>.

2. If you have made any customizations, apply them to the 10.0.2 .war file.
3. Redeploy the .war file to your web container, using the web container administration console or deployment command.

If you are using session failover, do not yet restart OpenAM.

4. If you are using session failover, you must ensure the session failover database is cleared as part of the update to OpenAM. OpenAM's internal representation of session objects has changed in this release. The session failover database must be restarted before starting the updated OpenAM.

To clear OpenMQ, run **amsfo stop** and then run **amsfo start**.

5. Start OpenAM, and run the upgrade process for the server.

Procedure 3.2. To Install OpenAM

If you have not yet installed OpenAM, install this release instead of OpenAM 10.0.0.

1. Download and unzip OpenAM 10.0.2.

The download page is <http://forgerock.org/openam.html>.

2. Follow the instructions in the *OpenAM 10.0.0 Installation Guide*.

Chapter 4. OpenAM Changes & Deprecated Functionality

This chapter covers both major changes to existing functionality, and also deprecated and removed functionality.

Note

The content of this chapter has not changed since OpenAM 10.0.0.

4.1. Major Changes to Existing Functionality

- The following web policy agents are compatible with OpenAM 10.0.2.

- Apache 2.0
- Apache 2.2
- Microsoft IIS 6
- Microsoft IIS 7

The following J2EE policy agents are compatible with OpenAM 10.0.2.

- GlassFish v2 & v3
- JBoss v4.2 & v5.x
- Jetty v6.1 & v7
- Tomcat v6
- WebSphere v6.1
- WebLogic v10
- Prior to OpenAM 9.5.2, trailing slashes (/) were ignored when matching resource names in policy evaluation. Therefore, /-*- matched /secret, but also /secret/, short for /secret/index.html on most web servers.

Now, /-*- matches /secret, but not /secret/.

- Since OpenAM 9.5.3, application shutdown hooks are no longer registered by default. This change only has an effect on standalone and web applications that use the OpenAM Client SDK. The changes do not affect OpenAM, distributed authentication services, or the Java EE policy agents.

For Java EE applications, ensure the OpenAM client SDK shuts down successfully by including the following context listener in your application's `web.xml` file.

```
<listener>
  <listener-class>
    com.sun.identity.common.ShutdownServletContextListener
  </listener-class>
</listener>
```

For standalone applications, set the following JVM property.

```
-Dopenam.runtime.shutdown.hook.enabled=true
```

4.2. Deprecated Functionality

The following functionality is deprecated in OpenAM 10.0.2.

- The Netscape LDAP API is to be removed from OpenAM, with OpenAM using the OpenDJ LDAP SDK instead. This affects all classes in `com.sun.identity.shared.ldap.*` packages.
- Support for Liberty Identity Web Services Framework (ID-WSF) is deprecated. The functionality is likely to be removed in a future release.
- OpenAM currently uses Sun Java System Application Framework (JATO). JATO is deprecated and is likely to be replaced in a future release.

4.3. Removed Functionality

OpenAM 10.0.2 does not include the **amtune** command.

OpenAM console only mode is no longer supported. Console only mode is likely to be replaced with a different solution in a future release.

The Test Beta Console has been removed. Its functionality is currently available through the **ssoadm** command.

OpenAM no longer includes the SafeWord and Unix authentication modules.

Chapter 5. OpenAM Fixes, Limitations, & Known Issues

OpenAM issues are tracked at <https://bugster.forgerock.org/jira/browse/OPENAM>. This chapter covers the status of key issues and limitations at release 10.0.2.

5.1. Fixes

The following issues were fixed in release 10.0.2.

- OPENAM-3353: LDAP auth does not set operation timeout; OpenAM freeze
- OPENAM-3330: Backport of LDAP Auth failover code
- OPENAM-3269: create-agent-grp or adding groupconfig in OpenAM console fails with NPE for subrealms
- OPENAM-3259: StackOverflowError when invalid pcookie is presented
- OPENAM-3252: LoginServlet reroute logic should consider AMAuthCookie as request parameter
- OPENAM-3226: Creating a realm may cause duplicate delegation privilege entries to be written to datastore if multiple servers are running
- OPENAM-3225: SAML authentication throws NPE with IDP metadata showing certain characteristics
- OPENAM-3217: JSP compilation error in Java Fedlet
- OPENAM-3210: In CDSSO scenario no Logout is triggered when choosing 'yes' on 'new_org.jsp'
- OPENAM-3189: IdP Proxy should invoke SP Adapter when sending the proxied SAML request
- OPENAM-3165: NPE during export-svc-cfg
- OPENAM-3160: AuthContext failover doesn't work
- OPENAM-3105: `CachedSubEntries.getSubEntries()` shouldn't sort `LDAPSearchResults`
- OPENAM-3057: DAS /UI/Logout does not work.
- OPENAM-3005: Exported IdP entity cannot be imported back via console

- OPENAM-2953: After upgrade export-svc-cfg + import-svc-cfg stops working
- OPENAM-2948: RESTful read performance: identityExists() is called twice before searching user entry
- OPENAM-2947: Missing statement close in DBHandler can lead to database resource issues.
- OPENAM-2922: SP initiated SLO can fail with IllegalStateException
- OPENAM-2875: Invalid group name error when group does not exist in LDAP
- OPENAM-2764: IdRepoJAXRPCObjectImpl and DirectoryManagerImpl notification URL cache can contain duplicate URLs
- OPENAM-2760: Validation of gotoOnFail URLs
- OPENAM-2757: PrivilegeEvaluator might deadlock if there was a referral privilege added during evaluation
- OPENAM-2737: ReplayPasswd fails in chain auth if PasswordCallback is not available in the last executed auth module
- OPENAM-2719: OAuth2 Consumer sends the OAuth2 token as an Authorization header and as a URL param.
- OPENAM-2689: OAuth2 Client module does not work when used with SAML
- OPENAM-2686: ServiceSchemaManagerImpl.isValid does unnecessary search against config store
- OPENAM-2682: DBFormatter re-generate timestamp causing inaccurate timestamp
- OPENAM-2671: LDAPConnectionPool.getConnFromPool could lead to ArrayIndexOutOfBoundsException
- OPENAM-2644: Cannot resolve element with ID "s2..."
- OPENAM-2628: Case insensitivity for realms is not enforced in AuthenticateToRealmCondition.getConditionDecision
- OPENAM-2619: OpenAM is not verbose enough for installation failures
- OPENAM-2616: Zero page login restriction is too strong
- OPENAM-2612: Personal password reset questions cannot be set

- OPENAM-2596: ssoadm show-privileges result misleading if no identity with given type exists
- OPENAM-2580: DAS loses its configuration on JBoss after a restart
- OPENAM-2544: OpenAM with Internal Server Error after upgrade
- OPENAM-2530: RemoteHttpServletRequest should store headers in CaseInsensitiveHashMap
- OPENAM-2514: Remove-privileges command doesn't handle All Authenticated Users role correctly in subrealms
- OPENAM-2502: show-privileges command returns incorrect values for subrealms
- OPENAM-2494: Request serialization fails on weblogic
- OPENAM-2490: Sessions tab on console makes HTTP request to local server as well
- OPENAM-2478: Checking if stats are being collected in NetworkMonitor loads Entitlement configuration on every call.
- OPENAM-2472: SubjectConfirmationImpl.toXMLString processing not compliant with SAML2 core spec processing rules for SubjectConfirmationType
- OPENAM-2462: extended information in console about property 'Trusted Remote Hosts' for cert auth is incorrect
- OPENAM-2426: Calling Logout and passing a goto URL parameter with an expired session causes the goto URL to be ignored.
- OPENAM-2408: It is not possible to edit all Properties defined in a Current Session Property condition if more than one is defined.
- OPENAM-2402: Unable to delete Property Items in a Current Session Property Condition
- OPENAM-2400: Agent property inheritance does not work as expected
- OPENAM-2370: OpenAM cannot identify the property: com.sun.am.replaypasswd.key
- OPENAM-2369: Export Agent Configuration in the console fails with exception if locale is set to fr
- OPENAM-2274: Default SP Account Mapper can't autofederate using the NameID

- OPENAM-2266: Special chars in ResponseSet XML causing parse errors
- OPENAM-2265: Entitlement Conditions may be evaluated multiple times for a single policy evaluation
- OPENAM-2224: Deadlock in LDAPv3EventService
- OPENAM-2212: AMHostnameVerifier does not work if no keystore is defined
- OPENAM-2153: cert-auth module does not allow to disable CRL in-memory cache
- OPENAM-2152: cert-auth module does not allow storage of several CRLs for the same issuer
- OPENAM-2134: IDPProxy fails to redirect to IDP with an exception. NameIDPolicy is not available in the AuthRequest from remote SP
- OPENAM-2117: ssoadm create-agent command should not require serverurl/agenturl for web/j2ee agents
- OPENAM-2112: ssoadm add-privileges does not work for All Authenticated Users role
- OPENAM-2110: Upgrade fails if external configstore is using non-default user
- OPENAM-2104: noconsole/headless 10.0.1 war doesn't function properly after restart
- OPENAM-2102: LDAPConnection does not handle unsolicited extended responses
- OPENAM-2093: Cleaned up remote sessions shouldn't have destroyed state
- OPENAM-2059: ssoadm export-svc-cfg throws NullPointerException if no SubConfiguration exists for a given service
- OPENAM-2057: OpenSSOPrivilege.evaluate() should not return null
- OPENAM-2053: Log Number of History files count is ignored when log rotation is based on time
- OPENAM-1981: Mis-translated French property items for Agent Console page
- OPENAM-1980: HTTP Redirect SAML requests are incorrectly inflated when they are longer than the configured buffer length

- OPENAM-1964: Performance issues when using AMIdentitySubject with groups
- OPENAM-1933: ReplayPasswd only supports passwords with max 16 characters
- OPENAM-1791: When in message level debug, amUpgrade file logs entries on every request to OpenAM console
- OPENAM-1739: HOTP module may ignore SMTP settings in the configuration
- OPENAM-1655: AttributeQueryUtil ignores configured SPAttributeMapper
- OPENAM-1641: LoginState paramHash is not always correctly initialized when using request serialization
- OPENAM-1569: Remove objectclass=ldapsubentry from LDAP requests
- OPENAM-1512: LDAPConnectionPool is not re-initialized correctly if failover server is down
- OPENAM-1511: closing of LDAPConnection in LDAPConnectionPool is not synchronized
- OPENAM-1453: The read RESTful interface returns an NPE instead of ObjectNotFound when trying to query a nonexistent user
- OPENAM-1180: Login URL problems when using Federation
- OPENAM-1098: During installation I found a link to Oracle
- OPENAM-1083: Using Federation redirects with the valid goto URL whitelist causes problems
- OPENAM-1051: SessionActiveCount also count agent user sessions
- OPENAM-1012: IDP initiated SAML2 SLO error when SP does not have SLO binding
- OPENAM-973: LDAPConnectionPool#decreaseCurrentConnection() could throw ArrayIndexOutOfBoundsException
- OPENAM-844: If Directory Server is started after OpenAM, LDAPv3Repo will never recover
- OPENAM-688: REOPEN -LDAP Error 80 can result in build up of LDAPv3EventService::RetryTask objects

- OPENAM-340: Failed to create new Authentication Context error when zero page login fails on DAS
- OPENAM-6: wantLogoutResponseSigned incorrectly evaluated

5.2. Limitations

Note

The content of this section has not changed since OpenAM 10.0.0.

ForgeRock supports the stable software releases that you can download from ForgeRock, not nightly builds or pre-release software. ForgeRock OpenAM downloads do not include OpenAM extensions. Therefore, ForgeRock does not support OpenAM extensions. If you have a special request for capabilities not currently in a software release, contact ForgeRock at info@forgerock.com.

Do not run different versions of OpenAM together in the same OpenAM site.

Not all features of OpenAM work with IPv6.

The Database Repository type of data store is experimental and not supported for production use.

By default, the REST and SOAP APIs return different responses depending on whether the user name provided is valid or invalid. This behavior could allow an attacker to build list of valid user names, after which only passwords would be required to gain access to user account details. To prevent this risk, set the server configuration property `openam.auth.soap.rest.generic.authentication.exception=true`. You can set this property in OpenAM console under Configuration > Servers and Sites > Servers > Server Name > Advanced.

By default OpenAM does not enforce session quotas when running in Site mode without session failover. To work around this behavior, set the server configuration property `openam.session.useLocalSessionsInMultiServerMode=true`. You can set this property in OpenAM console under Configuration > Servers and Sites > Servers > Server Name > Advanced.

5.3. Known Issues

OpenAM 10.0.2 has a number of outstanding issues that have been noted in the OpenAM bug tracker. Check <https://bugster.forgerock.org/jira/browse/OPENAM> for the latest list of issues.

Chapter 6. How to Report Problems & Provide Feedback

Note

The content of this chapter has not changed since OpenAM 10.0.0.

If you have questions regarding OpenAM which are not answered by the documentation, there is a mailing list which can be found at <https://lists.forgerock.org/mailman/listinfo/openam> where you are likely to find an answer.

If you have found issues or reproducible bugs within OpenAM 10.0.2, report them in <https://bugster.forgerock.org>.

When requesting help with a problem, include the following information:

- Description of the problem, including when the problem occurs and its impact on your operation
- Machine type, operating system version, web container and version, Java version, and OpenAM release version, including any patches or other software that might be affecting the problem
- Steps to reproduce the problem
- Any relevant access and error logs, stack traces, or core dumps

Chapter 7. Support

Note

The content of this chapter has not changed since OpenAM 10.0.0.

You can purchase OpenAM support subscriptions and training courses from ForgeRock and from consulting partners around the world and in your area. To contact ForgeRock, send mail to info@forgerock.com. To find a partner in your area, see <http://www.forgerock.com/partners.html>.

