

OpenIDM 2.1.0 Release Notes

**Mark Craig
Lana Frost
Andi Egloff**

Software release date: February 20, 2013

Publication date: April 26, 2013

Copyright © 2011-2013 ForgeRock AS

Abstract

Notes covering OpenIDM software requirements, fixes, known issues. The OpenIDM project offers flexible, open source services for automating management of the identity life cycle.



This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/> or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.

Trademarks are the property of their respective owners.

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DejaVu Fonts

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: [fonts at gnome dot org](mailto:fonts@gnome dot org).

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: [tavmjong @ free . fr](mailto:tavmjong@free.fr).

Table of Contents

- 1. What's New in OpenIDM 2.1.0 1
- 2. Before You Install OpenIDM Software 3
- 3. OpenIDM Fixes, Limitations, & Known Issues 5
- 4. OpenIDM Compatibility 11
- 5. How to Report Problems & Provide Feedback 15
- 6. Support 17

Chapter 1. What's New in OpenIDM 2.1.0

Important

OpenIDM 2.1.0 is a milestone release from the main development branch of the product. This release contains selected key features and all current fixed issues. The release has undergone important functional testing but not the complete testing cycle that is done for a full enterprise release. Many of the interfaces provided in this release are still evolving and are not guaranteed to be supported in the enterprise release.

This release is supported through a ForgeRock subscription. Its goal is to enable you to start build phases earlier, with the most recent features, instead of having to wait for the full release date. Fixes to issues that are discovered in this release will be delivered as patches to ForgeRock customers, and are guaranteed to be delivered in the full release that follows. This release will be supported for a grace period after the full version has been released.

With the exception of these Release Notes, the official documentation for this release is still in progress, and is accessible at <http://openidm.forgerock.org/docs.html>. The complete, validated documentation set will be available with the full release.

OpenIDM 2.1.0 provides many new features, including the following:

- Browser-based user interface

Includes self service capabilities, a generic platform to expose and invoke workflows, and a notification service for tasks.

For more information, see *OpenIDM User Interface* in the *Integrator's Guide*.

- BPMN 2.0 workflow engine, embedded as an OSGi bundle and accessible over REST.

For more information, see *Integrating Business Processes and Workflows* in the *Integrator's Guide*.

- Configurable task scheduling service, including support for clustered schedules and scanning tasks.

For more information, see *Scheduling Tasks and Events* in the *Integrator's Guide*.

- Configurable policy service.

-
- For more information, see *Using Policies to Validate Data* in the *Integrator's Guide*.
 - Ability to perform batch scans to execute tasks
For more information, see *Scanning Data to Trigger Tasks* in the *Integrator's Guide*.
 - Ability to create custom RESTful endpoints.
For more information, see *Adding Custom Endpoints* in the *Integrator's Guide*.
 - Support for MS SQL JDBC as an internal repository.
For more information, see *To Set Up OpenIDM With MS SQL* in the *Installation Guide*.
 - Enhanced, multi-threaded reconciliation service, accessible over REST.
For more information, see *Configuring Synchronization* in the *Integrator's Guide*.
 - Support for Powershell scripts on the Active Directory connector.
For more information, see *Using PowerShell Scripts With the Active Directory Connector* in the *Integrator's Guide*.
 - Reusable server configuration and property value substitution in the configuration.
For more information, see *Using Property Value Substitution in the Configuration* in the *Integrator's Guide*.
 - Support for calling LiveSync operations over REST, or using the resource API.
For more information, see *Triggering LiveSync Over REST* in the *Integrator's Guide*.
- For installation instructions and several samples to familiarize you with the features, see the *Installation Guide*.
- For an architectural overview and high-level presentation of OpenIDM, see the *Architectural Overview* chapter in the *Integrator's Guide*.

Chapter 2. Before You Install OpenIDM Software

This chapter covers prerequisites for installing and running OpenIDM software.

For OpenIDM 2.1.0, the following configurations are supported for use in production.

Repository

The following JDBC repositories are supported for use in production:

- MySQL 5.1 or 5.5 with Connector/J 5.1.18 or later
- Microsoft SQL Server 2008 Express

OrientDB is provided for evaluation only.

Stand-alone installation

You must install OpenIDM as a stand-alone service, using Apache Felix and Jetty as provided. Alternate containers are not supported.

Connectors

OpenIDM 2.1.0 comes packaged with these OpenICF connectors:

- CSV File
- LDAP
- Scripted SQL
- XML File

ForgeRock provides additional connectors, as listed on the OpenICF project connectors site.

If you have a special request to support a component or combination not listed here, contact ForgeRock at info@forgerock.com.

OpenIDM requires Java SE JDK 6 update 24 or later. When using the Oracle JDK, you also need Java Cryptography Extension (JCE) policy files.

On Windows systems, use Java SE JDK 7 update 6 or later, to take advantage of a recent JVM fix relating to non-blocking sockets with the default Jetty configuration.

You need 130 MB disk space and 256 MB memory for a minimal evaluation installation. For a production installation, disk space and memory

requirements will depend on the size of the repository, and on size of the audit and service log files that OpenIDM writes.

Chapter 3. OpenIDM Fixes, Limitations, & Known Issues

Note

The current list of fixes and issues reflects OpenIDM 2.1.0 in progress as of February 15, 2013.

OpenIDM issues are tracked at <https://bugster.forgerock.org/jira/browse/OPENIDM>.

3.1. Fixes and Improvements

OpenIDM 2.1.0 includes the following major fixes and improvements.

- OPENIDM-1122: Populate the X-Requested-With header in the requests
- OPENIDM-1118: Enforce origin by default, CORS whitelist with default to disable CORS
- OPENIDM-1081: Move to OrientDB 1.3.0 release version
- OPENIDM-1060: JSON Resource should decode URI (normalize)
- OPENIDM-1055: Add base type check to OpenIDMELResolver to resolve only openidm router operations
- OPENIDM-1023: Potential NPE in JsonResourceObjectSet
- OPENIDM-1008: Add not null check to openidm calls in ScopeFactoryService to avoid NPE when handling the result
- OPENIDM-1007: Update the MS SQL JDBC Repository support in 2.1.0
- OPENIDM-988: OpenDJ Password Synchronization Plugin raising error on password change in OpenDJ
- OPENIDM-987: Remove old startprocessinstance syntax from workflow integration
- OPENIDM-970: OpenIDM Livesync: entry deleted on source leads to UNQUALIFIED situation. Should be SOURCE_MISSING
- OPENIDM-965: Encrypted password in boot.properties example does not authenticate
- OPENIDM-961: Must have an easy way to integrate servlet filter based access managers

- OPENIDM-956: OpenIDM assembly depends on ScriptedSQL conn. 1.1.0.0. Should be 1.1.0.1
- OPENIDM-940: onValidate not triggering during recon via rest
- OPENIDM-930: Align provisioner parameters with the new naming convention
- OPENIDM-921: Provisioner fail coerce from String to some primitive types
- OPENIDM-914: CLI.SH configimport not working when using replaceAll option
- OPENIDM-913: CLI.SH configimport not working when importing all set of files
- OPENIDM-911: OpenIDM LiveSync failed to sync user changes from OpenDJ source.
- OPENIDM-885: Convert all samples to be self contained, i.e. start-able via -p option
- OPENIDM-883: Align API with CREST 2.0 for compatibility
- OPENIDM-827: Parallel execution support of reconciliation tasks
- OPENIDM-818: Customizable OpenIDM info service
- OPENIDM-802: Recon: Source reconciliation gives NP exception in certain UNQUALIFIED situation and default DELETE action.
- OPENIDM-797: Sample 3 - MySQL script is not correct on Windows + workaround
- OPENIDM-756: Authentication module needs to be able to propagate user id, not just user name
- OPENIDM-741: Back-end password policy support
- OPENIDM-730: Add legacy java lib drop folder to allow non OSGi jars add to Connector classloader
- OPENIDM-729: Remote Shell script password and username parameters requires special care
- OPENIDM-727: UTC date representation in openidm should show UTC time zone with "Z" post-fix as specified by ISO 8601
- OPENIDM-715: OpenIDM freezes on reconciliation

- OPENIDM-695: MS SQL Server JDBC repository
- OPENIDM-686: Include remote Activiti integration artifacts with the default OpenIDM package
- OPENIDM-685: Upgrade to Activiti 5.10
- OPENIDM-682: REST API: Failed to delete a system object w/ condition in openDJ
- OPENIDM-679: Productize script execution on system objects
- OPENIDM-674: Lazy loading of source or target objects during reconciliation
- OPENIDM-670: Scheduler General Configuration
- OPENIDM-669: Scheduler JSON Resource API
- OPENIDM-661: Special characters are not saved properly in MySQL Database with the default sample configuration.
- OPENIDM-659: Provide more helpful log messages to locate the configuration or usage problems.
- OPENIDM-652: Simple way/flag to restrict authorized URL access in the authorization script
- OPENIDM-638: Performance optimization
- OPENIDM-637: Allow to specify history level of the embedded Activiti ProcessEngine
- OPENIDM-635: Use single ConnectorFacade per service
- OPENIDM-631: Remove the reconId from links
- OPENIDM-630: Enable connection pool by default
- OPENIDM-629: Repository needs to ensure selects do not start implicit transactions
- OPENIDM-613: Allow authentication module to configure which properti(es) constitute password or role
- OPENIDM-612: Support authentication query with user roles
- OPENIDM-602: Authentication bug in backend which makes impossible authentication with encrypted password
- OPENIDM-600: Audit log flag to mark password change/reset

- OPENIDM-598: nullpointer exception when reading from activedirectory group, crash when writing to active drirectory group
- OPENIDM-593: The Json Resource Restlet 1.2.2 fails with the http://localhost:8080/openidm/managed/user?_action=create request
- OPENIDM-564: OpenIDM and the Connector Server, under some conditions, fails to esablish a connection with each other
- OPENIDM-549: onValidate hook should only be invoked before managed object accepts changes to store, not upon retrieval
- OPENIDM-546: Create audit log records with timestamp
- OPENIDM-540: Ability to easily maintain multiple scenario set-ups and to switch between them
- OPENIDM-527: All connectors must distinguish between successful empty results, and failures to obtain results
- OPENIDM-492: Align sample UI with new Authentication mechanisms

3.2. Limitations

A conditional GET request, with the If-None-Match request header, is not currently supported.

3.3. Known Issues

OpenIDM 2.1.0 has the following known issues.

- OPENIDM-1176: Disabled schedules via dynamic scheduler API disappear
- OPENIDM-1170: Linux startup script generator is not working correctly
- OPENIDM-1162: With OrientDB, for a MISSING/CREATE situation/action, reconciliation creates a new link instead of using an existing link
- OPENIDM-1133: Certain sample files contain unnecessary, unused entries
- OPENIDM-1129: OpenIDM freezes when the connection to the repository is interrupted
- OPENIDM-1117: Malformed content-type request header produces 500 error
- OPENIDM-1115: When an LDAP user is created through the REST API, the _id that is returned is not normalized

- OPENIDM-1098: onDelete script generates exception
- OPENIDM-1096: A PUT command on a configuration object may return an incorrect value
- OPENIDM-1094: Starting a second OpenIDM instance with a conflicting port causes the instance to freeze
- OPENIDM-1093: A user's accountStatus (active or inactive) has no effect on the UI or the REST API
- OPENIDM-964: An incorrect password in boot.properties causes OpenIDM to hang on startup
- OPENIDM-848: Conflicting behavior might be observed between the default fields set by the onCreate script and policy enforcement
- OPENIDM-803: For reconciliation, the default DELETE action does not delete target objects when targets are ambiguous, including UNQUALIFIED situations, if there is more than one target

Chapter 4. OpenIDM Compatibility

This chapter covers both major changes to existing functionality, and also deprecated and removed functionality.

4.1. Major Changes to Existing Functionality

The following changes will have an impact on existing deployments. Read these changes carefully and adjust existing scripts and clients accordingly.

Changes to the scheduler configuration

The way in which scheduled tasks is configured has changed, as described in *Scheduling Tasks and Events*.

Schedules are now defined in files named `openidm/conf/schedule-*.json`. If you use the previous naming convention (`scheduler-*.json`), the schedules will not be launched.

Reconciliation now on recon service

In previous releases, reconciliation was called on the sync service. This API has been deprecated and reconciliation is now called on the recon service. For example, a reconciliation operation that previously targeted the following URL:

```
"http://localhost:8080/openidm/recon?_action=sync&mapping=systemLdapAccounts_managedUser"
```

would now use the following URL:

```
"http://localhost:8080/openidm/recon?_action=recon&mapping=systemLdapAccounts_managedUser"
```

Audit log changes

Timestamps now have milliseconds and are in UTC timezone.

The access log now has an additional field, `userid`, which is the OpenIDM ID for a managed or internal user who is logged in. For authentication via SSL mutual auth only, the `userid` is currently null because there is no direct associated user in OpenIDM.

Database schema changes

The `reconID` column has been removed from the `links` table.

The size of the `linkType` column in the `links` table has been reduced to 255 characters. This is because MySQL can only create unique indexes on that size for UTF-8 encoding.

The links table indexes have been changed to unique indexes to prevent duplication.

The auditactivity table contains two new columns - changedfields and passwordchanged, for additional auditing functionality.

Tables have been added for the scheduler configuration and for User Interface notifications.

The openidm user is created with all the required privileges to update the openidm database by default.

Changes to token definitions in OrientDB query definitions

Existing repo.orientdb.json query definitions with tokens like \${mytoken} must be reviewed and adjusted to match the new definition which aligns declarations for regular and prepared statement uses.

Existing \${token} tokens are now suitable for quoted strings by default. Prefixes such as unquoted: and dotnotation: allow you to use queries in contexts where the unquoted value or the JSON pointer converted to OrientDB dot notation should be inserted.

New queries in repo.*.json definitions query-by-linkType

Security context changes

The request context now includes the security context of the user that is associated with the call.

The "user" property has been renamed "username", the name used to log in (for example, to authenticate against an access manager).

Name change for the query-id parameter

The query-id parameter has been renamed queryID for consistency across the API.

4.2. Minor Changes to Existing Functionality

The following changes should not have an impact on existing deployment configurations.

Connection pooling is on by default

For existing configurations, keep this setting off unless you explicitly require it to be changed.

Explicit definition of username, password, and role

The authentication configuration now explicitly defines which properties from the query represent the username, password, and role. Existing

configurations rely on the logic of the query order to determine which property is which.

Prefetching of links during reconciliation operations

All links are now queried at the start of a correlation and the results of that query are used.

For more information, see *Prefetching Links* in the *Integrator's Guide*.

4.3. Deprecated Functionality

The following functionality is deprecated in OpenIDM 2.1.0.

- Reconciliation is no longer called on the sync service. For more information, see the list of changes to existing functionality.

No additional functionality is planned to be deprecated at this time.

4.4. Removed Functionality

No functionality has been removed in OpenIDM 2.1.0.

No functionality is planned to be removed at this time.

4.5. Functionality That Will Change in the Future

These capabilities are expected to change in upcoming releases:

- The way you generate connector configurations for access to external resources, described in *Creating Default Connector Configurations*.

Chapter 5. How to Report Problems & Provide Feedback

If you have questions regarding OpenIDM which are not answered by the documentation, there is a mailing list which can be found at <https://lists.forgerock.org/mailman/listinfo/openidm> where you are likely to find an answer.

If you have found issues or reproducible bugs within OpenIDM 2.1.0, report them in <https://bugster.forgerock.org>.

When requesting help with a problem, please include the following information:

- Description of the problem, including when the problem occurs and its impact on your operation
- Machine type, operating system version, Java version, and OpenIDM release version, including any patches or other software that might be affecting the problem
- Steps to reproduce the problem
- Any relevant access and error logs, stack traces, or core dumps

Chapter 6. Support

You can purchase OpenIDM support subscriptions and training courses from ForgeRock and from consulting partners around the world and in your area. To contact ForgeRock, send mail to info@forgerock.com. To find a partner in your area, see <http://forgerock.com/partners/find-a-partner/>.

