



# OpenIDM Release Notes

Version 3.1.0

Mark Craig  
Lana Frost  
Mike Jang  
Andi Egloff

ForgeRock AS  
33 New Montgomery St.,  
Suite 1500  
San Francisco, CA 94105, USA  
+1 415-599-1100 (US)  
[www.forgerock.com](http://www.forgerock.com)

---

Copyright © 2011-2014 ForgeRock AS

## Abstract

Notes covering OpenIDM software requirements, fixes, known issues. The OpenIDM project offers flexible, open source services for automating management of the identity life cycle.



This work is licensed under the [Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License](http://creativecommons.org/licenses/by-nc-nd/3.0/).

To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/> or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.

ForgeRock™ is the trademark of ForgeRock Inc. or its subsidiaries in the U.S. and in other countries. Trademarks are the property of their respective owners.

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DejaVu Fonts

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: fonts at gnome dot org.

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: tavmjong @ free . fr.

---

---

# Table of Contents

1. What's New in OpenIDM 3.1.0 .....	1
2. Before You Install OpenIDM Software .....	3
3. OpenIDM Fixes, Limitations, & Known Issues .....	7
3.1. Fixes and Improvements .....	7
3.2. Limitations .....	13
3.3. Known Issues .....	13
4. OpenIDM Compatibility .....	19
4.1. Major Changes to Existing Functionality .....	19
4.2. Minor Changes to Existing Functionality .....	19
4.3. Deprecated Functionality .....	20
4.4. Removed Functionality .....	20
4.5. Functionality That Will Change in the Future .....	20
5. How to Report Problems & Provide Feedback .....	21
6. Support .....	23



---

## Chapter 1

# What's New in OpenIDM 3.1.0

OpenIDM 3.1.0 provides many new features and product enhancements. The following list describes the main new features affecting an end user.

### Administration User Interface

The new web-based Admin UI enables you to configure connectors, customize managed objects, set up attribute mappings between resources, configure reconciliation and synchronization rules, and more. For more information, see [Configuring OpenIDM from the Admin UI](#) in the *Integrator's Guide*.

### Addition of an *aggregated view* to the User View UI

The User View UI now includes a read-only view of the user account in each of the external resources to which it is linked. For more information, see [To View a User's Account in External Resources](#) in the *Integrator's Guide*.

### Reconciliation Performance Improvements

To improve reconciliation query performance on slower systems, you can now preload the entire result set into memory on the source or target system, or on both systems. For more information, see [Improving Reconciliation Query Performance](#) in the *Integrator's Guide*.

### Updated Connectors, New Connectors and Samples

Several of the connectors bundled with OpenIDM have been updated. For details of the latest versions, see [Connectors Supported With OpenIDM 3.1.0](#) in the *Integrator's Guide*.

[OpenIDM Enterprise](#) bundles two new connectors, and corresponding sample configurations - a Google Apps Connector and a Salesforce connector.

---

For more information, see [Connecting to Salesforce With the Salesforce Connector](#) and [Connecting to Google With the Google Apps Connector](#) in the *Installation Guide*.

#### Support for PostgreSQL

OpenIDM 3.1.0 supports PostgreSQL, 9.3 or higher, as an internal repository. For information on configuring OpenIDM with a PostgreSQL repository, see [To Set Up OpenIDM With PostgreSQL](#) in the *Installation Guide*.

#### Improvements to the Audit Facility

- Audit logs for synchronization operations

The reconciliation audit facility has been extended to LiveSync and implicit sync operations. For more information, see [Querying the Synchronization Audit Log](#) in the *Integrator's Guide*.

- Ability to purge audit logs

OpenIDM 3.1.0 provides the ability to purge audit logs at a scheduled interval, or when the logs reach a certain size. For more information, see [Purging Obsolete Audit Information](#) in the *Integrator's Guide*.

- Ability to filter audit logs

The audit facility provides a new mechanism that enables you to filter audit data, thereby reducing the volume of data that is logged. For more information, see [Filtering Data for Audits](#) in the *Integrator's Guide*.

For installation instructions and several samples to familiarize you with the OpenIDM features, see the [Installation Guide](#).

For an architectural overview and high-level presentation of OpenIDM, see the [Architectural Overview](#) chapter in the *Integrator's Guide*.

---

## Chapter 2

# Before You Install OpenIDM Software

This chapter covers prerequisites for installing and running OpenIDM software.

For OpenIDM 3.1.0, the following configurations are supported for use in production.

### Repository

The following JDBC repositories are supported for use in production:

- MySQL 5.1 or 5.5 with Connector/J 5.1.18 or later
- Microsoft SQL Server 2008
- Oracle Database 11g
- PostgreSQL 9.3 or higher

OrientDB is provided for evaluation only.

### Stand-alone installation

You must install OpenIDM as a stand-alone service, using Apache Felix and Jetty, as provided. Alternate containers are not supported.

OpenIDM 3.1.0 bundles Jetty version 8.1.9.v20130131.

### Connectors

OpenIDM 3.1.0 comes packaged with these OpenICF connectors:

- CSV File Connector

- 
- Database Table Connector
  - Generic LDAP Connector
  - XML File Connector
  - Groovy Connector Toolkit

This toolkit enables you to create scripted connectors to virtually any resource

A corresponding PowerShell Connector Toolkit is available for download from [ForgeRock Backstage](#), and enables you to create scripted connectors to address the requirements of your Microsoft Windows ecosystem.

The following connectors are available only with [OpenIDM Enterprise](#):

- Google Apps Connector
- Salesforce Connector

ForgeRock provides additional connectors, as listed on the [OpenICF project connectors site](#).

When using the LDAP connector to provision to Active Directory, OpenIDM 3.1.0 supports Active Directory Domain Controllers, Active Directory Global Catalogues, and Active Directory Lightweight Directory Services (LDS).

OpenIDM 3.1.0 also provides support for Windows 2012 R2 as the remote system for connectors and password synchronization plugins.

The following table lists the supported connector, connector server, and password synchronization plugins for this OpenIDM release.

**Table 2.1. Supported Connectors, Connector Servers, and Plugins**

Connector	Version
CSV File Connector	1.1.0.2
Database Table Connector	1.1.0.1
Google Apps Connector	1.4.0.0
Scripted Groovy Connector Toolkit	1.4.1.0
Generic LDAP Connector	1.4.0.0
XML Connector	1.1.0.2



---

Connector	Version
PowerShell Connector Toolkit	1.4.1.0
Active Directory Connector	1.4.0.0
Java Connector Server	1.4.1.0
.NET Connector Server	1.4.1.0
OpenDJ Password Synchronization Plugin	1.0.3
Active Directory Password Synchronization Plugin	1.0.3

#### Browsers

ForgeRock has tested many browsers with the OpenIDM UI, including the following browsers.

- Chrome and Chromium, latest stable version
- Firefox, latest stable version
- Safari, latest stable version
- Internet Explorer 9 and later

#### Operating Systems

OpenIDM 3.1.0 is supported on CentOS Linux 6.5 and on Windows 2008 R2 and Windows 2012 R2. It has been tested on most variations of Linux.

If you have a special request to support a component or combination not listed here, contact ForgeRock at [info@forgerock.com](mailto:info@forgerock.com).

OpenIDM requires Java SE JDK 6 update 24 or later. When using the Oracle JDK, you also need Java Cryptography Extension (JCE) [policy files](#).

On Windows systems, use Java SE JDK 7 update 6 or later, to take advantage of a recent JVM fix relating to non-blocking sockets with the default Jetty configuration.

OpenIDM 3.1.0 also supports OpenJDK 1.7.

You need 150 MB disk space and 1 GB memory for an evaluation installation. For a production installation, disk space and memory requirements will depend on the size of the repository, and on size of the audit and service log files that OpenIDM writes.



---

## Chapter 3

# OpenIDM Fixes, Limitations, & Known Issues

OpenIDM issues are tracked at <https://bugster.forgerock.org/jira/browse/OPENIDM>.

## 3.1 Fixes and Improvements

OpenIDM 3.1.0 includes the following major fixes and improvements.

- [OPENIDM-2611](#): review queries using QueryFilter with explicit tables in Oracle referring to CLOB field
- [OPENIDM-2610](#): QueryFilter used with explicitTables not working with Oracle or MS SQL Server
- [OPENIDM-2605](#): Missing queries from Oracle repo.jdbc.json
- [OPENIDM-2589](#): provisioner files in sample2x do not have enableFilteredResultsHandler set to false
- [OPENIDM-2549](#): unexpected results for queryFilters on integer properties when using JDBC repo
- [OPENIDM-2547](#): Base64 encoded attributes are not properly decoded to byte[]
- [OPENIDM-2538](#): Unable to login after changing the Session timeout setting via the UI

- [OPENIDM-2531](#): QueryFilter-generated SQL for OrientDB for sw "" is incorrect
- [OPENIDM-2529](#): searchBases in powershell2AD sample are not aligned among the scripts
- [OPENIDM-2526](#): Repo README.txt files need to be updated
- [OPENIDM-2525](#): QueryFilter-generated SQL for OrientDB does not parse
- [OPENIDM-2500](#): properties set as encrypted in managed.json written in plain text in activity audit when new and old values are the same
- [OPENIDM-2497](#): Query queryId=audit-by-recon-id not working on MS-SQL
- [OPENIDM-2489](#): Task scanner does not work using MS-SQL repository
- [OPENIDM-2485](#): Country Empty, but State is filled in
- [OPENIDM-2484](#): Multiple provisioner instances created for the same name
- [OPENIDM-2481](#): PostgreSQL query using wrong value
- [OPENIDM-2480](#): Enable READ\_COMMITTED\_SNAPSHOT isolation w/MSSQL
- [OPENIDM-2456](#): Workflow Sample not working with MS-SQL as repo
- [OPENIDM-2446](#): The exception attribute in the audit sync entries is not being pre-formatted before the entry is created.
- [OPENIDM-2437](#): TaskScannerContext should store the ScriptEntry
- [OPENIDM-2429](#): disabled connectors returned from system?action=test need to return connectorRef details
- [OPENIDM-2425](#): Query with queryFilter on managed users fails when using MS-SQL as repo
- [OPENIDM-2424](#): The `__ALL__` object class should use a default object class endpoint if it is not defined in the provisioner config.
- [OPENIDM-2421](#): Consider making the ObjectType properties value in provisioner configs not required or allow it to be empty.
- [OPENIDM-2406](#): Update UID and DN of an ldap entry returns status 500 and Internal Server Error
- [OPENIDM-2394](#): Cannot REST query with a single quote in parameter value
- [OPENIDM-2386](#): Service creation scripts hard-code memory options to 1024m
- [OPENIDM-2385](#): queryFilter support for `_id` fields

- [OPENIDM-2381](#): condition on route config entries are ignored
- [OPENIDM-2375](#): obsolete router.json file in samples/misc and openidm-api-servlet/src/tests
- [OPENIDM-2364](#): update main samples README with last additions/modifications
- [OPENIDM-2355](#): Update linkedView to use queryFilter
- [OPENIDM-2344](#): OpenAM sample UI is not working
- [OPENIDM-2330](#): system?action=test disabled connectors need to return with the same details as an broken/active connector.
- [OPENIDM-2324](#): ScriptedRest connector 1.4 sample scripts exceptions are not properly thrown
- [OPENIDM-2323](#): ScriptedRest connector 1.4 - GET\_LATEST\_SYNC\_TOKEN throws exception - /changelog doesn't support paged search
- [OPENIDM-2321](#): external/rest calls to SSL endpoints result in jetty exception
- [OPENIDM-2315](#): linkedView throws null exception when there is no sync defined
- [OPENIDM-2314](#): Script launched from router.json by onResponse hook is unable to update response data
- [OPENIDM-2312](#): SmartEvent framework maintains a unbounded event name cache which consumes the entire heap
- [OPENIDM-2288](#): Single Quote character in managed object causes OrientDB error
- [OPENIDM-2283](#): A node in a cluster doesn't currently listen for configuration changes
- [OPENIDM-2269](#): unable to use a ScriptTaskListener
- [OPENIDM-2240](#): Recon with situation MISSING and action CREATE behave differently in MySQL and PostgreSQL
- [OPENIDM-2238](#): Sync Audit Log record storage in PostgreSQL fails with error 'column "rev" of relation "auditsync" does not exist'
- [OPENIDM-2237](#): Create default connector configuration for Scripted SQL connector version 1.4.0.0 raises a 500 error
- [OPENIDM-2233](#): ScriptedSQL sample3 - liveSync doesn't work

- [OPENIDM-2224](#): Enhance recon service to return a result indicating the status of the request reconciliation run
- [OPENIDM-2223](#): Update of connector info provider causes all remote connectors unavailable.
- [OPENIDM-2203](#): Pagination on managed users not working with PostgreSQL as repo
- [OPENIDM-2202](#): TaskScanner not working with PostgreSQL as repo
- [OPENIDM-2201](#): In Recon Summary the situation FOUND\_ALREADY\_LINKED is missing
- [OPENIDM-2200](#): Failure on writing sync audit log when action is exception with MySQL as repo
- [OPENIDM-2190](#): With PostgreSQL as repo, creating same user twice gets a 500 instead of 412
- [OPENIDM-2189](#): With PostgreSQL as repo, DELETE on managed user is not working
- [OPENIDM-2184](#): NPE thrown from within ObjectMapping \$SyncOperation.isValidSource() during reconciliation.
- [OPENIDM-2180](#): Repo command action should be disallowed via HTTP
- [OPENIDM-2179](#): Sample 6 : The sample LDIF file provided is not valid
- [OPENIDM-2165](#): sourceCondition must work with maps
- [OPENIDM-2154](#): Use effectiveRoles of managed user instead of roles attribute in UI workflow scripts
- [OPENIDM-2153](#): Column name mismatch for notification tables when using SQLServer repository
- [OPENIDM-2134](#): only the last role was applied when multiple replaceTarget roles with the same property name were assigned to a user
- [OPENIDM-2127](#): Switching existing schedule from persisted=false to persisted=true results in duplicate scheduled jobs.
- [OPENIDM-2116](#): mergeWithTarget and replaceTarget on role definition fails if using Dynamic Assignment
- [OPENIDM-2106](#): Audit filter assumes action is a RequestType and improperly filters recon entries

- [OPENIDM-2089](#): Remove the need to store certificates in the default java keystore when doing ssl over jdbc.
- [OPENIDM-2087](#): Enabled:false needs to not return an error state for provisioners
- [OPENIDM-2079](#): Cannot PATCH managed user when ID contains special characters.
- [OPENIDM-2078](#): PermGen leak in "source" scripts
- [OPENIDM-2074](#): When the workflow module is disabled, shutdown errors are displayed on the console
- [OPENIDM-2067](#): For an MS SQL repository, queries in the repo config file containing concatenation functions do not work
- [OPENIDM-2062](#): openidm/system/NAME?\_action=createFullConfig does not properly handle encrypted values causing the tests to fail.
- [OPENIDM-2061](#): Recon Fails to create users from AD "REV" : invalid identifier [Oracle]
- [OPENIDM-2058](#): Issues on status code and response content for REST API of Configuration with put and delete
- [OPENIDM-2057](#): Issues on status code and response content for REST API of System with post, and delete
- [OPENIDM-2056](#): Recon audit log entry formatting has issues (missing entries and extra entries)
- [OPENIDM-2055](#): Issues on status code and response content for REST API of Scheduler with query, put, and delete
- [OPENIDM-2046](#): Failed to start user onboarding workflow in usercase2 when external repo(MSSQL) was used.
- [OPENIDM-2021](#): If a query is made on an attribute that is not part of the object schema, OpenIDM returns an inaccurate message
- [OPENIDM-2002](#): Failed to Decrypt Jwt errors (badPaddingException)
- [OPENIDM-1990](#): OpenIDM ignoring min/max pool sizes in orient repo config
- [OPENIDM-1988](#): Scripted SQL 1.4 unable to find jdbc driver
- [OPENIDM-1959](#): cli.bat fails to export configuration when we give an absolute path in argument on Windows

- [OPENIDM-1954](#): Enabling the OrientDB Studio UI doesn't take effect until the second restart of OpenIDM
- [OPENIDM-1949](#): Update managed user with patch by query in POST should return modified object instead of null
- [OPENIDM-1946](#): Working location flag (-w) not working as documented
- [OPENIDM-1935](#): The ICF 1.4's RetryableException is wrapped incorrectly by IDM.
- [OPENIDM-1889](#): UI failed to recover from password changing failure
- [OPENIDM-1866](#): Delete of workflow definitions and instances via REST should return the deleted object
- [OPENIDM-1821](#): Deleting a role assigned to user(s) should not be possible
- [OPENIDM-1784](#): OpenIDM doesn't throw error on startup for provisioner's incorrect connectorRef
- [OPENIDM-1756](#): Cancelling "completed" taskscanner task sets its state to "cancelled" whereas it should have no effect
- [OPENIDM-1658](#): Hard-coded reference to database schema and table name in jdbc config files
- [OPENIDM-1560](#): when starting OpenIDM with -p option logging.properties file is not taken in project location
- [OPENIDM-1409](#): The query-all and get-users-of-direct-role queries are not consistent across different repos
- [OPENIDM-1365](#): Recon Audit Log Entries Should Contain "messageDetails" for ScriptExceptions During Reconciliation
- [OPENIDM-1354](#): Recon Log Entries Missing "messageDetail" From Errors During Recon
- [OPENIDM-1337](#): Recon.csv and recon detail over REST are not aligned.
- [OPENIDM-1252](#): Unable to perform search queries with AND or OR operators in where clause for ScriptedSQL.
- [OPENIDM-1101](#): Inform administrator when property specified in sync.json as a target is missing from provisioner conf
- [OPENIDM-746](#): CLI.SH command "validate" does not detect an extra bracket that makes a JSON file not valid



- [OPENIDM-469](#): The ObjectMapping can change the `_id` and then the OpenIDM can not find the original target object any more

## 3.2 Limitations

OpenIDM 3.1.0 has the following known limitations:

- When you add or edit a connector through the Admin UI, the list of *required* Base Connector Details is not necessarily accurate for your deployment. Some of these details might be required for specific deployment scenarios only. If you need a connector configuration where not all the Base Connector Details are required, you need to create your connector configuration file over REST (see [Creating Default Connector Configurations](#) in the *Integrator's Guide*) or edit the connector configuration file (`conf/provisioner.openicf-connector-type.json`) directly.
- For OracleDB repositories, queries that use the `queryFilter` syntax do not work on CLOB columns in explicit tables.
- A conditional GET request, with the If-Match request header, is not currently supported.
- OpenIDM provides an embedded workflow and business process engine based on Activiti and the Business Process Model and Notation (BPMN) 2.0 standard. As an embedded system, local integration is supported. Remote integration is not currently supported.
- The OpenIDM implementation of roles does not enforce referential integrity. In other words, you can set up users with a hypothetical role `x`, before you create that referential role `x`.

When dynamically assigned roles are added, OpenIDM does not set up provisioning for previously existing users. Any updates to dynamically assigned roles will not update users assigned with those roles.

## 3.3 Known Issues

OpenIDM 3.1.0 has the following known issues.

- [OPENIDM-2637](#): OpenID Connect Auth Module is shown in the Admin UI, but is not supported
- [OPENIDM-2627](#): Connectors with an underscore in the ID cannot be edited via Admin UI

- [OPENIDM-2626](#): The User View UI does not currently work with Internet Explorer
- [OPENIDM-2622](#): For JDBC repos, accessing the audit log over REST shows incorrect "userid" and "roles" attribute values
- [OPENIDM-2621](#): Attempting to read a non-existent audit record over REST raises an exception in the console
- [OPENIDM-2612](#): queryFilter command in sample3 fails with status 500
- [OPENIDM-2607](#): Validating the connector configuration from the UI fails for Sample 3
- [OPENIDM-2604](#): For the ScriptedCREST sample, the connection to OpenDJ occasionally times out
- [OPENIDM-2593](#): RuntimeException using OSGI Service for datasource
- [OPENIDM-2590](#): Missing records in LDAP cause Data Association Management grid to fail
- [OPENIDM-2580](#): Workflow can not be started by key by a non-admin user
- [OPENIDM-2569](#): When OpenIDM is started with a provisioner.openicf.connectorinfoprovider.json file, the required bundle is not loaded correctly

Workaround : Add a space or a line to the provisioner.openicf.connectorinfoprovider.json file, which reloads the associated bundle.

- [OPENIDM-2568](#): Reconcile Duration counter remains at 0:00 until reconciliation is complete
- [OPENIDM-2560](#): Required script file fields for Scripted Groovy Connector configuration preventing validation
- [OPENIDM-2502](#): Instructions associated with RC init creation script are incomplete
- [OPENIDM-2496](#): When SSL is enabled on LDAP connector with right CA certificate, validation failed on UI
- [OPENIDM-2460](#): JAVA\_TYPE\_DATE nativeType not supported
- [OPENIDM-2454](#): REST errors (4xx and 5xx) interfere with CORS response headers
- [OPENIDM-2349](#): Implement openidm.xx() method resolution running in the remote Activiti engine

- [OPENIDM-2348](#): Implement external webapp for the remote Activiti server
- [OPENIDM-2347](#): Implement OpenIDM -> external resource communication
- [OPENIDM-2265](#): Got "ORA-01843: not a valid month" while trying to liveSync from Oracle database
- [OPENIDM-2260](#): Inconsistencies in encoding/decoding the IDs used of managed users
- [OPENIDM-2244](#): AD PW Sync Setup script wizard fails when browsing for a PKCS12 format certificate file
- [OPENIDM-2141](#): When creating a provisioner with CREST no errors are thrown when a provisioner already exists
- [OPENIDM-2107](#): Deleting managed/user via REST or UI leaves links records behind
- [OPENIDM-2034](#): Support arbitrary [commons] auth modules via className
- [OPENIDM-2028](#): The .NET Connector Server Exception displays an incorrect connector error
- [OPENIDM-2016](#): sync on unsupported object class with remote java connector returns 500 instead of 400
- [OPENIDM-2005](#): OpenICF query filter does not support literal expressions
- [OPENIDM-2004](#): NPE in OpenICF Provisioner query w/o filter
- [OPENIDM-1991](#): IDM blocked accessing Orientdb ReadWriteDiskCache
- [OPENIDM-1981](#): Importing all config files with CLI configimport fails with Java 8
- [OPENIDM-1948](#): Creating managed user with PUT on managed/user// endpoint is accepted whereas it should be refused
- [OPENIDM-1941](#): "pattern" property in access.js rules does not work when used on system endpoints
- [OPENIDM-1907](#): Recon failures as a result of policy violations do not indicate the cause of the violation in the recon audit log.
- [OPENIDM-1898](#): Representation of request-object differs between code and json-representation
- [OPENIDM-1860](#): Null pointer exception when setting target attribute during onUnlink

- [OPENIDM-1823](#): getScriptBindings function of ServiceScript (ScriptRegistryImpl.java) slows down extremely when accessed parallel from multiple threads
- [OPENIDM-1742](#): Launching a recon by ID on a non-existent ID is not handled correctly
- [OPENIDM-1664](#): Memory usage of AD connector continue to increase.
- [OPENIDM-1654](#): No sync/ service is registered if a sync.json file is not present in the configuration
- [OPENIDM-1632](#): create-openidm-logrotate.sh is not properly defined
- [OPENIDM-1619](#): OperationOptions specified within the provisioner configuration are not passed to connectors by OpenIDM
- [OPENIDM-1600](#): Cluster with Oracle DB backend
- [OPENIDM-1564](#): \_\_NAME\_\_ attribute incorrectly required as part of object definition for a create action
- [OPENIDM-1562](#): Route to endpoint service not found if there is a resourcename after the name of the endpoint
- [OPENIDM-1530](#): OpenIDM self-signed certificates in keystore and truststore does not match
- [OPENIDM-1504](#): OpenICFProvisionerService handle method performs logger.isDebugEnabled() checks but logs at the error level
- [OPENIDM-1501](#): sync?\_action=performAction with an action=DELETE results in a delete on the source rather than the target
- [OPENIDM-1488](#): XDate locales could not be initialized correctly
- [OPENIDM-1465](#): cannot access Remote Activiti engine - http://localhost:9090/openidm-workflow-remote-2.1.0-SNAPSHOT/, because of 500 - Internal server error
- [OPENIDM-1452](#): Incorrect bundleVersion in provisioner config yields confusing error
- [OPENIDM-1445](#): Provisioner service does not decrypt encrypted attributes before passing them to OpenICF framework
- [OPENIDM-1430](#): OpenIDM needs a restart after importing a new cert via REST API
- [OPENIDM-1269](#): some issues with Case Sensitivity options for Sync

- [OPENIDM-1219](#): DB/Config bootstrapping should use IdentityServer support for getting properties, including boot prop
- [OPENIDM-1186](#): PATCH with POST using MVCC are successful even if revision wrong
- [OPENIDM-1165](#): EXCEPTION action when doing liveSync stops the synctoken processing
- [OPENIDM-1074](#): disabling automatic polling for changes of config file not possible on new install
- [OPENIDM-848](#): Conflicting behavior might be observed between the default fields set by the onCreate script and policy enforcement
- [OPENIDM-662](#): query-all-ids always returns the revision as 0, even after the object has been updated to a newer revision
- [OPENIDM-470](#): OpenIDM cannot rename objects - if the identifier of the object changes, the associated link breaks



---

## Chapter 4

# OpenIDM Compatibility

This chapter covers major and minor changes to existing functionality, as well as deprecated and removed functionality in this release of OpenIDM. You must read this chapter before commencing a migration from a previous OpenIDM release.

### 4.1 Major Changes to Existing Functionality

The following changes will have an impact on existing deployments. Read these changes carefully and adjust existing scripts and clients accordingly.

Changes to indexing for JDBC repositories

To improve indexing across the various supported JDBC repositories, a change has been made for all generic object mappings. The size of the `propvalue` column in the `objectproperties` tables (used for searches) is now limited to 2000 characters for all repositories other than MS SQL. Longer values are truncated. For MS SQL repositories, the `propvalue` column is restricted to 195 characters.

Incoming searches are trimmed accordingly, so that search filters such as `equals` do not break for the truncated column values.

### 4.2 Minor Changes to Existing Functionality

The following changes should not have an impact on existing deployment configurations.

#### Change to roles assignment operation scripts

The scripts that specify how role values are assigned (`replaceTarget.js` and `mergeWithTarget.js`) now pass back a map containing the new value for the target object field and, optionally, an updated `attributesInfo` object. Previously, these scripts simply returned the new value of the target object field.

#### Changes to connector configuration creation

The way in which you generate connector configurations for access to external resources has changed. There are now three separate actions involved in creating the connector configuration. For more information, see [Creating Default Connector Configurations](#) in the *Integrator's Guide*.

The previous method of creating a connector configuration is retained in this release, for compatibility.

#### New location for sample JDBC repository configurations

The sample JDBC repository configurations, previously located at `openidm/samples/misc/repo.jdbc-repo-type.json`, are now located at `openidm/db/repo-type/conf/repo.jdbc.json`. The files no longer need to be renamed before being copied to your project's `conf` directory.

## 4.3 Deprecated Functionality

No functionality has been deprecated in OpenIDM 3.1.0.

No additional functionality is planned to be deprecated at this time.

## 4.4 Removed Functionality

No functionality has been removed in OpenIDM 3.1.0.

No functionality is planned to be removed at this time.

## 4.5 Functionality That Will Change in the Future

The [Active Directory \(AD\) .NET Connector](#) will be deprecated in a future OpenICF release, and, ultimately, support for its use with OpenIDM will be discontinued.

For simple Active Directory (and Active Directory LDS) deployments, the [Generic LDAP Connector](#) works better than the Active Directory connector, in most circumstances. For more complex Active Directory deployments, use the [Powershell Connector Toolkit](#).



---

## Chapter 5

# How to Report Problems & Provide Feedback

If you have questions regarding OpenIDM which are not answered by the documentation, there is a mailing list which can be found at <https://lists.forgerock.org/mailman/listinfo/openidm> where you are likely to find an answer.

If you have found issues or reproducible bugs within OpenIDM 3.1.0, report them in <https://bugster.forgerock.org>.

When requesting help with a problem, please include the following information:

- Description of the problem, including when the problem occurs and its impact on your operation
- Machine type, operating system version, Java version, and OpenIDM release version, including any patches or other software that might be affecting the problem
- Steps to reproduce the problem
- Any relevant access and error logs, stack traces, or core dumps



---

## Chapter 6

# Support

You can purchase OpenIDM support subscriptions and training courses from ForgeRock and from consulting partners around the world and in your area. To contact ForgeRock, send mail to [info@forgerock.com](mailto:info@forgerock.com). To find a partner in your area, see <http://forgerock.com/partners/find-a-partner/>.

