



API Reference v1

Real-time misinformation, phishing & AI-voice-fraud detection over a simple REST API.

• Production

Base URL: app.authentiscanapp.com

HTTPS · JSON

Bearer auth

1 · Quickstart

Send any URL or text and get back a 0–100 risk score with a verdict and explanation.

```
curl -X POST https://app.authentiscanapp.com/api/v1/analyze \  
  -H "Authorization: Bearer ask_test_XXXXXXXXXXXXXXXXXXXX" \  
  -H "Content-Type: application/json" \  
  -d '{ "content": "https://paypal-security-alert-login.com" }'
```

```
{  
  "request_id": "req_7a83e420ca24a5f9c1ddb95b",  
  "mode": "url",  
  "risk_score": 95,  
  "risk_level": "critical",  
  "verdict": "fake",  
  "title": "High Misinformation Risk",  
  "summary": "Fraudulent phishing domain impersonating PayPal.",  
  "explanation": "The domain paypal-security-alert-login.com is a classic phishing scam...",  
  "credibility_signals": [ ... ],  
  "analyzed_at": "2026-06-16T22:40:43.373Z"  
}
```

2 · Authentication

Every request must include a Bearer API key:

```
Authorization: Bearer <api_key>
```

Prefix	Environment	Daily limit	Notes
ask_test_	Sandbox	100 req/day	For evaluation — no billing
authentiscan_sk_live_	Production	Per plan	Live traffic

Keys are secret — use them only server-side. Missing/invalid key → 401 UNAUTHORIZED ; revoked key → 403 FORBIDDEN .

3 · POST /api/v1/analyze

Analyzes a URL, free text, or audio clip and returns a risk score with level, verdict and explanation.

Request body

Field	Type	Required	Description
content	string	yes ¹	URL or raw text. 5–10,000 characters.
type	string	optional	url , text or audio . Auto-detected from content .
audio	string	yes ²	Base64 audio (audio mode). Max 25 MB decoded.
audioMime	string	optional	audio/wav (default), audio/mp3 , audio/m4a .
include_signals	boolean	optional	Include credibility_signals . Default true .

¹ Required for text/URL mode. ² Required for audio mode. Language is detected automatically.

Response — 200 OK

Field	Type	Description
<code>request_id</code>	string	Unique id for this analysis.
<code>mode</code>	string	<code>url</code> , <code>text</code> or <code>audio</code> .
<code>risk_score</code>	integer	0–100.
<code>risk_level</code>	string	<code>low</code> , <code>medium</code> , <code>high</code> , <code>critical</code> .
<code>verdict</code>	string	<code>real</code> , <code>unverified</code> , <code>misleading</code> , <code>fake</code> .
<code>title</code> / <code>summary</code> / <code>explanation</code>	string	Headline, one-line finding, full analysis.
<code>credibility_signals</code>	array	Up to 4 signals: <code>{ name, finding, score, level }</code> .
<code>transcription</code>	string	Audio mode only (≤ 300 chars).
<code>analyzed_at</code>	string	ISO-8601 timestamp.

Risk level mapping

Level	Score	Meaning
LOW	0–34	Appears credible. No significant risk signals.
MEDIUM	35–64	Some signals warrant caution. Verify further.
HIGH	65–80	Multiple red flags. Do not share without verification.
CRITICAL	81–100	Strong evidence of fraud or disinformation.

4 · Code examples

Node.js

```
const r = await fetch("https://app.authentiscanapp.com/api/v1/analyze", {
  method: "POST",
  headers: {
    "Content-Type": "application/json",
    "Authorization": `Bearer ${process.env.AUTHENTISCAN_KEY}`,
  },
  body: JSON.stringify({ content: "https://example.com/article" }),
});
const result = await r.json();
console.log(result.risk_score, result.risk_level);
```

Python

```
import os, requests
r = requests.post(
    "https://app.authentiscanapp.com/api/v1/analyze",
    headers={"Authorization": f"Bearer {os.environ['AUTHENTISCAN_KEY']}"},
    json={"content": "https://example.com/article"},
)
print(r.json()["risk_score"], r.json()["risk_level"])
```

5 • Rate limits

Limits are enforced per API key. Every response includes:

```
X-RateLimit-Limit:      100
X-RateLimit-Remaining: 97
X-RateLimit-Reset:      1781654400    # Unix time (UTC) of daily reset
```

When exhausted the API returns `429 RATE_LIMIT_EXCEEDED`. Retry after `X-RateLimit-Reset`.

6 • Errors

All errors use a consistent envelope: `{ "error": "CODE", "detail": "message" }`

HTTP	Error code	Meaning
400	INVALID_REQUEST	Malformed payload or missing field.
400	CONTENT_TOO_LONG	Text > 10,000 chars or audio > 25 MB.
401	UNAUTHORIZED	API key missing or invalid.
403	FORBIDDEN	Key revoked or lacks access.
405	METHOD_NOT_ALLOWED	Unsupported HTTP method.
422	AUDIO_FORMAT_UNSUPPORTED	Audio could not be processed.
429	RATE_LIMIT_EXCEEDED	Daily quota reached — retry after reset.
500	INTERNAL_ERROR	Unexpected server error — safe to retry.
503	SERVICE_UNAVAILABLE	Temporary upstream unavailability.

7 • Health check

```
curl https://app.authentiscanapp.com/api/ping
→ { "status": "ok", "version": "1.0", "timestamp": "..." }
```

8 • Webhooks — Beta

Push notifications on scan completion (`scan.complete` , `scan.high_risk`) with HMAC-signed payloads are on the roadmap. Contact us to join the beta.